

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12386239
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Naito; Go et al.

Image blur correction device having image blur-correcting function

Abstract

An image blur correction device that forms a strong rolling surface on a movable member having a resin part and is improved in strength of the movable member. The image blur correction device includes a fixed member, rolling balls, and the movable member that includes a sheet metal member and the resin part molded integrally with the sheet metal member, holds an image capture device, and is movable in a direction orthogonal to an optical axis of the image capture device, relative to the fixed member. Part of the movable member, where the sheet metal member is exposed from the resin part, forms the rolling surfaces on which the rolling members roll, and the sheet metal member is formed into a shape surrounding the image capture device, as viewed from the optical axis direction.

Inventors:	Naito; Go (Kawasaki, JP), Kimura; Masafumi (Kawasaki, JP)
Applicant:	CANON KABUSHIKI KAISHA (Tokyo, JP)
Family ID:	71097624
Assignee:	CANON KABUSHIKI KAISHA (Tokyo, JP)
Appl. No.:	18/298628
Filed:	April 11, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230305361 A1	Sep. 28, 2023

Foreign Application Priority Data

JP	2018-237496	Dec. 19, 2018
JP	2019-116536	Jun. 24, 2019
JP	2019-116537	Jun. 24, 2019

Related U.S. Application Data

division parent-doc US 16710433 20191211 US 11656530 child-doc US 18298628

Publication Classification

Int. Cl.: **G03B5/00** (20210101); **G02B27/64** (20060101); **H04N23/68** (20230101)

U.S. Cl.:

CPC **G03B5/00** (20130101); **G02B27/646** (20130101); **H04N23/687** (20230101);
G03B2205/0015 (20130101); G03B2205/0069 (20130101); G03B2205/0084 (20130101)

Field of Classification Search

CPC: G02B (27/646); G03B (2205/0015); G03B (2205/0069); G03B (2205/0084); G03B (5/00); G03B (2205/0038); H04N (23/687); H04N (23/54); H04N (23/55); H04N (23/6812)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7471886	12/2007	Hirota et al.	N/A	N/A
7961220	12/2010	Orihashi	N/A	N/A
7983544	12/2010	Yoneoka et al.	N/A	N/A
9609219	12/2016	Howarth et al.	N/A	N/A
2006/0056829	12/2005	Hirota	396/54	H04N 23/6812
2009/0310953	12/2008	Yoneoka	396/55	G03B 17/00
2011/0298970	12/2010	Shinohara	N/A	N/A
2012/0211640	12/2011	Suzuki	N/A	N/A
2016/0033786	12/2015	Kim	N/A	N/A
2017/0139225	12/2016	Lim	N/A	N/A
2017/0139227	12/2016	Kim	N/A	N/A
2017/0324905	12/2016	Yu et al.	N/A	N/A
2018/0070799	12/2017	Sekido	N/A	N/A
2019/0208654	12/2018	Hamaguchi	N/A	B29B 7/90
2020/0225506	12/2019	Awazu	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2006078891	12/2005	JP	N/A
2008064863	12/2007	JP	N/A
2009300708	12/2008	JP	N/A
2011004075	12/2010	JP	N/A
2012175273	12/2011	JP	N/A
2013190653	12/2012	JP	N/A
2013231923	12/2012	JP	N/A
2015537247	12/2014	JP	N/A

2016149620	12/2015	JP	N/A
1020200133703	12/2019	KR	N/A
1020220042894	12/2021	KR	N/A
2016194074	12/2015	WO	N/A

OTHER PUBLICATIONS

Notice of Allowance issued in U.S. Appl. No. 16/710,433 mailed Jan. 24, 2023. cited by applicant

Primary Examiner: Spinks; Antoinette T

Attorney, Agent or Firm: ROSSI, KIMMS & McDOWELL LLP

Background/Summary

BACKGROUND OF THE INVENTION

Field of the Invention

(1) The present invention relates to an image blur correction device having an image blur-correcting function.

Description of the Related Art

(2) In recent years, there have been proposed some types of a system of an image blur correction mechanism equipped in an image capture apparatus or a lens barrel. For example, there are known a system of driving some of lenses of a photographing optical system for image blur correction and a system of driving an image capture device included in a camera body for image blur correction. Further, there is known a system in which the above-mentioned systems are combined for image blur correction, so as to drive both of the some of lenses of the photographing optical system and the image capture device.

(3) The above-mentioned image blur correction mechanism that drives the lens and/or the image capture device (hereinafter generically referred to as the optical element) generally employs a system for moving the optical element in a direction orthogonal to a photographing optical axis. As a system for driving the optical element, there is known one referred to as the voice coil motor (VCM) system. The VCM system has a configuration in which magnets are provided in one of a fixed member and a movable member, a coil is provided in the other, and the coil is energized in a magnetic circuit formed by the magnets to thereby generate a driving force derived from the Lorentz force. In the VCM system, a predetermined space is formed between the magnets and the coil, and rolling members, such as balls, are provided in this space, whereby it is possible to smoothly drive the optical element with less loss caused by friction. Surfaces on which the rolling members rolls during driving is referred to as the rolling surfaces. The rolling surfaces are generally formed by a method of affixing a roll reception member having a hard surface to the movable member and the fixed member.

(4) In combination, to prevent the rolling members from falling off, a mechanism is generally integrated which generates an urging force for urging both of the fixed member and the movable member toward the rolling members. As the urging method, there are known a method of urging the fixed member and the movable member using a spring such that the rolling members are sandwiched between the movable member and the fixed member, and a method of arranging magnets and a magnetic component (object to be attracted) in one and the other of the movable member and the fixed member, respectively, thereby causing the movable member and the fixed member to magnetically attract each other.

(5) Further, for an image capture apparatus equipped with an image blur correction mechanism

(image plane anti-vibration mechanism) that translationally moves an image capture device package holding an image capture device, there has been proposed a technique focusing on a problem caused in a case where part for holding the image capture device package is formed of resin. Japanese Laid-Open Patent Publication (Kokai) No. 2008-64863 discloses a technique focusing on heat dissipation of the image capture device package, and using, in a case where a movable frame for holding the image capture device package is formed of resin, resin having a high thermal conductivity. According to the technique disclosed in Japanese Laid-Open Patent Publication (Kokai) No. 2008-64863, it is possible to prevent excessive temperature rise of the image capture device package and an image sensor, whereby it is possible to provide a proper image with suppressed thermal noise.

(6) Incidentally, in Japanese Laid-Open Patent Publication (Kokai) No. 2013-231923, when the movable member is molded of resin, the rolling surfaces described above are formed by molding the movable member integrally with a ball receiving sheet metal. With this, a step for mounting a member forming the rolling surfaces is eliminated. However, since the movable member is mainly formed of resin, in a case where the optical element held by the movable member is relatively large or heavy, it is important to ensure the strength of the movable member for driving the movable member such that the function of the optical element is properly maintained. Particularly, in a case where the method of forming the rolling surfaces as disclosed in Japanese Laid-Open Patent Publication (Kokai) No. 2013-231923 is employed, the strength of the movable member is not considered, which may cause insufficiency of the strength.

(7) Further, the technique disclosed in Japanese Laid-Open Patent Publication (Kokai) No. 2008-64863 focuses on the temperature of the sensor, but does not consider deformation of a component, caused due to temperature change. For example, there is a fear that there may arise such a problem that the image plane is bent due to temperature change, making it is impossible to adjust the focus on the whole screen. Particularly, in a case where the components are fixed with an adhesive, there is a fear that it is impossible to maintain the performances of the components due to thermal stress occurring on adhesion interface. Therefore, there is room for improvement in suppressing lowering of the reliability, which can be caused due to thermal stress occurring on the adhesion interface.

SUMMARY OF THE INVENTION

(8) The present invention provides an image blur correction device that forms a strong rolling surface on a movable member having a resin part and is improved in strength of the movable member.

(9) Further, the present invention provides an image blur correction device that suppresses occurrence of thermal stress on an adhesion interface and is thereby improved in reliability.

(10) In a first aspect of the present invention, there is provided an image blur correction device comprising a fixed member, a rolling member, and a movable member that includes a sheet metal member and a resin part molded integrally with the sheet metal member, holds an optical element, and is movable via the rolling member relative to the fixed member in a direction orthogonal to an optical axis of the optical element, wherein part of the movable member, where the sheet metal member is exposed from the resin part, forms a rolling surface on which the rolling member rolls, and wherein the sheet metal member is formed into a shape surrounding the optical element, as viewed from an optical axis direction.

(11) In a second aspect of the present invention, there is provided an image blur correction device comprising an image capture device package including an image capture device, a holding member that holds the image capture device package, a fixed part that holds the holding member such that the holding member is relatively displaceable, and an adhesive for fixing a first adhesion interface on the image capture device package and a second adhesion interface on the holding member, wherein a linear expansion coefficient of part forming the first adhesion interface is larger than a linear expansion coefficient of the image capture device, wherein part forming the second adhesion interface is formed of resin, and a linear expansion coefficient of the part forming the second

adhesion interface is larger than the linear expansion coefficient of the part forming the first adhesion interface, and wherein the linear expansion coefficient of the part forming the second adhesion interface is smaller than a linear expansion coefficient of any of an aluminum alloy and a magnesium alloy.

(12) In a third aspect of the present invention, there is provided an image blur correction device comprising an image capture device package including an image capture device, a holding member that includes a sheet metal member and a resin part molded integrally with the sheet metal member, and holds the image capture device package, a fixed part that holds the holding member such that the holding member is relatively displaceable, and an adhesive for fixing a first adhesion interface on the image capture device package and a second adhesion interface on the holding member, wherein a linear expansion coefficient of part forming the first adhesion interface is larger than a linear expansion coefficient of the image capture device, wherein the second adhesion interface is formed by the resin part, and a linear expansion coefficient of part forming the second adhesion interface is larger than the linear expansion coefficient of the part forming the first adhesion interface, and wherein the linear expansion coefficient of the part forming the second adhesion interface is smaller than a linear expansion coefficient of the sheet metal member.

(13) According to the first aspect of the present invention, it is possible to form the strong rolling surface on the movable member having the resin part and improve the strength of the movable member.

(14) Further, according to the second and third aspects of the present invention, it is possible to suppress occurrence of thermal stress on the adhesion interface, and thereby improve the reliability.

(15) Further features of the present invention will become apparent from the following description of exemplary embodiments (with reference to the attached drawings).

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1A is a cross-sectional view of an image capture apparatus to which an image blur correction device is applied.

(2) FIG. 1B is a block diagram showing an electrical configuration of the image capture apparatus to which the image blur correction device is applied.

(3) FIG. 2A is a perspective view of a camera-side shake correction unit.

(4) FIG. 2B is an exploded perspective view of the camera-side shake correction unit.

(5) FIG. 3A is a view of a movable member, as viewed from a + (positive) side in a z-axis direction.

(6) FIG. 3B is a view of the movable member, as viewed from a - (negative) side in the z-axis direction.

(7) FIG. 3C is a view of the movable member, as viewed from the - (negative) side in the z-axis direction.

(8) FIG. 4A is a view of the camera-side shake correction unit, as viewed from the + (positive) side in the z-axis direction.

(9) FIG. 4B is a view showing part of a cross-section taken along A-A in FIG. 4A.

(10) FIG. 4C is a view showing part of a cross-section taken along B-B in FIG. 4A.

(11) FIG. 5A is a view of the camera-side shake correction unit, as viewed from the + (positive) side in the z-axis direction.

(12) FIG. 5B is a view of the movable member, as viewed from the - (negative) side in the z-axis direction.

(13) FIG. 5C is a view showing part of a cross-section taken along C-C in FIG. 5A.

(14) FIG. 5D is a view showing part of a cross-section taken along D-D in FIG. 5A.

- (15) FIG. 6A is a view of the camera-side shake correction unit, as viewed from the + (positive) side in the z-axis direction.
- (16) FIG. 6B is a view showing part of a cross-section taken along E-E in FIG. 6A.
- (17) FIG. 7A is a view of the camera-side shake correction unit, as viewed from the + (positive) side in the z-axis direction.
- (18) FIG. 7B is a view showing part of a cross-section taken along F-F in FIG. 7A.
- (19) FIG. 7C is a cross-sectional view of a comparative example.
- (20) FIG. 8A is a view of the movable member, as viewed from the + (positive) side in the z-axis direction.
- (21) FIG. 8B is a cross-sectional view taken along J-J in FIG. 8A.
- (22) FIG. 9A is a view of a lens-side shake correction unit, as viewed from the + (positive) side in the z-axis direction.
- (23) FIG. 9B is a cross-sectional view taken along G-G in FIG. 9A.
- (24) FIG. 9C is a cross-sectional view taken along H-H in FIG. 9A.
- (25) FIG. 10A is a cross-sectional view of an image capture apparatus to which an image blur correction device according to a seventh embodiment of the present invention is applied.
- (26) FIG. 10B is a block diagram showing an electrical configuration of the image capture apparatus to which the image blur correction device is applied.
- (27) FIG. 11 is an exploded perspective view of essential parts of an anti-vibration mechanism.
- (28) FIG. 12A is a schematic cross-sectional view showing a form of adhesion between an image capture device package and a movable frame.
- (29) FIG. 12B is a schematic cross-sectional view showing another form of adhesion between the image capture device package and the movable frame.
- (30) FIG. 12C is a cross-sectional view schematically showing distortion of the image capture device package.
- (31) FIG. 13A is a view of the anti-vibration mechanism, as viewed from an optical axis direction.
- (32) FIG. 13B is a cross-sectional view taken along A-A in FIG. 13A.

DESCRIPTION OF THE EMBODIMENTS

- (33) The present invention will now be described in detail below with reference to the accompanying drawings showing embodiments thereof.
- (34) FIG. 1A is a cross-sectional view of an image capture apparatus to which an image blur correction device according to a first embodiment of the present invention is applied. FIG. 1B is a block diagram showing an electrical configuration of the image capture apparatus, denoted by reference numeral **1000**. This image capture apparatus **1000** is formed by a camera body **1** and a lens barrel **2**. The lens barrel **2** is removable from the camera body **1** and the image capture apparatus **1000** is a so-called lens interchangeable camera. Note that the present invention can be applied even to an image capture apparatus including the lens barrel **2** which is fixed to the camera body **1** and cannot be removed therefrom.
- (35) The lens barrel **2** includes a photographing optical system **3**, a lens system controller **12**, a lens drive section **13**, and a lens-side shake detection section **16**. The photographing optical system **3** is formed by a plurality of lenses. The lens drive section **13** drives a focus lens for adjusting focus and a shake correction lens **3a** for performing shake correction. The lens drive section **13** has a lens-side shake correction unit **13a**. The lens-side shake correction unit **13a** drives the shake correction lens **3a** in a direction orthogonal to an optical axis **4** (photographing optical axis) of the photographing optical system **3**. The lens-side shake detection section **16** detects a shake amount of the image capture apparatus **1000**.
- (36) The camera body **1** includes a camera system controller **5**, an image capture device **6**, an image processor **7**, a memory section **8**, a display section **9**, an operation detection section **10**, a camera-side shake correction unit **14**, a camera-side shake detection section **15**, and an electric contact **11**. The image capture device **6** is an optical element that photoelectrically converts an

optical image formed through the lens barrel **2**. The display section **9** includes a rear-side display device **9a** provided on a rear side of the camera body **1** and an EVF (electronic viewfinder) **9b** provided within a finder of the camera body **1**. The operation detection section **10** detects a signal output from an operation section including a shutter release button, not shown, and so forth. The electric contact **11** is for communication between the camera body **1** and the lens barrel **2**. The camera-side shake correction unit **14** drives the image capture device **6** in a direction orthogonal to the optical axis **4**. The camera-side shake detection section **15** detects a shake amount of the image capture apparatus **1000**.

(37) The image capture apparatus **1000** formed by the camera body **1** and the lens barrel **2** has an image capture unit, an image processing unit, a recording/reproduction unit, and a control unit. The image capture unit mentioned here includes the photographing optical system **3** and the image capture device **6**, and the image processing unit includes the image processor **7**. Further, the recording/reproduction unit includes the memory section **8** and the display section **9**. The control unit includes the camera system controller **5**, the operation detection section **10**, the camera-side shake detection section **15**, the camera-side shake correction unit **14**, the lens system controller **12**, and the lens-side shake detection section **16**, and further includes the lens drive section **13** including the lens-side shake correction unit **13a**. Note that the lens system controller **12** and the lens drive section **13** can drive not only the shake correction lens **3a**, but also the focus lens, a diaphragm, and so forth, none of which are shown.

(38) The camera-side shake detection section **15** and the lens-side shake detection section **16** are capable of detecting rotation of the image capture apparatus **1000** about the optical axis **4**, and the detection of rotation is realized by using e.g. a vibrating gyroscope. The camera-side shake correction unit **14** is a mechanism that drives the image capture device **6** on a plane orthogonal to the optical axis **4**. The lens-side shake correction unit **13a** is a mechanism that drives the shake correction lens **3a** in a direction orthogonal to the optical axis **4**.

(39) The above-described image capture unit is an optical processing system configured to form through the photographing optical system **3** an image of light from an object on an image plane of the image capture device **6**. A focus evaluation amount and a proper exposure amount can be obtained from the image capture device **6** and the photographing optical system **3** is properly adjusted based on signals thereof, whereby the image capture device is exposed to an object light with a proper light amount to form an object image at or in the vicinity of the image capture device **6**.

(40) The image processor **7** has an analog-to-digital converter, a white balance adjustment circuit, a gamma correction circuit, an interpolation calculation circuit, etc., therein, and is capable of generating an image for recording. A color interpolation processor is included in this image processor **7** and generates a color image by performing color interpolation (demosaicing) on Bayer signals. Further, the image processor **7** compresses a still image, a moving image, sound, and so forth, using a predetermined method. Note that the image processor **7** can also generate a shake detection signal based on comparison between a plurality of images obtained from the image capture device **6**, and hence the camera-side shake detection section **15** may be formed by the image capture device **6** and the image processor **7**.

(41) The memory section **8** includes a storage medium. The camera system controller **5** outputs an image to the memory section **8** and displays an image to be presented to a user on the display section **9**. The camera system controller **5** generates and outputs a timing signal, and so forth, for use in image capture. The camera system controller **5** controls the image capture system, the image processing system, and the recording and reproduction system, in response to an external operation. For example, when it is detected by the operation detection section **10** that the shutter release button, not shown, has been pressed, the camera system controller **5** controls driving of the image capture device **6**, the operations of the image processor **7**, including compression processing, and so forth. Further, the camera system controller **5** controls the state of each segment on the display

section 9. Note that the rear-side display device 9a is implemented by a touch panel and hence the rear-side display device 9a may serve as both the display section 9 and the operation section.

(42) The operation for adjusting the optical system will be described. The image processor 7 is connected to the camera system controller 5, and the camera system controller 5 determines an appropriate focus position and diaphragm position based on signals output from the image capture device 6. The camera system controller 5 sends commands to the lens system controller 12 via the electric contact 11, and the lens system controller 12 properly controls a focus lens drive section and a diaphragm drive section, neither of which is shown. Further, in a mode for performing shake correction, the camera system controller 5 properly controls the camera-side shake correction unit 14 based on signals obtained from the camera-side shake detection section 15. Similarly, the lens system controller 12 properly controls the lens-side shake correction unit 13a based on signals obtained from the lens-side shake detection section 16.

(43) More specifically, first, the camera system controller 5 and the lens system controller 12 acquire camera shake signals detected by the camera-side shake detection section 15 and the lens-side shake detection section 16, respectively. Then, the camera system controller 5 and the lens system controller 12 calculate a driving amount of the image capture device 6 and a driving amount of the shake correction lens 3a for correcting image blur, based on the acquired shake signals, respectively. After that, the camera system controller 5 and the lens system controller 12 send the calculated driving amounts to the camera-side shake correction unit 14 and the lens-side shake correction unit 13a as the command values to drive the image capture device 6 and the shake correction lens 3a, respectively.

(44) Further, as described above, the camera system controller 5 and the lens system controller 12 control the operations of the components of the camera body 1 and the lens barrel 2 in response to user operations performed on respective operation sections provided on the camera 1 and the lens barrel 2. This makes it possible to photograph a still image and a moving image.

(45) FIGS. 2A and 2B are a perspective view and an exploded perspective view of the camera-side shake correction unit 14, respectively. The camera-side shake correction unit 14 that displaces the image capture device 6 in the direction orthogonal to the optical axis 4 will be described with reference to FIGS. 2A and 2B. The directions of the camera-side shake correction unit 14 will be described using coordinate axes indicated in FIG. 2A. More specifically, a longitudinal direction of the image capture device 6 is defined as an x-axis, a shorter direction of the image capture device 6 is defined as a y-axis, and a direction of the optical axis 4 (photographing optical axis direction) is defined as a z-axis. A+ (positive) side in the z-axis direction is an object side. A+ (positive) side in the y-axis direction is the upper side of the image capture apparatus 1000 in a normal use state.

(46) The camera-side shake correction unit 14 includes a movable unit and a fixed member 28 as the main components. This movable unit includes a movable member 20, coils 21, position detection sections 22, a flexible circuit board 23, and the image capture device 6. The movable unit formed by integrally assembling these components can be displaced in the direction orthogonal to the optical axis 4 relative to the fixed member 28.

(47) As shown in FIG. 2B, as the coils 21 for driving, there are provided three coils (21a, 21b, and 21c). The coil 21a drives the movable member 20 in the x-axis direction and the coils 21b and 21c drive the same in the y-axis direction. With these three coils 21, the movable member 20 is displaceable in the x-axis direction and the y-axis direction, and further, rotationally displaceable about the z-axis.

(48) The position detection sections 22 (22a, 22b, and 22c) are provided inside the coils 21a, 21b, and 21c, respectively. The position detection sections 22a, 22b, and 22c detect positions of the coils 21a, 21b, and 21c, respectively. Each position detection section 22 is formed e.g. by a Hall element, and detects a position of a corresponding one of the coils 21 by detecting a change in magnetic flux density within a magnetic field generated by magnets, described hereinafter, whereby the position of the movable member 20 is detected. The coils 21 and the position detection

sections **22** are mounted on the flexible circuit board **23**. The flexible circuit board **23** electrically connects between a driving circuit, not shown, and the movable member **20**.

(49) The camera-side shake correction unit **14** further includes a plurality of magnets **24** for driving, a first yoke **25**, and a second yokes **29**. The second yoke **29** is divided into two parts: a second yoke **29a** opposed to the coil **21a** and a second yoke **29b** opposed to the coils **21b** and **21c**. However, the second yoke **29** is not necessarily required to be divided into the two parts. Spacers **27** are members for securing a fixed space between the fixed member **28** and the first yoke **25** which are fixed to each other. The spacers **27** also serve as a drive regulation section which is brought into abutment with the movable member **20** before the movable member **20** is displaced up to a drive limit area during driving. The drive limit area is a maximum range within which the coils **21** do not extend outside the area where the magnets **24** are arranged.

(50) The camera-side shake correction unit **14** is provided with a total of twelve magnets **24**. Magnets **24g** to **24l** of the magnets **24** are fixed to the fixed member **28** via the second yoke **29**. The magnets **24g** to **24l** are inserted through openings formed in the fixed member **28**, and the second yoke **29** is fixed to the fixed member **28** from a – (negative) side in the z-axis direction, whereby the positions of the magnets **24g** to **24l** are fixed. Magnets **24a** to **24f** are arranged on an opposite side from the fixed member **28** across the movable member **20** in the direction of the optical axis **4**. Three rolling balls **26** as rolling members are arranged between the movable member **20** and the fixed member **28**. The rolling balls **26** roll when the movable member **20** is driven with respect to the fixed member **28**, whereby the movable member **20** can be displaced relative to the fixed member **28** with less friction.

(51) Next, the roles of the above-described components when the movable member **20** is driven will be described. In a case where the movable member **20** is driven in the x-axis direction, the movable member **20** is driven in the x-axis direction by the coil **21a** and the magnets **24a**, **24b**, **24g**, and **24h**, opposed to the coil **21a**. By energizing the coil **21a** arranged in a magnetic circuit formed by the magnets **24a**, **24b**, **24g**, and **24h**, the coil **21a** receives the Lorentz force, whereby the movable member **20** is moved in the x-axis direction.

(52) In a case where the movable member **20** is driven in the y-axis direction, the movable member **20** is driven in the y-axis direction by the coils **21b** and **21c** and the magnets **24c**, **24d**, **24e**, **24f**, **24i**, **24j**, **24k**, and **24l**, opposed to the coils **21b** and **21c**. By energizing the coil **21b** arranged in a magnetic circuit formed by the magnets **24c**, **24d**, **24i**, and **24j**, the coil **21b** receives the Lorentz force in the y-axis direction. Similarly, by energizing the coil **21c** arranged in a magnetic circuit formed by the magnets **24e**, **24f**, **24k**, and **24l**, the coil **21c** receives the Lorentz force in the y-axis direction. In a case where the coils **21b** and **21c** are energized to receive the forces in the same direction, the movable member **20** is translationally moved in the y-axis direction. In a case where the coils **21b** and **21c** are energized to receive the forces in the directions opposite to each other, respectively, the movable member **20** is rotationally moved about a rotational axis parallel to the z-axis direction. Therefore, the movable member **20** of the camera-side shake correction unit **14** can be translationally moved within a plane (x-y plane) orthogonal to the optical axis **4** and be rotationally moved about the z-axis direction.

(53) FIGS. **3A** and **3B** are views of the movable member **20**, as viewed from the + (positive) side in the z-axis direction and the – (negative) side in the z-axis direction, respectively. FIG. **3C** is a view of the movable unit including the movable member **20** and the image capture device **6**, as viewed from the – (negative) side in the z-axis direction. Not only the movable unit, but also formation of rolling surfaces using an insert sheet metal will be described with reference to FIGS. **3A** to **3C**.

(54) As shown in FIG. **3A**, the movable member **20** has a resin part **20a** and a sheet metal member **20b**. In the movable member **20**, the resin part **20a** is molded integrally with the sheet metal member **20b**. That is, the resin part **20a** is molded integrally with the sheet metal member **20b** by insert molding. In FIGS. **3A** and **3B**, part indicated by a broken line is the sheet metal member **20b**. Basically (except the rolling surfaces, denoted by reference numeral **30**, described hereinafter), the

resin part **20a** is molded integrally with the sheet metal member **20b** such that the sheet metal member **20b** is covered with the resin part **20a**. The sheet metal member **20b** is made of a metal having magnetism.

(55) As shown in FIG. 3B, the movable member **20** is provided with the rolling surfaces **30** (**30a**, **30b**, and **30c**), which are brought into contact with the rolling balls **26**, respectively. Each rolling surface **30** is part of the sheet metal member **20b**, and in the movable member **20**, parts exposed from the resin part **20a** toward the – (negative) side in the z-axis direction form the rolling surfaces **30**. The rolling surfaces **30** are provided in plural as the surfaces on which the rolling balls **26** roll when the movable member **20** is moved in the x-axis direction and the y-axis direction, and in the present embodiment, the three rolling surfaces **30** are formed on the movable member **20**. When integrally forming the sheet metal member **20b** and the resin part **20a**, the rolling surfaces **30a** to **30c** are formed by causing portions of the sheet metal member **20b** to be exposed from the resin part **20a**.

(56) The movable member **20** is brought into contact with the fixed member **28** via the rolling balls **26**, and hence if the camera body **1** receives an impact, caused e.g. by dropping, the movable member **20** receives the impact from the fixed member **28** via the rolling balls **26**. At this time, if flaws and dents are generated and remain in the rolling surfaces **30**, each rolling ball **26** does not smoothly move where the flaws and dents are formed, during afterward shake correction, which adversely affects the shake correction. Therefore, the rolling surfaces **30** are required to have such hardness as will be resistant to impact. For this reason, in a case where the movable member **20** is made of a material having relatively low hardness, such as resin, it is necessary to additionally use a member having high hardness for a member forming the rolling surfaces **30**. Conventionally, when forming the movable member of e.g. resin, there is mostly used a method of affixing a sheet metal having high hardness to the rolling surface as an additional member. However, in a case where the sheet metal is affixed, an additional affixing step is required, and further, a problem is caused that not only a component tolerance of the sheet metal as a single component but also an assembling tolerance due to e.g. oblique assembling of the component into the movable member **20** is included.

(57) In the present embodiment, since the sheet metal member **20b** is brought into contact with the rolling balls **26** on the rolling surfaces **30**, the rolling surfaces **30** can have sufficient hardness to be resistant to impact. Further, since the resin part **20a** is molded integrally with the sheet metal member **20b**, the affixing step is not required to be included in the process for manufacturing the movable member **20**, and further, it is possible to avoid variation of the rolling surfaces **30** due to affixing.

(58) As is clear from comparison between FIG. 3C and FIG. 3B, the sheet metal member **20b** is arranged such that it surrounds the image capture device **6**, as viewed from the z-axis direction (or the direction of the optical axis **4**). Thus, the sheet metal member **20b** is formed into a shape surrounding the image capture device **6**, whereby although the movable member **20** is mainly formed of resin, it is possible to increase the strength of the movable member **20**. Particularly, when driving a relatively large component element of the image capture apparatus **1000**, such as the image capture device **6** and a large optical member, if impact caused e.g. by dropping is received, a large force is applied to the movable member **20**. Therefore, if the movable member **20** is formed only of resin, the movable member **20** cannot resist the impact, which causes deformation and breakage and can adversely affect a photographed image. To prevent this, the resin part **20a** is molded integrally with the sheet metal member **20b**, and the inserted sheet metal member **20b** is arranged on the whole movable member **20** such that it surrounds the image capture device **6**, whereby it is possible to increase the strength of the movable member **20** and thereby prevent deformation and breakage.

(59) Further, by arranging the sheet metal member **20b** such that it surrounds the image capture device **6**, it is also possible to reduce noise (image deterioration) occurring on the image capture

device **6**. As described with reference to FIGS. 2A and 2B, the movable member **20** is driven by the Lorentz force generated by energizing the coils **21** arranged in the magnetic circuits formed by the magnets **24**. At this time, a signal which is originally not expected to be imaged is sometimes generated in the image capture device **6** as noise (hereinafter referred to as the magnetic noise) due to the influence of the magnetic fields formed in the coils **21**. However, since the sheet metal member **20b** is arranged such that it surrounds the image capture device **6**, the magnetic fields generated by the coils **21** are shielded by the sheet metal member **20b** and hard to reach the image capture device **6**. Thus, the arrangement of the sheet metal member **20b**, surrounding the image capture device **6**, also makes it possible to reduce the magnetic noise generated by energizing the coils **21**.

(60) Next, an urging mechanism (urging unit) of the camera-side shake correction unit **14** for urging the movable member **20** against the fixed member **28** will be described with reference to FIGS. 4A to 4C. FIG. 4A is a view of the camera-side shake correction unit **14**, as viewed from the + (positive) side in the z-axis direction. FIGS. 4B and 4C are views showing part of a cross-section taken along A-A and part of a cross-section taken along B-B in FIG. 4A, respectively.

(61) As shown in FIG. 4B, the image capture device **6** is fixedly mounted on the movable member **20** with an adhesive **40**. With this, the movable member **20** fixedly holds the image capture device **6**. A reason why a surface of the movable member **20**, which is bonded to the image capture device **6** with the adhesive **40**, is formed by the resin part **20a** will be described. In general, when bonding components using an adhesive, it is necessary to provide a place where the adhesive is applied (hereinafter referred to as the adhesive pool). In general, the same image capture device **6** can be used for a lot of models, but on the other hand, the movable member **20** is designed on a model-by-model basis, and hence the adhesive pool is also designed on a model-by-model basis. For this reason, to make it possible to freely arrange the adhesive pool with a higher degree of freedom in shape, it is preferable that the bonding surface is formed by the resin part **20a**.

(62) Further, when the camera body **1** is exposed to a high-temperature or low-temperature environment, if a difference in the linear expansion coefficient is large between an outer periphery portion of the image capture device **6**, as one bonding surface, and part of the movable member **20**, as the other bonding surface, the image capture device **6** and the movable member **20** may warp in a direction opposite to each other. This is caused by occurrence of thermal distortion. If the image capture device **6** thus warps from the movable member **20**, a problem is caused that the image capture device **6** tilts with respect to the optical axis **4** and hence tilts with respect to the image plane of the image capture apparatus **1000**, which may cause blur in part of a photographed image. One solution for this problem is that the linear expansion coefficient of the bonding surface of the movable member **20**, bonded to the image capture device **6**, and the linear expansion coefficient of the bonding surface of the image capture device **6** are made closer to each other.

(63) In the present embodiment, the movable member **20** is formed by the resin part **20a** and the sheet metal member **20b**. Assuming that the sheet metal member **21b** is largely different in the linear expansion coefficient from the image capture device **6**, it is preferable that the resin part **20a** is formed by a resin material having a linear expansion coefficient close to that of the image capture device **6**. Thus, considering the degree of freedom in selecting the material, it is also preferable to form the bonding surface of the movable member **20** where the image capture device **6** is bonded, by using the resin part **20a**. As described above, from the viewpoint of the degree of freedom in shape and the viewpoint of the physical properties of the materials, it is preferable that the surface of the movable member **20** where the image capture device **6** is bonded is formed by the resin part **20a**.

(64) Next, the urging mechanism for urging the movable member **20** against the fixed member **28** will be described. As shown in FIG. 4C, the rolling balls **26** are arranged on the - (negative) side in the z-axis direction of the movable member **20**. In this case, it is preferable that the movable member **20** is also urged toward the - (negative) side in the z-axis direction. In general, in a case

where a fixed member and a movable member are urged, it is necessary to additionally arrange a member for urging them. However, in the present embodiment, an urging force is obtained by using magnetism of the sheet metal member **20b** and the magnets **24**.

(65) The sheet metal member **20b** is formed of magnetic material. As is clear from FIG. **4B**, part of the sheet metal member **20b** is opposed to the magnets **24**, and hence the sheet metal member **20b** is attracted by the magnets **24**. The action of attracting the sheet metal member **20b** by the magnets **24** is hereinafter referred to as the “magnetic attraction”. Therefore, whether the movable member **20** is more strongly magnetically-attracted toward the first yoke **25** (+ (positive) side in the z-axis direction) or the second yoke **29b** (– (negative) side in the z-axis direction) is determined depending on a distance from the sheet metal member **20b** to the magnets **24** in the z-axis direction.

(66) Here, reference numeral **41** in FIG. **4B** indicates a distance from the sheet metal member **20b** to the magnets **24e** and **24f** mounted on the first yoke **25**. Reference numeral **42** indicates a distance from the sheet metal member **20b** to the magnets **24k** and **24l** mounted the second yoke **29b**. Note that when comparing these distances **41** and **42**, the position of the sheet metal member **20b** is represented by the position of the center of the sheet metal member **20b** in a direction of the thickness thereof. In the present embodiment, the distance **42** is shorter than the distance **41**.

Therefore, the attraction force applied to the sheet metal member **20b** is stronger on the – (negative) side in the z-axis direction than on the + (positive) side in the z-axis direction, and as a result, the movable member **20** is urged toward the fixed member **28**. Further, similarly, the sheet metal member **20b** is closer to the magnets **24g** and **24h** (see FIG. **2B**) than to the magnets **24a** and **24b**. Therefore, it is possible to smoothly drive the rolling balls **26** on the rolling surfaces **30** with less loss caused by friction.

(67) As described above, in the movable member **20**, the resin part **20a** is molded integrally with the sheet metal member **20b** such that it is closer to the magnets **24** on the – (negative) side in the z-axis direction than to the magnets **24** on the + (positive) side in the z-axis direction. With this, the sheet metal member **20b** not only provides the rolling surfaces **30**, but also is capable of functioning as the urging mechanism.

(68) According to the present embodiment, parts of the sheet metal member **20b** in the movable member **20**, exposed from the resin part **20a**, form the rolling surfaces **30**. This makes it possible to form the strong rolling surfaces on the movable member **20** including the resin part and reduce the number of steps for forming the rolling surfaces **30**. Further, the movable member **20** is formed by molding the resin part **20a** integrally the sheet metal member **20b**, and the sheet metal member **20b** is formed into the shape surrounding the image capture device **6**, as viewed from the direction of the optical axis **4**. This makes it possible to increase the strength of the movable member **20**. What is more, it is possible to reduce magnetic noise caused by energization of the coils **21**.

(69) Further, the movable member **20** and the fixed member **28** are urged such that they are attracted to each other, by using part (magnetic portion) of the sheet metal member **20b**. What is more, since the distance **42** is shorter than the distance **41**, the movable member **20** is urged toward the fixed member **28**. This makes it possible to simplify the manufacturing process by eliminating the need of an additional urging member for preventing the rolling balls **26** from falling off.

(70) Further, the image capture device **6** is fixed to the resin part **20a** of the movable member **20**. This makes it possible to increase the degree of freedom in selecting the material and the shape, for the bonding surface where the image capture device **6** is bonded to the movable member **20**.

(71) An image capture apparatus according to a second embodiment of the present invention will be described with reference to FIGS. **5A** to **5D**. The present embodiment differs from the first embodiment in the components of the sheet metal member **20b** of the movable member **20** and is basically the same in the other components as the first embodiment. Therefore, the description will be mainly given of the different points from the first embodiment.

(72) FIG. **5A** is a view of the camera-side shake correction unit **14**, as viewed from the + (positive) side in the z-axis direction. FIG. **5B** is a view of the movable member, as viewed from the –

(negative) side in the z-axis direction. FIGS. 5C and 5D are views showing part of a cross-section taken along C-C in FIG. 5A and part of a cross-section taken along D-D in FIG. 5A, respectively.

(73) The camera-side shake correction unit **14** includes the movable member, denoted by reference numeral **50**. The movable member **50** includes not only a resin part **50a** and a sheet metal member **50b**, but also a magnetic sheet metal **50c** for magnetic attraction. The movable member **50**, the resin part **50a**, and the sheet metal member **50b** correspond to the movable member **20**, the resin part **20a**, and the sheet metal member **20b** in the first embodiment, respectively. In the movable member **50**, the resin part **50a** is molded integrally with the sheet metal member **50b** and the magnetic sheet metal **50c**. Parts of the sheet metal member **50b** are exposed to form the rolling surfaces **30a** to **30c** (only the rolling surface **30b** is shown in FIG. 5D).

(74) Although the sheet metal member **20b** in the first embodiment is formed of magnetic material, the sheet metal member **50b** is formed of non-magnetic material. On the other hand, the magnetic sheet metal **50c** is formed of magnetic material. As shown in FIG. 5C, the magnetic sheet metal **50c** is arranged such that the whole movable member **50** is attracted toward the – (negative) side in the z-axis direction. That is, a distance from the magnetic sheet metal **50c** to the magnets **24** (**24g** to **24l**) on the – (negative) side in the z-axis direction is shorter than a distance from the magnetic sheet metal **50c** to the magnets **24** (**24a** to **24f**) on the + (positive) side in the z-axis direction. Therefore, the movable member **50** is urged toward the fixed member **28**.

(75) Since the sheet metal member **50b** is a non-magnetic body, the sheet metal member **50b** is not attracted by the magnets **24**. The urging force is caused by the magnetic sheet metal **50c**, and hence it is unnecessary to arrange the sheet metal member **50b** at a location remote from the magnets **24** on the + (positive) side in the z-axis direction. If this state is described by referring to the first embodiment (see FIG. 4B), it is unnecessary to make the distance **42** shorter than the distance **41**. Compared with the first embodiment, it is possible to offset the movable member **50** toward the – (negative) side in the z-axis direction without changing the position of the rolling surfaces **30** in the z-axis direction. For example, as shown in FIG. 5D, it is possible to reduce the thickness of the movable member **50** by an amount corresponding to an offset amount **51**. Accordingly, it is possible to offset the first yoke **25** and the magnets **24** (**24a** to **24f**) fixed to the first yoke **25** toward the – (negative) side in the z-axis direction. As a result, it is possible to reduce the thickness of the camera-side shake correction unit **14** in the z-axis direction.

(76) According to the present embodiment, it is possible to obtain the same advantageous effects as provided by the first embodiment, in forming the strong rolling surfaces **30**, reducing the number of processing steps for forming the rolling surfaces **30**, and increasing the strength of the movable member **50**. Further, it is possible to obtain the urging force using the magnetic sheet metal **50c** which is a member different from the sheet metal member **50b**, and what is more, since the sheet metal member **50b** is formed of non-magnetic material, this contributes to size reduction and thinning of the camera-side shake correction unit **14**.

(77) An image capture apparatus according to a third embodiment of the present invention will be described with reference to FIGS. 6A and 6B. The present embodiment differs from the first embodiment in the components of the urging mechanism for urging the movable member against the fixed member **28** in the camera-side shake correction unit, and is basically the same in the other components as the first embodiment. Therefore, the description will be mainly given of the different points from the first embodiment.

(78) FIG. 6A is a view of a camera-side shake correction unit, as viewed from the + (positive) side in the z-axis direction. FIG. 6B is a view showing part of a cross-section taken along E-E in FIG. 6A. The image capture apparatus according to the present embodiment includes the camera-side shake correction unit, denoted by reference numeral **60**, which corresponds to the camera-side shake correction unit **14**.

(79) The camera-side shake correction unit **60** includes a movable member **61**. The movable member **61** includes a sheet metal member **61b** and a resin part **61a**, and the resin part **61a** is

molded integrally with the sheet metal member **61b**. The movable member **61**, the resin part **61a**, and the sheet metal member **61b** correspond to the movable member **20**, the resin part **20a**, and the sheet metal member **20b** in the first embodiment, respectively. Portions of the sheet metal member **61b** are exposed to form the rolling surfaces **30** (not shown in FIGS. **6A** and **6B**).

(80) An urging spring **63** is engaged between the movable member **61** and the fixed member **28**. One end of the urging spring **63** is engaged with a spring hook portion provided **61c** on the sheet metal member **61b**, and the other end is engaged with a spring hook portion **28a** provided on the fixed member **28**. The locations on the movable member **61** and the fixed member **28**, where the urging spring **63** is engaged, do not matter. The urging spring **63** is hooked in a tensioned state. Therefore, the movable member **61** and the fixed member **28** are urged in a direction attracted to each other. With this, it is unnecessary to use the sheet metal member for the urging mechanism. Therefore, the sheet metal member **61b** may be formed of non-magnetic material.

(81) According to the present embodiment, it is possible to obtain the same advantageous effects as provided by the first embodiment, in forming the strong rolling surfaces **30**, reducing the number of processing steps for forming the rolling surfaces **30**, and increasing the strength of the movable member **61**. Further, since the movable member **61** and the fixed member **28** are urged by the urging spring **63**, it is possible to simplify the urging mechanism without requiring to be configured such that a magnetic body is used therefor.

(82) Note that the urging spring **63** may be provided in addition to the urging mechanism using the magnetic body in the first and second embodiments.

(83) A fourth embodiment of the present invention will be described with reference to FIGS. **7A** to **7C**. The present embodiment differs from the first embodiment in the shape of the sheet metal member of the movable member **20**, and is basically the same in the other components as the first embodiment. Therefore, the description will be mainly given of the different points from the first embodiment.

(84) FIG. **7A** is a view of the camera-side shake correction unit **14**, as viewed from the + (positive) side in the z-axis direction. FIG. **7B** is a view showing part of a cross-section taken along F-F in FIG. **7A**. Further, FIG. **7C** is a view showing part of a cross-section of the camera-side shake correction unit **14** in the first embodiment, taken along F-F, as a comparative example. Detailed description of FIG. **7C** is omitted.

(85) The movable member **20** in the present embodiment includes the resin part **20a** and a sheet metal member **70**. The sheet metal member **70** corresponds to the sheet metal member **20b** in the first embodiment, and is formed of a magnetic material. Referring to FIG. **7B**, the sheet metal member **70** is bent at a bending portion **70a**, and has a step portion formed at the bending portion **70a** as a boundary. With this step portion, the other area than the area of the rolling surfaces **30** (only **30b** is shown in FIG. **7B**) is closer to the fixed member **28**. In other words, part of the sheet metal member **70** which is opposed to the magnets **24** and used to urge the movable member **20** by magnetic attraction can be made closer to the magnets **24** (**24g** to **24l**) on the – (negative) side in the z-axis direction, compared with the first embodiment. The part of the sheet metal member **70** opposed to the magnets **24**, mentioned here, is the area other than the rolling surfaces **30**, and it is better for the purpose of magnetic attraction that this part is closer to the magnets **24** on the – (negative) side in the z-axis direction. By forming the bending portion **70a**, it is possible to position this part on the – (negative) side in the z-axis direction with respect to a + (positive) side end position of each rolling ball **26** in the z-axis direction.

(86) As a result, it is possible to reduce the thickness of the movable member **20** by an amount corresponding to an offset amount **71**, indicated in FIG. **7B**. Accordingly, it is also possible to offset the first yoke **25** and the magnets **24** (**24a** to **24f**) fixed to the first yoke **25** toward the – (negative) side in the z-axis direction. As a result, it is possible to reduce the thickness of the camera-side shake correction unit **14** in the z-axis direction.

(87) According to the present embodiment, it is possible to obtain the same advantageous effects as

provided by the first embodiment, in forming the strong rolling surfaces **30**, reducing the number of processing steps for forming the rolling surfaces **30**, and increasing the strength of the movable member **20**. Further, since the sheet metal member **70** is formed with the step (bending portion **70a**), and the part of the sheet metal member **70**, other than the rolling surfaces **30**, is closer to the fixed member **28** in the direction of the optical axis **4**, this contributes to size reduction and thinning of the camera-side shake correction unit **14**.

(88) A fifth embodiment of the present invention will be described with reference to FIGS. **8A** and **8B**. The present embodiment differs from the first embodiment in the components of the movable member **20**, and is basically the same in the other components as the first embodiment. Therefore, the description will be mainly given of the different points from the first embodiment.

(89) In general, a problem is known that if there is fine dust on the image capture device in the image capture apparatus, an image of the dust is included in a photographed image. As a countermeasure for this, a dust removing mechanism is sometimes employed that includes a cover glass provided on an object side of the image capture device and conveys and removes fine dust by vibrating the cover glass. In the present embodiment, this dust removing mechanism is employed.

(90) FIG. **8A** is a view of a movable member **801**, as viewed from the + (positive) side in the z-axis direction. FIG. **8B** is a cross-sectional view taken along J-J in FIG. **8A**. Note that the same component elements as those of the first embodiment are denoted by the same reference numerals. The movable member **801**, a resin part **801a**, and a sheet metal member **801b** correspond to the movable member **20**, the resin part **20a**, and the sheet metal member **20b** in the first embodiment, respectively.

(91) The movable member **801** includes a piezoelectric element **802**, a vibration member **803**, and an electrically conductive member **804**. The vibration member **803** is a member in which vibrations are excited by the piezoelectric element **802**. The piezoelectric element **802** is fixed to the vibration member **803**. The vibration member **803** is arranged such that it covers the whole area of the image capture device **6** from the object side of the image capture device **6** in the direction of the optical axis **4** (opposite side from the fixed member **28** in the direction of the optical axis **4**). The vibration member **803** is a cover member which has the same function as the cover glass of the above-described dust removing mechanism. That is, the vibration member **803** plays a role of preventing attachment of fine dust to the image capture device **6**. The vibration member **803** is vibrated by the piezoelectric element **802**, whereby it is possible to remove fine dust attached to the vibration member **803**.

(92) The electrically conductive member **804** places the piezoelectric element **802** and the vibration member **803** in a state fixed to the resin part **801a**, and has a function of electrically connecting the piezoelectric element **802** and the vibration member **803** to the sheet metal member **801b**. An electrical conduction screw **805** as a fastening member is electrically conductive and electrically connects between the electrically conductive member **804** and the sheet metal member **801b**. The sheet metal member **801b** has an electrically conductive connection portion **801c**. The electrically conductive connection portion **801c** is formed e.g. by bending or burring the sheet metal member **801b** such that its height in the direction of the optical axis **4** is secured. The electrically conductive connection portion **801c** is formed with a female screw into which a male screw of the electrical conduction screw **805** is screwed.

(93) The male screw of the electrical conduction screw **805** is screwed into the female screw of the electrically conductive connection portion **801c** of the sheet metal member **801b** via the resin part **801a**, whereby the electrically conductive member **804** is fixed to the resin part **801a** and the sheet metal member **801b** together with the piezoelectric element **802** and the vibration member **803**. Further, the electrical conduction screw **805** and the electrically conductive connection portion **801c** are brought into contact with each other, whereby the vibration member **803** is electrically connected to the sheet metal member **801b** via the electrically conductive member **804**.

(94) Incidentally, in general, it is known that the piezoelectric element generates static electricity

due to its property of repeating expansion and compression at high speed. This causes a problem that the static electricity attracts fine dust around the piezoelectric element. To solve this problem, there is a conventionally known configuration for removing static electricity generated in the piezoelectric element, in which an electrically conductive member is provided around the piezoelectric element and the electrically conductive member is connected to a large metallic member. The present embodiment employs this configuration.

(95) As described above, in the present embodiment, the movable member **801** is formed by integrally molding the resin part **801a** with the sheet metal member **801b**. Therefore, it is preferable to provide the electrically conductive member **804** around the piezoelectric element **802** and electrically connect the electrically conductive member **804** to the sheet metal member **801b**. For this reason, the electrically conductive member **804** is formed into a shape surrounding the piezoelectric element **802**, as viewed from the direction of the optical axis **4**. Further, the electrically conductive member **804** and the sheet metal member **801b** are connected at the electrically conductive connection portion **801c** via the electrical conduction screw **805**. This makes it possible to eliminate static electricity generated in the piezoelectric element **802**.

(96) According to the present embodiment, it is possible to obtain the same advantageous effects as provided by the first embodiment, in forming the strong rolling surfaces **30**, reducing the number of processing steps for forming the rolling surfaces **30**, and increasing the strength of the movable member **801**.

(97) Further, even in a case where the piezoelectric element **802** and the vibration member **803** are provided to remove fine dust, it is possible to eliminate static electricity by electrically connecting between the electrically conductive member **804** and the sheet metal member **801b**.

(98) Next, a sixth embodiment of the present invention will be described. Although in the first to fifth embodiments, the image blur correction device is applied to the camera body **1**, in the sixth embodiment of the present invention, the image blur correction device is applied to the lens barrel **2**. More specifically, the present invention is applied to the lens-side shake correction unit **13a** (see FIGS. **1A** and **1B**).

(99) FIG. **9A** is a view of the lens-side shake correction unit **13a**, as viewed from the + (positive) side in the z-axis direction. FIGS. **9B** and **9C** are cross-sectional views taken along G-G and H-H in FIG. **9A**, respectively.

(100) A movable member **80** includes a resin part **80a** and a sheet metal member **80b**. The resin part **80a** is molded integrally with the sheet metal member **80b**. The shake correction lens **3a** is fixed to the movable member **80** and can be displaced in accordance with driving of the movable member **80**. The movable member **80** includes coils **81** (**81a** and **81b**), position detection sections **82** (**82a** and **82b**), magnets **83** (**83a** to **83h**), a yoke **84**, rolling balls **85**, a fixed member **86**, an adhesive **88**, rolling surfaces **89** (**89a**, **89b** and **89c**), and an optical axis urging spring **87** for holding the movable member **80** at the center of the optical axis **4**. The coils **81**, the position detection sections **82**, the magnets **83**, and the yoke **84** of the movable member **80** correspond to the coils **21**, the position detection sections **22**, the magnets **24**, and the first yoke **25** of the movable member **20** (see FIG. **4B** and the like), respectively. The rolling balls **85**, the fixed member **86**, the adhesive **88**, and the rolling surfaces **89** of the movable member **80** correspond to the rolling balls **26**, the fixed member **28**, the adhesive **40**, and the rolling surfaces **30** of the movable member **20**, respectively.

(101) In the movable member **80**, the position detection sections **82** (**82a** and **82b**) are provided in association with the coils **81** (**81a** and **81b**). The movable member **80** includes the eight magnets **83** formed by a group of the magnets **83a**, **83b**, **83e**, and **83f** which are arranged in an opposed relation to the coil **81a**, and a group of the magnets **83c**, **83d**, **83g**, and **83h** which are arranged in an opposed relation to the coil **81b**. By energizing the coils **81** arranged in magnetic circuits generated by these magnets **83**, the movable member **80** receives the Lorentz force, whereby it is translationally movable in the x-axis direction and the y-axis direction.

(102) Each rolling surface **89** is part of the sheet metal member **80b** exposed from the resin part **80a** of the movable member **80** and is brought into contact with the rolling ball **85**. The rolling surfaces **89** are provided at three locations (rolling surfaces **89a**, **89b**, and **89c**). Further, as is clear from FIGS. **9A** and **9B**, the sheet metal member **80b** is arranged such that it surrounds the shake correction lens **3a** as the optical element, as viewed from the direction of the optical axis **4**. This increases the strength of the movable member **80**. Further, a bonding surface of the movable member **80**, bonded to the shake correction lens **3a** with the adhesive **88**, is formed by the resin part **80a**.

(103) As shown in FIG. **9B**, the rolling balls **85** are arranged on the – (negative) side in the z-axis direction of the movable member **80**. Therefore, it is preferable that the movable member **80** is urged toward the – (negative) side in the z-axis direction. To this end, similar to the first embodiment, the urging mechanism using magnetism of the sheet metal member **80b** is provided. Here, reference numeral **91** in FIG. **9C** indicates a distance from the sheet metal member **80b** to the magnets **83e** to **83h** in the direction of the optical axis **4**. Reference numeral indicates a distance **92** from the sheet metal member **80b** to the magnets **83a** to **83d**. The distance **92** is shorter than the distance **91**. Therefore, the attraction force applied to the sheet metal member **80b** is stronger on the – (negative) side in the z-axis direction than on the + (positive) side in the z-axis direction, and as a result, the movable member **80** is urged toward the fixed member **86**.

(104) According to the present embodiment, in the lens-side shake correction unit **13a** of the lens barrel **2**, it is possible to obtain the same advantageous effects as provided by the first embodiment, in forming the strong rolling surfaces **89**, reducing the number of processing steps for forming the rolling surface **89**, and increasing the strength of the movable member **80**.

(105) Note that at least one of the characteristic features of the image blur correction device applied to the camera body **1**, described as the second to fifth embodiments, may be employed in the image blur correction device applied to the lens barrel **2** of the present embodiment. Further, two or more of the first to fifth embodiments may be appropriately combined, insofar as no inconsistency occurs when realizing the combination.

(106) Note that when considering an object to which the present invention is applied, the camera body **1** having the image blur correction function may be regarded as the “image capture apparatus”. Further, the present invention may be applied to both of the image blur correction devices of the camera body **1** and the lens barrel **2**.

(107) Note that in the above-described embodiments, the image blur correction function is provided in both of the camera body **1** and the lens barrel **2**. In a case where the present invention is applied to the camera body **1** as a single unit, the camera-side shake correction unit **14** is needed. In a case where the present invention is applied to the lens barrel **2** as a single unit, the lens-side shake correction unit **13a** is needed. However, in a case where the present invention is applied to a lens-integrated type image capture apparatus, the image blur correction function may be provided in at least one of the camera body **1** and the lens barrel **2**.

(108) FIG. **10A** is a cross-sectional view of an image capture apparatus to which an image blur correction device according to a seventh embodiment of the present invention is applied. FIG. **10B** is a block diagram showing an electrical configuration of the image capture apparatus, denoted by reference numeral **1000'**. Component elements in the present embodiment, corresponding to those of the first embodiment described with reference to FIGS. **1A** and **1B**, are denoted by the same reference numerals. This image capture apparatus **1000'** is formed by a camera body **1001**, and a lens barrel **1002**. The lens barrel **1002** is removable from the camera body **1001** and the image capture apparatus **1000'** is a so-called lens interchangeable camera. Note that the camera body **1001** and the lens barrel **1002**, which are fixed to each other and cannot be removed from each other, may be regarded as the image capture apparatus, and the present invention can be applied to this image capture apparatus.

(109) The lens barrel **1002** includes the photographing optical system **3**, the lens system controller

12, and the lens drive section **13**. The photographing optical system **3** is formed by a plurality of lenses. The lens drive section **13** is capable of driving the focus lens, the shake correction lens, the diaphragm, and so forth.

(110) The camera body **1001** includes the camera system controller **5**, the image processor **7**, the memory section **8**, the display section **9**, the operation detection section **10**, a shake detection section **15'**, an anti-vibration mechanism **114**, an image capture device package **6'**, a shutter mechanism **116**, and the electric contact **11**. The image capture device package **6'** includes an image sensor **6a** (see FIG. **12A**) as an image capture device that photoelectrically converts an optical image formed through the lens barrel **1002**. The display section **9** includes the rear-side display device **9a** provided on the rear side of the camera body **1001** and the EVF (electronic viewfinder) **9b** provided within the finder of the camera body **1001**. The operation detection section **10** detects signals output from an operation section including a shutter release button, not shown, and so forth. The electric contact **11** is for communication between the camera body **1001** and the lens barrel **1002**.

(111) The shake detection section **15'** is formed by a plurality of inertial sensors, and is capable of detecting displacement of the camera body **1001**, such as movement and rotation. More specifically, the shake detection section **15'** is formed by an accelerometer, a vibrating gyroscope, and so forth. The anti-vibration mechanism **114** is a mechanism for translationally moving the image capture device package **6'** within a plane orthogonal to the optical axis **4** (photographing optical axis) of the photographing optical system **3**, and rotating the same about the optical axis **4**. Details of the structure of the anti-vibration mechanism **114** will be described hereinafter. A shake correction unit is formed by the anti-vibration mechanism **114**, the shake-detection section **15'**, and the camera system controller **5** that controls these components.

(112) The image capture apparatus **1000'** formed by the camera body **1001** and the lens barrel **1002** includes an image capture unit, an image processing unit, a recording/reproduction unit, and a control unit. The image capture unit mentioned here includes the photographing optical system **3**, the image capture device package **6'**, and the shutter mechanism **116**. The image processing unit includes the image processor **7**. Further, the recording/reproduction unit includes the memory section **8** and the display section **9**. The control unit includes the camera system controller **5**, the operation detection section **10**, the lens system controller **12**, the lens drive section **13**, the anti-vibration mechanism **114**, and the shake detection section **15'**.

(113) The above-mentioned image capture unit is an optical processing system configured to form through the photographing optical system **3** an image of light from an object on an image plane of the image capture device package **6'**. A focus evaluation amount and a proper exposure amount can be obtained from the image capture device package **6'** and the photographing optical system **3** is properly adjusted based on signals thereof, whereby the image capture device package **6'** is exposed to an object light with a proper light amount to form an object image at or in the vicinity of the image capture device package **6'**.

(114) The shutter mechanism **116** controls running of a shutter curtain to thereby control whether or not to cause the object image to reach the image capture device package **6'**. The shutter mechanism **116** includes at least a curtain (mechanical rear curtain) for shielding an object image, and exposure is completed by the operation of the shutter mechanism **116**. The camera body **1001** has a mode (electronic front curtain mode) in which the timing of starting exposure is controlled by the image capture device package **6'** resetting charges on a line-by-line basis before running the rear curtain of the shutter mechanism **116**. The camera body **1001** performs, in the electronic front curtain mode, exposure control by causing the electronic front curtain of the image capture device package **6'** for resetting charge and the rear curtain of the shutter mechanism **116** to operate in synchronism with each other. A lot of prior arts related to the electronic front curtain have already been disclosed and hence description thereof is omitted.

(115) The image processor **7** incorporates an analog-to-digital converter, a white balance

adjustment circuit, a gamma correction circuit, an interpolation calculation circuit, and so forth, and is capable of generating an image for recording. A color interpolation processor is included in the image processor **7**, and generates a color image by performing color interpolation (demosaicing) on Bayer signals. Further, the image processor **7** compresses a still image, a moving image, sound, and so forth, using a predetermined method.

(116) The memory section **8** includes a storage medium. The camera system controller **5** outputs an image to the memory section **8**, and displays an image to be presented to a user on the display section **9**. The camera system controller **5** generates and outputs a timing signal, and so forth, for use in image capture. The camera system controller **5** controls the image capture system, the image processing system, and the recording and reproduction system, in response to an external operation. For example, when it is detected by the operation detection section **10** that the shutter release button, not shown, has been pressed, the camera system controller **5** controls driving of the image capture device **6**, the operations of the image processor **7**, including compression processing, and so forth. Further, the camera system controller **5** controls the state of each segment on the display section **9**. Note that the rear-side display device **9a** is implemented by a touch panel and is connected to the operation detection section **10**.

(117) The operation for adjusting the optical system will be described. The image processor **7** is connected to the camera system controller **5**, and the camera system controller **5** determines an appropriate focus position and a diaphragm position based on signals output from the image capture device package **6'**. More specifically, the camera system controller **5** performs photometry and ranging operations based on the signals output from the image capture device package **6'**, and determines exposure conditions (an F-number, a shutter speed, etc.). The camera system controller **5** sends commands to the lens system controller **12** via the electric contact **11** and the lens system controller **12** properly controls the lens drive section **13**. Further, in a mode for performing shake correction, the camera system controller **5** controls the lens drive section **13** to properly control the shake correction lens based on signals obtained from the image capture device package **6'**.

(118) Further, as described above, the camera system controller **5** and the lens system controller **12** controls the operations of the components of the camera body **1001** and the lens barrel **1002** according to user operations performed on respective operation sections provided on the camera body **1001** and the lens barrel **1002**. With this, it is possible to photograph a still image and a moving image.

(119) A brief description will be given of a flow of the shake correction control. As described above, the shake correction unit is formed by the shake detection section **15'** that detects a shake, the anti-vibration mechanism **114** that performs the shake correction operation, and the camera system controller **5** that generates an operation target value of the anti-vibration mechanism **114** based on signals output from the shake detection section **15'** and controls the driving of the anti-vibration mechanism **114**. The operation detection section **10** detects a user operation of half-pressing the shutter release button, not shown, to start a photographing preparation operation. This photographing preparation operation is a so-called aiming operation for determining the composition. In the photographing preparation operation, to make it easy to determine the composition, the camera system controller **5** performs an anti-vibration operation using the anti-vibration mechanism **114**. More specifically, the camera system controller **5** realizes anti-vibration by properly controlling the anti-vibration mechanism **114** based on signals output from the shake detection section **15'**. After that, the operation detection section **10** detects a user operation of fully pressing the shutter release button to start the photographing operation. In the photographing operation, to suppress blur of an object image acquired by the exposure operation, the camera system controller **5** performs the anti-vibration operation using the anti-vibration mechanism **114**. When a certain time period has elapsed after the exposure operation, the anti-vibration operation is stopped.

(120) FIG. **11** is an exploded perspective view of a mechanism for correcting a shake, which is

included in the anti-vibration mechanism **114**. Although the anti-vibration mechanism **114** has an electric mechanism additionally provided for execution of control, the electric mechanism is omitted from illustration. Referring to FIG. **11**, a direction along vertical dashed-dotted lines is parallel to the optical axis **4**. The description is given defining the direction of the optical axis **4** (photographing optical axis direction) as the z-axis direction. The + (positive) side in the z-axis direction is the object side.

(121) A member group not displaced in shake correction is a fixed unit **100**, and in FIG. **11**, component elements of the member group which are not displaced are denoted by reference numerals in **100s**. A member group displaced in shake correction is a movable unit **200**, and in FIG. **11**, component elements of the member group which are displaced are denoted by reference numerals in **200s**. Further, rolling members sandwichingly held between the fixed unit **100** and the movable unit **200** are balls **301** (**301a**, **301b**, and **301c**).

(122) The anti-vibration mechanism **114** includes an upper yoke **101**, screws **102** (**102a**, **102b**, and **102c**), upper magnets **103** (**103a**, **103b**, **103c**, **103d**, **103e**, and **103f**), and auxiliary spacers **104** (**104a** and **104b**). Further, the anti-vibration mechanism **114** includes main spacers **105** (**105a**, **105b**, and **105c**), fixed unit rolling plates **106** (**106a**, **106b**, and **106c**), and lower magnets **107** (**107a**, **107b**, **107c**, **107d**, **107e**, and **107f**). Further, the anti-vibration mechanism **114** includes a lower yoke **108**, screws **109** (**109a**, **109b**, and **109c**), a base plate **110**, an FPC (flexible circuit board) **201**, a movable PCB (electric wiring board) **203**, and movable unit rolling plates **204** (**204a**, **204b**, and **204c**). Further, the anti-vibration mechanism **114** includes coils **205** (**205a**, **205b**, and **205c**), a movable frame **206** (holding member), and the balls **301a**, **301b**, and **301c**.

(123) The upper yoke **101**, the upper magnets **103**, the lower magnets **107**, and the lower yoke **108** form magnetic circuits, and these components form so-called closed magnetic circuits. The upper magnets **103** are fixedly bonded to the upper yoke **101** in an attracted state. Similarly, the lower magnets **107** are fixedly bonded to the lower yoke **108** in an attracted state. The upper magnets **103** and the lower magnets **107** are each magnetized in the direction of the optical axis **4** (vertical direction, as viewed in FIG. **11**). The magnets adjacent to each other (such as the upper magnet **103a** and the upper magnet **103b**, and magnets having the same positional relationship as these) of the upper magnets **103** and the lower magnets **107** are magnetized in directions different from each other. Further, the magnets, opposed to each other (such as the upper magnet **103a** and the lower magnet **107a**, and magnets having the same positional relationship as these) are magnetized in the same direction. By magnetizing the magnets as described above, a strong magnetic flux density is generated in the optical axis direction between the upper yoke **101** and the lower yoke **108**.

(124) Since a strong attraction force is generated between the upper yoke **101** and the lower yoke **108**, a proper space is secured between the upper yoke **101** and the lower yoke **108** by the main spacers **105** and the auxiliary spacers **104**. The proper space mentioned here is a space which makes it possible to arrange the coils **205** and the FPC **201** between the upper magnets **103** and the lower magnets **107**, and secure a proper gap. The main spacers **105** are each formed with a screw hole, and the upper yoke **101** is fixed to the main spacers **105** by the corresponding screws **102**. Rubber is arranged on a body portion of each main spacer **105**, and this rubber functions as a regulating portion (so-called stopper) when the movable unit **200** is displaced

(125) The base plate **110** is formed with openings such that the lower magnets **107** can be received therein and the surfaces of the lower magnets **107** protrude from these openings. Each lower magnet **107** is thicker than the base plate **110**. When the base plate **110** and the lower yoke **108** are fixed by the screws **109**, the lower magnets **107**, larger in the dimension in the thickness direction than the base plate **110**, protrude from the base plate **110** toward the + (positive) side in the z-axis direction.

(126) The movable frame **206** is formed of resin containing a large amount of a plasticizer and is light in weight and high in rigidity. Further, the movable frame **206** has a low linear expansion coefficient. The linear expansion coefficient will be explained hereinafter with reference to FIGS.

12A to 12C. The movable unit **200** is formed by fixing a plurality of component elements to the movable frame **206**. The FPC **201** has position detection elements, disposed on a surface on a side hidden in FIG. **11** (the – (negative) side in the z-axis direction), at respective locations indicated by mounting positions **202a**, **202b**, and **202c**. Each position detection element employs e.g. a Hall element so as to make it possible to perform position detection using the above-mentioned magnetic circuit. The Hall element is small-sized, and hence the position detection elements are arranged in a state nested within the coils **205a**, **205b**, and **205c**, respectively.

(127) The movable PCB **203** forms part of the image capture device package **6'**, as described hereinafter. Further, the coils **205** and the above-mentioned position detection elements are connected to the movable PCB **203**. Electrical communication is performed with the outside via a connector on the movable PCB **203**. The fixed unit rolling plates **106** are fixedly bonded to the base plate **110**. The movable unit rolling plates **204** are fixedly bonded to the movable frame **206**. The fixed unit rolling plates **106** and the movable unit rolling plates **204** form the rolling surfaces of the balls **301**. The movable unit **200** is displaced relative to the fixed unit **100** via the balls **301**. The movable unit **200** and the fixed unit **100** are brought into contact with each other via the balls **301**, and hence an external force applied to the movable unit **200** and distortion generated in the movable unit **200** are not transmitted to the fixed unit **100**. That is, even when distortion is generated in the movable unit **200**, distortion is not generated in the fixed unit **100**. Further, even when distortion is generated due to temperature change in the members, such as the image capture device package **6'**, which are in contact with the movable unit **200**, the generated distortion is transmitted only up to the movable frame **206**. Therefore, to cope with occurrence of thermal stress due to temperature change in the image capture device package **6'**, it is only required to pay attention to the linear expansion coefficients of the components in a range from the image capture device package **6'** to the movable frame **206**. Note that since the rolling plates are additionally or separately provided, it is easy to design the surface roughness and hardness of the rolling plates in a preferable state.

(128) By causing electric current to flow through the coils **205** in the above-mentioned magnetic circuit, the coils **205** receive the Lorentz force, whereby the movable unit **200** can be displaced. Further, the camera system controller **5** can perform feedback control using signals output from the position detection elements. The camera system controller **5** properly controls the values of signals of the position detection elements, whereby it is possible to translationally move the movable frame **206** within a plane orthogonal to the optical axis **4** and rotate the same about the optical axis. Further, it is possible to generate a rotational motion of the movable frame **206** substantially about the optical axis **4**, by driving the signals of the position detection elements disposed at the mounting positions **202b** and **202c** in opposite phase while maintaining a signal of the position detection element disposed at the mounting position **202a** to a fixed value.

(129) The magnetic flux density in the optical axis direction is detected at each mounting position **202**. The magnetic circuits formed by the upper magnets **103**, the lower magnets **107**, and so forth, generally have non-linear characteristics. Therefore, the magnetic flux densities detected at the mounting positions **202** do not necessarily have a fixed resolution in the whole driving range, in other words, the detection resolution varies with the position. This is because there are positions where the magnetic flux density rapidly changes and positions where the magnetic flux density moderately changes, and the amount of change of the magnetic flux density with respect to the movement amount is larger at the position where the magnetic flux density more rapidly changes, resulting in a higher detection resolution. In the magnetic circuits in the anti-vibration mechanism **114** shown in FIG. **11**, a boundary position between the magnets (such as a boundary position between the upper magnet **103a** and the upper magnet **103b**) has the largest change in magnetic flux density and hence the highest detection resolution.

(130) FIGS. **12A** and **12B** are schematic cross-sectional views of the image capture device package **6'** and the movable frame **206**. The movable frame **206** is a holding member for holding the image

capture device package **6'**. FIG. **12A** and FIG. **12B** differ from each other in the form of adhesion between the movable frame **206** and the image capture device package **6'**. Although the present embodiment employs the form of adhesion shown in FIG. **12A**, the form of adhesion shown in FIG. **12B** may be employed. FIG. **12C** is a cross-sectional view schematically showing a state of distortion of the image capture device package **6'**, caused in a case where there are differences in linear expansion coefficient between the components within the image capture device package **6'**. (131) As shown in FIG. **12A**, the image capture device package **6'** includes the image sensor **6a**, a glass lid **6b**, an image capture device-holding frame **6c**, and the movable PCB **203**. The image capture device package **6'** and the movable frame **206** are fixedly bonded to each other with an adhesive **40'**. Particularly, in the illustrated example in FIG. **12A**, the movable PCB **203** as the component of the image capture device package **6'** and the movable frame **206** are bonded to each other. In the illustrated example in FIG. **12B**, the image capture device-holding frame **6c** as the component of the image capture device package **6'** and the movable frame **206** are bonded to each other.

(132) In the movable unit **200**, a surface bonded to the image capture device package **6'** with the adhesive **40'** is formed of resin. A reason for this will be described. In general, when bonding components with an adhesive, it is necessary to provide a place where the adhesive is applied (hereinafter referred to as the adhesive pool). In general, the same image capture device can be used for a lot of models, but on the other hand, the movable member **20** is designed on a model-by-model basis, and hence the adhesive pool is also designed on a model-by-model basis. For this reason, to make it possible to freely arrange the adhesive pool with a higher degree of freedom in shape, it is preferable that the bonding surface is formed by a resin.

(133) Further, when the camera body **1** is exposed to a high-temperature or low-temperature environment, if a difference in the linear expansion coefficient is large between an outer periphery portion of the image capture device **6'**, as one bonding surface, and part of the movable member **200**, as the other bonding surface, the image capture device **6'** and the movable member **200** may warp in a direction opposite to each other. This is caused by occurrence of thermal distortion. Thus, if the image capture device **6'** warps from the movable member **200**, a problem is caused that the image capture device **6'** tilts with respect to the optical axis **4** and hence tilts with respect to the image plane of the camera body **1001**, which may cause blur in part of a photographed image. One solution for this problem is that the linear expansion coefficient of the bonding surface of the movable member **200**, bonded to the image capture device **6**, and the linear expansion coefficient of the bonding surface of the image capture device **6'** are made closer to each other. In the present embodiment, the linear expansion coefficients of the bonding surfaces are set taking this into consideration.

(134) First, in the illustrated example in FIG. **12A**, part (surface on the – (negative) side in the z-axis direction) of the movable PCB **203** of the image capture device package **6'**, which is in contact with the adhesive **40'**, is a first adhesion interface B1. Therefore, the part forming the first adhesion interface B1 is part of the movable PCB **203**. Further, part (inside surface) of the movable frame **206** of the movable unit **200**, which is in contact with the adhesive **40'**, is a second adhesion interface B2. Therefore, the part forming the second adhesion interface B2 is part of the movable frame **206**.

(135) On the other hand, in the illustrated example in FIG. **12B**, part (surface on the – (negative) side in the z-axis direction) of the image capture device-holding frame **6c** of the image capture device package **6'**, which is in contact with the adhesive **40'**, is the first adhesion interface B1. Therefore, the part forming the first adhesion interface B1 is part of the image capture device-holding frame **6c** which is a resin member. Further, similar to the illustrated example in FIG. **12A**, part of the movable frame **206** of the movable unit **200**, which is in contact with the adhesive **40'**, is the second adhesion interface B2. Therefore, the part forming the second adhesion interface B2 is part of the movable frame **206**.

(136) Deformation (warp) of the image capture device package **6'** as a single unit, caused due to temperature change, will be described with reference to FIG. **12C**. If the linear expansion coefficient is largely different between the image sensor **6a**, the glass lid **6b**, the image capture device-holding frame **6c**, and the movable PCB **203**, which are the components of the image capture device package **6'**, distortion is sometimes caused in the image capture device package **6'** due to temperature change. For example, a warp, similar to a warp of so-called bimetal, is sometimes caused.

(137) FIG. **12C** shows an example of deformation caused in a case where the linear expansion coefficient of the movable PCB **203** is larger than that of the glass lid **6b** and the temperature rises. The movable PCB **203** extends more than the glass lid **6b** due to increase in temperature, and hence such a warp as shown in FIG. **12C** is generated. As a result, distortion is caused on the surface of the image sensor **6a**, which makes it difficult to accurately adjust the focus. To suppress this phenomenon, materials whose linear expansion coefficients are close to each other are often selected for the components of the image capture device package **6'**.

(138) The image sensor **6a** is made of silicon single crystal, and hence its linear expansion coefficient is small, and is approximately $2.6 \times 10^{-6}/K$ at normal temperature. This value is smaller by approximately one digit, compared with metal, such as aluminum (approximately $23.1 \times 10^{-6}/K$), magnesium (approximately $24.8 \times 10^{-6}/K$), and stainless steel (SUS304: approximately $17.8 \times 10^{-6}/K$). Therefore, a circuit board material having a low linear expansion coefficient is employed for the movable PCB **203**. A material having a linear expansion coefficient in a range of approximately $2 \times 10^{-6}/K$ to $5 \times 10^{-6}/K$ can be used for a circuit board using glass cloth having a low linear expansion coefficient. Similarly, a material having a low linear expansion coefficient is employed for the glass lid **6b** as well. For example, so-called Pyrex (registered trademark) glass having a low linear expansion coefficient of approximately $3 \times 10^{-6}/K$ is employed.

(139) A so-called low linear expansion resin for package or the like is employed for the image capture device-holding frame **6c**. Examples of the material include one formed by filling epoxy with plasticizer at a high rate, and the material having a linear expansion coefficient of approximately $10 \times 10^{-6}/K$ is provided. As in the above-described example, it is possible to suppress warp or the like, caused by temperature change, by using materials each having a low linear expansion coefficient, for the components forming the image capture device package **6'**. This reduces the phenomenon that the image plane is bent and the focus on the whole screen cannot be adjusted.

(140) However, if the linear expansion coefficient is largely different between the image capture device package **6'** and the movable frame **206**, the adhesive **40'** is deformed when the temperature has change, and thermal stress is caused in the adhesive **40'** and the adhesion interface. If the camera body **1001** is exposed to a condition that the temperature rapidly changes, the bonding surfaces can be peeled. Polycarbonate as resin generally used for a lot of image capture apparatuses mostly has a linear expansion coefficient of approximately $50 \times 10^{-6}/K$. Even a polycarbonate composition formed by filling glass has a linear expansion coefficient in a range of approximately $20 \times 10^{-6}/K$ to $40 \times 10^{-6}/K$. As described hereinafter, resin having a linear expansion coefficient in a range of approximately $17 \times 10^{-6}/K$ to $24 \times 10^{-6}/K$ is employed for the movable frame **206**. In general, the resin material tends to be reduced in shock resistance when the linear expansion coefficient is reduced and plasticizer is filled at a high rate. That is, if the material is selected only from the viewpoint of the linear expansion coefficient, there is a fear that a crack is caused in the movable frame **206** when the image capture apparatus is dropped.

(141) To prevent this, in the present embodiment, the linear expansion coefficients of the components are set such that the linear expansion coefficient is gradually increased in an order from the silicon having a low linear expansion coefficient (image sensor **6a**) to the movable frame **206**. The order of stepwise increase in the magnitude of the linear expansion coefficient in this case

is expressed by using the inequality of (image sensor **6a**)<(part forming the first adhesion interface B1)<(part forming the second adhesion interface B2)<(aluminum alloy or magnesium alloy).

(142) That is, the linear expansion coefficient of the part forming the first adhesion interface B1 (the part of the movable PCB **203** in the example in FIG. **12A** and the part of the image capture device-holding frame **6c** in the example in FIG. **12B**) is larger than the linear expansion coefficient of the image sensor **6a**. Further, the part forming the second adhesion interface B2 (part of the movable frame **206**) is formed of resin. What is more, the linear expansion coefficient of the part forming the second adhesion interface B2 (part of the movable frame **206**) is larger than the linear expansion coefficient of the part forming the first adhesion interface B1 (the part of the movable PCB **203** in the example in FIG. **12A** and the part of the image capture device-holding frame **6c** in the example in FIG. **12B**). Further, the linear expansion coefficient of the part forming the second adhesion interface B2 (the part of the movable frame **206**) is smaller than the linear expansion coefficient of any of the aluminum alloy and the magnesium alloy.

(143) By arranging the components such that the linear expansion coefficient is gradually increased from the image sensor **6a** to the movable frame **206** in the order expressed by the above inequality, a difference of the linear expansion coefficient between each adjacent components becomes small, compared with a case where the components are arranged in a disorderly manner. As a result, it is possible to suppress thermal stress caused due to a difference of the linear expansion coefficient between the fixed components adjacent to each other, and reduce the influence caused by temperature change without extremely narrowing the range of choices of the material. Further, since the linear expansion coefficient of the part forming the second adhesion interface B2 is smaller than the linear expansion coefficient of any of the aluminum alloy and magnesium alloy, it is possible to reduce thermal stress more than in a case where the aluminum alloy or the magnesium alloy, which is a general material of the movable frame, is used.

(144) Examples of the resin material of the movable frame **206**, satisfying the above inequality, include TORELINA A310MX04 (registered trademark), manufactured by Toray Industries, Inc. This resin contains PPS, epoxy, or nylon, as a base resin. In this resin, the linear expansion coefficient is suppressed to a range of approximately $17 \times 10^{-6}/K$ to $24 \times 10^{-6}/K$ by highly filling plasticizer while using PPS as the base resin. Further, this resin satisfies the requirement of the level of the shock resistance for the movable frame. Examples of this resin, which is easy to obtain good characteristics while being highly filled with plasticizer, include PPS, epoxy, or nylon. It is only required to form the movable frame **206** by using a material formed by using any of these resin materials as the base.

(145) According to the present embodiment, the components are arranged with the adhesive **40'** interposed therein such that the linear expansion coefficient is gradually increased from the image sensor **6a** to the movable frame **206** in the order expressed by the above-described inequality. This makes it possible to suppress occurrence of thermal stress on the adhesion interface, caused due to temperature change, and thereby enhance the reliability of the image blur correction function.

(146) Further, the balls **301** are sandwichingly held between the movable unit **200** and the fixed unit **100**, and the fixed unit **100** holds the movable unit **200** via the balls **301** such that it is relatively displaceable. With this, even when distortion is caused in the movable unit **200** due to temperature change, the distortion is not transmitted to the fixed unit **100** and is hard to adversely affect the fixed unit **100**. In this point as well, it is also possible to enhance the reliability of the image blur correction function.

(147) Next, an eighth embodiment of the present invention will be described. In the eighth embodiment, the movable frame **206** is formed by a sheet metal member and a resin part molded integrally with the sheet metal member. The present embodiment differs from the first embodiment in the construction of the movable frame **206** and the form of adhesion between the movable frame **206** and the image capture device package **6'**, and is the same in the other components as the first embodiment.

(148) FIG. 13A is a view of the anti-vibration mechanism 114, as viewed from the optical axis direction. FIG. 13B is a cross-sectional view taken along A-A in FIG. 13A. The same component elements in FIGS. 13A and 13B as those of the first embodiment are denoted by the same reference numerals.

(149) As shown in FIG. 13B, the movable member 206 includes a resin part 206a and a sheet metal member 206b. In the movable member 206, the resin part 206a is molded integrally with the sheet metal member 206b such that the resin part 206a covers the sheet metal member 206b. That is, the resin part 206a is formed integrally with the sheet metal member 206b by insert molding.

(150) The balls 301 are arranged on the – (negative) side in the z-axis direction with respect to the movable unit 200. Therefore, it is preferable that the movable unit 200 is urged toward the – (negative) side in the z-axis direction. In general, in a case where two members are urged to approach each other, it is necessary to additionally provide a member for urging them. However, in the present embodiment, the urging force is obtained by making use of the magnetism of the sheet metal member 206b and the lower magnets 107.

(151) The sheet metal member 206b is formed by a metallic material having magnetism. Part of the sheet metal member 206b is opposed to the upper magnets 103 and the lower magnets 107, and hence the sheet metal member 206b is attracted by the upper magnets 103 and the lower magnets 107 (magnetic attraction). Therefore, whether the movable unit 200 is more strongly magnetically-attracted toward the + (positive) side in the z-axis direction or the – (negative) side in the z-axis direction is determined depending on distances from the sheet metal member 206b to the upper magnets 103 and the lower magnets 107 in the z-axis direction.

(152) Here, reference numeral 41' in FIG. 13B indicates a distance from the sheet metal member 206b to the upper magnets 103e and 103f. Reference numeral 42' indicates a distance from the sheet metal member 206b to the lower magnets 107e and 107f. Note that when comparing these distances 41' and 42', the position of the sheet metal member 206b is represented by the position of the center of the sheet metal member 206b in a direction of the thickness of the sheet metal member 206b. In the present embodiment, the distance 42' is shorter than the distance 41'. Therefore, the attraction force applied to the sheet metal member 206b is stronger on the – (negative) side in the z-axis direction than on the + (positive) side in the z-axis direction, and as a result, the movable member 200 is urged toward the base plate 110. The balls 301 are sandwichingly held by this urging force. The balls 301 are enabled to smoothly roll with less loss caused by friction.

(153) In the present embodiment, the sheet metal member 206b of the movable frame 206 is covered with the resin part 206a. If a difference of the linear expansion coefficient between the sheet metal member 206b and the image capture device package 6' is large, it is preferable to form the resin part 206a using a resin material having a linear expansion coefficient closer to that of the image capture device package 6'. Thus, from the viewpoint of the degree of freedom in shape and the viewpoint of the physical properties of the material, it is preferable that the surface of the movable unit 200, bonded to the image capture device package 6', is formed by the resin part 206a.

(154) For this reason, in the present embodiment, the image capture device package 6' and the resin part 206a are bonded with the adhesive 40'. Part of the image capture device package 6' (a side surface of the image capture device package 6' including at least a side surface of the image capture device-holding frame 6c), which is in contact with the adhesive 40', is a first adhesion interface D1. Therefore, the part forming the first adhesion interface D1 includes part of the image capture device-holding frame 6c. Further, part (inside surface) of the resin part 206a of the movable frame 206, which is in contact with the adhesive 40', is a second adhesion interface D2. Therefore, the part forming the second adhesion interface B2 includes part of the resin part 206a.

(155) Here, the linear expansion coefficient of each component is considered. Stainless steel or the like is suitable for the sheet metal member 206b, and the linear expansion coefficient in this case is (SUS304: approximately $17.8 \times 10^{-6}/K$). The materials of the components of the image capture device package 6' are the same as those used in the first embodiment. As described hereinafter,

resin having a linear expansion coefficient of approximately $12 \times 10^{-6}/K$ is used for the movable frame **206**. The linear expansion coefficient of each component is set such that the linear expansion coefficient is gradually increased in an order from the image sensor **6a** to the movable frame **206**. The order of increase in the magnitude of the linear expansion coefficient in this case is expressed by using the inequality of (image sensor **6a**) < (part forming the first adhesion interface D1) < (part forming the second adhesion interface D2) < (sheet metal member **206b**).

(156) By arranging the components in the order expressed by the above inequality, it is possible to suppress thermal stress caused by a difference of the linear expansion coefficient between the fixed components, adjacent to each other, and reduce the influence caused by temperature change without extremely narrowing the range of choices of the material. Further, it is possible to reduce thermal stress more than in a case where the sheet metal member **206b** is bonded without covering the sheet metal member **206b**. Since the sheet metal member **206b** is formed of metal, a range of choices of the linear expansion coefficient is narrow. However, by forming the second adhesion interface D2 using the resin part **206a** of the movable frame **206**, the range of choices of the material is increased.

(157) Examples of the material of the resin part **206a**, satisfying the above-mentioned condition, include TORELINA H501 (registered trademark), manufactured by Toray Industries, Inc. In this resin, the linear expansion coefficient is suppressed to approximately $12 \times 10^{-6}/K$ by highly filling plasticizer while using PPS as the base resin. Further, this resin satisfies the requirement of the level of the shock resistance for the movable frame. It is only required to form the movable frame **206** by using a material formed by using this resin as the base, for the resin part **206a**.

(158) According to the present embodiment, the components are arranged with the adhesive **40'** interposed therein such that the linear expansion coefficient is gradually increased from the image sensor **6a** to the movable frame **206** in the order expressed by the above inequality. With this, it is possible to obtain the same advantageous effects as provided by the seventh embodiment in suppressing occurrence of thermal stress on the adhesion interface to thereby enhance the reliability of the image blur correction function. Further, it is possible to obtain the same advantageous effects as provided by the seventh embodiment in that distortion caused in the movable unit **200** is hard to be transmitted to the fixed unit **100**.

(159) While the present invention has been described with reference to exemplary embodiments, it is to be understood that the invention is not limited to the disclosed exemplary embodiments. The scope of the following claims is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures and functions.

(160) This application claims the benefit of Japanese Patent Application No. 2018-237496, filed Dec. 19, 2018, No. 2019-116537, filed Jun. 24, 2019, and No. 2019-116536, filed Jun. 24, 2019, which are hereby incorporated by reference herein in their entirety.

Claims

1. An image blur correction device comprising: an image capture device package including an image capture device; a holding member that holds the image capture device package; a fixed part that holds the holding member such that the holding member is relatively displaceable; a rolling member sandwichingly held between the holding member and the fixed part, wherein the fixed part holds the holding member via the rolling member such that the holding member is relatively displaceable; and an adhesive for fixing a first adhesion interface on the image capture device package and a second adhesion interface on the holding member, wherein a linear expansion coefficient of a part forming the first adhesion interface is larger than a linear expansion coefficient of the image capture device, wherein a part forming the second adhesion interface is formed of resin, and a linear expansion coefficient of the part forming the second adhesion interface is larger than the linear expansion coefficient of the part forming the first adhesion interface, and wherein

- the linear expansion coefficient of the part forming the second adhesion interface is smaller than a linear expansion coefficient of any of an aluminum alloy and a magnesium alloy.
2. The image blur correction device according to claim 1, wherein the image capture device package includes a circuit board and the first adhesion interface is provided on the circuit board.
 3. The image blur correction device according to claim 1, wherein the first adhesion interface is provided on a resin member included in the image capture device package.
 4. The image blur correction device according to claim 1, wherein the part forming the second adhesion interface is formed of resin having PPS, epoxy, or nylon as a base resin.
 5. An image blur correction device comprising: an image capture device package including an image capture device; a holding member that includes a sheet metal member and a resin part molded integrally with the sheet metal member, and holds the image capture device package; a fixed part that holds the holding member such that the holding member is relatively displaceable; a rolling member sandwichingly held between the holding member and the fixed part wherein the fixed part holds the holding member via the rolling member such that the holding member is relatively displaceable; and an adhesive for fixing a first adhesion interface on the image capture device package and a second adhesion interface on the holding member, wherein a linear expansion coefficient of a part forming the first adhesion interface is larger than a linear expansion coefficient of the image capture device, wherein the second adhesion interface is formed by the resin part, and a linear expansion coefficient of the resin part forming the second adhesion interface is larger than the linear expansion coefficient of the part forming the first adhesion interface, and wherein the linear expansion coefficient of the resin part forming the second adhesion interface is smaller than a linear expansion coefficient of the sheet metal member.
 6. The image blur correction device according to claim 5, wherein the first adhesion interface is arranged on a resin member included in the image capture device package.
 7. The image blur correction device according to claim 5, wherein the resin part forming the second adhesion interface is formed of resin having PPS, epoxy, or nylon as a base resin.
-