

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12386870
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Patnaik; Pratyus et al.

System for routing of requests

Abstract

Systems for processing queries may first determine correspondence between the parameters of the query and a set of existing data entries, a set of previous queries that have been received, or both the existing data entries and the previous queries. If the query parameters do not correspond to the data entries or pervious queries, correspondence is determined between the query parameters and group data that associates at least a subset the query parameters with a particular group that may generate a response to the query. The same group or the generated response may be used when similar queries are received. If the group transmits the query to a different group or if negative user feedback is received, the group data may be modified to indicate the different group or to remove the association with the initial group that received the query.

Inventors: Patnaik; Pratyus (Los Altos, CA), Montgomery; Marissa Mary (San Francisco, CA), Srinivasan; Jay (San Francisco, CA), Agarwal; Suchit (Jersey City, NJ), Samdani; Rajhans (Belmont, CA), Kaneda; David Colby (San Francisco, CA), Rook; Nathaniel Ackerman (San Francisco, CA)

Applicant: Okta, Inc. (San Francisco, CA)

Family ID: 71074987

Appl. No.: 18/429125

Filed: January 31, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240168982 A1	May. 23, 2024

Related U.S. Application Data

continuation parent-doc US 17877886 20220730 US 11928139 child-doc US 18429125
continuation parent-doc US 16814149 20200310 US 11468105 20221011 child-doc US 17877886

Publication Classification

Int. Cl.: **G06F16/332** (20250101); **G06F16/33** (20250101); **G06F16/334** (20250101); **G06F21/60** (20130101); **G06F21/62** (20130101)

U.S. Cl.:

CPC **G06F16/3325** (20190101); **G06F16/3326** (20190101); **G06F16/334** (20190101); **G06F21/604** (20130101); **G06F21/6227** (20130101);

Field of Classification Search

CPC: G06Q (10/063112); G06Q (10/063114); H04M (3/5233); G06F (16/3325); G06F (16/3326); G06F (16/334); G06F (21/604); G06F (21/6227)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4992653	12/1990	Kawahara et al.	N/A	N/A
5634051	12/1996	Thomson	N/A	N/A
5659732	12/1996	Kirsch	N/A	N/A
5937027	12/1998	Thevenin et al.	N/A	N/A
5966126	12/1998	Szabo	N/A	N/A
6026388	12/1999	Liddy	707/999.005	G06F 16/3344
6385329	12/2001	Sharma et al.	N/A	N/A
6829008	12/2003	Kondo et al.	N/A	N/A
6865571	12/2004	Inaba et al.	N/A	N/A
7038820	12/2005	Kindt et al.	N/A	N/A
7078701	12/2005	Ishii et al.	N/A	N/A
7088395	12/2005	Takayama et al.	N/A	N/A
7099056	12/2005	Kindt	N/A	N/A
7154547	12/2005	Oda	N/A	N/A
7181438	12/2006	Szabo	N/A	N/A
7277130	12/2006	Korthout et al.	N/A	N/A
7554071	12/2008	Moholt	N/A	N/A
7801896	12/2009	Szabo	N/A	N/A
7827125	12/2009	Rennison	N/A	N/A
8477225	12/2012	Moholt	N/A	N/A
8886587	12/2013	Hainsworth et al.	N/A	N/A
9147712	12/2014	Moholt	N/A	N/A
9245271	12/2015	Ahmed et al.	N/A	N/A
9654640	12/2016	Brydon	N/A	G06Q 10/10
9930264	12/2017	Moholt	N/A	N/A
10388274	12/2018	Hoffmeister	N/A	N/A
10497039	12/2018	Singh et al.	N/A	N/A

10565181	12/2019	Hjermstad et al.	N/A	N/A
10567235	12/2019	Shah et al.	N/A	N/A
10681284	12/2019	Moholt	N/A	N/A
10685047	12/2019	Patnaik et al.	N/A	N/A
10795886	12/2019	Samdani et al.	N/A	N/A
10817483	12/2019	Samdani et al.	N/A	N/A
11328019	12/2021	Bonin et al.	N/A	N/A
11468105	12/2021	Patnaik et al.	N/A	N/A
11531707	12/2021	Samdani et al.	N/A	N/A
11544334	12/2022	Gottumukkala et al.	N/A	N/A
11803556	12/2022	Samdani et al.	N/A	N/A
11928139	12/2023	Patnaik et al.	N/A	N/A
2002/0101532	12/2001	Takayama et al.	N/A	N/A
2002/0107842	12/2001	Biebesheimer et al.	N/A	N/A
2004/0051802	12/2003	Krymski	N/A	N/A
2004/0072143	12/2003	Timmis et al.	N/A	N/A
2004/0243568	12/2003	Wang	707/E17.084	G06F 16/24522
2005/0001143	12/2004	Rhodes	N/A	N/A
2005/0086046	12/2004	Bennett	704/E15.04	G06F 16/24522
2005/0088552	12/2004	Erhardt et al.	N/A	N/A
2005/0094848	12/2004	Carr et al.	N/A	N/A
2005/0151866	12/2004	Ando et al.	N/A	N/A
2005/0205761	12/2004	Shah	N/A	N/A
2006/0007498	12/2005	Mcdermott	N/A	N/A
2006/0113459	12/2005	Yang et al.	N/A	N/A
2006/0139470	12/2005	Mcgowan	N/A	N/A
2006/0160065	12/2005	Timmis et al.	N/A	N/A
2007/0046799	12/2006	Moholt	N/A	N/A
2008/0052056	12/2007	Timmis et al.	N/A	N/A
2008/0071769	12/2007	Jagannathan	N/A	N/A
2008/0077570	12/2007	Tang et al.	N/A	N/A
2008/0218608	12/2007	Rossi et al.	N/A	N/A
2008/0235283	12/2007	Turnball et al.	N/A	N/A
2009/0006360	12/2008	Liao et al.	N/A	N/A
2009/0182609	12/2008	Kelleher	705/7.14	G06Q 10/087
2009/0244348	12/2008	Moholt	N/A	N/A
2010/0005081	12/2009	Bennett	704/9	G06F 40/237
2010/0070554	12/2009	Richardson	709/202	H04L 67/306
2010/0076998	12/2009	Podgorny	707/772	G06Q 10/10
2010/0094878	12/2009	Soroca et al.	N/A	N/A
2010/0115040	12/2009	Sargent et al.	N/A	N/A
2010/0332583	12/2009	Szabo	N/A	N/A
2011/0004588	12/2010	Leitersdorf et al.	N/A	N/A

2011/0047163	12/2010	Chechik et al.	N/A	N/A
2011/0258049	12/2010	Ramer et al.	N/A	N/A
2012/0041937	12/2011	Dhillon et al.	N/A	N/A
2012/0078890	12/2011	Fan	707/723	G09B 7/00
2013/0007037	12/2012	Azzam	707/769	G06F 16/3329
2013/0212096	12/2012	Ben Shahr	707/730	G06F 16/3334
2013/0282594	12/2012	Gaedcke	705/304	G06Q 30/0201
2013/0284890	12/2012	Moholt	N/A	N/A
2014/0040181	12/2013	Kuznetsov	706/55	G06F 40/268
2014/0040246	12/2013	Rubinstein et al.	N/A	N/A
2014/0120513	12/2013	Jenkins et al.	N/A	N/A
2014/0149411	12/2013	Anand	707/737	G06F 16/35
2014/0172882	12/2013	Clark	707/749	G06N 5/022
2015/0120718	12/2014	Luo	707/728	G06F 16/335
2015/0172294	12/2014	Bittner	726/4	G06F 21/6245
2015/0294246	12/2014	Guven Kaya	705/7.28	G06Q 10/06393
2015/0365579	12/2014	Moholt	N/A	N/A
2016/0019280	12/2015	Unger	707/736	G06F 16/3329
2016/0034457	12/2015	Bradley et al.	N/A	N/A
2016/0063118	12/2015	Campbell et al.	N/A	N/A
2016/0171373	12/2015	Allen	706/50	G06N 5/04
2016/0180726	12/2015	Ahuja	434/322	G06N 5/022
2016/0188575	12/2015	Sawaf	N/A	N/A
2016/0203215	12/2015	Allen	706/46	G06F 16/2455
2016/0335554	12/2015	Koll	N/A	G06Q 30/04
2017/0004204	12/2016	Bastide et al.	N/A	N/A
2017/0017694	12/2016	Roytman et al.	N/A	N/A
2017/0228372	12/2016	Moreno	N/A	G06F 16/24522
2017/0235792	12/2016	Mawji et al.	N/A	N/A
2017/0242899	12/2016	Jolley	N/A	G06F 16/242
2017/0243107	12/2016	Jolley	N/A	G06N 5/02
2017/0249566	12/2016	Mandel	N/A	H04M 3/5166
2017/0337264	12/2016	Barbosa et al.	N/A	N/A
2018/0144064	12/2017	Krasadakis	N/A	G06F 16/90332
2018/0173698	12/2017	Dubey et al.	N/A	N/A
2018/0176443	12/2017	Moholt	N/A	N/A

2018/0196822	12/2017	Lewin-Eytan et al.	N/A	N/A
2018/0212904	12/2017	Smullen	N/A	H04L 69/14
2018/0227190	12/2017	Healing	N/A	G06F 16/285
2018/0285423	12/2017	Ciano et al.	N/A	N/A
2019/0108486	12/2018	Jain et al.	N/A	N/A
2019/0130049	12/2018	Jussila et al.	N/A	N/A
2019/0155916	12/2018	Huang et al.	N/A	N/A
2020/0259986	12/2019	Moholt	N/A	N/A
2021/0157860	12/2020	Li et al.	N/A	N/A
2021/0256066	12/2020	Srinivasan et al.	N/A	N/A
2022/0365954	12/2021	Patnaik et al.	N/A	N/A
2023/0095077	12/2022	Samdani et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2014286166	12/2016	AU	G06F 16/24564
0393945	12/1989	EP	N/A
1227662	12/2001	EP	N/A
02/56581	12/2001	WO	N/A

OTHER PUBLICATIONS

Faed, A. "Handling e-complaints in customer complaint management system using FMEA as a qualitative system," 6th International Conference on Advanced Information Management and Service, Nov. 30- Dec. 2, 2010, pp. 205-209. cited by applicant

Primary Examiner: Truong; Dennis

Attorney, Agent or Firm: Holland & Hart LLP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of and claims priority to U.S. patent application Ser. No. 17/877,886, filed Jul. 30, 2022, and entitled "System for Routing Requests," which is a continuation of U.S. patent application Ser. No. 16/814,149 filed Mar. 10, 2020, now U.S. Pat. No. 11,468,105, and entitled "System for Routing Requests," which is a continuation of U.S. patent application Ser. No. 15/373,312, now U.S. Pat. No. 10,685,047, filed Dec. 8, 2016, and entitled "Request Processing System," each of which is incorporated herein by reference in its entirety.

BACKGROUND

(1) Individuals within companies or other organizations may submit requests for information or services. The requests may be processed by a variety of systems.

Description

BRIEF DESCRIPTION OF FIGURES

(1) The detailed description is set forth with reference to the accompanying figures. In the figures, the left-most digit(s) of a reference number identifies the figure in which the reference number first appears. The use of the same reference numbers in different figures indicates similar or identical items or features.

(2) FIG. 1 depicts a system for processing a received query to generate a response.

(3) FIG. 2 depicts a system for determining particular data entries that may be accessed responsive to a received query.

(4) FIG. 3 depicts a system for determining a manner in which a response to a previous query may be generated based on a current quantity of existing data entries and a current quantity of previous queries.

(5) FIG. 4 is a flow diagram illustrating a method for determining a response based on a received query.

(6) FIG. 5 is a flow diagram illustrating a method for generating responses and notifications based on whether a user is authorized to access a data entry or data repository.

(7) FIG. 6 is a flow diagram illustrating a method for providing a response to a query and receiving feedback data indicative of whether the response resolved the query.

(8) FIG. 7 is a block diagram depicting a computing device within the scope of the present disclosure.

(9) FIG. 8 depicts a series of block diagrams illustrating one or more user interfaces that may be provided to a user device.

(10) FIG. 9 is a flow diagram illustrating a method for providing a query to one or more human users.

(11) While implementations are described in this disclosure by way of example, those skilled in the art will recognize that the implementations are not limited to the examples or figures described. It should be understood that the figures and detailed description thereto are not intended to limit implementations to the particular form disclosed but, on the contrary, the intention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope as defined by the appended claims. The headings used in this disclosure are for organizational purposes only and are not meant to be used to limit the scope of the description or the claims. As used throughout this application, the word “may” is used in a permissive sense (i.e., meaning having the potential to) rather than the mandatory sense (i.e., meaning must). Similarly, the words “include,” “including,” and “includes” mean “including, but not limited to.”

DETAILED DESCRIPTION

(12) Companies and other organizations may process requests for information or services from a user through various types of partially-automated systems, such as ticketing systems, or by manually processing requests. For example, an employee of a company may electronically submit a query, such as “What is the fax number for the human resources department?,” “How do I set up my computer to send faxes?,” or “How do I enroll in the company benefits program?.” In some cases, the employee may transmit the query, such as through e-mail or a messaging program, to a department or a particular individual associated with the company. In other cases, the employee may transmit the query through a web portal or messaging system to an employee or group of employees responsible for routing messages to appropriate departments or individuals that may address the query. In still other cases, the employee transmitting the request may select or specify a department or individual to receive the request. Periodically, a company may review the queries that were resolved during a period of time and create articles or other sources of knowledge that may be used to answer subsequent queries of a similar nature. For example, if a company receives numerous questions within a month regarding the process for enrolling employees in a benefits program, an individual within the company may generate a web page, article, or other type of data

entry that explains this process. During the next month, subsequent queries relating to enrollment in a benefits program may be resolved by directing the employee providing the subsequent query to the existing data entry.

(13) In some cases, queries from a user may be inadvertently directed toward an employee or department that is unable to resolve the query, either by the user submitting the query, other users responsible for routing the query, or an automated system. In other cases, similarities between a current query and one or more previous queries may not be readily apparent, depending on the particular language, grammar, or format of the query. In still other cases, a particular data entry may appear relevant to a received query, such as due to common keywords present in both the data entry and the query, but the data entry may not actually address the question presented by the user.

(14) Described in this disclosure are techniques for analyzing a query received from a user and generating a response. The query may be received through a messaging system, short message service (SMS), e-mail, a web portal, and so forth. An augmented query may be generated using the received query, such as through use of natural language processing techniques. In some implementations, language data indicative of particular weights applied to certain terms of the query and synonyms of particular query terms may be used to process the received query. For example, a user query may include the text “What is the fax number for the human resources department?” The language data may indicate that certain terms, such as “what,” “is,” “the,” and “for” are unimportant for resolving the query, and thus have a weight of zero. The language data may indicate a high weight value for the terms “fax,” “human,” and “resources,” and a moderate weight value for the terms “number” and “department.” Additionally, the language data may indicate synonyms for one or more terms in the query. For example, the language data may indicate that synonyms for the term “fax” may include “facsimile,” “scanner,” “copier,” and so forth. Similarly, the language data may indicate the synonyms “HR” and “H.R.” for the terms “human resources.” Continuing the example, the received query may be processed to generate an augmented query, such as “fax facsimile scanner copier number human resources HR H.R. department.”

(15) To determine an appropriate response to the query, the augmented query may be compared with an existing set of data entries, a set of previously received queries, or both. For example, in some cases, the time or computing resources needed to compare the augmented query with previously received queries within a system may be greater than the time or computing resources needed to compare the augmented query with existing data entries. In such cases, correspondence between the augmented query and the existing data entries may be determined more efficiently than correspondence between the augmented query and the numerous previous queries. Alternatively, the time or computing resources associated with analysis using the data entries may exceed the time or computing resources associated with analysis using the previous queries. In such cases, correspondence between the augmented query and the previously received queries may be determined more efficiently than correspondence between the augmented query and the numerous data entries.

(16) In some implementations, correspondence may be determined by matching keywords found within data entries to keywords within the augmented query. The particular keywords that correspond to a particular data entry and the weight associated with each keyword may be used to determine a correspondence value (e.g., a confidence value). If the correspondence value exceeds a threshold, then the particular data entry may correspond to the augmented query. At least a subset of the existing data entries that correspond to the query may be determined. In other implementations, the determined subset of data entries may include a fixed number of data entries, such as the fifty data entries that have the greatest associated correspondence values. In still other implementations, a combination of a fixed count and a threshold value may be used. For example, fifty-five out of five hundred data entries may be determined to have a correspondence value greater than a threshold value, while the determined subset may include the twenty data entries of

those fifty-five that have the greatest correspondence. As another example, the twenty data entries having the greatest correspondence values may be determined, however only sixteen out of the twenty data entries may have a correspondence value greater than a threshold value. Therefore, the determined subset may include those sixteen data entries.

(17) After determining at least a subset of the data entries that correspond to the augmented query, the augmented query may be analyzed using the previous queries for which one or more data entries of the subset was used to resolve the previous query. For example, correspondence between the augmented query and each of the previous queries may be determined. In some implementations, each query that is received and resolved using a data entry may be recorded. Data indicative of a query that is resolved using a particular data entry may be stored in association with data indicative of the data entry. Thus, each data entry of the determined subset may have been used to resolve one or more previous queries. Correspondence between the augmented query and the previous queries associated with the subset of data entries may be used to determine a particular query having a greatest correspondence value compared to the other previous queries. For example, keywords within each of the previous queries may be compared to the keywords of the augmented query to determine a correspondence value. The correspondence value may be determined by the quantity of matched words, the weight of the words that are matched, whether a keyword from the original received query is matched, whether a synonym included in the augmented query is matched, similarities between grammatical arrangements of the received query and a previous query, and so forth. In some cases, words may not necessarily be matched, but may be synonyms of a keyword or associated with keywords. For example, keywords such as “internet” and “wifi” may not be synonyms, but may occur in similar contexts. Continuing the example, a query that includes the term “internet” may correspond to a response that includes the term “wifi.” The particular data entry that corresponds to the previous query having the greatest correspondence value may be included in a response to the initial query received from a user. For example, a response to the received query may include all or a portion of the text of the data entry, a link or instructions to access the data entry, and so forth.

(18) In some implementations, if no data entry that corresponds to the augmented query is determined, correspondence may instead be determined between the augmented query and the previous queries received for each data entry. For example, if no correspondence value determined for any data entry exceeds a threshold value, no subset of data entries that correspond to the augmented query may be determined. In such a case, a particular previous query may still have keywords or other parameters that correspond to the received query. If correspondence between one or more previous queries and the augmented query is determined, one or more data entries associated with the corresponding previous queries may be relevant to the received query. The data entry associated with the previous query that has the greatest correspondence value may be used to generate a response.

(19) If no data entry that corresponds to the augmented query is determined, and no previous query that corresponds to the augmented query is determined, a notification may be generated to request human intervention to resolve the received query. Additionally, in some implementations, correspondence may be determined between the keywords or other parameters of the received query and group data indicative of users or groups of users within an organization. This correspondence may be used to determine a group, team, or department that is suitable to receive and resolve the query. For example, the group data may associate the terms “benefits,” “human,” “resources,” or “HR” with an e-mail address for the human resources department of a company, while the terms “computer,” “configure,” “set up,” or “IT” are associated with the information technology department of the company. If the keywords of the query match the particular terms associated with a user, group, team, or department, the query may be provided to that entity. If no correspondence between the parameters of a received query and the group data is determined, the query may be provided to a default destination, such as one or more users responsible for routing

queries or addressing queries of a general nature. The particular groups that receive and resolve queries may be stored as additional group data, so that subsequent queries having similar parameters may be provided to the same groups. In some cases, a response provided by a user or group of users may be stored in association with an indication of the query, such that the response may be provided responsive to subsequent queries having similar parameters.

(20) In other cases, it may be more efficient to compare a received query to previously-received queries to determine previous queries that are similar to the received query, rather than to attempt to determine correspondence between the received query and a large number of existing data entries. For example, a company may store a large number of knowledge articles that may be used to respond to queries, using a newly-established ticketing system that has not yet processed a large volume of previous queries. In some implementations, the received query may be used to generate an augmented query, such as through use of natural language processing techniques, as described above. Correspondence between the augmented query and the previously received queries may then be determined. For example, a correspondence value for each previous query may be determined based on the keywords or other parameters of the previous query that match the keywords or parameters of the augmented query. At least a subset of the previous queries having a correspondence value greater than a threshold value may be determined. In other implementations, a fixed number of previous queries, such as the one hundred previous queries having the greatest correspondence values may be determined. In still other implementations, a combination of a fixed number and a threshold value may be used. After a subset of previous queries has been determined, correspondence between the augmented query and the data entries associated with the subset of previous queries may be determined. The data entry having the greatest correspondence value may be used to generate a response to the query.

(21) In some implementations, if no previous query that corresponds to the augmented query is determined, correspondence between the augmented query and the data entries may instead be determined. If no data entry that corresponds to the augmented query is determined, a notification may be generated to request human intervention to resolve the received query. Additionally, in some implementations, as described above, correspondence between the keywords or other parameters of the query and group data indicative of users or groups of users within an organization may be used to determine a group to receive the query. If no correspondence is determined between the parameters of a received query and one or more users or user groups, the query may be provided to a default destination, such as an e-mail address associated with a user or department responsible for routing queries to other departments or resolving queries of a general nature.

(22) Queries that are resolved using one or more of the techniques described in this disclosure may be stored for future use to analyze and resolve subsequent queries. For example, a first query may be received, and a particular data entry may be used to resolve the first query. Subsequently, a second query that is identical or similar to the first query may be received. Correspondence between the second query and the first query may be determined, and the same data entry may be used to generate a response to the second query. In some implementations, feedback data associated with a response may be determined. For example, a user receiving a response may be requested to indicate whether the response appropriately resolved the received query. If the feedback data corresponds to one or more threshold feedback values, such as an indication that the response was useful, the received query may be stored for future comparison to subsequent queries. If the feedback data deviates from the threshold feedback values, such as by indicating that the response was not useful, a notification requesting human intervention to resolve the query may be generated. In some implementations, if a query is resolved by one or more human users, the resolution by the human user(s) may function as feedback data, indicating that the particular user or group of users to which the query was provided is a suitable destination for subsequent queries having similar parameters. In other implementations, if a query is routed from a first user or group of users to a second user or group of users, this routing may function as feedback data indicating that the second

user or group of users is a suitable destination for subsequent queries having similar parameters. Additionally, if the query was resolved by the generation of a data entry, the received query may be stored in association with the generated data entry, such that subsequent queries having similar parameters may be resolved using the generated data entry.

(23) In some implementations, data associated with a received query may be used to determine a source of the query. For example, a query received via SMS may be associated with a telephone number, which may be used to identify a user, device, or account, which in turn may be used to identify a company or other organization associated with the user, device or account. As another example, a query received via a web portal from a computing device within an office may be associated with a network identifier that may be used to identify the device, department, or user account associated with the query. In some cases, particular users may not be authorized to access particular data entries. For example, a user may provide a query requesting restricted information, such as information relating to salaries or bonuses awarded to individuals within a company. Based on a lack of correspondence between the source of the query and security data that associates sources of queries with sources of data entries, it may be determined that the user or account associated with the query is not permitted to access the responsive data entry. In some implementations, a notification indicative of an attempt to access the data entry may be generated and provided to an administrator associated with the data entry. In other implementations, in place of the responsive data entry, the response to the query may include an indication of an individual to be contacted for assistance resolving the query. For example, responsive to a query associated with restricted salary information, a user that is not authorized to access a data entry that includes such information may be provided with an e-mail address of an individual in a company's human resources department that may be able to resolve the query or recommend alternate sources of information.

(24) In other implementations, data indicative of the source of a query may be used to determine particular bodies of data entries that may be used to respond to the query. For example, a system may store data entries from multiple sources, such as respective data repositories containing data entries associated with different companies. In many cases, data entries associated with a first company may not include information that is useful to resolve queries from employees of a second company, independent of any similar keywords or other parameters that are common between a data entry and a query. Additionally, many data entries for a particular company may include information intended to be restricted to individuals associated with the particular company. As such, when a query is received, data indicative of the source of the query may be used to determine a particular device, user, account, or organization associated with the query. Correspondence between the source of the query and security data that associates sources of queries with sources of data entries may be used to determine the particular body of data entries that may be used to respond to the query.

(25) FIG. 1 depicts a system **100** for processing a received query **102** to generate a response **104**. The received query **102** may include, for example, a request for information, one or more services, and so forth. For example, a user within a company or other organization may access a user device **106** to generate a query, which may be provided from the user device **106** to a query server **108** for processing. The user device **106** may include any type of computing device including, without limitation, a smartphone, tablet computer, wearable computer, or other type of mobile or portable device, a desktop computer, laptop computer, or other type of personal computer, an automotive computer, a set-top box, a server, a game controller, and so forth. While FIG. 1 depicts a single user device **106** providing the received query **102** directly to the query server **108**, in other implementations, the user device **106** may include multiple computing devices, or the user device **106** may provide the received query **102** to one or more intermediate computing devices, access points, and so forth, which in turn provide the received query **102** to the query server **108**. Additionally, while FIG. 1 depicts a single query server **108** receiving the received query **102**, the

query server **108** may include any number and any type of computing devices including, without limitation, the types of computing devices described with regard to the user device **106**. The received query **102** may include any manner of data including, without limitation, alphanumeric data, audio data, image data, and so forth. For example, FIG. **1** depicts the received query **102** including the text “How do I set up my computer to send a fax?,” which may be input using a keyboard, touch sensor, or other input device associated with the user device **106**. In other implementations, the received query **102** may be input using a microphone in conjunction with speech-to-text software or a camera or other image sensor in conjunction with optical character recognition software.

(26) The received query **102** may include various parameters, such as keywords having a particular arrangement such as a grammatical structure or format. For example, the received query **102** may include a question or statement expressed in natural language. The parameters of the received query **102** may include the particular words used in the query, the arrangement of the words, the formatting of one or more words, additional characters such as punctuation, and so forth. For example, a terminal question mark may indicate that the received query **102** includes a question, the presence of intermediate periods or a word containing all capital letters may indicate that one or more terms within the received query **102** include an abbreviation or acronym, or the presence of a capitalized word within the received query **102** may indicate that the particular word is a proper noun.

(27) A language module **110** associated with the query server **108** may process the received query **102** using language data **112**, to generate an augmented query **114**. The language data **112** may associate various keywords or other parameters of queries with weight values. For example, words that are unlikely to indicate the nature of a received query **102**, or words that are likely to be common to a large number of unrelated queries, such as “I,” “my,” “to,” and “a” may be assigned a low weight value, or a weight value of zero. Continuing the example, words having a weight value of zero may be disregarded or omitted from the augmented query **114**. Conversely, words that are likely to indicate the nature of the received query **102** or words that are less likely to be included in a large number of other queries may be assigned a high weight value. Similarly, words that are moderately likely to indicate the nature of the received query **102** may be assigned a moderate weight value. As an illustrative example, FIG. **1** depicts the language data **112** assigning a weight value of “1” to the query term “How,” a weight value of “0” to the query term “I,” a weight value of “3” to the query term “Send,” and a weight value of “5” to the query term “Fax.” Continuing the example, in the received query **102** “How do I set up my computer to send a fax?,” the term “I” does not identify the nature of the received query **102** and would be likely to occur in a large number of other unrelated queries, and is thus assigned a weight value of zero. The term “How” indicates that the received query **102** relates to a request for instructions to accomplish a task, but does not indicate the nature of the query and is likely to occur in other unrelated queries, and is thus assigned a weight value of one. The term “Send” is moderately indicative of the nature of the received query **102** and moderately likely to occur in other queries, and is thus assigned a weight value of three. The term “Fax” is highly indicative of the nature of the received query **102** and is only likely to occur in other queries relating to the transmission or configuration of a fax, and is thus assigned a weight value of five. Other terms of the received query **102** may similarly be included in the language data **112** and associated with a weight value. Words in the received query **102** that are not included in the language data **112** may be assigned a default weight value. In some implementations, the arrangement, punctuation, formatting, and so forth of particular words within the received query **102** may also be assigned a weight value.

(28) The language data **112** may also indicate one or more synonyms associated with particular keywords within the received query **102**. For example, the language data **112** may indicate the term “Transmit” is a synonym for the term “Send,” the terms “Facsimile” and “Message” are synonyms for the term “Fax,” the terms “Setup” and “Configure” are synonyms for the terms “Set Up,” and

so forth. When determining a response **104** that corresponds to the received query **102**, the determined synonyms may also be used to locate corresponding materials for inclusion in the response **104**. In some implementations, a single synonym may be associated with multiple words within the received query **102**, such as the synonym “Configure” for the terms “Set Up.” Similarly, multiple synonyms may correspond to a single term of the query, such as the synonyms “Facsimile” and “Message” for the query term “Fax.”

(29) The augmented query **114** may be generated by removing one or more terms from the received query **102** that have a weight value less than a threshold value. For example, the terms “How,” “Do,” “I,” “My,” “To,” and “A” may have a weight value of zero, or a weight value less than a threshold value, such as three. The augmented query **114** may also include one or more of the synonyms determined to correspond to the terms of the received query **102**. For example, in addition to the initial terms of the received query **102**, the augmented query **114** may include the synonyms “Setup,” “Configure,” “Transmit,” “Facsimile,” and “Message.” As a result, the initial received query **102** of “How do I set up my computer to send a fax?” may be used to generate the augmented query **114** of “Set Up Setup Configure Computer Send Transmit Fax Facsimile Message.” In some implementations, the augmented query **114** may include additional data indicative of the weight values of each term included therein. In other implementations, the augmented query **114** may also include data indicative of other parameters of the received query **102**, such as arrangements of words, capitalization, formatting, punctuation, and so forth.

(30) A knowledge module **116** associated with the query server **108** may access a data repository **118** or other source of data entries **120** to determine one or more data entries **120** that correspond to the augmented query **114**. A data entry **120** may include alphanumeric data, audio data, image data, or one or more other types of data that may be used to convey information to a user. For example, a data entry **120** may include a document, spreadsheet, database, web page, audio file, video file, one or more images, and so forth. Each data entry **120** within the data repository **118** may include various terms or other parameters. For example, a first data entry **120** may include information for contacting the human resources department of a company via a fax transmission, a second data entry **120** may include information for setting up an office telephone, while a third data entry **120** may include information for setting up an office computer to send and receive fax transmissions. The knowledge module **116** may determine correspondence between the parameters of the augmented query **114** and the parameters of the data entries **120** within the data repository **118** to identify a subset of data entries **120** that correspond to the augmented query **114** and may potentially be used to generate a response **104**. For example, the knowledge module **116** may determine that one or more particular data entries **120** share a threshold number of common keywords with the augmented query **114**. As another example, the augmented query **114** may include the indication of the weight value for one or more keywords, and the knowledge module **116** may determine a subset of data entries **120** having common keywords with the augmented query **114** that are associated with an aggregate weight value that exceeds a threshold weight value. Continuing the example, a first data entry **120** with the terms “HR” and “Fax” may share the common term “Fax” with the augmented query **114**, and the term “Fax” may have a weight value of five. A second data entry **120** with the terms “Setup” and “Phone” may share the common term “Setup” with the augmented query **114**, which may have a weight value of three. A third data entry **120** with the terms “Setup” and “Fax” may share both of these terms with the augmented query **114**, and the aggregate weight value of these terms may be eight. If the threshold weight value is five, the knowledge module **116** may determine that the first and third data entries **120** have an aggregate weight value equal to or exceeding the threshold weight value. In some implementations, one or more data entries **120** may be accompanied by metadata indicating synonyms or associated parameters that correspond to the data entries **120**. For example, a particular data entry **120** may not contain specific keywords found in a query, however, the metadata associated with that data entry **120** may indicate that those specific keywords are related to the data entry **120**. Therefore, the data

entry **120** may correspond to the augmented query **114** even if the data entry **120** does not contain the particular keywords found in the query.

(31) A query module **122** associated with the query server **108** may process the data entries **120** determined by the knowledge module **116** to determine a particular responsive data entry **124** that may be used to generate the response **104** to the received query **102**. The query module **122** may access query data **126**, which may include data indicative of previous queries received by the query server **108**. The query data **126** may indicate each data entry **120** determined by the knowledge module **116** and one or more previous queries for which a respective data entry **120** was determined to be responsive. As one illustrative example, FIG. **1** depicts the previous queries “Call HR” and “Fax HR Dept.” associated with the data entry “HR Fax #” and the previous queries “Configure fax” and “Setup fax” associated with the data entry “Setup Fax.” The query module **122** may determine correspondence between the previous queries for each data entry **120** determined by the knowledge module **116** and one or more of the augmented query **114** or the received query **102**. For example, the query module **122** may determine common terms shared by one or more previous queries and the augmented query **114**. In some implementations, the query module **122** may determine an aggregate weight value for the terms shared by each previous query and the augmented query **114** or received query **102**. In one specific implementation, based on correspondence between the query data **126** and the augmented query **114** or received query **102**, the query module **122** may determine a particular previous query that is more similar to the augmented query **114** or received query **102** than other previous queries associated with the data entries **120**. The responsive data entry **124** may be the particular data entry **120** that is associated with the particular previous query most similar to the augmented query **114** or received query **102**. In other implementations, the query module **122** may determine correspondence values associated with at least a portion of the previous queries that are associated with the data entries **120** determined by the knowledge module **116**. The particular responsive data entry **124** may be determined based on a combination of the correspondence value for that data entry **120** determined by the knowledge module **116** and the correspondence values for the associated previous queries determined by the query module **122**. In some implementations, if no particular previous query corresponds to the augmented query **114** or received query **102**, a notification may be generated to request human intervention to resolve the received query **102**. For example, if the aggregate weight value for the terms shared by each previous query and the augmented query **114** is less than a threshold value, a notification may be provided to the user device **106** indicating that human intervention has been requested to resolve the received query **102**. In other implementations, if no particular previous query corresponds to the augmented query **114** or received query **102**, the data entry **120** having the greatest correspondence value may be used to generate the response **104**.

(32) A response module **128** associated with the query server **108** may generate the response **104** based on the responsive data entry **124** and response data **130**, which may indicate the manner in which a response **104** is to be formatted or transmitted, other data for inclusion in the response **104**, and so forth. For example, the response data **130** may indicate that the instructions “Click this link to access fax configuration instructions” are to be included in a response **104** associated with the particular data entry **120** “Setup Fax.” The response data **130** may also indicate particular images or links to be included, the placement and formatting of such elements, and so forth. In cases where the response data **130** does not include content or formatting specific to a particular data entry **120**, the response data **130** may include default content. For example, in the absence of response data **130** for a particular data entry **120**, the text of the data entry **120**, itself, may be provided to the user device **106** as the response **104**.

(33) FIG. **2** depicts a system **200** for determining particular data entries **120** that may be accessed responsive to a received query **102**. As described with regard to FIG. **1**, a user device **106** may provide a query to a query server **108**. For example, the received query **102** may include the text “What is Mr. Smith's current salary?.” In some cases, a received query **102** may be associated with

restricted or confidential information. For example, access to information associated with employee salaries, passwords, account information, and so forth, may be restricted to particular users. In other cases, access to information contained within a particular data repository **118** may be restricted to particular users or groups of users, such as employees of a particular company or of a particular department within a company. Additionally, in some cases, a system **200** may include multiple data repositories **118** or other sources of data entries **120**. For example, a first data repository **118(1)** may store data entries **120** associated with a first company while a second data repository **118(2)** stores data entries **120** associated with a second company. The information contained in data entries **120** associated with one company may not be useful to employees of other companies. Furthermore, information contained within data entries **120** associated with a particular company may be restricted, confidential, private, proprietary, and so forth, and may be intended to be viewed only by users associated with the particular company.

(34) In some implementations, prior to generation of a response **104**, a received query **102** may be provided to a security module **202** associated with the query server **108**. The security module **202** may determine correspondence between user data **204** associated with the received query **102** and security data **206**. The user data **204** may include data indicative of a source of the received query **102**, such as a particular user device **106**, user account, company, location, and so forth. For example, the user data **204** may include a user identifier, such as a user name or account name, a device identifier, a token value, or other type of identifier. As another example, the user data **204** may include a telephone number, e-mail address, an Internet Protocol (IP) address or another type of network address, and so forth. The security data **206** may indicate particular elements of user data **204** that are indicative of users permitted to access particular data repositories **118**. For example, the security data **206** may indicate one or more particular telephone numbers that may be determined from the user data **204** are associated with a particular company. Based on correspondence between the telephone number associated with a received query **102** and the security data **206**, a particular data repository **118** associated with a particular company may be queried. Additionally, the security data **206** may indicate that one or more particular user accounts are authorized to access particular data entries **120**, data repositories **118**, or other types of information. Based on correspondence between the security data **206** and the user data **204**, access may be granted to the requested data. In some implementations, if the user data **204** does not correspond to the security data **206**, one or more notifications indicative of the attempted access may be provided to the user device **106** or to an administrator associated with the system **200**. For example, a user that is not authorized to access a particular data entry **120** may be provided with a response **104** indicating an individual that the user should contact to resolve the query, rather than a response **104** containing information from the data entry **120**.

(35) Based on the user data **204** associated with the received query **102** and the security data **206**, the security module **202** may generate a security determination **208** indicative of the particular data repository **118** to be queried, and whether the user device **106** is permitted to access the particular data repository **118**. For example, based on the telephone number determined from the user data **204**, the security determination **208** may indicate that the user device **106** providing the received query **102** is associated with a particular user (e.g., user “ABC”) of a particular company (e.g., “Company X”). The security data **206** may further indicate particular types of restricted data, such as data associated with salaries and passwords. In other implementations, the security data **206** may indicate particular data repositories **118** or data entries **120** for which access is restricted.

Correspondence between the user data **204** and the security data **206** may indicate that the user device **106** is authorized to access particular data repositories **118**, data entries **120**, or types or categories of data. If the user data **204** associated with a received query **102** does not correspond to the security data **206**, access to a particular data repository **118** or data entry **120** may be denied. In some cases, a notification indicative of the attempted access may be provided to an administrator of the system **200**. In other cases, the response **104** provided to the user device **106** may include

contact information associated with a human that may assist in resolving the query rather than content associated with a restricted data entry **120**.

(36) Based in part on the security determination **208**, the knowledge module **116** may access the first data repository **118(1)**, which may be associated with a company that corresponds to the user data **204** accompanying the received query **102**. The knowledge module **116** may determine one or more data entries **120** that correspond to the parameters of the received query **102**. In some implementations, a language module **110** may be used to generate an augmented query **114** based on the received query **102**, as described with regard to FIG. 1, and the knowledge module **116** may determine data entries **120** that correspond to the augmented query **114**. A query module **122** may determine correspondence between the determined data entries **120** and query data **126** to determine previous queries that are similar to the received query **102**. Aggregate correspondence values, based on the correspondence value for each data entry **120** and the correspondence values for each previous query associated with that data entry **120**, may be determined. The data entry **120** having the greatest aggregate correspondence value may be used to generate the response **104**, based in part on response data **130**.

(37) FIG. 3 depicts a system **300** for determining a manner in which a response **104** to a received query **102** may be generated based on a current quantity of existing data entries **120** and a current quantity of previous queries **302**. As described with regard to FIGS. 1 and 2, a query may be provided from a user device **106** to a query server **108**, which may process the received query **102** to generate a response **104**. In some implementations, a thresholding module **304** associated with the query server **108** may determine the manner in which the received query **102** is processed. For example, the thresholding module **304** may determine a current quantity of data entries **120** within a data repository **118** that may be analyzed for correspondence to the received query **102**. The thresholding module **304** may also determine, based on query data **126**, a current quantity of previous queries **302** associated with the data entries **120**. As discussed above, if the number of existing data entries **120** exceeds the number of previous queries **302**, it may be more efficient to first determine correspondence between the received query **102** and the smaller number of previous queries **302** to determine a subset of previous queries **302** that correspond to the received query **102**. Then, correspondence between the received query **102** and the data entries **120** associated with the subset of previous queries **302** may be determined. If the number of previous queries **302** exceeds the number of data entries **120**, it may be more efficient to first determine correspondence between the received query **102** and the data entries **120** to determine a subset of data entries **120** that correspond to the received query **102**. Then, correspondence between the received query **102** and the previous queries **302** associated with the subset of data entries **120** may be determined. In other implementations, an efficiency value associated with processing of the data entries **120** or previous queries **302** may be determined in place of or in addition to determining a number of data entries **120** or previous queries **302**. For example, based on the size or format associated with one or more data entries **120**, determining correspondence between the data entries **120** and a received query **102** may be more efficient than determining correspondence between the received query **102** and previous queries **302**, independent of the number of data entries **120** or previous queries **302**.

(38) The thresholding module **304** may generate a thresholding determination **306**, indicative of whether the received query **102** will first be processed by the knowledge module **116** or the query module **122**. As described with regard to FIG. 1, the knowledge module **116** may determine correspondence between the received query **102** and the data entries **120** within the data repository **118**. The query module **122** may determine correspondence between the received query **102** and the previous queries **302** of the query data **126**. In some implementations, the thresholding module **304** may generate the thresholding determination **306** based at least in part on threshold data **308**. The threshold data **308** may indicate one or more relationships between the data entries **120** and the previous queries **302** that may determine the manner in which a received query **102** may be processed with the greatest efficiency. For example, in some cases, due to the size or format of at

least a portion of the data entries **120**, determining correspondence between a received query **102** and a large number of data entries **120** may be accomplished more quickly than determining correspondence between a received query **102** and a smaller number of previous queries **302**. The threshold data **308** may indicate the extent to which the number of data entries **120** may exceed the number of previous queries **302** before determining correspondence between the received query **102** and the previous queries **302** may be accomplished with greater efficiency than determining correspondence between the received query **102** and the data entries **120**. In other cases, determining correspondence between the received query **102** and a large number of previous queries **302** may be accomplished more quickly than determining correspondence between the received query **102** and a smaller number of data entries **120**. In some implementations, the threshold data **308** may include one or more user-selected or default values. In other implementations, the threshold data **308** may be automatically or dynamically modified as additional data entries **120** and previous queries **302** are stored, based on the characteristics of each data entry **120** and previous query **302**.

(39) In cases where correspondence between a received query **102** and the data entries **120** may be determined more efficiently than correspondence between the received query **102** and the previous queries **302**, the received query **102** may first be processed by the knowledge module **116**. The knowledge module **116** may determine correspondence between the received query **102** and the data entries **120** in the data repository **118** to determine at least a subset of the data entries **120** that may be used to generate a response **104**. The query module **122** may then determine the previous queries **302** that are associated with the subset of the data entries **120**, and determine correspondence between those previous queries **302** and the received query **102**. The correspondence values associated with the previous queries **302** and those associated with the data entries **120** may be used to identify the particular data entry **120** having the greatest total correspondence value, which may be included in a response **104** generated by the response module **128**.

(40) In cases where correspondence between a received query **102** and the previous queries **302** may be determined more efficiently than correspondence between the received query **102** and the data entries **120**, the received query **102** may first be processed by the query module **122**. The query module **122** may determine correspondence between parameters of the received query **102** and parameters of one or more previous queries **302** received by the query server **108**. The knowledge module **116** may then determine the particular data entries **120** that correspond to the previous queries **302** identified by the query module **122**. Based on correspondence between the received query **102** and the particular data entries **120** and between the received query **102** and the previous queries **302**, a responsive data entry **124** having the greatest correspondence value may be determined. The response module **128** may generate a response **104** based on the responsive data entry **124**.

(41) FIG. 4 is a flow diagram **400** illustrating a method for determining a response **104** based on a received query **102**. Block **402** receives a query from a user device **106**. For example, as described with regard to FIG. 1, a user device **106** may include any type of computing device, such as a desktop or laptop computer associated with a computing network within a company, a smartphone or tablet computer owned by an employee of the company, and so forth. A query may be generated using any type of input device associated with the user device **106**, including without limitation a keyboard, mouse device, touch sensor, microphone, or image sensor. The query may then be provided to the query server **108** or other type of computing device associated with one or more data repositories **118** in various ways. For example, a smartphone may be used to provide a query to the query server **108** via SMS or a similar type of messaging service or application. As another example, a desktop computer associated with a company network may access a web portal or similar application configured to provide a user interface to the user device **106**. The user interface may be configured to receive a query and, in some implementations, user data **204** such as

identifying information for a user account, company, or user device **106**.

(42) Block **404** determines, based on security data **206** and user data **204** associated with the received query **102**, a data repository **118** that corresponds to the source of the received query **102**. For example, user data **204** may be received from the user device **106**, determined from the user device **106**, or determined from data associated with the received query **102**. The user data **204** may include information from which the source of the received query **102** may be determined. For example, the user data **204** may include user account information, such as a user name, company affiliation, and so forth. As another example, the user data **204** may include a user's telephone number, determined from a SMS communication, an IP address associated with the user device **106**, and so forth. The user data **204** may be used to determine an identity of the user, user account, or user device **106** associated with the received query **102**. For example, the user data **204** may be used to determine a particular company associated with the user account or user device **106** providing the query. The security data **206** may associate one or more sources of queries with one or more data repositories **118**. For example, a first data repository **118** may store data entries **120** associated with a first company or department, while a second data repository **118** may store data entries associated with a second company or department. Based on the source of the received query **102** determined from the user data **204**, a data repository **118** that corresponds to the source of the received query **102** may be determined from the security data **206**. For example, a telephone number may be determined from a user providing a query via SMS using a smartphone. The security data **206** may associate one or more user telephone numbers with particular data repositories **118** or with particular sources of data entries **120**. Continuing the example, the security data **206** may indicate that the particular telephone number associated with the received query **102** is associated with a particular employee of Company X, and that a particular data repository **118** contains data entries **120** associated with Company X. Based on this determination, the particular data repository **118** of Company X may be accessed to process the received query **102**. As another example, the security data **206** may indicate that an IP address associated with the received query **102** is associated with a computing device located within a computing network of Company Y, and that the particular data repository **118** contains data entries **120** associated with Company Y. Based on this determination, the particular data repository **118** of Company Y may be accessed to process the received query **102**.

(43) Block **406** generates an augmented query **114** based on language data **112** and the received query **102**. As described with regard to FIG. 1, a language module **110** associated with the query server **108** may determine one or more parameters of the received query **102**. Parameters may include characteristics of the received query **102** such as particular words, characters, or groups of words or characters, arrangements of words or characters, such a grammatical structure, a format of one or more portions of the received query **102**, a language of the received query **102**, and so forth. In some implementations, the received query **102** may include types of data other than or in addition to alphanumeric data, such as image data, audio data, video data, or haptic data. In such cases, the parameters of the received query **102** may also include the type, location, and characteristics of this data. The language data **112** may associate particular parameters of queries with weight values. For example, particular words within the received query **102** that do not demonstrate the nature of the received query **102** and that commonly occur in many queries may be associated with a low weight value. Words that relate to the nature of the received query **102** and that are not commonly found in other queries may be associated with a high weight value. Other types of parameters of the received query **102** may also be associated with particular weight values. The language data **112** may also associate one or more synonyms with particular words. In some implementations, the language data **112** may also associate synonyms with other parameters of the received query **102**. For example, a particular grammatical structure may be considered to be synonymous with another grammatical structure. Generation of the augmented query **114** may include removing one or more words or other parameters from the received query **102**. For

example, particular words such as “a” may have a weight value of zero. Generation of the augmented query **114** may also include adding one or more words or other parameters to the received query **102**. For example, the term “HR” may include the synonyms “Human Resources,” “H.R.,” “Human Resources Department,” and so forth. The augmented query **114** may also include an indication of other parameters, such as arrangements or formats of words or characters. The augmented query **114** may further include an indication of the weight value associated with each word or other parameter. In some implementations, a synonym may have a weight value equal to that of the parameter of the received query **102** associated with the synonym. In other implementations, a synonym may include a weight value different from that of the associated parameter in the received query **102**.

(44) Block **408** determines a first efficiency value for analyzing the data entries **120** in the data repository **118** and a second efficiency value for analyzing previous queries **302** associated with the data entries **120**. As described with regard to FIG. 3, a thresholding module **304** may generate a threshold determination **306** indicative of whether it would be more efficient to first analyze the augmented query **114** based on the data entries **120** in the data repositories, or to first analyze the augmented query **114** based on the previous queries **302** associated with the data entries **120**. To facilitate generation of the threshold determination **306**, the thresholding module **304** may determine an efficiency value associated with each analysis. The efficiency value may be measured using one or more of elapsed time, computing cycles or other computational resources, electrical power or other resources, and so forth. In some implementations, determining an efficiency value may include determining a number, size, format, or other characteristics of the data entries **120** in the data repository **118**, and a number, size, format, or other characteristics of the previous queries **302**. In some implementations, the efficiency value(s) may include a numeric or quantifiable value. In other implementations, the efficiency value may include a comparison between characteristics of the data entries **120** and characteristics of the previous queries **302** that may not necessarily be expressed as a number or quantifiable value.

(45) Block **410** determines whether the first efficiency value is greater than the second efficiency value. In cases where the efficiency values are not expressed as quantities, block **410** may determine whether the first and second efficiency values indicate whether analysis of the augmented query **114** using the data entries **120** prior to the previous queries **302** would be more economical, faster, or more advantageous than analysis of the received query **102** using the previous queries **302** prior to the data entries **120**.

(46) If the first efficiency value is greater than the second efficiency value, this may indicate that analysis of the augmented query **114** using the data entries **120** prior to the previous queries **302** is more efficient than first analyzing the augmented query **114** using the previous queries **302**. Block **412** may be performed if the first efficiency value is greater than or equal to the second efficiency value. Block **412** may determine correspondence values for a subset of the data entries **120** that correspond to the augmented query **114**. As described with regard to FIG. 1, a knowledge module **116** associated with the query server **108** may determine correspondence between the data entries **120** in the data repository **118** and the augmented query **114**. Determining this correspondence may include determining correspondence values for the data entries **120**. The correspondence value for a particular data entry **120** may be determined based on parameters that are common between the augmented query **114** and the particular data entry **120** and in some cases, the weight values for the parameters. In one example implementation, a correspondence value may be determined by calculating the sum of the weight values for each parameter shared by the particular data entry **120** and the augmented query **114**. The knowledge module **116** may determine the subset of the data entries **120** by determining a selected number of data entries **120** having the greatest correspondence values, such as the data entries **120** associated with the one-hundred greatest correspondence values. In other implementations, the knowledge module **116** may determine the subset of data entries **120** by determining the data entries **120** having an associated correspondence

value that exceeds a threshold correspondence value. In still other implementations, the knowledge module **116** may determine the subset of data entries **120** using a combination of threshold values and a selected number of data entries **120**.

(47) Block **414** determines correspondence values for particular previous queries **302** associated with the subset of data entries **120**. As described with regard to FIGS. **1** and **3**, a query module **122** associated with the query server **108** may determine the previous queries **302** that are associated with the subset of data entries **120** determined by the knowledge module **116**. A previous query **302** may be associated with a data entry **120** if the response **104** to that previous query **302** included information indicative of the data entry **120**. In some cases, the previous query **302** may be associated with the data entry **120** only if feedback data indicating that the response **104** led to the resolution of the previous query **302** was received. Query data **126** may indicate the associations between each data entry **120** and one or more previous queries **302**. The query module **122** may determine correspondence between each of the previous queries **302** associated with the determined subset of data entries **120** and the augmented query **114**. For example, determining correspondence may include determining correspondence values for the previous queries **302**. The correspondence value for a particular previous query **302** may be determined based on parameters that are common between the augmented query **114** and the particular previous query **302** and in some cases, the weight values for the parameters. In some implementations, if no correspondence value for a previous query **302** exceeds a threshold correspondence value, a notification may instead be generated to request human intervention to resolve the received query **102**.

(48) Block **416** generates a response **104** indicative of the data entry **120** having the largest aggregate correspondence value. The aggregate correspondence value may be based on the correspondence value determined between the query and the data entry **120**. The aggregate correspondence value may also be based on one or more correspondence values determined between the query and the previous queries **302** that are associated with the data entry **120**. The response **104** may include at least a portion of the content of the data entry **120**. In other implementations, the response **104** may include a link or description of the data entry **120** or instructions for accessing the data entry **120**. A response module **128** associated with the query server **108** may generate the response **104**. In some implementations, the response **104** may be based at least partially on response data **130**, which may indicate particular formats, types of data, or other information to be included in the response **104**.

(49) If the second efficiency value is greater than the first efficiency value, this may indicate that analysis of the augmented query **114** using the previous queries **302** prior to the data entries **120** is more efficient than first analyzing the augmented query **114** using the data entries **120**. Block **418** may be performed if the first efficiency value is less than the second efficiency value. Block **418** determines correspondence values for a subset of the previous queries **302** that correspond to the augmented query **114**. The query module **122** may determine correspondence between the parameters of the previous queries **302** associated with the data entries **120** in the data repository **118** and the parameters of the augmented query **114**. Determination of this correspondence may include determining correspondence values for the previous queries **302**. In one implementation, a correspondence value for a particular previous query **302** may be determined by calculating the sum of the weight values for each parameter shared by the augmented query **114** and the particular previous query **302**. The subset of previous queries **302** may include a preselected number of previous queries **302**, such as the fifty previous queries **302** having the greatest associated correspondence values. In other implementations, the subset of previous queries **302** may include previous queries **302** having a correspondence value that exceeds a threshold correspondence value. In still other implementations, the subset of previous queries **302** may be determined using a combination of threshold values and preselected numbers of previous queries **302**.

(50) Block **420** determines correspondence values for data entries **120** associated with the subset of previous queries **302**. For example, the knowledge module **116** may determine a portion of the data

entries **120** that are associated with the subset of previous queries **302**. The associated data entries **120** may include the data entries **120** that were used to generate responses **104** to the subset of previous queries **302**. In some implementations, a data entry **120** may be associated with a previous query **302** only if feedback data indicating that the response **104** led to the resolution of the previous query **302** was received. The correspondence value for a particular data entry **120** may be determined based on parameters that are common between the augmented query **114** and the particular data entry **120** and in some cases, the weight values for the parameters. In some implementations, if no correspondence value for a data entry **120** exceeds a threshold correspondence value, a notification may instead be generated to request human intervention to resolve the received query **102**.

(51) After performance of block **420**, block **416** may be performed to determine the particular data entry **120** having the largest correspondence value. Block **416** generates a response **104** indicative of the particular data entry **120**. The response **104** may include at least a portion of the content of the particular data entry **120**. In other implementations, the response **104** may include a link or other means to access the data entry **120** or instructions regarding the manner in which the data entry **120** may be accessed.

(52) FIG. 5 is a flow diagram **500** illustrating a method for generating responses **104** and notifications based on whether a user is authorized to access a data entry **120** or data repository **118**. Block **502** receives a query from a user device **106**. As described with regard to FIG. 1, a user device **106** may generate and provide a received query **102** to a query server **108**. User data **204** associated with the received query **102** may be used to determine a source of the received query **102**.

(53) Block **504** determines, based on security data **206** and user data **204** associated with the received query **102**, whether the user device **106** is authorized to access a data repository **118**. As described with regard to FIG. 2, a security module **202** associated with the query server **108** may determine correspondence between the user data **204** and security data **206** that associates sources of queries with sources of data entries **120**. Correspondence between the user data **204** and the security data **206** may indicate that the user device **106** is permitted to access a particular data repository **118**. A lack of correspondence between the user data **204** and the security data **206** may indicate that the user device **106** is not authorized to access the data repository **118**. In some implementations, a user device **106** may be permitted to access certain data entries **120** within a data repository **118**, but not other data entries **120** therein. In such cases, the security module **202** or another module associated with the query server **108** may determine correspondence between one or more of the terms or parameters in the received query **102** and security data **206** that indicates the particular terms or parameters for which access may be restricted. Correspondence between the parameters may indicate that the user device **106** is not authorized to access the data entries **120** that may be responsive to the received query **102** unless the source of the query indicated in the user data **204** corresponds to the authorized users indicated in the security data **206**.

(54) If the user data **204** corresponds to the security data **206**, this correspondence may indicate that the user device **106** is authorized to access a data repository **118** or data entry **120**. Block **506** may be performed based on this correspondence. Block **506** generates an augmented query **114** based on the language data **112** and the received query **102**. As described with regard to FIGS. 1 and 4, a language module **110** associated with the query server **108** may add or remove parameters to or from the received query and associate weight values with at least a portion of the parameters to generate the augmented query **114**.

(55) Block **508** may then determine correspondence values for a subset of the data entries **120** within the data repository **118** that correspond to the augmented query **114**. A correspondence value for a particular data entry **120** may be determined based on the parameters that are common between the augmented query **114** and the particular data entry **120**. The subset of data entries **120** may include a fixed quantity of data entries **120**, a set of data entries **120** having a correspondence

value that exceeds a threshold, or may be determined using a combination of threshold values or fixed quantities.

(56) In some implementations, after determination of the subset of data entries **120**, the security module **202** may determine correspondence between the subset of data entries **120**, the security data **206**, and the user data **204**. This correspondence may indicate whether the user device **106** is authorized to access one or more of the particular data entries **120** within the subset.

(57) Block **510** determines correspondence values for previous queries **302** associated with the subset of data entries **120**. As described with regard to FIGS. **1** and **3**, a query module **122** associated with the query server **108** may determine the previous queries **302** associated with the subset of the data entries **120** determined by the knowledge module **116**. The query module **122** may also determine correspondence between the previous queries **302** and the augmented query **114**, such as by determining common parameters shared by the previous queries **302** and augmented query **114**. Block **512** generates a response **104** indicative of the data entry **120** associated with the largest aggregate correspondence value, which may be based on the correspondence values determined at block **508** and **510**.

(58) In some implementations, after determination of the particular data entry **120** that may be used to generate a response **104**, but prior to providing a response **104** to the user device **106**, the security module **202** may determine correspondence between the particular data entry **120**, the security data **206**, and the user data **204**. This correspondence may indicate whether the user device **106** is authorized to access the particular data entry **120**.

(59) If block **504** determines a lack of correspondence between the security data **206** and the user data **204**, this lack of correspondence may indicate that the user device **106** is not authorized to access the data repository **118** or one or more of the data entries **120**. Block **514** may be performed responsive to determination of a lack of correspondence between the user data **204** and security data **206**. Block **514** generates a notification indicative of an attempt to access the data repository **118** by an unauthorized user. For example, such a notification may be provided to an administrator associated with the data repository **118**. A notification may include an indication of the user data **204**, all or a portion of the received query **102**, an indication of the data repository **118** or data entry **120** that may be applicable to the received query **102**, and so forth.

(60) Block **516** may generate a response **104** indicative of one or more of the lack of authorization to access the data repository **118** or an alternate method to provide or resolve the query. For example, a response **104** may be provided to the user device **106** that indicates the user device **106** is not authorized to access one or more sources of data applicable to the received query **102**. In some implementations, the response may include additional information, such as other sources of data that the user device **106** may be authorized to access, instructions for requesting human intervention to resolve the query, instructions regarding particular individuals or departments that may be contacted to resolve the query or to obtain authorization to access particular sources of data, and so forth.

(61) FIG. **6** is a flow diagram **600** illustrating a method for providing a response **104** to a query and receiving feedback data indicative of whether the response **104** resolved the query. Block **602** receives a query from a user device **106**. The received query **102** may include any manner of data, such as alphanumeric data expressing a question or search query in natural language.

(62) Block **604** generates an augmented query **114** based on language data **112**. As discussed with regard to FIGS. **1**, **4**, and **5**, to generate the augmented query **114**, a language module **110** associated with the query server **108** may add or remove parameters to or from the received query **102** and associate weight values with one or more of the parameters.

(63) Block **606** determines correspondence values for a subset of the data entries **120** within a data repository **118** that correspond to the augmented query **114**. For example, a knowledge module **116** associated with the query server **108** may determine particular data entries **120** having parameters in common with the augmented query **114**. Based on the particular common parameters and the

weight values associated with each parameter, a correspondence value may be determined for each data entry **120**. The subset of data entries **120** determined by the knowledge module **116** may include data entries **120** having a correspondence value in excess of a threshold or a fixed number of data entries **120**. In other implementations, the subset of data entries **120** may be determined using a combination of threshold values and fixed quantities.

(64) Block **608** determines, based on query data **126**, correspondence values for previous queries **302** associated with the subset of data entries **120**, and whether at least one correspondence value exceeds a threshold. For example, a query module **122** associated with the query sever **108** may determine the previous queries **302** that are associated with the subset of data entries **120** determined by the knowledge module **116**. The query data **126** may associate particular previous queries **302** with data entries **120** that were used to generate a response **104** to those previous queries **302**. The query module **122** may also determine correspondence between the previous queries **302** and the augmented query **114**, which may include determining correspondence values for the previous queries **302** based on common parameters and the weight values associated with each parameter. If none of the correspondence values exceed a selected threshold value, then none of the determined data entries **120** or previous queries **302** may be suitable for generation of a response **104**. In such a case, the method may proceed to block **618** to intervention by a human or team of humans to resolve the query.

(65) If at least one correspondence value exceeds the threshold, block **610** generates a response **104** indicative of the particular data entry **120** that is associated with the largest aggregate correspondence value. The response **104** may include all or a portion of the data entry **120**, a link or other means by which the data entry **120** may be accessed, instructions for accessing the data entry **120**, and so forth.

(66) Block **612** receives feedback data from the user device **106** indicative of whether the response **104** resolved the query. For example, subsequent to providing the response **104**, a user interface may be provided to the user device **106** requesting feedback data. In other implementations, resolution of the received query **102** may be determined in the absence of user-input feedback data. For example, a received query **102** may request instructions for configuring a computing device to access a particular network. Subsequently, if access to the network by the computing device is detected, this detection may indicate that the response **104** resolved the received query **102**. As another example, subsequent to a response **104**, the user device **106** may provide a communication to an individual or group of individuals responsible for resolving queries. Based on this communication, it may be determined that the response **104** did not resolve the received query **102**.

(67) Block **614** determines whether the feedback data corresponds to one or more feedback values. For example, a user interface requesting feedback data may request that a user select or indicate text, a button, a link, or another type of feature, to indicate whether the response **104** resolved the received query **102**. Continuing the example, a threshold feedback value may include selection of a button labeled “Yes.” If the feedback data corresponds to a threshold feedback value, this may indicate that the response **104** was useful in resolving the received query **102**. If the feedback data deviates from the threshold feedback value(s), this may indicate that the response **104** was not useful in resolving the received query **102**.

(68) If the feedback data corresponds to a threshold feedback value, block **616** may be performed. Block **616** stores the received query **102** as additional query data **126** associated with the particular data entry **120** that was used to generate the response **104**. Subsequently, if another query similar to the received query **102** is received by the query server **108**, similarities between this query and the received query **102** may facilitate use of the associated data entry **120** to resolve the subsequent query.

(69) If the feedback data does not correspond to a threshold feedback value, block **618** may be performed. Block **618** generates a notification requesting human or team intervention to resolve the query. In other implementations, additional data entries **120** may be queried or provided to the user

device **106**. For example, if the data entry **120** associated with the previous query **302** having the greatest correspondence value is not useful to resolve a query, the data entry **120** associated with the previous query **302** having the second greatest correspondence value may be used to generate a second response **104**. In some implementations, an indication of the lack of correspondence between the feedback value and the threshold feedback value(s) may be stored as additional query data **126**. For example, if a particular data entry **120** was not useful to resolve a particular received query **102**, generation of additional query data **126** indicative of this result may decrease the likelihood that the particular data entry **120** will correspond to subsequent similar queries.

Continuing the example, the additional query data **126** may include the addition of parameters having negative weights, the reduction of weights associated with existing parameters, and so forth.

(70) In some implementations, block **618** may determine a particular type of human or team intervention to be requested. For example, a team or individual user may be associated with group data. The group data may include a title or description associated with a human or team, an indication of previous data entries **120** created or edited by the human or team, an indication of previous requests addressed or resolved by the human or team, and so forth. Continuing the example, if a received query **102** corresponds with the group data for a particular team within a threshold level of correspondence, the received query may be provided to the particular team. In cases where a received query **102** does not correspond to the group data for any human or team within the threshold level of correspondence, the received query **102** may be provided to a human or team tasked to resolve general queries or to route queries to other sources.

(71) In each instance that human intervention is used to resolve a query, an indication of the particular team or human that addressed the query may be stored as additional query data **126**. If the resolution involved the creation, editing, or use of a particular data entry **120**, the query data **126** may also include an indication of the data entry **120**.

(72) FIG. 7 is a block diagram **700** depicting a computing device **702** within the scope of the present disclosure. The computing device **702** may include, without limitation, one or more servers, personal computers, smartphones or other mobile devices, set-top boxes, tablet computers, wearable computers, automotive computers, and so forth. For example, the computing device **702** may include a query server **108**, such as the query server **108** described with regard to FIGS. 1-3. Additionally, while FIG. 7 depicts a single example computing device **702**, in some implementations, computing functions described within the scope of the present disclosure may be performed by multiple computing devices **702**, such as a distributed network of query servers **108** or other computing devices **702** in communication therewith. For example, a first computing device **702** may store one or more modules that may act upon data stored in a second computing device **702**.

(73) One or more power supplies **704** may be configured to provide electrical power suitable for operating the components of the computing device **702**. In some implementations, the power supply **704** may include a rechargeable battery, fuel cell, photovoltaic cell, power conditioning circuitry, and so forth.

(74) The computing device **702** may include one or more hardware processor(s) **706** (processors) configured to execute one or more stored instructions. The processor(s) **706** may include one or more cores. One or more clocks **708** may provide information indicative of date, time, ticks, and so forth. For example, the processor(s) **706** may use data from the clock **708** to generate a timestamp, trigger a preprogrammed action, and so forth.

(75) The computing device **702** may include one or more communication interface(s) **710**, such as input/output (I/O) interface(s) **712**, network interface(s) **714**, and so forth. The communication interfaces **710** may enable the computing device **702**, or components of the computing device **702**, to communicate with other computing devices **702** or components thereof. The I/O interface(s) **712** may include interfaces such as Inter-Integrated Circuit (I2C), Serial Peripheral Interface bus (SPI), Universal Serial Bus (USB) as promulgated by the USB Implementers Forum, RS-232, and so

forth.

(76) The I/O interface(s) **712** may couple to one or more I/O device(s) **716**. The I/O devices **716** may include any manner of input device or output device associated with the computing device **702** or with another computing device **702** in communication therewith. For example, I/O devices **716** may include touch sensors, keyboards, mouse devices, microphones, image sensors (e.g., cameras), scanners, displays, speakers, lights, haptic devices, printers, motion sensors, location sensors, and so forth. In some implementations, the I/O device(s) **716** may be physically incorporated with a computing device **702** or may be externally placed.

(77) The network interface(s) **714** may be configured to provide communications between the computing device **702** and other devices, such as the I/O devices **716**, routers, access points, user devices **106**, other computing devices **702**, and so forth. The network interface(s) **714** may include devices configured to couple to one or more networks, including local area networks (LANs), wireless LANs, wide area networks (WANs), wireless WANs, and so forth. For example, the network interfaces **714** may include computing devices **702** compatible with Ethernet, Wi-Fi, Wi-Fi Direct, Bluetooth, Bluetooth Low Energy, ZigBee, Z-Wave, 3G, 4G, LTE, and so forth.

(78) The computing device **702** may include one or more busses or other internal communications hardware or software that allows for the transfer of data between the various modules and components of the computing device **702**.

(79) As shown in FIG. 7, the computing device **702** may include one or more memories **718**. The memory **718** may include one or more computer-readable storage media (CRSM). The CRSM may be any one or more of an electronic storage medium, a magnetic storage medium, an optical storage medium, a quantum storage medium, a mechanical computer storage medium, and so forth. The memory **718** may provide storage of computer-readable instructions, data structures, program modules, and other data for the operation of the computing device **702**. A few example modules are shown stored in the memory **718**, although the same functionality may alternatively be implemented in hardware, firmware, or as a system on a chip (SoC).

(80) The memory **718** may include one or more operating system (OS) modules **720**. The OS module **720** may be configured to manage hardware resource devices such as the I/O interfaces **712**, the network interfaces **714**, the I/O devices **716**, and to provide various services to applications or modules executing on the processors **706**. The OS module **720** may implement a variant of the FreeBSD operating system as promulgated by the FreeBSD Project; UNIX or a UNIX-like operating system; a variation of the Linux operating system as promulgated by Linus Torvalds; the Windows operating system from Microsoft Corporation of Redmond, Washington, USA; or other operating systems.

(81) A data store **722** and one or more of the following modules may also be stored in the memory **718**. The modules may be executed as foreground applications, background tasks, daemons, and so forth. The data store **722** may use a flat file, database, linked list, tree, executable code, script, or other data structure to store information. In some implementations, the data store **722** or a portion of the data store **722** may be distributed across one or more other devices including other computing devices **702**, network attached storage devices, and so forth.

(82) A communication module **724** stored in the memory **718** may be configured to establish communications with user devices **106**, query servers **108**, or other computing devices **702**. For example, the communication module **724** may be configured to receive queries from user devices **106** or other computing devices **702** and to provide responses **104** or other data to other computing devices **702**.

(83) The memory **718** may store a language module **110**. The language module **110** may be configured to determine parameters of a received query **102**. For example, a received query **102** may include one or more of alphanumeric data, video data, audio data, image data, or other types of data. The language module **110** may determine the types of data within the received query **102** and particular parameters associated with one or more types of data. For example, the language module

110 may determine particular words within a received query **102**, such as by determining correspondence between alphanumeric data in the received query **102** and language data **112**, which in some implementations may include dictionary data indicative of words of one or more natural languages. As another example, the language module **110** may include an optical character recognition (OCR) module configured to recognize text embedded within image data, an image recognition module configured to recognize characteristics of images, and so forth. As yet another example, the language module **110** may include a speech recognition, speech-to-text, or text-to-speech module configured to determine words present in audio data.

(84) Based on the language data **112**, the language module **110** may determine a weight value associated with one or more of the parameters determined in the received query **102**. For example, the language data **112** may associate particular query parameters with corresponding weight values. Continuing the example, words within a received query **102** that are not indicative of the purpose of the received query **102** and may commonly occur in many queries may have a weight value of zero or a low weight value. Words that are indicative of the purpose of the received query **102** and do not commonly occur within other queries may have a high weight value. In some implementations, the language module **110** may be configured to remove one or more parameters from the received query **102** when generating an augmented query **114**. For example, query parameters having a weight value of zero or a weight value less than a threshold weight value may be removed from the received query **102** to generate the augmented query **114**. In some implementations, parameters that lack an associated weight value may be assigned a default weight value. In other implementations, parameters that lack an associated weight value may be disregarded.

(85) In some implementations, the language data **112** may also associate one or more synonyms with particular query parameters. In such cases, the language module **110** may add one or more synonyms to the received query **102** to generate the augmented query **114**. The augmented query **114** may include an indication of the weight value of each parameter. In some implementations, a synonym may have a weight value equal to the weight value of the query parameter for which the synonym was determined. In other implementations, a synonym may be associated with a different weight value than that of the query parameter for which the synonym was determined.

(86) The memory **718** may also store the knowledge module **116**. The knowledge module **116** may be configured to determine correspondence between an augmented query **114** and one or more data entries **120**. For example, the augmented query **114** may include one or more parameters, such as the query parameters determined by the language module **110** and the parameters added to the received query **102** by the language module **110** to generate the augmented query **114**. Each data entry **120** may also include one or more parameters. For example, a data entry **120** may include one or more of alphanumeric data, audio data, video data, image data, and so forth. Continuing the example, the data entry **120** may include one or more words or groups of words, one or more grammatical elements or arrangements of words, or other parameters that are included in the augmented query **114**. Each parameter common between the data entry **120** and augmented query **114** may have an associated weight value, indicated in the language data **112**. In some implementations, the knowledge module **116** may determine a correspondence value for each data entry **120** based on the common parameters for each data entry **120** that are shared with the augmented query **114**, and the weight value for each parameter.

(87) In some implementations, the knowledge module **116** may be configured to determine a subset of the data entries **120**. The subset of data entries **120** may include all data entries having a correspondence value greater than a threshold correspondence value. In other implementations, the knowledge module **116** may be configured to determine a selected quantity of data entries **120**, such as the forty data entries **120** having the greatest forty correspondence values. In still other implementations, the subset of data entries **120** may be determined using a combination of threshold correspondence values and a selected quantity of data entries **120**. For example, the

knowledge module **116** may determine the twenty data entries **120** having the greatest correspondence values, as long as each correspondence value exceeds a threshold correspondence value. In cases, where twenty of the data entries **120** do not have correspondence values that exceed the threshold correspondence value, only the data entries **120** having a correspondence value in excess of the threshold may be included in the subset.

(88) The memory **718** may also include the query module **122**. The query module **122** may be configured to determine, based on query data **126**, the correspondence values for previous queries **302** received by the computing device **702** that are associated with the subset of data entries **120** determined by the knowledge module **116**. For example, the query data **126** may associate particular previous queries **302** with particular data entries **120**. The query module **122** may also determine correspondence between previous queries **302** and the augmented query **114**. For example, each previous query **302** may include one or more parameters, such as words, grammatical structures, formats, images, audio data, and so forth. A particular previous query **302** may have one or more parameters in common with the augmented query **114**. Based on the weight value for each common parameter, as indicated in the language data **112**, a correspondence value for the previous query **302** may be determined.

(89) The memory **718** may additionally store the response module **128**. The response module **128** or the query module **122** may be configured to determine the particular data entry **120** that corresponds to the previous query **302** having the greatest correspondence value. The response module **128** may generate a response **104** based on the particular data entry **120** and response data **130**. The response data **130** may include alphanumeric data, audio data, video data, image data, or other data that may be included in the response **104**, one or more formats or arrangements of data, and so forth. For example, the response data **130** may include one or more fonts, templates, styles, and so forth that may be applied to the text of the particular data entry **120**. As another example, the response data **130** may include instructional text to be provided in association with a hyperlink that may be used to access the particular data entry **120**. In some implementations, different response data **130** may be associated with different data entries **120**. For example, a response **104** associated with a first data entry **120** may include the full text of that data entry **120**, presented in a particular font and arrangement indicated in the response data **130**. A response **104** associated with a second data entry **120** may include instructional text and a hyperlink used to access the second data entry **120**.

(90) The memory **718** may further store the security module **202**. The security module **202** may determine correspondence between user data **204**, determined from a received query **102**, and security data **206**, to determine whether a particular user device **106** is authorized to access a data repository **118** or data entry **120**. For example, security data **206** may associate sources of queries with sources of data entries **120**. A source of the received query **102** may be determined based on the user data **204**. For example, the user data **204** may include an IP address or other network address or identifier. The security data **206** may associate various network addresses or identifiers with corresponding sources of queries, such as user accounts, user names or identifiers, user companies, and so forth. As such, the security data **206** may indicate particular sources of queries, such as user devices **106** or user accounts, that are authorized to access particular data entries **120** or particular sources of data entries **120**. Based on correspondence between the user data **204** and the security data **206**, the security module **202** may determine whether a user device **106** is authorized to access a specific data entry **120** or data repository **118** and either cause the user device **106** to be provided with access or prevent access by the user device **106**. In some implementations, the security module **202** may generate one or more notifications indicative of a successful or unsuccessful attempt to access a particular data entry **120** or data repository **118**. In some cases, notifications may be provided to an administrator associated with the computing device **702**. In other cases, notifications may be provided to the user device **106** submitting the query. In some implementations, based on a lack of correspondence between the user data **204** and

security data **206**, the security module **202** may generate a response **104** to a received query **102** that indicates one or more of a lack of authorization to access applicable data sources, alternate means for resolving the query, contact information for individuals or groups of individuals that may assist with resolving the query or obtaining access to the data sources, and so forth. The particular content of such a response **104** may be determined based in part on the particular data entry **120** or data repository **118** associated with the received query **102**, the response data **130**, and the security data **206**.

(91) The memory **718** may also store the thresholding module **304**. The thresholding module **304** may determine the quantity and characteristics (e.g., data size, data types, formats) of the data entries **120** and previous queries **302** stored in the data store **722**. Based on the quantity and characteristics of the data entries **120** and previous queries **302**, the thresholding module **304** may determine a first efficiency value indicative of the time or resources that may be used to determine correspondence between a query and the data entries **102**, and a second efficiency value indicative of the time or resources that may be used to determine correspondence between the query and the previous queries **302**. The efficiency values may include a length of time that may be used to process a query, a quantity of computing resources, such as processor cycles, that may be used to process the query, a quantity of external resources, such as electrical power, that may be used to process the query, and so forth. The manner in which the efficiency values are calculated may be determined based on one or more rules or algorithms indicated by threshold data **308**. Based on the quantity and characteristics of the data entries **120** and previous queries **302**, the thresholding module **304** may generate a thresholding determination **306** indicating whether a query is first analyzed by determining correspondence between the query and the data entries **120**, or by determining correspondence between the query and the previous queries **302**. The thresholding data **308** may include data indicative of relationships between the previous queries **302** and data entries **120** or between the first and second efficiency values that may determine whether initially analyzing a query using the data entries **120** or the previous queries **302** would consume less time or resources.

(92) Other modules **726** may also be present in the memory **718**. For example, encryption modules may be used to encrypt and decrypt communications between computing devices **702**. User account modules may be configured to receive and process user data **204**. Administrator modules may be used to modify default settings and preferences. Machine learning modules may be configured to determine relationships between queries and data entries **120** and between query parameters and language data **112**. User interface modules may be used to provide user interfaces that may receive queries, user data **204**, feedback data, and so forth. Feedback modules may receive feedback data and determine correspondence between the feedback data and threshold feedback value, which may in turn determine whether a received query **102** is stored as additional query data **126**.

(93) Other data **728** within the data store **722** may include default configurations and settings associated with computing devices **702**. Other data **728** may also include security data, such as encryption keys and schema, access credentials, and so forth. Other data **728** may further include user interface content and formats, algorithms used to process and analyze feedback data, and so forth.

(94) In different implementations, different computing devices **702** may have different capabilities or capacities. For example, query servers **108** may have significantly more processor **706** capability and memory **718** capacity compared to the processor **706** capability and memory **718** capacity of user devices **106**.

(95) FIG. **8** depicts a series of block diagrams **800** illustrating one or more user interfaces that may be provided to a user device **106**. For example, a first user interface **802** may be used to receive user data **204** from a user. Continuing the example, the first user interface **802** may request a user identifier, such as an account name, a password, or other information indicative of a user, a user device **106**, a company of the user, a location of the user, and so forth. In other implementations,

user data **204** may be determined based on an IP address or other information that may be determined from the user device **106** without soliciting user input from the user. Based on the user data **204**, a particular source of data entries **120** associated with a particular company may be determined.

(96) A second user interface **804** may be provided to the user device **106** to request input of a query. For example, an employee of a company may input a query regarding how to setup a particular feature of the user device **106**. The particular output **806** provided to the user device **106** may depend on one or more of the user data **204**, security data **206**, or response data **130**. For example, a first output **806(1)** that includes a link used to access a data entry **120** and an instruction to access the link may be provided to the user device **106** if the response data **130** indicates that a response **104** associated with a particular responsive data entry **124** is to include a link for accessing the responsive data entry **124**. A second output **806(2)** that includes alphanumeric data indicative of the content of the responsive data entry **124** may be provided to the user device **106** if the response data **130** indicates that a response **104** should include the content of the responsive data entry **124**.

(97) A third output **806(3)** may be provided to the user device **106** if the user data **204** determined from the user device **106** does not correspond to security data **206**, which may indicate that the user device **106** or associated user account is not authorized to access a particular data entry **120** or source of data entries **120**. In such a case the third output **806(3)** may indicate a lack of authorization to access one or more data entries **120** and instructions regarding contacting an individual that may be able to assist with resolution of the query.

(98) A fourth output **806(4)** may be provided to the user device **106** if no data entry **120** or previous query **302** corresponds to the received query **102**, or an augmented query **114** based on the received query **102**. For example, if a correspondence value for each data entry **120** or previous query **302** is less than a threshold correspondence value, this may indicate that none of the existing data entries **120** are relevant to the received query **102**. In such a case, correspondence may be determined between the parameters of the received query **102** and group data, which may indicate particular parameters or types of queries that are addressed by a particular individual or group. Based on correspondence between the received query **102** and the group data, a particular recipient for the query may be determined. The fourth output **806(4)** may indicate the particular individual or group, such as a department of a company, that has received the query. In some implementations, the fourth output **806(4)** may also indicate a method of tracking the query, such as a ticket number. In some cases, a response **104** provided by a particular individual or group may be converted into a data entry **120** that may be stored in association with the corresponding received query **102**. A response **104** to subsequent queries that have parameters similar to the received query **102** may include at least a portion of the stored data entry **120**.

(99) FIG. **9** is a flow diagram **900** illustrating a method for providing a query to one or more human users. Block **902** receives a query from a user device **106**. The received query **102** may include various parameters, such as keywords, groups of words, arrangements of words, formats of words or letters, punctuation, and so forth.

(100) Block **904** determines a lack of data entries **120** that correspond to the query. For example, in some cases, for a particular received query **102**, no existing data entry **120** may include parameters that correspond to those of the received query **102** within a threshold level of confidence. Block **906** determines a lack of previous queries **302** that correspond to the received query **102**.

Continuing the example, in some cases, for a particular received query **102**, no existing previous query **302** may include parameters that correspond to those of the received query **102** within a threshold level of confidence.

(101) Responsive to the lack of corresponding data entries **120** and previous queries **302**, block **908** determines correspondence between the parameters of the query and group data that associates particular users (or groups of users) with particular parameters. For example, the group data may indicate a particular e-mail address to which particular queries may be sent if the queries include

certain keywords. In some implementations, if no user or group of users indicated in the group data corresponds with the parameters of the received query **102**, the query may be provided to a default destination, such as an e-mail address associated with users that resolve queries of a general nature or route queries to other users. Block **910** provides the query to a corresponding user or group of users. For example, the group data may indicate one or more e-mail addresses, telephone numbers, or addresses associated with other messaging or communication services. The query may be provided to the one or more users in a manner indicated in the group data.

(102) If the user(s) that receive the query resolve the query, such as by preparing a response **104**, block **912** provides the response **104** generated by the user or group of users to the user device **106**. In some cases, the response **104** may include a data entry **120** generated by the user or group of users, the data entry **120** including information responsive to the received query **102**. Block **914** may store an indication of the response **104** in association with an indication of the received query **102**, to enable the response **104** to be used to resolve subsequent queries similar to the received query **102**. For example, if a subsequent query having similar parameters is received, a data entry **120** generated by the user(s) may be used to form the response **104** in place of or in addition to providing the query to the corresponding group of users.

(103) In some cases, the user(s) that receive a query may send the query to one or more other users rather than generating a response **104**. For example, a particular group of users may be responsible for routing queries that do not correspond to the group data to suitable users for resolution. As another example, a particular query may include parameters that correspond to a particular group of users, but that group of users may be unsuitable for providing a response **104**. Continuing the example, the query, “Is it against company policy to configure a co-worker's computer to send faxes” may correspond to group data indicative of a company's IT department due to the terms “configure,” “computer,” and “faxes.” However, a query associated with company policy may be better addressed by the company's HR department. Block **916** may modify the group data to prevent routing of subsequent queries similar to the received query **102** to the user or group of users. For example, the group data may be modified such that subsequent queries having the term “company policy” are not to be provided to the IT department, independent of whether the queries include the terms “computer” and “configure.”

(104) Block **918** may provide a response **104** generated by one or more other users, to the user device **106**. In some cases, the response **104** may be generated by one or more users other than the user(s) that initially received the query. For example, the user(s) that initially receive the query may provide the query to another user or group of users rather than generating a response **104**. Responses **104** generated by the other users may similarly be stored in association with an indication of the query to enable the response(s) **104** to be used to resolve subsequent queries that are similar to the received query **102**, as indicated in block **914**.

(105) The processes discussed in this disclosure may be implemented in hardware, software, or a combination thereof. In the context of software, the described operations represent computer-executable instructions stored on one or more computer-readable storage media that, when executed by one or more hardware processors, perform the recited operations. Generally, computer-executable instructions include routines, programs, objects, components, data structures, and the like that perform particular functions or implement particular abstract data types. Those having ordinary skill in the art will readily recognize that certain steps or operations illustrated in the figures above may be eliminated, combined, or performed in an alternate order. Any steps or operations may be performed serially or in parallel. Furthermore, the order in which the operations are described is not intended to be construed as a limitation.

(106) Embodiments may be provided as a software program or computer program product including a non-transitory computer-readable storage medium having stored thereon instructions (in compressed or uncompressed form) that may be used to program a computer (or other electronic device) to perform processes or methods described in this disclosure. The computer-

readable storage medium may be one or more of an electronic storage medium, a magnetic storage medium, an optical storage medium, a quantum storage medium, and so forth. For example, the computer-readable storage media may include, but is not limited to, hard drives, floppy diskettes, optical disks, read-only memories (ROMs), random access memories (RAMs), erasable programmable ROMs (EPROMs), electrically erasable programmable ROMs (EEPROMs), flash memory, magnetic or optical cards, solid-state memory devices, or other types of physical media suitable for storing electronic instructions. Further, embodiments may also be provided as a computer program product including a transitory machine-readable signal (in compressed or uncompressed form). Examples of transitory machine-readable signals, whether modulated using a carrier or unmodulated, include, but are not limited to, signals that a computer system or machine hosting or running a computer program can be configured to access, including signals transferred by one or more networks. For example, the transitory machine-readable signal may comprise transmission of software by the Internet. Separate instances of these programs can be executed on or distributed across any number of separate computer systems. Although certain steps have been described as being performed by certain devices, software programs, processes, or entities, this need not be the case, and a variety of alternative implementations will be understood by those having ordinary skill in the art.

(107) Additionally, those having ordinary skill in the art will readily recognize that the techniques described above can be utilized in a variety of devices, environments, and situations. Although the subject matter has been described in language specific to structural features or methodological acts, it is to be understood that the subject matter defined in the appended claims is not necessarily limited to the specific features or acts described. Rather, the specific features and acts are disclosed as exemplary forms of implementing the claims.

Claims

1. A method comprising: receiving, by a first computing device and from a user device, a first query including one or more first query parameters; comparing a first efficiency value associated with computationally analyzing a plurality of data entries to a second efficiency value associated with computationally analyzing a plurality of previous queries; determining, based on the comparison, one of: first correspondence values based on the first efficiency value being greater than or equal to the second efficiency value and based on correspondence between the one or more first query parameters and the plurality of data entries; or second correspondence values based on the first efficiency value being less than the second efficiency value and based on correspondence between the one or more first query parameters and the plurality of previous queries; determining, based on the determined one of the first correspondence values or the second correspondence values being less than a first threshold correspondence value, a correspondence level between the one or more first query parameters and a first group of a plurality of groups of a first organization; transmitting to one or more computing devices associated with the first group, data indicative of the first query; receiving, from a computing device associated with a group of the plurality of groups, information responsive to the first query; transmitting, to the user device, and based on the information responsive to the first query, a response to the first query; obtaining feedback data associated with the response to the first query; and storing, based on the feedback data satisfying a feedback threshold, the first query as one of the plurality of previous queries.
2. The method of claim 1, wherein the first efficiency value is based on elapsed processing time, computational resources, or electrical power resources associated with the plurality of data entries, and wherein the second efficiency value is based on elapsed processing time, computational resources, or electrical power resources associated with the plurality of previous queries.
3. The method of claim 1, further comprising: determining that the data indicative of the first query has been transmitted from the one or more computing devices associated with the first group to one

or more second computing devices associated with a second group of the plurality of groups; and modifying second group data associated with the second group to reflect a higher correspondence level between the one or more first query parameters and the second group data than the correspondence level between the one or more first query parameters and first group data associated with the first group.

4. The method of claim 3, further comprising: receiving a second query including one or more second query parameters that correspond to the one or more first query parameters; and based on the higher correspondence level between the one or more first query parameters and the second group data, providing data indicative of the second query to the one or more second computing devices associated with the second group.

5. The method of claim 1, wherein obtaining the feedback data comprises receiving the feedback data from the user device, wherein the feedback data indicates that the response to the first query was useful, the method further comprising: determining, based on the feedback data indicating that the response to the first query was useful, that the feedback data satisfies the feedback threshold.

6. The method of claim 1, wherein the computing device associated with the group of the plurality of groups is a computing device associated with the first group.

7. The method of claim 6, wherein obtaining the feedback data comprises: generating, based on receiving the information responsive to the first query from the computing device associated with the first group, the feedback data, wherein the feedback data indicates resolution by a user of the first group; and determining, based on the feedback data indicating resolution by the user of the first group, that the feedback data satisfies the feedback threshold.

8. The method of claim 1, wherein the computing device associated with the group of the plurality of groups is a computing device associated with a second group of the plurality of groups.

9. The method of claim 8, wherein obtaining the feedback data comprises: generating, based on receiving the information responsive to the first query from the computing device associated with the second group, the feedback data, wherein the feedback data indicates resolution by a user of the second group; and determining, based on the feedback data indicating resolution by a user of the second group, that the feedback data satisfies the feedback threshold.

10. The method of claim 1, further comprising: receiving a second query including one or more second query parameters that correspond to the one or more first query parameters associated with the first query; and determining, based on the feedback data associated with the first query, a response to the second query.

11. The method of claim 1, further comprising: obtaining, after transmission of the response to the user device, configuration data associated with the user device or communication data transmitted from the user device to a computing device associated with one of the plurality of groups; and determining, based on the configuration data or the communication data, the feedback data.

12. An apparatus, comprising: one or more memories storing processor-executable code; and one or more processors coupled with the one or more memories and individually or collectively operable to execute the code to cause the apparatus to: receive, by a first computing device and from a user device, a first query including one or more first query parameters; compare a first efficiency value associated with computational analysis of a plurality of data entries to a second efficiency value associated with computational analysis of a plurality of previous queries; determine, based on the comparison, one of: first correspondence values base on the first efficiency value being greater than or equal to the second efficiency value and based on correspondence between the one or more first query parameters and the plurality of data entries; or second correspondence values base on the first efficiency value being less than the second efficiency value and based on correspondence between the one or more first query parameters and the plurality of previous queries; determine, based on the determined one of the first correspondence values or the second correspondence values being less than a first threshold correspondence value, a correspondence level between the one or more first query parameters and a first group of a plurality of groups of a first organization;

transmit to one or more computing devices associated with the first group, data indicative of the first query; receive, from a computing device associated with a group of the plurality of groups, information responsive to the first query; transmit, to the user device, and based on the information responsive to the first query, a response to the first query; obtain feedback data associated with the response to the first query; and store, based on the feedback data satisfying a feedback threshold, the first query as one of the plurality of previous queries.

13. The apparatus of claim 12, wherein the first efficiency value is based on elapsed processing time, computational resources, or electrical power resources associated with the plurality of data entries, and wherein the second efficiency value is based on elapsed processing time, computational resources, or electrical power resources associated with the plurality of previous queries.

14. The apparatus of claim 12, wherein the one or more processors are individually or collectively further operable to execute the code to cause the apparatus to: determine that the data indicative of the first query has been transmitted from the one or more computing devices associated with the first group to one or more second computing devices associated with a second group of the plurality of groups; modify second group data associated with the second group to reflect a higher correspondence level between the one or more first query parameters and the second group data than the correspondence level between the one or more first query parameters and first group data associated with the first group; receive a second query including one or more second query parameters that correspond to the one or more first query parameters; and based on the higher correspondence level between the one or more first query parameters and the second group data, provide data indicative of the second query to the one or more second computing devices associated with the second group.

15. The apparatus of claim 12, wherein, to obtain the feedback data, the one or more processors are individually or collectively operable to execute the code to cause the apparatus to receive the feedback data from the user device, wherein the feedback data indicates that the response to the first query was useful, and wherein the one or more processors are individually or collectively further operable to execute the code to cause the apparatus to: determine, based on the feedback data indicating that the response to the first query was useful, that the feedback data satisfies the feedback threshold.

16. The apparatus of claim 12, wherein the computing device associated with the group of the plurality of groups is a computing device associated with the first group, and wherein, to obtain the feedback data, the one or more processors are individually or collectively operable to execute the code to cause the apparatus to: generate, based on receipt of the information responsive to the first query from the computing device associated with the first group, the feedback data, wherein the feedback data indicates resolution by a user of the first group; and determine, based on the feedback data indicating resolution by the user of the first group, that the feedback data satisfies the feedback threshold.

17. The apparatus of claim 12, wherein the computing device associated with the group of the plurality of groups is a computing device associated with a second group of the plurality of groups, and wherein, to obtain the feedback data, the one or more processors are individually or collectively operable to execute the code to cause the apparatus to: generate, based on receipt of the information responsive to the first query from the computing device associated with the second group, the feedback data, wherein the feedback data indicates resolution by a user of the second group; and determine, based on the feedback data indicating resolution by a user of the second group, that the feedback data satisfies the feedback threshold.

18. The apparatus of claim 12, wherein the one or more processors are individually or collectively further operable to execute the code to cause the apparatus to: receive a second query including one or more second query parameters that correspond to the one or more first query parameters associated with the first query; and determine, based on the feedback data associated with the first

query, a response to the second query.

19. The apparatus of claim 12, wherein the one or more processors are individually or collectively further operable to execute the code to cause the apparatus to: obtain, after transmission of the response to the user device, configuration data associated with the user device or communication data transmitted from the user device to a computing device associated with one of the plurality of groups; and determine, based on the configuration data or the communication data, the feedback data.

20. A non-transitory computer-readable medium storing code, the code comprising instructions executable by one or more processors to: receive, by a first computing device and from a user device, a first query including one or more first query parameters; compare a first efficiency value associated with computational analysis of a plurality of data entries to a second efficiency value associated with computational analysis of a plurality of previous queries; determine, based on the comparison, one of: first correspondence values base on the first efficiency value being greater than or equal to the second efficiency value and based on correspondence between the one or more first query parameters and the plurality of data entries; or second correspondence values base on the first efficiency value being less than the second efficiency value and based on correspondence between the one or more first query parameters and the plurality of previous queries; determine, based on the determined one of the first correspondence values or the second correspondence values being less than a first threshold correspondence value, a correspondence level between the one or more first query parameters and a first group of a plurality of groups of a first organization; transmit to one or more computing devices associated with the first group, data indicative of the first query; receive, from a computing device associated with a group of the plurality of groups, information responsive to the first query; transmit, to the user device, and based on the information responsive to the first query, a response to the first query; obtain feedback data associated with the response to the first query; and store, based on the feedback data satisfying a feedback threshold, the first query as one of the plurality of previous queries.
