

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12388816
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Drechsler; Kyle Joseph et al.

Techniques for token proximity transactions

Abstract

Systems and methods are provided to enable a user to conduct a transaction using their credentials stored on a secure server computer (e.g., a computer associated with a partner such as another merchant) by merely presenting their authentication data at a physical location via an auxiliary device. An auxiliary device may be provided for interfacing with a partner's backend server (e.g., the secure server computer). In some embodiments, biometric authentication may provide a mechanism for a true seamless and potentially frictionless (in the case of modalities that do not require physical contact) interaction. Payment can occur without any need for a card, phone, wearable, or any other user device as long as the auxiliary device is able to recognize the user and retrieve a credential that can be linked to that user.

Inventors: Drechsler; Kyle Joseph (San Francisco, CA), Jones; Christopher (Greenbrae, CA), Venkat; Gayathri (Austin, TX), Shenker; Gavin (Los Angeles, CA), Leyva; Raul (Round Rock, TX), Sarma; Janardana (Foster City, CA), Lavender; Phillip (Foster City, CA), Movahedian; Leila (Foster City, CA), Roy; Pinesh (Redwood City, CA), Lopez; Eduardo (Menlo Park, CA)

Applicant: Visa International Service Association (San Francisco, CA)

Family ID: 70165127

Assignee: Visa International Service Association (San Francisco, CA)

Appl. No.: 18/670201

Filed: May 21, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240305628 A1	Sep. 12, 2024

Related U.S. Application Data

continuation parent-doc US 17282375 US 12028337 WO PCT/US2019/055233 20191008 child-
doc US 18670201
us-provisional-application US 62816752 20190311
us-provisional-application US 62813686 20190304
us-provisional-application US 62742818 20181008

Publication Classification

Int. Cl.: **H04L29/00** (20060101); **G06Q20/02** (20120101); **G06Q20/20** (20120101); **G06Q20/38** (20120101); **G06Q20/40** (20120101); **H04L9/32** (20060101); **H04L9/40** (20220101); **G06Q20/32** (20120101); **H04W12/06** (20210101)

U.S. Cl.:

CPC **H04L63/0853** (20130101); **G06Q20/02** (20130101); **G06Q20/202** (20130101); **G06Q20/3821** (20130101); **G06Q20/3829** (20130101); **G06Q20/385** (20130101); **G06Q20/401** (20130101); **G06Q20/40975** (20130101); **H04L9/3213** (20130101); **H04L63/0807** (20130101); **H04L63/0838** (20130101); **H04L63/0861** (20130101); **G06Q20/204** (20130101); **G06Q20/327** (20130101); **H04W12/06** (20130101)

Field of Classification Search

CPC: H04L (63/0853); H04L (9/3213); H04L (63/0807); H04L (63/0838); H04L (63/0861); G06Q (20/02); G06Q (20/202); G06Q (20/3821); G06Q (20/3829); G06Q (20/385); G06Q (20/401); G06Q (20/40975); G06Q (20/204); G06Q (20/327); G06Q (20/3226); H04W (12/06)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5280527	12/1993	Gullman et al.	N/A	N/A
5613012	12/1996	Hoffman et al.	N/A	N/A
5781438	12/1997	Lee et al.	N/A	N/A
5883810	12/1998	Franklin et al.	N/A	N/A
5930767	12/1998	Reber et al.	N/A	N/A
5953710	12/1998	Fleming	N/A	N/A
5956699	12/1998	Wong et al.	N/A	N/A
6000832	12/1998	Franklin et al.	N/A	N/A
6014635	12/1999	Harris et al.	N/A	N/A
6044360	12/1999	Picciallo	N/A	N/A
6163771	12/1999	Walker et al.	N/A	N/A
6227447	12/2000	Campisano	N/A	N/A
6236981	12/2000	Hill	N/A	N/A
6267292	12/2000	Walker et al.	N/A	N/A
6327578	12/2000	Linehan	N/A	N/A
6341724	12/2001	Campisano	N/A	N/A
6385596	12/2001	Wiser et al.	N/A	N/A

6422462	12/2001	Cohen	N/A	N/A
6425523	12/2001	Shem-Ur et al.	N/A	N/A
6453301	12/2001	Niwa	N/A	N/A
6592044	12/2002	Wong et al.	N/A	N/A
6636833	12/2002	Flitcroft et al.	N/A	N/A
6708182	12/2003	Kobayashi	N/A	G06Q 20/40975
6748367	12/2003	Lee	N/A	N/A
6805287	12/2003	Bishop et al.	N/A	N/A
6879965	12/2004	Fung et al.	N/A	N/A
6891953	12/2004	DeMello et al.	N/A	N/A
6901387	12/2004	Wells et al.	N/A	N/A
6931382	12/2004	Laage et al.	N/A	N/A
6938019	12/2004	Uzo	N/A	N/A
6941285	12/2004	Sarcanin	N/A	N/A
6980670	12/2004	Hoffman et al.	N/A	N/A
6990470	12/2005	Hogan et al.	N/A	N/A
6991157	12/2005	Bishop et al.	N/A	N/A
7051929	12/2005	Li	N/A	N/A
7069249	12/2005	Stolfo et al.	N/A	N/A
7103576	12/2005	Mann, III et al.	N/A	N/A
7113930	12/2005	Eccles et al.	N/A	N/A
7136835	12/2005	Flitcroft et al.	N/A	N/A
7177835	12/2006	Walker et al.	N/A	N/A
7177848	12/2006	Hogan et al.	N/A	N/A
7194437	12/2006	Britto et al.	N/A	N/A
7207477	12/2006	Ramachandran	235/375	G06Q 20/3276
7209561	12/2006	Shankar et al.	N/A	N/A
7264154	12/2006	Harris	N/A	N/A
7287692	12/2006	Patel et al.	N/A	N/A
7292999	12/2006	Hobson et al.	N/A	N/A
7350230	12/2007	Forrest	N/A	N/A
7353382	12/2007	Labrou et al.	N/A	N/A
7379919	12/2007	Hogan et al.	N/A	N/A
RE40444	12/2007	Linehan	N/A	N/A
7415443	12/2007	Hobson et al.	N/A	N/A
7444676	12/2007	Asghari-Kamrani et al.	N/A	N/A
7469151	12/2007	Khan et al.	N/A	N/A
7548889	12/2008	Bhambri et al.	N/A	N/A
7567934	12/2008	Flitcroft et al.	N/A	N/A
7567936	12/2008	Peckover et al.	N/A	N/A
7571139	12/2008	Giordano et al.	N/A	N/A
7571142	12/2008	Flitcroft et al.	N/A	N/A
7580898	12/2008	Brown et al.	N/A	N/A
7584153	12/2008	Brown et al.	N/A	N/A
7593896	12/2008	Flitcroft et al.	N/A	N/A
7606560	12/2008	Labrou et al.	N/A	N/A
7627531	12/2008	Breck et al.	N/A	N/A

7627895	12/2008	Gifford et al.	N/A	N/A
7650314	12/2009	Saunders	N/A	N/A
7685037	12/2009	Reiners et al.	N/A	N/A
7702578	12/2009	Fung et al.	N/A	N/A
7707120	12/2009	Dominguez et al.	N/A	N/A
7712655	12/2009	Wong	N/A	N/A
7734527	12/2009	Uzo	N/A	N/A
7753265	12/2009	Harris	N/A	N/A
7770789	12/2009	Oder, II et al.	N/A	N/A
7784685	12/2009	Hopkins, III	N/A	N/A
7793851	12/2009	Mullen	N/A	N/A
7801826	12/2009	Labrou et al.	N/A	N/A
7805376	12/2009	Smith	N/A	N/A
7805378	12/2009	Berardi et al.	N/A	N/A
7818264	12/2009	Hammad	N/A	N/A
7828220	12/2009	Mullen	N/A	N/A
7835960	12/2009	Breck et al.	N/A	N/A
7841523	12/2009	Oder, II et al.	N/A	N/A
7841539	12/2009	Hewton	N/A	N/A
7844550	12/2009	Walker et al.	N/A	N/A
7848980	12/2009	Carlson	N/A	N/A
7849020	12/2009	Johnson	N/A	N/A
7853529	12/2009	Walker et al.	N/A	N/A
7853995	12/2009	Chow et al.	N/A	N/A
7865414	12/2010	Fung et al.	N/A	N/A
7873579	12/2010	Hobson et al.	N/A	N/A
7873580	12/2010	Hobson et al.	N/A	N/A
7890393	12/2010	Talbert et al.	N/A	N/A
7891563	12/2010	Oder, II et al.	N/A	N/A
7896238	12/2010	Fein et al.	N/A	N/A
7908216	12/2010	Davis et al.	N/A	N/A
7922082	12/2010	Muscato	N/A	N/A
7931195	12/2010	Mullen	N/A	N/A
7937324	12/2010	Patterson	N/A	N/A
7938318	12/2010	Fein et al.	N/A	N/A
7954705	12/2010	Mullen	N/A	N/A
7959076	12/2010	Hopkins, III	N/A	N/A
7996288	12/2010	Stolfo	N/A	N/A
8025223	12/2010	Saunders et al.	N/A	N/A
8046256	12/2010	Chien et al.	N/A	N/A
8060448	12/2010	Jones	N/A	N/A
8060449	12/2010	Zhu	N/A	N/A
8074877	12/2010	Mullen et al.	N/A	N/A
8074879	12/2010	Harris	N/A	N/A
8082210	12/2010	Hansen et al.	N/A	N/A
8095113	12/2011	Kean et al.	N/A	N/A
8104679	12/2011	Brown	N/A	N/A
RE43157	12/2011	Bishop et al.	N/A	N/A
8109436	12/2011	Hopkins, III	N/A	N/A
8121942	12/2011	Carlson et al.	N/A	N/A

8121956	12/2011	Carlson et al.	N/A	N/A
8126449	12/2011	Beenau et al.	N/A	N/A
8132723	12/2011	Hogg et al.	N/A	N/A
8171525	12/2011	Pelly et al.	N/A	N/A
8175973	12/2011	Davis et al.	N/A	N/A
8190523	12/2011	Patterson	N/A	N/A
8196813	12/2011	Vadhri	N/A	N/A
8205791	12/2011	Randazza et al.	N/A	N/A
8219489	12/2011	Patterson	N/A	N/A
8224702	12/2011	Mengerink et al.	N/A	N/A
8225385	12/2011	Chow et al.	N/A	N/A
8229852	12/2011	Carlson	N/A	N/A
8265993	12/2011	Chien et al.	N/A	N/A
8280777	12/2011	Mengerink et al.	N/A	N/A
8281991	12/2011	Wentker et al.	N/A	N/A
8328095	12/2011	Oder, II et al.	N/A	N/A
8336088	12/2011	Raj et al.	N/A	N/A
8346666	12/2012	Lindelsee et al.	N/A	N/A
8376225	12/2012	Hopkins, III	N/A	N/A
8380177	12/2012	Laracey	N/A	N/A
8387873	12/2012	Saunders et al.	N/A	N/A
8401539	12/2012	Beenau et al.	N/A	N/A
8401898	12/2012	Chien et al.	N/A	N/A
8402555	12/2012	Grecia	N/A	N/A
8403211	12/2012	Brooks et al.	N/A	N/A
8412623	12/2012	Moon et al.	N/A	N/A
8412837	12/2012	Emigh et al.	N/A	N/A
8417642	12/2012	Oren	N/A	N/A
8447699	12/2012	Batada et al.	N/A	N/A
8453223	12/2012	Svigals et al.	N/A	N/A
8453925	12/2012	Fisher et al.	N/A	N/A
8458487	12/2012	Palgon et al.	N/A	N/A
8484134	12/2012	Hobson et al.	N/A	N/A
8485437	12/2012	Mullen et al.	N/A	N/A
8494959	12/2012	Hathaway et al.	N/A	N/A
8498908	12/2012	Mengerink et al.	N/A	N/A
8504475	12/2012	Brand et al.	N/A	N/A
8504478	12/2012	Saunders et al.	N/A	N/A
8510816	12/2012	Quach et al.	N/A	N/A
8528067	12/2012	Hurry et al.	N/A	N/A
8533116	12/2012	Davis et al.	N/A	N/A
8533860	12/2012	Grecia	N/A	N/A
8538845	12/2012	Liberty	N/A	N/A
8555079	12/2012	Shablygin et al.	N/A	N/A
8566168	12/2012	Bierbaum et al.	N/A	N/A
8567670	12/2012	Stanfield et al.	N/A	N/A
8571939	12/2012	Lindsey et al.	N/A	N/A
8577336	12/2012	Mechaley, Jr.	N/A	N/A
8577803	12/2012	Chatterjee et al.	N/A	N/A
8577813	12/2012	Weiss	N/A	N/A

8578176	12/2012	Mattsson	N/A	N/A
8583494	12/2012	Fisher	N/A	N/A
8584251	12/2012	McGuire et al.	N/A	N/A
8589237	12/2012	Fisher	N/A	N/A
8589271	12/2012	Evans	N/A	N/A
8589291	12/2012	Carlson et al.	N/A	N/A
8595098	12/2012	Starai et al.	N/A	N/A
8595812	12/2012	Bomar et al.	N/A	N/A
8595850	12/2012	Spies et al.	N/A	N/A
8606638	12/2012	Dragt	N/A	N/A
8606700	12/2012	Carlson et al.	N/A	N/A
8606720	12/2012	Baker et al.	N/A	N/A
8615468	12/2012	Varadarajan	N/A	N/A
8620754	12/2012	Fisher	N/A	N/A
8635157	12/2013	Smith et al.	N/A	N/A
8646059	12/2013	Von Behren et al.	N/A	N/A
8651374	12/2013	Brabson et al.	N/A	N/A
8656180	12/2013	Shablygin et al.	N/A	N/A
8751391	12/2013	Freund	N/A	N/A
8751642	12/2013	Vargas et al.	N/A	N/A
8762263	12/2013	Gauthier et al.	N/A	N/A
8793186	12/2013	Patterson	N/A	N/A
8838982	12/2013	Carlson et al.	N/A	N/A
8856539	12/2013	Weiss	N/A	N/A
8887308	12/2013	Grecia	N/A	N/A
8924297	12/2013	Kumnick et al.	N/A	N/A
9065643	12/2014	Hurry et al.	N/A	N/A
9070129	12/2014	Sheets et al.	N/A	N/A
9100826	12/2014	Weiss	N/A	N/A
9160741	12/2014	Wentker et al.	N/A	N/A
9229964	12/2015	Stevelinck	N/A	N/A
9245267	12/2015	Singh	N/A	N/A
9249241	12/2015	Dai et al.	N/A	N/A
9256871	12/2015	Anderson et al.	N/A	N/A
9280765	12/2015	Hammad	N/A	N/A
9530011	12/2015	French	N/A	N/A
9530137	12/2015	Weiss	N/A	N/A
9646303	12/2016	Karpenko et al.	N/A	N/A
9680942	12/2016	Dimmick	N/A	N/A
9996829	12/2017	Baig	N/A	G06Q 20/102
10242357	12/2018	Dorogusker	N/A	G06Q 20/3229
10318952	12/2018	Wade	N/A	H04B 5/24
10373149	12/2018	Sather	N/A	G06Q 20/409
10475024	12/2018	Behren	N/A	G06Q 20/204
10581611	12/2019	Osborn	N/A	H04L 9/002
10878402	12/2019	Blackie	N/A	G06Q 20/204
10997583	12/2020	Blackie	N/A	G06Q 20/3278
11087301	12/2020	Razaghi	N/A	G07F 7/088

11195159	12/2020	Alkasimi	N/A	B64D 11/00
11514437	12/2021	Jarosch	N/A	G06Q 20/38215
11636468	12/2022	Jarosch	705/76	G06Q 20/385
12028337	12/2023	Drechsler	N/A	H04L 63/0807
2001/0029485	12/2000	Brody et al.	N/A	N/A
2001/0034720	12/2000	Armes	N/A	N/A
2001/0054003	12/2000	Chien et al.	N/A	N/A
2002/0007320	12/2001	Hogan et al.	N/A	N/A
2002/0016749	12/2001	Borecki et al.	N/A	N/A
2002/0029193	12/2001	Ranjan et al.	N/A	N/A
2002/0035548	12/2001	Hogan et al.	N/A	N/A
2002/0073045	12/2001	Rubin et al.	N/A	N/A
2002/0096570	12/2001	Wong	235/494	G06K 19/07703
2002/0116341	12/2001	Hogan et al.	N/A	N/A
2002/0133467	12/2001	Hobson et al.	N/A	N/A
2002/0147913	12/2001	Lun Yip	N/A	N/A
2003/0028481	12/2002	Flitcroft et al.	N/A	N/A
2003/0130955	12/2002	Hawthorne	N/A	N/A
2003/0191709	12/2002	Elston et al.	N/A	N/A
2003/0191945	12/2002	Keech	N/A	N/A
2004/0010462	12/2003	Moon et al.	N/A	N/A
2004/0050928	12/2003	Bishop et al.	N/A	N/A
2004/0059682	12/2003	Hasumi et al.	N/A	N/A
2004/0093281	12/2003	Silverstein et al.	N/A	N/A
2004/0139008	12/2003	Mascavage, III	N/A	N/A
2004/0143532	12/2003	Lee	N/A	N/A
2004/0151353	12/2003	Topping	382/124	G06F 3/03543
2004/0158532	12/2003	Breck et al.	N/A	N/A
2004/0210449	12/2003	Breck et al.	N/A	N/A
2004/0210498	12/2003	Freund	N/A	N/A
2004/0232225	12/2003	Bishop et al.	N/A	N/A
2004/0236632	12/2003	Maritzen et al.	N/A	N/A
2004/0260646	12/2003	Berardi et al.	N/A	N/A
2005/0037735	12/2004	Coutts	N/A	N/A
2005/0080730	12/2004	Sorrentino	N/A	N/A
2005/0108178	12/2004	York	N/A	N/A
2005/0199709	12/2004	Linlor	N/A	N/A
2005/0246293	12/2004	Ong	N/A	N/A
2005/0269401	12/2004	Spitzer et al.	N/A	N/A
2005/0269402	12/2004	Spitzer et al.	N/A	N/A
2006/0016874	12/2005	Bonalle	235/380	G06K 19/0716
2006/0016875	12/2005	Bonalle	235/492	G07C 9/27
2006/0235795	12/2005	Johnson et al.	N/A	N/A
2006/0237528	12/2005	Bishop et al.	N/A	N/A
2006/0278704	12/2005	Saunders et al.	N/A	N/A

2007/0107044	12/2006	Yuen et al.	N/A	N/A
2007/0118891	12/2006	Buer	726/8	G06F 21/445
2007/0129955	12/2006	Dalmia et al.	N/A	N/A
2007/0136193	12/2006	Starr	N/A	N/A
2007/0136211	12/2006	Brown et al.	N/A	N/A
2007/0170247	12/2006	Friedman	N/A	N/A
2007/0179885	12/2006	Bird et al.	N/A	N/A
2007/0203732	12/2006	Griegel	235/379	G06Q 30/02
2007/0208671	12/2006	Brown et al.	N/A	N/A
2007/0245414	12/2006	Chan et al.	N/A	N/A
2007/0288377	12/2006	Shaked	N/A	N/A
2007/0291995	12/2006	Rivera	N/A	N/A
2008/0015988	12/2007	Brown et al.	N/A	N/A
2008/0029607	12/2007	Mullen	N/A	N/A
2008/0035738	12/2007	Mullen	N/A	N/A
2008/0052226	12/2007	Agarwal et al.	N/A	N/A
2008/0054068	12/2007	Mullen	N/A	N/A
2008/0054079	12/2007	Mullen	N/A	N/A
2008/0054081	12/2007	Mullen	N/A	N/A
2008/0065554	12/2007	Hogan et al.	N/A	N/A
2008/0065555	12/2007	Mullen	N/A	N/A
2008/0128513	12/2007	Hammad	235/492	G06Q 20/325
2008/0201264	12/2007	Brown et al.	N/A	N/A
2008/0201265	12/2007	Hewton	N/A	N/A
2008/0203152	12/2007	Hammad	235/380	G06Q 20/4097
2008/0203170	12/2007	Hammad	705/64	G06Q 20/20
2008/0228646	12/2007	Myers et al.	N/A	N/A
2008/0243702	12/2007	Hart et al.	N/A	N/A
2008/0245855	12/2007	Fein et al.	N/A	N/A
2008/0245861	12/2007	Fein et al.	N/A	N/A
2008/0270298	12/2007	McElroy	705/39	G06Q 40/02
2008/0283591	12/2007	Oder, II et al.	N/A	N/A
2008/0302869	12/2007	Mullen	N/A	N/A
2008/0302876	12/2007	Mullen	N/A	N/A
2008/0313264	12/2007	Pestoni	N/A	N/A
2009/0006262	12/2008	Brown et al.	N/A	N/A
2009/0010488	12/2008	Matsuoka et al.	N/A	N/A
2009/0037333	12/2008	Flitcroft et al.	N/A	N/A
2009/0037388	12/2008	Cooper et al.	N/A	N/A
2009/0043702	12/2008	Bennett	N/A	N/A
2009/0048971	12/2008	Hathaway et al.	N/A	N/A
2009/0106112	12/2008	Dalmia et al.	N/A	N/A
2009/0106160	12/2008	Skowronek	N/A	N/A
2009/0134217	12/2008	Flitcroft et al.	N/A	N/A
2009/0157555	12/2008	Biffle et al.	N/A	N/A
2009/0159673	12/2008	Mullen et al.	N/A	N/A
2009/0159700	12/2008	Mullen et al.	N/A	N/A
2009/0159707	12/2008	Mullen et al.	N/A	N/A
2009/0173782	12/2008	Muscato	N/A	N/A

2009/0200371	12/2008	Kean et al.	N/A	N/A
2009/0248583	12/2008	Chhabra	N/A	N/A
2009/0276347	12/2008	Kargman	N/A	N/A
2009/0281948	12/2008	Carlson	N/A	N/A
2009/0294527	12/2008	Brabson et al.	N/A	N/A
2009/0307139	12/2008	Mardikar et al.	N/A	N/A
2009/0308921	12/2008	Mullen	N/A	N/A
2009/0327131	12/2008	Beenau et al.	N/A	N/A
2010/0008535	12/2009	Abulafia et al.	N/A	N/A
2010/0088237	12/2009	Wankmueller	705/64	G06Q 20/382
2010/0094755	12/2009	Kloster	N/A	N/A
2010/0106644	12/2009	Annan et al.	N/A	N/A
2010/0120408	12/2009	Beenau et al.	N/A	N/A
2010/0133334	12/2009	Vadhri	N/A	N/A
2010/0138347	12/2009	Chen	N/A	N/A
2010/0145860	12/2009	Pelegero	N/A	N/A
2010/0161433	12/2009	White	N/A	N/A
2010/0185545	12/2009	Royyuru et al.	N/A	N/A
2010/0211505	12/2009	Saunders et al.	N/A	N/A
2010/0223186	12/2009	Hogan et al.	N/A	N/A
2010/0228668	12/2009	Hogan et al.	N/A	N/A
2010/0235284	12/2009	Moore	N/A	N/A
2010/0258620	12/2009	Torreyson et al.	N/A	N/A
2010/0291904	12/2009	Musfeldt et al.	N/A	N/A
2010/0299267	12/2009	Faith et al.	N/A	N/A
2010/0306076	12/2009	Taveau et al.	N/A	N/A
2010/0325041	12/2009	Berardi et al.	N/A	N/A
2011/0010292	12/2010	Giordano et al.	N/A	N/A
2011/0016047	12/2010	Wu et al.	N/A	N/A
2011/0016320	12/2010	Bergsten et al.	N/A	N/A
2011/0040640	12/2010	Erikson	N/A	N/A
2011/0047076	12/2010	Carlson et al.	N/A	N/A
2011/0083018	12/2010	Kesanupalli et al.	N/A	N/A
2011/0087596	12/2010	Dorsey	N/A	N/A
2011/0093397	12/2010	Carlson et al.	N/A	N/A
2011/0125597	12/2010	Oder, II et al.	N/A	N/A
2011/0153437	12/2010	Archer et al.	N/A	N/A
2011/0153498	12/2010	Makhotin et al.	N/A	N/A
2011/0154466	12/2010	Harper et al.	N/A	N/A
2011/0161232	12/2010	Brown	705/76	G06Q 20/3278
2011/0161233	12/2010	Tieken	N/A	N/A
2011/0178926	12/2010	Lindelsee et al.	N/A	N/A
2011/0191244	12/2010	Dai	N/A	N/A
2011/0238511	12/2010	Park et al.	N/A	N/A
2011/0238573	12/2010	Varadarajan	N/A	N/A
2011/0246317	12/2010	Coppinger	N/A	N/A
2011/0258111	12/2010	Raj et al.	N/A	N/A
2011/0272471	12/2010	Mullen	N/A	N/A
2011/0272478	12/2010	Mullen	N/A	N/A

2011/0276380	12/2010	Mullen et al.	N/A	N/A
2011/0276381	12/2010	Mullen et al.	N/A	N/A
2011/0276424	12/2010	Mullen	N/A	N/A
2011/0276425	12/2010	Mullen	N/A	N/A
2011/0295745	12/2010	White et al.	N/A	N/A
2011/0302081	12/2010	Saunders et al.	N/A	N/A
2011/0314539	12/2010	Horton	726/20	H04W 12/30
2012/0023567	12/2011	Hammad	N/A	N/A
2012/0028609	12/2011	Hruska	N/A	N/A
2012/0030047	12/2011	Fuentes et al.	N/A	N/A
2012/0035998	12/2011	Chien et al.	N/A	N/A
2012/0041881	12/2011	Basu et al.	N/A	N/A
2012/0047237	12/2011	Arvidsson et al.	N/A	N/A
2012/0066078	12/2011	Kingston et al.	N/A	N/A
2012/0072350	12/2011	Goldthwaite et al.	N/A	N/A
2012/0078735	12/2011	Bauer et al.	N/A	N/A
2012/0078798	12/2011	Downing et al.	N/A	N/A
2012/0078799	12/2011	Jackson et al.	N/A	N/A
2012/0095852	12/2011	Bauer et al.	N/A	N/A
2012/0095865	12/2011	Doherty et al.	N/A	N/A
2012/0116902	12/2011	Cardina et al.	N/A	N/A
2012/0123882	12/2011	Carlson et al.	N/A	N/A
2012/0123940	12/2011	Killian et al.	N/A	N/A
2012/0129514	12/2011	Beenau et al.	N/A	N/A
2012/0131354	12/2011	French	N/A	N/A
2012/0136732	12/2011	McMillen	705/16	G06Q 20/105
2012/0143754	12/2011	Patel	N/A	N/A
2012/0143767	12/2011	Abadir	N/A	N/A
2012/0143772	12/2011	Abadir	N/A	N/A
2012/0158580	12/2011	Eram et al.	N/A	N/A
2012/0158593	12/2011	Garfinkle et al.	N/A	N/A
2012/0173431	12/2011	Ritchie et al.	N/A	N/A
2012/0185386	12/2011	Salama et al.	N/A	N/A
2012/0197807	12/2011	Schlessner et al.	N/A	N/A
2012/0203664	12/2011	Torossian et al.	N/A	N/A
2012/0203666	12/2011	Torossian et al.	N/A	N/A
2012/0215688	12/2011	Musser et al.	N/A	N/A
2012/0215696	12/2011	Salonen	N/A	N/A
2012/0221421	12/2011	Hammad	N/A	N/A
2012/0221468	12/2011	Kumnick	705/44	G06Q 20/306
2012/0226582	12/2011	Hammad	N/A	N/A
2012/0231844	12/2011	Coppinger	N/A	N/A
2012/0233004	12/2011	Bercaw	N/A	N/A
2012/0246070	12/2011	Vadhri	N/A	N/A
2012/0246071	12/2011	Jain et al.	N/A	N/A
2012/0246079	12/2011	Wilson	705/67	G06Q 20/3226
2012/0265631	12/2011	Cronic et al.	N/A	N/A
2012/0271770	12/2011	Harris et al.	N/A	N/A
2012/0278241	12/2011	Brown	705/67	H04W 12/068

2012/0297446	12/2011	Webb et al.	N/A	N/A
2012/0300932	12/2011	Cambridge et al.	N/A	N/A
2012/0303503	12/2011	Cambridge et al.	N/A	N/A
2012/0303961	12/2011	Kean et al.	N/A	N/A
2012/0304273	12/2011	Bailey et al.	N/A	N/A
2012/0310725	12/2011	Chien et al.	N/A	N/A
2012/0310831	12/2011	Harris et al.	N/A	N/A
2012/0316992	12/2011	Oborne	N/A	N/A
2012/0317035	12/2011	Royyuru et al.	N/A	N/A
2012/0317036	12/2011	Bower et al.	N/A	N/A
2013/0017784	12/2012	Fisher	N/A	N/A
2013/0018757	12/2012	Anderson et al.	N/A	N/A
2013/0019098	12/2012	Gupta et al.	N/A	N/A
2013/0031006	12/2012	McCullagh et al.	N/A	N/A
2013/0048714	12/2012	Sharma	235/379	G06Q 20/346
2013/0054337	12/2012	Brendell et al.	N/A	N/A
2013/0054466	12/2012	Muscato	N/A	N/A
2013/0054474	12/2012	Yeager	N/A	N/A
2013/0081122	12/2012	Svigals et al.	N/A	N/A
2013/0091028	12/2012	Oder, II et al.	N/A	N/A
2013/0110658	12/2012	Lyman et al.	N/A	N/A
2013/0111599	12/2012	Gargiulo	N/A	N/A
2013/0117185	12/2012	Collison et al.	N/A	N/A
2013/0124290	12/2012	Fisher	N/A	N/A
2013/0124291	12/2012	Fisher	N/A	N/A
2013/0124364	12/2012	Mittal	N/A	N/A
2013/0138525	12/2012	Bercaw	N/A	N/A
2013/0144888	12/2012	Faith et al.	N/A	N/A
2013/0145148	12/2012	Shablygin et al.	N/A	N/A
2013/0145172	12/2012	Shablygin et al.	N/A	N/A
2013/0159178	12/2012	Colon et al.	N/A	N/A
2013/0159184	12/2012	Thaw	N/A	N/A
2013/0166402	12/2012	Parento et al.	N/A	N/A
2013/0166456	12/2012	Zhang et al.	N/A	N/A
2013/0173736	12/2012	Krzeminski et al.	N/A	N/A
2013/0185202	12/2012	Goldthwaite et al.	N/A	N/A
2013/0191227	12/2012	Pasa et al.	N/A	N/A
2013/0191286	12/2012	Cronic et al.	N/A	N/A
2013/0191289	12/2012	Cronic et al.	N/A	N/A
2013/0198071	12/2012	Jurss	N/A	N/A
2013/0198080	12/2012	Anderson et al.	N/A	N/A
2013/0200146	12/2012	Moghadam	N/A	N/A
2013/0204775	12/2012	Midkiff	705/39	G06Q 20/10
2013/0204787	12/2012	Dubois	N/A	N/A
2013/0204793	12/2012	Kerridge et al.	N/A	N/A
2013/0212007	12/2012	Mattsson et al.	N/A	N/A
2013/0212017	12/2012	Bangia	N/A	N/A
2013/0212019	12/2012	Mattsson et al.	N/A	N/A
2013/0212024	12/2012	Mattsson et al.	N/A	N/A
2013/0212026	12/2012	Powell et al.	N/A	N/A

2013/0212666	12/2012	Mattsson et al.	N/A	N/A
2013/0218698	12/2012	Moon et al.	N/A	N/A
2013/0218769	12/2012	Pourfallah et al.	N/A	N/A
2013/0226799	12/2012	Raj	N/A	N/A
2013/0226802	12/2012	Hammad et al.	N/A	N/A
2013/0226813	12/2012	Voltz	N/A	N/A
2013/0246199	12/2012	Carlson	N/A	N/A
2013/0246202	12/2012	Tobin	N/A	N/A
2013/0246203	12/2012	Laracey	N/A	N/A
2013/0246258	12/2012	Dessert	N/A	N/A
2013/0246259	12/2012	Dessert	N/A	N/A
2013/0246261	12/2012	Purves et al.	N/A	N/A
2013/0246267	12/2012	Tobin	N/A	N/A
2013/0254028	12/2012	Salci	N/A	N/A
2013/0254052	12/2012	Royyuru et al.	N/A	N/A
2013/0254102	12/2012	Royyuru	N/A	N/A
2013/0254117	12/2012	von Mueller et al.	N/A	N/A
2013/0262296	12/2012	Thomas et al.	N/A	N/A
2013/0262302	12/2012	Lettow et al.	N/A	N/A
2013/0262315	12/2012	Hruska	N/A	N/A
2013/0262316	12/2012	Hruska	N/A	N/A
2013/0262317	12/2012	Collinge et al.	N/A	N/A
2013/0275300	12/2012	Killian et al.	N/A	N/A
2013/0275307	12/2012	Khan	N/A	N/A
2013/0275308	12/2012	Paraskeva et al.	N/A	N/A
2013/0282502	12/2012	Jooste	N/A	N/A
2013/0282575	12/2012	Mullen et al.	N/A	N/A
2013/0282588	12/2012	Hruska	N/A	N/A
2013/0297501	12/2012	Monk et al.	N/A	N/A
2013/0297504	12/2012	Nwokolo et al.	N/A	N/A
2013/0297508	12/2012	Belamant	N/A	N/A
2013/0304649	12/2012	Cronic et al.	N/A	N/A
2013/0308778	12/2012	Fosmark et al.	N/A	N/A
2013/0311382	12/2012	Fosmark et al.	N/A	N/A
2013/0317982	12/2012	Mengerink et al.	N/A	N/A
2013/0332344	12/2012	Weber	N/A	N/A
2013/0339253	12/2012	Sincai	N/A	N/A
2013/0346305	12/2012	Mendes	N/A	N/A
2013/0346314	12/2012	Mogollon et al.	N/A	N/A
2014/0007213	12/2013	Sanin et al.	N/A	N/A
2014/0013106	12/2013	Redpath	N/A	N/A
2014/0013114	12/2013	Redpath	N/A	N/A
2014/0013452	12/2013	Aissi et al.	N/A	N/A
2014/0019352	12/2013	Shrivastava	N/A	N/A
2014/0025581	12/2013	Calman	N/A	N/A
2014/0025585	12/2013	Calman	N/A	N/A
2014/0025958	12/2013	Calman	N/A	N/A
2014/0032417	12/2013	Mattsson	N/A	N/A
2014/0032418	12/2013	Weber	N/A	N/A
2014/0040137	12/2013	Carlson et al.	N/A	N/A

2014/0040139	12/2013	Brudnicki et al.	N/A	N/A
2014/0040144	12/2013	Plomske et al.	N/A	N/A
2014/0040145	12/2013	Ozvat et al.	N/A	N/A
2014/0040148	12/2013	Ozvat et al.	N/A	N/A
2014/0040628	12/2013	Fort	713/182	H04L 63/18
2014/0041018	12/2013	Bomar et al.	N/A	N/A
2014/0046853	12/2013	Spies et al.	N/A	N/A
2014/0047551	12/2013	Nagasundaram et al.	N/A	N/A
2014/0052532	12/2013	Tsai et al.	N/A	N/A
2014/0052620	12/2013	Rogers et al.	N/A	N/A
2014/0052637	12/2013	Jooste et al.	N/A	N/A
2014/0068706	12/2013	Aissi	N/A	N/A
2014/0074637	12/2013	Hammad	N/A	N/A
2014/0108172	12/2013	Weber et al.	N/A	N/A
2014/0114857	12/2013	Griggs et al.	N/A	N/A
2014/0143137	12/2013	Carlson	N/A	N/A
2014/0164243	12/2013	Aabye et al.	N/A	N/A
2014/0164254	12/2013	Dimmick	705/44	G06Q 20/4012
2014/0188586	12/2013	Carpenter et al.	N/A	N/A
2014/0249945	12/2013	Gauthier et al.	N/A	N/A
2014/0294701	12/2013	Dai et al.	N/A	N/A
2014/0297534	12/2013	Patterson	N/A	N/A
2014/0310183	12/2013	Weber	N/A	N/A
2014/0324690	12/2013	Allen et al.	N/A	N/A
2014/0330721	12/2013	Wang	N/A	N/A
2014/0330722	12/2013	Laxminarayanan et al.	N/A	N/A
2014/0331265	12/2013	Mozell et al.	N/A	N/A
2014/0337236	12/2013	Wong et al.	N/A	N/A
2014/0344153	12/2013	Raj et al.	N/A	N/A
2014/0372308	12/2013	Sheets	N/A	N/A
2015/0019443	12/2014	Sheets et al.	N/A	N/A
2015/0032625	12/2014	Dill	705/44	G06Q 20/4016
2015/0032626	12/2014	Dill et al.	N/A	N/A
2015/0032627	12/2014	Dill et al.	N/A	N/A
2015/0046338	12/2014	Laxminarayanan et al.	N/A	N/A
2015/0046339	12/2014	Wong et al.	N/A	N/A
2015/0052064	12/2014	Karpenko et al.	N/A	N/A
2015/0066768	12/2014	Williamson	705/44	G06Q 20/405
2015/0081544	12/2014	Schulz et al.	N/A	N/A
2015/0088756	12/2014	Makhotin et al.	N/A	N/A
2015/0106239	12/2014	Gaddam et al.	N/A	N/A
2015/0112870	12/2014	Nagasundaram et al.	N/A	N/A
2015/0112871	12/2014	Kumnick	N/A	N/A
2015/0120472	12/2014	Aabye et al.	N/A	N/A
2015/0127529	12/2014	Makhotin et al.	N/A	N/A

2015/0127547	12/2014	Powell	705/67	G06Q 20/4016
2015/0140960	12/2014	Powell et al.	N/A	N/A
2015/0142673	12/2014	Nelsen et al.	N/A	N/A
2015/0161597	12/2014	Subramanian et al.	N/A	N/A
2015/0178724	12/2014	Ngo et al.	N/A	N/A
2015/0180836	12/2014	Wong et al.	N/A	N/A
2015/0186864	12/2014	Jones et al.	N/A	N/A
2015/0193222	12/2014	Pirzadeh et al.	N/A	N/A
2015/0195133	12/2014	Sheets et al.	N/A	N/A
2015/0199679	12/2014	Palanisamy et al.	N/A	N/A
2015/0199689	12/2014	Kumnick et al.	N/A	N/A
2015/0220917	12/2014	Aabye et al.	N/A	N/A
2015/0269566	12/2014	Gaddam et al.	N/A	N/A
2015/0278799	12/2014	Palanisamy	N/A	N/A
2015/0287037	12/2014	Salmon et al.	N/A	N/A
2015/0295921	12/2014	Cao	N/A	N/A
2015/0312038	12/2014	Palanisamy	N/A	N/A
2015/0319158	12/2014	Kumnick	N/A	N/A
2015/0324736	12/2014	Sheets et al.	N/A	N/A
2015/0332262	12/2014	Lingappa	N/A	N/A
2015/0356560	12/2014	Shastri et al.	N/A	N/A
2015/0363781	12/2014	Badenhorst	N/A	N/A
2016/0028550	12/2015	Gaddam et al.	N/A	N/A
2016/0036790	12/2015	Shastri et al.	N/A	N/A
2016/0042263	12/2015	Gaddam et al.	N/A	N/A
2016/0048828	12/2015	Lee	705/39	G06Q 20/401
2016/0063480	12/2015	Ballesteros	705/17	G06Q 20/204
2016/0065370	12/2015	Le Saint et al.	N/A	N/A
2016/0092696	12/2015	Guglani	N/A	N/A
2016/0092872	12/2015	Prakash et al.	N/A	N/A
2016/0092874	12/2015	O'Regan et al.	N/A	N/A
2016/0103675	12/2015	Aabye et al.	N/A	N/A
2016/0119296	12/2015	Laxminarayanan et al.	N/A	N/A
2016/0125417	12/2015	Huang	705/71	G06Q 20/34
2016/0132878	12/2015	O'Regan et al.	N/A	N/A
2016/0140545	12/2015	Flurscheim et al.	N/A	N/A
2016/0148197	12/2015	Dimmick	N/A	N/A
2016/0148212	12/2015	Dimmick	N/A	N/A
2016/0171479	12/2015	Prakash et al.	N/A	N/A
2016/0173483	12/2015	Wong et al.	N/A	N/A
2016/0197725	12/2015	Hammad	N/A	N/A
2016/0210628	12/2015	McGuire	N/A	N/A
2016/0217461	12/2015	Gaddam et al.	N/A	N/A
2016/0218875	12/2015	Le Saint et al.	N/A	N/A
2016/0224976	12/2015	Basu et al.	N/A	N/A
2016/0224977	12/2015	Sabba et al.	N/A	N/A
2016/0232513	12/2015	Purves	N/A	G06F 16/24573

2016/0232527	12/2015	Patterson	N/A	N/A
2016/0239842	12/2015	Cash et al.	N/A	N/A
2016/0253651	12/2015	Park	705/39	G06Q 20/34
2016/0269391	12/2015	Gaddam et al.	N/A	N/A
2016/0301683	12/2015	Laxminarayanan	N/A	H04L 67/02
2016/0308995	12/2015	Youdale et al.	N/A	N/A
2016/0335639	12/2015	Merz	N/A	G06Q 20/4016
2016/0379208	12/2015	Deliwala et al.	N/A	N/A
2017/0046696	12/2016	Powell et al.	N/A	N/A
2017/0061422	12/2016	Castinado et al.	N/A	N/A
2017/0076288	12/2016	Awasthi	N/A	G06Q 20/3821
2017/0091765	12/2016	Lloyd	N/A	G06Q 20/321
2017/0103387	12/2016	Weber	N/A	N/A
2017/0109745	12/2016	Al-Bedaiwi et al.	N/A	N/A
2017/0148013	12/2016	Rajurkar et al.	N/A	N/A
2017/0161733	12/2016	Koletsy	N/A	G06Q 20/405
2017/0163617	12/2016	Laxminarayanan et al.	N/A	N/A
2017/0163629	12/2016	Law et al.	N/A	N/A
2017/0186001	12/2016	Reed et al.	N/A	N/A
2017/0200156	12/2016	Karpenko et al.	N/A	N/A
2017/0200165	12/2016	Laxminarayanan et al.	N/A	N/A
2017/0201520	12/2016	Chandoor et al.	N/A	N/A
2017/0220818	12/2016	Nagasundaram et al.	N/A	N/A
2017/0221054	12/2016	Flursheim et al.	N/A	N/A
2017/0221056	12/2016	Karpenko et al.	N/A	N/A
2017/0228723	12/2016	Taylor et al.	N/A	N/A
2017/0228728	12/2016	Sullivan	N/A	N/A
2017/0236113	12/2016	Chitalia et al.	N/A	N/A
2017/0293914	12/2016	Girish et al.	N/A	N/A
2017/0295155	12/2016	Wong	N/A	N/A
2017/0337542	12/2016	Kim	N/A	G06Q 20/386
2017/0337549	12/2016	Wong	N/A	N/A
2017/0345000	12/2016	Kohli	N/A	G06Q 30/0233
2017/0364903	12/2016	Lopez	N/A	N/A
2017/0364914	12/2016	Howard	N/A	N/A
2017/0373852	12/2016	Cassin	N/A	N/A
2018/0005227	12/2017	Sandelov et al.	N/A	N/A
2018/0006821	12/2017	Kinagi	N/A	N/A
2018/0063152	12/2017	Erich	N/A	H04L 63/0861
2018/0075081	12/2017	Chipman	N/A	N/A
2018/0089434	12/2017	Sibert	N/A	H04L 63/0853
2018/0165680	12/2017	Sharma et al.	N/A	N/A
2018/0181934	12/2017	Baig	N/A	G06Q 20/381

2018/0247303	12/2017	Raj et al.	N/A	N/A
2018/0262334	12/2017	Hammad	N/A	N/A
2018/0268399	12/2017	Spector et al.	N/A	N/A
2018/0268405	12/2017	Lopez	N/A	N/A
2018/0276647	12/2017	Geupel	N/A	G06Q 20/4012
2018/0285875	12/2017	Law et al.	N/A	N/A
2018/0324184	12/2017	Kaja et al.	N/A	N/A
2018/0324584	12/2017	Lopez	N/A	N/A
2019/0020478	12/2018	Girish	N/A	H04L 9/3271
2019/0034934	12/2018	Trelin	N/A	G06F 21/32
2019/0066069	12/2018	Faith et al.	N/A	N/A
2019/0080075	12/2018	Ekberg	N/A	H04L 63/10
2019/0102773	12/2018	Dawley	N/A	G06Q 20/351
2019/0147439	12/2018	Wang et al.	N/A	N/A
2019/0356489	12/2018	Palanisamy	N/A	N/A
2019/0361901	12/2018	Purves	N/A	G06Q 20/36
2019/0384896	12/2018	Jones	N/A	N/A
2019/0392431	12/2018	Chitalia et al.	N/A	N/A
2020/0013059	12/2019	Mariappan	N/A	G06Q 20/4016
2020/0052897	12/2019	Girish	N/A	H04L 9/3271
2020/0267153	12/2019	Kang et al.	N/A	N/A
2020/0314644	12/2019	Dean et al.	N/A	N/A
2021/0103932	12/2020	Turgeon	N/A	G06Q 20/4093
2021/0117988	12/2020	Kresge	N/A	G06Q 40/02
2021/0182835	12/2020	Kurylko	N/A	G06Q 20/3552
2021/0182852	12/2020	Sukhija	N/A	G06Q 20/405
2023/0153792	12/2022	Kurani	705/76	G06Q 20/354

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1028401	12/1999	EP	N/A
2156397	12/2009	EP	N/A
0014648	12/1999	WO	N/A
0135304	12/2000	WO	N/A
0135304	12/2001	WO	N/A
2004042536	12/2003	WO	N/A
2004051585	12/2003	WO	N/A
2005001751	12/2004	WO	N/A
2006113834	12/2005	WO	N/A
2009032523	12/2008	WO	N/A
2010078522	12/2009	WO	N/A
2012068078	12/2011	WO	N/A
2012098556	12/2011	WO	N/A
2012142370	12/2011	WO	N/A
2012167941	12/2011	WO	N/A

2013048538	12/2012	WO	N/A
2013056104	12/2012	WO	N/A
2013119914	12/2012	WO	N/A
2013179271	12/2012	WO	N/A
2017201301	12/2016	WO	N/A
2018125444	12/2017	WO	N/A

OTHER PUBLICATIONS

U.S. Appl. No. 17/282,375 , “Non-Final Office Action”, filed Sep. 22, 2023, 21 pages. cited by applicant

U.S. Appl. No. 17/282,375 , “Notice of Allowance”, filed Feb. 23, 2024, 7 pages. cited by applicant

EP19870317.5 , “Extended European Search Report”, Oct. 15, 2021, 7 pages. cited by applicant

EP19870317.5 , “Intention to Grant”, Apr. 29, 2024, 8 pages. cited by applicant

EP19870317.5 , “Office Action”, Mar. 2, 2023, 5 pages. cited by applicant

PCT/US2019/055233 , “International Preliminary Report on Patentability”, Apr. 22, 2021, 21 pages. cited by applicant

PCT/US2019/055233 , “International Search Report and Written Opinion”, Apr. 10, 2020, 27 pages. cited by applicant

PCT/US2019/055233 , “Invitation to Pay Additional Fees and, Where Applicable, Protest Fee”, Jan. 10, 2020, 7 pages. cited by applicant

SG11202103377W , “Written Opinion”, Feb. 13, 2023, 9 pages. cited by applicant

SG11202103377W , “Further Written Opinion”, Nov. 11, 2024, 8 pages. cited by applicant

EP24203059.1 , “Extended European Search Report”, Oct. 16, 2024, 8 pages. cited by applicant

CN201980066097.7 , “Office Action”, Jul. 26, 2024, 16 pages. cited by applicant

CN201980066097.7 , “Office Action”, Feb. 21, 2025, 16 pages. cited by applicant

CN201980066097.7 , “Office Action”, Apr. 26, 2025, 14 pages. cited by applicant

Primary Examiner: Zhao; Don G

Attorney, Agent or Firm: Kilpatrick Townsend & Stockton LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is continuation application of U.S. patent application Ser. No. 17/282,375, which is a National Stage of International Application No. PCT/US2019/055233, filed Oct. 8, 2019, which claims priority to U.S. Patent Application No. 62/742,818, filed on Oct. 8, 2018, U.S. Patent Application No. 62/813,686, filed Mar. 4, 2019, and U.S. Patent Application No. 62/816,752, filed Mar. 11, 2019, the disclosures of which are herein incorporated by reference in their entirety for all purposes.

BACKGROUND

(1) A user can utilize a user device such as a mobile phone to perform transactions. A user device is used to perform a token provisioning process that enables a token to be stored at the user device. The user may cause the user device to interact with an access device, and may pass the token to the access device to conduct a transaction. During the transaction, a real credential associated with the user may replace the token during an authorization process. Separately, to perform a transaction using the user device, the user needs to authenticate himself or herself. The user may authenticate himself or herself with a personal identification number or other authentication data. Consequently, performing a transaction with a user device can involve a number of steps with is cumbersome.

(2) In addition, physical user devices are often needed to conduct transactions at access devices. The need to have a physical user device to access a resource at an access device is also cumbersome. For example, a user may not be in possession of a physical user device when the user wants to conduct a transaction, yet may wish to conduct a transaction nonetheless.

(3) Still further, existing physical access devices may be legacy access devices, that may not be capable of conducting transactions using tokens or credentials that originate from a source other than a user device. As such, legacy access devices may be incapable of running certain types of transactions that would otherwise be desirable to conduct.

(4) Embodiments of this disclosure address these and other problems, individually and collectively.

SUMMARY

(5) One embodiment of the invention is directed to a method. The method may comprise receiving, by an auxiliary device in communication with an access device, authentication data from a user. The method may further comprise initiating, by the auxiliary device, verifying the authentication data. The method may further comprise requesting, by the auxiliary device, a token from a secure server computer. The method may further comprise receiving, by the auxiliary device, the token and a transaction authentication verification value. The method may further comprise providing, by the auxiliary device, the token and the transaction authentication verification value to the access device, wherein the access device generates an authorization request message.

(6) Another embodiment of the invention is directed to an auxiliary device. The auxiliary device may be in communication with An access device. The auxiliary may comprise a processor and a computer readable medium coupled to the processor, the computer readable medium comprising code executable by the processor to cause the auxiliary device to perform operations. The operations may comprise receiving authentication data associated with a user. The operations may further comprise verifying the authentication data. The operations may further comprise requesting a token from a secure server computer. The operations may further comprise receiving the token from the secure server computer. The operations may further comprise obtaining a verification value for the token. The operations may further comprise providing the token and the verification value to the access device, wherein the access device generates an authorization request message.

(7) Another embodiment of the invention is directed to another method. The method may comprise receiving, by a processing network computer from an access device, an authorization request message comprising data in a first transaction data format. The method may further comprise converting, by the processing network computer, the data in the first transaction data format to a second transaction data format. The method may further comprise transmitting, by the processing network computer, an authorization request message including data in the second transaction data format to an authorizing entity computer for authorization.

(8) Another embodiment of the invention is directed to a processing network computer comprising a processor and a computer readable medium coupled to the processor, the computer readable medium comprising code executable by the processor to cause the processing network computer to perform operations. The operations may comprise receiving an authorization request message comprising data in a first transaction data format. The operations may comprise converting the data in the first transaction data format to a second transaction data format. The operations may comprise transmitting an authorization request message including data in the second transaction data format to an authorizing entity computer for authorization.

(9) Another embodiment of the invention is directed to another method. The method may comprise generating, by a first computer, a request for a plurality of cryptograms for transactions involving tokens. The method may comprise transmitting the request to a second computer. The method may comprise receiving, by the first computer from the second computer, the plurality of cryptograms. The method may comprise storing, by the first computer, the plurality of cryptograms for subsequent use. In some embodiments, the first computer is a token provider computer and the second computer is a secure server computer.

(10) Another embodiment of the invention is directed to a token provider computer comprising a processor and a computer readable medium coupled to the processor, the computer readable medium comprising code executable by the processor to cause the token provider computer to perform operations. The operations may comprise receiving, from a token requestor computer, a request for a token. The operations may comprise generating the token. The operations may comprise receiving, from the token requestor computer, a cryptogram request for a number of cryptograms associated with the token. The operations may comprise obtaining profile data for a token requestor corresponding to the token requestor computer. The operations may comprise determining that the token requestor associated with the token requestor computer is authorized to pre-fetch multiple cryptograms in a single request. The operations may comprise transmitting a response with a plurality of cryptograms to the token requestor computer.

(11) Another embodiment of the invention is directed to another method. The method may comprise receiving, by a device in communication with an access device, a token and a single use value associated with a credential of a user. The method may comprise receiving, by the device from the access device, access device data comprising at least an unpredictable value. The method may comprise generating, by the device, an authorization request cryptogram. The method may comprise transmitting, by the device, the token and the authorization request cryptogram to the access device. In some embodiments, the access device generates an authorization request message and transmits the authorization request message to an authorizing computer for authorization. In some embodiments, the device may be an auxiliary device.

(12) Another embodiment of the invention is directed to a device comprising a processor and a computer readable medium coupled to the processor, the computer readable medium comprising code executable by the processor to cause the device to perform operations. In some embodiments, the device is in communication with an access device. The operations may comprise receiving a single use value and a token associated with a credential of a user. The operations may comprise receiving access device data comprising at least an unpredictable value. The operations may comprise generating an authorization request cryptogram. The operations may comprise transmitting the token and the authorization request cryptogram to an access device in communication with the device. In some embodiments, the access device generates an authorization request message and transmits the authorization request message to an authorizing computer for authorization. In some embodiments, the device is an auxiliary device or a secure element device.

(13) Another embodiment of the invention is directed to another method. The method may comprise receiving, by a secure element device in communication with an auxiliary device and an access device, a token and a cryptographic key associated with a credential of a user. In some embodiments, the token and cryptographic key may be received from the auxiliary device. The method may further comprise receiving, by the secure element device from the access device, access device data comprising at least an unpredictable value. The method may further comprise generating, by the secure element device, an interaction cryptogram. The method may further comprise transmitting, by the secure element device, the token and the interaction cryptogram to the access device. In some embodiments, the access device generates an authorization request message and transmits the authorization request message to an authorizing computer for authorization.

(14) Another embodiment of the invention is directed to a secure element device comprising a secure memory space, a processor, and a computer readable medium coupled to the processor, the computer readable medium comprising code executable by the processor to cause the secure element device to perform operations. In some embodiments, the secure element device may be in communication with an access device and an auxiliary device. The operations may comprise receiving, from the auxiliary device, a token and cryptographic key associated with a credential of a user. The operations may comprise storing the token and the cryptographic key in the secure

memory space. The operations may comprise receiving access device data comprising at least an unpredictable value. The operations may comprise generating an interaction cryptogram. The operations may comprise transmitting the token and the interaction cryptogram to an access device in communication with the secure element device. In some embodiments, the access device generates an authorization request message and transmits the authorization request message to an authorizing computer for authorization.

(15) Further details regarding embodiments of the invention can be found in the Detailed Description and the Figures.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 shows an exemplary system and a process flow diagram, in accordance with at least one embodiment.

(2) FIG. 2 shows an exemplary system and a process flow diagram illustrating a token and/or cryptogram provisioning process, in accordance with at least one embodiment.

(3) FIGS. 3-6 shows exemplary methods for authenticating a user, in accordance with at least one embodiment.

(4) FIG. 7 shows a process flow diagram for an exemplary process for generating multiple cryptograms, in accordance with at least one embodiment.

(5) FIG. 8 shows an exemplary process flow diagram for performing a biometric enrollment process, in accordance with at least one embodiment.

(6) FIG. 9 shows an exemplary system and process flow diagram for performing a biometric enrollment process during a transaction, in accordance with at least one embodiment.

(7) FIG. 10 shows an exemplary process flow diagram for performing a transaction utilizing biometric data associated with a user, in accordance with at least one embodiment.

(8) FIG. 11 shows an exemplary system and process flow diagram illustrating a limited-use key provisioning process, according to some embodiments.

(9) FIG. 12 shows an exemplary system and process flow diagram illustrating use case in which an auxiliary device is used to emulate a user device, according to some embodiments.

(10) FIG. 13 shows an exemplary process flow diagram illustrating a use case in which secure element device is used to perform a transaction, according to some embodiments.

(11) FIG. 14 shows an exemplary process flow diagram for utilizing a single use value for generating a cryptogram, according to at least one embodiment.

(12) FIG. 15 shows an exemplary process flow diagram for utilizing a single use value for generating a cryptogram, according to at least one embodiment.

(13) FIG. 16 shows an exemplary auxiliary device, in accordance with at least one embodiment.

(14) FIG. 17 shows an exemplary secure server computer, in accordance with at least one embodiment.

(15) FIG. 18 shows an exemplary secure element, in accordance with at least one embodiment.

DETAILED DESCRIPTION

(16) Prior to discussing embodiments of the invention, some terms can be described in further detail.

(17) A “user” may include an individual or a computing device. In some embodiments, a user may be associated with one or more personal accounts and/or mobile devices. In some embodiments, the user may be a cardholder, account holder, or consumer.

(18) A “computing device” may be any suitable electronic device that can process and communicate information to other electronic devices. The computing device may include a processor and a computer readable medium coupled to the processor, the computer readable

medium comprising code, executable by the processor. The computing device may also each include an external communication interface for communicating with each other and other entities. Examples of computing devices may include user devices, access devices, mobile devices, auxiliary devices, server computers, resource provider computers, processing network computers, authorizing entity computers, transport computers, token provider computers, and the like.

(19) A “user device” may be any suitable device operated by a user. User devices may be in any suitable form. Some examples of user devices include cellular phones, smartphones, mobile phones, payment cards, smartcards, PDAs, personal computers (PCs), tablet computers, and the like. In some embodiments, where a user device is a mobile device, the mobile device may include a display, a memory, a processor, a computer-readable medium, and any other suitable component.

(20) A “mobile device” may comprise any suitable electronic device that may be transported and operated by a user, which may also provide remote communication capabilities to a network. A mobile device such as a mobile communication device may communicate using a mobile phone (wireless) network, wireless data network (e.g. 3G, 4G or similar networks), Wi-Fi, Bluetooth, Bluetooth Low Energy (BLE), Wi-Max, or any other communication medium that may provide access to a network such as the Internet or a private network. Examples of mobile devices include mobile phones (e.g. cellular phones), PDAs, tablet computers, net books, laptop computers, wearable devices (e.g., watches), vehicles such as automobiles and motorcycles, personal music players, hand-held specialized readers, etc. A mobile device may comprise any suitable hardware and software for performing such functions, and may also include multiple devices or components (e.g. when a device has remote access to a network by tethering to another device—i.e. using the other device as a modem—both devices taken together may be considered a single mobile device).

(21) An “access device” may be any suitable device for providing access to an external computer system. An access device may be in any suitable form. Some examples of access devices include point of sale (POS) devices, cellular phones, PDAs, personal computers (PCs), tablet PCs, hand-held specialized readers, set-top boxes, electronic cash registers (ECRs), automated teller machines (ATMs), virtual cash registers (VCRs), kiosks, security systems, access systems, Websites, and the like. An access device may use any suitable contact or contactless mode of operation to send or receive data from, or associated with, a mobile device. In some embodiments, where an access device may comprise a POS terminal, any suitable POS terminal may be used and may include a reader, a processor, and a computer-readable medium. A reader may include any suitable contact or contactless mode of operation. For example, exemplary card readers can include radio frequency (RF) antennas, optical scanners, bar code readers, or magnetic stripe readers to interact with a mobile device.

(22) An “auxiliary device” may include any suitable computing device that provides supporting functionality to a process. By way of example, an auxiliary device may provide supporting functionality to a payment process.

(23) A “secure element device” may include any suitable computing device that includes a secure element such as secure memory. “Secure memory” refers to any suitable memory of the computing device that is protected such that processes and/or entities not allocated to the secure memory may not access the secure memory. An example of secure memory may include an enclave (e.g., memory that is encrypted and managed by a chipset of the computing device). In some embodiments, information stored in secure memory may be encrypted.

(24) An “application” may be a computer program that is used for a specific purpose.

(25) “Authentication data” may include any data suitable for authenticating a user or device. Authentication data may be obtained from a user or a device that is operated by the user. Examples of authentication data obtained from a user may include PINs (personal identification numbers), biometric data (e.g., fingerprint, facial scan, retina scan, etc.), passwords, etc. Examples of authentication data that may be obtained from a device may include device serial numbers, hardware secure element identifiers, device fingerprints, phone numbers, IMEI numbers, etc.

(26) “Access data” may include any suitable data that can be used to access a resource or create data that can access a resource. In some embodiments, access data may be account information for a payment account. Account information may include a PAN (primary account number), payment token, expiration date, verification values (e.g., CVV, CVV2, dCVV, dCVV2), etc. In other embodiments, access data may be data that can be used to activate account data. For example, in some cases, account information may be stored on a mobile device, but may not be activated until specific information is received by the mobile device. In other embodiments, access data could include data that can be used to access a location. Such access data may be ticket information for an event, data to access a building, transit ticket information, etc. In yet other embodiments, access data may include data used to obtain access to sensitive data. Examples of access data may include codes or other data that are needed by a server computer to grant access to the sensitive data.

(27) An “access request” may include a request for access to a resource. The resource may be a physical resource (e.g., good), digital resources (e.g., electronic document, electronic data, etc.), or services. In some cases, an access request may be submitted by transmission of an access request message that includes access request data. Typically a device associated with a requestor may transmit the access request message to a device associated with a resource provider.

(28) “Access request data” may include any information surrounding or related to an access request. Access request data may include access data. Access request data may include information useful for processing and/or verifying the access request. For example, access request data may include details associated with entities (e.g., resource provider computer, processor server computer, authorization computer, etc.) involved in processing the access request, such as entity identifiers (e.g., name, etc.), location information associated with the entities, and information indicating the type of entity (e.g., category code). Exemplary access request data may include information indicating an access request amount, an access request location, resources received (e.g., products, documents, etc.), information about the resources received (e.g., size, amount, type, etc.), resource providing entity data (e.g., resource provider data, document owner data, etc.), user data, date and time of an access request, a method utilized for conducting the access request (e.g., contact, contactless, etc.), and other relevant information. Access request data may also be known as access request information, transaction data, transaction information, or the like.

(29) A “digital wallet” can include an electronic device that allows an individual to conduct electronic commerce transactions. A digital wallet may store user profile information, credentials, bank account information, one or more digital wallet identifiers and/or the like and can be used in a variety of transactions, such as, but not limited to, e-commerce transactions, social network transactions, money transfer/personal payment transactions, mobile commerce transactions, proximity payment transactions, gaming transactions, etc. A digital wallet may be designed to streamline the purchase and payment process. A digital wallet may allow the user to load one or more payment cards onto the digital wallet so as to make a payment without having to enter an account number or present a physical card. A provider (e.g., an entity that hosts the digital wallet) may be referred to as a “digital wallet provider.”

(30) A “biometric” may be any human characteristic that is unique to an individual. For example, a biometric may be a person's fingerprint, voice sample, face, DNA, retina, etc.

(31) A “biometric reader” may include a device for capturing data from an individual's biometric sample. Examples of biometric readers may include fingerprint readers, front-facing cameras, microphones, and iris scanners.

(32) A “biometric sample” may include data obtained by a biometric reader. The data may be either an analog or digital representation of the user's biometric, generated prior to determining distinct features needed for matching. For example, a biometric sample of a user's face may be image data. In another example, a biometric sample of a user's voice may be audio data.

(33) A “biometric template” or “biometric sample template” may include a file containing distinct characteristics extracted from a biometric sample that may be used during a biometric

authentication process. For example, a biometric template may be a binary mathematical file representing the unique features of an individual's fingerprint, eye, hand or voice needed for performing accurate authentication of the individual.

(34) “Biometric data” includes data that can be used to uniquely identify an individual based upon one or more intrinsic physical or behavioral traits. For example, biometric data may include fingerprint data and retinal scan (e.g. eye scan) data. Further examples of biometric data include digital photographic data (e.g., facial recognition data), deoxyribonucleic acid (DNA) data, palm print data, hand geometry data, and iris recognition data.

(35) A “credential” may be any suitable information that serves as reliable evidence of worth, ownership, identity, or authority. A credential may be a string of numbers, letters, or any other suitable characters, as well as any object or document that can serve as confirmation. Examples of credentials include value credentials, identification cards, certified documents, access cards, passcodes and other login information, etc. Other examples of credentials include PANs (primary account numbers), PII (personal identifiable information) such as name, address, and phone number, and the like.

(36) “Payment credentials” may include any suitable information associated with an account (e.g. a payment account and/or payment device associated with the account). Such information may be directly related to the account or may be derived from information related to the account. Examples of account information may include a PAN (primary account number or “account number”), user name, expiration date, CVV (card verification value), dCVV (dynamic card verification value), CVV2 (card verification value 2), CVC3 card verification values, etc. CVV2 is generally understood to be a static verification value associated with a payment device. CVV2 values are generally visible to a user (e.g., a consumer), whereas CVV and dCVV values are typically embedded in memory or authorization request messages and are not readily known to the user (although they are known to the issuer and payment processors). Payment credentials may be any information that identifies or is associated with a payment account. Payment credentials may be provided in order to make a payment from a payment account. Payment credentials can also include a user name, an expiration date, a gift card number or code, and any other suitable information.

(37) An “authorizing entity” may be an entity that authorizes a request, typically using an authorizing computer to do so. An authorizing entity may be an issuer, a governmental agency, a document repository, an access administrator, etc. An “issuer” may typically include a business entity (e.g., a bank) that maintains an account for a user. An issuer may also issue payment credentials stored on a user device, such as a cellular telephone, smart card, tablet, or laptop to the user. A computing device operated by or on behalf of an authorizing entity may be referred to as an “authorizing entity computer.”

(38) A “resource provider” can be any suitable entity that provides resources (e.g., goods, services, access to secure data, access to locations, or the like). For example, a resource providing entity can be a merchant, a payment processor, a digital wallet provider, a venue operator, a building owner, a governmental entity, etc. A “merchant” may typically be an entity that engages in transactions and can sell goods or services, or provide access to goods or services. A computing device operated by or on behalf of a resource provider may be referred to as a “resource provider computer.”

(39) A “partner” can be an entity such as a resource provider such as a merchant (or computers operated by such entities). A “partner device” can be any suitable computing device operating by or on behalf of a partner.

(40) A “secure server computer” can be a server computer that securely stores data. As a non-limiting example, a secure server computer can be part of a partner's cloud-computing environment. A “cloud-computing environment” may include a network of one or more server computers hosted on a network (e.g., the Internet) that are utilized to store, manage, and process data.

(41) An “acquirer” may typically be a business entity (e.g., a commercial bank) that has a business relationship with a resource provider. Some entities can perform both issuer and acquirer functions. Some embodiments may encompass such single entity issuer-acquirers. A computing device operated by or on behalf of a resource provider may be referred to as a “transport computer.”

(42) A “token provider computer” can include an electronic device that services payment tokens and/or cryptograms. In some embodiments, a token provider computer can facilitate requesting, determining (e.g., generating) and/or issuing (provisioning, transmitting, etc.) tokens and/or cryptograms, as well as maintaining an established mapping of tokens to primary account numbers (PANs) (e.g., real account identifiers) and/or cryptograms in a repository. In some embodiments, the token provider computer may establish a token assurance level for a given token to indicate the confidence level of the token to PAN binding. The token provider computer may include or be in communication with a token data store wherein the generated tokens/cryptograms are stored. The token provider computer may support token processing of payment transactions submitted using tokens by de-tokenizing the token to obtain the actual PAN. In some embodiments, a token provider computer may include a tokenization computer alone, or in combination with other computers such as a transaction processing computer. Various entities of a tokenization ecosystem may assume the roles of the token provider computer. For example, payment networks and issuers or their agents may become the token provider computer by implementing the token services according to embodiments of the present invention.

(43) A “processing network computer” may include a server computer used for processing transactions from a network. In some embodiments, the processing network computer may be coupled to a database and may include any hardware, software, other logic, or combination of the preceding for servicing the requests from one or more client computers or user devices. The processing network computer may comprise one or more computational apparatuses and may use any of a variety of computing structures, arrangements, and compilations for servicing the requests from one or more client computers or user devices. In some embodiments, the processing network computer may operate multiple server computers. In such embodiments, each server computer may be configured to process a transaction for a given region or handles transactions of a specific type based on transaction data.

(44) The processing network computer may include data processing subsystems, networks, and operations used to support and deliver authorization services, exception file services, and clearing and settlement services. An exemplary processing network computer may include VisaNet™. Networks that include VisaNet™ are able to process credit card transactions, debit card transactions, and other types of commercial transactions. VisaNet™, in particular, includes an integrated payments system (Integrated Payments system) which processes authorization requests and a Base II system, which performs clearing and settlement services. The processing network computer may use any suitable wired or wireless network including the Internet.

(45) The processing network computer may process transaction-related messages (e.g., authorization request messages and authorization response messages) and determine the appropriate destination computer (e.g., issuer computer/authorizing entity computer) for the transaction-related messages. In some embodiments, the processing network computer may authorize transactions on behalf of an issuer. The processing network computer may also handle and/or facilitate the clearing and settlement of financial transactions.

(46) A “cryptographic key” (also referred to as a “key”) may include a piece of information that is used in a cryptographic algorithm to transform data into another representation. A cryptographic algorithm can be an encryption algorithm that transforms original data into an alternate representation, or a decryption algorithm that transforms encrypted information back to the original data. Examples of cryptographic algorithms may include triple data encryption standard (TDES), data encryption standard (DES), advanced encryption standard (AES), etc.

(47) A “limited use key” may include a cryptographic key for which use is limited. By way of

example, a limited use key may be a cryptographic key associated with a limited use threshold. A limited-use threshold may be exceeded or exhausted when an underlying condition is met. For example, a limited-use threshold may include a time-to-live that indicates an amount of time for which a piece of information (e.g., a limited use key) is valid, and once that amount of time has elapsed, the limited-use threshold is exceeded or exhausted, and the piece of information (e.g., the limited use key) may become invalid and may no longer be used. As another example, a limited-use threshold may include a number of times that a piece of information (e.g., the limited use key) can be used, and once the piece of information (e.g., the limited use key) has been used for that number of times, the limited-use threshold is exceeded or exhausted, and the piece of information (e.g., the limited use key) may become invalid and may no longer be used. A limited use key may be derived from account data of a user, and may be provided to a user device operated by a user. It may alternatively be generated by the user device.

(48) A “cryptogram” may include an encrypted representation of some information. A cryptogram may include a token authentication verification value (TAVV) associated with a token. A cryptogram can be used by a recipient to determine if the generator of the cryptogram is in possession of a proper key, for example, by encrypting the underlying information with a valid key, and comparing the result to the received cryptogram. A cryptogram may include encrypted characters. Cryptograms can be of any suitable length and may be formed using any suitable data transformation process. Exemplary data transformation processes include encryption, and encryption processes such as DES, triple DES, AES, and ECC may be used. Keys used with such encryption process can be of any appropriate length and may have any suitable characteristics. In some embodiments, a cryptogram may include encrypted token data associated with a token (e.g., a token domain, a token expiry date, etc.). In some embodiments, a cryptogram may be used to validate the token. For example, a cryptogram may be used to validate that the token is being used within a token domain and/or by a token expiry date associated with the token. In some embodiments, a cryptogram may be used in a payment process, and may be generated by a card or device with the unique derivation key (UDK) or a limited-use key (LUK) and additional information (e.g., a primary account number, token, and/or information from a chip and point-of-sale (POS)). Different types of payment cryptograms can be used in different settings.

(49) An “interaction cryptogram” may include a cryptogram that is generated in response to an interaction between entities. In some embodiments, an interaction cryptogram may be generated using a limited-use key, an encryption algorithm, and inputs. An “ARQC” (also referred to as an authorization request cryptogram) may include a cryptogram that is generated utilizing a single use value. A “single use value” may be a value that may be used only once. In some embodiments, a single use value may be a counter, an unpredictable number, etc.

(50) A “token domain” may indicate an area and/or circumstance in which a token can be used. Examples of the token domain may include, but are not limited to, payment channels (e.g., e-commerce, physical point of sale (POS), etc.), POS entry modes (e.g., contactless, magnetic stripe, etc.), and resource provider identifiers (e.g., merchant identifiers) to uniquely identify where the token can be used. A set of parameters (i.e. token domain restriction controls) may be established as part of token issuance by the token service provider that may allow for enforcing appropriate usage of the token in transactions. For example, the token domain restriction controls may restrict the use of the token with particular presentment modes, such as contactless or e-commerce presentment modes. In some embodiments, the token domain restriction controls may restrict the use of the token at a particular resource provider (e.g., a merchant) that can be uniquely identified. Some exemplary token domain restriction controls may require the verification of the presence of a token cryptogram that is unique to a given transaction. In some embodiments, a token domain can be associated with a token requestor.

(51) “Token expiry date” may include the expiration date/time of the token. The token expiration date may be a numeric value (e.g. a 4-digit numeric value). In some embodiments, the token expiry

date can be expressed as a time duration as measured from the time of issuance.

(52) A “digital signature” may include the result of applying an algorithm based on a public/private key pair, which allows a signing party to manifest, and/or a verifying party to verify, the authenticity and/or integrity of a document. The signing party acts by means of the private key and the verifying party acts by means of the public key. This process certifies the authenticity of the sender, the integrity of the signed document and the so-called principle of nonrepudiation, which does not allow disowning what has been signed. A certificate or other data that includes a digital signature by a signing party is said to be “signed” by the signing party. In some embodiments, the digital signature may be performed in accordance with RSA public key cryptography.

(53) A “master derivation key” (MDK) can be a key used to generate other keys. An MDK may be managed by an issuer of an account. MDKs may be managed on a per bank identification number (BIN) basis. The MDK may be used for card production, payment processing, etc. In some embodiments, an MDK may be managed by a processor computer that performs token management functions. Such an MDK may be used for token management and validation.

(54) A “cryptogram generation key,” (e.g., a unique derivation key (UDK)), can be a key for generating cryptograms. A cryptogram generation key may be generated from an MDK, directly or by way of another key. In some embodiments, a cryptogram generation key is a per-card key. The cryptogram generation key may be stored on a chip on a card or a device (e.g. mobile phone).

(55) A “real account identifier” may include an original account identifier associated with a payment account. For example, a real account identifier may be a primary account number (PAN) issued by an issuer for a card account (e.g., credit card, debit card, etc.). For instance, in some embodiments, a real account identifier may include a sixteen digit numerical value such as “4147 0900 0000 1234.” The first six digits of the real account identifier (e.g., “414709”), may represent a real issuer identifier (BIN) that may identify an issuer associated with the real account identifier.

(56) A “token” may be a substitute value for a credential. A token may be a string of numbers, letters, or any other suitable characters. Examples of tokens include payment tokens, access tokens (e.g., for accessing a location), personal identification tokens, etc.

(57) A “payment token” may include an identifier for a payment account that is a substitute for an account identifier, such as a primary account number (PAN). For example, a token may include a series of alphanumeric characters that may be used as a substitute for an original account identifier. For example, a token “4900 0000 0000 0001” may be used in place of a PAN “4147 0900 0000 1234.” In some embodiments, a token may be “format preserving” and may have a numeric format that conforms to the account identifiers used in existing transaction processing networks (e.g., ISO 8583 financial transaction message format). In some embodiments, a token may be used in place of a PAN to initiate, authorize, settle or resolve a payment transaction or represent the original credential in other systems where the original credential would typically be provided. In some embodiments, a token value may be generated such that the recovery of the original PAN or other account identifier from the token value may not be computationally derived. Further, in some embodiments, the token format may be configured to allow the entity receiving the token to identify it as a token and recognize the entity that issued the token.

(58) A “token request message” may be an electronic message for requesting a token. A token request message may include information usable for identifying a payment account (e.g., a real account identifier) or a service provider account (e.g., a digital wallet account), and/or information for generating a token (e.g., a payment token) and/or a unique cryptogram (e.g., a TAVV).

(59) A “token response message” may be a message that responds to a token request message. A token response message may include an indication that a token request was approved or denied. A token response message may also include a token (e.g., a payment token), a cryptogram (e.g., a TAVV), and/or any other suitable information.

(60) A “cryptogram request message” may be an electronic message for requesting a cryptogram. A cryptogram request message may include information usable for identifying a payment account

(e.g., a real account identifier) or a service provider account (e.g., a digital wallet account), and/or information for generating a cryptogram. A cryptogram request message may be in the same or a different format than a token request message.

(61) A “cryptogram response message” may be a message that responds to a cryptogram request message. A cryptogram response message may include an indication that a cryptogram request was approved or denied. A cryptogram response message may include a cryptogram (e.g., a TAVV), and/or any other suitable information. A cryptogram response message may be in the same or a different format than a token response message.

(62) An “enrollment request message” may be an electronic message for requesting enrollment. An enrollment request message may be in any suitable form and may include any suitable data.

(63) An “enrollment response message” may be a message that responds to an enrollment request message. A enrollment response message may include an indication that enrollment was successful or unsuccessful. An enrollment response message may be in any suitable form and may include any suitable data.

(64) An “encryption key request message” may be an electronic message for requesting an encryption key. An encryption key request message may be in any suitable form and may include any suitable data.

(65) An “encryption key response message” may be a message that responds to an encryption key request message. A enrollment response message may include an indication that enrollment was successful or unsuccessful. An enrollment response message may be in any suitable form and may include any suitable data.

(66) The term “authentication” and its derivatives may include a process by which the credential of an endpoint (including but not limited to applications, people, devices, processes, and systems) can be verified to ensure that the endpoint is who they are declared to be.

(67) The term “verification” and its derivatives may include a process that utilizes information to determine whether an underlying subject is valid under a given set of circumstances. Verification may include any comparison of information to ensure some data or information is correct, valid, accurate, legitimate, and/or in good standing.

(68) An “authorization request message” may be an electronic message that is sent to a payment processing network and/or an issuer of a payment card to request authorization for a transaction. An authorization request message according to some embodiments may comply with ISO 8583, which is a standard for systems that exchange electronic transaction information associated with a payment made by a user using a payment device or payment account. The authorization request message may include an issuer account identifier that may be associated with a payment device or payment account. An authorization request message may also comprise additional data elements corresponding to “identification information” including, by way of example only: a service code, a CVV (card verification value), a dCVV (dynamic card verification value), an expiration date, etc. An authorization request message may also comprise “transaction information,” such as any information associated with a current transaction, such as the transaction amount, merchant identifier, merchant location, etc., as well as any other information that may be utilized in determining whether to identify and/or authorize a transaction.

(69) An “authorization response message” may be an electronic message reply to an authorization request message generated by an issuing financial institution or a payment processing network. The authorization response message may include, by way of example only, one or more of the following status indicators: Approval—transaction was approved; Decline—transaction was not approved; or Call Center—response pending more information, merchant must call the toll-free authorization phone number. The authorization response message may also include an authorization code, which may be a code that a credit card issuing bank returns in response to an authorization request message in an electronic message (either directly or through the payment processing network) to the merchant's access device (e.g., POS equipment) that indicates approval of the

transaction. The code may serve as proof of authorization. As noted above, in some embodiments, a payment processing network may generate or forward the authorization response message to the merchant.

(70) A “transaction data format” may include a data format utilized for a transaction. By way of example, a transaction data format may include a format utilized for an authorization request message and/or authorization response message. In some embodiments, the transaction data format may comply with ISO 8583. Some example transaction data formats may depend on a type of transaction. By way of example, a card-on-file transaction may have the same or different data format as a card-not-present. That is a card-on-file transaction may include the same or a different set of data fields in a same or different order as a card-not-present transaction.

(71) A “server computer” is typically a powerful computer or cluster of computers. For example, the server computer can be a large mainframe, a minicomputer cluster, or a group of servers functioning as a unit. In one example, the server computer may be a database server coupled to a Web server.

(72) A “processor” may include any suitable data computation device or devices. A processor may comprise one or more microprocessors working together to accomplish a desired function. The processor may include CPU comprises at least one high-speed data processor adequate to execute program components for executing user and/or system-generated requests. The CPU may be a microprocessor such as AMD's Athlon, Duron and/or Opteron; IBM and/or Motorola's PowerPC; IBM's and Sony's Cell processor; Intel's Celeron, Itanium, Pentium, Xeon, and/or XScale; and/or the like processor(s).

(73) A “memory” may be any suitable device or devices that can store electronic data. A suitable memory may comprise a non-transitory computer readable medium that stores instructions that can be executed by a processor to implement a desired method. Examples of memories may comprise one or more memory chips, disk drives, etc. Such memories may operate using any suitable electrical, optical, and/or magnetic mode of operation.

(74) Embodiments can improve partner systems by providing rapid integration with a token service computer. They can provide token service integration options for partners that allow them to leverage in-store access devices such as NFC (near field communication) point of sale terminals to initiate transactions that use credentials stored in the cloud, rather than credentials stored on portable user devices. Transactions conducted using credentials stored in the cloud may be characterized as CNP (card not present) transactions in some instances. This can be an integration option with a token service system to simplify purchase solutions provided by the partners. In some embodiments, a partner may initiate token transactions such as a card-on-file transaction (e.g., in a first transaction data format) at point of sale terminals in stores. These transaction can be converted to card-not-present transactions (e.g., in a second transaction data format) before sending them to the issuers for payment transaction processing. Embodiments increase the number different types of transactions that can be conducted at merchant access devices (e.g., card not present and card present) without modifying existing legacy access devices or building new access devices.

(75) Embodiments provide the flexibility to the merchant partners to send card present NFC contactless transactions (e.g., payWave transactions) using card-on-file tokens (e.g., tokens that have been previously associated with a card on file) to a payment processing network such as VisaNet™ and convert them to card-not-present token transactions before sending them to the issuer/issuer processor. This can help particular merchants and allow them to send the COF token transactions as if they are card present transactions to reduce the level of integration changes between the merchant and the partner.

(76) In some embodiments, a user (e.g., a consumer) may walk into a partner's physical store. The partner may provide/operate an auxiliary device in the store that enables the consumer to use an existing card-on-file (e.g., payment credential previously provided via a partner's website, credentials stored at a secure server computer, etc.) to use for payments in store. In some

embodiments, the user may provide biometric data via the auxiliary device (e.g., via a biometric reader connected to or include in the auxiliary device). The user may be authenticated (e.g., at the auxiliary device, at the secure server computer, etc.) utilizing the biometric data. If verified, the partner can make a request for a card-on-file (COF) token and/or a cryptogram associated with the user/token. The token and/or cryptogram may be associated with a credential of the user (e.g., a payment credential such as a real account identifier). In some embodiments, the secure server computer can request and store more than one cryptogram associated with the user/token at a time. In some embodiments, the auxiliary device may retrieve all cryptograms associated with the user/token from the secure server computer. The auxiliary device may provide the COF token and a cryptogram to another computer device (e.g., an access device). According to various embodiments, the COF token and the pre-fetched cryptograms may not be stored (or stored permanently) locally on the auxiliary device. In some embodiments, such information may only be stored on the secure server computer.

(77) In some embodiments, the access device (or another resource provider computer) sends an authorization request message for a card present (CP) transaction to a processing network computer via a transport computer associated with an acquirer. The payment processing network may convert the authorization request message from a first transaction data format (e.g., a CP transaction format) to a second transaction data format (e.g., a card-not-present (CNP) transaction format). The authorization request message may be then sent to an authorizing entity computer (e.g., operated by or on behalf of an issuer associated with the credential). According to various embodiments, the processing network computer may include a transaction-by-identity identifier (e.g. flag) to the authorization request message. Upon receiving a transaction authorization response message from the issuer for the CNP transaction, the processing network computer may convert the authorization response message from the second transaction data format to the first transaction data format before sending the response to the resource provider (e.g., the access device) via the transport computer.

(78) In some embodiments, a secure element device may be disposed between an auxiliary device and an access device. The auxiliary device may provide the token and/or or any suitable data for generating a cryptogram to the secure element device. By way of example, a limited-use key may be retrieved from a token provider computer by a secure server computer and provided to an auxiliary device. In some embodiments, the limited-use key may be provided by the auxiliary device to a secure element device where it may be stored (at least for a time). The limited-use key and the token may not be stored at the auxiliary device. In some embodiments, the auxiliary device may further provide the secure element device transaction information. The secure element device may receive additional access device data. According to various embodiments, the cryptograms may be associated with security features such as they can be limited to one-time use or a limited time use (associated with an expiration date/time). There may also be sequence limits/restrictions on how the cryptograms may be fetched.

(79) As provided above, according to various embodiments, a secure server computer may retrieve from a token provider computer, a COF token and one or more cryptograms stored in connection with a credential of a user (e.g., a consumer). The token provider computer may store multiple cryptograms associated with a credential (e.g., a real account identifier) of the user. The secure server computer may retrieve and cache the pre-fetched cryptogram(s) to ensure that the token and cryptogram(s) are on hand (e.g., accessible without transmitting another request to the token provider computer) when a customer is standing at the checkout counter at the time of a transaction.

(80) Embodiments may provide a new API to enable a token requestor (e.g. a partner device such as a secure server computer operated by or on behalf of a partner) to obtain a list of cryptograms. In some embodiments, only transaction authentication verification value (TAVV) cryptograms may be supported. In some embodiments, no token or payment instrument information is returned to the partner device. Embodiments may determine and incorporate an attribute to the partner profile at

the payment processing network to indicate a maximum number of cryptograms that the partner device can retrieve per API call (e.g. 3, 5, 10, etc.).

(81) FIG. 1 shows an exemplary system **100** and a process flow diagram, in accordance with at least one embodiment. The system **100** includes a user **102** operating a user device (not depicted), an auxiliary device **104**, a secure server computer **108**, a token provider computer **110**, an access device **112**, a transport computer **114**, a processing network computer **116**, and an authorizing entity computer **118**. In some embodiments, the access device **112** may be coupled to the auxiliary device **104** or otherwise in communication with the auxiliary device. The secure server computer **108** can communicate with the user device (not depicted), the auxiliary device **104**, and the token provider computer **110**. In some embodiments, the auxiliary device **104** may have an API that allows it to communicate with the secure server computer **108**. The access device **112** may be in communication with a processing network computer **116** and an authorizing entity computer **118** via a transport computer **114** (e.g., a computer operated on behalf of the acquirer of a merchant/provider of the access device **112**).

(82) The auxiliary device **104** and the access device **112** may be operatively coupled to each other in any suitable manner. For example, the auxiliary device **104** can be coupled to the access device **112** through a wired or wireless connection.

(83) One method that can be performed by the system in FIG. 1 may include receiving, by an auxiliary device **104** in communication with an access device, authentication data from a user. In some embodiments, the auxiliary device **104** may request a token from the secure server computer **108** and may receive from the secure server computer **108** the token and a cryptogram (e.g., a transaction authentication verification value (TAVV) generated by the token provider computer **110** in response to its request. The auxiliary device **104** may provide the token and the TAVV to the access device **112**, where the access device **112** can generate an authorization request message that may be transmitted to the authorizing entity computer **118** via the transport computer **114** and the processing network computer **116**.

(84) In some embodiments, the user **102** may walk into a partner's store and initiate a transaction. For example, the user **102** may select a number of items and an agent of the partner may scan the items to obtain a total amount owed by the user **102** to the partner. The total amount may include a total price for the items plus any suitable taxes and/or fees. The process flow described in connection with FIG. 1 may be utilized by the user **102** to provide payment for the transaction.

(85) An exemplary process is illustrated in FIG. 1. At step 1, a credential (e.g., a real account identifier which has been tokenized) can be stored at the secure server computer **108**. As an example, the user **102** may utilize a user device (not depicted) to access a website and/or an application hosted by a partner to provide the credential as part of an enrollment process performed by the user. As an example, the user may associate a payment credential (e.g., a credit card, a debit card, a banking account number, etc.) with their user account associated with the partner's website. The payment credential can be stored at the secure server computer **108** (e.g., the partner's or another entity's cloud-computing environment) for subsequent use.

(86) At step 2, the user **102** can then conduct an authentication process with the auxiliary device **104**. By way of example, the user **102** can enter (e.g., via a keyboard, touchpad, biometric reader, etc.) a username and password, a PIN, biometric data, or any suitable data with which the user can be authenticated (e.g., any suitable data that can be compared to previous data stored at the secure server computer **108** and associated with the user **102**).

(87) At step 3, the auxiliary device **104** may initiate verification of the authentication data. In some embodiments, the auxiliary device **104** may store authentication data in local memory and may verify the authentication data at the auxiliary device **104**. In the example depicted, the auxiliary device **104** initiates verification by requesting verification be conducted by the secure server computer **108**. In some embodiments, the auxiliary device **104** may request verification by requesting verification when requesting a token and/or a cryptogram from the secure server

computer **108**. Advantageously, a single message may be sent from the auxiliary device **104** to the secure server **108** to perform two functions including authenticating the user **102** and requesting the token. This advantageously reduces the number of steps relative to conventional transaction processing.

(88) Verifying the authentication data received at the auxiliary device **104** may include comparing the received authentication data to previously stored authentication data associated with the user. As an example, the user **102** may provide a username and password, a PIN, biometric data, or the like at the auxiliary device **104** and the provided data transmitted to the secure server computer **108** and is compared to data stored at the secure server computer **108**. If the received data matches the previously stored data, the user may be authenticated and the process may continue to step **4**. If the received data does not match the previously stored data, the user **102** may not be authenticated and access to the token and/or cryptogram may be denied (e.g., a message may be transmitted from the secure server computer **108** to the auxiliary device **104** indicating authentication failed and an indication may be presented at the auxiliary device **104**).

(89) At step **4**, the secure server computer **108** may request a token (e.g., a payment token corresponding to a credential stored at the secure server computer **108** and associated with the recently authenticated user **102**) and/or a cryptogram (e.g., a transaction authentication verification value) from the token provider computer **110**. A TAVV cryptogram can be one that accompanies a payment token in an authorization request message. In some embodiments, the TAVV may only be valid for a particular type of transaction channel (e.g., only e-commerce or only physical point of sale transactions). If the token is received during a transaction and the correct TAVV does not accompany the token, then the transaction may be denied (e.g., by the processing network computer **116** operated by or on behalf of a processing network).

(90) The token provider computer **110** can generate a token and a TAVV using issuer provided cryptographic keys, an encryption algorithm, and input data such as data associated with a real credential or token. It should be appreciated that the secure server computer **108** may transmit a request for the token in a separate message (e.g., a token request message) and then transmit a request for the cryptogram (e.g., a cryptogram request message). In some embodiments, the secure server computer **108** can request multiple cryptograms (e.g., multiple TAVVs) for the same token. Each cryptogram may be individually be utilized in a subsequent transactions. A cryptogram request for multiple cryptograms may utilize a same or different message than a token request message and/or cryptogram request message. Methods for requesting multiple cryptograms may be discussed further with respect to FIG. **7**.

(91) At step **5**, the token provider computer **110** can transmit the generated token and cryptogram(s) to the secure server computer **108**. The secure server computer **108** can store the token and cryptogram(s) in memory at the secure server computer **108** (and/or at another storage location accessible to the secure server computer **108**).

(92) At step **6**, the secure server computer **108** may transmit the token and a cryptogram (e.g., a TAVV) to the auxiliary device **104**.

(93) At step **7**, the auxiliary device **104** can generate (e.g., via an application operating at the auxiliary device **104**) a near field communications (NFC) payload incorporating the token and the cryptogram and can initiate an NFC transaction with the access device **112**. It should be appreciated that the auxiliary device **104** can utilize any suitable data communication not necessarily NFC to transmit the token and the cryptogram to the access device **112**. In some embodiments, the auxiliary device **104** may emulate a payment card (e.g., a smartcard) and may exchange data with the access device **112**. Card emulation may be discussed in more detail with respect to FIG. **11**. Still alternatively, the auxiliary device **104** may be hardwired or connected via a cable connector to the access device **112** in other embodiments.

(94) At step **8**, the access device **112** may send an authorization request message (e.g., an authorization request message indicating a card present transaction) to the transport computer **114**

operated by an acquirer. The authorization request message can include data in a first transaction data format such as a card present contactless transaction data format.

(95) At step **9**, the transport computer **114** may transmit the authorization request message to the processing network computer **116**. The processing network computer **116** can extract the cryptogram (e.g., the TAVV) and can validate the TAVV cryptogram. The TAVV can be validated by obtaining cryptogram inputs (e.g., a token, counter, etc.) from the authorization request message, and then the inputs may be encrypted using a cryptographic key corresponding to the cryptographic key used to form the TAVV. The generated TAVV can then be compared to the TAVV in the authorization request message. If they match, the TAVV is validated and the transaction may continue to proceed. If they do not match, then the transaction may be declined. In other embodiments, the TAVV can be validated by decrypting the TAVV in the authorization request message using a corresponding cryptographic key to obtain the inputs to the TAVV. The recovered inputs may be compared with the inputs in the authorization request message to validate the TAVV.

(96) At step **10**, the processing network computer **116** may detokenize the token to obtain a real account identifier (e.g., a personal account number (PAN) associated with the token. In this regard, the processing network computer **116** may communicate with the token provider computer **110**. For example, the processing network computer **116** may provide the token and the cryptogram to the token provider computer **110**. The token provider computer **110** may verify that the token and the cryptogram are associated with one another. If so, the token provider computer **110** may respond with the real account identifier associated with the token and cryptogram.

(97) At step **11**, the processing network computer **116** may convert the authorization request message to a second transaction data format (e.g., a card not present or e-commerce transaction data format). In some embodiments, the second transaction data format may include an indicator (e.g., an e-commerce (EC) 17 indicator). As an example, the processing network computer **116** may be configured to utilize the following table for performing conversions between a first and second transaction data format.

(98) TABLE-US-00001 1st transaction data 2nd transaction data format (card present) format (card-not-present) Field 22: POS Entry Field 22-POS Entry Mode Code = 07 Mode Code = 01 Field 35-Track 2 Data No field 35 Field 44.5-CVV/ICVV No field 44.5 Results Code Field 45-Track 1 Data No field 45 Field 55-Cryptogram No field 55 Chip Data No field 44.13 Filed 44.13-CAVV Results Code Field 60.8-Electronic Field 60-Electronic Commerce Indicator = 5 Commerce Indicator = 7 TLV Field 123, Usage 2, TLV Field 123, Usage 2, Dataset ID 66-AVS Data Dataset ID 66-AVS Data TLV Field 123, Usage 2, TLV Field 123, Usage 2, Dataset ID 68-AVS Data Dataset ID 68-AVS Data No field 126.9 Field 126.9, Usage 3, Position 7, 3-D Secure CAVV, Revised Format (e.g., moved from field 55 of 1st transaction data format)

(99) At step **12**, the processing network computer **116** may transmit the converted authorization request message to the authorizing entity computer **118**. The authorizing entity computer **118** receives the authorization request message with the PAN, the TAVV, and an EC17 indicator. An EC17 indicator may be an indicator that the TAVV and/or the authorization request message was validated.

(100) At step **13**, the authorizing entity computer **118** can approve or decline the authorization request message and can transmit an authorization response message back to processing network computer **116**. The authorization response message may be in any suitable format (e.g., the second transaction data format).

(101) At step **14**, the processing network computer **116** may transmit the authorization response message to the transport computer **114**. It should be appreciated that, in some embodiments, the processing network computer **116** may convert the authorization response message from a second transaction data format to a first transaction data format prior to the transmission.

(102) At step **15**, the transport computer **114** may transmit the authorization response message to the access device **112**.

(103) At step **16**, the auxiliary device **104** can then delete the token and/or cryptogram from memory. It should be appreciated that this deletion can occur at any suitable time after performance of the operations of step **7**. In some embodiments, the access device **112** can transmit an indication that the authorization response message of step **15** was received, which can cause the auxiliary device **104** to delete the token and cryptogram from memory. Deletion of the data in the auxiliary device **104** can occur manually (e.g., in response to a user selecting a button on the auxiliary device **104**) or automatically (e.g., in response to receiving an authorization response message for the transaction or after a predetermined period of time (e.g., 10 minutes).

(104) At a subsequent time, a clearing and settlement process can be conducted between the transport computer **114**, the processing network computer **116**, and the authorizing entity computer **118**.

(105) FIG. **2** shows an exemplary system **200** and a process flow diagram illustrating a token and/or cryptogram provisioning process, in accordance with at least one embodiment. In some embodiments, some parts the process illustrated in FIG. **2** (e.g., steps **1-7**, steps **1-10**, etc.) may be performed prior to the process depicted in FIG. **1**.

(106) At step **1**, a user **102** may utilize an enrollment device **202** to input payment card data (e.g., a credit card number, a debit card number, an expiration date, a cardholder name, a CVV, etc.). In some embodiments, the enrollment device **202** may be an example of the auxiliary device **104** of FIG. **1** and the enrollment device **202** may be located in a physical store (e.g., a merchant's store). The enrollment device **202** may, in that use case, be provided by a partner (e.g., a merchant) for interfacing with the partner's backend system (e.g., the secure server computer **108**). As another example, the enrollment device **202** may be a user device of the user **102** and the enrollment device **202** may be utilized to access the partner's website (e.g., hosted by the secure server computer **108** or another suitable system) in order to provide the payment card data.

(107) In either scenario, at step **2**, the enrollment device **202** may be utilized to provide the payment card data to the secure server computer **108**. The payment card data may be stored at the secure server computer **108** and associated with the user **102** (e.g., via a user account associated with the user **102** and managed by the secure server computer **108**).

(108) At step **3**, the secure server computer **108** may submit a token request to a token provider computer **110** for a token (e.g., for a card on file token). The token request may be in any suitable form (e.g., a token request message).

(109) At step **4**, the token provider computer **110** may perform an eligibility check. By way of example, the token provider computer **110** may transmit a message (e.g., a token request message or any suitable message) to the authorizing entity computer **118** to check for the issuer's participation and/or to request tokenization. In some embodiments, the token provider computer **110** may request approval to generate the token from the authorizing entity computer **118** without performing identification and/or verification of the user **102**. Accordingly, in some embodiments, the token provider computer **110** may rely on authentication efforts and/or an assertion that the user **102** has been authenticated as provided by the secure server computer **108**.

(110) At step **5**, the authorizing entity computer **118** may use the data received at step **4** to determine whether to approve or decline the request. The authorizing entity computer **118** may transmit a response (e.g., a token response message or any suitable message) to the token provider computer **110** indicating the request has been approved or declined.

(111) At step **6**, based on receiving an indication that the request was approved, the token provider computer **110** may generate a token for the payment data and maintain an association (e.g., a mapping) between the token and the payment card data in memory. In some embodiments, the token provider computer **110** may be configured to generate one or more cryptograms for the newly generated token. If so, the cryptogram(s) (e.g., multiple TAVVs) may also be associated with (e.g., mapped to) the token and the payment card data in memory. In some embodiments, the token provider computer **110** may generate one or more cryptograms as part of a separate request (e.g., in

response to receiving a cryptogram request message).

(112) At step **7**, the token provider computer **110** may provide the token (and if cryptogram(s) were generated, the cryptogram(s)) to the secure server computer **108** (e.g., via a token response message).

(113) In some embodiments, the secure server computer **108** can request one or more cryptograms via a separate request. For example, at step **8**, the secure server computer **108** can transmit a cryptogram request message to the token provider computer **110**. The cryptogram request message may be in any suitable form. In some embodiments, the cryptogram request message may utilize a particular predefined API specifically for requesting a list of cryptograms. In some embodiments, the cryptogram request message may include a token identifier for the token and/or a number of cryptograms requested. In some embodiments, if a number is not provided, the token provider computer **110** may default the request to one cryptogram being requested. The cryptogram request message may include a transaction type (e.g., an e-commerce transaction type to be used for transaction initiated online via a website, a recurring payment transaction type, a point-of-sale transaction type, etc.).

(114) At step **9**, the token provider computer may perform a process for generating one or more cryptograms (e.g., TAVVs). This process may be discussed further below in connection with FIG. **7**.

(115) At step **10**, the token provider computer **110** may provide the one or more cryptograms to the secure server computer **108** via a cryptogram response message. In some embodiments, the cryptogram response message may include the token identifier, the token, a list of the one or more cryptograms, an e-commerce indicator, an error code, or any suitable combination of the above. In some embodiments, the token provider computer **110** may provide a cryptogram response message that includes an error code rather than the one or more cryptograms requested. By way of example, the token provider computer **110** may provide a cryptogram response message that indicate the token requestor (e.g., the secure server computer **108**) is not authorized to use the particular API for requesting multiple cryptograms. As another example, the token provider computer **110** may provide a cryptogram response message that includes an error code that indicates the requested action is not allowed.

(116) FIGS. **3-6** shows exemplary methods for authenticating a user, in accordance with at least one embodiment.

(117) FIG. **3** shows an exemplary method **300** for authenticating a user with a one-time password after the process described in FIG. **2** has been completed, in accordance with at least one embodiment. In some embodiments, the user **102** may be authenticated using a one-time password after enrollment has occurred and a token has been generated (e.g., by the token provider computer **110**).

(118) At step **1**, the token provider computer **110** may generate a one-time password. The one-time password may be associated with the user **102** (e.g., via a mapping maintained by the token provider computer **110** including, for example, an identifier for the user **102**, the credential of the user (e.g., payment card data), the token generated for the credential, and the one-time password). The token provider computer **110** may be configured to maintain a record that indicates that the token is active (e.g., available for use) or inactive (e.g., unavailable for use) based on whether the user has been verified with a one-time password. If the user **102** has not been verified with a one-time password, the token may be inactive. If the user **102** has been verified with a one-time password, the token may be recorded as being active.

(119) At step **2**, the token provider computer **110** may transmit the one-time password to the authorizing entity computer **118**. The authorizing entity computer **118** may be configured to maintain one or more contact data for the user **102**. By way of example, the authorizing entity computer **118** may include a phone number (e.g., for SMS messaging) and/or an email address (e.g., for electronic mail).

(120) At step 3, the authorizing entity may prompt the user (e.g., via the enrollment device **202**) to indicate a preferred contact method (e.g., email, SMS messaging, etc.).

(121) At step 4, the user **102** may select a preferred contact method (e.g., SMS messaging). As in FIG. 2, the enrollment device may be a user device associated with the user **102** or the auxiliary device **104** of FIG. 1, but generally the enrollment device **202** may be the device utilized by the user **102** to perform the enrollment process of FIG. 2.

(122) At step 5, the selection may be transmitted back to the authorizing entity computer **118**.

(123) At step 6, the authorizing entity computer **118** may transmit the one-time password using the selected preferred contact method (e.g., SMS messaging). The one-time password may, for example, be transmitted via SMS message to the user device **302** using a phone number known to the authorizing entity computer **118** and associated with the user **102**. It should be appreciated that, in some embodiments, the user device **302** may be the same device as the enrollment device **202**.

(124) At step 7, the user may enter the one-time password received at user device **302** into an interface provided at the enrollment device **202** (e.g., the auxiliary device **104**). The input may be transmitted to the authorizing entity computer **118** at step 8 and forwarded to the token provider computer **110** at step 9. The token provider computer **110** may be configured to activate the token for use if the one-time password received at step 9 matches the one-time password generated at step 1.

(125) FIG. 4 shows an exemplary method **400** for authenticating a user with a one-time password during a transaction, in accordance with at least one embodiment. In some embodiments, the user **102** may have performed the enrollment process described in FIG. 2 but has not yet authenticated himself using a one-time password as described in FIG. 3. In some embodiments, the user **102** may be prompted during a transaction for the one-time password. Thus, prior to performing the method **400**, the secure server computer **108** may store a token corresponding to a credential (e.g., payment data) associated with the user **102**.

(126) At step 1, the user **102** can then authenticate to the auxiliary device **104**. By way of example, the user **102** can enter (e.g., via a keyboard, touchpad, biometric reader, etc.) authentication data (e.g., a username and password, a PIN, biometric data, or any suitable data with which the user can be authenticated) into the auxiliary device **104**.

(127) At step 2, the auxiliary device **104** may initiate verification of the authentication data. In the example depicted, the auxiliary device **104** initiates verification by requesting verification be conducted by the secure server computer **108**. In some embodiments, the auxiliary device **104** may request verification of the authentication data at the same time that the auxiliary device **104** requests a token and/or a cryptogram from the secure server computer **108**. In some embodiments, the secure server computer **108** stores the token associated with the credential of the user **102**. In some embodiments, the token is inactive. Verifying the authentication data received at the auxiliary device **104** may include comparing the received authentication data to previously stored authentication data associated with the user. If the received authentication data matches the previously stored data, the user may be authenticated by the secure server computer **108** and the process may continue to step 4. If the received data does not match the previously stored data, the user **102** may not be authenticated and access to the token and/or cryptogram may be denied (e.g., a message may be transmitted from the secure server computer **108** to the auxiliary device **104** indicating authentication failed and an indication may be presented at the auxiliary device **104**).

(128) At step 4, the secure server computer **108** may request (e.g., from the token provider computer **110**) a cryptogram corresponding to the token stored at the secure server computer **108**. A TAVV cryptogram can be one that accompanies a payment token in an authorization request message. In some embodiments, the TAVV may only be valid for a particular type of transaction channel (e.g., only e-commerce or only physical point of sale transactions). If the token is received during a transaction and the correct TAVV does not accompany the token, then the transaction may be denied (e.g., by the processing network computer **116** operated by or on behalf of a processing

network).

(129) At step 5, the token provider computer **110** can determine that the token is in an inactive state and may generate a one-time passcode. The token provider computer **110** can provide the one-time password to the authorizing entity computer **118** at step 6.

(130) At step 7, the authorizing entity computer **118** may transmit the one-time password using a previously selected preferred contact method (e.g., SMS messaging) or utilizing one or more contact methods (e.g., SMS messaging, email, etc.) based at least in part on contact data previously provided to the authorizing entity by the user **102**. The one-time password may, for example, be transmitted via email message to an email address known to the authorizing entity computer **118** and associated with the user **102**. The email message may be viewable from the user device **302**.

(131) At step 8, the user may enter the one-time password received at user device **302** into an interface provided at the auxiliary device **104**. In some embodiments, the token provider computer **110** may transmit (e.g., in response to receiving the request at step 4) an indication to the secure server computer **108** that the user **102** has not been authenticated via a one-time password. In response to receiving this indication, the secure server computer **108** may cause the auxiliary device **104** to provide the interface. The input provided via the interface may be transmitted to the secure server computer **108** at step 9 and forwarded to the token provider computer **110** at step 10. The token provider computer **110** may be configured to activate the token for use if the one-time password received at step 10 matches the one-time password generated at step 5.

(132) If the token is activated, the steps 11-22 may be performed. Steps 11-22 of FIG. 4 may correspond to steps 5-16 of FIG. 1 and will not be repeated here for brevity.

(133) FIG. 5 shows an exemplary method 500 for authenticating a user with a one-time password, in accordance with at least one embodiment. In some embodiments, the user **102** may have performed the enrollment process described in FIG. 2, but has not yet authenticated himself using a one-time password. In some embodiments, a token may be generated as described in connection with FIG. 1. However, the token may be activated for limited use. By way of example, a number of limited use thresholds may be associated with the token by the token provider computer **110** such that the token may be activated for a time period or for a certain number of transactions (e.g., 1, 2, 5, etc.) before it is inactivated if the user has not been authenticated with a one-time password prior to expiration of the limited use thresholds.

(134) FIG. 5 depicts a use case in which the one-time password is prompted by the partner and provided via an interface associated with the partner. The method 500 may be performed as part of the process of FIG. 1 (e.g., after the token is provided to the secure server computer **108** at step 5).

(135) At step 1 of method 500, the secure server computer **108** may request a one-time password from the token provider computer **110**.

(136) At step 2, the token provider computer **110** may generate a one-time passcode. The token provider computer **110** can provide the one-time password to the authorizing entity computer **118** at step 3.

(137) At step 4, the authorizing entity computer **118** may transmit the one-time password using a previously selected preferred contact method (e.g., SMS messaging) or utilizing one or more contact methods (e.g., SMS messaging, email, etc.) based at least in part on contact data previously provided to the authorizing entity by the user **102**. The one-time password may, for example, be transmitted via SMS message to phone number known to the authorizing entity computer **118** and associated with the user **102**. The SMS message may be viewable from the user device **402**.

(138) At step 6, the user may utilize the user device **402** (or another suitable computing device) to access an interface provided by the secure server computer **108** (e.g., a webpage interface hosted by the partner via the secure server computer **108** or another suitable web server computer). The user **102** may enter the one-time password received at user device **302** into an interface provided by the secure server computer **108**. The input may be received by the secure server computer **108** via the interface.

(139) At step 7, the secure server computer **108** may forward the input to the token provider computer **110**.

(140) At step 8, the token provider computer **110** may be configured to activate the token for use if the one-time password received at step 7 matches the one-time password generated at step 2.

(141) FIG. 6 shows another exemplary method **600** for authenticating a user via an issuer application, in accordance with at least one embodiment. In some embodiments, the user **102** may have performed the enrollment process described in FIG. 2, but has not yet authenticated himself via an issuer application. In some embodiments, a token may be generated as described in connection with FIG. 1. However, the token may be activated for limited use. By way of example, a number of limited use thresholds may be associated with the token by the token provider computer **110** such that the token may be activate for a time period or for a certain number of transactions (e.g., 1, 2, 5, etc.) before it is inactivated if the user has not been authenticated via an issuer application prior to expiration of the limited use thresholds.

(142) FIG. 6 depicts a use case in which authentication is prompted by the issuer and provided via an interface associated with the issuer. The method **600** may be performed as part of the process of FIG. 2 (e.g., after step 4 when an approval for generating a token is received by the authorizing entity computer **118**) or at any suitable time.

(143) At step 1, the authorizing entity computer **118** may transmit instructions to the user device **602** for performing authentication utilizing a one-time password. The instructions may be received by the user device **602** via a client application **604** executing on the user device **602** and hosted by the issuer.

(144) At step 2, the user **102** may review instructions (e.g., from the authorizing entity computer **118**) via an client application **604** associated with the issuer and operating at the user device **602**. By way of example, the user **102** may receive a hyperlink and instructions to complete an authentication process via an interface of the client application **604**. The instructions may detail that the user **102** is to login to his account via the client application **604**.

(145) At step 3, the user **102** may attempt to login to an account associated with the issuer utilizing the client application **604** by providing a credential (e.g., a username and password, a PIN, biometric data, or the like).

(146) At step 4, the credential may be transmitted to the authorizing entity computer **118** (the computer hosting the client application **604**). If the credential matches one stored by the issuer and associated with the user **102**, the authorizing entity computer **118** may determine the user **102** is authenticated and the method **600** may proceed to step 5.

(147) At step 5, the authorizing entity computer **118** may transmit an indication that the user **102** has been verified. This indication may be included in the message transmitted at step 5 of FIG. 2 in some embodiments. The token provider computer **110** may be configured to activate the token upon receiving the indication at step 5.

(148) FIG. 7 shows an process flow diagram for an exemplary process **700** for generating multiple cryptograms, in accordance with at least one embodiment. The process depicted in FIG. 7 may be performed by the token provider computer **110** of FIG. 2.

(149) The process **700** may begin at **702**, where a cryptogram request may be received (e.g., via a cryptogram request message). By way of example, the token provider computer **110** may receive a cryptogram request message from a token requestor (e.g., the secure server computer **108** of FIG. 2).

(150) At **704**, the token provider computer **110** may obtain a profile associated with the token requestor. As a non-limiting example, a token requestor (e.g., a partner associated with the secure server computer **108**) may have previously performed an enrollment process and/or entered into an agreement with the token provider associated with the token provider computer **110**. The token provider computer **110** may be configured to store profile data for one or more token requestors that include data corresponding to that enrollment process and/or agreement. By way of example,

the profile data may include data such as a number of cryptograms that are allowed to be requested by the token requestor in a given request (or a number of cryptograms allowed to be requested by the token requestor for a given token). In some embodiments, the partner may be an electronic wallet provider that provides an electronic wallet application at the auxiliary device **104** of FIG. **2** that is hosted by the secure server computer **108**.

(151) At **706**, the token provider computer **110** may determine whether the token requestor may pre-fetch cryptograms (e.g., whether the token requestor is allowed to request multiple cryptograms for a given token and/or for a given request).

(152) If the token requestor (e.g., the secure server computer **108**) is not allowed to pre-fetch cryptograms (e.g., as indicated in the profile data associated with the secure server computer **108**/the partner), the flow may proceed to **708**, where an error code indicating the request is not allowed and the process **700** may end.

(153) Alternatively, if the token requestor (e.g., the secure server computer **108**) is not allowed to pre-fetch cryptograms (e.g., as indicated in the profile data associated with the secure server computer **108**/the partner), the flow may proceed to **710**. At **710**, the token provider computer **110** may determine whether a number of requested cryptograms included in the cryptogram request message is less than a maximum number of cryptograms allowed for the token requestor (and/or for a single token).

(154) If the number of cryptograms requested in the request is greater than or equal to the maximum number of cryptograms allowed for the token requestor (and/or for a single token) the flow may proceed to **712**. At **712**, the requested number of cryptograms may be set to the maximum number of cryptograms allowed and the flow may proceed to **714**. If the number of cryptograms requested in the request is less than the maximum number of cryptograms allowed for the token requestor (and/or for a single token) the flow may proceed directly to **714**.

(155) At **714**, the token provider computer **110** may obtain a cryptogram (e.g., generate a cryptogram such as a TAVV) using any suitable cryptogram generation process.

(156) At **716**, the token provider computer **110** may add the obtained cryptogram to a list of cryptograms and the flow may proceed to **718**.

(157) At **718**, the token provider computer **110** may be configured to determine whether the requested number of cryptograms have been obtained. If the requested number of cryptograms has been obtained, the flow may proceed to **720** where a cryptogram response message may be transmitted to the token requestor (e.g., the secure server computer **108**). The cryptogram response message may include the list of cryptograms. If the requested number of cryptograms has not been obtained, the flow may proceed back to **714**. Steps **714** through **718** may be repeated any suitable number of times corresponding to the number of cryptograms requested (or the number of cryptograms requested after **712**).

(158) FIG. **8** shows an exemplary system **800** (e.g., the system **100** of FIG. **1**) and a process flow diagram for performing a biometric enrollment process, in accordance with at least one embodiment. In some embodiments, at least some portion of the process illustrated in FIG. **8** may be performed prior to the process depicted in FIG. **1**.

(159) At step **1**, a user **102** may utilize a computing device **802** to provide biometric data (e.g., a fingerprint, a retina scan, an facial image, etc.). In some embodiments, the computing device **802** may be an example of a user device or an auxiliary device (e.g., the auxiliary device **104** of FIG. **1**). The computing device **802** may include one or more input devices configured to receive biometric data. For example, the computing device **802** may include a biometric reader, a camera, a retina scanner, and/or the like. The computing device **802** may, in some cases, be provided by a partner (or a merchant) for interfacing with the partner's backend system (e.g., the secure server computer **108**). As another example, the computing device **802** may be a user device of the user **102** and the computing device **802** may be utilized to access the partner's website (e.g., hosted by the secure server computer **108** or another suitable system) in order to provide biometric data.

(160) According to various embodiments, the computing device **802** (e.g., the auxiliary device **104** of FIG. **1**) may be a biometric capable device that meets the security, functional, and/or biometric capture requirements defined by one or more of a token provider, a processing network, and/or an issuer. Generally, the computing device **802** can be capable of capturing one or more of the biometric modalities (e.g. fingerprint, facial imprint, eye/retina scan, voice sample). The computing device **802** may also protect and transmit the captured biometric data to the secure server computer **108** (e.g., for storage) and the computing device **802** may protect cardholder data and payment credentials (PCI and PII). In addition, some embodiments may use an existing access device (e.g., a POS device) to process payment transaction. For such embodiments, the computing device **802** may include hardware capable of interacting with the existing access devices (NFC, QR Code, Magnetic stripe, etc.). Depending on the biometric modality or modalities, the hardware may also have additional sensors to detect the proximity of consumers in order to assist in determining whether, and which, consumer is intending to make a payment.

(161) Systems discussed in connection with various embodiments may also include client applications (e.g. application software) developed to run on the computing device **802**. During enrollment, the application may guide a user through the enrollment process and interact with the necessary biometric credential and payment credential repositories (e.g., the secure server computer **108**). For example, the client application may instruct the user how to interact in order that sufficient biometric data for a modality is captured. For example, if using a fingerprint modality, the client application may instruct the consumer to roll a finger on the sensor or present the same finger multiple times and at multiple angles. The client application may further be configured to provide the necessary data to link the biometric to a payment credential. In some embodiments, the client application may be configured to complete all necessary identification and/or verification processes to authenticate the user **102**.

(162) At step **2**, the computing device **802** may be utilized to provide the biometric data to the secure server computer **108**. In some embodiments, the biometric data may be provided with a credential (e.g., a username/password, a PIN, etc.) associated with a previously existing user account. In some embodiments, the credential (e.g., payment card data) may be captured from a physical card (e.g., via NFC, a camera, a chip, a magstripe payment card, etc.) to be linked to the captured biometric data.

(163) At step **3**, the secure server computer **108** may create a user account (or access a previously existing user account with the credential provided) in response to receiving the biometric data. The biometric data may be stored at the secure server computer **108** and associated with the user **102** (e.g., via the user account managed by the secure server computer **108**).

(164) At step **4**, the computing device **802** may be utilized by the user **102** to provide a payment data (e.g., an account identifier, a PAN, a credit card number, a debit card number, etc.) to the secure server computer **108**. In some embodiments, the user account accessed at step **3** may already be associated with payment data. Thus, in some examples, step **4** would not necessarily be performed. It should also be appreciated that step **4** may, in some embodiments, be performed before step **2** and that the user account, if created, may be created response to receiving the credential. Thus, either the credential or the biometric data may be received first.

(165) At step **5**, the secure server computer **108** may submit a token request to a token provider computer **110** for a token (e.g., for a card on file token). The token request may be in any suitable form (e.g., a token request message).

(166) At step **6**, the token provider computer **110** may perform an eligibility check. By way of example, the token provider computer **110** may transmit a message (e.g., a token request message or any suitable message) to the authorizing entity computer **118** to check for the issuer's participation and/or to request tokenization. In some embodiments, the token provider computer **110** may request approval to generate the token from the authorizing entity computer **118** without performing identification and/or verification of the user **102**. Accordingly, in some embodiments,

the token provider computer **110** may rely on authentication efforts and/or an assertion that the user **102** has been authenticated as provided by the secure server computer **108**.

(167) At step **7**, the authorizing entity computer **118** may use the data received at step **6** to determine whether to approve or decline the request. The authorizing entity computer **118** may transmit a response (e.g., a token response message or any suitable message) to the token provider computer **110** indicating the request has been approved or declined.

(168) At step **8**, based on receiving an indication that the request was approved, the token provider computer **110** may generate a token for the payment data and maintain an association (e.g., a mapping) between the token, the payment card data, and the biometric data in memory.

(169) In some embodiments, the token provider computer **110** may be configured to generate one or more cryptograms for the newly generated token. If so, the cryptogram(s) (e.g., multiple TAVVs) may also be associated with (e.g., mapped to) the token and the payment card data in memory. In some embodiments, the token provider computer **110** may generate one or more cryptograms as part of a separate request (e.g., in response to receiving a cryptogram request message).

(170) At step **9**, the token provider computer **110** may provide the token (and if cryptogram(s) were generated, the cryptogram(s)) to the secure server computer **108** (e.g., via a token response message). The token (and cryptogram(s)) may be stored at the secure server computer **108**.

(171) In some embodiments, the secure server computer **108** can request one or more cryptograms via a separate request. For example, operations corresponding to steps **8-10** of FIG. **2** may be performed to obtain one or more cryptograms corresponding to the token.

(172) FIG. **8** merely shows one example biometric enrollment process. In the enrollment process described above, sufficient biometric data may be captured to be able to perform a near real-time identification and match of biometric data. While not necessarily performed on the same device as used to capture the biometric data, a key component of enrollment is the ability to verify the identity of the user **102**. Thus, in some embodiments one or more of the secure server computer **108**, the token provider computer **110**, or the authorizing entity computer **118** may perform an identification and verification process with the user **102**. Embodiments disclosed herein assure that there is a strong link between the cardholder, their biometric data, and their chosen credential(s).

(173) FIG. **9** shows an exemplary system **900** (e.g., the system **100** of FIG. **1**) and process flow diagram for performing a biometric enrollment process during a transaction, in accordance with at least one embodiment. In some embodiments, a partner (e.g., a merchant different from a merchant associated with the access device **112**) may provide a computing device (e.g. auxiliary device **104**) for the user **102** to use in order to utilize an existing payment credential (e.g., a payment credential such as a payment card previously provided via a website hosted by the partner and stored at the secure server computer **108**) for payments in a physical store (e.g., a store operated by the merchant associated with the access device **112**).

(174) At step **1**, the user **102** may provide a credential associated with a user account managed by the secure server computer **108**. For example, the user **102** may enter a username and password, a PIN, or any suitable credential associated with the user account. Additionally, the user **102** may provide biometric data at a biometric device (e.g., a biometric scanner, a biometric reader, etc.) of the auxiliary device **104** (e.g., or a biometric device in communication with the auxiliary device **104**). By way of example, the user **102** may provide his fingerprint via a fingerprint scanner of the auxiliary device **104**. As another example, the user **102** may utilize a camera of the auxiliary device **104** to provide an image of his face.

(175) At step **2**, the auxiliary device **104** may transmit an enrollment request including the credential and the biometric data to the secure server computer **108** for enrollment. The credential and biometric data may be transmitted via any suitable message (e.g., an enrollment request message) of any suitable format.

(176) At step **3**, the secure server computer **108** may authenticate the user **102** by comparing the credential to previously stored credentials (e.g., credentials associated with the user's account and

previously provided at a partner website). If the credentials provided do not match the previously stored credentials, the enrollment request may be denied and the user **102** may be notified (e.g., via the auxiliary device **104**) that the enrollment failed. If the credentials received match the previously stored credentials, the secure server computer **108** may associate the biometric data with the user account and/or credentials.

(177) Steps **4-16** of FIG. **9** substantially match steps **4-16** discussed in connection with FIG. **1** and will not be repeated here for brevity.

(178) FIG. **10** shows a system **1000** (e.g., the system **100** of FIG. **1**) and an exemplary process flow diagram for performing a transaction utilizing biometric data associated with a user, in accordance with at least one embodiment. In some embodiments, the user **102** may walk into a partner's store and initiate a transaction. For example, the user **102** may select a number of items and an agent of the partner may scan the items to obtain a total amount owed by the user **102** to the partner. The total amount may include a total price for the items plus any suitable taxes and/or fees. The process flow described in connection with FIG. **10** may be utilized by the user **102** to provide payment for the transaction.

(179) At step **1**, the user **102** may authenticate himself using biometric data provided at a biometric device (e.g., a biometric scanner, a biometric reader, etc.) of the auxiliary device **104** (e.g., or a biometric device in communication with the auxiliary device **104**). By way of example, the user **102** may provide his fingerprint via a fingerprint scanner of the auxiliary device **104**. As another example, the user **102** may utilize a camera of the auxiliary device **104** to provide an image of his face.

(180) At step **2**, the auxiliary device **104** may transmit a token request (e.g., a token request message) to request a token and a cryptogram (e.g., a TAVV). In some embodiments, the token request may include the biometric data obtained at step **1**. In some embodiments, the biometric data may be transmitted first to the secure server computer **108** via another message (e.g., a validation request message) prior to the transmission of the token request. In some embodiments, the biometric data may be authenticated prior to token operations. The biometric data may be transmitted via any suitable message format. In some embodiments, the biometric data may be provided in a request for a token transmitted to the secure server computer **108**.

(181) Although not depicted, it should be appreciated that, in some embodiments, the auxiliary device **104** may store biometric data of the user **102** previously provided to the secure server computer **108**. If so, the auxiliary device **104** may authenticate the user **102** by comparing the received biometric data to the biometric data stored at the auxiliary device **104** and associated with the user **102**. In these examples, the biometric data may not be sent to the secure server computer **108**.

(182) At step **3**, the secure server computer **108** may authenticate the user **102** by comparing the received biometric data to previously stored biometric data. If the credentials provided do not match the previously stored credentials, the token request may be denied and the user **102** may be notified (e.g., via the auxiliary device **104**) that the transaction failed. If the credentials received match the previously stored credentials, the process may proceed to step **4**.

(183) At step **4**, the secure server computer **108** may transmit the token and a cryptogram (e.g., a TAVV) to the auxiliary device **104** in response to authenticating the biometric identity of the user **102**.

(184) Steps **5-14** of FIG. **9** substantially match steps **7-16** discussed in connection with FIG. **1** and will not be repeated here for brevity.

(185) FIG. **11** shows an exemplary system **1100** and process flow diagram illustrating a limited-use key provisioning process, according to some embodiments. The computers of FIG. **11** may be examples of the corresponding computers of FIG. **1**.

(186) In some embodiments, the user **102** may walk into a partner's store and initiate a transaction. For example, the user **102** may select a number of items and an agent of the partner may scan the

items to obtain a total amount owed by the user **102** to the partner. The total amount may include a total price for the items plus any suitable taxes and/or fees. The process flow described in connection with FIG. **10** may be utilized by the user **102** to provide payment for the transaction. (187) Steps **1-4** of FIG. **11** may correspond to steps **1-4** of FIG. **8**. That is, a process for providing biometric data and a credential may be performed in order to create a user account and to generate and maintain a mapping between the user **102**, the biometric data and the credential.

(188) At step **5**, the secure server computer **108** may be configured to generate an authorization request message that includes zero amount. The authorization may be transmitted to the transport computer **114**.

(189) At step **6**, the transport computer **114** may transmit the zero amount authorization request message to the processing network computer **116**.

(190) At step **7**, the processing network computer **116** may transmit the zero amount authorization request message to the authorizing entity computer **118**. Upon receipt, the authorizing entity computer **118** may determine whether to approve or decline the authorization request message. In some embodiments, a zero amount authorization request message may be considered by the authorizing entity computer **118** to be an indication that the user has provided biometric data. The authorizing entity computer **118** may be configured to perform any suitable authentication of the user **102** based at least in part on the data provided in the authorization request message.

(191) At step **8**, the authorizing entity computer **118** may generate an authorization response message indicating that the request was approved or declined. The authorization response message may also include a zero amount. The authorizing entity computer **118** may transmit the authorization response message to the processing network computer **116**.

(192) At step **9**, the processing network computer **116** may transmit the zero amount authorization response message to the transport computer **114**.

(193) At step **10**, the transport computer **114** may transmit the zero amount authorization response message to the secure server computer **108**. The secure server computer **108** may determine that the authorization response message indicates that the authorization request was authorized (e.g., indicating that the user **102** was authenticated).

(194) At step **11**, the secure server computer **108** may transmit a token request (e.g., via a token request message) to the token provider computer **110**. In some embodiments, the token request message may indicate a particular type of data. For example, the token request message may indicate a request for a cryptographic key (e.g., a limited-use key).

(195) At step **12**, the token provider computer **110** may perform an eligibility check. By way of example, the token provider computer **110** may transmit a message (e.g., a token request message or any suitable message) to the authorizing entity computer **118** to check for the issuer's participation and/or to request tokenization. In some embodiments, the token provider computer **110** may request approval to generate the token (e.g., a cryptographic key such as a limited-use key) from the authorizing entity computer **118** without performing identification and/or verification of the user **102**. Accordingly, in some embodiments, the token provider computer **110** may rely on authentication efforts and/or an assertion that the user **102** has been authenticated as provided by the secure server computer **108**.

(196) At step **13**, the authorizing entity computer **118** may use the data received at step **12** to determine whether to approve or decline the token request. The authorizing entity computer **118** may transmit a response (e.g., a token response message or any suitable message) to the token provider computer **110** indicating the request has been approved or declined.

(197) If the request is approved, the token provider computer **110** may be configured to generate a limited-use key (LUK **1104**) and a token (e.g., a token for the credential/payment data) at step **14**. By way of example, in some embodiments, the token provider computer **110** may implement a set of key management functions that manages issuer master derivation keys (MDKs) from which the limited-use keys (LUKs) for cloud-based transactions are derived. In some embodiments, the token

provider computer **110** may use a master derivation key (MDK) associated with issuer (e.g., the issuer associated with the authorizing entity computer **118**) to generate the LUK **1104**. In some embodiments, authorizing entity computer **118** may provide the token provider computer **110** with the issuer's MDK if the MDK is maintained or managed by authorizing entity computer **118**, or authorizing entity computer **118** may generate the LUK **1104** and provide the token provider computer **110** with the LUK **1104**. In either case, the LUK **1104** can be generated based on a key index (e.g., a counter) that acts as a seed for the generation of the LUK, and the key index can be shared between token provider computer **110** and the authorizing entity computer **118** to facilitate processing of transactions using the LUK. The token provider computer **110** (and/or the authorizing entity computer **118**) may maintain and enforce a number of limited-use threshold that limit usage of the LUK **1104** (e.g., for a threshold time period, for a threshold number of transactions, etc.). In some embodiments, once the usage of the LUK **1104** has exhausted or exceeded the set of one or more limited-use thresholds, a further transaction conducted using that LUK **1104** will be declined even if the underlying account is still in good standing. The set of one or more limited-use thresholds to enforce can be determined, for example, by an issuer of the account (and provided in the token response message from the authorizing entity computer **118**) or by the token provider computer **110**.

(198) The set of one or more limited-use thresholds may include at least one of a time-to-live indicating the duration of time for which the LUK **1104** is valid, a predetermined number of transactions for which the LUK **1104** is valid, and/or a cumulative transaction amount indicating the total transaction amount summed across one or more transactions for which the LUK **1104** is valid, or any combination thereof. For example, the LUK **1104** may be valid for a time-to-live of five days, and a transaction conducted using that LUK **1104** after five days have elapsed since the LUK **1104** was generated may be declined. As another example, a LUK **1104** may be valid for a predetermined number of five transactions, and a sixth transaction (and any subsequent transaction) conducted using that LUK **1104** may be declined. As a further example, a LUK **1104** may be valid for a cumulative transaction amount of five hundred dollars, and a transaction conducted using the LUK **1104** after that LUK **1104** has already been used for transactions totaling more than five hundred dollars may be declined.

(199) It should be understood that the limited usage values described above are just examples, and that other usage limits can be used. For example, the number of transactions usage limit can be set to a number in the range of 2 to 10 transactions, or a number in the range of 5 to 50 transactions, etc., and the cumulative transaction amount can be set to a value in the range of \$100 to \$5,000, or a value in the range of \$10 to \$1000, etc.

(200) It should also be noted that in some embodiments, the number of transactions limited-use threshold can be set to one transaction such each LUK **1104** is valid for only one transaction. However, in some embodiments, the network bandwidth available to a portable communication device may be limited, or the portable communication device may not always have uninterrupted network connectivity. As such, the number of transactions limited-use threshold can be set to more than one transaction (e.g., five transactions) in some embodiments, for example, to reduce the frequency and amount of LUK replenishments over time, and hence reduce the amount of network traffic used by the portable communication device over time.

(201) In some embodiments, the set of one or more limited-use thresholds may also include an international usage threshold and a domestic usage threshold indicating separate limits for international transactions versus domestic transactions. For example, the number of transactions that a LUK (e.g., the LUK **1104**) may be valid for can be higher for domestic transactions than for international transactions, if international transactions are deemed to be more risky. The set of one or more limited-use thresholds may also include a low value transaction threshold and a high value transaction threshold indicating separate limits for low value transactions versus high value transactions. For example, the number of transactions that a LUK may be valid for can be higher

for low value transactions (e.g., LUK valid for ten transactions under \$20) than for high value transactions (e.g., LUK valid for five transactions over \$20) such that low value transactions will trigger replenishment of the LUK less frequently than high value transactions.

(202) In some embodiments, the set of one or more limited-use thresholds associated with an account may change when the LUK is replenished such that a new LUK replacing a previous LUK may have one or more different usage limits than the previous LUK. This may occur, for example, based on changes in the consumer spending habits, the location of the portable communication device, or the time of the year, etc. For example, a new LUK may have a higher usage limit if the user has a recent pattern of conducting many high value transactions, or when it is during the holiday season when transaction activity is expected to increase. As another example, a new LUK may have a lower usage limit if the location of the portable communication device indicates that the user may have traveled to a high risk country where fraud is prevalent.

(203) In embodiments in which a LUK (e.g., LUK **1104**) is associated with more than one limited-use thresholds, the usage of the LUK (e.g., LUK **1104**) can be exhausted when any one of the limited-use thresholds is exceeded, or when some combination of the limited-use thresholds is exceeded. Hence, replenishment of the LUK may be triggered when any one of the limited-use thresholds is exceeded or is about to be exceeded, or when some combination of the limited-use thresholds is exceeded or is about to be exceeded.

(204) At step **15**, the token provider computer **110** may transmit the LUK **1104**, the corresponding key index, and the generated token to the secure server computer **108** where the LUK **1104** and token may be stored. The LUK **1104** may be utilized (e.g., by the auxiliary device **104** of FIG. **12** or the secure element device **1302** of FIG. **3**) during a transaction to calculate a transaction cryptogram or limited-use dynamic data such as a verification value to support transactions that use verification values (e.g., dynamic card verification value (dCVV)).

(205) FIG. **12** shows an exemplary system **1200** and process flow diagram illustrating use case in which an auxiliary device is used to emulate a user device (e.g., a payment card), according to some embodiments. The computers of FIG. **12** may be examples of the corresponding computers of FIG. **1**.

(206) Embodiments depicted in FIG. **12** may identify and prevent a skimming attempts between the auxiliary device **104** and the access device **112**. In some embodiments, the messages exchanged between the auxiliary device **104** and the access device **112** may be similar to the messages exchanged between a payment card and the access device **112**, such that the auxiliary device may emulate a payment card. The auxiliary device **104** may act as an entry point for a transaction (e.g. the auxiliary device **104** retrieves the LUK **1104** of FIG. **11** from the secure server computer **108**, initiates the transaction with the access device **112**, etc.). The pickpocketing/skimming risk may originate during the transmission of the credentials (e.g. payment data, card data, account data) from the partner standalone device (e.g. the auxiliary device **104**) to the access device **112** using a skimming device. Embodiments may prohibit out of band key sharing with the partner (neither Merchant's key nor Issuer Key). Embodiments may also prohibit additional storage of any variable from the processing network side.

(207) In some embodiments, the user **102** may walk into a partner's store and initiate a transaction. For example, the user **102** may select a number of items and an agent of the partner may scan the items to obtain a total amount owed by the user **102** to the partner. The total amount may include a total price for the items plus any suitable taxes and/or fees. The process flow described in connection with FIG. **10** may be utilized by the user **102** to provide payment for the transaction. In some embodiments, the auxiliary device **104** (or an application operating on the auxiliary device **104**) may communicate with the access device **112** using card emulation APIs of an operating system of the auxiliary device **104**. Thus, a transaction can be carried out without requiring the use of a secure element (although a secure element can be used as described in FIG. **13**).

(208) At step **1**, the user **102** may authenticate himself using biometric data provided at a biometric

device (e.g., a biometric scanner, a biometric reader, etc.) of the auxiliary device **104** (e.g., or a biometric device in communication with the auxiliary device **104**). By way of example, the user **102** may provide his fingerprint via a fingerprint scanner of the auxiliary device **104**. As another example, the user **102** may utilize a camera of the auxiliary device **104** to provide an image of his face.

(209) At step **2**, the auxiliary device **104** may transmit a token request (e.g., a token request message) to request data such as the token, the LUK **1104**, and the key index associated with the LUK **1104**. In some embodiments, the token request may include the biometric data obtained at step **1**.

(210) At step **3**, the secure server computer **108** may authenticate the user **102** by comparing the received biometric data to previously stored biometric data. If the received biometric data does not match previously provided biometric data, the token request may be denied and the user **102** may be notified (e.g., via the auxiliary device **104**) that the transaction has failed. If the biometric data matches previously stored biometric data the process may proceed to step **4**.

(211) At step **4**, the secure server computer **108** may transmit the token, the LUK **1104**, and the corresponding key index to the auxiliary device **104** in response to authenticating the biometric identity of the user **102**.

(212) At step **5**, the auxiliary device **104** may utilize the LUK to calculate a cryptogram (also referred to as an “interaction cryptogram”) or limited-use dynamic data such as a verification value to support legacy transactions that use verification values (e.g., dynamic card verification value (dCVV)).

(213) At step **6**, the auxiliary device **104** transmits track-2 equivalent data and the cryptogram generated with the LUK to the access device **112**. In some embodiments, the track-2 equivalent data may include an account identifier (e.g., the token), an expiry date, a service code, a PIN verification field, track-2 discretionary data, etc. In some embodiments, the LUK and the corresponding key index may be embedded in the track-2 discretionary data included in the authorization request message.

(214) In some embodiments, the key index associated with the LUK may be the key index include information pertaining to the generation of the LUK as described herein. For example, the key index may be a seed that was used to generate the LUK, and may include time information (e.g., a timestamp) indicating when the LUK was generated, and/or may include a replenishment counter value indicating the number of times that the LUK has been renewed or replenished for a particular account, mobile application, or portable communication device. In some embodiments, the key index may include an application transaction counter value indicating the number of transactions that has been previously conducted by a mobile application of the portable communication device at the time the LUK is generated, or may include a pseudo random number generated by the token provider computer **110** or by a suitable entity such as an issuer involved in processing the transaction.

(215) At step **7**, the access device **112** may generate and send an authorization request message to the transport computer **114** operated by an acquirer. The authorization request message can include the track-2 equivalent data, the LUK, the key index, and the token.

(216) At step **8**, the transport computer **114** may transmit the authorization request message to the processing network computer **116**.

(217) At step **9**, the processing network computer **116** may detokenize the token to obtain a real account identifier (e.g., a personal account number (PAN) associated with the token. In this regard, the processing network computer **116** may communicate with the token provider computer **110**. For example, the processing network computer **116** may provide the token and the cryptogram to the token provider computer **110**. The token provider computer **110** may verify that the token and the cryptogram are associated with one another. If so, the token provider computer **110** may respond with the real account identifier associated with the token and cryptogram.

(218) At step **10**, the processing network computer **116** may forward the authorization request message to the authorizing entity computer **118** (an issuer associated with the real account identifier. After authorizing entity computer **118** receives the authorization request message, the authorization request message may be parsed, and the information in the authorization request message may be verified. For example, authorizing entity computer **118** may verify that the transaction cryptogram was generated by a valid LUK, and that the set of one or more limited-use thresholds associated with the LUK has not been exceeded. In some embodiments, some or all of the information in the authorization request message can also be sent to the token provider computer **110** for verification and processing. For example, if authorizing entity computer **118** does not have the capability to verify the cryptogram, the processing network computer **116** and/or the authorizing entity computer **118** may forward the cryptogram to the token provider computer **110** for verification.

(219) At step **11**, the authorizing entity computer **118** can approve or decline the authorization request message and can transmit an authorization response message back to processing network computer **116**.

(220) At step **12**, the processing network computer **116** may transmit the authorization response message to the transport computer **114**.

(221) At step **13**, the transport computer **114** may transmit the authorization response message to the access device **112**.

(222) At step **14**, the auxiliary device **104** can delete the token, the LUK **1104**, the key index, and/or cryptogram from memory. It should be appreciated that this deletion can occur at any suitable time after performance of the operations of step **6**. In some embodiments, the access device **112** can transmit an indication that the authorization response message of step **14** was received, which can cause the auxiliary device **104** to delete the token, the LUK **1104**, the key index, and/or cryptogram from memory.

(223) FIG. **13** shows an exemplary system **1300** and a process flow diagram illustrating a use case in which secure element device is used to perform a transaction, according to some embodiments. In some embodiments, a secure element device **1302** may be disposed between an auxiliary device **104** and an access device **112**. In some embodiments, the secure element device **1302** may be configured to communicate with the auxiliary device **104** and/or the access device **112** via a short-range wireless communications protocol (e.g., Bluetooth®). The auxiliary device may provide the token and/or or any suitable data for generating a cryptogram to the secure element device. By way of example, a token, the LUK **1104**, and a corresponding key index used to generate the LUK **1104** may be retrieved from the secure server computer **108** and provided to an auxiliary device **104**. In some embodiments, the token, the LUK **1104**, and the corresponding key index used to generate the LUK **1104** may be provided by the auxiliary device **104** to the secure element device **1302** where they may be stored (at least for a time). In some embodiments, the auxiliary device may further provide the secure element device **1302** additional transaction information (e.g., such as track-2 equivalent data). The secure element device **1302** may receive additional access device data (e.g., a terminal identifier, etc.). The remaining computers of FIG. **13** may be examples of the corresponding computers of FIG. **1**.

(224) Embodiments depicted in FIG. **13** may identify and prevent a skimming attempts between the secure element device **1302** and the access device **112**. In some embodiments, the messages exchanged between the secure element device **1302** and the access device **112** may be similar to the messages exchanged between a payment card and the access device **112**, such that the secure element device **1302** may emulate a payment card. The pickpocketing/skimming risk may originate during the transmission of data between the secure element device **1302** and the access device **112** using a skimming device.

(225) In some embodiments, the user **102** may walk into a partner's store and initiate a transaction. For example, the user **102** may select a number of items and an agent of the partner may scan the

items to obtain a total amount owed by the user **102** to the partner. The total amount may include a total price for the items plus any suitable taxes and/or fees. The process flow described in connection with FIG. **10** may be utilized by the user **102** to provide payment for the transaction. (226) At step **1**, the user **102** may authenticate himself using biometric data provided at a biometric device (e.g., a biometric scanner, a biometric reader, etc.) of the auxiliary device **104** (e.g., or a biometric device in communication with the auxiliary device **104**). By way of example, the user **102** may provide his fingerprint via a fingerprint scanner of the auxiliary device **104**. As another example, the user **102** may utilize a camera of the auxiliary device **104** to provide an image of his face.

(227) At step **2**, the auxiliary device **104** may transmit a token request (e.g., a token request message) to request data such as the token, the LUK **1104**, and the key index associated with the LUK **1104**. In some embodiments, the token request may include the biometric data obtained at step **1**.

(228) At step **3**, the secure server computer **108** may authenticate the user **102** by comparing the received biometric data to previously stored biometric data. If the received biometric data does not match previously provided biometric data, the token request may be denied and the user **102** may be notified (e.g., via the auxiliary device **104**) that the transaction has failed. If the biometric data matches previously stored biometric data the process may proceed to step **4**.

(229) At step **4**, the secure server computer **108** may transmit the token, the LUK **1104**, and the corresponding key index to the auxiliary device **104** in response to authenticating the biometric identity of the user **102**.

(230) At step **5**, the auxiliary device **104** may transmit the token, the LUK **1104**, and the corresponding key index to the secure element device **1302**.

(231) At step **6**, the secure element device **1302** may request and receive additional transaction data from the access device **112** (e.g., such as a terminal identifier, transaction data such as a total price, a merchant identifier, etc.).

(232) At step **7**, the secure element device **1302** may utilize the LUK **1104** to calculate a cryptogram (an interaction cryptogram) or limited-use dynamic data such as a verification value to support legacy transactions that use verification values (e.g., dynamic card verification value (dCVV)). The secure element device **1302** may transmit track-2 equivalent data and the cryptogram generated with the LUK **1104** to the access device **112**. In some embodiments, the track-2 equivalent data may include an account identifier (e.g., the token), an expiry date, a service code, a PIN verification field, track-2 discretionary data, etc. In some embodiments, the LUK and the corresponding key index may be embedded in the track-2 discretionary data included in the authorization request message. In some embodiments, the key index associated with the LUK may be the key index include information pertaining to the generation of the LUK as described herein. For example, the key index may be a seed that was used to generate the LUK, and may include time information (e.g., a timestamp) indicating when the LUK was generated, and/or may include a replenishment counter value indicating the number of times that the LUK has been renewed or replenished for a particular account, mobile application, or portable communication device. In some embodiments, the key index may include an application transaction counter value indicating the number of transactions that has been previously conducted by a mobile application of the portable communication device at the time the LUK is generated, or may include a pseudo random number generated by the token provider computer **110** or by a suitable entity such as an issuer involved in processing the transaction.

(233) At step **8**, the secure element device **1302** may delete the token, the LUK **1104**, and the key index from memory.

(234) Steps **9-15** of FIG. **13** substantially match steps **7-13** of FIG. **12** and will not be repeated here for brevity.

(235) FIG. **14** shows an exemplary system **1400** and process flow diagram for utilizing a single use

value to generate a cryptogram, according to at least on embodiment. In some embodiments, a single use value (e.g., a cryptographic key that is derived differently from a limited-use key) may be utilized to generate a cryptogram (e.g., an authorization request cryptogram, also referred to as an “ARQC”). FIG. 14 depicts a process for generating a cryptogram to prevent a pickpocketing/skimming risk at the partner level for transaction processing. In the example depicted in FIG. 14, the user 102 is presumed to have previously performed a biometric (authentication data) enrollment process that has already linked authentication data (e.g., biometric data) to a credential (e.g., a payment account identifier) associated with the user 102. Additionally, the secure server computer 108 is presumed to have previously requested a token for the credential from the token provider computer 110. The token may already be stored at the secure server computer 108 prior to the process depicted in FIG. 14.

(236) At step 1, a user 102 may utilize the auxiliary device 104 to provide authentication data (e.g., a username/password, PIN, biometric data such as a fingerprint, a retina scan, an facial image). In some embodiments, the auxiliary device 104 may include one or more input devices configured to receive the authentication data. For example, the auxiliary device 104 may include a biometric reader, a camera, a retina scanner, and/or the like. The auxiliary device 104 may, in some cases, be provided by a partner (or a merchant) for interfacing with the partner's backend system (e.g., the secure server computer 108).

(237) According to various embodiments, the auxiliary device 104 may be a biometric capable device that meets the security, functional, and/or biometric capture requirements defined by one or more of a token provider, a processing network, and/or an issuer. Generally, the auxiliary device 104 can be capable of capturing one or more of the biometric modalities (e.g. fingerprint, facial imprint, eye/retina scan, voice sample). The auxiliary device 104 may also protect (e.g., encrypt) and transmit the captured biometric data to the secure server computer 108 (e.g., for storage) and the auxiliary device 104 may protect (e.g., encrypt) cardholder data and payment credentials (PCI and PII data). In addition, some embodiments may use an existing POS to process payment transaction. For such embodiments, the auxiliary device 104 may include hardware capable of interacting with an access device 112 using any suitable communications protocol. Depending on the biometric modality or modalities, the hardware may also have additional sensors to detect the proximity of consumers in order to assist in determining whether, and which, consumer is intending to make a payment. Systems discussed in connection with various embodiments may also include client applications (e.g. application software) developed to run on the auxiliary device 104.

(238) At step 2, the auxiliary device 104 may be utilized (e.g., via the client application) to provide the authentication data (e.g., the biometric data) to the secure server computer 108. In some embodiments, the authentication data may be encrypted by the auxiliary device 104 and decrypted by the secure server computer 108 (e.g., using a shared secret, etc.).

(239) At step 3, the secure server computer 108 compare the received authentication data (e.g., the biometric data) to previously stored authentication data (e.g., biometric data associated with the user 102). If the received authentication data matches previously stored authentication data associated with the user 102, the process may proceed to step 4. Otherwise, the user 102 may be notified (e.g., via the auxiliary device 104) that the authentication has failed.

(240) At step 4, the secure server computer 108 may request payment data by calling the token provider computer 110 using a dedicated application programming interface (e.g., a GetPaymentData API). The token provider computer 110 may be configured to generate a transaction authentication verification value (TAVV) and a single use value (SUV) (e.g., an encryption key, SUV 1402) based at least in part on receiving a request via the dedicated API. The token provider computer 110 (or another suitable component of system 1400) may derive SUV 1402 from a Unique Derivation Key (UDK) (e.g., associated with an issuer) and a transaction counter. In some embodiments, the token provider computer 110 may include, or be in communication with a hardware security module (HSM) (not depicted) within which the SUV may

be derived.

(241) At step 5, the token server **306** may send a TAVV, a token expiry date associated with the token (e.g., the token already stored at the secure server computer **108**), and the SUV to the secure server computer **108**. The secure server computer **108** may store the TAVV and the SUV in memory for subsequent use.

(242) At step 6, the secure server computer **108** sends the token, the TAVV, a token expiry date, and SUV **1402** to the auxiliary device **104**.

(243) At step 7, the auxiliary device **104** may receive at least an unpredictable number from the access device **112**. The unpredictable number may be received in command data of a particular message such as a GPO (Get Processing Options) command message.

(244) At step 8, the auxiliary device **104** may compute a hash value of dynamic data (e.g., the unpredictable number and the SUV **1402**) and transmit some portion of the hash value to the access device **112**. In some embodiments, the auxiliary device **104** may compute the hash value by extracting the unpredictable number (UN) from the command data (e.g. the last 4 bytes of the command data). Once extracted, the unpredictable number may be concatenated with the SUV **1402**. The concatenated value may be utilized as input into a hashing algorithm to generate a hash value. In some embodiments, the auxiliary device **104** may be configured to utilize only a portion of the calculated hash value as an authorization request cryptogram (ARQC). By way of example, the auxiliary device **104** may extract the leading 8 bytes of the hash value and utilize those 8 bytes as an ARQC. The auxiliary device **104** may transmit any suitable combination of the token, the transaction counter, the ARQC, the unpredictable number, and transaction data to the access device **112** at step 8.

(245) At step 9, the access device **112** may generate an authorization request message including the token, the transaction counter, the ARQC, the unpredictable number, and transaction data. The access device **112** may transmit the authorization request message to the transport computer **114**.

(246) At step 10, the transport computer **114** may transmit the authorization request message including the ARQC and other information to the processing network computer **116**. According to various embodiments, the token provider computer **110** and the processing network computer **116** may be managed by or integrated with a same entity (e.g., a payment processor).

(247) At step 11, the processing network computer **116** may retrieve the SUV **1402** (e.g., from the token provider computer **110**) and may compute the hash value in the manner described above in connection with step 8. In some embodiments, the processing network computer **116** may provide the transaction counter to the token provider computer **110**. The token provider computer **110** may increment and store the counter such that the next single use value may be derived using a different counter value (thus ensuring uniqueness between single use values). The processing network computer **116** may compare a portion of the computed hash value (e.g., the computed ARQC) with the ARQC received in the authorization request message. If the values match, the process may proceed to step 12. Otherwise, the authorization request message may be declined. In some embodiments, the processing network computer **116** may perform a conversion from a first transaction data format to a second transaction data format as discussed above in connection with FIG. 1 prior to step 12.

(248) At step 12, the processing network computer **116** may transmit the authorization request message to the authorizing entity computer **118**.

(249) At step 13, the authorizing entity computer **118** can approve or decline the authorization request message and can transmit an authorization response message back to processing network computer **116**. The authorization response message may be in any suitable format (e.g., the second transaction data format).

(250) At step 14, the processing network computer **116** may transmit the authorization response message to the transport computer **114**. It should be appreciated that, in some embodiments, the processing network computer **116** may convert the authorization response message from a second

transaction data format to a first transaction data format prior to the transmission.

(251) At step **15**, the transport computer **114** may transmit the authorization response message to the access device **112**.

(252) At step **16**, the auxiliary device **104** can delete the token, the SUV **1402**, the token expiry date, and/or the ARQC from memory. It should be appreciated that this deletion can occur at any suitable time after performance of the operations of step **8**. In some embodiments, the access device **112** can transmit an indication that the authorization response message of step **15** was received, which can cause the auxiliary device **104** to delete this data from memory.

(253) By utilizing the single use key and an unpredictable number from the access device **112** to derive unique ARQCs, the system **1400** can protect against replay and relay attacks.

(254) FIG. **15** shows another exemplary system **1500** and process flow diagram for utilizing a single use value to generate a cryptogram, according to at least one embodiment. In the example depicted in FIG. **15**, the user **102** is presumed to have previously performed a biometric (authentication data) enrollment process that has already linked authentication data (e.g., biometric data) to a credential (e.g., a payment account identifier) associated with the user **102**. Additionally, the secure server computer **108** is presumed to have previously requested a token for the credential from the token provider computer **110**. The token may already be stored at the secure server computer **108** prior to the process depicted in FIG. **15**. Steps **1-3** of FIG. **15** are substantially similar to steps **1-3** of FIG. **14** and will not be repeated here for brevity.

(255) At step **4**, the secure server computer **108** (e.g. a backend server for the partner, the token requestor) sends a request (e.g., via a dedicated API, via a specific message such as an encryption key request message) to the token provider computer **110** requesting an encryption key. The request may include, among other things, the token associated with the credential of user **102** and an application transaction counter (ATC)). According to some embodiments, the secure server computer **108** may track the ATC as the credential is utilized for transaction over time.

(256) At step **5**, the token provider computer **110** may derive a single use key (SUK) (e.g., SUK **1502**). In some embodiments, the SUK may be derived in a hardware security module (HSM) of the token provider computer **110** (not depicted). According to various embodiments, SUK **1502** may be derived from a Unique Derivation Key (UDK) associated with the issuer and the ATC provided by the secure server computer **108**. The token provider computer **110** may transmit the SUK **1502** to the secure server computer **108** (e.g., via an encryption key response message). The secure server computer **108** may store the SUK **1502** for subsequent use. In some embodiments, the secure server computer **108** can pre-fetch SUKs ahead of time. For example, multiple SUKs can be obtained and stored at the secure server computer **108**. The process for obtaining multiple SUKs may be substantially similar to the process for obtaining multiple cryptograms discussed in connection with FIG. **7**.

(257) At step **6**, the auxiliary device **104** in communication with the access device **112** may send a request for payment details to the access device **112**. The access device **112** may respond with an unpredictable number, among other terminal data (e.g., transaction amount), at step **7**.

(258) At step **8**, the auxiliary device **104** may transmit the data received from the access device **112** to the secure server computer **108** to request a cryptogram from the secure server computer **108**.

(259) At step **9**, the secure server computer **108** may generate a cryptogram (e.g., an ARQC), using the SUK **1502**, the token, the ATC, and the unpredictable number in the manner described above in connection with FIG. **14**. In some embodiments, an ARQC may be generated using the SUK **1502**, the token, the ATC, the unpredictable number, and a transaction amount provided by the access device **112**. The secure server computer **108** may return the cryptogram to the auxiliary device **104**.

(260) Steps **10-17** of FIG. **15** are substantially similar to steps **9-16** of FIG. **14** and will not be repeated here for brevity.

(261) It should be appreciated that, in the examples provided in FIGS. **1-15**, data transmitted between any two components (e.g., any suitable combination of computers or devices) may be

encrypted using a transport key (e.g. a symmetric transport key or an asymmetric transport key). For example, the transmitter of the data may encrypt the data using a symmetric transport key and the receiver of the data may utilize the symmetric transport key to decrypt. It should be appreciated that different transport keys may be utilized between each pair of devices in communication with one another.

(262) FIG. 16 shows an exemplary auxiliary device **1600**, in accordance with at least one embodiment. Auxiliary device **1600** may be an example of the auxiliary device **104** of the figures above. The auxiliary device **1600** may comprise a processor **1600A**, a network interface **1600B**, a data store **1600C**, input/output devices **1600D**, and a computer readable medium **1600E**.

(263) The network interface **1600B** may be any suitable interface that enables the auxiliary device **1600** to communicate with access devices, secure server computers, secure element devices, and the like.

(264) In some embodiments, the input/output devices **1600D** may include a keyboard, touchpad, mouse, printer, biometric device(s) (e.g., biometric reader, retina scanner, fingerprint scanner, etc.).

(265) The computer readable medium **1600E** may comprise a data processing module **1600F**, an enrollment module **1600G**, a transaction module **1600H**, a cryptogram generation module **1600I**, and an interface module **1600J**, and any other suitable software module. The computer readable medium **1600E** may also comprise code, executable by the processor **1600A** for implementing any of functions described herein with respect to an auxiliary device.

(266) The data processing module **1600F** may comprise code that causes the processor **1600A** to process data. By way of example, the data processing module **1600F** may be configured to cause the processor **1600A** to receive any suitable data. By way of example, the data processing module **1600F** may be configured to receive any suitable authentication data (e.g., username/password, biometric data, one-time passwords, etc.). In some embodiments, the data processing module **1600F** may comprise code that causes the processor **1600A** to compare received authentication data to stored authentication data (e.g., authentication data store in data store **1600C** or obtained by the data processing module **1600F** from another source accessible to the secure server computer **1700**).

(267) The enrollment module **1600G** may comprise code that causes the processor **1600A** to perform any suitable operations associated with an auxiliary device and discussed above in the enrollment processes of FIGS. 2, 8, and 9, for example.

(268) The transaction module **1600H** may comprise code that causes the processor **1600A** to perform transaction. For example, the transaction module **1600H** may contain logic that causes the processor **1600A** to request authentication of a user via authentication data received from user input. The transaction module **1600H** may be able request a token and/or a cryptogram from a remote system (e.g., the secure server computer **108** of FIG. 1). The transaction module **1600H** may include code that, when executed, causes the processor **1600A** to call code associated with the cryptogram generation module **1600I**. The transaction module **1600H** may include code that causes the processor **1600A** to transmit data to a secure server computer, an access device, or a secure element device. In some embodiments, the transaction module **1600H** may be configured to cause the processor **1600A** to exchange data with an access device in a similar manner as a payment card. In some embodiments, the transaction module **1600H** may be configured to cause the processor **1600A** to transmit and/or receive data to/from a secure server computer and/or an access device.

(269) In some embodiments, the cryptogram generation module **1600I** may be configured to cause the processor **1600A** to receive a limited-use key and/or a single key (e.g., from a secure server computer). The cryptogram generation module **1600I** may be configured with code that may cause the processor **1600A** to generate one or more cryptograms (e.g., an interaction cryptogram, an ARQC, etc.) utilizing at least a limited-use key or a single use key. For example, the cryptogram generation module **1600I** may cause the processor **1600A** to generate a cryptogram according to the methods discussed above in connection with FIGS. 12 and 14.

(270) In some embodiments, the interface module **1600J** may comprise code that causes the

processor **1600A** to provide one or more interfaces associated with the functions described above in connection with an auxiliary. By way of example, the interface module **1600J** may provide interfaces for providing authentication data (e.g., a credential such as payment data, a one-time password, biometric data, or other suitable user input for enrollment or authentication purposes). The interface module **1600J** may cause the processor **1600A** to provide any suitable interface to enable the processor **1600A** to perform the functions described above in connection with the FIGS. **1-15**.

(271) FIG. **17** shows an exemplary secure server computer, in accordance with at least one embodiment. Secure server computer **1700** may be an example of the secure server computer **108** of the figures above. The secure server computer **1700** may comprise a processor **1700A**, a network interface **1700B**, a data store **1700C**, and a computer readable medium **1700E**.

(272) The data store **1700C** may be configured to store one or more tokens, cryptograms, cryptographic keys (e.g., a limited-use key, a single use value, etc.), user account data, biometric data, authentication data, or any suitable data for performing the functions described above in connection with FIGS. **1-16**.

(273) The computer readable medium **1700E** may comprise a data processing module **1700F**, an enrollment module **1700G**, a transaction module **1700H**, a cryptogram generation module **1700I**, and an interface module **1700J**, and any other suitable software module. The computer readable medium **1700E** may also comprise code, executable by the processor **1700A** for implementing any of functions described herein with respect to a secure server computer.

(274) The network interface **1700B** may be any suitable interface that enables the secure server computer **1700** to communicate with auxiliary devices, token provider computers, and the like.

(275) The data processing module **1700F** may comprise code that causes the processor **1700A** to process data. By way of example, the data processing module **1700F** may be configured to cause the processor **1700A** to receive any suitable data. By way of example, the data processing module **1700F** may be configured to receive any suitable authentication data (e.g., username/password, biometric data, one-time passwords, etc.). In some embodiments, the data processing module **1700F** may comprise code that causes the processor **1700A** to compare received authentication data to stored authentication data (e.g., authentication data store in data store **1700C** or obtained by the data processing module **1700F** from another source accessible to the secure server computer **1700**).

(276) The enrollment module **1700G** may comprise code that causes the processor **1600A** to perform any suitable operations associated with a secure server computer and discussed above in the enrollment processes of FIGS. **2, 8, and 9**, for example.

(277) The transaction module **1700H** may comprise code that causes the processor **1700A** to perform transaction. For example, the transaction module **1700H** may contain logic that causes the processor **1700A** to request a token and/or a cryptogram from a remote system (e.g., the secure server computer **108** of FIG. **1**). The transaction module **1700H** may include code that, when executed, causes the processor **1700A** to call code associated with the cryptogram generation module **1700I**. In some embodiments, the transaction module **1700H** may be configured to cause the processor **1700A** to transmit and/or receive data to/from an auxiliary device and/or a token provider computer.

(278) In some embodiments, the cryptogram generation module **1600I** may be configured to cause the processor **1700A** to receive a limited-use key and/or a single key (e.g., from a secure server computer). The cryptogram generation module **1600I** may be configured with code that may cause the processor **1700A** to generate one or more cryptograms (e.g., an interaction cryptogram, an ARQC, etc.) utilizing at least a limited-use key or a single use key. For example, the cryptogram generation module **1700I** may cause the processor **1700A** to generate a cryptogram according to the methods discussed above in connection with FIGS. **12 and 15**.

(279) In some embodiments, the interface module **1700J** may comprise code that causes the processor **1700A** to provide one or more interfaces associated with the functions described above in

connection with a secure server computer. By way of example, the interface module **1700J** may provide interfaces associated with an online website associated with a partner (e.g., an electronic marketplace provider, a merchant, etc.). These interfaces may enable the user to enter user account data (e.g., authentication data, payment data, etc.). The user account data may be stored in the data store **1700C** for subsequent use (e.g., for authentication purposes, to retrieve payment data, etc.). (280) FIG. **18** shows an exemplary secure element device, in accordance with at least one embodiment. Secure element device **1800** may be an example of the secure element device **1302** of FIG. **13**. The secure element device **1800** may comprise a processor **1800A**, a network interface **1800B**, a secure data store **1800C**, and a computer readable medium **1800E**. (281) The secure data store **1800C** may be configured to store one or more tokens, cryptograms, cryptographic keys (e.g., a limited-use key, a single use value, etc.), transaction data, access device data, or any suitable data for performing the functions described above in connection with FIG. **13**. Generally, any data for generating any cryptogram discussed above may be stored in the secure data store **1800C**. Data stored in the secure data store **1800C** may be encrypted or otherwise protected such that only the processor **1800A** and/or the components of the secure element device **1800** may access the stored data.

(282) The computer readable medium **1800E** may comprise a data processing module **1800F** and a cryptogram generation module **1800G**, and any other suitable software module. The computer readable medium **1800E** may also comprise code, executable by the processor **1800A** for implementing any of functions described herein with respect to a secure element device.

(283) The network interface **1800B** may be any suitable interface that enables the secure element device **1800** to communicate with auxiliary devices, access devices, and the like.

(284) The data processing module **1800F** may comprise code that causes the processor **1800A** to process data. By way of example, the data processing module **1800F** may be configured to cause the processor **1800A** to receive any suitable data such as transaction data, token data (e.g., a token, a token expiry date, etc.), one or more cryptographic keys (e.g., a limited-use key, a single use key, etc.). In some embodiments, the data processing module **1800F** may comprise code that causes the processor **1800A** to store the received data in the secure data store **1800C**.

(285) In some embodiments, the cryptogram generation module **1800G** may be configured to cause the processor **1800A** to receive a limited-use key and/or a single key (e.g., from an auxiliary device). The cryptogram generation module **1800G** may be configured with code that may cause the processor **1800A** to generate one or more cryptograms (e.g., an interaction cryptogram, an ARQC, etc.) utilizing at least a limited-use key or a single use key. For example, the cryptogram generation module **1800G** may cause the processor **1800A** to generate a cryptogram according to the methods discussed above in connection with FIGS. **12** and **15**. In some embodiments, the generated cryptogram may be transmitted to an auxiliary device and/or an access device.

Technical Advantages

(286) As provided above, a consumer may conduct a transaction using their credentials stored on the partner server (e.g., a secure server computer) by merely presenting their authentication data at a physical location (e.g., via an auxiliary device). For example, biometrics, and specifically biometrics that are not matched on the consumer's device, may provide a mechanism for a true seamless and potentially frictionless (in the case of modalities that do not require physical contact) interaction at a point of sale. Payment can occur without any need for a card, phone, wearable, or any other consumer device as long as the point of interaction is able to recognize the consumer and retrieve a credential that can be linked to that consumer. Embodiments discussed herein for match-in-cloud biometric solutions aids device manufacturers, software developers, payment service providers, merchants, and acquirers in providing a reliable, convenient, secure payment experience.

(287) As discussed above, physical user device are often needed to conduct transaction at access device, but the need to carry a physical user device to access a resource at an access device can be cumbersome. Utilizing the techniques provided herein, a transaction may be conducted without the

need of a physical user device, utilizing the systems discussed herein.

(288) Furthermore, embodiments provide that existing legacy access devices may be utilized for transactions despite these devices lacking the capability of conducting transactions using token or credentials that originate from a source other than a user device. By utilizing the techniques disclosed herein, these legacy access devices can be used to perform a greater number of different types of transactions than would otherwise be available.

(289) The techniques disclosed herein provide for a number of efficiency advantages. By way of example, traditionally, authentication requests and requests for tokens may be conducted utilizing processes and initiated using separate messages. Embodiments provide efficiency benefits by initiating both authentication and token procurement utilizing a single message. As another efficiency example, the ability to pre-fetch a number of cryptograms and stored those cryptograms for subsequent use enables transactions to be conducted quicker as a separate token request for each token would no longer be required. By utilizing previously obtained tokens stored at the secure server computer, each subsequent transaction may be performed in less time by retrieving the token from the secure server computer rather than requesting a new token upon each transaction.

(290) Any of the computing devices described herein may be an example of a computer system that may be used to implement any of the entities or components described above. The subsystems of such a computer system may be interconnected via a system bus. Additional subsystems include a printer, keyboard, storage device, and monitor, which is coupled to display adapter. Peripherals and input/output (I/O) devices, which couple to I/O controller, can be connected to the computer system by any number of means known in the art, such as a serial port. For example, I/O port or external interface can be used to connect the computer apparatus to a wide area network such as the Internet, a mouse input device, or a scanner. The interconnection via system bus may allow the central processor to communicate with each subsystem and to control the execution of instructions from system memory or the storage device, as well as the exchange of information between subsystems. The system memory and/or the storage device may embody a computer-readable medium.

(291) As described, the inventive service may involve implementing one or more functions, processes, operations or method steps. In some embodiments, the functions, processes, operations or method steps may be implemented as a result of the execution of a set of instructions or software code by a suitably-programmed computing device, microprocessor, data processor, or the like. The set of instructions or software code may be stored in a memory or other form of data storage element which is accessed by the computing device, microprocessor, etc. In other embodiments, the functions, processes, operations or method steps may be implemented by firmware or a dedicated processor, integrated circuit, etc.

(292) Any of the software components or functions described in this application, may be implemented as software code to be executed by a processor using any suitable computer language such as, for example, Java, C++ or Perl using, for example, conventional or object-oriented techniques. The software code may be stored as a series of instructions, or commands on a computer readable medium, such as a random access memory (RAM), a read only memory (ROM), a magnetic medium such as a hard-drive or a floppy disk, or an optical medium such as a CD-ROM. Any such computer readable medium may reside on or within a single computational apparatus, and may be present on or within different computational apparatuses within a system or network.

(293) The above description is illustrative and is not restrictive. Many variations of the invention may become apparent to those skilled in the art upon review of the disclosure. The scope of the invention can, therefore, be determined not with reference to the above description, but instead can be determined with reference to the pending claims along with their full scope or equivalents.

(294) One or more features from any embodiment may be combined with one or more features of

any other embodiment without departing from the scope of the invention.

(295) A recitation of “a”, “an” or “the” is intended to mean “one or more” unless specifically indicated to the contrary.

(296) All patents, patent applications, publications, and descriptions mentioned above are herein incorporated by reference in their entirety for all purposes. None is admitted to be prior art.

Claims

1. A method, comprising: receiving, by a processing network computer from an access device, an authorization request message comprising data in a first transaction data format; converting, by the processing network computer, the data in the first transaction data format to be in a second transaction data format; transmitting, by the processing network computer, the authorization request message including the data in the second transaction data format to an authorizing entity computer for authorization; receiving, by the processing network computer from the authorizing entity computer, an authorization response message comprising data in the second transaction data format; converting, the data in the second transaction data format to be in the first transaction data format; and transmitting the authorization response message including data in the first transaction data format to the access device via a transport computer.
2. The method of claim 1, wherein the data is converted from the first transaction data format to the second transaction data format in response to identifying an indicator that an auxiliary device in communication with the access device has been utilized to generate the authorization request message.
3. The method of claim 2, wherein the auxiliary device is programmed to authenticate a user conducting a transaction at the access device.
4. The method of claim 1, wherein the first transaction data format is a card on file transaction data format and wherein the second transaction data format is a card not present transaction data format.
5. The method of claim 1, wherein the first transaction data format comprises track 1 and track 2 data of a payment device.
6. The method of claim 1, wherein converting from the first transaction data format to the second transaction data format comprises deleting data from one data field and storing the data in a different data field.
7. The method of claim 1, wherein the first transaction data format of the authorization request message is indicated by a first electronic commerce indicator value.
8. A method, comprising: receiving, by a processing network computer from an access device, an authorization request message comprising data in a first transaction data format; converting, by the processing network computer, the data in the first transaction data format to be in a second transaction data format; and transmitting, by the processing network computer, the authorization request message including the data in the second transaction data format to an authorizing entity computer for authorization, wherein the first transaction data format of the authorization request message is indicated by a first electronic commerce indicator value, and wherein the second transaction data format of the authorization request message is indicated by a second electronic commerce indicator value that is different from the first electronic commerce indicator value.
9. The method of claim 1, wherein the first transaction data format is an e-commerce transaction data format and the second transaction data format is a contactless transaction data format.
10. The method of claim 1 wherein the authorization request message is for a payment transaction.
11. The method of claim 1, wherein the authorization request message comprises a transaction amount.
12. A processing network computer, comprising: a processor; and a computer readable medium coupled to the processor, the computer readable medium comprising code executable by the processor to cause the processing network computer to: receive an authorization request message

comprising data in a first transaction data format from an access device; convert the data in the first transaction data format to be in a second transaction data format; and transmit the authorization request message including the data in the second transaction data format to an authorizing entity computer for authorization, wherein the computer readable medium further comprises code executable by the processor to cause the processing network computer to: receive an authorization response message comprising data in the second transaction data format from the authorizing entity computer; convert the data in the second transaction data format to be in the first transaction data format; and transmit the authorization response message including data in the first transaction data format to the access device via a transport computer.

13. The processing network computer of claim 12, wherein the data is converted from the first transaction data format to the second transaction data format in response to identifying an indicator that an auxiliary device in communication with the access device has been utilized to generate the authorization request message.

14. The processing network computer of claim 13, wherein the auxiliary device is different from a user device.

15. The processing network computer of claim 14, wherein the first transaction data format is a card on file transaction data format and wherein the second transaction data format is a card not present transaction data format.

16. The processing network computer of claim 12, wherein the first transaction data format comprises track 1 and track 2 data of a payment device.

17. The processing network computer of claim 12, wherein converting from the first transaction data format to the second transaction data format comprises deleting data from one data field and storing the data in a different data field.

18. The processing network computer of claim 12, wherein the first transaction data format of the authorization request message is indicated by a first electronic commerce indicator value.

19. A processing network computer, comprising: a processor; and a computer readable medium coupled to the processor, the computer readable medium comprising code executable by the processor to cause the processing network computer to: receive an authorization request message comprising data in a first transaction data format; convert the data in the first transaction data format to be in a second transaction data format; and transmit the authorization request message including the data in the second transaction data format to an authorizing entity computer for authorization, wherein the first transaction data format of the authorization request message is indicated by a first electronic commerce indicator value, and wherein the second transaction data format of the authorization request message is indicated by a second electronic commerce indicator value that is different from the first electronic commerce indicator value.

20. The processing network computer of claim 12, wherein the first transaction data format is an e-commerce transaction data format and the second transaction data format is a contactless transaction data format.
