

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396530
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Jin; Shimin

External lamp structure

Abstract

An external lamp structure includes a light strip and two first fixing structures. The light strip is integrally formed or detachably connected with the two first fixing structures. The two first fixing structures are sleevedly provided on both ends of the light strip, respectively. The two first fixing structures are configured to mount the light strip on an umbrella structure.

Inventors:	Jin; Shimin (Taizhou, CN)
Applicant:	Linhai Zhongtian Electronic Appliance co.,ltd (Taizhou, CN)
Family ID:	1000008779187
Assignee:	Linhai Zhongtian Electronic Appliance co.,ltd (Taizhou, CN)
Appl. No.:	18/916637
Filed:	October 15, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20250031813 A1	Jan. 30, 2025

Foreign Application Priority Data

CN	202420270579.2	Feb. 04, 2024
----	----------------	---------------

Publication Classification

Int. Cl.: F21S4/20 (20160101); A45B3/04 (20060101); F21V19/00 (20060101); F21V19/04 (20060101)

U.S. Cl.:

Field of Classification Search

CPC: A45B (2200/1018); F21S (4/20); F21S (4/22); F21S (4/24); F21S (4/26); F21S (4/28)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
11098861	12/2020	Wang	N/A	N/A
2007/0189002	12/2006	Thode	362/102	A45B 3/04

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
209594935	12/2018	CN	N/A
2015124121	12/2014	WO	N/A

Primary Examiner: Gramling; Sean P

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application claims the benefit of priority from Chinese Patent Application No. 202420270579.2, filed on Feb. 4, 2024. The content of the aforementioned application, including any intervening amendments thereto, is incorporated herein by reference in its entirety.

TECHNICAL FIELD

(2) This application relates to lighting facilities, and more particularly to an external lamp structure.

BACKGROUND

(3) In the prior art, the light strip is fixed to the umbrella mainly through the following fixing methods. (1) A variety of lamps are directly fastened to an umbrella with a rope, which is not elegant and reliable. (2) For many low-end umbrellas, holes are made in their ribs for mounting the light strips, and the light is radiated through the holes. Such method has a main limitation that it is inconvenient for the users to replace the light strips in the case of failure. (3) Middle-end and high-end umbrellas generally use built-in light strips, which is beautiful but expensive, and the built-in light strips cannot be replaced in the case of failure.

SUMMARY

(4) An object of this application is to provide an external lamp structure, so as to solve problems that it is required to select different light strips for different light-equipped parasols. This application has advantages of independent assembly and disassembly of light strips, convenient maintenance and repair, and elegant appearance and low cost, and is suitable for various grades of parasols.

(5) In order to achieve the above objectives, the following technical solutions are adopted.

(6) This application provides an external lamp structure, comprising: a light strip; and two first fixing structures; wherein the light strip is integrally formed or detachably connected with the two first fixing structures; one of the two first fixing structures is sleevedly provided on a first end of

the light strip, and the other of the two first fixing structures is sleevedly provided on a second end of the light strip; and the two first fixing structures are configured to mount the light strip on an umbrella structure.

(7) In an embodiment, the external lamp structure further comprises a second fixing structure; wherein the second fixing structure is sleevedly provided on a middle of the light strip; and the second fixing structure is configured to mount the light strip on the umbrella structure.

(8) In an embodiment, each of the two first fixing structures comprises: a first top plate; a first bottom plate; and two first side plates; wherein the two first side plates are arranged opposite to each other; a first side of the first top plate is connected with a top of one of the two first side plates, and a second side of the first top plate is connected with a top of the other of the two first side plates; a first side of the first bottom plate is connected with a bottom of one of the two first side plates, and a second side of the first bottom plate is connected with a bottom of the other of the two first side plates; the first top plate, the first bottom plate and the two first side plates are configured to form a first space; a first end of the first space is configured for a rib of the umbrella structure and the light strip to pass through, and a second end of the first space is configured for the rib of the umbrella structure to pass through.

(9) In an embodiment, the first end of the first space is larger than the second end of the first space in size.

(10) In an embodiment, the first top plate is provided with a positioning groove; the rib of the umbrella structure is provided with a first positioning hole corresponding to the positioning groove; and the positioning groove and the first positioning hole are configured to allow a first connecting structure to pass therethrough to realize a connection between each of the two first fixing structures and the rib of the umbrella structure.

(11) In an embodiment, the first bottom plate is provided with a first protrusion; and the first protrusion is configured to limit the first end and the second end of the light strip.

(12) In an embodiment, each of the two first fixing structures or the second fixing structure comprises: a second top plate assembly; a second bottom plate; and two second side plates; wherein the two second side plates are arranged opposite to each other; a first side of the second top plate assembly is connected with a top of one of the two second side plates, and a second side of the second top plate assembly is connected with a top of the other of the two second side plates; a first side of the second bottom plate is connected with a bottom of one of the two second side plates, and a second side of the second bottom plate is connected with a bottom of the other of the two second side plates; and the second top plate assembly, the second bottom plate and the two second side plates are configured to form a second space configured for the rib of the umbrella structure and the light strip to pass through.

(13) In an embodiment, a first open groove is provided between the second top plate assembly and each of the two second side plates.

(14) In an embodiment, the second top plate assembly is provided with a first fastener assembly; the rib of the umbrella structure is provided with a second positioning hole; the first fastener assembly is configured to extend into the second positioning hole to realize connection of each of the two first fixing structures or the second fixing structure and the rib of the umbrella structure.

(15) In an embodiment, the second top plate assembly comprises two second top plates; the first fastener assembly comprises two first fasteners; a first side of one of the second top plates is connected with the top of one of the two second side plates, and a first side of the other of the two second top plates is connected with the top of the other of the two second side plates; a first gap is provided between a second side of one of the two second top plates and a second side of the other of the two second top plates; one of the two first fasteners is provided on one of the two second top plates, and the other of the two first fasteners is provided on the other of the second top plates; a second gap is provided between the two first fasteners; the two first fasteners are configured to extend into the second positioning hole on the rib of the umbrella structure to realize the connection

between each of the two first fixing structures or the second fixing structure and the rib of the umbrella structure.

(16) In an embodiment, each of the two first fixing structures comprises: a sliding block; a third bottom plate; and two third side plates; wherein the two third side plates are arranged opposite to each other; a first side of the third bottom plate is connected with a bottom of one of the two third side plates, and a second side of the third bottom plate is connected with a bottom of the other of the two third side plates; the third bottom plate and the two third side plates are configured to form a first U-shaped structure, and a sliding rail is provided in the first U-shaped structure; the sliding block is in slidable connection with the sliding rail; an end of the sliding rail and an end of the sliding block are configured to limit the first end and the second end of the light strip; the sliding block is provided with a second fastener; the rib of the umbrella structure is provided with a third positioning hole; the second fastener is configured to extend into the third positioning hole; the sliding block is provided with a first connecting hole; the rib of the umbrella structure is provided with a first fixing hole corresponding to the first connecting hole; and the first connecting hole and the first fixing hole are configured to allow a first rivet to pass therethrough.

(17) In an embodiment, the end of the sliding block is provided with a flange.

(18) In an embodiment, each of the two first fixing structures comprises: a first fixing body; and a rotary fastener; wherein the first fixing body is provided with a first clamping groove and a second clamping groove; the rotary fastener is in snap-fit connection with the first clamping groove; the light strip is located in the second clamping groove; the rotary fastener is provided with a second connecting hole; the rib of the umbrella structure is provided with a second fixing hole corresponding to the second connecting hole; and the second connecting hole and the second fixing hole are configured to allow a second rivet to pass therethrough.

(19) In an embodiment, a side wall of the rotary fastener is provided with at least one stop block; an inner wall of the first clamping groove is provided with an annular clamping strip; and the annular clamping strip is provided with a notch, and the number of the notch is the same as the number of the at least one stop block.

(20) In an embodiment, the rotary fastener is provided with a toggling part.

(21) In an embodiment, a side of the toggling part away from the rotary fastener and facing toward a circumferential surface of the rotary fastener is provided with a bump.

(22) In an embodiment, a first notch is formed between the bump and the rotary fastener.

(23) In an embodiment, each of the at least one stop block is provided with a second protrusion; and the annular clamping strip is provided with a recess fitting the second protrusion.

(24) In an embodiment, each of the two first fixing structures comprises a second fixing body; the second fixing body is provided with a third clamping groove; the light strip is located in the third clamping groove; the second fixing body is provided with a third connecting hole; the rib of the umbrella structure is provided with a fourth positioning hole corresponding to the third connecting hole; the third connecting hole and the fourth positioning hole are configured to allow a second connecting structure to pass therethrough to realize the connection between each of the two first fixing structures and the rib of the umbrella structure.

(25) In an embodiment, each of the two first fixing structures or the second fixing structure comprises: a fourth bottom plate; and two fourth side plates; wherein the two fourth side plates are arranged opposite to each other; a first side of the fourth bottom plate is connected with a bottom of one of the two fourth side plates, and a second side of the fourth bottom plate is connected with a bottom of the other of the two fourth side plates; the fourth bottom plate and the two fourth side plates are configured to form a second U-shaped structure; an inner side of each of the two fourth side plates is provided with a third fastener, and the number of the third fastener is two; the third fastener of one of the two fourth side plates is close to a first end of the light strip, and the third fastener of the other of the two fourth side plates is close to a second end of the light strip; the rib of the umbrella structure is provided with a fifth positioning hole; and the third fastener is

configured to extend into the fifth positioning hole to realize the connection of each of the two first fixing structures or the second fixing structure and the rib of the umbrella structure.

(26) The present disclosure has the following beneficial effects.

(27) The external lamp structure is provided. The light strip can be externally fixed on the rib of the umbrella, which solves problems that a parasol with lights needs to be mounted with different light strips. In addition, this application has advantages of independent disassembly and convenient maintenance, which is convenient for electrification of the parasol.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) To illustrate the technical solutions of the embodiments of this application or the prior art more clearly, the accompanying drawings required in the following description will be briefly introduced below. It is obvious that presented in the following accompanying drawings are only some embodiments of this application, and for those of ordinary skill in the art, other accompanying drawings can also be obtained according to these drawings without making creative effort.

(2) FIG. 1 is an exploded view of an external lamp structure according to Embodiment 1 of the present disclosure and a rib.

(3) FIG. 2 is a sectional view of the external lamp structure according to Embodiment 1 of the present disclosure and the rib.

(4) FIG. 3 is an exploded view of the external lamp structure according to Embodiment 2 of the present disclosure and the rib.

(5) FIG. 4 is a sectional view of the external lamp structure according to Embodiment 2 of the present disclosure and the rib.

(6) FIG. 5 is a structural diagram of a first fixing structure according to Embodiment 2 of the present disclosure.

(7) FIG. 6 is a structural diagram of a second fixing structure according to Embodiment 2 of the present disclosure.

(8) FIG. 7 is an exploded view of the external lamp structure according to Embodiment 3 of the present disclosure (without the second fixing structure) and the rib.

(9) FIG. 8 is a sectional view of the external lamp structure according to Embodiment 3 of the present disclosure and the rib.

(10) FIG. 9 is a structural diagram of a sliding block according to an embodiment of the present disclosure.

(11) FIG. 10 is an exploded view of the external lamp structure according to Embodiment 4 of the present disclosure (without the second fixing structure) and the rib.

(12) FIG. 11 is a structural diagram of a rotary fastener according to an embodiment of the present disclosure.

(13) FIG. 12 is a front view of a first fixing body according to an embodiment of the present disclosure.

(14) FIG. 13 is a rear view of the first fixing body according to Embodiment 4 of the present disclosure.

(15) FIG. 14 is a sectional view of the external lamp structure according to Embodiment 4 of the present disclosure and the rib.

(16) FIG. 15 is an exploded view of the external lamp structure according to Embodiment 5 of the present disclosure (without the second fixing structure) and the rib.

(17) FIG. 16 is a sectional view of the external lamp structure according to Embodiment 5 of the present disclosure and the rib.

(18) FIG. 17 is an exploded view of the external lamp structure according to Embodiment 6 of the

present disclosure and the rib.

(19) FIG. **18** is a sectional view of the external lamp structure according to Embodiment 6 of the present disclosure and the rib.

(20) FIG. **19** schematically shows the external lamp structure according to an embodiment of the present disclosure assembled on a middle-column umbrella.

(21) FIG. **20** schematically shows the external lamp structure according to an embodiment of the present disclosure assembled on a banana umbrella.

(22) FIG. **21** schematically shows the external lamp structure according to an embodiment of the present disclosure assembled on a roman umbrella.

(23) In the figures: **100**, rib; **200**, light strip; **300**, first fixing structure; **400**, second fixing structure; **1**, first top plate; **2**, first bottom plate; **3**, first side plate; **4**, first positioning hole; **5**, first connecting structure; **6**, third top plate; **7**, fifth bottom plate; **8**, fifth side plate; **9**, fourth connecting hole; **10**, sixth positioning hole; **11**, second connecting structure; **12**, second top plate assembly; **13**, first limit plate; **14**, second bottom plate; **15**, second side plate; **16**, first fastener assembly; **17**, second positioning hole; **18**, second top plate; **19**, first fastener; **21**, first protrusion; **22**, first open groove; **23**, flange; **27**, sliding block; **28**, third bottom plate; **29**, third side plate; **30**, sliding rail; **31**, second fastener; **32**, third positioning hole; **33**, first fixing hole; **34**, rivet; **35**, first fixing body; **351**, first clamping groove; **36**, rotary fastener; **361**, stop block; **3611**, second protrusion; **362**, toggling part; **3621**, bump; **3622**, first notch; **37**, third clamping groove; **371**, clamping strip; **3711**, second notch; **3712**, recess; **38**, second connecting hole; **39**, second fixing hole; **40**, second fixing body; **41**, rivet nut; **42**, second clamping groove; **43**, third connecting hole; **44**, fourth positioning hole; **45**, third connecting structure; **46**, fourth bottom plate; **47**, second limit plate; **48**, fourth side plate; **49**, third fastener; **50**, fifth positioning hole; and **55**, positioning groove.

DETAILED DESCRIPTION OF EMBODIMENTS

(24) The technical solutions of the embodiments of the present disclosure will be clearly and completely described with reference to the accompanying drawings of the embodiments of the present disclosure. It is obvious that described herein are only some embodiments of the present disclosure, rather than all embodiments. Based on the embodiments of the present disclosure, other embodiments obtained by those of ordinary skill in the art without making creative effort shall fall within the scope of the present disclosure.

(25) It should be noted that the terms, such as “up”, “down”, “left”, “right”, “front”, “rear” and other directional indications used herein, are only used for illustrating relative position relationship and motion between components in a specific state (as shown in the accompanying drawings). If the specific state changes, the directional indication accordingly changes.

(26) In addition, the terms “first” and “second” are only used for distinguishment rather than indicating or implying the relative importance or implicitly specifying the number of technical features indicated. Therefore, a feature defined with “first” or “second” may explicitly or implicitly indicates the inclusion of at least one of such features. Besides, the term “and/or” used herein includes three solutions, for example, “A” and/or “B” includes solution “A”, solution “B”, and a combination thereof. Technical solutions of embodiments can be combined with each other as long as the combined solution can be implemented by those skilled in the art. When a combination of the technical solutions is contradictory or cannot be realized, it should be considered that such a combination does not exist, and is not within the scope of the present disclosure.

(27) An object of the present disclosure is to provide an external lamp structure, so as to solve problems that a parasol with lights needs to be mounted with different light strips. The present disclosure has advantages of independent disassembly, convenient maintenance, beauty and low cost, and is suitable for any grade of parasols.

(28) To make the above object, features and advantages of the present disclosure more clearly, the present disclosure will be further described below with reference to the accompanying drawings and the specific embodiments.

Embodiment 1

(29) Referring to FIGS. 1-2, an external lamp structure is provided, including a light strip **200** and two first fixing structures **300**. The light strip **200** is integrally formed or detachably connected with the two first fixing structures **300**. Each of the two first fixing structures **300** is integrally formed. One of the two first fixing structures **300** is sleevedly provided on a first end of the light strip **200**, and the other of the two first fixing structures **300** is sleevedly provided on a second end of the light strip **200**. The two first fixing structures **300** are configured to mount the light strip **200** on an umbrella structure. The external lamp structure further includes a lamp line. A first end of the lamp line is connected with the light strip **200**, and a second end of the lamp line passes through a line hole on a rib **100**, extends in the rib **100**, and is connected with a controller.

(30) In this embodiment, each of the two first fixing structures **300** is made of a plastic material.

(31) When the light strip **200** is relatively longer, the external lamp structure further includes a second fixing structure **400**. The second fixing structure **400** is integrally formed, and is sleevedly provided on a middle of the light strip **200**. The second fixing structure **400** is configured to mount the light strip **200** on the umbrella structure and prevent the light strip **200** from wearing.

(32) In this embodiment, the second fixing structure **400** is made of the plastic material.

(33) In this embodiment, each of the two first fixing structures **300** includes a first top plate **1**, a first bottom plate **2** and two first side plates **3**. The two first side plates **3** are arranged opposite to each other. A first side of the first top plate **1** is connected with a top of one of the two first side plates **3**, and a second side of the first top plate **1** is connected with a top of the other of the two first side plates **3**. A first side of the first bottom plate **2** is connected with a bottom of one of the two first side plates **3**, and a second side of the first bottom plate **2** is connected with a bottom of the other of the two first side plates **3**. The first top plate **1**, the first bottom plate **2** and the two first side plates **3** are configured to form a first space. A first end of the first space is larger than a second end of the first space in size, so as to form a flared opening, which is configured to mount the light strip **200**, and is convenient for each of the two first fixing structures **300** to be sleeved on the rib. The first end of the first space is configured for the rib **100** of the umbrella structure and the light strip **200** to pass through, and the second end of the first space is configured for the rib of the umbrella structure to pass through. The first bottom plate **2** is provided with a first protrusion **21** configured to limit the first end and the second end of the light strip **200**. The first top plate **1** is provided with a positioning groove **55**. The rib **100** is provided with a first positioning hole **4** corresponding to the positioning groove **55**. The positioning groove **55** and the first positioning hole **4** are configured to allow a first connecting structure **5** to pass therethrough to realize a connection of each of the two first fixing structures **300** and the rib **100**. The first connecting structure **5** is a screw, a rivet or a fastener. The first connecting structure **5** and the first positioning hole **4** are configured to limit the two first fixing structures **300** and prevent the two first fixing structures **300** from sliding on the rib, resulting in separation of the light strip **200**.

(34) In this embodiment, the second fixing structure **400** includes a third top plate **6**, a fifth bottom plate **7** and two fifth side plates **8**. The two fifth side plates **8** are arranged opposite to each other. A first side of the third top plate **6** is connected with a top of one of the two fifth side plates **8**, and a second side of the third top plate **6** is connected with a top of the other of the two fifth side plates **8**. A first side of the fifth bottom plate **7** is connected with a bottom of one of the two fifth side plates **8**, and a second side of the fifth bottom plate **7** is connected with a bottom of the other of the two fifth side plates **8**. The third top plate **6**, the fifth bottom plate **7** and the two fifth side plate **8** are configured to form a third space configured for the rib **100** and the light strip **200** to pass through. The third top plate **6** is provided with a fourth connecting hole **9**. The rib **100** is provided with a sixth positioning hole **10** corresponding to the fourth connecting hole **9**. The fourth connecting hole **9** and the sixth positioning hole **10** are configured to allow a second connecting structure **11** to pass therethrough to realize a connection of the second fixing structure **400** and the rib **100**. The second connecting structure **11** is the screw or the rivet. The second connecting structure **11** and the fourth

connecting hole **9** are configured to limit the second fixing structures **400** and prevent the second fixing structures **400** from sliding on the rib.

(35) In a case of use, each of the two first fixing structures **300** and the second fixing structure **400** are configured to be sleeved on the rib **100** through the first end and the second end of the rib **100**. The connection of each of the two first fixing structures **300** and the rib **100** is realized by the screw, or the rivet or the fastener passing through the positioning groove **55** and the first positioning hole **4**. The connection of the second fixing structure **400** and the rib **100** is realized by the screw, or the rivet passing through the fourth connecting hole **9** and the sixth positioning hole.

(36) In this embodiment, the two first fixing structures **300** and the second fixing structure **400** adopt a fully enclosed structure, which has advantages of good stability, comprehensive protection and high reliability.

Embodiment 2

(37) Referring to FIGS. **3-6**, this embodiment is similar to Embodiment 1 except the following differences.

(38) In this embodiment, each of the two first fixing structures **300** and the second fixing structure **400** includes a second top plate assembly **12**, a second bottom plate **14** and two second side plates **15**. The two second side plates **15** are arranged opposite to each other. A first side of the second top plate assembly **12** is connected with a top of one of the two second side plates **15**, and a second side of the second top plate assembly **12** is connected with a top of the other of the two second side plates **15**. A first open groove **22** is provided between the second top plate assembly **12** and each of the second side plates **15**. A first side of the second bottom plate **14** is connected with a bottom of one of the two second side plates **15**, and a second side of the second bottom plate **14** is connected with a bottom of the other of the two second side plates **15**. The second top plate assembly **12**, the second bottom plate **14** and the two second side plates **15** are configured to form a second space configured for the rib **100** and the light strip **200** to pass through. The second top plate assembly **12** is provided with a first fastener assembly **16**. The rib **100** is provided with a second positioning hole **17**. The first fastener assembly **16** is configured to extend into the second positioning hole **17** to realize a connection of each of the two first fixing structures **300** or the second fixing structure **400** and the rib **100**. The first fastener assembly **16** and the second positioning hole **17** are configured to limit the two first fixing structures **300** and the second fixing structure **400** to prevent the two first fixing structures **300** and the second fixing structure **400** from sliding on the rib **100**, resulting in separation of the light strip **200**.

(39) In this embodiment, the two first fixing structures **300** and the second fixing structure **400** also adopt the fully enclosed structure. Compared to Embodiment 1, in this embodiment, the first fastener assembly **16** and the two first fixing structures **300** are integrally formed, and the first fastener assembly **16** and the second fixing structure **400** are integrally formed, which has advantages of convenient installation.

(40) Referring to FIGS. **5-6**, on the basis of the first fixing structure **300** or the second fixing structure **400** according to Embodiment 1, in the first fixing structure **300** or the second fixing structure **400** in this embodiment, the second top plate assembly **12** includes two second top plates **18**, and the first fastener assembly **16** includes two first fasteners **19**. A first side of one of the second top plates **18** is connected with the top of one of the two second side plates **15**, and a first side of the other of the second top plates **18** is connected with the top of the other of the two second side plates **15**. A first gap is provided between a second side of one of the second top plates **18** and a second side of the other of the second top plates **18**. One of the two first fasteners **19** is provided on one of the second top plates **18**, and the other of the two first fasteners **19** is provided on the other of the second top plates **18**. A second gap is provided between one of the two first fasteners **19** and the other of the two first fasteners **19**. Each of the two first fasteners **19** is configured to extend into the second positioning hole **17** to realize the connection of each of the two first fixing structures or the second fixing structure and the rib **100**.

(41) During mounting, the two second side plates **15** are configured to be applied with a certain force to increase the first gap until the first gap is configured for the rib **100** to pass therethrough, so that the rib **100** is configured to enter the second space through the first gap, and the two first fasteners **19** are configured to be enclosed to form the first fastener assembly **16**, which has a tightening effect on the light strip **200**. The two first fasteners **19** are configured to be enclosed and insert into the second positioning hole **17** to complete installation of one of the two first fixing structures **300** or the second fixing structure **400**.

(42) Each of the two first fixing structures **300** further includes a first limit plate **13**. The first limit plate **13** is connected with an end of the second top plate assembly **12**, an end of the second bottom plate **14** and an end of each of the second side plates **15**, respectively. The first limit plate **13** of one of the two first fixing structures **300** is located on an outer side of an end of the light strip **200**, and the first limit plate **13** of the other of the two first fixing structures **300** is located on an outer side of the other end of the light strip **200**. The first limit plate **13** is configured to limit the first end and the second end of the light strip **200**.

(43) During use, the two first fixing structures **300** and the second fixing structure **400** are configured to be sleeved on the rib **100**. The first fastener assembly **16** is configured to extend into the second positioning hole **17** to realize the connection of each of the two first fixing structures or the second fixing structure and the rib **100**. Or the two first fasteners **19** are configured to extend into the second positioning hole **17** to realize the connection of each of the two first fixing structures or the second fixing structure and the rib **100**.

(44) In this embodiment, the two first fixing structures **300** and the second fixing structure **400** adopt a fully enclosed structure with a first opening. Owing to the opening, the two first fixing structures **300** and the second fixing structure **400** do not need to be sleeved through both ends of the rib, which is convenient for installation.

Embodiment 3

(45) Referring to FIGS. 7-9, this embodiment is similar to Embodiment 2 except the following differences.

(46) In this embodiment, each of the two first fixing structures **300** includes a sliding block **27**, a third bottom plate **28** and two third side plates **29**. The two third side plates **29** are arranged opposite to each other. A first side of the third bottom plate **28** is connected with a bottom of one of the two third side plates **29**, and a second side of the third bottom plate **28** is connected with a bottom of the other of the two third side plates **29**. The third bottom plate **28** and the two third side plates **29** are configured to form a first U-shaped structure, and a sliding rail **30** is provided in the first U-shaped structure. The sliding block **27** is in slidable connection with the sliding rail **30**. The sliding block **27** is configured as a stator, and the first U-shaped structure is configured as a mover. An end of the sliding rail **30** and an end of the sliding block **27** are configured to limit the first end and the second end of the light strip **200**. The rib **100** is provided with a third positioning hole **32**. The sliding block **27** is provided with a second fastener **31** configured to extend into the third positioning hole **32**. The sliding block **27** is provided with a first connecting hole. The rib **100** is provided with a first fixing hole **33** corresponding to the first connecting hole. The first connecting hole and the first fixing hole **33** are configured to allow a rivet **34** to pass therethrough.

(47) In this embodiment, the end of the sliding block **27** is provided with a flange **23**. The flange **23** is configured to limit and position the two first fixing structures **300**, so that each of the two first fixing structures **300** can slide quickly to a specified position and be limited, and will not be separates from the other end of the sliding block **27**.

(48) During use, the second fastener **31** is configured to extend into the third positioning hole **32** to connect the sliding block **27** and the rib **100**. The rivet **34** is configured to pass through the first connecting hole and the first fixing hole **33** to realize a connection of the slicing block **27** and the rib **100**. Then the mover is configured to be pushed to realize a snap-fit connection of the sliding block **27** and the mover, so as to realize the connection of the two first fixing structures **300** and the

rib **100**. The connection of the second fixing structure **400** and the rib **100** is the same as that in Embodiment 2.

(49) In this embodiment, the two first fixing structures **300** adopt a sliding cover structure, so that the two first fixing structures **300** are not limited to a size of the rib **100**, and can be adapted to the rib **100** with multiple sizes. In addition, the light strip **200** can be assembled and disassembled by sliding the two first fixing structures **300**, which is convenient and fast.

Embodiment 4

(50) Referring to FIGS. **10-14**, this embodiment is similar to Embodiment 2 except the following differences.

(51) In this embodiment, each of the two first fixing structures **300** includes a first fixing body **35** and a rotary fastener **36**. The first fixing body **35** is provided with a third clamping groove **37** and a first clamping groove **351**. The rotary fastener **36** is in snap-fit connection with the third clamping groove **37**. The light strip **200** is located in the first clamping groove **351**. The rotary fastener **36** is provided with a second connecting hole **38**. The rib **100** is provided with a second fixing hole **39** corresponding to the second connecting hole **38**. The second connecting hole **38** and the second fixing hole **39** are configured to allow the rivet **34** to pass therethrough.

(52) In this embodiment, the first fixing body **35** has a long strip-shaped groove structure with openings on both ends. The third clamping groove **37** is arranged on a first end of an inner bottom surface of the first fixing body **35**, and the first clamping groove **351** is arranged on a second end of the inner bottom surface of the first fixing body **35**. The third clamping groove **37** is vertical to a bottom surface of the first fixing body **35**. The first clamping groove **351** is a rectangular groove. An end of the first clamping groove **351** away from the third clamping groove **37** is provided with a second opening. The rotary fastener **36** is cylindrical, and the third clamping groove **37** is round, which is fitting the rotary fastener **36**. In this embodiment, the third clamping groove **37** is configured to pass through a bottom of the first fixing body **35**. A cross section of the first clamping groove **351** is U-shaped, which is fitting the light strip **200**.

(53) In this embodiment, a circumference of the rotary fastener **36** is provided with at least one stop block **361**. An inner wall of the third clamping groove **37** is provided with an annular clamping strip **371**. The annular clamping strip **371** is provided with a second notch **3711**, and the number of the second notch **3711** is the same as the number of the at least one stop block **361**. When the number of the at least one stop block **361** is one, the one stop block **361** is arranged on the circumference of the rotary fastener **36**. When the number of the at least one stop block **361** is at least two, the at least two stop block **361** are arranged on the circumference of the rotary fastener **36** in a circular array.

(54) In this embodiment, the rotary fastener **36** is provided with a toggling part **362**. The toggling part **362** is configured to drive the rotary fastener **36** to rotate, and the toggling part **362** is in a strip shape. In an embodiment, the toggling part **362** is arranged along a tangential direction of the rotary fastener **36**. The toggling part **362** is configured to be parallel to the at least one stop block **361**. A side of the toggling part **362** away from the rotary fastener **36** and facing toward the circumferential surface of the rotary fastener **36** is provided with a bump **3621**. The bump **3621** is trilateral. The bump **3621** is configured to facilitate driving the toggling part **362**, and a first notch **3622** is formed between the bump **3621** and the rotary fastener **36**.

(55) In this embodiment, the at least one stop block **361** is provided with a second protrusion **3611**, and the annular clamping strip **371** is provided with a recess **3712** fitting the second protrusion **3611**. In an embodiment, each of the at least one stop block **361** is arranged on a lower part of the rotary fastener **36**. The second protrusion **3611** is arranged on a top surface of each of the at least one stop block **361**. The second protrusion **3611** is in the strip shape and is arranged parallel to the toggling part **362**. The recess **3712** is arranged on a back of the first fixing body **35**, and is in the strip shape. The recess **3712** is arranged parallel to a length direction of the first fixing body **35**. The second notch **3711** is arranged on the annular clamping strip **371** deviated from the recess

3712. The first notch **3622** is configured for a side wall of the first fixing body **35** to insert into the first notch **3622** after fixing of the first fixing body **35** by the rotary fastener **36**. At this moment, the first notch **3622** is in snap-fit connection with the side wall of the first fixing body **35**, which can further improve an effect of installation and fixing.

(56) During use, the rivet **34** is configured to mount the rotary fastener **36** on the rib **100**, and the third clamping groove **37** is fastened on the rotary fastener **36**. The first clamping groove **351** is configured to support the first end and the second end of the light strip **200**. The rotary fastener **36** is configured to be rotated to be in snap-fit connection with the third clamping groove **37** to realize the connection of the two first fixing structures **300** and the rib **100**. The connection of the second fixing structure **400** and the rib **100** is the same as that in Embodiment 2.

(57) In an embodiment, during mounting, the light strip **200** is configured to be accommodated in the first clamping groove **351**. Then the rotary fastener **36** is configured to be aligned with the third clamping groove **37** and inserted into the third clamping groove **37**, so that each of the at least one stop block **361** is configured to be inserted into the second notch **3711** from top to bottom and pass through the annular clamping strip **371**. Then the toggling part **362** is configured to be applied with an external force to drive the rotary fastener **36** to rotate. The rotary fastener **36** is configured to rotate to drive the at least one stop block **361**. When each of the at least one stop block **361** rotates to reach a position below the annular clamping strip **371**, the annular clamping strip **371** is configured to limit the at least one stop block **361**. The rotary fastener **36** is configured to drive the second protrusion **3611** to synchronously rotate. At this moment, the second protrusion **3611** slides in a bottom surface of the annular clamping strip **371**. When the second protrusion **3611** slides into the recess **3712**, the recess **3712** is configured to clamp the second protrusion **3611** to limit rotation of the rotary fastener **36**. The mounting of the two first fixing structures **300** is completed.

(58) In this embodiment, the two first fixing structures **300** adopt a rotary disassembly structure, which is not limited to the size of the rib **100**. In addition, the rotary fastener **36** is configured to assemble and disassemble the light strip, which is convenient and fast.

Embodiment 5

(59) Referring to FIGS. **15-16**, this embodiment is similar to Embodiment 2 except the following differences.

(60) In this embodiment, each of the two first fixing structures **300** includes a second fixing body **40** and a rivet nut **41**. The second fixing body **40** is provided with a second clamping groove **42**. The light strip **200** is located in the second clamping groove **42**. The second fixing body **40** is provided with a third connecting hole **43**. The rib **100** is provided with a fourth positioning hole **44** corresponding to the third connecting hole **43**. The rivet nut **41** is located in the fourth positioning hole **44**, the third connecting hole **43** is configured to allow a third connecting structure **45** to pass therethrough to realize the connection of each of the two first fixing structures **300** and the rib **100**. The third connecting structure **45** is the screw, the fastener or the rivet.

(61) During use, the light strip **200** is configured to be in snap-fit connection with the second clamping groove **42**. Then the second fixing body **40** is connected with the rivet nut **41** through the screw, or the fastener or the rivet, to realize the connection of each of the two first fixing structures **300** and the rib **100**. The connection of the second fixing structure **400** and the rib **100** is the same as Embodiment 2.

(62) In this embodiment, the two first fixing structures **300** adopt a cover plate structure, which is not limited to the size of the rib, and has a simple structure and good stability.

Embodiment 6

(63) Referring to FIGS. **17-18**, this embodiment is similar to Embodiment 1 except the following differences.

(64) In this embodiment, each of the two first fixing structures **300** or the second fixing structure **400** includes a fourth bottom plate **46** and two fourth side plates **48**. The two fourth side plates **48** are arranged opposite to each other. A first side of the fourth bottom plate **46** is connected with a

bottom of one of the two fourth side plates **48**, and a second side of the fourth bottom plate **46** is connected with a bottom of the other of the two fourth side plates **48**. The fourth bottom plate **46** and the two fourth side plates **48** are configured to form a second U-shaped structure. An inner side of each of the two fourth side plates **48** includes a third fastener **49**. The third fastener **49** of one of the two fourth side plates **48** is close to the first end of the light strip **200**, and the third fastener **49** of the other of the two fourth side plates **48** is close to the second end of the light strip **200**. The rib **100** is provided with a fifth positioning hole **50**. The third fastener **49** is configured to extend into the fifth positioning hole **50** to realize the connection of each of the two first fixing structures **300** or the second fixing structure and the rib **100**. Each of the two first fixing structures **300** includes a second limit plate **47**. The second limit plate **47** is connected with an end of the fourth bottom plate **46**, an end of one of the two fourth side plates **48** and an end of the other of the two fourth side plates **48**, respectively. The second limit plate **47** of one of the two fourth side plates **48** is located on an outer side of the first end of the light strip **200**, and the second limit plate **47** of the other of the two fourth side plates **48** is located on an outer side of the second end of the light strip **200**.

(65) During use, an upper opening of each of the two first fixing structures **300** is configured to be aligned with the rib **100**, and is configured to be pushed from bottom to top. When the third fastener **49** is aligned with the fifth positioning hole **50**, and inserts into the fifth positioning hole **50**, the connection of the each of the two first fixing structures **300** or the second fixing structure **400** and the rib **100** is realized.

(66) In this embodiment, the two first fixing structures **300** and the second fixing structure **400** adopt a semi-enclosed structure with an opening, such that the two first fixing structures **300** and the second fixing structure **400** do not need to be sleeved through both ends of the rib, which is convenient for installation.

(67) Referring to FIGS. **19-21**, which show applications of the external lamp structure of the present disclosure, the light strip **200** can be a light guide strip or a rope light. The external lamp structure can be applied on a central pole umbrella, a banana umbrella, a roman umbrella and other umbrella structures.

(68) This embodiment discloses the external lamp structure, so that the light strip **200** can be externally arranged on the rib **100**, which solves the problem that a parasol with lights needs to be mounted with different light strips **200**. In addition, this application has advantages of independent disassembly of the light strip **200** and convenient maintenance, which is convenient for electrification of the parasol.

(69) The principle and implementation of this application have been described with reference to embodiments. The above embodiments are only for illustrating the method and the core idea of this application, are not intended to limit this application. It should be understood that various modifications, variations and replacements made by those of ordinary skill in the art without departing from the spirit of this application shall fall within the scope of this application defined by the appended claims.

Claims

1. An external lamp structure, comprising: a light strip; and two first fixing structures; wherein the light strip is integrally formed or detachably connected with the two first fixing structures; one of the two first fixing structures is sleevedly provided on a first end of the light strip, and the other of the two first fixing structures is sleevedly provided on a second end of the light strip; and the two first fixing structures are configured to mount the light strip on an umbrella structure; and each of the two first fixing structures comprises a top plate, a bottom plate and two side plates; the two side plates are arranged opposite to each other; a first side of the top plate is connected with a top of one of the two side plates, and a second side of the top plate is connected with a top of the other of the two side plates; a first side of the bottom plate is connected with a bottom of one of the two side

- plates, and a second side of the bottom plate is connected with a bottom of the other of the two side plates; the top plate, the bottom plate and the two side plates are configured to form a space; a first end of the space is configured for a rib of the umbrella structure and the light strip to pass through, and a second end of the space is configured for the rib of the umbrella structure to pass through.
2. The external lamp structure of claim 1, further comprising: a second fixing structure; wherein the second fixing structure is sleevedly provided on a middle of the light strip; and the second fixing structure is configured to mount the light strip on the umbrella structure.
3. The external lamp structure of claim 1, wherein the first end of the space is larger than the second end of the space in size.
4. The external lamp structure of claim 1, wherein the top plate is provided with a positioning groove; the rib of the umbrella structure is provided with a positioning hole corresponding to the positioning groove; and the positioning groove and the positioning hole are configured to allow a connecting structure to pass therethrough to realize connection between each of the two first fixing structures and the rib of the umbrella structure.
5. The external lamp structure of claim 1, wherein the bottom plate is provided with a protrusion; and the protrusion is configured to limit the first end and the second end of the light strip.
6. The external lamp structure of claim 2, wherein each of the two first fixing structures or the second fixing structure comprises: a top plate assembly; a bottom plate; and two side plates; wherein the two side plates are arranged opposite to each other; a first side of the top plate assembly is connected with a top of one of the two side plates, and a second side of the top plate assembly is connected with a top of the other of the two side plates; a first side of the bottom plate is connected with a bottom of one of the two side plates, and a second side of the bottom plate is connected with a bottom of the other of the two side plates; and the top plate assembly, the bottom plate and the two side plates are configured to form a space configured for a rib of the umbrella structure and the light strip to pass through.
7. The external lamp structure of claim 6, wherein an open groove is provided between the top plate assembly and each of the two side plates.
8. The external lamp structure of claim 6, wherein the top plate assembly is provided with a fastener assembly; the rib of the umbrella structure is provided with a positioning hole; the fastener assembly is configured to extend into the positioning hole to realize connection between each of the two first fixing structures or the second fixing structure and the rib of the umbrella structure.
9. The external lamp structure of claim 8, wherein the top plate assembly comprises two top plates; the fastener assembly comprises two fasteners; a first side of one of the two top plates is connected with the top of one of the two side plates, and a first side of the other of the two top plates is connected with the top of the other of the two side plates; a first gap is provided between a second side of one of the two top plates and a second side of the other of the two top plates; one of the two fasteners is provided on one of the two top plates, and the other of the two fasteners is provided on the other of the two top plates; a second gap is provided between the two fasteners; the two fasteners are configured to extend into the positioning hole on the rib of the umbrella structure to realize the connection between each of the two first fixing structures or the second fixing structure and the rib of the umbrella structure.
10. The external lamp structure of claim 1, wherein each of the two first fixing structures comprises a fixing body; the fixing body is provided with a clamping groove; the light strip is located in the clamping groove; the fixing body is provided with a connecting hole; a rib of the umbrella structure is provided with a positioning hole corresponding to the connecting hole; the connecting hole and the positioning hole are configured to allow a connecting structure to pass therethrough to realize connection between each of the two first fixing structures and the rib of the umbrella structure.
11. The external lamp structure of claim 2, wherein each of the two first fixing structures or the second fixing structure comprises: a bottom plate; and two side plates; wherein the two side plates are arranged opposite to each other; a first side of the bottom plate is connected with a bottom of

one of the two side plates, and a second side of the bottom plate is connected with a bottom of the other of the two side plates; the bottom plate and the two side plates are configured to form a U-shaped structure; an inner side of each of the two side plates is provided with a fastener; a rib of the umbrella structure is provided with a positioning hole; and the fastener is configured to extend into the positioning hole to realize connection between each of the two first fixing structures or the second fixing structure and the rib of the umbrella structure.

12. An external lamp structure, comprising: a light strip; and two fixing structures; wherein the light strip is integrally formed or detachably connected with the two fixing structures; one of the two fixing structures is sleevedly provided on a first end of the light strip, and the other of the two fixing structures is sleevedly provided on a second end of the light strip; and the two fixing structures are configured to mount the light strip on an umbrella structure; and each of the two fixing structures comprises a sliding block, a bottom plate and two side plates; the two side plates are arranged opposite to each other; a first side of the bottom plate is connected with a bottom of one of the two side plates, and a second side of the bottom plate is connected with a bottom of the other of the two side plates; the bottom plate and the two side plates are configured to form a U-shaped structure, and a sliding rail is provided in the U-shaped structure; the sliding block is in slidable connection with the sliding rail; an end of the sliding rail and an end of the sliding block are configured to limit the first end and the second end of the light strip; the sliding block is provided with a fastener; a rib of the umbrella structure is provided with a positioning hole; the fastener is configured to extend into the positioning hole; the sliding block is provided with a connecting hole; the rib of the umbrella structure is provided with a fixing hole corresponding to the connecting hole; and the connecting hole and the fixing hole are configured to allow a rivet to pass therethrough.

13. The external lamp structure of claim 12, wherein the end of the sliding block is provided with a flange.

14. An external lamp structure, comprising: a light strip; and two fixing structures; wherein the light strip is integrally formed or detachably connected with the two fixing structures; one of the two fixing structures is sleevedly provided on a first end of the light strip, and the other of the two fixing structures is sleevedly provided on a second end of the light strip; and the two fixing structures are configured to mount the light strip on an umbrella structure; and each of the two fixing structures comprises a fixing body and a rotary fastener; wherein the fixing body is provided with a first clamping groove and a second clamping groove; the rotary fastener is in snap-fit connection with the first clamping groove; the light strip is located in the second clamping groove; the rotary fastener is provided with a connecting hole; a rib of the umbrella structure is provided with a fixing hole corresponding to the connecting hole; and the connecting hole and the fixing hole are configured to allow a rivet to pass therethrough.

15. The external lamp structure of claim 14, wherein a side wall of the rotary fastener is provided with at least one stop block; an inner wall of the first clamping groove is provided with an annular clamping strip; and the annular clamping strip is provided with a notch, and the number of the notch is the same as the number of the at least one stop block.

16. The external lamp structure of claim 15, wherein the rotary fastener is provided with a toggling part.

17. The external lamp structure of claim 16, wherein a side of the toggling part away from the rotary fastener and facing toward a circumferential surface of the rotary fastener is provided with a bump.

18. The external lamp structure of claim 17, wherein a notch is formed between the bump and the rotary fastener.

19. The external lamp structure of claim 15, wherein each of the at least one stop block is provided with a protrusion; and the annular clamping strip is provided with a recess fitting the protrusion.
