

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12400157
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Lord; Richard T. et al.

System and methods for transporting end users

Abstract

Computationally implemented methods and systems that are designed for receiving one or more first directives that direct a transportation vehicle unit to transport a first end user; receiving, while the transportation vehicle unit is en route to or is transporting the first end user, one or more second directives that direct the transportation vehicle unit to transport a second end user while transporting the first end user, the transportation vehicle unit having been determined to be able to accommodate transport of the second end user while transporting the first end user; and verifying that compliance with the one or more second directives will not conflict with one or more obligations to transport the first end user by the transportation vehicle unit. In addition to the foregoing, other aspects are described in the claims, drawings, and text.

Inventors: Lord; Richard T. (San Francisco, CA), Lord; Robert W. (San Francisco, CA), Myhrvold; Nathan P. (San Francisco, CA), Tegreene; Clarence T. (San Francisco, CA)

Applicant: Uber Technologies, Inc. (San Francisco, CA)

Family ID: 1000008779241

Assignee: Uber Technologies, Inc. (San Francisco, CA)

Appl. No.: 18/732596

Filed: June 03, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240370786 A1	Nov. 07, 2024

Related U.S. Application Data

continuation parent-doc US 17965182 20221013 US 12001975 child-doc US 18732596
continuation parent-doc US 16849984 20200415 US 11669785 child-doc US 17965182

continuation parent-doc US 15985652 20180521 US 10657468 20200519 child-doc US 16849984
continuation parent-doc US 15588502 20170505 US 10002333 20180619 child-doc US 15985652
continuation parent-doc US 14621151 20150212 US 9715667 20170725 child-doc US 15588502
continuation parent-doc US 14619812 20150211 US 9552559 20170124 child-doc US 14621151
continuation parent-doc US 14596904 20150114 US 9483744 20161101 child-doc US 14597631
continuation parent-doc US 14563134 20141208 US 9671239 20170606 child-doc US 14564358
continuation parent-doc US 14536967 20141110 US 9792574 20171017 child-doc US 14537313
continuation parent-doc US 14510383 20141009 US 9569740 20170214 child-doc US 14511706
continuation parent-doc US 14464587 20140820 US 9110925 child-doc US 14476042
continuation parent-doc US 14455534 20140808 US 9581455 20170228 child-doc US 14456627
continuation parent-doc US 14328002 20140710 US 10458801 20191029 child-doc US 14329451
continuation-in-part parent-doc US 14597631 20150115 US 9886671 20180206 child-doc US
14619812
continuation-in-part parent-doc US 14564358 20141209 US 9689694 20170627 child-doc US
14596904
continuation-in-part parent-doc US 14537313 20141110 US 9558469 20170131 child-doc US
14563134
continuation-in-part parent-doc US 14511706 20141010 US 9767423 20170919 child-doc US
14536967
continuation-in-part parent-doc US 14476042 20140903 US 9488484 20161108 child-doc US
14510383
continuation-in-part parent-doc US 14456627 20140811 US 9534912 20170103 child-doc US
14464587
continuation-in-part parent-doc US 14329451 20140711 ABANDONED child-doc US 14455534
continuation-in-part parent-doc US 14318182 20140627 ABANDONED child-doc US 14328002
us-provisional-application US 61989394 20140506

Publication Classification

Int. Cl.: G06Q50/40 (20240101); G06Q10/06 (20230101); G06Q10/0631 (20230101)

U.S. Cl.:

CPC G06Q10/06 (20130101); G06Q10/063114 (20130101); G06Q10/06315 (20130101);
G06Q50/40 (20240101);

Field of Classification Search

CPC: G06Q (10/063114); G06Q (10/06); G06Q (50/40); G06Q (10/06315)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5557522	12/1995	Nakayama	N/A	N/A
5948040	12/1998	DeLorme	N/A	N/A
6058339	12/1999	Takiguchi	N/A	N/A
6233517	12/2000	Froeberg	N/A	N/A
6321158	12/2000	DeLorme	N/A	N/A

6608566	12/2002	Davis	N/A	N/A
6756913	12/2003	Ayed	N/A	N/A
6832092	12/2003	Suarez	N/A	N/A
7062376	12/2005	Oesterling	N/A	N/A
7263437	12/2006	Hirose	N/A	N/A
7957871	12/2010	Echeruo	N/A	N/A
7970749	12/2010	Uhler	N/A	N/A
8412667	12/2012	Zhang	N/A	N/A
8630987	12/2013	Dhuse	N/A	N/A
8843307	12/2013	Kolodziej	N/A	N/A
8954094	12/2014	Mishra	N/A	N/A
9070101	12/2014	Abhayanker	N/A	N/A
9075136	12/2014	Joao	N/A	N/A
9127946	12/2014	Menon	N/A	N/A
9172738	12/2014	daCosta	N/A	N/A
9244147	12/2015	Soundararajan	N/A	N/A
9483744	12/2015	Lord	N/A	G06Q 10/047
9552559	12/2016	Lord	N/A	G06Q 10/06
9558469	12/2016	Lord	N/A	G06Q 10/08
9610893	12/2016	Lopez-Hinojosa	N/A	N/A
9689694	12/2016	Lord	N/A	G06Q 10/06311
9886667	12/2017	Lord	N/A	N/A
9886671	12/2017	Lord	N/A	G06Q 10/06311
9911170	12/2017	Kim	N/A	N/A
10002333	12/2017	Lord	N/A	N/A
10074065	12/2017	Jones	N/A	N/A
10152053	12/2017	Smith	N/A	N/A
10178890	12/2018	Andon	N/A	N/A
10328855	12/2018	Lopez-Hinojosa	N/A	N/A
10339474	12/2018	Lord	N/A	G06Q 10/06311
10572964	12/2019	Kim	N/A	N/A
10721327	12/2019	Cheng	N/A	N/A
10769555	12/2019	Wild	N/A	B60L 53/67
11196838	12/2020	Cheng	N/A	N/A
11441921	12/2021	Vereshshagin	N/A	N/A
11551325	12/2022	Tolkin	N/A	N/A
11924308	12/2023	Cheng	N/A	N/A
2003/0040944	12/2002	Hileman	N/A	N/A
2003/0058082	12/2002	Mallick	N/A	N/A
2004/0158483	12/2003	Lecouturier	N/A	N/A
2004/0249818	12/2003	Isaac	N/A	N/A
2005/0004757	12/2004	Neeman	N/A	N/A
2005/0021227	12/2004	Matsumoto	N/A	N/A
2005/0227704	12/2004	Ferra	N/A	N/A
2005/0278063	12/2004	Hersh	N/A	N/A
2006/0023569	12/2005	Agullo	N/A	N/A
2006/0034201	12/2005	Umeda	N/A	N/A

2006/0059023	12/2005	Mashinsky	N/A	N/A
2006/0155460	12/2005	Raney	N/A	N/A
2006/0173841	12/2005	Bill	N/A	N/A
2006/0184341	12/2005	Couckuyt	N/A	N/A
2006/0276960	12/2005	Adamczyk et al.	N/A	N/A
2007/0150375	12/2006	Yang	N/A	N/A
2008/0033633	12/2007	Akiyoshi	N/A	N/A
2008/0195428	12/2007	O'Sullivan	N/A	N/A
2008/0270019	12/2007	Anderson	N/A	N/A
2008/0277183	12/2007	Huang	N/A	N/A
2009/0083111	12/2008	Carr	N/A	N/A
2009/0156241	12/2008	Staffaroni	N/A	N/A
2009/0172009	12/2008	Schmith	N/A	N/A
2009/0176508	12/2008	Lubeck	N/A	N/A
2009/0192851	12/2008	Bishop	N/A	N/A
2009/0216600	12/2008	Hill	N/A	N/A
2009/0235176	12/2008	Jayanthi	N/A	N/A
2009/0248587	12/2008	Van Buskirk	N/A	N/A
2009/0296990	12/2008	Holland	N/A	N/A
2010/0070168	12/2009	Sumcad	N/A	N/A
2010/0074383	12/2009	Lee	N/A	N/A
2010/0207812	12/2009	Demirdjian	N/A	N/A
2010/0280853	12/2009	Petralia	N/A	N/A
2011/0099040	12/2010	Felt	N/A	N/A
2011/0145089	12/2010	Khunger	N/A	N/A
2011/0153629	12/2010	Lehmann et al.	N/A	N/A
2011/0238755	12/2010	Khan	N/A	N/A
2011/0301997	12/2010	Gale et al.	N/A	N/A
2012/0004840	12/2011	Lee	N/A	N/A
2012/0023294	12/2011	Resnick	N/A	N/A
2012/0041675	12/2011	Juliver	N/A	N/A
2012/0239289	12/2011	Gontmakher	N/A	N/A
2012/0253548	12/2011	Davidson	N/A	N/A
2012/0253654	12/2011	Sun	N/A	N/A
2012/0265580	12/2011	Kobayashi	N/A	N/A
2012/0290950	12/2011	Rapaport	N/A	N/A
2013/0024249	12/2012	Zohar	N/A	N/A
2013/0046456	12/2012	Scofield	N/A	N/A
2013/0054281	12/2012	Thakkar	N/A	N/A
2013/0073327	12/2012	Edelberg	N/A	N/A
2013/0110392	12/2012	Kosseifi	N/A	N/A
2013/0124404	12/2012	Horstemeyer	N/A	N/A
2013/0132140	12/2012	Amin	N/A	N/A
2013/0144831	12/2012	Atlas	N/A	N/A
2013/0158861	12/2012	Lerenc	N/A	N/A
2013/0158869	12/2012	Lerenc	N/A	N/A
2013/0159028	12/2012	Lerenc	N/A	N/A
2013/0215843	12/2012	Diachina	N/A	N/A
2013/0262222	12/2012	Gibson	N/A	N/A
2014/0074536	12/2013	Meushar	N/A	N/A

2014/0082069	12/2013	Varoglu et al.	N/A	N/A
2014/0114562	12/2013	Zhou	N/A	N/A
2014/0129951	12/2013	Amin	N/A	N/A
2014/0149441	12/2013	Wang	N/A	N/A
2014/0172727	12/2013	Abhayanker, V	N/A	N/A
2014/0378159	12/2013	Dolbakian	N/A	N/A
2015/0006072	12/2014	Goldberg	N/A	N/A
2015/0045068	12/2014	Soffer	N/A	N/A
2015/0051833	12/2014	Geelen	N/A	N/A
2015/0055178	12/2014	Ishibashi	N/A	N/A
2015/0073645	12/2014	Davidsson	N/A	N/A
2015/0123818	12/2014	Sellschopp	N/A	N/A
2015/0161564	12/2014	Sweeney	N/A	N/A
2015/0161698	12/2014	Jones	N/A	N/A
2015/0185020	12/2014	Gimpl	N/A	N/A
2015/0204684	12/2014	Rostamian	N/A	N/A
2015/0219464	12/2014	Beaurepaire	N/A	N/A
2015/0248689	12/2014	Paul	N/A	N/A
2015/0254581	12/2014	Brahme	N/A	N/A
2015/0262430	12/2014	Farrelly	N/A	N/A
2015/0317568	12/2014	Grasso	N/A	N/A
2015/0323330	12/2014	Lord	N/A	N/A
2015/0324717	12/2014	Lord	N/A	N/A
2015/0324718	12/2014	Lord	N/A	N/A
2015/0325128	12/2014	Lord	N/A	N/A
2015/0338226	12/2014	Mason	N/A	N/A
2015/0339923	12/2014	Godafoss	N/A	N/A
2015/0339928	12/2014	Ramanujam	N/A	N/A
2015/0373482	12/2014	Barnard	N/A	N/A
2016/0019496	12/2015	Gorlin	N/A	N/A
2016/0026936	12/2015	Richardson	N/A	N/A
2016/0027306	12/2015	Lambert	N/A	N/A
2016/0132792	12/2015	Rosnow	N/A	N/A
2016/0320195	12/2015	Liu	N/A	N/A
2016/0321771	12/2015	Liu	N/A	N/A
2016/0364678	12/2015	Cao	N/A	N/A
2016/0364679	12/2015	Cao	N/A	N/A
2016/0364812	12/2015	Cao	N/A	N/A
2016/0364823	12/2015	Cao	N/A	N/A
2016/0370194	12/2015	Colijn	N/A	N/A
2017/0059347	12/2016	Flier et al.	N/A	N/A
2017/0083832	12/2016	Williams	N/A	N/A
2017/0115125	12/2016	Outwater	N/A	N/A
2017/0126837	12/2016	Wang	N/A	N/A
2017/0147959	12/2016	Sweeney	N/A	N/A
2017/0169535	12/2016	Tolkin	N/A	N/A
2017/0193404	12/2016	Yoo	N/A	N/A
2017/0240098	12/2016	Sweeney	N/A	N/A
2017/0255881	12/2016	Ritch	N/A	N/A
2017/0263120	12/2016	Durie, Jr.	N/A	N/A

2017/0270794	12/2016	Sweeney	N/A	N/A
2017/0308824	12/2016	Lord	N/A	N/A
2017/0314948	12/2016	Tsuneyama et al.	N/A	N/A
2017/0365030	12/2016	Shoham	N/A	N/A
2018/0005145	12/2017	Lo	N/A	N/A
2018/0060838	12/2017	Agrawal	N/A	N/A
2018/0091604	12/2017	Yamashita	N/A	N/A
2018/0101925	12/2017	Brinig	N/A	N/A
2018/0156623	12/2017	West	N/A	N/A
2018/0211351	12/2017	Kim	N/A	N/A
2018/0285846	12/2017	Oesterling	N/A	N/A
2018/0339714	12/2017	Smid	N/A	N/A
2018/0342035	12/2017	Sweeney	N/A	N/A
2018/0356239	12/2017	Marco	N/A	N/A
2018/0374350	12/2017	Sweeney	N/A	N/A
2019/0130764	12/2018	Karani	N/A	N/A
2019/0137288	12/2018	Rahematpura	N/A	N/A
2019/0244318	12/2018	Rajcok	N/A	N/A
2019/0265703	12/2018	Hicok	N/A	N/A
2019/0272486	12/2018	Lord	N/A	N/A
2020/0105140	12/2019	Wang	N/A	N/A
2020/0211070	12/2019	Singh	N/A	N/A
2020/0258344	12/2019	Brinig	N/A	N/A
2020/0258386	12/2019	Lu	N/A	N/A
2020/0272957	12/2019	Lord	N/A	N/A
2020/0273337	12/2019	Sweeney	N/A	N/A
2020/0322451	12/2019	Cheng	N/A	N/A
2021/0337047	12/2020	Cheng	N/A	N/A
2021/0364300	12/2020	Rahematpura	N/A	N/A
2021/0365848	12/2020	Lord	N/A	G06Q 10/06311
2021/0407032	12/2020	Kim	N/A	N/A
2022/0044186	12/2021	Hayama	N/A	N/A
2022/0223043	12/2021	Sweeney	N/A	N/A
2022/0412748	12/2021	Lord	N/A	N/A
2023/0044882	12/2022	Lord	N/A	N/A
2024/0163349	12/2023	Cheng	N/A	N/A
2024/0169461	12/2023	Kim	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2604321	12/2005	CA	N/A
10201607712	12/2015	DE	N/A
2708850	12/2013	EP	N/A
2 501 075	12/2012	GB	N/A
2004-302941	12/2003	JP	N/A
2004-362271	12/2003	JP	N/A
10-2006-0081193	12/2005	KR	N/A
10-2011-0132765	12/2010	KR	N/A

10-2013-0130978	12/2012	KR	N/A
10-2014-0023541	12/2013	KR	N/A
WO 2002/0006994	12/2001	WO	N/A
WO 2011-120161	12/2010	WO	N/A
WO 2014-100584	12/2013	WO	N/A

OTHER PUBLICATIONS

Fay et al., Decentralized routing control for guided transportation systems, 2008, IEEE, p. 1481-1487 (Year: 2008). cited by examiner

Duinkerken et al., Dynamic Free Range Routing for Automated Guided Vehicles, 2006, IEEE, p. 312-317 (Year: 2006). cited by examiner

Norman, A recursive method for traffic management through a complex path network, 2002, IEEE, p. 537-541 (Year: 2002). cited by examiner

Renaudin et al., Engineering, Human, and Legal Challenges of Navigation Systems for Personal Mobility, 2016, IEEE, p. 177-191 (Year: 2016). cited by examiner

Fang, Zhihan, MAC: Measuring the Impacts of Anomalies on Travel Time of Multiple Transportation Systems, Proc. ACM Interact. Mob. Wearable Ubiquitous Technol. 3, 2, Article 42 (Jun. 2019), 24 pages. cited by applicant

Petros, Lalos “A framework for dynamic car and taxi pools with the Use of Positioning Systems”, Future Computing, Service Computation, Cognitive, Adaptive Content, Patters, 2009. Computationword 09. Computation World: IEEE, Piscataway, NJ, USA, Nov. 15, 2009, pp. 385-391. cited by applicant

W. He, “Intelligent Carpool Routing for Urban Ridesharing by Mining GPS Trajectories” IEEE Transactions on Intelligent Transportation Systems, V. 15, No. 5, pp. 2286-2296, Oct. 2014. cited by applicant

Yaoping Zhang—Vehicle scheme of Evacuated Tube Transportation in the future logistics system, Computer and Automation Engineering (ICCAE), 2010 The 2nd Internatoinal Conference on, IEEE, Piscataway, NJ, USA, Feb. 26, 2010, pp. 190-192. cited by applicant

Amey, Utilizing Mobile Phone Technology to Improve Rideshare Services, 2011 Transportation Research Board Annual Meeting. cited by applicant

Andrew J. Hawkins, Lyft is now suggesting more convenient pickup locations, because a little walking won't kill you. Jun. 26, 2017 The Verge (www.theverge.com). cited by applicant

Boufaied, A Diagnostic Approach for Advanced Tracking of Commercial Vehicles with Time Window Constraints, IEEE Transactions on Intelligent Systems, vol. 14, No. 3, Sep. 2013. cited by applicant

Dessouky, et al, Real-time scheduling rules for demand responsive transit systems, 1998 IEEE pp. 2956-2961. cited by applicant

Dillenburg, The Intelligent Travel Assistant, IEEE 5.SUP.th .International Conference on Intelligent Transportation Systems, Sep. 3-6, 2002, Singapore. cited by applicant

Exam Report No. 1 in AU 2016366687 dated Oct. 6, 2021 (UP-155AU). cited by applicant

Exam Report No. 2 in AU 2017328067 dated Jan. 20, 2022 (UP-174-1AU). cited by applicant

Fawcett, Supporting human interaction with the Sentinent Vehicle, 2002, IEEE. pp. 307-312 (2002). cited by applicant

Fay et al, Decentralized control strategies for transportation systems, 2005, IEEE p. 898-903. cited by applicant

Fay et al, Decentralizing routing control for guided transportation systems, 2008 IEEE. cited by applicant

Fougeres, A push service for carpooling, 2012 IEEE International Conference on Green Computing and Communications, Conference on Internet of Things, and on Cubler, Physical and Social Computing, 2012. cited by applicant

Guc, Real-time, Scalable Route Planning using a Stream-Processing Infrastructure, 2010 13th International IEEE, Annual Conference on Intelligent Transport Systems, Madeira Island, Portugal, Sep. 19-22, 2010. cited by applicant

Koscher, Experimental Security Analysis of a Modern Automobile, 2010, IEEE, pp. 447-462 (2010). cited by applicant

Lalos, A Framework for dynamic car and taxi pools with the use of Positioning Systems, 2009 Computation World: Future Computing, Service Computation, Cognitive, Adaptive, Content, Patterns 2009. cited by applicant

Megalingam, Automated Wireless Carpooling System for an Eco-Friendly Travel, 2011 IEEE. cited by applicant

Muter, A structured approach to anomaly detection for in-vehicle networks, 2010, IEEE, pp. 92-98 (2010). cited by applicant

Office Action in CA 3017638 dated Jun. 22, 2022 (UP-174-1CA). cited by applicant

Office Action in CA 3017822 dated Jun. 1, 2022 (UP-174-2CA). cited by applicant

Office Action in EP 17771000.1 dated Aug. 23, 2021 (UP-174-2EP). cited by applicant

Office Action in KR 10-2016-7034177 dated Mar. 30, 2022. cited by applicant

Pelzer, et al., "A Partition-Based Match Making Algorithm for Dynamic Ridesharing", IEEE Transactions on Intelligent Transportation Systems, vol. 16, Issue: 5, pp. 2587-2596 (2015). cited by applicant

Rathore, Integrating biometric sensors into automotive Internet of Things, 2014, IEEE pp. 178-181 (2014). cited by applicant

Shahzada, Dynamic Vehicle Navigation: An A* Algorithm Based Approach Using Traffic and Road Information, 2011 International Conference on Computer Applications and Industrial Electronics, (ICCAIE 2011). cited by applicant

Vaqar et al, Smart Protocol for Communication in Mobile Ad Hoc Networks of Vehicles, 2007, IEEE, p. 1-6. cited by applicant

Vaughan-Nichols, Will Mobile Computing's Future be Location, Location, Location? Industry Trends, IEEE Computer Society, 2009 IEEE. cited by applicant

Primary Examiner: Marc; McDieunel

Attorney, Agent or Firm: Mahamedi IP Law LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 17/965,182 filed Oct. 13, 2022, which is a continuation of U.S. patent application Ser. No. 16/849,984, filed Apr. 15, 2020, now U.S. Pat. No. 11,669,785, which is a continuation of U.S. patent application Ser. No. 15/985,652, filed May 21, 2018, now U.S. Pat. No. 10,657,468; which is a continuation of U.S. patent application Ser. No. 15/588,502, filed May 5, 2017, now U.S. Pat. No. 10,002,333; which is a continuation of U.S. patent application Ser. No. 14/621,151, filed Feb. 12, 2015, now U.S. Pat. No. 9,715,667; which is a continuation of U.S. patent application Ser. No. 14/619,812, filed Feb. 11, 2015, now U.S. Pat. No. 9,552,559; which is a continuation-in-part of U.S. patent application Ser. No. 14/597,631, filed Jan. 15, 2015, now U.S. Pat. No. 9,886,671; which is a continuation of U.S. patent application Ser. No. 14/596,904, filed Jan. 14, 2015, now U.S. Pat. No. 9,483,744; which is a continuation-in-part of U.S. patent application Ser. No. 14/564,358, filed Dec. 9, 2014, now U.S. Pat. No. 9,689,694; which is a continuation of U.S. patent application Ser. No. 14/563,134, filed Dec. 8, 2014, now U.S. Pat. No.

9,671,239; which is a continuation of U.S. patent application Ser. No. 14/537,313 filed Nov. 10, 2014, now U.S. Pat. No. 9,558,469; which is a continuation of U.S. patent application Ser. No. 14/536,967, filed Nov. 10, 2014, now U.S. Pat. No. 9,792,574; which is a continuation-in-part of U.S. patent application Ser. No. 14/511,706, filed Oct. 10, 2014, now U.S. Pat. No. 9,767,423; which is a continuation of U.S. patent application Ser. No. 14/510,383, filed Oct. 9, 2014, now U.S. Pat. No. 9,569,740; which is a continuation-in-part of U.S. patent application Ser. No. 14/476,042, filed Sep. 3, 2014, now U.S. Pat. No. 9,488,484; which is a continuation of U.S. patent application Ser. No. 14/474,587, filed Sep. 2, 2014, now U.S. Pat. No. 9,599,481; which is a continuation-in-part of U.S. patent application Ser. No. 14/456,627, filed Aug. 11, 2014, now U.S. Pat. No. 9,534,912; which is a continuation of U.S. patent application Ser. No. 14/455,534, filed Aug. 8, 2014, now U.S. Pat. No. 9,581,455; which is a continuation-in-part of U.S. patent application Ser. No. 14/329,451, filed Jul. 11, 2014; which is a continuation of U.S. patent application Ser. No. 14/328,002, filed Jul. 10, 2014, now U.S. Pat. No. 10,458,801; which is a continuation-in-part of U.S. patent application Ser. No. 14/318,182, filed Jun. 27, 2014; which claims the benefit of U.S. Provisional Patent Application No. 61/989,394; filed May 6, 2014; all of the aforementioned priority applications being hereby incorporated by reference in their respective entireties.

SUMMARY OF THE INVENTION

(1) In one or more various aspects, a method includes, but is not limited to, receiving one or more first directives that direct a transportation vehicle unit to transport a first end user, receiving, while the transportation vehicle unit is en route to or is transporting the first end user, one or more second directives that direct the transportation vehicle unit to transport a second end user while transporting the first end user, the transportation vehicle unit having been determined to be able to accommodate transport of the second end user while transporting the first end user; and verifying that compliance with the one or more second directives will not conflict with one or more obligations to transport the first end user by the transportation vehicle unit. In various implementations, at least one of the above operations is performed by a machine or an article of manufacture. In addition to the foregoing, other method aspects are described in the claims, drawings, and text forming a part of the disclosure set forth herein.

(2) In one or more various aspects, one or more related systems may be implemented in machines, compositions of matter, or manufactures of systems, limited to patentable subject matter under 35 U.S.C. 101. The one or more related systems may include, but are not limited to, circuitry and/or programming for effecting the herein-referenced method aspects. The circuitry and/or programming may be virtually any combination of hardware, software, and/or firmware configured to effect the herein-referenced method aspects depending upon the design choices of the system designer, and limited to patentable subject matter under 35 USC 101.

(3) In one or more various aspects, a system includes, but is not limited to, means for receiving one or more first directives that direct a transportation vehicle unit to transport a first end user, means for receiving, while the transportation vehicle unit is en route to or is transporting the first end user, one or more second directives that direct the transportation vehicle unit to transport a second end user while transporting the first end user, the transportation vehicle unit having been determined to be able to accommodate transport of the second end user while transporting the first end user; and means for verifying that compliance with the one or more second directives will not conflict with one or more obligations to transport the first end user by the transportation vehicle unit. In addition to the foregoing, other system aspects are described in the claims, drawings, and text forming a part of the disclosure set forth herein.

(4) In one or more various aspects, a system includes, but is not limited to, circuitry for receiving one or more first directives that direct a transportation vehicle unit to transport a first end user, circuitry for receiving, while the transportation vehicle unit is en route to or is transporting the first end user, one or more second directives that direct the transportation vehicle unit to transport a

second end user while transporting the first end user, the transportation vehicle unit having been determined to be able to accommodate transport of the second end user while transporting the first end user; and circuitry for verifying that compliance with the one or more second directives will not conflict with one or more obligations to transport the first end user by the transportation vehicle unit. In addition to the foregoing, other system aspects are described in the claims, drawings, and text forming a part of the disclosure set forth herein.

(5) In one or more various aspects, a computer program product, comprising a signal bearing non-transitory storage medium, bearing one or more instructions including, but not limited to, receiving one or more first directives that direct a transportation vehicle unit to transport a first end user, receiving, while the transportation vehicle unit is en route to or is transporting the first end user, one or more second directives that direct the transportation vehicle unit to transport a second end user while transporting the first end user, the transportation vehicle unit having been determined to be able to accommodate transport of the second end user while transporting the first end user, and verifying that compliance with the one or more second directives will not conflict with one or more obligations to transport the first end user by the transportation vehicle unit. In addition to the foregoing, other computer program product aspects are described in the claims, drawings, and text forming a part of the disclosure set forth herein.

(6) In one or more various aspects, a system includes, but is not limited to, a directive receiving module configured to receive, while a transportation vehicle unit is en route to or is transporting a first end user, one or more directives that direct the transportation vehicle unit to transport a second end user while transporting the first end user, the transportation vehicle unit having been determined to be able to accommodate transport of the second end user while transporting the first end user; a non-conflict confirming module configured to confirm that compliance with the one or more second directives will not conflict with one or more obligations to transport the first end user by the transportation vehicle unit; a memory, and one or more processors.

(7) In one or more various aspects, a system includes, but is not limited to, circuitry for receiving, while a transportation vehicle unit is en route to or is transporting a first end user, one or more directives that direct the transportation vehicle unit to transport a second end user while transporting the first end user, the transportation vehicle unit having been determined to be able to accommodate transport of the second end user while transporting the first end user; and circuitry for confirming that compliance with the one or more second directives will not conflict with one or more obligations to transport the first end user by the transportation vehicle unit.

(8) In addition to the foregoing, various other method and/or system and/or program product aspects are set forth and described in the teachings such as text (e.g., claims and/or detailed description) and/or drawings of the present disclosure.

(9) The foregoing is a summary and thus may contain simplifications, generalizations, inclusions, and/or omissions of detail; consequently, those skilled in the art will appreciate that the summary is illustrative only and is NOT intended to be in any way limiting. Other aspects, features, and advantages of the devices and/or processes and/or other subject matter described herein will become apparent by reference to the detailed description, the corresponding drawings, and/or in the teachings set forth herein.

Description

BRIEF DESCRIPTION OF FIGURES

(1) For a more complete understanding of embodiments, reference now is made to the following descriptions taken in connection with the accompanying drawings. The use of the same symbols in different drawings typically indicates similar or identical items, unless context dictates otherwise. The illustrative embodiments described in the detailed description, drawings, and claims are not

meant to be limiting. Other embodiments may be utilized, and other changes may be made, without departing from the spirit or scope of the subject matter presented here.

(2) FIG. 1 illustrates a transport computing device **10*** operating in an exemplary environment

(3) FIG. 2A shows a high-level block diagram of a particular implementation of the transport computing device **10*** of FIG. 1 (illustrated as transport computing device **10'**).

(4) FIG. 2B shows another high-level block diagram of another implementation of the transport computing device **10*** of FIG. 1 (illustrated as transport computing device **10''**).

(5) FIG. 3A shows another perspective of the directive receiving module **202*** of FIGS. 2A and 2B (e.g., the directive receiving module **202'** of FIG. 2A or the directive receiving module **202''** of FIG. 2B) in accordance with various embodiments.

(6) FIG. 3B shows another perspective of the non-conflict confirming module **204*** of FIGS. 2A and 2B (e.g., the non-conflict confirming module **204'** of FIG. 2A or the non-conflict confirming module **204''** of FIG. 2B) in accordance with various embodiments.

(7) FIG. 3C shows another perspective of the instructive directive presenting module **208*** of FIGS. 2A and 2B (e.g., the instructive directive presenting module **208'** of FIG. 2A or the instructive directive presenting module **208''** of FIG. 2B) in accordance with various embodiments.

(8) FIG. 4A illustrates an exemplary route that an example transportation vehicle unit **20** of FIG. 1 may use in order to transport carpooling passengers.

(9) FIG. 4B illustrates another exemplary route that the example transportation vehicle unit **20** of FIG. 1 may use in order to transport carpooling passengers.

(10) FIG. 4C illustrates another exemplary route that the example transportation vehicle unit **20** of FIG. 1 may use in order to transport carpooling passengers.

(11) FIG. 4D illustrates another exemplary route that the example transportation vehicle unit **20** of FIG. 1 may use in order to transport carpooling passengers.

(12) FIG. 4E illustrates an exemplary robotic driver system **450** that includes the transport computing device **10*** of FIG. 2A or 2B.

(13) FIG. 5 is a high-level logic flowchart of a process, e.g., operational flow **500**, according to some embodiments.

(14) FIG. 6A is a high-level logic flowchart of a process depicting alternate implementations of the first directive receiving operation **502** of FIG. 5.

(15) FIG. 6B is a high-level logic flowchart of a process depicting alternate implementations of the first directive receiving operation **502** of FIG. 5.

(16) FIG. 6C is a high-level logic flowchart of a process depicting alternate implementations of the first directive receiving operation **502** of FIG. 5.

(17) FIG. 6D is a high-level logic flowchart of a process depicting alternate implementations of the first directive receiving operation **502** of FIG. 5.

(18) FIG. 7A is a high-level logic flowchart of a process depicting alternate implementations of the second directive receiving operation **504** of FIG. 5.

(19) FIG. 7B is a high-level logic flowchart of a process depicting alternate implementations of the second directive receiving operation **504** of FIG. 5.

(20) FIG. 7C is a high-level logic flowchart of a process depicting alternate implementations of the second directive receiving operation **504** of FIG. 5.

(21) FIG. 7D is a high-level logic flowchart of a process depicting alternate implementations of the second directive receiving operation **504** of FIG. 5.

(22) FIG. 8A is a high-level logic flowchart of a process depicting alternate implementations of the non-conflict verifying operation **506** of FIG. 5.

(23) FIG. 8B is a high-level logic flowchart of a process depicting alternate implementations of the non-conflict verifying operation **506** of FIG. 5.

(24) FIG. 8C is a high-level logic flowchart of a process depicting alternate implementations of the non-conflict verifying operation **506** of FIG. 5.

- (25) FIG. 8D is a high-level logic flowchart of a process depicting alternate implementations of the non-conflict verifying operation **506** of FIG. 5.
- (26) FIG. 8E is a high-level logic flowchart of a process depicting alternate implementations of the non-conflict verifying operation **506** of FIG. 5.
- (27) FIG. 8F is a high-level logic flowchart of a process depicting alternate implementations of the non-conflict verifying operation **506** of FIG. 5.
- (28) FIG. 8G is a high-level logic flowchart of a process depicting alternate implementations of the non-conflict verifying operation **506** of FIG. 5.
- (29) FIG. 9 is a high-level logic flowchart of another process, e.g., operational flow **900**, according to some embodiments.
- (30) FIG. 10 is a high-level logic flowchart of yet another process, e.g., operational flow **1000**, according to some embodiments.
- (31) FIG. 11 is a high-level logic flowchart of a process depicting alternate implementations of the instructive directive presenting operation **1008** of FIG. 10.

DETAILED DESCRIPTION

- (32) In the following detailed description, reference is made to the accompanying drawings, which form a part hereof. In the drawings, similar symbols typically identify similar or identical components or items, unless context dictates otherwise. The illustrative embodiments described in the detailed description, drawings, and claims are not meant to be limiting. Other embodiments may be utilized, and other changes may be made, without departing from the spirit or scope of the subject matter presented here.
- (33) Thus, in accordance with various embodiments, computationally implemented methods, systems, circuitry, articles of manufacture, ordered chains of matter, and computer program products are designed to, among other things, provide one or more wearable computing devices for the environment illustrated in FIG. 1.
- (34) The claims, description, and drawings of this application may describe one or more of the instant technologies in operational/functional language, for example as a set of operations to be performed by a computer. Such operational/functional description in most instances would be understood by one skilled the art as specifically-configured hardware (e.g., because a general purpose computer in effect becomes a special purpose computer once it is programmed to perform particular functions pursuant to instructions from program software).
- (35) Importantly, although the operational/functional descriptions described herein are understandable by the human mind, they are not abstract ideas of the operations/functions divorced from computational implementation of those operations/functions. Rather, the operations/functions represent a specification for the massively complex computational machines or other means. As discussed in detail below, the operational/functional language must be read in its proper technological context, i.e., as concrete specifications for physical implementations.
- (36) The logical operations/functions described herein are a distillation of machine specifications or other physical mechanisms specified by the operations/functions such that the otherwise inscrutable machine specifications may be comprehensible to the human mind. The distillation also allows one of skill in the art to adapt the operational/functional description of the technology across many different specific vendors' hardware configurations or platforms, without being limited to specific vendors' hardware configurations or platforms.
- (37) Some of the present technical description (e.g., detailed description, drawings, claims, etc.) may be set forth in terms of logical operations/functions. As described in more detail in the following paragraphs, these logical operations/functions are not representations of abstract ideas, but rather representative of static or sequenced specifications of various hardware elements. Differently stated, unless context dictates otherwise, the logical operations/functions will be understood by those of skill in the art to be representative of static or sequenced specifications of various hardware elements. This is true because tools available to one of skill in the art to

implement technical disclosures set forth in operational/functional formats-tools in the form of a high-level programming language (e.g., C, java, visual basic, etc.), or tools in the form of Very high speed Hardware Description Language (“VHDL,” which is a language that uses text to describe logic circuits)—are generators of static or sequenced specifications of various hardware configurations. This fact is sometimes obscured by the broad term “software,” but, as shown by the following explanation, those skilled in the art understand that what is termed “software” is a shorthand for a massively complex interchanging/specification of ordered-matter elements. The term “ordered-matter elements” may refer to physical components of computation, such as assemblies of electronic logic gates, molecular computing logic constituents, quantum computing mechanisms, etc.

(38) For example, a high-level programming language is a programming language with strong abstraction, e.g., multiple levels of abstraction, from the details of the sequential organizations, states, inputs, outputs, etc., of the machines that a high-level programming language actually specifies. See, e.g., Wikipedia, High-level programming language, http://en.wikipedia.org/wiki/High-level_programming_language (as of Jun. 5, 2012, 21:00 GMT). In order to facilitate human comprehension, in many instances, high-level programming languages resemble or even share symbols with natural languages. See, e.g., Wikipedia, Natural language, http://en.wikipedia.org/wiki/Natural_language (as of Jun. 5, 2012, 21:00 GMT).

(39) It has been argued that because high-level programming languages use strong abstraction (e.g., that they may resemble or share symbols with natural languages), they are therefore a “purely mental construct” (e.g., that “software”—a computer program or computer programming—is somehow an ineffable mental construct, because at a high level of abstraction, it can be conceived and understood in the human mind). This argument has been used to characterize technical description in the form of functions/operations as somehow “abstract ideas.” In fact, in technological arts (e.g., the information and communication technologies) this is not true.

(40) The fact that high-level programming languages use strong abstraction to facilitate human understanding should not be taken as an indication that what is expressed is an abstract idea. In fact, those skilled in the art understand that just the opposite is true. If a high-level programming language is the tool used to implement a technical disclosure in the form of functions/operations, those skilled in the art will recognize that, far from being abstract, imprecise, “fuzzy,” or “mental” in any significant semantic sense, such a tool is instead a near incomprehensibly precise sequential specification of specific computational machines—the parts of which are built up by activating/selecting such parts from typically more general computational machines over time (e.g., clocked time). This fact is sometimes obscured by the superficial similarities between high-level programming languages and natural languages. These superficial similarities also may cause a glossing over of the fact that high-level programming language implementations ultimately perform valuable work by creating/controlling many different computational machines.

(41) The many different computational machines that a high-level programming language specifies are almost unimaginably complex. At base, the hardware used in the computational machines typically consists of some type of ordered matter (e.g., traditional external linking devices (e.g., transistors), deoxyribonucleic acid (DNA), quantum devices, mechanical switches, optics, fluidics, pneumatics, optical devices (e.g., optical interference devices, molecules, etc.) that are arranged to form logic gates. Logic gates are typically physical devices that may be electrically, mechanically, chemically, or otherwise driven to change physical state in order to create a physical reality of Boolean logic.

(42) Logic gates may be arranged to form logic circuits, which are typically physical devices that may be electrically, mechanically, chemically, or otherwise driven to create a physical reality of certain logical functions. Types of logic circuits include such devices as multiplexers, registers, arithmetic logic units (ALUs), computer memory, etc., each type of which may be combined to form yet other types of physical devices, such as a central processing unit (CPU)—the best known

of which is the microprocessor. A modern microprocessor will often contain more than one hundred million logic gates in its many logic circuits (and often more than a billion transistors). See, e.g., Wikipedia, Logic gates,

(43) http://en.wikipedia.org/wiki/Logic_gates (as of Jun. 5, 2012, 21:03 GMT).

(44) The logic circuits forming the microprocessor are arranged to provide a microarchitecture that will carry out the instructions defined by that microprocessor's defined Instruction Set Architecture. The Instruction Set Architecture is the part of the microprocessor architecture related to programming, including the native data types, instructions, registers, addressing modes, memory architecture, interrupt and exception handling, and external Input/Output. See, e.g., Wikipedia, Computer architecture,

(45) http://en.wikipedia.org/wiki/Computer_architecture (as of Jun. 5, 2012, 21:03 GMT).

(46) The Instruction Set Architecture includes a specification of the machine language that can be used by programmers to use/control the microprocessor. Since the machine language instructions are such that they may be executed directly by the microprocessor, typically they consist of strings of binary digits, or bits. For example, a typical machine language instruction might be many bits long (e.g., 32, 64, or 128 bit strings are currently common). A typical machine language instruction might take the form

(47) “11110000101011110000111100111111” (a 32 bit instruction).

(48) It is significant here that, although the machine language instructions are written as sequences of binary digits, in actuality those binary digits specify physical reality. For example, if certain semiconductors are used to make the operations of Boolean logic a physical reality, the apparently mathematical bits “1” and “0” in a machine language instruction actually constitute shorthand that specifies the application of specific voltages to specific wires. For example, in some semiconductor technologies, the binary number “1” (e.g., logical “1”) in a machine language instruction specifies around +5 volts applied to a specific “wire” (e.g., metallic traces on a printed circuit board) and the binary number “0” (e.g., logical “0”) in a machine language instruction specifies around –5 volts applied to a specific “wire.” In addition to specifying voltages of the machines' configuration, such machine language instructions also select out and activate specific groupings of logic gates from the millions of logic gates of the more general machine. Thus, far from abstract mathematical expressions, machine language instruction programs, even though written as a string of zeros and ones, specify many, many constructed physical machines or physical machine states.

(49) Machine language is typically incomprehensible by most humans (e.g., the above example was just ONE instruction, and some personal computers execute more than two billion instructions every second). See, e.g., Wikipedia, Instructions per second,

http://en.wikipedia.org/wiki/Instructions_per_second (as of Jun. 5, 2012, 21:04 GMT). Thus, programs written in machine language—which may be tens of millions of machine language instructions long—are incomprehensible. In view of this, early assembly languages were developed that used mnemonic codes to refer to machine language instructions, rather than using the machine language instructions' numeric values directly (e.g., for performing a multiplication operation, programmers coded the abbreviation “mult,” which represents the binary number “011000” in MIPS machine code). While assembly languages were initially a great aid to humans controlling the microprocessors to perform work, in time the complexity of the work that needed to be done by the humans outstripped the ability of humans to control the microprocessors using merely assembly languages.

(50) At this point, it was noted that the same tasks needed to be done over and over, and the machine language necessary to do those repetitive tasks was the same. In view of this, compilers were created. A compiler is a device that takes a statement that is more comprehensible to a human than either machine or assembly language, such as “add 2+2 and output the result,” and translates that human understandable statement into a complicated, tedious, and immense machine language code (e.g., millions of 32, 64, or 128 bit length strings). Compilers thus translate high-level

programming language into machine language.

(51) This compiled machine language, as described above, is then used as the technical specification which sequentially constructs and causes the interoperation of many different computational machines such that humanly useful, tangible, and concrete work is done. For example, as indicated above, such machine language—the compiled version of the higher-level language—functions as a technical specification which selects out hardware logic gates, specifies voltage levels, voltage transition timings, etc., such that the humanly useful work is accomplished by the hardware.

(52) Thus, a functional/operational technical description, when viewed by one of skill in the art, is far from an abstract idea. Rather, such a functional/operational technical description, when understood through the tools available in the art such as those just described, is instead understood to be a humanly understandable representation of a hardware specification, the complexity and specificity of which far exceeds the comprehension of most any one human. With this in mind, those skilled in the art will understand that any such operational/functional technical descriptions—in view of the disclosures herein and the knowledge of those skilled in the art—may be understood as operations made into physical reality by (a) one or more interchained physical machines, (b) interchained logic gates configured to create one or more physical machine(s) representative of sequential/combinatorial logic(s), (c) interchained ordered matter making up logic gates (e.g., interchained electronic devices (e.g., transistors), DNA, quantum devices, mechanical switches, optics, fluidics, pneumatics, molecules, etc.) that create physical reality representative of logic(s), or (d) virtually any combination of the foregoing. Indeed, any physical object which has a stable, measurable, and changeable state may be used to construct a machine based on the above technical description. Charles Babbage, for example, constructed the first computer out of wood and powered by cranking a handle.

(53) Thus, far from being understood as an abstract idea, those skilled in the art will recognize a functional/operational technical description as a humanly-understandable representation of one or more almost unimaginably complex and time sequenced hardware instantiations. The fact that functional/operational technical descriptions might lend themselves readily to high-level computing languages (or high-level block diagrams for that matter) that share some words, structures, phrases, etc. with natural language simply cannot be taken as an indication that such functional/operational technical descriptions are abstract ideas, or mere expressions of abstract ideas. In fact, as outlined herein, in the technological arts this is simply not true. When viewed through the tools available to those of skill in the art, such functional/operational technical descriptions are seen as specifying hardware configurations of almost unimaginable complexity.

(54) As outlined above, the reason for the use of functional/operational technical descriptions is at least twofold. First, the use of functional/operational technical descriptions allows near-infinitely complex machines and machine operations arising from interchained hardware elements to be described in a manner that the human mind can process (e.g., by mimicking natural language and logical narrative flow). Second, the use of functional/operational technical descriptions assists the person of skill in the art in understanding the described subject matter by providing a description that is more or less independent of any specific vendor's piece(s) of hardware.

(55) The use of functional/operational technical descriptions assists the person of skill in the art in understanding the described subject matter since, as is evident from the above discussion, one could easily, although not quickly, transcribe the technical descriptions set forth in this document as trillions of ones and zeroes, billions of single lines of assembly-level machine code, millions of logic gates, thousands of gate arrays, or any number of intermediate levels of abstractions. However, if any such low-level technical descriptions were to replace the present technical description, a person of skill in the art could encounter undue difficulty in implementing the disclosure, because such a low-level technical description would likely add complexity without a corresponding benefit (e.g., by describing the subject matter utilizing the conventions of one or

more vendor-specific pieces of hardware). Thus, the use of functional/operational technical descriptions assists those of skill in the art by separating the technical descriptions from the conventions of any vendor-specific piece of hardware.

(56) In view of the foregoing, the logical operations/functions set forth in the present technical description are representative of static or sequenced specifications of various ordered-matter elements, in order that such specifications may be comprehensible to the human mind and adaptable to create many various hardware configurations. The logical operations/functions disclosed herein should be treated as such, and should not be disparagingly characterized as abstract ideas merely because the specifications they represent are presented in a manner that one of skill in the art can readily understand and apply in a manner independent of a specific vendor's hardware implementation.

(57) Those having skill in the art will recognize that the state of the art has progressed to the point where there is little distinction left between hardware, software, and/or firmware implementations of aspects of systems; the use of hardware, software, and/or firmware is generally (but not always, in that in certain contexts the choice between hardware and software can become significant) a design choice representing cost vs. efficiency tradeoffs. Those having skill in the art will appreciate that there are various vehicles by which processes and/or systems and/or other technologies described herein can be effected (e.g., hardware, software, and/or firmware), and that the preferred vehicle will vary with the context in which the processes and/or systems and/or other technologies are deployed. For example, if an implementer determines that speed and accuracy are paramount, the implementer may opt for a mainly hardware and/or firmware vehicle; alternatively, if flexibility is paramount, the implementer may opt for a mainly software implementation; or, yet again alternatively, the implementer may opt for some combination of hardware, software, and/or firmware in one or more machines, compositions of matter, and articles of manufacture, limited to patentable subject matter under 35 USC 101. Hence, there are several possible vehicles by which the processes and/or devices and/or other technologies described herein may be effected, none of which is inherently superior to the other in that any vehicle to be utilized is a choice dependent upon the context in which the vehicle will be deployed and the specific concerns (e.g., speed, flexibility, or predictability) of the implementer, any of which may vary. Those skilled in the art will recognize that optical aspects of implementations will typically employ optically-oriented hardware, software, and or firmware.

(58) In some implementations described herein, logic and similar implementations may include software or other control structures. Electronic circuitry, for example, may have one or more paths of electrical current constructed and arranged to implement various functions as described herein. In some implementations, one or more media may be configured to bear a device-detectable implementation when such media holds or transmits device detectable instructions operable to perform as described herein. In some variants, for example, implementations may include an update or modification of existing software or firmware, or of gate arrays or programmable hardware, such as by performing a reception of or a transmission of one or more instructions in relation to one or more operations described herein. Alternatively or additionally, in some variants, an implementation may include special-purpose hardware, software, firmware components, and/or general-purpose components executing or otherwise invoking special-purpose components. Specifications or other implementations may be transmitted by one or more instances of tangible transmission media as described herein, optionally by packet transmission or otherwise by passing through distributed media at various times.

(59) Alternatively or additionally, implementations may include executing a special-purpose instruction sequence or invoking circuitry for enabling, triggering, coordinating, requesting, or otherwise causing one or more occurrences of virtually any functional operations described herein. In some variants, operational or other logical descriptions herein may be expressed as source code and compiled or otherwise invoked as an executable instruction sequence. In some contexts, for

example, implementations may be provided, in whole or in part, by source code, such as C++, or other code sequences. In other implementations, source or other code implementation, using commercially available and/or techniques in the art, may be compiled//implemented/translated/converted into a high-level descriptor language (e.g., initially implementing described technologies in C or C++ programming language and thereafter converting the programming language implementation into a logic-synthesizable language implementation, a hardware description language implementation, a hardware design simulation implementation, and/or other such similar mode(s) of expression). For example, some or all of a logical expression (e.g., computer programming language implementation) may be manifested as a Verilog-type hardware description (e.g., via Hardware Description Language (HDL) and/or Very High Speed Integrated Circuit Hardware Descriptor Language (VHDL)) or other circuitry model which may then be used to create a physical implementation having hardware (e.g., an Application Specific Integrated Circuit). Those skilled in the art will recognize how to obtain, configure, and optimize suitable transmission or computational elements, material supplies, actuators, or other structures in light of these teachings.

(60) Those skilled in the art will recognize that it is common within the art to implement devices and/or processes and/or systems, and thereafter use engineering and/or other practices to integrate such implemented devices and/or processes and/or systems into more comprehensive devices and/or processes and/or systems. That is, at least a portion of the devices and/or processes and/or systems described herein can be integrated into other devices and/or processes and/or systems via a reasonable amount of experimentation. Those having skill in the art will recognize that examples of such other devices and/or processes and/or systems might include—as appropriate to context and application—all or part of devices and/or processes and/or systems of (a) an air conveyance (e.g., an airplane, rocket, helicopter, etc.), (b) a ground conveyance (e.g., a car, truck, locomotive, tank, armored personnel carrier, etc.), (c) a building (e.g., a home, warehouse, office, etc.), (d) an appliance (e.g., a refrigerator, a washing machine, a dryer, etc.), (e) a communications system (e.g., a networked system, a telephone system, a Voice over IP system, etc.), (f) a business entity (e.g., an Internet Service Provider (ISP) entity such as Comcast Cable, Qwest, Southwestern Bell, etc.), or (g) a wired/wireless services entity (e.g., Sprint, Cingular, Nextel, etc.), etc.

(61) In certain cases, use of a system or method may occur in a territory even if components are located outside the territory. For example, in a distributed computing context, use of a distributed computing system may occur in a territory even though parts of the system may be located outside of the territory (e.g., relay, server, processor, signal-bearing medium, transmitting computer, receiving computer, etc. located outside the territory).

(62) A sale of a system or method may likewise occur in a territory even if components of the system or method are located and/or used outside the territory. Further, implementation of at least part of a system for performing a method in one territory does not preclude use of the system in another territory

(63) In a general sense, those skilled in the art will recognize that the various embodiments described herein can be implemented, individually and/or collectively, by various types of electro-mechanical systems having a wide range of electrical components such as hardware, software, firmware, and/or virtually any combination thereof, limited to patentable subject matter under 35 U.S.C. 101; and a wide range of components that may impart mechanical force or motion such as rigid bodies, spring or torsional bodies, hydraulics, electro-magnetically actuated devices, and/or virtually any combination thereof. Consequently, as used herein, “electro-mechanical system” includes, but is not limited to, electrical circuitry operably coupled with a transducer (e.g., an actuator, a motor, a piezoelectric crystal, a Micro Electro Mechanical System (MEMS), etc.), electrical circuitry having at least one discrete electrical circuit, electrical circuitry having at least one integrated circuit, electrical circuitry having at least one application specific integrated circuit, electrical circuitry forming a general purpose computing device configured by a computer program

(e.g., a general purpose computer configured by a computer program which at least partially carries out processes and/or devices described herein, or a microprocessor configured by a computer program which at least partially carries out processes and/or devices described herein), electrical circuitry forming a memory device (e.g., forms of memory (e.g., random access, flash, read only, etc.)), electrical circuitry forming a communications device (e.g., a modem, communications switch, optical-electrical equipment, etc.), and/or any non-electrical analog thereto, such as optical or other analogs (e.g., graphene based circuitry). Those skilled in the art will also appreciate that examples of electro-mechanical systems include, but are not limited to, a variety of consumer electronics systems, medical devices, as well as other systems such as motorized transport systems, factory automation systems, security systems, and/or communication/computing systems. Those skilled in the art will recognize that electro-mechanical as used herein is not necessarily limited to a system that has both electrical and mechanical actuation except as context may dictate otherwise.

(64) In a general sense, those skilled in the art will recognize that the various aspects described herein which can be implemented, individually and/or collectively, by a wide range of hardware, software, firmware, and/or any combination thereof can be viewed as being composed of various types of “electrical circuitry.” Consequently, as used herein “electrical circuitry” includes, but is not limited to, electrical circuitry having at least one discrete electrical circuit, electrical circuitry having at least one integrated circuit, electrical circuitry having at least one application specific integrated circuit, electrical circuitry forming a general purpose computing device configured by a computer program (e.g., a general purpose computer configured by a computer program which at least partially carries out processes and/or devices described herein, or a microprocessor configured by a computer program which at least partially carries out processes and/or devices described herein), electrical circuitry forming a memory device (e.g., forms of memory (e.g., random access, flash, read only, etc.)), and/or electrical circuitry forming a communications device (e.g., a modem, communications switch, optical-electrical equipment, etc.). Those having skill in the art will recognize that the subject matter described herein may be implemented in an analog or digital fashion or some combination thereof.

(65) Those skilled in the art will recognize that at least a portion of the devices and/or processes described herein can be integrated into an image processing system. Those having skill in the art will recognize that a typical image processing system generally includes one or more of a system unit housing, a video display device, memory such as volatile or non-volatile memory, processors such as microprocessors or digital signal processors, computational entities such as operating systems, drivers, application programs, one or more interaction devices (e.g., a touch pad, a touch screen, an antenna, etc.), and/or control systems including feedback loops and control motors (e.g., feedback for sensing lens position and/or velocity; control motors for moving/distorting lenses to give desired focuses). An image processing system may be implemented utilizing suitable commercially available components, such as those typically found in digital still systems and/or digital motion systems.

(66) Those skilled in the art will recognize that at least a portion of the devices and/or processes described herein can be integrated into a data processing system. Those having skill in the art will recognize that a data processing system generally includes one or more of a system unit housing, a video display device, memory such as volatile or non-volatile memory, processors such as microprocessors or digital signal processors, computational entities such as operating systems, drivers, graphical user interfaces, and application programs, one or more interaction devices (e.g., a touch pad, a touch screen, an antenna, etc.), and/or control systems including feedback loops and control motors (e.g., feedback for sensing position and/or velocity; control motors for moving and/or adjusting components and/or quantities). A data processing system may be implemented utilizing suitable commercially available components, such as those typically found in data computing/communication and/or network computing/communication systems.

(67) Those skilled in the art will recognize that at least a portion of the devices and/or processes

described herein can be integrated into a mote system. Those having skill in the art will recognize that a typical mote system generally includes one or more memories such as volatile or non-volatile memories, processors such as microprocessors or digital signal processors, computational entities such as operating systems, user interfaces, drivers, sensors, actuators, application programs, one or more interaction devices (e.g., an antenna USB ports, acoustic ports, etc.), control systems including feedback loops and control motors (e.g., feedback for sensing or estimating position and/or velocity, control motors for moving and/or adjusting components and/or quantities). A mote system may be implemented utilizing suitable components, such as those found in mote computing/communication systems. Specific examples of such components entail such as Intel Corporation's and/or Crossbow Corporation's mote components and supporting hardware, software, and/or firmware.

(68) For the purposes of this application, “cloud” computing may be understood as described in the cloud computing literature. For example, cloud computing may be methods and/or systems for the delivery of computational capacity and/or storage capacity as a service. The “cloud” may refer to one or more hardware and/or software components that deliver or assist in the delivery of computational and/or storage capacity, including, but not limited to, one or more of a client, an application, a platform, an infrastructure, and/or a server. The cloud may refer to any of the hardware and/or software associated with a client, an application, a platform, an infrastructure, and/or a server. For example, cloud and cloud computing may refer to one or more of a computer, a processor, a storage medium, a router, a switch, a modem, a virtual machine (e.g., a virtual server), a data center, an operating system, a middleware, a firmware, a hardware back-end, a software back-end, and/or a software application. A cloud may refer to a private cloud, a public cloud, a hybrid cloud, and/or a community cloud. A cloud may be a shared pool of configurable computing resources, which may be public, private, semi-private, distributable, scaleable, flexible, temporary, virtual, and/or physical. A cloud or cloud service may be delivered over one or more types of network, e.g., a mobile communication network, and the Internet.

(69) As used in this application, a cloud or a cloud service may include one or more of infrastructure-as-a-service (“IaaS”), platform-as-a-service (“PaaS”), software-as-a-service (“SaaS”), and/or desktop-as-a-service (“DaaS”). As a non-exclusive example, IaaS may include, e.g., one or more virtual server instantiations that may start, stop, access, and/or configure virtual servers and/or storage centers (e.g., providing one or more processors, storage space, and/or network resources on-demand, e.g., EMC and Rackspace). PaaS may include, e.g., one or more software and/or development tools hosted on an infrastructure (e.g., a computing platform and/or a solution stack from which the client can create software interfaces and applications, e.g., Microsoft Azure). SaaS may include, e.g., software hosted by a service provider and accessible over a network (e.g., the software for the application and/or the data associated with that software application may be kept on the network, e.g., Google Apps, Salesforce). DaaS may include, e.g., providing desktop, applications, data, and/or services for the user over a network (e.g., providing a multi-application framework, the applications in the framework, the data associated with the applications, and/or services related to the applications and/or the data over the network, e.g., Citrix). The foregoing is intended to be exemplary of the types of systems and/or methods referred to in this application as “cloud” or “cloud computing” and should not be considered complete or exhaustive.

(70) One skilled in the art will recognize that the herein described components (e.g., operations), devices, objects, and the discussion accompanying them are used as examples for the sake of conceptual clarity and that various configuration modifications are contemplated. Consequently, as used herein, the specific exemplars set forth and the accompanying discussion are intended to be representative of their more general classes. In general, use of any specific exemplar is intended to be representative of its class, and the non-inclusion of specific components (e.g., operations), devices, and objects should not be taken as limiting.

(71) The herein described subject matter sometimes illustrates different components contained within, or connected with, different other components. It is to be understood that such depicted architectures are merely exemplary, and that in fact many other architectures may be implemented which achieve the same functionality. In a conceptual sense, any arrangement of components to achieve the same functionality is effectively “associated” such that the desired functionality is achieved. Hence, any two components herein combined to achieve a particular functionality can be seen as “associated with” each other such that the desired functionality is achieved, irrespective of architectures or intermedial components. Likewise, any two components so associated can also be viewed as being “operably connected” or “operably coupled” to each other to achieve the desired functionality, and any two components capable of being so associated can also be viewed as being “operably couplable” to each other to achieve the desired functionality. Specific examples of operably couplable include, but are not limited, to physically mateable and/or physically interacting components, and/or wirelessly interactable, and/or wirelessly interacting components, and/or logically interacting, and/or logically interactable components.

(72) To the extent that formal outline headings are present in this application, it is to be understood that the outline headings are for presentation purposes, and that different types of subject matter may be discussed throughout the application (e.g., device(s)/structure(s) may be described under process(es)/operations heading(s) and/or process(es)/operations may be discussed under structure(s)/process(es) headings and/or descriptions of single topics may span two or more topic headings). Hence, any use of formal outline headings in this application is for presentation purposes, and is not intended to be in any way limiting.

(73) Throughout this application, examples and lists are given, with parentheses, the abbreviation “e.g.,” or both. Unless explicitly otherwise stated, these examples and lists are merely exemplary and are non-exhaustive. In most cases, it would be prohibitive to list every example and every combination. Thus, smaller, illustrative lists and examples are used, with focus on imparting understanding of the claim terms rather than limiting the scope of such terms.

(74) With respect to the use of substantially any plural and/or singular terms herein, those having skill in the art can translate from the plural to the singular and/or from the singular to the plural as is appropriate to the context and/or application. The various singular/plural permutations are not expressly set forth herein for sake of clarity.

(75) One skilled in the art will recognize that the herein described components (e.g., operations), devices, objects, and the discussion accompanying them are used as examples for the sake of conceptual clarity and that various configuration modifications are contemplated. Consequently, as used herein, the specific exemplars set forth and the accompanying discussion are intended to be representative of their more general classes. In general, use of any specific exemplar is intended to be representative of its class, and the non-inclusion of specific components (e.g., operations), devices, and objects should not be taken as limiting.

(76) Although one or more users may be shown and/or described herein as a single illustrated figure, those skilled in the art will appreciate that one or more users may be representative of one or more human users, robotic users (e.g., computational entity), and/or substantially any combination thereof (e.g., a user may be assisted by one or more robotic agents) unless context dictates otherwise. Those skilled in the art will appreciate that, in general, the same may be said of “sender” and/or other entity-oriented terms as such terms are used herein unless context dictates otherwise.

(77) In some instances, one or more components may be referred to herein as “configured to,” “configured by,” “configurable to,” “operable/operative to,” “adapted/adaptable,” “able to,” “conformable/conformed to,” etc. Those skilled in the art will recognize that such terms (e.g. “configured to”) generally encompass active-state components and/or inactive-state components and/or standby-state components, unless context requires otherwise.

(78) In the following detailed description, reference is made to the accompanying drawings, which form a part hereof. In the drawings, similar symbols typically identify similar or identical

components or items, unless context dictates otherwise. The illustrative embodiments described in the detailed description, drawings, and claims are not meant to be limiting. Other embodiments may be utilized, and other changes may be made, without departing from the spirit or scope of the subject matter presented here.

(79) One of the newest trends in the field of transportation services particularly in urban settings is the development of transportation networking services provided by web-based companies such as Uber and Lyft that allow users to retain drivers/vehicles for transportation services through, for example, mobile applications. The increasingly popularity of such “ridesharing” services have already made some of the early entrants in this new field household names. As with many new technological ventures, the functionalities provided through such services are somewhat limited. However there appears to be ample opportunities for adding new and value adding functionalities to such services (as well as to more traditional transportation services such as Taxi services) in order to provide more robust transportation networking systems.

(80) Generally, these types of online transportation services provide services and functionalities that are already provided by traditional taxi and limo companies but being provided through the latest technological innovations (e.g., using the Internet and mobile devices, such as Smartphones, in order to request transport services). One possible future avenue for growth is providing true ridesharing services (e.g., carpooling) where a group of nonaffiliated passengers (e.g., passengers or end users who do not have any social, business, and/or professional relationship with each other) are assigned to be transported by a single vehicle (note that “passengers” and “end users” will be used interchangeably herein, thus, they are synonymous unless indicated otherwise). There are already a few online carpooling services that provide some level of true carpooling services. However, these carpooling services generally provide basic carpooling services (e.g., providing a listing of vehicles/drivers that are scheduled to depart at a particular future time from one departure point and going to a particular destination point) that typically require arrangements in advance of a carpooling trip (e.g., taking a group of unaffiliated end users from one or more rendezvous locations to one or more destination locations).

(81) Accordingly, network systems are proposed that coordinate matching of for-hire passenger vehicles (herein “transportation vehicle units”) to prospective carpooling passengers (e.g., end users) in real-time (e.g., to assign a prospective passenger to a carpooling vehicle that is already en route to or is already transporting other passengers). In some cases, these network systems may be able to coordinate the matching of a transportation vehicle unit with one or more end users (e.g., passengers or customers) even when, for example, the transportation vehicle unit is already en route to or is already transporting one or more other end users. The matching of a transportation vehicle unit that may already be transporting passengers (e.g., “old” passengers) with “new” passengers may be based on a number of factors including space availability of the transportation vehicle unit to accommodate the new passengers, the current location of the transportation vehicle unit relative to the pick-up or rendezvous location for the new passengers (which may be the current location of the new passengers), the proximity of the destination of the new passengers to the destination of the old passengers, and so forth.

(82) One drawback that these network systems (e.g., network servers) may have is that in some situations they may not always have the most up-to-date information related to current passenger transport obligations of transportation vehicle units. Thus, in order to ensure, for example, that a particular transportation vehicle unit will be able to transport one or more “new” end users without violating current passenger transport obligations of the transportation vehicle unit, systems and methods are provided herein that may be implemented locally at the transportation vehicle unit and that may be designed to, among other things, verify or confirm that one or more directives that direct the transportation vehicle unit, which is already en route to or is already transporting a first end user, to transport a second end user while transporting the first end user does not violate one or more obligations to transport the first end user (e.g., an obligation to transport the first end user to a

destination location without significant delays).

(83) In various embodiments, the verification or confirmation process may be performed by comparing the requirements for transporting the second end user to the requirements for transporting the first end user. In some embodiments, the systems and methods may be implemented by a transport computing device that may be associated with a transportation vehicle unit (which includes at least a transport vehicle such as a gas or electric powered vehicle and a human or robotic driver) that is already en route to secure the first end user or that is already transporting the first end user. In some cases, the transport computing device may be a mobile computing device such as a Smartphone or a tablet computer that executes specialized software, or may be a dedicated computing device with, for example, specialized hardware, software, and/or firmware and specifically tailored to perform the various functions and operations to be described herein.

(84) Referring now to FIG. 1, which illustrates a transport computing device **10*** operating in an exemplary environment **100**. In various embodiments, the various operations and functionalities to be described herein may be implemented by the transport computing device **10***, which in some cases, may be associated with a transportation vehicle unit **20**. The transport computing device **10*** may be designed to, among other things, receive one or more first directives that direct a transportation vehicle unit **20** to transport a first end user **12a**; receive while the transportation vehicle unit **20** is en route to or is transporting the first end user **12a**, one or more second directives that direct (e.g., instruct) the transportation vehicle unit **20** to transport a second end user **12b** while transporting the first end user **12a**, the transportation vehicle unit **20** having been determined (e.g., determined remotely by, for example, a real-time carpooling management system **16**) to be able to accommodate transport of the second end user **12b** while transporting the first end user **12a**; and verify or confirm that compliance with the one or more second directives will not conflict with one or more obligations to transport the first end user **12a** by the transportation vehicle unit **20**.

(85) Note that for purposes of the following description “*” represents a wildcard. Thus, references in the following description to, for example, “transport computing device **10***” may be in reference to the transport computing device **10'** of FIG. 2A, as well as to the transport computing device **10''** of FIG. 2B, which are two different implementations of the transport computing device **10*** of FIG. 1.

(86) Referring back to FIG. 1, in various embodiments, the transport computing vehicle unit **20** may be in communication with a variety of entities via one or more wireless and/or wired networks **18** including, for example, one or more end users **12*** (via one or more end user devices **14** such as Smartphones), a real-time carpooling coordinating system **15**, and/or a real-time carpooling management system **16**. In this example illustration, the end users **12*** (a first end user **12a** and a second end user **12b**) are unaffiliated parties needing transportation services. Note that for ease of illustration and explanation, only two end users, a first end user **12a** and a second end user **12b**, are illustrated in FIG. 1. However, those of ordinary skill in the art will recognize that in alternative embodiments many more end users **12*** (as well as many more transportation vehicle units **20**) may be included in the network environment of FIG. 1.

(87) The real-time carpooling management system **16** may be one or more network servers that coordinates and matches one or more end users **12*** to a transportation vehicle unit **20** for transport to their destinations. The matching operations performed by the real-time carpooling management system **16** may be as a result of making a determination as whether, for example, a particular transportation vehicle unit **20** is able to accommodate transport of one or more end users (e.g., the second end user **12b**) when the particular transportation vehicle unit **20** is already en route to or is already transporting one or more other end users (e.g., the first end user **12a**). A number of factors may be considered in determining whether the particular transportation vehicle unit **20** is able to accommodate transport of the one or more end users (the second end user **12b**) while transporting one or more other end users (e.g., the first end user **12a**) including, for example, whether there is

sufficient available passenger space for the end users (e.g., the second end user **12b**), whether the transportation vehicle unit **20** is in the proximate vicinity of the pickup location (e.g., rendezvous location which, in some cases, may be the current location) for the one or more end users (e.g., the second end user **12b**), whether the transportation vehicle unit **20** will be traveling near to the destination location of the one or more end users (e.g., the second end user **12b**), whether adding the one or more end users (e.g., the second end user **12b**) will cause significant delay to the transport of the one or more other end users (e.g., the first end user **12a**) in reaching the one or more other end users' destination(s), and so forth.

(88) The one or more wireless and/or wired networks **18** may comprise of, for example, one or more of a local area network (LAN), metropolitan area network (MAN), a wireless local area network (WLAN), a personal area network (PAN), a Worldwide Interoperability for Microwave Access (WiMAX), public switched telephone network (PTSN), a general packet radio service (GPRS) network, a cellular network, a Client/Server network, a virtual private network (VPN), and so forth. Note again that for ease of illustration and explanation, FIG. **1** does not illustrate multiple transportation vehicle units **20** being in communication with the real-time carpooling management system **16** nor more than two end users **12*** being in communication with the real-time carpooling management system **16**. However, for purposes of the following description, the real-time carpooling management system **16** may, in fact, be in communication with multiple transportation vehicle units **20** (via multiple transport computing devices **10***) and numerous end users **12***.

(89) In some cases, the real-time carpooling management system **16**, which may or may not be located overseas or across national borders, may communicate with a transportation vehicle unit **20** (via transport computing device **10***) through a real-time carpooling coordinating system **15**, which may be a locally based network server(s). In order to try to match a prospective passenger, such as the second end user **12b** of FIG. **1**, to a transportation vehicle unit **20** for transport, the real-time carpooling management system **16** may check the current end user transport obligations (e.g., obligations for transporting other passengers such as the first end user **12a** of FIG. **1**) of the transportation vehicle unit **20**. That is, a transportation vehicle unit **20** (via their own associated transport computing device **10***) may periodically or continuously provide its current outstanding obligations (including no obligation) for transporting end users to the real-time carpooling management system **16** (sometimes via the real-time carpooling coordinating system **15**). By comparing the current end user transport obligations (e.g., an obligation to transport the first end user **12a** of FIG. **1**) of the transportation vehicle unit **20** with the requirements for transporting a prospective passenger (e.g., the second end user **12b**) and determining that transport of the second end user **12b** will not conflict with the obligation to transport the first end user **12a**, the real-time carpooling management system **16** may match the prospective passenger (e.g., the second end user **12b**) to the appropriate transportation vehicle unit **20**. Note the phrase “real-time” is used herein because when, for example, a second end user **12b** is being assigned to a transportation vehicle unit **20** for transport, the transportation vehicle unit **20** may already be en route to or is already transporting a first end user **12a**.

(90) Note, however, that in many situations the matching operations (that may be performed by the real-time carpooling management system **16**) may be faulty because the real-time carpooling management system **16** may not have the most current information related to the current end user transport obligations of a transportation vehicle unit **20**. This may be as a result of many factors including, for example, the reporting of current end user transport obligations by the transportation vehicle unit **20** may only be random or sporadic due to communication disruptions between the transportation vehicle unit **20** and the real-time carpooling management system **16**, or failure of human drivers to record/report changes to end user transport obligations.

(91) In order to facilitate understanding of the various concepts related to the processes and operations to be described herein, the following illustrative scenario is provided that shows how a transportation vehicle unit **20** may become obligated to transport a first end user **12a** and how a

second end user **12b** (e.g., a prospective passenger) may be assigned to be transported by the same transportation vehicle unit **20** while transporting the first end user **12a**, the assignment of the second end user **12b** to the transportation vehicle unit **20** being executed while the transportation vehicle unit **20** is already en route to (e.g., traveling to a rendezvous location to secure the first end user **12a**) or is already transporting the first end user **12a** (note that this may include the span in time when the transportation vehicle unit **20** is at the rendezvous location awaiting for the arrival of the first end user **12a**). When an end user, such as the first end user **12a** of FIG. **1**, seeks transportation services, a transport request may be transmitted by the first end user **12a** using an end user device **14**. The transport request may then be received by the real-time carpooling management system **16** (in some cases, via the real-time carpooling coordinating system **15**). In various embodiments, the transport request that may be transmitted may be a request that specifically requests for a carpooling vehicle that may be used in order to transport other end users while transporting the first end user **12a**. In some cases, the transportation vehicle unit **20** that may be assigned to transport the first end user **12a** may only be permitted (e.g., as permitted by the first end user **12a** or by a third party such as a ridesharing company) to transport other end users while transporting the first end user **12a** only when certain conditions can be met (e.g., no significant delay, such as no more than 15 minute delay, for transporting the first end user **12a** to his or her destination and as a result of the transportation vehicle unit **20** transporting other end users while transporting the first end user **12a**).

(92) The real-time carpooling management system **16** upon receiving the request from the first end user **12a** may then assign a transportation vehicle unit **20** to transport the first end user **12a** based on one or more factors including the current availability the transportation vehicle unit **20** (e.g., whether the transportation vehicle unit **20** is in-service or off-duty or whether it is in the proximate vicinity of the first end user **12a**), and the current outstanding passenger transport obligations of the transportation vehicle unit **20**. That is, based on the known obligations and status of the transportation vehicle units **20**, the real-time carpooling management system **16** may determine that the transportation vehicle unit **20** should be assigned to transport the first end user **12a**.

(93) In any event, after determining/selecting the transportation vehicle units **20** for transporting the first end user **20**, the real-time carpooling management system **16** may direct or instruct the selected transportation vehicle unit **20** to transport the first end user **12a** by transmitting to a transport computing device **10*** associated with the selected transportation vehicle unit **20** one or more first directives that direct (e.g., instruct) the selected transportation vehicle unit **20** to rendezvous with the first end user **12a** at a first end user rendezvous location (which, in some cases, may be the location of the first end user **12a** at the time when the first end user **12a** requested transportation services). In some cases, the real-time carpooling management system **16** may transmit the one or more first directives to a transport computing device **10*** associated with the transportation vehicle unit **20** indirectly through the real-time carpooling coordinating system **15**.

(94) The one or more first directives that may be transmitted to the transport computing device **10*** may indicate a variety of information including a first end user rendezvous location for rendezvousing with the first end user **12a**, a first end user destination location, carpooling preferences (alternatively, the carpooling preferences may be received separately from the one or more first directives), and so forth. Carpooling preferences may include, for example, the amount of travel delay that may be acceptable for a particular end user and as a result of transporting other end users, maximum number of drop-offs (e.g., passenger offload stops) permitted prior to a particular end user being dropped-off, and so forth. Upon the one or more first directives being received and accepted by the logic of the transport computing device **10***, the one or more directives may become one or more obligations for transporting the first end user **12a**. After the one or more first directives are accepted, the real-time carpooling management system **16** may transmit (in some cases via the real-time carpooling coordinating system **15**) a confirmation that the one or more first directives have been accepted.

(95) While the transportation vehicle unit **20** is still en route to a first end user rendezvous location for rendezvousing with the first end user **12a** or while the transportation vehicle unit **20** is transporting the first end user **12a**, a second end user **12b** may transmit a request for transportation services (which may or may not request specifically for carpooling services—e.g., share a ride with other end users) to the real-time carpooling management system **16**. After determining that the transportation vehicle unit **20** is able to accommodate transport of the second end user **12b** while transporting the first end user **12a**, the real-time carpooling management system **16** may then transmit to the transport computing device **10*** associated with the transportation vehicle unit **20** one or more second directives that direct the transportation vehicle unit **20** to pick-up and transport the second end user **12b** while transporting the first end user **12a**. The determination as to whether the transportation vehicle unit **20** may accommodate transport of the second end user **12b** while transporting the first end user **12a** may be based on one or more factors including, for example, a determination that the transportation vehicle unit **20** having sufficient space to accommodate the second end user **12b**, a determination that the transportation vehicle unit **20** is in the proximate vicinity of the second end user **12b**, a determination the transportation vehicle unit **20** will be traveling near to the destination location of the second end user **12b** while transporting the first end user **12a** or other end users, a determination that transport of the first end user **12a** and the second end user **12b** together will comply with the carpooling preferences of the first end user **12a**, the second end user **12b**, or a third party, and so forth.

(96) The one or more second directives that are received by the transport computing device **10*** may include a variety of information including end user information (e.g., identity and/or image of the second end user **12b**), a rendezvous location for rendezvousing with the second end user **12b**, a destination location for the second end user **12b**, end user carpooling preferences of the second end user **12b**, and so forth. After receiving the one or more second directives, the transport computing device **10*** associated with the transportation vehicle unit **20** may verify or confirm that the one or more second directives do not conflict with one or more obligations to transport the first end user **12a**. The verification or confirmation may be needed because the real-time carpooling management system **16** will often not have the most up-to-date status and obligation information related to the transportation vehicle unit **20**. Instead, only the transport computing device **10*** may have the most up-to-date status and passenger obligation information of the transportation vehicle unit **20**.

(97) The verification (e.g., confirmation) process may involve looking at a number of factors in order to confirm that the one or more second directives do not conflict with the one or more obligations to transport the first end user **12a**. These factors may be the same factors considered by the real-time carpooling management system **16** in determining that the transportation vehicle unit **20** is able to accommodate transport of the second end user **12b**. These factors include, for example, a determination that the transportation vehicle unit **20** having sufficient space to accommodate the second end user **12b**, a determination that the transportation vehicle unit **20** is in the proximate vicinity of the second end user **12b**, a determination the transportation vehicle unit **20** will be traveling near to the destination location of the second end user **12b** while transporting the first end user **12a** or other end users, a determination that transport of the first end user **12a** and the second end user **12b** together will comply with the carpooling preferences of the first end user **12a**, the second end user **12b**, or a third party, and so forth. In some cases, the verification or confirmation process may also include a determination of transport rate or rates (e.g., transport fees) for the first end user **12a** and/or the second end user **12b** that may be based on the transportation vehicle unit **20** transporting both the first end user **12a** and the second end user **12b**. A more detailed discussion related to the confirmation/verification procedures will be provided in the processes to be described herein.

(98) Once the logic of the transport computing device **10*** of the transportation vehicle unit **20** verifies or confirms that the one or more second directives do not conflict with the one or more obligations of the transportation vehicle unit **20** to transport the first end user **12a**, the transport

computing device **10*** may transmit to, for example, the real-time carpooling management system **16** and/or to one or more end user devices **14** one or more confirmations that indicate that the transportation vehicle unit **20** will, in fact, be transporting the second end user **12b**. If, on the other hand, the logic of the transport computing device **10*** is unable to make the verification or confirmation, then the transport computing device **10*** may transmit to the real-time carpooling management system **16** a notification that the transportation vehicle unit **20** is unable to accommodate transport of the second end user **12b**.

(99) After the logic of the transport computing device **10*** of the transportation vehicle unit **20** verifies or confirms that the one or more second directives do not conflict with the one or more obligations of the transportation vehicle unit **20** to transport the first end user **12a**, the transport computing device **10*** may also present one or more instructive directives that direct (e.g., instructs) the transportation vehicle unit **20** to rendezvous with and transport the second end user **12b**. In cases where the transportation vehicle unit **20** employs a human driver, the one or more instructive directives may be visually and/or audibly presented. In other cases where the transportation vehicle unit **20** employs a robotic driver system **450** (see FIG. 4E) the one or more instructive directives may be electronically presented to a navigation system **452** of the robotic driver system **450**.

(100) Turning now to FIGS. 4A to 4D, which illustrate various routes that the transportation vehicle unit **20** of FIG. 1 may use in order to transport the first end user **12a** and the second end user **12b** to their destination(s) (e.g., destination location(s)) for different example scenarios (e.g., scenario 1, scenario 2, scenario 3, and scenario 4). These scenarios may better facilitate understanding of the various concepts to be introduced with respect to the various operations and processes to be described herein. Referring particularly now to FIG. 4A, which illustrates a route that the transportation vehicle unit **20** of FIG. 1 may take in order to transport the first end user **12a** and the second end user **12b** to their destination locations (e.g., 1.sup.st end user destination location **404** and 2.sup.nd end user destination location **410**) in accordance with scenario 1. In scenario 1, the transportation vehicle unit **20** is en route to rendezvous with the first end user **12a** at a first end user rendezvous location **402** when it is assigned/selected to transport the second end user **12b**.

(101) As illustrated, the transportation vehicle unit (TVU) **20** is depicted as being currently en route to rendezvous with the first end user **12a** at the first end user rendezvous location **402** and being currently located at current location **406** when it is selected for transport of the second end user **12b**. FIG. 4A further illustrates an original direct route **403** that the TVU (e.g., transportation vehicle unit **20** of FIG. 1) could have taken to transport the first end user **12a** from the first end user rendezvous location **402** to a first end user destination location **404** if the TVU was not selected for transporting the second end user **12b**. However, because the TVU is selected to transport the second end user **12b**, the TVU must take detour **414a** in order to secure the second end user **12b** from second end user rendezvous location **408** and take detour **414b** to drop off the second end user **12b** at a second end user destination location **410**. As a result, the first end user **12a** may be delayed in being transported to his/her destination location (e.g., first end user destination location **404**). In various embodiments, the transport of the second end user **12b** by the TVU may be permitted so long as the delay in transporting the first end user **12a** is permitted by the first end user **12a** and/or permitted by a third party such as a ridesharing company associated with the real-time carpooling management system **16**.

(102) Turning now to FIG. 4B, which illustrates a scenario 2 in which the TVU (e.g., the transportation vehicle unit **20** of FIG. 1) uses a particular route (e.g., direct route **420**) to transport the first end user **12a** and the second end user **12b** to a common destination location **422**. In contrast to scenario 1 illustrated in FIG. 4A, in scenario 2 both the first end user **12a** and the second end user **12b** are scheduled to go to the same destination (e.g., common destination location **422**). Further, the second end user rendezvous location **408** for rendezvousing with the second end user **12b** is located along the direct route **420** for transporting the first end user **12a** from a first end user

rendezvous location **402** to the first end user's destination location (e.g., common destination location **422**). In FIG. **4B**, the TVU is currently located, at a point in time when the TVU (e.g., transportation vehicle unit **20**) is selected for transport of the second end user **12b**, at current location **406** that is the same as the first end user rendezvous location **402**. Thus, in scenario **2**, the first end user **12a** will not incur a significant delay because the second end user rendezvous location **408** is located along the direct route **420** and the second end user **12b** is going to the same common destination location **422** as the first end user **12a**.

(103) Scenario **2** reflects many true life situations. For example, scenario **2** may occur when a number of end users from the same general neighborhood are intent on attending the same sporting or concert event.

(104) FIG. **4C** illustrates a scenario **3** in which the TVU (e.g., the transportation vehicle unit **20** of FIG. **1**) is already transporting the first end user **12a** when the transportation vehicle unit **20** is selected or assigned (e.g., selected by the real-time carpooling management system **16**) to transport the second end user **12b**. As illustrated, when the transportation vehicle unit **20** is selected to transport the second end user **12b**, the TVU is located at current location **406** along the direct route **430** from the first end user rendezvous location **402** to the first end user destination location **404** (which continues on to second end user destination location **410**). In order to transport the second end user **12b**, the TVU uses a detour **414a** to secure the second end user **12b** at rendezvous location **408**. Note that in scenario **3**, the second end user **12b** is designated to be dropped off at second end user destination location **410**, which is scheduled to occur after the first end user **12a** has already been dropped off at a first end user destination location **404**. Thus, the delay to transport of first end user **12a** to his or her destination location (e.g., first end user destination location **404**) as a result of the transportation vehicle unit **20** transporting the second end user **12b** may be relatively minimal. That is, the only delay to the transport of the first end user **12a** may be as a result of the transportation vehicle unit **20** being rerouted to rendezvous with the second end user **12b** at the rendezvous location **408** using detour **414a**.

(105) FIG. **4D** illustrates a scenario **4** in which the TVU (e.g., the transportation vehicle unit **20** of FIG. **1**) is to rendezvous with the first end user **12a** and the second end user **12b** at a common rendezvous location **440** and to transport the first end user **12a** and the second end user **12b** to a common destination location **442**. Because there are no detours, there is little or no delay in transporting the first end user **12a** to his/her destination (e.g., common destination location **442**) except for any extended time that the TVU may have to stay at the common rendezvous location **440** in order to wait for the arrival of the second end user **12b**. There are several real life situations in which such a scenario can occur. For example, at the end of a sporting event such as at a football game and a number of the spectators leaving the stadium with the intent to go to a popular bar/nightclub.

(106) Referring now to FIGS. **2A** and **2B**, which illustrate two block diagrams representing two different implementations of the transport computing device **10*** of FIG. **1**. In particular, and as will be further described herein, FIG. **2A** illustrates a transport computing device **10'** that is the "hardwired" or "hard" implementation of the transport computing device **10*** of FIG. **1** that can implement the operations and processes to be described herein. The transport computing device **10'** includes certain logic modules including a directive receiving module **202'**, a non-conflict confirming module **204'**, a confirmation transmitting module **206'**, and an instructive directive presenting module **208'** that are implemented using purely hardware or circuitry components (e.g., application specific integrated circuit (or ASIC)). In contrast, FIG. **2B** illustrates a transport computing device **10''** that is the "soft" implementation of the transport computing device **10*** of FIG. **1** in which certain logic modules including a directive receiving module **202''**, a non-conflict confirming module **204''**, a confirmation transmitting module **206''**, and an instructive directive presenting module **208''** are implemented using programmable circuitry **230** (e.g., one or more processors **230** including one or more microprocessors, controllers, CPUs, GPUs, FPGAs, and/or

other types of programmable circuitry) executing one or more programming instructions (e.g., software). Note that in some embodiments, the transport computing device **10''** illustrated in FIG. 2B may be a general purposes computing device (e.g., a mobile computing device such as a Smartphone or tablet computer) that executes specialized computer readable instructions (e.g., software). In alternative embodiments, the transport computing device **10''** may be a dedicated device designed specifically to execute the various operations and processes to be described herein. (107) The embodiments of the transport computing device **10*** illustrated in FIGS. 2A and 2B (e.g., the transport computing device **10'** of FIG. 2A and the transport computing device **10''** of FIG. 2B) are two extreme implementations of the transport computing device **10*** in which all of the logic modules (e.g., the directive receiving module **202'**, the non-conflict confirming module **204'**, the confirmation transmitting module **206''**, and the instructive directive presenting module **208'**) are implemented using purely hardware solutions (e.g., circuitry such as ASIC) as illustrated in FIG. 2A or in which all of the logic modules (e.g., the directive receiving module **202''**, the non-conflict confirming module **204''**, the confirmation transmitting module **206''**, and the instructive directive presenting module **208''**) are implemented using software solutions (e.g., programmable instructions being executed by programmable circuitry **230** such as field programmable gate array (FPGA) or one or more processors) as illustrated in FIG. 2B. Since there are many ways of combining hardware, software, and/or firmware in order to implement the various logic modules (e.g., the directive receiving module **202***, the non-conflict confirming module **204***, the confirmation transmitting module **206***, and the instructive directive presenting module **208''**), only the two extreme implementations (e.g., the purely hardware solution as illustrated in FIG. 2A and the software solution of FIG. 2B) are illustrated here. It should be noted here that with respect to the “soft” implementation illustrated in FIG. 2B, hardware in the form of programmable circuitry such as one or more processors **230** (or FPGA) are still needed in order to execute the software (or firmware). Further details related to the two implementations of the transport computing device **10*** illustrated in FIGS. 2A and 2B will be provided in greater detail below.

(108) In some instances, one or more components may be referred to herein as “configured to,” “configured by,” “configurable to,” “operable/operative to,” “adapted/adaptable,” “able to,” “conformable/conformed to,” “designed to,” etc. Those skilled in the art will recognize that such terms (e.g., “configured to”) generally encompass active-state components and/or inactive-state components and/or standby-state components, unless context requires otherwise.

(109) Referring particularly now to FIG. 2A, which illustrates that the transport computing device **10'**, in addition to the directive receiving module **202'**, the non-conflict confirming module **204'**, the confirmation transmitting module **206'**, and the instructive directive presenting module **208'**, may further include programmable circuitry **230** (e.g., one or more processors, controllers, and so forth), a network interface **240** (network interface card or NIC), memory **220**, and/or a user interface **250**. In various embodiments, memory **220** may comprise of volatile and/or non-volatile memory. In some embodiments, memory **220** may comprise of one or more of mass storage device, cache memory, read-only memory (ROM), programmable read-only memory (PROM), erasable programmable read-only memory (EPROM), cache memory such as random access memory (RAM), flash memory, synchronous random access memory (SRAM), dynamic random access memory (DRAM), and/or other types of memory devices. In some embodiments, the memory **220** may be employed to store a variety of programming instructions (e.g., software) and data including data indicating current end user transport obligations of the transportation vehicle unit **10'**, carpooling preferences of end users and/or third parties, and so forth.

(110) Turning now to FIG. 2B, which illustrates a transport computing device **10''** in which certain logic modules (the directive receiving module **202''**, the non-conflict confirming module **204''**, the confirmation transmitting module **206''**, and the instructive directive presenting module **208''**) are implemented using programmable circuitry **230** (e.g., one or more processors, one or more controllers, FPGAs, and/or other types of programmable circuitry). In addition, the transport

computing device **10'** may further include a memory **220**, a network interface **240**, and/or a user interface **250** similar to the transport computing device **10'** of FIG. 2A.

(111) In various embodiments the directive receiving module **202*** of FIG. 2A or 2B (e.g., the directive receiving module **202'** of FIG. 2A or the directive receiving module **202''** of FIG. 2B) may be configured to, among other things, receive one or more first directives that direct the transportation vehicle unit **20** to transport a first end user **12a**. The directive receiving module **202*** may further be configured to receive, while the transportation vehicle unit **20** is en route to secure the first end user **12a** or is transporting the first end user **12a**, one or more second directives that direct the transportation vehicle unit **20** to transport a second end user **12b** while transporting the first end user **12a**, the transportation vehicle unit having been determined to be able to accommodate transport of the second end user **12b** while transporting the first end user **12a**. In contrast, the non-conflict confirming module **204*** of FIG. 2A or 2B (e.g., the non-conflict confirming module **204'** of FIG. 2A or the non-conflict confirming module **204''** of FIG. 2B) may be configured to, among other things, verify or confirm that compliance with the one or more second directives will not conflict with one or more obligations to transport the first end user **12a** by the transportation vehicle unit **20**. Meanwhile, the confirmation transmitting module **206*** of FIG. 2A or 2B may be configured to, among other things, transmit one or more confirmations that the one or more second directives have been accepted for execution by the transportation vehicle unit **20**. On the other hand, the instructive directive presenting module **208*** of FIG. 2A or 2B may be configured to, among other things, present, in response to verification or confirmation that compliance with the one or more second directives will not conflict with one or more obligations to transport the first end user **12a** by the transportation vehicle unit **20**, one or more instructive directives that direct the transportation vehicle unit **20** to transport the second end user **12b**.

(112) Referring now to FIG. 3A illustrating a particular implementation of the directive receiving module **202*** (e.g., the directive receiving module **202'** or the directive receiving module **202''**) of FIG. 2A or 2B. As illustrated, the directive receiving module **202*** may include one or more sub-logic modules in various alternative implementations. For example, in various embodiments, the directive receiving module **202*** may further include a carpooling preference receiving module **302**, a transport rate data receiving module **304**, and/or an image data receiving module **306**. Specific details related to the directive receiving module **202*** as well as the above-described sub-modules of the directive receiving module **202*** will be provided below with respect to the operations and processes to be described herein.

(113) FIG. 3B illustrates a particular implementation of the non-conflict confirming module **204*** (e.g., the non-conflict confirming module **204'** or the non-conflict confirming module **204''**) of FIG. 2A or 2B. As illustrated, the non-conflict confirming module **204*** may include one or more sub-logic modules in various alternative implementations. For example, in various embodiments, the non-conflict confirming module **204*** may further include a rendezvous location proximity confirming module **308**, a spatial availability confirming module **310**, a vicinity traveling confirming module **312**, a carpooling preference non-conflict confirming module **314**, and/or a transport rate ascertaining module **316**. Specific details related to the non-conflict confirming module **204*** as well as the above-described sub-module of the non-conflict confirming module **204***.

(114) FIG. 3C illustrates a particular implementation of the instructive directive presenting module **208*** (e.g., instructive directive presenting module **208'** or the instructive directive presenting module **208''**) of FIG. 2A or 2B. As illustrated, the instructive directive presenting module **208*** may include one or more sub-logic modules in various alternative implementations. For example, in various embodiments, the instructive directive presenting module **208*** may further include a visual/audible instructive directive presenting module **320** and/or an electronic instructive directive presenting module **322**. Specific details related to the instructive directive presenting module **208*** as well as the above-described sub-module of the instructive directive presenting module **208*** will

be provided below with respect to the operations and processes to be described herein.

(115) Turning now to FIG. 4E, which illustrates a block diagram of a robotic driver system **450** that may be employed by a transportation vehicle unit **20**. The robotic driver system **450** may be employed in order to replace a human driver and may include, among other things, a transport computing device **10*** of FIG. 2A or 2B, a navigation system **452**, and a transportation vehicle control system **454**. The navigation system **452** may be designed to provide navigational functionalities (e.g., plans routes to a destination location from a starting location, keeps track of the location of the transportation vehicle unit **20** using GPS data, and so forth) while the transportation vehicle control system **454** may be employed to control the various driving components (e.g., steering, gas, brakes, transmission, and so forth) of the vehicle portion (e.g., gas or electric powered vehicle) of the transportation vehicle unit **20**.

(116) In the following, various operations associated with the above described transport computing device **10*** (e.g., the transport computing device **10'** of FIG. 2A or the transport computing device **10''** of FIG. 2B) will be presented in accordance with various alternative embodiments. FIG. 5, for example, illustrates an operational flow **500** representing example computationally-implemented operations that may be implemented for, among other things, verifying that compliance with the one or more second directives that direct a transportation vehicle unit **20** to transport a second end user **12b** will not conflict with one or more obligations to transport a first end user **12a** by the transportation vehicle unit **20**.

(117) In FIG. 5 and in the following figures that include various examples of operational flows, discussions and explanations will be provided with respect to the transport computing device **10*** described above and as illustrated in FIGS. 2A, 2B, 3A, 3B, and 3C, and/or with respect to other examples (e.g., as provided in FIGS. 1 and 4A, 4B, 4C, 4D, and 4E) and contexts. However, it should be understood that the operational flows may be executed in a number of other environments and contexts, and/or in modified versions of FIGS. 1, 2A, 2B, 3A, 3B, 3C, 4A, 4B, 4C, 4D, and/or 4E. Also, although the various operational flows are presented in the sequence(s) illustrated, it should be understood that the various operations may be performed in orders other than those which are illustrated, or may be performed concurrently.

(118) Further, in FIG. 5 and in the figures to follow thereafter, various operations may be depicted in a box-within-a-box manner. Such depictions may indicate that an operation in an internal box may comprise an optional example embodiment of the operational step illustrated in one or more external boxes. However, it should be understood that internal box operations may be viewed as independent operations separate from any associated external boxes and may be performed in any sequence with respect to all other illustrated operations, or may be performed concurrently. Still further, these operations illustrated in FIG. 5 as well as the other operations to be described herein are performed by at least one of a machine, an article of manufacture, or a composition of matter unless indicated otherwise.

(119) For ease of understanding, the flowcharts are organized such that the initial flowcharts present implementations via an example implementation and thereafter the following flowcharts present alternate implementations and/or expansions of the initial flowchart(s) as either sub-component operations or additional component operations building on one or more earlier-presented flowcharts. Those having skill in the art will appreciate that the style of presentation utilized herein (e.g., beginning with a presentation of a flowchart(s) presenting an example implementation and thereafter providing additions to and/or further details in subsequent flowcharts) generally allows for a rapid and easy understanding of the various process implementations. In addition, those skilled in the art will further appreciate that the style of presentation used herein also lends itself well to modular and/or object-oriented program design paradigms.

(120) In any event, after a start operation, the operational flow **500** of FIG. 5 may move to a first directive receiving operation **502** for receiving one or more first directives that direct a

transportation vehicle unit to transport a first end user. For instance, and as illustration, the directive receiving module **202*** of the transport computing device **10*** of FIG. 2A or 2B (e.g., the directive receiving module **202'** of FIG. 2A or the directive receiving module **202''** of FIG. 2B) receiving one or more first directives that direct (e.g., instructs) a transportation vehicle unit **20** to transport a first end user **12a**. As will be further described below, the one or more first directives that are received may provide various information including pickup location (e.g., rendezvous location) for rendezvousing with the first end user, the destination (e.g., destination location) for the first end user, carpooling preferences, and so forth. In various implementations, the one or more first directives may be received from a network entity (e.g., a real-time carpooling coordinating system **15** or a real-time carpooling management system **16** of FIG. 1) or may entered by a human driver (who may have picked-up a street fare—e.g., the first end user **12a**) associated with the transportation vehicle unit **20**.

(121) Operational flow **500** may also include a second directive receiving operation **504** for receiving, while the transportation vehicle unit is en route to or is transporting the first end user, one or more second directives that direct the transportation vehicle unit to transport a second end user while transporting the first end user, the transportation vehicle unit having been determined to be able to accommodate transport of the second end user while transporting the first end user. For instance, the directive receiving module **202*** (e.g., the directive receiving module **202'** of FIG. 2A or the directive receiving module **202''** of FIG. 2B) of the transport computing device **10*** of FIG. 2A or 2B receiving, while the transportation vehicle unit **20** is en route to rendezvousing with the first end user **12a** at a first end user rendezvous location or is transporting the first end user **12a**, one or more second directives that direct (e.g., instruct) the transportation vehicle unit **20** to transport a second end user **12b** while transporting the first end user **12a**, the transportation vehicle unit **20** having been determined by, for example, the real-time carpooling management system **16** of FIG. 1, to be able to accommodate transport of the second end user **12b** while the transportation vehicle unit **20** is transporting the first end user **12a**. Note that for purposes of this description the phrase “en route to or is transporting the first end user” may also include the point or span in time in which the transportation vehicle unit **20a** has reached a rendezvous location for rendezvousing with the first end user **12a** and is waiting for the first end user **12a** to reach the rendezvous location.

(122) As further illustrated in FIG. 5, operational flow **500** may further include a non-conflict verifying operation **506** for verifying that compliance with the one or more second directives will not conflict with one or more obligations to transport the first end user by the transportation vehicle unit. For instance, the non-conflict confirming module **204*** (e.g., the non-conflict confirming module **204'** of FIG. 2A or the non-conflict confirming module **204''** of FIG. 2B) of the transport computing device **10*** of FIG. 2A or 2B verifying or confirming that compliance with the one or more second directives to transport the second end user **12b** by the transportation vehicle unit **20** will not conflict with one or more obligations to transport the first end user **12a** by the transportation vehicle unit **20**. For example, verifying or confirming that the transportation vehicle unit **20** can still fulfill an obligation to transport the first end user **12a** to a first end user destination location without significant delay even if the transportation vehicle unit **20** transports the second end user **12b** while transporting the first end user **12a**.

(123) As will be described below, the first directive receiving operation **502**, the second directive receiving operation **504**, and the non-conflict verifying operation **506** may be executed in a variety of different ways in various alternative implementations. FIGS. 6A, 6B, 6C, and 6D, for example, illustrate at least some of the alternative ways that the first directive receiving operation **502** of FIG. 5 may be executed in various alternative implementations. In some cases, for example, the first directive receiving operation **502** may include an operation **602** for receiving the one or more first directives electronically via one or more wireless and/or wired networks as illustrated in FIG. 6A. For instance, the directive receiving module **202*** of the transport computing device **10*** (e.g., the transport computing device **10'** of FIG. 2A or the transport computing device **10''** of FIG. 2B)

receiving the one or more first directives electronically via one or more wireless and/or wired networks **18** (e.g., cellular data network, WLAN, WAN, MAN (metropolitan area network), Ethernet, etc.). In some cases, the directive receiving module **202*** may control a network interface **240** in order to electronically receive the one or more package delivery directives.

(124) In various implementations, the first directive receiving operation **502** may include an operation **603** for receiving one or more first directives that identify a rendezvous location for rendezvousing with the first end user and/or that identifies a first end user destination location for the first end user. For instance, the directive receiving module **202*** of the transport computing device **10*** of FIG. 2A or 2B receiving one or more first directives that identify a rendezvous location (e.g., the current GPS location of the first end user **12a** when the first directives are received) for the transportation vehicle unit to rendezvous with the first end user and/or that identifies a first end user destination location for the first end user.

(125) In the same or alternative implementations, the first directive receiving operation **502** may alternatively or additionally include an operation **604** for receiving the one or more first directives including receiving one or more carpooling preferences associated with transport of the first end user by the transportation vehicle unit. For instance, the directive receiving module **202*** including the carpooling preference receiving module **302** (see FIG. 3A) of the transport computing device **10*** of FIG. 2A or 2B receiving the one or more first directives including receiving one or more carpooling preferences associated with transport of the first end user **12a** by the transportation vehicle unit **20**. For example, the one or more carpooling preferences may indicate that the transportation vehicle unit **20** will be permitted to transport other end users (not associated with the first end user **12a**) while transporting the first end user **12a** if transport of the end users will not cause a significant delay (e.g., more than 15 minutes delay) in the first end user **12a** reaching his or her destination.

(126) As further illustrated in FIG. 6A, in various implementations, operation **604** may include an operation **605** for receiving the one or more carpooling preferences from an end user device associated with the first end user. For instance, the carpooling preference receiving module **302** of the transport computing device **10*** of FIG. 2A or 2B receiving the one or more carpooling preferences from an end user device **14** (e.g., a mobile device such as a Smartphone or tablet computer, a laptop computer, and so forth) associated with the first end user **12a**.

(127) In the same or alternative implementations, operation **604** may alternatively or additionally include an operation **606** for receiving one or more carpooling preferences that permit transport, by the transportation vehicle unit, of one or more other end users not affiliated with the first end user while the transportation vehicle unit is transporting the first end user only if one or more specified conditions can be or have already been realized. For instance, the carpooling preference receiving module **302** of the transport computing device **10*** of FIG. 2A or 2B receiving one or more carpooling preferences that permit transport, by the transportation vehicle unit **20**, of one or more other end users not affiliated with the first end user **12a** while the transportation vehicle unit **20** is transporting the first end user **12a** only if one or more specified conditions can be or have already been realized (e.g., transport of the other end users will not cause significant delays for transporting the first end user **12a** to his/her destination or the transportation vehicle unit **20** has sufficient passenger space to accommodate the other end users).

(128) In some implementations, operation **606** may actually involve an operation **607** for receiving one or more carpooling preferences that permit transport, by the transportation vehicle unit, of the one or more other end users while the transportation vehicle unit is transporting the first end user so long as transport of the one or more other users by the transportation vehicle unit does not cause a delay in transporting the first end user to a first end user destination location that is greater than a predefined amount of maximum permitted delay. For instance, the carpooling preference receiving module **302** of the transport computing device **10*** of FIG. 2A or 2B receiving one or more carpooling preferences that permit transport, by the transportation vehicle unit **20**, of the one or

more other end users while the transportation vehicle unit **20** is transporting the first end user **12a** as long as transport of the one or more other users by the transportation vehicle unit **20** does not cause a delay in transporting the first end user to a first end user destination location that is greater than a predefined amount of maximum permitted delay (e.g., maximum allowable delay of 25 minutes or less). In some cases, a delay that may be caused by transporting other end users may be calculated by, for example, first estimating the amount of time it would take to transport the first end user **12a** to a destination location when the transportation vehicle unit **20** is not transporting other end users then estimating the amount of time it would take to transport the first end user **12a** to the destination location when the transportation vehicle unit **20** is transporting other end users, and then determining the difference between the two estimated times in order to determine the estimated time delay that would result as a result of the transportation vehicle unit **20** transporting other end users while transporting the first end user **12a**.

(129) In some cases, operation **607** may further involve an operation **608** for receiving one or more carpooling preferences that permit transport, by the transportation vehicle unit, of the one or more other end users while the transportation vehicle unit is transporting the first end user so long as transport of the one or more other users by the transportation vehicle unit does not cause a delay in transporting the first end user to a first end user destination location that is greater than a 20 minutes of maximum permitted delay. For instance, the carpooling preference receiving module **302** of the transport computing device **10*** of FIG. 2A or 2B receiving one or more carpooling preferences that permit (e.g., as permitted by the logic of the transport computing device **10*** when the logic abides with the one or more carpooling preferences) transport, by the transportation vehicle unit **20**, of the one or more other end users while the transportation vehicle unit **20** is transporting the first end user **12a** as long as transport of the one or more other users by the transportation vehicle unit **20** does not cause a delay in transporting the first end user **12a** to a first end user destination location that is greater than a 20 minutes of maximum permitted delay.

(130) Turning to FIG. 6B, in the same or alternative implementations, operation **606** for receiving one or more carpooling preferences that permit transport, by the transportation vehicle unit, of one or more other end users not affiliated with the first end user while the transportation vehicle unit is transporting the first end user only if one or more specified conditions can be or have already been realized may additionally or alternatively include an operation **609** for receiving one or more carpooling preferences that permit transport, by the transportation vehicle unit, of the one or more other end users while the transportation vehicle unit is transporting the first end user so long as transport of the one or more other end users by the transportation vehicle unit does not cause the transportation vehicle unit to have a number of end user drop-offs prior to the first end user being dropped-off that is greater than a predefined amount of maximum permitted end user drop-offs permitted before the first end user is dropped-off. For instance, the carpooling preference receiving module **302** of the transport computing device **10*** of FIG. 2A or 2B receiving one or more carpooling preferences that permit (e.g., as permitted by the logic of the transport computing device **10*** when the logic complies with the one or more carpooling preferences) transport, by the transportation vehicle unit **20**, of the one or more other end users while the transportation vehicle unit **20** is transporting the first end user **12a** as long as transport of the one or more other end users by the transportation vehicle unit **20** does not cause the transportation vehicle unit **20** to have a number of end user drop-offs (e.g., the act or acts of off-loading passengers at their destination location(s)) prior to the first end user **12a** being dropped-off that is greater than a predefined amount of maximum permitted end user drop-offs permitted before the first end user is dropped-off. For example, if the maximum number of permitted end user drop-offs prior to the first end user **12a** is two but the addition of other end users during transport of the first end user **12a** would result in the transportation vehicle unit **20** having three end user drop-offs prior to the first end user **12a** being dropped-off at the first end user's destination location, then the transport of the other end users by the transportation vehicle unit **20** while transporting the first end user **12a** will not be

permitted by the logic of the transport computing device **10*** (e.g., the logic of the transport computing device **10*** will reject directives to transport the other end users).

(131) In some cases, operation **609** may actually involve an operation **610** for receiving one or more carpooling preferences that permit transport, by the transportation vehicle unit, of the one or more other end users while the transportation vehicle unit is transporting the first end user so long as transport of the one or more other users by the transportation vehicle unit does not cause the transportation vehicle unit to have a number of end user drop-offs prior to the first end user being dropped-off that is greater than a maximum of three end user drop-offs permitted before the first end user is dropped-off. For instance, the carpooling preference receiving module **302** of the transport computing device **10*** of FIG. 2A or 2B receiving one or more carpooling preferences that permit (e.g., as permitted by the logic of the transport computing device **10*** when the logic complies with the one or more carpooling preferences) transport, by the transportation vehicle unit **20**, of the one or more other end users while the transportation vehicle unit **20** is transporting the first end user **12a** as long as transport of the one or more other users by the transportation vehicle unit **20** does not cause the transportation vehicle unit **20** to be scheduled to have a number of end user drop-offs prior to the first end user **12a** being dropped-off that is greater than a maximum of three end user drop-offs permitted before the first end user **12a** is dropped-off

(132) In the same or alternative implementations, operation **606** may additionally or alternatively include an operation **611** for receiving one or more carpooling preferences that permit transport, by the transportation vehicle unit, of the one or more other end users while the transportation vehicle unit is transporting the first end user so long as transport of the one or more other users by the transportation vehicle unit does not cause any end user drop-off to occur prior to drop-off of the first end user. For instance, the carpooling preference receiving module **302** of the transport computing device **10*** of FIG. 2A or 2B receiving one or more carpooling preferences that permit (e.g., as permitted by the logic of the transport computing device **10*** when the logic complies with the one or more carpooling preferences) transport, by the transportation vehicle unit **20**, of the one or more other end users while the transportation vehicle unit **20** is transporting the first end user **12a** as long as transport of the one or more other users by the transportation vehicle unit **20** does not cause any end user drop-off (e.g., end user offloading) to occur prior to drop of the first end user **12a**.

(133) In the same or alternative implementations, operation **606** may additionally or alternatively include an operation **612** for receiving one or more carpooling preferences that permit transport, by the transportation vehicle unit, of the one or more other end users while the transportation vehicle unit is transporting the first end user, the one or more carpooling preferences defining maximum permitted number of rendezvous stops permitted for rendezvousing with end users during a single carpooling trip. For instance, the carpooling preference receiving module **302** of the transport computing device **10*** of FIG. 2A or 2B receiving one or more carpooling preferences that permit (e.g., as permitted by the logic of the transport computing device **10*** when the logic complies with the one or more carpooling preferences) transport, by the transportation vehicle unit **20**, of the one or more other end users while the transportation vehicle unit **20** is transporting the first end user **12a**, the one or more carpooling preferences defining maximum permitted number of rendezvous stops permitted for rendezvousing with end users during a single carpooling trip (e.g., a trip route to transport a group of unaffiliated end users from one or more rendezvous locations to one or more destination locations).

(134) In the same or alternative implementations, operation **606** may additionally or alternatively include an operation **613** for receiving one or more carpooling preferences that permit transport, by the transportation vehicle unit, of the one or more other end users while the transportation vehicle unit is transporting the first end user, the one or more carpooling preferences defining maximum number of end user drop-off stops for dropping-off of end users permitted during a single carpooling trip. For instance, the carpooling preference receiving module **302** of the transport

computing device **10*** of FIG. 2A or 2B receiving one or more carpooling preferences that permit (e.g., as permitted by the logic of the transport computing device **10*** when the logic complies with the one or more carpooling preferences) transport, by the transportation vehicle unit **20**, of the one or more other end users while the transportation vehicle unit **20** is transporting the first end user **12a**, the one or more carpooling preferences defining maximum number of end user drop-off stops permitted for dropping-off of end users including the first end user **12a** during a single carpooling trip.

(135) Turning now to FIG. 6C, in various implementations, operation **606** may include an operation **614** for receiving one or more carpooling preferences that permit transport, by the transportation vehicle unit, of the one or more other end users while the transportation vehicle unit is transporting the first end user, the one or more carpooling preferences defining a single rendezvous location for the transportation vehicle unit to rendezvous with all end users including the first end user to be transported by the transportation vehicle unit. For instance, the carpooling preference receiving module **302** of the transport computing device **10*** of FIG. 2A or 2B receiving one or more carpooling preferences that permit transport, by the transportation vehicle unit **20**, of the one or more other end users while the transportation vehicle unit **20** is transporting the first end user **12a**, the one or more carpooling preferences defining a single rendezvous location for the transportation vehicle unit **20** to rendezvous with all end users including the first end user **12a** to be transported by the transportation vehicle unit **20** during a single carpooling trip.

(136) In the same or alternative implementations, operation **606** may alternatively or additionally include an operation **615** for receiving one or more carpooling preferences that permit transport, by the transportation vehicle unit, of the one or more other end users while the transportation vehicle unit is transporting the first end user, the one or more carpooling preferences defining a single destination location for dropping-off all end users including the first end user to be transported by the transportation vehicle unit. For instance, the carpooling preference receiving module **302** of the transport computing device **10*** of FIG. 2A or 2B receiving one or more carpooling preferences that permit transport, by the transportation vehicle unit **20**, of the one or more other end users while the transportation vehicle unit **20** is transporting the first end user **12a**, the one or more carpooling preferences defining a single destination location for dropping-off all end users including the first end user **12a** to be transported by the transportation vehicle unit **20** during a single carpooling trip.

(137) In the same or alternative implementations, operation **606** may additionally or alternatively include an operation **616** for receiving one or more carpooling preferences that permit transport, by the transportation vehicle unit, of the one or more other end users while the transportation vehicle unit is transporting the first end user, the one or more carpooling preferences including a preference that all other end users to be transported by the transportation vehicle unit while the transportation vehicle unit is transporting the first end user share at least one specified common interest. For instance, the carpooling preference receiving module **302** of the transport computing device **10*** of FIG. 2A or 2B receiving one or more carpooling preferences that permit transport, by the transportation vehicle unit **20**, of the one or more other end users while the transportation vehicle unit **20** is transporting the first end user **12a**, the one or more carpooling preferences including a preference that all other end users to be transported by the transportation vehicle unit **20** while the transportation vehicle unit **20** is transporting the first end user **12a** share at least one specified common interest (e.g., all end users to be transported by the transportation vehicle unit **20** are fans of the New York Jets).

(138) In the same or alternative implementations, operation **606** may additionally or alternatively include an operation **617** for receiving the one or more carpooling preferences via a user interface or via one or more wireless and/or wired networks. For instance, the carpooling preference receiving module **302** of the transport computing device **10*** of FIG. 2A or 2B receiving the one or more carpooling preferences via a user interface **250** (e.g., a keypad or touchscreen) or via one or more wireless and/or wired networks **18** through a network interface **240**. That is, in some cases,

the carpooling preferences may be entered by a human driver, who may be provided with carpooling preferences from the first end user **12a**. Alternatively, such carpooling preferences may be received wirelessly from a network device such as the realtime carpooling management system **16** or from a real-time carpooling coordinating system **15** of FIG. **1**.

(139) Referring now to FIG. **6D**, in the same or alternative implementations, the first directive receiving operation **502** may additionally or alternatively include an operation **618** for receiving the one or more first directives including receiving transport rate data that indicates one or more transport rates for the first end user that are based, at least in part, on the transportation vehicle unit transporting one or more other end users while transporting the first end user. For instance, the carpooling preference receiving module **302** including the transport rate data receiving module **304** (see FIG. **3A**) of the transport computing device **10*** of FIG. **2A** or **2B** receiving the one or more first directives including receiving, by the transport rate data receiving module **304**, transport rate data that indicates one or more transport rates for the first end user **12a** that are based, at least in part, on the transportation vehicle unit **20** transporting one or more other end users (e.g., a second end user **12b**) while transporting the first end user **12a**. Note that in some cases, the one or more transport rates may be received separately from the one or more first directives.

(140) In some implementations, operation **618** may further include an operation **619** for receiving transport rate data that indicates one or more transport rates for the first end user that are based, at least in part, on the number of other end users that the transportation vehicle unit will be transporting while transporting the first end user, the other end users not being affiliated with the first end user. For instance, the transport rate data receiving module **304** of the transport computing device **10*** of FIG. **2A** or **2B** receiving transport rate data that indicates one or more transport rates for the first end user **12a** that are based, at least in part, on the number of other end users that the transportation vehicle unit **20** will be transporting while transporting the first end user **12a**, the other end users (e.g., a second end user **12b**) not being affiliated with the first end user **12a**.

(141) In some cases, operation **618** may additionally or alternatively include an operation **620** for receiving transport rate data that indicates one or more transport rates for the first end user that are based, at least in part, on the number of end user drop-offs scheduled to occur at least during transport of the first end user by the transportation vehicle unit. For instance, the transport rate data receiving module **304** of the transport computing device **10*** of FIG. **2A** or **2B** receiving transport rate data that indicates one or more transport rates for the first end user **12a** that are based, at least in part, on the number of end user drop-offs scheduled to occur at least during transport of the first end user **12a** by the transportation vehicle unit **20**.

(142) In some implementations, the first directive receiving operation **502** may include an operation **621** for receiving the one or more first directives including receiving image data for one or more facial images of the first end user. For instance, the directive receiving module **202*** including the image data receiving module **306** (see FIG. **3A**) of the transport computing device **10*** of FIG. **2A** or **2B** receiving the one or more first directives including receiving, by the image data receiving module **306**, image data for one or more facial images of the first end user **12a**. By providing the facial image of the first end user **12a**, a human driver may be able to quickly recognize the first end user **12a** particularly in a crowded venue such as at a stadium exit after a football game.

(143) Referring back to the second directive receiving operation **504** of FIG. **5**, the second directive receiving operation **504** similar to the first directive receiving operation **502** of FIG. **5** may be executed in a number of different ways in various alternative embodiments as illustrated, for example, in FIGS. **7A**, **7B**, **7C**, and **7D**. In some cases, for example, the second directive receiving operation **504** may actually include an operation **722** for receiving the one or more second directives electronically via one or more wireless and/or wired networks. For instance, the directive receiving module **202*** of the transport computing device **10*** of FIG. **2A** or **2B** receiving the one or more second directives electronically using a network interface **240** via one or more wireless

and/or wired networks **18**.

(144) In the same or alternative implementation, the second directive receiving operation **504** may include an operation **723** for receiving, while the transportation vehicle unit is en route to or is transporting the first end user, the one or more second directives by receiving the one or more second directives when the transportation vehicle unit is spatially moving towards a first end user rendezvous location in order to rendezvous with the first end user. For instance, the directive receiving module **202*** of the transport computing device **10*** of FIG. 2A or 2B receiving, while the transportation vehicle unit **20** is en route to rendezvousing with a first end user **12a** or is transporting the first end user **12a**, the one or more second directives by receiving the one or more second directives when the transportation vehicle unit **20** is spatially moving towards a first end user rendezvous location (e.g., first end user rendezvous location **402** of FIG. 4A) in order to rendezvous with the first end user **12a**.

(145) In some cases, operation **723** may actually involve an operation **724** for receiving the one or more second directives when the transportation vehicle unit is spatially moving towards the first end user rendezvous location and is within four miles from the first end user rendezvous location. For instance, the directive receiving module **202*** of the transport computing device **10*** of FIG. 2A or 2B receiving the one or more second directives when the transportation vehicle unit **20** is spatially moving towards the first end user rendezvous location and is within four miles from reaching the first end user rendezvous location for rendezvousing with the first end user **12a**.

(146) In some implementations, the second directive receiving module **504** may actually include an operation **725** for receiving, while the transportation vehicle unit is en route to or is transporting the first end user, the one or more second directives by receiving the one or more second directives when the transportation vehicle unit has already secured the first end user. For instance, the directive receiving module **202*** of the transport computing device **10*** of FIG. 2A or 2B receiving, while the transportation vehicle unit **20** is en route to rendezvousing with a first end user **12a** or is transporting the first end user **12a**, the one or more second directives by receiving the one or more second directives when the transportation vehicle unit **20** has already secured the first end user **12a**.

(147) In some implementations, the second directive receiving module **504** may include an operation **726** for receiving, while the transportation vehicle unit is en route to or is transporting the first end user, the one or more second directives by receiving the one or more second directives when the transportation vehicle unit is within 15 minutes or less from rendezvousing with the first end user. For instance, the directive receiving module **202*** of the transport computing device **10*** of FIG. 2A or 2B receiving, while the transportation vehicle unit **20** is en route to rendezvousing with a first end user **12a** or is transporting the first end user **12a**, the one or more second directives by receiving the one or more second directives when the transportation vehicle unit **20** is within 15 minutes or less from rendezvousing with the first end user **12a**.

(148) In some implementations, the second directive receiving operation **504** may include an operation **727** for receiving the one or more second directives by receiving one or more second directives that identify a second end user rendezvous location for rendezvousing with the second end user. For instance, the directive receiving module **202*** of the transport computing device **10*** of FIG. 2A or 2B receiving the one or more second directives by receiving one or more second directives that identify a second end user rendezvous location (e.g., GPS data indicating current location of the second end user **12b**) for rendezvousing (by the transportation vehicle unit **20**) with the second end user **12b**.

(149) In some implementations, the second directive receiving operation **504** may include an operation **728** for receiving the one or more second directives by receiving one or more second directives that identify a second end user destination location for dropping-off the second end user as illustrated in FIG. 7B. For instance, the directive receiving module **202*** of the transport computing device **10*** of FIG. 2A or 2B receiving the one or more second directives by receiving one or more second directives that identify a second end user destination location for dropping-off

(e.g., the act of offloading one or more passengers or end users) the second end user **12b**.

(150) In some implementations, the second directive receiving operation **504** may include an operation **729** for receiving the one or more second directives by receiving one or more second directives that identify the number of passengers and/or luggage to be transported with the second end user. For instance, the directive receiving module **202*** of the transport computing device **10*** of FIG. 2A or 2B receiving the one or more second directives by receiving one or more second directives that identify the number of passengers and/or luggage to be transported with the second end user **12b**.

(151) In some implementations, the second directive receiving operation **504** may include an operation **730** for receiving the one or more second directives that direct the transportation vehicle unit to transport the second end user by receiving one or more second directives that direct the transportation vehicle unit to drop-off the first end user and the second end user in a particular order. For instance, the directive receiving module **202*** of the transport computing device **10*** of FIG. 2A or 2B receiving the one or more second directives that direct the transportation vehicle unit **20** to transport the second end user **12b** by receiving one or more second directives that direct (e.g., instruct) the transportation vehicle unit **20** to drop-off the first end user **12a** and the second end user **12b** in a particular order.

(152) In some implementations, the second directive receiving operation **504** may include an operation **731** for receiving the one or more second directives that direct the transportation vehicle unit to transport the second end user by receiving one or more second directives that identify a route for dropping-off the first end user and the second end user. For instance, the directive receiving module **202*** of the transport computing device **10*** of FIG. 2A or 2B receiving the one or more second directives that direct the transportation vehicle unit **20** to transport the second end user **12b** by receiving one or more second directives that identify a route (e.g., street-by-street/turn-by-turn route) for dropping-off the first end user **12a** and the second end user **12b**.

(153) In various implementations, the second directive receiving operation **504** may include an operation **732** for receiving the one or more second directives that direct the transportation vehicle unit to transport the second end user including receiving one or more carpooling preferences of the second end user. For instance, the directive receiving module **202*** including the carpooling preference receiving module **302** (see FIG. 3A) of the transport computing device **10*** of FIG. 2A or 2B receiving the one or more second directives that direct the transportation vehicle unit **20** to transport the second end user **12b** including receiving one or more carpooling preferences of the second end user **12b**. In various implementations, the one or more carpooling preferences may be received separately from the one or more second directives. In some cases, the one or more carpooling preferences may be provided by the second end user **12b**, while in other cases, the one or more carpooling preferences may be provided by a third party such as by a ridesharing company that is administrating the carpooling services.

(154) In some implementations, operation **732** may further include an operation **733** for receiving one or more carpooling preferences of the second end user that indicates maximum number of end user drop-offs permitted prior to the second end user being dropped-off. For instance, the carpooling preference receiving module **302** of the transport computing device **10*** of FIG. 2A or 2B receiving one or more carpooling preferences of the second end user **12b** that indicates maximum number of end user drop-offs permitted prior to the second end user **12b** being dropped-off.

(155) As In the same or alternative implementations, operation **732** may additionally or alternatively include an operation **734** for receiving one or more carpooling preferences of the second end user that indicate maximum amount of time delay permitted in transporting the second end user to a second end user destination location and as a result of the transportation vehicle unit transporting one or more other end users including the first end user. For instance, the carpooling preference receiving module **302** of the transport computing device **10*** of FIG. 2A or 2B receiving

one or more carpooling preferences of the second end user **12b** that indicate maximum amount of time delay permitted in transporting the second end user **12b** to a second end user destination location and as a result of the transportation vehicle unit **20** transporting one or more other end users including the first end user **12a**.

(156) In the same or alternative implementations, the second directive receiving operation **504** may include an operation **735** for receiving the one or more second directives that direct the transportation vehicle unit to transport the second end user including receiving transport rate data that indicates a transport rate for transporting the second end user by the transportation vehicle unit. For instance, the directive receiving module **202*** including the transport rate data receiving module **304** (see FIG. 3A) of the transport computing device **10*** of FIG. 2A or 2B receiving the one or more second directives that direct the transportation vehicle unit **20** to transport the second end user **12b** including receiving, by the transport rate data receiving module **304**, transport rate data that indicates a transport rate (e.g., a fare or fee) for transporting the second end user **12b** by the transportation vehicle unit **20**.

(157) As further illustrated in FIG. 7C, in various implementations, operation **735** may actually include one or more additional operations including, in some cases, an operation **736** for receiving the transport rate data separately from reception of the one or more second directives. For instance, the transport rate data receiving module **304** of the transport computing device **10*** of FIG. 2A or 2B receiving (e.g., receiving electronically) the transport rate data separately from reception of the one or more second directives.

(158) In the same or alternative implementations, operation **735** may additionally or alternatively include an operation **737** for receiving transport rate data that indicates a discounted transport rate for the second end user, the discount transport rate for the second end user being based, at least in part, on the total number of end users being transported by the transportation vehicle unit while transporting the second end user. For instance, the transport rate data receiving module **304** of the transport computing device **10*** of FIG. 2A or 2B receiving transport rate data that indicates a discounted transport rate for the second end user **12b**, the discount transport rate for the second end user **12b** being based, at least in part, on the total number of end users (including the first end user **12a**) being transported by the transportation vehicle unit **20** while transporting the second end user **12b**.

(159) In some implementations, operation **735** may include an operation **738** for receiving transport rate data that indicates a discounted transport rate for the second end user, the discount transport rate for the second end user being based, at least in part, on the number of planned end user drop-offs to be made by the transportation vehicle unit prior to the second end user being dropped-off at a second end user destination location. For instance, the transport rate data receiving module **304** of the transport computing device **10*** of FIG. 2A or 2B receiving transport rate data that indicates a discounted transport rate for the second end user **12b**, the discount transport rate for the second end user **12b** being based, at least in part, on the number of planned end user drop-offs to be made by the transportation vehicle unit **20** prior to the second end user **12b** being dropped-off at a second end user destination location.

(160) In some implementations, operation **735** may include an operation **739** for receiving transport rate data that indicates a premium transport rate for the second end user, the premium transport rate for the second end user being a higher transport rate than a transport rate for the first end user for being transported by the transportation vehicle unit. For instance, the transport rate data receiving module **304** of the transport computing device **10*** of FIG. 2A or 2B receiving transport rate data that indicates a premium transport rate for the second end user **12b**, the premium transport rate for the second end user **12b** being a higher transport rate than a transport rate for the first end user **12a** for being transported by the transportation vehicle unit **20**. For example, if the first end user **12a** is being charged 12 dollars then the second end user **12b** may be charged in the amount greater than 12 dollars such as 16 dollars. This may be done in some cases to provide an incentive for the first

end user **12a** to permit other end users (e.g., the second end user **12b**) to join the first end user **12a** in being transported by the transportation vehicle unit **20**. That is, by making the second end user **12b** pay a larger portion of the total fare (and having the first end user **12a** pay a smaller share of the total fare), the first end user **12a** may be provided an incentive to accept other end users.

(161) In some implementations, operation **735** may include an operation **740** for receiving transport rate data that indicates a discounted transport rate for the first end user, the discounted transport rate being as a result of the second end user being assigned to be transported by the transportation vehicle unit, the discounted transport rate for the first end user being less than a transport rate for the first end user that was provided prior to assignment of the second end user to the transportation vehicle unit. For instance, the transport rate data receiving module **304** of the transport computing device **10*** of FIG. **2A** or **2B** receiving transport rate data that indicates a discounted transport rate for the first end user **12a**, the discounted transport rate being as a result of or based on the second end user **12b** being assigned to be transported by the transportation vehicle unit **20**, the discounted transport rate for the first end user **12a** being less than a transport rate for the first end user **12a** that was provided prior to assignment of the second end user **12b** to the transportation vehicle unit **20**.

(162) In some implementations, operation **735** may include an operation **741** for receiving transport rate data that indicates a discounted transport rate for the first end user, the discounted transport rate being as a result of the transportation vehicle unit making an additional passenger drop-off prior to the first end user being dropped-off at a first end user destination location and as a result of the second end user being assigned to be transported by the transportation vehicle unit. For instance, the transport rate data receiving module **304** of the transport computing device **10*** of FIG. **2A** or **2B** receiving transport rate data that indicates a discounted transport rate for the first end user **12a**, the discounted transport rate being as a result of the transportation vehicle unit **20** making an additional passenger drop-off prior to the first end user **12a** being dropped-off at a first end user destination location and as a result of the second end user **12b** being assigned to be transported by the transportation vehicle unit **20**.

(163) In various implementations, the second directive receiving operation **504** may include an operation **742** for receiving the one or more second directives that direct the transportation vehicle unit to transport a second end user, the transportation vehicle unit having been remotely determined across one or more wireless and/or wired networks to be able to accommodate transport of the second end user while transporting the first end user as illustrated in FIG. **7D**. For instance, the directive receiving module **202*** of the transport computing device **10*** of FIG. **2A** or **2B** receiving the one or more second directives that direct the transportation vehicle unit **20** to transport a second end user **12b**, the transportation vehicle unit **20** having been remotely determined (e.g., determined by the real-time carpooling management system **16** of FIG. **1**) across one or more wireless and/or wired networks **18** to be able to accommodate (e.g., having sufficient cabin space and/or is located in the proximate vicinity of the second end user **12b**) transport of the second end user **12b** while transporting the first end user **12a**.

(164) In the same or alternative implementations, the second directive receiving operation **504** may include an operation **743** for receiving the one or more second directives that direct the transportation vehicle unit to transport a second end user, the transportation vehicle unit having been determined, when the one or more second directives are received, to be in the proximate vicinity of a second end user rendezvous location for rendezvousing with the second end user. For instance, the directive receiving module **202*** of the transport computing device **10*** of FIG. **2A** or **2B** receiving the one or more second directives that direct the transportation vehicle unit **20** to transport a second end user **12b**, the transportation vehicle unit **20** having been determined (e.g., by the real-time carpooling management system **16**), when the one or more second directives are received by the transport computing device **10***, to be in the proximate vicinity (e.g., within 5 miles) of a second end user rendezvous location (e.g., current location of the second end user **12b**) for rendezvousing with the second end user **12b**. Note that in various embodiments the phrase

“when the one or more second directives are received by the transport computing device **10***,” as used herein, may be in reference to a time span that includes at least when the one or more second directives are transmitted by the real-time carpooling management system **16** to when the transport computing device **10*** receives the one or more second directives.

(165) In the same or alternative implementations, the second directive receiving operation **504** may include an operation **744** for receiving the one or more second directives that direct the transportation vehicle unit to transport a second end user, the transportation vehicle unit having been determined, when the one or more second directives are received, to have sufficient available space to accommodate the second end user. For instance, the directive receiving module **202*** of the transport computing device **10*** of FIG. 2A or 2B receiving the one or more second directives that direct the transportation vehicle unit **20** to transport a second end user **12b**, the transportation vehicle unit **20** having been determined (e.g., by the real-time carpooling management system **16**), when the one or more second directives are received by the transport computing device **10***, to have sufficient available space to accommodate the second end user **12b**.

(166) In the same or alternative implementations, the second directive receiving operation **504** may include an operation **745** for receiving the one or more second directives that direct the transportation vehicle unit to transport a second end user, the transportation vehicle unit having been determined, when the one or more second directives are received, scheduled for traveling near to a second end user destination location of the second end user when transporting one or more other end users including the first end user. For instance, the directive receiving module **202*** of the transport computing device **10*** of FIG. 2A or 2B receiving the one or more second directives that direct the transportation vehicle unit **20** to transport a second end user **12b**, the transportation vehicle unit **20** having been determined (e.g., by the real-time carpooling management system **16**), when the one or more second directives are received by the transport computing device **10***, scheduled for traveling near to (e.g., within 3 miles) a second end user destination location of the second end user **12b** when transporting one or more other end users including the first end user **12a**.

(167) In the same or alternative implementations, the second directive receiving operation **504** may include an operation **746** for receiving the one or more second directives that direct the transportation vehicle unit to transport a second end user, the transportation vehicle unit having been determined, when the one or more second directives are received, to be able to accommodate transport of the second end user while transporting the first end user without violating one or more carpooling preferences. For instance, the directive receiving module **202*** of the transport computing device **10*** of FIG. 2A or 2B receiving the one or more second directives that direct the transportation vehicle unit to transport a second end user **12b**, the transportation vehicle unit **20** having been determined (e.g., by the real-time carpooling management system **16**), when the one or more second directives are received, to be able to accommodate transport of the second end user **12b** while transporting the first end user **12a** without violating one or more carpooling preferences (e.g., carpooling preferences of the first end user **12a**, the second end user **12b**, and/or a third party-preferences related to permitted number of end user drop-offs, permitted delays in transporting each of the end users, etc.).

(168) Referring back to the non-conflict verifying operation **506** of FIG. 5, the non-conflict verifying operation **506**, similar to the first directive receiving operation **502** and the second directive receiving operation **504** of FIG. 5, may be executed in a number of different ways in various alternative embodiments as illustrated, for example, in FIGS. 8A, 8B, 8C, 8D, 8E, 8F, and 8G. In some cases, for example, the non-conflict verifying operation **506** may actually include an operation **847** for verifying that compliance with the one or more second directives will not conflict with one or more obligations to transport the first end user by the transportation vehicle unit, the one or more obligations being based, at least in part, on the received one or more first directives. For instance, the non-conflict confirming module **204*** of the transport computing device **10*** of

FIG. 2A or 2B verifying or confirming that compliance with the one or more second directives will not conflict with (e.g., will not violate) one or more obligations to transport the first end user **12a** by the transportation vehicle unit **20**, the one or more obligations being based, at least in part, on the received one or more first directives.

(169) In the same or alternative implementations, the non-conflict verifying operation **506** may include an operation **848** for verifying that compliance with the one or more second directives will not conflict with one or more obligations to transport the first end user by the transportation vehicle unit, the one or more obligations defining one or more conditional directives that permit the transportation vehicle unit to transport one or more other end users while the transportation vehicle unit is transporting the first end user only if one or more specified conditions can be or have already been realized as illustrated in FIGS. **8A**, **8B**, **8C**, and **8D**. For instance, the non-conflict confirming module **204*** of the transport computing device **10*** of FIG. 2A or 2B verifying (e.g., confirming) verifying that compliance with the one or more second directives will not conflict with one or more obligations to transport the first end user **12a** by the transportation vehicle unit **20**, the one or more obligations defining one or more conditional directives that permit the transportation vehicle unit **20** to transport one or more other end users (who are not affiliated with the first end user **12a**), such as the second end user **12b**, while the transportation vehicle unit **20** is transporting the first end user **12a** only if one or more specified conditions can be or have already been realized (e.g., the one or more specified conditions can be met by transporting the one or more other end users and while transporting the first end user **12a** or the one or more specified conditions have already been met). In some cases, the logic of the transport computing device **10*** may, upon determining that the one or more specified have been or can be met, permit the transport of a second end user **12b** by the transportation vehicle unit **20** by simply presenting (e.g., presenting to a human driver or a robotic driver) the one or more second directives.

(170) As further illustrated in FIGS. **8A**, **8B**, **8C**, and **8D**, in various alternative implementations, operation **848** may include one or more additional operations including, in some cases, an operation **849** for verifying that compliance with the one or more second directives will not conflict with one or more obligations to transport the first end user by the transportation vehicle unit, the one or more obligations defining one or more conditional directives that permit transport, by the transportation vehicle unit, of the second end user while the transportation vehicle unit is transporting the first end user only if transport of the one or more other end users by the transportation vehicle unit does not cause a delay in transporting the first end user to a first end user destination location that is greater than a predefined amount of maximum permitted delay as illustrated in FIG. **8A**. For instance, the non-conflict confirming module **204*** of the transport computing device **10*** of FIG. 2A or 2B verifying (e.g., confirming) that compliance with the one or more second directives will not conflict with one or more obligations to transport the first end user **12a** by the transportation vehicle unit **20**, the one or more obligations defining one or more conditional directives that permit transport, by the transportation vehicle unit **20**, of the one or more other end users while the transportation vehicle unit **20** is transporting the first end user **12a** only if transport of the second end user (e.g., the second end user **12b**) by the transportation vehicle unit **20** does not cause a delay in transporting the first end user **12a** to a first end user destination location that is greater than a predefined amount of maximum permitted delay (e.g., 15 minutes of maximum delay).

(171) In some implementations, operation **849** may further include an operation **850** for verifying that compliance with the one or more second directives will not conflict with one or more obligations to transport the first end user by the transportation vehicle unit, the one or more obligations defining one or more conditional directives that permit transport, by the transportation vehicle unit, of the second end user while the transportation vehicle unit is transporting the first end user only if transport of the one or more other end users by the transportation vehicle unit does not cause a delay in transporting the first end user to a first end user destination location that is greater

than a 20 minutes of maximum permitted delay. For instance, the non-conflict confirming module **204*** of the transport computing device **10*** of FIG. 2A or 2B verifying (e.g., confirming) that compliance with the one or more second directives will not conflict with one or more obligations to transport the first end user **12a** by the transportation vehicle unit **20**, the one or more obligations defining one or more conditional directives that permit transport, by the transportation vehicle unit **20**, of the second end user **12b** while the transportation vehicle unit **20** is transporting the first end user **12a** only if transport of the one or more other end users (e.g., second end user **12b**) by the transportation vehicle unit **20** does not cause a delay in transporting the first end user **12a** to a first end user destination location that is greater than a 20 minutes of maximum permitted delay.

(172) In the same or alternative implementations, operation **848** may include an operation **851** for verifying that compliance with the one or more second directives will not conflict with one or more obligations to transport the first end user by the transportation vehicle unit, the one or more obligations defining one or more conditional directives that permit transport, by the transportation vehicle unit, of the second end user while the transportation vehicle unit is transporting the first end user only if transport of the one or more other end users by the transportation vehicle unit does not cause the transportation vehicle unit to have a number of end user drop-offs prior to the first end user being dropped-off that is greater than a predefined amount of maximum permitted end user drop-offs permitted before the first end user is dropped-off as illustrated in FIG. 8B. For instance, the non-conflict confirming module **204*** of the transport computing device **10*** of FIG. 2A or 2B verifying or confirming that compliance with the one or more second directives will not conflict with one or more obligations to transport the first end user **12a** by the transportation vehicle unit **20**, the one or more obligations defining one or more conditional directives that permit transport, by the transportation vehicle unit **20**, of the second end user **12b** while the transportation vehicle unit **20** is transporting the first end user **12a** only if transport of the one or more other end users (e.g., the second end user **12b**) by the transportation vehicle unit **20** does not cause the transportation vehicle unit **20** to have a number of end user drop-offs prior to the first end user **12a** being dropped-off that is greater than a predefined amount of maximum permitted end user drop-offs (e.g., four drop-offs or passenger offloading stops) permitted before the first end user **12a** is dropped-off.

(173) In some cases, operation **851** may further include an operation **852** for verifying that compliance with the one or more second directives will not conflict with one or more obligations to transport the first end user by the transportation vehicle unit, the one or more obligations defining one or more conditional directives that permit transport, by the transportation vehicle unit, of the one or more other end users while the transportation vehicle unit is transporting the first end user only if transport of the one or more other end users by the transportation vehicle unit does not cause the transportation vehicle unit to have a number of end user drop-offs prior to the first end user being dropped-off that is greater than a maximum of three end user drop-offs permitted before the first end user is dropped-off. For instance, the non-conflict confirming module **204*** of the transport computing device **10*** of FIG. 2A or 2B verifying (e.g., confirming) that compliance with the one or more second directives will not conflict with one or more obligations to transport the first end user **12a** by the transportation vehicle unit **20**, the one or more obligations defining one or more conditional directives that permit transport, by the transportation vehicle unit **20**, of the second end user **12b** while the transportation vehicle unit **20** is transporting the first end user **12a** only if transport of the one or more other end users (e.g., second end user **12b**) by the transportation vehicle unit **20** does not cause the transportation vehicle unit **20** to have a number of end user drop-offs prior to the first end user **12a** being dropped-off that is greater than a maximum of three end user drop-offs (e.g., passenger offloading stops) permitted before the first end user **12a** is dropped-off.

(174) In the same or alternative implementations, operation **848** may include an operation **853** for verifying that compliance with the one or more second directives will not conflict with one or more

obligations to transport the first end user by the transportation vehicle unit, the one or more obligations defining one or more conditional directives that permit transport, by the transportation vehicle unit, of the one or more other end users while the transportation vehicle unit is transporting the first end user only if transport of the one or more other end users by the transportation vehicle unit does not cause any end user drop-off to occur prior to drop of the first end user being dropped-off that is greater than a maximum of three end user drop-offs permitted before the first end user is dropped-off as illustrated in FIG. 8C. For instance, the non-conflict confirming module **204*** of the transport computing device **10*** of FIG. 2A or 2B verifying (e.g., confirming) that compliance with the one or more second directives will not conflict with one or more obligations to transport the first end user **12a** by the transportation vehicle unit **20**, the one or more obligations defining one or more conditional directives that permit transport, by the transportation vehicle unit **20**, of the one or more other end users (e.g., the second end user **12b**) while the transportation vehicle unit **20** is transporting the first end user **12a** only if transport of the one or more other end users (e.g., the second end user **12b**) by the transportation vehicle unit **20** does not cause the transportation vehicle unit to have a number of end user drop-offs prior first end user **12a** being dropped-off that is greater than a maximum of three end user drop-offs permitted before the first end user **12a** is dropped-off.

(175) In the same or alternative implementations, operation **848** may include an operation **854** for verifying that compliance with the one or more second directives will not conflict with one or more obligations to transport the first end user by the transportation vehicle unit, the one or more obligations defining one or more conditional directives that permit transport, by the transportation vehicle unit, of the one or more other end users while the transportation vehicle unit is transporting the first end user only if transport of the one or more other end users by the transportation vehicle unit does not result in the transportation vehicle unit having a total number of rendezvous stops for rendezvousing with end users including the first end user and the one or more other end users that exceed a maximum permitted number of rendezvous stops permitted for rendezvousing with the end users during a single carpooling trip. For instance, the non-conflict confirming module **204*** of the transport computing device **10*** of FIG. 2A or 2B verifying (e.g., confirming) that compliance with the one or more second directives will not conflict with one or more obligations to transport the first end user **12a** by the transportation vehicle unit **20**, the one or more obligations defining one or more conditional directives that permit transport, by the transportation vehicle unit **20**, of the one or more other end users (e.g., the second end user **12b**) while the transportation vehicle unit **20** is transporting the first end user **12a** only if transport of the one or more other end users (e.g., the second end user **12b**) by the transportation vehicle unit **20** does not result in the transportation vehicle unit **20** having a total number of rendezvous stops for rendezvousing with end users including the first end user **12a** and the one or more other end users that exceed a maximum permitted number of rendezvous stops permitted for rendezvousing with end users during a single carpooling trip.

(176) In the same or alternative implementations, operation **848** may include an operation **855** for verifying that compliance with the one or more second directives will not conflict with one or more obligations to transport the first end user by the transportation vehicle unit, the one or more obligations defining one or more conditional directives that permit transport, by the transportation vehicle unit, of the one or more other end users while the transportation vehicle unit is transporting the first end user only if transport of the one or more other end users by the transportation vehicle unit does not result in the transportation vehicle unit having a total number of end user drop-off stops that exceeds a maximum permitted number of end user drop-off stops permitted during a single carpooling trip. For instance, the non-conflict confirming module **204*** of the transport computing device **10*** of FIG. 2A or 2B verifying (e.g., confirming) that compliance with the one or more second directives will not conflict with one or more obligations to transport the first end user **12a** by the transportation vehicle unit **20**, the one or more obligations defining one or more

conditional directives that permit transport, by the transportation vehicle unit **20**, of the one or more other end users (e.g., the second end user **12b**) while the transportation vehicle unit **20** is transporting the first end user **12a** only if transport of the one or more other end users (e.g., the second end user **12b**) by the transportation vehicle unit **20** does not result in the transportation vehicle unit **20** having a total number of end user drop-off stops that exceeds a maximum permitted number of end user drop-off stops permitted during a single carpooling trip.

(177) In the same or alternative implementations, operation **848** may include an operation **856** for verifying that compliance with the one or more second directives will not conflict with one or more obligations to transport the first end user by the transportation vehicle unit, the one or more obligations defining one or more conditional directives that permit transport, by the transportation vehicle unit, of the one or more other end users while the transportation vehicle unit is transporting the first end user only if the one or more other end users will be rendezvousing with the transportation vehicle unit at a rendezvous location that is the designating location for the first end user to rendezvousing with the transportation vehicle unit as illustrated in FIG. **8D**. For instance, the non-conflict confirming module **204*** of the transport computing device **10*** of FIG. **2A** or **2B** verifying (e.g., confirming) that compliance with the one or more second directives will not conflict with one or more obligations to transport the first end user **12a** by the transportation vehicle unit **20**, the one or more obligations defining one or more conditional directives that permit transport, by the transportation vehicle unit **20**, of the one or more other end users (e.g., the second end user **12b**) while the transportation vehicle unit **20** is transporting the first end user **12a** only if the one or more other end users (e.g., the second end user **12b**) will be rendezvousing with the transportation vehicle unit **20** at a rendezvous location that is the designating location for the first end user **12a** to rendezvousing with the transportation vehicle unit **20**.

(178) In the same or alternative implementations, operation **848** may include an operation **857** for verifying that compliance with the one or more second directives will not conflict with one or more obligations to transport the first end user by the transportation vehicle unit, the one or more obligations defining one or more conditional directives that permit transport, by the transportation vehicle unit, of the one or more other end users while the transportation vehicle unit is transporting the first end user only if the one or more other end users are to be transported to a destination location that is the same as the destination location for the first end user. For instance, the non-conflict confirming module **204*** of the transport computing device **10*** of FIG. **2A** or **2B** verifying (e.g., confirming) that compliance with the one or more second directives will not conflict with one or more obligations to transport the first end user **12a** by the transportation vehicle unit **20**, the one or more obligations defining one or more conditional directives that permit transport, by the transportation vehicle unit **20**, of the one or more other end users (e.g., the second end user **12b**) while the transportation vehicle unit **20** is transporting the first end user **12a** only if the one or more other end users (e.g., the second end user **12b**) are to be transported to a destination location that is the same as the destination location for the first end user **12a**.

(179) In the same or alternative implementations, operation **848** may include an operation **858** for verifying that compliance with the one or more second directives will not conflict with one or more obligations to transport the first end user by the transportation vehicle unit, the one or more obligations defining one or more conditional directives that permit transport, by the transportation vehicle unit, of the one or more other end users while the transportation vehicle unit is transporting the first end user only if the one or more other end users have at least one specified common interest with the first end user. For instance, the non-conflict confirming module **204*** of the transport computing device **10*** of FIG. **2A** or **2B** verifying (e.g., confirming) that compliance with the one or more second directives will not conflict with one or more obligations to transport the first end user **12a** by the transportation vehicle unit **20**, the one or more obligations defining one or more conditional directives that permit transport, by the transportation vehicle unit **20**, of the one or more other end users (e.g., the second end user **12b**) while the transportation vehicle unit **20** is

transporting the first end user **12a** only if the one or more other end users (e.g., the second end user **12b**) have at least one specified common interest (e.g., New York Yankees) with the first end user **12a**.

(180) Referring now to FIG. **8E**, in various implementations, the non-conflict verifying operation **506** may include an operation **859** for verifying that the transportation vehicle unit is in the proximate vicinity of a second end user rendezvous location for rendezvousing with the second end user. For instance, the rendezvous location proximity confirming module **308** (see FIG. **3B**) of the transport computing device **10*** of FIG. **2A** or **2B** verifying (e.g., confirming) that the transportation vehicle unit **20** is in the proximate vicinity (e.g., within 5 miles) of a second end user rendezvous location for rendezvousing with the second end user **12b**.

(181) In the same or alternative implementations, the non-conflict verifying operation **506** may include an operation **860** for verifying that the transportation vehicle unit has sufficient available space to accommodate the second end user. For instance, the spatial availability confirming module **310** (see FIG. **3B**) of the transport computing device **10*** of FIG. **2A** or **2B** verifying (e.g., confirming) that the transportation vehicle unit **20** has sufficient available passenger space (as well as luggage space) to accommodate the second end user **12b**.

(182) In the same or alternative implementations, the non-conflict verifying operation **506** may include an operation **861** for verifying that the transportation vehicle unit is scheduled for traveling near to a second end user destination location of the second end user when transporting one or more other end users including the first end user. For instance, the spatial availability confirming module **310** (see FIG. **3B**) of the transport computing device **10*** of FIG. **2A** or **2B** verifying (e.g., confirming) that the transportation vehicle unit **20** is scheduled for traveling near to (e.g., in the vicinity-within 3 miles) a second end user destination location of the second end user **12b** when transporting one or more other end users including the first end user **12a**.

(183) In the same or alternative implementations, the non-conflict verifying operation **506** may include an operation **862** for verifying that compliance with the one or more second directives will not conflict with the one or more obligations to transport the first end user by the transportation vehicle unit by verifying that transport of the second end user by the transportation vehicle unit while transporting the first end user will not violate one or more carpooling preferences of the first end user. For instance, the non-conflict confirming module **204*** including the carpooling preference non-conflict confirming module **314** (see FIG. **3B**) of the transport computing device **10*** of FIG. **2A** or **2B** verifying (e.g., confirming) that compliance with the one or more second directives will not conflict with the one or more obligations to transport the first end user **12a** by the transportation vehicle unit **20** by having the carpooling preference non-conflict confirming module **314** verify or confirm that transport of the second end user **12b** by the transportation vehicle unit **20** while transporting the first end user **12a** will not violate one or more carpooling preferences (e.g., no significant delay, such as a 15 minute delay, in being transported with other end users, being transported with other end users who are New York Jets fans, preference for being dropped-off first, and so forth) of the first end user **12a**.

(184) In the same or alternative implementations, the non-conflict verifying operation **506** may include an operation **863** for verifying that compliance with the one or more second directives will not conflict with the one or more obligations to transport the first end user by the transportation vehicle unit by verifying that transport of the second end user by the transportation vehicle unit while transporting the first end user will not violate one or more carpooling preferences of the second end user. For instance, the non-conflict confirming module **204*** including the carpooling preference non-conflict confirming module **314** of the transport computing device **10*** of FIG. **2A** or **2B** verifying (confirming) that compliance with the one or more second directives will not conflict with the one or more obligations to transport the first end user **12a** by the transportation vehicle unit **20** by having the carpooling preference non-conflict confirming module **314** verify or confirm that transport of the second end user **12b** by the transportation vehicle unit **20** while

transporting the first end user **12a** will not violate one or more carpooling preferences of the second end user **12b**.

(185) Turning now to FIG. **8F**, in various implementations, the non-conflict verifying operation **506** may include an operation **864** for determining a transport rate for the first end user that is based, at least in part, on the transportation vehicle unit transporting one or more other end users including the second end user while transporting the first end user. For instance, the transport rate ascertaining module **316** (see FIG. **3B**) of the transport computing device **10*** of FIG. **2A** or **2B** determining or ascertaining a transport rate for the first end user **12a** (e.g., a fee for transporting the first end user **12a**) that is based, at least in part, on the transportation vehicle unit **20** transporting one or more other end users including the second end user **12b** while transporting the first end user **12a**. In some cases, the determined transport rate may be used to verify a transport rate for the first end user **12a** that was provided by a network entity (e.g., the real-time carpooling management system **16** of FIG. **1**).

(186) As further illustrated in FIG. **8F**, in various implementations, operation **864** may involve an operation **865** for determining a transport rate for the first end user that is based, at least in part, on the number of other end users that the transportation vehicle unit will be transporting while transporting the first end user, the other end users not being affiliated with the first end user. For instance, the transport rate ascertaining module **316** of the transport computing device **10*** of FIG. **2A** or **2B** determining (e.g., ascertaining) a transport rate for the first end user **12a** that is based, at least in part, on the number of other end users including the second end user **12b** that the transportation vehicle unit **20** will be transporting while transporting the first end user **12a**, the other end users not being affiliated with (e.g., having no business and/or personal relationship with) the first end user **12a**.

(187) In some implementations, operation **864** may involve an operation **866** for determining a transport rate for the first end user that is based, at least in part, on the number of end user drop-offs scheduled to occur at least during transport of the first end user by the transportation vehicle unit. For instance, the transport rate ascertaining module **316** of the transport computing device **10*** of FIG. **2A** or **2B** determining (e.g., ascertaining) a transport rate for the first end user **12a** that is based, at least in part, on the number of end user drop-offs scheduled to occur at least during transport of the first end user **12a** by the transportation vehicle unit **20**.

(188) In some implementations, operation **864** may involve an operation **867** for determining a discounted transport rate for the first end user, the discounted transport rate being as a result of the second end user being assigned to be transported by the transportation vehicle unit, the discounted transport rate for the first end user being less than a transport rate for the first end user that was provided prior to assignment of the second end user to the transportation vehicle unit. For instance, the transport rate ascertaining module **316** of the transport computing device **10*** of FIG. **2A** or **2B** determining (e.g., ascertaining) a discounted transport rate for the first end user **12a**, the discounted transport rate being as a result of the second end user **12b** being assigned to be transported by the transportation vehicle unit **20**, the discounted transport rate for the first end user **12a** being less than a transport rate for the first end user **12a** that was provided prior to assignment of the second end user **12b** to the transportation vehicle unit **20**, the discounted transport rate being as a result of the second end user **12b** being assigned to be transported by the transportation vehicle unit **20** while transporting the first end user **12a**.

(189) In some implementations, operation **864** may involve an operation **868** for determining a discounted transport rate for the first end user, the discounted transport rate being as a result of the transportation vehicle unit making an additional passenger drop-off prior to the first end user being dropped-off at a first end user destination location and as a result of the second end user being assigned to be transported by the transportation vehicle unit. For instance, the transport rate ascertaining module **316** of the transport computing device **10*** of FIG. **2A** or **2B** determining (e.g., ascertaining) a discounted transport rate for the first end user **12a**, the discounted transport rate

being as a result of the transportation vehicle unit **20** making an additional passenger drop-off prior to the first end user **12a** being dropped-off (e.g., offloaded) at a first end user destination location and as a result of the second end user **12b** being assigned to be transported by the transportation vehicle unit **20**.

(190) Referring now to FIG. **8G**, in various implementations, the non-conflict verifying operation **506** may include an operation **869** for determining a transport rate for the second end user that is based, at least in part, on the transportation vehicle unit transporting one or more other end users including the first end user while transporting the second end user. For instance, the transport rate ascertaining module **316** of the transport computing device **10*** of FIG. **2A** or **2B** determining or ascertaining a transport rate for the second end user **12b** (e.g., a fare for transporting the second end user **12b**) that is based, at least in part, on the transportation vehicle unit **20** transporting one or more other end users including the first end user **12a** while transporting the second end user **12b**. In some cases, the determined transport rate may be used to verify a transport rate for the second end user **12b** that was provided by a network entity (e.g., the real-time carpooling management system **16** of FIG. **1**).

(191) As further illustrated in FIG. **8G**, in some implementations, operation **869** may involve an operation **870** for determining a discounted transport rate for the second end user, the discount transport rate for the second end user being based, at least in part, on the total number of end users being transported by the transportation vehicle unit while transporting the second end user. For instance, the transport rate ascertaining module **316** of the transport computing device **10*** of FIG. **2A** or **2B** determining (e.g., ascertaining) a discounted transport rate for the second end user **12b**, the discount transport rate for the second end user **12b** being based, at least in part, on the total number of end users (including the first end user **12a**) being transported by the transportation vehicle unit **20** while transporting the second end user **12b**.

(192) In some implementations, operation **869** may involve an operation **871** for determining a discounted transport rate for the second end user, the discount transport rate for the second end user being based, at least in part, on the number of planned end user drop-offs to be made by the transportation vehicle unit prior to the second end user being dropped off at a second end user destination location. For instance, the transport rate ascertaining module **316** of the transport computing device **10*** of FIG. **2A** or **2B** determining (e.g., ascertaining) a discounted transport rate for the second end user **12b**, the discount transport rate for the second end user **12b** being based, at least in part, on the number of planned end user drop-offs to be made by the transportation vehicle unit **20** prior to the second end user **12b** being dropped off at a second end user destination location and during the carpooling trip that results in the second end user **12b** and the first end user **12a** being transported to their destination locations.

(193) In some implementations, operation **869** may involve an operation **872** for determining a premium transport rate for the second end user, the premium transport rate for the second end user being a higher transport rate than a transport rate for the first end user for being transported by the transportation vehicle unit. For instance, the transport rate ascertaining module **316** of the transport computing device **10*** of FIG. **2A** or **2B** determining (e.g., ascertaining) a premium transport rate for the second end user **12b**, the premium transport rate for the second end user **12b** being a higher transport rate than a transport rate for the first end user **12a** for being transported by the transportation vehicle unit **20**.

(194) Turning now to FIG. **9** illustrating another operational flow **900**. Operational flow **900** includes certain operations that mirror the operations included in operational flow **500** of FIG. **5**. These operations include a first directive receiving operation **902**, a second directive receiving operation **904**, and a non-conflict verifying operation **906** that corresponds to and mirrors the first directive receiving operation **502**, the second directive receiving operation **504**, and the non-conflict verifying operation **506**, respectively, of FIG. **5**.

(195) In addition, operational flow **900** further include a confirmation transmitting operation **908**

for transmitting one or more confirmations that the one or more second directives have been accepted for execution by the transportation vehicle unit. For instance, the confirmation transmitting module **206*** of the transport computing device **10*** of FIG. 2A or 2B transmitting electronically, via one or more wireless and/or wired networks **18**, one or more confirmations that the one or more second directives have been accepted for execution by the transportation vehicle unit **20**. In some cases, the one or more confirmations may be transmitted to a real-time carpooling management system **16**.

(196) As further illustrated in FIG. 9, in some implementations, the confirmation transmitting operation **908** may actually involve an operation **910** for transmitting the one or more confirmations in response to verification that compliance with the one or more second directives will not conflict with one or more obligations to transport the first end user by the transportation vehicle unit. For instance, the confirmation transmitting module **206*** of the transport computing device **10*** of FIG. 2A or 2B transmitting the one or more confirmations in response to verification that compliance with the one or more second directives will not conflict with one or more obligations to transport the first end user **12a** by the transportation vehicle unit **20**.

(197) Turning now to FIG. 10 illustrating another operational flow **1000**. Operational flow **1000** includes certain operations that mirror the operations included in operational flow **500** of FIG. 5. These operations include a first directive receiving operation **1002**, a second directive receiving operation **1004**, and a non-conflict verifying operation **1006** that corresponds to and mirrors the first directive receiving operation **502**, the second directive receiving operation **504**, and the non-conflict verifying operation **506**, respectively, of FIG. 5.

(198) In addition, operation **1000** further includes an instructive directive presenting operation **1008** for presenting, in response to verification that compliance with the one or more second directives will not conflict with one or more obligations to transport the first end user by the transportation vehicle unit, one or more instructive directives that direct the transportation vehicle unit to transport the second end user. For instance, the instructive directive presenting module **208*** of the transport computing device **10*** of FIG. 2A or 2B presenting, in response to verification that compliance with the one or more second directives will not conflict with one or more obligations to transport the first end user **12a** by the transportation vehicle unit **20**, one or more instructive directives that direct the transportation vehicle unit **20** to transport the second end user **12b**.

(199) As further illustrated in FIG. 11, the instructive directive presenting operation **1008** may be implemented in a variety of different ways in various alternative implementations. For example, in some implementations, the instructive directive presenting operation **1008** may involve an operation **1176** for presenting visually and/or audibly the one or more instructive directives via user interface. For instance, the visual/audible instructive directive presenting module **320** (see FIG. 3C) of the transport computing device **10*** of FIG. 2A or 2B presenting visually and/or audibly the one or more instructive directives via user interface **250** (e.g., a display screen and/or one or more speakers)

(200) In the same or alternative implementations, the instructive directive presenting operation **1008** may involve an operation **1177** for presenting electronically the one or more instructive directives to a navigation system of a robotic driver system of the transportation vehicle unit. For instance, the electronic instructive directive presenting module **322** (see FIG. 3C) of the transport computing device **10*** of FIG. 2A or 2B presenting electronically the one or more instructive directives to a navigation system **452** of a robotic driver system **450** of the transportation vehicle unit **20**.

(201) In the same or alternative implementations, the instructive directive presenting operation **1008** may involve an operation **1178** for presenting the one or more instructive directives by presenting one or more instructive directives that identify a rendezvous location for rendezvousing with the second end user and/or that identify a second end user destination location for the second end user. For instance, the instructive directive presenting module **208*** of the transport computing

device **10*** of FIG. 2A or 2B presenting the one or more instructive directives by presenting one or more instructive directives that identify a rendezvous location for rendezvousing with the second end user **12b** and/or that identify a second end user destination location for the second end user **12b**.

(202) In the same or alternative implementations, the instructive directive presenting operation **1008** may involve an operation **1179** for presenting the one or more instructive directives by presenting one or more instructive directives that indicate the order in which the first end user and the second end user are to be dropped-off. For instance, the instructive directive presenting module **208*** of the transport computing device **10*** of FIG. 2A or 2B presenting the one or more instructive directives by presenting one or more instructive directives that indicate the order in which the first end user **12a** and the second end user **12b** are to be dropped-off. In some cases, the one or more instructive directives may provide a specific route for dropping-off (e.g., offloading) the first end user **12a** and the second end user **12b**.

(203) In the same or alternative implementations, the instructive directive presenting operation **1008** may involve an operation **1180** for presenting the one or more instructive directives by presenting one or more instructive directives that indicate one or more transport rates for the first end user and/or the second end user. For instance, the instructive directive presenting module **208*** of the transport computing device **10*** of FIG. 2A or 2B presenting the one or more instructive directives by presenting one or more instructive directives that indicate one or more transport rates (e.g., transport fares or fees) for the first end user **12a** and/or the second end user **12b**.

(204) While particular aspects of the present subject matter described herein have been shown and described, it will be apparent to those skilled in the art that, based upon the teachings herein, changes and modifications may be made without departing from the subject matter described herein and its broader aspects and, therefore, the appended claims are to encompass within their scope all such changes and modifications as are within the true spirit and scope of the subject matter described herein. It will be understood by those within the art that, in general, terms used herein, and especially in the appended claims (e.g., bodies of the appended claims) are generally intended as “open” terms (e.g., the term “including” should be interpreted as “including but not limited to,” the term “having” should be interpreted as “having at least,” the term “includes” should be interpreted as “includes but is not limited to,” etc.).

(205) It will be further understood by those within the art that if a specific number of an introduced claim recitation is intended, such an intent will be explicitly recited in the claim, and in the absence of such recitation no such intent is present. For example, as an aid to understanding, the following appended claims may contain usage of the introductory phrases “at least one” and “one or more” to introduce claim recitations. However, the use of such phrases should not be construed to imply that the introduction of a claim recitation by the indefinite articles “a” or “an” limits any particular claim containing such introduced claim recitation to claims containing only one such recitation, even when the same claim includes the introductory phrases “one or more” or “at least one” and indefinite articles such as “a” or “an” (e.g., “a” and/or “an” should typically be interpreted to mean “at least one” or “one or more”); the same holds true for the use of definite articles used to introduce claim recitations. In addition, even if a specific number of an introduced claim recitation is explicitly recited, those skilled in the art will recognize that such recitation should typically be interpreted to mean at least the recited number (e.g., the bare recitation of “two recitations,” without other modifiers, typically means at least two recitations, or two or more recitations).

(206) Furthermore, in those instances where a convention analogous to “at least one of A, B, and C, etc.” is used, in general such a construction is intended in the sense one having skill in the art would understand the convention (e.g., “a system having at least one of A, B, and C” would include but not be limited to systems that have A alone, B alone, C alone, A and B together, A and C together, B and C together, and/or A, B, and C together, etc.). In those instances where a convention analogous to “at least one of A, B, or C, etc.” is used, in general such a construction is intended in

the sense one having skill in the art would understand the convention (e.g., “a system having at least one of A, B, or C” would include but not be limited to systems that have A alone, B alone, C alone, A and B together, A and C together, B and C together, and/or A, B, and C together, etc.). It will be further understood by those within the art that typically a disjunctive word and/or phrase presenting two or more alternative terms, whether in the description, claims, or drawings, should be understood to contemplate the possibilities of including one of the terms, either of the terms, or both terms unless context dictates otherwise. For example, the phrase “A or B” will be typically understood to include the possibilities of “A” or “B” or “A and B.”

(207) With respect to the appended claims, those skilled in the art will appreciate that recited operations therein may generally be performed in any order. Also, although various operational flows are presented in a sequence(s), it should be understood that the various operations may be performed in other orders than those which are illustrated, or may be performed concurrently. Examples of such alternate orderings may include overlapping, interleaved, interrupted, reordered, incremental, preparatory, supplemental, simultaneous, reverse, or other variant orderings, unless context dictates otherwise. Furthermore, terms like “responsive to,” “related to,” or other past-tense adjectives are generally not intended to exclude such variants, unless context dictates otherwise.

(208) This application may make reference to one or more trademarks, e.g., a word, letter, symbol, or device adopted by one manufacturer or merchant and used to identify and/or distinguish his or her product from those of others. Trademark names used herein are set forth in such language that makes clear their identity, that distinguishes them from common descriptive nouns, that have fixed and definite meanings, or, in many if not all cases, are accompanied by other specific identification using terms not covered by trademark. In addition, trademark names used herein have meanings that are well-known and defined in the literature, or do not refer to products or compounds for which knowledge of one or more trade secrets is required in order to divine their meaning. All trademarks referenced in this application are the property of their respective owners, and the appearance of one or more trademarks in this application does not diminish or otherwise adversely affect the validity of the one or more trademarks. All trademarks, registered or unregistered, that appear in this application are assumed to include a proper trademark symbol, e.g., the circle R or bracketed capitalization (e.g., [trademark name]), even when such trademark symbol does not explicitly appear next to the trademark. To the extent a trademark is used in a descriptive manner to refer to a product or process, that trademark should be interpreted to represent the corresponding product or process as of the date of the filing of this patent application.

(209) Throughout this application, the terms “in an embodiment,” “in one embodiment,” “in some embodiments,” “in several embodiments,” “in at least one embodiment,” “in various embodiments,” and the like, may be used. Each of these terms, and all such similar terms should be construed as “in at least one embodiment, and possibly but not necessarily all embodiments,” unless explicitly stated otherwise. Specifically, unless explicitly stated otherwise, the intent of phrases like these is to provide non-exclusive and non-limiting examples of implementations of the invention. The mere statement that one, some, or may embodiments include one or more things or have one or more features, does not imply that all embodiments include one or more things or have one or more features, but also does not imply that such embodiments must exist. It is a mere indicator of an example and should not be interpreted otherwise, unless explicitly stated as such.

(210) Those skilled in the art will appreciate that the foregoing specific exemplary processes and/or devices and/or technologies are representative of more general processes and/or devices and/or technologies taught elsewhere herein, such as in the claims filed herewith and/or elsewhere in the present application.

Claims

1. A computer system comprising: one or more processors; a memory to store instructions; wherein the one or more processors execute the instructions to: while a transportation vehicle unit is fulfilling a first directive to transport a first end user to a first destination, make a determination as to whether the transportation vehicle unit is capable of fulfilling a second directive in which the transportation vehicle unit is rerouted to a rendezvous location to pickup and transport a second end user to a second destination, without violating a condition for fulfilling the second directive; and based on the determination, transmit a second directive to cause the transportation vehicle unit to transport the second end user to the second destination.
2. The computer system of claim 1, wherein the condition is based on a preference of the second user.
3. The computer system of claim 2, wherein the preference identifies a maximum permitted delay to a travel time for transporting the second user to the second destination, while also fulfilling the first directive.
4. The computer system of claim 2, wherein the preference identifies a maximum permitted number of stops for transporting the second user to the second destination of the second user, while also fulfilling the first directive.
5. The computer system of claim 2, wherein the preference of the second user is received separately from the second directive.
6. The computer system of claim 2, wherein the condition is based on a preference of a third-party.
7. The computer system of claim 1, wherein the condition is specified in connection with administering a service.
8. The computer system of claim 1, wherein transmitting the second directive included displaying navigation instructions on an electronic device of the transportation vehicle unit.
9. The computer system of claim 1, wherein the vehicle transport unit is a robotic vehicle.
10. The computer system of claim 1, wherein the determination is made while the vehicle transport unit transports the first end user to the first destination.
11. The computer system of claim 1, wherein the determination is made while the vehicle transport unit is enroute to rendezvous with the first end user.
12. A non-transitory computer-readable medium that stores instructions, which when executed by one or more processors of a computer system, cause the computer system to perform operations that include: while a transportation vehicle unit is fulfilling a first directive to transport a first end user to a first destination, making a determination as to whether the transportation vehicle unit is capable of fulfilling a second directive in which the transportation vehicle unit is rerouted to a rendezvous location to pickup and transport a second end user to a second destination, without violating a condition for fulfilling the second directive; and based on the determination, transmitting a second directive to cause the transportation vehicle unit to transport the second end user to the second destination.
13. The non-transitory computer-readable medium of claim 12, wherein the condition is based on a preference of the second user.
14. The non-transitory computer-readable medium of claim 13, wherein the preference identifies a maximum permitted delay to a travel time for transporting the second user to the second destination, while also fulfilling the first directive.
15. The non-transitory computer-readable medium of claim 13, wherein the preference identifies a maximum permitted number of stops for transporting the second user to the second destination of the second user, while also fulfilling the first directive.
16. The non-transitory computer-readable medium of claim 13, wherein the preference of the second user is received separately from the second directive.
17. The non-transitory computer-readable medium of claim 12, wherein the condition is based on a preference of a third-party.

18. The non-transitory computer-readable medium of claim 12, wherein the condition is specified in connection with administering a service.

19. The non-transitory computer-readable medium of claim 12, wherein transmitting the second directive included displaying navigation instructions on an electronic device of the transportation vehicle unit.

20. A computer-implemented method comprising: while a transportation vehicle unit is fulfilling a first directive to transport a first end user to a first destination, making a determination as to whether the transportation vehicle unit is capable of fulfilling a second directive in which the transportation vehicle unit is rerouted to a rendezvous location to pickup and transport a second end user to a second destination, without violating a condition for fulfilling the second directive; and based on the determination, transmit a second directive to reroute the transportation vehicle unit to the rendezvous location before fulfilling the first directive.
