

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12401900
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Song; Wonseok et al.

Electronic device for stabilizing image and method for operating same

Abstract

An electronic device includes a processor causing the electronic device to enter a video capturing mode in which a camera is activated, display a live-preview corresponding to the video capturing mode using images obtained via the camera, while in the video capturing mode, display a user interface including a first graphical object indicative of a first degree of motion stabilization and a second graphical object indicative of a second degree of motion stabilization greater than the first degree, receive an input via the user interface to select one of the first graphical object or the second graphical object, based on the first graphical object being selected, display a live-preview by performing, based on motion information and a first marginal area having a first size, a first stabilization with respect to the obtained images, and based on the second graphical object being selected, display the live-preview by performing, based on the motion information and a second marginal area having a second size larger than the first size, a second stabilization with respect to the obtained images.

Inventors: Song; Wonseok (Gyeonggi-do, KR), Lee; Bohee (Gyeonggi-do, KR), Lee; Sehyun (Gyeonggi-do, KR), Jo; Junghwan (Gyeonggi-do, KR), Ha; Yonghyun (Gyeonggi-do, KR)

Applicant: Samsung Electronics Co., Ltd. (Gyeonggi-do, KR)

Family ID: 1000008779232

Assignee: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Appl. No.: 18/678780

Filed: May 30, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240314434 A1	Sep. 19, 2024

Foreign Application Priority Data

Related U.S. Application Data

continuation parent-doc US 18080398 20221213 US 12069369 child-doc US 18678780

continuation parent-doc US 16795340 20200219 US 11558553 20230117 child-doc US 18080398

Publication Classification

Int. Cl.: H04N23/68 (20230101)

U.S. Cl.:

CPC H04N23/683 (20230101); H04N23/6812 (20230101);

Field of Classification Search

CPC: H04N (23/683)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6115067	12/1999	Koyama	N/A	N/A
6510283	12/2002	Yamagishi	N/A	N/A
6747691	12/2003	Satoh et al.	N/A	N/A
7800697	12/2009	Ishigami et al.	N/A	N/A
9525821	12/2015	Chang	N/A	N/A
9563103	12/2016	Takeuchi	N/A	N/A
9609221	12/2016	Kim et al.	N/A	N/A
9628712	12/2016	Fujita et al.	N/A	N/A
9710629	12/2016	Alameh et al.	N/A	N/A
9860448	12/2017	Yoo et al.	N/A	N/A
9912869	12/2017	Miyahara	N/A	N/A
10218907	12/2018	Gytokuo	N/A	N/A
10382686	12/2018	Kang	N/A	N/A
10715761	12/2019	Lee	N/A	N/A
10863091	12/2019	Song et al.	N/A	N/A
11025876	12/2020	Seok	N/A	N/A
11558553	12/2022	Song	N/A	N/A
12069369	12/2023	Song	N/A	H04N 23/683
2005/0061952	12/2004	Kawahara	N/A	N/A
2012/0120264	12/2011	Lee et al.	N/A	N/A
2014/0285677	12/2013	Fujita et al.	N/A	N/A
2016/0054642	12/2015	Takeuchi	N/A	N/A
2016/0165137	12/2015	Kang	N/A	N/A
2017/0026580	12/2016	Gyotoku	N/A	N/A
2017/0034410	12/2016	Yoo et al.	N/A	N/A

2017/0201684	12/2016	Kang et al.	N/A	N/A
2017/0208250	12/2016	Uemura	N/A	N/A
2018/0048825	12/2017	Wang	N/A	N/A
2019/0034756	12/2018	Kim	N/A	N/A
2019/0068886	12/2018	Baek	N/A	N/A
2019/0089906	12/2018	Joo	N/A	N/A
2019/0222763	12/2018	Takayanagi	N/A	N/A
2020/0077023	12/2019	Kang	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
105376475	12/2015	CN	N/A
106375656	12/2016	CN	N/A
107018313	12/2016	CN	N/A
108476277	12/2016	CN	N/A
107666581	12/2017	CN	N/A
107750451	12/2017	CN	N/A
107770433	12/2017	CN	N/A
3 276 950	12/2017	EP	N/A
2000-32330	12/1999	JP	N/A
2002-333644	12/2001	JP	N/A
2014-171110	12/2013	JP	N/A
5869876	12/2015	JP	N/A
5910565	12/2015	JP	N/A
10-2006-0118344	12/2005	KR	N/A
10-2008-0000972	12/2007	KR	N/A
10-2013-0021701	12/2012	KR	N/A
20130033814	12/2012	KR	N/A
1020140116023	12/2013	KR	N/A
10-2015-0026268	12/2014	KR	N/A
10-2016-0087682	12/2015	KR	N/A
10-2017-0007772	12/2016	KR	N/A
10-2017-0013102	12/2016	KR	N/A
1020170013102	12/2016	KR	N/A
1020170083439	12/2016	KR	N/A
10-2018-0003235	12/2017	KR	N/A
10-2018-0078576	12/2017	KR	N/A
10-2018-0108201	12/2017	KR	N/A

OTHER PUBLICATIONS

International Search Report dated Jun. 16, 2020 issued in counterpart application No.

PCT/KR2020/002383, 8 pages. cited by applicant

European Search Report dated Feb. 7, 2022 issued in counterpart application No. 20759704.8-1209, 10 pages. cited by applicant

Korean Office Action dated Aug. 21, 2023 issued in counterpart application No. 10-2019-0019477, 14 pages. cited by applicant

Chinese Office Action dated Sep. 20, 2023 issued in counterpart application No. 202080015565.0, 11 pages. cited by applicant

KR Notice of Final Rejection dated Feb. 28, 2024 issued in counterpart application No. 10-2019-0019477, 8 pages. cited by applicant

Chinese Office Action dated Mar. 29, 2023 issued in counterpart application No. 202080015565.0, 17 pages. cited by applicant
Indian Examination Report dated Apr. 12, 2023 issued in counterpart application No. 202117041274, 6 pages. cited by applicant
Communication dated Jun. 21, 2024, issued by the Korean Patent Office in Korean Application No. 10-2019-0019477. cited by applicant
Communication dated Jul. 2, 2024, issued by the Korean Patent Office in Korean Application No. 10-2023-0141884. cited by applicant
Communication dated May 30, 2025, issued by Korean Intellectual Property Office in Korean Patent Application No. 10-2024-0132476. cited by applicant
Communication issued Jul. 9, 2025 by the European Patent Office in European Application No. 25175379.4. cited by applicant

Primary Examiner: Segura; Cynthia

Attorney, Agent or Firm: Sughrue Mion, PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S) (1) This application is a Continuation application of U.S. patent application Ser. No. 18/080,398, which was filed in the U.S. Patent and Trademark Office on Dec. 13, 2022, which is a Continuation application of U.S. patent application Ser. No. 16/795,340, filed in the United States Patent and Trademark Office on Feb. 19, 2020, issued as U.S. Pat. No. 11,558,553 on Jan. 17, 2023, which is based on and claims priority under 35 U.S.C. § 119 to Korean Patent Application No. 10-2019-0019477, filed in the Korean Intellectual Property Office on Feb. 19, 2019, the disclosures of which are incorporated herein by reference in their entireties.

BACKGROUND

1. Field

(1) The disclosure relates generally to an electronic device for providing an image capture function and, more particularly to an electronic device for stabilizing an image using a hand-shaking prevention technique and a method for operating the same.

2. Description of Related Art

(2) With the development of information communication and semiconductor technologies, various types of electronic devices have been developed into multimedia devices that provide various multimedia services. For example, electronic devices provide various multimedia services such as a messenger service, a broadcast service, a wireless internet service, a camera service, and a music playback service. Electronic devices include high pixel camera modules, and thus can take still images and moving images and can provide distinctive pictures to which various photographic effects are applied.

(3) Recently, a hand-shaking correction function has been provided to prevent a problem related to an afterimage occurring on a captured image due to a user's hand shaking or an unintentional motion in the case where a user takes a photograph using an electronic device. Video digital image stabilization or digital image stabilization may be used as a hand-shaking correction scheme.

(4) In general, such a video digital image stabilization scheme may correct shaking of a plurality of images (or image frames) based on the motion of an input image (e.g., motion of a subject or a background) and the motion of an electronic device. For example, the electronic device may correct shaking of the image by digital image stabilization which determines a part of an input image (e.g.,

90% of a region of an input image) as an output region based on a margin region (e.g., a correction range) and moves an output region within the input image in a direction opposite the motion of the electronic device.

(5) In addition, the performance of a stabilization scheme may be determined by the size ratio of an output image to an input image. The size ratio may be the size of a margin region obtained by subtracting the output image from the input image. For example, the wider the margin region, the wider the motion range of the output region, which means that correction for a large motion is possible.

(6) However, the size of an image that can be obtained by an electronic device requiring consideration of the portability is limited. For this reason, the digital image stabilization scheme of an electronic device may be suitable for correction for a small motion but may cause a problem of outputting an unnatural image if the correction is performed on a large motion

SUMMARY

(7) The present disclosure has been made to address the above-mentioned problems and disadvantages, and to provide at least the advantages described below.

(8) In accordance with an aspect of the disclosure, an electronic device includes a camera, a motion sensor configured to obtain motion information of the electronic device, a display, a memory storing at least one instruction, and a processor executing the at least one instruction stored in the memory, wherein the processor causes the electronic device to enter a video capturing mode in which the camera is activated, display a live-preview corresponding to the video capturing mode using images obtained via the camera, while in the video capturing mode, display a user interface including a first graphical object indicative of a first degree of motion stabilization and a second graphical object indicative of a second degree of motion stabilization greater than the first degree of motion stabilization, receive an input via the user interface to select one of the first graphical object or the second graphical object, based on the first graphical object being selected, display a live-preview by performing, based on motion information and a first marginal area having a first size, a first stabilization with respect to the obtained images, and based on the second graphical object being selected, display the live-preview by performing, based on the motion information and a second marginal area having a second size larger than the first size, a second stabilization with respect to the obtained images.

(9) In accordance with another aspect of the disclosure, a method of operating an electronic device including a camera includes entering a video capturing mode in which the camera is activated, displaying a live-preview corresponding to the video capturing mode using images obtained via the camera, while in the video capturing mode, displaying a user interface including a first graphical object indicative of a first degree of motion stabilization and a second graphical object indicative of a second degree of motion stabilization greater than the first degree of motion stabilization, receiving an input via the user interface to select one of the first graphical object or the second graphical object, obtaining motion information of the electronic device via a motion sensor, based on the first graphical object being selected, displaying a live-preview by performing, based on the motion information and a first marginal area having a first size, a first stabilization with respect to the obtained images, and based on the second graphical object being selected, displaying the live-preview by performing, based on the motion information and a second marginal area having a second size larger than the first size, a second stabilization with respect to the obtained images.

(10) In accordance with another aspect of the disclosure, a non-transitory computer readable recording medium is disclosed and stores instructions that, when executed by at least one processor of an electronic device, cause the electronic device to perform operations including entering a video capturing mode in which a camera is activated, displaying a live-preview corresponding to the video capturing mode using images obtained via the camera, while in the video capturing mode, displaying a user interface including a first graphical object indicative of a first degree of motion stabilization and a second graphical object indicative of a second degree of motion stabilization

greater than the first degree of motion stabilization, receiving an input via the user interface to select one of the first graphical object or the second graphical object, obtaining motion information of the electronic device via a motion sensor, based on the first graphical object being selected, displaying a live-preview by performing, based on the motion information and a first marginal area having a first size, a first stabilization with respect to the obtained images, and based on the second graphical object being selected, display the live-preview by performing, based on the motion information and a second marginal area having a second size larger than the first size, a second stabilization with respect to the obtained images.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The above and other aspects, features, and advantages of certain embodiments of the disclosure will be more apparent from the following description taken in conjunction with the accompanying drawings, in which:
- (2) FIG. 1 is a block diagram of an electronic device in a network environment, according to an embodiment;
- (3) FIG. 2 is a block diagram showing a camera module, according to an embodiment;
- (4) FIG. 3A is a block diagram showing the configuration of an electronic device, according to an embodiment;
- (5) FIG. 3B is a block diagram showing the configuration of a shaking correction unit, according to an embodiment;
- (6) FIG. 4 is a flowchart of an image stabilization operation performed by an electronic device, according to an embodiment;
- (7) FIG. 5A illustrates a stabilization scheme of an electronic device, according to an embodiment;
- (8) FIG. 5B illustrates a stabilization scheme of an electronic device, according to an embodiment;
- (9) FIG. 6A is a flowchart of an image stabilization scheme, according to an embodiment;
- (10) FIG. 6B illustrates a situation in which an image stabilization scheme is guided by an electronic device, according to an embodiment;
- (11) FIG. 6C is a flowchart describing an operation of determining an image stabilization scheme by an electronic device, according to an embodiment;
- (12) FIG. 7 is a flowchart describing an image stabilization operation by an electronic device, according to an embodiment;
- (13) FIG. 8 is a flowchart describing an operation of correcting rolling shutter distortion by an electronic device, according to an embodiment;
- (14) FIG. 9A illustrates an operation of processing motion information detected by an electronic device, according to an embodiment;
- (15) FIG. 9B illustrates an operation of processing motion information detected by an electronic device, according to an embodiment;
- (16) FIG. 10 is a flowchart describing an operation of determining a stabilization path by an electronic device, according to an embodiment;
- (17) FIG. 11A illustrates a parameter used to determine a stabilization path by an electronic device, according to an embodiment;
- (18) FIG. 11B illustrates a parameter used to determine a stabilization path by an electronic device, according to an embodiment;
- (19) FIG. 12 is a flowchart describing an operation of correcting at least one image by an electronic device, according to an embodiment;
- (20) FIG. 13A illustrates a situation in which notification information corresponding to a stabilization level is output by an electronic device, according to an embodiment;

- (21) FIG. 13B illustrates a situation in which notification information corresponding to a stabilization level is output by an electronic device, according to an embodiment;
- (22) FIG. 14 is a flowchart for performing an image stabilization operation by an electronic device, according to an embodiment; and
- (23) FIG. 15 illustrates a situation in which a stabilization scheme selection guide is provided by an electronic device, according to an embodiment.

DETAILED DESCRIPTION

- (24) Various embodiments of the present disclosure are described with reference to the accompanying drawings. However, various embodiments of the present disclosure are not limited to particular embodiments, and it should be understood that modifications, equivalents, and/or alternatives of the embodiments described herein can be variously made. With regard to description of drawings, similar components may be marked by similar reference numerals.
- (25) Various embodiments of the disclosure are to provide a method and an apparatus which correct shaking of a large motion as well as shaking of a small motion by an electronic device.
- (26) FIG. 1 is a block diagram illustrating an electronic device **101** in a network environment **100** according to various embodiments. Referring to FIG. 1, the electronic device **101** in the network environment **100** may communicate with an electronic device **102** via a first network **198** (e.g., a short-range wireless communication network), or an electronic device **104** or a server **108** via a second network **199** (e.g., a long-range wireless communication network). According to an embodiment, the electronic device **101** may communicate with the electronic device **104** via the server **108**. According to an embodiment, the electronic device **101** may include a processor **120**, memory **130**, an input device **150**, a sound output device **155**, a display device **160**, an audio module **170**, a sensor module **176**, an interface **177**, a haptic module **179**, a camera module **180**, a power management module **188**, a battery **189**, a communication module **190**, a subscriber identification module (SIM) **196**, or an antenna module **197**. In some embodiments, at least one (e.g., the display device **160** or the camera module **180**) of the components may be omitted from the electronic device **101**, or one or more other components may be added in the electronic device **101**. In some embodiments, some of the components may be implemented as single integrated circuitry. For example, the sensor module **176** (e.g., a fingerprint sensor, an iris sensor, or an illuminance sensor) may be implemented as embedded in the display device **160** (e.g., a display).
- (27) The processor **120** may execute, for example, software (e.g., a program **140**) to control at least one other component (e.g., a hardware or software component) of the electronic device **101** coupled with the processor **120**, and may perform various data processing or computation. According to one embodiment, as at least part of the data processing or computation, the processor **120** may load a command or data received from another component (e.g., the sensor module **176** or the communication module **190**) in volatile memory **132**, process the command or the data stored in the volatile memory **132**, and store resulting data in non-volatile memory **134**. According to an embodiment, the processor **120** may include a main processor **121** (e.g., a central processing unit (CPU) or an application processor (AP)), and an auxiliary processor **123** (e.g., a graphics processing unit (GPU), an image signal processor (ISP), a sensor hub processor, or a communication processor (CP)) that is operable independently from, or in conjunction with, the main processor **121**. Additionally or alternatively, the auxiliary processor **123** may be adapted to consume less power than the main processor **121**, or to be specific to a specified function. The auxiliary processor **123** may be implemented as separate from, or as part of the main processor **121**.
- (28) The auxiliary processor **123** may control at least some of functions or states related to at least one component (e.g., the display device **160**, the sensor module **176**, or the communication module **190**) among the components of the electronic device **101**, instead of the main processor **121** while the main processor **121** is in an inactive (e.g., sleep) state, or together with the main processor **121** while the main processor **121** is in an active state (e.g., executing an application). According to an embodiment, the auxiliary processor **123** (e.g., an ISP or a CP) may be implemented as part of

another component (e.g., the camera module **180** or the communication module **190**) functionally related to the auxiliary processor **123**.

(29) The memory **130** may store various data used by at least one component (e.g., the processor **120** or the sensor module **176**) of the electronic device **101**. The various data may include, for example, software (e.g., the program **140**) and input data or output data for a command related thereto. The memory **130** may include the volatile memory **132** or the non-volatile memory **134**.

(30) The program **140** may be stored in the memory **130** as software, and may include, for example, an operating system (OS) **142**, middleware **144**, or an application **146**.

(31) The input device **150** may receive a command or data to be used by another component (e.g., the processor **120**) of the electronic device **101**, from the outside (e.g., a user) of the electronic device **101**. The input device **150** may include, for example, a microphone, a mouse, a keyboard, or a digital pen (e.g., a stylus pen).

(32) The sound output device **155** may output sound signals to the outside of the electronic device **101**. The sound output device **155** may include, for example, a speaker or a receiver. The speaker may be used for general purposes, such as playing multimedia or playing a record, and the receiver may be used for an incoming calls. According to an embodiment, the receiver may be implemented as separate from, or as part of the speaker.

(33) The display device **160** may visually provide information to the outside (e.g., a user) of the electronic device **101**. The display device **160** may include, for example, a display, a hologram device, or a projector and control circuitry to control a corresponding one of the display, hologram device, and projector. According to an embodiment, the display device **160** may include touch circuitry adapted to detect a touch, or sensor circuitry (e.g., a pressure sensor) adapted to measure the intensity of force incurred by the touch.

(34) The audio module **170** may convert a sound into an electrical signal and vice versa. According to an embodiment, the audio module **170** may obtain the sound via the input device **150**, or output the sound via the sound output device **155** or a headphone of an external electronic device (e.g., an electronic device **102**) directly (e.g., wiredly) or wirelessly coupled with the electronic device **101**.

(35) The sensor module **176** may detect an operational state (e.g., power or temperature) of the electronic device **101** or an environmental state (e.g., a state of a user) external to the electronic device **101**, and then generate an electrical signal or data value corresponding to the detected state. According to an embodiment, the sensor module **176** may include, for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a proximity sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor.

(36) The interface **177** may support one or more specified protocols to be used for the electronic device **101** to be coupled with the external electronic device (e.g., the electronic device **102**) directly (e.g., wiredly) or wirelessly. According to an embodiment, the interface **177** may include, for example, a high definition multimedia interface (HDMI), a universal serial bus (USB) interface, a secure digital (SD) card interface, or an audio interface.

(37) A connecting terminal **178** may include a connector via which the electronic device **101** may be physically connected with the external electronic device (e.g., the electronic device **102**). According to an embodiment, the connecting terminal **178** may include, for example, an HDMI connector, a USB connector, an SD card connector, or an audio connector (e.g., a headphone connector).

(38) The haptic module **179** may convert an electrical signal into a mechanical stimulus (e.g., a vibration or a movement) or electrical stimulus which may be recognized by a user via his tactile sensation or kinesthetic sensation. According to an embodiment, the haptic module **179** may include, for example, a motor, a piezoelectric element, or an electric stimulator.

(39) The camera module **180** may capture a still image or moving images. According to an embodiment, the camera module **180** may include one or more lenses, image sensors, ISPs, or

flashes.

(40) The power management module **188** may manage power supplied to the electronic device **101**. According to one embodiment, the power management module **188** may be implemented as at least part of, for example, a power management integrated circuit (PMIC).

(41) The battery **189** may supply power to at least one component of the electronic device **101**. According to an embodiment, the battery **189** may include, for example, a primary cell which is not rechargeable, a secondary cell which is rechargeable, or a fuel cell.

(42) The communication module **190** may support establishing a direct (e.g., wired) communication channel or a wireless communication channel between the electronic device **101** and the external electronic device (e.g., the electronic device **102**, the electronic device **104**, or the server **108**) and performing communication via the established communication channel. The communication module **190** may include one or more CPs that are operable independently from the processor **120** (e.g., the AP) and supports a direct (e.g., wired) communication or a wireless communication. According to an embodiment, the communication module **190** may include a wireless communication module **192** (e.g., a cellular communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS) communication module) or a wired communication module **194** (e.g., a local area network (LAN) communication module or a power line communication (PLC) module). A corresponding one of these communication modules may communicate with the external electronic device via the first network **198** (e.g., a short-range communication network, such as Bluetooth™, wireless-fidelity (Wi-Fi) direct, or Infrared Data Association (IrDA)) or the second network **199** (e.g., a long-range communication network, such as a cellular network, the Internet, or a computer network (e.g., LAN or wide area network (WAN))). These various types of communication modules may be implemented as a single component (e.g., a single chip), or may be implemented as multi components (e.g., multi chips) separate from each other. The wireless communication module **192** may identify and authenticate the electronic device **101** in a communication network, such as the first network **198** or the second network **199**, using subscriber information (e.g., international mobile subscriber identity (IMSI)) stored in the subscriber identification module **196**.

(43) The antenna module **197** may transmit or receive a signal or power to or from the outside (e.g., the external electronic device) of the electronic device **101**. According to an embodiment, the antenna module **197** may include an antenna including a radiating element composed of a conductive material or a conductive pattern formed in or on a substrate (e.g., PCB). According to an embodiment, the antenna module **197** may include a plurality of antennas. In such a case, at least one antenna appropriate for a communication scheme used in the communication network, such as the first network **198** or the second network **199**, may be selected, for example, by the communication module **190** (e.g., the wireless communication module **192**) from the plurality of antennas. The signal or the power may then be transmitted or received between the communication module **190** and the external electronic device via the selected at least one antenna. According to an embodiment, another component (e.g., a radio frequency integrated circuit (RFIC)) other than the radiating element may be additionally formed as part of the antenna module **197**.

(44) At least some of the above-described components may be coupled mutually and communicate signals (e.g., commands or data) therebetween via an inter-peripheral communication scheme (e.g., a bus, general purpose input and output (GPIO), serial peripheral interface (SPI), or mobile industry processor interface (MIPI)).

(45) According to an embodiment, commands or data may be transmitted or received between the electronic device **101** and the external electronic device **104** via the server **108** coupled with the second network **199**. Each of the electronic devices **102** and **104** may be a device of a same type as, or a different type, from the electronic device **101**. According to an embodiment, all or some of the operations to be executed at the electronic device **101** may be executed at one or more of the external electronic devices **102**, **104**, or **108**. For example, if the electronic device **101** should

perform a function or a service automatically, or in response to a request from a user or another device, the electronic device **101**, instead of, or in addition to, executing the function or the service, may request the one or more external electronic devices to perform at least part of the function or the service. The one or more external electronic devices receiving the request may perform the at least part of the function or the service requested, or an additional function or an additional service related to the request, and transfer an outcome of the performing to the electronic device **101**. The electronic device **101** may provide the outcome, with or without further processing of the outcome, as at least part of a reply to the request. To that end, a cloud computing, distributed computing, or client-server computing technology may be used, for example.

(46) FIG. 2 is a block diagram **200** illustrating the camera module **180** according to various embodiments. Referring to FIG. 2, the camera module **180** may include a lens assembly **210**, a flash **220**, an image sensor **230**, an image stabilizer **240**, memory **250** (e.g., buffer memory), or an ISP **260**. The lens assembly **210** may collect light emitted or reflected from an object whose image is to be taken. The lens assembly **210** may include one or more lenses. According to an embodiment, the camera module **180** may include a plurality of lens assemblies **210**. In such a case, the camera module **180** may form, for example, a dual camera, a 360-degree camera, or a spherical camera. Some of the plurality of lens assemblies **210** may have the same lens attribute (e.g., view angle, focal length, auto-focusing, f number, or optical zoom), or at least one lens assembly may have one or more lens attributes different from those of another lens assembly. The lens assembly **210** may include, for example, a wide-angle lens or a telephoto lens.

(47) The flash **220** may emit light that is used to reinforce light reflected from an object. According to an embodiment, the flash **220** may include one or more light emitting diodes (LEDs) (e.g., a red-green-blue (RGB) LED, a white LED, an infrared (IR) LED, or an ultraviolet (UV) LED) or a xenon lamp. The image sensor **230** may obtain an image corresponding to an object by converting light emitted or reflected from the object and transmitted via the lens assembly **210** into an electrical signal. According to an embodiment, the image sensor **230** may include one selected from image sensors having different attributes, such as a RGB sensor, a black-and-white (BW) sensor, an IR sensor, or a UV sensor, a plurality of image sensors having the same attribute, or a plurality of image sensors having different attributes. Each image sensor included in the image sensor **230** may be implemented using, for example, a charged coupled device (CCD) sensor or a complementary metal oxide semiconductor (CMOS) sensor.

(48) The image stabilizer **240** may move the image sensor **230** or at least one lens included in the lens assembly **210** in a particular direction, or control an operational attribute (e.g., adjust the read-out timing) of the image sensor **230** in response to the movement of the camera module **180** or the electronic device **101** including the camera module **180**. This allows compensating for at least part of a negative effect (e.g., image blurring) by the movement on an image being captured. According to an embodiment, the image stabilizer **240** may sense such a movement by the camera module **180** or the electronic device **101** using a gyro sensor (not shown) or an acceleration sensor (not shown) disposed inside or outside the camera module **180**. According to an embodiment, the image stabilizer **240** may be implemented, for example, as an optical image stabilizer.

(49) The memory **250** may store, at least temporarily, at least part of an image obtained via the image sensor **230** for a subsequent image processing task. For example, if image capturing is delayed due to shutter lag or multiple images are quickly captured, a raw image obtained (e.g., a Bayer-patterned image, a high-resolution image) may be stored in the memory **250**, and its corresponding copy image (e.g., a low-resolution image) may be previewed via the display device **160**. Thereafter, if a specified condition is met (e.g., by a user's input or system command), at least part of the raw image stored in the memory **250** may be obtained and processed, for example, by the ISP **260**. According to an embodiment, the memory **250** may be configured as at least part of the memory **130** or as a separate memory that is operated independently from the memory **130**.

(50) The ISP **260** may perform one or more image processing with respect to an image obtained via

the image sensor **230** or an image stored in the memory **250**. The one or more image processing may include, for example, depth map generation, three-dimensional (3D) modeling, panorama generation, feature point extraction, image synthesizing, or image compensation (e.g., noise reduction, resolution adjustment, brightness adjustment, blurring, sharpening, or softening). Additionally or alternatively, the ISP **260** may perform control (e.g., exposure time control or read-out timing control) with respect to at least one (e.g., the image sensor **230**) of the components included in the camera module **180**. An image processed by the ISP **260** may be stored back in the memory **250** for further processing, or may be provided to an external component (e.g., the memory **130**, the display device **160**, the electronic device **102**, the electronic device **104**, or the server **108**) outside the camera module **180**. According to an embodiment, the ISP **260** may be configured as at least part of the processor **120**, or as a separate processor that is operated independently from the processor **120**. If the ISP **260** is configured as a separate processor from the processor **120**, at least one image processed by the ISP **260** may be displayed, by the processor **120**, via the display device **160** as it is or after being further processed.

(51) According to an embodiment, the electronic device **101** may include a plurality of camera modules **180** having different attributes or functions. In such a case, at least one of the plurality of camera modules **180** may form, for example, a wide-angle camera and at least another of the plurality of camera modules **180** may form a telephoto camera. Similarly, at least one of the plurality of camera modules **180** may form, for example, a front camera and at least another of the plurality of camera modules **180** may form a rear camera.

(52) FIG. 3A is a block diagram **300** showing the configuration of an electronic device. according to an embodiment.

(53) Referring to FIG. 3A, the electronic device includes a first camera **310**, a second camera **320**, a motion sensor **330**, a processor **340**, a display **350**, and a memory **360**.

(54) A first camera **310** and a second camera **320** may be a camera module **180**, and may capture (or obtain) an image (e.g., a photo or a video) viewed through a lens. For example, the first camera **310** and the second camera **320** may capture an image respectively or simultaneously. The first camera **310** and the second camera **320** may have different angles of view. For example, one of the first camera **310** or the second camera **320** may have an angle of view wider than that of the other camera. If the second camera **320** has an angle of view wider than that of the first camera **310**, the second camera **320** may capture an image of a wide angle of view, which includes an image captured by the first camera **310**. At least a part of the images captured by the first camera **310** and the second camera **320** may be output as a preview image through a display **350** (e.g., a display device **160**), or may be stored in a memory **130**.

(55) A motion sensor **330** (e.g., a sensor module **176**) may detect motion of the electronic device. The motion sensor **330** may detect motion of the electronic device while an image is being acquired through at least one of the first camera **310** or the second camera **320**. For example, the motion sensor **330** may be activated if at least one of the first camera **310** or the second camera **320** is operated. The motion sensor **330** may include a gyro sensor (or a gyroscope). Additionally or alternatively, the motion sensor **330** may be configured with various sensors capable of detecting motion of the electronic device, such as an acceleration sensor.

(56) A processor **340** may control the overall operation of the electronic device. The processor **340** may include an ISP **342** and a shaking correction unit **344**. Additionally or alternatively, the ISP **342** and the shaking correction unit **344** may be configured as a separate processor that is operated independently of the processor **340**.

(57) The processor **340** may determine a stabilization scheme for performing an image stabilization operation. As described later with reference to FIGS. 5A and 5B, the stabilization scheme may include a first stabilization scheme **334** for correcting shaking of an image based on a first margin region (e.g., a correction range), and a second stabilization scheme for correcting shaking of an image based on a second margin region larger than the first margin region. The margin region is a

region in which shaking can be corrected, and may be obtained by subtracting an output region from an input image.

(58) The processor **340** may determine one of the first stabilization scheme or the second stabilization scheme as a scheme for performing an image stabilization operation in response to detection of an image acquisition event (e.g., video capturing mode execution). The processor **340** may operate such that the scheme for performing the image stabilization operation is changed to another scheme (e.g., the second stabilization scheme) while the image stabilization operation is being performed using one of the first stabilization scheme or the second stabilization scheme. The stabilization scheme may be determined based on motion information of the electronic device (or image). Additionally or alternatively, the stabilization scheme may be selected based on user input as described with reference to FIGS. **14** and **15**. For example, the processor **340** may determine a stabilization scheme by providing a stabilization scheme selection guide and sensing an input for the stabilization scheme selection guide.

(59) The processor **340** may stabilize the at least one image acquired through the first camera **310** or the second camera **320**, based on the determined stabilization scheme, to correct shaking of the image. The processor **340** may perform the stabilization operation by controlling the ISP **342** and the shaking correction unit **344**.

(60) The ISP **342** may perform at least a part of a stabilization operation on a plurality of images acquired using the first camera **310** and the second camera **320**. For example, the ISP **342** may crop a region from a plurality of images (or a plurality of input images) acquired using the first camera **310** and the second camera **320**. A cropped image (e.g., an output region of an input image) may be output as a preview image through the display **350** or stored in the memory **360**. For example, the size of the output region may be designated in advance. The ISP **342** may secure a first margin region by cropping a designated output region in an image of a first size, acquired through the first camera **310**. The output region may be determined based on at least one of the specified number of pixels, a designated field of view, or a designated angle of view. In addition, the ISP **342** may secure a second margin region larger than the first margin region by cropping an output region having a designated size in an image of a second size, acquired through the second camera **320**. The margin region is a region, in which shaking can be corrected, and may be a region obtained by subtracting the output region from the input image.

(61) The shaking correction unit **344** may perform a stabilization operation on the plurality of images based on the first stabilization scheme. The first stabilization scheme may be a scheme for correcting shaking of a plurality of images of a first size acquired through the first camera **310**. The image of the first size may include a first margin region as described above. In an embodiment, the shaking correction unit **344** may adjust the position of an output region in an input image acquired through the first camera **310** based on motion information on the acquired image. The motion information may include first motion information on the motion of a subject or a background within the image, and second motion information on the motion of the electronic device. The first motion information may be acquired based on a result of comparing (e.g., comparing feature points) a plurality of images, and the second motion information may be acquired based on the motion sensor **330** of the electronic device. In addition, the first motion information and the second motion information may include translation component information and rotation component information. The translation component information may be information associated with translation coordinates, and the rotation component information may be information associated with an angle of rotation or inclination. For example, the shaking correction unit **344** may adjust the position of an output region of a current input image in the direction in which a subject has moved (or in the direction opposite the direction in which the electronic device has moved) in the output region of the current input image (e.g., an n.sub.th input image) acquired through the first camera **310** based on an output region of a previously input image (e.g., a n-1.sub.th input image) acquired through the first camera **310**. For example, the shaking correction unit **344** may perform shaking correction,

that is, the image stabilization operation, by adjusting the position of the output region in the first margin region of the input image having the first size.

(62) The shaking correction unit **344** may perform a stabilization operation on a plurality of images based on the second stabilization scheme. The second stabilization scheme may be a scheme for correcting shaking of a plurality of images of a second size acquired through the second camera **320**. The image of the second size may include a second margin region that is larger than the first margin region as described above.

(63) The shaking correction unit **344** may adjust the position of an output region in an input image acquired through the second camera **320** based on motion information on the acquired image. For example, the shaking correction unit **344** may adjust the position of an output region for a current input image in the direction in which a subject has moved (or in the direction opposite the direction in which the electronic device has moved) in the output region of the current input image (e.g., an n.sub.th input image) acquired through the second camera **320** based on an output region of a previously input image (e.g., a n-1.sub.th input image) acquired through the second camera **320**. The shaking correction unit **344** may perform shaking correction, that is, the image stabilization operation, by adjusting the position of the output region in the second margin region, having a size larger than that of the first margin region.

(64) The processor **340** may correct rolling shutter distortion of at least one image based on motion information of the electronic device (or the image) while correcting shaking of a plurality of images.

(65) FIG. **3B** is a block diagram **380** showing the configuration of a shaking correction unit, according to an embodiment.

(66) Referring to FIG. **3B**, the shaking correction unit **344** may include a frequency adjustment unit **382**, a stabilization path determination unit **384**, and a stabilization processing unit **386**.

(67) The frequency adjustment unit **382** may determine the frequency of detection of motion information. The detection frequency may include the frequency of detection by the motion sensor **330**. The frequency adjustment unit **382** may detect motion information based on a first specified frequency (e.g., approximately 100 hertz (Hz)) if the motion of the electronic device (or the image) is included in a designated frequency determination range (e.g., if the motion is small), and may increase the motion detection frequency to a second frequency (e.g., approximately 400 Hz to 500 Hz) if the motion is out of the designated frequency determination range (e.g., if the motion is large), thereby improving the performance of the image stabilization operation and achieving efficient battery consumption.

(68) The frequency adjustment unit **382** may determine the detection frequency based on the number of acquired images (e.g., the frame rate). For example, the frequency adjustment unit **382** may detect motion information based on a first specified frequency (e.g., approximately 100 Hz) if a frame rate is included in a designated frequency determination range (e.g., if the frame rate does not exceed 60 frames per second (fps)), and may increase the motion detection frequency to a second frequency (e.g., approximately 400 Hz to 500 Hz) if the motion is out of the designated frequency determination range (e.g., if exceeding 60 fps), thereby improving the performance of shaking and rolling shutter distortion correction. The above-described numerical values for the motion detection frequency are examples for better understanding, and the disclosure is not limited thereto. For example, the numerical value or the numerical range for the motion detection frequency may be changed by the designer and/or the performance of the electronic device.

(69) The stabilization path determination unit **384** may determine the stabilization path such that a shaking correction region (e.g., an output region of an input image) is not located outside of the original image. Determining a stabilization path may be also referred to as camera path planning. The motion of the electronic device or the image may be considered if the stabilization path determination unit **384** determines a stabilization path. As described above, the motion information may be determined based on a result of comparison of a plurality of images or sensor information

acquired through the motion sensor **330** of the electronic device. For example, as described below with reference to FIG. **10**, if the motion information is included in a first determination range, the stabilization path determining **384** may determine a stabilization path based on a first parameter. Additionally or alternatively, if the motion information of the electronic device is included in a second determination range, the stabilization path determination unit **384** may determine the stabilization path based on a second parameter.

(70) The stabilization processing unit **386** may dynamically control a stabilization operation, that is, the intensity of shaking correction. The stabilization processing unit **386** may reduce an image jitter phenomenon occurring due to the motion of the electronic device by adjusting the correction intensity based on the motion of the electronic device. For example, the stabilization processing unit **386** may prevent the occurrence of image jitter by lowering a shutter speed to a first speed if the motion of the electronic device (or the image) is included in a designated intensity adjustment range (for example, if the motion is small enough to avoid image jitter) and increasing the shutter speed to a second speed if the motion is out of the designated intensity adjustment range (e.g., if the motion is large enough to cause image jitter). The stabilization processing unit **386** may reduce the image jitter phenomenon occurring due to the motion of the electronic device by adjusting the correction intensity, based on at least one of motion information and ambient brightness information. For example, if the ambient brightness and the motion are included in the designated intensity adjustment range (e.g., if the motion of the electronic device located in a room is large), the stabilization processing unit **386** may lower the image stabilization performance to a first level and increase the image jitter improvement performance to a second level. Here, lowering the correction performance may mean lowering the correction intensity.

(71) The shaking correction may be based on the position (or trajectory) of a camera before a stabilization path determination and the position (or trajectory) of the camera after the stabilization path determination. For example, the shaking correction amount may be the difference between the position (or trajectory) of the camera before the stabilization path determination and the position (or trajectory) of the camera after the stabilization path determination. For example, the stabilization processing unit **360** may lower the correction performance to the first level to correct only a part of the correction amount. In addition, if the ambient brightness and the motion are out of the designated intensity adjustment range (e.g., if the motion of the electronic device located in a room is small), the stabilization processing unit **384** may also increase the shaking correction performance to the second level and reduce the image jitter improvement performance to the first level. For example, the stabilization processing unit **360** may increase the correction performance to the second level to correct the entire correction amount.

(72) According to an embodiment, the electronic device may include a camera, a motion sensor, a memory, and at least one processor. The at least one processor may be configured to acquire motion information of the electronic device from the motion sensor according to an image acquisition mode (i.e., upon executing an image acquisition mode), determine an image stabilization scheme, based on at least a part of the motion information, and perform a stabilization operation on at least one image acquired through the camera, based on the determined image stabilization scheme. For example, the image stabilization scheme may include a first stabilization scheme for correcting shaking of the at least one image based on a first margin region and a second stabilization scheme for correcting shaking of the at least one image based on a second margin region larger than the first margin region.

(73) The camera may include a first camera having a first angle of view and a second camera having a second angle of view wider than the first angle of view. The processor may be configured to operate the first camera in response to the determination of the first stabilization scheme and operate the second camera in response to the determination of the second stabilization scheme.

(74) The processor may be configured to determine an image acquisition speed for acquiring the plurality of images and determine a frequency of detection by the motion sensor based on at least

one of the image acquisition speed and the motion size.

(75) The processor may be configured to process the acquired motion information if it is impossible to change to the determined frequency of detection.

(76) The processor may be configured to determine a parameter for determining a stabilization path for correcting the at least one image based on the motion information of the electronic device.

(77) The processor may be configured to determine the ambient brightness of the electronic device and determine the intensity of a stabilization operation based on at least one of the ambient brightness or the size of the motion information of the electronic device.

(78) The electronic device may further include a display. The processor may be configured to output notification information corresponding to the determined intensity of the stabilization operation through the display.

(79) The processor may be configured to detect the motion of the electronic device in the state in which one of the first image stabilization scheme and the second image stabilization scheme is selected and change the selected image stabilization scheme to another image stabilization scheme if the detected motion satisfies a stabilization scheme change condition.

(80) The electronic device may further include a display. The processor may be configured to output information notifying the changed image stabilization scheme through the display.

(81) According to an embodiment, the electronic device may include a camera, a display, a memory, and at least one processor. The at least one processor may be configured to output a user interface designated to select one of a first stabilization scheme or a second stabilization scheme according to the execution at an image acquisition mode, select one of the first stabilization scheme or the second stabilization scheme based on input, and perform a stabilization operation on at least one image acquired through the camera based on the selected image stabilization scheme.

(82) The processor may be configured to acquire an image of a first size including a first correction region in response to the selection of the first stabilization scheme, and acquire an image of a second size, including a second correction region that is larger than the first correction region, in response to the selection of the second stabilization scheme.

(83) FIG. 4 is a flowchart **400** for performing an image stabilization operation by an electronic device, according to an embodiment. FIG. 5A is a view **500** illustrating a stabilization scheme of an electronic device according to an embodiment. FIG. 5B is a view **510** illustrating a stabilization scheme of an electronic device, according to an embodiment. The steps in FIG. 4 may be performed sequentially, but are not necessarily performed sequentially. For example, the order of each step may be changed, or at least two steps may be performed in parallel.

(84) Referring to FIG. 4, the electronic device (e.g., the processor **340**) performs an image acquisition mode in step **410**. The image acquisition mode may include a mode of acquiring at least one image through at least one of the first camera **310** (or the first image acquisition device) or the second camera **320** (or the second image acquisition device). The first camera **310** may acquire an image having a first angle of view, and the second camera **320** may acquire an image having a second angle of view larger than the first angle of view.

(85) The electronic device determines an image stabilization scheme, in step **420**, based on the motion information of the electronic device. The processor **340** may determine one of the first stabilization scheme and the second stabilization scheme as a scheme for performing an image stabilization operation. The first stabilization scheme may be a scheme, as illustrated in FIG. 5A, for securing a first margin region (e.g., **d1** and **d2**) by cropping a designated output region **504** from a plurality of first-size images **502** acquired through the first camera **310**. For example, the output region may be determined based on at least one of the specified number of pixels, a designated field of view, or a designated angle of view, as described above. In addition, the first stabilization scheme may correct **508** shaking of an image by adjusting **506** the position of the output region in the first margin region in the direction in which a subject has moved (or the direction opposite the direction in which the electronic device has moved). The second stabilization scheme may be a

scheme, as illustrated in FIG. 5B, for securing a second margin region (e.g., d3 and d4) by cropping the designated output region 514 from a plurality of second-size images 512 acquired through the second camera 320. The image of the second size may be a size larger than the image of the first size. The second stabilization scheme may correct shaking of the image by adjusting the position of the output region in the second margin region having a larger size than the first margin region in a direction in which a subject has moved (or the direction opposite the direction in which the electronic device has moved). The processor 340 may determine the image stabilization scheme based on at least one of motion information of the electronic device or user input.

(86) The electronic device acquires at least one image in step 430 based on the determined stabilization scheme. The processor may operate one of the first camera or the second camera based on the determined stabilization scheme.

(87) The electronic device performs stabilization on at least one acquired image in step 440. The processor 340 may correct shaking of the image using video digital image stabilization technology.

(88) FIG. 6A is a flowchart 600 of an image stabilization scheme determined by an electronic device, according to an embodiment. FIG. 6B is a view 370 illustrating the situation in which an image stabilization scheme is guided in an electronic device, according to an embodiment. The steps of FIGS. 6A to 6C, described below, may represent various embodiments of steps 420 and 430. The steps may be performed sequentially, but are not necessarily performed sequentially. For example, the order of each step may be changed, or at least two steps may be performed in parallel.

(89) Referring to FIG. 6A, the electronic device (e.g., the processor 340) acquires at least one image using the first camera 310 (or the first image acquisition device) in step 610. As described above, the first camera 310 may acquire an image of a first size having a first angle of view. The first angle of view may be within an approximate range of 50° and 80°. If a small motion below the reference range is sensed, the processor 340 may secure a first margin region by cropping the designated output region in the image of the first size. In addition, the processor 340 may perform the shaking correction, that is, the image stabilization operation by adjusting the position of an output region in the first margin region of an input image.

(90) The electronic device acquires motion information of the electronic device in step 620. The motion information may include translation component information and rotation component information. The translation component information may be information associated with the translation coordinates, and the rotation component information may be information associated with an angle of rotation or inclination. The processor 340 may acquire motion information through the motion sensor 330. Additionally or alternatively, the processor 340 may acquire motion information based on a result of a comparison of images (e.g., feature point comparison) acquired through the first camera 310.

(91) The electronic device determines whether the motion information satisfies an image stabilization condition in step 630. The image stabilization condition may be the reference value for determining whether the shaking of an output image occurs due to the motion of the electronic device. For example, the processor 340 may determine that the image stabilization condition is satisfied if the motion of the electronic device is greater than or equal to the reference motion. If the motion of the electronic device is less than the reference motion, the processor 340 may determine that the image stabilization condition is not satisfied.

(92) If it is determined that the image stabilization condition is satisfied, the electronic device acquires at least one image by using the second camera 320 (or the second image acquisition device) in step 640. As described above, the second camera 320 may acquire an image of a second size having a second angle of view that is wider than the first angle of view. The second angle of view may be within the approximate range of 70° and 130°. If a large motion beyond the reference range is sensed, the processor 340 may secure a second margin region by cropping a designated output region in the image of the second size. In addition, the processor 340 may perform the shaking correction, that is, the image stabilization operation by adjusting the position of the output

region in the second margin region of an input image. If it is determined that the image stabilization condition is satisfied, the processor **340** may also output guide information for changing the image stabilization scheme.

(93) As illustrated in FIG. **6B**, the processor **340** may output, through a display **672**, guide information **674** reporting that the image stabilization scheme according to the motion of the electronic device is executed. As illustrated in the drawing, the guide information **674** may include a menu for selecting or canceling a change to the image stabilization scheme. The processor **340** may change an image stabilization scheme corresponding to the motion of the electronic device or may control such that the previous image stabilization scheme is maintained, based on an input of the guide information **674**.

(94) If it is determined that the image stabilization condition is not satisfied, the electronic device maintains the operation of the first image acquisition device in steps **650**.

(95) In the above-described embodiment, a configuration of changing the camera for acquiring an image from the first camera **310** to the second camera **320**, based on the motion information, has been described. In contrast to the above-described embodiment, while an image is being acquired through the second camera **320**, an image may be acquired through the first camera **310** based on the motion information.

(96) FIG. **6C** is a flowchart **680** describing another operation of determining an image stabilization scheme by an electronic device, according to an embodiment. The steps of FIG. **6C** described below may represent various embodiments of step **640** of FIG. **6A**. In the following embodiments, the steps may be performed sequentially, but are not necessarily performed sequentially. For example, the order of each step may be changed, or at least two steps may be performed in parallel.

(97) Referring to FIG. **6C**, the electronic device acquires at least one image using the second camera **320** (or the second image acquisition device) in step **681**. As described above, the second camera **320** may acquire an image of a second size having a second angle of view.

(98) The electronic device acquires motion information of the electronic device in step **683**. As described above, the motion information may include translation component information and rotation component information. For example, the processor **340** may acquire motion information through the motion sensor **330**. Additionally or alternatively, the processor **340** may acquire motion information based on a result of a comparison of images (e.g., feature point comparison) acquired through the second camera **320**.

(99) The electronic device determines whether the motion information satisfies an image stabilization scheme change condition in step **685**. The image stabilization scheme change condition may be a reference value for determining whether an amount of shaking less than the reference motion occurs due to the motion of the electronic device. For example, if the motion of the electronic device is less than the reference motion, the processor **340** may determine that the image stabilization scheme change condition is satisfied. In addition, if the motion of the electronic device is greater than or equal to the reference motion, the processor **340** may determine that the image stabilization scheme change condition is not satisfied.

(100) If the electronic device determines that the image stabilization scheme change condition is satisfied (for example, if the motion of the electronic device is decreased less than the reference motion), at least one image is acquired using the first camera **310** (or the first image acquisition device) in step **687**. As described above, the first camera **310** may acquire an image of a first size having a first angle of view that is narrower than the second angle of view.

(101) If the electronic device determines that the image stabilization condition is not satisfied (for example, if the motion of the electronic device is maintained above the reference motion), the operation of the second image acquisition device is maintained in step **689**.

(102) FIG. **7** is a flowchart **700** for describing an image stabilization operation in an electronic device, according to an embodiment. The steps of FIG. **7** described below may represent various embodiments of step **640** of FIG. **6A**. In the following embodiments, the steps may be performed

sequentially, but are not necessarily performed sequentially. For example, the order of each step may be changed, or at least two steps may be performed in parallel.

(103) Referring to FIG. 7, according to various embodiments, the electronic device (e.g., the processor **340**) acquires motion information on the acquired image (or motion information of the electronic device) in step **710**. For example, the processor **340** may periodically acquire motion information while the second-size image is acquired through the second camera **320** (or the second image acquisition device).

(104) The electronic device determines a stabilization path for the acquired image of a second size in step **720**, based on the acquired motion information. Determining the stabilization path may be referred to as camera path planning. The processor **340** may determine a stabilization path which positions an output region of an image (e.g., an input image) in a direction corresponding to the motion of the image (e.g., the subject), or opposite the motion of the electronic device, based on the motion information. For example, if the electronic device **100** is shaken to the left and thus subjects included in input images are moved to the right, the processor **340** may determine the stabilization path that positions the output region of the image in the left direction.

(105) The electronic device corrects at least one image acquired through the second camera **320** (or the second image acquisition device) in step **730**, based on the determined stabilization path. For example, the processor **340** may adjust the position of an output region within a margin region of an input image so that the output region is not located outside of the input image. The processor **340** may correct rolling shutter distortion of at least one image, based on motion information of the electronic device (or the image) while correcting shaking of a plurality of images.

(106) The electronic device outputs the corrected image through the display **350** (or the display device **160**) in step **740**. The processor **340** may store the corrected image inside the electronic device (e.g., the memory **360**) or outside the electronic device.

(107) FIG. 8 is a flowchart **800** for describing an operation of correcting rolling shutter distortion by an electronic device, according to an embodiment. FIGS. 9A and 9B are a view **900** illustrating an operation of processing motion information detected by an electronic device, according to various embodiments. The steps of FIG. 8 described below may represent various embodiments of step **730**. In the following embodiments, the steps may be performed sequentially, but are not necessarily performed sequentially. For example, the order of each step may be changed, or at least two steps may be performed in parallel.

(108) Referring to FIG. 8, the electronic device (e.g., the processor **340**) detects a motion detection frequency change event in step **810**. The motion detection frequency may be associated with the performance of shaking correction and rolling shutter distortion correction. For example, the higher the motion detection frequency, the better the correction performance of the image. The processor **340** may sense, as a motion detection frequency change event, a situation in which motion of the electronic device exceeding the reference motion or a number of images (e.g., frame rate) exceeding the reference frame rate is sensed.

(109) The electronic device determines whether the motion detection frequency is changeable, in response to the motion detection frequency change event, in step **820**. The processor **340** may determine whether the detection frequency is changed based on state information of the electronic device. For example, state information of the electronic device may include at least one of a heating state of the electronic device, a remaining battery state of the electronic device, and a process operational capability state of the electronic device.

(110) If a motion detection frequency is changeable, the electronic device changes the motion detection frequency and acquire motion information in step **830**, based on the changed detection frequency. The processor **340** may change the detection frequency of the motion information from a first frequency (e.g., 100 Hz) to a second frequency (e.g. 500 Hz), which is higher than the first frequency, in response to the detection of a detection frequency event. As described above, the processor **340** may increase the amount of motion information used for shaking correction of an

image by changing the detection frequency, thereby improving image correction performance. In addition, the electronic device may correct the image in step **840** based on the acquired motion information.

(111) If the motion detection frequency is not changeable, the electronic device processes the detected motion information in step **850**. The processing of the motion information may include increasing the amount of motion information used for shaking correction on the image. The processor **340** may generate additional motion information by interpolating the detected motion information.

(112) The graph of FIG. **9A** shows the analysis of motion information in a frequency domain according to a first detection frequency (e.g., 200 Hz), and the graph of FIG. **9B** shows the analysis of motion information in a frequency domain according to a second detection frequency (e.g., 500 Hz). In addition, the Y axis of the graph represents a motion vector, the X axis thereof represents the number of frames in an image, the dotted lines **902** and **912** represent first motion information (e.g., motion with respect to a subject or background) obtained through the input image, and the solid lines **904** and **914** represent second motion information obtained through a motion sensor of the electronic device. The difference between the first motion information **902** and the second motion information **904** occurs in a part having many changes in the graph of FIG. **9A**. Almost no difference between the first motion information **912** and the second motion information **914** occurs in a part having many changes in the graph of FIG. **9B**. For example, the processor **340** may process the motion information detected based on the first frequency so as to make the motion information the same as or similar to the motion information detected based on the second frequency. In addition, the electronic device may correct the image in step **860** based on the processed motion information.

(113) FIG. **10** is a flowchart **1000** describing an operation of determining a stabilization path by an electronic device, according to an embodiment. FIG. **11A** describes a parameter used to determine a stabilization path in an electronic device, according to an embodiment. FIG. **11B** describes a parameter used to determine a stabilization path in an electronic device, according to an embodiment. The steps of FIG. **10** described below may represent various embodiments of step **720**. In the following embodiments, the steps may be performed sequentially, but are not necessarily performed sequentially. For example, the order of step operation may be changed, or at least two steps may be performed in parallel.

(114) Referring to FIG. **10**, the electronic device (e.g., the processor **340**) changes a stabilization path determination parameter in step **1010** based on the motion information of the image (or the electronic device).

(115) The processor **340** may determine a stabilization path by using different parameters for the case in which motion escapes from a specified level (e.g., if there is a lot of motion at a specified motion vector) and the case in which the motion does not escape therefrom.

(116) The graph **1110** and the graph **1120** of FIG. **11A** show parameters (e.g., first parameters) corresponding to the case in which motion does not exceed a specified level (e.g., the case in which motion is small, such as in the state in which an electronic device is held in a user's hand). In addition, the Y axis of each graph represents a motion vector, the X axis thereof represents the number of image frames, and the two-dot chain line (c) and the one-dot chain line (d) represent the maximum value of a correction range and the minimum value of the correction range, respectively. Further, the solid line (a) represents the position (or trajectory) of a camera after the stabilization path determination, and the dotted line (b) represents the position (or trajectory) of the camera before the stabilization path determination.

(117) As noted from the graph **1110** of FIG. **11A**, if the stabilization path is determined using the first parameter in a small-motion state, the propensity for the camera position, after the stabilization path determination, to show a straight line increases. This means that the amount of motion correction is determined by the difference between the solid line (a) and the dotted line (b), and

thus if the stabilization path is determined using the first parameter in the small-motion state, the shaking of the image has been corrected. On the other hand, as noted from the graph **1120** of FIG. **11A**, if the stabilization path is determined using the second parameter in a small-motion state, there is a trend that the camera position after the stabilization path determination becomes similar to the position of the camera before the stabilization path determination. This means that there is almost no difference between the solid line (a) and the dotted line (b), and thus if the stabilization path is determined using the second parameter in the small-motion state, the performance of image-shaking correction is deteriorated. Specifically, if comparing the relationship between the small-motion state, the large-motion state and the first parameter, in the small-motion state, as shown in the graph **1130** of FIG. **11A**, if the stabilization path is determined by the second parameter, the camera position is parallel, as represented by the dotted line (b), to the X axis regardless of changing the camera position before the stabilization path determination, which means that the performance of the image-shaking correction is improved. On the other hand, in the large-motion state, if the stabilization path is determined by the first parameter, the camera position is not parallel, as represented by the solid line (a), to the X axis along the changing camera position before the stabilization path determination, and thus the performance of the image-shaking correction is deteriorated.

(118) The graph **1160** and the graph **1170** of FIG. **11B** show parameters (e.g., second parameters) corresponding to the case in which motion exceeds a specified level (e.g., the case of a large-motion state). In addition, the Y axis of each graph represents a motion vector, the X axis thereof represents the number of image frames, and the solid line (a) and the one-dot chain line (d) represent the maximum value of a correction range and the minimum value of the correction range, respectively. Further, the dotted line (b) represents the position (or trajectory) of a camera before the stabilization path determination, and the two-dot chain line (c) represents the position (or trajectory) of the camera after the stabilization path determination. As noted from the graph **1160** of FIG. **11B**, if the stabilization path is determined using the second parameter in a large-motion state, the camera position after the stabilization path determination has a rugged form (e.g., a form in which the difference between the camera position before the stabilization path determination and the camera position after the stabilization path determination is small). On the other hand, as noted from the graph **1170** of FIG. **11B**, if the stabilization path is determined using the second parameter in a large-motion state, the camera position after the stabilization path determination has a curved form (e.g., the difference between the camera position before the stabilization path determination and the camera position after the stabilization path determination is relatively large). Specifically, comparing the relationship, in a large-motion state, between the small-motion state, the large-motion state and the second parameter, as shown in the graph **1180** of FIG. **11B**, if the stabilization path is determined by the first parameter (e.g., dotted line (b)), the performance of the image-shaking correction is deteriorated. On the other hand, in the large-motion state, if the stabilization path is determined by the second parameter (e.g., solid line (a)), the performance of the image-shaking correction is improved.

(119) The electronic device (e.g., the processor **340**) determines a stabilization path for a plurality of images based on the changed parameter in step **1020**. The image stabilization path serves to calculate the shortest distance to a camera from an input image, and the processor **340** may adjust the amount of the input image that is used to determine the stabilization path, based on the motion of the image. For example, the processor **340** may determine a stabilization path by using a greater number of input images in the case in which motion escapes from a specified level (e.g., if the motion is large at a specified motion vector) than the case in which the motion does not escape therefrom (e.g., if the motion is small at the specified motion vector).

(120) FIG. **12** is a flowchart **1200** describing an operation of correcting at least one image by an electronic device, according to an embodiment. FIG. **13A** is a view **1300** illustrating the situation in which the electronic device outputs notification information corresponding to a stabilization level,

according to an embodiment. FIG. 13B is a view **1300** illustrating the situation in which the electronic device outputs notification information corresponding to a stabilization level, according to an embodiment. The operations of FIG. 12 described below may represent various embodiments of step **730**. In the following embodiments, the steps may be performed sequentially, but are not necessarily performed sequentially. For example, the order of each step may be changed, or at least two steps may be performed in parallel.

(121) Referring to FIG. 12, the electronic device (e.g., the processor **340**) acquires additional information while correcting at least one image in step **1210**. The additional information may include ambient brightness information.

(122) The electronic device determines a stabilization level (or correction intensity), in step **1220**, based on at least one of additional information or motion information of an image. For example, the processor **340** may adjust the correction intensity so as to reduce an image jitter phenomenon that may occur during image stabilization. If the ambient brightness and the motion satisfy the specified first level (e.g., if the motion of the electronic device located in a room is large), the processor **340** may lower the shaking correction performance to the first level and increase the image jitter improvement performance to the second level. In addition, if the ambient brightness and the motion satisfy the specified second level (e.g., if the motion of the electronic device located in a room is small), the processor **340** may also increase the shaking correction performance to the second level and lower the image jitter improvement performance to the first level. The processor **340** may prevent the occurrence of image jitter by lowering a shutter speed to a first speed if motion of the electronic device (or the image) satisfies the specified level (e.g., if the motion is small enough to avoid image jitter) and increasing the shutter speed to a second speed if the motion is out of a range that satisfies the specified level (e.g., the motion is large enough to cause image jitter).

(123) The electronic device corrects an image, in step **1230**, based on the determined stabilization level. The processor **340** may output notification information indicating the determined stabilization level through a display device. For example, as shown in FIG. 13A, if the stabilization operation is performed on an input image **1310** having a small motion, the processor **340** may output notification information **1312** corresponding to a small motion (or a low stabilization level). In addition, as shown in FIG. 13B, if the stabilization operation is performed on an input image **1320** having a large motion, the processor **340** may output notification information **1322** corresponding to a large motion (or a high stabilization level).

(124) FIG. 14 is a flowchart **1400** of an image stabilization operation performed by an electronic device, according to an embodiment. FIG. 15 is a diagram **1500** for describing a situation of providing a stabilization scheme selection guide in an electronic device, according to an embodiment. In the following embodiments, the steps may be performed sequentially, but are not necessarily performed sequentially. For example, the order of each step may be changed, or at least two steps may be performed in parallel.

(125) Referring to FIG. 14, the electronic device (e.g., the processor **340**) executes an image acquisition mode in step **1410**. As described above, the image acquisition mode may include a mode which acquires at least one image through at least one of the first camera **310** (or the first image acquisition device) or the second camera **320** (or the second image acquisition device).

(126) The electronic device outputs a stabilization scheme selection guide in step **1420**. The stabilization scheme selection guide may include a user interface designated to select one of the first stabilization scheme or the second stabilization scheme. The first stabilization scheme may be a scheme, as illustrated in FIG. 5A, for securing a first margin region (e.g., d1 and d2) from a plurality of first-size images **502** acquired through the first camera **310**. In addition, the second stabilization scheme may be a scheme, as illustrated in FIG. 5B, for securing a second margin region (e.g., d3 and d4) from a plurality of second-size images **512** acquired through the second camera **320**. For example, as illustrated in FIG. 15, the processor **340** may visually output **1520** a stabilization scheme selection guide in the state **1510** in which the image acquisition mode is

executed. Additionally or alternatively, the stabilization scheme selection guide may be output in various ways, such as acoustically, tactually, or a combination thereof.

(127) The electronic device determines a stabilization scheme, in step **1430**, based on input. The processor **340** may determine one of the first stabilization scheme and the second stabilization scheme, based on input sensed through the output stabilization scheme selection guide.

(128) The electronic device acquires at least one image, in step **1440**, based on the determined stabilization scheme. The processor **340** may operate a camera corresponding to the determined stabilization scheme. For example, the processor **340** may operate the first camera **310** in response to the selection of the first stabilization scheme. In addition, the processor **340** may operate the second camera **320** in response to the selection of the second stabilization scheme.

(129) The electronic device performs stabilization on at least one acquired image in step **1450**. The processor **340** may correct shaking of an image using video digital image stabilization technology.

(130) According to an embodiment, a method for operating an electronic device may include acquiring motion information of the electronic device according to an image acquisition mode; determining an image stabilization scheme, based on at least a part of the motion information; and performing a stabilization operation on at least one image acquired through the camera, based on the determined image stabilization scheme. The image stabilization scheme may include a first stabilization scheme for correcting shaking of the at least one image based on a first margin region and a second stabilization scheme for correcting shaking of the at least one image based on a second margin region larger than the first margin region.

(131) Performing the stabilization operation may include activating a first camera having a first angle of view, in response to a determination of the first stabilization scheme; and activating a second camera having a second angle of view wider than the first angle of view, in response to a determination of the second stabilization scheme.

(132) Performing the stabilization operation may include determining an image acquisition speed at which the plurality of images are acquired; and determining a detection frequency of the motion information of the electronic device based on at least one of the image acquisition speed and the motion size.

(133) Performing the stabilization operation may include processing the obtained motion information if it is impossible to change to the determined detection frequency.

(134) Performing the stabilization operation may include determining a parameter of a stabilization path for correcting the at least one image based on motion information of the electronic device.

(135) Performing the stabilization operation may include determining an ambient brightness of the electronic device; and determining an intensity of a stabilization operation based on at least one of the ambient brightness or the size of the motion of the electronic device.

(136) Determining the intensity of the stabilization operation may include outputting notification information corresponding to the determined intensity.

(137) Performing the stabilization operation may include detecting a motion of the electronic device in a state in which one of the first image stabilization scheme and the second image stabilization scheme is selected; and changing the selected image stabilization scheme to another image stabilization scheme if the detected motion satisfies a stabilization scheme change condition.

(138) Changing the image stabilization scheme to another image stabilization scheme may include outputting information providing notification of the changed image stabilization scheme.

(139) According to various embodiments, the electronic device is capable of improving shaking correction performance of a large motion as well as a small motion by selectively using a first image stabilization scheme or a second image stabilization scheme, based on at least a part of motion information. In addition, the electronic device may enable a user to select a desired scheme among the first image stabilization scheme or the second image stabilization scheme, and to correct an image by outputting a user interface designated to select the first image stabilization scheme or the second image stabilization scheme according to executing an image acquisition mode.

(140) The electronic device according to various embodiments may be one of various types of electronic devices. The electronic devices may include, for example, a portable communication device (e.g., a smartphone), a computer device, a portable multimedia device, a portable medical device, a camera, a wearable device, or a home appliance. According to an embodiment of the disclosure, the electronic devices are not limited to those described above.

(141) It should be appreciated that various embodiments of the present disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular embodiments and include various changes, equivalents, or replacements for a corresponding embodiment. With regard to the description of the drawings, similar reference numerals may be used to refer to similar or related elements. It is to be understood that a singular form of a noun corresponding to an item may include one or more of the things, unless the relevant context clearly indicates otherwise.

(142) As used herein, each of such phrases as “A or B,” “at least one of A and B,” “at least one of A or B,” “A, B, or C,” “at least one of A, B, and C,” and “at least one of A, B, or C,” may include any one of, or all possible combinations of the items enumerated together in a corresponding one of the phrases. As used herein, such terms as “1st” and “2nd,” or “first” and “second” may be used to simply distinguish a corresponding component from another, and does not limit the components in other aspect (e.g., importance or order). It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively”, as “coupled with,” “coupled to,” “connected with,” or “connected to” another element (e.g., a second element), it means that the element may be coupled with the other element directly (e.g., wiredly), wirelessly, or via a third element.

(143) As used herein, the term “module” may include a unit implemented in hardware, software, or firmware, and may interchangeably be used with other terms, for example, “logic,” “logic block,” “part,” or “circuitry”. A module may be a single integral component, or a minimum unit or part thereof, adapted to perform one or more functions. For example, according to an embodiment, the module may be implemented in a form of an application-specific integrated circuit (ASIC).

(144) Various embodiments as set forth herein may be implemented as software (e.g., the program **140**) including one or more instructions that are stored in a storage medium (e.g., internal memory **136** or external memory **138**) that is readable by a machine (e.g., the electronic device **101**). For example, a processor (e.g., the processor **120**) of the machine (e.g., the electronic device **101**) may invoke at least one of the one or more instructions stored in the storage medium, and execute it, with or without using one or more other components under the control of the processor. This allows the machine to be operated to perform at least one function according to the at least one instruction invoked. The one or more instructions may include a code generated by a compiler or a code executable by an interpreter. The machine-readable storage medium may be provided in the form of a non-transitory storage medium. Wherein, the term “non-transitory” simply means that the storage medium is a tangible device, and does not include a signal (e.g., an electromagnetic wave), but this term does not differentiate between where data is semi-permanently stored in the storage medium and where the data is temporarily stored in the storage medium.

(145) A method according to various embodiments of the disclosure may be included and provided in a computer program product. The computer program product may be traded as a product between a seller and a buyer. The computer program product may be distributed in the form of a machine-readable storage medium (e.g., compact disc read only memory (CD-ROM)), or be distributed (e.g., downloaded or uploaded) online via an application store (e.g., PlayStore™), or between two user devices (e.g., smart phones) directly. If distributed online, at least part of the computer program product may be temporarily generated or at least temporarily stored in the machine-readable storage medium, such as memory of the manufacturer's server, a server of the application store, or a relay server.

(146) According to various embodiments, each component (e.g., a module or a program) of the

above-described components may include a single entity or multiple entities. According to various embodiments, one or more of the above-described components may be omitted, or one or more other components may be added. Alternatively or additionally, a plurality of components (e.g., modules or programs) may be integrated into a single component. In such a case, according to various embodiments, the integrated component may still perform one or more functions of each of the plurality of components in the same or similar manner as they are performed by a corresponding one of the plurality of components before the integration. According to various embodiments, operations performed by the module, the program, or another component may be carried out sequentially, in parallel, repeatedly, or heuristically, or one or more of the operations may be executed in a different order or omitted, or one or more other operations may be added.

Claims

1. An electronic device comprising: a camera; a motion sensor configured to obtain motion information of the electronic device; a display; a memory storing at least one instruction; and a processor executing the at least one instruction stored in the memory, wherein the processor causes the electronic device to: enter a video capturing mode in which the camera is activated; display a live-preview corresponding to the video capturing mode using images obtained via the camera; while in the video capturing mode, display a user interface including a first graphical object indicative of a first degree of motion stabilization and a second graphical object indicative of a second degree of motion stabilization greater than the first degree of motion stabilization; receive an input via the user interface to select one of the first graphical object or the second graphical object; based on the first graphical object being selected, display a live-preview by performing, based on the motion information and a first marginal area having a first size, a first stabilization with respect to the obtained images; and based on the second graphical object being selected, display the live-preview by performing, based on the motion information and a second marginal area having a second size larger than the first size, a second stabilization with respect to the obtained images.
2. The electronic device of claim 1, wherein the processor is further configured to: determine an image acquisition speed at which a plurality of images is acquired; and determine a frequency of detection by the motion sensor based on at least one of the image acquisition speed and a motion size of the electronic device.
3. The electronic device of claim 2, wherein the processor is further configured to process the motion information if a change to the determined frequency of detection is not possible.
4. The electronic device of claim 1, wherein the processor is further configured to determine a parameter for stabilization path determination for correction of at least one of the images, based on the motion information of the electronic device.
5. The electronic device of claim 1, wherein the processor is further configured to: determine an ambient brightness of the electronic device; and determine an intensity of a stabilization operation, based on at least one of the ambient brightness and a motion size of the electronic device.
6. The electronic device of claim 5, wherein the processor is further configured to output notification information corresponding to the determined intensity of the stabilization operation through the display.
7. The electronic device of claim 1, wherein the processor is further configured to: detect motion of the electronic device in a state in which one of the first stabilization or the second stabilization is selected; and change the selected image stabilization to another image stabilization if the detected motion satisfies a stabilization scheme change condition.
8. The electronic device of claim 7, wherein the processor is further configured to output, through the display, information providing notification of the changed image stabilization scheme.
9. The electronic device of claim 1, wherein the processor is further configured to: while the live-

preview is displayed using a corresponding set of a first set of images and a second set of images, receive a request to capture a video; in response to the corresponding set being the first set of images, generate the video using at least one image of the first set of images as stabilized according to the first stabilization; and in response to the corresponding set being the second set of images, generate the video using at least one image of the second set of images as stabilized according to the second stabilization.

10. The electronic device of claim 1, wherein the processor is further configured to: as part of performing the first stabilization, cropping a first area determined based at least in part on the motion information from one or more images; and as part of performing the second stabilization, cropping a second area determined based at least in part on the motion information from the one or more images.

11. The electronic device of claim 1, wherein the processor is further configured to: present, via the display, a first notification indicative of the first degree of motion stabilization in response to an activation of a first digital stabilization; and present, via the display, a second notification indicative of the second degree of motion stabilization in response to an activation of a second digital stabilization.

12. A method of operating an electronic device comprising a camera, the method comprising: entering a video capturing mode in which the camera is activated; displaying a live-preview corresponding to the video capturing mode using images obtained via the camera; while in the video capturing mode, displaying a user interface including a first graphical object indicative of a first degree of motion stabilization and a second graphical object indicative of a second degree of motion stabilization greater than the first degree of motion stabilization; receiving an input via the user interface to select one of the first graphical object or the second graphical object; obtaining motion information of the electronic device via a motion sensor; based on the first graphical object being selected, displaying a live-preview by performing, based on the motion information and a first marginal area having a first size, a first stabilization with respect to the obtained images; and based on the second graphical object being selected, displaying the live-preview by performing, based on the motion information and a second marginal area having a second size larger than the first size, a second stabilization with respect to the obtained images.

13. The method of claim 12, further comprising: determining an image acquisition speed at which a plurality of images is acquired; and determining a frequency of detection by the motion sensor based on at least one of the image acquisition speed and a motion size of the electronic device.

14. The method of claim 13, further comprising: processing the motion information if a change to the determined frequency of detection is not possible.

15. The method of claim 12, further comprising: determining a parameter for a stabilization path determination for correction of at least one of the images, based on the motion information of the electronic device.

16. The method of claim 12, further comprising: determining an ambient brightness of the electronic device; and determining an intensity of a stabilization operation, based on at least one of the ambient brightness and a motion size of the electronic device.

17. The method of claim 16, further comprising: outputting notification information corresponding to the determined intensity of the stabilization operation through a display.

18. The method of claim 12, further comprising: detecting motion of the electronic device in a state in which one of the first stabilization or the second stabilization is selected; and changing the selected image stabilization scheme to another image stabilization scheme if the detected motion satisfies a stabilization scheme change condition.

19. The method of claim 18, further comprising: outputting, through a display, information providing notification of the changed image stabilization scheme.

20. A non-transitory computer readable recording medium storing instructions that, when executed by at least one processor of an electronic device, cause the electronic device to perform operations

comprising: entering a video capturing mode in which a camera is activated; displaying a live-preview corresponding to the video capturing mode using images obtained via the camera; while in the video capturing mode, displaying a user interface including a first graphical object indicative of a first degree of motion stabilization and a second graphical object indicative of a second degree of motion stabilization greater than the first degree of motion stabilization; receiving an input via the user interface to select one of the first graphical object or the second graphical object; obtaining motion information of the electronic device via a motion sensor; based on the first graphical object being selected, displaying a live-preview by performing, based on the motion information and a first marginal area having a first size, a first stabilization with respect to the obtained images; and based on the second graphical object being selected, display the live-preview by performing, based on the motion information and a second marginal area having a second size larger than the first size, a second stabilization with respect to the obtained images.
