

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12402260
B2
August 26, 2025
Yano; Youzou et al.

Ventilation component

Abstract

A ventilation component **1** includes a ventilation path **10** for allowing ventilation between an inner space **2u** and an outer space **2s** of a housing **2**. The ventilation path **10** is a path for allowing ventilation between the internal space **2u** and the outer space **2s** when the ventilation component **1** is attached to an edge **2f**. The ventilation component **1** includes a supporting portion **12**, a gas-permeable membrane **11**, a protruding portion **13**, and a sealing member **14**. The supporting portion **12** surrounds the ventilation path **10**. The gas-permeable membrane **11** is bonded to the supporting portion **12** and closes the ventilation path **10** in a ventilatable manner. The protruding portion **13** is a part having a tubular shape, the part being arranged to protrude from the supporting portion **12** and surround one end of the ventilation path **10**, the part being configured to be in contact with the edge **2f** when the ventilation component **1** is attached to the edge **2f**. The ventilation component **1** satisfies a requirement $0.7 \leq D/W \leq 1.3$.

Inventors:	Yano; Youzou (Osaka, JP), Kasagi; Tomoyuki (Osaka, JP), Takahashi; Takumi (Osaka, JP)
Applicant:	NITTO DENKO CORPORATION (Ibaraki, JP)
Family ID:	1000008779210
Assignee:	NITTO DENKO CORPORATION (Osaka, JP)
Appl. No.:	17/784039
Filed (or PCT Filed):	December 09, 2020
PCT No.:	PCT/JP2020/045917
PCT Pub. No.:	WO2021/117779
PCT Pub. Date:	June 17, 2021

Prior Publication Data

Foreign Application Priority Data

JP 2019-222104 Dec. 09, 2019

Publication Classification

Int. Cl.: H05K5/02 (20060101)

U.S. Cl.:

CPC H05K5/0214 (20220801);

Field of Classification Search

CPC: H05K (5/0213); H05K (5/0214); H05K (5/0216); F16B (33/004)

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2008/0041624	12/2007	Sasaki	174/520	H05K 5/068
2013/0055898	12/2012	Yano	N/A	N/A
2014/0047981	12/2013	Uemura et al.	N/A	N/A
2017/0187018	12/2016	Pflueger et al.	N/A	N/A
2020/0088440	12/2019	Yano et al.	N/A	N/A
2020/0325928	12/2019	Treffert	N/A	F16F 1/18
2020/0340592	12/2019	Nakayama et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
19827896	12/1998	DE	F16B 33/004
102005029730	12/2006	DE	N/A
102014210231	12/2014	DE	N/A
102016224841	12/2016	DE	N/A
1363069	12/2018	EP	N/A
S4733102	12/1971	JP	N/A
2005150376	12/2004	JP	N/A
2006041304	12/2005	JP	N/A
2007048585	12/2006	JP	N/A
2012231089	12/2011	JP	N/A
2012243536	12/2011	JP	N/A
2018182030	12/2017	JP	N/A
2018199192	12/2017	WO	N/A

OTHER PUBLICATIONS

International Search Report issued for International Patent Application No. PCT/JP2020/045917, Date of mailing: Feb. 16, 2021, 5 pages including English translation. cited by applicant
Written Opinion issued for International Patent Application No. PCT/JP2020/045917, Date of mailing: Feb. 16, 2021, 6 pages including English translation. cited by applicant
Office Action issued for Indian Patent Application No. 202217038742, Date of Dispatch: Nov. 21, 2022, 5 pages. cited by applicant
Notice of Reasons for Refusal issued for Japanese Patent Application No. 2021-564008, Dispatch Date: Jun. 13, 2023, 7 pages including English machine translation. cited by applicant
Decision of Refusal issued for Japanese Patent Application No. 2021-564008, Dispatch Date: Nov. 14, 2023, 9 pages including English machine translation. cited by applicant
Request for the Submission of an Opinion issued for Korean Patent Application No. 10-2022-7020240, dated May 27, 2024, 10 pages including English machine translation. cited by applicant
Second Office Action issued for Chinese Patent Application No. 202080071964.9, dated Jun. 26, 2024, 9 pages including English machine translation. cited by applicant
Office Action issued for German Patent Application No. 11 2020 006 019.5, dated Jan. 27, 2025, 12 pages including English translation. cited by applicant
Notice of Final Rejection issued for Korean Patent Application No. 10-2022-7020240 , Dispatched date: Jan. 23, 2025, 8 pages including English machine translation. cited by applicant

Primary Examiner: Bosques; Edelmira

Assistant Examiner: Giordano; Michael James

Attorney, Agent or Firm: HSML P.C.

Background/Summary

TECHNICAL FIELD

(1) The present invention relates to a ventilation component.

BACKGROUND ART

(2) Ventilation components configured to be attached to an edge of an opening of a housing have been known. Ventilation components can be used, for example, in devices such as vehicle lamps, inverters, converters, electronic control units (ECUs), battery packs, millimeter-wave radars, and vehicle-mounted cameras to eliminate a pressure difference occurring between the inside and the outside of the devices due to a temperature variation. These devices are sometimes required to prevent substances such as foreign matters, water, oil, and salt from entering the devices. In response to such a request, ventilation components are attached to housings of the devices.

(3) For example, Patent Literature 1 describes a ventilation unit including: a ventilation member configured to be attached to an opening of a housing; a sealing member; and a washer. The sealing member seals a gap between the housing and the ventilation member. The washer is a ring-shaped member surrounding the sealing member. This configuration can prevent foreign matters from entering the housing from between the ventilation member and the housing even under a high external pressure environment created by, for example, jetting of high-pressure water toward automotive electrical components.

(4) Patent Literature 2 describes a ventilation structure including a housing, a ventilation member, and a sealing member. The housing is provided with an opening. The ventilation member is attached to the opening of the housing. The sealing member is held by the ventilation member. The opening has a tapered surface. The ventilation member includes a support having a ventilation path,

a waterproof gas-permeable membrane closing the ventilation path, and a cover covering the waterproof gas-permeable membrane. Around the ventilation path, the sealing member seals a gap between the housing and the support. The support has a pressing portion pressing the sealing member against the tapered surface. As the sealing member is placed in the opening, this configuration can prevent the sealing member from being directly exposed, due to, for example, jetting of high-pressure water toward automotive electrical components, to water coming from the outside.

(5) Patent Literature 3 describes a ventilation structure including an opening portion of a housing, a ventilation member, and a shield. The ventilation member is fixed to the opening portion and includes a gas-permeable membrane. The shield is in the shape of a protrusion arranged on a surface of the housing. In the case where the ventilation structure described in Patent Literature 3 is applied to an ECU in an engine room of an automobile, the ventilation structure improves the resistance to a water stream applied in high-pressure washing of the engine room. The shield blocks part of the water stream, so that the water pressure applied to the ventilation member can be decreased.

CITATION LIST

Patent Literature

(6) Patent Literature 1: JP 2012-231089 A Patent Literature 2: JP 2012-243536 A Patent Literature 3: JP 2007-048585 A

SUMMARY OF INVENTION

Technical Problem

(7) The techniques described in Patent Literatures 1 to 3 require the washer, the opening having the tapered surface, and the shield, which impose restrictions upon design and manufacturing of ventilation structures.

(8) Therefore, the present invention provides a ventilation component capable of reducing restrictions upon design and manufacture thereof and capable of preventing water from entering a housing upon exposure to a high-pressure water stream.

Solution to Problem

(9) The present invention provides a ventilation component configured to be attached to an edge of an opening of a housing, the opening communicating with an inner space and an outer space of the housing, the ventilation component comprising: a ventilation path for allowing ventilation between the inner space and the outer space when the ventilation component is attached to the edge; a supporting portion surrounding the ventilation path; a gas-permeable membrane bonded to the supporting portion and closing the ventilation path in a ventilatable manner; a protruding portion having a tubular shape, the protruding portion being arranged to protrude from the supporting portion and surround one end of the ventilation path, the protruding portion being configured to be in contact with the edge when the ventilation component is attached to the edge; and a sealing member disposed around the protruding portion, the sealing member being configured to seal a gap between an outer surface of the housing and the ventilation component when the ventilation component is attached to the edge, wherein the ventilation component satisfies a requirement $0.7 \leq D/W \leq 1.3$, where D is a distance from an outer edge of an outer face of the supporting portion to a boundary between the protruding portion and the supporting portion, the outer face being in contact with the protruding portion, the outer edge being defined when the outer face is viewed in plan, and W is a cross-sectional diameter of the sealing member.

Advantageous Effects of Invention

(10) The above ventilation component can reduce restrictions upon design and manufacturing of a ventilation structure. Moreover, the above ventilation component can prevent water from entering a housing upon exposure to a high-pressure water stream.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a cross-sectional view showing an example of a ventilation component according to the present invention.
- (2) FIG. 2A is a cross-sectional view showing an example of a ventilation structure provided using the ventilation component shown in FIG. 1.
- (3) FIG. 2B is a cross-sectional view showing an example of a ventilation structure provided using a ventilation component according to any one of Comparative Examples.
- (4) FIG. 3 is a plan view showing a specific part of the ventilation component shown in FIG. 1.
- (5) FIG. 4 is a cross-sectional view showing part of the ventilation component shown in FIG. 1.
- (6) FIG. 5 is a cross-sectional view showing another example of the ventilation component according to the present invention.
- (7) FIG. 6 is a cross-sectional view showing a ventilation component used in Examples and Comparative Examples.

DESCRIPTION OF EMBODIMENTS

- (8) Hereinafter, embodiments of the present invention will be described with reference to the drawings. The following description describes examples of the present invention, and the present invention is not limited to the following embodiments.
- (9) As shown in FIGS. 1 and 2A, the ventilation component 1 is configured to be attached to an edge 2f of an opening 21 of a housing 2, the opening 21 communicating with an internal space 2u and an outer space 2s of the housing 2. The ventilation component 1 includes a ventilation path 10. The ventilation path is a path for allowing ventilation between the internal space 2u and the outer space 2s when the ventilation component 1 is attached to the edge 2f. The ventilation component 1 includes a supporting portion 12, a gas-permeable membrane 11, a protruding portion 13, and a sealing member 14. The supporting portion 12 surrounds the ventilation path 10. The gas-permeable membrane 11 is bonded to the supporting portion 12 and closes the ventilation path 10 in a ventilatable manner. The protruding portion 13 is a part having a tubular shape, the part being arranged to protrude from the supporting portion 12 and surround one end of the ventilation path 10, the part being configured to be in contact with the edge 2f when the ventilation component 1 is attached to the edge 2f. The sealing member 14 is disposed around the protruding portion 13, and seals a gap between an outer surface 2g of the housing 2 and the ventilation component 1 when the ventilation component 1 is attached to the edge 2f. The ventilation component 1 satisfies a requirement $0.7 \leq D/W \leq 1.3$. FIG. 3 is a plan view of a part of the supporting portion 12 between an outer edge 12e of an outer face 12g of the supporting portion 12 and a boundary 12b between the protruding portion 13 and the supporting portion 12, the outer face 12g being in contact with the protruding portion 13, the outer edge 12e being defined when the outer face 12g is viewed in plan. As shown in FIG. 3, D represents a distance from the outer edge 12e to the boundary 12b. As shown in FIG. 4, W represents a cross-sectional diameter of the sealing member 14.
- (10) As shown in FIG. 2A, a ventilation structure 50 can be provided by attaching the ventilation component 1 to the edge 2f of the opening 21 of the housing 2. FIG. 2B shows a ventilation structure 50a provided using a ventilation component 1a according to any one of Comparative Examples. The ventilation component 1a is configured in the same manner as the ventilation component 1, unless otherwise described. The components of the ventilation component 1a that are the same as or correspond to those of the ventilation component 1 are denoted by the same reference characters.
- (11) For example, Deutsche Industrie Normen DIN 400 50 Part 9 describes a waterproofness test involving jetting of a high-temperature and high-pressure water to a product at angles of 30° and 60°. In the ventilation structure 50a, the sealing member 14 is disposed at a position distant from

the outside of the ventilation structure **50** to protect the sealing member **14** from a water stream **J1** coming from such oblique directions. Therefore, in the ventilation component **1a**, D/W is adjusted to a value greater than 1.3. This prevents direct exposure of the sealing member **14** to the water stream **J1**. As described above, from the viewpoint of waterproofness under jetting of high-temperature and high-pressure water, it is conventionally taken for granted that the value of D/W of a ventilation component is defined to be significantly greater than 1.3.

(12) However, according to studies by the present inventors, it is hard to say that a large D/W value is advantageous in facilitating drainage of water from around the sealing member **14** when a high-pressure water stream **J2** occurs toward the sealing member **14** of the ventilation component **1a**. This is because, in that case, a space located around the sealing member **14** and between the supporting portion **12** of the ventilation component **1a** and the outer surface **2g** of the housing **2** is long, and therefore a high water pressure is continuously applied to the space when the high-pressure water stream **J2** occurs toward the sealing member **14**. Continuous application of a high water pressure to the sealing member **14** may cause an unintended deformation of the sealing member **14** and may allow water to enter the housing **2**.

(13) Application of any of the techniques described in Patent Literatures 1 to 3 is conceivable to prevent exposure of a sealing member to a high water pressure. However, the techniques described in Patent Literatures 1 to 3 require a washer, an opening having a tapered surface, and a shield, which impose restrictions upon design and manufacturing of a ventilation structure. For example, it is hard to say that the techniques described in Patent Literatures 1 to 3 are advantageous from the viewpoint of high design flexibility and low manufacturing cost. Therefore, the present inventors made intensive studies to newly develop a ventilation component capable of reducing restrictions upon design and manufacturing of a ventilation structure and capable of preventing water from entering a housing upon exposure to a high-pressure water stream. That eventually led the present inventors to newly find that adjustment of the D/W value of a ventilation component within the above range can reduce restrictions upon design and manufacturing of a ventilation structure and can prevent water from entering the housing upon exposure to a high-pressure water stream.

(14) The ventilation component **1** satisfies the requirement $0.7 \leq D/W \leq 1.3$. Therefore, in the ventilation structure **50**, when a high-pressure water stream occurs toward the sealing member **14**, water can easily escape from around the sealing member **14** and drainage of water from around the sealing member **14** is facilitated, as shown in FIG. 2A. This makes it possible to avoid continuous application of a high water pressure to the sealing member **14** and thus can prevent water from entering the housing **2**.

(15) Around an axis **A1** of the ventilation component **1**, the value of D may be constant or may vary. In the case where the value of D varies around the axis **A1**, for example, the requirement $0.7 \leq D/W \leq 1.3$ is satisfied in an angle range of 50% or more of 360° around the axis **A1**. The angle range may be continuous around the axis **A1** or may be divided into a plurality of angle ranges around the axis **A1**. Desirably, the requirement $0.7 \leq D/W \leq 1.3$ is satisfied in an angle range of 60% or more of 360° around the axis **A1**. More desirably, the requirement $0.7 \leq D/W \leq 1.3$ is satisfied in an angle range of 70% or more of 360° around the axis **A1**. Even more desirably, the requirement $0.7 \leq D/W \leq 1.3$ is satisfied in an angle range of 80% or more of 360° around the axis **A1**. Particularly desirably, the requirement $0.7 \leq D/W \leq 1.3$ is satisfied in an angle range of 90% or more of 360° around the axis **A1**. Most desirably, the requirement $0.7 \leq D/W \leq 1.3$ is satisfied in 360° around the axis **A1**.

(16) The cross-sectional diameter W typically corresponds to a maximum dimension of a cross-section of the sealing member **14** along a plane including the axis **A1**, the maximum dimension being defined in a direction perpendicularly to the axis **A1**. The cross-sectional diameter W is typically constant around the axis **A1**. The cross-sectional diameter W may be considered constant around the axis **A1** when a difference between the maximum and the minimum of the cross-sectional diameter W around the axis **A1** is less than 10% of the minimum.

- (17) The value of D/W is not limited to a particular value as long as the requirement $0.7 \leq D/W \leq 1.3$ is satisfied. The value of D may be equal to or more than the value of W as shown in FIG. 4 or may be less than the value of W as shown in FIG. 5. The value of D/W may be 0.75 or more, 0.8 or more, or 0.85 or more. The value of D/W may be 1.25 or less, 1.2 or less, or 1.15 or less.
- (18) The cross-sectional diameter W is not limited to a particular value as long as the requirement $0.7 \leq D/W \leq 1.3$ is satisfied. The cross-sectional diameter W is, for example, 2.8 mm or more and 6.0 mm or less. In this case, in the ventilation structure 50, the contact area between the sealing member 14 and the supporting portion 12 and the contact area between the sealing member 14 and the outer surface 2g of the housing 2 are likely to be large. Consequently, in the ventilation structure 50, water can more reliably be prevented from entering the housing 2 when a high-pressure water stream occurs toward the sealing member 14.
- (19) The cross-sectional diameter W may be 2.9 mm or more, 3.0 mm or more, 3.2 mm or more, 3.4 mm or more, 3.6 mm or more, 4.0 mm or more, or 4.5 mm or more. The cross-sectional diameter W may be 5.9 mm or less, 5.6 mm or less, 5.3 mm or less, or 4.8 mm or less.
- (20) The distance D is not limited to a particular value as long as the requirement $0.7 \leq D/W \leq 1.3$ is satisfied. The distance D is, for example, 1.96 mm or more and 7.8 mm or less.
- (21) The distance D may be 2.2 mm or more, 2.4 mm or more, 2.6 mm or more, 2.8 mm or more, 3.0 mm or more, 3.2 mm or more, or 3.5 mm or more. The distance D may be 7.5 mm or less, 7.0 mm or less, 6.5 mm or less, or 6.0 mm or less.
- (22) The shape of the sealing member 14 is not limited to a particular shape. The sealing member 14 is typically a ring-shaped member. A cross-section of the sealing member 14 taken along a plane including an axis of the sealing member 14 is, for example, a circular plane, an elliptical plane, or a plane having a corner. The plane having a corner may be a polygon or a figure composed of a combination of a curved line and a straight line. The sealing member 14 may have a hollow structure having a ring-shaped inner space.
- (23) As shown in FIG. 4, the sealing member 14 includes, for example, a slope portion 14k. The slope portion 14k forms a slope between a first position 14f and a second position 14s each positioned in an outer peripheral portion of the sealing member 14. The second position 14s is closer to the supporting portion 12 than the first position 14f is, and is closer to the boundary 12b than the first position 14f is. According to this configuration, in the ventilation structure 50, when a high-pressure water stream occurs toward the sealing member 14, the water stream is likely to be led away from the outer surface 2g of the housing 2 after hitting the slope portion 14k. This facilitates drainage of water from around the sealing member 14. The first position 14f is, for example, at an outer end of the sealing member 14, the outer end being defined in the direction perpendicular to the axis of the sealing member 14.
- (24) As shown in FIG. 1, the protruding portion 13 includes, for example, a plurality of leg portions 13a. The plurality of leg portions 13a are disposed around a central axis of the protruding portion 13 and spaced from each other by a slit 13s extending from the end of the protruding portion 13 along the central axis of the protruding portion 13. At least one of the plurality of leg portions 13a includes an engaging portion 13k capable of being engaged with the housing 2. The engaging portion 13k protrudes outward in a direction perpendicular to the central axis of the protruding portion 13. According to this configuration, in a procedure, including insertion of the protruding portion 13 into the opening 21, for attaching the ventilation component 1 to the housing 2, the leg portion 13a elastically deforms inward when an end portion of the protruding portion 13 comes into contact with the edge 2f. Then, the deformed leg portion 13a returns to its original form when the engaging portion 13k passes through the opening 21, and the engaging portion 13k, for example, comes into contact with an inner surface 2n of the housing 2. In this manner, the engaging portion 13k is engaged with the housing 2 by snap-fitting and the ventilation component 1 is attached to the edge 2f of the housing 2.
- (25) The supporting portion 12 and the protruding portion 13 may be an integrally-molded

component or may be components separately produced. The materials of the supporting portion **12** and the protruding portion **13** are, for example, a thermoplastic resin in view of moldability. Examples of the thermoplastic resin can include polyamides (PA), polyethylene terephthalate (PET), polyphenylene sulfide (PPS), polybutylene terephthalate (PBT), polycarbonate (PC), polypropylene (PP), polyphenylene ether (PPE), and thermoplastic elastomers. The materials of the supporting portion **12** and the protruding portion **13** may be a thermosetting resin or a metal. The materials of the supporting portion **12** and the protruding portion **13** may be a rubber. Examples of the rubber include nitrile-butadiene rubber (NBR), ethylene propylene rubber (EPDM), silicone rubbers, fluorine rubbers, acrylic rubbers, and hydrogenated nitrile rubbers.

(26) As shown in FIG. 1, the supporting portion **12** typically includes an adherend surface **12s** to which the gas-permeable membrane **11** is attached. The adherend surface **12s** is, for example, a ring-shaped surface. The gas-permeable membrane **11** is disposed, for example, along the direction perpendicular to the central axis of the protruding portion **13**.

(27) The gas-permeable membrane **11** is not limited to a particular gas-permeable membrane as long as the gas-permeable membrane **11** has desirable gas permeability. The gas-permeable membrane **11** may be a single layer membrane, or may be a multilayer membrane. In the case where the gas-permeable membrane **11** is a multilayer membrane, each layer thereof can be one selected from the group consisting of a porous membrane, a nonwoven fabric, a cloth, and a mesh. The gas-permeable membrane **11** may include: a porous membrane and a nonwoven fabric; a porous membrane and at least one of a cloth and a mesh; or a plurality of nonwoven fabrics. Typically, the gas-permeable membrane **11** is composed of an organic polymer material (resin). The material of the porous membrane is, for example, a fluorine resin. As the fluorine resin can be used, for example, polytetrafluoroethylene (PTFE), polychlorotrifluoroethylene, a tetrafluoroethylene-hexafluoropropylene copolymer, or a tetrafluoroethylene-ethylene copolymer. The material of the porous membrane may be a polyolefin, such as a homopolymer or copolymer of a monomer(s) such as ethylene, propylene, or 4-methylpentene-1,1-butene. The porous membrane may be a porous nanofiber membrane made of, for example, polyacrylonitrile, nylon, or polylactic acid. The porous membrane can be manufactured by a known drawing or extraction technique. Examples of the materials of the nonwoven fabric, the cloth, and the mesh include polyesters such as polyethylene terephthalate, polyolefins such as polyethylene and polypropylene, nylon, aramids, and ethylene-vinyl acetate copolymer.

(28) The gas-permeable membrane **11** desirably includes a PTFE porous membrane. The PTFE porous membrane can ensure gas permeability with a small area and can effectively prevent entry of foreign matters. The PTFE porous membrane may be layered on a gas-permeable supporting member such as a nonwoven fabric.

(29) The gas-permeable membrane **11** may be subject to a liquid-repellant treatment as necessary. The liquid-repellant treatment is performed, for example, by forming a liquid-repellant coating film containing a fluorine surface modifier having a perfluoroalkyl group on the gas-permeable membrane **11**. The method for forming the liquid-repellant coating film is not limited to a particular formation method. The liquid-repellant coating film is formed, for example, by coating a porous resin membrane with a solution or dispersion of a fluorine surface modifier having a perfluoroalkyl group by a method such as air spraying, electrostatic spraying, dip coating, spin coating, roll coating, curtain flow coating, or impregnation. The liquid-repellant coating film may be formed by electrodeposition or plasma polymerization.

(30) The gas-permeable membrane **11** is, for example, adhered to the adherend surface **12s**. The gas-permeable membrane **11** may be welded to the adherend surface **12s**. The available welding method can be thermal welding, ultrasonic welding, and laser welding. Alternately, at the time of molding the supporting portion **12**, the gas-permeable membrane **11** may be attached to the adherend surface **12s** by insert molding, specifically, by pouring a resin in a mold for molding the supporting portion **12** with the gas-permeable membrane **11** disposed at a given position in the

mold. The gas-permeable membrane **11** may be attached to the adherend surface **12s** with a double-sided adhesive tape.

(31) The material of the sealing member **14** is not limited to a particular material as long as the sealing member **14** can exhibit desirable sealability. For example, any of the materials described above as examples of the materials of the supporting portion **12** and the protruding portion **13** can be used as the material of the sealing member **14**. The sealing member **14** is typically an elastic body that is elastically deformable, and the material of the sealing member **14** can be an elastomer such as a natural rubber, a synthetic rubber, or a thermoplastic elastomer.

(32) As shown in FIG. **1**, the ventilation component **1** further includes, for example, a cover **16**. The cover **16** is coupled to the supporting portion **12**. The cover **16** covers the gas-permeable membrane **11** and forms, between the gas-permeable membrane **11** and the cover **16**, a space **17** communicating with an outer space of the ventilation component **1**. The space **17** serves as a part of the ventilation path **10**. Owing to the cover **16**, the gas-permeable membrane **11** is protected appropriately.

(33) The cover **16** may be a component integrally molded with the supporting portion **12** or may be a component produced separately from the supporting portion **12**. Any of the materials described as examples of the material of the supporting portion **12**, for example, can be used as the material of the cover **16**.

(34) At least one of the supporting portion **12** and the cover **16** may have a side wall **18** disposed at an outer perimeter of the space **17**. The side wall **18** can include a plurality of side walls separately disposed in a perimeter direction of the space **17** at given intervals. The supporting portion **12** and the cover **16** each may have a plurality of side walls separately disposed in the perimeter direction at given intervals. In that case, the side walls of the supporting portion **12** and the side walls of the cover **16** may partially overlap in the perimeter direction.

(35) In the ventilation structure **50**, the housing **2** is, for example, a housing of an electronic device. Examples of the electronic device include automotive electronic devices, such as vehicle lamps, electronic control units (ECUs), electric power systems (EPSs), battery packs, inverters, converters, millimeter-wave radars, and vehicle-mounted cameras. The electronic device may be one used in applications other than use for automobiles. In the ventilation structure **50**, the ventilation path **10** can eliminate a pressure difference occurring between the internal space **2u** and the outer space **2s** of the housing **2** due to a temperature variation. Moreover, since the gas-permeable membrane **11** closes the ventilation path **10** in a ventilatable manner, entry of foreign matters into the internal space **2u** can be prevented and, for example, the ventilation structure **50** has dust proofness. Furthermore, the ventilation structure **50** can prevent entry of water, oil, salt, etc. into the internal space **2u**.

Examples

(36) Hereinafter, the present invention will be described in more detail by examples. The present invention is not limited to the examples given below.

(37) Ventilation components having a distance **D** of 1.5 mm, 1.8 mm, 2.5 mm, 3.0 mm, 3.5 mm, 4.0 mm, and 5.0 mm were each prepared by processing a portion of a ventilation component TEMISH Z series Z3-NTF210SE shown in FIG. **6** and manufactured by Nitto Denko Corporation into an outer face of a supporting portion, the distance **D** being from an outer edge of the outer face of the supporting portion to a boundary between a protruding portion and the supporting portion. As shown in FIG. **6**, the ventilation components each included the protruding portion having an outer diameter of 10 mm and an engaging portion having an outer diameter of 12.4 mm before the processing. TEMISH is a registered trademark of Nitto Denko Corporation. An O-ring α having a cross-sectional diameter **W** of 2.40 mm and an O-ring β having a cross-sectional diameter **W** of 3.85 mm were prepared. The hardness of the O-ring α and that of the O-ring β were measured using a type A durometer. The O-ring α had a hardness of 70, and the O-ring β had a hardness of 50. The O-ring α or the O-ring β was attached to each ventilation component after the processing to prepare

samples according to Examples 1 to 4 and Comparative Examples 1 to 4 as shown in Table 2.

(38) <Water Resistance Test>

(39) The protruding portions of the samples according to Examples 1 to 4 and Comparative Examples 1 to 4 were each inserted into and fixed to a housing having a circular opening having a diameter of 10.4 mm. The O-rings α and β had a compression rate (compression rate [%] of O-ring=O-ring compression squeeze (a decrease in length in a compression direction under compression)/cross-sectional diameter W of O-ring $\times$ 100) of 15% in a state where each sample was fixed to the housing. The samples according to Examples 1 to 4 and Comparative Examples 1 to 4 were subjected to a water resistance test (actual test) according to Deutsche Industrie Normen DIN 400 50 Part 9, except that conditions defined therein were changed to conditions shown in Table 1. Ingress of water was visually checked. Table 2 shows the results.

(40) TABLE-US-00001 TABLE 1 DIN 400 50 Part 9 (IPX9K) Actual test Temperature $80 \pm 5^\circ \text{C}$. 25°C . Pressure 8 to 10 MPa 8 MPa Amount of $15 \pm 1 \text{ L/min}$ 14 L/min water Distance 100 to 150 mm 150 mm Rotation 5 rpm 5 rpm speed Jetting angle $0^\circ, 30^\circ, 60^\circ, 90^\circ$ $0^\circ, 30^\circ, 60^\circ, 90^\circ$ Jetting 30 seconds at each 30 seconds at each duration angle angle

(41) TABLE-US-00002 TABLE 2 Cross- sectional Distance D diameter W Water [mm] [mm] D/W resistance test Example 1 1.8 2.40 0.750 No ingress of water Example 2 3.0 2.40 1.250 No ingress of water Example 3 3.5 3.85 0.909 No ingress of water Example 4 4.0 3.85 1.039 No ingress of water Comparative 1.5 2.40 0.625 Ingress of Example 1 water Comparative 3.5 2.40 1.458 Ingress of Example 2 water Comparative 2.5 3.85 0.649 Ingress of Example 3 water Comparative 5.2 3.85 1.351 Ingress of Example 4 water

Claims

1. A ventilation component configured to be attached to an edge of an opening of a housing, the opening communicating with an inner space and an outer space of the housing, the ventilation component comprising: a ventilation path for allowing ventilation between the inner space and the outer space when the ventilation component is attached to the edge; a supporting portion surrounding the ventilation path; a gas-permeable membrane bonded to the supporting portion and closing the ventilation path in a ventilatable manner; a protruding portion having a tubular shape, the protruding portion being arranged to protrude from the supporting portion and surround one end of the ventilation path, the protruding portion being configured to be in contact with the edge when the ventilation component is attached to the edge; and a sealing member disposed around the protruding portion, the sealing member being configured to seal a gap between an outer surface of the housing and the ventilation component when the ventilation component is attached to the edge, wherein the ventilation component satisfies a requirement $0.7 \leq D/W \leq 1.3$, where D is a distance from an outer edge of an outer face of the supporting portion to a boundary between the protruding portion and the supporting portion, the outer face being in contact with the protruding portion, the outer edge being defined when the outer face is viewed in plan, and W is a cross-sectional diameter of the sealing member.
2. The ventilation component according to claim 1, wherein the cross-sectional diameter W is 2.8 mm or more and 6.0 mm or less.
3. The ventilation component according to claim 1, wherein the distance D is 1.96 mm or more and 7.8 mm or less.
4. The ventilation component according to claim 1, wherein the protruding portion has an engaging portion capable of being engaged with the housing.
5. The ventilation component according to claim 1, further comprising a cover covering the gas-permeable membrane, the cover forming, between the gas-permeable membrane and the cover, a space communicating with an outer space of the ventilation component.
6. The ventilation component according to claim 1, wherein the protruding portion comprises a

plurality of leg portions, at least one of said leg portions being configured to engage with an inner edge of the housing.
