

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250277903

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

Moran; Mark D. et al.

NON-CONTACT GROUND MOISTURE LEVEL ESTIMATION AT VARIOUS DEPTHS USING REFLECTED ENERGY AT A WORK MACHINE

Abstract

A system for non-contact moisture estimation comprises a device housing extending outward from a work machine when coupled thereto. Sensors mounted to the housing generate output signals representing variables comprising a temperature, movement characteristics, and distances between respective sensors and ground surfaces across which the work machine travels. A radio antenna unit mounted to the housing receives reflected energy from respective ground regions, wherein the energy is emitted by the antenna or another antenna for that purpose. One or more local and/or remote processing units receive output signals representing the reflected energy via the radio antenna unit, estimate at least one moisture condition for each respective ground region, based on ground characteristics determined at least in part on the sensed variables and the reflected energy, and generate output signals representing the estimated at least one moisture condition for each respective ground region.

Inventors: Moran; Mark D. (Champaign, IL), Ogden; Nathan (Champaign, IL), Ackerman; Chad A. (Champaign, IL)

Applicant: Deere & Company (Moline, IL)

Family ID: 96881248

Appl. No.: 18/592766

Filed: March 01, 2024

Publication Classification

Int. Cl.: G01S13/88 (20060101); A01B76/00 (20060101); G01S7/03 (20060101); G01S7/41 (20060101)

U.S. Cl.:

Background/Summary

FIELD OF THE DISCLOSURE

[0001] The present disclosure relates generally to work machines having a device mounted thereto for capturing data related to ground moisture, and more particularly to systems and methods utilizing such devices for non-contact moisture estimation based on reflected energy from ground being traversed by work machines, at the surface and at depth.

BACKGROUND

[0002] Knowledge of soil moisture levels enables growers to make well-informed management decisions such as adjusting for uniform plant emergence, irrigation frequency, and the measure of other soil properties. Soil moisture greatly impacts germination, plant emergence, and yield. All these traits are agronomically integral for farmers to maximize and having accurate information will enable them to make informed management decisions.

[0003] Estimation of soil moisture is important across a wide range of earth working fields, including but not limited to agriculture, earth moving, road building, and turf construction and maintenance. Accordingly, exemplary work machines as discussed herein may include without limitation planters, sprayers, tillers, harvesters, road construction machines, excavators, loaders of various forms, etc.

BRIEF SUMMARY

[0004] The current disclosure provides enhancements to conventional soil moisture estimation systems, at least in part by providing a multi-sensor auxiliary unit for work machines capable of estimating surface and depth soil moisture using active radio frequencies. Working on a wide range of soils and conditions, this module allows farmers to make informed management decisions from the cab or otherwise remotely and substantially in real time with respect to traverse of the work area.

[0005] One example of such an auxiliary unit may include resident hardware coupled with models and software, collectively designed to be flexible in ascertaining soil moisture along with other soil characteristics such as identifying free and bound water determining plant available water, identifying the quantity and presence of various soil components (clay, organic matter, silt, etc.), and estimate soil physical and chemical characteristics (bulk density, salinity, structure, etc.). A vector network analyzer (VNA) may be utilized as a source of radio frequency (RF) energy further coupled to an antenna which radiates the RF energy outward towards the ground and receives the reflected energy therefrom.

[0006] In one particular and exemplary embodiment, a system is disclosed herein for non-contact moisture estimation. The system includes a work machine configured to travel across a ground surface via one or more ground-engaging units and further comprising a frame supported by the one or more ground-engaging units and one or more tools for working the ground. A housing coupled to, and extending outward from, the frame of the work machine has one or more sensors mounted with respect thereto and configured to generate output signals representing variables comprising a temperature, one or more movement characteristics, and a distance between a respective sensor and the ground surface across which the work machine travels. At least one radio antenna unit is also mounted with respect to the housing and configured to receive reflected energy from respective ground regions. One or more processing units are functionally linked to the one or more sensors and the at least one radio antenna unit, and configured to receive output signals representing the reflected energy via the at least one radio antenna unit, to estimate at least one

moisture condition for each respective ground region, based on ground characteristics determined at least in part on the sensed variables and the reflected energy, and to generate output signals representing the estimated at least one moisture condition for each respective ground region.

[0007] In an exemplary aspect according to the above-referenced system embodiment, each of the at least one radio antenna unit may be configured to emit energy and to receive the reflected energy.

[0008] In another exemplary aspect according to the above-referenced system embodiment, the at least one radio antenna unit may comprise a first radio antenna unit configured to emit energy and a second radio antenna unit configured to receive the reflected energy.

[0009] In another exemplary aspect according to the above-referenced system embodiment, the at least one radio antenna unit may be configured to receive reflected energy from the respective ground regions at the ground surface and at one or more ground depths, wherein the one or more processing units may be further configured to estimate at least one moisture condition for each of the ground surface and the one or more ground depths.

[0010] In another exemplary aspect according to the above-referenced system embodiment, the one or more processing units may comprise a vector network analyzer.

[0011] In another exemplary aspect according to the above-referenced system embodiment, at least one of the one or more processing units is mounted in association with the housing. The housing including the various sensors and at least one of the processing units may comprise a modular device for non-contact ground moisture estimation. In various embodiments, such a device may be mountable with respect to different work machines, e.g., to define respective systems, or may be mounted to a separate type of machine or even self-propelled to simply perform the non-contact ground moisture detection operations, or a subset thereof in combination with one or more other devices and systems.

[0012] In another exemplary aspect according to the above-referenced system embodiment, at least one of the one or more processing units is remotely positioned with respect to the work machine and configured to communicate with the one or more sensors and the at least one radio antenna unit via at least a wireless communications network.

[0013] For example, the output signals from the one or more processing units may be provided from a first processing unit associated with the work machine to a second processing unit remotely positioned with respect to the work machine, wherein the second processing unit is configured to plan one or more subsequent work operations associated with a work area comprising the respective ground regions based on the estimated moisture conditions.

[0014] In another exemplary aspect according to the above-referenced system embodiment, the output signals from the one or more processing units may be provided to at least one actuator for control of one or more operations of the work machine based on the estimated at least one moisture condition.

[0015] In another exemplary aspect according to the above-referenced system embodiment, the one or more processing units may be configured to estimate the at least one moisture condition for each respective ground region based on modeled correlations between the at least one moisture condition and inputs comprising the sensed variables and the reflected energy.

[0016] For example, the modeled correlations may be between the at least one moisture condition and inputs further comprising one or more soil properties further extracted from data storage as mapped to the ground region.

[0017] In another exemplary aspect according to the above-referenced system embodiment, the one or more processing units may be configured to estimate the at least one moisture condition for each respective ground region based at least in part on one or more soil properties further extracted from data storage as mapped to the ground region.

[0018] Numerous objects, features, and advantages of the embodiments set forth herein will be

readily apparent to those skilled in the art upon reading of the following disclosure when taken in conjunction with the accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0019] FIG. **1** is a block diagram representing an exemplary non-contact ground moisture estimation system according to an embodiment of the present disclosure.

[0020] FIG. **2** is a side view representing an exemplary work machine according to an embodiment of the present disclosure.

[0021] FIG. **3** is a side view representing an exemplary non-contact ground moisture estimation device according to an embodiment of the present disclosure.

[0022] FIG. **4** is a block diagram representing exemplary data sources, logic, and software modules in a non-contact ground moisture detection system or device according to an embodiment of the present disclosure.

[0023] FIG. **5** is a flowchart representing an exemplary non-contact ground moisture estimation method according to an embodiment of the present disclosure.

[0024] FIG. **6** is a flowchart representing a particular example of model generation and moisture estimation steps according to the method of FIG. **5**.

[0025] FIG. **7** is a graphical diagram representing exemplary test data for measured signal reflectance with respect to moisture levels.

[0026] FIGS. **8A** and **8B** are graphical diagrams representing indicia for indicating relative moisture levels and reflectance levels, respectively, on a user interface displaying all or part of a work area.

[0027] FIGS. **9A** and **9B** are graphical diagrams representing a main page of a user interface for an operator of a work machine, and a breakout screen selectively displayed and including moisture level indications for a highlighted portion of the work area, respectively.

DETAILED DESCRIPTION

[0028] With respect to the various figures, one of skill in the art may appreciate that the components thereof are not intended as limiting, are not drawn to scale, and are for illustrative purposes only. For example, the size, dimensions, structural layout, and quantity of the various components with respect to a first embodiment can and will vary in other embodiments unless otherwise specifically noted herein.

[0029] As represented in FIG. **1**, an embodiment of a non-passive ground moisture estimation system **100** as disclosed herein, in total or in relevant and sufficient portions for performing operations and methods as further disclosed herein, may include a work machine **200**, one or more mobile computing or other user devices **300**, and a remote server **400**. In some embodiments, a system and method according to the present disclosure may be self-contained with respect to the work machine **200**.

[0030] In some embodiments, a modular device **110** (as further described below) may be mounted to or otherwise associated with a work machine **200** as part of a system **100**, or the modular device **110** may be configured to independently perform or direct the performance of operations and methods as disclosed herein.

[0031] The work machine **200** may further include a display unit **202**, for example associated with a local user interface for input/output with respect to a controller **206**, various actuators **208**, and sensors **210**. In various embodiments, the display unit **202** may include a LCD display, a LED display, an OLED display, touch display, or other suitable user interface. The controller **206** may include or otherwise functionally communicate with a vector network analyzer (VNA) **204** or equivalent for implementing the non-contact moisture estimation operations and methods as

disclosed herein. The VNA **204** may for example perform radio frequency front-end functionality, for example the measurement of sample scattering parameters, which is then digitized and processed, locally or subsequent to transmission to a downstream processing unit such as moisture estimator **160**, controller **206**, or the like.

[0032] In an exemplary but non-limiting embodiment, VNA **204** may have an available range of 300 kHz to 9 GHz, although preferably only a subset of the available frequency range may be utilized during operation as further described below, and is connected to one or more directional antennas **114** using conventional media such as a coaxial transmission line.

[0033] The controller **206** may be part of a machine control system of the working machine, or it may be a separate control module. The controller **206** in the present embodiment is configured to receive input signals from some or all of sensors **210**. Various of the sensors **210** may typically be discrete in nature, but signals representative of more than one input parameter may be provided from the same sensor, and one or more sensors **210** as disclosed herein may further include or otherwise refer to signals provided from the machine control system.

[0034] The sensors **210** may include sensors associated with the moisture estimation device **110**, for example mounted on a housing **111** associated with the device **110** and not directly to the work machine **200** but functionally linked to the VNA **204** and optionally in communication with the controller **206** (if separate). In an embodiment as illustrated in FIG. 3, such sensors may include an inertial measurement unit (IMU) **112**, the one or more directional antennas **114**, a temperature sensor **116**, and a depth/range finding sensor **118**.

[0035] In an embodiment wherein the moisture estimation device **110** is configured to perform moisture analysis without reliance on a controller **206** of the work machine **200**, or at least to perform a portion of the moisture analysis in combination with the controller **206** of the work machine **200**, the device **110** may include a controller/processor comprising or otherwise associated with the VNA **204**.

[0036] In an embodiment the sensors **210** may include machine position determining sensors such as a separate IMU mounted on the work machine **200** itself, and/or a global positioning system (GPS) transceiver **120**, ground speed sensors, steering sensors, or the like, or equivalent inputs from the machine control system.

[0037] One of skill in the art may appreciate that IMUs are tools that capture a variety of motion- and position-based measurements, including, but not limited to, velocity, acceleration, angular velocity, and angular acceleration. IMUs may include one or more sensors including, but not limited to, accelerometers, which measure (among other things) velocity and acceleration, gyroscopes, which measure (among other things) angular velocity and angular acceleration, and magnetometers, which measure (among other things) strength and direction of a magnetic field. Generally, an accelerometer provides measurements, with respect to (among other things) force due to gravity, while a gyroscope provides measurements, with respect to (among other things) rigid body motion. The magnetometer provides measurements of the strength and the direction of the magnetic field, with respect to (among other things) known internal constants, or with respect to a known, accurately measured magnetic field. The magnetometer provides measurements of a magnetic field to yield information on positional, or angular, orientation of the IMU; similarly to that of the magnetometer, the gyroscope yields information on a positional, or angular, orientation of the IMU. Accordingly, the magnetometer may be used in lieu of the gyroscope, or in combination with the gyroscope, and complementary to the accelerometer, in order to produce local information and coordinates on the position, motion, and orientation of the IMU.

[0038] As conventionally known in the art, an accelerometer is an electro-mechanical device or tool used to measure acceleration (m/s^2), which is defined as the rate of change of velocity (m/s) of an object. Accelerometers sense either static forces (e.g., gravity) or dynamic forces of acceleration (e.g., vibration and movement). An accelerometer may receive sense elements measuring the force due to gravity. By measuring the quantity of static acceleration due to gravity

of the Earth, an accelerometer may provide data as to the angle the object is tilted with respect to the Earth, the angle of which may be established in an x-, y-, and z-axis coordinate frame. However, where the object is accelerating in a particular direction, such that the acceleration is dynamic (as opposed to static), the accelerometer produces data which does not effectively distinguish the dynamic forces of motion from the force due to gravity by the Earth. Also as conventionally known in the art, a gyroscope is a device used to measure changes in orientation, based upon the object's angular velocity (rad/s) or angular acceleration (rad/s²). A gyroscope may constitute a mechanical gyroscope, a micro-electro-mechanical system (MEMS) gyroscope, a ring laser gyroscope, a fiber-optic gyroscope, and/or other gyroscopes as are known in the art. Principally, a gyroscope is employed to measure changes in angular position of an object in motion, the angular position of which may be established in an x-, y-, and z-axis coordinate frame.

[0039] In an embodiment, sense elements from an IMU **112** mounted on the housing **111** of the device **110** may be fused with sense elements from IMU mounted on the work machine **200** or other position and/or orientation related inputs in an independent coordinate frame associated at least in part with the respective work machine **200**. Outputs from a device IMU **112**, alone or in combination with further outputs from one or more machine-based sensors, may be utilized to determine an orientation of the device housing **111** relative to the work machine **200** and thereby the ground surface, for example to confirm that the other components are operable to provide valid measurements in the context of a moisture estimation process as further described below.

[0040] The controller **206** of the work machine **200** may in some embodiments further receive inputs from and generate outputs to remote user devices **300** associated with a user via a respective user interface, for example a display unit **302** with touchscreen interface and associated input/output devices **306** and functionality. Data transmission, between for example a vehicle control system and a remote user interface, may take the form of a wireless communications system and associated components as are conventionally known in the art. In certain embodiments, a remote user interface and vehicle control systems for respective work machines **200** may be further coordinated or otherwise interact with a remote server **400** or other computing device for the performance of operations in a system **100** as disclosed herein.

[0041] The controller **206** may be configured to generate control signals for controlling the operation of respective actuators **208**, for example such as described below with respect to an exemplary work machine of FIG. 2. The controller **206** may generate signals for indirect control of relevant actuators **208** via intermediate control units, associated with for example a machine steering control system, a machine implement control system, an engine speed control system, etc. Such control systems may be independent or otherwise integrated together or as part of a machine control unit in various manners as known in the art.

[0042] The controller **206** may include, or be associated with, the processor **206**, as well as a computer readable medium, a communication unit, data storage such as for example a database network (not shown), and the aforementioned display unit **202** comprising or otherwise associated with a user interface or control panel. An input/output device, such as a keyboard, touch screen, or other user interface tool may be coupled to the controller **206** via the user interface so that the human operator may input instructions to the controller **206**.

[0043] It is understood that the controller **206** described herein may be a single controller having all of the described functionality, or it may include multiple controllers wherein the described functionality is distributed among the multiple controllers.

[0044] Various “computer-implemented” operations, steps or algorithms as described in connection with the controller **206** or alternative but equivalent computing devices or systems can be embodied directly in hardware, in a computer program product such as a software module executed by the processor **204**, or in a combination of the two. The computer program product can reside in RAM memory, flash memory, ROM memory, EPROM memory, EEPROM memory, registers, hard disk, a removable disk, or any other form of computer-readable medium known in the art. An exemplary

computer-readable medium can be coupled to the processor **204** such that the processor **204** can read information from, and write information to, the memory/storage medium. In the alternative, the medium can be integral to the processor **204**. The processor **204** and the medium can reside in an application specific integrated circuit (ASIC). The ASIC can reside in a user terminal. In the alternative, the processor **204** and the medium can reside as discrete components in a user terminal. [0045] The term “processor” **204** as used herein may refer to at least general-purpose or specific-purpose processing devices and/or logic as may be understood by one of skill in the art, including but not limited to a microprocessor, a microcontroller, a state machine, and the like. A processor **204** can also be implemented as a combination of computing devices, e.g., a combination of a digital signal processor (DSP) and a microprocessor, a plurality of microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration.

[0046] The communication unit may support or provide communications between the controller **206** and external systems or devices, and/or support or provide communication interface with respect to internal components of the self-propelled work machine **200**. The communications unit may include wireless communication system components (e.g., via cellular modem, WiFi, Bluetooth, or the like) and/or may include one or more wired communications terminals such as universal serial bus ports.

[0047] The data storage as further described below may, unless otherwise stated, generally encompass hardware such as volatile or non-volatile storage devices, drives, memory, or other storage media, as well as one or more databases residing thereon.

[0048] As noted above, various operations as disclosed herein, for example relating to non-contact ground moisture estimation, seeding, tillage or other earth working operations, and the like, may be executed via a controller **206** for a given work machine **200**, wherein the controller may be a discrete device or integrated with a vehicle control system or equivalent. In various embodiments as initially noted above operations may further or in the alternative be executed via a distributed system **100** including one or more remote processors **304**, **404**, such as for example are associated with hosted servers **400** in a cloud computing platform or mobile user devices **300**, independently or in association with a local controller **206** for each of one or more work machines **200a**, **200b**.

[0049] Each remote processor **304**, **404** may be respectively or collectively associated with hosted cloud data storage **412** or distributed/third party data storage having for example ground moisture models **414**, work models **416** relating to electronic worksite maps, planning information, work machine information, and the like retrievably stored thereon and collectively accessible for execution of operations and methods as disclosed herein.

[0050] Referring next to FIG. 2, an exemplary work machine **200** as disclosed herein may be a planter row unit configured to travel across a field while distributing seeds or other crop materials (e.g., roots, bulbs, or rhizomes) into the soil. However, as previously noted the scope of the present disclosure encompasses many alternative types of work machines **200** as may be appreciated by one of skill in the art.

[0051] In the illustrated embodiment, the planter row unit as work machine **200** can comprise a hopper **228** arranged in a generally upright position that is mounted to a frame **230**. A parallel arm arrangement **232** comprising upper and lower arms **234**, **236** and an actuation device can be mounted to the support frame **230** in a cantilever-like configuration, such that it extends outwardly and away from the frame **230**. In some embodiments, the actuation device may be mounted to at least one of the upper or lower arm **234**, **236** and can include mechanical, pneumatic, hydraulic, or other suitable actuators to apply lift and/or downforce on the planter row unit. A metering unit **238** having a generally circular configuration can be arranged beneath the hopper **228** and can be configured to distribute seeds received from the hopper **228** into a seed tube **240**. The seed tube **240** directs the seeds received from the metering unit **238** to an opening **244** formed in the soil **242** by a ground engaging device **220**. In some embodiments, a support member, which can be arranged to extend downwardly from the frame **230**, is mounted adjacent the seed tube **240**. The support

member can be operably coupled to a ground engaging device **220** and can comprise a shank, vertical post, or other suitable support structure. To regulate the penetration depth of the ground engaging device **220**, at least two gauge wheels **224** are mounted proximate the ground engaging device **220**. A closing wheel assembly **226** can be arranged following the ground engaging device **220** and the gauge wheels **224** and is operable to close the opening **244** formed by ground engaging device **220**.

[0052] Referring next to FIGS. **3** and **4**, various data sources and program modules may be described in relation to an embodiment of a system **100**, device **110**, and/or method **500** of the present disclosure.

[0053] As represented in FIG. **3**, each of the IMU **112**, directional antenna **114** (or antennas **114**), temperature sensor **116**, and depth sensor/range finder **118** are mounted to a housing **111**, which is further mounted to the work machine **200**. The housing **111** may be modular in nature, or in some embodiments may be permanently affixed or even integral to the frame of the work machine **200**. The housing **111** may comprise a simple bracket to which the aforementioned components are mounted and/or integrally fixed, or may define an interior containing one or more of the aforementioned components and having apertures as needed for the components to provide their respective measurements while being relatively protected from environmental impacts during operation.

[0054] The device **110** as illustrated is arranged to define a 25 cm air gap between the directional antenna(s) **114** and a surface of the ground traversed by the work machine **200**, but alternative heights may be contemplated depending on the context, configuration, etc. As represented in FIG. **7**, testing has indicated a root mean square error (RMSE) that is reduced for air gaps of 25 cm (~10 in.) with respect to smaller air gaps (e.g., 8-10 in.) when measuring moisture levels as a function of reflectance. Also, the RSME is further reduced in dual antenna configurations, wherein a first antenna is utilized for emission of RF energy while a second antenna is utilized for reflected RF energy, but single antenna configurations may be more practical due to reduced cost and complexity, and either configuration is considered as within the scope of a device **110** according to the present disclosure.

[0055] In the embodiment illustrated in FIG. **4**, the data sources associated with the device **110** include an IMU **112**, GPS transceiver **120**, depth sensor/range finder **118**, VNA **204**, and temperature sensor **116**. It may be understood that one or more of the data sources, such as the GPS transceiver **120** for example, may be located separately from the device **110** while providing the requisite functionality for the downstream processing.

[0056] Various data sources associated with the device **110** provide outputs to software estimators **130** which may be configured to transform, convert, or otherwise process the output signals to generate values represented thereby for use by a moisture estimator **160**. The software estimators **130** and the moisture estimator **160** may in some embodiments be part of the controller **206**, or discrete components such as microcontrollers separate from the other processing units described herein. The software estimators **130** and the moisture estimator **160** may in some embodiments be integrated with each other, or fully or partially discrete in configuration and functionality. The software estimators **130** as shown perform such data processing on the output signals from the depth sensor **118** and the temperature sensor **116** to generate a height value **134** and a temperature value **132**, respectively. Output signals from the IMU **112** and the GPS transceiver **120** in the example shown are provided to the moisture estimator **160** via one or more communication buses, for example a CAN bridge device **150** linking a plurality of respective bus networks.

[0057] The VNA **204** of the system **100** or device **110** serves as a source of radio frequency (RF) energy coupled to the one or more device antennas **114** which radiates the RF energy outward towards the ground and receives the reflected energy therefrom. Output signals from the VNA **204** may be provided, for example along with the height values **134**, for generation of a corrected frequency spectrum **164**. Scattering parameters, or other parameters relating to a reflection

coefficient or return loss attributable at least in part to an input/output relationship between ports and reflecting power transfer, may be generated by the VNA itself and provided to the moisture estimator **160**, or this functionality may be partially distributed or in some embodiments omitted. The VNA **204** may for example provide a windowing function to select, dynamically or programmatically in context, a target frequency or range of frequencies (e.g., as a preferably focused subset of the available frequency range) for a given hardware configuration, application, work area, portion of the work area, or the like, to potentially optimize data collection and avoid having to sweep across the entirety of an available frequency range for the respective antennas. [0058] Data storage local to the work machine or otherwise remote, for example in association with a hosted cloud platform or third party sources, may include one or more libraries **140** which can be accessed for further inputs to the moisture estimator **160**, for example ascertaining a soil type **136**. Libraries **140** may include historical actual soil moisture measurements for a given work area, or explicit references to a soil type **136** associated with the work area. A soil type **136** and/or other relevant information may be determined using input data obtained using for example near infrared spectroscopy and associated sensors **142**, a geodatabase **144** accessible for any preestablished soil geographic data relating to the work area, such as for example the USDA-NRCS Soil Survey Geographic (SSURGO) database, a soil bulk density database **146** accessible to provide relevant parameters for the moisture estimator **160**, and the like.

[0059] In some embodiments, information regarding soil properties for a particular location may be utilized for determining an optimal target frequency or range of frequencies for the RF energy. For example, relative proportions of clay, silt, sand, and the like in a given area may have previously been established and capable of being utilized to identify optimal frequencies for use in clay loam, sandy loam, silty clay, etc., to provide meaningful reflectance values at various depths without needing to sweep across an unnecessarily broad range of frequencies.

[0060] The moisture estimator **160** applies inputs from the device **110**, software estimators **130**, libraries **140**, and the like to selected soil models **162** and generates one or more moisture output signals, values, or the like **170**, such as for example plant available volumetric water content (VWC), for display on one or more display units **202**, **302**, for work machine control, for downstream work planning, etc.

[0061] In FIG. 5, the depicted flowchart represents an exemplary embodiment of a method **500** for non-contact ground moisture estimation using active radio frequency signals. The steps shown and described herein may in various alternative embodiments be performed in different order, or may in some contexts be combined into a single step, or even omitted altogether unless otherwise specifically noted herein.

[0062] In the embodiment shown, the method **500** includes the generation (e.g., development, training, testing) of one or more ground moisture models **510**. Exemplary techniques for predictive model development may include machine learning, for example supervised and unsupervised learning, hard and soft clustering, classification, forecasting, and the like.

[0063] With further reference to FIG. 6, an exemplary embodiment of moisture model generation includes obtaining or otherwise ascertaining inputs relating to actual soil properties **512**. In various embodiments, the soil properties may preferably correspond to soil properties which may reasonably be obtained during subsequent real-time operations, such as for example through third party data corresponding to a given location determined via GPS, sensing by the work machine performing the moisture estimation operation or a previous work machine, sensors mounted on other units such as drones, etc. The soil properties may for example include a type of soil, soil components, conductivity, permeability, texture, porosity, and the like.

[0064] Generation of a moisture model **510** may further include emitting RF energy **514** at various frequencies towards test areas including the actual soil for which properties have been obtained or otherwise ascertained. The various frequencies may include frequencies across an entire range of available frequencies for the RF emitting configuration, a user-selected frequency or subset of the

available frequencies, a frequency or subset of the available frequencies having already been learned and automatically applied by the system based on a priori knowledge regarding the current test conditions, etc.

[0065] Generation of a moisture model **510** may further include determining one or more ground characteristic values **516** based on the reflected RF energy, and mapping the determined ground characteristic values to respective test areas **518**. In various embodiments, the mapped ground characteristic values may preferably correspond to moisture estimation and/or the setting of target frequencies/ranges of frequencies, and may primarily consist of reflectance values obtained for a ground surface and at one or more subterranean depths, but are not limited to such and various additional or alternative ground characteristic values may be identified as correlative and practically available through development of models according to the present disclosure.

[0066] Generation of a moisture model **510** may further include determining various additional inputs **520** to be associated with the actual soil properties and RF energy collection for a respective test area, including one or more of for example location, temperature, distance to ground surface, depth within the ground surface, vibration and/or orientation of the RF emitters and receivers, etc.

[0067] Generation of a moisture model **510** may further include training the model over various iterations to identify correlations for the various additional inputs and RF energy reflectance with respect to the actual measured soil properties. In various embodiments, the model may further or in the alternative be trained to identify target frequencies or a target range of frequencies best correlating associated reflectance measurements to observed soil properties at respective depths (e.g., including a ground surface and subterranean depths) and further in association with a range of real-time measurable conditions.

[0068] Discontinuities may relate at least in part to changes in the dielectric media (i.e., air versus soil having various properties). For example, air itself has a relatively small dielectric constant of approximately 1, and although dry soil also has a relatively small dielectric constant (approximately 2.5), the dielectric constant of water is quite large (approximately 80) in comparison to air and dry soil, and the moisture content of the soil is accordingly impacted by and at least indirectly determinable from the dielectric changes.

[0069] Initial moisture measurement may be derived from a surface reflection, based on a first sensed dielectric change, whereas reflections from one or more depths (discontinuities) may be used to estimate relative changes in moisture. For example, in a context wherein the soil beneath the ground surface in a particular work area or portion thereof comprises a relatively dry soil zone (e.g., located above a subterranean water line) and a relatively moist soil zone (e.g., located below the water line), the two zones may be characterized based on their relative moisture contents, with the moist soil zone having a greater moisture content and dielectric value than that of the dry soil zone under most conditions, further resulting in corresponding RF signal path delays indicative of the respective moisture conditions and dielectric values.

[0070] It may further be noted that signal reflection generally increases with decreases in frequency. Whereas a broad range of frequencies may be available for projection and reflection via the directional antenna(s) and as sourced via the VNA, it may be determinable through training of the moisture model that a relative subset of the available frequencies results in a highly accurate spectrum of meaningful results with respect to the expected characteristics in a given area and associated range of reflectance values, while substantially reducing the operating requirements.

[0071] In an embodiment, a machine learning moisture estimation model **414** may include variable governing parameters which are optimized during training to better simulate (or approximate in a particular simulation) observed real-life performance data corresponding to an input dataset (e.g., soil properties, characteristic values such as RF reflectance, temperature, etc.). Such variables may comprise hyperparameters that may initially be set (e.g., user-specified) before training. Tuning of the hyperparameters, or in other words optimizing the values thereof, follows during training to obtain a set of values for the hyperparameters corresponding to an accurate input-output mapping

of the model for the training dataset. In various embodiments, tuning of parameters may be performed automatically during or between training iterations, manually based on user selection via a system interface, or combinations thereof.

[0072] Returning to FIG. 5, with models having been generated to at least a minimum confidence level, and without precluding further development and training of the models over time, the method 500 may proceed in association with a current working operation 520 for at least a first work machine, wherein a real-time active, non-contact moisture estimation is conducted 540.

[0073] With reference again to FIG. 6, an exemplary embodiment of moisture estimation includes measuring, obtaining, or otherwise ascertaining current, substantially real-time, inputs 542 including one or more of for example a current location, temperature, distance to ground surface, vibration and/or orientation of the RF emitters and receivers, etc.

[0074] Moisture estimation in the embodiment of FIG. 6 may further include identifying target frequencies (e.g., a target range of frequencies) 544 at which RF energy is to be emitted towards a ground surface. The target frequencies may be identified based on relevant factors which may include one or more of a given area, soil type, device configuration, work operation, etc.

[0075] Moisture estimation in the embodiment of FIG. 6 may further include emitting RF energy towards the ground surface at the target frequency (or across the target frequency range), and further receiving the reflected RF energy 546. In an embodiment, a first antenna may be utilized to emit the RF energy and a second antenna may be utilized to receive the reflected RF energy, but alternatively the same antenna may be utilized for both emission and reception of the RF energy.

[0076] Moisture estimation in the embodiment of FIG. 6 may further include determining one or more ground characteristic values 548 from analysis of the reflected RF energy, which may for example supplement other ground characteristic values which may be available by reference to other data sources.

[0077] Moisture estimation in the embodiment of FIG. 6 may further include reference to one or more selected moisture models as previously developed and trained, and further reference to the current inputs and ground characteristic values for ground moisture estimation 550.

[0078] Output signals representative of the estimated ground moisture values may further be generated 560, for example to be provided as inputs to a work planning module 562, to provide image data 564 for presentation and/or user interface on one or more displays 202, 302, to a controller as a basis for work machine control 566, and/or to one or more sensors associated with the work machine for calibration/confirmation of measured values 566.

[0079] In an embodiment, a cross sectional view of a work area, or a representative portion thereof, may be graphically represented on the display unit with indicia representing the one or more moisture values at the respective ground surface and one or more depths. In addition, or alternatively, an overhead view of the work area, or a representative portion thereof, may be graphically represented on the display unit with indicia corresponding to relative moisture values for the respective ground portions.

[0080] One exemplary user interface may represent a work area having multiple portions, each of which have respectively measured reflectance values at one or more depths, and respectively measured and/or estimated moisture values at the one or more depths. Such values may be graphically represented using indicia such as shown in FIGS. 8A and 8B, or preferably using color coding such as for example with underlying color swaths representing measured reflectance values throughout the work area and colored dots representing the moisture levels, or vice versa.

[0081] As illustrated in FIGS. 9A and 9B, an exemplary user interface 910 may include any number of representative images of a work area, data corresponding to current conditions or operating parameters, and in various embodiments one or more interface portions displaying information corresponding to determined soil parameters which may include moisture levels at the surface and/or one or more relevant depths. In an embodiment, upon user selection of a frame 912 including data and indicia (e.g., graphical icons, color coding) comprising a current moisture level

(e.g., as a percentage) and a representative descriptor for the current moisture level (e.g., “wet”), a pop-up frame **914** may be generated to provide further information regarding the data and/or indicia. For example, as illustrated in FIG. **9B** an information frame may be presented to clarify the descriptors and corresponding symbols for each of a plurality of moisture levels along a predetermined moisture scale.

[0082] In an embodiment, a work planning module **562** may generate a work plan for real-time control of a work operation **570** of the same work machine as the measured values and reflected RF energy is being provided for moisture estimation. The work planning module **562** may further or in the alternative generate a work plan for subsequent control of a work operation of the same or different work machine relating to the same work area being measured in the moisture estimation stage.

[0083] Output signals relating to moisture estimation, alone or in the context of further generated work plan, may be utilized by the controller to provide control signals to one or more actuators associated with the work machine **568** for controlling operations such as seeding, tilling, irrigation, etc.

[0084] As one example, a work plan may be generated in the context of a uniform emergence model which, e.g., correlates target seed depth to plant available moisture, wherein the planting depth may be dynamically controlled based on real-time moisture estimation in the work area (e.g., field) or based on previously estimated moisture characteristics which are mapped to respective locations in the work area.

[0085] As another example, a work plan may be generated in the context of an irrigation model which, e.g., seeks to provide a uniform and/or seasonably appropriate plant available moisture throughout a work area or portion thereof, wherein an amount and/or frequency of irrigation applied may be dynamically controlled based on real-time moisture estimation in the work area (e.g., field) or based on previously estimated moisture characteristics which are mapped to respective locations in the work area.

[0086] Additional examples of work plans may relate, e.g., to spraying, harvesting, earth moving, road construction, and various other applications and operations potentially impacted by ground moisture as may be appreciated by one of skill in the art.

[0087] In some embodiments, components of a work plan may be utilized for optimizing frequency selection or other aspects of the moisture estimation stage. For example, a target range of frequencies may be determined in the real-time moisture estimation stage based at least in part on a range of expected target planning depths, wherein the target planting depths are further determined based on a stored uniform emergence model correlating the one or more moisture values and expected crop growth at respective planting depths.

[0088] In various embodiments, output signals conveying information such as estimated moisture values, in association with a location, conditions, measured inputs, and the like, may provide feedback for continued development, training, testing, etc., of the moisture estimation models via observation and machine learning.

[0089] In various embodiments, output signals conveying information such as estimated moisture values, in association with a location, conditions, measured inputs, and the like, may provide feedback to one or more sensors associated with the work machine for optional use in condition measurement, calibration, confirmation, etc. For example, a work machine may be configured to estimate soil properties in real time based on one or more machine operating parameters during an earth working operation, wherein estimated soil moisture information (optionally further including measured values such as temperature, etc.) may be used as feedback to assist or confirm in these real-time estimations or in development of models therefor. This process may be synergistic in nature, as real time soil property estimations by the work machine controller, if sufficiently credible, may be provided to confirm or correct soil properties from third party sources as utilized by the soil moisture estimation systems and methods as disclosed herein.

[0090] As used herein, the phrase “one or more of,” when used with a list of items, means that different combinations of one or more of the items may be used and only one of each item in the list may be needed. For example, “one or more of” item A, item B, and item C may include, for example, without limitation, item A or item A and item B. This example also may include item A, item B, and item C, or item B and item C.

[0091] Thus, it is seen that the apparatus and methods of the present disclosure readily achieve the ends and advantages mentioned as well as those inherent therein. While certain preferred embodiments of the disclosure have been illustrated and described for present purposes, numerous changes in the arrangement and construction of parts and steps may be made by those skilled in the art, which changes are encompassed within the scope and spirit of the present disclosure as defined by the appended claims. Each disclosed feature or embodiment may be combined with any of the other disclosed features or embodiments.

Claims

1. A device for non-contact moisture estimation, comprising: a housing configured to be coupled to, and extend outward from, a work machine; one or more sensors mounted with respect to the housing and configured to generate output signals representing variables comprising a temperature, one or more movement characteristics, and a distance between a respective sensor and a surface of ground across which the work machine travels; at least one radio antenna unit mounted with respect to the housing and configured to receive reflected energy from respective ground regions; and one or more processing units functionally linked to the one or more sensors and the at least one radio antenna unit, and configured to receive output signals representing the reflected energy via the at least one radio antenna unit, estimate at least one moisture condition for each respective ground region, based on ground characteristics determined at least in part on the sensed variables and the reflected energy, and generate output signals representing the estimated at least one moisture condition for each respective ground region.
2. The device of claim 1, wherein each of the at least one radio antenna unit is configured to emit energy and to receive the reflected energy.
3. The device of claim 1, wherein the at least one radio antenna unit comprises a first radio antenna unit configured to emit energy and a second radio antenna unit configured to receive the reflected energy.
4. The device of claim 1, wherein the at least one radio antenna unit is configured to receive reflected energy from the respective ground regions at the ground surface and at one or more ground depths, and wherein the one or more processing units are configured to estimate at least one moisture condition for each of the ground surface and the one or more ground depths.
5. The device of claim 1, wherein the output signals from the one or more processing units are provided to at least one actuator for control of one or more operations of the work machine based on the estimated at least one moisture condition.
6. The device of claim 1, wherein the one or more processing units are configured to estimate the at least one moisture condition for each respective ground region based on modeled correlations between the at least one moisture condition and inputs comprising the sensed variables and the reflected energy.
7. The device of claim 6, wherein the modeled correlations are between the at least one moisture condition and inputs further comprising one or more soil properties further extracted from data storage as mapped to the ground region.
8. The device of claim 1, wherein the one or more processing units are configured to estimate the at least one moisture condition for each respective ground region based at least in part on one or more soil properties further extracted from data storage as mapped to the ground region.
9. A system for non-contact moisture estimation, comprising: a work machine configured to travel

across a ground surface via one or more ground-engaging units and further comprising a frame supported by the one or more ground-engaging units and one or more tools for working the ground; a housing coupled to, and extending outward from, the frame of the work machine; one or more sensors mounted with respect to the housing and configured to generate output signals representing variables comprising a temperature, one or more movement characteristics, and a distance between a respective sensor and the ground surface across which the work machine travels; at least one radio antenna unit mounted with respect to the housing and configured to receive reflected energy from respective ground regions; and one or more processing units functionally linked to the one or more sensors and the at least one radio antenna unit, and configured to receive output signals representing the reflected energy via the at least one radio antenna unit, estimate at least one moisture condition for each respective ground region, based on ground characteristics determined at least in part on the sensed variables and the reflected energy, and generate output signals representing the estimated at least one moisture condition for each respective ground region.

10. The system of claim 9, wherein each of the at least one radio antenna unit is configured to emit energy and to receive the reflected energy.

11. The system of claim 9, wherein the at least one radio antenna unit comprises a first radio antenna unit configured to emit energy and a second radio antenna unit configured to receive the reflected energy.

12. The system of claim 9, wherein the at least one radio antenna unit is configured to receive reflected energy from the respective ground regions at the ground surface and at one or more ground depths, and wherein the one or more processing units are configured to estimate at least one moisture condition for each of the ground surface and the one or more ground depths.

13. The system of claim 9, wherein the one or more processing units comprise a vector network analyzer.

14. The system of claim 9, wherein at least one of the one or more processing units is mounted in association with the housing.

15. The system of claim 9, wherein at least one of the one or more processing units is remotely positioned with respect to the work machine and configured to communicate with the one or more sensors and the at least one radio antenna unit via at least a wireless communications network.

16. The system of claim 15, wherein the output signals from the one or more processing units are provided from a first processing unit associated with the work machine to a second processing unit remotely positioned with respect to the work machine, wherein the second processing unit is configured to plan one or more subsequent work operations associated with a work area comprising the respective ground regions based on the estimated moisture conditions.

17. The system of claim 9, wherein the output signals from the one or more processing units are provided to at least one actuator for control of one or more operations of the work machine based on the estimated at least one moisture condition.

18. The system of claim 9, wherein the one or more processing units are configured to estimate the at least one moisture condition for each respective ground region based on modeled correlations between the at least one moisture condition and inputs comprising the sensed variables and the reflected energy.

19. The system of claim 18, wherein the modeled correlations are between the at least one moisture condition and inputs further comprising one or more soil properties further extracted from data storage as mapped to the ground region.

20. The system of claim 9, wherein the one or more processing units are configured to estimate the at least one moisture condition for each respective ground region based at least in part on one or more soil properties further extracted from data storage as mapped to the ground region.
