

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250277939

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

SHIMAZU; Takayuki et al.

SPACER AND SPACER STRUCTURE

Abstract

A spacer includes a first support portion, a second support portion, and a first holding plate portion. The first support portion and the second support portion are capable of being engaged with a vertically rising portion of a cable laying tray to support the spacer, and are capable of being engaged with the vertically rising portion at different positions in a first direction. The first holding plate portion is connected to the first support portion and the second support portion, and extends in parallel with a bottom portion when the first support portion and the second support portion are engaged with the vertically rising portion. A distance between the bottom portion and the first holding plate portion is larger than a distance obtained by totaling a diameter of a main cable and a diameter of a branch cord portion.

Inventors: SHIMAZU; Takayuki (Osaka-shi, JP), FUKUI; Junji (Kanagawa, JP), SHIBATA; Masahiro (Kanagawa, JP)

Applicant: SUMITOMO ELECTRIC INDUSTRIES, LTD. (Osaka-shi, JP); SUMITOMO ELECTRIC OPTIFRONTIER CO., LTD. (Yokohama-shi, JP)

Family ID: 96881225

Assignee: SUMITOMO ELECTRIC INDUSTRIES, LTD. (Osaka-shi, JP); SUMITOMO ELECTRIC OPTIFRONTIER CO., LTD. (Yokohama-shi, JP)

Appl. No.: 19/068339

Filed: March 03, 2025

Foreign Application Priority Data

JP	2024-032398	Mar. 04, 2024
----	-------------	---------------

Publication Classification

Int. Cl.: G02B6/36 (20060101); G02B6/44 (20060101)

Background/Summary

TECHNICAL FIELD

[0001] The present disclosure relates to a spacer and a spacer structure. This application claims priority based on Japanese Patent Application No. 2024-032398 filed on Mar. 4, 2024, and the entire contents of which are incorporated herein by reference.

BACKGROUND ART

[0002] JP2023-083096A discloses an optical branch cable that connects a server rack group including a plurality of server racks to a distribution board. The optical branch includes a main cable and branch cords that are branched from the main cable and connected to each of the server racks.

[0003] U.S. Pat. No. 6,625,373B discloses a cable laying tray and a drop nose. The cable laying tray is configured to enable an optical cable to be disposed in a groove portion defined by a bottom portion and a vertically rising portion. The drop nose is installed in engagement with the vertically rising portion. The drop cords pass through the inside of the drop nose and are lowered to the outside of the cable laying tray.

SUMMARY

[0004] A spacer according to one aspect of the present disclosure is a spacer installed on a cable laying tray capable of housing an optical branch cable, the spacer including: [0005] a first support portion; [0006] a second support portion; and [0007] a first holding plate portion, in which [0008] the cable laying tray is capable of housing the optical branch cable in a housing portion defined by a bottom portion extending in a first direction and a vertically rising portion rising upward from an end portion of the bottom portion in a direction intersecting the first direction, [0009] the optical branch cable includes a main cable including a plurality of optical fibers, and a branch cord portion formed by drawing at least one optical fiber from the main cable, [0010] the first support portion and the second support portion are capable of being engaged with the vertically rising portion to support the spacer, and are capable of being engaged with the vertically rising portion at positions different from each other in the first direction, [0011] the first holding plate portion is connected to the first support portion and the second support portion, and extends in parallel with the bottom portion when the first support portion and the second support portion are engaged with the vertically rising portion, [0012] the first holding plate portion is capable of disposing the optical branch cable on an upper portion of the first holding plate portion, and [0013] a distance between the bottom portion and the first holding plate portion is larger than a distance obtained by totaling a diameter of the main cable and a diameter of the branch cord portion.

Description

BRIEF DESCRIPTION OF DRAWINGS

[0014] FIG. 1 illustrates an example of an optical communication system according to the present embodiment.

[0015] FIG. 2 illustrates an example of a spacer structure according to the present embodiment.

[0016] FIG. 3 is a cross-sectional view taken along a III-III plane in FIG. 2.

[0017] FIG. 4 illustrates an example of a first spacer.

[0018] FIG. 5 illustrates an example of a second spacer installed in a cable laying tray.

[0019] FIG. 6 illustrates an example of arrangement of optical branch cables in a first layer.

[0020] FIG. 7 illustrates an example of arrangement of the first spacer.

[0021] FIG. 8 illustrates an example of arrangement of optical branch cables in a second layer.

[0022] FIG. 9 is an enlarged view of an IX portion in FIG. 3.

DESCRIPTION OF EMBODIMENTS

[0023] To respond to a server rack group having various sizes, it is desirable to increase the number of optical branch cables to be disposed on a single cable laying tray.

[0024] An object of the present disclosure is to provide a spacer and a spacer structure capable of increasing the number of optical branch cables to be disposed on a single cable laying tray.

[0025] According the present disclosure, it is possible to increase the number of optical branch cables to be disposed on a single cable laying tray.

Description of Embodiments of Present Disclosure

[0026] First, embodiments of the present disclosure will be listed and described.

[0027] (1) A spacer according to one aspect of the present disclosure is a spacer installed on a cable laying tray capable of housing an optical branch cable, the spacer including: [0028] a first support portion; [0029] a second support portion; and [0030] a first holding plate portion, in which [0031] the cable laying tray is capable of housing the optical branch cable in a housing portion defined by a bottom portion extending in a first direction and a vertically rising portion rising upward from an end portion of the bottom portion in a direction intersecting the first direction, [0032] the optical branch cable includes a main cable including a plurality of optical fibers, and a branch cord portion formed by drawing at least one optical fiber from the main cable, [0033] the first support portion and the second support portion are capable of being engaged with the vertically rising portion to support the spacer, and are capable of being engaged with the vertically rising portion at positions different from each other in the first direction, [0034] the first holding plate portion is connected to the first support portion and the second support portion, and extends in parallel with the bottom portion when the first support portion and the second support portion are engaged with the vertically rising portion, [0035] the first holding plate portion is capable of disposing the optical branch cable on an upper portion of the first holding plate portion, and [0036] a distance between the bottom portion and the first holding plate portion is larger than a distance obtained by totaling a diameter of the main cable and a diameter of the branch cord portion.

[0037] According to the spacer, since the first holding plate portion can dispose the optical branch cable on an upper portion thereof, the optical branch cables can be disposed in two layers with the first holding plate portion interposed therebetween. As a result, the number of optical branch cables to be housed in a single cable laying tray can be increased. Here, the distance between the bottom portion and the first holding plate portion is configured to be larger than the distance obtained by totaling the diameter of the main cable and the diameter of the branch cord portion. Accordingly, it is possible to prevent the branch cord portion of the optical branch cable disposed below the spacer from being pressed by provision of the spacer.

[0038] (2) In the spacer according to (1), in which [0039] a cord insertion passage configured to allow the branch cord portion of the optical branch cable disposed below the spacer to be inserted through the cord insertion passage may be formed in the first holding plate portion.

[0040] According to the spacer, since the cord insertion passage is formed in the first holding plate portion, it is possible to shorten a path through which the branch cord portion of the optical branch cable disposed below the spacer passes.

[0041] (3) In the spacer according to (2), in which [0042] each of the first support portion and the second support portion may include an arm portion rising upward from the first holding plate portion and a return portion connected to the arm portion and extending downward, and [0043] the arm portion and the return portion may be engaged with the vertically rising portion.

[0044] According to the spacer, since the arm portion and the return portion are engaged with the vertically rising portion, the spacer is stably installed on the cable laying tray.

[0045] (4) A spacer structure according to one aspect of the present disclosure is a spacer structure including a first spacer that is the spacer according to any one of (1) to (3), and a second spacer, in which [0046] the second spacer includes [0047] a third support portion and a fourth support portion engaged with the vertically rising portion to support the second spacer, the third support portion and the fourth support portion being engaged with the vertically rising portion at positions different from each other in the [0048] a second holding plate portion connected to the third support portion and the fourth support portion and extending in parallel with the bottom portion when the third support portion and the fourth support portion are engaged with the vertically rising portion, [0049] the second holding plate portion when the third support portion and the fourth support portion are engaged with the vertically rising portion is located above the first holding plate portion when the first support portion and the second support portion are engaged with the vertically rising portion, first direction, and [0050] the second holding plate portion is capable of disposing the optical branch cable on an upper portion of the second holding plate portion, and [0051] a distance between the first holding plate portion and the second holding plate portion is larger than a distance obtained by totaling a diameter of the main cable and a diameter of the branch cord portion. [0052] According to the spacer structure, the optical branch cables are allowed to be disposed not only on the first holding plate portion but also on the second holding plate portion, so that the optical branch cables can be disposed in three layers with the first holding plate portion and the second holding plate portion interposed therebetween. As a result, the number of optical branch cables to be housed in a single cable laying tray can be increased. Here, the distance between the first holding plate portion and the second holding plate portion is configured to be larger than the distance obtained by totaling the diameter of the main cable and the diameter of the branch cord portion. Accordingly, it is possible to prevent the branch cord portion of the optical branch cable disposed between the second spacer and the first spacer from being pressed by provision of the second spacer.

[0053] (5) In the spacer according to (4), in which [0054] a distance in the first direction from a third engagement position at which the third support portion engages with the vertically rising portion to a fourth engagement position at which the fourth support portion engages with the vertically rising portion may be larger than a distance in the first direction from a first engagement position at which the first support portion engages with the vertically rising portion to a second engagement position at which the second support portion engages with the vertically rising portion.

[0055] According to the spacer structure, the distance in the first direction from the third engagement position to the fourth engagement position is larger than the distance in the first direction to the second engagement position. As a result, even when the second spacer is provided, the second spacer can be disposed so that the third support portion and the fourth support portion are not disposed at the vertically rising portion between the first support portion and the second support portion that is likely to be the shortest path when the branch cord portion is drawn out of the cable laying tray and connected to the server rack.

Detailed Description of Embodiments of Present Disclosure

[0056] Specific examples of a spacer according to the embodiment of the present disclosure will be described below with reference to the drawings. Note that the present disclosure is not limited to the examples, but is indicated by the scope of the claims and is intended to include all modifications within the scope of the claims and meaning equivalent thereto.

[0057] FIG. 1 illustrates an example of an optical communication system **100** according to the present embodiment. As illustrated in FIG. 1, the optical communication system **100** includes a distribution board **110** and a plurality of server racks **120**. The distribution board **110** is connected to concentrated optical branch cables **1** used in the optical communication system **100**. Each server rack **120** houses a physical server. Each server rack **120** is connected to an optical fiber branched from the optical branch cable **1** housed in a cable laying tray **T**.

[0058] The optical branch cable **1** includes a main cable **10** and a branch cord portion **20**. The main

cable **10** includes a plurality of optical fibers. The branch cord portion **20** is a cord in which at least one optical fiber is drawn from the main cable **10**.

[0059] The cable laying tray **T** has a bottom portion **T1** and a vertically rising portion **T2**. The bottom portion **T1** extends in a first direction **D1**. The first direction **D1** is a horizontal direction. The vertically rising portion **T2** rises from an end portion of the bottom portion **T1** in a direction intersecting the first direction **D1**. In the present embodiment, two vertically rising portions **T2** are formed. The bottom portion **T1** and the vertically rising portions **T2** define a housing portion configured to house the optical branch cable **1**. In the present embodiment, the housing portion is formed to have a concave groove formed by the bottom portion **T1** and the vertically rising portions **T2**. The main cable **10** is housed in the concave groove, and the branch cord portion **20** passes over the vertically rising portion **T2** to be connected to the server rack **120**.

[0060] FIG. **2** illustrates an example of a spacer structure **200** according to the present embodiment. FIG. **3** is a cross-sectional view taken along III-III plane in FIG. **2**. As illustrated in FIGS. **2** and **3**, the spacer structure **200** is disposed and hung on the cable laying tray **T**. The spacer structure **200** includes a first spacer **210** and a second spacer **220**.

[0061] The optical branch cable **1** is disposed to extend in the first direction **D1**. In the present embodiment, plurality of optical branch cables **1** are aligned in parallel in a width direction of the bottom portion **T1** to form a layer of the optical branch cables **1** and are placed on the spacer structure **200** to form three layers of the optical branch cables **1** in a vertical direction.

[0062] FIG. **4** illustrates an example of the first spacer **210**. The first spacer **210** includes a first support portion **211**, a second support portion **212**, and a first holding plate portion **213**. The first support portion **211** and the second support portion **212** can be engaged with the vertically rising portion **T2** to support the first spacer **210**. The first support portion **211** and the second support portion **212** can be engaged with the vertically rising portion **T2** at different positions in the first direction **D1**. In the present embodiment, two first support portions **211** and two second support portions **212** are formed at intervals corresponding to a width distance of the cable laying tray **T** (a distance between the two vertically rising portions **T2**), so that the first spacer **210** is further stably installed on the cable laying tray **T**.

[0063] The first support portion **211** and the second support portion **212** each include an arm portion **214** and a return portion **215**. The arm portion **214** is a portion rising upward from the first holding plate portion **213**. The return portion **215** is a portion connected to the arm portion **214** and extending downward. As illustrated in FIG. **3**, the arm portion **214** and the return portion **215** are engaged with the vertically rising portion **T2**, thereby installing the first spacer **210** on the cable laying tray **T**.

[0064] The optical branch cable **1** can be disposed on an upper portion of the first holding plate portion **213**. The first holding plate portion **213** is a rectangular plate member having a width allowing the first holding plate portion **213** to be housed in the cable laying tray **T**. The two first support portions **211** and the two second support portions **212** are respectively provided at four corners of the first holding plate portion **213**. The first holding plate portion **213** is a portion extending in parallel with the bottom portion **T1** when the first support portion **211** and the second support portion **212** are engaged with the vertically rising portion **T2**. Here, “extending in parallel with the bottom portion **T1**” means that inclination of several degrees is permitted relative to a plane that is completely parallel to the bottom portion **T1**.

[0065] A cord insertion passage **P** configured to allow the branch cord portion **20** of the optical branch cable **1** disposed below the first spacer **210** to be inserted in the cord insertion passage **P** is formed in the first holding plate **213**. As illustrated by a dashed line in FIG. **4**, a portion of the first holding plate **213** is cut out. A cut-out portion of the first holding plate **213** is formed to serve as the cord insertion passage **P**. The cord insertion passage **P** has a dimension that allows the branch cord portion **20** to be inserted through the cord insertion passage **P**.

[0066] FIG. **5** illustrates an example of the second spacer **220** installed on the cable laying tray **T**.

The second spacer **220** includes a third support portion **221**, a fourth support portion **222**, and a second holding plate portion **223**. The third support portion **221** and the fourth support portion **222** can be engaged with the vertically rising portion **T2** to support the second spacer **220**. The third support portion **221** and the fourth support portion **222** can be engaged with the vertically rising portion **T2** at different positions in the first direction **D1**. In the present embodiment, two third support portions **221** and two fourth support portions **222** are formed.

[0067] The second spacer **220** also includes an arm portion **224** and a return portion **225**, similarly to the first spacer **210**. The arm portion **224** and the return portion **225** of the second spacer **220** are engaged with the vertically rising portion **T2**, thereby installing the second spacer **220** on the cable laying tray **T**. The arm portion **224** of the second spacer **220** has a dimension shorter than that of the arm portion **214** of the first spacer **210** in the vertical direction. As a result, when the first spacer **210** and the second spacer **220** are installed on the cable laying tray **T**, the second holding plate **223** is held above the first holding plate **213** as illustrated in FIG. 3.

[0068] The optical branch cable **1** can be disposed on an upper portion of the second holding plate portion **223**. The second holding plate portion **223** is a rectangular plate member having a width allowing the second holding plate portion **223** to be housed in the cable laying tray **T**. The two third support portions **221** and the two fourth support portions **222** are respectively provided at four corners of the second holding plate portion **223**. The second holding plate portion **223** is a portion extending in parallel with the bottom portion **T1** when the third support portion **221** and the fourth support portion **222** are engaged with the vertically rising portion **T2**. The second holding plate portion **223** when the third support portion **221** and the fourth support portion **222** are engaged with the vertically rising part **T2** is located above the first holding plate portion **213** when the first support portion **211** and the second support portion **212** are engaged with the vertically rising portion **T2** (refer to FIG. 3). Similarly to the first spacer **210**, a cord insertion passage configured to allow the branch cord portion **20** of the optical branch cable **1** disposed below the second spacer **220** to be inserted through the cord insertion passage is formed in the second holding plate portion **223** of the second spacer **220**.

[0069] When the first spacer **210** and the second spacer **220** are installed on the cable laying tray **T**, a dimension in the first direction **D1** of the second spacer **220** is larger than that of the first spacer **210**. A distance **L2** in the first direction **D1** from a third engagement position at which the third support portion **221** engages with the vertically rising portion **T2** to a fourth engagement position at which the fourth support portion **222** engages with the vertically rising portion **T2** is larger than a distance **L1** in the first direction **D1** from a first engagement position at which the first support portion **211** engages with the vertically rising portion **T2** to a second engagement position at which the second support portion **212** engages with the vertically rising portion **T2**.

[0070] Next, a description will be given as to installation of the spacer structure **200** and arrangement of the optical branch cable **1**. FIG. 6 illustrates an example of arrangement of the optical branch cables **1** in a first layer. The optical branch cables **1** in the first layer are arranged on the bottom portion **T1**. The optical branch cables **1** in the first layer are aligned in parallel in the width direction of the bottom portion **T1**. The branch cord portion **20** of each of the optical branch cables **1** is drawn from the main cable **10**, passes over the vertically rising portion **T2**, and is lowered from the cable laying tray **T**.

[0071] FIG. 7 illustrates an example of arrangement of the first spacer **210**. The first spacer **210** is installed on the layer of the optical branch cable **1** in the first layer. The first spacer **210** is installed so that the first holding plate portion **213** is disposed above a branched portion from which the branch cord portion **20** of the optical branch cable **1** in the first layer is drawn. The first spacer **210** is also provided to allow the branch cord portion **20** of the optical branch cable **1** in the first layer to pass through the cord insertion passage **P** of the first holding plate portion **213**. The branch cord portion **20** that passed through the cord insertion passage **P** of the first holding plate portion **213** is routed to pass over the vertically rising portion **T2**.

[0072] FIG. 8 illustrates an example of arrangement of the optical branch cables **1** in a second layer. The optical branch cable **1** in the second layer is disposed on the first holding plate portion **213**. The optical branch cables **1** in the second layer are aligned in parallel in the width direction of the bottom portion **T1**. The branch cord portion **20** of each of the optical branch cables **1** is drawn from the main cable **10**, passes over the vertically rising portion **T2**, and is lowered from the cable laying tray **T**.

[0073] Referring back to FIG. 5, the second spacer **220** is installed on the layer of the optical branch cable **1** in the second layer. The second spacer **220** is installed so that the second holding plate portion **223** is located above a branched portion from which the branch cord portion **20** of the optical branch cable **1** in the second layer is drawn. The second spacer **220** is also provided to allow the branch cord portion **20** of the optical branch cable **1** in the second layer to pass through the cord insertion passage of the second holding plate portion **223**. The branch cord portion **20** that passed through the cord insertion passage of the second holding plate portion **223** is routed to pass over the vertically rising portion **T2**.

[0074] Referring back to FIG. 2, the optical branch cable **1** in a third layer is disposed on the second holding plate portion **223**. The optical branch cables **1** in the third layer are aligned in parallel in the width direction of the bottom portion **T1**. The branch cord portion **20** of each of the optical branch cables **1** is drawn from the main cable **10**, passes over the vertically rising portion **T2**, and is lowered from the cable laying tray **T**.

[0075] Next, a description will be given as to a positional relationship between the first holding plate portion **213** and the second holding plate portion **223**. FIG. 9 is an enlarged view of an IX portion in FIG. 3. As illustrated in FIG. 9, the first holding plate portion **213** is located above the bottom portion **T1**, and the second holding plate portion **223** is located above the first holding plate portion **213**. The optical branch cable **1** in the first layer is disposed between the bottom portion **T1** and the first holding plate portion **213**, and the optical branch cable **1** in the second layer is disposed between the first holding plate portion **213** and the second holding plate portion **223**.

[0076] Here, a distance **H1** between the bottom portion **T1** and the first holding plate portion **213** is larger than a distance obtained by totaling a diameter **Dm** of the main cable **10** and a diameter **Db** of the branch cord portion **20**. Therefore, the optical branch cable **1** can be disposed to allow the branch cord portion **20** to pass over the main cable **10** while the main cable **10** is disposed between the bottom portion **T1** and the first holding plate portion **213**.

[0077] Similarly, a distance **H2** between the first holding plate portion **213** and the second holding plate portion **223** is larger than the distance obtained by totaling the diameter **Dm** of the main cable **10** and the diameter **Db** of the branch cord portion **20**. Therefore, the optical branch cable **1** can be disposed to allow the branch cord portion **20** to pass over the main cable **10** while the main cable **10** is disposed between the first holding plate portion **213** and the second holding plate portion **223**.

[0078] The branch cord portion **20** passes over the main cable **10** of another optical branch cable **1** and is lowered from the cable laying tray **T**. As a result, even when the first spacer **210** and the second spacer **220** are installed on the cable laying tray **T**, the first spacer **210** and the second spacer **220** are less likely to press the branch cord portion **20**.

[0079] According to the first spacer **210**, which is a spacer of the present embodiment, since the first holding plate portion **213** can dispose the optical branch cables **1** on the upper portion thereof, the optical branch cables **1** can be disposed in two layers with the first holding plate portion **213** interposed therebetween. As a result, the number of optical branch cables **1** to be housed in a single cable laying tray **T** can be increased. Here, the distance **H1** between the bottom portion **T1** and the first holding plate portion **213** is larger than the distance obtained by totaling the diameter **Dm** of the main cable **10** and the diameter **Db** of the branch cord portion **20**. Accordingly, it is possible to prevent the branch cord portion **20** of the optical branch cable **1** disposed below the first spacer **210** from being pressed by provision of the first spacer **210**.

[0080] According to the first spacer **210**, which is the spacer of the present embodiment, the cord

insertion passage P is formed in the first holding plate portion **213**, thereby shortening a path through which the branch cord portion **20** of the optical branch cable **1** disposed below the first spacer **210** passes.

[0081] According to the first spacer **210**, which is the spacer of the present embodiment, since the arm portion **214** and the return portion **215** are engaged with the vertically rising portion T2, the first spacer **210** is stably installed on the cable laying tray T.

[0082] The spacer structure **200** of the present embodiment enables the optical branch cables **1** to be disposed not only on the first holding plate portion **213** but also on the second holding plate portion **223**, so that the optical branch cables **1** can be disposed in three layers with the first holding plate portion **213** and the second holding plate portion **223** interposed therebetween. As a result, the number of optical branch cables **1** to be housed in a single cable laying tray T can be increased. Here, the distance H2 between the first holding plate portion **213** and the second holding plate portion **223** is configured to be larger than the distance obtained by totaling the diameter Dm of the main cable **10** and the diameter Db of the branch cord portion **20**. Accordingly, it is possible to prevent the branch cord portion **20** of the optical branch cable **1** disposed between the second spacer **220** and the first spacer **210** from being pressed by provision of the second spacer **220**.

[0083] As illustrated in FIG. 2, the branch cord portion **20** is disposed to pass over the vertically rising portion T2 located between the first support portion **211** and the second support portion **212**. The vertically rising portion T2 between the first support portion **211** and the second support portion **212** may be provided with a drop nose as disclosed in U.S. Pat. No. 6,625,373B. Therefore, it is desirable that a portion of the spacer structure **200** is not installed on the vertically rising portion T2 located between the first support portion **211** and the second support portion **212**.

[0084] According to the spacer structure **200** of the present embodiment, the distance L2 in the first direction D1 from the third engagement position to the fourth engagement position is larger than the distance L1 in the first direction D1 from the first engagement position to the second engagement position. As a result, even when the second spacer **220** is provided, the second spacer **220** can be disposed so that the third support portion **221** and the fourth support portion **222** are not disposed on the vertically rising portion T2 located between the first support portion **211** and the second support portion **212**, which is likely to be the shortest path when the branch cord portion **20** is drawn out of the cable laying tray T and connected to the server rack **120**.

[0085] Although the present disclosure has been described in detail and with reference to the specific embodiment, it is clear to those skilled in the art that various changes and modifications can be made without departing from the spirit and scope of the present disclosure. In addition, the number, positions, shapes, and the like of the components described above are not limited to the above-described embodiments, and can be changed to the number, positions, shapes, and the like suitable for implementing the present disclosure.

[0086] In the present embodiment, the spacer structure **200** includes the first spacer **210** and the second spacer **220**, but the number of spacers included in the spacer structure may be three or more.

Claims

1. A spacer installed on a cable laying tray capable of housing an optical branch cable, the spacer comprising: a first support portion; a second support portion; and a first holding plate portion, wherein the cable laying tray is capable of housing the optical branch cable in a housing portion defined by a bottom portion extending in a first direction and a vertically rising portion rising upward from an end portion of the bottom portion in a direction intersecting the first direction, the optical branch cable includes a main cable including a plurality of optical fibers, and a branch cord portion formed by drawing at least one optical fiber from the main cable, the first support portion and the second support portion are capable of being engaged with the vertically rising portion to

support the spacer, and are capable of being respectively engaged with the vertically rising portion at positions different from each other in the first direction, the first holding plate portion is connected to the first support portion and the second support portion, and extends in parallel with the bottom portion when the first support portion and the second support portion are engaged with the vertically rising portion, the first holding plate portion is capable of disposing the optical branch cable on an upper portion of the first holding plate portion, and a distance between the bottom portion and the first holding plate portion is larger than a distance obtained by totaling a diameter of the main cable and a diameter of the branch cord portion.

2. The spacer according to claim 1, wherein a cord insertion passage configured to allow the branch cord portion of the optical branch cable disposed below the spacer to be inserted through the cord insertion passage is formed in the first holding plate portion.

3. The spacer according to claim 1, wherein each of the first support portion and the second support portion includes an arm portion rising upward from the first holding plate portion and a return portion connected to the arm portion and extending downward, and the arm portion and the return portion are engaged with the vertically rising portion.

4. A spacer structure comprising a first spacer that is the spacer according to claim 1 and a second spacer, wherein the second spacer includes a third support portion and a fourth support portion engaged with the vertically rising portion to support the second spacer, the third support portion and the fourth support portion being engaged with the vertically rising portion at positions different from each other in the first direction, and a second holding plate portion connected to the third support portion and the fourth support portion and extending in parallel with the bottom portion when the third support portion and the fourth support portion are engaged with the vertically rising portion, the second holding plate portion when the third support portion and the fourth support portion are engaged with the vertically rising portion is located on an opposite side of the bottom portion with respect to the first holding plate portion when the first support portion and the second support portion are engaged with the vertically rising portion, the second holding plate portion is capable of disposing the optical branch cable on an upper portion of the second holding plate portion, and a distance between the first holding plate portion and the second holding plate portion is larger than a distance obtained by totaling a diameter of the main cable and a diameter of the branch cord portion.

5. The spacer structure according to claim 4, wherein a distance in the first direction from a third engagement position at which the third support portion engages with the vertically rising portion to a fourth engagement position at which the fourth support portion engages with the vertically rising portion is larger than a distance in the first direction from a first engagement position at which the first support portion engages with the vertically rising portion to a second engagement position at which the second support portion engages with the vertically rising portion.
