

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250277955

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

NAKAMURA; Ken

VEHICULAR CAMERA

Abstract

A vehicular camera includes a lens barrel, a circuit board, an imaging element, a first conductive member, and a housing. A large-diameter tubular portion of the housing includes a housing end surface, a first wall, a second wall, a third wall, and a fourth wall. The first conductive member includes a bottom surface portion located between inner and outer surfaces of the housing end surface, a first side surface portion located between the first inner side and outer side surfaces of the first wall, a second side surface portion located between the second inner side and outer surfaces of the second wall, a third side surface portion located between the third inner side and outer side surfaces of the third wall, and a fourth side surface portion located between the fourth inner side and outer side surfaces of the fourth wall.

Inventors: NAKAMURA; Ken (Kanagawa, JP)

Applicant: Panasonic Automotive Systems Co., Ltd. (Kanagawa, JP)

Family ID: 96881203

Appl. No.: 19/053045

Filed: February 13, 2025

Foreign Application Priority Data

JP 2024-030433

Feb. 29, 2024

Publication Classification

Int. Cl.: G02B7/02 (20210101)

U.S. Cl.:

CPC G02B7/02 (20130101);

Background/Summary

TECHNICAL FIELD

[0001] The present disclosure relates to a vehicular camera.

BACKGROUND ART

[0002] With demands for improvements in vehicle safety, introduction of autonomous driving functions and the like in recent years, development of vehicular cameras that are mounted on vehicles and capture the inside and outside of the vehicles have become active (for example, see Patent Literatures 1 to 4).

CITATION LIST

Patent Literature

[0003] Patent Literature 1: U.S. Pat. No. 10,367,984B [0004] Patent Literature 2: U.S. Pat. No. 10,506,141B [0005] Patent Literature 3: U.S. Pat. No. 10,694,090B [0006] Patent Literature 4: JP2017-147648A

SUMMARY OF INVENTION

[0007] Required levels relating to safety, automatic driving functions, and the like, which are required for vehicles, are improved, and further improvement in performance and the like are also required for vehicular cameras.

[0008] The present disclosure relates to a technique for providing a new vehicular camera.

[0009] The present disclosure provides a vehicular camera. The vehicular camera includes a lens barrel including a first tubular portion having a first tubular shape along an optical axis and at least one lens disposed inside the first tubular portion and on the optical axis; a circuit board including a first surface and a second surface opposite to the first surface; an imaging element electrically connected to a circuit of the circuit board and disposed on the first surface of the circuit board on the optical axis; a first conductive member disposed to accommodate at least the circuit board and the imaging element; and a housing made of a resin and disposed to accommodate at least the circuit board and the imaging element, the housing including a second tubular portion having a second tubular shape along the optical axis. The second tubular portion of the housing includes: a housing end surface that at least partially faces the second surface of the circuit board and has a first shape including at least a first side, a second side, a third side, and a fourth side in a plan view of the housing; a first wall having a first inner side surface and a first outer side surface, and extending along the optical axis from the first side of the housing end surface in a direction away from the housing end surface; a second wall having a second inner side surface and a second outer side surface, and extending along the optical axis from the second side of the housing end surface in the direction away from the housing end surface; a third wall having a third inner side surface and a third outer side surface, and extending along the optical axis from the third side of the housing end surface in the direction away from the housing end surface; and a fourth wall having a fourth inner side surface and a fourth outer side surface, and extending along the optical axis from the fourth side of the housing end surface in the direction away from the housing end surface. The first conductive member includes: a bottom surface portion at least partially located between an inner surface of the housing end surface and an outer surface of the housing end surface, and having a second shape at least including a fifth side, a sixth side, a seventh side, and an eighth side in a plan view of the first conductive member; a first side surface portion at least partially extending from the fifth side of the bottom surface portion along the optical axis in a direction away from the bottom surface portion and located between the first inner side surface and the first outer side surface of the first wall of the second tubular portion of the housing; a second side surface portion at least partially extending from the sixth side of the bottom surface portion along the optical axis in the direction away from the bottom surface portion and located between the

second inner side surface and the second outer side surface of the second wall of the second tubular portion of the housing; a third side surface portion at least partially extending from the seventh side of the bottom surface portion along the optical axis in the direction away from the bottom surface portion and located between the third inner side surface and the third outer side surface of the third wall of the second tubular portion of the housing; and a fourth side surface portion at least partially extending from the eighth side of the bottom surface portion along the optical axis in the direction away from the bottom surface portion and located between the fourth inner side surface and the fourth outer side surface of the fourth wall of the second tubular portion of the housing.

[0010] According to the present disclosure, the first conductive member that accommodates at least the circuit board and the imaging element has the bottom surface portion and the side surface portion. At least a part of the bottom surface portion is disposed between the inner surface of the housing end surface and the outer surface of the housing end surface, and at least a part of the side surface portion is disposed between the inner side surface and the outer side surface of the wall of the second tubular portion of the housing. Thus, it is possible to reduce the distance between the inner surface of the housing and a component such as a circuit board disposed inside the housing, and improve a heat dissipation effect.

Description

BRIEF DESCRIPTION OF DRAWINGS

[0011] FIG. 1 is an example of a vehicle, and is a top view of the vehicle on which vehicular cameras are mounted;

[0012] FIG. 2 is a block diagram illustrating a connection example of the vehicular cameras provided in the vehicle shown in FIG. 1, a camera ECU, and a display;

[0013] FIG. 3 is another example of the vehicle, and is a schematic diagram of a cabin of the vehicle on which a vehicular camera is mounted;

[0014] FIG. 4 is a top view of the vehicle in FIG. 3;

[0015] FIG. 5 is a block diagram illustrating a connection example of the vehicular camera provided in the vehicle shown in FIG. 3, a camera ECU, and a display device;

[0016] FIG. 6 is a front perspective view of the vehicular camera according to an embodiment;

[0017] FIG. 7 is a rear perspective view of the vehicular camera according to the embodiment;

[0018] FIG. 8 is an exploded perspective view of the vehicular camera according to the embodiment;

[0019] FIG. 9 is an exploded side view of the vehicular camera according to the embodiment;

[0020] FIG. 10 is a top view of the vehicular camera according to the embodiment;

[0021] FIG. 11 is a cross-sectional view taken along a line I-I in FIG. 9;

[0022] FIG. 12 is a top perspective view showing an inside of a housing;

[0023] FIG. 13 is a perspective view of a second conductive member; and

[0024] FIG. 14 is a bottom perspective view of a lens barrel bracket.

DESCRIPTION OF EMBODIMENTS

[0025] Hereinafter, embodiments that specifically disclose a vehicular camera according to the present disclosure will be described in detail with reference to the drawings as appropriate.

However, unnecessarily detailed descriptions may be omitted. For example, detailed descriptions of already well-known matters and redundant descriptions of substantially the same configuration may be omitted. This is to avoid unnecessary redundancy of the following descriptions and to facilitate understanding of those skilled in the art. It should be noted that the accompanying drawings and the following description are provided for those skilled in the art to fully understand the present disclosure, and are not intended to limit the subject matter described in the claims.

Vehicle on Which Vehicular Camera is Mounted

[0026] FIG. 1 is an example of a vehicle, and is a top view of the vehicle on which vehicular cameras are mounted. As a vehicular camera **100**, a vehicular camera **100A**, a vehicular camera **100B**, a vehicular camera **100C**, and a vehicular camera **100D** are mounted on a vehicle V. The vehicular camera **100A** is a front camera, the vehicular camera **100B** is a rear camera, the vehicular camera **100C** is a right side camera, and the vehicular camera **100D** is a left side camera. The vehicular cameras **100A** to **100D** are, for example, wide-angle cameras having an angle of view of about 180°, and are disposed to capture images showing an entire periphery of the vehicle V.

[0027] For example, the vehicular camera **100A** is provided in a front grille of the vehicle V, and captures an image of a front region in a direction of looking down obliquely with respect to the ground. The vehicular camera **100B** is provided in a roof spoiler of the vehicle V, and captures an image of a rear region in a direction of looking down obliquely with respect to the ground. The vehicular camera **100C** and the vehicular camera **100D** are provided in side mirrors of the vehicle V, and capture images of lateral regions in directions of looking down obliquely with respect to the ground, respectively.

[0028] FIG. 2 is a block diagram illustrating a connection example of the vehicular cameras **100A** to **100D** provided in the vehicle V shown in FIG. 1, a camera ECU **110**, and a display **7**. The camera electronic control unit (ECU) **110** in FIG. 2 synthesizes the images captured by the vehicular cameras **100A** to **100D**, and displays a synthesized image on the display **7** of a navigation system disposed on an instrument panel, for example. An occupant can visually recognize the display **7** and check a situation around the vehicle V.

[0029] FIG. 3 is another example of the vehicle, and is a schematic diagram of a cabin of the vehicle on which the vehicular camera is mounted, and FIG. 4 is a top view of the vehicle in FIG. 3. The vehicle V includes a display device **5** (for example, an electronic rearview mirror) at an attachment position of a rearview mirror which is a front portion between a driver's seat **3** and a passenger seat **4** in a cabin **2**. Further, the vehicle V is provided with the vehicular camera **100** at a rear side of a vehicle body. FIG. 5 is a block diagram illustrating a connection example of the vehicular camera **100** provided in the vehicle V shown in FIG. 3, a camera ECU **111**, and the display device **5**. The camera electronic control unit (ECU) **111** in FIG. 4 processes an image captured by the vehicular camera **100**, and the display device **5** displays the image. The occupant can visually recognize the display device **5** and check a rear situation of the vehicle V.

Embodiment of Vehicular Camera

[0030] FIG. 6 is a front perspective view of the vehicular camera **100** according to an embodiment. FIG. 7 is a rear perspective view of the vehicular camera **100** according to the embodiment. FIG. 8 is an exploded perspective view of the vehicular camera **100** according to the embodiment. FIG. 9 is an exploded side view of the vehicular camera **100** according to the embodiment. FIG. 10 is a top view of the vehicular camera **100** according to the embodiment. FIG. 11 is a cross-sectional view taken along a line I-I in FIG. 10. Coordinates including an X axis along one side of the vehicular camera **100**, a Y axis orthogonal to the X axis and along another side of the vehicular camera **100**, and a Z axis orthogonal to the X axis and the Y axis and along a height direction of the vehicular camera **100** are defined, and are used in the following description.

[0031] The vehicular camera **100** according to the present embodiment includes a ring member **20**, a lens barrel **30**, a circuit board **40**, an imaging element **50**, a housing **60**, a first conductive member **70**, a first resin member **90**, a second conductive member **75**, a second resin member **95**, and a lens barrel bracket **32**. FIGS. 8 and 9 show respective perspective views of the first conductive member **70** and the housing **60**, and a housing module **11** in which the first conductive member **70** and the housing **60** are combined, and show respective perspective views of the second conductive member **75** and the lens barrel bracket **32**, and a bracket module **12** in which the second conductive member **75** and the lens barrel bracket **32** are combined.

[0032] The ring member **20** is implemented by a rectangular annular member having a flat plate shape in a plan view, and is welded to the lens barrel **30**, the housing **60**, and the lens barrel bracket

32 by laser welding. An inner peripheral surface of the ring member **20** faces an outer peripheral surface of a first tubular portion **31** (to be described below) of the lens barrel **30**. An inner diameter of the ring member **20** has a length that allows the first tubular portion **31** of the lens barrel **30** to be inserted.

[0033] The ring member **20** can be formed of, for example, a resin. Accordingly, the ring member **20** can be easily formed at low cost.

[0034] The lens barrel **30** includes the first tubular portion **31** constituting a tubular lens barrel, and at least one lens that is accommodated inside the first tubular portion **31** and arranged on an optical axis L (an axis extending in a direction perpendicular to a paper surface of FIG. **10** and along the Z axis). The first tubular portion **31** has a tubular shape, and holds therein, for example, a lens group including a plurality of lenses. The respective lenses in the lens group are arranged in a state in which respective optical axes L are aligned with each other, and constitute the lens group used for capturing images of the inside and outside of the vehicle body of the vehicle V. The lens barrel **30** can be formed of, for example, a resin. Accordingly, the lens barrel **30** can be easily formed at low cost.

[0035] The circuit board **40** is disposed in an internal space of the housing **60**, and includes a first surface **40a** and a second surface **40b** opposite to the first surface **40a**. However, two or more circuit boards may be provided. The circuit board **40** has a circuit on at least one of the first surface **40a** or the second surface **40b**, but may have a circuit on both surfaces.

[0036] The circuit board **40** has a fourth shape having at least a thirteenth side **41a**, a fourteenth side **41b**, a fifteenth side **41c**, and a sixteenth side **41d** in a plan view of the circuit board **40** (a shape viewed in a direction of the optical axis L, that is, a direction along the Z axis, the same applies hereinafter). A third shape is, for example, a third quadrilateral shape, but may be a triangle or a polygon having pentagons or more sides. The circuit board **40** includes at least a first circuit board end surface **41a1** corresponding to the thirteenth side **41a**, a second circuit board end surface **41b1** corresponding to the fourteenth side **41b**, a third circuit board end surface **41c1** corresponding to the fifteenth side **41c**, and a fourth circuit board end surface **41d1** corresponding to the sixteenth side **41d**, which are located between the first surface **40a** and the second surface **40b**.

[0037] The imaging element **50** is disposed on the first surface **40a** of the circuit board **40** and on the optical axis L of at least one lens of the lens barrel **30**. The imaging element **50** is electrically connected to a circuit of the circuit board **40**, and can capture an image by directing external light to the imaging element **50**.

[0038] The housing **60** is a tubular member having the internal space, and serves to support the lens barrel **30** and accommodate at least the circuit board **40**, the imaging element **50**, and the first conductive member **70**. The housing **60** has a large-diameter tubular portion **61** having a second tubular shape along the optical axis L, and a small-diameter tubular portion **62** along the optical axis L. The large-diameter tubular portion **61** constituting a second tubular portion has a larger cross-sectional area than the small-diameter tubular portion **62**, and has a rectangular cross section. The large-diameter tubular portion **61** accommodates at least the circuit board **40** and the imaging element **50** therein. The small-diameter tubular portion **62** mainly accommodates a connector **80** that secures electrical connection with the outside of the vehicular camera **100** (to be described below). The large-diameter tubular portion **61** and the small-diameter tubular portion **62** may be integrally formed of a resin to be described later, and the large-diameter tubular portion **61** and the small-diameter tubular portion **62** prepared individually in advance may be joined by a method such as welding or screwing.

[0039] FIG. **12** is a top perspective view showing an inside of the housing **60**. The large-diameter tubular portion **61** of the housing **60** includes a housing end surface **69**, a first wall **65a**, a second wall **65b**, a third wall **65c**, and a fourth wall **65d**. The housing end surface **69** at least partially faces the second surface of the circuit board, and has a first shape including at least a first side **69a**, a second side **69b**, a third side **69c**, and a fourth side **69d** in a plan view of the housing. However, the

first side **69a** and the second side **69b** are hidden by the first wall **65a** and the second wall **65b** and cannot be seen in FIG. 12. The first shape is, for example, a first quadrilateral shape, but may be a triangle or a polygon having pentagons or more sides.

[0040] The first wall **65a** includes a first inner side surface **66a** and a first outer side surface **67a**, and extends along the optical axis L from the first side **69a** of the housing end surface **69** in a direction away from the housing end surface **69**. The first wall **65a** further includes a first housing end portion **63a** located between the lens barrel **30** and the housing end surface **69** of the housing **60**, and a first housing protrusion **64a** protruding in a direction away from the first housing end portion **63a** with reference to the housing end surface **69** of the housing **60**.

[0041] The second wall **65b** includes a second inner side surface **66b** and a second outer side surface **67b**, and extends along the optical axis L from the second side **69b** of the housing end surface **69** in the direction away from the housing end surface **69**. The second wall **65b** further includes a second housing end portion **63b** located between the lens barrel **30** and the housing end surface **69** of the housing **60**, and a second housing protrusion **64b** protruding in a direction away from the second housing end portion **63b** with reference to the housing end surface **69** of the housing **60**.

[0042] The third wall **65c** includes a third inner side surface **66c** and a third outer side surface **67c**, and extends along the optical axis L from the third side **69c** of the housing end surface **69** in the direction away from the housing end surface **69**. The third wall **65c** further includes a third housing end portion **63c** located between the lens barrel **30** and the housing end surface **69** of the housing **60**, and a third housing protrusion **64c** protruding in a direction away from the third housing end portion **63c** with reference to the housing end surface **69** of the housing **60**. However, in FIG. 12, the third housing protrusion **64c** is hidden by the third wall **65c** and cannot be seen.

[0043] The fourth wall **65d** includes a fourth inner side surface **66d** and a fourth outer side surface **67d**, and extends along the optical axis L from the fourth side **69d** of the housing end surface **69** in the direction away from the housing end surface **69**. The fourth wall **65d** further includes a fourth housing end portion **63d** located between the lens barrel **30** and the housing end surface **69** of the housing **60**, and a fourth housing protrusion **64d** (see FIG. 9) protruding in a direction away from the fourth housing end portion **63d** with reference to the housing end surface **69** of the housing **60**. However, in FIG. 12, the fourth housing protrusion **64d** is hidden by the fourth wall **65d** and cannot be seen.

[0044] The first conductive member **70** is disposed to accommodate at least the circuit board **40** and the imaging element **50** in the internal space of the housing **60**. The first conductive member **70** serves to shield electromagnetic wave noise coming from the outside of the housing **60** and electromagnetic wave noise to be radiated in the internal space. The first conductive member **70** is, for example, a metal such as aluminum or stainless steel. The first conductive member **70** may be formed by bending a single metal plate or by drawing.

[0045] The first conductive member **70** includes a flat bottom surface portion **71**, a first side surface portion **72a**, a second side surface portion **72b**, a third side surface portion **72c**, and a fourth side surface portion **72d**. The bottom surface portion **71** is at least partially located between an inner surface **69e** of the housing end surface **69** and an outer surface **69f** of the housing end surface **69**, and has a second shape at least including a fifth side **71a**, a sixth side **71b**, a seventh side **71c**, and an eighth side **71d** in a plan view of the first conductive member **70**. The second shape is, for example, a second quadrilateral shape, but may be a triangle or a polygon having pentagons or more sides.

[0046] The first side surface portion **72a** at least partially extends from the fifth side **71a** of the bottom surface portion **71** along the optical axis L in a direction away from the bottom surface portion **71**, and is located between the first inner side surface **66a** and the first outer side surface **67a** of the first wall **65a** of the large-diameter tubular portion **61** of the housing **60**. The second side surface portion **72b** at least partially extends from the sixth side **71b** of the bottom surface portion

71 along the optical axis **L** in the direction away from the bottom surface portion **71**, and is located between the second inner side surface **66b** and the second outer side surface **67b** of the second wall **65b** of the large-diameter tubular portion **61** of the housing **60**. The third side surface portion **72c** at least partially extends from the seventh side **71c** of the bottom surface portion **71** along the optical axis **L** in the direction away from the bottom surface portion **71**, and is located between the third inner side surface **66c** and the third outer side surface **67c** of the third wall **65c** of the large-diameter tubular portion **61** of the housing **60**. The fourth side surface portion **72d** at least partially extends from the eighth side **71d** of the bottom surface portion **71** along the optical axis **L** in the direction away from the bottom surface portion **71**, and is located between the fourth inner side surface **66d** and the fourth outer side surface **67d** of the fourth wall **65d** of the large-diameter tubular portion **61** of the housing **60**.

[0047] That is, in the present embodiment, at least a part of the first conductive member **70** is embedded in the housing end surface **69** of the housing **60** and the four walls to constitute the housing module **11**. Such a structure of the housing module **11** can be achieved by, for example, so-called insert molding in which the first conductive member **70** is embedded in the housing **60** when the housing **60** is molded.

[0048] In a vehicular camera in related art, a shield member corresponding to the first conductive member **70** is disposed on the inner surface of the housing. Further, an internal component such as a circuit board is disposed away from the shield member in order to avoid conduction due to contact with the shield member. As a result, the internal component is disposed away from the inner surface of the housing, and a space is formed around the internal component.

[0049] Since the internal component including the circuit board generate heat, it is necessary to dissipate the generated heat. However, due to the presence of the space, the heat dissipation effect may be reduced, and the function of the vehicular camera may be reduced.

[0050] In the present embodiment, the first conductive member **70** that accommodates at least the circuit board **40** and the imaging element **50** has the bottom surface portion **71** and the side surface portion. At least a part of the bottom surface portion **71** is disposed between the inner surface **69e** of the housing end surface **69** and the outer surface **69f** of the housing end surface **69**, and at least a part of the side surface portion is disposed between the inner side surface and the outer side surface of the wall of the large-diameter tubular portion **61** of the housing **60**. As a result, even when the internal component is disposed close to the inner surface of the housing **60**, contact and conduction with the first conductive member **70** can be avoided. Thus, it is possible to reduce a distance between the inner surface of the housing **60** and the internal component such as the circuit board **40** disposed inside the housing **60**, and improve the heat dissipation effect.

[0051] In addition, a first end portion **73a** (see FIGS. **8** and **9**) of the first side surface portion **72a** of the first conductive member **70** is exposed to the inside of the housing **60** from a part of the first inner side surface **66a** of the first wall **65a** of the large-diameter tubular portion **61** of the housing **60**. The first end portion **73a** is exposed from the first housing end portion **63a** of the first end portion **73a** along the optical axis **L**, and is located more inward than the first housing protrusion **64a** with reference to the optical axis **L**.

[0052] In addition, a second end portion **73b** (see FIG. **8**) of the second side surface portion **72b** of the first conductive member **70** is exposed to the inside of the housing **60** from a part of the second inner side surface **66b** of the second wall **65b** of the large-diameter tubular portion **61** of the housing **60**. The second end portion **73b** is exposed from the second housing end portion **63b** of the second end portion **73b** along the optical axis **L**, and is located more inward than the second housing protrusion **64b** with reference to the optical axis **L**.

[0053] In addition, as shown in FIG. **12**, a third end portion **73c** of the third side surface portion **72c** of the first conductive member **70** is exposed to the inside of the housing from a part of the third inner side surface **66c** of the third wall **65c** of the large-diameter tubular portion **61** of the housing **60**. The third end portion **73c** is exposed from the third housing end portion **63c** of the

third end portion **73c** along the optical axis **L**, and is located more inward than the third housing protrusion **64c** with reference to the optical axis **L**.

[0054] In addition, as shown in FIG. **12**, a fourth end portion **73d** of the fourth side surface portion **72d** of the first conductive member **70** is exposed to the inside of the housing **60** from a part of the fourth inner side surface **66d** of the fourth wall **65d** of the large-diameter tubular portion **61** of the housing **60**. The fourth end portion **73d** is exposed from the fourth housing end portion **63d** of the fourth end portion **73d** along the optical axis **L**, and is located more inward than the fourth housing protrusion **64d** with reference to the optical axis **L**.

[0055] Accordingly, since the end portion of the side surface portion of the first conductive member **70** is exposed to the inside of the housing **60**, a connection with another conductive member such as the second conductive member **75** described later can be secured, and the degree of freedom in designing a shielding effect by the conductive member can be increased.

[0056] FIG. **13** is a perspective view of the second conductive member **75**. The second conductive member **75** is at least partially disposed between the lens barrel **30** and the circuit board **40**.

Similarly to the first conductive member **70**, the second conductive member **75** serves to shield electromagnetic wave noise coming from the outside of the housing **60** and electromagnetic wave noise to be radiated in the internal space. The second conductive member **75** is, for example, a metal such as aluminum or stainless steel. The second conductive member **75** may be formed by bending a single metal plate or by drawing.

[0057] The second conductive member **75** has a planar portion **76** having a third shape including at least a ninth side **76a**, a tenth side **76b**, an eleventh side **76c**, and a twelfth side **76d** in a plan view. The third shape is, for example, a third quadrilateral shape, but may be a triangle or a polygon having pentagons or more sides, or a circle including an ellipse.

[0058] The second conductive member **75** further includes a first contact portion **77a** that is brought into contact with the first end portion **73a** of the first side surface portion **72a** of the first conductive member **70**, in particular, an inner surface of the first end portion **73a**, via a first contact **77a1**.

[0059] Accordingly, since the second conductive member **75** is in contact with the first conductive member **70** is provided, the shielding effect can be improved.

[0060] The second conductive member **75** includes a second contact portion **77b** that is brought into contact with the second end portion **73b** of the second side surface portion **72b** of the first conductive member **70**, in particular, an inner surface of the second end portion **73b**, via a second contact **77b1**. In addition, the second conductive member **75** includes a third contact portion **77c** that is brought into contact with the third end portion **73c** of the third side surface portion **72c** of the first conductive member **70**, in particular, an inner surface of the third end portion **73c**, via a third contact **77c1**. The second conductive member **75** further includes a fourth contact portion **77d** that is brought into contact with the fourth end portion **73d** of the fourth side surface portion **72d** of the first conductive member **70**, in particular, an inner surface of the fourth end portion **73d**, via a fourth contact **77d1**. Accordingly, since the second conductive member **75** is brought into contact with the first conductive member **70** via at least four contacts, the shielding effect by the second conductive member **75** can be reliably ensured.

[0061] In particular, the second conductive member **75** includes a first protrusion **78a** protruding from a first portion **76a1** of the ninth side **76a** of the planar portion **76** toward an inner surface of the first end portion **73a** of the first conductive member **70**. The second conductive member **75** includes a second protrusion **78b** protruding from a second portion **76b1** of the tenth side **76b** toward an inner surface of the second end portion **73b** of the first conductive member **70**. The second conductive member **75** includes a third protrusion **78c** protruding from a third portion **76c1** of the eleventh side **76c** toward an inner surface of the third end portion **73c** of the first conductive member **70**. The second conductive member **75** further includes a fourth protrusion **78d** protruding from a fourth portion **76d1** of the twelfth side **76d** toward an inner surface of the fourth end portion

73d of the first conductive member 70.

[0062] The first end portion 73a of the first side surface portion 72a of the first conductive member 70 is brought into contact with the first protrusion 78a of the second conductive member 75 via the first contact 77a1 of the second conductive member 75. The second end portion 73b of the second side surface portion 72b of the first conductive member 70 is brought into contact with the second protrusion 78b of the second conductive member 75 via the second contact 77b1 of the second conductive member 75. The third end portion 73c of the third side surface portion 72c of the first conductive member 70 is brought into contact with the third protrusion 78c of the second conductive member 75 via the third contact 77c1 of the second conductive member 75. The fourth end portion 73d of the fourth side surface portion 72d of the first conductive member 70 is brought into contact with the fourth protrusion 78d of the second conductive member 75 via the fourth contact 77d1 of the second conductive member 75.

[0063] Accordingly, since the protrusion protruding from the planar portion 76 of the second conductive member 75 is brought into contact with the end portion of the side surface portion of the first conductive member 70 via the contact, the contact between the first conductive member 70 and the second conductive member 75 can be made more reliable. The ninth side 76a, the tenth side 76b, the eleventh side 76c, and the twelfth side 76d may be defined along a portion where the protrusion of each side is bent toward the contact, as indicated by a rectangular broken line in FIG. 13.

[0064] The relationship between the circuit board 40 and the housing 60 will be described. At least a part of the first inner side surface 66a of the first wall 65a of the large-diameter tubular portion 61 of the housing 60 faces the first circuit board end surface 41a1 of the circuit board 40. At least a part of the second inner side surface 66b of the second wall 65b faces the second circuit board end surface 41b1 of the circuit board 40. At least a part of the third inner side surface 66c of the third wall 65c faces the third circuit board end surface 41c1 of the circuit board 40. At least a part of the fourth inner side surface 66d of the fourth wall 65d faces the fourth circuit board end surface 41d1 of the circuit board 40.

[0065] Accordingly, the circuit board 40 can be efficiently disposed inside the large-diameter tubular portion 61 of the housing 60.

[0066] The first resin member 90 has predetermined thermal conductivity and is disposed at least between the second surface 40b of the circuit board 40 and the inner surface 69e of the housing end surface 69 of the housing 60. Accordingly, since the first resin member 90 is disposed between the second surface 40b of the circuit board 40 and the inner surface 69e of the housing end surface 69, it is possible to reduce a space between the second surface 40b and the inner surface 69e and further improve the heat dissipation effect on the heat generated in the internal component.

[0067] The first resin member 90 is also disposed between the first inner side surface 66a of the first wall 65a of the large-diameter tubular portion 61 of the housing 60 and the first circuit board end surface 41a1 of the circuit board 40. In addition, the first resin member 90 is also disposed between the second inner side surface 66b of the second wall 65b of the large-diameter tubular portion 61 of the housing 60 and the second circuit board end surface 41b1 of the circuit board 40. In addition, the first resin member 90 is also disposed between the third inner side surface 66c of the third wall 65c of the large-diameter tubular portion 61 of the housing 60 and the third circuit board end surface 41c1 of the circuit board 40. Further, the first resin member 90 is also disposed between the fourth inner side surface 66d of the fourth wall 65d of the large-diameter tubular portion 61 of the housing 60 and the fourth circuit board end surface 41d1 of the circuit board 40.

[0068] Accordingly, since the first resin member 90 is also disposed between the inner side surface of the wall of the large-diameter tubular portion 61 of the housing 60 and the end surface of the circuit board 40, the heat dissipation effect can be further improved.

[0069] Furthermore, a plurality of first electronic components 42 are disposed on the second surface 40b of the circuit board 40 (see FIG. 9), and the inner surface 69e of the housing end

surface **69** of the housing **60** has a plurality of first recesses **69e1** corresponding to the plurality of first electronic components **42**.

[0070] Accordingly, since the first recesses **69e1** of the inner surface **69e** of the housing end surface **69** correspond to the first electronic components **42** disposed on the second surface **40b** of the circuit board **40**, it is possible to reduce a gap between the inner surface **69e** of the housing end surface **69** and the second surface **40b** of the circuit board **40** and improve the heat dissipation effect.

[0071] In such a structure, the first resin member **90** may be disposed between the plurality of first electronic components **42** and the plurality of first recesses **69e1** of the inner surface **69e** of the housing end surface **69**. Accordingly, since the first resin member **90** is also disposed between the first electronic components **42** and the first recesses **69e1**, the heat dissipation effect can be further improved.

[0072] FIG. **14** is a bottom perspective view of the lens barrel bracket **32**. The lens barrel bracket **32** is a resin member, at least a part of which is disposed between the lens barrel **30** and the first surface **40a** of the circuit board **40**. The lens barrel bracket **32** is connected to the housing **60** via the ring member **20** while supporting the lens barrel **30**. The lens barrel bracket **32** has a fifth shape including at least a seventeenth side **33a**, an eighteenth side **33b**, a nineteenth side **33c**, and a twentieth side **33d** in a plan view. The fifth shape is, for example, a quadrilateral shape, but may be a triangular shape or a polygonal shape having pentagons or more sides.

[0073] The lens barrel bracket **32** includes a first bracket surface **32a**, a second bracket surface **32b** that is opposite to the first bracket surface **32a** and at least partially faces the first surface **40a** of the circuit board **40**, and a bracket end surface **32c** that connects the first bracket surface **32a** and the second bracket surface **32b**. The bracket end surface **32c** includes at least a first bracket end surface **32c1**, a second bracket end surface **32c2**, a third bracket end surface **32c3**, and a fourth bracket end surface **32c4**.

[0074] Here, at least a part of the planar portion **76** of the second conductive member **75** is located between the first bracket surface **32a** and the second bracket surface **32b** of the lens barrel bracket **32**. At least a part of the first protrusion **78a** of the second conductive member **75**, in particular, the first contact **77a1** is exposed from the first bracket end surface **32c1**. At least a part of the second protrusion **78b**, in particular, the second contact **77b1**, is exposed from the second bracket end surface **32c2**. At least a part of the third protrusion **78c**, in particular, the third contact **77c1**, is exposed from the third bracket end surface **32c3**. At least a part of the fourth protrusion **78d**, in particular, the fourth contact **77d1**, is exposed from the fourth bracket end surface **32c4**.

[0075] That is, in the present embodiment, at least a part of the second conductive member **75** is embedded in the lens barrel bracket **32** and constitutes the bracket module **12**. Such a structure of the bracket module **12** can be achieved by, for example, insert molding in which the second conductive member **75** is embedded in the lens barrel bracket **32** when the lens barrel bracket **32** is molded.

[0076] Accordingly, since at least a part of the planar portion **76** of the second conductive member **75** is disposed inside the lens barrel bracket **32**, a distance between the second bracket surface **32b** of the lens barrel bracket **32** and the internal component such as the circuit board **40** disposed inside the housing **60** can be reduced, and the heat dissipation effect can be improved.

[0077] The second resin member **95** has predetermined thermal conductivity and is disposed at least between the first surface **40a** of the circuit board **40** and the second bracket surface **32b** of the lens barrel bracket **32**. Accordingly, a space between the first surface **40a** of the circuit board **40** and the second bracket surface **32b** of the lens barrel bracket **32** can be reduced, and the heat dissipation effect on the heat generated in the internal component can be further improved.

[0078] Further, a plurality of second electronic components **43** are disposed on the first surface **40a** of the circuit board **40** (see FIG. **9**), and the second bracket surface **32b** of the lens barrel bracket **32** has a plurality of second recesses **32b1** corresponding to the plurality of second electronic

components **43**.

[0079] Accordingly, since the second recesses **32b1** of the second bracket surface **32b** correspond to the second electronic components **43** disposed on the first surface **40a** of the circuit board, it is possible to reduce a gap between the second bracket surface **32b** and the second surface **40b** of the circuit board **40** and improve the heat dissipation effect.

[0080] In this structure, the second resin member **95** may be disposed between the plurality of second electronic components **43** disposed on the first surface **40a** of the circuit board **40** and the plurality of second recesses **32b1** of the second bracket surface **32b** of the lens barrel bracket **32**. Accordingly, since the second resin member **95** is also disposed between the second electronic components **43** and the second recesses **32b1**, the heat dissipation effect can be further improved.

[0081] The second resin member **95** can be disposed to surround the imaging element **50** disposed on the first surface **40a** of the circuit board **40**. Accordingly, it is possible to improve the heat dissipation effect while ensuring the function of the imaging element **50**.

[0082] As shown in FIG. **8**, at least a part of the second bracket surface **32b** of the lens barrel bracket **32** may be bonded to the first surface **40a** of the circuit board **40** with at least one adhesive **38**. Accordingly, the circuit board **40** can be stably disposed inside the large-diameter tubular portion **61** of the housing **60**.

[0083] Further, the lens barrel bracket **32** has a first hole **32d** corresponding to the optical axis L and penetrating the first bracket surface **32a** and the second bracket surface **32b**, and the second conductive member **75** has a second hole **76e** corresponding to the first hole **32d** of the lens barrel bracket **32** in the planar portion **76**.

[0084] Accordingly, the first hole **32d** of the lens barrel bracket **32** and the second hole **76e** of the second conductive member **75** correspond to each other, and thus light from the outside can be introduced into the inside of the housing **60**.

[0085] Further, the bottom surface portion **71** of the first conductive member **70** has a third hole **71e** penetrating the bottom surface portion **71**, and the housing **60** has a fourth hole **69g** corresponding to the third hole **71e** of the first conductive member **70** and penetrating the housing end surface **69**. The vehicular camera **100** is provided with the connector **80** that penetrates the third hole **71e** and the fourth hole **69g** and is electrically connected to the circuit of the circuit board **40**. The first resin member **90** is disposed to surround the connector **80**. Accordingly, the connector **80** can ensure electrical connection between the vehicular camera **100**, the outside, and a power supply.

[0086] The connector **80** includes a first connector end **81** disposed inside the housing **60** and electrically connected to the circuit of the circuit board **40**, and a second connector end **82** opposite to the first connector end **81** and disposed in the fourth hole **69g** of the housing end surface **69** of the housing **60**. When the vehicular camera **100** is disposed in the vehicle V, the second connector end **82** of the connector **80** is electrically connected to a wire of the vehicle V. Accordingly, the connector **80** can ensure electrical connection between the vehicular camera **100** and the wire of the vehicle V.

[0087] The first resin member **90** and the second resin member **95** may include a magnetic material such as ferrite. Accordingly, the shielding effect can also be imparted to the resin member.

[0088] The first resin member **90** may be brought into contact with the second resin member **95**. When the first resin member **90** is brought into contact with the second resin member **95**, heat generated from the circuit board **40** can be more efficiently conducted to the housing **60**.

[0089] From the above, at least the following matters are described in the present disclosure.

Components corresponding to those in the embodiment are shown in parentheses, but the present disclosure is not limited thereto. [0090] (1) A vehicular camera (vehicular camera **100**) including:

[0091] a lens barrel (lens barrel **30**) including a first tubular portion (first tubular portion **31**) having a first tubular shape along an optical axis (optical axis L) and at least one lens disposed inside the first tubular portion and on the optical axis; [0092] a circuit board (circuit board **40**)

including a first surface (first surface **40a**) and a second surface (second surface **40b**) opposite to the first surface; [0093] an imaging element (imaging element **50**) electrically connected to a circuit of the circuit board and disposed on the first surface of the circuit board on the optical axis; [0094] a first conductive member (first conductive member **70**) disposed to accommodate at least the circuit board and the imaging element; and [0095] a housing (housing **60**) made of a resin, the housing being disposed to accommodate at least the circuit board and the imaging element and including a second tubular portion (large-diameter tubular portion **61**) having a second tubular shape along the optical axis, in which [0096] the second tubular portion of the housing includes: [0097] a housing end surface (housing end surface **69**) that at least partially faces the second surface of the circuit board and has a first shape including at least a first side (first side **69a**), a second side (second side **69b**), a third side (third side **69c**), and a fourth side (fourth side **69d**) in a plan view of the housing; [0098] a first wall (first wall **65a**) having a first inner side surface (first inner side surface **66a**) and a first outer side surface (first outer side surface **67a**), and extending along the optical axis from the first side of the housing end surface in a direction away from the housing end surface; [0099] a second wall (second wall **65b**) having a second inner side surface (second inner side surface **66b**) and a second outer side surface (second outer side surface **67b**), and extending along the optical axis from the second side of the housing end surface in the direction away from the housing end surface; [0100] a third wall (third wall **65c**) having a third inner side surface (third inner side surface **66c**) and a third outer side surface (third outer side surface **67c**), and extending along the optical axis from the third side of the housing end surface in the direction away from the housing end surface; and [0101] a fourth wall (fourth wall **65d**) having a fourth inner side surface (fourth inner side surface **66d**) and a fourth outer side surface (fourth outer side surface **67d**), and extending along the optical axis from the fourth side of the housing end surface in the direction away from the housing end surface, and [0102] the first conductive member includes: [0103] a bottom surface portion (bottom surface portion **71**) at least partially located between an inner surface (inner surface **69e**) of the housing end surface and an outer surface (outer surface **69f**) of the housing end surface, and having a second shape at least including a fifth side (fifth side **71a**), a sixth side (sixth side **71b**), a seventh side (seventh side **71c**), and an eighth side (eighth side **71d**) in a plan view of the first conductive member; [0104] a first side surface portion (first side surface portion **72a**) at least partially extending from the fifth side of the bottom surface portion along the optical axis in a direction away from the bottom surface portion and located between the first inner side surface and the first outer side surface of the first wall of the second tubular portion of the housing; [0105] a second side surface portion (second side surface portion **72b**) at least partially extending from the sixth side of the bottom surface portion along the optical axis in the direction away from the bottom surface portion and located between the second inner side surface and the second outer side surface of the second wall of the second tubular portion of the housing; [0106] a third side surface portion (third side surface portion **72c**) at least partially extending from the seventh side of the bottom surface portion along the optical axis in the direction away from the bottom surface portion and located between the third inner side surface and the third outer side surface of the third wall of the second tubular portion of the housing; and [0107] a fourth side surface portion (fourth side surface portion **72d**) at least partially extending from the eighth side of the bottom surface portion along the optical axis in the direction away from the bottom surface portion and located between the fourth inner side surface and the fourth outer side surface of the fourth wall of the second tubular portion of the housing.

[0108] Accordingly, the first conductive member that accommodates at least the circuit board and the imaging element has the bottom surface portion and the side surface portion. At least a part of the bottom surface portion is disposed between the inner surface of the housing end surface and the outer surface of the housing end surface, and at least a part of the side surface portion is disposed between the inner side surface and the outer side surface of the wall of the second tubular portion of the housing. Thus, it is possible to reduce a distance between the inner surface of the housing

and a component such as a circuit board disposed inside the housing, and improve a heat dissipation effect. [0109] (2) The vehicular camera according to (1), in which [0110] a first end portion (first end portion **73a**) of the first side surface portion of the first conductive member is exposed to an inside of the housing from a part of the first inner side surface of the first wall of the second tubular portion of the housing, [0111] a second end portion (second end portion **73b**) of the second side surface portion of the first conductive member is exposed to the inside of the housing from a part of the second inner side surface of the second wall of the second tubular portion of the housing, [0112] a third end portion (third end portion **73c**) of the third side surface portion of the first conductive member is exposed to the inside of the housing from a part of the third inner side surface of the third wall of the second tubular portion of the housing, and [0113] a fourth end portion (fourth end portion **73d**) of the fourth side surface portion of the first conductive member is exposed to the inside of the housing from a part of the fourth inner side surface of the fourth wall of the second tubular portion of the housing.

[0114] Accordingly, since the end portion of the side surface portion of the first conductive member is exposed to the inside of the housing, a connection with another conductive member can be secured, and the degree of freedom in designing a shielding effect by the conductive member can be increased. [0115] (3) The vehicular camera according to (2), further including: [0116] a second conductive member (second conductive member **75**) at least partially disposed between the lens barrel and the circuit board, in which [0117] the second conductive member includes: [0118] a planar portion (planar portion **76**) having a third shape including at least a ninth side (ninth side **76a**), a tenth side (tenth side **76b**), an eleventh side (eleventh side **76c**), and a twelfth side (twelfth side **76d**) in a plan view of the second conductive member; and [0119] a first contact portion (first contact portion **77a**) that is brought into contact with the first end portion of the first side surface portion of the first conductive member via a first contact (first contact **77a1**).

[0120] Accordingly, since the second conductive member in contact with the first conductive member is provided, the shielding effect can be improved. [0121] (4) The vehicular camera according to (3), in which [0122] the second conductive member further includes: [0123] a second contact portion (second contact portion **77b**) that is brought into contact with the second end portion of the second side surface portion of the first conductive member via a second contact (second contact **77b1**); [0124] a third contact portion (third contact portion **77c**) that is brought into contact with the third end portion of the third side surface portion of the first conductive member via a third contact (third contact **77c1**); and [0125] a fourth contact portion (fourth contact portion **77d**) that is brought into contact with the fourth end portion of the fourth side surface portion of the first conductive member via a fourth contact (fourth contact **77d1**).

[0126] Accordingly, since the second conductive member is brought into contact with the first conductive member via at least four contacts, the shielding effect by the second conductive member can be reliably ensured. [0127] (5) The vehicular camera according to (4), in which [0128] the second conductive member further includes: [0129] a first protrusion (first protrusion **78a**) protruding from a first portion (first portion **76a1**) of the ninth side of the planar portion toward an inner surface of the first end portion of the first conductive member; [0130] a second protrusion (second protrusion **78b**) protruding from a second portion (second portion **76b1**) of the tenth side of the planar portion toward an inner surface of the second end portion of the first conductive member; [0131] a third protrusion (third protrusion **78c**) protruding from a third portion (third portion **76c1**) of the eleventh side of the planar portion toward an inner surface of the third end portion of the first conductive member; and [0132] a fourth protrusion (fourth protrusion **78d**) protruding from a fourth portion (fourth portion **76d1**) of the twelfth side of the planar portion toward an inner surface of the fourth end portion of the first conductive member, [0133] the first end portion of the first side surface portion of the first conductive member is brought into contact with the first protrusion of the second conductive member via the first contact, [0134] the second end portion of the second side surface portion of the first conductive member is brought into

contact with the second protrusion of the second conductive member via the second contact, [0135] the third end portion of the third side surface portion of the first conductive member is brought into contact with the third protrusion of the second conductive member via the third contact, and [0136] the fourth end portion of the fourth side surface portion of the first conductive member is brought into contact with the fourth protrusion of the second conductive member via the fourth contact. [0137] Accordingly, since the protrusion protruding from the planar portion of the second conductive member is brought into contact with the end portion of the side surface portion of the first conductive member via the contact, the contact between the first conductive member and the second conductive member can be made more reliable. [0138] (6) The vehicular camera according to (1), in which [0139] the circuit board has a fourth shape including at least a thirteenth side (thirteenth side **41a**), a fourteenth side (fourteenth side **41b**), a fifteenth side (fifteenth side **41c**), and a sixteenth side (sixteenth side **41d**) in a plan view of the circuit board, [0140] the circuit board includes a first circuit board end surface (first circuit board end surface **41a1**) corresponding to the thirteenth side, a second circuit board end surface (second circuit board end surface **41b1**) corresponding to the fourteenth side, a third circuit board end surface (third circuit board end surface **41c1**) corresponding to the fifteenth side, and a fourth circuit board end surface (fourth circuit board end surface **41d1**) corresponding to the sixteenth side, [0141] at least a part of the first inner side surface of the first wall of the second tubular portion of the housing faces the first circuit board end surface of the circuit board, [0142] at least a part of the second inner side surface of the second wall of the second tubular portion of the housing faces the second circuit board end surface of the circuit board, [0143] at least a part of the third inner side surface of the third wall of the second tubular portion of the housing faces the third circuit board end surface of the circuit board, and [0144] at least a part of the fourth inner side surface of the fourth wall of the second tubular portion of the housing faces the fourth circuit board end surface of the circuit board. [0145] Accordingly, the circuit board can be efficiently disposed inside the second tubular portion of the housing. [0146] (7) The vehicular camera according to (1), further including: [0147] a first resin member (first resin member **90**) having predetermined thermal conductivity and disposed at least between the second surface of the circuit board and the inner surface of the housing end surface of the housing. [0148] Accordingly, the first resin member can reduce the space between the second surface of the circuit board and the inner surface of the housing end surface, and can further improve the heat dissipation effect on the heat generated in the internal component. [0149] (8) The vehicular camera according to (6), in which [0150] the first resin member is disposed [0151] between the first inner side surface of the first wall of the second tubular portion of the housing and the first circuit board end surface of the circuit board, [0152] between the second inner side surface of the second wall of the second tubular portion of the housing and the second circuit board end surface of the circuit board, [0153] between the third inner side surface of the third wall of the second tubular portion of the housing and the third circuit board end surface of the circuit board, and [0154] between the fourth inner side surface of the fourth wall of the second tubular portion of the housing and the fourth circuit board end surface of the circuit board. [0155] Accordingly, since the first resin member is also disposed between the inner side surface of the wall of the second tubular portion of the housing and the end surface of the circuit board, the heat dissipation effect can be further improved. [0156] (9) The vehicular camera according to (7), in which [0157] the inner surface of the housing end surface of the housing has a plurality of first recesses (first recesses **69e1**) corresponding to a plurality of first electronic components (first electronic components **42**) disposed on the second surface of the circuit board. [0158] Accordingly, since the first recesses of the inner surface of the housing end surface correspond to the first electronic components disposed on the second surface of the circuit board, a gap between the inner surface of the housing end surface and the second surface of the circuit board can be reduced, and the heat dissipation effect can be improved. [0159] (10) The vehicular

camera according to (9), in which [0160] the first resin member is disposed between the plurality of first electronic components disposed on the second surface of the circuit board and the plurality of first recesses of the inner surface of the housing end surface of the housing.

[0161] Accordingly, since the first resin member is also disposed between the first electronic components and the first recesses, the heat dissipation effect can be further improved. [0162] (11) The vehicular camera according to (5), further including: [0163] a lens barrel bracket (lens barrel bracket **32**) made of a resin, at least a part of which is disposed between the lens barrel and the first surface of the circuit board, in which [0164] the lens barrel bracket includes: [0165] a first bracket surface (first bracket surface **32a**); [0166] a second bracket surface (second bracket surface **32b**) that is opposite to the first bracket surface and at least partially faces the first surface of the circuit board; and [0167] a bracket end surface (bracket end surface **32c**) that connects the first bracket surface and the second bracket surface and includes at least a first bracket end surface (first bracket end surface **32c1**), a second bracket end surface (second bracket end surface **32c2**), a third bracket end surface (third bracket end surface **32c3**), and a fourth bracket end surface (fourth bracket end surface **32c4**), [0168] at least a part of the planar portion of the second conductive member is located between the first bracket surface and the second bracket surface of the lens barrel bracket, [0169] at least a part of the first protrusion of the second conductive member is exposed from the first bracket end surface, [0170] at least a part of the second protrusion of the second conductive member is exposed from the second bracket end surface, [0171] at least a part of the third protrusion of the second conductive member is exposed from the third bracket end surface, and [0172] at least a part of the fourth protrusion of the second conductive member is exposed from the fourth bracket end surface.

[0173] Accordingly, since at least a part of the planar portion of the second conductive member is disposed inside the lens barrel bracket, a distance between the second bracket surface of the lens barrel bracket and the component such as the circuit board disposed inside the housing can be reduced, and the heat dissipation effect can be improved. [0174] (12) The vehicular camera according to (11), further including: [0175] a second resin member (second resin member **95**) having predetermined thermal conductivity and disposed at least between the first surface of the circuit board and the second bracket surface of the lens barrel bracket.

[0176] Accordingly, a space between the first surface of the circuit board and the second bracket surface of the lens barrel bracket can be reduced, and the heat dissipation effect on the heat generated in the internal component can be further improved. [0177] (13) The vehicular camera according to (12), in which [0178] the second bracket surface of the lens barrel bracket has a plurality of second recesses (second recesses **32b1**) corresponding to a plurality of second electronic components (second electronic components **43**) disposed on the first surface of the circuit board.

[0179] Accordingly, since the second recesses of the second bracket surface correspond to the second electronic components disposed on the first surface of the circuit board, it is possible to reduce a gap between the second bracket surface and the second surface of the circuit board and improve the heat dissipation effect. [0180] (14) The vehicular camera according to (13), in which [0181] the second resin member is disposed between the plurality of second electronic components disposed on the first surface of the circuit board and the plurality of second recesses of the second bracket surface of the lens barrel bracket.

[0182] Accordingly, since the second resin member is also disposed between the second electronic components and the second recesses, the heat dissipation effect can be further improved. [0183] (15) The vehicular camera according to (12), in which [0184] the second resin member is disposed to surround the imaging element disposed on the first surface of the circuit board.

[0185] Accordingly, it is possible to improve the heat dissipation effect while ensuring the function of the imaging element. [0186] (16) The vehicular camera according to (11), in which [0187] at least a part of the second bracket surface of the lens barrel bracket is bonded to the first surface of

the circuit board with at least one adhesive (adhesive **38**).

[0188] Accordingly, the circuit board can be stably disposed inside the second tubular portion of the housing. [0189] (17) The vehicular camera according to (11), in which [0190] the lens barrel bracket has a first hole (first hole **32d**) corresponding to the optical axis and penetrating the first bracket surface and the second bracket surface, and [0191] the second conductive member has a second hole (second hole **76e**) corresponding to the first hole in the planar portion.

[0192] Accordingly, the first hole of the lens barrel bracket and the second hole of the second conductive member correspond to each other, and thus light from the outside can be introduced into the inside of the housing. [0193] (18) The vehicular camera according to (17), in which [0194] the bottom surface portion of the first conductive member has a third hole (third hole **71e**) penetrating the bottom surface portion, [0195] the housing has a fourth hole (fourth hole **69g**) corresponding to the third hole and penetrating the housing end surface, [0196] the vehicular camera further includes a connector (connector **80**) that penetrates the third hole and the fourth hole and is electrically connected to the circuit of the circuit board, and [0197] the first resin member is disposed to surround the connector.

[0198] Accordingly, the connector can ensure electrical connection between the vehicular camera, the outside, and a power supply. [0199] (19) The vehicular camera according to (18), in which [0200] the connector includes: [0201] a first connector end (first connector end **81**) disposed inside the housing and electrically connected to the circuit of the circuit board; and [0202] a second connector end (second connector end **82**) opposite to the first connector end and disposed in the fourth hole of the housing end surface of the housing, and [0203] when the vehicular camera is disposed in a vehicle, the second connector end of the connector is electrically connected to a wire of the vehicle.

[0204] Accordingly, the connector can ensure electrical connection between the vehicular camera and the wire of the vehicle. [0205] (20) The vehicular camera according to (12), in which [0206] the first resin member and the second resin member include a magnetic material.

[0207] Accordingly, the shielding effect can also be imparted to the resin member.

[0208] Although the embodiments have been described above with reference to the accompanying drawings, the present disclosure is not limited thereto. It is apparent to a person skilled in the art that various modifications, corrections, substitutions, additions, deletions, and equivalents can be conceived within the scope described in the claims, and it is understood that such modifications, corrections, substitutions, additions, deletions, and equivalents also fall within the technical scope of the present disclosure. In addition, components in the embodiment described above may be combined freely in a range without departing from the gist of the invention.

INDUSTRIAL APPLICABILITY

[0209] The present disclosure is useful as a vehicular camera capable of reducing a distance between an inner surface of a housing and a component such as a circuit board disposed inside the housing and improving a heat dissipation effect.

CROSS-REFERENCE TO RELATED APPLICATIONS

[0210] This application is based on and claims priority under 35 USC 119 from Japanese Patent Application No. 2024-030433 filed on Oct. 20, 2023, the contents of which are incorporated herein by reference.

Claims

1. A vehicular camera comprising: a lens barrel including a first tubular portion having a first tubular shape along an optical axis and at least one lens disposed inside the first tubular portion and on the optical axis; a circuit board including a first surface and a second surface opposite to the first surface; an imaging element electrically connected to a circuit of the circuit board and disposed on the first surface of the circuit board on the optical axis; a first conductive member disposed to

accommodate at least the circuit board and the imaging element; and a housing made of a resin and disposed to accommodate at least the circuit board and the imaging element, the housing including a second tubular portion having a second tubular shape along the optical axis, wherein the second tubular portion of the housing includes: a housing end surface that at least partially faces the second surface of the circuit board and has a first shape including at least a first side, a second side, a third side, and a fourth side in a plan view of the housing; a first wall having a first inner side surface and a first outer side surface, and extending along the optical axis from the first side of the housing end surface in a direction away from the housing end surface; a second wall having a second inner side surface and a second outer side surface, and extending along the optical axis from the second side of the housing end surface in the direction away from the housing end surface; a third wall having a third inner side surface and a third outer side surface, and extending along the optical axis from the third side of the housing end surface in the direction away from the housing end surface; and a fourth wall having a fourth inner side surface and a fourth outer side surface, and extending along the optical axis from the fourth side of the housing end surface in the direction away from the housing end surface, and the first conductive member includes: a bottom surface portion at least partially located between an inner surface of the housing end surface and an outer surface of the housing end surface, and having a second shape at least including a fifth side, a sixth side, a seventh side, and an eighth side in a plan view of the first conductive member; a first side surface portion at least partially extending from the fifth side of the bottom surface portion along the optical axis in a direction away from the bottom surface portion and located between the first inner side surface and the first outer side surface of the first wall of the second tubular portion of the housing; a second side surface portion at least partially extending from the sixth side of the bottom surface portion along the optical axis in the direction away from the bottom surface portion and located between the second inner side surface and the second outer side surface of the second wall of the second tubular portion of the housing; a third side surface portion at least partially extending from the seventh side of the bottom surface portion along the optical axis in the direction away from the bottom surface portion and located between the third inner side surface and the third outer side surface of the third wall of the second tubular portion of the housing; and a fourth side surface portion at least partially extending from the eighth side of the bottom surface portion along the optical axis in the direction away from the bottom surface portion and located between the fourth inner side surface and the fourth outer side surface of the fourth wall of the second tubular portion of the housing.

2. The vehicular camera according to claim 1, wherein a first end portion of the first side surface portion of the first conductive member is exposed to an inside of the housing from a part of the first inner side surface of the first wall of the second tubular portion of the housing, a second end portion of the second side surface portion of the first conductive member is exposed to the inside of the housing from a part of the second inner side surface of the second wall of the second tubular portion of the housing, a third end portion of the third side surface portion of the first conductive member is exposed to the inside of the housing from a part of the third inner side surface of the third wall of the second tubular portion of the housing, and a fourth end portion of the fourth side surface portion of the first conductive member is exposed to the inside of the housing from a part of the fourth inner side surface of the fourth wall of the second tubular portion of the housing.

3. The vehicular camera according to claim 2, further comprising: a second conductive member at least partially disposed between the lens barrel and the circuit board, wherein the second conductive member includes: a planar portion having a third shape including at least a ninth side, a tenth side, an eleventh side, and a twelfth side in a plan view of the second conductive member; and a first contact portion that is brought into contact with the first end portion of the first side surface portion of the first conductive member via a first contact.

4. The vehicular camera according to claim 3, wherein the second conductive member further includes: a second contact portion that is brought into contact with the second end portion of the

second side surface portion of the first conductive member via a second contact; a third contact portion that is brought into contact with the third end portion of the third side surface portion of the first conductive member via a third contact; and a fourth contact portion that is brought into contact with the fourth end portion of the fourth side surface portion of the first conductive member via a fourth contact.

5. The vehicular camera according to claim 4, wherein the second conductive member further includes: a first protrusion protruding from a first portion of the ninth side of the planar portion toward an inner surface of the first end portion of the first conductive member; a second protrusion protruding from a second portion of the tenth side of the planar portion toward an inner surface of the second end portion of the first conductive member; a third protrusion protruding from a third portion of the eleventh side of the planar portion toward an inner surface of the third end portion of the first conductive member; and a fourth protrusion protruding from a fourth portion of the twelfth side of the planar portion toward an inner surface of the fourth end portion of the first conductive member, the first end portion of the first side surface portion of the first conductive member is brought into contact with the first protrusion of the second conductive member via the first contact, the second end portion of the second side surface portion of the first conductive member is brought into contact with the second protrusion of the second conductive member via the second contact, the third end portion of the third side surface portion of the first conductive member is brought into contact with the third protrusion of the second conductive member via the third contact, and the fourth end portion of the fourth side surface portion of the first conductive member is brought into contact with the fourth protrusion of the second conductive member via the fourth contact.

6. The vehicular camera according to claim 5, wherein the circuit board has a fourth shape including at least a thirteenth side, a fourteenth side, a fifteenth side, and a sixteenth side in a plan view of the circuit board, the circuit board includes a first circuit board end surface corresponding to the thirteenth side, a second circuit board end surface corresponding to the fourteenth side, a third circuit board end surface corresponding to the fifteenth side, and a fourth circuit board end surface corresponding to the sixteenth side, at least a part of the first inner side surface of the first wall of the second tubular portion of the housing faces the first circuit board end surface of the circuit board, at least a part of the second inner side surface of the second wall of the second tubular portion of the housing faces the second circuit board end surface of the circuit board, at least a part of the third inner side surface of the third wall of the second tubular portion of the housing faces the third circuit board end surface of the circuit board, and at least a part of the fourth inner side surface of the fourth wall of the second tubular portion of the housing faces the fourth circuit board end surface of the circuit board.

7. The vehicular camera according to claim 6, further comprising: a first resin member having predetermined thermal conductivity and disposed at least between the second surface of the circuit board and the inner surface of the housing end surface of the housing.

8. The vehicular camera according to claim 7, wherein the first resin member is disposed between the first inner side surface of the first wall of the second tubular portion of the housing and the first circuit board end surface of the circuit board, between the second inner side surface of the second wall of the second tubular portion of the housing and the second circuit board end surface of the circuit board, between the third inner side surface of the third wall of the second tubular portion of the housing and the third circuit board end surface of the circuit board, and between the fourth inner side surface of the fourth wall of the second tubular portion of the housing and the fourth circuit board end surface of the circuit board.

9. The vehicular camera according to claim 7, wherein the inner surface of the housing end surface of the housing has a plurality of first recesses corresponding to a plurality of first electronic components disposed on the second surface of the circuit board.

10. The vehicular camera according to claim 9, wherein the first resin member is disposed between the plurality of first electronic components disposed on the second surface of the circuit board and

the plurality of first recesses of the inner surface of the housing end surface of the housing.

11. The vehicular camera according to claim 7, further comprising: a lens barrel bracket made of a resin, at least a part of which is disposed between the lens barrel and the first surface of the circuit board, wherein the lens barrel bracket includes: a first bracket surface; a second bracket surface that is opposite to the first bracket surface and at least partially faces the first surface of the circuit board; and a bracket end surface that connects the first bracket surface and the second bracket surface and includes at least a first bracket end surface, a second bracket end surface, a third bracket end surface, and a fourth bracket end surface, at least a part of the planar portion of the second conductive member is located between the first bracket surface and the second bracket surface of the lens barrel bracket, at least a part of the first protrusion of the second conductive member is exposed from the first bracket end surface, at least a part of the second protrusion of the second conductive member is exposed from the second bracket end surface, at least a part of the third protrusion of the second conductive member is exposed from the third bracket end surface, and at least a part of the fourth protrusion of the second conductive member is exposed from the fourth bracket end surface.

12. The vehicular camera according to claim 11, further comprising: a second resin member having predetermined thermal conductivity and disposed at least between the first surface of the circuit board and the second bracket surface of the lens barrel bracket.

13. The vehicular camera according to claim 12, wherein the second bracket surface of the lens barrel bracket has a plurality of second recesses corresponding to a plurality of second electronic components disposed on the first surface of the circuit board.

14. The vehicular camera according to claim 13, wherein the second resin member is disposed between the plurality of second electronic components disposed on the first surface of the circuit board and the plurality of second recesses of the second bracket surface of the lens barrel bracket.

15. The vehicular camera according to claim 12, wherein the second resin member is disposed to surround the imaging element disposed on the first surface of the circuit board.

16. The vehicular camera according to claim 11, wherein at least a part of the second bracket surface of the lens barrel bracket is bonded to the first surface of the circuit board with at least one adhesive.

17. The vehicular camera according to claim 11, wherein the lens barrel bracket has a first hole corresponding to the optical axis and penetrating the first bracket surface and the second bracket surface, and the second conductive member has a second hole corresponding to the first hole in the planar portion.

18. The vehicular camera according to claim 17, wherein the bottom surface portion of the first conductive member has a third hole penetrating the bottom surface portion, the housing has a fourth hole corresponding to the third hole and penetrating the housing end surface, the vehicular camera further includes a connector that penetrates the third hole and the fourth hole and is electrically connected to the circuit of the circuit board, and the first resin member is disposed to surround the connector.

19. The vehicular camera according to claim 18, wherein the connector includes: a first connector end disposed inside the housing and electrically connected to the circuit of the circuit board; and a second connector end opposite to the first connector end and disposed in the fourth hole of the housing end surface of the housing, and when the vehicular camera is disposed in a vehicle, the second connector end of the connector is electrically connected to a wire of the vehicle.

20. The vehicular camera according to claim 12, wherein the first resin member and the second resin member include a magnetic material.
