

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250278123

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

Lin; Che-Hsien et al.

---

### ELECTRONIC DEVICE

---

#### Abstract

An electronic device including a first body, a second body and at least one pivot module is provided. The pivot module includes a first transmission wheel, a linkage assembly, a first sliding member, a first driven member and a first rope. The linkage assembly is connected to the first body and the second body. The first sliding member is connected to the first body and linked to the first transmission wheel. The first driven member is connected to the first transmission wheel and the linkage assembly. The first rope is connected to the first sliding member and the first transmission wheel. The rotation of the first body drives the first driven member and the linkage assembly to move, thereby driving the first transmission wheel to rotate, so as to drive the first sliding member and at least part of the first body to slide relative to the linkage assembly.

---

**Inventors:** Lin; Che-Hsien (Taipei City, TW), Chu; Che-Hsien (Taipei City, TW)

**Applicant:** COMPAL ELECTRONICS, INC. (Taipei City, TW)

**Family ID:** 96881269

**Assignee:** COMPAL ELECTRONICS, INC. (Taipei City, TW)

**Appl. No.:** 19/061957

**Filed:** February 24, 2025

#### Related U.S. Application Data

us-provisional-application US 63561238 20240304

---

#### Publication Classification

**Int. Cl.:** G06F1/16 (20060101)

**U.S. Cl.:**

## Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION [0001] This application claims the priority benefit of U.S. provisional application Ser. No. 63/561,238, filed on Mar. 4, 2024. The entirety of the above-mentioned patent application is hereby incorporated by reference herein and made a part of this specification.

### BACKGROUND

#### Technical Field

[0002] The disclosure relates to an electronic device.

#### Description of Related Art.

[0003] The modern electronic device includes two bodies and a pivot, with the two bodies rotatably connected through the pivot. When the two bodies are relatively flipped, there is a gap between the two bodies due to the structural limitations of the pivot, that is unfavorable for users to view and use the electronic device.

### SUMMARY

[0004] The disclosure provides an electronic device that is convenient to use.

[0005] The electronic device of the disclosure includes a first body, a second body and at least one pivot module. The first body is pivotably connected to the second body. The pivot module includes a first transmission wheel, a linkage assembly, a first sliding member, a first driven member and a first rope. The linkage assembly is connected to the first body and the second body. The first sliding member is connected to the first body and linked to the first transmission wheel. The first driven member is connected to the first transmission wheel and the linkage assembly.

[0006] The first rope is connected to the first sliding member and the first transmission wheel. The rotation of the first body relative to the second body drives the first driven member and the linkage assembly to move, thereby driving the first transmission wheel to rotate. The rotation of the first transmission wheel relative to the first rope drives the first sliding member and at least part of the first body to slide relative to a central axis of the linkage assembly.

[0007] Based on the above, the first body of the electronic device of the disclosure is connected to the linkage assembly of the pivot module. When the first body rotates, the first body leads the first transmission wheel to rotate through the first driven member and the linkage assembly, and the first transmission wheel drives the first sliding member to slide through the first rope. Thereby, at least part of the first body connected to the first sliding member slides relative to the center axis of the linkage assembly while the first body rotates relative to the second body, to improve the convenience of using the electronic device.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0008] FIG. 1 is a schematic diagram of an electronic device according to an embodiment of the disclosure.

[0009] FIG. 2 is another schematic diagram of the electronic device in FIG. 1.

[0010] FIG. 3 is a side view of the electronic device in FIG. 1.

[0011] FIG. 4 is a schematic diagram of the pivot module in FIG. 2.

[0012] FIG. 5 is an exploded view of the pivot module in FIG. 4.

[0013] FIG. 6 is a schematic diagram of the electronic device in FIG. 1 in the second status.

[0014] FIG. 7 is a partially enlarged view of the electronic device in FIG. 6.

[0015] FIG. 8 is a side view of the electronic device in FIG. 6.

[0016] FIG. 9 is a schematic diagram of the pivot module in FIG. 7.

[0017] FIG. 10A is a schematic diagram of an electronic device in the first status according to another embodiment of the disclosure.

[0018] FIG. 10B is a side view of the electronic device in FIG. 10A.

[0019] FIG. 11 is a schematic diagram of the pivot module in FIG. 10A.

[0020] FIG. 12A is a schematic diagram of the electronic device in FIG. 10A in the second status.

[0021] FIG. 12B is a side view of the electronic device in FIG. 12A.

[0022] FIG. 13 is a schematic diagram of the pivot module in FIG. 12A.

## DESCRIPTION OF THE EMBODIMENTS

[0023] FIG. 1 is a schematic diagram of an electronic device according to an embodiment of the disclosure. FIG. 2 is another schematic diagram of the electronic device in FIG. 1. FIG. 3 is a side view of the electronic device in FIG. 1. FIG. 4 is a schematic diagram of the pivot module in FIG. 2. FIG. 5 is an exploded view of the pivot module in FIG. 4. Please refer to FIG. 1 to FIG. 5 at the same time, the electronic device **100** includes a first body **110**, a second body **120**, and at least one pivot module **130**. The first body **110** is pivotally connected to the second body **120** through the pivot module **130**. Each pivot module **130** includes a first driving assembly **1301** and a linkage assembly **131**. The linkage assembly **131** is connected to the first body **110** and the second body **120**. The first driving assembly **1301** of the pivot module **130** includes a first transmission wheel **132a**, a first sliding member **133a**, a first driven member **135a**, and a first rope **134a**. The first driven member **135a** is connected to the first transmission wheel **132a** and the linkage assembly **131**. The first rope **134a** is connected to the first sliding member **133a** and the first transmission wheel **132a**. The first sliding member **133a** is connected to the first body **110**, and is linked to the first transmission wheel **132a** through the first rope **134a**.

[0024] The rotation of the first body **110** relative to the second body **120** leads the first driven member **135a** and the linkage assembly **131** to move, thereby driving the first transmission wheel **132a** to rotate. The rotation of the first transmission wheel **132a** relative to the first rope **134a** drives the first sliding member **133a** and at least part of the first body **110** to slide relative to the second body **120**. Thereby, a first function module **111** of the first body **110** may slide relative to a center axis **L4** of the linkage assembly **131** and a second function module **121** of the second body **120** through the first driving assembly **1301** while rotating. The electronic device **100** may switch between a first status **M1** (shown in FIG. 1) and a second status **M2** (shown in FIG. 6) to improve the convenience of use of the electronic device **100**. The number of pivot modules **130** in this embodiment is two, but not limited thereto. The electronic device **100** includes a linkage rod **140**, and the two pivot modules **130** are connected by the linkage rod **140**, so that the two pivot modules **130** may actsynchronously and stably. The first function module **111** and the second function module **121** may include an input module (for example, a keyboard) and/or a display module, but not limited thereto.

[0025] As shown in FIG. 1 to FIG. 3, the first body **110** of this embodiment further includes a first casing **112**, and the first function module **111** is slidably disposed on the first casing **112**, but not limited thereto. The first sliding member **133a** is connected to the first function module **111**, and may lead the first function module **111** to slide relative to the first casing **112** along a sliding axis **L31**. The second body **120** of this embodiment includes a second casing **122**, and the second function module **121** of the second body **120** is slidably disposed on the second casing **122**, but not limited thereto.

[0026] As shown in FIG. 3 to FIG. 5, the linkage assembly **131** includes a first shaft **1311**, a second shaft **1312**, a linkage portion **1313**, a connecting member **1314**, and a first rack structure **1315a**. The first shaft **1311** is linked to the second shaft **1312** through the linkage portion **1313**. The first shaft **1311** is linked to the first casing **112** of the first body **110**, and the second shaft **1312** is linked

to the second casing **122** of the second body **120**. The first shaft **1311** and the second shaft **1312** are movably sleeved on opposite ends of the connecting member **1314** respectively. The first rack structure **1315a** is formed on the end of the connecting member **1314** adjacent to the first shaft **1311**. The first shaft **1311** and the second shaft **1312** may rotate relative to the connecting member **1314**. The first driven member **135a** is connected to the first shaft **1311** and the first transmission wheel **132a**, so that the first transmission wheel **132a** is linked to the first shaft **1311**.

[0027] The linkage portion **1313** of this embodiment includes two main shaft gears **1316a**, **1316b** and a linkage gear **1317**. The two main shaft gears **1316a**, **1316b** are sleeved on the first shaft **1311** and the second shaft **1312** along the corresponding two main axes **L11**, **L12** respectively. The linkage gear **1317** is disposed between the two main shaft gears **1316a**, **1316b** along a connecting axis **L2** and engages with the two main shaft gears **1316a**, **1316b**. The two main axes **L11**, **L12** are parallel to each other, and the connecting axis **L2** and the sliding axis **L31** are perpendicular to the two main axes **L11**, **L12**. The center axis **L4** of the linkage assembly **131** is intersected with and is perpendicular to the connecting axis **L2**.

[0028] The linkage assembly **131** further includes a first bracket **137a** and a second bracket **137b**. The first bracket **137a** is connected to the first casing **112** of the first body **110** and includes two components **1371a**. The second bracket **137b** is connected to the second casing **122** of the second body **120** and includes two components **1371b**. The first shaft **1311** is fixedly connected to the first bracket **137a**, and may move with the first bracket **137a**. The first driven member **135a** and the connecting member **1314** (the first rack structure **1315a**) are rotatably connected to the first bracket **137a**, and are located between the two components **1371a**. The second shaft **1312** is fixedly connected to the second bracket **137b**, and may move with the second shaft **1312**.

[0029] When the first body **110** (the first bracket **137a**) rotates relative to the second body **120**, the first shaft **1311** is driven to rotate the main shaft gear **1316a**, thereby driving the linkage gear **1317** to rotate, which in turn drives the main shaft gear **1316b** to rotate, and leading to the rotation of the second shaft **1312** (the second bracket **137b**). The second body **120** is driven by the linkage assembly **131** to rotate relative to the first body **110**. The first shaft **1311** and the second shaft **1312** may rotate in opposite directions from each other. For example, when the first shaft **1311** is rotated in a clockwise direction, the second shaft **1312** is rotated in a counterclockwise direction. The linkage way of the first shaft **1311** and the second shaft **1312** (i.e., the structure of the linkage assembly **131**) is not limited to this embodiment.

[0030] As shown in FIG. 4 and FIG. 5, the first driven member **135a** includes a plurality of gears. In this embodiment, the number of gears is two, but not limited thereto. The two gears **1351a**, **1352a** are engaged with each other. A rod **138** of the gear **1351a** is connected to the first transmission wheel **132a**, and the gear **1352a** is engaged with the first rack structure **1315a** of the linkage assembly **131**. In this embodiment, the number of teeth of the two gears **1351a**, **1352a** is the same, but not limited thereto. In an embodiment not shown, the number of teeth of the two gears **1351a**, **1352a** may be different, to adjust the moving distance of the first sliding member **133a** on the sliding axis **L31** by the ratio of the number of teeth of the two gears **1351a**, **1352a**. The linkage rod **140** may be connected to the gear **1351a**. In an embodiment not shown, the number of gears of the first driven member **135a** may be three, four, or any arbitrary number. In an embodiment not shown, the number of gears of the first driven member **135a** may be one, and the gear may be connected to the first transmission wheel **132a** and the linkage rod **140**, and engaged with the first rack structure **1315a**.

[0031] As shown in FIG. 3, the first rope **134a** winds around at least part of the first transmission wheel **132a**. In this embodiment, the first rope **134a** winds around the entire first transmission wheel **132a**, in other words, the number of turns of the first rope **134a** winding around the first transmission wheel **132a** is one turn, but not limited thereto. By adjusting the number of turns of the first rope **134a**, the contact area between the first rope **134a** and the first transmission wheel **132a** may be adjusted, thereby adjusting the friction between the first rope **134a** and the first

transmission wheel **132a**. The first rope **134a** starts winding around the first transmission wheel **132a** from the edge farther from the first function module **111**, and after winding one turn, the first rope **134a** leaves the first transmission wheel **132a** from the same edge of the first transmission wheel **132a**, but not limited thereto.

[0032] The winding way and the number of turns of the first rope **134a** are not limited to this embodiment. In an embodiment not shown, the first rope **134a** may only abut against a part of the first transmission wheel **132a**. That is, the number of turns of the first rope **134a** may be less than one turn. In an embodiment not shown, the number of turns of the first rope **134a** may be greater than one turn. In an embodiment not shown, the first rope **134a** may start winding around the first transmission wheel **132a** from the edge closer to the first function module **111**, and leave the first transmission wheel **132a** from the same edge of the first transmission wheel **132a**.

[0033] The first driving assembly **1301** of the pivot module **130** further includes a first adjustment member **136a**. The shape of the first sliding member **133a** is, for example, U-shaped, but not limited thereto. One end of the first rope **134a** is fixed to the first sliding member **133a**, and the other end is connected to the first adjustment member **136a**. The first adjustment member **136a** is used to adjust the friction between the first transmission wheel **132a** and the first rope **134a**. Even if the friction between the first transmission wheel **132a** and the first rope **134a** decreases due to long-term use, the first rope **134a** may be maintained in a tightened state through the first adjustment member **136a**, thereby maintaining the certain friction between the first transmission wheel **132a** and the first rope **134a**, allowing the first transmission wheel **132a** to rotate and displace stably. The first adjustment member **136a** includes, for example, a stick **1361** and a nut **1362**, but not limited thereto. The stick **1361** is connected to the first rope **134a** and the first sliding member **133a**. The nut **1362** is movably connected to the stick **1361**, and the movement of the nut **1362** relative to the stick **1361** may adjust the relative position between the stick **1361** and the first sliding member **133a**.

[0034] As shown in FIG. 3 to FIG. 5, the pivot module **130** of this embodiment further includes a second driving assembly **1302**. The second driving assembly **1302** has a structure similar to the first driving assembly **1301**. Specifically, the second driving assembly **1302** of the pivot module **130** includes a second transmission wheel **132b**, a second sliding member **133b**, a second rope **134b**, a second driven member **135b**, and a second adjustment member **136b**. The linkage assembly **131** further includes a second rack structure **1315b**, the second rack structure **1315b** is formed on the other end of the connecting member **1314** near the second shaft **1312**. The second sliding member **133b** is connected to the second function module **121** of the second body **120**, and may lead the second function module **121** to slide relative to the second casing **122** along the sliding axis **L31**.

[0035] The second driven member **135b** is connected to the second transmission wheel **132b** and the second shaft **1312** of the linkage assembly **131**, thereby linking the second transmission wheel **132b** to the second shaft **1312**. The second driven member **135b** includes two gears **1351b**, **1352b**. The gears **1351b**, **1352b** are engaged with each other. The gear **1351b** is connected to the second transmission wheel **132b**, and the gear **1352b** is engaged with the second rack structure **1315b**. The linkage rod **140** is connected to the gear **1351b**. The second sliding member **133b** is linked to the second transmission wheel **132b**. One end of the second rope **134b** is fixedly connected to the second sliding member **133b**, and the other end is connected to the second adjustment member **136b**. The second rope **134b** surrounds and connects to the second transmission wheel **132b**. The second driven member **135b** and the connecting member **1314** (the second rack structure **1315b**) are rotatably connected to the second bracket **137b** and located between the two components **1371b**.

[0036] The rotation of the first body **110** relative to the second body **120** leads the linkage assembly **131** to move, thereby driving the second body **120** to rotate relative to the first body **110**, and leading the second driven member **135b** to drive the second transmission wheel **132b** to rotate. The

rotation of the second transmission wheel **132b** relative to the second rope **134b** drives the second sliding member **133b** and the second function module **121** of the second body **120** to slide along the sliding axis **L32** relative to the first body **110**. The two sliding axes **L31**, **L32** are parallel to each other.

[0037] FIG. 1 to FIG. 4 shown the electronic device **100** in the first status **M1**. In the first status **M1**, a first outer surface **113** of the first function module **111** of the first body **110** faces towards a second outer surface **123** of the second function module **121** of the second body **120**, the first body **110** is parallel to the second body **120**, and the electronic device **100** is closed. A projection of the first function module **111** to the first casing **112** is completely located on the first casing **112**, and a projection of the linkage assembly **131** to the first casing **112** is completely located on the first casing **112**. There is a distance **D1** between an end **114** of the first function module **111** and an end **115** of the first casing **112**. In this embodiment, the distance **D1** is greater than zero, but not limited thereto.

[0038] A projection of the second function module **121** to the second casing **122** is completely located on the second casing **122**, and a projection of the linkage assembly **131** to the second casing **122** is completely located on the second casing **122**. There is a distance **D2** between an end **124** of the second function module **121** and an end **125** of the second casing **122**. The distance **D1** is equal to the distance **D2**, but not limited thereto. The first sliding member **133a** and the second sliding member **133b** are in the position shown in FIG. 4. The sliding axes **L31**, **L32** are parallel to the connecting axis **L2**.

[0039] FIG. 6 is a schematic diagram of the electronic device in FIG. 1 in the second status. FIG. 7 is a partially enlarged view of the electronic device in FIG. 6. FIG. 8 is a side view of the electronic device in FIG. 6. FIG. 9 is a schematic diagram of the pivot module in FIG. 7. Please refer to FIG. 6 to FIG. 9 at the same time. When switching the electronic device **100** from the first status **M1** to the second status **M2**, the first body **110** (the first bracket **137a**) may be forced to rotate relative to the second body **120**, thereby leading the first shaft **1311** to rotate. The first driving assembly **1301** (i.e., the first transmission wheel **132a**, the first sliding member **133a**, the first rope **134b**, the first driven member **135a**, and the first adjustment member **136a**) is led by the first bracket **137a** to rotate relative to the first rack structure **1315a** of the linkage assembly **131** with the main axis **L11** as the axis.

[0040] Since the gear **1352a** of the first driven member **135a** is engaged with the first rack structure **1315a**, the rotation of the first driving assembly **1301** causes the gear **1352a** to rotate relative to the first rack structure **1315a** and the first bracket **137a**, thereby driving the gear **1351a** to rotate. The first transmission wheel **132a** is led by the gear **1351a** to rotate relative to the first rope **134a**, to drive the first sliding member **133a** to lead the first function module **111** of the first body **110** to slide relative to the first casing **112** along the sliding axis **L31**.

[0041] During the rotation process of the first shaft **1311**, the second shaft **1312** is led by the first shaft **1311** through the linkage portion **1313**, causing the second body **120** (the second bracket **137b**) to rotate relative to the first body **110**. The second driving assembly **1302** (i.e., the second transmission wheel **132b**, the second sliding member **133b**, the second rope **134b**, the second driven member **135b**, and the second adjustment member **136b**) is led by the second bracket **137b** to rotate relative to the second rack structure **1315b**. Thereby, the gears **1351b**, **1352b** of the second driven member **135b** are led by the second rack structure **1315b** to drive the second transmission wheel **132b** to rotate relative to the second rope **134b**, causing the second sliding member **133b** to lead the second function module **121** of the second body **120** to slide relative to the second casing **122** along the sliding axis **L32**. The first function module **111** and the second function module **121** move closer to each other.

[0042] The first body **110** continues to be forced until the first body **110** and the second body **120** relatively move to the position shown in FIG. 6. The electronic device **100** switches to the second status **M2**. In the second status **M2**, the angle between the first function module **111** and the second

function module **121** is 180 degrees, but not limited thereto. An edge **116** of the first outer surface **113** of the first function module **111** is closely attached to an edge **126** of the second outer surface **123** of the second function module **121**, to increase the continuity of the first outer surface **113** and the second outer surface **123**. The projection of the first function module **111** to the first casing **112** is partially located on the first casing **112**, and the projection of the second function module **121** to the second casing **122** is partially located within the second casing **122**. The first function module **111** and the second function module **121** jointly cover the pivot module **130** from the viewing angle in FIG. 6. The distance D3 between the end **114** of the first function module **111** and the end **115** of the first casing **112** is greater than the distance D1 (shown in FIG. 1) in the first status M1. The distance D4 between the end **124** of the second function module **121** and the end **125** of the second casing **122** is greater than the distance D2 (shown in FIG. 1) in the first status M1. The distance D3 is equal to the distance D4, but not limited thereto. The two sliding axes L31, L32 are perpendicular to the connecting axis L2.

[0043] When switching the electronic device **100** from the second status M2 to the first status M1, the first body **110** is forced to rotate towards the second body **120**. The first body **110** leads the first driving assembly **1301** and the linkage assembly **131** to move, causing the first function module **111** and the first casing **112** to rotate, and the first function module **111** to slide relative to the first casing **112**. Simultaneously, the linkage assembly **131** drives the second driving assembly **1302** to move, causing the second function module **121** and the second casing **122** to rotate, and the second function module **121** to slide relative to the second casing **122**. Thereby, the electronic device **100** moves from the position shown in FIG. 8 (the second status M2) to the position shown in FIG. 3 (the first status M1).

[0044] It can be understood that during the switching process of the electronic device **100** between the first status M1 and the second status M2, the first body **110** (the first function module **111** and the first casing **112**) rotates with the main axis L11 as the axis, and the first function module **111** slides relative to the first casing **112** along the sliding axis L31. The second body **120** (the second function module **121** and the second casing **122**) rotates with the main axis L12 as the axis, and the second function module **121** slides relative to the second casing **122** along the sliding axis L32.

[0045] FIG. 10A is a schematic diagram of an electronic device in the first status according to another embodiment of the disclosure. FIG. 10B is a side view of the electronic device in FIG.

[0046] 10A. FIG. 11 is a schematic diagram of the pivot module in FIG. 10A. FIG. 12A is a schematic diagram of the electronic device in FIG. 10A in a second status. FIG. 12B is a side view of the electronic device in FIG. 12A. FIG. 13 is a schematic diagram of the pivot module in FIG. 12A. Please refer to FIG. 2 and FIG. 10A to FIG. 13 at the same time, the electronic device **100a** of this embodiment is similar to the previous embodiment. The difference between the two is that the first sliding member **133c** of the linkage assembly **131a** of this embodiment is connected to the first casing **112a** of the first body **110a** to lead the first body **110a** to slide relative to the center axis LA of the linkage assembly **131a** and the second body **120a**. The second sliding member **133d** is connected to the second casing **122a** of the second body **120a** to lead the second body **120a** to slide relative to the first body **110a**. The first function module **111a** is fixedly disposed on the first casing **112a**, and the second function module **121a** is fixedly disposed on the second casing **122a**. The first bracket **137c** includes a slot **1372c** extending in a direction parallel to the sliding axis L31, and the second bracket **137d** includes a slot **1372d** extending in a direction parallel to the sliding axis L31. The slots **1372c**, **1372d** are formed on the components **1371c**, **1371d**.

[0047] The edge **116a** of the first outer surface **113a** is an end of the first casing **112a**. The edge **126a** of the second outer surface **123a** is an end of the second casing **122a**. A fastener (not shown) passes through the slot **1372c** to connect the first bracket **137c** to the first casing **122a**, and another fastener (not shown) passes through the slot **1372d** to connect the second bracket **137d** to the second casing **122b**. When the electronic device **100a** switches between the first status M1 and the second status M2, the first body **110a** (the first casing **112a**) rotates relative to the second body

**120a** with the main axis **L11** as the axis, and is led by the first sliding member **133c** to slide relative to the first bracket **137c** along the sliding axis **L31**. The second body **120a** (the second casing **122a**) rotates relative to the first body **110a** with the main axis **L12** as the axis, and is led by the second sliding member **133d** to slide relative to the second bracket **137d** along the sliding axis **L32**. The fasteners slide in the slots **1372c**, **1372d**. The electronic device **100a** of this embodiment has similar effect to the previous embodiment, and is not repeated herein.

[0048] The movement way of the first body **110**, **110a** and the second body **120**, **120a** of the electronic device **100**, **100a** is not limited to the above embodiments. For example, in an embodiment not shown, the pivot module **130**, **130a** may only include the linkage assembly **131** and the first driving assembly **1301** (i.e., the first transmission wheel, the first sliding member, the first rope, the first driven member, and the first adjustment member). When the electronic device **100**, **100a** switches between the first status **M1** and the second status **M2**, the first body **110**, **110a** may move relative to the second body **120**, **120a** through the first driving assembly **1301** in any way of the above embodiments, while the second body **120**, **120a** may only be driven by the linkage assembly **131** to rotate relative to the first body **110**, **110a**. That is, only the first outer surface **113**, **113a** may move towards the second outer surface **123**, **123a**, while the second outer surface **123**, **123a** does not move towards the first outer surface **113**, **113a**.

[0049] In summary, the first body of the electronic device of the disclosure is connected to the linkage assembly of the pivot module. When the first body rotates, the first body leads the first transmission wheel to rotate through the first driven member and the linkage assembly, and the first transmission wheel drives the first sliding member to slide through the first rope. Thereby, at least part of the first body connected to the first sliding member slides relative to the center axis of the linkage assembly while the first body rotates relative to the second body, to improve the convenience of using the electronic device.

## Claims

1. An electronic device, comprising: a first body; a second body, the first body is pivotally connected to the second body; and at least one pivot module, wherein each of the at least one pivot module comprises: a first transmission wheel; a linkage assembly, connected to the first body and the second body; a first sliding member, connected to the first body and linked to the first transmission wheel; a first driven member, connected to the first transmission wheel and the linkage assembly; and a first rope, connected to the first sliding member and the first transmission wheel, the rotation of the first body relative to the second body leads the linkage assembly and the first driven member to move, thereby driving the first transmission wheel to rotate, and the rotation of the first transmission wheel relative to the first rope drives the first sliding member and at least a part of the first body to move relative to a center axis of the linkage assembly.
2. The electronic device according to claim 1, wherein the first body comprises a first function module and a first casing, the first function module is slidably connected to the first casing, the first sliding member is connected to the first function module, and is adapted to lead the first function module to slide relative to the first casing.
3. The electronic device according to claim 2, wherein when the electronic device is in a first status, a projection of the first function module to the first casing is completely located on the first casing, and when the electronic device is in a second status, a projection of the first function module to the first casing is partially located on the first casing.
4. The electronic device according to claim 2, wherein a distance between an end of the first function module and an end of the first casing when the electronic device is in a first status is smaller than a distance between the end of the first function module and the end of the first casing when the electronic device is in a second status.
5. The electronic device according to claim 1, wherein the first body comprises a first function



module and a first casing, the first function module is disposed at the first casing, the first sliding member is connected to the first casing, and is adapted to lead the first body to slide relative to the second body.

**6.** The electronic device according to claim 1, wherein the linkage assembly comprises a first shaft, a second shaft and a linkage portion, the first shaft is linked to the first body, the second shaft is linked to the second body, the linkage portion comprises two main shaft gears and a linkage gear, the two main shaft gears are respectively sleeved on the first shaft and the second shaft, the linkage gear is disposed between the two main shaft gears and engages with the two main shaft gears.

**7.** The electronic device according to claim 6, wherein the linkage assembly comprises a first bracket and a second bracket, the first bracket is connected to the first body, the second bracket is connected to the second body, the first shaft is connected to the first bracket, and the second shaft is connected to the second bracket.

**8.** The electronic device according to claim 6, wherein the first driven member comprises a plurality of gears engaging with each other, the linkage assembly comprises a connecting member and a first rack structure, the first shaft and the second shaft are movably sleeved on the connecting member, the first rack structure is formed on the connecting member, one of the gears is connected to the first transmission wheel, and another of the gears engages with the first rack structure.

**9.** The electronic device according to claim 1, wherein each of the at least one pivot module further comprises a first adjustment member, the first rope is connected to the first sliding member and the first adjustment member.

**10.** The electronic device according to claim 1, wherein each of the at least one pivot module further comprises a second transmission wheel, a second sliding member, a second driven member and a second rope, the second driven member is connected to the second transmission wheel and the linkage assembly, the second sliding member is connected to the second body and linked to the second transmission wheel, the second rope is connected to the second sliding member and the second transmission wheel.

**11.** The electronic device according to claim 10, wherein the rotation of the first body relative to the second body leads the linkage assembly to move, thereby driving the second body to rotate relative to the first body, and leads the second driven member to drive the second transmission wheel to rotate, the rotation of the second transmission wheel relative to the second rope drives the second sliding member and at least part of the second body to slide relative to the first body.

**12.** The electronic device according to claim 10, wherein the second body comprises a second function module and a second casing, the second function module is slidably connected to the second casing, the second sliding member is connected to the second function module, and is adapted to lead the second function module to slide relative to the second casing.

**13.** The electronic device according to claim 12, wherein when the electronic device is in a first status, a projection of the second function module to the second casing is completely located on the second casing, when the electronic device is in a second status, a projection of the second function module to the second casing is partially located on the second casing.

**14.** The electronic device according to claim 12, wherein a distance between an end of the second function module and an end of the second casing when the electronic device is in a first status is smaller than a distance between the end of the second function module and the end of the second casing when the electronic device is in a second status.

**15.** The electronic device according to claim 10, wherein the second body comprises a second function module and a second casing, the second function module is disposed at the second casing, the second sliding member is connected to the second casing, and is adapted to lead the second body to slide relative to the first body.

**16.** The electronic device according to claim 10, wherein the linkage assembly comprises a first shaft, a second shaft, a linkage portion, a connecting member and a second rack structure, the first shaft is linked to the second shaft through the linkage portion, the second driven member comprises

a plurality of gears engaging with each other, the first shaft and the second shaft are movably sleeved on the connecting member, the second rack structure is formed on the connecting member, one of the gears is connected to the second transmission wheel, another of the gears engages with the second rack structure.

**17.** The electronic device according to claim 10, wherein each of the at least one pivot module further comprises a second adjustment member, the second rope is connected to the second sliding member and the second adjustment member.

**18.** The electronic device according to claim 1, further comprising a linkage rod, the at least one pivot module comprises two pivot modules, the linkage rod is connected to the two pivot modules.

---