

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12409002

Kind Code

B2

Date of Patent

September 09, 2025

Inventor(s)

Griffiths; Paul G et al.

System and method for monitoring control points during reactive motion

Abstract

Techniques for monitoring a computer-assisted device include a plurality of manipulators, each manipulator being configured to support an instrument, each manipulator having a control point; and a control unit. The control unit is configured to: determine a first spatial configuration of the plurality of control points, the first spatial configuration being prior to a movement of a table separate from the computer-assisted device, and the movement of the table causing motion of at least one control point; determine the movement of the table; determine, based on the movement of the table and the first spatial configuration, an expected spatial configuration of the plurality of control points; determine, based on a comparison of the expected spatial configuration with an actual spatial configuration of the plurality of control points, whether to perform a remedial action; and perform the remedial action in response to a determination to perform the remedial action.

Inventors: Griffiths; Paul G (Santa Clara, CA), Itkowitz; Brandon D. (San Jose, CA), Lynch; Goran A. (Oakland, CA)

Applicant: INTUITIVE SURGICAL OPERATIONS, INC. (Sunnyvale, CA)

Family ID: 55858278

Assignee: INTUITIVE SURGICAL OPERATIONS, INC. (Sunnyvale, CA)

Appl. No.: 18/765427

Filed: July 08, 2024

Prior Publication Data

Document Identifier

Publication Date

US 20240358462 A1

Oct. 31, 2024

Related U.S. Application Data

continuation parent-doc US 18320331 20230519 US 12064201 child-doc US 18765427
continuation parent-doc US 17835604 20220608 US 11737842 20230829 child-doc US 18320331
continuation parent-doc US 16862407 20200429 US 11413103 20220816 child-doc US 17835604
continuation parent-doc US 15522155 US 10682190 20200616 WO PCT/US2015/057670
20151027 child-doc US 16862407
us-provisional-application US 62134252 20150317
us-provisional-application US 62069245 20141027

Publication Classification

Int. Cl.: **G06F17/00** (20190101); **A61B34/20** (20160101); **A61B34/30** (20160101); **A61B34/32** (20160101); **A61B34/35** (20160101); **A61B34/37** (20160101); A61B17/00 (20060101); A61B18/00 (20060101)

U.S. Cl.:

CPC **A61B34/35** (20160201); **A61B34/20** (20160201); **A61B34/30** (20160201); **A61B34/32** (20160201); **A61B34/37** (20160201); A61B17/00234 (20130101); A61B2018/00898 (20130101); A61B2034/2059 (20160201)

Field of Classification Search

CPC: A61B (34/35); A61B (34/20); A61B (34/30); A61B (34/32); A61B (34/37); A61B (17/00234); A61B (2018/00898); A61B (2034/2059); A61B (34/70); A61G (13/02)

USPC: 700/248

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4456961	12/1983	Price et al.	N/A	N/A
4625837	12/1985	Zimmer et al.	N/A	N/A
4640663	12/1986	Niinomi et al.	N/A	N/A
4693665	12/1986	Friederichs et al.	N/A	N/A
4815006	12/1988	Andersson et al.	N/A	N/A
4894855	12/1989	Kresse	N/A	N/A
4928047	12/1989	Arai et al.	N/A	N/A
4945914	12/1989	Allen	N/A	N/A
5144213	12/1991	Sasaki et al.	N/A	N/A
5222499	12/1992	Allen et al.	N/A	N/A
5397323	12/1994	Taylor et al.	N/A	N/A
5402801	12/1994	Taylor	N/A	N/A
5657429	12/1996	Wang et al.	N/A	N/A
5784542	12/1997	Ohm et al.	N/A	N/A
5790307	12/1997	Mick et al.	N/A	N/A
5876325	12/1998	Mizuno et al.	N/A	N/A
5994864	12/1998	Inoue et al.	N/A	N/A
6035228	12/1999	Yanof et al.	N/A	N/A

6120433	12/1999	Mizuno et al.	N/A	N/A
6146200	12/1999	Ito et al.	N/A	N/A
6200024	12/2000	Negrelli	378/197	A61B 6/4476
6246200	12/2000	Blumenkranz et al.	N/A	N/A
6424885	12/2001	Niemeyer et al.	N/A	N/A
6471165	12/2001	Twisselmann	N/A	N/A
6471167	12/2001	Myers et al.	N/A	N/A
6560492	12/2002	Borders	N/A	N/A
6788018	12/2003	Blumenkranz	N/A	N/A
7074179	12/2005	Wang et al.	N/A	N/A
7089612	12/2005	Rocher et al.	N/A	N/A
7155315	12/2005	Niemeyer et al.	N/A	N/A
7155316	12/2005	Sutherland et al.	N/A	N/A
7189246	12/2006	Otsuka et al.	N/A	N/A
7720322	12/2009	Prisco et al.	N/A	N/A
7741802	12/2009	Prisco et al.	N/A	N/A
7763015	12/2009	Cooper et al.	N/A	N/A
7837674	12/2009	Cooper	N/A	N/A
7852030	12/2009	Kamiya	N/A	N/A
8004229	12/2010	Nowlin et al.	N/A	N/A
8041459	12/2010	Sutherland et al.	N/A	N/A
8069714	12/2010	Ortmaier et al.	N/A	N/A
8170717	12/2011	Sutherland et al.	N/A	N/A
8226072	12/2011	Murayama	N/A	N/A
8271130	12/2011	Hourtash et al.	N/A	N/A
8396598	12/2012	Sutherland et al.	N/A	N/A
8400094	12/2012	Schena	N/A	N/A
8457279	12/2012	Saracen	378/68	A61B 6/0487
8464720	12/2012	Pigazzi et al.	N/A	N/A
8541970	12/2012	Nowlin et al.	N/A	N/A
8548629	12/2012	Ortmaier	378/197	A61B 6/4458
8620473	12/2012	Diolaiti et al.	N/A	N/A
8621954	12/2013	Dellon et al.	N/A	N/A
8624537	12/2013	Nowlin et al.	N/A	N/A
8641621	12/2013	Razzaque et al.	N/A	N/A
8749189	12/2013	Nowlin et al.	N/A	N/A
8749190	12/2013	Nowlin et al.	N/A	N/A
8786241	12/2013	Nowlin et al.	N/A	N/A
8816628	12/2013	Nowlin et al.	N/A	N/A
8823308	12/2013	Nowlin et al.	N/A	N/A
8852208	12/2013	Gomez et al.	N/A	N/A
8911499	12/2013	Quaid et al.	N/A	N/A
8918211	12/2013	Diolaiti et al.	N/A	N/A
9060678	12/2014	Larkin et al.	N/A	N/A
9078686	12/2014	Schena	N/A	N/A
9084623	12/2014	Gomez et al.	N/A	N/A

9102058	12/2014	Hofmann et al.	N/A	N/A
9107633	12/2014	Muller	N/A	A61B 6/4458
9107683	12/2014	Houtash et al.	N/A	N/A
9138129	12/2014	Diolaiti	N/A	N/A
9195412	12/2014	Brown et al.	N/A	N/A
9220567	12/2014	Sutherland et al.	N/A	N/A
9295524	12/2015	Schena et al.	N/A	N/A
9296104	12/2015	Swarup et al.	N/A	N/A
9333042	12/2015	Diolaiti et al.	N/A	N/A
9334911	12/2015	Kameta et al.	N/A	N/A
9345544	12/2015	Hourtash et al.	N/A	N/A
9375284	12/2015	Hourtash	N/A	N/A
9387593	12/2015	Bonin et al.	N/A	N/A
9415510	12/2015	Hourtash et al.	N/A	N/A
9468501	12/2015	Hourtash et al.	N/A	N/A
9469034	12/2015	Diolaiti et al.	N/A	N/A
9492235	12/2015	Hourtash et al.	N/A	N/A
9492927	12/2015	Diolaiti et al.	N/A	N/A
9615728	12/2016	Charles et al.	N/A	N/A
9642606	12/2016	Charles et al.	N/A	N/A
9788909	12/2016	Larkin et al.	N/A	N/A
9918681	12/2017	Wallace et al.	N/A	N/A
10028793	12/2017	Griffiths et al.	N/A	N/A
10034717	12/2017	Miller et al.	N/A	N/A
10039473	12/2017	Zhao et al.	N/A	N/A
10064689	12/2017	Swarup et al.	N/A	N/A
10226306	12/2018	Itkowitz et al.	N/A	N/A
10231790	12/2018	Quaid et al.	N/A	N/A
10258414	12/2018	O'Grady et al.	N/A	N/A
10258419	12/2018	Auld et al.	N/A	N/A
10272569	12/2018	Swarup et al.	N/A	N/A
10376324	12/2018	Kerdok et al.	N/A	N/A
10405944	12/2018	Swarup et al.	N/A	N/A
10485617	12/2018	Crawford et al.	N/A	N/A
10555777	12/2019	Griffiths et al.	N/A	N/A
10603135	12/2019	Azizian et al.	N/A	N/A
10617479	12/2019	Itkowitz et al.	N/A	N/A
10624807	12/2019	Itkowitz et al.	N/A	N/A
10682190	12/2019	Griffiths et al.	N/A	N/A
10905500	12/2020	Griffiths et al.	N/A	N/A
10993772	12/2020	Itkowitz et al.	N/A	N/A
11130231	12/2020	Swarup et al.	N/A	N/A
11173005	12/2020	Azizian et al.	N/A	N/A
11179221	12/2020	Swarup et al.	N/A	N/A
11413103	12/2021	Griffiths et al.	N/A	N/A
11419687	12/2021	Itkowitz et al.	N/A	N/A
11426245	12/2021	Quaid et al.	N/A	N/A
11576737	12/2022	Itkowitz et al.	N/A	N/A
11672618	12/2022	Itkowitz et al.	N/A	N/A

11684448	12/2022	Swarup et al.	N/A	N/A
11737842	12/2022	Griffiths et al.	N/A	N/A
11759265	12/2022	Griffiths et al.	N/A	N/A
11806875	12/2022	Swarup et al.	N/A	N/A
11896326	12/2023	Itkowitz et al.	N/A	N/A
12024528	12/2023	Chu et al.	N/A	N/A
12035987	12/2023	Itkowitz et al.	N/A	N/A
12064201	12/2023	Griffiths et al.	N/A	N/A
12179359	12/2023	Swarup et al.	N/A	N/A
12186033	12/2024	Griffiths et al.	N/A	N/A
2001/0013764	12/2000	Blumenkranz et al.	N/A	N/A
2002/0082612	12/2001	Moll et al.	N/A	N/A
2002/0161446	12/2001	Bryan et al.	N/A	N/A
2003/0192758	12/2002	Murata et al.	N/A	N/A
2006/0025668	12/2005	Peterson et al.	N/A	N/A
2006/0101581	12/2005	Blanchard et al.	N/A	N/A
2006/0149418	12/2005	Anvari	N/A	N/A
2007/0096670	12/2006	Hashimoto et al.	N/A	N/A
2007/0185376	12/2006	Wilson et al.	N/A	N/A
2007/0270685	12/2006	Kang et al.	N/A	N/A
2007/0287992	12/2006	Diolaiti et al.	N/A	N/A
2008/0004633	12/2007	Arata et al.	N/A	N/A
2008/0046122	12/2007	Manzo et al.	N/A	N/A
2008/0064921	12/2007	Larkin et al.	N/A	N/A
2008/0065108	12/2007	Diolaiti	N/A	N/A
2008/0125649	12/2007	Meyer et al.	N/A	N/A
2008/0312529	12/2007	Amiot et al.	N/A	N/A
2009/0000136	12/2008	Crampton	N/A	N/A
2009/0024142	12/2008	Ruiz Morales	N/A	N/A
2009/0088774	12/2008	Swarup et al.	N/A	N/A
2009/0209976	12/2008	Rosielle	N/A	N/A
2009/0216372	12/2008	Watanabe et al.	N/A	N/A
2009/0326324	12/2008	Munoz et al.	N/A	N/A
2010/0042097	12/2009	Newton et al.	N/A	N/A
2010/0131102	12/2009	Herzog et al.	N/A	N/A
2010/0138183	12/2009	Jensen et al.	N/A	N/A
2010/0168762	12/2009	Osawa et al.	N/A	N/A
2010/0204713	12/2009	Ruiz Morales	N/A	N/A
2010/0228249	12/2009	Mohr et al.	N/A	N/A
2010/0228264	12/2009	Robinson et al.	N/A	N/A
2010/0275927	12/2009	Saracen	128/845	A61B 6/0487
2010/0286712	12/2009	Won et al.	N/A	N/A
2010/0292843	12/2009	Kariyazaki et al.	N/A	N/A
2011/0015521	12/2010	Faul	N/A	N/A
2011/0054688	12/2010	Ortmaier	700/255	A61B 6/102
2011/0071508	12/2010	Duval et al.	N/A	N/A
2011/0126801	12/2010	Walter	N/A	N/A

2011/0276179	12/2010	Banks et al.	N/A	N/A
2011/0282351	12/2010	Cooper et al.	N/A	N/A
2012/0029694	12/2011	Muller	700/248	A61B 6/4452
2012/0071895	12/2011	Stahler et al.	N/A	N/A
2012/0101508	12/2011	Wook Choi et al.	N/A	N/A
2013/0072822	12/2012	Auchinleck et al.	N/A	N/A
2013/0085510	12/2012	Stefanchik et al.	N/A	N/A
2013/0096701	12/2012	Suorajaervi et al.	N/A	N/A
2013/0110129	12/2012	Reid et al.	N/A	N/A
2013/0123799	12/2012	Smith et al.	N/A	N/A
2013/0152307	12/2012	Bennett-Guerrero	N/A	N/A
2013/0205558	12/2012	Sporer et al.	N/A	N/A
2013/0283980	12/2012	Petrak et al.	N/A	N/A
2013/0327902	12/2012	Frick et al.	N/A	N/A
2013/0338679	12/2012	Rosielle et al.	N/A	N/A
2014/0005488	12/2013	Charles et al.	N/A	N/A
2014/0005555	12/2013	Tesar	N/A	N/A
2014/0005654	12/2013	Batross et al.	N/A	N/A
2014/0033434	12/2013	Jackson	N/A	N/A
2014/0033436	12/2013	Jackson	N/A	N/A
2014/0039517	12/2013	Bowling et al.	N/A	N/A
2014/0039681	12/2013	Bowling et al.	N/A	N/A
2014/0052153	12/2013	Griffiths et al.	N/A	N/A
2014/0052154	12/2013	Griffiths et al.	N/A	N/A
2014/0055489	12/2013	Itkowitz et al.	N/A	N/A
2014/0163736	12/2013	Azizian et al.	N/A	N/A
2014/0222207	12/2013	Bowling et al.	N/A	N/A
2014/0276887	12/2013	Stein et al.	N/A	N/A
2014/0305995	12/2013	Shelton, IV et al.	N/A	N/A
2014/0316252	12/2013	Kwak et al.	N/A	N/A
2014/0316430	12/2013	Hourtash et al.	N/A	N/A
2014/0350387	12/2013	Siewerdsen et al.	N/A	N/A
2014/0358161	12/2013	Hourtash et al.	N/A	N/A
2015/0032126	12/2014	Nowlin et al.	N/A	N/A
2015/0051733	12/2014	Nowlin et al.	N/A	N/A
2015/0113733	12/2014	Diel et al.	N/A	N/A
2015/0117601	12/2014	Keeve et al.	N/A	N/A
2015/0119637	12/2014	Alvarez et al.	N/A	N/A
2015/0150639	12/2014	Diolaiti et al.	N/A	N/A
2015/0224845	12/2014	Anderson et al.	N/A	N/A
2016/0000512	12/2015	Gombert et al.	N/A	N/A
2016/0081754	12/2015	Kostrzewski et al.	N/A	N/A
2016/0098943	12/2015	Valeev et al.	N/A	N/A
2016/0113728	12/2015	Piron et al.	N/A	N/A
2016/0156288	12/2015	Sawamura et al.	N/A	N/A
2016/0242849	12/2015	Crawford et al.	N/A	N/A
2017/0079731	12/2016	Griffiths et al.	N/A	N/A
2017/0143429	12/2016	Richmond et al.	N/A	N/A
2017/0265949	12/2016	Crawford et al.	N/A	N/A

2018/0338808	12/2017	Swarup et al.	N/A	N/A
2018/0344421	12/2017	Cagle et al.	N/A	N/A
2019/0183593	12/2018	Hourtash et al.	N/A	N/A
2019/0192233	12/2018	O'Grady et al.	N/A	N/A
2019/0216550	12/2018	Eyre et al.	N/A	N/A
2019/0216555	12/2018	DiMaio et al.	N/A	N/A
2019/0231460	12/2018	DiMaio et al.	N/A	N/A
2020/0093549	12/2019	Chin et al.	N/A	N/A
2023/0263584	12/2022	Itkowitz et al.	N/A	N/A
2023/0301735	12/2022	Griffiths et al.	N/A	N/A
2023/0372029	12/2022	Griffiths et al.	N/A	N/A
2024/0009837	12/2023	Swarup et al.	N/A	N/A
2024/0115332	12/2023	Itkowitz et al.	N/A	N/A
2024/0315786	12/2023	Itkowitz et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1985773	12/2006	CN	N/A
2910169	12/2006	CN	N/A
101049248	12/2006	CN	N/A
101049697	12/2006	CN	N/A
101064060	12/2006	CN	N/A
101160104	12/2007	CN	N/A
101217913	12/2007	CN	N/A
101222889	12/2007	CN	N/A
201082167	12/2007	CN	N/A
101332137	12/2007	CN	N/A
101449292	12/2008	CN	N/A
101466342	12/2008	CN	N/A
101472546	12/2008	CN	N/A
101720269	12/2009	CN	N/A
101827735	12/2009	CN	N/A
101959656	12/2010	CN	N/A
102046360	12/2010	CN	N/A
101443163	12/2010	CN	N/A
102389334	12/2011	CN	N/A
102429726	12/2011	CN	N/A
101234033	12/2011	CN	N/A
102715924	12/2011	CN	N/A
102727312	12/2011	CN	N/A
102727358	12/2011	CN	N/A
103027818	12/2012	CN	N/A
103221015	12/2012	CN	N/A
103315818	12/2012	CN	N/A
103637895	12/2013	CN	N/A
103720514	12/2013	CN	N/A
103889663	12/2013	CN	N/A
104039629	12/2013	CN	N/A
104002296	12/2015	CN	N/A

3119577	12/1981	DE	N/A
10249786	12/2003	DE	N/A
202014000027	12/2013	DE	N/A
102010038800	12/2023	DE	A61B 34/30
1915963	12/2007	EP	N/A
1974870	12/2007	EP	N/A
2047805	12/2008	EP	N/A
2332477	12/2010	EP	N/A
2332479	12/2010	EP	N/A
2332482	12/2010	EP	N/A
2581073	12/2012	EP	N/A
2735278	12/2013	EP	N/A
2023843	12/2015	EP	N/A
H05138583	12/1992	JP	N/A
H06278063	12/1993	JP	N/A
H07185817	12/1994	JP	N/A
H07328016	12/1994	JP	N/A
H09254079	12/1996	JP	N/A
H09300264	12/1996	JP	N/A
H10100085	12/1997	JP	N/A
H11226062	12/1998	JP	N/A
2000107200	12/1999	JP	N/A
2000300579	12/1999	JP	N/A
2002307344	12/2001	JP	N/A
2002345831	12/2001	JP	N/A
2003131701	12/2002	JP	N/A
2003299674	12/2002	JP	N/A
2004216022	12/2003	JP	N/A
2004223128	12/2003	JP	N/A
2004358239	12/2003	JP	N/A
2006263894	12/2005	JP	N/A
2008259607	12/2007	JP	N/A
2008538301	12/2007	JP	N/A
2010194101	12/2009	JP	N/A
2011212837	12/2010	JP	N/A
2012005557	12/2011	JP	N/A
2012239709	12/2011	JP	N/A
2013252427	12/2012	JP	N/A
2015502768	12/2014	JP	N/A
20060135063	12/2005	KR	N/A
20100067846	12/2009	KR	N/A
WO-9403113	12/1993	WO	N/A
WO-2006039092	12/2005	WO	N/A
WO-2006069288	12/2005	WO	N/A
WO-2006079108	12/2005	WO	N/A
WO-2006124390	12/2005	WO	N/A
WO-2007136768	12/2006	WO	N/A
WO-2007136770	12/2006	WO	N/A
WO-2008002830	12/2007	WO	N/A
WO-2010068005	12/2009	WO	N/A

WO-2011060042	12/2010	WO	N/A
WO-2011060139	12/2010	WO	N/A
WO-2011109041	12/2010	WO	N/A
WO-2011143016	12/2010	WO	N/A
WO-2011143338	12/2010	WO	N/A
WO-2012064528	12/2011	WO	N/A
WO-2012158458	12/2011	WO	N/A
WO-2013048957	12/2012	WO	N/A
WO-2013071057	12/2012	WO	N/A
WO-2013181503	12/2012	WO	N/A
WO-2013181507	12/2012	WO	N/A
WO-2013181516	12/2012	WO	N/A
WO-2014028703	12/2013	WO	N/A
WO-2014146095	12/2013	WO	N/A
WO-2014146107	12/2013	WO	N/A
WO-2014146113	12/2013	WO	N/A
WO-2014146119	12/2013	WO	N/A
WO-2014146120	12/2013	WO	N/A
WO-2015142798	12/2014	WO	N/A
WO-2015142930	12/2014	WO	N/A
WO-2015142943	12/2014	WO	N/A
WO-2015142947	12/2014	WO	N/A
WO-2016069648	12/2015	WO	N/A
WO-2016069655	12/2015	WO	N/A
WO-2016069659	12/2015	WO	N/A
WO-2016069660	12/2015	WO	N/A
WO-2016069661	12/2015	WO	N/A
WO-2016069663	12/2015	WO	N/A
WO-2020257565	12/2019	WO	A61B 34/20

OTHER PUBLICATIONS

The Robo-Doctor Will See You Now (2012) (Year: 2012). cited by examiner

Allied Motion, Patient tables, 2023, 2 pages. cited by applicant

Allied Motion, Surgical Robotic Arm Systems and Hand Tools, 2023, 2 pages. cited by applicant

Extended European Search Report for Application No. 15855456.8, mailed on Sep. 25, 2018, 10 pages. cited by applicant

Extended European Search Report for Application No. EP15854136.7, mailed on Jun. 7, 2018, 11 pages. cited by applicant

Extended European Search Report for Application No. EP15854253, mailed on May 11, 2018, 11 pages. cited by applicant

Extended European Search Report for Application No. EP15854260.5, mailed on Jun. 7, 2018, 8 pages. cited by applicant

Extended European Search Report for Application No. EP15855051.7, mailed on May 3, 2018, 10 pages. cited by applicant

Extended European Search Report for Application No. EP15855097, mailed on Apr. 25, 2018, 11 pages. cited by applicant

Extended European Search Report for Application No. EP15855351.1, mailed on Apr. 30, 2018, 9 pages. cited by applicant

Extended European Search Report for Application No. EP20182993.4, mailed on Oct. 2, 2020, 13 pages. cited by applicant

Extended European Search Report for Application No. EP22178252, mailed on Sep. 30, 2022, 07 pages. cited by applicant

Extended European Search Report for European Application No. 21181826.5 dated Oct. 26, 2021, 8 pages. cited by applicant

Fresenius . . . “A Robot at the Operating Table.” 2019, 06 Pages. cited by applicant

Hesse S., et al., “Lexikon Der Elektrischen Antriebstechnik,” Festo Didactic GmbH & Co. KG, Jan. 1, 2004, 202 pages, XP055260002 [retrieved on Mar. 21, 2016], Retrieved from the Internet: url: http://www.boss.festo-cpx.com/pdf/539265_webprint.pdf/url. cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2015/057656, mailed on Feb. 1, 2016, 11 pages. cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2015/057658, mailed on Feb. 1, 2016, 12 pages. cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2015/057664, mailed on Feb. 1, 2016, 8 pages. cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2015/057669, mailed on Feb. 1, 2016, 9 pages. cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2015/057670, mailed on Feb. 1, 2016, 8 pages. cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2015/057671, mailed on Feb. 1, 2016, 6 pages. cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2015/057673, mailed on Feb. 1, 2016, 10 pages. cited by applicant

Laparoscopic Robot Surgery, Current Perspective and Future Directions, 2020, 10 pages. cited by applicant

Li J., et al., “Vibration Prediction of the Robotic Arm Based on Elastic Joint Dynamics Modeling,” Sensors, Aug. 2022, vol. 22(16), pp. 1-20. cited by applicant

Ma Y, and Li Y. Active Disturbance Compensation Based Robust Control for Speed Regulation System of Permanent Magnet Synchronous Motor, Applied Sciences, (Year: 2019), pp. 1-13. cited by applicant

Macrae M., “The Robo-Doctor Will See You Now,” Medical Equipment and Device Manufacturing, Robotics, The American Society of Mechanical Engineers, May 2012, 8 Pages. cited by applicant

Office Action for Chinese Application No. CN202010672351, mailed Nov. 28, 2023. 29 pages. cited by applicant

Partial Supplementary European Search Report for Application No. EP15855456.8, mailed on May 23, 2018, 11 pages. cited by applicant

Vertut, J., and Coiffet, P., “Robot Technology: Teleoperation and Robotics Evolution and Development,” English translation, Prentice-Hall, Inc., Englewood Cliffs, NJ, USA 1986, vol. 3A, 332 pages. cited by applicant

Wang Y., et al., “Disturbance Compensation based Controller for an Indoor Blimp Robot,” Robotics and Autonomous Systems, (Year: 2020), pp. 1-15. cited by applicant

Extended European Search Report for Application No. EP24210151.7, mailed on May 7, 2025, 11 pages. cited by applicant

Extended European Search Report for Application No. EP25162399.7, mailed on Jun. 26, 2025. 10 pages. cited by applicant

Primary Examiner: Mancho; Ronnie M

Attorney, Agent or Firm: Artegis Law Group, LLC

Background/Summary

RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 18/320,331, entitled “System and Method for Monitoring Control Points During Reactive Motion,” which was filed on May 19, 2023, which is a continuation of U.S. patent application Ser. No. 17/835,604, entitled “System and Method for Monitoring Control Points During Reactive Motion,” which was filed on Jun. 8, 2022, which is a continuation of U.S. patent application Ser. No. 16/862,407, entitled “System and Method for Monitoring Control Points During Reactive Motion,” which was filed on Apr. 29, 2020, which is a continuation of U.S. patent application Ser. No. 15/522,155, entitled “System and Method for Monitoring Control Points During Reactive Motion,” which was filed on Apr. 26, 2017, which is a U.S. National Stage patent application of International Patent Application No. PCT/US2015/057670, entitled “System and Method for Monitoring Control Points During Reactive Motion,” which was filed on Oct. 27, 2015, the benefit of which is claimed, and claims priority to U.S. Provisional Patent Application No. 62/134,252 entitled “System and Method for Monitoring Control Points During Reactive Motion,” which was filed on Mar. 17, 2015 and U.S. Provisional Patent Application No. 62/069,245 entitled “System and Method for Integrated Operating Table,” which was filed Oct. 27, 2014, each of which are hereby incorporated by reference in their entirety.

TECHNICAL FIELD

(1) The present disclosure relates generally to operation of devices with articulated arms and more particularly to monitoring control points during reactive motion.

BACKGROUND

(2) More and more devices are being replaced with autonomous and semiautonomous electronic devices. This is especially true in the hospitals of today with large arrays of autonomous and semiautonomous electronic devices being found in operating rooms, interventional suites, intensive care wards, emergency rooms, and the like. For example, glass and mercury thermometers are being replaced with electronic thermometers, intravenous drip lines now include electronic monitors and flow regulators, and traditional hand-held surgical instruments are being replaced by computer-assisted medical devices.

(3) These electronic devices provide both advantages and challenges to the personnel operating them. Many of these electronic devices may be capable of autonomous or semiautonomous motion of one or more articulated arms and/or end effectors. These one or more articulated arms and/or end effectors each include a combination of links and articulated joints that support motion of the articulated arms and/or end effectors. In many cases, the articulated joints are manipulated to obtain a desired position and/or orientation (collectively, a desired pose) of a corresponding instrument located at a distal end of the links and articulated joints of a corresponding articulated arm. Each of the articulated joints proximal to the instrument provides the corresponding articulated arm with at least one degree of freedom that may be used to manipulate the position and/or orientation of the corresponding instrument. In many cases, the corresponding articulated arms may include at least six degrees of freedom that allow for controlling a x, y, and z position of the corresponding instrument as well as a roll, pitch, and yaw orientation of the corresponding instrument. Each articulated arm may further provide a remote center of motion. In some cases, one or more articulated arms and corresponding remote centers of motion or other points on the articulated arms may be allowed to move in order to track the movement of other parts of the electronic device. For example, when an instrument is inserted into a body opening, such as an incision site or body orifice, on a patient during a surgical procedure and a surgical table on which the patient is placed is undergoing motion, it is important for the articulated arm to be able to adjust the position of the instrument to the changes in the positions of the body opening. Depending upon the design and/or

implementation of the articulated arm, the body opening on the patient may correspond to the remote center of motion for the articulated arm.

(4) As each of the one or more articulated arms track the underlying movement, the corresponding articulated arm and/or other parts of the electronic device attempt to compensate for the movement in the body opening. When the articulated arms are not able to fully compensate for the movement of the body opening points, this may result in undesirable and/or unsafe consequences. This lack of compliance with the movement of the incision point may result in injury to the patient, damage to the articulated arms, and/or other undesirable outcomes.

(5) Accordingly, it would be desirable to monitor the ability of the articulated arms to compensate for underlying movement in control points, such as body openings.

SUMMARY

(6) Consistent with some embodiments, a computer-assisted medical device includes one or more articulated arms each having a control point and a control unit coupled to the one or more articulated arms. The one or more articulated arms and corresponding control points are configured to track movement of a surgical table. The control unit monitors a spatial configuration of the one or more control points by determining an expected spatial configuration of the one or more control points during the movement of the surgical table, determining an actual spatial configuration of the one or more control points during the movement of the surgical table, and determining a difference between the expected spatial configuration and the actual spatial configuration.

(7) Consistent with some embodiments, a method of monitoring a spatial configuration of one or more control points of a computer-assisted medical device includes determining an expected spatial configuration of the one or more control points during movement of a surgical table, determining an actual spatial configuration of the one or more control points during the movement of the surgical table, and determining a difference between the expected spatial configuration and the actual spatial configuration. The one or more control points correspond to one or more articulated arms and are configured to track the movement of the surgical table.

(8) Consistent with some embodiments, a non-transitory machine-readable medium includes a plurality of machine-readable instructions which when executed by one or more processors associated with a medical device are adapted to cause the one or more processors to perform a method. The method includes determining an expected spatial configuration of one or more control points during movement of a surgical table, determining an actual spatial configuration of the one or more control points in during the movement of the surgical table, and determining a difference between the expected spatial configuration and the actual spatial configuration. The one or more control points correspond to one or more articulated arms and are configured to track the movement of the surgical table.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a simplified diagram of a computer-assisted system according to some embodiments.

(2) FIG. 2 is a simplified diagram showing a computer-assisted system according to some embodiments.

(3) FIG. 3 is a simplified diagram of a kinematic model of a computer-assisted medical system according to some embodiments.

(4) FIG. 4 is a simplified diagram of the method of monitoring one or more control points during table movement according to some embodiments.

(5) FIG. 5 is a simplified diagram of a control point position during table movement in a height-only mode according to some embodiments.

(6) FIG. 6 is a simplified diagram of a control point constellation during rotational table movement

according to some embodiments.

(7) FIGS. 7A-7G are simplified schematic views that illustrate various computer-assisted device system architectures that incorporate the integrated computer-assisted device and movable surgical table features described herein.

(8) In the figures, elements having the same designations have the same or similar functions.

DETAILED DESCRIPTION

(9) In the following description, specific details are set forth describing some embodiments consistent with the present disclosure. It will be apparent to one skilled in the art, however, that some embodiments may be practiced without some or all of these specific details. The specific embodiments disclosed herein are meant to be illustrative but not limiting. One skilled in the art may realize other elements that, although not specifically described here, are within the scope and the spirit of this disclosure. In addition, to avoid unnecessary repetition, one or more features shown and described in association with one embodiment may be incorporated into other embodiments unless specifically described otherwise or if the one or more features would make an embodiment non-functional. The term “including” means including but not limited to, and each of the one or more individual items included should be considered optional unless otherwise stated. Similarly, the term “may” indicates that an item is optional.

(10) FIG. 1 is a simplified diagram of a computer-assisted system **100** according to some embodiments. As shown in FIG. 1, computer-assisted system **100** includes a device **110** with one or more movable or articulated arms **120**. Each of the one or more articulated arms **120** supports one or more end effectors. In some examples, device **110** may be consistent with a computer-assisted surgical device. The one or more articulated arms **120** each provides support for one or more instruments, surgical instruments, imaging devices, and/or the like mounted to a distal end of at least one of the articulated arms **120**. Device **110** may further be coupled to an operator workstation (not shown), which may include one or more master controls for operating the device **110**, the one or more articulated arms **120**, and/or the end effectors. In some embodiments, device **110** and the operator workstation may correspond to a da Vinci® Surgical System commercialized by Intuitive Surgical, Inc. of Sunnyvale, California. In some embodiments, computer-assisted surgical devices with other configurations, fewer or more articulated arms, and/or the like may optionally be used with computer-assisted system **100**.

(11) Device **110** is coupled to a control unit **130** via an interface. The interface may include one or more wireless links, cables, connectors, and/or buses and may further include one or more networks with one or more network switching and/or routing devices. Control unit **130** includes a processor **140** coupled to memory **150**. Operation of control unit **130** is controlled by processor **140**. And although control unit **130** is shown with only one processor **140**, it is understood that processor **140** may be representative of one or more central processing units, multi-core processors, microprocessors, microcontrollers, digital signal processors, field programmable gate arrays (FPGAs), application specific integrated circuits (ASICs), and/or the like in control unit **130**. Control unit **130** may be implemented as a stand-alone subsystem and/or board added to a computing device or as a virtual machine. In some embodiments, control unit may be included as part of the operator workstation and/or operated separately from, but in coordination with the operator workstation.

(12) Memory **150** is used to store software executed by control unit **130** and/or one or more data structures used during operation of control unit **130**. Memory **150** may include one or more types of machine readable media. Some common forms of machine readable media may include floppy disk, flexible disk, hard disk, magnetic tape, any other magnetic medium, CD-ROM, any other optical medium, punch cards, paper tape, any other physical medium with patterns of holes, RAM, PROM, EPROM, FLASH-EPROM, any other memory chip or cartridge, and/or any other medium from which a processor or computer is adapted to read.

(13) As shown, memory **150** includes a motion control application **160** that supports autonomous

and/or semiautonomous control of device **110**. Motion control application **160** may include one or more application programming interfaces (APIs) for receiving position, motion, and/or other sensor information from device **110**, exchanging position, motion, and/or collision avoidance information with other control units regarding other devices, such as a surgical table and/or imaging device, and/or planning and/or assisting in the planning of motion for device **110**, articulated arms **120**, and/or the end effectors of device **110**. And although motion control application **160** is depicted as a software application, motion control application **160** may be implemented using hardware, software, and/or a combination of hardware and software.

(14) In some embodiments, computer-assisted system **100** may be found in an operating room and/or an interventional suite. And although computer-assisted system **100** includes only one device **110** with two articulated arms **120**, one of ordinary skill would understand that computer-assisted system **100** may include any number of devices with articulated arms and/or end effectors of similar and/or different design from device **110**. In some examples, each of the devices may include fewer or more articulated arms and/or end effectors.

(15) Computer-assisted system **100** further includes a surgical table **170**. Like the one or more articulated arms **120**, surgical table **170** supports articulated movement of a table top **180** relative to a base of surgical table **170**. In some examples, the articulated movement of table top **180** may include support for changing a height, a tilt, a slide, a Trendelenburg orientation, and/or the like of table top **180**. Although not shown, surgical table **170** may include one or more control inputs, such as a surgical table command unit for controlling the position and/or orientation of table top **180**. In some embodiments, surgical table **170** may correspond to one or more of the surgical tables commercialized by Trumpf Medical Systems GmbH of Germany.

(16) Surgical table **170** is also coupled to control unit **130** via a corresponding interface. The interface may include one or more wireless links, cables, connectors, and/or buses and may further include one or more networks with one or more network switching and/or routing devices. In some embodiments, surgical table **170** may be coupled to a different control unit than control unit **130**. In some examples, motion control application **160** may include one or more application programming interfaces (APIs) for receiving position, motion, and/or other sensor information associated with surgical table **170** and/or table top **180**. In some examples, motion control application **160** may plan and/or assist in the planning of motion for surgical table **170** and/or table top **180**. In some examples, motion control application **160** may contribute to motion plans associated with collision avoidance, adapting to and/or avoid range of motion limits in joints and links, movement of articulated arms, instruments, end effectors, surgical table components, and/or the like to compensate for other motion in the articulated arms, instruments, end effectors, surgical table components, and/or the like, adjust a viewing device such as an endoscope to maintain and/or place an area of interest and/or one or more instruments or end effectors within a field of view of the viewing device. In some examples, motion control application **160** may prevent motion of surgical table **170** and/or table top **180**, such as by preventing movement of surgical table **170** and/or table top **180** through use of the surgical table command unit. In some examples, motion control application **160** may help register device **110** with surgical table **170** so that a geometric relationship between device **110** and surgical table **170** is known. In some examples, the geometric relationship may include a translation and/or one or more rotations between coordinate frames maintained for device **110** and surgical table **170**.

(17) FIG. 2 is a simplified diagram showing a computer-assisted system **200** according to some embodiments. For example, the computer-assisted system **200** may be consistent with computer-assisted system **100**. As shown in FIG. 2, the computer-assisted system **200** includes a computer-assisted device **210** with one or more articulated arms and a surgical table **280**. Although not shown in FIG. 2, the computer-assisted device **210** and the surgical table **280** are coupled together using one or more interfaces and one or more control units so that at least kinematic information about the surgical table **280** is known to the motion control application being used to perform motion of

the articulated arms of the computer-assisted device **210**.

(18) The computer-assisted device **210** includes various links and joints. In the embodiments of FIG. 2, the computer-assisted device is generally divided into three different sets of links and joints. Starting at the proximal end with a mobile cart **215** or patient-side cart **215** is a set-up structure **220**. Coupled to a distal end of the set-up structure is a series of links and set-up joints **240** forming an articulated arm. And coupled to a distal end of the set-up joints **240** is a multi-jointed manipulator **260**. In some examples, the series of set-up joints **240** and manipulator **260** may correspond to one of the articulated arms **120**. And although the computer-assisted device is shown with only one series of set-up joints **240** and a corresponding manipulator **260**, one of ordinary skill would understand that the computer-assisted device may include more than one series of set-up joints **240** and corresponding manipulators **260** so that the computer-assisted device is equipped with multiple articulated arms.

(19) As shown, the computer-assisted device **210** is mounted on the mobile cart **215**. The mobile cart **215** enables the computer-assisted device **210** to be transported from location to location, such as between operating rooms or within an operating room to better position the computer-assisted device in proximity to the surgical table **280**. The set-up structure **220** is mounted on the mobile cart **215**. As shown in FIG. 2, the set-up structure **220** includes a two part column including column links **221** and **222**. Coupled to the upper or distal end of the column link **222** is a shoulder joint **223**. Coupled to the shoulder joint **223** is a two-part boom including boom links **224** and **225**. At the distal end of the boom link **225** is a wrist joint **226**, and coupled to the wrist joint **226** is an arm mounting platform **227**.

(20) The links and joints of the set-up structure **220** include various degrees of freedom for changing the position and orientation (i.e., the pose) of the arm mounting platform **227**. For example, the two-part column is used to adjust a height of the arm mounting platform **227** by moving the shoulder joint **223** up and down along an axis **232**. The arm mounting platform **227** is additionally rotated about the mobile cart **215**, the two-part column, and the axis **232** using the shoulder joint **223**. The horizontal position of the arm mounting platform **227** is adjusted along an axis **234** using the two-part boom. And the orientation of the arm mounting platform **227** may also be adjusted by rotation about an arm mounting platform orientation axis **236** using the wrist joint **226**. Thus, subject to the motion limits of the links and joints in the set-up structure **220**, the position of the arm mounting platform **227** may be adjusted vertically above the mobile cart **215** using the two-part column. The positions of the arm mounting platform **227** may also be adjusted radially and angularly about the mobile cart **215** using the two-part boom and the shoulder joint **223**, respectively. And the angular orientation of the arm mounting platform **227** may also be changed using the wrist joint **226**.

(21) The arm mounting platform **227** is used as a mounting point for one or more articulated arms. The ability to adjust the height, horizontal position, and orientation of the arm mounting platform **227** about the mobile cart **215** provides a flexible set-up structure for positioning and orienting the one or more articulated arms about a work space located near the mobile cart **215** where an operation or procedure is to take place. For example, arm mounting platform **227** may be positioned above a patient so that the various articulated arms and their corresponding manipulators and instruments have sufficient range of motion to perform a surgical procedure on the patient. FIG. 2 shows a single articulated arm coupled to the arm mounting platform **227** using a first set-up joint **242**. And although only one articulated arm is shown, one of ordinary skill would understand that multiple articulated arms may be coupled to the arm mounting platform **227** using additional first set-up joints.

(22) The first set-up joint **242** forms the most proximal portion of the set-up joints **240** section of the articulated arm. The set-up joints **240** may further include a series of joints and links. As shown in FIG. 2, the set-up joints **240** include at least links **244** and **246** coupled via one or more joints (not expressly shown). The joints and links of the set-up joints **240** include the ability to rotate the

set-up joints **240** relative to the arm mounting platform **227** about an axis **252** using the first set-up joint **242**, adjust a radial or horizontal distance between the first set-up joint **242** and the link **246**, adjust a height of a manipulator mount **262** at the distal end of link **246** relative to the arm mounting platform **227** along an axis **254**, and rotate the manipulator mount **262** about axis **254**. In some examples, the set-up joints **240** may further include additional joints, links, and axes permitting additional degrees of freedom for altering a pose of the manipulator mount **262** relative to the arm mounting platform **227**.

(23) The manipulator **260** is coupled to the distal end of the set-up joints **240** via the manipulator mount **262**. The manipulator **260** includes additional joints **264** and links **266** with an instrument carriage **268** mounted at the distal end of the manipulator **260**. An instrument **270** is mounted to the instrument carriage **268**. Instrument **270** includes a shaft **272**, which is aligned along an insertion axis. The shaft **272** is typically aligned so that it passes through a remote center of motion **274** associated with the manipulator **260**. Location of the remote center of motion **274** is typically maintained in a fixed translational relationship relative to the manipulator mount **262** so that operation of the joints **264** in the manipulator **260** result in rotations of the shaft **272** about the remote center of motion **274**. Depending upon the embodiment, the fixed translational relationship of the remote center of motion **274** relative to the manipulator mount **262** is maintained using physical constraints in the joints **264** and links **266** of the manipulator **260**, using software constraints placed on the motions permitted for the joints **264**, and/or a combination of both. Representative embodiments of computer-assisted surgical devices using remote centers of motion maintained using physical constraints in joints and links are described in U.S. patent application Ser. No. 13/906,888 entitled “Redundant Axis and Degree of Freedom for Hardware-Constrained Remote Center Robotic Manipulator,” which was filed May 13, 2013, and representative embodiments of computer-assisted surgical devices using remote centers of motion maintained by software constraints are described in U.S. Pat. No. 8,004,229 entitled “Software Center and Highly Configurable Robotic Systems for Surgery and Other Uses,” which was filed May 19, 2005, the specifications of which are hereby incorporated by reference in their entirety. In some examples, the remote center of motion **274** may correspond to a location of a body opening, such as an incision site or body orifice, in a patient **278** where shaft **272** is inserted into the patient **278**. Because the remote center of motion **274** corresponds to the body opening, as the instrument **270** is used, the remote center of motion **274** remains stationary relative to the patient **278** to limit stresses on the anatomy of the patient **278** at the remote center of motion **274**. In some examples, the shaft **272** may be optionally passed through a cannula (not shown) located at the body opening. In some examples, instruments having a relatively larger shaft or guide tube outer diameter (e.g., 4-5 mm or more) may be passed through the body opening using a cannula and the cannula may optionally be omitted for instruments having a relatively smaller shaft or guide tube outer diameter (e.g., 2-3 mm or less).

(24) At the distal end of the shaft **272** is an end effector **276**. The degrees of freedom in the manipulator **260** due to the joints **264** and the links **266** may permit at least control of the roll, pitch, and yaw of the shaft **272** and/or the end effector **276** relative to the manipulator mount **262**. In some examples, the degrees of freedom in the manipulator **260** may further include the ability to advance and/or withdraw the shaft **272** using the instrument carriage **268** so that the end effector **276** may be advanced and/or withdrawn along the insertion axis and relative to the remote center of motion **274**. In some examples, the manipulator **260** may be consistent with manipulators for use with the da Vinci® Surgical System commercialized by Intuitive Surgical, Inc. of Sunnyvale, California. In some examples, the instrument **270** may be an imaging device such as an endoscope, a gripper, a surgical instrument such as a cautery or a scalpel, and/or the like. In some examples, the end effector **276** may include additional degrees of freedom, such as roll, pitch, yaw, grip, and/or the like that allow for additional localized manipulation of portions of the end effector **276** relative to the distal end of the shaft **272**.

(25) During a surgery or other medical procedure, the patient **278** is typically located on the surgical table **280**. The surgical table **280** includes a table base **282** and a table top **284**, with the table base **282** being located in proximity to mobile cart **215** so that the instrument **270** and/or end effector **276** may be manipulated by the computer-assisted device **210** while the shaft **272** of instrument **270** is inserted into the patient **278** at the body opening. The surgical table **280** further includes an articulated structure **290** that includes one or more joints or links between the table base **282** and the table top **284** so that the relative location of the table top **284**, and thus the patient **278**, relative to the table base **282** is controlled. In some examples, the articulated structure **290** may be configured so that the table top **284** is controlled relative to a virtually-defined table motion isocenter **286** that may be located at a point above the table top **284**. In some examples, isocenter **286** may be located within the interior of the patient **278**. In some examples, isocenter **286** may be collocated with the body wall of the patient at or near one of the body openings, such as a body opening site corresponding to remote center of motion **274**.

(26) As shown in FIG. 2, the articulated structure **290** includes a height adjustment joint **292** so that the table top **284** may be raised and/or lowered relative to the table base **282**. The articulated structure **290** further includes joints and links to change both the tilt **294** and Trendelenburg **296** orientation of the table top **284** relative to the isocenter **286**. The tilt **294** allows the table top **284** to be tilted side-to-side so that either the right or left side of the patient **278** is rotated upward relative to the other side of the patient **278** (i.e., about a longitudinal or head-to-toc (cranial-caudal) axis of the table top **284**). The Trendelenburg **296** allows the table top **284** to be rotated so that either the feet of the patient **278** are raised (Trendelenburg) or the head of the patient **278** is raised (reverse Trendelenburg). In some examples, either the tilt **294** and/or the Trendelenburg **296** rotations may be adjusted to generate rotations about isocenter **286**. The articulated structure **290** further includes additional links and joints **298** to slide the table top **284** along the longitudinal (cranial-caudal) axis relative to the table base **282** with generally a left and/or right motion as depicted in FIG. 2.

(27) FIGS. 7A-7G are simplified schematic views that illustrate various computer-assisted device system architectures that incorporate the integrated computer-assisted device and movable surgical table features described herein. The various illustrated system components are in accordance with the principles described herein. In these illustrations, the components are simplified for clarity, and various details such as individual links, joints, manipulators, instruments, end effectors, etc. are not shown, but they should be understood to be incorporated in the various illustrated components.

(28) In these architectures, cannulas associated with one or more surgical instruments or clusters of instruments are not shown, and it should be understood that cannulas and other instrument guide devices optionally may be used for instruments or instrument clusters having a relatively larger shaft or guide tube outer diameter (e.g., 4-5 mm or more) and optionally may be omitted for instruments having a relatively smaller shaft or guide tube outer diameter (e.g., 2-3 mm or less).

(29) Also in these architectures, teleoperated manipulators should be understood to include manipulators that during surgery define a remote center of motion by using hardware constraints (e.g., fixed intersecting instrument pitch, yaw, and roll axes) or software constraints (e.g., software-constrained intersecting instrument pitch, yaw, and roll axes). A hybrid of such instrument axes of rotation may be defined (e.g., hardware-constrained roll axis and software-constrained pitch and yaw axes) are also possible. Further, some manipulators may not define and constrain any surgical instrument axes of rotation during a procedure, and some manipulators may define and constrain only one or two instrument axes of rotation during a procedure.

(30) FIG. 7A illustrates a movable surgical table **1100** and a single-instrument computer-assisted device **1101a** are shown. Surgical table **1100** includes a movable table top **1102** and a table support structure **1103** that extends from a mechanically grounded table base **1104** to support the table top **1102** at a distal end. In some examples, surgical table **1100** may be consistent with surgical table **170** and/or **280**. Computer-assisted device **1101a** includes a teleoperated manipulator and a single instrument assembly **1105a**. Computer-assisted device **1101a** also includes a support structure

1106a that is mechanically grounded at a proximal base **1107a** and that extends to support manipulator and instrument assembly **1105a** at a distal end. Support structure **1106a** is configured to allow assembly **1105a** to be moved and held in various fixed poses with reference to surgical table **1100**. Base **1107a** is optionally permanently fixed or movable with reference to surgical table **1100**. Surgical table **1100** and computer-assisted device **1101a** operate together as described herein. (31) FIG. 7A further shows an optional second computer-assisted device **1101b**, which illustrates that two, three, four, five, or more individual computer-assisted devices may be included, each having a corresponding individual teleoperated manipulator and single-instrument assembly (ies) **1105b** supported by a corresponding support structure **1106b**. Computer-assisted device **1101b** is mechanically grounded, and assemblies **1105b** are posed, similarly to computer-assisted device **1101a**. Surgical table **1100** and computer-assisted devices **1101a** and **1101b** together make a multi-instrument surgical system, and they operate together as described herein. In some examples, computer-assisted devices **1101a** and/or **1101b** may be consistent with computer-assisted devices **110** and/or **210**.

(32) As shown in FIG. 7B, another movable surgical table **1100** and a computer-assisted device **1111** are shown. Computer-assisted device **1111** is a multi-instrument device that includes two, three, four, five, or more individual teleoperated manipulator and single-instrument assemblies as shown by representative manipulator and instrument assemblies **1105a** and **1105b**. The assemblies **1105a** and **1105b** of computer-assisted device **1111** are supported by a combined support structure **1112**, which allows assemblies **1105a** and **1105b** to be moved and posed together as a group with reference to surgical table **1100**. The assemblies **1105a** and **1105b** of computer-assisted device **1111** are also each supported by a corresponding individual support structure **1113a** and **1113b**, respectively, which allows each assembly **1105a** and **1105b** to be individually moved and posed with reference to surgical table **1100** and to the one or more other assemblies **1105a** and **1105b**. Examples of such a multi-instrument surgical system architecture are the da Vinci Si® Surgical System and the da Vinci® Xi™ Surgical System, commercialized by Intuitive Surgical, Inc. Surgical table **1100** and a surgical manipulator system comprising an example computer-assisted device **1111** operate together as described herein. In some examples, computer-assisted device **1111** is consistent with computer-assisted devices **110** and/or **210**.

(33) The computer-assisted devices of FIGS. 7A and 7B are each shown mechanically grounded at the floor. But, one or more such computer-assisted devices may optionally be mechanically grounded at a wall or ceiling and be permanently fixed or movable with reference to such a wall or ceiling ground. In some examples, computer-assisted devices may be mounted to the wall or ceiling using a track or grid system that allows the support base of the computer-assisted systems to be moved relative to the surgical table. In some examples, one or more fixed or releasable mounting clamps may be used to mount the respective support bases to the track or grid system. As shown in FIG. 7C, a computer-assisted device **1121a** is mechanically grounded at a wall, and a computer-assisted device **1121b** is mechanically grounded at a ceiling.

(34) In addition, computer-assisted devices may be indirectly mechanically grounded via the movable surgical table **1100**. As shown in FIG. 7D, a computer-assisted device **1131a** is coupled to the table top **1102** of surgical table **1100**. Computer-assisted device **1131a** may optionally be coupled to other portions of surgical table **1100**, such as table support structure **1103** or table base **1104**, as indicated by the dashed structures shown in FIG. 7D. When table top **1102** moves with reference to table support structure **1103** or table base **1104**, the computer-assisted device **1131a** likewise moves with reference to table support structure **1103** or table base **1104**. When computer-assisted device **1131a** is coupled to table support structure **1103** or table base **1104**, however, the base of computer-assisted device **1131a** remains fixed with reference to ground as table top **1102** moves. As table motion occurs, the body opening where instruments are inserted into the patient may move as well because the patient's body may move and change the body opening locations relative to the table top **1102**. Therefore, for embodiments in which computer-assisted device **1131a**

is coupled to the table top **1102**, the table top **1102** functions as a local mechanical ground, and the body openings move with reference to the table top **1102**, and so with reference to the computer-assisted device **1131a** as well. FIG. 7D also shows that a second computer-assisted device **1131b** optionally may be added, configured similarly to computer-assisted device **1131a** to create a multi-instrument system. Systems that include one or more computer-assisted device coupled to the surgical table operate as disclosed herein.

(35) In some embodiments, other combinations of computer-assisted devices with the same or hybrid mechanical groundings are possible. For example, a system may include one computer-assisted device mechanically grounded at the floor, and a second computer-assisted device mechanically grounded to the floor via the surgical table. Such hybrid mechanical ground systems operate as disclosed herein.

(36) Inventive aspects also include single-body opening systems in which two or more surgical instruments enter the body via a single body opening. Examples of such systems are shown in U.S. Pat. No. 8,852,208 entitled “Surgical System Instrument Mounting,” which was filed Aug. 12, 2010, and U.S. Pat. No. 9,060,678 entitled “Minimally Invasive Surgical System,” which was filed Jun. 13, 2007, both of which are incorporated by reference. FIG. 7E illustrates a teleoperated multi-instrument computer-assisted device **1141** together with surgical table **1100** as described above. Two or more instruments **1142** are each coupled to a corresponding manipulator **1143**, and the cluster of instruments **1142** and instrument manipulators **1143** are moved together by a system manipulator **1144**. The system manipulator **1144** is supported by a support assembly **1145** that allows system manipulator **1144** to be moved to and fixed at various poses. Support assembly **1145** is mechanically grounded at a base **1146** consistent with the descriptions above. The two or more instruments **1142** are inserted into the patient at the single body opening. Optionally, the instruments **1142** extend together through a single guide tube, and the guide tube optionally extends through a cannula, as described in the references cited above. Computer-assisted device **1141** and surgical table **1100** operate together as described herein.

(37) FIG. 7F illustrates another multi-instrument, single-body opening computer-assisted device **1151** mechanically grounded via the surgical table **1100**, optionally by being coupled to table top **1102**, table support structure **1103**, or table base **1104**. The descriptions above with reference to FIG. 7D also applies to the mechanical grounding options illustrated in FIG. 7F. Computer-assisted device **1151** and surgical table **1100** work together as described herein.

(38) FIG. 7G illustrates that one or more teleoperated multi-instrument, single-body opening computer-assisted devices **1161** and one or more teleoperated single-instrument computer-assisted devices **1162** may be combined to operate with surgical table **1100** as described herein. Each of the computer-assisted devices **1161** and **1162** may be mechanically grounded, directly or via another structure, in various ways as described above.

(39) FIG. 3 is a simplified diagram of a kinematic model **300** of a computer-assisted medical system according to some embodiments. As shown in FIG. 3, kinematic model **300** may include kinematic information associated with many sources and/or devices. The kinematic information is based on known kinematic models for the links and joints of a computer-assisted medical device and a surgical table. The kinematic information is further based on information associated with the position and/or orientation of the joints of the computer-assisted medical device and the surgical table. In some examples, the information associated with the position and/or orientation of the joints may be derived from one or more sensors, such as encoders, measuring the linear positions of prismatic joints and the rotational positions of revolute joints.

(40) The kinematic model **300** includes several coordinate frames or coordinate systems and transformations, such as homogeneous transforms, for transforming positions and/or orientation from one of the coordinate frames to another of the coordinate frames. In some examples, the kinematic model **300** may be used to permit the forward and/or reverse mapping of positions and/or orientations in one of the coordinate frames in any other of the coordinate frames by composing the

forward and/or reverse/inverse transforms noted by the transform linkages included in FIG. 3. In some examples, when the transforms are modeled as homogenous transforms in matrix form, the composing is accomplished using matrix multiplication. In some embodiments, the kinematic model **300** may be used to model the kinematic relationships of the computer-assisted device **210** and the surgical table **280** of FIG. 2.

(41) The kinematic model **300** includes a table base coordinate frame **305** that is used to model a position and/or orientation of a surgical table, such as surgical table **170** and/or surgical table **280**. In some examples, the table base coordinate frame **305** may be used to model other points on the surgical table relative to a reference point and/or orientation associated with the surgical table. In some examples, the reference point and/or orientation may be associated with a table base of the surgical table, such as the table base **282**. In some examples, the table base coordinate frame **305** may be suitable for use as a world coordinate frame for the computer-assisted system.

(42) The kinematic model **300** further includes a table top coordinate frame **310** that may be used to model positions and/or orientations in a coordinate frame representative of a table top of the surgical table, such as the table top **284**. In some examples, the table top coordinate frame **310** may be centered about a rotational center or isocenter of the table top, such as isocenter **286**. In some examples, the z-axis of the table top coordinate frame **310** may be oriented vertically with respect to a floor or surface on which the surgical table is placed and/or orthogonal to the surface of the table top. In some examples, the x- and y-axes of the table top coordinate frame **310** may be oriented to capture the longitudinal (head to toe) and lateral (side-to-side) major axes of the table top. In some examples, a table base to table top coordinate transform **315** is used to map positions and/or orientations between the table top coordinate frame **310** and the table base coordinate frame **305**. In some examples, one or more kinematic models of an articulated structure of the surgical table, such as articulated structure **290**, along with past and/or current joint sensor readings is used to determine the table base to table top coordinate transform **315**. In some examples consistent with the embodiments of FIG. 2, the table base to table top coordinate transform **315** models the composite effect of the height, tilt, Trendelenburg, and/or slide settings associated with the surgical table.

(43) The kinematic model **300** further includes a device base coordinate frame that is used to model a position and/or orientation of a computer-assisted device, such as computer-assisted device **110** and/or computer-assisted device **210**. In some examples, the device base coordinate frame **320** may be used to model other points on the computer-assisted device relative to a reference point and/or orientation associated with the computer-assisted device. In some examples, the reference point and/or orientation may be associated with a device base of the computer-assisted device, such as the mobile cart **215**. In some examples, the device base coordinate frame **320** may be suitable for use as the world coordinate frame for the computer-assisted system.

(44) In order to track positional and/or orientational relationships between the surgical table and the computer-assisted device, it is often desirable to perform a registration between the surgical table and the computer-assisted device. As shown in FIG. 3, the registration may be used to determine a registration transform **325** between the table top coordinate frame **310** and the device base coordinate frame **320**. In some embodiments, the registration transform **325** may be a partial or full transform between the table top coordinate frame **310** and the device base coordinate frame **320**. The registration transform **325** is determined based on the architectural arrangements between the surgical table and the computer-assisted device.

(45) In the examples of FIGS. 7D and 7E, where the computer-assisted device is mounted to the table top **1102**, the registration transform **325** is determined from the table base to table top coordinate transform **315** and knowing where the computer-assisted device is mounted to the table top **112**.

(46) In the examples of FIGS. 7A-7C, 7E, and 7F, where the computer-assisted device is placed on the floor or mounted to the wall or ceiling, determination of the registration transform **325** is

simplified by placing some restrictions on the device base coordinate frame **320** and the table base coordinate frame **305**. In some examples, these restrictions include that both the device base coordinate frame **320** and the table base coordinate frame **305** agree on the same vertical up or z-axis. Under the assumption that the surgical table is located on a level floor, the relative orientations of the walls of the room (e.g., perpendicular to the floor) and the ceiling (e.g., parallel to the floor) are known it is possible for a common vertical up or z axis (or a suitable orientation transform) to be maintained for both the device base coordinate frame **320** and the table base coordinate frame **305** or a suitable orientation transform. In some examples, because of the common z-axis, the registration transform **325** may optionally model just the rotational relationship of the device base to the table base about the z-axis of the table base coordinate frame **305** (e.g., a Oz registration). In some examples, the registration transform **325** may optionally also model a horizontal offset between the table base coordinate frame **305** and the device base coordinate frame **320** (e.g., a XY registration). This is possible because the vertical (z) relationship between the computer-assisted device and the surgical table are known. Thus, changes in a height of the table top in the table base to table top transform **315** are analogous to vertical adjustments in the device base coordinate frame **320** because the vertical axes in the table base coordinate frame **305** and the device base coordinate frame **320** are the same or nearly the same so that changes in height between the table base coordinate frame **305** and the device base coordinate frame **320** are within a reasonable tolerance of each other. In some examples, the tilt and Trendelenburg adjustments in the table base to table top transform **315** may be mapped to the device base coordinate frame **320** by knowing the height of the table top (or its isocenter) and the $\theta_{sub.Z}$ and/or XY registration. In some examples, the registration transform **325** and the table base to table top transform **315** may be used to model the computer-assisted surgical device as if it were attached to the table top even when this is architecturally not the case.

(47) The kinematic model **300** further includes an arm mounting platform coordinate frame **330** that is used as a suitable model for a shared coordinate frame associated with the most proximal points on the articulated arms of the computer-assisted device. In some embodiments, the arm mounting platform coordinate frame **330** may be associated with and oriented relative to a convenient point on an arm mounting platform, such as the arm mounting platform **227**. In some examples, the center point of the arm mounting platform coordinate frame **330** may be located on the arm mounting platform orientation axis **236** with the z-axis of the arm mounting platform coordinate frame **330** being aligned with arm mounting platform orientation axis **236**. In some examples, a device base to arm mounting platform coordinate transform **335** is used to map positions and/or orientations between the device base coordinate frame **320** and the arm mounting platform coordinate frame **330**. In some examples, one or more kinematic models of the links and joints of the computer-assisted device between the device base and the arm mounting platform, such as the set-up structure **220**, along with past and/or current joint sensor readings are used to determine the device base to arm mounting platform coordinate transform **335**. In some examples consistent with the embodiments of FIG. 2, the device base to arm mounting platform coordinate transform **335** may model the composite effect of the two-part column, shoulder joint, two-part boom, and wrist joint of the setup structure portion of the computer-assisted device.

(48) The kinematic model **300** further includes a series of coordinate frames and transforms associated with each of the articulated arms of the computer-assisted device. As shown in FIG. 3, the kinematic model **300** includes coordinate frames and transforms for three articulated arms, although one of ordinary skill would understand that different computer-assisted devices may include fewer and/or more articulated arms (e.g., one, two, four, five, or more). Consistent with the configuration of the links and joints of the computer-assisted device **210** of FIG. 2, each of the articulated arms is modeled using a manipulator mount coordinate frame, a remote center of motion coordinate frame, and an instrument or camera coordinate frame, depending on a type of instrument mounted to the distal end of the articulated arm.

(49) In the kinematic model **300**, the kinematic relationships of a first one of the articulated arms is captured using a manipulator mount coordinate frame **341**, a remote center of motion coordinate frame **342**, an instrument coordinate frame **343**, an arm mounting platform to manipulator mount transform **344**, a manipulator mount to remote center of motion transform **345**, and a remote center of motion to instrument transform **346**. The manipulator mount coordinate frame **341** represents a suitable model for representing positions and/or orientations associated with a manipulator, such as manipulator **260**. The manipulator mount coordinate frame **341** is associated with a manipulator mount, such as the manipulator mount **262** of the corresponding articulated arm. The arm mounting platform to manipulator mount transform **344** is then based on one or more kinematic models of the links and joints of the computer-assisted device between the arm mounting platform and the corresponding manipulator mount, such as the corresponding set-up joints **240**, along with past and/or current joint sensor readings of the corresponding set-up joints **240**.

(50) The remote center of motion coordinate frame **342** is associated with a remote center of motion of the instrument mounted on the manipulator, such as the corresponding remote center of motion **274** of the corresponding manipulator **260**. The manipulator mount to remote center of motion transform **345** is then based on one or more kinematic models of the links and joints of the computer-assisted device between the corresponding manipulator mount and the corresponding remote center of motion, such as the corresponding joints **264**, corresponding links **266**, and corresponding carriage **268** of the corresponding manipulator **260**, along with past and/or current joint sensor readings of the corresponding joints **264**. When the corresponding remote center of motion is being maintained in fixed positional relationship to the corresponding manipulator mounts, such as in the embodiments of FIG. 2, the manipulator mount to remote center of motion transform **345** includes an essentially static translational component that does not change as the manipulator and instrument are operated and a dynamic rotational component that changes as the manipulator and instrument are operated.

(51) The instrument coordinate frame **343** is associated with an end effector located at the distal end of the instrument, such as the corresponding end effector **276**. The remote center of motion to instrument transform **346** is then based on one or more kinematic models of the links and joints of the computer-assisted device that move and/or orient the corresponding instrument, end effector, and remote center of motion, along with past and/or current joint sensor readings. In some examples, the remote center of motion to instrument transform **346** accounts for the orientation at which the shaft, such as the corresponding shaft **272**, passes through the remote center of motion and the distance to which the shaft is advanced and/or withdrawn relative to the remote center of motion. In some examples, the remote center of motion to instrument transform **346** may be constrained to reflect that the insertion axis of the shaft of the instrument passes through the remote center of motion and accounts for rotations of the shaft and the end effector about the axis defined by the shaft.

(52) In the kinematic model **300**, the kinematic relationships of a second one of the articulated arms is captured using a manipulator mount coordinate frame **351**, a remote center of motion coordinate frame **352**, an instrument coordinate frame **353**, an arm mounting platform to manipulator mount transform **354**, a manipulator mount to remote center of motion transform **355**, and a remote center of motion to instrument transform **356**. The manipulator mount coordinate frame **351** represents a suitable model for representing positions and/or orientations associated with a manipulator, such as manipulator **260**. The manipulator mount coordinate frame **351** is associated with a manipulator mount, such as the manipulator mount **262** of the corresponding articulated arm. The arm mounting platform to manipulator mount transform **354** is then based on one or more kinematic models of the links and joints of the computer-assisted device between the arm mounting platform and the corresponding manipulator mount, such as the corresponding set-up joints **240**, along with past and/or current joint sensor readings of the corresponding set-up joints **240**.

(53) The remote center of motion coordinate frame **352** is associated with a remote center of

motion of the manipulator mounted on the articulated arm, such as the corresponding remote center of motion **274** of the corresponding manipulator **260**. The manipulator mount to remote center of motion transform **355** is then based on one or more kinematic models of the links and joints of the computer-assisted device between the corresponding manipulator mount and the corresponding remote center of motion, such as the corresponding joints **264**, corresponding links **266**, and corresponding carriage **268** of the corresponding manipulator **260**, along with past and/or current joint sensor readings of the corresponding joints **264**. When the corresponding remote center of motion is being maintained in fixed positional relationship to the corresponding manipulator mounts, such as in the embodiments of FIG. 2, the mount to remote center of motion transform **355** includes an essentially static translational component that does not change as the manipulator and instrument are operated and a dynamic rotational component that changes as the manipulator and instrument are operated.

(54) The instrument coordinate frame **353** is associated with an end effector located at the distal end of the instrument, such as the corresponding instrument **270** and/or end effector **276**. The remote center of motion to instrument transform **356** is then based on one or more kinematic models of the links and joints of the computer-assisted device that move and/or orient the corresponding instrument, end effector, and remote center of motion, along with past and/or current joint sensor readings. In some examples, the remote center of motion to instrument transform **356** accounts for the orientation at which the shaft, such as the corresponding shaft **272**, passes through the remote center of motion and the distance to which the shaft is advanced and/or withdrawn relative to the remote center of motion. In some examples, the remote center of motion to instrument transform **356** may be constrained to reflect that the insertion axis of the shaft of the instrument passes through the remote center of motion and accounts for rotations of the shaft and the end effector about the insertion axis defined by the shaft.

(55) In the kinematic model **300**, the kinematic relationships of a third one of the articulated arms is captured using a manipulator mount coordinate frame **361**, a remote center of motion coordinate frame **362**, a camera coordinate frame **363**, an arm mounting platform to manipulator mount transform **364**, a manipulator mount to remote center of motion transform **365**, and a remote center of motion to camera transform **366**. The manipulator mount coordinate frame **361** represents a suitable model for representing positions and/or orientations associated with a manipulator, such as manipulator **260**. The manipulator mount coordinate frame **361** is associated with a manipulator mount, such as the manipulator mount **262** of the corresponding articulated arm. The arm mounting platform to manipulator mount transform **364** is then based on one or more kinematic models of the links and joints of the computer-assisted device between the arm mounting platform and the corresponding manipulator mount, such as the corresponding set-up joints **240**, along with past and/or current joint sensor readings of the corresponding set-up joints **240**.

(56) The remote center of motion coordinate frame **362** is associated with a remote center of motion of the manipulator mounted on the articulated arm, such as the corresponding remote center of motion **274** of the corresponding manipulator **260**. The manipulator mount to remote center of motion transform **365** is then based on one or more kinematic models of the links and joints of the computer-assisted device between the corresponding manipulator mount and the corresponding remote center of motion, such as the corresponding joints **264**, corresponding links **266**, and corresponding carriage **268** of the corresponding manipulator **260**, along with past and/or current joint sensor readings of the corresponding joints **264**. When the corresponding remote center of motion is being maintained in fixed positional relationship to the corresponding manipulator mounts, such as in the embodiments of FIG. 2, the mount to remote center of motion transform **365** includes an essentially static translational component that does not change as the manipulator and instrument are operated and a dynamic rotational component that changes as the manipulator and instrument are operated.

(57) The camera coordinate frame **363** is associated with an imaging device, such an endoscope,

mounted on the articulated arm. The remote center of motion to camera transform **366** is then based on one or more kinematic models of the links and joints of the computer-assisted device that move and/or orient the imaging device and the corresponding remote center of motion, along with past and/or current joint sensor readings. In some examples, the remote center of motion to camera transform **366** accounts for the orientation at which the shaft, such as the corresponding shaft **272**, passes through the remote center of motion and the distance to which the shaft is advanced and/or withdrawn relative to the remote center of motion. In some examples, the remote center of motion to camera transform **366** may be constrained to reflect that the insertion axis of the shaft of the imaging device passes through the remote center of motion and accounts for rotations of the imaging device about the axis defined by the shaft.

(58) As discussed above and further emphasized here, FIG. 3 is merely an example which should not unduly limit the scope of the claims. One of ordinary skill in the art would recognize many variations, alternatives, and modifications. According to some embodiments, the registration between the surgical table and the computer-assisted device may be determined between the table top coordinate frame **310** and the device base coordinate frame **320** using an alternative registration transform. When the alternative registration transform is used, registration transform **325** is determined by composing the alternative registration transform with the inverse/reverse of the table base to table top transform **315**. According to some embodiments, the coordinate frames and/or transforms used to model the computer-assisted device may be arranged differently dependent on the particular configuration of the links and joints of the computer-assisted device, its articulated arms, its end effectors, its manipulators, and/or its instruments. According to some embodiments, the coordinate frames and transforms of the kinematic model **300** may be used to model coordinate frames and transforms associated with one or more virtual instruments and/or virtual cameras. In some examples, the virtual instruments and/or cameras may be associated with previously stored and/or latched instrument positions, projections of instruments and/or cameras due to a motion, reference points defined by a surgeon and/or other personnel, and/or the like.

(59) As described previously, as a computer-assisted system, such as computer-assisted systems **100** and/or **200**, is being operated it would be desirable to allow continued control of the instrument and/or end effectors while motion of a surgical table, such as surgical tables **170** and/or **280**, is allowed. In some examples, this may allow for a less time-consuming procedure as surgical table motion occurs without having to remove instruments from body openings on the patient. In some examples, this allows a surgeon and/or other medical personnel to monitor organ movement while the surgical table motion is occurring to obtain a more optimal surgical table pose. In some examples, this also permits active continuation of a surgical procedure during surgical table motion. Some modes of operation allow motion of the articulated structure in the surgical table (i.e., table movement) while one or more instruments are inserted into body openings on the patient to the patient. Examples of systems permitting active continuation of a surgical procedure during surgical table motion are shown in U.S. Provisional Patent Application No. 62/134,207 entitled "System and Method for Integrated Surgical Table," which was filed Mar. 17, 2015, and concurrently filed PCT Patent Application No. PCT/US2015/057656 entitled "System and Method for Integrated Surgical Table" and published as WO2016/069648 A1, both of which are hereby incorporated by reference in their entirety. During the table movement, it is generally desired to have the remote centers of motion or other control points, corresponding to body openings, body orifices, and/or locations where an instrument is inserted through an incision site on the patient, move with the patient to limit stresses on the anatomy of the patient at the incision points and/or to maintain instrument positioning. In some examples, this may be accomplished using instrument dragging by releasing and/or unlocking one or more joints of the articulated arm and allowing the body wall of the patient at the body opening to drag the control points and the associated instruments as the patient moves. However, an articulated arm and/or end effector may occasionally encounter a disturbance that results in a loss of the ability to freely track the table movement so that the control

points do not remain coincident with the body openings. Examples of disturbances that may cause loss of tracking ability include reaching range of motion limits in the joints of the articulated arms, encountering an obstruction such as a tangled cable, loss of cannula retention (i.e., the cannula associated with a control point slipping out from the body wall at the body opening), movement of the patient on the table, a brake release failure, a collision between two arms and/or between an arm and the patient body, and/or the like. Accordingly, in some examples, it may be desired to monitor the configuration of the control points during table movement to ensure that their actual configuration at a given time is consistent with their expected configuration based on the table motion. When a deviation between the actual and expected configurations of the control points is detected, a corresponding remedial action, such as disabling table movement, braking the articulated arms, alerting the user and/or the like, may be taken. Further, according to some embodiments, it may be desirable to detect and/or report offending arms (i.e., the one or more articulated arms was subject to and/or was most impacted by the disturbance that caused the alert to be raised) to facilitate corrective action.

(60) FIG. 4 is a simplified diagram of the method **400** of monitoring one or more control points during table movement according to some embodiments. One or more of the processes **410-460** of method **400** may be implemented, at least in part, in the form of executable code stored on non-transient, tangible, machine readable media that when run by one or more processors (e.g., the processor **140** in control unit **130**) may cause the one or more processors to perform one or more of the processes **410-460**. In some embodiments, method **400** may be used to detect disturbances that prevent control points, such as those located at a body opening, body orifice, or incision site in patient from tracking table movement as expected. In some examples consistent with the embodiments of FIG. 2, the one or more control points may be instances of remote center of motion **274**, and table movement may correspond to motion of articulated structure **290** in the surgical table **280**. One of ordinary skill would understand that method **400** may be adapted to monitor the movement of remote centers of motion or any other control points that are expected to predictably move as a result of the table movement.

(61) According to some embodiments, method **400** supports one or more useful improvements over methods that do not monitor one or more control points during table movement. In some examples, method **400** may reduce the likelihood of injury to the patient or equipment during table movement by detecting a disturbance that prevents the control points from freely tracking the table movement and allowing a corresponding remedial action to be taken, such as halting table movement and/or alerting an operator of the disturbance. In some examples, method **400** may further facilitate operator intervention by reporting one or more offending arms that were subject to and/or were most impacted by the disturbance. In some examples, method **400** may reduce the likelihood of raising false alarms over other methods by monitoring a selected set of geometric attributes of the control point configuration and/or by setting thresholds that accurately distinguish routine aberrations from unsafe disturbances.

(62) At a process **410**, a latched configuration of the control points is determined. The latched configuration specifies one or more attributes of the geometric arrangement of the control points (collectively referred to as the control point constellation) in a reference frame. In some embodiments, the geometric attributes may include the positions of the control points, the orientation of the control point constellation, the point-to-point distances between pairs of control points, the interior angles formed between sets of three control points, the center of curvature of the control point constellation, and/or the like. In some examples, the latched configuration may be determined using sensor readings and/or kinematic models, such as kinematic model **300**, to ascertain the position of each control point and/or to derive corresponding geometric attributes of the control point constellation. The selection of the reference frame depends on an operating mode. In some embodiments, the reference frame may be any coordinate frame that is fixed relative to a world coordinate frame. In such examples, consistent with the embodiments of FIGS. 2 and 3, any

of the device base coordinate frame **320**, arm mounting platform coordinate frame **330**, and/or table base coordinate frame **305** may be used as the reference frame. A fixed reference frame may be used in some operating modes for tracking the positions of each control point individually. In some embodiments, the reference frame may be a dynamic coordinate frame where the position of the origin and/or the orientation of the axes of the reference frame depend upon the current position and/or orientation of the control points, table top, and/or other moving components of the system. One example of a dynamic reference frame is a barycentric reference frame, where the origin of the reference frame is an average and/or weighted average position of the control points at a current time and the orientation of the reference frame is fixed relative to a world coordinate frame or a table top coordinate frame. A barycentric reference frame may optionally be used in some operating modes for tracking the movement of the control points relative to one another, in which case common-mode translational motion of the control points (i.e. translational motion that applies to all control points equally) is irrelevant. Once the process **410** is complete, table movement may commence.

(63) At a process **420**, an expected configuration of the control points is determined based on the table movement. The expected configuration accounts for predicted changes in the position and/or orientation of the control points relative to the latched configuration determined during process **410** based on table movement. In some embodiments, the expected configuration may specify a set of geometric attributes corresponding to those specified by the latched configuration. In some embodiments, the expected configuration may instead and/or additionally specify one or more differential attributes that are defined relative to the latched configuration, such as a change in position, a change in orientation, and/or the like. In some examples, such as when using instrument dragging, the control points are expected to move with the table. In such embodiments, for example, when the height of the table changes by a given distance, the vertical position of each of the control points in a fixed reference frame is expected to change by the same distance. Similarly, when the table is rotated by a given angle, such as a tilt, Trendelenburg, and/or reverse Trendelenburg rotation, the orientation of the control point constellation in a barycentric reference frame is expected to rotate by the same angle. According to some embodiments, one or more geometric attributes of the control point constellation is not expected to change during table movement. For example, the interior angles, point-to-point distances, the center of curvature of the control point constellation, and/or the like is expected to remain constant during table movement.

(64) At a process **430**, an actual configuration of the control points during table movement is determined. In some examples, the actual configuration may be determined using position sensors and/or kinematic models to ascertain the position of each control point and/or the corresponding geometric attributes of the control point constellation in the reference frame of the process **410**. In some embodiments, the actual configuration specifies a set of geometric attributes that correspond to those specified by the latched configuration of the process **410** and/or the expected configuration determined by process **420**.

(65) At a process **440**, the actual and expected configurations of the control points are compared to determine if a difference between the configurations exceeds one or more predetermined thresholds. The types and/or values of the predetermined thresholds depend upon the geometric attributes being compared. In some examples, when the geometric attributes include control point positions, the predetermined threshold represents a maximum allowable distance between the actual and expected positions. Similarly, when the geometric attributes include the orientation of the control point constellation, the predetermined threshold represents a maximum allowable angle between the actual and expected orientations. In some examples, when the geometric attributes include a position associated with the control point constellation, such as the centroid position, the predetermined threshold represents a maximum allowable distance between the actual and expected position. In further examples, when the geometric attributes include the center of curvature of the control point constellation, the predetermined threshold represents a restriction that the center of

curvature be located below the centroid of the control point constellation. Various other types and/or values of predetermined thresholds may optionally be applied to other geometric attributes in a manner consistent with the underlying characteristics of the attributes being compared.

(66) In general, the values of the predetermined thresholds are selected according to the desire to accurately detect unsafe disturbances to the control point configuration while minimizing false alarms resulting from routine deviations between the actual and expected configurations (e.g., small oscillations in the articulated arms, small lags due to instrument dragging, allowable distortions in the body wall of the patient, and/or the like). In some embodiments, the value of the one or more of the predetermined thresholds is selected based on a clinically acceptable distance that a control point can move relative to the patient's body during table movement. In some embodiments, the clinically acceptable distance is about 12 mm. Thus, in some embodiments, the process **440** may include performing one or more computations to determine a value for a predetermined threshold that is consistent with the clinically acceptable distance being maintained. The computations depend on the characteristics of the geometric attributes being compared. For example, when the geometric attribute is an angle, the computation involves converting the clinically acceptable distance into an equivalent angular value in the reference frame.

(67) Comparing the actual and expected configurations to determine if a difference between the configurations exceeds one or more predetermined thresholds may be achieved in a variety of ways. Thus, the process **440** as described above is merely an example and should not be unduly limiting. According to some examples, rather than converting a clinically acceptable distance into a predetermined threshold consistent with a geometric attribute being compared, the geometric attribute being compared may instead be converted into a distance value consistent with the clinically acceptable distance. According to some examples, rather than comparing the actual and expected configurations directly, a range of allowable values for the geometric attributes of the actual configuration may be determined based on the expected configuration and the predetermined threshold. According to such examples, when the geometric attribute of the actual configuration is not within the range of allowable values, the predetermined threshold is determined to be exceeded.

(68) During the process **440**, when it is determined that the one or more predetermined thresholds have not been exceeded, then table movement is allowed to proceed and the method **400** returns to the process **420** to continue monitoring the control point configuration. However, when it is determined that one or more predetermined thresholds have been exceeded, then an alert is raised and the method **400** proceeds to a process **450** described below.

(69) At a process **450**, one or more control points and corresponding arms that caused the alert to be raised at the process **440** (referred to as offending arms) are determined. One or more techniques for determining the offending arms may be used. In some embodiments, when a joint reaches a range of motion limit, an articulated arm that corresponds to the range of motion limit event may be identified as an offending arm. In some embodiments, an error value associated with each control point is determined and the corresponding articulated arm with the greatest error value (i.e., the worst offender arm) and/or the one or more corresponding articulated arms with an error value that exceeds a threshold is identified as the one or more offending arms. In some embodiments, when the actual and expected configurations specify actual and expected positions for each control point, the error value includes the distance between the actual and expected positions. In some embodiments, the error value includes the difference between an actual and expected path length, where the path length indicates an amount of distance that each control point has traveled during table motion. To illustrate how the path length difference works, the following example is provided. An expected position travels to the right by 10 units and then to left by 5 units, while an actual position travels to the right by 7 units and then to the left by 2 units. Both the actual and expected positions end up 5 units to the right of the starting position after the movement, so the distance between the actual and expected positions is 0 units. However, the expected position traveled along a path with a length of 15 units while the actual position traveled a path with a

length of 9 units, so the difference between the actual and expected path length is 6 units. Thus, in some embodiments, the path length difference is used to capture certain deviations between the actual and expected positions that are obscured when using the final distance between the actual and expected positions as the error value.

(70) At a process **460**, one or more remedial actions are taken based on the alert raised at the process **440** and/or based on the offending arms determined at the process **450**. In some embodiments, the remedial actions includes one or more of stopping and/or disabling table movement, alerting an operator to the disturbance, reporting the offending arms to the operator, applying brakes to one or more of the articulated arms, applying compensation to one or more of the articulated arms, logging and/or dispatching an error report, and/or the like. In some embodiments, table movement is stopped as soon as the alert is raised and optionally remains disabled until the operator performs one or more actions, such as manually repositioning the offending arms and/or performing an inspection to identify and correct the disturbances. In some embodiments, the operator may optionally be alerted to the disturbance using an audio, visual, and/or haptic signaling mechanism such as an audio alarm, a flashing light (e.g. an LED), a message on a display screen, a vibration of a surgical table command unit, and/or the like. Similarly, the offending arms may optionally be reported to the operator using any appropriate signaling mechanism, such as the audio, visual, and/or haptic signaling mechanisms mentioned above. In some embodiments, brakes may be fully and/or partially applied to one or more of the articulated arms, including the offending arms and/or all of the articulated arms, to prevent and/or reduce further motion of the control points relative to the table. In some embodiments, an error signal may optionally be sent to one or more joints of the articulated arms to attempt to compensate for the deviation of between the actual and expected configuration by applying a counteracting force to the one or more joints. In some embodiments, an error report, which includes details relevant to the alert being raised such as a timestamp, system identifier, operator identifier, offending arm identifiers, and/or the like, may be logged and/or dispatched to a local and/or remote computer application for informational purposes and/or to allow additional remedial actions to be taken.

(71) As discussed above and further emphasized here, FIG. **4** is merely an example which should not unduly limit the scope of the claims. One of ordinary skill in the art would recognize many variations, alternatives, and modifications. According to some embodiments, method **400** may omit one or more of processes **410-460**. For example, some embodiments may omit the process **450** of offending arm detection and alert the operator of disturbances without identifying offending arms. Some embodiments may omit the process **420** of determining an expected configuration (stated differently, the expected configuration may be equivalent to the latched configuration determined at the process **410**), particularly when the geometric attributes specified by the latched configuration are not expected to change during table motion. Geometric attributes that are not expected to change during table motion may include point-to-point distances between control points, interior angles formed by sets of three control points, the center of curvature of the control point constellation in a barycentric reference frame, and/or the like. Such embodiments may be used, for example, when no information about the table movement is available and/or when the table movement is performed without convert the table movement into the reference frame of the control point constellation using a registration transform. According to some embodiments, the sequence of the processes **410-460** performed during method **400** may be rearranged and/or one or more of the processes **410-460** may be performed concurrently. In some examples, the process **420** of determining an expected configuration may be performed before, concurrently with, or after the process **430** of determining an actual configuration. In some examples, the process **450** of determining the offending arms may be performed before, concurrently with, or after the process **460** of raising an alert. According to some examples, a plurality of predetermined thresholds may be checked during the process **440** to trigger remedial actions of varying severity at the process

460. For example, a first predetermined threshold may, when exceeded, trigger a warning to the operator at the process **460** but allow continued table movement, and a second predetermined threshold may, when exceeded, disable table movement at the process **460**.

(72) FIG. 5 is a simplified diagram of a control point position **500** during table movement in a height-only mode according to some embodiments. FIG. 5 depicts traces of vertical position (z axis) versus time (1 axis). In some embodiments consistent with the embodiments of FIG. 4, FIG. 5 illustrates an application of the method **400** during table movement in a height-only mode (i.e. where the table movement is restricted to translation in a vertical direction). In some examples consistent with FIGS. 2 and 3, the height-only mode may be enforced when the number of control points being monitored is less than three and/or when the registration between the surgical table and the computer-assisted device has not been performed and the table base to device base transform **325** is not known.

(73) Expected position **510** and actual position **520** are traces that depict an expected position and actual position of a control point over time, respectively. Predetermined threshold **530** is a range of allowable positions corresponding to expected position **510** over time. Phases **540** include a pre-latching phase **540a**, a tracking phase **540b**, an undetected disturbance phase **540c**, and a detected disturbance phase **540d**. During pre-latching phase **540a**, no table movement is permitted, as the control point monitoring has not yet begun. Between pre-latching phase **540a** and tracking phase **540b**, a latched position of the control point is determined and height-only table movement is subsequently permitted. In embodiments consistent with FIG. 4, the latched position is determined using the process **410** where the control point configuration specifies the position of the control point in a fixed reference coordinate frame.

(74) During tracking phase **540b**, height-only table movement occurs, and the control point freely tracks the table movement. When the table is raised as depicted in FIG. 5, the expected position **510** rises with the table. The actual position **520** generally tracks the expected position **510** during tracking phase **540b**, although some small, routine deviations between the actual and expected positions may be observed. In embodiments consistent with FIG. 4, the expected position **510** is determined using the process **420** and the actual position **520** is determined using the process **430**. The expected position **510** and actual position **520** may be represented in the reference frame of the latched position and/or differentially represented relative to the latched position. Also during tracking phase **540b**, the expected position **510** and actual position **520** are compared to determine whether the actual position **520** is within the allowable range given by the predetermined threshold **530**. In embodiments consistent with FIG. 4, the comparison is performed using the process **440** where the value of the predetermined threshold is set to a clinically acceptable distance, such as 12 mm. Although only the vertical component of the allowable range of positions is depicted in FIG. 5 for simplicity, it is to be understood that the comparison may be performed in up to three dimensions, such that a deviation between the expected position **510** and actual position **520** in any direction may be detected. Thus, in some embodiments, the allowable range of positions forms a sphere of allowable positions in three dimensions. As depicted in FIG. 5, during the tracking phase **540b** the difference between the expected position **510** and actual position **520** does not exceed the predetermined threshold **530**.

(75) Between tracking phase **540b** and undetected disturbance phase **540c**, a disturbance **550** occurs that prevents the control point from freely tracking the table movement. Disturbance **550** may include any of the disturbances discussed above with respect to FIG. 4, such as encountering an obstacle that blocks the control point from rising beyond a given height as depicted in FIG. 5. Thus, during undetected disturbance phase **540c** the actual position **520** no longer closely tracks the expected position **510**. However, the distance between the actual position **520** and expected position **510** does not yet exceed the predetermined threshold **530**. Therefore, table movement is allowed to continue while the distance between the actual position **520** and expected position **510** approaches the predetermined threshold **530**.

(76) Between undetected disturbance phase **540c** and detected disturbance phase **540d**, the distance between the actual position **520** and expected position reaches the predetermined threshold **530**, causing an alert to be raised. In embodiments consistent with FIG. 4, offending arm detection using the process **450** and/or remedial actions using the process **460** may subsequently occur at the beginning of detected disturbance phase **540d**. In the embodiment depicted in FIG. 5, table movement is disabled during disturbance detected phase **540d** such that the difference between the actual position **520** and expected position **510** does not increase beyond the predetermined threshold **530**. Further, when more than one control point is being monitored, the one or more offending arms may be determined using any of the mechanisms discussed previously with respect to the process **450**, such as by identifying the control point with the largest difference between actual and expected positions and/or by identifying all of the control points for which the predetermined threshold **530** is exceeded. The operator may optionally be alerted to the detected disturbance and/or the identity of the offending arms by any of the feedback mechanisms discussed with respect to the process **460**, such as an audible alarm indicating that a disturbance was detected and/or flashing lights that indicate the offending arms. In some embodiments, table movement may remain disabled until the operator addresses the disturbance, such as by manually repositioning the one or more offending arms.

(77) As discussed above and further emphasized here, FIG. 5 is merely an example which should not unduly limit the scope of the claims. One of ordinary skill in the art would recognize many variations, alternatives, and modifications. According to some embodiments, the z axis of FIG. 5 may represent any geometric attribute of a control point constellation, including a vertical or horizontal position, an orientation, a point-to-point distance, interior angle, and/or the like. Accordingly, procedure **500** may illustrate a method for monitoring any geometric attribute of the control point constellation.

(78) FIG. 6 is a simplified diagram of a control point constellation **600** during rotational table movement according to some embodiments. FIG. 6 depicts a three-dimensional arrangement of a control point constellation in a barycentric reference frame with the origin located at the average position of the plurality of control points. In some embodiments consistent with the embodiments of FIG. 4, FIG. 6 illustrates an application of the method **400** to table movement in a mode where rotations such as tilt, Trendelenburg, and/or reverse Trendelenburg rotations are allowed. In some examples consistent with FIGS. 2 and 3, rotational table movement may be allowed when the registration transform **325** is known, such as when the number of control points being monitored is at least three and/or after a registration between the surgical table and the computer-assisted device has been performed.

(79) Expected configuration **610** includes paths **610a-c** that represent the expected positions of control points in control point constellation **600** over time, actual configuration **620** includes paths **620a-c** that represent actual positions of the control points over time, and predetermined threshold **630** includes ranges of allowable positions **630a-c** corresponding to the expected configuration **610** over time. Reference frame **640** represents a barycentric reference frame used to determine the control point positions. Prior to rotating the table and/or prior to determining a latched configuration of the control point constellation, a registration transform is determined. In some embodiments consistent with FIGS. 2 and 3, the registration transform may correspond to registration transform **325** and/or alternate registration transform **325** and may be determined using a 0% registration and/or an XY registration. Accordingly, a rotation of the table relative to table base coordinates **305** by a given angle may be converted into device base coordinates **320** by application of registration transform **325**.

(80) At the beginning of table motion, and after $\theta_{sub.Z}$ and/or XY registration, a latched configuration of the control point constellation is determined. In some embodiments consistent with the embodiments of FIG. 4, the latched configuration is determined using the process **410** in the reference frame **640** before table rotation. The latched configuration specifies the position of

each control point and/or one or more geometric attributes of the control point constellation such as the magnitude of the angle formed by the control point constellation relative to the reference frame **640** before table rotation. Once the latched configuration is determined, control point monitoring during table movement begins. In some embodiments consistent with the embodiments of FIG. 4, control point monitoring is performed using the processes **420-440** to determine whether the actual configuration of the control point constellation has deviated from the expected configuration of the control point constellation by more than the predetermined threshold **630**. Because reference frame **640** is barycentric, translational movement of the table, such as a height adjustment, slide adjustment, and/or translational movement corresponding to a rotational movement of the table at positions other than an isocenter, does not change the expected configuration **610**. Meanwhile, rotational movement of the table changes the orientation of the expected configuration **610**, with the direction and magnitude of the change being determined using the detected table movement and the registration transform. It should be noted that although the actual center of the control point constellation may be translating, because the coordinate frames **640** are barycentric it is only the relative positions about the center of the control point constellation that are considered.

(81) Control point constellation **600** illustrates a rotation that results in a change in the orientation of expected configuration relative to the reference frame **640**. Like the example shown in FIG. 5, the actual configuration **620** generally tracks the expected configuration **610** within the predetermined threshold **630**. For simplicity, the geometric attribute depicted in FIG. 6 is position, but it is to be understood that other geometric attributes, such as the magnitude of the angle formed by the actual configuration **620** relative to reference frame **640**, may also be compared with expected configuration **610** and checked against a corresponding threshold value (i.e., a rotation magnitude check).

(82) Control point constellation **600** also illustrates a disturbance **650** that results in control point path **620c** diverging from the expected path **610c** beyond the allowable range **630c**. In some embodiments consistent with the embodiments of FIG. 4, surpassing the threshold results in an alert being raised during the process **440** such that one or more of the processes of offending arm identification **450** and/or remedial action **460** are performed. In some embodiments, the offending arm corresponding to control point path **620c** may be determined using any of the mechanisms discussed previously with respect to the process **450**, such as by identifying the control point with the largest difference between the actual and expected path lengths. In some embodiments, such as when performing a rotation magnitude check, all of the arms may be identified as offending arms. The operator may be alerted to the detected disturbance and/or the identity of the offending arms by any of the feedback mechanisms discussed with respect to the process **460**, such as an audible alarm indicating that a disturbance was detected and/or flashing lights that indicate the offending arm.

(83) As discussed above and further emphasized here, FIG. 6 is merely an example which should not unduly limit the scope of the claims. One of ordinary skill in the art would recognize many variations, alternatives, and modifications. According to some embodiments, control point constellation **600** may include more or less than the three control points depicted. According to some embodiments, the control points may be approximately collinear (i.e. forming a nearly straight line rather than a triangle and/or the like) in which case the sensitivity to rotational movement along one or more axes may decrease. In such embodiments, one or more compensatory actions may be taken when a low sensitivity arrangement is identified, such as disabling rotational table movement, reducing the predetermined thresholds, alerting the operator to the reduced sensitivity and/or increased uncertainty of the monitoring, and/or the like.

(84) Some examples of control units, such as control unit **130** may include non-transient, tangible, machine readable media that include executable code that when run by one or more processors (e.g., processor **140**) may cause the one or more processors to perform the processes of method **400**. Some common forms of machine readable media that may include the processes of method

400 are, for example, floppy disk, flexible disk, hard disk, magnetic tape, any other magnetic medium, CD-ROM, any other optical medium, punch cards, paper tape, any other physical medium with patterns of holes, RAM, PROM, EPROM, FLASH-EPROM, any other memory chip or cartridge, and/or any other medium from which a processor or computer is adapted to read. (85) Although illustrative embodiments have been shown and described, a wide range of modification, change and substitution is contemplated in the foregoing disclosure and in some instances, some features of the embodiments may be employed without a corresponding use of other features. One of ordinary skill in the art would recognize many variations, alternatives, and modifications. Thus, the scope of the invention should be limited only by the following claims, and it is appropriate that the claims be construed broadly and in a manner consistent with the scope of the embodiments disclosed herein.

Claims

1. A computer-assisted device comprising: a plurality of manipulators, each manipulator of the plurality of manipulators being configured to support an instrument, each manipulator of the plurality of manipulators having a control point of a plurality of control points; and a control unit communicatively coupled to the plurality of manipulators; wherein the control unit is configured to: determine a first spatial configuration of the plurality of control points, the first spatial configuration being prior to a movement of a table associated with the computer-assisted device, the table being separate from the computer-assisted device, and the movement of the table causing motion of at least one control point of the plurality of control points; determine the movement of the table; determine, based on the movement of the table and the first spatial configuration, an expected spatial configuration of the plurality of control points; determine, based on a comparison of the expected spatial configuration with an actual spatial configuration of the plurality of control points, whether to perform a remedial action; and perform the remedial action in response to a determination to perform the remedial action.
2. The computer-assisted device of claim 1, wherein manipulators of the plurality of manipulators are mechanically grounded to a common support structure.
3. The computer-assisted device of claim 2, wherein the common support structure comprises a cart physically separate from the table.
4. The computer-assisted device of claim 1, further comprising: a master control; wherein the control unit is further configured to teleoperate a first manipulator of the plurality of manipulators to pivot about the control point of the first manipulator in response to a user input to the master control.
5. The computer-assisted device of claim 1, wherein to determine the movement of the table, the control unit is configured to receive position or motion information from a control unit of the table, the position or motion information being of the table or a top of the table.
6. The computer-assisted device of claim 1, wherein to determine the expected spatial configuration, the control unit is configured to predict one or more changes in a position of the at least one control point based on the first spatial configuration and the movement of the table.
7. The computer-assisted device of claim 1, wherein the control unit is further configured to perform the comparison by: determining a geometric attribute of the actual spatial configuration; determining an expected range for the geometric attribute based on the expected spatial configuration; and determining whether the geometric attribute is within the expected range.
8. The computer-assisted device of claim 7, wherein the geometric attribute is selected from the group consisting of: a position of a first control point of the plurality of control points, a distance between two control points of the plurality of control points, an interior angle formed by three control points of the plurality of control points, a relative position of the first control point about a center of a control point constellation formed from the plurality of control points, a position of the

center, an orientation of the control point constellation, and a center of curvature of the control point constellation.

9. The computer-assisted device of claim 1, wherein the control unit is further configured to perform the comparison by: determining a difference between a first geometric attribute of the actual spatial configuration and a corresponding second geometric attribute of the expected spatial configuration.

10. The computer-assisted device of claim 9, wherein: the corresponding second geometric attribute is not expected to change from the first spatial configuration to the expected spatial configuration; and the corresponding second geometric attribute is selected from the group consisting of: a distance between two of the plurality of control points; an interior angle formed by three of the plurality of control points; and a relative position of one of the plurality of control points about a center, the center being of a control point constellation formed from the plurality of control points.

11. The computer-assisted device of claim 1, wherein to perform the comparison, the control unit is configured to: determine a first actual path, the first actual path representative of actual positions of a first control point of the plurality of control points over time between the first spatial configuration and the actual spatial configuration; determine an expected path, the expected path representative of expected positions of the first control point over time between the first spatial configuration and the expected spatial configuration due to the movement of the table; and determine a difference between a first length of the first actual path and a second length of the expected path.

12. The computer-assisted device of claim 1, wherein a first control point of the plurality of control points corresponds to: a remote center of motion of a first manipulator of the plurality of manipulators.

13. The computer-assisted device of claim 1, wherein the remedial action comprises at least one action selected from the group consisting of: disabling movement of the table, alerting an operator, applying compensation to at least one of the plurality of manipulators, reporting an offending manipulator, and logging an error.

14. A method comprising: determining, by a control unit, a first control point constellation of a plurality of control points of a computer-assisted device, the computer-assisted device comprising a plurality of manipulators, each manipulator of the plurality of manipulators being configured to support an instrument, each manipulator of the plurality of manipulators having a control point of the plurality of control points, the first control point constellation being prior to a movement of a table associated with the computer-assisted device, the table being separate from the computer-assisted device, and the movement of the table causing motion of at least one control point of the plurality of control points; determining, by the control unit, the movement of the table; determining, by the control unit based on the movement of the table and the first control point constellation, an expected control point constellation of the plurality of control points; determining, by the control unit based on a comparison of the expected control point constellation with an actual control point constellation of the plurality of control points, whether to perform a remedial action; and performing, by the control unit, the remedial action in response to a determination to perform the remedial action.

15. The method of claim 14, further comprising: teleoperating a first manipulator of the plurality of manipulators to pivot about the control point of the first manipulator in response to a user input to a master control.

16. The method of claim 14, wherein determining the movement of the table comprises receiving position or motion information from a control unit of the table, the position or motion information being of the table or a top of the table.

17. The method of claim 14, wherein determining the expected control point constellation comprises predicting one or more changes in a position or an orientation of the at least one control

point based on the first control point constellation and the movement of the table.

18. The method of claim 14, further comprising: determining, by the control unit, a geometric attribute of the actual control point constellation; determining, by the control unit, an expected range for the geometric attribute based on the expected control point constellation; and determining, by the control unit, whether the geometric attribute is within the expected range.

19. The method of claim 14, wherein performing the comparison comprises: determining a first actual path, the first actual path representative of actual positions of a first control point of the plurality of control points over time between the first control point constellation and the actual control point constellation; determining an expected path, the expected path representative of expected positions of the first control point over time between the first control point constellation and the expected control point constellation due to the movement of the table; and determining a difference between a first length of the first actual path and a second length of the expected path.

20. A non-transitory machine-readable medium comprising a plurality of machine-readable instructions which when executed by one or more processors associated with a computer-assisted device are adapted to cause the one or more processors to perform a method comprising: determining a first geometric configuration of a plurality of control points of the computer-assisted device, the computer-assisted device comprising a plurality of manipulators, each manipulator of the plurality of manipulators being configured to support an instrument, each manipulator of the plurality of manipulators having a control point of the plurality of control points, the first geometric configuration being prior to a movement of a table associated with the computer-assisted device, the table being separate from the computer-assisted device, and the movement of the table causing motion of at least one control point of the plurality of control points; determining the movement of the table; determining, based on the movement of the table and the first geometric configuration, an expected geometric configuration of the plurality of control points; determining, based on a comparison of the expected geometric configuration with an actual geometric configuration of the plurality of control points, whether to perform a remedial action; and performing the remedial action in response to a determination to perform the remedial action.

21. The non-transitory machine-readable medium of claim 20, wherein the method further comprises: teleoperating a first manipulator of the plurality of manipulators to pivot about the control point of the first manipulator in response to a user input to a master control.
