

(12) **United States Patent**
Richardson et al.

(10) **Patent No.:** **US 12,409,290 B2**
(45) **Date of Patent:** **Sep. 9, 2025**

(54) **PATIENT INTERFACE AND ASPECTS THEREOF**

(71) Applicant: **Fisher & Paykel Healthcare Limited**,
Auckland (NZ)

(72) Inventors: **Thomas Mark Richardson**, Auckland
(NZ); **Jonathan Mark Downey**,
Auckland (NZ); **Janine Elizabeth
Collins**, Auckland (NZ)

(73) Assignee: **Fisher & Paykel Healthcare Limited**,
Auckland (NZ)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **18/482,405**

(22) Filed: **Oct. 6, 2023**

(65) **Prior Publication Data**

US 2024/0082525 A1 Mar. 14, 2024

Related U.S. Application Data

(63) Continuation of application No. 17/378,586, filed on
Jul. 16, 2021, now Pat. No. 11,806,475, which is a
continuation of application No. 15/560,992, filed as
application No. PCT/IB2016/051665 on Mar. 24,
2016, now Pat. No. 11,097,077.

(60) Provisional application No. 62/261,177, filed on Nov.
30, 2015, provisional application No. 62/139,562,
filed on Mar. 27, 2015.

(51) **Int. Cl.**
A61M 16/06 (2006.01)
A61M 16/08 (2006.01)

(52) **U.S. Cl.**
CPC **A61M 16/0616** (2014.02); **A61M 16/0666**
(2013.01); **A61M 16/0611** (2014.02); **A61M**
16/08 (2013.01)

(58) **Field of Classification Search**

CPC A61M 16/0666-0677; A61M 16/0616;
A61M 16/0611-0622

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,739,755 A 4/1988 White et al.
4,782,832 A 11/1988 Trimble et al.

(Continued)

FOREIGN PATENT DOCUMENTS

CA 2919449 4/2022
EP 2022528 2/2009

(Continued)

OTHER PUBLICATIONS

Farkas et al., "Geography of the nose: a morphometric study",
Aesthetic Plastic Surgery, vol. 10, No. 4, pp. 191-223, 1986.

(Continued)

Primary Examiner — Joseph D. Boecker


Assistant Examiner — Thomas W Greig

(74) *Attorney, Agent, or Firm* — VIA LLP

(57) **ABSTRACT**

A patient interface can have a frame supporting a sealing
member. Various features of the sealing member can
improve comfort and sealing performance in the context of
forming seals with the nares of a user, as well as contact with
other facial surfaces. The sealing member can include con-
vex portions, concave portions and thickness variations for
providing various sealing, comfort, and deformability
effects.

9 Claims, 43 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

6,431,172	B1 *	8/2002	Bordewick	A61M 16/0666	128/207.18
7,987,850	B2	8/2011	Zollinger et al.		
9,205,215	B2	12/2015	McAuley et al.		
11,097,077	B2	8/2021	Richardson et al.		
11,229,761	B2	1/2022	Downey et al.		
11,806,475	B2	11/2023	Richardson et al.		
2005/0028822	A1 *	2/2005	Sleeper	A61M 16/0833	128/207.18
2007/0125387	A1	6/2007	Zollinger et al.		
2007/0163600	A1	7/2007	Hoffman		
2008/0060657	A1 *	3/2008	McAuley	A61M 16/024	128/207.18
2009/0000623	A1	1/2009	Lynch		
2009/0044808	A1	2/2009	Guney et al.		
2009/0183739	A1 *	7/2009	Wondka	A61M 16/0875	128/207.18
2009/0217929	A1	9/2009	Kwok et al.		
2010/0229868	A1	9/2010	Rummery et al.		
2010/0294281	A1	11/2010	Ho		
2011/0146685	A1	6/2011	Allan et al.		
2012/0067349	A1	3/2012	Barlow et al.		
2012/0132209	A1	5/2012	Rummery et al.		
2012/0204870	A1	8/2012	McAuley et al.		
2012/0266890	A1	10/2012	Baecke et al.		
2013/0133664	A1	5/2013	Startare et al.		
2013/0186403	A1 *	7/2013	Chang	A61M 16/06	128/205.25
2014/0174446	A1	6/2014	Prentice et al.		
2014/0366885	A1	12/2014	Haibach		
2016/0095996	A1	4/2016	Gusky et al.		
2018/0078725	A1	3/2018	Richardson et al.		
2019/0022343	A1	1/2019	Kooij et al.		
2019/0117923	A1	4/2019	Downey et al.		
2021/0386950	A1	12/2021	Downey et al.		
2022/0249793	A1	8/2022	Downey et al.		

FOREIGN PATENT DOCUMENTS

EP	2679266	1/2014
EP	2679267	1/2014
JP	5102774	12/2012
WO	WO 2006/130903	12/2006
WO	WO 2007/064660	6/2007
WO	WO 2008/100860	8/2008
WO	WO 2009/151344	12/2009
WO	WO 2012/020359	2/2012
WO	WO 2013/168134	11/2013
WO	WO 2014/110626	4/2014
WO	WO 2014/155329	10/2014
WO	WO 2015/009172	1/2015
WO	WO 2015/020540	2/2015
WO	WO 2016/043607	3/2016
WO	WO 2016/157040	10/2016

OTHER PUBLICATIONS

Australian Government, Examination Report No. 1 for Standard Patent Application, Application No. 2016241413, dated Nov. 15, 2019, in 5 pages.

European Patent Office, Extended European Search Report, Application No. PCT/IB2017/052292, dated Nov. 12, 2019, in 5 pages. European Search Report and Search Opinion for Application No. 16 771 484.9.

European Patent Office, Extended European Search Report, Application No. 20191302.7-1122, dated Oct. 29, 2020, in 9 pages.

European Search Report, PCT/IB2016/051665, dated Nov. 13, 2018, in 9 pages.

International Search Report, Application No. PCT/IB2016/051665, dated Jun. 7, 2016, in 4 pages.

International Search Report for International Application No. PCT/IB2017/052292 mailed on Aug. 7, 2017.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 7D







FIG. 7E






FIG. 8




FIG. 9




FIG. 10




FIG. 11





FIG. 13




FIG. 14







FIG. 15






FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34

Seal Compression - Bellows Designs A-B




FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 40




FIG. 41




FIG. 42A




FIG. 42B




FIG. 42C




FIG. 42D




FIG. 42E




FIG. 42F




FIG. 42G




FIG. 42H




FIG. 42I




FIG. 43




FIG. 44




FIG. 45




FIG. 46




FIG. 47




FIG. 48




FIG. 49




FIG. 50A




FIG. 50B




FIG. 50C




FIG. 51




FIG. 52




FIG. 53A




FIG. 53B




FIG. 54A




FIG. 54B




FIG. 54C

1

PATIENT INTERFACE AND ASPECTS THEREOF

INCORPORATION BY REFERENCE TO ANY PRIORITY APPLICATIONS

Any and all applications for which a foreign or domestic priority claim is identified in the Application Data Sheet as filed with the present application are hereby incorporated by reference herein in their entireties and made a part of the present disclosure. The present application claims the priority benefit of U.S. Provisional Application No. 62/139,562, filed Mar. 27, 2015, and 62/261,177, filed Nov. 30, 2015, the entirety of each of which is hereby incorporated by reference herein.

BACKGROUND OF THE INVENTIONS

Field of the Inventions

The inventions disclosed herein generally relate to interfaces for providing a supply of breathable gas to a recipient.

Description of Related Art

Breathing gases can be delivered to users with a variety of different mask styles and can be delivered for a variety of different purposes. For example, users can be ventilated using non-invasive ventilation (NIV). In addition, continuous positive airway pressure (CPAP) or variable airway pressure can be delivered using masks to treat a medical disorder, such as obstructive sleep apnea (OSA), chronic obstructive pulmonary disease (COPD), or congestive heart failure (CHF).

These non-invasive ventilation and pressure support therapies generally involve the placement of a user interface device, which is typically a nasal or nasal/oral mask, on the face of a user. The flow of breathing gas can be delivered from the pressure/flow generating device to the airway of the user through the mask.

Typically, patient interface devices include a mask frame that supports a sealing member. The sealing member contacts the facial surfaces of the user, including regions surrounding the nose, including the nose and the nares. Because such masks are typically worn for an extended period of time, a variety of concerns must be taken into consideration. For example, in providing CPAP to treat OSA, the user normally wears the mask all night long while he or she sleeps. One concern in such a situation is that the mask should be as comfortable as possible. It is also important that the mask provide a sufficient seal against a user's face without significant discomfort.

SUMMARY OF THE INVENTIONS

Accordingly, it is an object of certain embodiments of the present disclosure to provide an improved sealing member for use in a mask assembly that overcomes the shortcomings of conventional sealing members.

In some configurations, a nasal seal includes a seal body formed of a soft flexible material and having a sidewall that at least partially defines an inner cavity. The seal body comprises a sealing portion having a first nostril prong and a second nostril prong. A base portion of the seal body defines a supply opening that allows a supply of breathing gases to be provided to the inner cavity. A bellows portion is defined by the sidewall. The bellows portion is located

2

between the sealing portion and the supply opening. The bellows portion comprises an indentation that extends circumferentially around the seal body and supports both the first nostril prong and the second nostril prong.

5 In some configurations, the indentation has a curved shape in cross-section.

In some configurations, the indentation extends around an entire circumference of the seal body.

10 In some configurations, the indentation is concave and defined between a convex base portion of the seal body and a convex sealing portion of the seal body. The convex base portion extends between the indentation and the supply opening and the convex sealing portion extending between the indentation and the first and second nostril prongs.

15 In some configurations, the bellows portion is configured to allow for linear compression and/or expansion of the seal body in an axial direction along an axis extending through a center of the supply opening and between the first and second nostril prongs.

20 In some configurations, the bellows portion allows the prongs to pivot such that an angle of the prongs relative to the supply opening can vary.

In some configurations, a volume of a portion of the inner cavity defined by the base portion is less than a volume of a portion of the inner cavity defined by the sealing portion.

25 In some configurations, a curvature of the bellows portion corresponds to a curvature of a lower surface of the sealing portion adjacent the indentation, and wherein a distance between the bellows portion and the lower surface of the sealing portion is substantially constant around a circumference of the seal body.

In some configurations, a thickness of the bellows portion is substantially constant throughout the bellows portion.

35 In some configurations, the sealing portion comprises a pair thickened regions, each associated with one of the first nostril prong and the second nostril prong.

In some configurations, the seal body comprises a thickened portion surrounding the supply opening.

40 In some configurations, a middle section of the bellows portion is thinner than a section of the bellows portion adjacent the supply opening and a section of the bellows portion closest to the first and second nostril prongs.

In some configurations, the supply opening is generally elliptical and a thickened portion that extends around and defines the supply opening is generally elliptical.

45 In some configurations, a nasal seal includes a seal body formed of a soft flexible material and defines an inner cavity and a supply opening for supply of breathing gases to the inner cavity. The seal body comprises a first nostril prong, a second nostril prong and a rolling section disposed in a sidewall portion of the seal body. The rolling section being located between the supply opening and the first and second nostril prongs. The rolling section is configured to roll over on itself to reduce a distance between the supply opening and the first and second nostril prongs.

55 In some configurations, the rolling section further comprises a rib that extends in a circumferential direction of the seal body.

60 In some configurations, the rib is configured to contact an interior surface of the seal body to limit the roll of the rolling section and maintain the first and second nostril prongs in an operational position.

In some configurations, the rib extends only partially around a circumference of the seal body.

65 In some configurations, the rib defines a gap in the front of the seal body.

In some configurations, the gap allows the rolling section in the front of the seal body to roll further towards or over the supply opening than the back of the seal.

In some configurations, the rib is disposed between the supply opening and the first and second nostril prongs and projects inwardly or outwardly from the sidewall portion.

In some configurations, the rib is positioned halfway between sealing surfaces of the first and second nostril prongs and the supply opening.

In some configurations, a thickness of the rolling section gradually varies between the rib and the supply opening, the rolling portion being thicker adjacent the rib and thinner adjacent the supply opening.

In some configurations, the rib is cantilevered from the sidewall portion, the rib tapering in thickness between a thicker portion adjacent the sidewall portion and a thinner portion further from the sidewall portion.

In some configurations, the supply opening is kidney bean shaped and generally follows the overall shape of the seal body.

In some configurations, an intersection between the rolling section and an end of the seal body that defines the supply opening is curved in a lateral direction of the nasal seal.

In some configurations, a nasal seal includes a seal body formed of a soft flexible material and defining an inner cavity that receives a supply of breathing gases. The seal body comprises a first nostril prong and a second nostril prong. Each of the first and second nostril prongs are non-conical and asymmetrical.

In some configurations, the seal body defines a supply opening through which the supply of breathing gases passes into the inner cavity, wherein the supply opening is non-circular in shape.

In some configurations, the supply opening is bean-shaped.

In some configurations, each of the first and second nostril prongs comprises a medial portion, wherein the medial portion is oriented at an angle relative to a central plane of the seal body.

In some configurations, the medial portion comprises an upper portion and a lower portion, wherein the angle relative to the central plane of the lower portion is greater than the angle relative to the central plane of the upper portion.

In some configurations, a rolling portion is defined by a sidewall portion of the seal body and configured to roll over on itself, the rolling portion comprising an upper portion configured to be distal of an upper lip of a user and a lower portion configured to be proximate the upper lip of the user. The upper portion provides less resistance to roll than the lower portion.

In some configurations, a proximal wall of the seal body comprises a concave portion extending in a lateral direction of the seal body and having a shape that generally conforms to a shape of an upper lip of a user.

In some configurations, the first nostril prong comprises a first sealing surface and the second nostril prong comprises a second sealing surface, wherein portions of the first and second sealing surfaces are convex.

In some configurations, the seal body comprises a central wall portion extending between and connecting the first nostril prong and the second nostril prong, wherein the central wall portion is spaced deeply from an end surface of the first and second nostril prongs such that contact between the central wall portion and a septum of the user is reduced or eliminated.

Various features, aspects and advantages of the present embodiments can be implemented in any of a variety of manners. For example, while several embodiments will be described herein, sets or subsets of features from any of the embodiments can be used with sets or subsets of features from any of the other embodiments.

The term “comprising” is used in the specification and claims, means “consisting at least in part of” When interpreting a statement in this specification and claims that includes “comprising”, features other than that or those prefaced by the term may also be present. Related terms such as “comprise” and “comprises” are to be interpreted in the same manner.

In this specification where reference has been made to patent specifications, other external documents, or other sources of information, this is generally for the purpose of providing a context for discussing the features of the inventions. Unless specifically stated otherwise, reference to such external documents is not to be construed as an admission that such documents, or such sources of information, in any jurisdiction, are prior art, or form part of the common general knowledge in the art.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other features, aspects and advantages of the present inventions are described below with reference to the following drawings.

FIG. 1 is a front, top, and right side perspective view of a patient interface including a seal, a conduit connector, and a gas supply conduit, configured in accordance with an embodiment.

FIG. 2 is a side elevational view of the interface of FIG. 1.

FIG. 3 is a view of the interface as viewed along line 3, of FIG. 2.

FIG. 4 is a front, left, and top perspective view of the interface of FIG. 1.

FIG. 5 is an embodiment of a seal body that can be used with the interface of FIGS. 1-4, viewed in a direction such as that on by arrow 3, in FIG. 2.

FIG. 6 is an enlarged schematic and partial sectional view of nostrils of a human patient.

FIG. 7 is a sectional view of the seal of FIG. 5 engaged with human nostrils schematically illustrated in FIG. 6.

FIG. 7a is a sectional view of the embodiment of FIG. 7, with certain lines removed.

FIG. 7b this is a schematic diagram illustrating variations in dimensions of nares amongst some human populations.

FIG. 7c is a view of the seal of FIG. 5, which schematic indications of examples of optional locations of sealing between the seal and the nares of differently-shaped human noses.

FIG. 7d is a top plan view of the seal with the schematic indications of FIG. 7c.

FIG. 7e is a left side elevational view of the seal with the schematic indications of FIG. 7c.

FIG. 7f is a top, front, and left side perspective view of a modification of the seal of FIG. 5.

FIG. 7g is a sectional view of the seal of FIG. 7f, taken along section line 7g.-7g.

FIG. 7h is a sectional view of the seal of FIG. 7f, taken along section line 7h.-7h.

FIG. 8 is a perspective and partial sectional view of the seal of FIG. 5.

5

FIG. 9 is another partial sectional and perspective view of the seal of FIG. 5.

FIG. 10 is a perspective view of the seal of FIG. 5.

FIG. 11 is a front elevational view of the seal of FIG. 5.

FIG. 12 is a perspective view of a modification of the seal of FIGS. 5-11.

FIG. 13 is a side elevational view of the seal of FIG. 12.

FIG. 14 is a sectional view of the seal taken along line 14-14 of FIG. 13.

FIG. 15 is an enlarged view of a portion of the sectional view of FIG. 14.

FIG. 16 is a sectional view of the seal taken along line 16-16 of FIG. 13.

FIG. 17 is a top plan view of seal of FIG. 12.

FIG. 18 is a skewed view of the seal of FIG. 12 as viewed in the direction of arrow 3, of FIG. 2.

FIG. 19 is a sectional view of the seal taken along line 16-16 of FIG. 13 and illustrating a lateral movement.

FIG. 20 is a top, front and left side perspective view of the seal member of FIG. 12, including shaded contours corresponding to optional thicknesses.

FIG. 21 is a left side elevational view of the seal with the thickness shading of FIG. 20.

FIG. 22 is a bottom, rear and left side perspective view of the seal with the thickness shading of FIG. 20.

FIG. 23 is a rear elevational view of the seal and with the thickness shading of FIG. 23.

FIG. 24 is a skewed view of the seal of FIG. 12 taken along a direction identified by arrow 3, of FIG. 2, and including schematic lines and shading as optional boundaries of different portions of the seal.

FIG. 25 is a top plan view of the seal of FIG. 20.

FIG. 26 is a side elevational view of the seal of FIG. 20.

FIG. 27 is a bottom plan view of the seal of FIG. 20.

FIG. 28 is a front elevational view of the seal of FIG. 20.

FIG. 29 is perspective view of the seal of FIG. 20.

FIG. 30 is a rear, right, and bottom perspective view of the seal of FIG. 20.

FIG. 31 is a perspective view of the seal of FIG. 20.

FIG. 32 is a perspective view of an example embodiment of a seal including a bellows.

FIG. 33 is a sectional view of the seal of FIG. 32 showing a longitudinal axis and possible pivoting movement of the seal.

FIG. 34 is a sectional view of the seal of FIG. 32 showing an outline of a compressed profile of the seal.

FIG. 35 is a force vs. compression graph.

FIG. 36 is a sectional view of the seal of FIG. 32.

FIG. 37 is another sectional view of the seal of FIG. 32.

FIG. 38 is a sectional view of the seal of FIG. 32 showing widths of various parts of the seal.

FIG. 39 is a sectional view of the seal of FIG. 32 showing an outline of a splayed profile of the seal.

FIG. 40 is sectional view of the seal of FIG. 32 showing an outline of an inflated profile of the seal.

FIG. 41 is a perspective view of an embodiment of the seal of FIG. 32 including a thickened region.

FIG. 42A is a sectional view of the seal of FIG. 32.

FIG. 42B is a view of the seal of FIG. 32 as viewed along line 3, of FIG. 2.

FIG. 42C is a side elevational view of the seal of FIG. 32.

FIGS. 42D, 42E and 42F show various views of the seal of FIG. 32 showing interior volumes of various regions of the seal.

FIGS. 42G, 42H and 42I show various views of the seal of FIG. 32 showing interior volumes of various regions of the seal.

6

FIG. 43 is a sectional view of an example embodiment of a seal having a rolling section.

FIG. 44 is a sectional view of the seal of FIG. 43 showing an outline of the rolling section of the seal in a rolled state.

FIG. 45 is a detail view of a portion of a sectional view of the seal of FIG. 43 showing an internal rib.

FIG. 46 is a detail view of a portion of a sectional view of the seal of FIG. 43 showing varying thickness in the rolling section.

FIG. 47 is a theoretical force v. displacement profile of the seal of FIG. 43.

FIG. 48 shows a force profile of the seal of FIG. 43.

FIG. 49 shows a heat map illustrating the thickness of various regions of the seal of FIG. 43.

FIGS. 50A, 50B and 50C illustrate front elevational views of the seal of FIG. 43.

FIG. 51 is a sectional view of the seal of FIG. 43 showing a depth of the rolling section.

FIG. 52 is a sectional view of the seal of FIG. 43 showing an outline of the seal in a splayed state.

FIG. 53A is a top view of the seal of FIG. 43.

FIG. 53B is a detail view of a connector receiving portion of the seal of FIG. 43.

FIGS. 54A, 54B and 54C are various views of the seal of FIG. 43.

DETAILED DESCRIPTION

FIGS. 1-4 schematically illustrate a patient interface 100 that can include one or any combination of certain features, aspects, and advantages described herein. The interface 100 can be used to supply pressurized breathing gases to a recipient, such as a user or a patient. The interface 100 can be used for providing breathing gases to a recipient in situations where significant pressure changes may be encountered. For example but without limitation, the interface 100 can be used for delivering continuous positive airway pressure (CPAP).

With continued reference to FIGS. 1-4, the patient interface 100 is shown separated from a patient who might wear the interface 100. Some aspects of the patient interface 100, and variations on each aspect, have been described in U.S. patent application Ser. No. 12/945,141, filed Nov. 12, 2010, which is hereby incorporated by reference in its entirety. The interface 100 can be in the form of a mask 102. In some configurations, a strap 104 can be used to secure the mask to a patient. In some configurations, the interface can also comprise a flexible supply conduit 106 which can connect to the mask 102.

The mask 102 can be configured to fit over or overlies both nostrils of a patient. The strap 104 can be wrapped around the user's head in a simple loop above the user's ears, although other configurations and uses for the strap 104 are also available. In some configurations, the mask 102 can include lateral extending portions (not shown) configured to curve around toward each lateral side of a nose of a patient. Such lateral portions can form a perimeter seal on outwardly facing surfaces of flanks of the nose. On the other hand, the embodiments disclosed herein are described in the context of masks, which can be referred to as nasal pillow masks, which do not include laterally extending portions configured to curve around toward each lateral side of the nose of a patient to contact or form a perimeter seal on outwardly facing surfaces of flanks of the nose of a patient, such as the wings 130 disclosed in PCT Application No. PCT/NZ2014/000150 filed Jul. 17, 2014. Some of the embodiments disclosed herein can provide beneficial advantages of

enhanced seals sealing performance and comfort while eliminating such laterally extending portions.

The flexible conduit 106 can depend from a central connection 112. In some configurations, the central connection 112 can be positioned at a frontal portion of the mask 102. The central connection 112 can include a swiveling elbow. Such a swiveling elbow can be configured to allow the flexible conduit 106 to pivot relative to the mask 102. By enabling pivoting, the elbow can help the interface 100 to better adapt to the sleeping positions of a patient. In some configurations, the central connection 112 may comprise a ball joint so that the elbow can pivot about axes parallel to and perpendicular to its connection with the mask 102. In some configurations, the central connection 112 may comprise a swivel or swivel elbow.

The illustrated mask 102 can generally comprise a seal 114 and a body or frame 116. The seal 114 and the frame 116 can be connected in any suitable manner.

The seal 114 can define a supple pocket or envelope that can contain a recess region. In some configurations, the seal 114 can comprise a low wall thickness and can be formed of any suitable material. For example but without limitation, the seal 114 can be formed of latex, vinyl, silicone or polyurethane. In some configurations the wall thickness can be below about 0.5 millimeters and could be lower than about 0.2 millimeters in some regions and in some configurations. Additionally, as described below, some portions of the seal 114 can include thickened regions having thicknesses of 0.7 millimeters, 0.9 millimeters, 1.2 millimeters, as well as greater thicknesses. In some configurations, the seal 114 can be formed of a material having sufficient elasticity and yield strength so that the combination renders the seal 114 supple. The seal 114 can be configured to withstand repeated drastic deformations without failure.

With continued reference to FIGS. 1-4, the seal 114 can include one or two nostril prongs 120, 121. The nostril locators 120, 121, can protrude from the seal 114. In some configurations, the nostril locators 120, 121 extend generally upwardly and rearwardly from a proximal wall 124 of the seal 114. As used herein, the term "proximal" is intended to refer to portions of the mask 102 that are proximate or closer to a patient during use. On the other hand, the term "distal" is used to refer to portions of the mask 102 which are disposed further away from a patient during use.

In the configurations illustrated in FIGS. 1-4, the nostril prongs 120, 121 are formed integrally (i.e., in a single monolithic piece) with the seal 114. Each nostril prong 120, 121 can comprise an outward aperture 118, 119 through which gas can be supplied from the flexible conduit 106, to nostrils of the patient. In some configurations, the gas can be supplied from within the pocket or envelope defined by the seal 114. In other configurations, the gas that is supplied can be separate from the gas supplied to the pocket or envelope defined by the seal 114.

The seal 114 can also be considered as having a distal wall 122. As such, an outer surface of the distal wall 122 would face away from the user during use, while an outer surface of the proximal wall 124 would face the user.

The seal 114 can also include left and right lateral walls 125, 126 disposed on the left and right sides, respectively, of the nostril prongs 120, 121. Additionally, the seal 114 can include an intermediate wall portion 127 extending between the nostril prongs 120, 121. The walls 122, 124, 125, 126 extend from the nostril prongs 120, 121 toward the flexible conduit 106, along the direction of arrow A in FIG. 2. Thus, proximal portions of the walls 122, 124, 125, 126 can be considered as connecting with the nostril prongs 120, 121.

Distal ends of the walls 122, 124, 125, 126 can extend to an inlet orifice 130 (FIG. 7). The inlet orifice 130 can be connected to the frame 116 and/or directly to the flexible conduit 106.

As such, the envelope or pocket described above can be defined within at least the distal wall 122 and the proximal wall 124 and/or optionally, the lateral walls 125, 126, or a combination thereof. The seal 114 can be configured to achieve a desired seal without wrapping around the tip or lower portion (e.g., locations below the bridge) onto substantial portions of the outer surfaces a user's nose. However, in some embodiments, the seal 114 can be designed to wrap around the tip or lower portion of a user's nose. The seal 114 can also be considered as including a central portion 128 which can be considered as including the nostril prongs 120, 121, and the central wall 127. The central portion 128 can, in some embodiments, include sealing surfaces of the mask 102 which form seals with the nostrils of a user during use. The central wall 127 can be disposed significantly deeper and further distally from the orifices 118, 119 than the other portions, such as the sealing surface within the central portion 128. As such, the central wall 127 provides improved clearance for the user's septum, reducing contact and potential discomfort or irritation.

As described above, optionally, a substantial portion of the seal 114 can be supple. For example, a region surrounding the nostril locators, such as the central region 128, can be more supple than distal portions of the walls 122, 124, 125, 126. Further, optionally, the proximal wall 124 and the nostril prongs 120, 121 can be very supple so that they can expand to conform to the contours of a user's nares. The supple portions of the seal 114 can be of sufficient dimension and shape that when positive pressure of gases within the seal 114 can partially expand portions of the seal 114 to enhance a seal between the seal 114 and the user's face, for example, nostrils of the user. Additionally, portions of the seal, for example, along proximal portions of the proximal wall 124 can rest against or provide the sealing engagement with a portion of the user's upper lip.

Optionally, portions of the seal 114 can have an increased rigidity to improve form, fit, and function of the mask 102. For example, portions of the seal 114 can be made significantly stiffer to provide control of ballooning of other regions of the seal 114. Further, distal portions of the walls 122, 124, 125, 126, for example, regions or areas adjacent to or proximate to the inlet orifice 130 (FIG. 7) can be less supple. Thus, for example, one or more the walls 122, 124, 125, 126 can have a decreasing suppleness from the proximal portions thereof to the distal portions thereof. Such less supple regions can be formed of a different material or can be formed of the same material but with an increased thickness.

The frame 116 can have any arrangement for fixation or connection to the seal 114. In some configurations, an annular wall can extend from a proximal side of the frame 116 around a perimeter of an opening extending to the connector 112. The annular wall can include an outwardly extending lip. The inlet orifice 130 of the seal 114 can engage over the outwardly extending lip of the annular wall. In some configurations, the inlet orifice 130 of the seal 114 can be stretched to fit over the annular wall. The inlet orifice 130 of the seal 114 can be provided with a thickened or reinforced wall section, for example but with limitation. In some configurations, an extended portion of the inlet orifice 130 can be rolled up over the annular wall of the frame 116. In other configurations, the seal 114 can be provided with a

portion of a connector on at least one of the frame 116 and the conduit 106 can include a complimentary connector portion.

The frame 116 can be configured to be minimal in size. For example, a small sized frame 116 can enable a clear field of vision for the user and can allow a user to wear glasses while wearing the interface 100. The frame 116 can be formed of an elastomeric material, which can allow the frame 116 to flex to conform slightly to the face of the user. The frame 116, however, can provide some support for the seal 114. By providing support for the seal 114, the seal 114 can be more effectively pressed into contact with the face and nose of the user. The frame 116 can be formed by injection molding, preferably from an elastic material, such as silicone or polyurethane, for example but without limitation. In some configurations, the frame 116 can be formed of more rigid materials, such as polycarbonate, polyester polystyrene, or nylon, for example but without limitation.

In use, portions of the seal 114 can be inflated and thus expanded outwardly. Pressure within the seal 114 (e.g., inflated from the flow of pressurized gases supplied to the patient interface 100) can press the sealing surfaces of the seal 114 against the skin of a user and to further conform to contours of the outside surfaces of the nose of the user, to surfaces of the lower portion of the nose of the user, to various portions of the nares of the user, as well as surfaces of the upper lip of the user immediately below the nose.

With reference to FIG. 6, the lower portion of a human nose 200 (illustrated in front elevation and partial cross section) can be considered as including the walls and surfaces and portions described below, the names of which are included herein for facilitating understanding of the present disclosure.

With continued reference to FIG. 6, the lower end of a human nose 200 can include a right nostril lateral wall 202, a left nostril lateral wall 204, and a septum 206. The right nostril lateral wall 202 extends from a forward facing surface of the patient's face, to the tip of the nose. Similarly, the left nostril lateral wall 204 extends from a left side of the user's face toward the tip of the nose. The septum 206 extends from the user's face to the tip of the nose, and between the left and right nostril lateral walls 202, 204. As such, the right nostril lateral wall 202 and the septum 206 define the right nostril 208 of the user. Similarly, the left nostril lateral wall 204 and the septum 206 define the right nostril 210 of the user.

The lower ends of the lateral walls 202, 204 and the septum 206 can be also considered as forming the nares of the user, including outer, inner and lower surfaces thereof.

For example, the lower portion of the right nostril lateral wall 202 can be considered as having lateral outer surface 212, bottom surface 214, and intermedial surface 216. Similarly, the lower portion of the left nostril lateral wall 204 can be considered as including outer lateral surface 218, bottom surface 220, and intermedial surface 222.

The septum 206 can be considered as including right lateral surface 224, bottom surface 226 and left lateral surface 228.

With reference to FIG. 5, the right and left nostril prongs 120, 121 can also be considered as including lateral, medial, proximal, and distal portions. For example, the right nostril prong 120 can be considered as including a proximal portion 240, a lateral portion 242, a distal portion 244 and a medial portion 246. Similarly, the left nostril prong 121 can be considered as including a proximal portion 250, a lateral portion 252, a distal portion 254 and a medial portion 256.

With continued reference to FIG. 7, as noted above, the seal 114 can be configured to be sufficiently supple that it can be inflated and thus expanded by positive pressure within the seal 114. Thus, for example, as illustrated in FIG. 7, such pressure can beneficially push the lateral portions 242, 252 of the right and left nostril prongs 120, 121 into enhanced contact with the medial surfaces 216, 222, and optionally further contact with the bottom surfaces 214, 220, and further optionally, the lateral surfaces 212, 218, optionally without making contact with substantial portions of the lateral surfaces 212, 218. Similarly, the medial portions 246, 256 can be pushed inwardly by the positive pressure, thereby increasing contact and sealing effect against the lateral walls 224, 228.

With continued reference to FIGS. 7 and 7a, as described above, the nostril prongs 120, 121 can be configured to seal against the septum 206 and the lateral nostril walls 202, 204, differently. For example, as described above, the medial portions 246, 256 of the nostril prongs 120, 121 can be configured, oriented, and/or shaped to press more against the lateral surfaces 220a, 224 of the septum 206 and reduce or minimize contact with bottom surface 226 of the septum 206. Optionally, the central wall 127, as noted above, can be spaced deeply between the nostril prongs 120, 121, so as to reduced or eliminate the likelihood of contact with any or a substantial portion of the bottom surface 226 of the septum 206. The degree to which the medial portions 246, 256 press against the lateral surfaces 224, 228 and less on the bottom surface 226 can be contrasted with the configuration, shape, and orientation of the laterals portions 242 and 252.

Optionally, the lateral portions 242, 252 can be shaped, configured and/or oriented so as to contact less of the medial portions 216, 222 of the right and left nostril walls 202, 204 and more of the bottom surfaces 214, 220 and the lateral surfaces 212, 218, during use, as compared with the contact of the medial portions 246, 256 with the corresponding portions of the septum 206, described above.

Asymmetric Prongs

With reference to FIGS. 7 and 7a, optionally, in some embodiments, the nostril prongs 120, 121 can be configured to provide a differential sealing contact with a user's nose 200, with an asymmetric prong shape. Certain aspects of the asymmetry of the prongs 120, 121 can be described with reference to a central plane P bisecting the seal 114 in a direction directly between the prongs 120, 121. For example, as shown in FIG. 7a, the medial portion 256 of the nostril prong 121 extends in a direction that is nearly vertical or in other words, parallel, nearly parallel, substantially parallel, or within approximately 10 degrees of the central plane P. In some embodiments, the medial portion 256 of nostril prong 121 extends at an angle, with respect to central plane P, of approximately 10 degrees, 0-15 degrees, 0-5 degrees, 5-10 degrees, 10-15 degrees, 5-15 degrees, greater than 0 degrees, or various sub-ranges of 0-15 degrees. The slope of the medial portion 256 is represented by line 270. With regard to this description of the seal 114, and other descriptions set forth below, in some instances, features are only described in connection with one of the prongs 120, 121, but it is to be understood that both of the prongs 120, 121 can have the same shape, and thus the descriptions would apply equally to both prongs 120, 121. With continued reference to FIG. 7a, in some embodiments, the medial portion 256 comprises an upper portion 256a and a lower portion 256b. The upper portion 256a can be angled, with respect to plane P, at approximately 10 degrees, 0-15 degrees, 0-5 degrees, 5-10 degrees, 10-15 degrees, 5-15 degrees, greater than 0 degrees, or various sub-ranges of

0-15 degrees. The lower portion **256b** of the medial portion **256** can be angled, with respect to plane P, at approximately 20 degrees, 0-30 degrees, 0-20 degrees, 10-30 degrees, 15-25 degrees. In some embodiments, the upper portion **256a** of the medial portion **256** comprises up to one half of the medial portion **256**.

In contrast to the slope of the medial portion **256**, the slope of the lateral portion **252** is not nearly parallel, approximately parallel or substantially parallel with the central plane P. Rather, the slope of the lateral portion **252** is transverse to the plane P and optionally can be nearly perpendicular to the plane P. In FIG. 7a, the slope of the lateral portion **252** is identified by the line **272**. The line **272** extends at an angle of about 75 degrees relative to the plane P. In some embodiments, the slope **272** can be within the range of approximately 60-90 degrees relative to the plane P. In some embodiments, the angle is approximately 70 degrees, 60-70 degrees, 70-80 degrees, 80-90 degrees, 60-75 degrees, 75-90 degrees, less than 90 degrees, or various sub-ranges of 60-90 degrees.

With continue reference to FIGS. 5 and 7a, the difference in shape between the medial portions **246**, **256** and the lateral portions **242**, **252** also extends, optionally, partly into the distal and proximal portions **244**, **254**, **240**, **250**. Additionally, the distal and proximal portions **244**, **254** can extend through contours so as to smoothly transition between the different shapes of the medial portions **246**, **256** and the lateral portions **242**, **252**. For example, portions of the proximal and distal portions **250**, **254** adjacent to the lateral portion **252** can have a similar shape, while portions of the proximal and distal portions **250**, **254** adjacent to the medial portion **256** can have a shape similar to the medial portion **256**, so as to provide a smooth transition around the periphery of the prongs **120**, **121**.

Convex Sealing Surface

Optionally, the seal **114** can include further features for sealing differently against the left and right lateral walls **202**, **204** compared to sealing against the septum **206**. For example, with reference to FIG. 7a, as noted above, the medial portions **246**, **256** of the prongs **120**, **121** extend generally vertical or parallel with the central plane P. In contrast, the lateral portions **242**, **252** can include a convex sealing surface positioned for contact with the lower portion of the patient's lateral nostril walls **202**, **204**.

As shown in FIG. 7a, a proximal end of the lateral portion **242** includes a concave portion **280**. Distal from the portion **280** is a convex portion **282**. The concave and convex portions **280**, **282** fall within the central area **128** which can be considered as comprising the sealing surfaces of the seal **114**, described above with reference to FIG. 3.

In some embodiments, the concave portion **280** can be smaller than the convex portion **282**. Thus, the concave portion may only act as a sealing surface on patients with particularly small nares. The convex portion **282** can be larger to accommodate a larger range of different size nares, and preferentially sealing against such nares with the convex portion **282** which is convex in a relaxed state, but may be deformed into a concave state upon application against a patient's nose **280**. In this respect, in at least some patients, the concave portion **280** may be a locating or alignment feature and the convex portion **282** is a sealing surface. Extending in a substantially horizontal angle can help limit the depth to which the nostril prongs **120**, **121** extend into the patient's nostrils **208**, **210**. Inserting prongs too deeply into a patient's nose can cause contact with sensitive internal surfaces of the nares and cause irritation and discomfort for the patient. Thus, the depth of the prongs **120**, **121** and the

extent to which prongs **120**, **121** would extend into a nose can be balanced with the need for stability provided by the prongs **120**, **121**, which is enhanced when the prongs **120**, **121** sit far enough within the nostrils that they aren't too easily displaced when the mask **102** moves on the patient's face. In a non-limiting example, the distance between the medial surface **246** and the lateral end of the concave portion **280** is approximately 12.7 millimeters, and the width of the convex portion **282** can be approximately 6.8 millimeters, as measured in the directions identified in FIG. 7a.

As noted above, the prongs **120**, **121** and have a concave sealing area which can be configured to provide reduced contact area with nares a user, so as to reduce irritation of the nares. Measurements of human noses have revealed that among at least some groups of human populations, the width x of a human septum **226**, is fairly constant, i.e., varies little. On the other hand, such measurements have revealed that the length y of human nares, as well as the outermost width of human nares, vary relatively more. Thus, the shape of the openings and the prongs **120**, **121** themselves, are generally non-conical and asymmetric so as to better accommodate these variations. For example, as noted above, because the width x of the human septum **226** varies little, the shape of the prongs **120**, **121**, in those areas which would contact a septum **226**, such as the medial walls **256**, **246**, can be fairly vertical so as to reduce the likelihood of irritation caused on the nares, such as the lateral wall portions **224**, **228**, and the lower wall of the septum **226**.

For example, with reference to FIG. 7c, longer and narrower nostrils can tend to seal around the prong **120** along sealing line **286**, smaller nostrils can tend to seal around the prong **120** along sealing line **287**, and wider nostrils can tend to seal around the prong **120** along sealing line **288**. With regard to FIG. 7d, comparison of the lines **286**, **287**, **288**, shows a distal-proximal variation Vz (generally corresponding to the "z" dimension identified above with reference to FIG. 7b) in the lateral locations of the lines **286**, **287**, **288**, on the lateral portions **242**, **252**, of the prongs **120**, **121**.

Similarly, with reference to FIG. 7e, comparison of the lines **286**, **287**, **288** shows a medial-lateral variation Vy (generally corresponding to the "y" dimension identified above with reference to FIG. 7b) of the locations of the feeling lines **286**, **287**, **288**, on the distal portions **244**, **254**, of the prongs **120**, **121**.

FIGS. 7f-7h illustrate a modification of the seal **114**, identified generally by the reference numeral **114a** that can also include the features described above with reference to seal **114** as well as the features described below with reference to seal **1114**.

Semi-Inflating Seal

As noted above, the sealing surfaces extending around the nostril prongs **120**, **121** can be made sufficiently flexible and supple so as to inflate to a degree when subject to positive air pressure within the seal **114**. Such inflation allows for more positive engagement between the sealing surfaces and the lower surfaces of the patient's nose. More specifically, the proximal, lateral, distal, and medial portions **240**, **242**, **244**, **246** of the nostril prong **120**, which comprise the sealing surfaces within the area **128**, can be made sufficiently thin and/or supple so as to partially inflate and deflect under positive pressure generated within the seal **114**. As such, these portions **240**, **242**, **244**, **246** can deflect to a degree, i.e., outwardly, so as to provide better positive sealing and engagement with the medial surface **228** of the septum **206** and the medial, bottom, and lateral surfaces **222**, **220**, **218** of the patient's lateral nostril wall **204**.

Lip Engagement

Optionally, the seal **114** can also include enhanced comfort and/or engagement with an upper lip of a patient. For example, with reference to FIG. 5, the proximal wall **124** can include a concave portion **290** extending in a lateral direction, transverse to the central plane P. This concave portion **290** can have a shape that generally conforms to a typical shape of a human's upper lip, and particularly the portion of the upper lip proximal to the lower end of the user's nose. Typically, the upper lip of a human extends in a lateral direction and has a generally convex shape. Thus, the concave portion **290** is configured to fit a typical human upper lip configuration. In some embodiments, the concave portion **290** extends over a distance **292** which is approximately equal to a distance between the centers of the nostril prongs **120**, **121**. However, other lengths of the concave portion can also be used.

In some embodiments, the concave portion **290** includes a radius of curvature **291** of approximately 12.5 mm, 10-15 mm, 12-13 mm, or various sub-ranges thereof. However, other configurations can also be used. Optionally, the thickness of the proximal wall **124**, in the area of the concave portion **290**, can be reduced so that it conforms more readily to the lip geometry of individual users. In a non-limiting exemplary embodiment, the thickness of the proximal wall **124** is approximately 0.7 mm.

Rolling Section

Optionally, the seal **114** can include a configuration for a preferential rolling deformation in the vicinity of the connection between the side walls of the seal **114** and the inlet orifice **130**. For example, as described above with reference to FIG. 2, the proximal, lateral, and distal walls **124**, **125**, **126**, **122**, extend from the nostril prongs **120**, **121** to the inlet orifice **130**. The distal ends of the walls **124**, **125**, **126**, **122**, include rolling portions formed in the vicinity of the inlet orifice **130**, for example, including the last few millimeters of the walls. For example, the walls can extend toward the inlet orifice **130** along the direction A (FIGS. 2 and 7), overshoot the connection point to the inlet orifice **130**, and curl back, in a direction opposite to the direction of arrow A. This overshoot and curl configuration generates an area in these walls which tends to deform first when forces are applied, causing a rolling deformation effect.

With reference to FIG. 11, the rolling portions at the distal ends of the walls **122**, **124**, **125**, **126** can be considered as being within the area **300**. Thus, the walls **122**, **124**, **125**, **126** can have associated rolling portions **302**, **304**, **306**, **308**, within the rolling area **300**, as illustrated in FIG. 11. The cross-section of FIG. 7 illustrates a configuration of the portions **306**, **308**.

As shown in FIG. 7, the wall **126** extends distally from the nostril prong **120** to the rolling portion **306**. The rolling portion **306** extends beyond the connection point **310**; i.e., lower than the connection point **310** as viewed in FIG. 7, then extends upwardly in a direction opposite to the direction of arrow A, to the connection point **310**. This overshoot and curled back configuration of the rolling portion **306** can provide for enhanced and preferential deformation and rolling of the rolling area **300**.

FIG. 9 illustrates rolling portions **302** and **304**. As shown in FIG. 9, the rolling portion **302** is generally larger than the rolling portion **304**. One characteristic of the rolling portion **302** that is larger than the rolling portion **304** is the magnitude of the overshoot, identified generally by the reference numeral **320**. As illustrated in FIG. 9, the overshoot **320** is larger than the overshoot **322**. In some embodiments, the

overshoot **320** can be approximately 1 millimeters and the overshoot **322** can be approximately 0.5 millimeters.

Another differentiating characteristic of the rolling portions **302** and **304** is the radial dimensions of the rolling portions **302**, **304**. For example, as shown in FIG. 9 the rolling portion **302** has a radial dimension **324** that is larger than a corresponding radial dimension **326** of the rolling portion **304**. In some embodiments, the radial dimension **324** is approximately 8 mm. In some embodiments, the radial dimension **326** is approximately 3 mm.

These dimensional differences provide a differential rolling propensity of the rolling portions **302** and **304**. For example, the larger overshoot **320** and larger radial dimension **324** can cause the rolling portion **302** to roll more readily and through larger magnitudes of rolling deformation than the rolling portion **304**.

As such, although the rolling area **300** can extend around the entire periphery of the inlet orifice **130**, it can be configured to more readily roll and deform at the distal portions of the seal **114**. Thinner wall sections, near the inlet orifice **130**, for example, in the rolling area **300**, can help determine points at which rolling deformation is initiated or greater in magnitude.

The rolling area **300** can act as a shock absorber that can isolate effects of hose drag, for example, forces on the conduit **106** and tension that may be generated in the head gear or strap **104** (FIG. 1), preventing those forces or tensions from affecting the seal performance. This can help reduce the likelihood that the nostril prongs **120**, **121** are pulled away from the patient's nose **200**, thereby preventing or reducing the likelihood of leaking.

With reference to FIG. 9, during use, the inlet orifice **130** can be relatively close to the upper lip of the user. Thus, lower portions of the frame **116** and connector **112** can also be close to the upper lip of the user. Thus, by providing the rolling section **304** with smaller dimensions and or larger thicknesses can provide the optional benefit of a lower propensity for rolling. Optionally, the rolling portion **304** can be configured for very little rolling in this area. Such rolling portions **300** can help reduce the likelihood that the seal **114** will collapse on the patient's lip or other parts of the face, thereby providing an enhanced degree of stability that helps maintain the position of the sealing surfaces relative to the lower nasal surfaces of the user's nose **200**. Optionally, the rolling portion **302** can have a continuous curve to thereby increase the likelihood that the portion **302** will roll rather than collapse or fold during use.

FIGS. 12-31 illustrate a modification of the seal **114**, identified generally by the reference numeral **1114**. Parts, components, and features of the seal **1114** which are similar or the same as corresponding parts, components, or features of the seal **114** are identified with the same reference numeral, except that 1000 has been added thereto.

With reference to FIGS. 12-19, the seal **1114** can include the same features of the seal **114** noted above with respect to asymmetric prongs, convex sealing surfaces, semi-inflating, lip engagement, and rolling. Thus, those features which can optionally be embodied in the seal **1114**, are not further described below.

The seal **1114** includes an optional configuration for enhancing response to lateral forces and a rolling movement accommodated by the lateral walls **1125**, **1126**.

With reference to FIG. 16, the lateral wall **1125** can be considered as extending from the nostril prong **120**, in the direction of arrow A, toward the inlet orifice **1130**. The seal **1114** can optionally include the rolling portion **306** in the area proximal to the inlet orifice **1130**. Additionally, the seal

15

1114 can include an additional rolling portion 1400 in the lateral wall 1125. The seal 1114 can include an additional rolling portion 1400 in the lateral wall 1126. For brevity, the description set forth below of the rolling portion 1400 only with reference to the lateral wall 1125, however, this description also applies equally to the lateral wall 1126.

With reference to FIG. 19, as noted above with reference to the seal 1114 and FIG. 7a, the medial portion 1256 comprises an upper portion 1256a and a lower portion 1256b. The upper portion 1256a can be angled, with respect to plane P, at approximately 10 degrees, 0-15 degrees, 0-5 degrees, 5-10 degrees, 10-15 degrees, 5-15 degrees, greater than 0 degrees, or various sub-ranges of 0-15 degrees. The lower portion 1256b of the medial portion 1256 can be angled, with respect to plane P, at approximately 20 degrees, 0-30 degrees, 0-20 degrees, 10-30 degrees, 15-25 degrees. In some embodiments, the upper portion 1256a of the medial portion 1256 comprises up to one half of the medial portion 1256.

As viewed in the cross-section of FIG. 16, the rolling portion 1400 can comprise a concave portion of the lateral wall 1125. With reference to FIG. 12, the concave portion 1400 can extend across the lateral wall 1125, in the circumferential direction around the seal 1114. Optionally, portions of the concave portion 1400 can extend onto portions of the distal wall 1122 and the proximal wall 1124. As noted above, the lateral 1126 can include the same or similar concave portion 1400.

By including a concave portion 1400 along the lateral wall 1125, between the nostril prong 120 and the rolling portion 306, the concave portion 1400 can help facilitate a more dispersed and larger magnitude rolling deformations. For example, with reference to FIG. 19, when a user is wearing a mask including the seal 1114, a lateral force F can cause deformation of the seal 1114. The force F can be caused by numerous different sources. For example, the force F can be generated when a user sleeps on their side with the side of their head resting on a pillow. In such as position, the pillow can push on a side of the seal 1114, frame 116 or the conduit 106. The force F can be caused in other ways as well.

In response to the force F, the seal 1114 can deform, for example, the inlet orifice 1130 can be pushed laterally towards the right, as viewed in FIG. 19, causing the side wall 1126 to deform, allowing the inlet orifice 1130 to move laterally relative to the nostril prongs 120, 121. This is also known as a “racking” motion. The concave portions 1400 can help allow the side walls 1125, 1126 to rack in response to the force F and thus more readily allow the motion to be accommodated without collapsing the seal 1114. In addition to “racking” motion, there may be some rolling or rotating (not shown) of the inlet orifice 1130 in response to the force F.

With reference to FIGS. 14 and 15, the seal 1114 can also include a thickened area 1410. As shown in FIG. 14, the thickened area 1410 can be approximately centered in the lateral walls 125, 126. Thus, as shown in the sectional view of FIG. 14, as the lateral wall 126 extends from the proximal wall 1124 toward the distal wall 1122, the thickness of the lateral wall 1126 starts from a thinner thickness adjacent to the proximal wall 1124, thickens in the thickened portion 1410, then reduces thickness again in the portions approaching the distal wall 1122. In some embodiments, the portions adjacent to the proximal wall 1124 can be in the range of 0.7 to 0.9 millimeters. The thickened portion can have a thickness of 1.2 millimeters, and the portions of the lateral wall 1126 adjacent the distal wall 1122 can have a thinner

16

thickness, for example, 0.7 millimeters. The above mentioned thicknesses are merely example and are not intended to be limiting.

With reference to FIGS. 20-23, the thickened portion 1410 of the seal 1114 can be roughly circular and can optionally be disposed within the concave portion 1400. As shown in the various views of FIGS. 20-23, the areas indicated by shading 1420 can be approximately 0.75 millimeters, the thickness of the region shaded 1422 can be approximately 0.9 millimeters, and the thickness of the region shaded 1424 can be approximately 1.1 millimeters. These thicknesses are merely examples of an embodiment, and other thicknesses can be used. As shown in FIGS. 21-23, additional thickened areas can be disposed near the rolling portion 1300.

The additional rolling structure provided to the lateral walls 1125, 1126 can provide for additional comfort and sealing performance. The concave portion 1400 and/or the thickened portion 1410 can provide an additional rolling section that forms a cushion and can act as a shock absorber, such that movement of the sealing surfaces extending around the nostril prongs 120, 121 and the movements of the frame 116 can be more isolated from one another. The concave portion 1400 can extend on portions of the seal 1114 forward from the patient's face and on lateral walls 1125, 1126, as described above.

The concave sections 1400 can be configured to provide more stability under lateral, side-to-side movement of the seal 1114, such as that illustrated and described above with reference to FIG. 19. An additional benefit is that the concave portions 1400 can help reduce the overall visual appearance of the sides of the seal 1114, improving patient acceptance.

Seal with Bellows

FIGS. 32-421 illustrate an example embodiment of a seal 500 that includes a sealing portion 510 and a lower bellows portion 520. The sealing portion 510 includes nostril prongs 120, 121 and sealing surfaces 512 that form seals with the nostrils of a user during use, which may be similar to other embodiments shown and described herein. The lower bellows portion 520 supports the sealing portion 510. The lower bellows portion 520 includes a bellows structure 522 and the inlet orifice 130.

The bellows structure 522 extends circumferentially around a portion or an entirety of a base and/or the inlet orifice 130 of the seal 500. The bellows structure 522 allows for linear compression and/or expansion of the seal 500 in an axial direction (e.g., along an axis extending through a center of the inlet orifice 130 and between the prongs 120, 121 as shown by the dashed lines in FIG. 33) as shown by outline 524 in FIG. 34. Such compression and/or expansion can advantageously compensate for and/or isolate hose drag (i.e., forces applied to the seal 500 by a conduit coupled to the inlet orifice 130) and/or can advantageously allow for adaptation to differing facial geometry of different users. In use, the lower bellows portion 520, e.g., the bellows structure 522, is configured to be in a compressed state when the seal 500 is fitted to the user's face. Therefore, if hose drag occurs, the lower bellows portion 520 expands away from the user's face before the sealing surfaces 512 and/or prongs 120, 121 are pulled away from the user's face, which can cause or allow for leaks between the seal 500 and user's face. A greater range of possible compression and extension of the lower bellows portion 520 allows the seal 500 to withstand a greater degree of hose drag. In some embodiments, an initial (i.e., in a relaxed state in which the seal 500 has not been expanded, compressed, splayed, or inflated as

described herein) height of the seal **500** (indicated by h_1 in FIG. **34**) is 32 mm. In some embodiments, when the seal **500** is fully or maximally compressed, a connector coupled to the inlet orifice **130** can be displaced (where the amount of displacement is indicated by h_2 in FIG. **34**) relative to the sealing surface **512** by up to 12 mm without adversely affecting the performance of the sealing surface **512**.

The bellows structure **522** may be any suitable bellows arrangement that permits relative movement between the base and the prongs **120**, **121**, such as the movement described immediately above or elsewhere herein. For example, the bellows structure **522** may be a structure of reduced cross sectional area or, alternatively, may be a thinner section on the inner side of the wall, or a combination thereof. The bellows section may have a planar outer wall shape/structure (or a curved shape that is continuous with portions of the seal **500** outside of the bellows section) and may have an internal thinning of the wall to result in the same/similar function as the bellows structure **522**.

A further alternative arrangement is that the bellows section could be a convex bellows rather than a concave section as shown. The current illustrated embodiment shows a bellows section **522** or a pleat that is concave in shape, but alternatively the bellows section **522** may be a pleat that is convex and extends outwardly. In at least some configurations, the convex bellows would expand outwardly when compressed. Such a convex bellows section can act as a support to prevent the seal from over rotating about the center of the bellows.

The sealing portion **210** can pivot around the center of the bellows structure **522** (for example, as indicated by the curved arrows in FIG. **33**) such that the sealing portion **210** can be angled relative to the lower bellows portion **520**. Such pivoting can allow the seal **500** to compensate for angled forces applied to the seal **500** by the conduit attached to the inlet orifice **130** and can help inhibit or reduce disturbance to the sealing surface **512** that may result from such angled forces. The pivoting can also allow the seal **500** to adjust for and accommodate variability in the angle of the user's lower nasal surfaces for different users.

In some embodiments, the center of the inlet orifice **130** and center of the sealing surface **512** are aligned or approximately aligned, as indicated by the horizontal arrows and dashed lines in FIG. **33**. Such alignment can advantageously encourage the bellows structure **522** to compress rather than form a hinge about which the sealing portion **510** and lower bellows portion **520** bend relative to each other. The forces applied to the inlet orifice **130** and the sealing surface **512** can be offset, but oriented in the same direction or parallel to one another. In some configurations, the offset is small relative to a size of the seal **500**, such as relative to a cross-sectional dimension of the connector opening **130** or interior cavity of the seal **500**.

As shown, the seal **500** can have a rounded cross-sectional profile. In other words, the seal **500** may not have sharp corners. A rounded cross-sectional profile can advantageously promote a smooth compression motion of the seal **500** and a substantially linear increase in force as displacement or compression of the seal **500** increases during at least a portion of the range of compression, as shown in the force vs. extension graph of FIG. **35**.

In the illustrated embodiment, the seal **500** has a relatively large inlet orifice **130** in comparison with an overall size of the seal **500** (e.g., cross-sectional dimension of the cavity or other portion of the seal **500**). A relatively large inlet orifice **130** can allow the seal **500** to be removed from a mold tool more easily during manufacturing. As shown, a perimeter of

the inlet orifice **130** is inwardly offset from an outer perimeter of the lower bellows portion **520**. This offset is large enough such that the inlet orifice **130** does not significantly interfere with the function of the lower bellows portion **520** and bellows structure **522**.

As shown by the generally horizontal arrow in FIG. **36**, lateral sides of the lower bellows portion **520** can curve toward the sealing portion **510** (upward in the orientation of FIG. **36**). In the illustrated embodiment, a curvature of the lower bellows portion **520** matches or corresponds to (or substantially or generally matches or corresponds to) a curvature of the lower surfaces of the sealing portion **510**. In such embodiments, a distance between the lower bellows portion **520** and the lower surfaces of the sealing portion **510** (indicated by the generally vertical arrows in FIG. **36**) is substantially the same or equal around an entire circumference of the seal **500**. In some embodiments, the distance between the lower bellows portion **520** and the lower surfaces of the sealing portion **510** is 6 mm. A constant distance between the lower bellows portion **520** and lower surfaces of the sealing portion **510** around the circumference of the seal **500** can advantageously allow for a more even compression of the seal **500** around the entire lower bellows portion **520**. In other words, the seal **500** is less likely to bottom out in one area of the seal **500** before a remainder of the circumference of the seal **500**. The curvature of the lower bellows portion **520** can also give the seal **500** a smaller appearance.

The perimeter of the lower bellows portion **520** and bellows structure **522** can be smaller than the perimeter of the sealing portion **510** as shown in FIGS. **37-38**. A relatively smaller lower bellows portion **520** can advantageously help reduce or minimize the size of the seal **500**. As shown in FIG. **37**, the lower bellows portion **520** can offset (indicated by arrow **523**) from a back of the sealing portion **510** (e.g., from a lowest, in the orientation of FIG. **37**, point of proximal wall **124**). Such an offset can inhibit the lower bellows portion **520** from contacting the user's lip in use. In some embodiments, the sealing portion **510** has a greatest width (indicated by W_4 in FIG. **38**) of 43 mm, the inlet orifice **130** has a width (indicated by W_1 in FIG. **38**) of 28 mm, the lower bellows portion **520** has a greatest width (indicated by W_2 in FIG. **38**) of 34 mm, and the bellows structure **522** has a width (indicated by W_3 in FIG. **38**) of 26.5 mm. Such dimensions are exemplary and may vary. However, in some configurations, the relative sizes can be as illustrated.

In some embodiments, the sealing portion **510** and/or prongs **120**, **121** can flex outwardly or away from each other as indicated by dashed lines showing a flexed or splayed prong profile in FIG. **39**. Flexing of the prongs **120**, **121** or sealing portion **510** can advantageously allow the seal **500** to accommodate users having relatively large nares and/or nares that are spaced apart by a relatively wide septum. Reducing or minimizing a height of a portion of the sealing portion **510** not including the prongs **120**, **121** (indicated by "h" in FIG. **39**) advantageously allows for a tight, continuously curved outer surface in the sealing portion **520**, which can increase the ability of the prongs **120**, **121** to splay outwards without the outer surfaces of the seal **500** collapsing as a shorter, more curved surface is generally less likely to buckle and/or collapse. In some embodiments, the height h is 19 mm. In some embodiments, the prongs **120**, **121** can splay outwardly away from each other by 2 mm or more. In some embodiments, a distance between innermost edges of

19

the prongs **120**, **121** in a relaxed state is 7.5 mm and a distance between the innermost edges of the prongs **120**, **121** is a splayed state is 9.5 mm.

In some embodiments, the seal **500** is semi-inflatable. When the prongs **120**, **121** are engaged and sealed with the user's nares and CPAP pressure is applied in use, the seal **500** inflates slightly. The seal **500** can extend or increase in height (along a direction parallel to an axis extending through the center of the inlet orifice **130**, indicated by the dashed lines in FIG. 33) and/or the prongs **120**, **121** can splay apart from each other as shown by the inflated profile outline shown in FIG. 40. Such inflation can advantageously allow the prongs **120**, **121** to engage the user's nares more securely and improve the seal with the user's nares. In some embodiments, the seal **500** can increase in height by 2 mm or more when inflated. In some embodiments, the prongs **120**, **121** can splay apart from each other by 2 mm or more when the seal **500** is inflated.

In some embodiments, a thickness of the bellows structure **522** is consistent or constant throughout the bellows structure **522**. The thickness of the bellows structure **522** can be 0.75 mm. In some embodiments a thickness of the lower bellows portion **520** is consistent or constant throughout the lower bellows portion **520**. A constant thickness can advantageously provide unbiased compression over the entirety of the bellows structure **522** and/or lower bellows portion **520**. In such an embodiment, the cross-sectional profile of the seal **500** would therefore have a more significant impact on how compression of the seal **500** occurs than the thickness of the seal **500**.

In some embodiments, the seal **500** includes a thickened region **530** as shown in FIG. 41 that has a greater cross-sectional thickness than a remainder of the seal **500**. In the illustrated embodiment, the thickened region **530** extends along lateral front portions of the seal **500**. The thickened region **530** can help prevent or inhibit the sealing surface **512** from collapsing in the thickened region **530**. In some embodiments, the thickened region **530** has a thickness of 1 mm and a remainder of the seal **500** has a thickness of 0.75 mm or similar relative thicknesses.

Alternatively, the bellows section may have a varying thickness. The base section of the bellows may be thickest and the portion of the bellows at the top, i.e., closest to the prong or pillow is thinnest, or vice-versa. The thin portion of the bellow allows for greater flexing/pivoting. The thicker base allows for greater stability at the base.

In a further alternative, the bellow may be thick at the base and at the top and thin in the middle. The middle being thinner than the top and the bottom of the bellow. This allows for greater flexibility and flexure in the middle section of the bellow, while the thicker section provide for greater support at the top and bottom of the seal, allowing the prong to maintain its shape and also maintain orientation.

In some embodiments, an inner volume of the lower bellows portion **520**, indicated by area 3 in FIG. 421, is about 3966 mm³. In some embodiments, an inner volume of sealing portion **510** is about 11,158 mm³. An inner volume of each half of the sealing portion **510** (indicated by areas 1 and 2 in FIG. 421 where the sealing portion **510** is separated by a plane extending between the prongs **120**, **121**) can be 5579 mm³. Thus, the areas 1 and 2 can be collectively greater than the volume 3. In some configurations, each of the volumes 1 and 2 can be greater than the volume 3.

Seal with Rolling Section

FIGS. 43-54C illustrate an example embodiment of a seal **600** that includes a rolling section **620** between the sealing surface **610** and a connector receiving portion **630**. The

20

rolling section **620** can advantageously at least partially isolate the sealing surface **610** from hose drag forces. The rolling section **620** and sealing surface **610** are delimited or separated by a stiffener or stiffening member, such as a rib **640**, that projects inwardly from an inner surface of the seal **600**. The rolling section **620** is configured to roll over the connector receiving portion **630**, as indicated by the dashed line profile in FIG. 44, to absorb or accommodate for forces on the connector receiving portion **630** and inhibit deformation of the sealing surface **610**. In some embodiments, a height of the seal **600** in a neutral state, indicated by h1 in FIG. 44, is 34.5 mm. In some embodiments, a height of the seal **600** can decrease by approximately 5 mm or more when the rolling section **620** is rolled over the connector receiving portion **630**. In some embodiments, the height of the seal **600** in a compressed state in which the rolling section **620** is rolled over the connector receiving portion **630**, indicated by h2 in FIG. 44, is approximately 29.9 mm. In other configurations, the height may differ from that described above, but the relative amount of roll can remain the same.

The rib **640** can advantageously separate the rolling section **620** from the sealing surface **610** to help isolate movement of the connector receiving portion **630** from the sealing surface **610** and reduce or minimize the effect of hose drag. The rib **640** and/or rolling section **620** can also advantageously allow the sealing surface **610** to be positioned at differing angles relative to the connector receiving portion **630** such that the seal **600** can adapt to and accommodate varying facial geometries of different users. In some embodiments, the rib **640** is positioned approximately half-way between the sealing surface **610** (e.g., a portion of the sealing surface **610** between the prongs **120**, **121**) and the connector receiving portion **630**.

The rib **640** can extend around an entire inner perimeter of the seal **600**. In other embodiments, the rib **640** includes a gap **642** extending along at least a portion of the front of the seal **600** as shown in FIGS. 43-44. Once the rolling section **620** rolls over the connector receiving portion **630** to a certain extent, the rib **640** contacts internal surfaces of the rolling section **620** and/or the connector receiving portion **630** to prevent or inhibit further movement. In embodiments in which the rib **640** includes a gap **642** along the front of the seal **600**, the gap allows the rolling section **620** in the front of the seal **600** to roll farther over the connector receiving portion **630** than the back of the seal **600**. This allows for a greater travel or range of motion of the rolling portion **620** in the front of the seal **600** and the rolling section **620** in the front of the seal **600** may therefore not bottom out.

In some embodiments, the seal **600** is configured to be fitted to the user in use such that the rolling section **620** is at least partially rolled over the connector receiving portion **630** at least a majority of the time. This advantageously allows the connector receiving portion **630** to be pulled away from the sealing surface **610** to some extent without the sealing surface **610** losing contact with the user's nares.

In some embodiments, the rib **640** is made of silicone. In some embodiments, the rib **640** has an inner thickness (indicated by dimension Y in FIG. 45) in the range of 1 mm-4 mm, for example, 1.7 mm, an outer thickness (indicated by dimension Z in FIG. 45) in the range of 1 mm-5 mm, for example, 2.5 mm, and a length (indicated by dimension X in FIG. 45) in the range of 1 mm-6 mm, for example, 3 mm. The inner thickness can be less than the outer thickness. The length can be greater than the inner and outer thicknesses. In some embodiments, the rib **640** has rounded edges.

21

A thickness of the rolling section 620 can gradually transition between the rib 640 and the connector receiving portion 630 as shown in FIG. 46. For example, in some embodiments, the thickness transitions from 0.5 mm proximate or adjacent the connector receiving portion 630 to 0.8 mm proximate or adjacent the rib 640. In other configurations, the actual dimension may differ, but the proportions can be the same. The transitioning thickness advantageously allows the rolling section 620 to have a spring force that increases as the seal 600 becomes more compressed, which can help prevent or inhibit sharp increases in force that may be caused by the seal 600 suddenly bottoming out. This can advantageously improve user comfort. The force on the seal 600 increases substantially linearly as the rolling section 620 is displaced and remains relatively low until the rolling section 620 bottoms out, for example as shown in the theoretical force vs. displacement profile shown in FIG. 47 and force profile shown in FIG. 48. The thickness of the seal 600 can be consistent or constant throughout the sealing surface 610. In some embodiments, the thickness of the sealing surface 610 is 0.75 mm. FIG. 49 shows a heat map showing the generally constant thickness in the sealing surface 610 and varying thickness at the rib 640, rolling section 620, and connector receiving portion 630.

In some embodiments, the connector receiving portion 630 is generally kidney bean shaped and follows the overall shape of the seal 600 as shown in FIGS. 50A-50C. In such embodiments, the rolling section 620 extends outwardly from the connector receiving portion 630 a substantially or relatively more uniform depth or distance (indicated by the arrows in FIG. 50A as well as D1 and D2 in FIG. 51) around the entire perimeter or circumference of the seal 600. In contrast, if the connector receiving portion 630 had a generally oval shape, indicated by the dashed line in FIG. 50B, the rolling section 620 would have an uneven depth or distance as indicated by the arrows in FIG. 50B. A relatively more uniform depth of the rolling section 620, as provided by the kidney bean shaped connector receiving portion 630, advantageously allows the seal 600, e.g., the rolling section 620, to roll more evenly across the entire lower half of the seal 600 or around an entire perimeter or circumference of the seal 600.

In some embodiments, the prongs 120, 121 can splay apart from each other to accommodate varying septum widths of different users as shown in FIG. 52. The rolling section 620 advantageously allows the prongs 120, 121 to splay apart without the sealing surfaces 610 collapsing or collapsing to a significant extent.

The connector receiving portion 630 extends from an intersection 634 with the rolling section 620 to an open base end 632 configured to receive, for example, a conduit or connector. In the illustrated embodiment, the open base end 632 and intersection 634 with the rolling section 620 are curved. The curvature of the intersection 634 can encourage consistent movement of the rolling section 620 around the perimeter or circumference of the seal 600. The curvature of the intersection 634 and/or base end 632 can also make the seal 600 shorter and/or give the seal 600 a relatively smaller appearance compared to a seal having a flat or straight intersection and/or base end. In some embodiments, the curvature is such that a distance (indicated by h1 in FIG. 53A) between a center of the base end 632 or intersection 634 and a lateral side of the base end 632 or intersection 634, respectively, along a line parallel to an axis extending through the center of the connector receiving portion 630 and between the prongs 120, 121 is approximately 3.26 mm.

22

Unless the context clearly requires otherwise, throughout the description and the claims, the words “comprise”, “comprising”, and the like, are to be construed in an inclusive sense as opposed to an exclusive or exhaustive sense, that is to say, in the sense of “including, but not limited to”.

Reference to any prior art in this specification is not, and should not be taken as, an acknowledgement or any form of suggestion that that prior art forms part of the common general knowledge in the field of endeavor in any country in the world.

The inventions disclosed herein may also be said broadly to consist in the parts, elements and features referred to or indicated in the specification of the application, individually or collectively, in any or all combinations of two or more of said parts, elements or features.

Where, in the foregoing description reference has been made to integers or components having known equivalents thereof, those integers are herein incorporated as if individually set forth.

It should be noted that various changes and modifications to the presently preferred embodiments described herein will be apparent to those skilled in the art. Such changes and modifications may be made without departing from the spirit and scope of the inventions and without diminishing its attendant advantages. For instance, various components may be repositioned as desired. It is therefore intended that such changes and modifications be included within the scope of the inventions. Moreover, not all of the features, aspects and advantages are necessarily required to practice the present inventions. Accordingly, the scope of some of the present inventions is intended to be defined only by the claims that follow.

What is claimed is:

1. A nasal seal comprising:

a seal body formed of a soft flexible material and defining an inner cavity that receives a supply of breathing gases, the seal body comprising:

a first nostril prong;

a second nostril prong;

wherein each of the first nostril prong and the second nostril prong are non-conical and asymmetrical; and a rolling portion defined by a sidewall portion of the seal body and configured to roll over on itself, the rolling portion comprising an upper portion configured to be distal of an upper lip of a user and a lower portion configured to be proximate the upper lip of the user, wherein the upper portion provides less resistance to roll than the lower portion.

2. The nasal seal of claim 1, wherein the seal body defines a supply opening through which the supply of breathing gases passes into the inner cavity, wherein the supply opening is non-circular in shape.

3. The nasal seal of claim 2, wherein the supply opening is bean-shaped.

4. The nasal seal of claim 1, wherein each of the first nostril prong and the second nostril prong comprises a medial portion, wherein the medial portion is oriented at an angle relative to a central plane of the seal body.

5. The nasal seal of claim 4, wherein the medial portion comprises an upper portion and a lower portion, wherein the angle relative to the central plane of the lower portion is greater than the angle relative to the central plane of the upper portion.

6. The nasal seal of claim 1, wherein a proximal wall of the seal body comprises a concave portion extending in a lateral direction of the seal body and having a shape that generally conforms to a shape of an upper lip of a user.

7. The nasal seal of claim 1, wherein the first nostril prong comprises a first sealing surface and the second nostril prong comprises a second sealing surface, wherein portions of the first sealing surface and the second sealing surface are convex.

5

8. The nasal seal of claim 1, wherein the seal body comprises a central wall portion extending between and connecting the first nostril prong and the second nostril prong, wherein the central wall portion is spaced deeply from an end surface of the first nostril prong and second nostril prong such that contact between the central wall portion and a septum of a user is reduced or eliminated.

10

9. The nasal seal of claim 1, wherein the upper rolling portion has a radial dimension that is larger than a corresponding radial dimension of the lower rolling portion.

15

* * * * *