


(12) **United States Patent**
Månsson et al.

(10) **Patent No.:** **US 12,409,316 B2**
(45) **Date of Patent:** ***Sep. 9, 2025**

- (54) **HEADSET FOR TRANSCRANIAL DIRECT-CURRENT STIMULATION, TDCS, AND A SYSTEM COMPRISING THE HEADSET**
- (71) Applicant: **FLOW NEUROSCIENCE AB**, Malmö (SE)
- (72) Inventors: **Daniel Månsson**, Simrishamn (SE); **Erik Rehn**, Enebyberg (SE)
- (73) Assignee: **FLOW NEUROSCIENCE AB**, Malmö (SE)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.
- (21) Appl. No.: **18/909,869**
- (22) Filed: **Oct. 8, 2024**
- (65) **Prior Publication Data**
US 2025/0025683 A1 Jan. 23, 2025
- Related U.S. Application Data**
- (63) Continuation of application No. 18/670,531, filed on May 21, 2024, now abandoned, which is a (Continued)
- (51) **Int. Cl.**
A61N 1/36 (2006.01)
A61N 1/04 (2006.01)
A61N 1/20 (2006.01)
- (52) **U.S. Cl.**
CPC **A61N 1/0456** (2013.01); **A61N 1/0484** (2013.01); **A61N 1/36025** (2013.01); **A61N 1/3603** (2017.08); **A61N 1/20** (2013.01)

- (58) **Field of Classification Search**
CPC A61N 1/0456; A61N 1/0484; A61N 1/36025; A61N 1/3603; A61N 1/20
See application file for complete search history.
- (56) **References Cited**
U.S. PATENT DOCUMENTS
5,469,578 A 11/1995 Mattes
7,976,451 B2 7/2011 Zangen et al.
(Continued)
FOREIGN PATENT DOCUMENTS
BR PI1100124 A2 4/2013
CN 1296854 A 5/2001
(Continued)
OTHER PUBLICATIONS
Extended European Search Report for European Application No. EP23188609.4 dated Feb. 20, 2024, 4 pages.
(Continued)
Primary Examiner — James M Kish
Assistant Examiner — Natasha Patel
(74) *Attorney, Agent, or Firm* — COOLEY LLP
- (57) **ABSTRACT**
A headset for transcranial brain stimulation including: a forehead frame defining an elongated arch; a first electrode arranged at a first end portion of the forehead frame; a second electrode arranged at a second end portion of the forehead frame; a bracket arranged at a center portion of the forehead frame; and a circuit comprising the first and second electrodes and configured to be powered according to a schedule for performing the transcranial brain stimulation.
- 31 Claims, 2 Drawing Sheets**



Related U.S. Application Data

continuation of application No. 16/480,678, filed as application No. PCT/EP2017/052251 on Feb. 2, 2017, now Pat. No. 12,017,062.

(56)

References Cited**U.S. PATENT DOCUMENTS**

8,265,910	B2	9/2012	Mishelevich et al.
8,277,371	B2	10/2012	Zangen et al.
8,388,510	B2	3/2013	Zangen et al.
8,523,753	B2	9/2013	Schneider et al.
8,771,163	B2	7/2014	Zangen et al.
8,795,148	B2	8/2014	Schneider et al.
8,903,494	B2	12/2014	Goldwasser et al.
9,132,278	B2	9/2015	Zangen et al.
9,248,308	B2	2/2016	Zangen et al.
9,254,394	B2	2/2016	Zangen et al.
9,352,167	B2	5/2016	Schneider
9,370,658	B2	6/2016	Neuvonen et al.
9,440,070	B2	9/2016	Goldwasser et al.
9,492,679	B2	11/2016	Schneider et al.
9,533,168	B2	1/2017	Zangen et al.
9,636,517	B2	5/2017	Pell et al.
9,694,178	B2	7/2017	Ruffini et al.
9,782,602	B1	10/2017	Lowin
9,802,058	B2	10/2017	Zangen et al.
9,808,642	B2	11/2017	Zangen et al.
10,029,113	B2	7/2018	Zangen et al.
10,173,049	B2	1/2019	Neuvonen et al.
10,293,177	B2	5/2019	Malchano et al.
10,327,984	B2	6/2019	Goodall et al.
10,335,606	B2	7/2019	Pell et al.
10,537,703	B2	1/2020	Tyler et al.
10,576,279	B2	3/2020	Muller et al.
10,589,118	B2	3/2020	Schneider
10,625,091	B2	4/2020	Zangen et al.
10,814,131	B2	10/2020	Goldwasser et al.
10,918,855	B2	2/2021	Eriksson et al.
11,000,669	B2	5/2021	Derung
11,033,731	B2	6/2021	Jeffery et al.
11,052,251	B2	7/2021	Muller et al.
11,207,540	B2	12/2021	Zangen et al.
11,241,584	B2	2/2022	Pell et al.
11,253,701	B2	2/2022	Hagedorn
11,324,963	B2	5/2022	Etkin et al.
11,351,362	B2	6/2022	Månsson et al.
11,400,289	B2	8/2022	Alyagon et al.
11,464,973	B2	10/2022	Hagedorn
11,577,090	B2	2/2023	Etkin et al.
2005/0197556	A1*	9/2005	Stoler A61B 5/369 600/383
2009/0287108	A1	11/2009	Levy
2010/0057159	A1	3/2010	Lozano
2012/0163616	A1	6/2012	Birch
2013/0096363	A1	4/2013	Schneider et al.
2013/0317281	A1	11/2013	Schneider et al.
2014/0073996	A1	3/2014	Jaguan
2014/0200388	A1	7/2014	Schneider et al.
2014/0350431	A1	11/2014	Hagedorn
2015/0005840	A1	1/2015	Pal et al.
2015/0119689	A1	4/2015	Pascual-Leone et al.
2015/0181323	A1	6/2015	Raklev
2015/0190635	A1	7/2015	Neuvonen et al.
2015/0238762	A1	8/2015	Pal et al.
2015/0335875	A1	11/2015	Goldwasser et al.
2015/0335888	A1	11/2015	Demers et al.
2015/0351655	A1	12/2015	Coleman
2016/0008620	A1	1/2016	Stubbeman
2016/0008632	A1	1/2016	Wetmore et al.
2016/0023015	A1	1/2016	Schneider et al.
2016/0067516	A1	3/2016	Schneider et al.
2016/0074657	A1	3/2016	Kwan et al.
2016/0175589	A1	6/2016	Wingeier
2016/0317809	A1	11/2016	Pal et al.
2016/0360990	A1*	12/2016	Altshuler A61B 5/6803
2017/0056642	A1	3/2017	Moffitt et al.

2017/0080234	A1	3/2017	Gillespie et al.
2017/0106203	A1	4/2017	Schneider et al.
2017/0113057	A1	4/2017	Goodall et al.
2017/0113058	A1	4/2017	Schneider
2017/0151430	A1	6/2017	Neuvonen et al.
2017/0165485	A1*	6/2017	Sullivan A61B 5/0022
2017/0224978	A1*	8/2017	Lee A61N 1/04
2017/0224990	A1	8/2017	Goldwasser et al.
2017/0224991	A1	8/2017	Wingeier et al.
2017/0319852	A1	11/2017	Wingeier et al.
2017/0361094	A1	12/2017	Cartledge et al.
2017/0368297	A1	12/2017	Tyler et al.
2018/0133431	A1	5/2018	Malchano et al.
2018/0133504	A1	5/2018	Malchano et al.
2018/0236231	A1	8/2018	Wingeier
2019/0046794	A1	2/2019	Goodall et al.
2019/0113757	A1	4/2019	Van Heugten
2019/0159715	A1	5/2019	Mishra Ramanathan et al.
2019/0224481	A1	7/2019	Wingeier
2019/0232054	A1	8/2019	Levenberg
2020/0129119	A1	4/2020	Ruffini et al.
2020/0147340	A1	5/2020	Tyler et al.
2020/0175688	A1	6/2020	Krummen et al.
2020/0297999	A1	9/2020	Pal
2020/0302825	A1	9/2020	Sachs et al.
2021/0128905	A1	5/2021	Månsson et al.
2021/0162204	A1	6/2021	Eriksson et al.
2021/0169417	A1	6/2021	Burton
2021/0275801	A1	9/2021	Månsson et al.
2021/0299434	A1	9/2021	Månsson et al.
2021/0370047	A1	12/2021	Rigaux
2022/0096833	A1	3/2022	Muller et al.
2022/0280801	A1	9/2022	Etkin et al.
2022/0288409	A1	9/2022	Järnefelt
2022/0296903	A1	9/2022	Maron-Katz et al.
2023/0022546	A1	1/2023	Malchano et al.
2023/0082594	A1	3/2023	Hagedorn
2023/0104621	A1	4/2023	Malchano et al.
2023/0111776	A1	4/2023	Malchano et al.
2025/0025684	A1	1/2025	Månsson et al.

FOREIGN PATENT DOCUMENTS

CN	105266802	A	1/2016
GB	2521877	A	7/2015
GB	2541947	A	3/2017
KR	101628299	B1	6/2016
KR	20160095579	A	8/2016
WO	WO-2009137683	A2	11/2009
WO	WO-2009137683	A3	2/2010
WO	WO-2011123548	A2	10/2011
WO	WO-2014082064	A1	5/2014
WO	WO-2015184447	A1	12/2015
WO	WO-2016017954	A1	2/2016
WO	WO-2016042499	A1	3/2016
WO	WO-2016179272	A1	11/2016
WO	WO-2018141389	A1	8/2018
WO	WO-2018141830	A1	8/2018
WO	WO-2020025388	A1	2/2020
WO	WO-2022027030	A1	2/2022

OTHER PUBLICATIONS

Final Office Action for U.S. Appl. No. 16/480,678 dated Dec. 14, 2021, 15 pages.
 Final Office Action for U.S. Appl. No. 16/480,678 dated Nov. 2, 2022, 19 pages.
 International Preliminary Report on Patentability mailed on Aug. 6, 2019 for PCT/EP2017/052251, 7 pages.
 International Search Report and Written Opinion mailed on Oct. 26, 2017 for PCT/EP2017/052251, 10 pages.
 Non-Final Office Action for U.S. Appl. No. 16/480,678 dated Jul. 20, 2021, 13 pages.
 Non-Final Office Action for U.S. Appl. No. 16/480,678 dated May 27, 2022, 15 pages.
 Non-Final Office Action for U.S. Appl. No. 18/909,870 mailed Dec. 13, 2024, 7 pages.

(56)

References Cited


OTHER PUBLICATIONS

Office Action issued on Mar. 24, 2023 for Chinese Application No. 201780085021.X, with English translation, 11 pages.

Office Action issued on Oct. 27, 2022 for Chinese Application No. 201780085021.X, with English translation, 7 pages.

U.S. Appl. No. 18/670,531, filed May 21, 2024, by MÅnsson et al.

* cited by examiner

*Fig. 1*




FIG. 2

1

HEADSET FOR TRANSCRANIAL DIRECT-CURRENT STIMULATION, tDCS, AND A SYSTEM COMPRISING THE HEADSET

CROSS-REFERENCE TO RELATED APPLICATION

This application is a Continuation Application of U.S. patent application Ser. No. 18/670,531, filed May 21, 2024, which is a Continuation Application of U.S. patent application Ser. No. 16/480,678, filed Jul. 25, 2019, now issued as U.S. Pat. No. 12,017,062, which is a U.S. National Stage Application under 35 U.S.C. § 371 of International Patent Application No. PCT/EP2017/052251, filed Feb. 2, 2017, the contents of each of which are incorporated herein by reference in their entireties.

TECHNICAL FIELD

The present invention relates to a headset for transcranial brain stimulation and a system comprising the headset.

BACKGROUND OF THE INVENTION

Transcranial brain stimulation, for example in the form of transcranial direct current stimulation, tDCS, which is a well-known technique for non-invasive neurostimulation of the brain. The transcranial brain stimulation is, e.g., used to help stroke recovery and patients with brain injuries and to treat depression. Transcranial brain stimulation uses external electrodes placed on the head of the patient, whereby the head of the patient together with the electrodes forms a closed circuit. A current, either direct or alternating, is applied to the circuit, which acts on the neurons of the brain. The placement of the electrodes can be done by a physician, but when transcranial brain stimulation is used to treat depression it should be performed so often that it is highly impractical for a physician to be present. The patient may be given the electrodes and instructions on how to place them, but this is of course error-prone. Another problem is patient compliance—the patient must apply the therapy often enough for it to have effect, but not too often as this may lead to unwanted side effects. The lack of presence of a physician when the therapy is self-performed also leads to a lack of patient feedback and monitoring.

SUMMARY OF THE INVENTION

In view of the above, an objective of the invention is to solve or at least reduce one or several of the drawbacks discussed above. Generally, the above objective is achieved by the attached independent patent claims.

According to a first aspect, the present invention is realized by a headset for transcranial brain stimulation, the headset comprising:

- a forehead frame, the forehead frame defining an elongated arch;
- a first electrode arranged at a first end portion of the forehead frame
- a second electrode arranged at a second end portion of the forehead frame;
- a bracket arranged at a center portion of the forehead frame; and
- a circuit comprising the first and second electrodes and being configured to be powered according to a schedule for performing the transcranial brain stimulation;

2

wherein upon use of the headset:

the forehead frame is configured such that the first electrode is located at a left side of a forehead of a user of the headset, and such that the second electrode is located at a right side of the forehead of the user of the headset, and the bracket is configured to extend from the forehead frame over the skull of the user towards a neck portion of the user.

This provides a headset for performing transcranial brain stimulation wherein the electrodes are unlikely to be placed incorrectly on the forehead of the user. This has the advantage of allowing for transcranial brain stimulation to be performed without a physician available to place the electrodes on the head of the patient. Furthermore, the headset may be designed to be lightweight and comfortable, eliminating the need for fabric headwear which may be warm and uncomfortable when worn for extended periods of time. This further provides a comfortable headset which is impossible to mount such that the direction of the current is reversed, which may be critical in for example transcranial direct current stimulation, tDCS. During electrical transcranial brain stimulation, the potential of neuronal cells are influenced by an applied electric field. This field influences the neuronal cells under the stimulated area and pushes them closer or further away from their activation threshold.

The headset may further comprise:

- a memory configured to store the schedule for performing the transcranial brain stimulation;
- a controller configured to periodically power the circuit according to the schedule for performing the transcranial brain stimulation, thereby providing a current to the electrodes; and
- a power source configured to provide power to the circuit and the controller circuit.

Means for safer transcranial brain stimulation are hence provided. Further the need for involvement of a physician upon performing the transcranial brain stimulation is reduced.

The memory may further be configured to store information pertaining to performed transcranial brain stimulation. Hence, means for monitoring the patient's progress through the therapy is provided. This further reduces the need for involvement of a physician upon performing the transcranial brain stimulation.

The controller may further be configured to remind the user to use the headset according to the schedule for performing the transcranial brain stimulation. Counteracting negligence or unwitting non-compliance, e.g. due to misunderstanding or miscommunication, in relation to the therapy on account of the patient is provided.

The first and second electrodes may be pivotable such that they can adapt to the shape of the forehead of the user. A more comfortable headset which is adaptable to many different shapes of patient foreheads and reduces the need for size adaptability of the headset is provided.

The first and second electrodes may comprise an adhesive layer configured such that it adheres to the forehead of the user. Ensuring that the headset does not drift during use, securing it in place on the head of the patient is provided.

In a second aspect, the current invention also relates to a system comprising a headset for transcranial brain stimulation and a non-transitory computer-readable recording medium having recorded thereon a program which is executable on an electronic device having processing capabilities,

wherein the headset comprises:

- a forehead frame, the forehead frame defining an elongated arch;

3

a first electrode arranged at a first end portion of the forehead frame;
 a second electrode arranged at a second end portion of the forehead frame;
 a bracket arranged at a center portion of the forehead frame;
 a circuit comprising the first and second electrodes and being configured to be powered according to a schedule for performing the transcranial brain stimulation; and

wherein upon use of the headset:

the forehead frame is configured such that the first electrode is located at a left side of a forehead of a user of the headset, and such that the second electrode is located at a right side of the forehead of the user of the headset, and

the bracket is configured to extend from the forehead frame over the skull of the user towards a neck portion of the user,

wherein the program comprises program code portions which when executed on the electronic device is configured to:

store the schedule for performing the transcranial brain stimulation in a computer memory; and

control the electronic device to send a control signal to the headset such that transcranial brain stimulation is performed according to the schedule for performing the transcranial brain stimulation.

This provides the possibility for a user to perform a transcranial brain stimulation therapeutic schedule themselves with the aid of an electronic device, further limiting the need for visits to or by a physician.

The headset may further comprise:

a transceiver configured to communicate with the electronic device;

a controller configured to control the first and second electrodes according to the control signal; and

a power source configured to provide power to the circuit and the controller circuit.

This provides a system where the headset does not need to be wired to any external circuitry or power supply, improving portability of the headset and increasing user comfort and convenience.

The program may further comprise program code portions which when executed on the electronic device is configured to remind the user to use the headset according to the schedule for performing the transcranial brain stimulation. This provides a system for performing transcranial brain stimulation where the user can be conveniently prompted to wear the headset and signaled when to remove it. This provides a safety measure against over-use of the headset by the user due to negligence or ignorance.

The program may further comprise program code portions which when executed on the electronic device is configured to display information on a display of the electronic device in accordance with a schedule for displaying the information, wherein the schedule for displaying information is related to the schedule for performing the transcranial brain stimulation.

The program may further comprise program code portions which when executed on the electronic device is configured to prompt the user to input information pertaining to status of the user.

The program may further comprise program code portions which when executed on the electronic device is configured to update the schedule for performing the transcranial brain stimulation.

4

The program may further comprise program code portions which when executed on the electronic device is configured to store information pertaining to performed transcranial brain stimulation on a computer memory.

The electronic device may be a handheld electronic device.

The program may be an application downloadable to the electronic device via an application providing service.

The above mentioned features of the method, when applicable, apply to this second aspect as well. In order to avoid undue repetition, reference is made to the above.

A further scope of applicability of the present invention will become apparent from the detailed description given below. However, it should be understood that the detailed description and specific examples, while indicating preferred embodiments of the invention, are given by way of illustration only, since various changes and modifications within the scope of the invention will become apparent to those skilled in the art from this detailed description.

Hence, it is to be understood that this invention is not limited to the particular component parts of the device described or steps of the methods described as such device and method may vary. It is also to be understood that the terminology used herein is for purpose of describing particular embodiments only, and is not intended to be limiting. It must be noted that, as used in the specification and the appended claim, the articles "a," "an," "the," and "said" are intended to mean that there are one or more of the elements unless the context clearly dictates otherwise. Thus, for example, reference to "a unit" or "the unit" may include several devices, and the like. Furthermore, the words "comprising", "including", "containing" and similar wordings does not exclude other elements or steps.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other aspects of the present invention will now be described in more detail, with reference to appended drawings showing embodiments of the invention. The figures should not be considered limiting the invention to the specific embodiment; instead they are used for explaining and understanding the invention.

As illustrated in the figures, the sizes of layers and regions are exaggerated for illustrative purposes and, thus, are provided to illustrate the general structures of embodiments of the present invention. Like reference numerals refer to like elements throughout.

FIG. 1 illustrates a system comprising a headset for transcranial brain stimulation and an electronic device configured to control the headset.

FIG. 2 is a schematic sketch of a headset for transcranial brain stimulation.

DETAILED DESCRIPTION OF THE INVENTION

The present invention will now be described more fully hereinafter with reference to the accompanying drawings, in which currently preferred embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein; rather, these embodiments are provided for thoroughness and completeness, and fully convey the scope of the invention to the skilled person.

In FIG. 1, a view of the headset 100 for transcranial brain stimulation is disclosed. The headset 100 comprises a forehead frame 101, a first and second electrodes 102A, 102B and a bracket 104.

5

The shape of the forehead frame **101** is designed to fit a forehead of a user of the headset **100**. The forehead frame **101** is defining an elongated arch. This allows the forehead frame **101** to follow approximately the shape of the forehead of the user when placed on the head. The forehead frame **101** may be manufactured by e.g. plastic, composite materials, metal or any other suitable material. The forehead frame **101** is configured to support the first and second electrodes **102A**, **102B**. The forehead frame **101** is configured to support the bracket **104**. The first electrode **102A** is arranged at a first end portion of the forehead frame **101**. The second electrode **102B** is arranged at a second end portion of the forehead frame **101**. Hence, the first and second electrodes **102A**, **102B** are placed on the forehead frame **101** such that when the forehead frame **101** is worn by the user, the first and second electrodes **102A**, **102B** will come in contact with the forehead on either side of the user's head.

The first and second electrodes **102A**, **102B** may be configured to pivot to some degree. Thus, a headset **100** is provided where the major surface of each electrode **102A**, **102B** is pivoted to be principally parallel to the surface of the forehead of the user. The first and second electrodes **102A**, **102B** need not be configured to pivot.

The first and second electrodes **102A**, **102B** may be of any type of conducting material suitable for repeated use. Alternatively, the first and second electrodes **102A**, **102B** may be configured for one-time use only, in which case they are to be replaced by the user between uses.

The first and second electrodes **102A**, **102B** may comprise an adhesive layer. The adhesive layer may be discarded after use. The adhesive layer ensures proper contact between the electrode and the forehead of the user while also providing a hygienic solution.

The headset **100** may of course be provided with further electrodes, in case the desired scheme for transcranial brain stimulation so requires.

For some schemes of transcranial brain stimulation, the first and second electrodes **102A**, **102B** correspond to a first and second side of the user's forehead, respectively. By this is meant that each electrode **102A**, **102B** is configured to be brought into contact only with either the left or the right side of the user's forehead.

The bracket **114** is arranged at a center portion of the forehead frame **101**. The bracket **104** may be arranged to the forehead frame **101** in any suitable way. For example, the bracket **104** may be screwed, glued or fastened in any other suitable way to the forehead frame **101**. In this context the phrase "center portion" should be understood to refer to any part of the longitudinal extension of the forehead frame **101** which lies between the first and second electrodes **102A**, **102B**. The bracket **104** has a longitudinal extension which, when the headset **100** is used, extends from the forehead of the user towards the back of the user's head. In this way, the bracket **104** ensures that the user wears the headset **100** such that the first and second electrodes **102A**, **102B** come in contact only with their respective side of the user's forehead. The bracket **104** may be constructed such that its extension from the frame is variable, ensuring a better fit for the user. This can be achieved in many ways, which the skilled person understands. Alternatively, the bracket **104** may be of fixed length. The bracket **104** may further comprise a support cushion **105** arranged at an end portion of the bracket **104** being opposite to where the bracket **104** is arranged at the forehead frame **101**. The cushion **105** makes the bracket **104** more comfortable for the user.

The first and second electrodes **102A**, **102B** are further comprised in a circuit **200**. The circuit **200** will now be

6

further described in connection with FIG. 2. The circuit **200** is configured to be powered according to a schedule for performing transcranial brain stimulation.

The first and second electrodes **102A**, **102B** are connected in the circuit **200**. The circuit **200** further comprises a power source **202** and a switch **203**. Upon the headset **100** being worn by the user and upon the switch **203** is engaged, a closed circuit comprising the first and second electrodes **102A**, **102B**, the user's forehead and the power source **202** is formed. This allows current to flow through the user's cranium. The power source **202** may be a battery.

The headset **100** may further comprise a controller **210**. The controller **210** is configured to periodically power the circuit **200** according to a schedule for performing transcranial brain stimulation. Thereby a current is periodically provided to user's brain for performing the transcranial brain stimulation. The controller **210** is configured to periodically control the switch **203**. The controller **210** may be hardware or software implemented. The controller **210** may comprise a microcontroller, a system of microcontrollers, or any type of processor or control circuit which can engage and disengage the switch **202**. This provides a headset **100** which may vary the electric impulses to the head of the user according to schemes for transcranial brain stimulation.

The headset **100** may further comprise a memory **212**. The memory may be any type of non-volatile memory configured to store digital data. The memory **212** may, e.g., be a ROM, a solid state drive, a flash memory or any other device which can persistently store digital information. The memory **212** may, e.g., be configured to store a schedule for performing the transcranial brain stimulation. The schedule for performing the transcranial brain stimulation may comprise information pertaining to when to open and close the switch **203**. The schedule for performing the transcranial brain stimulation may comprise information pertaining to when the user shall wear the headset and for what duration in order to receive the transcranial brain stimulation. The controller **210** may be arranged to read data from the memory **212**. Hence, the controller **210** may be configured to receive information from the memory **212** on the schedule for performing the transcranial brain stimulation. However, it is realized that the schedule for transcranial brain stimulation may be stored elsewhere in some other memory accessible by the controller **210**. This will be discussed in more detail below. The controller **210** may further be configured to write data to the memory **212**. Hence, the controller **210** may be configured to write data to the memory pertaining to performed transcranial brain stimulation.

The schedule for performing the transcranial brain stimulation may comprise information pertaining to when to open and close the switch **203**. The schedule for performing the transcranial brain stimulation may comprise information pertaining to when the user shall wear the headset **100** and for what duration in order to receive the transcranial brain stimulation. The controller **210** may be arranged to read data from the memory **212**. Hence, the controller **210** may be configured to receive information from the memory **212** on the schedule for performing the transcranial brain stimulation. However, it is realized that the schedule for transcranial brain stimulation may be stored elsewhere in some other memory accessible by the controller **210**. This will be discussed in more detail below. The controller **210** may further be configured to write data to the memory **212**. Hence, the controller **210** may be configured to write data to the memory pertaining to performed transcranial brain stimulation.

The headset **100** may further be configured to signal when the user shall wear or take off the headset **100** for receiving the transcranial brain stimulation. This can be done in many different ways. For this purpose, the headset **100** may comprise a speaker **216**. The controller **210** may be configured to control the speaker **216**. The speaker **216** is configured to emit sound pertaining to information reminding the user to wear or remove the headset **100**. Some non-limiting examples of sounds are beeping sounds and voice synthesis. The loudspeaker **216** may be arranged in the forehead frame **101**. The headset **100** may comprise a light source **218**. The light source **218** may e.g. comprise one or more LED: s. The controller **210** may be configured to control the light source **218**. The light source **218** is configured to emit light pertaining to information reminding the user to wear or remove the headset **100**. For example, the light source **218** may be configured to emit light having different colors for reminding the user to wear or remove the headset **100**. The light source **218** may be configured to emit light pulses of different frequency to remind the user. The light source **218** may be arranged in the forehead frame **101**. The headset may comprise a vibrator **220**. The controller **210** may be configured to control the vibrator **220**. The vibrator **220** is configured to emit vibrate in order to remind the user to wear or remove the headset **100**. The vibrator may be arranged in the forehead frame **101**. Any combination of the loudspeaker **216**, the light source **218** or the vibrator **220** may be used for reminding the user to wear or remove the headset **100**. Hence, just one of them, two of them, or all of them may be used for reminding the user to wear or remove the headset **100**.

The headset **100** may be included in a system **300** for transcranial brain stimulation. As illustrated in FIG. 1 the system **300** comprises the headset **100** as described above and an electronic device **150**. The electronic device **150** having processing capabilities and is configured to execute a computer program. The electronic device may e.g. be a handheld electronic device, such as a laptop, a smartphone, or a smartwatch. In order to communicate with the electronic device **150**, the headset **100** may further comprise a transceiver **214**, see FIG. 2. The transceiver **214** is a wireless transceiver configured to communicate over a suitable wireless protocol, such as Bluetooth, Wi-Fi, ZigBee, or wireless USB. Hence, the transceiver **214** is used to communicate with the electronic device **214**.

The computer program may be an application downloadable to the electronic device via an application providing service. The computer program comprises code portions which when executed on the electronic device **150** is configured to perform different acts.

A code portion of the computer program is configured to store the schedule for performing the transcranial brain stimulation in a computer memory. The computer memory may be the memory **212** of the headset **100**. Alternatively, the computer memory may be a memory of the electronic device. Yet alternatively, the computer memory may be a memory of a server (not shown), the electronic device **150** being connected to the server. Yet alternatively, the computer memory may comprise one or more of the above mentioned memories. Hence, different portions of the schedule may be stored on different memories. Hence, the storing of the schedule may be distributed over a plurality of memories.

A code portion of the computer program is configured to control the electronic device **150** to send a control signal to the controller **210** of the headset **100**. The control signal comprising information pertain to how to control the switch **203** for performing the transcranial brain stimulation.

A code portion of the computer program may further be configured to remind the user to use the headset according to the schedule for performing the transcranial brain stimulation. The reminder may be prompted to the user using one or more of the loudspeaker **216**, the light source **218** and the vibrator **220** of the headset. Alternatively or in combination, the reminder may be prompted to the user using one or more of a loudspeaker of the electronic device, a light source of the electronic device, a vibrator of the electronic device and a display of the electronic device. For example, the user may be prompted by a message displayed on the display of the electronic device.

A code portion of the computer program may further be configured to display information on the display of the electronic device in accordance with a schedule for displaying information. The schedule for displaying information may related to the schedule for performing the transcranial brain stimulation. The displayed information may e.g. be a video sequence to be watched in connection with receiving the transcranial brain stimulation. The video sequence may be video lesson being part of a treatment program. The video sequence may be an instructions video instructing the user how to put on and use the headset **100**.

A code portion of the computer program may further be configured to prompt the user to input information pertaining to status of the user. The user may be prompted by displaying a message on the display of the electronic device **150**. The input information prompted for may be information pertaining to information about the user's current health. The user may input such information through input means of the electronic device. An example of an input means is a keyboard (virtual on a touch screen or realized as mechanical buttons). The input information may then be stored in the computer memory. The input information may then be provided to a physician for reviewing the schedule for the transcranial brain stimulation of the user.

A code portion of the computer program may further be configured to store information pertaining to performed transcranial brain stimulation in the computer memory. The information pertaining to performed transcranial brain stimulation may then be provided to a physician for reviewing the schedule for the transcranial brain stimulation of the user.

By being provided with the input information and the information pertaining to performed transcranial brain stimulation the physician is provided with the possibility to assess the progress of the user and to immediately make any adjustments required to the user's schedule for transcranial brain stimulation as well as inform the user that such adjustments have been made.

A code portion of the computer program may further be configured to update the schedule for performing the transcranial brain stimulation. This gives the possibility for e.g. the physician to adjust the schedule for transcranial brain stimulation.

The person skilled in the art realizes that the present invention by no means is limited to the preferred embodiments described above. On the contrary, many modifications and variations are possible within the scope of the appended claims.

As described above, the headset comprises a transceiver. This provides the possibility for the headset to communicate wirelessly with the electronic device over a network protocol such as Bluetooth or Wi-Fi. The skilled person understands that any network protocol capable of transmitting digitally represented data is possible to use.

9

The system may, through the electronic device, also provide the user with information about the transcranial brain stimulation progress such as logs of their use, changes to their schedule recommended by the physician, status of the headset regarding e.g. battery charge state or malfunctions, or any other information.

As shown through this description, a headset and system for transcranial brain stimulation is provided which allows a user to autonomously and conveniently perform steps of such treatment which previously required visits to or by a physician.

Additionally, variations to the disclosed embodiments can be understood and effected by the skilled person in practicing the claimed invention, from a study of the drawings, the disclosure, and the appended claims.

The invention claimed is:

1. A headset, comprising:

a frame configured to fit across a forehead of a user;

a first electrode coupled to the frame at a first end portion of the frame such that the first electrode is configured to be disposed on a first side of the forehead when the frame is fitted across the forehead;

a second electrode coupled to the frame at a second end portion of the frame such that the second electrode is configured to be disposed on a second side of the forehead when the frame is fitted across the forehead, the first and second electrodes collectively configured to provide a scheme for transcranial stimulation to the user when in contact with the first and second sides of the forehead;

a bracket coupled to a center portion of the frame, the bracket configured to extend from the frame, over a top of a head of the user, and to a back of the head when the frame is fitted across the forehead, the bracket configured to support the frame when fitted across the forehead to ensure that the first and second electrodes only come in contact with their respective sides of the forehead such that current flows in a predetermined direction between the first and second electrodes; and

a processor operatively coupled to the first and second electrodes, the processor configured to control the first and second electrodes to deliver current through a brain of the user in the predetermined direction to provide the scheme for the transcranial stimulation.

2. The headset of claim 1, wherein the bracket extends from the frame in a manner that prevents the frame from being fitted in a different orientation across the forehead of the user such that the current delivered by the first and second electrodes remains in the predetermined direction.

3. The headset of claim 1, wherein the bracket includes a longitudinal extension that is coupled to a support structure having a wider profile than the longitudinal extension.

4. The headset of claim 3, wherein the support structure is configured to rest on a back of the head when the frame is fitted across the forehead.

5. The headset of claim 4, wherein the support structure is a support cushion.

6. The headset of claim 1, wherein the frame, when fitted across the forehead of the user, terminates at the first and second sides of the forehead.

7. The headset of claim 1, wherein the first and second electrodes are pivotable relative to the frame such that, when the frame is fitted across the forehead of the user, a surface of the first electrode can be parallel to the first side of the forehead of the user and a surface of the second electrode can be parallel to the second side of the forehead of the user.

10

8. The headset of claim 1, wherein each of the first electrode and the second electrode includes an adhesive layer that is configured to adhere to a surface of the forehead.

9. The headset of claim 8, wherein the adhesive layers of the first and second electrodes are removable from the first and second electrodes such that the adhesive layers can be discarded after use.

10. The headset of claim 1, wherein the bracket is configured to be adjustable in length such that the bracket can be fitted around different sizes of heads of users.

11. The headset of claim 1, further comprising:

a memory configured to store a schedule for performing the transcranial stimulation,

the processor configured to control the first and second electrodes to deliver the current based on the schedule.

12. A headset, comprising:

a frame defining an elongated arch sized to fit across a forehead of a user;

a first electrode disposed at a first end portion of the frame;

a second electrode disposed at a second end portion of the frame; and

a longitudinal extension having a first end coupled to a center portion of the frame and a second end that terminates in a support structure configured to contact a back of a head of the user,

the longitudinal extension mountable on the head to support the frame in a configuration extends across the forehead of the user and places the first electrode in coupling with a left side of the forehead and the second electrode in coupling with a right side of the forehead to deliver current in a predetermined direction without being mountable on the head to support the frame in a different configuration that reverses the predetermined direction of the current,

the first electrode and the second electrodes configured to form part of a closed circuit that is configured to deliver the current in the predetermined direction to provide transcranial stimulation to the user when in coupling with the left and right sides of the forehead, respectively.

13. The headset of claim 12, wherein the first and second electrodes are pivotable relative to the frame such that, when the frame is supported on the head, a surface of the first electrode can be parallel to the left side of the forehead of the user and a surface of the second electrode can be parallel to the right side of the forehead of the user.

14. The headset of claim 12, wherein each of the first electrode and the second electrode includes an adhesive layer that is configured to adhere to a surface of the forehead.

15. The headset of claim 14, wherein the adhesive layers of the first and second electrodes are removable from the first and second electrodes such that the adhesive layers can be discarded after use.

16. The headset of claim 12, wherein the longitudinal extension is configured to be adjustable in length such that the longitudinal extension can be fitted around different sizes of heads of users.

17. The headset of claim 12, wherein the longitudinal extension has a width that is less than a width of the frame.

18. The headset of claim 13, wherein the first and second electrodes are disposed on structures coupled to the frame that have a lateral dimension that is greater than a width of the frame.

19. The headset of claim 12, further comprising:

a memory configured to store a schedule for performing the transcranial stimulation; and

11

a processor coupled to the memory, the circuit, and the first and second electrodes, the processor configured to control the circuit such that the first and second electrodes deliver current based on the schedule to provide the transcranial stimulation.

20. The headset of claim **12**, wherein the support structure has a wider profile than the longitudinal extension.

21. The headset of claim **13**, wherein the frame, when fitted across the forehead of the user, terminates at the right and left sides of the forehead.

22. The headset of claim **12**, wherein the closed circuit via the first electrode and the second electrode is configured to deliver the current from the second electrode on the right side of the forehead, through a portion of the head of the user, and to the first electrode on the left side of the forehead.

23. A headset, comprising:

a frame;

a first electrode disposed at a first end portion of the frame;

a second electrode disposed at a second end portion of the frame, the frame configured to be worn on a forehead of a user such that the first and second electrodes are in coupling with first and second sides of the forehead and are configured to deliver current in a predetermined direction to the user to provide transcranial stimulation;

a longitudinal extension having a first end coupled to a center portion of the frame and a second end extending away from the frame, the longitudinal extension being shaped to extend over a head of the user such that the longitudinal extension prevents the frame from being worn in an orientation in which a direction of current delivered by the first and second electrodes is reversed due to the first and second electrodes being placed incorrectly on the forehead; and

12

a processor operatively coupled to the first and second electrodes, the processor configured to activate the first and second electrodes such that the first and second electrodes deliver the current in the predetermined direction.

24. The headset of claim **23**, wherein the second end of the longitudinal extension is coupled to a support structure having a wider profile than the longitudinal extension.

25. The headset of claim **24**, wherein the support structure is a support pad.

26. The headset of claim **24**, wherein the support structure is configured to rest on a back of the head when the frame is worn on the forehead.

27. The headset of claim **23**, wherein the first and second sides of the forehead are left and right sides of the forehead, and the frame terminates at the left and right sides of the forehead when worn on the forehead.

28. The headset of claim **23**, wherein the first and second electrodes are pivotable relative to the frame such that, when the frame is fitted across the forehead of the user, a surface of the first electrode can be parallel to the first side of the forehead of the user and a surface of the second electrode can be parallel to the second side of the forehead of the user.

29. The headset of claim **23**, wherein each of the first electrode and the second electrode includes an adhesive layer that is configured to adhere to a surface of the forehead.

30. The headset of claim **29**, wherein the adhesive layers of the first and second electrodes are removable from the first and second electrodes such that the adhesive layers can be discarded after use.

31. The headset of claim **23**, wherein the longitudinal extension is configured to be adjustable in length such that the longitudinal extension can be fitted around different sizes of heads of users.

* * * * *