

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409371
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Beaver; Richard James et al.

Fast-rope training apparatus

Abstract

A training apparatus for fast-rope training includes a platform-supporting structure having one or more containers and at least one platform configured for use in fast-rope training. At least one attachment is provided for attaching a fast-rope. The platform-supporting structure is supportable by a surface. The at least one attachment is located higher than the platform and spaced laterally from the platform-supporting structure such that the at least one attachment overhangs the surface so a fast rope can hang from the at least one attachment, past the platform and toward the surface.

Inventors: Beaver; Richard James (Church Stretton, GB), Beaver; Thomas Edward (Church Stretton, GB)

Applicant: Beaverfit Limited (Church Stretton, GB)

Family ID: 56894971

Assignee: Beaverfit Limited (Church Stretton, GB)

Appl. No.: 18/650936

Filed: April 30, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240278100 A1	Aug. 22, 2024

Foreign Application Priority Data

GB	1610911	Jun. 22, 2016
----	---------	---------------

Related U.S. Application Data

continuation parent-doc US 18122764 20230317 ABANDONED child-doc US 18650936
continuation parent-doc US 17181752 20210222 US 11612797 20230328 child-doc US 18122764

Publication Classification

Int. Cl.: **A63B69/00** (20060101); **A63B17/00** (20060101); **A63B17/02** (20060101); **E04H1/12** (20060101); **E04H12/00** (20060101); **G09B9/00** (20060101); **G09B19/00** (20060101); A63B71/02 (20060101)

U.S. Cl.:

CPC **A63B69/0048** (20130101); **A63B17/00** (20130101); **A63B17/02** (20130101); **E04H1/1205** (20130101); **E04H12/00** (20130101); **G09B9/003** (20130101); **G09B19/0038** (20130101); A63B71/02 (20130101); E04H2001/1283 (20130101)

Field of Classification Search

CPC: A63B (17/00); A63B (17/02); A63B (69/0048); A63B (71/02); E04H (12/00); E04H (2001/1283); G09B (9/003); G09B (19/0038)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5667267	12/1996	Talucci	296/26.15	B60P 3/14
6357550	12/2001	Willson	182/141	E04H 1/1205
6799975	12/2003	Dunn	434/226	G09B 19/00
7244123	12/2006	Barron	434/366	G09B 9/00
7931564	12/2010	Wu	482/37	A63B 69/0048
8016686	12/2010	Liggett	182/36	A63G 31/00
9016001	12/2014	Heger	52/79.5	E04B 1/34384
9295871	12/2015	Luedeka	N/A	A63B 21/0414
9750999	12/2016	Monaco	N/A	A63B 71/023
10105564	12/2017	Garland	N/A	A62B 35/0062
D845406	12/2018	Gilchrist	D21/686	N/A
2002/0185049	12/2001	Broderick	114/264	A63B 9/00
2006/0090960	12/2005	Liggett	182/36	A63G 33/00
2006/0101727	12/2005	Holgerson	52/79.1	A62C 99/0081
2006/0135272	12/2005	Liggett	472/92	A63G 31/02
2006/0258511	12/2005	Postma	482/37	A63B 69/0048
2007/0113487	12/2006	Warminsky	52/79.1	E04H 9/10
2007/0117503	12/2006	Warminsky	454/187	E04H 9/10
2007/0191123	12/2006	Liggett	472/15	A63G 31/02

2009/0282749	12/2008	Warminsky	52/745.03	E04H 9/10
2011/0023925	12/2010	Johnson	29/897.3	B60P 3/341
2012/0118668	12/2011	Ernstsen	182/115	E04H 12/00
2012/0144762	12/2011	Eatock	52/79.5	G09B 19/00
2014/0259978	12/2013	Walton	52/79.8	H01Q 1/44
2015/0014212	12/2014	Beaver	206/579	B65D 25/10
2015/0059257	12/2014	Beaver	52/27	A63B 26/00
2016/0059104	12/2015	Monaco	280/30	A63B 71/023
2017/0095743	12/2016	Gustafson	N/A	A63G 21/22
2017/0136278	12/2016	Gilchrist	N/A	A63B 5/20

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2768112	12/2005	CN	N/A
20 2011 103 114	12/2011	DE	N/A
2 016 058	12/2015	NL	N/A
WO 2010/133260	12/2009	WO	N/A
WO 2014/177880	12/2013	WO	N/A

OTHER PUBLICATIONS

AirSource Military, Aug. 27, 2014, “Air Guardsman—Rapelling and Fast Rope Use”, youtube.com, [online], Available from: <https://www.youtube.com/watch?v=YoeBY4nSzuQ> [Accessed Sep. 26, 2016] See whole video, especially 3:00 to 3:40. cited by applicant

BeaverFit, 2010-2016, “BeaverFit Training Equipment”, beaverfiteu.com, [online], Available from: <https://web.archive.org/web/20160511174256/http://www.beaverfiteu.com/> [Accessed Sep. 26, 2016] Applicant's prior art. See Operational Lockers—Custom Lockers. cited by applicant

International Search Report and Written Opinion of International Application No.

PCT/GB2017/051822 dated Sep. 13, 2017, 9 pages. cited by applicant

U.K. Search Report of British Application No. GB1610911.8 dated Sep. 28, 2016, 4 pages. cited by applicant

Primary Examiner: Lee; Joshua

Attorney, Agent or Firm: Lippes Mathias LLP

Background/Summary

(1) This application is a continuation of U.S. patent application Ser. No. 18/122,764 which was filed on Mar. 17, 2023 and is still pending. That application is a continuation of U.S. patent application Ser. No. 17/181,752 which was filed on Feb. 22, 2021 and granted as U.S. Pat. No. 11,612,797 on Mar. 28, 2023. (2) That application in turn is a continuation of U.S. patent application Ser. No. 16/312,708 which was filed on Dec. 21, 2018 and has granted as U.S. Pat. No. 10,940,380 which issued on Mar. 9, 2021. That application, in turn, was the entry into the U.S. national phase of International Application Serial No. PCT/GB2017/051822 which was filed on Jun. 21, 2017. The disclosures of each of those applications are incorporated hereinto by reference in their entirety.

BACKGROUND OF THE DISCLOSURE

(1) The present disclosure relates to a fast-rope training apparatus, particularly a tower for fast-rope

training.

(2) Fast-rope is a technique used primarily by military and emergency service personnel in order to lower personnel at a height (such as in a hovering helicopter) to a lower level (such as the ground). In fast-rope, a rope suitable for fast-rope is hung toward the ground, a user is attached to the rope and a user lowers themselves to the ground under gravity and controls their speed, usually with their hands.

(3) As this is a high-risk and high-skilled operation, the user requires significant training to ensure they can safely perform fast-rope. Current training facilities are inadequate, expensive and complex. One such training facility comprises a large permanent building, such as a hanger. A fast-rope training apparatus has been constructed inside the building, making use of the structure of the building, such as the building's beams, to support the apparatus. This fast-rope training apparatus is made bespoke to fit inside the building and is therefore of no use for mass-production. Further, it is expensive and time consuming to design and erect.

(4) The present disclosure addresses these issues and provides other significant advantages as is clear from the following description.

SUMMARY OF THE DISCLOSURE

(5) In one aspect, the present disclosure provides a fast-rope training apparatus comprising a platform-supporting structure comprising one or more containers; at least one platform configured for use in fast-rope training; and at least one attachment for attaching a fast-rope, wherein the platform-supporting structure is supportable by a surface, and wherein the at least one attachment is located higher than the platform and spaced laterally from the platform and/or platform-supporting structure such that the at least one attachment overhangs the surface, and possibly also the platform, so a fast-rope can hang from the at least one attachment, past the platform and toward the surface.

(6) In another aspect, the present disclosure provides a fast-rope training apparatus comprising a platform-supporting structure comprising one or more containers; at least one platform configured for use in fast-rope training; wherein the platform-supporting structure is supportable by a surface, and wherein the at least one platform extends outward from the platform-supporting structure such that the at least one platform overhangs the surface.

(7) This training apparatus may comprise at least one attachment for attaching a fast rope. The attachment may be located higher than the platform.

(8) The attachment may be spaced laterally from the platform (and the platform-supporting structure). In this way, the at least one attachment may overhang the surface (but not the platform) so a fast-rope can hang (at least substantially vertically) from the at least one attachment, past the platform and toward the surface.

(9) Alternatively, the attachment may be spaced laterally from the platform-supporting structure (and preferably vertically above the platform) such that the at least one attachment overhangs the platform (and the surface) so a fast-rope can hang (at least substantially vertically) from the at least one attachment, past/through the platform (e.g. a through a hatch in the platform, see below) and toward the surface.

(10) The attachment and the platform may preferably be arranged so that there would be no contact between the rope and the platform as the rope hangs (in its natural state) from the attachment.

(11) Alternatively, the attachment may be spaced laterally from the platform-supporting structure (and preferably vertically above the platform) such that the at least one attachment overhangs the platform (and the surface) so a fast-rope can hang at least partially vertically from the at least one attachment to an edge of the platform, past the platform, and then substantially vertically from the edge of the platform to the surface.

(12) In this case, for example, the fast rope may contact the platform

(13) The present disclosure provides a simple and cheap fast-rope training apparatus. In the prior art, fast-rope training is performed using training equipment with a complex set up: the training

equipment is supported by the structure of a permanent building and so the training equipment has to be designed and configured to fit around and be supported by the structure of the permanent building. In contrast, the platform-supporting structure may provide the sufficient height for the fast-rope training in a simple and cost-effective manner, and removes the need for the training apparatus to be supported by a permanent building (or any other structure). Further, the nature of the containers allows the training apparatus to be semi-transportable, i.e. when there is a plurality of the containers, they may be “unstacked” and transported to another location where they are “restacked” to form the platform-supporting structure/training apparatus. The training equipment of the prior art is not transportable at all in order to transport it, it would require a complete disassembly of the entire training equipment.

(14) The platform-supporting structure may consist of one or more containers. The platform-supporting structure may be formed of a plurality of containers arranged in a stack. In this case, the platform-supporting structure may be a stack. The stack may comprise or consist of a stack of containers.

(15) When a plurality of containers form the stack, the training apparatus may be a tower for fast-rope training.

(16) When stacked, the containers may be secured to each other. Further, the lower-most structure may be arranged to rest on the surface (e.g. under gravity), or to be secured to the surface.

(17) The platform-supporting structure may be of such a height such that it is useful and suitable for fast-rope training. The platform-supporting structure may be at least 4 m, preferably at least 6 m, preferably at least 7 m, preferably less than 15 m, preferably less than 10 m, preferably 4-15 m, preferably 7-10 m high. The training apparatus as a whole may be at least 8 m, preferably at least 10 m, preferably less than 15 m, preferably less than 12 m, preferably 8-15 m, preferably 10-12 m high.

(18) A platform may be configured for use in fast-rope training if it is provided with suitable equipment on or in the vicinity of the platform. For instance, to perform fast-roping, suitable attachments (such as bars and/or hooks and/or loops) may be required for attaching a rope, or indeed a suitable rope may be required. Such attachments must be capable of supporting the weight of a user, e.g. capable of supporting vertical loads of at least 50 kg, 100 kg, 150 kg or 200 kg. Further, suitable access to the edge of the platform may be required (such as a gate or hatch). Further, the platform may be required to be of a certain height above the ground, such as at least 1 m, preferably at least 5 m, preferably at least 8 m, preferably less than 15 m, preferably less than 12 m, preferably less than 10 m, preferably 1-15 m, preferably 5-12 m, preferably 8-10 m. Further, a platform may be configured for use in fast-rope training if there is a free vertical path between the platform and the surface (e.g. there is nothing in the way of a user that fast-ropes from the platform to the surface). Further, a platform may be configured for use in fast-rope training if the surface of the platform is generally flat/horizontal and provides enough space for at least 1, 2 or 3 users to stand and move comfortably in the vicinity of the rope or the platform edge. Such an area may be at least 2 m², 4 m², 6 m², 8 m², or 10 m². The platform edge local to the rope may be at least, 0.5 m, 1 m, 2 m or 3 m long. The platform is preferably generally rectangular in shape.

(19) The surface may be a ground surface, and the surface is preferably flat/horizontal. The platform-supporting structure may be directly supportable (e.g. in direct contact with) or indirectly supportable (e.g. with an element, such as a trailer (with wheels), in between the platform-supporting structure and the ground surface) by the ground surface.

(20) The at least one attachment may overhang the surface (and possibly the platform) in such a way that a fast-rope can hang past/through/by the platform within a user's arm's reach of the edge of the platform, e.g. less than 1 m or 0.5 m from the edge of the platform.

(21) The at least one attachment may overhang the surface (and possibly the platform) in such a way that a fast-rope can hang from the attachment means such that when it is used by a user there is

no (or very little) risk of the user hitting the platform-supporting structure. For example, the attachment means may overhang the surface by at least 0.5 m, preferably 1 m, preferably 1.5 m, preferably 2 m, preferably 2.5 m, with respect to the nearest lateral side of the platform-supporting structure and/or platform (when viewed from vertically above).

(22) The “overhang” mentioned in this disclosure is overhang when viewed from vertically above the training apparatus. An overhang should be considered to be when one element (such as the attachment) is spaced laterally outward from a lateral periphery of a second element (such as the platform-supporting structure) such that it is vertically above a third element (such as the surface or the platform). In this case, in consistent usage with the term “overhang” as used in this specification, the first element overhangs the third element, with respect to the second element. When the attachment overhangs the surface it may or may not also overhang the platform, e.g. it may overhang the surface only when it is vertically above the surface but not vertically above the platform, or it may overhang both the surface and the platform when it is vertically above the platform and the surface. Preferably, there is nothing vertically between the platform (or at least the peripheral lateral edge of the platform past which the rope may hang) and the surface to affect the path of the rope, or to affect/prevent the user from fast-rope between the platform and the rope.

(23) The training apparatus may comprise at least one rope for use in fast-rope. The rope may hang (at least substantially vertically) from the attachment. The rope may pass by the platform within a user's arm's reach (of the edge of the platform). The rope may pass through the platform within a user's arm's reach (of the edge of the platform, which may be an edge of the hatch). In cases where the attachment overhangs the platform (e.g. the attachment is vertically above the platform) the fast-rope may hang non-vertically from the attachment until it contacts the platform (such as an edge of the platform or a skid-see below) and then may hang vertically from the platform toward the surface. In cases where the attachment overhangs the platform (e.g. the attachment is vertically above the platform) the fast-rope may hang substantially vertically from the attachment through the platform (e.g. via a hatch, see below) and then may hang vertically from the platform toward the surface.

(24) There may be a plurality of attachments. Any combination of the position of attachments with respect to the platform mentioned above is possible. A rope for use in fast-rope may be attached to each of the attachments.

(25) The one or more containers may (each) be a transportable structure, such as a transportable cabin. The transportable structure may be loadable onto a trailer of a lorry for example. The one or more containers may be cheap and readily available, and may simplify construction and deployment of the training apparatus. This is particularly advantageous over the prior art where training equipment is secured to a permanent building in a complex manner. The present solution is therefore much cheaper, and more transportable. For example, the present training apparatus could be quite straightforwardly temporarily erected in a training ground, e.g. in a military base. The present disclosure could subsequently be easily moved to any appropriate location. Further, the present training apparatus could be constructed in a modular form and transported to a desired location where it is then erected. This modular construction would greatly ease erection of the training apparatus.

(26) Thus, the training apparatus may preferably have a modular construction. The modules may be the one or more containers, and may also include the top training apparatus assembly (see below).

(27) Preferably, the one or more containers are pre-fabricated containers. Just because a container is described as “pre-fabricated”, it does not mean that absolutely no fabrication/modification of the container is possible. Rather, a pre-fabricated container may be one that has its own structural integrity prior to construction of the platform-supporting structure, such as an ISO container or a portable building (such as a porta-cabin) or any similar pre-fabricated structure. Thus, a pre-fabricated container may be one in which the components of the container, such as the walls, roof and floor, are secured to one another such that the container may be considered to be one modular

element. Further, a pre-fabricated structure may be one that can be sourced/purchase in an off-the-shelf manner, rather than requiring specific construction steps by the constructor of the training apparatus.

(28) Preferably, the one or more containers comprise one or more ISO shipping containers. These may be 10' (3 m), 20' (6.1 m) or 40' (12.2 m) ISO shipping containers. These are length measurements. Preferably, the 20' ISO shipping container is used. ISO shipping containers are typically around 8' (2.4 m) wide and 8-10' (2.4-3.0 m) high. ISO shipping containers provide many advantages. For instance, they are strong enough for stacking without significant (or any) structural reinforcement. Further, they are durable. Further, they are cheap and readily available. Further, they are easily transportable. Further, they are easily modified to include the additional features of the present disclosure (e.g. since they are typically made from metal, and since this metal is easily worked with). Preferably, the/each container is an ISO container.

(29) Preferably, each container has substantially the same dimensions. Preferably, each container has substantially the same width and length dimensions. Preferably, each container has substantially the same height dimension. This allows the containers to be easily stacked to form the platform-supporting structure.

(30) Preferably the/each container is cuboid-shaped.

(31) Preferably, the platform-supporting structure has a substantially vertical wall below the platform. Preferably all of the walls of the platform-supporting structure are substantially vertical. It is advantageous not to have the base of the platform-supporting structure wider than the top as this would mean a long platform is needed in order to achieve the platform's overhang of the surface. However, it is advantageous not have the base narrower than the top of the platform-supporting structure as this would lead to a potentially unstable platform-supporting structure. The wall may be formed of the respective walls of the one or more containers.

(32) The training apparatus may be free-standing. Thus, the training apparatus may be arranged such that it does not require structural support from any other structure/building. This is advantageous as it allows the training apparatus to be erected in any suitable location. The prior art training equipment discussed above, on the other hand, requires the training equipment to be structurally supported by a permanent building structure. This severely limits the locations in which the training equipment can be erected, and severely increases its complexity.

(33) The platform-supporting structure may comprise an uppermost portion. The at least one platform may comprise an uppermost portion-level platform at substantially the same height as the uppermost portion. This location is desirable as it allows the uppermost portion-level platform to be supported on the platform-supporting structure whilst allowing the maximum possible distance between the platform and the surface, which is beneficial for fast-rope training. The uppermost portion of the platform-supporting structure may be the top of the top container (or the only container), such as the top surface (e.g. the roof) of the top container (or the only container). The uppermost portion-level platform may extend laterally outward from the uppermost portion of the platform-supporting structure, such that it overhangs the surface. Said platform may be located at an end of the platform-supporting structure (with respect to the length of the one or more containers).

(34) The training apparatus may comprise a plurality of uppermost portion-level platforms. Preferably there are two (only). Each of said platforms may be located at opposite respective ends of the platform-supporting structure (with respect to the length of the one or more containers). Preferably, these are at substantially the same height as each other.

(35) The at least one platform may also comprise a platform at a location above the uppermost portion of the platform-supporting structure, e.g. a platform that is held above the uppermost portion of the platform-supporting structure by a frame. The frame may comprise one or more substantially vertically oriented bars. The frame may extend from the platform-supporting structure. This frame and platform may be or may be part of the top training apparatus assembly

discussed below. It may be a module (preferably a prefabricated module) that can be installed and removed from the platform-supporting structure.

(36) Additionally/alternatively, at least one of the one or more containers may comprise a floor. The at least one platform may comprise a floor-level platform at substantially the same height as said floor. Said container may preferably be the top container of the platform-supporting structure. Said container may be second container from the top. Said container may be any of the containers in the platform-supporting structure other than the bottom container. This location of platform allows a lower training height to be used, which can be advantageous for progressive learning/training. Further, this location of platform allows the floor of said container to be used as the platform, to support the platform and/or to allow access to the platform. The platform may extend from the floor at substantially the same height as the floor, such that it overhangs the surface. Said platform may be located at an end of the platform-supporting structure (with respect to the length of the one or more containers).

(37) The floor-level platform may be vertically below the uppermost-level platform. Preferably the floor-level platform and the uppermost-level platform extend laterally outward from the same end of the platform-supporting structure, and extend in the same direction.

(38) Preferably the uppermost-level platform extends further from the platform-supporting structure than the floor-level platform. This allows users to fast-rope from both platforms at the same time without interfering with each other.

(39) The floor-level platform may have a length equal to the width of the platform-supporting structure.

(40) The training apparatus may comprise a plurality of floor-level platforms. Preferably there are two (only). Each of said platforms may be located at opposite respective ends of the platform-supporting structure (with respect to the length of the one or more containers). Preferably, these are at substantially the same height as each other.

(41) The floor-level platform may equally be thought of as a roof-level platform, level with the roof of the container immediately below the platform. In this case, said platform has substantially the same height as the roof of the container. The container in question may be the second container from the top, the third container from the top, or the bottom container. Said container may be any of the containers except the top container. The platform may extend from the roof at substantially the same height as the roof, such that it overhangs the surface. Said platform may be located at an end of the platform-supporting structure (with respect to the length of the one or more containers).

(42) The roof-level platform may be vertically below the uppermost-level platform (see below). Preferably the roof-level platform and the uppermost-level platform extend laterally outward from the same end of the platform-supporting structure, and extend in the same direction.

(43) Preferably the uppermost-level platform extends further from the platform-supporting structure than the roof-level platform. This allows users to fast-rope from both platforms at the same time without interfering with each other.

(44) The training apparatus may comprise a plurality of roof-level platforms. Preferably there are two (only). Each of said platforms may be located at opposite respective ends of the platform-supporting structure (with respect to the length of the one or more containers). Preferably, these are at substantially the same height as each other.

(45) Whether the platform is thought of as a roof-level platform or a floor-level platform may come down to preference of the given situation. However, it should be understood that these two platforms are at least substantially similar, and may be equivalent in many situations.

(46) The external wall of the platform-supporting structure may comprise a door for accessing the platform. Preferably, the door may be the external wall of one of the one or more containers. The door may be in the end wall of the container. The door may be adjacent to the platform. The door may be a roller door. The door may be configured such that when the door is shut, the external wall of the container/platform-supporting structure is substantially completely closed. The door may be

configured such that when the door is open, the end wall of the container is substantially completely open. When the door is in a wall of a container, the platform is preferably the floor-level platform of that container (or roof-level platform of the container below).

(47) The platform may be moveable between a deployed position (e.g. ready for use) and a retracted position (e.g. ready for assembly/disassembly of the training apparatus and transportation of the one or more containers). The moveable portion may be the portion of the platform that overhangs the surface. The movement may be a hinging/pivoting movement. The platform may be attached to one of the one or more containers via a hinge. Preferably, the hinge/pivot is orientated horizontally and extends parallel to the wall of the container and is arranged such that the platform may pivot downwards to a horizontal deployed position and upwards to a vertical retracted position (e.g. for a floor-level platform). The hinge may alternatively be arranged such that the platform may pivot upwardly to its deployed position and downwardly to its vertical retracted position (e.g. for a roof-level platform). When in the vertical retracted position the platform may be substantially flush with, or at least substantially parallel to and adjacent to, the outside of the container/platform-supporting structure. The platform may comprise a stay or brace or strut configured to maintain the platform in the deployed position, e.g. to act against vertical downward loads on the platform to ensure the platform is maintained in the deployed (horizontal) position.

(48) Additionally/alternatively, the platform-supporting structure may comprise an external wall. The at least one platform may comprise an external wall platform that is attached to and supported by the external wall. The external wall of the platform-supporting structure may preferably be a substantially vertical wall, and may be made from external walls of the one or more containers. The platform may be attached to the external wall and extend horizontally therefrom. The platform may also be supported by the surface, preferably via at least partially vertical supporting member(s). The platform may preferably be attached to the bottom container. This lower height is preferable as it allows for easier and safer demonstrations and learning. Said platform may be located on a side wall (as opposed to an end wall, with respect to the length of the one or more containers).

(49) The platform may extend with a horizontal length less than or equal to the length of the platform-supporting structure/one or more containers.

(50) Between the platform and the ground surface there may extend a wall, preferably a vertical wall, which may be used for climbing.

(51) The training apparatus may comprise a plurality of external wall platforms. Preferably there are two (only). Each of said platforms may be located on opposite or the same side wall of the platform-supporting structure (with respect to the length of the one or more containers). Each may have substantially the same height or different heights.

(52) The at least one platform may comprise at least one hatch. The hatch may allow a rope to pass through the platform, and may allow the user to fast-rope through the platform. The hatch may be hinged to the remainder of the platform. The hatch may have an area of at least 0.5 m.^{sup.2}, preferably at least 1 m.^{sup.2}. The platform, may comprise a plurality of hatches. When there is more than one platform present, any or all of the platforms may comprise at least one hatch. The hatch, when opened, may provide at least one platform edge.

(53) The upper surface of the platform may comprise at least one attachment, preferably a plurality of attachments. These attachments may preferably surround the hatch.

(54) The at least one platform may comprise at least one skid. The skid may be a skid such as that found on a helicopter's undercarriage. Such a skid may comprise a generally horizontal bar running parallel with the adjacent edge of the platform. The horizontal bar may be lower than the platform surface and may be spaced laterally outward from the platform edge. This mimics a helicopter's skid, and so can be used for practicing fast-roping from helicopters. The platform may comprise a plurality of skids. When more than one platform is present, any or all of the platforms may comprise at least one skid. The skid may be thought of as part of the platform, or as attached to the platform. When the rope hangs partially vertically from the attachment to contact the platform, it

may contact the (horizontal bar of) the skid.

(55) The at least one platform may comprises at least one jettied deck. The jettied deck may extend horizontally from the platform, preferably in a direction perpendicular to the side walls of the platform-supporting structure. The jettied deck may extend from the platform from between the platform-supporting structure and the outer edge of the platform. The jettied deck may comprise an outer edge distant from the platform. The outer edge may extend horizontally in a direction perpendicular to the end walls of the platform-supporting structure. The outer edge of the jettied deck may overhang only the ground surface, i.e. it has lateral clearance from the platform-supporting structure/platform to avoid overhanging any other components of the training apparatus. The jettied deck may extend laterally from the platform, and perpendicular to the plane of the first side wall of the platform-supporting structure, by at least 0.4 m, preferably 0.5 m. The jettied deck may be rectangular and may have a length of at least 1 m, but less than the width of the platform, and may have a width of at least 0.4 m, preferably at least 0.5 m. The upper surface of the jettied deck may be flush/continuous with the upper surface of the platform.

(56) The skid may be attached to the outer edge of the jettied deck.

(57) The at least one attachment may be provided on a frame. The frame may be supported at least partially by the platform. Additionally/alternatively, the frame may be supported by the surface, particularly with regard to the external wall platform. The frame may comprise at least one at least partially vertical member extending to a height above the platform, preferably above a user's head height. The frame may also comprise at least one at least partially horizontal member extending outward, preferably over the edge of the platform, preferably outward from the upper portion of the at least one at least partially vertical member. The frame may comprise at least one strut supporting the at least one at least partially horizontal member relative to the at least one at least partially vertical member. The attachment may be connected (directly or indirectly) to the outer portion of the at least one at least partially horizontal member.

(58) Preferably, the frame comprises at least two at least partially vertical members and at least two respective at least partially horizontal members. These may be spaced relative to one another such that a bar may extend horizontally between the outer portions of the respective at least partially horizontal members. The bar may be substantially parallel to the adjacent edge of the platform. The attachment may be mounted to the bar. The bar may extend substantially the length of the adjacent platform edge. The two at least partially vertical (and the respective two at least partially horizontal) members may be located at opposite ends of the adjacent edge of the platform. By "adjacent edge" it is intend to mean the edge nearest to the attachment, over which the attachment is mounted.

(59) However, it is not necessary to have a frame above the platform. For instance, when one platform is above another (e.g. the floor-level platform may be vertically below the upper-most level platform), the attachment for the lower platform may be provided on the upper platform. For instance, the attachment may be provided on the underside of the upper platform, or may be provided on the upper side of the upper platform and a passage for the rope (e.g. the hatch) may allow for the rope to hang down through the upper platform and past the lower platform.

(60) The attachment may be a hoop, a ring, a swivel, a pulley or any other means suitable for hanging a fast-rope. There may be a plurality of attachments. There may be a plurality of attachments on the bar. There may be a plurality of attachments on each platform, and/or on each edge of the/each platform.

(61) The training apparatus may comprise a gate configured to optionally block a user's pathway to the platform or to an edge of the platform. This gate may be part of a balustrade blocking a user's pathway to the platform or to an edge of the platform. The gate (and balustrade) acts to improve the safety of the users. The platform may comprise a plurality of gates. When there is more than one platform present, any or all of the platforms may comprise at least one gate.

(62) The balustrade described in this disclosure may be a railing, bannister, fence, wall or any

suitable barrier.

(63) The training apparatus may comprise an anchor device for securing a user to the training apparatus in order to prevent the user falling from the platform. The anchor device may be located above the platform. The anchor device is preferably above head-height of the user. An anchor device that allows movement of the user around the platform is preferable. A rail provides such functionality. The user can be secured to the anchor via a carabiner, or any other suitable clip, and a rope, or any other suitable tether. The anchor device may preferably comprise a rail. The rail may extend across or along the platform, preferably in a linear direction, preferably across/along above a central portion of the platform (e.g. toward the centre, away from the outer edge(s) of the platform).

(64) The training apparatus may comprise climbing equipment for accessing the at least one platform.

(65) The climbing equipment may comprise a climbing wall. The climbing wall may be attached to an external wall, or may be formed on, an external wall of the platform-supporting structure. Preferably, the climbing wall extends from the bottom of the platform-supporting structure to the top of the platform-supporting structure. Preferably, the climbing wall extends substantially across the horizontal length of the platform-supporting structure. Preferably, the climbing wall is located adjacent/on the side wall of the platform-supporting structure (with respect to the length of the one or more containers), e.g. not the end wall. The climbing wall is preferably substantially vertical, but may be non-vertical. The climbing wall may be a facade that is attached to the external wall of the platform-supporting structure. Alternatively, the climbing wall may comprise (specifically designed climbing) holds attached to the external wall of the platform-supporting structure to allow users to climb up the platform-supporting structure.

(66) Additionally/alternatively, the training apparatus may comprise a climbing wall that extends substantially across the horizontal width of the platform-supporting structure. Preferably, the climbing wall is located adjacent/on the end wall of the platform-supporting structure (with respect to the length of the one or more containers), e.g. not the side wall. The climbing wall is preferably angled or non-vertical, but may also be vertical. The climbing wall may be a facade that is attached to the external wall of the platform-supporting structure. Alternatively, the climbing wall may comprise (specifically designed climbing) holds attached to the external wall of the platform-supporting structure to allow users to climb up the platform-supporting structure.

(67) The training apparatus may also comprise an attachment for attaching safety ropes for the climbing wall, in order to prevent the user from falling from the climbing wall. The safety rope(s) may also be provided.

(68) Combining a climbing wall with the training apparatus allows for improved training, as the mental and physical fitness of the users can be pushed in between practicing fast-roping. In the prior art, steps or stairs are used to allow the user to reach the platform. This does not have the same benefits as a climbing wall.

(69) The term climbing wall is intended to cover a wall that includes modifications, such as purpose-built holds, that are specially positioned and configured to allow a user to climb up the wall.

(70) Additionally/alternatively, the climbing equipment may comprise at least one ladder. The at least one ladder may extend from the surface to the top of the platform-supporting structure.

(71) The ladder may be external to the platform-supporting structure, and may be attached to an external wall of the platform-supporting structure (preferably the opposite side wall to the climbing wall). The ladder may pass by the external wall platform to allow access to the external wall platform (e.g. it may pass with 1 m, preferably 0.5 m, of the external wall platform). Preferably the ladder is attached to the same external wall as the external wall platform. Preferably the ladder comprises a cage for protecting the user, preferably the cage is only present at heights above the height of the external wall platform so as to allow the user to step off the ladder onto the external

wall platform.

(72) Alternatively, the at least one ladder may be internal to the platform-supporting structure. The ladder may extend directly from the bottom of the platform-supporting structure through the one or more containers to the top of the platform-supporting structure. Alternatively, the ladder may extend from the floor of a lower container to the floor of a higher container. There may be a plurality of such ladders, providing a path from the bottom to the top of the platform-supporting structure.

(73) Additionally/alternatively, the climbing equipment may comprise a staircase external to the platform-supporting structure. The staircase may be a spiral staircase. The platform-supporting structure may comprise external doors. The doors and the staircase may be arranged such that the staircase provides access to the doors. Each of the one or more containers that make up wall where the staircase is adjacent to may comprise a door. Each door may provide access through the wall of a given container.

(74) Additionally/alternatively, the climbing equipment may comprise steps or stairs. The steps or stairs may be internal to the platform-supporting structure. There may preferably be a flight of stairs extending from a floor of a lower container to a floor of a higher container, or from a floor of a (or the) container to a roof of the same container. There may be a plurality of such flights providing a path from the bottom of the platform-supporting structure to the top of the platform-supporting structure.

(75) On the inside of the platform-supporting structure, the one or more containers may comprise openings in their walls, roofs and/or floors to allow users to move between the one or more containers of the platform-supporting structure as desired.

(76) The platform-supporting structure may comprise an uppermost portion.

(77) The training apparatus may further comprise a top training apparatus assembly. The top training apparatus assembly may be arranged on the uppermost portion of the platform-supporting structure, and may comprise a first portion that at least partially overlaps with the platform-supporting structure and a second portion that overhangs the surface thus forming the at least one platform. This platform may be the uppermost-level platform.

(78) When the platform-supporting structure is a stack, and the training apparatus is a tower, the top training apparatus assembly may be a top tower assembly.

(79) The top training apparatus assembly may be a pre-fabricated module, or may be made of a plurality of prefabricated modules. This allows for the construction of the training apparatus to be simplified. The top training apparatus assembly may be secured to the platform-supporting structure. The prefabricated module(s) may have a length equal to or greater than the length of one of said one or more containers and a width substantially equal to the width of one of said one or more containers.

(80) The first portion overlapping with the platform-supporting structure is overlapping when viewed from vertically above.

(81) Other components of the training apparatus, such as the balustrade(s), the gate(s), the anchor(s), the attachment(s), the skid(s), the hatch(es), etc., can be provide as part of the top training apparatus assembly.

(82) The top training apparatus assembly may comprise a floor portion, a first portion of which at least partially overlaps with the platform-supporting structure and a second portion of which overhangs the surface thus forming the at least one platform.

(83) The top training apparatus assembly may have substantially the same width as the platform-supporting structure, but may be longer than the platform-supporting structure.

(84) The top training apparatus assembly may be arranged on the platform-supporting structure such that there is no overhang of the platform assembly over the side walls of the platform-supporting structure. The top training apparatus assembly may be arranged such that there is an overhang of the top training apparatus assembly over at least one of the end (and preferably both

ends) of the platform-supporting structure.

(85) The training apparatus may comprise a roof. The roof may be a cover or awning. The roof may substantially cover the platform-supporting structure. The roof may substantially cover the at least one platform. The roof may substantially cover all the platforms, except possibly the external wall platform. The roof may be attached to the top training apparatus assembly and may substantially cover the top training apparatus assembly, preferably the floor portion of the top training apparatus assembly. The roof is preferably above head-height in relation to the at least one platform, preferably in relation to the uppermost-level platform, preferably in relation to the floor of the top training apparatus assembly.

(86) The training apparatus may comprise a frame. The roof may be supported by the frame.

(87) The frame of the top training apparatus assembly may incorporate vertical and horizontal members, so as to preferably provide the overhanging attachment(s) for platforms and to provide support for the roof. The horizontal members may be above head height of a user standing on the top training apparatus assembly.

(88) The one or more containers and the platform-supporting structure may be rectangular when viewed from above. The length of the one or more containers (e.g. the longest measurement of the rectangle) may define a side wall of the platform-supporting structure. The width of the one or more containers may define an end wall of the platform-supporting structure.

(89) The platform may be rectangular when viewed from above.

(90) When the platform is the uppermost level platform, the length of the platform (as used in this specification) may be in the direction perpendicular to the side walls of the platform-supporting structure. The width of the platform may be in the direction perpendicular to the end walls of the platform-supporting structure. Whilst the length may be longer than the width of the platform, the width may also be longer than the length: here “length” and “width” may merely relative terms.

(91) When the platform is the floor-level platform, the length the length of the platform (as used in this specification) may be in the direction perpendicular to the side walls of the platform-supporting structure. The width of the platform may be in the direction perpendicular to the end walls of the platform-supporting structure. Whilst the length may be longer than the width of the platform, the width may also be longer than the length: here “length” and “width” may merely relative terms.

(92) The jettied deck may be rectangular when viewed from above. The length of the jettied deck (as used in this specification) may be perpendicular to the end walls of the platform-supporting structure. The width of the jettied deck may be in the direction perpendicular to the side walls of the platform-supporting structure. Whilst the length may be longer than the width of the jettied deck, the width may also be longer than the length: here “length” and “width” may merely relative terms.

(93) The platform-supporting structure may comprise (or consist of) single containers stacked on top of each other, or even just one single container. However, the platform-supporting structure may also comprise two or more containers arranged horizontally relative one another. These containers may form layers of the platform-supporting structure, with layers stacked on top of each other. The two or more containers arranged horizontally may be adjacent each other, preferably contacting each other and further preferably fixed to each other. This has the advantage of increasing the width of the platform-supporting structure, and hence increasing the stability of the platform-supporting structure. Since the area of the platform-supporting structure (when viewed from above) is increased, the size of the platform area(s) may also be increased.

(94) The platform-supporting structure may have a length substantially equal to the length of a single container. The platform-supporting structure may have a width larger than (or equal to) the width of a single container. The length of the platform-supporting structure may be defined by the length of the one or more containers. The width of the platform-supporting structure may be defined by the width of one, two, three or more containers arranged in a layer.

(95) Preferably, each layer comprises (only) two containers.

- (96) The containers of each layer may be attached to each other such that respective side walls of the containers are adjacent each other (such that they face each other) and such that respective end walls are in line with each other. The respective shipping containers of a given layer may be arranged horizontally with respect to each other. All the layers may have a similar way form. The layers may be stacked on top of each other such that the side walls and the end walls of the containers form vertical walls of the platform-supporting structure. This may form a platform-supporting structure that has a width substantially equal to the sum of the widths of the containers used in a given layer, and a length substantially equal to the length of an individual container.
- (97) The platform-supporting structure may also be thought of as a plurality (preferably two) columns of containers placed adjacent each other such that the side walls of the respective containers are adjacent each other and such that the end walls are aligned.
- (98) The platform-supporting structure is preferably made of (only) three layers of the shipping containers stacked vertically on top of one another. The containers may be stacked such that the floor of the containers of an upper layer container rests and may be attached to the roof of the containers of a lower layer. Respective lateral walls of the containers in a given column may be in the same general planes. End walls of the containers may be in the same general planes. In this way, the containers of a given column may be stacked in an aligned arrangement, such that their peripheral walls and ends are aligned with each other.
- (99) A first layer may be arranged on the ground surface (not shown). A second layer may be arranged on the first layer. A third layer may be arranged on the second layer.
- (100) The aligned lateral side walls of containers may form respective lateral side walls of the platform-supporting structure. The aligned ends of the containers may form respective end walls of the platform-supporting structure.
- (101) The training apparatus with such a platform-supporting structure may comprise any of the features of the training apparatus discussed herein. However, some of said features may be slightly different or modified when a larger platform-supporting structure is used.
- (102) For instance, floor-level platform and the uppermost-level platform may be larger, as it is accommodated by the larger platform-supporting structure. When n containers form a given layer, the platform may be n times longer/larger than the platform when the platform-supporting structure has a width equal to that of a single container.
- (103) In another aspect, the disclosure can provide a climbing training apparatus comprising a structure comprising one or more containers; and a climbing wall attached to, or formed on, an external side wall of the structure.
- (104) Preferably, the climbing wall extends from the bottom of the structure to the top of the structure. Preferably, the climbing wall extends substantially across the horizontal length of the structure. Preferably, the climbing wall is located adjacent to/on the side wall of the structure (with respect to the length of the containers), e.g. not the end wall. The climbing wall is preferably substantially vertical. The climbing wall may be a facade that is attached to the external wall of the structure. Alternatively, the climbing wall may comprise holds specially attached to the external wall of the structure to allow users to climb up the structure.
- (105) The climbing training apparatus may also comprise an attachment for attaching safety ropes for the climbing wall, in order to prevent the user from falling from the climbing wall.
- (106) Such a climbing training apparatus is advantageous as it is cheap and easy to manufacture and transport. This climbing training apparatus may comprise any of the features discussed above in relation to the other aspects of this disclosure. The structure may comprise any of the features discussed herein in relation to the platform-supporting structure. The structure may (or may not) be a platform-supporting structure.
- (107) The skilled person would immediately appreciate that any different combinations of the above-discussed features are possible.
-

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Certain preferred embodiments will now be described by way of example only and with reference to the accompanying drawings, in which:
- (2) FIG. 1 shows a perspective view of a tower according to an embodiment of the present disclosure;
- (3) FIG. 2 shows another perspective view of the tower of FIG. 1;
- (4) FIG. 3 shows another perspective view of the tower of FIG. 1;
- (5) FIG. 4 shows an end-on view of the tower of FIG. 1;
- (6) FIG. 5 shows a side-on view of the tower of FIG. 1;
- (7) FIG. 6 shows a plan view of the tower of FIG. 1;
- (8) FIG. 7 shows an end-on view of another tower according to another embodiment of the present disclosure;
- (9) FIG. 8 shows a side-on view of the tower of FIG. 7;
- (10) FIG. 9 shows a plan view of the tower of FIG. 7.
- (11) FIG. 10 shows a perspective view of another tower according to another embodiment of the present disclosure;
- (12) FIG. 11 shows an end-on view of the tower of FIG. 10;
- (13) FIG. 12 shows another perspective view of the tower of FIG. 10;
- (14) FIG. 13 shows a side-on view of another tower according to another embodiment of the present disclosure; and
- (15) FIG. 14 shows an end-on view of the tower of FIG. 13.

DETAILED DESCRIPTION OF THE DISCLOSURE

- (16) Shown in FIG. 1 is an embodiment of the apparatus 1 for fast-rope training. This apparatus is in the form of a tower 1. The tower 1 comprises a platform-supporting structure 3. The platform-supporting structure 3 takes the form of a stack 3 of ISO shipping containers 10, 20, 30 and a plurality of platform assemblies 100, 200, 300 configured for use in fast-rope training.
- (17) The containers 10, 20, 30 are cuboid-shaped. Each ISO shipping container 10, 20, 30 is of substantially the same dimensions, having a lateral length of around 20' (6.1 m), a lateral width of around 8' (2.4 m) and a vertical height of around 8' (2.4 m).
- (18) Each of the containers 10, 20, 30 comprises a first lateral external side wall 11, 21, 31 extending vertically along the length of the container 10, 20, 30; a second lateral external side wall 12, 22, 32 extending vertically along the length of the container 10, 20, 30 and parallel to the first lateral external side wall 11, 21, 31; a first end 13, 23, 33 extending vertically between and perpendicular to the first lateral external side wall 11, 21, 31 and the second lateral external side wall 12, 22, 32 at an end of the first lateral external side wall 11, 21, 31 and the second lateral external side wall 12, 22, 32; a second end 14, 24, 34 extending vertically between the first lateral external side wall 11, 21, 31 and the second lateral external side wall 12, 22, 32, perpendicularly to the first lateral external side wall 11, 21, 31 and the second lateral external side wall 12, 22, 32 at the other end of the first lateral external side wall 11, 21, 31 and the second lateral external side wall 12, 22, 32, and parallel to the first end 13, 23, 33; a roof 15, 25, 35 extending horizontally between an uppermost portion of the first lateral side wall 11, 21, 31, the second lateral side wall 12, 22, 32, the first end 13, 23, 33 and the second end 14, 24, 34; and a floor 16, 26, 36 extending horizontally between the lowermost portion of the first lateral side wall 11, 21, 31, the second lateral side wall 12, 22, 32, the first end 13, 23, 33 and the second end 14, 24, 34 parallel to the roof 15, 25, 35.
- (19) The stack 3 is made of three ISO shipping containers 10, 20, 30 stacked vertically on top of one another. The containers are stacked such that the floor 26, 36 of an upper container 20, 30 rests

and may be attached to the roof **15**, **25** of a lower container **10**, **20**; and such that the first lateral walls **11**, **21**, **31** are all in the same general plane; and such that the second lateral walls **12**, **22**, **32** are all in the same general plane; and such that the first ends **13**, **23**, **33** are all in the same general plane; and such that the second ends **14**, **24**, **34** are all in the same general plane. In this way, the containers **10**, **20**, **30** are stacked in an aligned arrangement, such that their peripheral walls and ends are aligned with each other.

(20) A first container **10** is arranged on the ground surface (not shown). A second container **20** is arranged on the first container. A third container **30** is arranged on the second container.

(21) The aligned first lateral side walls **11**, **21**, **31** thus generally form a first lateral side wall **4** of the stack **3**. The aligned second lateral side walls **12**, **22**, **32** thus generally form a second lateral side wall **5** of the stack **3**. The aligned first ends **13**, **23**, **33** thus generally form a first end **6** of the stack. The aligned second ends **14**, **24**, **34** thus generally form a second end **7** of the stack.

(22) The stack **3** rests on a preferably flat and horizontal ground surface (not shown).

(23) The tower **1** comprises a first platform assembly **100**. The first platform assembly **100** is an external wall **4** platform assembly. The first platform assembly **100** comprises a first platform **101** that is attached to the external side wall **11** of the first container **10**. The first platform **101** is an external wall platform. The first platform **101** extends horizontally outward from the external side wall **11**. The first platform **101** overhangs the ground surface. The first platform **101** is general rectangular and has horizontal dimensions of around 1-2 m by 1-2 m, preferably around 1 m by 1.5 m. The first platform **101** is between 1-2 m above the ground surface. The first platform **101** comprises an outer edge **102** that is horizontal and runs parallel to the external wall **4**. The outer edge **102** is the laterally outermost edge of the platform **101** when viewed from above.

(24) At opposite ends of its outer edge **102**, the first platform **101** is supported by and attached to two vertical members **103**, **104**. The first platform **101** is directly attached to the two vertical members **103**, **104** and respective struts may be connected between the first platform **101** and the vertical members **103**, **104** for additional support. The vertical members **103**, **104** are 1-2 m, preferably around 1 m, away from the external wall **4** of the stack **3**. The vertical members **103**, **104** extend vertically from the ground surface to a height of around 2-5 m, preferably around 3.5 m, above the ground and preferably at least around 2 m above the first platform **101** (e.g. above head height of someone on the platform **101**). The bottoms of each of the vertical members **103**, **104** contact the ground via ground engaging plates. The tops of each of the vertical members **103**, **104** are attached to respective horizontal members **105**, **106** that extend perpendicular to the external wall **4** of the stack and attach to the first lateral side wall **21** of the second container **20**. The tops of each of the vertical members **103**, **104** are connected together by a horizontal member **107** that extends parallel to the lateral external side **4** of the stack **3** and parallel to the outer edge **102** of the platform **101**. The horizontal member **107** has generally the same length as the length of the outer edge **102** and is substantially directly vertically above the outer edge **102**.

(25) Extending horizontally and laterally (perpendicular to the side wall **4** of the stack **3**) outward from the tops of each of the vertical members **103**, **104** are respective horizontal members **108**, **109**. These may each extend less than 1 m, preferably less than 0.5 m, laterally of the platform edge **102**. Laterally outward ends the horizontal members **108**, **109** are connected to the respective vertical members **103**, **104** via respective off-vertical struts to provide support to the horizontal members **108**, **109**. The horizontal members **108**, **109** are connected by a horizontal beam **110** that extends parallel to the lateral external wall **4** of the stack **3**. The height of the beam **110** is substantially the same as the height of the vertical members **103**, **104**. The height of the beam **110** is around 2-5 m, preferably around 3.5 m, above the ground and preferably at least around 2 m above the first platform **101** (e.g. above head height of someone on the platform **101**). The beam **110** is located at the laterally outward peripheral ends of the horizontal members **108**, **109**. The beam **110** is less than 1 m, preferably less than 0.5 m, laterally of the platform edge **102**. The beam **110** has generally the same length as the length of the outer edge **102** of the first platform **101** and

is parallel to the outer edge **102**.

(26) On the beam **110** is provided a plurality of attachment rings **111** for attaching a fast rope. The attachments **111** are spaced substantially equally along the beam, by at least 0.2 m, preferably 0.3 m, preferably 0.4 m, preferably 0.5 m.

(27) In the way described above, when ropes are attached to respective attachments **111** on the beam **110**, they may hang vertically from a height above the user's head height and toward the ground surface and may pass the outer edge **102** of the platform **101** within a user's arm's reach. Further, as can be seen from the above description, the attachment **111** is supported by a frame **103, 104, 105, 106, 107, 108, 109, 110**.

(28) The tower **1** comprises a second platform assembly **200**. The second platform assembly **200** is a floor-level platform assembly. The second platform assembly comprises a second platform **201**. The second platform **201** is a floor-level platform. The second platform **201** overhangs the ground surface. The second platform **201** is located at an end **6** of the stack **3**. The second platform **201** extends across substantially the entirety of the width of the stack **3**, i.e. from the first side **4** to the second side **5**. The second platform **201** is rectangular in shape and has an outer peripheral edge **202** (when in the deployed position) that extends across substantially the entirety of the width of the stack **3** and is spaced from the first end **6** of the stack **3**. The second platform **201** has a length approximately equal to the width of the stack **3**, e.g. around 8' (2.4 m). The second platform **201** as a width (i.e. the distance that the outer edge **202** extends beyond the end **6** of the stack when view from above) of less than 1 m, preferably less than or equal to 0.5 m. Thus, when in the deployed position the peripheral edge **202** is preferably less than 1 m, preferably less than or equal to 0.5 m, from the end **6** of the stack **3**. This is preferable so that users using the second platform assembly **200** do not interfere with or interrupt using the third platform assembly **300** (see below). The upper surface of the second platform **201** is flush with the upper surface of the floor **36** of the container, when in the deployed position. There is a minimal gap (preferably no gap) between the floor **36** and the platform **201**, i.e. the upper surface of the second platform **201** and the floor **36** are substantially continuous.

(29) The second platform **201** is attached to a lower portion (e.g. floor **36** or lower portion of first end **33**) of the third container **30** via hinges **203**. The hinges **203** allow for the second platform **201** to pivot about a horizontal axis parallel to the length of the second platform **201** and perpendicular to the plane of the side walls **4, 5** of the stack **3**. The axis of rotation defined by the hinges **203** may be located proximate the corner of the stack **3** where the first end **33** meets the floor **36** of the container **30**.

(30) The second platform **201** may therefore pivot between a vertical retracted position and a horizontal deployed position. Here vertical and horizontal refer to the orientation of the upper surface of the second platform **201**. When in the retracted position, the plane defined by the platform **201** is parallel to the first end **6** of the stack **3**, and the platform **201** is adjacent to and the upper surface (when in use) of the platform **201** may contact the first end **6** of the stack **3**. The platform **201** generally rotates upwards toward the retracted position. When in the deployed position, the plane defined by the platform **201** is horizontal. The platform **201** generally rotates downwards toward the deployed position.

(31) The second platform assembly **200** comprises second platform support struts **204** that support the second platform **201** relative to the stack **3**, when in the deployed position. The support struts **204** may themselves be hinged and may also be foldable in a central portion of the support struts **204** to allow for the platform **201** to pivot between its retracted and deployed positions. Each support strut **204** is connected between respective ends of the platform **201** and respective locations on the stack **3**, preferably to a location higher than the platform **201** when the platform is in the deployed position. The struts **204** connect to the platform **201** proximate the outer edge **202**.

(32) The platform **201** is attached to the container **30** by brackets **205**. Each bracket **205** is attached to a respective external side wall **31, 32** of the container **30** proximate the end **33** of the container

30. Each bracket **205** may comprise respective hinges **203**. Each strut **204** may connect to respective brackets **205**.

(33) Each bracket **205** extends substantially vertically, the hinge **203** being toward the bottom of the bracket **205** and the strut **204** being connected toward the top of the bracket **205**.

(34) The first end **33** of the container **30** comprises a door **206** for accessing the second platform **201** and for closing off the first end **33** when the platform **201** is retracted or not in use, e.g. for transport. The door **206** may be a roller shutter door. The door **206** is configured so that when it is opened substantially the entirety (or at least a majority) of the first end **33** of the container **30** is open.

(35) The first end **33** of the container **30** comprises a gate **207** for accessing the second platform **201** and for preventing access to the second platform **201**. The gate **207** is hinged to the inside of the external side walls **31**, **32** of the container **30**. The gate **207** is configured so that when it is opened access is provided to the platform **201** across substantially the entirety (or at least a majority) of the width of first end **33**.

(36) The second platform assembly **200** comprises attachments **211** for attaching a fast rope to, such as rings, hooks, etc. As can be seen in FIG. 2, these attachments **211** are attached to and supported by an underside of the third platform **301** (see below). The third platform **301** overhangs both the ground surface and the second platform **201**. The third platform **301** extends outward from the end **6** of the stack **3** beyond the second platform **201**. This allows the attachments **211** to be attached to the underside of the third platform **301** at locations such that when ropes are attached to respective attachments **211**, they may hang vertically from a height above the user's head height and toward the ground surface and may past the outer edge **202** of the platform **201** within a user's arm's reach. Preferably, the attachments **211** are located within 1 m, preferably less than or equal to 0.5 m, from the outer edge **202** of the platform **201** (when viewed from above).

(37) The attachments **211** are spaced (substantially equally) in a linear fashion on the underside of the third platform **301**. This line is parallel with the outer edge **202** of the second platform **201**. The attachments may be spaced by at least 0.2 m, preferably 0.3 m, preferably 0.4 m, preferably 0.5 m.

(38) As can be seen from the above description, the attachment **211** is supported by a platform **301** above the second platform **201**.

(39) Although shown in the first end of **33** of container **30**, the second platform assembly **200** could be located in the second end **34** of container **30**, the first end **23** of container **20** or the second end **24** of container **20**. It could be located in either end of any container that is not resting on the ground surface.

(40) There is another second platform assembly **200'** that is substantially identical to second platform assembly **200** (i.e. comprising all the features discussed above), but it is located at the other end **34** of the container **30**. In FIG. 1 this second platform assembly **200'** is shown in the retracted position.

(41) It should be understood that the second platform assembly/assemblies **200**, **200'** may additionally/alternatively be located in the second container **20**, or indeed any container that is not resting on the ground surface. There may be (only) one second platform assembly **200**, **200'** per end **6**, **7** of the stack **3**. There may (only) be a second platform assembly **200**, **200'** located at the first end **23** of the second container **20** and a second platform assembly **200**, **200'** located at the second end **24** of the second container **20**. There may (only) be a second platform assembly **200**, **200'** located at the first end **23** of the second container **20** and a second platform assembly **200**, **200'** located at the second end **34** of the third container **30**. There may (only) be a second platform assembly **200**, **200'** located at the first end **33** of the third container **20** and a second platform assembly **200**, **200'** located at the second end **24** of the second container **20**. There may (only) be a second platform assembly **200**, **200'** located at the first end **33** of the third container **20** and a second platform assembly **200**, **200'** located at the second end **34** of the third container **20**.

(42) The tower **1** comprises a third platform assembly **300**. The third platform assembly **300** is an

uppermost-level platform assembly. The third platform assembly **300** comprises a third platform **301**. The third platform **301** is an uppermost-level platform.

(43) The third platform **301** is at substantially the same height as the uppermost portion of the stack **3**, e.g. the roof **35** of the third/top container **30**. The third platform **301** extends laterally outward from the stack

(44) The third platform **301** overhangs the ground surface, and the second platform **201**. The third platform **301** is located at an end **6** of the stack **3**. The third platform **301** extends across substantially the entirety of the width of the stack **3**, i.e. from the first side **4** to the second side **5**. The third platform **301** is generally rectangular in shape and has an outer peripheral edge **302** that extends across substantially the entirety of the width of the stack **3** and is spaced from the first end **6** of the stack **3**. The third platform **301** has a length (i.e. the dimension of the third platform **301** in the direction perpendicular to the side walls **4**, **5** of the stack, which is perpendicular to the length dimension of the containers **10**, **20**, **30**) such that the outer edge **302** extends beyond the end **6** of the stack when view from above approximately equal to the width of the stack **3**, e.g. around 8' (2.4 m). The third platform **301** as a width (i.e. the distance that the outer edge **302** extends beyond the end **6** of the stack when view from above) of less than 3 m, preferably less than or approximately equal to 2 m, preferably greater than 1 m, preferably greater than 1.5 m. Thus, in the peripheral edge **302** is preferably less than 3 m, preferably less than or approximately equal to 2 m, preferably greater than 1 m, preferably greater than 1.5 m, from the end **6** of the stack **3**. The outer peripheral edge **302** of platform **301** extends beyond the outer peripheral edge **202** of platform **202**, preferably by at least 1 m, 1.5 m, or 2 m. This is preferable so that users using the second platform assembly **200** do not interfere with or interrupt using the third platform assembly **300**.

(45) At opposite ends of its outer edge **302**, two vertical members **303**, **304** extend upward from the third platform **301**. The vertical members **303**, **304** extend vertically from the platform **301** to a height of between 2-3 m, preferably at least around 2 m above the platform **301** (e.g. above head height of someone on the platform **301**). The tops of each of the vertical members **303**, **304** are attached to respective horizontal members **305**, **306** that extend perpendicular to the end wall **6** of the stack **3** and form part of an overhead framework **406** of the top tower assembly **400**. The tops of each of the vertical members **303**, **304** are connected together by a horizontal member **307** that extends parallel to the lateral end wall **6** of the stack **3** and parallel to the outer edge **302** of the platform **301**. The horizontal member **307** has generally the same length as the length of the outer edge **302** and is substantially directly vertically above the outer edge **302**.

(46) Extending horizontally and laterally (perpendicular to the end wall **6** of the stack **3**) outward from the tops of each of the vertical members **303**, **304** are respective horizontal members **308**, **309**. These may each extend less than 1 m, preferably less than 0.5 m, laterally of the platform edge **302**. Laterally outward ends the horizontal members **308**, **309** are connected to the respective vertical members **303**, **304** via respective off-vertical struts to provide support to the horizontal members **308**, **309**. The horizontal members **308**, **309** are connected by a horizontal beam **310** that extends parallel to the end wall **6** of the stack **3**. The height of the beam **310** is substantially the same as the height of the vertical members **303**, **304**. The height of the beam **310** is between 2-3 m, preferably at least around 2 m above the platform **301** (e.g. above head height of someone on the platform **301**). The beam **310** is located at the laterally outward peripheral ends of the horizontal members **308**, **309**. The beam **310** is less than 1 m, preferably less than 0.5 m, laterally of the platform edge **102**. The beam **310** has generally the same length as the length of the outer edge **302** of the third platform **301** and is parallel to the outer edge **302**.

(47) On the beam **310** is provided a plurality of attachment rings **311** for attaching a fast rope. The attachments **311** are spaced substantially equally along the beam, by at least 0.2 m, preferably 0.3 m, preferably 0.4 m, preferably 0.5 m.

(48) In the way described above, when ropes are attached to respective attachments **311** on the beam **310**, they may hang vertically from a height above the user's head height and toward the

ground surface and may pass the outer edge **302** of the platform **301** within a user's arm's reach. Further, as can be seen from the above description, the attachment **311** is supported by a frame **303**, **304**, **305**, **306**, **307**, **308**, **309**, **310**.

(49) The platform assembly **300** comprises a gate **312** for preventing and allowing access to the platform edge **302**. The gate **312** is located proximate, preferably immediately next to, the edge **302**. The gate **312**, when closed, extends parallel to and along the edge **302**. The gate **312** is (hingedly) attached to and supported by the vertical members **303**, **304** located at either end of the outer edge. The gate **312** is configured so that when it is opened access is provided to the edge **302** across substantially the entirety (or at least a majority) of the width of the edge **302**, and/or to only a (central) portion of the edge **302**. This may be achieved by having a three-fold gate as shown in FIG. 1.

(50) The third platform also comprises a hatch **313**. The hatch **313** may be attached to the remainder of the platform **301** via a hinge or hinges. The hatch **313** is located in toward the centre of the platform **301**. The hatch **313** allows rope to pass through the platform **301**, and allows the user to fast-rope through the platform. The hatch **313** has an area of at least 0.5 m^{sup.2}, preferably at least 1 m^{sup.2}. The hatch **313** is rectangular and has dimensions of around 0.5 m by 1 m, for example 0.6 m by 0.9 m. The hatch **313** overhangs the ground surface but does not overhang the second platform **201**—it is further laterally from the stack **3** than the outer edge **202** of the second platform **201**.

(51) The upper surface of the platform **301** comprises a plurality of attachments **314**. These attachments **314** are recessed in the surface so they do not protrude above the general plane of the surface of the platform **301**. The attachments **314** may be recessed swivel tie down rings. The attachments **314** are arranged around the hatch **313**. There may be at least 5, 10 or 15 attachments **314**.

(52) The third platform assembly **300** further comprises a first jettied deck **315**. The first jettied deck **315** extends horizontally from the platform **301** in a direction perpendicular to the side walls **4**, **5** of the stack **3** and parallel to the outer edge **302**. The jettied deck **315** extends from the platform **301** from between the stack **3** and the outer edge **302** of the platform. The first jettied deck **315** comprises an outer edge **316** distant from the platform **301**. The outer edge **316** extends horizontally in a direction perpendicular to the end walls **6**, **7** of the stack **3**. In this way, the outer edge **316** of the jettied deck **315** overhangs only the ground surface, i.e. it has lateral clearance to avoid overhanging the second platform **201**. The jettied deck **315** extends laterally from the platform **301**, and perpendicular to the plane of the first side wall **4** of the stack **3**, by at least 0.4 m, preferably 0.5 m. The jettied deck **315** is rectangular and may have a length of at least 1 m, but less than the width of the platform **301**, and may have a width of at least 0.4 m, preferably at least 0.5 m. The midpoint of the length of the jettied deck **315** may be approximately aligned with the midpoint of the width of the platform **301**. The midpoint of the length of the jettied deck **315** is around 1 m from the general plane of the first end **6** of the stack **3**. The upper surface of the jettied deck **315** is flush/continuous with the upper surface of the platform **301**.

(53) Attached to the outer edge **316** of the jettied deck **315** is a skid **317**. The skid **317** comprises a horizontal bar **318** running parallel with the adjacent edge **316** of the jettied deck **315**. The horizontal bar **318** is connected to the outer edge **316** by two parallel connecting members **319**. The connecting members **319** connect between the bar **318** and the outer edge **316**, preferably opposite ends of the outer edge **316**. The connecting members **319** are angled downward (at around 30-60° from the vertical) from the outer edge **316** such that the horizontal bar **318** is spaced laterally outward of the edge **316** and vertically downward from the edge **316**. Preferably the bar **318** extends parallel to the edge **316** along the entire length of the edge **316**, and is longer than the edge **316**. The horizontal bar **318** may be around 1-2 m long and maybe spaced 0.1-0.5 m laterally from the edge and may be spaced 0.3-1 m vertically from the upper surface of the jettied deck **315**. In this way, the horizontal bar **318** is positioned so a user can step down from the jettied deck **315** to

the bar **318** safely and in a manner that mimics a helicopter's skid.

(54) Beyond opposite ends of the outer edge **316** two vertical members **303**, **320** extend upward from the third platform **301**. One vertical member **303** extends from laterally outward of the jettied deck **315** and one vertical member **320** extends from laterally inward of the jettied deck **315**, with respect to the general plane of the first end **6** of the stack **3**. The vertical members **303**, **320** extend vertically from the platform **301** to a height of between 2-3 m, preferably at least around 2 m above the platform **301** (e.g. above head height of someone on the platform **301**). The tops of each of the vertical members **303**, **320** are attached to respective horizontal members **307**, **321** that extend parallel to the end wall **6** of the stack **3** and form part of an overhead framework **406** of the top tower assembly **400**. The tops of each of the vertical members **303**, **320** are connected together by a horizontal member **305** that extends perpendicular to the lateral end wall **6** of the stack **3** and parallel to the outer edge **316** of the jettied deck **315**. The horizontal member **305** has generally the same length as the width of the platform **301** (i.e. the distance the platform **301** overhangs the surface).

(55) Extending horizontally and laterally (parallel to the end wall **6** of the stack **3**) outward from the tops of each of the vertical members **303**, **304** are respective horizontal members **322**, **323**. These may each extend less than 1 m, preferably less than 0.5 m, laterally of the platform **301**. Preferably these extend the same distance from the platform as the jettied deck **315** does. Laterally outward ends the horizontal members **322**, **323** are connected to the respective vertical members **103**, **320** via respective off-vertical struts to provide support to the horizontal members **322**, **323**. The horizontal members **322**, **323** are connected by a horizontal beam **324** that extends perpendicular to the end wall **6** of the stack **3**. The height of the beam **324** is substantially the same as the height of the vertical members **303**, **320**. The height of the beam **324** is between 2-3 m, preferably at least around 2 m above the platform **301** (e.g. above head height of someone on the platform **301**). The beam **324** is located at the laterally outward peripheral ends of the horizontal members **322**, **323**. The beam **324** is directly vertically above the edge **316** of the jettied deck **315**, so that the horizontal bar **318** of the skid **317** extends laterally beyond the beam **324**. The beam **310** has generally the same length as the width of the third platform **301** and is parallel to the outer edge **316**.

(56) On the beam **324** is provided a plurality of attachment rings **325** for attaching a fast rope. The attachments **325** are spaced substantially equally along the beam, by at least 0.2 m, preferably 0.3 m, preferably 0.4 m, preferably 0.5 m.

(57) In the way described above, when ropes are attached to respective attachments **325** on the beam **324**, they may hang from a height above the user's head height in an off-vertical manner to the horizontal bar **318**. The ropes contact the bar **318** and then hang vertically downward toward the surface. This may mimic the situation in a helicopter. Alternatively, the beam **324** could be laterally spaced beyond the skid **317** so that a rope could hang vertically from the beam **324** past the skid **317** and on toward the ground.

(58) As can be seen from the above description, the attachment **325** is supported by a frame **303**, **320**, **321**, **306**, **322**, **323**, **324**.

(59) The platform assembly **300** comprises a (second) gate **326** for preventing and allowing access to the jettied deck **315**. The gate **326** is located proximate, preferably immediately next to, the jettied deck **315**. The gate **326**, when closed, extends parallel to the edge **316**. The gate **326** is attached to and supported by the vertical members **303**, **320** via fixed balustrade portions. The gate **326** is hinged to said balustrade. The gate **326** is configured so that when it is opened access is provided to the jettied deck **315** across substantially the entirety (or at least a majority) of the length of the jettied deck **315**.

(60) The jettied deck **315**, skid **317** and/or frame discussed above may be located on the side of the platform **301** nearest the first external side wall **4** of the stack **3** (the first side of the platform **301**), and/or may be located on the side of the platform **301** nearest the second external side wall **5** of the

stack **3** (the second side of the platform **301**). Two such jettied decks **315**, skids **317** and frames etc. (as described above) may be provided by the platform assembly **300**.

(61) The platform assembly **300** may comprise two rails **327** running across the width of the platform **301**. The rails **327** are at least 1.5 m, 1.75 m, 2 m above the platform **301**, such that they are above head height of a user standing on the platform **301**. The rails **327** are parallel with each other and are perpendicular to the general plane of the end **6** of the stack **3**. The rails **327** are horizontal. The rails **327** are attached to horizontal members **307**, **321** and run perpendicular to horizontal members **307**, **321**.

(62) The rails **327** are configured such that a user can anchor themselves to one or both of the rails, as a safety means. The point at which the user is anchored to the rails **327** may move/slide along the rail **327**. Two rails **327** are preferable as it allows multiple users to use the multiple edges **302**, **316** for fast-roping simultaneously.

(63) The tower **1** may comprise another third platform assembly **300'** comprising some or all of the features discussed above in relation to the third platform assembly **300**. This third platform assembly **300'** may be at the opposite end **7** of the stack compared to the end **6** at which the third platform assembly **300** is.

(64) The tower **1** further comprises a top training apparatus assembly **400**. The top training apparatus assembly **400** is a top tower assembly **400**. The top tower assembly **400** is arranged on the uppermost portion of the stack **3**, i.e. the roof **35** of the third container **30**. The top tower assembly **400** comprises a first portion **401** that overlaps with the stack **3**, a second portion **402** that overhangs the surface thus forming the third platform assembly/assemblies **300**, **300'**.

(65) The top tower assembly **400** comprises a floor portion **404**, a first portion of which at least partially overlaps with the stack **3** and a second portion of which overhangs the surface thus forming the at least one platform **301**. The floor portion **404** has a width substantially identical to the width of the stack **3**, e.g. around 8' (2.4 m). The length of the floor portion **404** is longer than the length of the stack **3**, thus allowing the second portion **402** to overhang the ground surface. The second portion of the floor portion **404** is the platform(s) **301** (and the jettied deck(s) **315**). Thus the upper surface of the platform(s) **301** are flush and continuous with the floor of the remainder of the floor portion **404**.

(66) The top tower assembly **400** comprises a balustrade **405** around its periphery.

(67) The top tower assembly **400** comprises a frame **406**. The frame **406** is constructed of vertical members **407** extending from the periphery of the floor portion **404** at evenly spaced intervals. The vertical members **407** are connected together by horizontal members **408**, some of which extend across the width of the stack **3** and some of which extend in a direction parallel to the length of the stack **3**. The vertical members **407** and the horizontal members **408** are arranged such that the horizontal members are at least 1.5, 1.75 or 2 m above the floor portion **404**. This allows the horizontal parts of the frame **406** to be above head height.

(68) The third platform assembly/assemblies **300**, **300'** is/are an integral part of the top tower assembly **400**. The third platform(s) **301**, and the jettied deck(s) **315**, are integral parts of the floor portion **404** of the top tower assembly **400**. The vertical members **407** comprise vertical members **303**, **304** **320**. Horizontal members **408** comprise horizontal members **305**, **306**, **307**, **321**. Further, the rails **327** are part of the top tower assembly **400**, and extend along substantially the entire length of the top tower assembly **400** (e.g. from one platform assembly **300** to the other **300'**).

(69) As an aside, as shown in the Figures, the horizontal members **408**, **305**, **306**, **307**, **321** may have a construction comprising two (vertically) spaced horizontal beams connected by angled truss members. This provides a strong horizontal member. This collection of beams and trusses are referred to as a "horizontal member" as they rigidly joined and generally extend horizontally.

(70) The top tower assembly **400** is a pre-fabricated module, which is placed on top of and attached to the stack **3** of containers **10**, **20**, **30**.

(71) The tower **1** comprises a roof **409**. The roof **409** is a cover. The roof **409** substantially covers

the remainder of the tower **1**. The roof **409** extends substantially across the length and width of the tower **1** (e.g. the length and width of the top tower assembly **400**). The roof **409** is connected to the upper side of the frame **406** of the top tower assembly **400**. (Each of) the horizontal beams **408** extending across the width of top tower assembly may be attached to a respective vertical member **410** extending vertically upward from the midpoint of the horizontal beams **408**. The roof **409** is supported along the centre-line of the width of the top tower assembly **400** by the top of these vertical members **410**. The roof **409** slopes downward toward the periphery of the frame **408**. Preferably, each of the vertical members **407** may have a respective horizontal member **411** attached thereto and extending outwardly in a direction perpendicular to the general plane of the side walls **4, 5** of the stack **3** so as to overhang the ground surface. These horizontal members **407** include horizontal members **322, 323**. The roof **409** is attached to the outer periphery of the horizontal members **407**, to increase coverage of the tower **1**. The roof **409** is made from a flexible waterproof material such as waterproof cloth or plastic sheeting.

(72) The tower **1** comprises a ladder **500** extending vertically from near the ground surface to the top tower assembly **400**, for providing access to the top tower assembly **400**. The ladder **500** is positioned on the first side wall **4** of the stack **3**, and is positioned close enough to the first platform assembly **100** to allow a user to access the first platform **101** using the ladder **500**. The ladder comprises a cage **501** for protecting the user climbing the ladder **500**. The cage **501** may be attached to the ladder **500** and may extend from the top of the ladder **500** to a location higher than the first platform **101**. The ladder **500** provides a path for the user to reach the first platform **101** and the third platform(s) **301**.

(73) The top of the ladder **500** may be adjacent to a portion of the top tower assembly **400** where the balustrade **405** is interrupted. There is a gate **502** here to prevent and allow access to the top of the ladder **500**. The gate **502** can extend across the interruption of the balustrade **405**. The gate **502** is hinged to the balustrade **405**.

(74) The tower **1** comprises a climbing wall **503**. The climbing wall **503** is a facade that is attached to the second side wall **5** of the stack **3**. The climbing wall **503** extends from the ground surface to the top of the stack **3**. The climbing wall **503** extends along substantially the entirety of the length of the stack **3**, i.e. from one end **6, 7** to the other **7, 6** of the stack **3**. The climbing wall **503** comprises a plurality of hand/foot holds **504**. The climbing wall **503** provides a path for the user to reach the second platform(s) **201** and the third platform(s) **301**. The climbing wall **503** is constructed from a plurality of panels **505**. The panels **505** are pre-fabricated and are arranged to form a complete climbing wall **503** when attached to the stack **3** and/or each other.

(75) The tower **1** comprises an internal climbing path. The lowermost container **10** comprises a door **506** that provides and prevents access into the stack **3**. The door **506** is a door as readily found on ISO containers. Inside each of the containers **10, 20, 30** is stair case (or set of steps) **507** connecting, and allowing access between: the floor **16** of the first container **10** and the floor **26** of the second container **20** (through the roof **15** of the first container **10**); the floor **26** of the second container **20** and the floor **36** of the third container **30** (through the roof **25** of the second container **20**); and the floor **36** of the third container **30** and the floor **404** of the top tower assembly **400** (through the roof **35** of the third container). There is a set of steps **507** associated with each container **10, 20, 30**.

(76) FIGS. **1** to **6** show different views of this same embodiment. FIGS. **7-8** show a very similar embodiment, identical in every way except that the tower does not have the roof **400** or horizontal members **411** or vertical members **410**, or the climbing wall **503**.

(77) FIGS. **10** to **12** show another embodiment of a tower **1001** according to the present disclosure. Except where discussed below, the tower **1001** is identical or at least largely similar to the tower **1**.

(78) Thus, the tower **1001** comprises a stack **1003** of ISO shipping containers **1010, 1020, 1030, 1040, 1050, 1060** and a plurality of platform assemblies **1100, 1200, 1300** configured for use in fast-rope training.

(79) However, whereas the stack 3 of tower 1 was made by stacking single containers 10, 20, 30 one on top of the other, the tower 1001 is made of layers of containers 1010, 1020, 1030, 1040, 1050, 1060. Each layer comprises two containers 1010, 1020, 1030, 1040, 1050, 1060. The shipping containers 1010, 1020, 1030, 1040, 1050, 1060 of each layer are attached to each other such that respective side walls of the containers are adjacent each other (such that they face each other) and such that respective end walls 1013, 1023, 1033, 1043, 1053, 1063 are in line with each other. The respective shipping containers 1010, 1020, 1030, 1040, 1050, 1060 of a given layer are arranged horizontally with respect to each other. All the layers are made in a similar way, and are stacked on top of each other such that the side walls and the end walls of the containers 1010, 1020, 1030, 1040, 1050, 1060 form a vertical wall of the stack 1003. This forms a stack 1003 that has a width substantially equal to twice the width of an individual container, and a length substantially equal to the length of an individual container.

(80) The stack 1003 may equally be thought of as two columns of containers 1010, 1020, 1030, 1040, 1050, 1060 placed adjacent each other such that the side walls of the respective containers 1010, 1020, 1030, 1040, 1050, 1060 are adjacent each other and such that the end walls are aligned.

(81) The stack 3 is made of three layers of the shipping containers 1010, 1020, 1030, 1040, 1050, 1060 stacked vertically on top of one another. The containers are stacked such that the floor of the containers 1020, 1030, 1050, 1060 of an upper layer container rests and may be attached to the roof of the lower containers 1010, 1020, 1040, 1050; and such that lateral walls of the containers 1010, 1020, 1030, 1040, 1050, 1060 in a given column are in the same general planes; and the end walls of the containers are in the same general planes. In this way, the containers 1010, 1020, 1030, 1040, 1050, 1060 of a given column are stacked in an aligned arrangement, such that their peripheral walls and ends are aligned with each other.

(82) A first layer is arranged on the ground surface (not shown). A second layer is arranged on the first layer. A third layer is arranged on the second layer.

(83) The aligned lateral side walls of containers 1010, 1020, 1030 thus generally form a first lateral side wall 1004 of the stack 1003. The aligned lateral side walls of containers 1040, 1050, 1060 thus generally form a second lateral side wall 1005 of the stack 1003. The aligned ends of the containers 1010, 1020, 1030, 1040, 1050, 1060 thus generally form a first end 1006 and a second end 1007 of the stack 1003. The aligned second ends 14, 24, 34 thus generally form a second end 7 of the stack.

(84) The tower 1 comprises a first platform assembly 1100. The first platform assembly 1100 is an external wall 1005 platform assembly. The first platform assembly 1100 comprises a first platform 1101 that is attached to an external side wall of container 1040. The first platform 1101 is an external wall platform. The first platform 1101 extends horizontally outward from the external side wall of the stack 1003. The first platform 1101 overhangs the ground surface. The first platform 1101 is general rectangular and has horizontal width (i.e. the distance it extends from the stack 1003) of around 1-3 m (preferably 2-2.5 m), and a horizontal length (i.e. the distance it runs parallel to the length of the stack/containers) substantially equal to the stack/containers. The first platform 1101 is between 1-3 m above the ground surface. The first platform 1101 comprises an outer edge 1102 that is horizontal and runs parallel to the external wall of the stack. The outer edge 1102 is the laterally outermost edge of the platform 1101 when viewed from above.

(85) At the outermost edge 1102, the platform 1101 is supported by a plurality of vertical members 1103 that extend to the ground surface and contact the ground via ground engaging plates. The tops of each of the vertical members 103, 104 are attached to respective horizontal members 1105 the external wall 1005 of the stack 1003 and attach to the lateral side wall of the container 1040.

(86) Between the outermost edge 1102 and the ground, there extends a vertical wall 1108. This may be used as a climbing or abseiling wall. This wall 1108 is supported by the vertical members 1103.

(87) The tower 1001 comprises a second platform assembly 1200. This is substantially identical to the second platform assembly 200 except that there are essentially two platform assemblies 200 next to each other, one in the end wall 1033 of a first upper container 1030 and one in the end wall

of a second upper container **1060** adjacent to the first upper container (both said containers being in the same layer). The two platforms **201** next to each other effectively form one larger platform.

(88) There may be another second platform assembly, which is substantially identical to second platform assembly **1200**, located at the other end of the container stack **1003**. However, in the embodiment of FIGS. **10-12**, at the other end of the stack **1003**, there is instead a climbing wall **1600**. The climbing wall **1600** is non-vertical and extends from the ground surface to the floor of the upper layer (the floor of upper containers **1030**, **1060**). The wall **1600** has a width such that it extends across the width of the stack **1003**. The ends of the containers **1030**, **1060** proximate the wall **1600** each comprise respective doors **1206** for accessing the wall **1600** (substantially identical to door **206**) and gates **1207** for accessing the wall **1600** (substantially identical to the gate **1207**). The tower **1001** may comprise ropes for climbing up or abseiling down the wall **1600**.

(89) It should be understood that the second platform assembly/assemblies **1200** and/or the wall **1600** may additionally/alternatively be located in the second layer containers **1020**, **1050**, or indeed any container that is not resting on the ground surface.

(90) The tower **1001** comprises a third platform assembly **1300**. The third platform assembly **1300** is substantially identical to the third platform assembly **300** except that it extends across the width of two containers in the stack **1003** (i.e. it is wider). Further, it may comprise two hatches **1313**, and may comprise an additional gate **1312**. The outer peripheral edge **1302** of the third platform assembly **1300** is approximately twice the width of edge **302**, i.e. it extends substantially across the width of the stack **1003**. As is explained below in more detail, the third platform assembly **1300** is formed of two symmetrical portions that are fixed to each other. The horizontal beam **1324** is supported by angled (between horizontal and vertical) members **1470** that are in turn supported by vertical members **1407**, **1412** as discussed below.

(91) The tower **1001** further comprises a top tower assembly **1400**. The top tower assembly **1400** is substantially identical to the top tower assembly **400** except that it extends across the width of two containers in the stack **1003** (i.e. it is wider). Further, the top tower assembly **1400** forms only one third platform assembly **1300**, instead of two third platform assemblies **300**, **300'**. Further, the top tower assembly **1400** is constructed of two portions **1450**, **1460**, which are substantially symmetrical. The two portions have a width substantially equal to the width of a container **1010**, **1020**, **1030**, **1040**, **1050**, **1060**, and length greater than the length of a container **1010**, **1020**, **1030**, **1040**, **1050**, **1060**. The two portions **1450**, **1460** are attached to one another along their length to form the top tower assembly **1400**.

(92) The first portion **1401** overlaps with the stack **1003** and the second portion **1402** overhangs the ground surface thus forming the third platform assembly **1300**. There may be no overhang of the floor portion **1404** over the wall **1600**, as there may not be a third platform assembly above the wall **1600**.

(93) The frame **1406** is constructed of vertical members **1407** extending from the periphery of the floor portion **1404** and vertical members **1412** at the centre line of the floor portion **1404** (i.e. at the location where the two portions **1450** and **1460** meet, e.g. directly above where side walls of the containers **1010**, **1020**, **1030**, **1040**, **1050**, **1060** meet). The vertical members **1412** are longer than the vertical members **1407**. Connecting the tops the vertical members **1412** to respective vertical members **1407** are angled members **1470**. The angled members **1470** extend at an angle between the vertical and the horizontal and in a direction parallel to the width of the stack **1003**. The angled members **1470** extend beyond the side walls **1004**, **1005** of the stack **1003**.

(94) The two portions **1450**, **1460** are pre-fabricated modules, which are attached together and placed on top of and attached to the stack **1003**.

(95) The roof **1409** is supported by the angled members **1470**. The roof **1409** is made of a rigid material, such as corrugated plastic or metal. The roof **1409** extends beyond the side walls **1004**, **1005** of the stack **1003**, covers the third platform assembly **1300** and overhangs the wall **1600**.

(96) On the inside of the stack **1003**, the containers **1010**, **1020**, **1030**, **1040**, **1050**, **1060** may

comprise openings in their walls/roofs/floors to allow users to move between the containers of the stack **1003** as desired.

(97) FIGS. **13** to **14** show another embodiment of a tower **2001** according to the present disclosure. Except where discussed below, the tower **2001** is identical or at least largely similar to the tower **1001**.

(98) The tower **2001** comprises two third platform assemblies **1300** and two second platform assemblies **1200**, one of each being located on each of the ends **1006**, **1007** of the stack **1003**. There is no wall **1600** or first platform assembly **1100**. However, the tower **2001** comprises a staircase **2500** extending from the ground surface to the top tower assembly **1400**, for providing access to the top tower assembly **1400**. The staircase **2500** is a spiral staircase. The stack **1003** comprises doors **2501** in the side wall **1004** of the stack **1003**. The doors **2501** and the staircase **2500** are arranged such that the staircase **2500** provides access to the doors **2501**. Each of the containers **1010**, **1020**, **1030** that make up the side wall **1004** comprises a door **2501**. Each door **2501** provides access through the side wall of a given container **1010**, **1020**, **1030**.

(99) The skilled person would immediately appreciate that different combinations of the above-discussed features are possible without departing from the scope of the disclosure. Whilst there may be particularly preferable combinations of features, any combination of ladders, stairs, climbing walls, ropes, platforms, containers, top tower assemblies may be used.

Claims

1. A fast-rope training apparatus comprising: a platform-supporting structure comprising one or more containers; at least one platform configured for use in fast-rope training; wherein the at least one platform comprises at least one hatch; and at least one attachment for attaching a fast-rope, wherein the platform-supporting structure is supportable by a surface, wherein the at least one platform extends outward from the platform-supporting structure such that the at least one platform overhangs the surface to define an overhanging portion, the at least one hatch being provided in the overhanging portion, and wherein the at least one attachment is located higher than the at least one platform and spaced laterally from the platform-supporting structure such that the at least one attachment overhangs the surface so a fast-rope can hang from the at least one attachment and pass through the at least one hatch in the at least one platform and toward the surface.
2. The training apparatus as claimed in claim 1, further comprising a further attachment for attaching a fast rope, wherein the further attachment is located higher than the at least one platform and is spaced laterally from the platform-supporting structure such that the at least one attachment overhangs the surface so a further fast-rope can hang from the at least one further attachment, past the at least one platform and toward the surface.
3. The training apparatus as claimed in claim 1, wherein the platform-supporting structure comprises a plurality of containers.
4. The training apparatus as claimed in claim 1, wherein the one or more containers is/are pre-fabricated container(s).
5. The training apparatus as claimed in claim 1, wherein the training apparatus is free-standing.
6. The training apparatus as claimed in claim 1, wherein the platform-supporting structure comprises an uppermost portion, and the at least one platform comprises an uppermost portion-level platform at substantially the same height as the uppermost portion.
7. The training apparatus as claimed in claim 1, wherein at least one of the one or more containers comprises a floor, and the at least one platform comprises a floor-level platform at substantially the same height as said floor.
8. The training apparatus as claimed in claim 1, wherein the platform-supporting structure comprises an external wall, and the at least one platform comprises an external wall platform that is attached to and supported by the external wall.

9. The training apparatus as claimed in claim 1, wherein the at least one platform comprises at least one skid.
 10. The training apparatus as claimed in claim 1, further comprising a gate configured to optionally block a user's pathway to the at least one platform or to an edge of the at least one platform.
 11. The training apparatus as claimed in claim 1, further comprising an anchor device for securing a user to the training apparatus in order to prevent the user falling from the at least one platform.
 12. The training apparatus as claimed in claim 11, wherein the anchor device is located above the at least one platform.
 13. The training apparatus as claimed in claim 1, further comprising climbing equipment for accessing the at least one platform.
 14. The training apparatus as claimed in claim 13, wherein the climbing equipment comprises a climbing wall.
 15. The training apparatus as claimed in claim 1, wherein the platform-supporting structure comprises an uppermost portion and the training apparatus further comprises a top training apparatus assembly arranged on the uppermost portion of the platform-supporting structure and comprising a first portion that at least partially overlaps with the platform-supporting structure and a second portion that overhangs the surface thus forming the at least one platform.
 16. The training apparatus as claimed in claim 1, wherein the platform-supporting structure has a width substantially equal to the width of a single one of said one or more containers.
 17. The training apparatus as claimed in claim 1, wherein the platform-supporting structure has a width greater than the width of a single one of said one or more containers.
 18. A fast-rope training apparatus comprising: a platform-supporting structure; at least one platform configured for use in fast-rope training, wherein the at least one platform comprises at least one hatch; and at least one attachment for attaching a fast-rope, wherein the platform-supporting structure is supportable by a surface, the platform-supporting structure having a vertical wall below the at least one platform, wherein the at least one platform extends outward from the platform-supporting structure such that the at least one platform overhangs the surface to define an overhanging portion, the at least one hatch being provided in the overhanging portion, and wherein the at least one attachment is located higher than the at least one platform and spaced laterally from the platform-supporting structure such that the at least one attachment overhangs the surface so a fast-rope can hang from the at least one attachment and pass through the at least one hatch in the at least one platform and toward the surface.
 19. The fast-rope training apparatus as claimed in claim 18, wherein the at least one hatch is hinged to a remainder of the at least one platform.
 20. The fast-rope training apparatus as claimed in claim 18, wherein the at least one platform comprises a plurality of hatches for fast-rope training.
-