

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12411355
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Son; Ju Hwa

Camera module having specified relative radius of curvature of lens surfaces

Abstract

A camera module includes: an optical imaging system including a frontmost lens disposed closest to an object side, a rearmost lens disposed closest to an imaging plane, and at least one middle lens disposed between the frontmost lens and the rearmost lens. An image-side surface of the rearmost lens is concave and an inflection point is formed on the image-side surface of the rearmost lens. $0.2 < D/TTL$ is satisfied, D being a shortest distance between the rearmost lens and the imaging plane, and TTL being a distance from an object-side surface of the frontmost lens to the imaging plane.

Inventors:	Son; Ju Hwa (Suwon-si, KR)
Applicant:	Samsung Electro-Mechanics Co., Ltd. (Suwon-si, KR)
Family ID:	58720889
Assignee:	Samsung Electro-Mechanics Co., Ltd. (Suwon-si, KR)
Appl. No.:	18/467948
Filed:	September 15, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240004213 A1	Jan. 04, 2024

Foreign Application Priority Data

KR	10-2015-0164238	Nov. 23, 2015
----	-----------------	---------------

Related U.S. Application Data

continuation parent-doc US 18110520 20230216 US 11860381 child-doc US 18467948
continuation parent-doc US 16801488 20200226 US 11609435 20230321 child-doc US 18110520
continuation parent-doc US 15184264 20160616 US 10613343 20200407 child-doc US 16801488

Publication Classification

Int. Cl.: **G02B7/08** (20210101); **G02B9/60** (20060101); **G02B13/00** (20060101); **G02B15/14** (20060101); **G02B27/64** (20060101)

U.S. Cl.:

CPC **G02B27/646** (20130101); **G02B7/08** (20130101); **G02B9/60** (20130101); **G02B13/0045** (20130101); **G02B15/145** (20190801); **G02B15/1451** (20190801); **G02B15/145121** (20190801)

Field of Classification Search

CPC: G02B (9/60); G02B (13/0045); G02B (15/145)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7126760	12/2005	Yamada	N/A	N/A
8456758	12/2012	Huang et al.	N/A	N/A
8705181	12/2013	Hsu et al.	N/A	N/A
8879166	12/2013	Tsai et al.	N/A	N/A
9091801	12/2014	Huang	N/A	N/A
9348117	12/2015	Chang et al.	N/A	N/A
9798116	12/2016	Hashimoto	N/A	N/A
10613343	12/2019	Son	N/A	N/A
2006/0072200	12/2005	Yamada	N/A	N/A
2011/0134305	12/2010	Sano et al.	N/A	N/A
2012/0087019	12/2011	Tang et al.	N/A	N/A
2013/0033762	12/2012	Tsai et al.	N/A	N/A
2013/0107375	12/2012	Huang et al.	N/A	N/A
2013/0176631	12/2012	Tsai et al.	N/A	N/A
2013/0182336	12/2012	Hsu et al.	N/A	N/A
2013/0329292	12/2012	Wu	N/A	N/A
2014/0313596	12/2013	Hashimoto	N/A	N/A
2015/0022714	12/2014	Huang	348/360	G02B 13/0045
2015/0085385	12/2014	Tanaka et al.	N/A	N/A
2015/0103414	12/2014	Baik	N/A	N/A
2015/0168695	12/2014	Tsai et al.	N/A	N/A
2015/0177483	12/2014	You	N/A	N/A
2015/0185436	12/2014	Park	N/A	N/A
2015/0185445	12/2014	Ahn et al.	N/A	N/A

2015/0241660	12/2014	Son	N/A	N/A
2015/0241661	12/2014	Shih et al.	N/A	N/A
2015/0260951	12/2014	Yu	N/A	N/A
2015/0301314	12/2014	Chen et al.	N/A	N/A
2015/0323765	12/2014	Hashimoto	N/A	N/A
2016/0223792	12/2015	Tang et al.	N/A	N/A
2016/0238817	12/2015	Liu et al.	N/A	N/A
2017/0023775	12/2016	Shigemitsu	N/A	N/A
2017/0031134	12/2016	Liu et al.	N/A	N/A
2017/0052346	12/2016	Tang et al.	N/A	N/A
2017/0082835	12/2016	Tang et al.	N/A	N/A
2017/0285303	12/2016	Lai et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1332232	12/2006	CN	N/A
101782676	12/2009	CN	N/A
202494826	12/2011	CN	N/A
202583582	12/2011	CN	N/A
103076665	12/2012	CN	N/A
103389568	12/2012	CN	N/A
103777323	12/2013	CN	N/A
103837962	12/2013	CN	N/A
104749751	12/2014	CN	N/A
104765129	12/2014	CN	N/A
204536635	12/2014	CN	N/A
104880804	12/2014	CN	N/A
104914559	12/2014	CN	N/A
2014-178623	12/2013	JP	N/A
2014-211586	12/2013	JP	N/A
2015-60170	12/2014	JP	N/A
10-2005-0035541	12/2004	KR	N/A
10-2010-0001525	12/2009	KR	N/A
10-2015-0043186	12/2014	KR	N/A
10-2015-0072154	12/2014	KR	N/A
201215942	12/2011	TW	N/A
201534961	12/2014	TW	N/A

OTHER PUBLICATIONS

Korean Office Action issued Dec. 21, 2016, in counterpart Korean Application No. 10-2015-0164238 (10 pages in English, 6 pages in Korean). cited by applicant

Taiwanese Office Action issued on May 8, 2017 in corresponding Taiwanese Patent Application No. 105119358 (5 pages in English and 5 pages in Taiwanese). cited by applicant

Korean Office Action issued on Aug. 28, 2017 in corresponding Korean Patent Application No. 10-2015-0164238 (7 pages in English and 4 pages in Korean). cited by applicant

Chinese Office Action issued on Nov. 22, 2018 in Chinese Patent Application No. 201610536779.8 (7 pages in English, 7 pages in Chinese). cited by applicant

Chinese Office Action issued on Jun. 11, 2019 in corresponding Chinese Patent Application No. 201610536779.8 (14 pages in English, 9 pages in Chinese). cited by applicant

Chinese Office Action issued on Mar. 24, 2021 in counterpart Chinese Patent Application No.

201911125342.5 (10 pages in English and 11 pages in Chinese). cited by applicant
Korean Office Action Issued on May 3, 2021, in Counterpart Korean Application No. 10-2018-0015684 (6 pages in English and 4 pages in Korean). cited by applicant
Notice of Reason for Rejection issued on Oct. 27, 2021, in counterpart Korean Patent Application No. 10-2021-0134900 (6 pages in English and 4 pages in Korean). cited by applicant
Korean Office Action issued on Jul. 26, 2022, in counterpart Korean Patent Application No. 10-2022-0083559 (6 pages in English and 4 pages in Korean). cited by applicant

Primary Examiner: Dunning; Ryan S

Attorney, Agent or Firm: NSIP Law

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 18/110,520 filed on Feb. 16, 2023, now U.S. Pat. No. 11,860,381 issued on Jan. 2, 2024, which is a continuation of U.S. patent application Ser. No. 16/801,488 filed on Feb. 26, 2020, now U.S. Pat. No. 11,609,435, which is a continuation of U.S. patent application Ser. No. 15/184,264 filed on Jun. 16, 2016, now U.S. Pat. No. 10,613,343, which claims the benefit under 35 USC 119 (a) of Korean Patent Application No. 10-2015-0164238 filed on Nov. 23, 2015, in the Korean Intellectual Property Office, the entire disclosures of which are incorporated herein by reference for all purposes.

BACKGROUND

1. Field

(1) The following description relates to a camera module having a hand-shake compensation function.

2. Description of Related Art

(2) Functions of a camera module for a portable terminal have been gradually improved. For example, the camera module includes an optical imaging system composed of multiple lenses in order to capture high resolution images. In addition, the camera module includes a hand-shake compensation unit that is operable to prevent an image quality deterioration phenomenon due to vibrations.

(3) Camera modules have been gradually miniaturized in accordance with the thinning of portable terminals. However, the miniaturization of optical imaging systems may cause problems such as a decrease in available mounting space in the hand-shake compensation unit, and a decrease in movement space of the optical imaging system by the hand-shake compensation unit.

(4) Therefore, a camera module capable of being miniaturized and allowing sufficient space for a hand-shake compensation unit to be secured therein is desirable.

SUMMARY

(5) This Summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used as an aid in determining the scope of the claimed subject matter.

(6) According to one general aspect, a camera module includes: an optical imaging system including a frontmost lens disposed closest to an object side, a rearmost lens disposed closest to an imaging plane, and at least one middle lens disposed between the frontmost lens and the rearmost lens. An image-side surface of the rearmost lens is concave and an inflection point is formed on the image-side surface of the rearmost lens. $0.2 < D/TTL$ is satisfied, D being a shortest distance

between the rearmost lens and the imaging plane, and TTL being a distance from an object-side surface of the frontmost lens to the imaging plane.

(7) The at least one middle lens may include three lenses.

(8) The camera module may further include a hand-shake compensation unit configured to move the optical imaging system in a direction intersecting an optical axis of the optical imaging system.

(9) The camera module may further include an auto-focusing unit configured to move the optical imaging system in an optical axis direction of the optical imaging system.

(10) D may be greater than 0.9 mm.

(11) $TTL/ImgH < 0.7$ may be satisfied, ImgH being a diagonal length of the imaging plane. $75^\circ < FOV$ may be satisfied, FOV being a field of view of the optical imaging system.

(12) According to another general aspect, a camera module includes: an optical imaging system including lenses, each of the lenses having a refractive power; and an imaging plane on which an image of light refracted by the optical imaging system is formed. $0.8\text{ mm} < D$ is satisfied, where D is a shortest distance between an image-side surface of a fifth lens of the lenses and the imaging plane. $TTL/ImgH < 0.7$ is satisfied, where TTL is a distance from an object-side surface of a first lens of the lenses to the imaging plane, and ImgH is a diagonal length of the imaging plane. The first lens is closest to the object side and the fifth lens is closest to the imaging plane.

(13) The lenses comprise the first lens comprises a positive refractive power, a second lens having a negative refractive power, a third lens having a positive refractive power, a fourth lens having a negative refractive power, and the fifth lens having a positive refractive power, the first to fifth lenses being sequentially disposed from an object side to the imaging plane.

(14) The object-side surface of the first lens may be convex.

(15) An object-side surface of the third lens may be concave.

(16) An object-side surface of the fourth lens and an image-side surface of the fourth lens may be concave.

(17) The image-side surface of the fifth lens may be concave and an inflection point may be formed on the image-side surface of the fifth lens.

(18) $0.24 < D/f$ may be satisfied, f being an overall focal length of the optical imaging system.

(19) $TTL < 4.25\text{ mm}$ may be satisfied.

(20) An F number of the optical imaging system may be 2.10 or less.

(21) $TTL/ImgH < 0.68$ may be satisfied.

(22) According to another general aspect, a camera module includes: an optical imaging system including a frontmost lens having a positive refractive power, a rearmost lens having a positive refractive power, and middle lenses disposed between the frontmost lens and the rearmost lens; and an imaging plane on which an image of light refracted by the optical imaging system is formed, the imaging plane being positioned rearward of the rearmost lens. $TTL/ImgH$ is less than 0.7, TTL being a distance from an object-side surface of the frontmost lens to the imaging plane, and ImgH being a diagonal length of the imaging plane. D/f is greater than 0.24, D being a shortest distance between an image-side surface of the rearmost lens and the imaging plane, and f being an overall focal length of the optical imaging system.

(23) The middle lenses may include three lenses. One or more of the three lenses may have negative refractive power.

(24) D/TTL may be greater than 0.2.

(25) D may be greater than 0.8 mm.

(26) According to another general aspect, a camera module includes: an optical imaging system including a first lens positioned closest to an object side of the optical image system, and a last lens positioned closest to an image side of the optical imaging system; and an imaging plane on which an image of light refracted by the optical imaging system is formed. D/f is greater than 0.24, D being a shortest distance between an image-side surface of the last lens and the imaging plane, and f being an overall focal length of the optical imaging system. TTL is less than 4.25 mm, TTL being

a distance from an object-side surface of the first lens to the imaging plane.

(27) The optical imaging system may further include: a second lens having a negative refractive power; a third lens having a positive refractive power; and a fourth lens having a negative refractive power, wherein the first lens, the second lens, the third lens, the fourth lens and the last lens are sequentially arranged from the object side to the imaging plane.

(28) The image-side surface of the last lens may be concave and may include an inflection point.

(29) The object-side surface of the first lens may be convex. An object-side surface of the second lens may be convex. An object-side surface of the third lens may be concave. An image-side surface and an object-side surface of the fourth lens may be concave.

(30) Other features and aspects will be apparent from the following detailed description, the drawings, and the claims.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a view of an optical imaging system of a camera module, according to an embodiment.

(2) FIG. 2 includes graphs having curves representing aberration characteristics of the optical imaging system illustrated in FIG. 1, according to an embodiment.

(3) FIG. 3 is a graph representing a modulation transfer function (MTF) of the optical imaging system illustrated in FIG. 1, according to an embodiment.

(4) FIG. 4 is a table illustrating respective characteristics of lenses of the optical imaging system illustrated in FIG. 1, according to an embodiment.

(5) FIG. 5 is a table illustrating respective aspherical surface coefficients of lenses of the optical imaging system illustrated in FIG. 1, according to an embodiment.

(6) FIG. 6 is a view of an optical imaging system of a camera module, according to another embodiment.

(7) FIG. 7 includes graphs having curves representing aberration characteristics of the optical imaging system illustrated in FIG. 6, according to an embodiment.

(8) FIG. 8 is a graph representing a modulation transfer function (MTF) of the optical imaging system illustrated in FIG. 6, according to an embodiment.

(9) FIG. 9 is a table illustrating respective characteristics of lenses of the optical imaging system illustrated in FIG. 6, according to an embodiment.

(10) FIG. 10 is a table illustrating respective aspherical surface coefficients of lenses of the optical imaging system illustrated in FIG. 6, according to an embodiment.

(11) FIG. 11 is a view of an optical imaging system of a camera module, according to another embodiment.

(12) FIG. 12 includes graphs having curves representing aberration characteristics of the optical imaging system illustrated in FIG. 11, according to an embodiment.

(13) FIG. 13 is a graph representing a modulation transfer function (MTF) of the optical imaging system illustrated in FIG. 11, according to an embodiment.

(14) FIG. 14 is a table illustrating respective characteristics of lenses of the optical imaging system illustrated in FIG. 11, according to an embodiment.

(15) FIG. 15 is a table illustrating respective aspherical surface coefficients of lenses of the optical imaging system illustrated in FIG. 11, according to an embodiment.

(16) FIG. 16 is a partially enlarged cross-sectional view of the camera module of FIG. 1, according to an embodiment.

(17) FIG. 17 is a cross-sectional view of the camera module of FIG. 16, taken along line I-I of FIG. 16.

DETAILED DESCRIPTION

(18) The following detailed description is provided to assist the reader in gaining a comprehensive understanding of the methods, apparatuses, and/or systems described herein. However, various changes, modifications, and equivalents of the methods, apparatuses, and/or systems described herein will be apparent to one of ordinary skill in the art. The sequences of operations described herein are merely examples, and are not limited to those set forth herein, but may be changed as will be apparent to one of ordinary skill in the art, with the exception of operations necessarily occurring in a certain order. Also, descriptions of functions and constructions that are well known to one of ordinary skill in the art may be omitted for increased clarity and conciseness.

(19) The features described herein may be embodied in different forms, and are not to be construed as being limited to the examples described herein. Rather, the examples described herein have been provided so that this disclosure will be thorough and complete, and will convey the full scope of the disclosure to one of ordinary skill in the art.

(20) Throughout the specification, it will be understood that when an element, such as a layer, region or wafer (substrate), is referred to as being “on,” “connected to,” or “coupled to” another element, it can be directly “on,” “connected to,” or “coupled to” the other element or other elements intervening therebetween may be present. In contrast, when an element is referred to as being “directly on,” “directly connected to,” or “directly coupled to” another element, there may be no elements or layers intervening therebetween. Like numerals refer to like elements throughout. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items.

(21) It will be apparent that though the terms first, second, third, etc. may be used herein to describe various members, components, regions, layers and/or sections, these members, components, regions, layers and/or sections should not be limited by these terms. These terms are only used to distinguish one member, component, region, layer or section from another region, layer or section. Thus, a first member, component, region, layer or section discussed below could be termed a second member, component, region, layer or section without departing from the teachings of the disclosed embodiments.

(22) Spatially relative terms, such as “above,” “upper,” “below,” and “lower” and the like, may be used herein for ease of description to describe one element's relationship to another element(s) as shown in the figures. It will be understood that the spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. For example, if the device in the figures is turned over, elements described as “above,” or “upper” other elements would then be oriented “below,” or “lower” the other elements or features. Thus, the term “above” can encompass both the above and below orientations depending on a particular direction of the figures. The device may be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein may be interpreted accordingly.

(23) The terminology used herein is for describing particular embodiments only and is not intended to be limiting of the inventive concept. As used herein, the singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “comprises,” and/or “comprising” when used in this specification, specify the presence of stated features, integers, steps, operations, members, elements, and/or groups thereof, but do not preclude the presence or addition of one or more other features, integers, steps, operations, members, elements, and/or groups thereof.

(24) Hereinafter, embodiments will be described with reference to schematic views illustrating the embodiments. In the drawings, for example, due to manufacturing techniques and/or tolerances, modifications of the shape shown may be estimated. Thus, the disclosed embodiments should not be construed as being limited to the particular shapes of regions shown herein, for example, to include a change in shape results in manufacturing. The following embodiments may also be

constituted by one or a combination thereof.

(25) In addition, it is to be noted that in the following description, a first lens refers to a lens that is the closest to an object (or a subject) and a fifth lens refers to a lens that is the closest to an imaging plane (or an image sensor). In the following description, all numerical values of radii of curvature, thicknesses, TTL, ImgH (a diagonal length of the imaging plane), and focal lengths of lenses are indicated in millimeters (mm). Further, thicknesses of the lenses, intervals between the lenses, and the TTL are distances along an optical axis of the lens. Further, in descriptions of lens shapes, the meaning of one surface of the lens being convex is that an optical axis portion (i.e., a paraxial region) of the corresponding surface is convex, and the meaning of one surface of the lens being concave is that an optical axis portion of the corresponding surface is concave. Therefore, even in the case that it is described that one surface of the lens is convex, an edge portion of the lens may be concave. Likewise, even in the case that it is described that one surface of the lens is concave, an edge portion of the lens may be convex.

(26) Further, in the present specification, an object-side surface of the lens refers to a surface of the corresponding lens closest to the object, and an image-side surface of the lens refers to a surface of the corresponding lens closest to the imaging plane.

(27) An optical imaging system may include a plurality of lenses. For example, the optical imaging system may include five lenses. The first to fifth lenses configuring the optical imaging system may be sequentially disposed in a direction from the object side toward the imaging plane. For example, the first lens may be a lens closest to the object side, and the fifth lens may be a lens closest to the imaging plane.

(28) Next, five lenses configuring the optical imaging system will be described in detail.

(29) The first lens may, for example, have a positive refractive power.

(30) At least one surface of the first lens may be convex. For example, an object-side surface of the first lens is convex.

(31) The first lens may have an aspherical surface. For example, the object-side surface and an image-side surface of the first lens are aspherical. The first lens may be formed of a material having high light transmittance and excellent workability. For example, the first lens may be formed of plastic. However, a material of the first lens is not limited to plastic. For example, the first lens may also be formed of glass.

(32) The second lens may, for example, have a negative refractive power.

(33) The second lens may have a meniscus shape. For example, an image-side surface of the second lens is concave.

(34) The second lens may have an aspherical surface. For example, the image-side surface of the second lens is aspherical. The second lens may be formed of a material having high light transmittance and excellent workability. For example, the second lens is formed of plastic or a polyurethane material. However, a material of the second lens is not limited to plastic. For example, the second lens may also be formed of glass.

(35) The second lens may be formed of a material having a high refractive index. For example, the refractive index of the second lens may be 1.60 or more. The second lens may further have a low Abbe number. For example, the Abbe number of the second lens may be 30 or less. The second lens as described above may decrease chromatic aberrations of the first lens.

(36) The third lens may, for example, have a positive refractive power.

(37) The third lens may have a meniscus shape. For example, an object-side surface of the third lens may be concave.

(38) The third lens may have an aspherical surface. For example, the object-side surface and an image-side surface of the third lens are aspherical. The third lens may be formed of a material having high light transmittance and excellent workability. For example, the third lens may be formed of plastic or a polyurethane material. However, a material of the third lens is not limited to plastic. For example, the third lens may also be formed of glass.

(39) The fourth lens may, for example, have a negative refractive power.

(40) The fourth lens may have a meniscus shape. For example, an object-side surface and an image-side surface of the fourth lens may be concave.

(41) The fourth lens may have an aspherical surface. For example, the object-side surface and the image-side surface of the fourth lens may be aspherical. The fourth lens may be formed of a material having high light transmittance and excellent workability. For example, the fourth lens may be formed of plastic or a polyurethane material. However, a material of the fourth lens is not limited to plastic. For example, the fourth lens may also be formed of glass.

(42) The fourth lens may be formed of a material having a high refractive index. For example, the refractive index of the fourth lens may be 1.60 or more. The fourth lens may further have a low Abbe number. For example, the Abbe number of the fourth lens may be 30 or less.

(43) The fifth lens may, for example, have a positive refractive power.

(44) The fifth lens may have a meniscus shape. For example, an image-side surface of the fifth lens is concave. The fifth lens may also have an inflection point. For example, the inflection point may be formed on the image-side surface of the fifth lens.

(45) The fifth lens may have an aspherical surface. For example, the image-side surface and an object-side surface of the fifth lens are aspherical. The fifth lens may be formed of a material having high light transmittance and excellent workability. For example, the fifth lens may be formed of plastic or a polyurethane material. However, a material of the fifth lens is not limited to plastic. For example, the fifth lens may also be formed of glass.

(46) As indicated above, at least one of the first to fifth lenses may have an aspherical shape. According to an example, among the first to fifth lenses, only the fifth lens may have the aspherical shape. Further, at least one the object-side surface or the image-side surface of the first to fifth lenses may be aspherical. The aspherical surface of each of the lenses may be represented by Equation 1.

(47)

$$Z = \frac{cr^2}{1 + \sqrt{1 - (1+k)c^2r^2}} + Ar^4 + Br^2 + Cr^8 + Dr^{10} + Er^{12} + Fr^{14} + Gr^{16} + Hr^{18} + Jr^{20} \quad [\text{Equation 1}]$$

(48) In Equation 1, c is an inverse of a radius of curvature of the corresponding lens, K is a conic constant, r is a distance from a certain point on an aspherical surface to an optical axis, A to J are aspherical constants, and Z is a height from the certain point on the aspherical surface to an apex of the corresponding aspherical surface in an optical axis direction.

(49) The camera module may satisfy the following Conditional Expressions:

$0.2 < D/TTL$ [Conditional Expression 1]

$0.8 \text{ mm} < D$ [Conditional Expression 2]

$0.9 \text{ mm} < D$ [Conditional Expression 3]

$TTL/ImgH < 0.7$ [Conditional Expression 4]

$75 \text{ degrees} < FOV$ [Conditional Expression 5]

$0.24 < D/f$ [Conditional Expression 6]

$TTL < 4.25 \text{ mm}$ [Conditional Expression 7]

$F \text{ No.} \leq 2.1$ [Conditional Expression 8]

In the preceding Conditional Expressions, D is a shortest distance between an image-side surface of the lens closest to an imaging plane and the imaging plane, TTL is a distance from the an object-side surface of the lens closest to the object to the imaging plane, ImgH is the diagonal length of the imaging plane, FOV is a maximum field of view of the optical imaging system, and f is an overall focal length of the optical imaging system.

(50) The camera module satisfying the above Conditional Expressions is miniaturized to thereby be mounted on a small sized terminal. In addition, the camera module satisfying the above Conditional Expressions may realize high resolution in capturing images. Further, the camera module satisfying the above Conditional Expressions may be sufficiently compact to provide a

space between the optical imaging system and the imaging plane that is large enough to enable a hand-shake compensation unit to be mounted in the space.

(51) Hereinafter, optical imaging systems according to several example embodiments will be described.

(52) FIG. 1 illustrates a camera module **100**, according to an embodiment. The camera module **100** includes an optical imaging system **110**, a filter **120**, and an imaging plane **130**. The optical imaging system **110** includes a plurality of lenses having refractive power. For example, the optical imaging system **110** includes a first lens **111**, a second lens **112**, a third lens **113**, a fourth lens **114**, and a fifth lens **115**.

(53) In the camera module **100**, the optical imaging system **110** may move in a direction intersecting an optical axis. For example, a shortest distance D from the fifth, rearmost lens **115** of the optical imaging system **110** to the imaging plane **130** may be about 0.8 mm or more. For example, the shortest distance D may be about 0.9 mm or more. The numerical value of D may be a minimum value enabling movement of the optical imaging system **110** while enabling disposition of the filter **130** between the fifth, rearmost lens **115** and the imaging plane **130**. For reference, in the embodiment of FIG. 1, the shortest distance D is about 0.908 mm.

(54) The first lens **111** has positive refractive power. An object-side surface of the first lens **111** is convex and an image-side surface of the first lens **111** is convex.

(55) The second lens **112** has negative refractive power. An object-side surface of the second lens **112** is convex and an image-side surface of the second lens **112** is concave.

(56) The third lens **113** has positive refractive power. An object-side surface of the third lens **113** is concave and an image-side surface of the third lens **113** is convex.

(57) The fourth lens **114** has negative refractive power. An object-side surface and an image-side surface of the fourth lens **114** are concave.

(58) The fifth lens **115** has positive refractive power. An object-side surface of the fifth lens **115** is convex and an image-side surface of the fifth lens **115** is concave. The fifth lens **115** may include one or more inflection points on its object-side surface and its image side-surface.

(59) The optical imaging system **110** further include a stop **ST** that is operable to adjust an amount of light incident in the optical system **110**. The stop **ST** may be disposed between the second and third lenses **112** and **113**.

(60) The optical imaging system **110** as described above may exhibit aberration characteristics and MTF characteristics as illustrated in FIGS. 2 and 3. FIGS. 4 and 5 are tables providing example characteristics of lenses and aspherical characteristics of the optical imaging system **110**. In FIGS. 4 and 5 the reference characters **S1** through **S14** refer to the following surfaces in the optical imaging system **110**: **S1** and **S2**: object-side surface and image-side surface, respectively, of first lens **111** **S3** and **S4**: object-side surface and image-side surface, respectively, of second lens **112** **S5**: stop **ST** **S6** and **S7**: object-side surface and image-side surface, respectively, of third lens **113** **S8** and **S9**: object-side surface and image-side surface, respectively, of fourth lens **114** **S10** and **S11**: object-side surface and image-side surface, respectively, of fifth lens **115** **S12** and **S13**: object-side surface and image-side surface, respectively, of filter **120** **S14**: imaging plane **130**

(61) An effective radius of the optical imaging system **110** may decrease from the first lens **111** toward the stop **ST**, but may increase from the stop **ST** toward the imaging plane **130**, as illustrated in FIG. 4. A maximum effective radius of the optical imaging system **110** may be about 3.133 mm, greater than $\frac{1}{2}$ of a diagonal length $ImgH$ of the imaging plane **130**.

(62) FIG. 6 illustrates a camera module **200**, according to another embodiment. The camera module **200** includes an optical imaging system **210**, a filter **220**, and an imaging plane **230**. The optical imaging system **210** includes a plurality of lenses having refractive power. For example, the optical imaging system **210** includes a first lens **211**, a second lens **212**, a third lens **213**, a fourth lens **214**, and a fifth lens **215**.

(63) In the camera module **200**, the optical imaging system **210** may move in a direction

intersecting the optical axis. For example, a shortest distance D from the fifth, rearmost lens **215** of the optical imaging system **210** to the imaging plane **230** may be about 0.8 mm or more. For example, the shortest distance D may be about 0.9 mm or more. The numerical value is a minimum value enabling movement of the optical imaging system **210** while enabling disposition of the filter **230** between the fifth, rearmost lens **215** and the imaging plane **230**. For reference, in the embodiment of FIG. 6, the shortest distance D is about 0.918 mm.

(64) The first lens **211** has positive refractive power. An object-side surface of the first lens **211** is convex, and an image-side surface of the first lens **211** is concave.

(65) The second lens **212** has negative refractive power. An object-side surface of the second lens **212** is convex, and an image-side surface of the second lens **212** is concave.

(66) The third lens **213** has positive refractive power. An object-side surface of the third lens **213** is concave, and an image-side surface of the third lens **213** is convex.

(67) The fourth lens **214** has negative refractive power. An object-side surface and an image-side surface of the fourth lens **214** are concave.

(68) The fifth lens **215** has positive refractive power. An object-side surface of the fifth lens **215** is convex, and an image-side surface of the fifth lens **215** is concave. The fifth lens **215** may include one or more inflection points on its object-side surface and its image side-surface.

(69) The optical imaging system **210** may further include a stop ST operable to adjust an amount of light incident in the optical imaging system **210**. The stop ST may be disposed between the second and third lenses **212** and **213**.

(70) The optical imaging system **210** as described above may exhibit aberration characteristics and MTF characteristics as illustrated in FIGS. 7 and 8. FIGS. 9 and 10 are tables providing example characteristics of lenses and aspherical characteristics of the optical imaging system **110**. The surfaces S1-S14 in FIGS. 9 and 10 correspond to the surfaces S1-S14 in FIGS. 4 and 5.

(71) An effective radius of the optical imaging system **210** may decrease from the first lens **211** toward the stop ST, but may increase from the stop ST toward the imaging plane **230**, as illustrated in FIG. 9. A maximum effective radius of the optical imaging system **210** may be about 3.133 mm, greater than $\frac{1}{2}$ of a diagonal length ImgH of the imaging plane **230**.

(72) FIG. 11 shows a camera module **300**, according to another embodiment. The camera module **300** includes an optical imaging system **310**, a filter **320**, and an imaging plane **330**. The optical imaging system **310** includes a plurality of lenses having refractive power. For example, the optical imaging system **310** includes a first lens **311**, a second lens **312**, a third lens **313**, a fourth lens **314**, and a fifth lens **315**.

(73) In the camera module **300**, the optical imaging system **310** may move a direction intersecting the optical axis. For example, a shortest distance D from the fifth, rearmost lens **315** of the optical imaging system **310** to the imaging plane **330** may be about 0.8 mm or more. For example, the shortest distance D may be about 0.9 mm or more. The numerical value may be a minimum value enabling movement of the optical imaging system **310** while enabling disposition of the filter **330** between the fifth, rearmost lens **315** and the imaging plane **330**. For reference, in the embodiment of FIG. 11, the shortest distance D is about 0.919 mm.

(74) The first lens **311** has positive refractive power. An object-side surface of the first lens **311** is convex, and an image-side surface of the first lens **311** is concave.

(75) The second lens **312** has negative refractive power. An object-side surface of the second lens **312** is convex, and an image-side surface of the second lens **312** is concave.

(76) The third lens **313** has positive refractive power. An object-side surface of the third lens **313** is concave, and an image-side surface of the third lens **313** is convex.

(77) The fourth lens **314** has negative refractive power. The object-side surface and the image-side surface of the fourth lens **314** are concave.

(78) The fifth lens **315** has positive refractive power. An object-side surface of the fifth lens **315** is convex, and an image-side surface of the fifth lens **315** is concave. The fifth lens **315** may include

one or more inflection points on its object-side surface and its image side-surface.

(79) The optical imaging system **310** may further include a stop ST operable to adjust an amount of light incident in the optical imaging system **310**. The stop ST may be disposed between the second and third lenses **312** and **313**.

(80) The optical imaging system **310** as described above may exhibit aberration characteristics and MTF characteristics as illustrated in FIGS. **12** and **13**. FIGS. **14** and **15** are tables providing example characteristics of lenses and aspherical characteristics of the optical imaging system **310**. The surfaces S1-S14 in FIGS. **14** and **15** correspond to the surfaces S1-S14 in FIGS. **4** and **5**.

(81) An effective radius of the optical imaging system **310** may decrease from the first lens **311** toward the stop ST, but may increase from the stop ST toward the imaging plane **330**, as illustrated in FIG. **14**. A maximum effective radius of the optical imaging system may be about 3.120 mm, equal to $\frac{1}{2}$ of a diagonal length ImgH of the imaging plane **330**.

(82) Table 1 includes values of optical characteristics and Conditional Expressions of the optical imaging systems **110**, **210** and **310**, according to the example embodiments. In Table 1, all lengths are indicated in millimeters (mm). As shown in Table 1, an overall focal length f of the optical imaging system **110/210/310** may be configured within a range of about 3.50 mm to about 3.90 mm. A focal length f1 of the first lens may be configured within a range of about 2.20 mm to about 2.40 mm. A focal length f2 of the second lens may be configured within a range of about -4.70 mm to about -4.10 mm. A focal length f3 of the third lens may be configured within a range of about 16 mm to about 29 mm. A focal length f4 of the fourth lens may be configured within a range of about -11 mm to about -8.0 mm. A focal length f5 of the fifth lens may be configured within a range of about 70 mm to about 130 mm. An overall length of the optical imaging system may be about 4.20 mm or less. A maximum field of view of the optical imaging system may be about 78 mm or more. D may be about 0.8 mm or more. However, it may be more advantageous in mounting a hand-shake compensation unit if D is about 0.9 mm or more. The F No. may be about 2.1 or less. TTL/ImgH may be smaller than about 0.7. However, TTL/ImgH may be smaller than about 0.68, which may be advantageous in miniaturizing the optical imaging system.

(83) TABLE-US-00001

	First	Second	Third	Remarks	Embodiment	Embodiment
Embodiment f	3.6965	3.7577	3.7341	f1	2.3464	2.3717
				f2	-4.2246	-4.5776
				f3	17.1792	27.5840
				f4	-9.6898	-9.1597
				f5	125.4764	76.3495
				TTL	4.1969	4.1953
				BFL	1.0730	1.0690
				F No.	2.070	2.100
				FOV	79.200	78.000
				ImgH	6.240	6.240
				D	0.9080	0.9190
				D/TTL	0.2164	0.2191
				TTL/ImgH	0.6726	0.6723
				D/f	0.2456	0.2446
					0.2458	

(84) Next, a configuration of an actuator of the camera module **100** will be described with reference to FIGS. **16** and **17**. It should be understood that the described configuration of the actuator also applies to the cameral modules **200** and **300**.

(85) As shown in FIGS. **16** and **17**, the camera module **100** includes an actuator operable to move the optical imaging system **110**. For example, the camera module **100** includes an auto-focusing unit **160** and a hand-shake compensation unit **170**.

(86) The auto-focusing unit **160** is operable to move the optical imaging system **110** in the optical axis direction. To this end, the auto-focusing unit **160** includes a first magnet **162** and a first coil **164**. The first magnet **162** is disposed on a lens barrel **140** accommodating the optical imaging system **110** therein, and the first coil **164** is disposed on a housing **150** accommodating the lens barrel **140** therein. The first magnet **162** and the first coil **164** are disposed on one side surface of the lens barrel **140** and one side surface of the housing **150**, respectively, to face each other as illustrated in FIG. **17**.

(87) The hand-shake compensation unit **170** is operable to move the optical imaging system **110** in the direction intersecting the optical axis. To this end, the hand-shake compensation unit **170** includes a second magnet **172** and a second coil **174**. The second magnet **172** is disposed on the lens barrel **140** accommodating the optical imaging system **110** therein, and the second coil **174** is

disposed on the housing **150** accommodating the lens barrel **140** therein. In more detail, the second magnet **172** and the second coil **174** are disposed on another side surface of the lens barrel **140** and another side surface of the housing **150**, respectively, on which the auto-focusing unit **160** is not disposed, to face each other as illustrated in FIG. **17**.

(88) In the camera module **100** as described above, since the overall length of the optical imaging system **110** may be about 4.20 mm or less, the camera module **100** may be miniaturized. Further, since a sufficient space may be provided between the optical imaging system **110** and the imaging plane **130**, the auto-focusing unit **160** and the hand-shake compensating unit **170** may be mounted in the space. Therefore, according to the disclosed embodiments, a camera module having high resolution and high performance may be provided.

(89) As set forth above, according to example embodiments disclosed herein, a thin camera module may be provided.

(90) While this disclosure includes specific examples, it will be apparent to one of ordinary skill in the art that various changes in form and details may be made in these examples without departing from the spirit and scope of the claims and their equivalents. The examples described herein are to be considered in a descriptive sense only, and not for purposes of limitation. Descriptions of features or aspects in each example are to be considered as being applicable to similar features or aspects in other examples. Suitable results may be achieved if the described techniques are performed in a different order, and/or if components in a described system, architecture, device, or circuit are combined in a different manner, and/or replaced or supplemented by other components or their equivalents. Therefore, the scope of the disclosure is defined not by the detailed description, but by the claims and their equivalents, and all variations within the scope of the claims and their equivalents are to be construed as being included in the disclosure.

Claims

1. A camera module, comprising: an optical imaging system comprising a first lens, a second lens, a third lens, a fourth lens, and a fifth lens having a concave image-side surface at an optical axis thereof, and wherein the first to fifth lenses are sequentially disposed from an object side to an imaging plane, wherein the optical imaging system has a total number of five lenses with refractive power, wherein $75^\circ < \text{FOV}$, where FOV is a field of view of the optical imaging system, wherein a thickness of the first lens is greater than a thickness of the fifth lens, and wherein a radius of curvature of an object-side surface of the fourth lens is less than a radius of curvature of an image-side surface of the third lens.
2. The camera module of claim 1, wherein the first lens has a convex object-side surface.
3. The camera module of claim 1, wherein the second lens has a convex object-side surface.
4. The camera module of claim 1, wherein the third lens has a concave object-side surface.
5. The camera module of claim 1, wherein the fourth lens has a concave object-side surface.
6. The camera module of claim 1, wherein the fifth lens has a convex object-side surface.
7. A camera module, comprising: an optical imaging system comprising a first lens, a second lens having negative refractive power, a third lens having a concave object-side surface in a paraxial region thereof, a fourth lens, and a fifth lens having a concave image-side surface, and wherein the first to fifth lenses are sequentially disposed from an object side to an imaging plane, wherein the optical imaging system has a total number of five lenses with refractive power, wherein $75^\circ < \text{FOV}$, where FOV is a field of view of the optical imaging system, and wherein a numerical value of a radius of curvature of an object-side surface of the fourth lens is less than a numerical value of a radius of curvature of an image-side surface of the third lens and a numerical value of a radius of curvature of an image-side surface of the fourth lens.
8. The camera module of claim 7, wherein the first lens has a convex object-side surface.
9. The camera module of claim 7, wherein the second lens has a convex object-side surface.

10. The camera module of claim 7, wherein the fourth lens has a concave object-side surface.
 11. The camera module of claim 7, wherein the fifth lens has a convex object-side surface.
-