

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12412423
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Norimatsu; Kouji

Guidance acquisition device for ascertaining cause of authentication error and providing guidance, guidance acquisition method, and storage medium

Abstract

Face image data is acquired and a face image is captured, and a difference between a face image indicated by the face image data and the face image that is captured or a candidate of the difference is detected on the basis of at least one of the face image indicated by the face image data that is acquired, and the face image that is captured. Guidance is acquired on the basis of the difference or the candidate of the difference which is detected, and an output unit is controlled to output the guidance.

Inventors:	Norimatsu; Kouji (Tokyo, JP)
Applicant:	NEC Corporation (Tokyo, JP)
Family ID:	58239649
Assignee:	NEC CORPORATION (Tokyo, JP)
Appl. No.:	18/514316
Filed:	November 20, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240087363 A1	Mar. 14, 2024

Foreign Application Priority Data

JP	2015-177813	Sep. 09, 2015
----	-------------	---------------

Related U.S. Application Data

continuation parent-doc US 17958535 20221003 US 11861939 child-doc US 18514316
continuation parent-doc US 16884801 20200527 US 11501567 20221115 child-doc US 17958535
continuation parent-doc US 15758136 US 10706266 20200707 WO PCT/JP2016/074639
20160824 child-doc US 16884801

Publication Classification

Int. Cl.: **G06K9/00** (20220101); **G06T7/73** (20170101); **G06V20/20** (20220101); **G06V40/16** (20220101); **G07C9/10** (20200101); **G07C9/25** (20200101); **G10L13/00** (20060101); **H04N23/611** (20230101)

U.S. Cl.:

CPC **G06V40/172** (20220101); **G06T7/74** (20170101); **G06V20/20** (20220101); **G06V40/165** (20220101); **G06V40/173** (20220101); **G07C9/10** (20200101); **G07C9/253** (20200101); **G10L13/00** (20130101); **H04N23/611** (20230101); G06T2207/30201 (20130101); G07C9/257 (20200101)

Field of Classification Search

CPC: G06T (2207/30201); G06V (40/16); G06V (40/161); G06V (40/162); G06V (40/164); G06V (40/165); G06V (40/167); G06V (40/168); G06V (40/169); G06V (40/171); G06V (40/172); G06V (40/173); G06V (40/174); G06V (40/176); G06V (40/18); G06V (40/19); G06V (40/193); G06V (40/197); H04N (21/44218); H04N (5/23219); H04N (21/441); H04N (21/4415); H04N (1/4406); H04N (1/442); G07C (9/00563); G07C (9/25); G07C (9/253); G07C (9/257); G07C (9/26); G07C (9/10); G07C (9/15); G07C (9/37); G07C (9/00); G07C (9/20); G07C (9/22); E06B (11/08); G06F (21/30); G06F (21/32); H04L (63/0853); H04L (63/0861)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7868917	12/2010	Nakamura	348/208.14	H04N 23/634
9235750	12/2015	Sutton	N/A	B60R 25/10
2007/0086626	12/2006	Mariani	382/115	G06V 40/161
2007/0098223	12/2006	Kamata	382/115	G06K 9/00912
2010/0053363	12/2009	Kim	N/A	N/A
2010/0266206	12/2009	Jo	382/190	H04N 23/611
2011/0235870	12/2010	Ichikawa	382/118	G06F 21/32
2012/0075496	12/2011	Akifusa	348/222.1	G06T 5/50
2012/0293642	12/2011	Berini	348/77	G06V 40/197
2013/0215275	12/2012	Berini	348/150	G06V 10/993
2013/0247175	12/2012	Nechyba	726/19	G06V 40/16
2014/0062658	12/2013	Vrijen	340/5.83	G07F 7/1008
2014/0063191	12/2013	Bataller	340/541	G08B 13/22
2014/0270404	12/2013	Hanna	382/116	G06V 40/45
2015/0379332	12/2014	Matsunaga	348/77	G06V 40/172

2016/0063314	12/2015	Samet	348/78	G06F 21/31
2016/0070952	12/2015	Kim	382/118	G06T 17/00
2016/0125228	12/2015	Son	382/118	A61B 5/0077
2016/0171805	12/2015	Jang	382/118	G08B 13/19645
2016/0196475	12/2015	Martin	382/117	G06K 9/00221
2016/0269401	12/2015	Saito	N/A	G07C 9/20
2016/0314635	12/2015	Chen	N/A	G07C 9/00896
2016/0364561	12/2015	Lee	N/A	N/A
2017/0118209	12/2016	Saravanan	N/A	G06K 9/00288
2018/0047230	12/2017	Nye	N/A	G07C 9/37
2018/0121724	12/2017	Ovsiannikov	N/A	G06V 40/1312
2019/0272691	12/2018	Nye	N/A	G07C 9/38
2020/0412133	12/2019	Baldasare	N/A	G06V 40/172

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
H06-119433	12/1993	JP	N/A
2000-293663	12/1999	JP	N/A
2002-008070	12/2001	JP	N/A
2003-151016	12/2002	JP	N/A
2005-078589	12/2004	JP	N/A
2006-063172	12/2004	JP	N/A
2005-135310	12/2004	JP	N/A
2005-149370	12/2004	JP	N/A
2007-140946	12/2006	JP	N/A
2007-252587	12/2006	JP	N/A
2007-322521	12/2006	JP	N/A
2008-004003	12/2007	JP	N/A
2008-033810	12/2007	JP	N/A
2008-250829	12/2007	JP	N/A
2009-176208	12/2008	JP	N/A
2010-67008	12/2009	JP	N/A
2010-277504	12/2009	JP	N/A
2011-039959	12/2010	JP	N/A
201139994	12/2010	JP	N/A
2012-133477	12/2011	JP	N/A
2012-528379	12/2011	JP	N/A
2013-097760	12/2012	JP	N/A
2014-078052	12/2013	JP	N/A
2011-0094947	12/2010	KR	G07C 9/37
2015/001791	12/2014	WO	N/A

OTHER PUBLICATIONS

Japanese Office Action for JP Application No. 2020-124731 mailed on Jun. 7, 2022 with English Translation. cited by applicant

Japanese Office Action for JP Application No. 2020-124731 mailed on Sep. 7, 2021 with English Translation. cited by applicant

Communication dated Sep. 16, 2019 from the United States Patent and Trademark Office in U.S. Appl. No. 15/758,136. cited by applicant

Communication dated Feb. 28, 2020 from the United States Patent and Trademark Office in U.S. Appl. No. 15/758,136. cited by applicant
International Search Report of PCT/JP2016/074639 dated Nov. 1, 2016. cited by applicant
Communication dated Oct. 23, 2019, issued by the Japan Patent Office in corresponding Japanese Application No. 2018-233808. cited by applicant
Communication issued Jul. 26, 2019 by the U.S. Patent and Trademark Office in U.S. Appl. No. 16/279,220. cited by applicant
Communication dated Jul. 3, 2018 from the Japanese Patent Office in counterpart Japanese application No. 2017-539101. cited by applicant
Decision to Grant a Patent dated Nov. 13, 2018 issued by the Japanese Patent Office in counterpart Japanese Application No. 2017-539101. cited by applicant
Communication Issued Apr. 21, 2020 by the Japanese Patent Office in Japanese Application No. 2018-233808. cited by applicant
Communication dated Feb. 6, 2018 from the Japanese Patent Office in counterpart Japanese Application No. 2017-539101. cited by applicant
U.S. Office Communication for U.S. Appl. No. 16/884,801 mailed on Sep. 20, 2021. cited by applicant
U.S. Office Communication for U.S. Appl. No. 16/884,601 mailed on Feb. 22, 2022. cited by applicant
U.S. Notice of Allowance for U.S. Appl. No. 16/884,801 mailed on Jul. 8, 2022. cited by applicant
JP Office Action for JP Application No. 2022-142295, mailed on Aug. 15, 2023 with English Translation. cited by applicant

Primary Examiner: Fitzpatrick; Atiba O

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) The present application is a continuation application of U.S. patent application Ser. No. 17/958,535 filed on Oct. 3, 2022, which is a continuation application of U.S. patent application Ser. No. 16/884,801 filed on May 27, 2020, which is issued as U.S. Pat. No. 11,501,567, which is a continuation application of U.S. patent application Ser. No. 15/758,136 filed on Mar. 7, 2018, which is issued as U.S. Pat. No. 10,706,266, which is a National Stage Entry of international application PCT/JP2016/074639 filed on Aug. 24, 2016, which claims the benefit of priority from Japanese Patent Application 2015-177813 filed on Sep. 9, 2015, the disclosures of all of which are incorporated in their entirety by reference herein.

TECHNICAL FIELD

(1) The present invention relates to a guidance acquisition device, a guidance acquisition method, and a program.

BACKGROUND ART

(2) As one of identity verification methods such as for management of entrance into and exit from a predetermined area, face authentication is known. In face authentication, a face image of an authentication target is captured in advance, and the face image is compared with a face image captured in advance to perform determination of identity.

(3) Here, several technologies for improving accuracy of the face authentication are suggested. For example, a face collation device described in Patent Document 1 includes a photographing unit that captures a face image of a person to be photographed, a light direction detection unit that detects a

direction of the brightest light in front of the photographing unit, and a guide unit that guides the person to be photographed so as to stand in the direction of the light on the basis of the light direction that is detected. Patent Document 1 describes that even in a case where the face collation device is provided outdoors or in a location in which external light shines, the person to be photographed is guided to an appropriate photographing position, and thus an appropriate face image can be captured according to the above-described configuration.

CITATION LIST

Patent Literature

(4) [Patent Document 1]

(5) Japanese Unexamined Patent Application, First Publication No. 2008-4003

SUMMARY OF INVENTION

Technical Problem

(6) As a cause of a problem in which the face authentication cannot be appropriately performed, various causes are considered in addition to light direction, and thus a way to handle failure of the face authentication are different depending on the causes of a failure of the face authentication. However, there is a possibility that it is difficult to understand what is a cause when observing from an outer side of a device that performs the face authentication, and thus an appropriate response may not be performed. Particularly, there is a possibility that the authentication target cannot understand the way to handle the failure and feel stress, and some time may be taken until authentication is accepted.

(7) An object of the invention is to provide a guidance acquisition device, a guidance acquisition method, and a program which are capable of solving the above-described problems.

Solution to Problem

(8) According an aspect of the invention, there is provided a guidance acquisition device including: a data acquisition unit that is configured to acquire face image data; a photographing unit that is configured to capture a face image; a difference detection unit that is configured to detect a difference between a face image indicated by the face image data acquired by the data acquisition unit and the face image captured by the photographing unit or a candidate of the difference on the basis of at least one of the face image indicated by the face image data acquired by the data acquisition unit and the face image captured by the photographing unit; a guidance acquisition unit that is configured to acquire guidance on the basis of the difference or the candidate of the difference which is detected by the difference detection unit; and an output control unit that is configured to control an output unit to output the guidance that is acquired by the guidance acquisition unit.

(9) According to another aspect of the invention, there is provided a guidance acquisition method that is executed by a guidance acquisition device including a correlation information storage unit that is configured to store correlation information that indicates a correlation between a difference between a face image indicated by face image data and a face image obtained through photographing, and guidance for a person to be photographed with respect to the difference, in advance. The method includes: a data acquisition step of acquiring the face image data; a photographing step of capturing the face image; a difference detection step of detecting the difference between the face image indicated by the face image data acquired in the data acquisition step, and the face image captured in the photographing step; a guidance acquisition step of acquiring guidance that represents guidance correlated with the difference detected in the difference detection step in the correlation information; and an output control step of controlling an output unit to output the guidance acquired in the guidance acquisition step.

(10) According to still another aspect of the invention, there is provided a program that causes a computer including a photographing unit, and a correlation information storage unit that is configured to store correlation information that indicates a correlation between a difference between a face image indicated by face image data and a face image obtained through

photographing, and guidance for a person to be photographed with respect to the difference, in advance to execute: a data acquisition step of acquiring the face image data; a photographing step of capturing the face image by the photographing unit; a difference detection step of detecting the difference between the face image indicated by the face image data acquired in the data acquisition step, and the face image captured in the photographing step; a guidance acquisition step of acquiring guidance correlated with the difference detected in the difference detection step in the correlation information; and an output control step of controlling an output unit to output the guidance acquired in the guidance acquisition step.

Advantageous Effects of Invention

(11) According to the invention, in a case where a device that is configured to perform face authentication cannot appropriately face authentication, it is possible to increase the probability in which an authentication target can understand a way to handle a failure of the face authentication.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a schematic block diagram showing a functional configuration of a face authentication device according to an embodiment of the invention.

(2) FIG. 2 is a view showing an example of a display screen image of a display unit in a state in which the face authentication device of the embodiment is in execution of the face authentication.

(3) FIG. 3 is a view showing an example of a display screen image of the display unit in a case where an error occurs in the face authentication of the face authentication device of the embodiment.

(4) FIG. 4 is a view showing an example of correlation information that is stored in a correlation information storage unit of the embodiment.

(5) FIG. 5 is a view showing an example of an image that is captured by a photographing unit in a case where a distance between a person to be photographed and the photographing unit is long in the embodiment.

(6) FIG. 6 is a view showing an example of an image that is captured by the photographing unit in a case where a position of the person to be photographed deviates in a horizontal direction in the embodiment.

(7) FIG. 7 is a flowchart showing an example of a processing procedure that is performed by the face authentication device of the embodiment.

(8) FIG. 8 is a schematic block diagram showing a minimum configuration of a guidance acquisition device according to the invention.

DESCRIPTION OF EMBODIMENTS

(9) Hereinafter, an embodiment of the invention will be described, but the following embodiment does not limit the invention in the following appended claims. In addition, it cannot be said that the entirety of combinations of characteristics described in the embodiment are essential for the solution to problem.

(10) FIG. 1 is a schematic block diagram showing a functional configuration of a face authentication device in an embodiment of the invention. In the drawing, a face authentication device **100** includes a data acquisition unit **110**, a photographing unit **120**, an output unit **130**, a storage unit **170**, and a control unit **180**.

(11) The output unit **130** includes a display unit **131** and a voice output unit **132**.

(12) The storage unit **170** includes a correlation information storage unit **171**.

(13) The control unit **180** includes a difference detection unit **181**, a guidance acquisition unit **182**, a face authentication unit **183**, and an output control unit **184**.

(14) The face authentication device **100** is a device that is configured to perform identity

verification as face authentication. Hereinafter, a description will be provided of a case where the face authentication device **100** performs identity verification during immigration examination at an airport or the like as an example.

(15) However, application fields of the face authentication device **100** are not limited to the immigration examination. For example, the face authentication device **100** may be a device that verifies whether or not authority of entrance into and exit from a specific facility is present through face authentication. In this case, the face authentication device **100** may read out face image data from identification paper (for example, an ID card) that is carried by an authentication target, and may compare the face image data with a captured image to perform the face authentication.

Alternatively, the face authentication device **100** may store face image data of an entrance/exit-authorized person in advance.

(16) In addition, the face authentication device **100** corresponds to an example of a guidance acquisition device, and output guidance in a case where an error occurs in the face authentication. The face authentication error stated here represents a case where a face authentication result cannot be obtained, that is, a case where the face authentication device **100** cannot determine whether or not an authentication target is the same person as a person shown in face authentication data. In addition, the guidance that is output by the face authentication device **100** is information that shows a method of handling the face authentication error, by the authentication target.

(17) For example, the face authentication device **100** is realized when a computer on which a camera and the like are mounted executes a program. Alternatively, the face authentication device **100** may be configured by using dedicated hardware.

(18) The data acquisition unit **110** acquires face image data. Specifically, the data acquisition unit **110** includes a passport reader device, and reads out face image data, which is registered in an IC (integrated circuit) chip in advance, from the IC chip that is embedded in the passport.

(19) In addition, the data acquisition unit **110** acquires attribute data indicating attributes such as nationality, sexuality, and an age of an authentication target (a person to be captured by the photographing unit **120** (hereinafter, simply referred to a person to be photographed)) from the IC chip embedded in the passport in addition to the face image data. The attributes of the authentication target stated here represents innate characteristics of the authentication target (that is, characteristics which are determined when the authentication target was born). Examples of the attributes of the authentication target include nationality, sexuality, and age as described above.

(20) Furthermore, the data acquisition unit **110** may acquire at least any one between the face image data and the attribute data from elsewhere other than from a passport.

(21) For example, in a case where the face authentication device **100** is a device that verifies whether or not authority of entrance into and exit from a specific facility is present through face authentication, the data acquisition unit **110** may read out face image data (face image data indicating a face image of an authentication target) of the authentication target and attribute data (attribute data indicating an attribute of the authentication target) of the authentication target, from identification paper (for example, an ID card).

(22) Alternatively, the storage unit **170** may store the face image data and the attribute data in advance (before the face authentication device **100** performs the face authentication), and the data acquisition unit **110** may read out the face image data of the authentication target and the attribute data of the authentication target from the storage unit **170**.

(23) Furthermore, acquisition of the attribute data of the authentication target by the data acquisition unit **110** is not an essential requirement. The data acquisition unit **110** may acquire at least the face image data.

(24) The photographing unit **120** is provided with a camera to perform photographing. Particularly, the photographing unit **120** repetitively captures the face image of the authentication target. The repetitive photographing stated here may be photographing capable of repetitively obtaining the face image. For example, the photographing unit **120** may photograph a moving image, and may

repeat capturing of a still image at predetermined time intervals (for example, every second).

(25) The output unit **130** outputs information. Particularly, the output unit **130** outputs guidance.

(26) The output of the guidance stated here may be an output of a signal indicating the guidance. Alternatively, the output of the guidance stated here may be presentation of guidance in an aspect in which the authentication target can understand guidance such as display of guidance and voice output of guidance.

(27) For example, the display unit **131** includes a display screen such as a liquid crystal panel and a light-emitting diode (LED) panel, and displays various images. Particularly, the display unit **131** displays a face image indicated by face image data that is acquired by the data acquisition unit **110**, and a face image (face image obtained through photographing performed by the photographing unit **120**) that is captured by the photographing unit **120**. In addition, the display unit **131** displays guidance.

(28) Display of the guidance by the display unit **131** corresponds to an example of the output of the guidance.

(29) FIG. 2 is a view showing an example of a display screen image of the display unit **131** in a state in which the face authentication device **100** is in execution of the face authentication. An image P11 represents an example of a face image (a face image indicated by face image data that is acquired by the data acquisition unit **110**) of a passport. The face image of the passport is an image that is used in face authentication. When the display unit **131** displays the face image of the passport, and a person to be photographed (authentication target) adjusts their facial expression, their position, and the like to the facial expression, position, and the like at the time of capturing the face image of the passport, it is possible to reduce the probability of an error occurring in the face authentication.

(30) In addition, the image P12 represents an example of an image obtained by horizontally inverting an image captured by the photographing unit **120**. Since the display unit **131** displays an image that is obtained by horizontally inverting the latest image captured by the photographing unit **120**, in a case where a position of the person to be photographed deviates in a horizontal direction with respect to a position of the photographing unit **120** (a photographing range of the photographing unit **120**), the person to be photographed can intuitively understand to which of a left direction or a right direction is deviated. Furthermore, the image P12 may display the latest image captured by the photographing unit **120** as is without the horizontal inversion.

(31) In addition, the display unit **131** displays a message of “your face is being photographed” in a region A11. Since the display unit **131** displays the message, the person to be photographed can understand that the face authentication device **100** is in execution of the face authentication.

(32) FIG. 3 is a view showing an example of a display screen image of the display unit **131** in a case where an error occurs in the face authentication by the face authentication device **100**. An image P21 represents an example of the face image (face image indicated by the face image data that is acquired by the data acquisition unit **110**) of the passport. In addition, an image P22 represents an example of an image that is used in the face authentication by the face authentication device **100** among images captured by the photographing unit **120**. Both of the images P21 and P22 are images which are used in the face authentication by the face authentication device **100**. As described above, since the display unit **131** displays the two images which are used in the face authentication, the authentication target can estimate the cause of an error by comparing the two images.

(33) In addition, the image P23 represents an example of an image obtained by horizontally inverting the latest image captured by the photographing unit **120**. When the display unit **131** displays the face image of the passport and the latest image captured by the photographing unit **120**, and the authentication target detects a difference between the two images and takes countermeasures to reduce the difference, it is possible to reduce the probability of an error occurring in the face authentication performed by the face authentication device **100**.

- (34) Furthermore, the image P23 may be an image which is displayed as it is without horizontal inverting the latest image captured by the photographing unit **120**.
- (35) In addition, the display unit **131** displays a message of “please, come closer” in a region A21. The message corresponds to an example of the guidance, and shows a handling method in which the person to be photographed approaches the camera of the photographing unit **120**.
- (36) In addition, the display unit **131** displays an arrow B21. The arrow B21 also corresponds to an example of the guidance, and shows a handling method in which the person to be photographed approaches the camera of the photographing unit **120** as in the message in the region A21.
- (37) As described above, when the display unit **131** displays the guidance through display of an icon such as an arrow, various persons to be photographed, who use different languages, can understand the guidance. For example, when the display unit **131** displays a movement direction of the person to be photographed with an arrow, various persons to be photographed, who use different languages, can understand the movement direction.
- (38) The voice output unit **132** includes a speaker and outputs sound. Particularly, the voice output unit **132** outputs the guidance with a voice.
- (39) Furthermore, a method of outputting the guidance by the face authentication device **100** is not limited to display or voice output of the guidance. For example, the output unit **130** may be constituted as a device independent from the face authentication device **100**, and the face authentication device **100** may allow the output unit **130** to output (transmit) a signal indicating the guidance.
- (40) The storage unit **170** is constituted by using a storage device that is provided in the face authentication device **100**, and stores various pieces of information.
- (41) The correlation information storage unit **171** stores correlation information. The correlation information that is stored in the correlation information storage unit **171** is information indicating a correlation between a difference between the face image (face image indicated by the face image data acquired by the data acquisition unit **110**) of the passport and the face image captured by the photographing unit **120**, and the guidance for the person to be photographed with regard to the difference.
- (42) FIG. 4 is a view showing an example of the correlation information that is stored in the correlation information storage unit **171**.
- (43) The correlation information storage unit **171** shown in the drawing has a table-type data structure, and a difference column and a handling method column are included in each row.
- (44) The difference column is a column in which information indicating a difference between the face image of the passport and the face image captured by the photographing unit **120** is stored. In addition, the handling method column is a column in which information indicating a handling method of the person to be photographed (authentication target) with regard to the difference shown in the difference column is stored. The information stored in the handling method column corresponds to an example of the guidance for the person to be photographed.
- (45) As described above, in the correlation information, a difference between the face image indicated by the face image data acquired by the data acquisition unit **110** and the face image captured by the photographing unit **120**, and the guidance for the person to be photographed with regard to the difference are correlated in every row.
- (46) For example, in a case where the face image of the passport and the face image captured by the photographing unit **120** are different in facial expression, as a handling method of the person to be photographed, it can be considered that the person to be photographed shows the same facial expression as in the face image of the passport such as being expressionless. Accordingly, as a handling method in a case where the difference is “facial expression”, the correlation information in FIG. 4 shows a handling method of “please, be expressionless”.
- (47) In addition, as a handling method in a case where it is difficult to immediately eliminate the difference between the face image of the passport and the face image captured by the

photographing unit **120**, the correlation information in FIG. **4** shows a handling method of “please, notify an attendant”.

(48) For example, in a case where a facial hair is not present in the face image of the passport, but the facial hair is shown in the face image captured by the photographing unit **120**, it is considered that it is difficult to take countermeasures by saving off the facial hair in that situation.

Accordingly, as a handling method for a case where the difference is “facial hair”, the correlation information in FIG. **4** shows a handling method of “please, notify an attendant”. When the face authentication device **100** outputs (for example, displays) the handling method, the authentication target can be made aware that a handling method is contacting the attendant to inquire a countermeasure method.

(49) Furthermore, the correlation information that is stored in the correlation information storage unit **171** is not limited to storage of information indicating a handling method of the person to be photographed as guidance for the person to be photographed. For example, the correlation information storage unit **171** may store correlation information that includes information indicating a difference between the face image of the passport and the face image captured by the photographing unit **120** as the guidance for the person to be photographed. In this case, the information indicating the difference between the face image of the passport and the face image captured by the photographing unit **120** corresponds to an example of the guidance.

(50) For example, the display unit **131** may display the face image of the passport, and guidance of “the facial expression is different”. In this case, the person to be photographed can understand and execute a handling method of showing the same facial expression as in the face image of the passport with reference to the face image of the passport.

(51) The control unit **180** controls respective units of the face authentication device **100** to perform various kinds of processing. For example, the control unit **180** is realized when a central processing unit (CPU) of the face authentication device **100** reads out a program from the storage unit **170** and executes the program.

(52) The difference detection unit **181** detects the difference between the face image indicated by the face image data acquired by the data acquisition unit **110**, and the face image captured by the photographing unit **120**, or a candidate of the difference on the basis of at least one of the face image indicated by the face image data acquired by the data acquisition unit **110**, and the face image captured by the photographing unit **120**.

(53) Particularly, the difference detection unit **181** may detect the candidate of the difference on the basis of the face image indicated by the face image data acquired by the data acquisition unit **110**. For example, in a case where the face image of the passport which is acquired by the data acquisition unit **110** is an eyeglass wearing image, the difference detection unit **181** may detect wearing or non-wearing of eyeglasses as the candidate of the difference.

(54) In a case where the difference detection unit **181** detects the candidate, for example, the display unit **131** displays the face image of the passport in a manner of emphasizing eyeglasses, and thus the person to be photographed can be made aware of necessity to wear eyeglasses. When the person to be photographed, who does not wear eyeglasses, wears eyeglasses, it is possible to reduce the probability of an error occurring in the face authentication performed by the face authentication device **100**.

(55) In addition, in this case, even in a state in which the photographing unit **120** does not photograph the face of the person to be photographed, the difference detection unit **181** can detect the candidate of the difference. Accordingly, at an early stage, for example, before the person to be photographed stands within a photographing range of the photographing unit **120**, the display unit **131** can display a suggestion to wear eyeglasses.

(56) Alternatively, the difference detection unit **181** may detect the difference between the face image indicated by the face image data acquired by the data acquisition unit **110**, and the face image captured by the photographing unit **120**, or the candidate of the difference on the basis of the

face image captured by the photographing unit **120**. For example, in a case where the face image captured by the photographing unit **120** is a mask-wearing face image, the difference detection unit **181** may detect wearing or non-wearing of the mask as the candidate of the difference. In a case where the difference detection unit **181** detects the candidate, for example, the display unit **131** displays a message of “please, take off the mask”, and thus the person to be photographed can be made aware of necessity to take off the mask. When the person to be photographed takes off the mask, it is possible to reduce the probability of an error occurring in the face authentication that is performed by the face authentication device **100**.

(57) In addition, in this case, even in a state in which the data acquisition unit **110** does not acquire data of the face image, the difference detection unit **181** can detect the candidate of the difference. Accordingly, at an early stage, for example, before the person to be photographed brings the passport into contact with a passport reader device, the display unit **131** can display a suggestion to take off the mask.

(58) Furthermore, the difference detection unit **181** may detect the candidate of the difference other than the wearing or non-wearing of the mask by detecting that the face image captured by the photographing unit **120** faces a lateral side.

(59) Alternatively, the difference detection unit **181** may detect the difference between the face image indicated by the face image data acquired by the data acquisition unit **110** and the face image captured by the photographing unit **120**. Particularly, in a case where an error occurs in the face authentication that is performed by the face authentication unit **183**, the difference detection unit **181** detects a difference that becomes the cause of the face authentication error, the difference being the difference between the face image indicated by the face image data acquired by the data acquisition unit **110** and the face image captured by the photographing unit **120**. A description will be provided of the difference that is detected by the difference detection unit **181** with reference to FIG. 5 and FIG. 6.

(60) FIG. 5 is a view showing an example of an image that is captured by the photographing unit **120** in a case where a distance between the person to be photographed and the photographing unit **120** is long. In the drawing, an example of a display screen image (image that is displayed on the display screen by the display unit **131**) of the display unit **131** is shown. An image P31 represents an example of a face image (face image indicated by the face image data acquired by the data acquisition unit **110**) of the passport. In addition, an image P32 represents an example of an image obtained by horizontally inverting an image captured by the photographing unit **120**. In an example of FIG. 5, the photographing unit **120** is capturing an image of the person to be photographed which includes a face image (image P33) of the person to be photographed.

(61) For example, the difference detection unit **181** detects a position of eyes in the image captured by the photographing unit **120**, and extracts a face portion in the image captured by the photographing unit **120**.

(62) In addition, the difference detection unit **181** determines whether or not a gap size (length indicated by an arrow B31) between a left eye and a right eye is smaller than a gap threshold value, and whether or not a size of the face portion is smaller than a face portion threshold value. Here, the gap threshold value and the face portion threshold value are predetermined threshold values (for example, constants) which are set as threshold values in determination as to whether or not the distance between the person to be photographed and the photographing unit **120** is long. In addition, the size of the face portion may be any one of an area of the image of the face portion, a vertical length of the image of the face portion, and a horizontal width of the image of the face portion, or a combination thereof.

(63) Between two conditions such things as the size of the gap between the left eye and the right eye is smaller than the gap threshold value, and the size of the face portion is smaller than the face portion threshold value, in a case where it is determined that one or more conditions are satisfied, the difference detection unit **181** determines (detects) that the distance between the person to be

photographed and the photographing unit **120** is long.

(64) Furthermore, the difference in which the distance between the person to be photographed and the photographing unit **120** is long corresponds to a difference of “distance (far)” in the example of FIG. **4**.

(65) Furthermore, a method in which the difference detection unit **181** detects the difference in which the distance between the person to be photographed and the photographing unit **120** is long is not limited to the above-described method. For example, the difference detection unit **181** may detect the difference in which the distance between the person to be photographed and the photographing unit **120** is long on the basis of only any one of the gap size between the left eye and the right eye, and the size of the face portion.

(66) FIG. **6** is a view showing an example of an image that is captured by the photographing unit **120** in a case where a position of the person to be photographed deviates in a horizontal direction. The drawing shows an example of a display screen image of the display unit **131**. An image **P41** represents an example of a face image (face image acquired by the data acquisition unit **110**) of the passport. In addition, an image **P42** represents an example of an image obtained by horizontally inverting an image captured by the photographing unit **120**. In the example of FIG. **6**, the photographing unit **120** is capturing an image of the person to be photographed which includes a face image (image **P43**) of the person to be photographed. In addition, an x-axis is a coordinate axis in a horizontal direction in the image **P42**. A y-axis is a coordinate axis in a vertical direction in the image **P42**.

(67) For example, the difference detection unit **181** detects a position of eyes in the image captured by the photographing unit **120**, and extracts a face portion in the image captured by the photographing unit **120**.

(68) In addition, the difference detection unit **181** determines whether or not the x-coordinate of the left eye is greater than a rightward deviation threshold value of the left eye coordinates, whether or not the x-coordinate of the right eye is greater than a rightward deviation threshold value of the right eye coordinates, and whether or not an x-coordinate of the face portion (for example, an average value of an x-coordinate on a left end and a y-coordinate on a right end in a region extracted as the face portion) is greater than a rightward deviation threshold value of the face portion coordinates.

(69) Here, the rightward deviation threshold value of the left eye coordinates, the rightward deviation threshold value of the right eye coordinates, and the rightward deviation threshold value of the face portion coordinates are predetermined threshold values (for example, constants) which are set as threshold values in determination as to whether or not a position of the person to be photographed deviates to the right side with respect to the photographing unit **120** when seen from the person to be photographed.

(70) Among three conditions including a condition in which the x-coordinate of the left eye is greater than the rightward deviation threshold value of the left eye coordinates, a condition in which the x-coordinate of the right eye is greater than the rightward deviation threshold value of the right eye coordinates, and a condition in which the x-coordinate of the face portion is greater than the rightward deviation threshold value of the face portion coordinates, in a case where it is determined that one or more conditions are satisfied, the difference detection unit **181** determines (detects) that the position of the person to be photographed deviates to a right side with respect to photographing unit **120** when seen from the person to be photographed.

(71) Similarly, among three conditions including a condition in which the x-coordinate of the left eye is less than a leftward deviation threshold value of the left eye coordinates, a condition in which the x-coordinate of the right eye is less than a leftward deviation threshold value of the right eye coordinates, and a condition in which the x-coordinate of the face portion is less than a leftward deviation threshold value of the face portion coordinates, in a case where it is determined one or more conditions are satisfied, the difference detection unit **181** determines (detects) that the

position of the person to be photographed deviates to a left side with respect to photographing unit **120** when seen from the person to be photographed.

(72) Here, the leftward deviation threshold value of the left eye coordinates, the leftward deviation threshold value of the right eye coordinates, and the leftward deviation threshold value of the face portion coordinates are predetermined threshold values (for example, constants) which are set as threshold values in determination as to whether or not the position of the person to be photographed deviates to the left side with respect to the photographing unit **120** when seen from the person to be photographed.

(73) Furthermore, the difference in which the position of the person to be photographed deviates to the right side with respect to the photographing unit **120** when seen from the person to be photographed corresponds to a positional deviation (right) in a “positional deviation (right and left)” in the example of FIG. 4.

(74) In this case, the output unit **130** outputs (for example, displays) a handling method of “please, move to the left side”.

(75) In addition, the difference in which the position of the person to be photographed deviates to the left side with respect to the photographing unit **120** when seen from the person to be photographed corresponds to a positional deviation (left) in the “positional deviation (right and left)” in the example of FIG. 4.

(76) In this case, the output unit **130** outputs (for example, displays) a handling method of “please, move to the right side”.

(77) Furthermore, a method in which the difference detection unit **181** detects a difference in which the position of the person to be photographed deviates in a horizontal direction is not limited to the above-described method.

(78) For example, the difference detection unit **181** may detect the difference in which the position of the person to be photographed deviates in the horizontal direction (deviates to a left side, or deviates to a right side) on the basis of one or more among an x-coordinate of a left ear, an x-coordinate of a right ear, an x-coordinate of a nose, and an x-coordinate of a mouth instead of the x-coordinate of the left eye, the x-coordinate of the right eye, and the x-coordinate of the face portion or in addition to one or more among the x-coordinates.

(79) Furthermore, as the x-coordinate of the face portion, the difference detection unit **181** may use an x-coordinate of the center of the portion, or an x-coordinate of a left end of the portion, or an x-coordinate of a right end of the portion.

(80) The guidance acquisition unit **182** acquires guidance on the basis of the difference that is detected by the difference detection unit **181**, or a candidate of the difference.

(81) For example, as described above, in a case where the difference detection unit **181** detects that the face image of the passport is an eyeglass-wearing face image, the guidance acquisition unit **182** may acquire information indicating processing of displaying the face image of the passport in a manner of emphasizing eyeglasses. In order for the difference detection unit **181** to acquire the information, the difference detection unit **181** or the storage unit **170** stores information, in which a candidate of the difference in which the face image of the passport is the eyeglass-wearing face image (candidate of the difference between wearing and non-wearing of eyeglasses), and the processing of displaying the face image of the passport in the manner of emphasizing the eyeglasses are correlated with each other, in advance.

(82) Furthermore, displaying of the face image of the passport in the manner of emphasizing the eyeglasses corresponds to an example of the guidance that suggests the person be photographed wearing eyeglasses.

(83) Alternatively, as described above, in a case where the difference detection unit **181** detects that the face image captured by the photographing unit **120** is a mask-wearing face image, the guidance acquisition unit **182** may acquire a message of “please, take off the mask”. In order for the difference detection unit **181** to acquire the message, the difference detection unit **181** or the

storage unit **170** may store information, in which a candidate of the difference corresponding to the fact that the face image captured by the photographing unit **120** is the mask-wearing face image (candidate of the difference between wearing and non-wearing of the mask), and the message of “please, take off the mask” are correlated with each other, in advance.

(84) Furthermore, the message “please, take off the mask” corresponds to an example of guidance that suggests the person be photographed without a mask.

(85) Alternatively, as described above, in a case where the difference detection unit **181** detects that the face image captured by the photographing unit **120** is a lateral face image, the guidance acquisition unit **182** may acquire a message of “please, face the front”. Alternatively, in this case, the guidance acquisition unit **182** may acquire information indicating processing of presenting a position of the camera to the person to be photographed.

(86) Alternatively, the guidance acquisition unit **182** acquires guidance that is correlated with the difference detected by the difference detection unit **181** in correlation information.

(87) For example, the correlation information storage unit **171** stores correlation information in which a difference between the image of the passport and the image that is captured by the photographing unit **120**, and a message as guidance are correlated. In addition, the guidance acquisition unit **182** fetches the message as the guidance from the correlation information to acquire the guidance.

(88) Alternatively, the guidance acquisition unit **182** may acquire the guidance by a method other than the method of fetching the guidance from the correlation information. For example, the guidance acquisition unit **182** may fetch the message from the correlation information, and may translate the message into a language which the authentication target uses to acquire the guidance.

(89) In addition, for example, the data acquisition unit **110** may fetch attribute data indicating the nationality of the authentication target from the passport, and may translate the message into a language corresponding to the nationality that is fetched to acquire the guidance of a language corresponding to the nationality. As described above, the guidance acquisition unit **182** may acquire guidance corresponding to attribute indicated by the attribute data that is acquired by the data acquisition unit **110**.

(90) Furthermore, the correlation information storage unit **171** may store the message according to each of a plurality of languages as the guidance in correlation information, and the guidance acquisition unit **182** may fetch a message in a language corresponding to the nationality that is fetched by the data acquisition unit **110** from the correlation information.

(91) The face authentication unit **183** performs the face authentication by using the face image indicated by the face image data that is acquired by the data acquisition unit **110**, and the face image that is captured by the photographing unit **120**. The face authentication unit **183** performs identity verification of the authentication target through the face authentication. That is, the face authentication unit **183** determines whether or not a person of the face image indicated by the face image data that is acquired by the data acquisition unit **110**, and a person indicated by the face image that is captured by the photographing unit **120** are the same person.

(92) Furthermore, the face authentication unit **183** may be constituted as a part of the face authentication device **100**, or a device independent from the face authentication device **100**.

(93) The output control unit **184** controls the output unit **130** in order for the output unit **130** to output the guidance acquired by the guidance acquisition unit **182**.

(94) Furthermore, as in the above-described example, in a case where the face image indicated by the face image data acquired by the data acquisition unit **110** is the eyeglass-wearing image, the output control unit **184** may control the output unit **130** in order for the output unit **130** to output an eyeglass-wearing instruction that recommends the person to be photographed to wear eyeglasses. When the person to be photographed wears the eyeglasses in response to the eyeglass-wearing instruction, it is possible to reduce the probability of an error occurring in the face authentication that is performed by the face authentication unit **183**.

(95) In addition, the output control unit **184** allows the display unit **131** to display the face image indicated by the face image data acquired by the data acquisition unit **110**. In addition, the output control unit **184** may control the output unit **130** in order for the output unit **130** to output a condition adjusting instruction that recommends the person to be photographed to adjust conditions, under which the photographing unit **120** captures the face image, to conditions shown in the face image displayed by the display unit **131**.

(96) For example, in the example of the eyeglass-wearing instruction, the output control unit **184** may allow the display unit **131** to display the face image (face image indicated by the face image data acquired by the data acquisition unit **110**) of the passport.

(97) The person to be photographed can confirm instruction contents of the condition adjusting instruction with reference to the face image by displaying the face image of the passport by the display unit **131**.

(98) In addition, the output control unit **184** may control the output unit **130** in order for the output unit **130** to output difference information indicating the difference that is detected by the difference detection unit **181**. For example, as described above, the output control unit **184** may control the display unit **131** in order for the display unit **131** to display guidance of “facial expression is different”.

(99) According to this, the person to be photographed can understand the difference between the face image of the passport and the face image captured by the photographing unit **120**. When the person to be photographed understands the difference, it is possible to increase the probability of understanding a handling method for the difference (for example, a handling method of reducing the difference).

(100) In addition, the output control unit **184** may allow the display unit **131** to display a portion different between the face image (face image indicated by the face image data acquired by the data acquisition unit **110**) of the passport and the face image captured by the photographing unit **120** as difference information that is shown in any one or both of the face image of the passport and the face image captured by the photographing unit **120**.

(101) For example, in a case where the face image of the passport does not wear eyeglasses, and the face image captured by the photographing unit **120** wears eyeglasses, the display unit **131** may display the eyeglasses on the face image of the passport with a broken line, or may perform emphasizing display such things as the eyeglasses in the face image captured by the photographing unit **120** are surrounded by a broken line in accordance with the control of the output control unit **184**.

(102) According to this, the person to be photographed can more reliably understand a difference between the face image of the passport and the face image captured by the photographing unit **120**, and it is possible to increase the probability that the person to be photographed can understand a handling method for the difference (for example, a handling method of reducing the difference).

(103) In addition, the output control unit **184** may allow the display unit **131** to display an image including the face image (face image indicated by the face image data acquired by the data acquisition unit **110**) of the passport, the latest face image captured by the photographing unit **120**, and display of guidance acquired by the guidance acquisition unit **182**.

(104) The image P21 in FIG. 3 corresponds to an example of the face image of the passport. In addition, the image P23 in FIG. 3 corresponds to an example of the latest face image captured by the photographing unit **120**. In addition, display of a message in the region A21 in FIG. 3 corresponds to an example of the display of guidance acquired by the guidance acquisition unit **182**.

(105) In addition, the output control unit **184** may allow the display unit **131** to display an image including a face image which is captured by the photographing unit **120** and is used in the face authentication by the face authentication unit **183**, and in which an error occurs in the face authentication, the latest face image that is captured by the photographing unit **120**, and display of

the guidance that is acquired by the guidance acquisition unit **182**.

(106) The image P22 in FIG. 3 corresponds to an example of the face image which is captured by the photographing unit **120** and is used in the face authentication by the face authentication unit **183**, and in which an error occurs in the face authentication. In addition, the image P23 in FIG. 3 corresponds to an example of the latest face image that is captured by the photographing unit **120**. In addition, display of a message in the region A21 in FIG. 3 corresponds to an example of the display of the guidance that is acquired by the guidance acquisition unit **182**.

(107) According to this, the person to be photographed can confirm whether or not the cause of an error in the face image, which is captured by the photographing unit **120** and is used in the face authentication by the face authentication unit **183**, and in which an error occurs in the face authentication, is eliminated in the latest face image that is captured by the photographing unit **120**.

(108) In addition, the output control unit **184** may allow the display unit **131** to display an image including the face image (face image indicated by the face image data acquired by the data acquisition unit **110**) of the passport, the face image which is captured by the photographing unit **120** and is used in the face authentication by the face authentication unit **183**, and in which an error occurs in the face authentication, the latest face image captured by the photographing unit **120**, and display of the guidance acquired by the guidance acquisition unit **182**.

(109) The image P21 in FIG. 3 corresponds to an example of the face image of the passport. In addition, the image P22 in FIG. 3 corresponds to an example of the face image which is captured by the photographing unit **120** and is used in the face authentication by the face authentication unit **183**, and in which an error occurs in the face authentication. In addition, the image P23 in FIG. 3 corresponds to an example of the latest face image captured by the photographing unit **120**. In addition, display of a message in the region A21 in FIG. 3 corresponds to an example of display of the guidance acquired by the guidance acquisition unit **182**.

(110) In addition, the output control unit **184** may allow the display unit **131** to display the guidance acquired by the guidance acquisition unit **182** with text information. According to this, the person to be photographed can understand the guidance through reading-out of display of the guidance with the text information.

(111) Display of a message in the region A21 in FIG. 3 corresponds to an example of display of the guidance acquired by the guidance acquisition unit **182** with the text information.

(112) In addition, the output control unit **184** may allow the display unit **131** to display the guidance for the person to be photographed with an icon. Display of the arrow B21 in FIG. 3 corresponds to an example of the icon display of the guidance for the person to be photographed.

(113) In addition, the correlation information storage unit **171** may store correlation information in which a difference in a face position between the face image (face image indicated by the face image data acquired by the data acquisition unit **110**) of the passport and the face image captured by the photographing unit **120**, and guidance representing a direction in which the person to be photographed moves the face to reduce the difference in the face position are correlated with each other. In addition, in a case where the difference detection unit **181** detects the difference in the face position between the face image of the passport and the face image captured by the photographing unit **120**, the output control unit **184** may allow the display unit **131** to display guidance that shows a direction in which the person to be photographed moves (particularly, the face is moved) with an arrow.

(114) Display of the arrow B21 in FIG. 3 corresponds to an example of display of the guidance that shows the direction in which the person to be photographed moves the face with an arrow.

(115) In addition, the output control unit **184** may allow the voice output unit **132** to output the guidance at least with a voice.

(116) According to this, even in a case where the person to be photographed is not looking at the display screen of the display unit **131**, or cannot see the display screen of the display unit **131** due to visual impairment and the like, the person to be photographed can understand the guidance.

(117) In addition, the output control unit **184** may allow the output unit **130** to output an alarm indicating that the output unit **130** outputs the guidance. For example, the output control unit **184** may allow the display unit **131** to display the guidance, and may allow the voice output unit **132** to output a voice message of “please, check guidance”. According to this, it is possible to reduce the probability that the person to be photographed erroneously understand the guidance (for example, the probability that display of the guidance may be overlooked).

(118) Next, a description will be provided of an operation of the face authentication device **100** with reference to FIG. 7. FIG. 7 is a flowchart showing an example of a procedure of processing that is executed by the face authentication device **100**. For example, when the passport is placed on a passport reader device of the data acquisition unit **110**, the face authentication device **100** initiates the processing in the drawing.

(119) In the processing in FIG. 7, the data acquisition unit **110** reads out data from an IC chip that is embedded in the passport (step **S101**). Particularly, the data acquisition unit **110** reads out image data of the face image (face image of the passport), which is registered in advance, from the IC chip.

(120) In addition, the photographing unit **120** photographs an authentication target (person to be photographed) with a camera to acquire a face image (step **S102**).

(121) In addition, the face authentication unit **183** performs face authentication by using the face image indicated by the image data acquired by the data acquisition unit **110**, and the face image captured by the photographing unit **120** (step **S103**).

(122) In addition, the face authentication unit **183** determines whether or not a result of the face authentication can be obtained, or an error has occurred in the face authentication (step **S104**).

(123) In a case where it is determined that the result of the face authentication can be obtained (YES in step **S104**), the face authentication device **100** performs processing based on the authentication result (step **S111**).

(124) For example, in a case where authentication succeeds (that is, in a case where it is determined that the authentication target is the same as a person described in the passport), the face authentication device **100** displays a message indicating that immigration is permitted. In addition, the face authentication device **100** allows a door of a gate to be opened in order for the authentication target to pass through the gate. On the other hand, in a case where the authentication fails (that is, in a case where it is determined that the authentication target is different from the person described in the passport), the face authentication device **100** displays a message that recommends the authentication target to contact an attendant.

(125) After step **S111**, the processing in FIG. 7 is terminated.

(126) On the other hand, in a case where it is determined that an error has occurred in the face authentication (NO in step **S104**), the difference detection unit **181** detects a difference between the face image obtained from the passport in step **S101**, and the face image captured by the photographing unit **120** in step **S102** (step **S121**).

(127) In addition, the guidance acquisition unit **182** acquires guidance representing a handling method with respect to the difference obtained in step **S121** (step **S122**). For example, as described above, the correlation information storage unit **171** stores correlation information in which the difference between the face images, and the guidance representing the handling method with respect to the difference are correlated with each other. In addition, the guidance acquisition unit **182** fetches the guidance, which is correlated with the difference obtained in step **S121**, from the correlation information.

(128) In addition, the output unit **130** outputs the guidance obtained in step **S122** in accordance with a control of the output control unit **184** (step **S123**).

(129) After step **S123**, the processing returns to step **S102**.

(130) Furthermore, in a case where an error occurs predetermined number of times or more, the face authentication device **100** may perform predetermined processing such as displaying of a

message that recommends the authentication target to contact an attendant.

(131) Specifically, the face authentication unit **183** counts the number of times of determination as occurrence of an error in the face authentication in step **S104**, and determines whether or not the number of times is equal to or more than predetermined number of times. In a case where it is determined that the number of times of determination as occurrence of an error in the face authentication in step **S104** is equal to or more than the predetermined times, for example, the output control unit **184** allows the display unit **131** to display a message that recommends the authentication target contact the attendant.

(132) According to this, the face authentication device **100** can handle with a case where it is difficult to eliminate the error in the face authentication.

(133) As described above, the data acquisition unit **110** acquires the face image data. In addition, the photographing unit **120** captures the face image of the authentication target. In addition, the correlation information storage unit **171** stores correlation information, which represents a correlation between the difference between the face image indicated by the face image data acquired by the data acquisition unit **110** and the face image captured by the photographing unit **120**, and the guidance for the person to be photographed with respect to the difference, in advance.

(134) In addition, the difference detection unit **181** detects the difference between the face image indicated by the face image data acquired by the data acquisition unit **110**, and the face image captured by the photographing unit **120**. In addition, the guidance acquisition unit **182** acquires guidance that is correlated with the difference detected by the difference detection unit **181** in correlation information. In addition, the output control unit **184** controls the output unit **130** in order for the output unit **130** to output the guidance acquired by the guidance acquisition unit **182**.

(135) According to this, in a case where the face authentication device **100** cannot appropriately perform the face authentication, it is possible to increase the probability that the authentication target can understand the handling method.

(136) Hereinafter, the above-described various examples will be collectively described.

(137) The data acquisition unit **110** acquires the face image data from the passport.

(138) According to this, it is not necessary to prepare the face image data exclusively for the processing in the face authentication device **100**, and thus a burden on a manager of the face authentication device **100** is reduced in the above-described viewpoint.

(139) In addition, it is not necessary for the storage unit **170** to store the face image data in advance. Due to this viewpoint, storage capacity of the storage unit **170** decreases, and thus the manufacturing cost of the face authentication device **100** is reduced.

(140) In addition, the data acquisition unit **110** acquires attribute data indicating an attribute of the person to be photographed from the passport. In addition, the guidance acquisition unit **182** acquires guidance corresponding to the attribute indicated by the attribute data acquired by the data acquisition unit **110**.

(141) According to this, the face authentication device **100** can output appropriate guidance in correspondence with the attribute of the person to be photographed.

(142) For example, the data acquisition unit **110** acquires the attribute data indicating the nationality of the person to be photographed from the passport. In addition, the guidance acquisition unit **182** acquires guidance of a language corresponding to the nationality indicated by the attribute data.

(143) According to this, the face authentication device **100** can output guidance in a language that can be understood by the person to be photographed.

(144) In addition, in a case where the face image indicated by the face image data acquired by the data acquisition unit **110** is an eyeglass-wearing image, the output control unit **184** controls the output unit **130** in order for the output unit **130** to output an eyeglass-wearing instruction that recommends the person to be photographed to wear eyeglasses.

(145) When the person to be photographed wears eyeglasses in response to the eyeglass-wearing

instruction, a difference between the face image indicated by the face image data acquired by the data acquisition unit **110** and the face image captured by the photographing unit **120** is reduced, and thus it is possible to reduce the probability of an error occurring in the authentication that is performed by the face authentication unit **183**.

(146) Furthermore, before the face authentication unit **183** performs the face authentication, the output control unit **184** may allow the output unit **130** to output the eyeglass-wearing instruction that recommends the person to be photographed to wear eyeglasses.

(147) Alternatively, in a case where the face authentication unit **183** performs the face authentication, and an error occurs in the face authentication, the output control unit **184** may allow the output unit **130** to output the eyeglass-wearing instruction that recommends the person to be photographed to wear eyeglasses. The eyeglass-wearing instruction in this case corresponds to an example of guidance.

(148) In addition, the output control unit **184** allows the output unit **130** to display the face image indicated by the face image data acquired by the data acquisition unit **110**. In addition, the output control unit **184** may control the output unit **130** in order for the output unit **130** to output a condition adjusting instruction that recommends the person to be photographed to adjust conditions, under which the photographing unit **120** captures the face image, to conditions shown in the face image displayed by the display unit **131**.

(149) Since the person to be photographed performs handling of adjusting the conditions, under which the photographing unit **120** captures the face image, to conditions shown in the face image displayed by the display unit **131** according to the condition adjusting instruction, it is possible to reduce the probability of an error occurring in the face authentication performed by the face authentication unit **183**.

(150) In addition, the output control unit **184** controls the output unit **130** in order for the output unit **130** to output difference information indicating the difference that is detected by the difference detection unit **181**.

(151) According to this, the person to be photographed can understand a difference between the face image indicated by the face image data acquired by the data acquisition unit **110**, and the face image captured by the photographing unit **120** with reference to the difference information. When the person to be photographed understands the difference, it is possible to increase the probability capable of understanding a handling method for the difference (for example, a handling method of reducing the difference).

(152) In addition, the output control unit **184** may allow the display unit **131** to display a portion different between the face image indicated by the face image data acquired by the data acquisition unit **110** and the face image captured by the photographing unit **120** as difference information that is shown in any one or both of the face image indicated by the face image data acquired by the data acquisition unit **110** and the face image captured by the photographing unit **120**. For example, in a case where the face image (face image indicated by the face image data acquired by the data acquisition unit **110**) of the passport does not wear eyeglasses, and the face image captured by the photographing unit **120** wears eyeglasses, the display unit **131** may display the eyeglass on the face image of the passport with a broken line, or may perform emphasizing display such things as the eyeglasses in the face image captured by the photographing unit **120** are surrounded with a broken line.

(153) According to this, the person to be photographed can more reliably understand a difference between the face image of the passport and the face image captured by the photographing unit **120**. Since the person to be photographed understands the difference, it is possible to increase the probability that the person to be photographed can understand a handling method for the difference (for example, a handling method of reducing the difference).

(154) In addition, in a case where an error occurs in the face authentication that is performed by the face authentication unit **183**, the difference detection unit **181** can estimate (detect) a difference that

becomes the cause of the face authentication error, the difference being a difference between the face image indicated by the face image data acquired by the data acquisition unit **110** and the face image captured by the photographing unit **120**.

(155) Since the output control unit **184** controls the output unit **130** in order for the output unit **130** to output a handling method corresponding to the difference, the person to be photographed can understand a handling method corresponding to the cause of the face authentication error (for example, a handling method of reducing the difference that becomes the cause of the error in the face authentication).

(156) In addition, the output control unit **184** allows the display unit **131** to display an image including the face image indicated by the face image data acquired by the data acquisition unit **110**, the latest face image captured by the photographing unit **120**, and display of the guidance acquired by the guidance acquisition unit **182**.

(157) Since the display unit **131** displays the guidance, the person to be photographed can understand a handling method for the difference between the face image indicated by the face image data acquired by the data acquisition unit **110** and the face image captured by the photographing unit **120**. In addition, when the display unit **131** displays the face image indicated by the face image data acquired by the data acquisition unit **110**, and the latest face image captured by the photographing unit **120**, the person to be photographed can also understand the difference between the face image indicated by the face image data acquired by the data acquisition unit **110** and the face image captured by the photographing unit **120**, and thus it is possible to increase the probability that the person to be photographed can understand a handling method for the difference.

(158) In addition, the output control unit **184** allows the display unit **131** to display an image including a face image which is captured by the photographing unit **120** and is used in the face authentication by the face authentication unit **183**, and in which an error occurs in the face authentication, the latest face image that is captured by the photographing unit **120**, and display of the guidance that is acquired by the guidance acquisition unit **182**.

(159) According to this, the person to be photographed can confirm whether or not the cause of an error in the face image, which is captured by the photographing unit **120** and is used in the face authentication by the face authentication unit **183** and in which an error occurs in the face authentication, is eliminated in the latest face image that is captured by the photographing unit **120**.

(160) In addition, the output control unit **184** may allow the output unit to display an image including the face image indicated by the face image data acquired by the data acquisition unit **110**, the face image which is captured by the photographing unit **120** and is used in the face authentication by the face authentication unit **183**, and in which an error occurs in the face authentication, the latest face image captured by the photographing unit **120**, and display of the guidance acquired by the guidance acquisition unit **182**.

(161) Since the display unit **131** displays the face image indicated by the face image data acquired by the data acquisition unit **110**, and the face image which is captured by the photographing unit **120** and is used in the face authentication by the face authentication unit **183**, and in which an error occurs in the face authentication, the person to be photographed can confirm a difference between the two face images. Since the person to be photographed confirms the difference, it is expected that the person to be photographed can accurately understand the guidance that is displayed on the display unit **131**.

(162) In addition, the output control unit **184** allows the display unit **131** to display the guidance acquired by the guidance acquisition unit **182** with text information.

(163) According to this, the person to be photographed can understand the guidance through reading-out of display of the guidance with the text information.

(164) In addition, the output control unit **184** allows the display unit **131** to display the guidance for the person to be photographed with an icon.

(165) As described above, the display unit **131** displays the guidance through display of an icon

such as an arrow, various persons to be photographed who use different languages can understand the guidance.

(166) In addition, the correlation information storage unit **171** stores correlation information in which a difference in a face position between the face image indicated by the face image data acquired by the data acquisition unit **110** and the face image captured by the photographing unit **120**, and guidance representing a direction in which the person to be photographed moves the face to reduce the difference in the face position are correlated with each other. In addition, in a case where the difference detection unit **181** detects the difference in the face position between the face image indicated by the face image data acquired by the data acquisition unit **110**, and the face image captured by the photographing unit, the output control unit **184** allows the display unit **131** to display guidance that shows the direction with an arrow.

(167) According to this, various persons to be photographed who use different languages can understand the movement direction.

(168) In addition, the output control unit **184** allows the voice output unit **132** to output the guidance at least with a voice.

(169) According to this, even in a case where the person to be photographed is not looking at the display screen of the display unit **131**, or cannot see the display screen of the display unit **131** due to visual impairment and the like, the person to be photographed can understand the guidance.

(170) In addition, the output control unit **184** allows the output unit **130** to output an alarm indicating that the output unit **130** outputs the guidance.

(171) According to this, it is possible to reduce the probability that the person to be photographed erroneously understand the guidance.

(172) Next, a minimum configuration of the invention will be described with reference to FIG. **8**.

(173) FIG. **8** is a schematic block diagram showing a minimum configuration of the guidance acquisition device according to the invention. A guidance acquisition device shown in the drawing includes a data acquisition unit **11**, a photographing unit **12**, a correlation information storage unit **13**, a difference detection unit **14**, a guidance acquisition unit **15**, and an output control unit **16**.

(174) In the configuration, the data acquisition unit **11** acquires face image data. In addition, the photographing unit **12** captures a face image. In addition, the correlation information storage unit **13** stores correlation information that indicates a correlation between a difference between the face image indicated by the face image data acquired by the data acquisition unit **11** and the face image captured by the photographing unit **12**, and guidance for the person to be photographed with respect to the difference, in advance. In addition, the difference detection unit **14** detects a difference between the face image indicated by the face image data acquired by the data acquisition unit **11** and the face image captured by the photographing unit **12**. In addition, the guidance acquisition unit **15** acquires the guidance that is correlated with the difference detected by the difference detection unit **14** in the correlation information. In addition, the output control unit **16** controls the output unit to output the guidance acquired by the guidance acquisition unit **15**.

(175) According to this, in a case where a device, which performs the face authentication by using the face image indicated by the face image data acquired by the data acquisition unit **11** and the face image captured by the photographing unit **12**, cannot appropriately perform the face authentication, it is possible to increase the probability that the authentication target can understand a handling method.

(176) Furthermore, all functions or partial functions of the control unit **180**, the difference detection unit **14**, the guidance acquisition unit **15**, and the output control unit **16** in the above-described embodiment can be realized when the CPU reads out and executes a program.

(177) In this case, the program for realizing the functions may be recorded in a computer-readable recording medium, and the program recorded in the recording medium may be read out and executed by a computer system to realize the functions.

(178) Furthermore, it is assumed that the “computer system” stated here includes an OS and

hardware such as peripherals.

(179) In addition, the “computer-readable recording medium” represents a storage device such as a portable medium including a flexible disk, a magneto-optical disc, a ROM, a CD-ROM, and the like, and a hard disk drive that is embedded in the computer system.

(180) In addition, the “computer-readable recording medium” may also include a configuration in which a program is dynamically retained for a short time as in a communication line in a case where the program is transmitted through a network such as the Internet and a communication channel such as a telephone line, and a configuration in which the program is retained for a constant time as in a volatile memory in the computer system which becomes a server or a client in this case.

(181) In addition, the program may be configured to realize parts of the above-described functions, may be configured to realize the above-described functions in a combination with a program that is recorded in the computer system in advance, or may be realized by using a programmable logic device such as a field programmable gate array (FPGA).

(182) Hereinbefore, the embodiment of the invention has been described in detail with reference to the accompanying drawings. However, a specific configuration is not limited to the embodiment, and includes a design and the like in a range not departing from the gist of the invention.

(183) The entirety or parts of the above-described embodiment can be described as in the following additional statements, but there is no limitation thereto.

(184) (Additional Statement 1)

(185) A guidance acquisition device, including: a data acquisition unit that is configured to acquire face image data; a photographing unit that is configured to capture a face image; a difference detection unit that is configured to detect a difference between a face image indicated by the face image data acquired by the data acquisition unit and the face image captured by the photographing unit or a candidate of the difference on the basis of at least one of the face image indicated by the face image data acquired by the data acquisition unit and the face image captured by the photographing unit; a guidance acquisition unit that is configured to acquire guidance on the basis of the difference or the candidate of the difference which is detected by the difference detection unit; and an output control unit that is configured to control an output unit to output the guidance that is acquired by the guidance acquisition unit.

(Additional Statement 2)

(186) The guidance acquisition device according to Additional Statement 1, further including: a correlation information storage unit that is configured to store correlation information that indicates a correlation between the difference between the face image indicated by the face image data acquired by the data acquisition unit and the face image captured by the photographing unit, and guidance for a person to be photographed with respect to the difference, in advance, wherein the difference detection unit is configured to detect the difference between the face image indicated by the face image data acquired by the data acquisition unit, and the face image captured by the photographing unit, and the guidance acquisition unit is configured to acquire guidance that is correlated with the difference detected by the difference detection unit in the correlation information.

(Additional Statement 3)

(187) The guidance acquisition device according to Additional Statement 1 or 2, wherein the data acquisition unit is configured to acquire the face image data from a passport.

(Additional Statement 4)

(188) The guidance acquisition device according to Additional Statement 3, wherein the data acquisition unit is configured to acquire attribute data indicating an attribute of a person to be photographed from the passport, and the guidance acquisition unit is configured to acquire guidance corresponding to the attribute indicated by the attribute data acquired by the data acquisition unit.

(Additional Statement 5)

(189) The guidance acquisition device according to Additional Statement 4, wherein the data acquisition unit is configured to acquire the attribute data indicating the nationality of the person to be photographed, and the guidance acquisition unit is configured to acquire guidance in a language corresponding to the nationality.

(Additional Statement 6)

(190) The guidance acquisition device according to any one of Additional Statements 1 to 5, wherein in a case where the face image indicated by the face image data acquired by the data acquisition unit is an eyeglass-wearing image, the output control unit is configured to control the output unit to output an eyeglass-wearing instruction that recommends a person to be photographed to wear eyeglasses.

(Additional Statement 7)

(191) The guidance acquisition device according to any one of Additional Statements 1 to 6, wherein the output control unit is configured to control the output unit in order for the output unit to display the face image indicated by the face image data acquired by the data acquisition unit, and control the output unit to output a condition adjusting instruction that recommends a person to be photographed to adjust conditions, under which the photographing unit is configured to capture the face image, to conditions shown in the face image that is displayed by the output unit.

(Additional Statement 8)

(192) The guidance acquisition device according to any one of Additional Statements 1 to 7, wherein the output control unit is configured to control the output unit to output difference information indicating the difference detected by the difference detection unit.

(Additional Statement 9)

(193) The guidance acquisition device according to Additional Statement 8, wherein the output control unit is configured to control the output unit to display a portion different between the face image indicated by the face image data acquired by the data acquisition unit and the face image captured by the photographing unit as difference information that is shown in at least any one of the face image indicated by the face image data acquired by the data acquisition unit and the face image captured by the photographing unit.

(Additional Statement 10)

(194) The guidance acquisition device according to any one of Additional Statements 1 to 9, further including: a face authentication unit that is configured to perform face authentication using the face image indicated by the face image data acquired by the data acquisition unit, and the face image captured by the photographing unit, wherein in a case where an error occurs in the face authentication that is performed by the face authentication unit, the difference detection unit is configured to detect a difference that becomes the cause of the face authentication error, the difference being the difference between the face image indicated by the face image data acquired by the data acquisition unit and the face image captured by the photographing unit.

(Additional Statement 11)

(195) The guidance acquisition device according to any one of Additional Statements 1 to 10, wherein the photographing unit is configured to perform capturing of the face image repetitively, and the output control unit is configured to control the output unit to display an image including the face image indicated by the face image data acquired by the data acquisition unit, the latest face image captured by the photographing unit, and display of the guidance acquired by the guidance acquisition unit.

(Additional Statement 12)

(196) The guidance acquisition device according to Additional Statement 10, the photographing unit is configured to perform capturing of the face image repetitively, and the output control unit is configured to control the output unit to display an image including a face image which is captured by the photographing unit and is used in the face authentication by the face authentication unit, and

in which an error occurs in the face authentication, the latest face image that is captured by the photographing unit, and display of the guidance that is acquired by the guidance acquisition unit.
(Additional Statement 13)

(197) The guidance acquisition device according to Additional Statement 10, wherein the photographing unit is configured to perform capturing of the face image repetitively, and the output control unit is configured to control the output unit to display an image including the face image indicated by the face image data acquired by the data acquisition unit, a face image which is captured by the photographing unit and is used in the face authentication by the face authentication unit, and in which an error occurs in the face authentication, the latest face image that is captured by the photographing unit, and display of the guidance that is acquired by the guidance acquisition unit.

(Additional Statement 14)

(198) The guidance acquisition device according to any one of Additional Statements 1 to 13, wherein the output control unit is configured to control the output unit to display the guidance acquired by the guidance acquisition unit with text information.

(Additional Statement 15)

(199) The guidance acquisition device according to any one of Additional Statements 11 to 14, wherein the output control unit is configured to control the output unit to display the guidance for a person to be photographed with an icon.

(Additional Statement 16)

(200) The guidance acquisition device according to Additional Statement 15, wherein the correlation information storage unit is configured to store correlation information in which a difference in a face position between the face image indicated by the face image data acquired by the data acquisition unit and the face image captured by the photographing unit, and guidance representing a direction in which the person to be photographed moves the face to reduce the difference in the face position are correlated with each other, and in a case where the difference detection unit detects the difference in the face position between the face image indicated by the face image data acquired by the data acquisition unit and the face image captured by the photographing unit, the output control unit controls the output unit to display the guidance that shows the direction with an arrow.

(Additional Statement 17)

(201) The guidance acquisition device according to any one of Additional Statements 1 to 16, wherein the output control unit is configured to control the output unit to output the guidance at least with a voice.

(Additional Statement 18)

(202) The guidance acquisition device according to any one of Additional Statements 1 to 17, wherein the output control unit is configured to control the output unit to output an alarm indicating that the output unit outputs the guidance

(Additional Statement 19)

(203) A guidance acquisition method that is executed by a guidance acquisition device including a correlation information storage unit that is configured to store correlation information that indicates a correlation between a difference between a face image indicated by face image data and a face image obtained through photographing, and guidance for a person to be photographed with respect to the difference, in advance, the method including: a data acquisition step of acquiring the face image data; a photographing step of capturing the face image; a difference detection step of detecting the difference between the face image indicated by the face image data acquired in the data acquisition step, and the face image captured in the photographing step; a guidance acquisition step of acquiring guidance that represents guidance correlated with the difference detected in the difference detection step in the correlation information; and an output control step of controlling an output unit to output the guidance acquired in the guidance acquisition step.

(Additional Statement 20)

(204) A program that causes a computer including a photographing unit, and a correlation information storage unit that is configured to store correlation information that indicates a correlation between a difference between a face image indicated by face image data and a face image obtained through photographing, and guidance for a person to be photographed with respect to the difference in advance to execute: a data acquisition step of acquiring the face image data; a photographing step of capturing the face image by the photographing unit; a difference detection step of detecting the difference between the face image indicated by the face image data acquired in the data acquisition step, and the face image captured in the photographing step; a guidance acquisition step of acquiring guidance correlated with the difference detected in the difference detection step in the correlation information; and an output control step of controlling an output unit to output the guidance acquired in the guidance acquisition step.

INDUSTRIAL APPLICABILITY

(205) According to the invention, in a case where a device that is configured to perform face authentication cannot appropriately perform the face authentication, it is possible to increase the probability that an authentication target can understand a handling method.

REFERENCE SIGNS LIST

(206) **10** Guidance acquisition device **11, 110** Data acquisition unit **12, 120** Photographing unit **13, 171** Correlation information storage unit **14, 181** Difference detection unit **15, 182** Guidance acquisition unit **16, 184** Output control unit **100** Face authentication device **130** Output unit **131** Display unit **132** Voice output unit **170** Storage unit **180** Control unit **183** Face authentication unit

Claims

1. A face authentication system comprising: a camera configured to capture face images of a target; a reader configured to read a face image from an identification document or an integrated circuit (IC) chip embedded within the identification document; a memory storing instructions; and a processor configured to execute the instructions to: control the reader to acquire a read face image; before the face image is actually captured by the camera, detect based on the read face image, a difference candidate between a face image of the target and the read face image, output, based on the read face image, a first guidance comprising instructions on reducing a probability of an error in face authentication using the face image of the target and the read face image, and display an image of the read face image in which a portion corresponding to the detected difference candidate is emphasized; control the camera to capture the face image of the target; perform the face authentication using the face of the target captured by the camera and the read face image; control a gate to open when the error has been determined to not have occurred in the face authentication, and output a second guidance different from the first guidance when the face authentication fails; and output, when the error has been determined to have occurred in the face authentication, a third guidance different from the first guidance and the second guidance, and re-perform the face authentication by controlling the camera to capture the face image of the target again.
2. The face authentication system according to claim 1, wherein the processor is configured to: acquire the read face image and attribute data of the target from a passport or the integrated circuit chip embedded within the passport; and output the first guidance corresponding to an attribute indicated by the attribute data.
3. The face authentication system according to claim 1, wherein the processor is further configured to: store the first guidance corresponding to the difference candidate for each difference candidate; and acquire the stored first guidance corresponding to the detected difference candidate, and output the acquired first guidance.
4. The face authentication system according to claim 1, wherein the processor is further configured to: detect a difference in facial expression between the read face image and the captured face

image, and wherein the processor is configured to output the third guidance that recommends the target to make the facial expression expressionless.

5. The face authentication system according to claim 1, wherein the processor is further configured to: detect, as a difference, whether or not a mask is worn between the read face image and the captured face image, and wherein the processor is configured to output the third guidance that recommends the target to take off the mask.

6. The face authentication system according to claim 1, wherein the processor is further configured to: detect a distance between the target and the camera based on a gap size between two eyes of the target in the captured face image; and wherein the processor is configured to output the third guidance corresponding to the detected distance.

7. The face authentication system according to claim 1, wherein the processor is configured to: output the first guidance including a condition adjusting instruction that recommends the target to adjust a capturing condition for the camera to a condition shown in the read face image.

8. The face authentication system according to claim 1, wherein the processor is further configured to: detect a difference in a face position between the read face image and the captured face image, and wherein the processor is configured to output the third guidance indicating a movement direction for the target.

9. The face authentication system according to claim 1, wherein the processor is configured to: output the second guidance for the target to contact an attendant when the error occurs a predetermined number of times.

10. A face authentication method performed by a computer and comprising: controlling a reader, which reads out a face image from an identification document or an integrated circuit (IC) chip embedded within the identification document, to acquire a read face image; before the face image is actually captured by a camera, detecting based on the read face image, a difference candidate between a face image of a target and the read face image, outputting, based on the read face image, a first guidance comprising instructions on reducing a probability of an error in face authentication using the face image of the target and the read face image, and displaying an image of the read face image in which a portion corresponding to the detected difference candidate is emphasized; controlling the camera to acquire the face image of the target; performing the face authentication using the face of the target captured by the camera and the read face image; controlling a gate to open when the error has been determined to not have occurred in the face authentication, and output a second guidance different from the first guidance when the face authentication fails; and outputting, when the error has been determined to have occurred in the face authentication, a third guidance different from the first guidance and the second guidance, and re-perform the face authentication by controlling the camera to capture the face image of the target again.

11. A non-transitory computer-readable storage medium storing a program executable by a computer to perform a process comprising: controlling a reader, which reads out a face image from an identification document or an integrated circuit (IC) chip embedded within the identification document, to acquire a read face image; before the face image is actually captured by a camera, detecting based on the read face image, a difference candidate between a face image of a target and the read face image, outputting, based on the read face image, a first guidance comprising instructions on reducing a probability of an error in face authentication using the face image of the target and the read face image, and displaying an image of the read face image in which a portion corresponding to the detected difference candidate is emphasized; controlling the camera to acquire the face image of the target; performing the face authentication using the face of the target captured by the camera and the read face image; controlling a gate to open when the error has been determined to not have occurred in the face authentication, and output a second guidance different from the first guidance when the face authentication fails; and outputting, when the error has been determined to have occurred in the face authentication, a third guidance different from the first guidance and the second guidance, and re-perform the face authentication by controlling the

camera to capture the face image of the target again.

12. The face authentication system according to claim 1, wherein the processor is further configured to: display an image obtained by horizontally inverting the face image of the target captured by the camera while displaying the read face image, and output the first guidance.

13. The face authentication system according to claim 12, wherein the first guidance comprises information that the camera is in a process of capturing the target, in addition to the instructions on reducing the probability of the error.
