

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409672
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Naoi; Shinya et al.

Image forming apparatus and control method of image forming apparatus

Abstract

An image forming apparatus includes: a main part that forms an image on a continuous medium in a state in which a tension is applied to the continuous medium, the continuous medium being fed from a first roll and conveyed to be taken up on a second roll; and a tension maintaining part that maintains the tension of the continuous medium at the main part during a manipulation for replacing at least one of the first roll and the second roll.

Inventors: Naoi; Shinya (Tokyo, JP), Okuzawa; Sho (Tokyo, JP), Soda; Sho (Tokyo, JP)

Applicant: Konica Minolta, Inc. (Tokyo, JP)

Family ID: 88792033

Assignee: KONICA MINOLTA, INC. (Tokyo, JP)

Appl. No.: 18/317454

Filed: May 15, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230373231 A1	Nov. 23, 2023

Foreign Application Priority Data

JP	2022-081574	May. 18, 2022
----	-------------	---------------

Publication Classification

Int. Cl.: B65H19/20 (20060101); B41J15/16 (20060101); G03G15/00 (20060101)

U.S. Cl.:

CPC **B41J15/16** (20130101); **B65H19/20** (20130101); **G03G15/6517** (20130101);
G03G15/652 (20130101);

Field of Classification Search

CPC: B41J (15/16); G03G (15/6517); G03G (15/652); B65H (19/20)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2003/0209629	12/2002	Hirata	242/554.2	B65H 19/1852
2007/0051264	12/2006	Sakamoto	101/484	B41J 15/16
2016/0136976	12/2015	Shinjo	347/104	B41J 15/16

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2004035226	12/2003	JP	B65H 23/182
2018005194	12/2017	JP	N/A

Primary Examiner: Ameh; Yaovi M

Attorney, Agent or Firm: CANTOR COLBURN LLP

Background/Summary

CROSS REFERENCES TO RELATED APPLICATIONS

(1) The present invention claims priority under 35 U.S.C. § 119 to Japanese Application, 2022-081574, filed on May 18, 2022, the entire contents of which being incorporated herein by reference.

BACKGROUND

Technological Field

(2) The present invention relates to an image forming apparatus and a control method of the image forming apparatus.

Description of Related Art

(3) In some image forming apparatuses such as those of an electrophotographic system and an ink jet system, a continuous medium such as a roll sheet or a continuous form is conveyed in a roll-to-roll manner to form an image on the conveyed continuous medium.

(4) In the image forming apparatuses described above, the continuous medium is conveyed while a predetermined tension is applied to the continuous medium such that the continuous medium can be conveyed along a conveyance path. This prevents the continuous medium from entering a portion other than the conveyance path.

(5) For example, in the image forming apparatuses such as those of an electrophotographic system or an inkjet system, there is a possibility that a conveyance trouble such as a jam may occur when the continuous medium enters the portion other than the conveyance path. Further, the image forming apparatuses of the electrophotographic system include a fixing part for fixing a formed

image, and when the continuous medium enters a high-temperature portion of the fixing part, the continuous medium may be deformed or discolored.

(6) In order not to cause the above-described problems, a predetermined tension is applied to the continuous medium and image formation is performed by controlling the fixing part to a predetermined temperature only when the predetermined tension is applied to the continuous medium.

(7) The above-described image forming apparatuses include a supply roll that supplies the continuous medium to an apparatus main part, a take-up roll that takes up the continuous medium supplied to the apparatus main part, and/or the like. The supply roll is replaced in accordance with, for example, the remaining amount of the continuous medium in the supply roll, and the take-up roll is replaced in accordance with, for example, the take-up amount of the continuous medium in the take-up roll.

(8) In the above-described image forming apparatuses, when the supply roll or the take-up roll is replaced, the continuous medium is cut in the vicinity of the supply roll or the take-up roll. Accordingly, a predetermined tension cannot be applied to the continuous medium. For example, in an image forming apparatus disclosed in Japanese Patent Application Laid-Open No. 2018-005194, a fixing part is brought into a stopped state in order to reduce deformation or the like of the continuous medium in a case where a predetermined tension cannot be applied to the continuous medium as described above.

(9) Meanwhile, since a predetermined tension cannot be applied to the continuous medium at the time of roll replacement as described above, a configuration related to image formation, for example, the fixing part or the like, is brought into the stopped state. Since the configuration related to the image formation is in the stopped state, a preliminary operation for stabilizing the configuration related to the image formation (for example, warm-up for raising the temperature of the fixing part to a predetermined temperature, or the like) is required after the roll replacement. The preliminary operation requires a long waiting time before completion of the preliminary operation, and when the preliminary operation is performed after the roll replacement, the downtime of the apparatus becomes longer. Therefore, it is demanded that the preliminary operation can be performed without stopping the configuration related to image formation at the time of roll replacement, and the downtime of the apparatus is reduced.

SUMMARY

(10) An object of the present invention is to provide an image forming apparatus and a control method of the image forming apparatus capable of reducing downtime of the apparatus.

(11) An image forming apparatus in which one aspect of the present invention is reflected in an attempt to at least partly achieve the above-mentioned object includes: a main part that forms an image on a continuous medium in a state in which a tension is applied to the continuous medium, the continuous medium being fed from a first roll and conveyed to be taken up on a second roll; and a tension maintaining part that maintains the tension of the continuous medium at the main part during a manipulation for replacing at least one of the first roll and the second roll.

(12) A control method of an image forming apparatus in which one aspect of the present invention is reflected in an attempt to at least partly achieve the above-mentioned object includes: forming an image on a continuous medium by a main part in a state in which a tension is applied to the continuous medium, the continuous medium being fed from a first roll and conveyed to be taken up on a second roll; operating a tension maintaining part to maintain the tension of the continuous medium at the main part during a manipulation for replacing at least one of the first roll and the second roll.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) The advantages and features provided by one or more embodiments of the invention will become more fully understood from the detailed description given hereinbelow and the appended drawings which are given by way of illustration only, and thus are not intended as a definition of the limits of the present invention.
- (2) FIG. 1 is a diagram schematically illustrating an overall configuration of an image forming apparatus according to an embodiment of the present invention and illustrates a printing standby state of the apparatus.
- (3) FIG. 2 is a diagram illustrating a printing state of the image forming apparatus illustrated in FIG. 1.
- (4) FIG. 3 is a diagram illustrating a roll replacement state of the image forming apparatus illustrated in FIG. 1.
- (5) FIG. 4 is a diagram illustrating a steady state of the image forming apparatus illustrated in FIG. 1.
- (6) FIG. 5 is a block diagram illustrating a principal part of a control system of the image forming apparatus illustrated in FIG. 1.
- (7) FIG. 6 is an explanatory view for explaining a transition to each apparatus state of the image forming apparatus illustrated in FIG. 1.
- (8) FIG. 7 is a flowchart illustrating a transition from the printing standby state to the roll replacement state in the image forming apparatus illustrated in FIG. 1.
- (9) FIG. 8 is a diagram illustrating a supply part of the image forming apparatus in a case where the continuous medium is held by a holding part in the order according to the flowchart illustrated in FIG. 7.
- (10) FIG. 9 is a diagram illustrating the supply part of the image forming apparatus in a case where the rotation of a motor of a tension applying part is stopped in the order according to the flowchart illustrated in FIG. 7.
- (11) FIG. 10 is a diagram illustrating the supply part of the image forming apparatus in a case where processing is performed in a different order from the flowchart illustrated in FIG. 7.
- (12) FIG. 11 is a flowchart for explaining a transition from the roll replacement state to the printing standby state in the image forming apparatus illustrated in FIG. 1.
- (13) FIG. 12 is a diagram illustrating the supply part of the image forming apparatus in a case where the motor of the tension applying part is rotated and tension is applied to the continuous medium in the order according to the flowchart illustrated in FIG. 11.
- (14) FIG. 13 is a diagram illustrating the supply part of the image forming apparatus in the case where the holding of the continuous medium by the holding part is released in the order according to the flowchart illustrated in FIG. 11.
- (15) FIG. 14 is a diagram illustrating the supply part of the image forming apparatus in a case where the processing is performed in a different order from the flowchart illustrated in FIG. 11.
- (16) FIG. 15 is a flowchart illustrating a transition from the roll replacement state to the steady state in the image forming apparatus illustrated in FIG. 1.

DETAILED DESCRIPTION OF EMBODIMENTS

- (17) Hereinafter, one or more embodiments of the present invention will be described with reference to the drawings. However, the scope of the invention is not limited to the disclosed embodiments.
- (18) Hereinafter, an embodiment of the present invention will be described in detail with reference to the drawings.
- (19) Configuration of Image Forming Apparatus
- (20) FIG. 1 to FIG. 4 are diagrams schematically illustrating the entire configuration of image forming apparatus 1 according to the present embodiment, and respectively illustrate a printing

standby state, a printing state, a roll replacement state, and a steady state of the image forming apparatus. FIG. 5 is a block diagram illustrating a principal part of a control system of image forming apparatus **1** according to the present embodiment.

(21) Image forming apparatus **1** is capable of forming an image on continuous medium **S**, which is, for example, a continuous sheet, cloth (fabric), recording medium made of resin, or the like. Accordingly, as illustrated in FIGS. **1** to **4**, image forming apparatus **1** includes image-forming-apparatus main part **100** (the main part in the present invention), supply part **70**, and collection part **80**. Supply part **70** supplies continuous medium **S** wound in a roll form to image-forming-apparatus main part **100**, and collection part **80** collects continuous medium **S** in a roll form from image-forming-apparatus main part **100**.

(22) Image-forming-apparatus main part **100** is a color image forming apparatus of an intermediate transfer system using electrophotographic process technology. That is, image-forming-apparatus main part **100** transfers (primary-transfers) toner images of colors of CMYK formed on a photoconductor to an intermediate transfer member and superimposes the toner images of the four colors on one another on the intermediate transfer member. Then, image-forming-apparatus main part **100** secondary-transfers the resultant image to continuous medium **S**, thereby forming an image. Note that, "CMYK" represents C (cyan), M (magenta), Y (yellow), and K (black).

(23) A longitudinal tandem system is adopted for image-forming-apparatus main part **100**. By way of example, in the longitudinal tandem system, the respective photoconductors corresponding to the four colors of CMYK are placed in series in the travelling direction of the intermediate transfer member, and the toner images of the four colors are sequentially transferred to the intermediate transfer member in one cycle.

(24) As illustrated in FIG. 5, image forming apparatus **1** includes operation/display part **20**, image processing part **30**, image forming part **40**, conveyance part **50**, fixing part **60**, supply part **70**, collection part **80**, control part **200** (hardware processor), communication part **211**, storage part **212**, and the like.

(25) Control part **200** includes central processing unit (CPU) **201**, read only memory (ROM) **202**, random access memory (RAM) **203** and the like. CPU **201** reads a program suited to processing contents out of ROM **202**, loads the program into RAM **203**, and integrally controls an operation of each block of image forming apparatus **1** in cooperation with the loaded program. Upon this control, various data such as a Look Up Table (LUT) stored in storage part **212** is referred to. Storage part **212** is composed of, for example, a non-volatile semiconductor memory (so-called flash memory) or a hard disk drive.

(26) Control part **200** transmits and receives various data to and from an external apparatus (for example, a personal computer) connected to a communication network such as a local area network (LAN) or a wide area network (WAN), through communication part **211**. Control part **200** receives, for example, image data transmitted from the external apparatus, and performs control to form an image on continuous medium **S** based on this image data (input image data). Communication part **211** is composed of, for example, a communication control card such as a LAN card.

(27) Control part **200** is connected with an operation/display part **20**, image processing part **30**, image forming part **40**, conveyance part **50**, fixing part **60**, supply part **70**, collection part **80**, communication part **211**, and storage part **212**. These parts perform predetermined processing based on an instruction from control part **200**.

(28) In image-forming-apparatus main part **100**, operation/display part **20** includes, for example, a liquid crystal display (LCD) provided with a touch panel, and functions as display part **21** and operation part **22**. Display part **21** displays various operation screens, image conditions, operating statuses of each function, and/or the like in accordance with display control signals input by control part **200**. Operation part **22** equipped with various operation keys, such as a numeric keypad and a start key, receives various input operations by users and outputs operation signals to control part **200**.

(29) Image processing part **30** includes a circuit and/or the like that, in accordance with default settings or user settings, performs predetermined image processing on input image data transmitted, for example, from an external apparatus. Image forming part **40** is controlled based on the image data that has been subjected to the image processing.

(30) Image-forming-apparatus main part **100** may include an image reading part including an Auto Document Feeder (ADF), document image scanning device (scanner), and the like. The auto document feeder conveys, with a conveyance part, a document placed on a document tray, to send out the document to the document image scanner. The document image scanner optically scans the document conveyed from the auto document feeder to read a document image. Then, the image reading part generates input image data based on a result read by the document image scanner. In this case, image processing part **30** may perform the above-described predetermined image processing on the input image data generated by the image reading part.

(31) Image forming part **40** includes image forming unit **41**, intermediate transfer unit **42**, secondary transfer unit **43**, and the like. Based on the image data from the image processing part **30**, image forming unit **41Y** forms an image of a Y-component colored toner. Similarly, image forming unit **41M** forms an image using an M-component colored toner, image forming unit **41C** forms an image using a C-component colored toner, and image forming unit **41K** forms an image using a K-component colored toner.

(32) Image forming units **41Y**, **41M**, **41C**, and **41K** have the same configuration. Specifically, image forming units **41Y**, **41M**, **41C**, and **41K** include exposing devices **411**, developing devices **412**, photoconductor drums **413**, charging devices **414**, drum cleaning devices **415**, and the like, respectively. In FIG. 1 to FIG. 4, reference numerals of the exposing devices, the developing devices, the photoconductor drums, the charging devices, and the drum cleaning devices in image forming units **41M**, **41C**, and **41K** are omitted. Further, a known technique can be employed as exposing devices **411**, developing devices **412**, photoconductor drums **413**, charging devices **414**, and drum cleaning devices **415**, and thus detailed description thereof is omitted here.

(33) Intermediate transfer unit **42** includes intermediate transfer belt **421** and the like. Intermediate transfer belt **421** is wound under tension around a plurality of support rollers in a loop form and travels in the direction of arrow A (see FIG. 2). The plurality of support rollers include rollers such as a backup roller, a primary transfer roller, and a driving roller. Illustration of these rollers are omitted here. Intermediate transfer belt **421** is brought into pressure contact with photoconductor drums **413**, whereby toner images from photoconductor drums **413** are transferred to intermediate transfer belt **421**.

(34) Note that intermediate transfer unit **42** may be configured to include a belt cleaning device including a plate-shaped belt cleaning blade or the like that makes sliding contact with the surface of intermediate transfer belt **421**. The belt cleaning device removes transfer residual toner and the like remaining on the surface of intermediate transfer belt **421** after the secondary transfer.

(35) Secondary transfer unit **43** includes secondary transfer roller **431** and the like. Secondary transfer roller **431** is pressed against intermediate transfer belt **421**. As a result, a secondary transfer nip is formed between intermediate transfer belt **421** and secondary transfer roller **431**.

(36) In secondary transfer unit **43**, when continuous medium S is conveyed to the secondary transfer nip, the toner images of the respective colors carried on intermediate transfer belt **421** are collectively transferred onto continuous medium S. Continuous medium S on which the toner image is transferred is conveyed toward fixing part **60** by secondary transfer roller **431**.

(37) Secondary transfer unit **43** may be a belt-type secondary transfer unit having a secondary transfer belt or the like wound under tension around a plurality of support rollers, instead of a roller-type secondary transfer unit having secondary transfer roller **431** or the like.

(38) Conveyance part **50** includes a plurality of conveyance rollers **51** and **52**, a conveyance guide, and the like, although a part of the conveyance part is not illustrated. Conveyance part **50** conveys continuous medium S supplied from supply part **70** to image forming part **40** (secondary transfer

nip) and fixing part **60**. Then, continuous medium S on which an image is formed via image forming part **40** (secondary transfer nip) and fixing part **60** is conveyed to collection part **80**.

(39) Fixing part **60** includes fixing roller **61**, pressurizing roller **62**, and the like. Fixing roller **61** and pressurizing roller **62** are configured to vertically move to be separated from continuous medium S or to nip continuous medium S.

(40) Fixing roller **61** is heated to a predetermined fixing temperature, and pressurizing roller **62** forms a fixing nip for nipping and conveying continuous medium S between the pressurizing roller and fixing roller **61**. In this fixing part **60**, conveyed continuous medium S on which toner images are secondary-transferred is heated and pressurized at the fixing nip, to fix the toner images on continuous medium S.

(41) Supply part **70** is disposed on the upstream side of image-forming-apparatus main part **100** in conveyance direction T (see FIG. 2) in which continuous medium S is conveyed. Supply part **70** includes first roll **71**, tension applying part **72**, tension adjustment part **73**, tension detection part **74**, splice table **75**, driven roller **76**, and the like.

(42) The configuration and operation of supply part **70** will be described later. Supply part **70** is configured to feed continuous medium S wound around first roll **71** in a state where a predetermined tension is applied to the continuous medium, to supply continuous medium S to image-forming-apparatus main part **100**.

(43) Collection part **80** is disposed on the downstream side of image-forming-apparatus main part **100** in conveyance direction T. Collection part **80** includes second roll **81**, tension applying part **82**, tension adjustment part **83**, tension detection part **84**, nip rollers **85**, and the like.

(44) The configuration and operation of collection part **80** will be described later. Collection part **80** is configured to collect continuous medium S by taking up, on second roll **81**, continuous medium S on which an image is formed in image-forming-apparatus main part **100** and that is discharged from image-forming-apparatus main part **100**, in a state where a predetermined tension is applied to the continuous medium.

(45) Supply part **70** feeds continuous medium S from first roll **71** in a state where a predetermined tension is applied to the continuous medium, and collection part **80** takes up continuous medium S around second roll **81** in a state where a predetermined tension is applied. Thus, continuous medium S is conveyed. In this way, image-forming-apparatus main part **100** forms an image on continuous medium S conveyed in a state where a tension is applied to the continuous medium.

(46) Meanwhile, in the conventional image forming apparatus, as described above, a predetermined tension cannot be applied to the continuous medium at the time of roll replacement, and therefore, the configuration related to image formation, for example, a fixing part or the like, is brought into a stopped state. Since the configuration related to the image formation is brought into the stopped state, a preliminary operation such as warm-up for stabilizing the configuration related to the image formation is required after the roll replacement. The preliminary operation requires a long waiting time before completion of the preliminary operation, and when the preliminary operation is performed after the roll replacement, the downtime of the apparatus becomes longer. Therefore, it is demanded that the preliminary operation can be performed without stopping the configuration related to image formation at the time of roll replacement, and the downtime of the apparatus is reduced.

(47) Therefore, in the present embodiment, image forming apparatus **1** includes tension maintaining parts **701** and **801** that maintain the tension of continuous medium S in image-forming-apparatus main part **100** at the time of a manipulation for replacing at least one of first roll **71** and second roll **81**. The manipulation for replacing at least one of first roll **71** and second roll **81** is, for example, an operation for transitioning to the roll replacement state described below. Tension maintaining parts **701** and **801** include at least a tension applying part and a holding part which will be described below. Further, tension maintaining parts **701** and **801** may further include a tension adjustment part described below.

(48) Although the details will be described below, in the present embodiment, tension applying part **72** of supply part **70** and tension applying part **82** of collection part **80** are used as tension applying parts. As the holding part, holding part **751** (first clamp **75a** and table **75c**) in splice table **75** of supply part **70** is used. As the holding part, holding part **851** (first nip roller **85a** and second nip roller **85b**) in nip rollers **85** of collection part **80** is used. As the tension adjustment part, tension adjustment part **73** of supply part **70** and tension adjustment part **83** of collection part **80** are used.

(49) Configuration and Operation of Supply Part and Collection Part

(50) The configuration and operation of supply part **70** and collection part **80** will be described with reference to FIG. **1** to FIG. **4**.

(51) As described above, supply part **70** includes first roll **71**, tension applying part **72**, tension adjustment part **73**, tension detection part **74**, splice table **75**, driven roller **76**, and the like. Supply part **70** is configured to feed continuous medium **S** wound around first roll **71**, in a state where a predetermined tension is applied to the continuous medium, to supply continuous medium **S** to image-forming-apparatus main part **100**.

(52) Further, collection part **80** includes second roll **81**, tension applying part **82**, tension adjustment part **83**, tension detection part **84**, nip rollers **85**, and the like. Collection part **80** is configured to collect continuous medium **S** by taking up, on second roll **81**, continuous medium **S** on which an image is formed in image-forming-apparatus main part **100** and that is discharged from image-forming-apparatus main part **100**, in a state where a predetermined tension is applied to the continuous medium.

(53) Tension applying part **72** of supply part **70** and tension applying part **82** of collection part **80** apply a predetermined tension to continuous medium **S** from opposite end portion sides of continuous medium **S**.

(54) Although not illustrated, tension applying part **72** of supply part **70** includes a rotation drive shaft, a clutch, a motor, and the like, which are controlled by control part **200**. First roll **71** has a roll shape around which continuous medium **S** is wound and is configured to be attachable to and detachable from the rotation drive shaft.

(55) The rotation drive shaft holds first roll **71** attached to the outer periphery thereof such that the first roll is rotatable and rotates in a direction in which continuous medium **S** is pulled (take-up direction) in the printing standby state (see FIG. **1**) and the printing state (see FIG. **2**). The direction of pulling is a clockwise direction (see dotted arrow) in FIG. **1** and FIG. **2**.

(56) The rotation drive shaft is rotationally driven by the motor via the clutch. The clutch transmits or interrupts rotation from the motor to the rotation drive shaft, and is, for example, a powder clutch.

(57) When the torque of the powder clutch is less than a predetermined torque, the powder clutch connects an input side to an output side of the powder clutch and transmits the rotation from the motor to the rotation drive shaft. On the other hand, when the torque of the powder clutch is equal to or higher than the predetermined torque, the powder clutch disconnects the input side from the output side, and the transmission of the rotation from the motor to the rotation drive shaft is interrupted.

(58) The motor rotates in the direction of pulling continuous medium **S**, and the powder clutch is connected or disconnected depending on whether or not the torque is less than the predetermined torque. Therefore, the motor pulls continuous medium **S** with the predetermined torque through the powder clutch, and the predetermined tension is applied to continuous medium **S**.

(59) Tension applying part **82** of collection part **80** has the same configuration as tension applying part **72** of supply part **70**, and includes a rotation drive shaft, a clutch, a motor, and the like (not illustrated), which are also controlled by control part **200**. Second roll **81** takes up continuous medium **S** in a roll shape and is configured to be attachable to and detachable from the rotation drive shaft.

(60) The rotation drive shaft holds second roll **81** attached to the outer periphery of the rotation

drive shaft such that the second roll is rotatable and rotates in a direction (take-up direction) in which continuous medium S is pulled in the printing standby state and the printing state. The direction of pulling is a counterclockwise direction (see dotted arrow) in FIG. 1 and FIG. 2.

(61) The rotation drive shaft is also rotationally driven by the motor via the powder clutch. With such a configuration, the motor pulls continuous medium S with a predetermined torque through the powder clutch, and a predetermined tension is applied to continuous medium S.

(62) Tension adjustment part **73** of supply part **70** and tension adjustment part **83** of collection part **80** control the tension of continuous medium S to stabilize the tension to the predetermined tension.

(63) At opposite end portions of continuous medium S, the predetermined tension is applied to the continuous medium by tension applying parts **72** and **82** described above. Further, supply part **70**, collection part **80**, and image-forming-apparatus main part **100** include a plurality of rollers (conveyance rollers **51** and **52**, driven roller **76**, and the like) that convey and guide continuous medium S. Tension adjustment parts **73** and **83** are disposed to stabilize the tension of continuous medium S to a predetermined tension at positions distant from tension applying parts **72** and **82** (e.g., in section SC including image-forming-apparatus main part **100**) also through a large number of rollers.

(64) In conveyance direction T (see FIG. 2), tension adjustment part **73** is disposed on the upstream side of image-forming-apparatus main part **100** and on the downstream of splice table **75** including holding part **751**.

(65) Tension adjustment part **73** includes guide rollers **73a** and **73b**, dancer roller **73c**, and the like. Guide rollers **73a** and **73b** are disposed respectively on the upstream and downstream sides of dancer roller **73c** in conveyance direction T. Dancer roller **73c** has a predetermined weight (own weight or a weight of a predetermined weight) and is configured to be vertically movable within a predetermined movable range.

(66) Guide rollers **73a** and **73b** make contact with the lower surface of continuous medium S, and dancer roller **73c** disposed between guide roller **73a** and guide roller **73b** is configured to make contact with the upper surface of continuous medium S to convey continuous medium S. Therefore, between guide roller **73a** and guide roller **73b**, continuous medium S is pulled downward by the weight of dancer roller **73c**, whereby the tension of continuous medium S can be stabilized to a predetermined tension.

(67) Tension adjustment part **83** is disposed on the downstream side of image-forming-apparatus main part **100** in conveyance direction T and is disposed on the upstream side of nip rollers **85** having holding part **851**.

(68) Similarly to tension adjustment part **73**, tension adjustment part **83** also includes guide rollers **83a** and **83b**, dancer roller **83c**, and the like, and the tension of continuous medium S can be stabilized to a predetermined tension by the same configuration as tension adjustment part **73**.

(69) As described above, since tension adjustment parts **73** and **83** are disposed on the upstream side and the downstream side of image-forming-apparatus main part **100**, respectively, in conveyance direction T, the tension of continuous medium S can be stabilized to a predetermined tension in section SC between tension adjustment part **73** and tension adjustment part **83**.

(70) Tension adjustment parts **73** and **83** are provided respectively with tension detection parts **74** and **84** that detect the tension of continuous medium S. Tension detection parts **74** and **84** are, for example, proximity sensors, and are disposed in the vicinities of the lowermost portions of the movable ranges of dancer rollers **73c** and **83c**.

(71) When the tension of continuous medium S is loosened or lost, the weight of dancer rollers **73c** and **83c** causes dancer rollers **73c** and **83c** to move downward. The proximity sensors detect that the tension of continuous medium S is low (abnormal tension) by detecting dancer rollers **73c** and **83c** having moved to the vicinities of the lowermost portions of the movable ranges.

(72) Further, as tension detection parts **74** and **84**, the proximity sensors may be disposed in the vicinities of the uppermost portions of the movable ranges of dancer rollers **73c** and **83c**. In this

case, when the tension of continuous medium S becomes higher than a predetermined tension due to a trouble or the like, dancer rollers **73c** and **83c** move upward due to the tension. The proximity sensors detect dancer rollers **73c** and **83c** having moved to the vicinities of the uppermost portions of the movable ranges, thereby detecting that the tension of continuous medium S is high (abnormal tension).

(73) In the case of such a tension abnormality, for example, control part **200** stops the conveyance of continuous medium S itself and notifies a user of an error message of the tension abnormality (tension decrease, tension excess, or the like). In addition, control part **200** may terminate the operation of maintaining the tension of continuous medium S.

(74) Here, although the proximity sensors are described as an example as tension detection parts **74** and **84**, any sensor can be used as long as it is a sensor that detects the tension (or the physical quantity correlated with the tension) of continuous medium S. For example, tension detection parts **74** and **84** may be those sensors that detect the tension based on the positions of the vertical movements of dancer rollers **73c** and **83c**.

(75) Splice table **75** of supply part **70** is used for cutting continuous medium S and connecting continuous media S to each other during replacement of first roll **71**. Splice table **75** includes first clamp **75a**, second clamp **75b**, table **75c**, and the like.

(76) The operation of first clamp **75a** and second clamp **75b** will be described with reference to the roll replacement state illustrated in FIG. **3**, which will be described later. Each of the clamps is configured to be vertically movable under the control of control part **200**. For example, except when splice table **75** is in use, first clamp **75a** and second clamp **75b** are moved to an upper position and are spaced upward from table **75c** (see, e.g., FIG. **1**).

(77) In use of splice table **75**, one or both of first clamp **75a** and second clamp **75b** are moved to a lower position to hold continuous medium S on table **75c**. Thus, first clamp **75a** and second clamp **75b** clamp continuous medium S between them and table **75c** to hold continuous medium S (see, for example, FIG. **3**).

(78) In the present embodiment, as described later with reference to FIG. **3**, first clamp **75a** and table **75c** of splice table **75** are used as holding part **751**. During the replacement of first roll **71**, holding part **751** (first clamp **75a** and table **75c**) holds continuous medium S so as to maintain the tension of continuous medium S in image-forming-apparatus main part **100**. At this time, holding part **751** holds continuous medium S in a state where a predetermined tension is applied to continuous medium S.

(79) Nip rollers **85** of collection part **80** are used to convey continuous medium S. Nip rollers **85** include first nip roller **85a**, second nip roller **85b**, and the like.

(80) The operations of first nip roller **85a** and second nip roller **85b** will be described later with reference to FIG. **1** to FIG. **4**, and each of them is configured to be vertically movable under the control of control part **200**. Further, under the control of control part **200**, at least one of first nip roller **85a** and second nip roller **85b** is rotationally driven to convey continuous medium S in conveyance direction T (see FIG. **2**).

(81) For example, first nip roller **85a** is moved downward and second nip roller **85b** is moved upward to nip continuous medium S therebetween (see FIG. **1** and FIG. **3**). Further, while continuous medium S is nipped between first nip roller **85a** and second nip roller **85b**, first nip roller **85a** and second nip roller **85b** are rotationally driven to convey continuous medium S (FIG. **2**). In addition, first nip roller **85a** is moved upward and second nip roller **85b** is moved downward to separate them from continuous medium S (see FIG. **4**).

(82) In the present embodiment, as described later with reference to FIG. **3**, first nip roller **85a** and second nip roller **85b** of nip rollers **85** are used as holding part **851**. During the replacement of second roll **81**, holding part **851** (first nip roller **85a** and second nip roller **85b**) holds continuous medium S so as to maintain the tension of continuous medium S in image-forming-apparatus main part **100**. At this time, holding part **851** holds continuous medium S in a state where a

predetermined tension is applied to continuous medium S.

(83) Apparatus State of Image Forming Apparatus

(84) Next, the printing standby state, printing state, roll replacement state, and steady state of image forming apparatus **1** will be described with reference to FIG. **1** to FIG. **4**.

(85) Printing Standby State

(86) FIG. **1** is a diagram illustrating the printing standby state of image forming apparatus **1**. The printing standby state (the image formable state in the present invention) is a state in which the image formation (printing) on continuous medium S can be started in image forming apparatus **1**, and when an instruction from the user (a printing instruction illustrated in FIG. **6** to be described later) is received, the image formation (printing) on continuous medium S is started.

(87) In the printing standby state, when an instruction is given from control part **200**, image forming part **40** can perform a preliminary operation such as operation check for stabilizing the configuration related to image formation. Further, fixing roller **61** and pressurizing roller **62** of fixing part **60** are in a state of being separated from each other and separated from continuous medium S, and when an instruction is given from control part **200**, continuous medium S can be nipped, and the preliminary operation such as warm-up for stabilizing the fixing and pressurizing rollers can be performed.

(88) Further, in the printing standby state, first clamp **75a** and second clamp **75b** of splice table **75** are spaced upward from table **75c**. That is, continuous medium S is not held between first clamp **75a** and second clamp **75b** and table **75c**.

(89) Further, in the printing standby state, continuous medium S is held between first nip roller **85a** and second nip roller **85b**, that is, by holding part **851**, but nip rollers **85** are not rotationally driven and continuous medium S is not conveyed.

(90) Further, in the printing standby state, the output side of the powder clutch, the rotation drive shaft, and first roll **71** are not rotating, but the motor and the input side of the powder clutch of tension applying part **72** are rotating in the direction of pulling continuous medium S. Therefore, the output side of the powder clutch, the rotation drive shaft, and first roll **71** are in a state of being pulled at a predetermined torque by the rotation of the motor and the input side of the powder clutch of tension applying part **72**. As a result, tension applying part **72** applies a predetermined tension to continuous medium S from the upstream end portion in conveyance direction T in section SA between first roll **71** and nip rollers **85**.

(91) Further, in the printing standby state, the output side of the powder clutch, the rotation drive shaft, and second roll **81** are not rotating, but the motor and the input side of the powder clutch of tension applying part **82** are also rotating in the direction of pulling continuous medium S. Therefore, the output side of the powder clutch, the rotation drive shaft, and second roll **81** are in a state of being pulled at a predetermined torque by the rotation of the motor and the input side of the powder clutch of tension applying part **82**. Accordingly, tension applying part **82** applies a predetermined tension to continuous medium S from the downstream end portion in conveyance direction T in section SB between nip rollers **85** and second roll **81**.

(92) As described above, in the printing standby state, in above-described section SA, tension applying part **72** applies a predetermined tension to continuous medium S. In above-described section SA, tension adjustment part **73** and tension adjustment part **83** stabilize the tension of continuous medium S to a predetermined tension, and stabilize the tension of continuous medium S to a predetermined tension also in above-described section SC.

(93) Here, the preliminary operation will be described. As described above, image-forming-apparatus main part **100** includes developing devices **412** (developing parts in the present invention), photoconductor drums **413**, intermediate transfer belt **421** (transfer part in the present invention), fixing part **60**, and the like.

(94) In developing devices **412**, as the preliminary operation, concentration adjustment and color misregistration adjustment (calibration) of an image (toner image) to be developed on

photoconductor drums **413** are performed.

(95) Further, as the preliminary operation, photoconductor drums **413** perform image adjustment of the image (toner image) to be transferred to intermediate transfer belt **421**, and intermediate transfer belt **421** performs image adjustment of the image (toner image) to be transferred to continuous medium S, as the preliminary operation.

(96) In the above-described calibration and image adjustment, developing devices **412** develop the toner image on photoconductor drums **413**, photoconductor drums **413** transfer the developed toner image to intermediate transfer belt **421**, and the transferred toner image is read by an image reader (not illustrated).

(97) In addition, fixing part **60** raises the temperature (warm-up) to a predetermined temperature as the preliminary operation in order to fix the image (toner image) transferred to continuous medium S.

(98) When the tension of continuous medium S is loosened during the preliminary operation described above, continuous medium S may be wound around driving parts such as intermediate transfer belt **421**, fixing roller **61**, and pressurizing roller **62**, and thus the preliminary operation may be incorrectly performed, or malfunction may be caused in the above-described driving parts. Therefore, in the above-described preliminary operation, the tension of continuous medium S needs to be maintained.

(99) Accordingly, in the present embodiment, holding parts **751** and **851** also hold tensioned continuous medium S not only in the printing standby state and the printing state but also during below-described roll replacement. Therefore, even in the roll replacement state, the above-described preliminary operation can be performed, and downtime of the apparatus can be reduced. In addition, since the above-described preliminary operation can be performed during the roll replacement, for example, the number of preliminary operations performed in the printing state can be reduced, and the efficiency of image formation (printing) can also be improved.

(100) Printing State

(101) FIG. **2** is a diagram illustrating the printing state of image forming apparatus **1**. The printing state is a state in which an image is being formed (printed) on continuous medium S in accordance with an instruction from the user (a printing instruction illustrated in FIG. **6**).

(102) In the printing state, when an instruction is given from control part **200**, image forming part **40** can perform a preliminary operation such as operation check. Further, fixing roller **61** and pressurizing roller **62** of fixing part **60** are in a state of nipping continuous medium S therebetween and of conveying continuous medium S in conveyance direction T, and the preliminary operation such as warm-up can be performed when the instruction is given from control part **200**.

(103) Further, in the printing state, first clamp **75a** and second clamp **75b** of splice table **75** are spaced upward from table **75c**, and continuous medium S is not held between the clamps and table **75c**.

(104) In the printing state, nip rollers **85** nip continuous medium S and are rotationally driven in conjunction with the image formation in image-forming-apparatus main part **100**, and continuous medium S is conveyed.

(105) Further, in the printing state, the motor and the input side of the powder clutch of tension applying part **72** rotate in the direction of pulling continuous medium S. Further, the output side of the powder clutch and the rotation drive shaft of tension applying part **72**, and first roll **71** are rotated in the direction opposite to the rotation direction of the motor and the input side of the powder clutch of tension applying part **72** by the conveyance of continuous medium S by the rotation drive of nip rollers **85**. When the tension of continuous medium S decreases and the torque of the powder clutch of tension applying part **72** becomes less than a predetermined torque during the conveyance of continuous medium S, the powder clutch is brought into the connected state and continuous medium S is pulled by the predetermined torque. Thus, tension applying part **72** applies the predetermined tension to continuous medium S.

(106) Further, in the printing state, the motor and the input side of the powder clutch of tension applying part **82** rotate in the direction of pulling continuous medium S. In addition, the output side of the powder clutch and the rotation drive shaft of tension applying part **82**, and second roll **81** rotate in the same direction as the rotation direction of the motor and the input side of the powder clutch of tension applying part **82** in conjunction with the conveyance of continuous medium S by the rotation drive of nip rollers **85**. When the tension of continuous medium S decreases and the torque of the powder clutch of tension applying part **82** becomes less than a predetermined torque during the conveyance of continuous medium S, the powder clutch is brought into the connected state and continuous medium S is pulled at the predetermined torque. Thus, tension applying part **82** applies the predetermined tension to continuous medium S.

(107) In the printing state, tension adjustment part **73** and tension adjustment part **83** stabilize the tension of conveyed continuous medium S to a predetermined tension. As a result, the tension of continuous medium S is stabilized via the plurality of rollers to a predetermined tension in section SC (see FIG. **1**) distant from tension applying part **72** and tension applying part **82**.

(108) In a case where the tension of continuous medium S is loosened or lost due to a trouble or the like in the printing state, tension detection parts **74** and **84** detect that the tension of continuous medium S is lower than a predetermined tension. Then, control part **200** notifies the user of an error message such as that of a decrease in tension and/or prohibits the preliminary operation or the conveyance of continuous medium S based on the detection results of tension detection parts **74** and **84**.

(109) Roll Replacement State

(110) FIG. **3** is a diagram illustrating the roll replacement state of image forming apparatus **1**. The roll replacement state is a state in which the roll replacement can be performed in accordance with an instruction from the user ("Roll Replacement ON" illustrated in FIG. **6** to be described later).

(111) In the roll replacement state, when an instruction is given from control part **200**, image forming part **40** can perform a preliminary operation such as operation check. Further, fixing roller **61** and pressurizing roller **62** of fixing part **60** are in a state of being separated from each other and separated from continuous medium S, and when an instruction is given from control part **200**, a preliminary operation such as warm-up can be performed. As described below, since the tension of continuous medium S in image-forming-apparatus main part **100** is maintained also in the roll replacement state, the above-described preliminary operation can be performed. Further, since the tension of continuous medium S in image-forming-apparatus main part **100** is maintained in the roll replacement state, the preliminary operation may be performed while the tension is maintained.

(112) In the roll replacement state, first clamp **75a** of splice table **75** is moved downward, and continuous medium S (cut continuous medium Sr) is held by holding part **751**, that is, between first clamp **75a** and table **75c**.

(113) In supply part **70**, holding part **751** holds tensioned continuous medium S, thereby holding continuous medium S so as to maintain a predetermined tension.

(114) Second clamp **75b** of splice table **75** is spaced upward from table **75c**, but as will be described later, when continuous media S are to be connected to each other, the second clamp is moved downward, and new continuous media S is held between second clamp **75b** and table **75c**.

(115) Further, in the roll replacement state, nip rollers **85** are not rotationally driven, and continuous medium S is not conveyed, but continuous medium S (cut continuous medium Sr) is held by holding part **851** (between first nip roller **85a** and second nip roller **85b**).

(116) In collection part **80**, holding part **851** holds tensioned continuous medium S, thereby holding continuous medium S so as to maintain a predetermined tension.

(117) In the case where both of first roll **71** and second roll **81** are replaced, continuous medium S is held by holding part **751** and holding part **851** before continuous medium S is cut, and continuous medium S is held by these parts such that a predetermined tension is maintained. Further, even after continuous medium S is cut, opposite end portions of continuous medium Sr are

held by holding parts **751** and **851**, respectively, and a predetermined tension is maintained in continuous medium **Sr**.

(118) When only first roll **71** is replaced, continuous medium **S** may be held by holding part **751** described above, and holding part **851** may hold continuous medium **S** or does not have to hold continuous medium **S**. When continuous medium **S** is not held by holding part **851**, the rotation of the motor of tension applying part **82** is not stopped, and tension applying part **82** applies a predetermined tension to continuous medium **S** from the downstream end portion in conveyance direction **T**.

(119) When only second roll **81** is replaced, continuous medium **S** may be held by holding part **851** described above, and holding part **751** may hold continuous medium **S** or does not have to hold continuous medium **S**. When continuous medium **S** is not held by holding part **751**, the rotation of the motor of tension applying part **72** is not stopped, and tension applying part **72** applies a predetermined tension to continuous medium **S** from the upstream end portion in conveyance direction **T**.

(120) When only one or both of first roll **71** and second roll **81** is replaced, tension adjustment part **73** and tension adjustment part **83** stabilize the tension of continuous medium **S** to a predetermined tension in section **SD** between holding part **751** and holding part **851** in either case. Therefore, also in section **SC**, tension adjustment part **73** and tension adjustment part **83** stabilize the tension of continuous medium **S** to a predetermined tension.

(121) When first roll **71** is replaced, the rotation of the motor of tension applying part **72** is stopped, and no tension is applied to continuous medium **S** between holding part **751** and first roll **71**. By cutting continuous medium **S** between holding part **751** and first roll **71**, first roll **71** can be detached from the rotation drive shaft of tension applying part **72**, and new first roll **71** can be attached to the rotation drive shaft.

(122) Similarly, when second roll **81** is replaced, the rotation of the motor of tension applying part **82** is stopped, and no tension is applied to continuous medium **S** between holding part **851** and second roll **81**. By cutting continuous medium **S** between holding part **851** and second roll **81**, second roll **81** can be detached from the rotation drive shaft of tension applying part **82**, and new second roll **81** can be attached to the rotation drive shaft.

(123) In a case where the tension of continuous medium **S** is loosened or lost due to a trouble or the like in the roll replacement state, tension detection parts **74** and **84** detect that the tension of continuous medium **S** is lower than a predetermined tension. Control part **200** notifies the user of an error message such as that of a decrease in tension and/or prohibits the preliminary operation based on the detection results of tension detection parts **74** and **84**. In this case, control part **200** transitions from the roll replacement state to the steady state, as described later with reference to FIG. 6.

(124) A procedure for the roll replacement will be described later with reference to FIG. 7 to FIG. 14, and the cutting of continuous medium **S** and the connection between continuous media **S** using splice table **75** of supply part **70** in the roll replacement state will be described below.

(125) When first roll **71** is replaced in the roll replacement state described above, first, continuous medium **S** is cut using splice table **75** as described below.

(126) In the roll replacement state, as described in FIG. 8 and FIG. 9, first clamp **75a** of splice table **75** is lowered and continuous medium **S** is nipped between first clamp **75a** and table **75c**, so that holding part **751** holds continuous medium **S** (see FIG. 8). Thereafter, the rotation of the motor of tension applying part **72** is stopped (see FIG. 9). Second clamp **75b** of splice table **75** remains spaced upward from table **75c**.

(127) Then, on table **75c** between first clamp **75a** and second clamp **75b**, continuous medium **S** is cut by a cutter or the like (not illustrated) in the region between the first clamp and the second clamp.

(128) After continuous medium **S** is cut, cut continuous medium **Sr** on the first clamp **75a** side

remains held by holding part **751** (between first clamp **75c** and the table). On the other hand, since continuous medium **S** on the second clamp **75b** side is not held by second clamp **75b** and the like, first roll **71** can be detached from the rotation drive shaft.

(129) In the above-described procedure of cutting continuous medium **S**, when the user selects “Roll Replacement ON” described later with reference to FIG. **6**, control part **200** automatically controls the procedure entirely or partially.

(130) When continuous media **S** are to be connected to each other by using splice table **75** after continuous medium **S** is cut as described above, new first roll **71** is attached to the rotation drive shaft. Next, a leading end portion of continuous medium **Sn** (see FIG. **12**) of new first roll **71** is passed between second clamp **75b** and table **75c**. Next, on table **75c** between first clamp **75a** and second clamp **75b**, the end portions of cut continuous medium **Sr** and continuous medium **Sn** of new first roll **71** are placed on each other.

(131) Next, second clamp **75b** is lowered downward, and continuous medium **Sn** of new first roll **71** is nipped between second clamp **75b** and table **75c** such that continuous medium **Sn** is held. At this time, cut continuous medium **Sr** is held by holding part **751** (between first clamp **75a** and table **75c**).

(132) Next, on table **75c** between first clamp **75a** and second clamp **75b**, two overlapping continuous media **Sr** and **Sn** in the region between the first and the second clamps are cut and cut continuous media **Sr** and **Sn** are connected to each other by an adhesive member such as adhesive tape **Ta**. Next, the motor of tension applying part **72** is rotated to apply tension to connected continuous medium **Sn** (see FIG. **12** to be described later).

(133) Next, first clamp **75a** and second clamp **75b** are raised upward and separated from table **75c** (see FIG. **13** described later). Since cut continuous medium **Sr** is connected to continuous medium **Sn** of new first roll **71**, these continuous media **Sr** and **Sn** are united into single continuous medium **S**. The tension is applied by tension applying part **72** to continuous medium **Sn**. Accordingly, the replacement of first roll **71** ends while the tension of one-piece continuous medium **S** (continuous media **Sr** and **Sn**) is maintained.

(134) Control part **200** also automatically controls the above-described procedure of connection between continuous media **S** entirely or partially.

(135) Note here that, the cutting of continuous medium **S** and the connection of continuous medium **S** using splice table **75** of supply part **70** have been described, but the same configuration may be provided in collection part **80** to cut continuous medium **S** and connect continuous media **S** to each other.

(136) Steady State

(137) FIG. **4** is a diagram illustrating the steady state of image forming apparatus **1**. The steady state is a state in which, if there is an instruction from the user (“Printing Standby ON” instruction illustrated in FIG. **6** to be described later), the image forming apparatus transitions to the printing standby state and is a state before the tension is applied to continuous medium **S** as described below.

(138) Since the steady state is a state before the tension is applied to continuous medium **S**, the preliminary operation cannot be performed. Therefore, in the steady state, image forming part **40** cannot perform the preliminary operation such as operation check. Further, fixing roller **61** and pressurizing roller **62** of fixing part **60** are separated from each other and separated from continuous medium **S**. Continuous medium **S** is not held between the fixing roller and the pressurizing roller, and the preliminary operation such as warm-up cannot be performed.

(139) Further, in the steady state, first clamp **75a** and second clamp **75b** of splice table **75** are spaced upward from table **75c**, and continuous medium **S** is not held between the first and the second clamps and table **75c**. That is, holding part **751** does not hold continuous medium **S**.

(140) In addition, in the steady state, first nip roller **85a** and second nip roller **85b** of nip rollers **85** are separated from each other and separated from continuous medium **S**. Continuous medium **S** is

not held between the first and the second nip rollers, and continuous medium S is not conveyed. That is, holding part **851** does not hold continuous medium S.

(141) In addition, in the steady state, the motor and the input side of the powder clutch of tension applying part **72** does not rotate. Therefore, tension applying part **72** is not applying a predetermined tension to continuous medium S. Further, since continuous medium S is not conveyed by nip rollers **85**, the output side of the powder clutch and the rotation drive shaft of tension applying part **72**, and first roll **71** are also not rotated.

(142) In addition, in the steady state, the motor and the input side of the powder clutch of tension applying part **82** are also not rotated. Therefore, tension applying part **82** is not applying a predetermined tension to continuous medium S. Further, since continuous medium S is not conveyed by nip rollers **85**, the output side of the powder clutch and the rotation drive shaft of tension applying part **82**, and second roll **81** are also not rotated.

(143) As described above, in the steady state, continuous medium S is not held by holding parts **751** and **851**, and no tension is applied by tension applying parts **72** and **82**. Therefore, in tension adjustment part **73** and tension adjustment part **83**, dancer rollers **73c** and **83c** moves downward due to the weight of dancer rollers **73c** and **83c**, and accordingly, corresponding portions of continuous medium S droop downward.

(144) In this state, tension detection parts **74** and **84** detect that the tension of continuous medium S is lower than a predetermined tension. Control part **200** notifies the user of an error message such as that of a decrease in tension based on the detection results of tension detection parts **74** and **84**, and/or prohibits the above-described preliminary operation and conveyance of continuous medium S.

(145) Transition of Apparatus State

(146) As described above, image forming apparatus **1** according to the present embodiment has, as the apparatus state, the printing standby state, the printing state, the roll replacement state, the steady state, and the like, and transitions the apparatus state in accordance with an instruction from a user and/or the apparatus state. FIG. **6** is an explanatory view for explaining the transition to each apparatus state in image forming apparatus **1**.

(147) When the initial state of image forming apparatus **1** is power OFF state **C0**, and when the user gives an instruction of power ON **C1** to image forming apparatus **1**, image forming apparatus **1** transitions to above-described steady state **C2**. In this steady state **C2**, as described above, the preliminary operation is prohibited since continuous medium S is in a state prior to the application of tension.

(148) In steady state **C2**, when continuous medium S is set in image forming apparatus **1** and a tension can be applied to continuous medium S, the user gives an instruction of printing standby ON **C3** to image forming apparatus **1** and accordingly image forming apparatus **1** transitions to above-described printing standby state **C4**. In printing standby state **C4**, as described above, the preliminary operation is permitted since tension is applied to continuous medium S.

(149) In printing standby state **C4**, when the user gives printing instruction **C5** to image forming apparatus **1**, image forming apparatus **1** transitions to above-described printing state **C6** and executes printing. As described above, since tension is applied to continuous medium S also in this printing state **C6**, the preliminary operation is permitted. After the printing is completed, image forming apparatus **1** transitions (returns) to printing standby state **C4** described above.

(150) Further, in printing standby state **C4**, when the user gives an instruction of roll replacement ON **C7** to image forming apparatus **1**, image forming apparatus **1** transitions to roll replacement state **C8** described above. In roll replacement state **C8**, the user performs roll replacement of at least one of first roll **71** and second roll **81**. Since tension is applied to continuous medium S also in this roll replacement state **C8** as described above, the preliminary operation is permitted. The transition from printing standby state **C4** to roll replacement state **C8** will be described later with reference to FIG. **7** to FIG. **10**.

(151) After the roll replacement, when the user gives an instruction of roll replacement OFF C9 to image forming apparatus 1, image forming apparatus 1 transitions (returns) to printing standby state C4 described above. The transition from roll replacement state C8 to printing standby state C4 will be described later with reference to FIG. 11 to FIG. 14.

(152) When the tension applied to continuous medium S is loosened or lost during the roll replacement, and when tension detection parts 74 and 84 detect that the tension of continuous medium S is lower than a predetermined tension (abnormal tension), image forming apparatus 1 transitions to above-described steady state C2. The transition from roll replacement state C8 to steady state C2 will be described later with reference to FIG. 15.

(153) In this case, when the tension of continuous medium S is lower than the predetermined tension, it is detected that the tension is abnormal, and the process transitions to above-described steady state C2. Also, when the tension of continuous medium S is higher than the predetermined tension, it may be detected that the tension is abnormal, and the process may transition to above-described steady state C2.

(154) In this case, as described above, the proximity sensors are disposed in the vicinities of the uppermost portions of the movable ranges of dancer rollers 73c and 83c. When dancer rollers 73c and 83c are close to the proximity sensors, it is detected that the tension of continuous medium S is higher than the predetermined tension. Further, when the abnormal tension of continuous medium S is detected in above-described printing state C6, that is, during printing, the transition to above-described steady state C2 may be made.

(155) Transition from Printing Standby State to Roll Replacement State

(156) The above-described transition from printing standby state C4 to roll replacement state C8 will be described later also with reference to FIG. 7 to FIG. 10.

(157) FIG. 7 is a flowchart for explaining the transition from printing standby state C4 to roll replacement state C8 in image forming apparatus 1. FIG. 8 is a diagram illustrating supply part 70 of image forming apparatus 1 in the case where continuous medium S is held by holding part 751 in the order according to the flowchart illustrated in FIG. 7. FIG. 9 is a diagram illustrating supply part 70 of image forming apparatus 1 in the case where the rotation of the motor of tension applying part 72 is stopped in the order according to the flowchart illustrated in FIG. 7. FIG. 10 is a diagram illustrating supply part 70 of image forming apparatus 1 in the case where the processing is performed in a different order from the flowchart illustrated in FIG. 7.

(158) Here, supply part 70 will be described as an example, and it is assumed that continuous medium S is held by holding part 851 at the side of collection part 80, for example.

(159) (Step S11)

(160) In the printing standby state, control part 200 checks whether or not a roll replacement button is on. When the roll replacement button is on (YES), the process proceeds to step S12, and when the roll replacement button is not on (NO), step S11 is repeated. Although not illustrated here, for example, control part 200 checks whether or not a printing instruction button is on, and when the printing instruction button is on, transition to printing state C5 is made as described with reference to FIG. 6, and printing is performed.

(161) (Step S12)

(162) Control part 200 moves first clamp 75a of splice table 75 downward to cause holding part 751 (first clamp 75a and table 75c) to hold continuous medium S. At this time, the motor of tension applying part 72 keeps rotating, and a predetermined tension is applied to continuous medium S by pulling continuous medium S with a predetermined torque via the powder clutch (see FIG. 8). Holding part 751 thus holds continuous medium S in a state where a predetermined tension is applied to continuous medium S, and maintains the tension of continuous medium S.

(163) (Step S13)

(164) Control part 200 stops the rotation of the motor of tension applying part 72 (see FIG. 9). That is, the application of tension to continuous medium S is stopped.

(165) As described above, continuous medium S is held by holding part **751** before the rotation of the motor of tension applying part **72** is stopped. Accordingly, in section SD illustrated in FIG. **3**, the tension of continuous medium S can be reliably maintained, and the tension of continuous medium S can be maintained even in section SC.

(166) When the order of step **S12** and step **S13** is reversed, the rotation of the motor of tension applying part **72** is stopped before holding part **751** holds continuous medium S.

(167) In this case, in section SD, the tension applied from tension applying part **72** to continuous medium S is lost. Then, in tension adjustment part **73**, dancer roller **73c** moves downward due to the weight of dancer roller **73c**, and continuous medium S of the portion droops downward (see FIG. **10**). This is the same state as the steady state illustrated in FIG. **4**, in which the tension of continuous medium S in section SC is also lost, continuous medium S is not placed along a predetermined conveyance path, and the preliminary operation cannot be executed.

(168) Therefore, in order to maintain the tension of continuous medium S in sections SD and SC, holding part **751** needs to hold continuous medium S before the rotation of the motor of tension applying part **72** is stopped.

(169) (Step **S14**)

(170) Control part **200** transitions from printing standby state **C4** to roll replacement state **C8** as the apparatus state.

(171) Here, although supply part **70** has been described as an example, the same procedure is also applied to collection part **80**. Repetitive descriptions of the same procedure will be omitted. In this case, it is assumed that continuous medium S is held by holding part **751** at the supply part **70** side, for example.

(172) Transition from Roll Replacement State to Printing Standby State

(173) The transition from roll replacement state **C8** to printing standby state **C4** described above will be described below with reference also to FIG. **11** to FIG. **14**.

(174) FIG. **11** is a flowchart for explaining the transition from roll replacement state **C8** to printing standby state **C4** in image forming apparatus **1**. FIG. **12** is a diagram illustrating supply part **70** of image forming apparatus **1** in the case where the motor of tension applying part **72** is rotated and tension is applied to continuous medium S in the order according to the flowchart illustrated in FIG. **11**. FIG. **13** is a diagram illustrating supply part **70** of image forming apparatus **1** in the case where the holding of continuous medium S at holding part **751** is released in the order according to the flowchart illustrated in FIG. **11**. FIG. **14** is a diagram illustrating supply part **70** of image forming apparatus **1** in a case where the processing is performed in a different order from the flowchart illustrated in FIG. **11**.

(175) Here again, supply part **70** will be described as an example, and it is assumed that continuous medium S is held by holding part **851** at the collection part **80** side, for example.

(176) (Step **S21**)

(177) In the roll replacement state, control part **200** checks whether or not the roll replacement button is off. When the roll replacement button is off (YES), the process proceeds to step **S22**, and when the roll replacement button is not off (NO), step **S21** is repeated.

(178) (Step **S22**)

(179) Control part **200** rotates the motor of tension applying part **72** stopped in above-described step **S13**, to apply tension to continuous media **Sr** and **Sn** (see FIG. **12**). At this time, first clamp **75a** and second clamp **75b** of splice table **75** have been moved downward, and respectively hold continuous media **Sr** and **Sn** between the clamps and table **75c**. Holding part **751** (first clamp **75a** and table **75c**) holds continuous medium **Sr** and maintains the tension of continuous medium **Sr**.

(180) (Step **S23**)

(181) Control part **200** moves first clamp **75a** and second clamp **75b** upward to release the holding of continuous medium **Sr** at holding part **751** having held continuous medium S in above-described step **S12**. The holding of continuous medium **Sr** between second clamp **75b** and table **75c** is also

released (see FIG. 13).

(182) As is understood, prior to releasing the holding of continuous media Sr and Sn at holding part 751, the motor of tension applying part 72 is rotated to apply tension to continuous media Sr and Sn. Thus, in section SD (see FIG. 3), the tension of continuous medium Sr can be reliably maintained, and the tension of continuous medium Sr can be maintained also in section SC.

(183) When the order of step S22 and step S23 is reversed, the holding of continuous medium S at holding part 751 is released prior to application of the tension to continuous media Sr and Sn by rotation of the motor of tension applying part 72.

(184) In this case, holding part 751 releases the holding of continuous medium Sr at holding part 751, whereby the tension of continuous medium Sr in section SD that is maintained by holding continuous medium Sr is lost. At this time, at tension adjustment part 73, dancer roller 73c moves downward due to the weight of dancer roller 73c, and a corresponding portion of continuous medium Sr droops downward (see FIG. 14). This is the same state as the steady state illustrated in FIG. 4, in which the tension of continuous medium Sr in section SC is also lost, continuous medium S is not placed along the predetermined conveyance path, and the preliminary operation cannot be executed.

(185) Therefore, in order to maintain the tension of continuous medium Sr in sections SD and SC, it is required to rotate the motor of tension applying part 72 to apply the tension to continuous media Sr and Sn prior to releasing the holding of continuous medium Sr at holding part 751.

(186) (Step S24)

(187) Control part 200 transitions from roll replacement state C8 to printing standby state C4 as the apparatus state. The apparatus state of image forming apparatus 1 becomes the printing standby state illustrated in FIG. 1.

(188) Here, although supply part 70 has been described as an example, the same procedure is also applied to collection part 80. Repetitive descriptions of the same procedure will be omitted. In this case, it is assumed that continuous medium S is held by holding part 751 at the supply part 70 side, for example.

(189) Transition from Roll Replacement State to Steady State

(190) The transition from roll replacement state C8 to steady state C2 described above will be described later with reference also to FIG. 15.

(191) FIG. 15 is a flowchart for explaining the transition from roll replacement state C8 to steady state C2 in image forming apparatus 1.

(192) When the tension of continuous medium S is abnormal, control part 200 transitions from roll replacement state C8 to steady state C2 as the apparatus state.

(193) (Step S31)

(194) In the roll replacement state, control part 200 checks whether or not the tension of continuous medium S is abnormal. For example, control part 200 checks whether or not the tension of continuous medium S is abnormal by using the above-described tension detection parts 74 and 84. When the tension of continuous medium S is abnormal (YES), the process proceeds to step S32, and when the tension of continuous medium S is not abnormal (NO), step S31 is repeated.

(195) (Step S32)

(196) Control part 200 prohibits the preliminary operation. Control part 200 prohibits the above-described preliminary operation, for example, a preliminary operation such as warm-up of fixing part 60.

(197) (Step S33)

(198) Control part 200 stops the rotation of the motors of tension applying parts 72 and 82, to stop the application of tension to continuous medium S.

(199) (Step S34)

(200) Control part 200 releases the holding of continuous medium S at holding parts 751 and 851 holding continuous medium S.

(201) Specifically, control part **200** moves first clamp **75a** upward to release the holding of continuous medium **S** at holding part **751**. At this time, when second clamp **75b** holds continuous medium **S** between itself and table **75c**, second clamp **75b** is also moved upward to release the holding of continuous medium **S** at that portion. Further, first nip roller **85a** and second nip roller **85b** are separated from each other to release the holding of continuous medium **S** at holding part **851**.

(202) (Step **S35**)

(203) Control part **200** transitions from roll replacement state **C8** to steady state **C2** as the apparatus state. The apparatus state of image forming apparatus **1** becomes the steady state illustrated in FIG. **4**.

Summary

(204) As described above, image forming apparatus **1** of the present embodiment includes tension maintaining parts **701** and **801** that maintain the tension of continuous medium **S** in image-forming-apparatus main part **100** at the time of a manipulation for replacing at least one of first roll **71** and second roll **81**.

(205) Further, in the control method of the image forming apparatus according to the present embodiment, tension maintaining parts **701** and **801** are operated to maintain the tension of continuous medium **S** in image-forming-apparatus main part **100** at the time of a manipulation for replacing at least one of first roll **71** and second roll **81**.

(206) According to the image forming apparatus and the control method of the present embodiment configured as described above, first roll **71** and second roll **81** can be replaced in a state where the tension of continuous medium **S** in image-forming-apparatus main part **100** is maintained.

(207) Holding parts **751** and **851** hold tensioned continuous medium **S** not only in the printing standby state and the printing state but also during the roll replacement. Thus, the preliminary operation can be performed even in the roll replacement state. Therefore, downtime of the apparatus can be reduced. Further, by performing the preliminary operation during the roll replacement, the number of preliminary operations in the printing state can be reduced, and the efficiency of image formation (printing) can also be improved.

(208) In addition, since holding parts **751** and **851** hold tensioned continuous medium **S** during the roll replacement, continuous medium **S** is disposed along a predetermined conveyance path in image forming apparatus **1** including image-forming-apparatus main part **100**. Therefore, continuous medium **S** does not enter a portion other than the conveyance path during the roll replacement, and for example, when the conveyance of continuous medium **S** is resumed, a conveyance trouble or the like is not caused. As a result, downtime of the apparatus can be reduced.

OTHER EMBODIMENTS

(209) In the above-described embodiment, an image forming apparatus using an electrophotographic process technology is described as an example of image-forming-apparatus main part **100**, but the present invention is also applicable to an image forming apparatus using an inkjet technology as image-forming-apparatus main part **100**.

(210) Note that, the aforementioned embodiments merely describe examples of implementations for practicing the present invention and should not be construed as limiting the technical scope of the present invention. That is, the present invention can be embodied in various forms without departing from the spirit, scope, or principal features of the present invention.

(211) Although embodiments of the present invention have been described and illustrated in detail, the disclosed embodiments are made for purpose of illustration and example only and not limitation. The scope of the present invention should be interpreted by terms of the appended claims.

Claims

1. An image forming apparatus, comprising: a main part that forms an image on a continuous medium in a state in which a tension is applied to the continuous medium, the continuous medium being fed from a first roll and conveyed to be taken up on a second roll; and a tension maintaining part that maintains the tension of the continuous medium at the main part during a manipulation for replacing at least one of the first roll and the second roll; wherein: the tension maintaining part includes: a tension applier that applies a predetermined tension to the continuous medium, and a holder that holds the continuous medium in a state in which the predetermined tension is applied to the continuous medium, and when the image forming apparatus transitions from an image formable state to a roll replacement state, the holder is operated such that the holder holds the continuous medium, and thereafter stops the tension applier applying the tension.
2. The image forming apparatus according to claim 1, wherein during the manipulation, the main part performs a preliminary operation of image formation while the tension is maintained.
3. The image forming apparatus according to claim 1, wherein the tension maintaining part includes: a tension applier that applies a predetermined tension to the continuous medium, and a holder that holds the continuous medium in the state in which the predetermined tension is applied to the continuous medium.
4. The image forming apparatus according to claim 3, wherein the holder holds at least one of an upstream side and a downstream side of the continuous medium with respect to the main part in a conveyance direction in which the continuous medium is conveyed.
5. The image forming apparatus according to claim 3, wherein the holder includes a nip roller that nips and conveys the continuous medium.
6. The image forming apparatus according to claim 3, further comprising: a splice table that presses the continuous medium onto a table with a clamp when the continuous medium is cut or the continuous medium is connected to one another; wherein the holder includes the clamp.
7. The image forming apparatus according to claim 1, further comprising: a tension detector that detects the tension of the continuous medium at the main part, wherein when the tension detected is abnormal, the tension maintaining part terminates an operation of maintaining the tension depending on the manipulation.
8. The image forming apparatus according to claim 3, wherein: the tension maintaining part further includes a tension adjustment part that adjusts the tension of the continuous medium, and the tension adjustment part is disposed on the main part side of the holder in a conveyance direction in which the continuous medium is conveyed.
9. The image forming apparatus according to claim 8, wherein the tension adjustment part includes a dancer roller that is disposed to be vertically movable and that applies its own weight to the continuous medium.
10. The image forming apparatus according to claim 9, further comprising: a tension detector that detects that the tension is abnormal, when the dancer roller is at a lowermost portion or an uppermost portion of a range of vertical movement.
11. The image forming apparatus according to claim 1, further comprising: a hardware processor that controls the image forming apparatus based on an instruction from a user by manipulation, wherein the hardware processor permits a preliminary operation of image formation, when transitioning, in accordance with the instruction of the user, to the roll replacement state for replacing at least one of the first roll and the second roll.
12. The image forming apparatus according to claim 11, wherein when the hardware processor is in an image formable state in which starting formation of the image is allowed, the hardware processor transitions to the roll replacement state in accordance with the instruction of the user.
13. The image forming apparatus according to claim 11, wherein when the hardware processor is in the roll replacement state, the hardware processor transitions to an image formable state in which starting formation of the image is allowed, in accordance with an instruction from the user.

14. The image forming apparatus according to claim 13, wherein: the tension maintaining part includes: a tension applier that applies a predetermined tension to the continuous medium, and a holder that holds the continuous medium in a state in which the predetermined tension is applied to the continuous medium, and when the hardware processor transitions from the roll replacement state to the image formable state, the hardware processor starts the tension applier applying a tension, and thereafter operates the holder such that holding of the continuous medium is released.
15. The image forming apparatus according to claim 11, wherein: the tension maintaining part includes: a tension applier that applies a predetermined tension to the continuous medium, and a holder that holds the continuous medium in a state in which the predetermined tension is applied to the continuous medium, and when the tension is abnormal in the roll replacement state, the hardware processor releases the roll replacement state, operates the holder such that holding of the continuous medium is released, and stops the tension applier applying the tension.
16. A control method of an image forming apparatus, comprising: forming an image on a continuous medium by a main part of the image forming apparatus in a state in which a tension is applied to the continuous medium, the continuous medium being fed from a first roll and conveyed to be taken up on a second roll; operating a tension maintaining part to maintain the tension of the continuous medium at the main part during a manipulation for replacing at least one of the first roll and the second roll; wherein: the tension maintaining part includes: a tension applier that applies a predetermined tension to the continuous medium, and a holder that holds the continuous medium in a state in which the predetermined tension is applied to the continuous medium, and when the image forming apparatus transitions from an image formable state to a roll replacement state, the holder is operated such that the holder holds the continuous medium, and thereafter stops the tension applier applying the tension.
-