

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409763
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Umlauf; James

Vehicle door guard

Abstract

Vehicle door guards can be used in conjunction with a vehicle seat cover to provide protection to doors. A vehicle door guard may include a cover portion that is configured to be secured to a lower portion of a vehicle seat cover when the vehicle seat cover is installed on a vehicle seat. The vehicle door guard may also include one or more fasteners for supporting the cover portion from a portion of the vehicle.

Inventors:	Umlauf; James (Glendale, AZ)
Applicant:	4Knines, LLC (Oklahoma City, OK)
Family ID:	88977955
Assignee:	4Knines, LLC (Oklahoma City, OK)
Appl. No.:	17/834670
Filed:	June 07, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230391238 A1	Dec. 07, 2023

Publication Classification

Int. Cl.: B60N2/58 (20060101); B60N2/60 (20060101)

U.S. Cl.:

CPC B60N2/5833 (20130101); B60N2/60 (20130101); B60N2/6009 (20130101); B60N2/6036 (20130101);

Field of Classification Search

CPC: B60N (2/5833); B60N (2/60); B60N (2/6009); B60N (2/6036)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2641773	12/1952	Kramer	5/94	B60N 2/2854
3735430	12/1972	Platz	5/118	A47D 9/005
4512286	12/1984	Rux	119/771	A01K 1/0272
4924814	12/1989	Beaudet	280/749	A01K 1/0272
4943105	12/1989	Kacar	297/229	B60N 2/2854
5133294	12/1991	Reid	119/771	A01K 1/0272
5215345	12/1992	Orphan	296/37.16	B60N 2/6009
5294166	12/1993	Shapland	297/229	B60N 2/6036
5322335	12/1993	Niemi	296/97.23	B60R 13/01
5487361	12/1995	Dean	119/28.5	A01K 1/0272
6352299	12/2001	Ames	297/228.1 X	B60J 1/025
6676209	12/2003	Szabo	297/229	B60R 7/043
6926341	12/2004	Addesso	296/153	B60R 11/00
7261375	12/2006	Godshaw	297/229	A01K 1/0272
7287813	12/2006	Aliev	297/229	B60R 13/011
7677662	12/2009	Thompson	297/228.12 X	B60N 2/6009
8414071	12/2012	Rabson	297/228.12 X	A47C 31/113
8870283	12/2013	Daley	297/228.12 X	B60N 2/28
9402369	12/2015	Burns Baker	N/A	B60R 7/046
9610877	12/2016	Umlauf	N/A	B60N 2/6018
9669742	12/2016	Bailey	N/A	B60R 5/006
9815395	12/2016	Umlauf	N/A	B60N 2/60
9845033	12/2016	Umlauf	N/A	B60N 2/6018
9878646	12/2017	Umlauf	N/A	B60R 5/04
9963086	12/2017	Umlauf	N/A	B60N 2/60
10081278	12/2017	Balzer	N/A	B60N 2/60
10343568	12/2018	Umlauf	N/A	B60N 2/6036
10363847	12/2018	Umlauf	N/A	B60N 2/6018
10406951	12/2018	Leon Guerrero	N/A	B60N 2/6009
10518676	12/2018	Umlauf	N/A	B60J 7/0007
10647233	12/2019	Umlauf	N/A	B60R 13/011
10960798	12/2020	Li	N/A	B60N 2/876
11135952	12/2020	Umlauf	N/A	B60N 2/6018
11345265	12/2021	Wang	N/A	B60N 2/6027
11432527	12/2021	Pan	N/A	B60N 2/6027
11535132	12/2021	Umlauf	N/A	B60N 2/36
11691550	12/2022	Umlauf	297/229	B60N 2/6027
11844328	12/2022	Pan	N/A	B60N 2/6009
2004/0183347	12/2003	Szabo	297/229	B60N 2/60
2005/0236874	12/2004	Godshaw	119/28.5	B60N 2/6009

2008/0179926	12/2007	Kushner	297/229	B60N 2/6018
2016/0066694	12/2015	Blakeney	297/228.13 X	A47C 7/021
2016/0107552	12/2015	Wakeman	297/229	B60N 2/6009
2019/0327932	12/2018	Adrain	N/A	B60N 2/6018

Primary Examiner: White; Rodney B

Attorney, Agent or Firm: Kirton McConkie

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) N/A

BACKGROUND

(2) The present invention relates to a vehicle door guard. In particular, the present invention relates to a vehicle door guard that can be used in conjunction with a vehicle seat/cargo cover to extend protection to the door and other areas to the sides of a vehicle's seat(s) and/or cargo bed. Many vehicle seat covers exist but provide minimal, if any, protection to the door and surrounding areas.

BRIEF SUMMARY

(3) The present invention extends to vehicle door guards that can be used in conjunction with a vehicle seat cover to provide protection to doors. A vehicle door guard may include a cover portion that is configured to be secured to a lower portion of a vehicle seat cover when the vehicle seat cover is installed on a vehicle seat. The vehicle door guard may also include one or more fasteners for supporting the cover portion from a portion of the vehicle.

(4) In some embodiments, the present invention may be implemented as a vehicle door guard that includes a cover portion and one or more fasteners. The cover portion may have a top and a bottom and may include a fastening strip that is positioned towards the bottom. The fastening strip may be configured to secure the cover portion to a lower portion of a vehicle seat cover when the vehicle seat cover is installed on a vehicle seat in a vehicle. The one or more fasteners may extend from the cover portion and may be configured to support the cover portion from a portion of the vehicle.

(5) In some embodiments, the fastening strip may be configured to secure the cover portion to an underside of the lower portion of the vehicle seat cover.

(6) In some embodiments, the fastening strip may include one of: a hook and loop material, an adhesive material, or a magnetic material.

(7) In some embodiments, the fastening strip may extend across a width of the cover portion.

(8) In some embodiments, the cover portion may include a fold line towards the bottom and the fastening strip may be positioned between the fold line and the bottom.

(9) In some embodiments, the one or more fasteners may extend from the top of the cover portion.

(10) In some embodiments, each of the one or more fasteners may extend from a corner of the cover portion.

(11) In some embodiments, the one or more fasteners may comprise two fasteners that extend from opposing corners of the cover portion at a 45-degree angle.

(12) In some embodiments, each of the one or more fasteners may comprise a strap and a fastening component.

(13) In some embodiments, the one or more fasteners may comprise two fasteners, and the fastening components of the two fasteners may interconnect to support the cover portion from the portion of the vehicle.

(14) In some embodiments, at least one of the one or more fasteners may include a fastening

component that is configured to attach to a window of the vehicle.

(15) In some embodiments, at least one of the one or more fasteners may include a fastening component that is configured to attach to a handle of the vehicle.

(16) In some embodiments, at least one of the one or more fasteners may include a fastening component that is configured to attach to a headrest of the vehicle.

(17) In some embodiments, the cover portion may include a stiffening member.

(18) In some embodiments, the present invention may be implemented as a vehicle protection system that includes a vehicle seat cover and a vehicle door guard. The vehicle seat cover may comprise a lower portion that is configured to protect a seat portion of a vehicle seat and an upper portion that is configured to protect a back portion of the vehicle seat. The vehicle door guard may comprise a cover portion that is configured to be secured to the lower portion of the vehicle seat cover and one or more fasteners that are configured to support the cover portion from a portion of the vehicle.

(19) In some embodiments, the cover portion may be configured to be secured to an underside of the lower portion of the vehicle seat cover.

(20) In some embodiments, the one or more fasteners may be configured to support the cover portion from a window, a handle, or a headrest of the vehicle.

(21) In some embodiments, the vehicle seat cover may comprise a front portion that is configured to protect a back portion of a frontward vehicle seat.

(22) In some embodiments, the one or more fasteners may comprise opposing fasteners that extend from top corners of the cover portion, and the cover portion may further comprise a stiffening member that extends between the opposing fasteners.

(23) In some embodiments, the present invention may be implemented as a vehicle door guard that includes a cover portion and one or more fasteners. The cover portion may have a top and a bottom and may be configured to attach to a lower portion of a vehicle seat cover when the vehicle seat cover is installed on a seat portion of a vehicle seat in a vehicle. The one or more fasteners may extend from the cover portion and may be configured to support the cover portion from a portion of the vehicle while the cover portion is secured to the lower portion of the vehicle seat cover to thereby position the cover portion over a door of the vehicle.

(24) This summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Understanding that these drawings depict only typical embodiments of the invention and are not therefore to be considered limiting of its scope, the invention will be described and explained with additional specificity and detail through the use of the accompanying drawings in which:

(2) FIG. 1A provides an example of a vehicle seat cover with which a vehicle door guard can be used in accordance with one or more embodiments of the present invention;

(3) FIG. 1B provides an example of how the vehicle seat cover of FIG. 1A can be used to protect seats of a vehicle;

(4) FIG. 2 provides an example of a vehicle door guard that is configured in accordance with embodiments of the present invention;

(5) FIG. 3 provides an example of how the vehicle door guard of FIG. 2 can be used in conjunction with the vehicle seat cover of FIG. 1B;

(6) FIG. 3A provides examples of how the vehicle door guard of FIG. 2 can be secured;

(7) FIG. 3B provides additional examples of how the vehicle door guard of FIG. 2 can be secured;

- (8) FIG. 4 provides an example of how the vehicle door guard of FIG. 2 can be used in conjunction with another vehicle seat cover;
- (9) FIGS. 5A-5C each provide another example of a vehicle door guard that can be used in conjunction with a vehicle seat cover;
- (10) FIG. 6 provides an example of a vehicle door guard that includes a reinforcement structure;
- (11) FIG. 7 provides an example of another vehicle seat guard with which a vehicle door guard can be used;
- (12) FIGS. 8A and 8B provide examples of how a vehicle door guard can be used with the vehicle seat guard of FIG. 7;
- (13) FIG. 9 provides an example of a fastener that could be used to support a vehicle door guard; and
- (14) FIG. 10 provides an example of another fastener that could be used to support a vehicle door guard.

DETAILED DESCRIPTION

(15) In this specification and the claims, the term “vehicle seat” should be construed as encompassing a bench seat, one or more bucket seats, and other types of vehicle seats. A vehicle seat may be configured to fold and may have multiple sections (e.g., in the case of a bench seat). A vehicle seat will be described as having a seat portion, which is the generally horizontal portion on which an individual may sit, and a back portion, which is the generally vertical portion against which an individual may support his or her back. A “vehicle seat cover” should be construed as an article that covers a vehicle seat. For example, a vehicle seat cover may cover only the seat portion of a vehicle seat or both the seat portion and the back portion of a vehicle seat. Also, as described below, a vehicle seat cover may cover the seat portion and back portion of a rearward seat and a rear side of a back portion of a frontward seat. A vehicle seat cover may also be configured to cover a vehicle seat when the seat portion is folded up such as when the rear seat(s) of a crew cab are folded up. In such cases, the vehicle seat cover could also cover a rear side of a back portion of a frontward seat. A vehicle door guard configured in accordance with embodiments of the present invention can be used with a wide variety of vehicle seat covers to provide protection to a vehicle door and other portions of the vehicle that are positioned to the side of a vehicle seat (e.g., the trim surrounding the door).

(16) FIGS. 1A and 1B provide an example of a vehicle seat cover **10** (or simply cover **10**) with which a vehicle door guard could be used. Cover **10** includes a lower portion **12** that is configured to cover the seat portion of a vehicle seat, an upper portion **14** that is coupled to lower portion **12** and configured to cover the back portion of the vehicle seat, and a front portion **38** that extends from a front edge **40** of lower portion **12** and is configured to cover the rear side of a back portion of another vehicle seat (e.g., the front seat(s)). As shown in FIG. 1B, lower portion **12**, upper portion **14**, and front portion **38** cause cover **10** to resemble a hammock when installed.

(17) Upper portion **14** may include one or more fasteners **28** that are configured to secure/support upper portion **14** to/from the vehicle seat (e.g., by wrapping around the headrests of the rear or middle bench seat). Similarly, front portion **38** may include one or more fasteners **42** that are configured to secure/support front portion **38** to/from the other vehicle seat (e.g., by wrapping around the headrests of the front bucket seats/bench). Fasteners **28** and **42** could be in any suitable form such as straps with buckles, hook and loop, magnets, etc.

(18) Lower portion **12** can have a width that corresponds with the width of the vehicle seat (e.g., to extend across the entirety of the seat portion). In some embodiments, lower portion **12** can include extensions **12a** that extend outwardly from the sides of lower portion **12** and are configured to extend downwardly overtop the sides of the seat portion. In contrast, in some embodiments, lower portion **12** may not include extensions **12a**.

(19) Upper portion **14** may also have a width that corresponds with the width of the vehicle seat (e.g., to extend across the entirety of the back portion). In some embodiments, upper portion **14**

may include one or more vertical slits that enable portions of the vehicle seat to be folded when upper portion **14** is installed. For example, in FIG. **1A**, vertical slits **24** and **26** extend downwardly from an upper edge **22** of upper portion **14** and divide upper portion **14** into sections **16**, **18**, and **20** which may generally match the sections of the vehicle seat on which cover **10** is intended to be used.

(20) Openings **30**, **32**, **34**, and **36** may be formed between upper portion **14** and lower portion **12** to allow seat belts to pass through. In some embodiments, vertical slits **24** and **26** may extend to openings **30** and **32** respectively to allow sections **16** and **20** to be folded back along fold lines **35** and **37** respectively. In this way, upper portion **14** can accommodate vehicle seats with different folding configurations.

(21) FIG. **2** provides an example of a vehicle door guard **200** (or guard **200**) that is configured in accordance with one or more embodiments of the present invention. Guard **200** includes a cover portion **210** that may be made of one or more layers of a fabric material and that is configured to cover at least a portion of a vehicle door while being secured to a vehicle seat cover such as cover **10**. In some embodiments, an edge **211** may extend around cover portion **210**. In some embodiments, including the depicted embodiments, cover portion **210** may have a rectangular shape. However, a cover portion **210** may have different shapes and sizes such as based on the type of vehicle with which it is intended to be used. For example, cover portion **210** may have a width that generally corresponds with the width of lower portion **12** and a height that is sufficient to ensure that cover portion **210** extends up to and possibly beyond the window of the vehicle's door when cover portion **210** is secured to lower portion **12**.

(22) For example, a fastening strip **213** may be formed at or towards a bottom **210a** of cover portion **210**. In some embodiments, fastening strip **213** may be hook and loop material, an adhesive material, a magnetic material, a zipper, one or more buttons, etc. Fastening strip **213** may extend across all or a portion of bottom **210a** and be configured to secure to a corresponding fastening strip formed on/in the lower portion of a vehicle seat cover. A fold line **214** may be formed towards bottom **210a** to facilitate securing fastening strip **213** to the lower portion of the vehicle seat cover such as by folding bottom **210a** underneath the lower portion.

(23) Additionally, one or more fasteners **220** may be formed at or towards a top **210b** of cover portion **210**. In the depicted example, opposing fasteners **220** extend at a 45-degree angle from the corners of top **210b**. However, a fastener **220** could extend from any portion of top **210b**. For example, a single fastener **220** could extend upwardly from a center of top **210b**.

(24) Fasteners **220** could be formed of straps **221** (or other elongated material) and may be secured at one end to cover portion **210**. In some embodiments, a reinforced section **212** may be formed on cover portion **210** and straps **221** may be secured to cover portion **210** at a reinforced section **212**. Each fastener **220** may also include a fastening component **222** that is configured to enable the corresponding strap **221** to be fastened to the other strap **221** and/or to be coupled to a portion of the vehicle. For example, in FIG. **2**, fastening components **222** are interlocking components of a buckle. In other embodiments, a fastening component **222** could be or include a suction cup for attaching strap **221** to the window, could form a buckle or other mechanical or magnetic structure for securing a strap **221** around a headrest, a handle, or other portion of the vehicle, a clip for supporting a strap **221** from the top of the window or other upwardly oriented portion of the vehicle, etc.

(25) FIG. **3** provides an example of how cover portion **210** may be used in conjunction with cover **10** to protect a vehicle door. As shown, bottom **210a** of cover portion **210** can be positioned underneath lower portion **12** of cover **10** and secured thereto via fastening strip **213**. For example, if fastening strip **213** is hook and loop material, corresponding hook and loop material could be included on the underside of lower portion **12**. Alternatively, corresponding hook and loop material could be included on extension **12a**. By employing fastening strip **213** to secure cover portion **210** to lower portion **12**, no gaps will exist between lower portion **12** and cover portion **210**. This can

minimize the likelihood of objects falling between the vehicle seat and the door.

(26) FIG. 3 also generally represents that fasteners **220** can be used to maintain cover portion **210** in a generally vertical orientation while bottom **210a** remains secured to lower portion **12**. In this way, cover portion **210** can protect the door and other areas to the side of the vehicle seat. For example, top **210b** is positioned above the bottom of the window and the sides of cover portion **210** extend substantially across the gap between the back portions of the front and rear seats.

(27) FIG. 3A provides examples of how fasteners **220** can be used to support cover portion **210**. A frontward fastener **220** includes a fastening component **222** in the form of a suction cup that is attached to the window. A rearward fastener **220** includes a fastening component **222** in the form of a buckle or clip that secures strap **221** around the headrest of the rear seat. In this configuration (i.e., with the frontward fastener **220** secured towards the front of the window and the rearward fastener **220** not secured to the door), the door could be opened without removing guard **200**, or more specifically, without disconnecting fasteners **220** or fastening strip **213**.

(28) FIG. 3B provides an example where fasteners **220** are used to support cover portion **210** from the handle above the door. For example, fastening components **222** could form a buckle to allow straps **221** to be looped through the handle. In this example, the door could also be opened without removing guard **200**. This configuration could also be accomplished with a single fastener **220** such as by using a fastening component **222** in the form of a clip or hook that attaches to the handle.

(29) FIG. 4 provides an example of how guard **200** may be used in conjunction with a vehicle seat cover **10a** (or simply cover **10a**) that does not include a front portion **38**. To the contrary, cover **10a** includes a skirt **12b** that extends around lower portion **12**. As with cover **10**, bottom **210a** of cover portion **210** can be secured to lower portion **12** of cover **10a** and fastener(s) **220** can be used to secure cover portion **210** to a portion of the vehicle.

(30) FIGS. 5A-5C provide examples where cover portion **210** of guard **200** has a different shape. In FIG. 5A, which otherwise matches FIG. 3, cover portion **210** is wider at top **210b** than at bottom **210a** such that cover portion **210** has a trapezoidal shape. For example, the side of cover portion **210** towards the rear may more closely align with the angle of the back portion of the rear seat.

(31) In FIG. 5B, which otherwise matches FIG. 4, the width of cover portion **210** is greater than the width/depth of lower portion **12**. Therefore, a portion **510** of cover portion **210** extends frontwardly beyond the seat portion of the vehicle seat. Such configurations may be beneficial when guard **200** is used with a cover, such as cover **10a**, that does not include front portion **38** because guard **200** can protect frontward portions of the door.

(32) FIG. 5C matches FIG. 5B except that portion **510** also extends further downwardly. In other words, portion **510**, which extends frontwardly beyond the seat portion of the vehicle seat, can also extend downwardly beyond the portion of cover portion **210** that is secured to lower portion **12** (e.g., the portion on which fastening strip **213** is positioned). Such configurations can be used to extend protection to the bottom of the door or otherwise towards the floor of the vehicle.

(33) In some embodiments, guard **200** may include a stiffening member to maintain cover portion **210** in a planar orientation. For example, in FIG. 6, a stiffening member **215** is incorporated into cover portion **210** and extends between reinforced sections **212**. Stiffening member **215** can ensure that top **210b** remains planar regardless of how fasteners **220** may be used to support cover portion **210**. Stiffening member **215** could be formed of a metal or plastic bar or any elongated rigid or semi-rigid material. Stiffening member **215** could be formed inside layers of cover portion **210** or may extend along the front or rear surface of cover portion **210**. A stiffening member could also be integrated into cover portion **210** at other locations (e.g., at a midpoint between bottom **210a** and top **210b**).

(34) In some embodiments, the rear side of cover portion **210** (i.e., the side that is configured to face the door) may be formed of a non-slip material. This non-slip material could minimize movement of cover portion **210** relative to the door such as when a pet may lean on or otherwise contact cover portion **210**.

(35) In some embodiments, a vehicle door guard may be a component of a vehicle seat cover. For example, cover **10** and one or more guards **200** could be provided as a vehicle protection system.

(36) FIG. 7 provides an example of a vehicle seat cover **10b** (or simply cover **10b**) that is substantially the same as cover **10** but is designed for use when the seat portion is folded up. As shown, cover **10b** includes upper portion **14**, lower portion **12**, and front portion **38**, but upper portion **14** covers the folded-up seat portion and rear portion of the rearward vehicle seat and lower portion **12** may rest on the floor between the rearward seat and the frontward seat.

(37) FIG. 8A, which is a view from inside the vehicle, and FIG. 8B, which is a view from outside the vehicle with the door open, provide an example of how door guard **200** can be used with cover **10b**. In this example, a front fastener **220** is used to support door guard **200** from a handle along the front side of the window and a rear fastener **220** is used to support door guard from a headrest of the rearward seat.

(38) FIG. 9 provides an example of a fastener **900** that could be used with fastener **220**. Fastener **900** includes an adjustable strap **901** that may be selectively secured around a component of the vehicle such as a handle. For example, strap **901** could include hook and loop material to allow it to be tightened around handles or other components of various sizes. Fastener **900** may also include a fastening component **902** that corresponds with fastening component **222**. Accordingly, fastening component **222** can be coupled to fastening component **902** to support door guard **200** from any component to which fastener **900** may be secured.

(39) FIG. 10 provides an example of a fastener **1000** that could be used with fastener **220**. Fastener **1000** includes a hooking member **1001** (e.g., a carabiner, quick link, hook, etc.) that can be secured to a headrest or other component of the vehicle. An adjustable strap **1002** can be secured between hooking member **1001** and a fastening component **1003**. Fastening component **1003** can correspond with fastening component **222** so that door guard can be supported from any component to which fastener **1000** may be secured.

(40) In summary, a vehicle door guard can be configured to be secured to a lower portion of a car seat cover and to one or more portions of the vehicle to thereby extend protection to the door and/or portions of the vehicle to the side of a vehicle seat. The vehicle door guard can eliminate any gap to the side of the vehicle seat to thereby block objects from falling between the vehicle seat and door. The vehicle door guard may also be quickly detached from the vehicle seat cover if desired but need not be removed to open and close the door. Accordingly, a vehicle door guard can provide additional protection when a dog or other pet is transported in a vehicle.

(41) The present invention may be embodied in other specific forms without departing from its spirit or essential characteristics. The described embodiments are to be considered in all respects only as illustrative and not restrictive. The scope of the invention is, therefore, indicated by the appended claims rather than by the foregoing description.

Claims

1. A vehicle door guard configured to cover and protect at least a portion of a door, the door guard comprising: a cover portion having a top and a bottom, the cover portion including a fastening strip that is positioned towards the bottom, the fastening strip being configured to selectively secure the cover portion to an underside of a lower portion of a vehicle seat cover when the vehicle seat cover is installed on a vehicle seat in a vehicle, the underside of the lower portion of the vehicle seat cover being configured to face an upholstery of the vehicle when the vehicle seat cover is installed on the vehicle seat, wherein the fastening strip is further configured to selectively detach from the underside of the lower portion of the vehicle seat cover, wherein when the fastening strip is detached from the underside of the lower portion of the vehicle seat cover, the bottom of the cover portion extends below the vehicle seat to protect a lower portion of a door disposed below the vehicle seat; and one or more fasteners that extend from the cover portion, the one or more

fasteners being configured to selectively support the cover portion from a portion of the vehicle and retain the cover portion in a substantially vertical orientation to protect a door of the vehicle when the door is closed, wherein the one or more fasteners are further configured to selectively retain the cover portion in the substantially vertical orientation when the door is open, thereby selectively providing a barrier between an interior and an exterior of the vehicle when the door is open, and wherein a top of the vehicle door guard includes an elongated bar extending from a first corner to a second corner, the elongated bar being configured to maintain the top of the vehicle door guard in a planar configuration.

2. The vehicle door guard of claim 1, wherein the fastening strip comprises at least one of: a hook and loop material, an adhesive material, and a magnetic material.

3. The vehicle door guard of claim 2, wherein the underside of the lower portion of the vehicle seat cover comprises a corresponding fastening strip extending across a width of the lower portion of the vehicle seat cover, wherein the fastening strip extends across a width of the cover portion, and wherein the fastening strip is configured to secure to the corresponding fastening strip along the width of the lower portion and the width of the cover portion.

4. The vehicle door guard of claim 1, wherein the cover portion includes a fold line towards the bottom, the fastening strip being positioned between the fold line and the bottom, wherein the fold line allows a folding portion of the cover portion to be selectively disposed in: (i) a substantially horizontal orientation such that the fastening strip can selectively couple the cover portion to the lower portion of the vehicle seat cover; and (ii) a substantially vertical orientation such that the cover portion extends downwardly past the lower portion of the vehicle seat cover.

5. The vehicle door guard of claim 1, wherein the one or more fasteners extend from the top of the cover portion or from a corner of the cover portion.

6. The vehicle door guard of claim 5, wherein the one or more fasteners comprise two fasteners that extend from opposing corners of the cover portion at a 45-degree angle.

7. The vehicle door guard of claim 1, wherein each of the one or more fasteners comprises a strap and a fastening component.

8. The vehicle door guard of claim 7, wherein the one or more fasteners comprise two fasteners, and wherein the fastening components of the two fasteners interconnect to support the cover portion from the portion of the vehicle.

9. The vehicle door guard of claim 1, wherein at least one of the one or more fasteners includes a fastening component that is configured to attach to at least one of a window of the vehicle, a handle of the vehicle, and a headrest of the vehicle.

10. The vehicle door guard of claim 1, wherein the top of the cover portion is stiff enough to be maintained in a planar orientation, whereas the bottom of the cover portion is flexible enough to fold.

11. A vehicle protection system comprising: a vehicle seat cover comprising a lower portion that is configured to protect a seat portion of a vehicle seat and an upper portion that is configured to protect a back portion of the vehicle seat; and a vehicle door guard comprising a cover portion that is configured to be selectively secured to the lower portion of the vehicle seat cover and one or more fasteners that are configured to selectively support the cover portion from a portion of the vehicle and retain the cover portion in a substantially vertical orientation to protect a door of the vehicle when the door is closed, wherein the one or more fasteners are further configured to selectively retain the cover portion in the substantially vertical orientation when the door is open, thereby selectively providing a barrier between an interior and an exterior of the vehicle when the door is open, and wherein a top of the vehicle door guard includes an elongated bar extending from a first corner to a second corner, the elongated bar being configured to maintain the top of the vehicle door guard in a planar configuration.

12. The vehicle protection system of claim 11, wherein a bottom of the cover portion is flexible, and wherein the bottom of the cover portion is configured to be secured to an underside of the

lower portion of the vehicle seat cover.

13. The vehicle protection system of claim 11, wherein the cover comprises multiple layers of material, and wherein the elongated bar is incorporated between layers of the material.

14. The vehicle protection system of claim 11, wherein the elongated bar extends along a rear surface of the cover portion.

15. The vehicle protection system of claim 11, wherein the elongated bar extends along a front surface of the cover portion.

16. A vehicle door guard comprising: a cover portion having a top and a bottom, the cover portion being configured to selectively attach to a lower portion of a vehicle seat cover when the vehicle seat cover is installed on a seat portion of a vehicle seat in a vehicle; and one or more fasteners that extend from the cover portion, the one or more fasteners being configured to selectively support the cover portion from a portion of the vehicle while the cover portion is secured to the lower portion of the vehicle seat cover to thereby position the cover portion over a door of the vehicle and retain the cover portion in a substantially vertical orientation to protect the door when the door is closed, wherein the one or more fasteners are further configured to selectively retain the cover portion in the substantially vertical orientation when the door is open, thereby selectively providing a barrier between an interior and an exterior of the vehicle when the door is open, wherein a top of the vehicle door guard includes an elongated bar extending from a first corner to a second corner, the elongated bar being configured to maintain the top of the vehicle door guard in a planar configuration, and wherein a rear side of the cover portion configured to face the door comprises a non-slip material configured to minimize movement of the cover portion relative to the door.

17. The vehicle door guard of claim 16, wherein the cover portion is configured to selectively extend downward beyond the lower portion of the vehicle seat cover.

18. The vehicle door guard of claim 16, wherein the cover portion has a width that is greater than a width of the seat portion.

19. The vehicle door guard of claim 16, wherein a side of the cover portion is sloped, thereby allowing the side of the cover portion to more closely align with an angle of a seatback portion of the vehicle.
