

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12410818
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Nelson; Christopher et al.

Hydrogen recirculation pump heating and sealing assemblies and methods

Abstract

A recirculation pump includes an impeller, a pump motor assembly, and a heater. The pump motor assembly includes a pump housing having a pump cavity and a pump motor arranged in the pump cavity that drives the impeller, the pump housing arranged axially away from the impeller. The heater is disposed on or in the pump housing and spaced apart from the impeller. The heater is configured to increase a temperature of any portion of the fluid that leaks from the impeller into the pump cavity and resides in the pump cavity. The increase in the temperature causes the fluid that resides in the pump cavity to flow toward the impeller and exit the pump cavity.

Inventors: Nelson; Christopher (Columbus, IN), Epp; Bryn (Barrie, CA), Joos; Nathaniel Ian (Toronto, CA)

Applicant: CUMMINS INC. (Columbus, IN); HYDROGENICS CORPORATION (Mississauga, CA)

Family ID: 88413823

Assignee: CUMMINS INC. (Columbus, IN); HYDROGENICS CORPORATION (Mississauga, CA)

Appl. No.: 18/482858

Filed: October 07, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240128483 A1	Apr. 18, 2024

Related U.S. Application Data

us-provisional-application US 63379557 20221014

Publication Classification

Int. Cl.: **H01M8/04089** (20160101); **F04D13/06** (20060101); **F04D25/06** (20060101); **F04D29/046** (20060101); **F04D29/08** (20060101); **F04D29/58** (20060101); **F04D29/70** (20060101); **H01M8/04007** (20160101); **H01M8/04303** (20160101); **H01M8/04701** (20160101); **H01M8/04746** (20160101); **H01M8/04955** (20160101)

U.S. Cl.:

CPC **F04D29/588** (20130101); **F04D13/06** (20130101); **F04D25/06** (20130101); **F04D25/0606** (20130101); **F04D29/046** (20130101); **F04D29/08** (20130101); **F04D29/584** (20130101); **F04D29/586** (20130101); **F04D29/706** (20130101); **H01M8/04007** (20130101); **H01M8/04097** (20130101); **H01M8/04303** (20160201); **H01M8/04708** (20130101); **H01M8/04753** (20130101); **H01M8/04955** (20130101); **F05D2260/6022** (20130101)

Field of Classification Search

CPC: F04D (29/588); F04D (13/06); F04D (25/06); F04D (25/0606); F04D (29/046); F04D (29/08); F04D (29/584); F04D (29/586); F04D (29/706); H01M (8/04007); H01M (8/04097); H01M (8/04303); H01M (8/04708); H01M (8/04753); H01M (8/04955); F05D (2260/6022)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6964820	12/2004	Shimonosono et al.	N/A	N/A
2008/0118787	12/2007	Wexel et al.	N/A	N/A
2009/0169928	12/2008	Nishimura et al.	N/A	N/A
2021/0190135	12/2020	Pawellek et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
111156181	12/2019	CN	N/A
113007122	12/2020	CN	N/A
113153769	12/2020	CN	N/A
1770806	12/2006	EP	N/A
2004190688	12/2003	JP	N/A
20120115768	12/2011	KR	N/A
2009/049715	12/2008	WO	N/A
2012/022549	12/2011	WO	N/A
WO-2024050033	12/2023	WO	B60H 1/3226

OTHER PUBLICATIONS

US Motors, Heaters and Trickle Voltage: Heating to Combat Motor Condensation, <https://acim.nidec.com/motors/usmotors/techdocs/profacts/heaters-tricklevoltage>. cited by applicant

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This nonprovisional application claims the benefit and priority, under 35 U.S.C. § 119(e) and any other applicable laws or statutes, to U.S. Provisional Application Ser. No. 63/379,557 filed on Oct. 14, 2022, the entire disclosure of which is hereby expressly incorporated herein by reference.

TECHNICAL FIELD

(1) The present disclosure generally relates to fuel cell assemblies, and in particular, hydrogen recirculation pumps of fuel cell assemblies.

BACKGROUND

(2) A single fuel cell is one of many repeating units of a fuel cell stack that may provide power or energy for personal and/or industrial use. The typical proton exchange membrane (PEM) fuel cell is comprised of many fuel cell assemblies compressed and bound into a fuel cell stack. A PEM fuel cell is a multi-component assembly that often comprises a membrane electrode assembly (MEA) at the center, a gas diffusion layer (GDL) on either side of the membrane electrode assembly (MEA), and a bipolar plate (BPP) on either side of the gas diffusion layer (GDL). The membrane electrode assembly (MEA) is the component that enables electrochemical reactions in the fuel cell and/or fuel cell stack. Typically, a PEM fuel cell and/or fuel cell stack is assembled with the aforementioned components to operate in a useful and reliable manner.

(3) In many mobility applications, the reactants supplied to the fuel cell are pure hydrogen for the anode and an oxidant for the cathode. In the cathode, nitrogen often accompanies oxygen as the supply is from atmospheric air to avoid onboard storage. The anode is typically supplied with pure hydrogen from highly compressed gaseous or liquefied hydrogen stored in onboard tanks. A cooling system is often required to provide a heat sink to manage excess heat produced during the electrochemical reactions, and to keep the fuel cell at an appropriate temperature during operation.

(4) Typical PEM fuel cells use a hydrogen recirculation pump (HRP) to continually present fresh hydrogen to the PEM anode side. As hydrogen is consumed by the PEM fuel cell, it must be refreshed. While additional hydrogen is added, it is vital that the hydrogen is moved across the PEM cell to achieve peak performance.

(5) With reactant gas molecules present in the active area, the MEA will produce a voltage potential, and current draw or load is supported by reactant flow rate. During the generation of electricity, moisture is created on the anode side of the cell and humidifies the hydrogen fuel such that humidified water may form. Moving or pumping, the (now humidified) hydrogen is done in several ways. Pumps of various types are employed as are ejector type systems. For pump-based systems, it is vital to the longevity of the pump that minimal water, which condenses from the humidified hydrogen, is permitted to reside within the pump's interior (pump motor cavity).

(6) Accordingly, it would be advantageous to provide a fuel cell assembly, and in particular a pump system, that could at least remove water from inside the pump motor cavity or even prevent entry of water into the cavity altogether.

SUMMARY

(7) According to a first aspect of the present disclosure, a recirculation pump for a fuel cell system includes an impeller, a pump motor assembly, and at least one heater. The impeller is configured to rotate and impel a fluid from an inlet to an outlet. The pump motor assembly includes a pump housing having a pump cavity therein and a pump motor arranged in the pump cavity and

configured to drive the impeller, the pump housing arranged axially away from the impeller. The at least one heater is disposed on or in the pump housing and spaced apart from the impeller, the at least one heater being configured to increase a temperature of any portion of the fluid that leaks from the impeller into the pump cavity and resides in the pump cavity. The increase in the temperature causes the fluid that resides in the pump cavity to flow toward the impeller and exit the pump cavity.

(8) In some embodiments, the recirculation pump further includes an impeller assembly including an impeller housing having an impeller cavity therein and having the inlet and the outlet, the inlet spaced apart from the outlet on a first side of the impeller housing. Each of the inlet and outlet opening into the impeller cavity. The impeller assembly further includes the impeller arranged in the impeller cavity and configured to impel the fluid entering the impeller cavity from the inlet to the outlet such that the fluid exits the impeller housing via the outlet.

(9) In some embodiments, the pump housing is disposed on a second side of the impeller housing opposite the first side, and a first heater of the at least one heater is arranged on a second side of the pump housing opposite a first side of the pump housing facing the impeller housing. A second heater of the at least one heater is arranged on an outer surface of the pump housing axially between the first side and the second side of the pump housing. The second heater is located axially closer to the second side of the pump housing than the first side of the pump housing.

(10) In some embodiments, at least one additional heater of the at least one heater and the second heater are arranged on the outer surface of the pump housing axially between the first side and the second side of the pump housing. The pump motor is coupled to the impeller via a drive shaft, and wherein the pump motor drives rotation of the drive shaft and rotation of the impeller.

(11) In some embodiments, the recirculation pump further includes a bearing assembly arranged axially between the pump motor assembly and the impeller assembly, the bearing assembly including a bearing housing having a first side arranged on a second side of the impeller housing opposite the first side of the impeller housing and having a bearing cavity defined therein, the bearing assembly further including a bearing seal arranged in the bearing cavity. The drive shaft extends from the pump motor through the bearing cavity and to the impeller, and wherein the drive shaft is arranged within and rotatably supported by the bearing seal.

(12) In some embodiments, the bearing assembly further includes a lip seal disposed within the bearing cavity between the bearing seal and the impeller and a grease material disposed within the bearing cavity between the lip seal and the bearing seal, the grease material being arranged adjacent to and abutting the bearing seal and arranged around a circumferential outer surface of the drive shaft. The lip seal is arranged so as to retain the grease material in position abutting the bearing seal, so as to allow pressure to escape the pump cavity, and so as to seal against pressure from the impeller cavity. In some embodiments, the lip seal is comprised of a fluoroelastomeric material and the grease material is comprised of a hydrogen resistant material. In some embodiments, the grease material is comprised of perfluoropolyether.

(13) According to a further aspect of the present disclosure, a recirculation pump for a fuel cell system includes an impeller and a bearing assembly. The impeller includes a drive shaft centrally coupled to the impeller, the impeller being configured to rotate and impel a fluid from an inlet of the impeller to an outlet of the impeller. The bearing assembly is arranged axially away from the impeller, the bearing assembly including a bearing housing having a bearing cavity defined therein and a bearing seal arranged in the bearing cavity. The drive shaft extends from the impeller and through the bearing cavity. The drive shaft is arranged within and rotatably supported by the bearing seal. The bearing assembly further includes a lip seal disposed within the bearing cavity and a grease material disposed within the bearing cavity between the lip seal and the bearing seal.

(14) In some embodiments, the lip seal is arranged so as to retain the grease material between the lip seal and the bearing seal, so as to allow pressure to escape the pump cavity, and so as to seal against pressure from the impeller cavity. In some embodiments, the lip seal is comprised of a

fluoroelastomeric material and the grease material is comprised of a hydrogen resistant material. In some embodiments, the grease material is comprised of perfluoropolyether.

(15) In some embodiments, the recirculation pump further includes a pump motor assembly and at least one heater. The pump motor assembly includes a pump housing having a pump cavity therein and a pump motor arranged in the pump cavity, the drive shaft being coupled to the pump motor such that the pump motor is configured to drive the impeller, the pump housing being arranged adjacent to the bearing housing on a side of the bearing housing opposite the impeller. The at least one heater is disposed on or in the pump housing and spaced apart from the bearing housing, the at least one heater being configured to increase a temperature of any portion of the fluid that leaks from the impeller, through the bearing cavity, and into the pump cavity and resides in the pump cavity. The increase in the temperature causes the fluid that resides in the pump cavity to flow toward the impeller and exit the pump cavity.

(16) In some embodiments, a first heater of the at least one heater is arranged on a second side of the pump housing opposite a first side of the pump housing facing the bearing housing, and a second heater of the at least one heater is arranged on an outer surface of the pump housing axially between the first side and the second side of the pump housing.

(17) According to a further aspect of the present disclosure, a method includes providing a pump motor assembly including a pump housing having a pump cavity therein and a pump motor arranged in the pump cavity, arranging at least one heater on or in the pump housing and spaced apart from an impeller, and rotating the impeller via the pump motor such that the impeller impels the fluid from an inlet of the impeller to an outlet of the impeller, wherein the pump housing is arranged axially away from the impeller. The method further includes, in response to the fuel cell system being shut off, via a controller, activating the at least one heater and increasing a temperature of any portion of the fluid that leaks from the impeller into the pump cavity and resides in the pump cavity. Increasing the temperature causes the fluid residing in the pump cavity to flow toward the impeller and exit the pump cavity. The method further includes, in response to the at least one heater having been active for a first amount of time based on a first operating condition of the fuel cell system, via the controller, deactivating the at least one heater.

(18) In some embodiments, the first operating condition is when all fluid residing in the pump cavity has exited the pump cavity via the increase in temperature caused by the at least one heater.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) This disclosure will be more fully understood from the following detailed description taken in conjunction with the accompanying drawings, in which:

(2) FIG. 1A is a schematic view of an exemplary fuel cell system including an air delivery system, a hydrogen delivery system, and a fuel cell module including a stack of multiple fuel cells;

(3) FIG. 1B is a cutaway view of an exemplary fuel cell system including an air delivery system, hydrogen delivery systems, and a plurality of fuel cell modules each including multiple fuel cell stacks;

(4) FIG. 1C is a perspective view of an exemplary repeating unit of a fuel cell stack of the fuel cell system of FIG. 1A;

(5) FIG. 1D is a cross-sectional view of an exemplary repeating unit of the fuel cell stack of FIG. 1C;

(6) FIG. 2A is a cross-sectional view of a hydrogen recirculation pump according to a first aspect of the present disclosure, showing that the hydrogen recirculation pump includes an impeller, a pump motor assembly, and heaters disposed on a pump housing of the pump motor assembly;

(7) FIG. 2B is a schematic front view of the impeller of the hydrogen recirculation pump of FIG.

2A;

- (8) FIG. 2C is a cross-sectional view of the hydrogen recirculation pump of FIG. 2A, showing that the heaters arranged in the pump cavity of the pump housing;
- (9) FIG. 2D is a cross-sectional view of the hydrogen recirculation pump of FIG. 2A, showing that the heaters arranged in the outer wall of the pump housing;
- (10) FIG. 3 is a schematic view of the hydrogen recirculation pump of FIG. 2A, showing the arrangement of the hydrogen recirculation pump relative to the fuel cell system components of the fuel cell system of FIGS. 1A-1D;
- (11) FIG. 4A is a cross-sectional view of a hydrogen recirculation pump according to a further aspect of the present disclosure, showing that the hydrogen recirculation pump includes an impeller, a pump motor assembly, and a bearing assembly between the impeller and the pump motor assembly, and showing that the bearing assembly including a bearing cavity through which a drive shaft of a pump motor of the pump motor assembly extends, a bearing seal arranged around the drive shaft in the bearing cavity, and a lip seal and a grease material arranged in the bearing cavity around the shaft and adjacent the bearing seal;
- (12) FIG. 4B is a cross-sectional view of the bearing seal, the lip seal, and the grease material of the hydrogen recirculation pump of FIG. 4A;
- (13) FIG. 4C is a cross-sectional view of the bearing seal, the grease material, and an alternative lip seal of the hydrogen recirculation pump of FIG. 4A, differing from the lip seal shown in FIGS. 4A and 4B in that the alternative lip seal includes a lip that rests on an outer surface of the bearing housing;
- (14) FIG. 5 is a cross-sectional view of a hydrogen recirculation pump according to a further aspect of the present disclosure, showing that the hydrogen recirculation pump includes a heating flow system configured to pump warm water through the pump cavity so as to heat condensed water residing in the pump cavity; and
- (15) FIG. 6 is a schematic view of a controller and related components configured to be utilized with the hydrogen recirculation pumps of FIGS. 1-5.

DETAILED DESCRIPTION

- (16) As shown in FIG. 1A, fuel cell systems **10** often include one or more fuel cell stacks **12** (“STK”) or fuel cell modules **14** connected to a balance of plant (BOP) **16**, including various components, to support the electrochemical conversion, generation, and/or distribution of electrical power to help meet modern day industrial and commercial needs in an environmentally friendly way. As shown in FIGS. 1B and 1C, fuel cell systems **10** may include fuel cell stacks **12** comprising a plurality of individual fuel cells **20**. Each fuel cell stack **12** may house a plurality of fuel cells **20** assembled together in series and/or in parallel. The fuel cell system **10** may include one or more fuel cell modules **14** as shown in FIGS. 1A and 1B.
- (17) Each fuel cell module **14** may include a plurality of fuel cell stacks **12** and/or a plurality of fuel cells **20**. The fuel cell module **14** may also include a suitable combination of associated structural elements, mechanical systems, hardware, firmware, and/or software that is employed to support the function and operation of the fuel cell module **14**. Such items include, without limitation, piping, sensors, regulators, current collectors, seals, and insulators.
- (18) The fuel cells **20** in the fuel cell stacks **12** may be stacked together to multiply and increase the voltage output of a single fuel cell stack **12**. The number of fuel cell stacks **12** in a fuel cell system **10** can vary depending on the amount of power required to operate the fuel cell system **10** and meet the power need of any load. The number of fuel cells **20** in a fuel cell stack **12** can vary depending on the amount of power required to operate the fuel cell system **10** including the fuel cell stacks **12**.
- (19) The number of fuel cells **20** in each fuel cell stack **12** or fuel cell system **10** can be any number. For example, the number of fuel cells **20** in each fuel cell stack **12** may range from about 100 fuel cells to about 1000 fuel cells, including any specific number or range of number of fuel cells **20** comprised therein (e.g., about 200 to about 800). In an embodiment, the fuel cell system **10**

may include about 20 to about 1000 fuel cells stacks **12**, including any specific number or range of number of fuel cell stacks **12** comprised therein (e.g., about 200 to about 800). The fuel cells **20** in the fuel cell stacks **12** within the fuel cell module **14** may be oriented in any direction to optimize the operational efficiency and functionality of the fuel cell system **10**.

(20) The fuel cells **20** in the fuel cell stacks **12** may be any type of fuel cell **20**. The fuel cell **20** may be a polymer electrolyte membrane or proton exchange membrane (PEM) fuel cell, an anion exchange membrane fuel cell (AEMFC), an alkaline fuel cell (AFC), a molten carbonate fuel cell (MCFC), a direct methanol fuel cell (DMFC), a regenerative fuel cell (RFC), a phosphoric acid fuel cell (PAFC), or a solid oxide fuel cell (SOFC). In an exemplary embodiment, the fuel cells **20** may be a polymer electrolyte membrane or proton exchange membrane (PEM) fuel cell or a solid oxide fuel cell (SOFC).

(21) In an embodiment shown in FIG. **1C**, the fuel cell stack **12** includes a plurality of proton exchange membrane (PEM) fuel cells **20**. Each fuel cell **20** includes a single membrane electrode assembly (MEA) **22** and a gas diffusion layers (GDL) **24**, **26** on either or both sides of the membrane electrode assembly (MEA) **22** (see FIG. **1C**). The fuel cell **20** further includes a bipolar plate (BPP) **28**, **30** on the external side of each gas diffusion layers (GDL) **24**, **26**, as shown in FIG. **1C**. The above-mentioned components, in particular the bipolar plate **30**, the gas diffusion layer (GDL) **26**, the membrane electrode assembly (MEA) **22**, and the gas diffusion layer (GDL) **24** comprise a single repeating unit **50**.

(22) The bipolar plates (BPP) **28**, **30** are responsible for the transport of reactants, such as fuel **32** (e.g., hydrogen) or oxidant **34** (e.g., oxygen, air), and cooling fluid **36** (e.g., coolant and/or water) in a fuel cell **20**. The bipolar plates (BPP) **28**, **30** can uniformly distribute reactants **32**, **34** to an active area **40** of each fuel cell **20** through oxidant flow fields **42** and/or fuel flow fields **44** formed on outer surfaces of the bipolar plates (BPP) **28**, **30**. The active area **40**, where the electrochemical reactions occur to generate electrical power produced by the fuel cell **20**, is centered, when viewing the stack **12** from a top-down perspective, within the membrane electrode assembly (MEA) **22**, the gas diffusion layers (GDL) **24**, **26**, and the bipolar plate (BPP) **28**, **30**.

(23) The bipolar plates (BPP) **28**, **30** may each be formed to have reactant flow fields **42**, **44** formed on opposing outer surfaces of the bipolar plate (BPP) **28**, **30**, and formed to have coolant flow fields **52** located within the bipolar plate (BPP) **28**, **30**, as shown in FIG. **1D**. For example, the bipolar plate (BPP) **28**, **30** can include fuel flow fields **44** for transfer of fuel **32** on one side of the plate **28**, **30** for interaction with the gas diffusion layer (GDL) **26**, and oxidant flow fields **42** for transfer of oxidant **34** on the second, opposite side of the plate **28**, **30** for interaction with the gas diffusion layer (GDL) **24**. As shown in FIG. **1D**, the bipolar plates (BPP) **28**, **30** can further include coolant flow fields **52** formed within the plate (BPP) **28**, **30**, generally centrally between the opposing outer surfaces of the plate (BPP) **28**, **30**. The coolant flow fields **52** facilitate the flow of cooling fluid **36** through the bipolar plate (BPP) **28**, **30** in order to regulate the temperature of the plate (BPP) **28**, **30** materials and the reactants. The bipolar plates (BPP) **28**, **30** are compressed against adjacent gas diffusion layers (GDL) **24**, **26** to isolate and/or seal one or more reactants **32**, **34** within their respective pathways **44**, **42** to maintain electrical conductivity, which is required for robust operation of the fuel cell **20** (see FIGS. **1C** and **1D**).

(24) The fuel cell system **10** described herein, may be used in stationary and/or immovable power system, such as industrial applications and power generation plants. The fuel cell system **10** may also be implemented in conjunction with an air delivery system **18**. Additionally, the fuel cell system **10** may also be implemented in conjunction with a hydrogen delivery system and/or a source of hydrogen **19** such as a pressurized tank, including a gaseous pressurized tank, cryogenic liquid storage tank, chemical storage, physical storage, stationary storage, an electrolysis system, or an electrolyzer. In one embodiment, the fuel cell system **10** is connected and/or attached in series or parallel to a hydrogen delivery system and/or a source of hydrogen **19**, such as one or more hydrogen delivery systems and/or sources of hydrogen **19** in the BOP **16** (see FIG. **1A**). In another

embodiment, the fuel cell system **10** is not connected and/or attached in series or parallel to a hydrogen delivery system and/or a source of hydrogen **19**.

(25) In some embodiments, the fuel cell system **10** may include an on/off valve **10XV1**, a pressure transducer **10PT1**, a mechanical regulator **10REG**, and a venturi **10VEN** arranged in operable communication with each other and downstream of the hydrogen delivery system and/or source of hydrogen **19**. The pressure transducer **10PT1** may be arranged between the on/off valve **10XV1** and the mechanical regulator **10REG**. In some embodiments, a proportional control valve may be utilized instead of a mechanical regulator **10REG**. In some embodiments, a second pressure transducer **10PT2** is arranged downstream of the venturi **10VEN**, which is downstream of the mechanical regulator **10REG**.

(26) In some embodiments, the fuel cell system **10** may further include a recirculation pump **10REC** downstream of the stack **12** and operably connected to the venturi **10VEN**. The fuel cell system **10** may also include a further on/off valve **10XV2** downstream of the stack **12**, and a pressure transfer valve **10PSV**.

(27) The present fuel cell system **10** may also be comprised in mobile applications. In an exemplary embodiment, the fuel cell system **10** is in a vehicle and/or a powertrain **100**. A vehicle **100** comprising the present fuel cell system **10** may be an automobile, a pass car, a bus, a truck, a train, a locomotive, an aircraft, a light duty vehicle, a medium duty vehicle, or a heavy-duty vehicle. Type of vehicles **100** can also include, but are not limited to commercial vehicles and engines, trains, trolleys, trams, planes, buses, ships, boats, and other known vehicles, as well as other machinery and/or manufacturing devices, equipment, installations, among others.

(28) The vehicle and/or a powertrain **100** may be used on roadways, highways, railways, airways, and/or waterways. The vehicle **100** may be used in applications including but not limited to off highway transit, bobtails, and/or mining equipment. For example, an exemplary embodiment of mining equipment vehicle **100** is a mining truck or a mine haul truck.

(29) In addition, it may be appreciated by a person of ordinary skill in the art that the fuel cell system **10**, fuel cell stack **12**, and/or fuel cell **20** described in the present disclosure may be substituted for any electrochemical system, such as an electrolysis system (e.g., an electrolyzer), an electrolyzer stack, and/or an electrolyzer cell (EC), respectively. As such, in some embodiments, the features and aspects described and taught in the present disclosure regarding the fuel cell system **10**, stack **12**, or cell **20** also relate to an electrolyzer, an electrolyzer stack, and/or an electrolyzer cell (EC). In further embodiments, the features and aspects described or taught in the present disclosure do not relate, and are therefore distinguishable from, those of an electrolyzer, an electrolyzer stack, and/or an electrolyzer cell (EC).

(30) The present disclosure is directed to systems, assemblies, and methods of removing water from inside a pump motor cavity of a hydrogen recirculation pump and/or preventing entry of water into the cavity altogether. This is accomplished via the disclosed hydrogen recirculation pumps **110**, **210**, **310** (as shown in FIGS. 2A, 4A, and 5), which include a heater configured to heat water residing in the pump cavity so as to cause the water to move out of the pump cavity and/or a seal configured to keep water out of the pump cavity. The disclosed hydrogen recirculation pumps **110**, **210**, **310** are also resistant to damage from hydrogen flowing outside of the pump cavity that interacts with the seal. The hydrogen recirculation pumps **110**, **210**, **310** disclosed herein may be utilized with the fuel cell system **10** described above. A person skilled in the art will appreciate that the assemblies and methods described herein with reference to the hydrogen recirculation pumps **110**, **210**, **310** may be applicable to other types of pumps, including alternative types of recirculation pumps.

(31) FIG. 2A shows a cross-section of the hydrogen recirculation pump **110** according to a first aspect of the present disclosure. As described above, the hydrogen recirculation pump **110** is configured to continually present fresh hydrogen to the anode side of a fuel cell **20** of the fuel cell stack **12** of the fuel cell system **10**, which in some embodiments may be the gas diffusion layer **26**,

as shown in FIGS. 1C and 1D.

(32) As can be seen in FIG. 2A, the hydrogen recirculation pump **110** includes a pump motor assembly **120**, a bearing assembly **150**, and an impeller assembly **180**. As will be described in greater detail, various components of the assemblies **120**, **150**, **180** are configured to rotate about a central axis **112** of the pump **110**. The pump motor assembly **120** is configured to drive an impeller **184** of the impeller assembly **180** (see FIG. 2B). Referring back to FIG. 2A, the bearing assembly **150** is configured to provide rotational support to a drive shaft **131** of a pump motor **130** of the pump motor assembly **120** via a bearing seal **154**. Illustratively, the bearing assembly **150** is arranged axially between the pump motor assembly **120** and the impeller assembly **180**.

(33) The pump motor assembly **120** includes a pump housing **122** configured to house the components of the pump motor **130**, as shown in FIG. 2A. The pump housing **122** may be formed with an outer wall **124** that defines a pump cavity **123** within which at least some of the components of the pump motor **130** are housed. In some embodiments, the outer wall **124** may be cylindrical such that the central axis of the cylindrical outer wall **124** extends in the same direction as the central axis **112** of the pump **110**. In some embodiments, the central axis of the cylindrical outer wall **124** is colinear with the central axis **112** of the pump **110**, as shown in FIG. 2A. Illustratively, the pump cavity **123** is defined by an inner surface **125** of the outer wall **124**, as shown in FIG. 2A. In some embodiments, the inner surface **125** is also cylindrical. A person skilled in the art will understand that additional components or structures may be arranged on the inner surface **125** of the outer wall **124** such that the additional components or structures define the pump cavity **123**.

(34) As shown in FIG. 2A, at least some components of the pump motor **130** are arranged within the pump cavity **123** and operate therein. The pump motor **130** is configured to rotationally drive a central drive shaft **131** of the pump motor **130**, which is coupled to the impeller **184** so as to drive the impeller **184**. Illustratively, the pump motor **130** is an electric motor that includes the drive shaft **131**, a rotor **132** circumferentially surrounding the drive shaft **131** and arranged in the pump cavity **123**, and a plurality of stators **134** annularly arranged around and spaced apart from the rotor **132**. In some embodiments, as shown in FIG. 2A, the stators **134** are arranged within the outer wall **124** and include coils configured to electromagnetically interact with magnets of the rotor **132** so as to selectively rotate the rotor **132**. In some embodiments, the rotor **132** is cylindrical and generally matches the contour of the inner surface **125**. A person skilled in the art will understand that motors other than electric motors may be utilized as the pump motor **130**, so long as the motor is capable of rotating the impeller **184** at the requisite rotational speeds and torque required of the hydrogen recirculation pump **110**.

(35) The pump housing **122** may further include a support cavity **127** that is axially offset from the pump cavity **123** and opens into the pump cavity **123**, as shown in FIG. 2A. In particular, the support cavity **127** may be formed as a cylindrical or annular cavity having one axial end opening **1270** into the pump cavity **123** and the opposite axial end being an end wall **127E** of the cavity **127** defined by the inner surface **125** of the outer wall **124**. Illustratively, the diameter of the support cavity **127** is less than the diameter of the pump cavity **123**, as shown in FIG. 2A. In some embodiments, the diameter of the support cavity **127** is approximately half of the diameter of the pump cavity **123**.

(36) As will be described in greater detail below, a first axial end portion **131A** of the drive shaft **131** extends through the bearing assembly **150** and is coupled to the impeller **184**, as shown in FIG. 2A. The first axial end portion **131A** is rotationally supported within the bearing cavity **153** of the bearing housing **152** via a first bearing seal **154**. Similarly, a second axial end portion **131B** of the drive shaft **131** extends into the support cavity **127** and is rotationally supported therein via a second bearing seal **160**. In some embodiments, the second bearing seal **160** may be sized such that an outer surface **161** of the bearing seal **160** contacts the inner surface **127S** of the support cavity **127**, as shown in FIG. 2C. A person skilled in the art will understand that any known type of

bearing may be utilized as the first and second bearing seals **154**, **160** so long as the bearings are capable of rotationally supporting the drive shaft **131** during operation of the pump **110**.

(37) Illustratively, the pump motor assembly **120** further includes a heating assembly **140**, as shown in FIGS. 2A, 2C, and 2D. As will be described in greater detail below, the heating assembly **140** is configured to increase a temperature of any portion of the fluid (e.g. condensed water **192** described below) that leaks from the impeller **184** into the pump cavity **123** and resides in the pump cavity **123**. The increase in the temperature causes the fluid to flow toward the impeller **184** and exit the pump cavity **123**. The heating assembly **140** includes at least one heater **142**, **144**, **146**, **147**, **148** arranged on or in the pump housing **122**.

(38) As shown in FIG. 2A, the heating assembly **140** can include a plurality of heaters **142**, **144**, **146** arranged in various locations around the outside of the pump housing **122**. For example, a first heater **142** may be arranged on an axial end surface **129**, or second side **129**, of the pump housing **122** opposite a first side **128** of the housing **122** that is arranged on the bearing housing **152**.

(39) Additional heaters **144**, **146** can be arranged around an outer annular surface **126** of the outer wall **124** of the pump housing **122**. In some embodiments, the additional heaters **144**, **146** can include two heaters, but in other embodiments, more heaters may be placed around the circumference of the pump housing **122** based on the heating requirements of the pump **110**. In some embodiments, the heating assembly **140** may only include the two additional heaters **144**, **146** (or only a single heater, heater **144** or heater **146**) arranged around the outer annular surface **126**. In some embodiments, the additional heater or heaters **144**, **146** are arranged on the outer annular surface **126** of the pump housing **122** axially between the first side **128** and the second side **129** of the pump housing **122**.

(40) In some embodiments, the heating assembly **140** can include, alternatively to or in addition to the heaters **142**, **144**, **146** described above, an additional heater **147** or multiple additional heaters **147** arranged on the inside of the pump cavity **123**, as shown in FIG. 2C. The heaters **147** can be arranged on the inner surface **125** of the outer wall **124** in some embodiments. In some embodiments, the heating assembly **140** can include, alternatively to or in addition to the heaters **142**, **144**, **146**, **147** described above, an additional heater **148** or multiple additional heaters **148** arranged within the outer wall **124** of the pump housing **122**, as shown in FIG. 2D. The heaters **148** can be arranged so as to be spaced apart from the inner surface **125** of the outer wall **124** in some embodiments.

(41) A person skilled in the art will understand that any number of heaters **142**, **144**, **146**, **147**, **148** may be utilized based on the heating requirements of the pump **110**. For example, in some embodiments, the heating assembly **140** can include heaters **142**, **144**, **146** on the outside of the pump housing **122** as well as heaters **147**, **148** within the pump cavity **123** and within the outer wall **124**. In some embodiments, the heating assembly **140** can only include heaters **142**, **144**, **146** on the outside of the pump housing **122** and heaters **147** within the pump cavity **123**. In some embodiments, the heating assembly **140** can only include heaters **142**, **144**, **146** on the outside of the pump housing **122** and heaters **148** within the outer wall **124**. In some embodiments, the heating assembly **140** can only include heaters **147** within the pump cavity **123** and heaters **148** within the outer wall **124**.

(42) As will be described in greater detail below, the heaters **142**, **144**, **146**, **147**, **148** are arranged in spaced apart relation to the impeller **184**, i.e. the hydrogen process flow, as shown in FIGS. 2A, 2C, and 2D. In some embodiments, the heaters **142**, **144**, **146**, **147**, **148** are arranged axially closer to the second side **129** of the pump housing **122** than the first side **128** of the pump housing **122**. In this way, the condensed water **192** that flows into the pump cavity **123** is heated at a position away from the impeller **184**. As such, when the condensed water **192** in the pump cavity **122** is heated, it will flow towards the cooler impeller **184** in the direction **194**, and thus exit the pump cavity **122**, as shown in FIG. 2A.

(43) The heaters **142**, **144**, **146**, **147**, **148** may be any heater known in the art that is capable of

heating condensed water to a temperature high enough such that the water moves out of the pump cavity **123**. In some embodiments, the heaters **142, 144, 146, 147, 148** are electrical heaters. In some embodiments, the heaters **142, 144, 146, 147, 148** are heated coolant-based heaters. In some embodiments, the heaters **142, 144, 146, 147, 148**, in particular the heaters disposed within the pump cavity **122**, are configured to be water-resistant such that any water residing in the pump cavity **122** does not short-circuit or affect performance of the heater. In some embodiments, as will be described in more detail below, the heaters **142, 144, 146, 147, 148** can be controlled via a controller **510** based on specific operating parameters and operating conditions of the pump **110**.

(44) As shown in FIG. 2A, the bearing assembly **150** includes a bearing housing **152**, the bearing housing **152** having a first side **152A** arranged on a second side **186** of the impeller housing **182** and a second side **152B** arranged on the first side **128** of the pump housing **122**. The bearing housing **152** may be formed to be cylindrical similar to the pump housing **122**. The axial extent of the bearing housing **152** is shorter than the axial extent of the pump housing **122**, as can be seen in FIG. 2A. The bearing housing **152** includes the bearing cavity **153** formed therein, which includes the first bearing seal **154**. In some embodiments, the bearing cavity **153** is also formed to be annular and is sized similarly to the support cavity **127**.

(45) In some embodiments, as shown in FIG. 2A, the bearing cavity **153** includes at least a portion that has a diameter equal to the diameter of the support cavity **127**. In this way, the first bearing seal **154** can be sized equally to the bearing seal **160**. In some embodiments, the first bearing seal **154** may be sized such that an outer surface **154S** of the bearing seal **154** contacts the inner surface **153S** of the bearing cavity **153**, as shown in FIG. 2C. In some embodiments, the bearing cavity **153** can be stepped such that a first, larger portion **153A** of the stepped bearing cavity **153** has a greater diameter than a second, smaller portion **153B** of the stepped bearing cavity **153**.

(46) As can be seen in FIG. 2A, the drive shaft **131** extends through the bearing cavity **153** and is rotationally supported by the first bearing seal **154**. The drive shaft **131** is coupled to the impeller **184** at the terminal end **131AT** of the first axial end portion **131A**. The impeller **184** is arranged within an impeller cavity **183** defined within the impeller housing **182** of the impeller assembly **180**. The impeller cavity **183** opens into the bearing cavity **153** so as to allow for the drive shaft **131** to extend through the bearing cavity **153** into the impeller cavity **183** and couple to the impeller **184**. Similarly, the bearing cavity **153** opens into the pump cavity **123** so as to allow for the drive shaft **131** to extend from the pump cavity **123** into the bearing cavity **153** and subsequently to the impeller **184**. As such, water which is to be eventually heated by the heating assembly **140** may leak into the pump cavity **122** via the impeller cavity **183** and into the bearing cavity **153** (i.e. through small gaps between the bearing seal **154** and the inner surface of the bearing cavity **153**) and subsequently into the pump cavity **123**.

(47) The impeller housing **182** may be formed to be cylindrical similar to the pump housing **122** and the bearing housing **152**, as shown in FIG. 2A. The axial extent of the impeller housing **182** may be greater than the axial extent of the bearing housing **152** and shorter than the axial extent of the pump housing **122**. The impeller cavity **183** defined within the impeller housing **182** is sized so as to closely enclose the impeller **184** therein. As shown schematically in FIG. 2B, the impeller housing **182** includes two openings **187, 188**, also referred to as an inlet **187** and an outlet **188**. The inlet **187** and outlet **188** are formed in an axially end surface **185**, or first side **185**, of the impeller housing **182**, one of which (outlet **188**) is shown in FIG. 2A. The first side **185** may be opposite of the second side **186** of the impeller housing **182** that faces the bearing housing **152**.

(48) In operation, hydrogen **190**, or other fluids depending on the usage of the pump **110**, may flow into the impeller cavity **183** and thus into the impeller **184** via the inlet **187**. The impeller **184** may then be rotated by the drive shaft **131** of the pump motor **130** so as to impel the hydrogen **190** and output it via the output **188**. The inlet **187** is spaced apart from the outlet **188** on the axially end surface **185** of the impeller housing **182**.

(49) In some embodiments, the hydrogen recirculation pump **110** is located at a periphery of the

fuel cell **20** and/or of the fuel cell stack **12**, as shown in FIG. 3. As such, the hydrogen recirculation pump **110** is one of the first components of the fuel cell system **10** to cool when the system **10** is shut down. As warmer humidified hydrogen **190** resides within the fuel cell system **10**, the pump **110**, which is cooler than the other components of the system **10** at this point in time, acts as a condenser and will attract and retain condensed water **192** from the humidified hydrogen **190**. This condensed water **192** will remain in the pump cavity **122** of the pump housing **122** of the pump **110**.

(50) In order to prevent the condensed water **192** from residing in the pump cavity **122** for an extending period of time, the heating assembly **140** described above is utilized, in particular the heaters **142, 144, 146, 147, 148** shown in FIGS. 2A, 2C, and 2D. The heaters **142, 144, 146, 147, 148** are arranged in spaced apart relation to the impeller **184**, and as such, when the condensed water **192** in the pump cavity **122** is heated, it will flow towards the cooler impeller **184** in the direction **194** and exit the pump cavity **122**. As a result, the amount of time that the condensed water **192** remains in the pump cavity **122** is significantly reduced. In this way, pump motor **130** internal components are kept dry for much longer periods of time, thus improving life and durability of the hydrogen recirculation pump **110**.

(51) As described above, the heaters **142, 144, 146** may be arranged on the outside of the pump housing **122**, within the pump cavity **123**, within the outer wall **124** of the pump housing **122**, or any combination of these locations. These arrangements of the heaters **142, 144, 146** are advantageous over the heaters **142, 144, 146** being placed near or on the impeller housing **182**. Although placing them near the impeller housing **182** could prevent the impeller **184** from freezing, this arrangement would drive the condensed water toward the cooler pump cavity **123**, which would result in the water residing in the pump cavity **123**. This would have the opposite of the desired effect of the described hydrogen recirculation pump **110**, in particular to remove water from the pump cavity **123** and/or restrict entry of any water to the pump cavity **123**. The arrangement of the heaters **142, 144, 146** on the pump housing **122** will nevertheless prevent freezing of the pump impeller **184**.

(52) Another embodiment of a hydrogen recirculation pump **210** in accordance with the present disclosure is shown in FIGS. 4A-4C. The hydrogen recirculation pump **210** is substantially similar to the hydrogen recirculation pump **110** described herein. Accordingly, similar reference numbers in the **200** series indicate features that are common between the hydrogen recirculation pump **210** and the hydrogen recirculation pump **110**. The description of the hydrogen recirculation pump **110** is incorporated by reference to apply to the hydrogen recirculation pump **210**, except in instances when it conflicts with the specific description and the drawings of the hydrogen recirculation pump **210**. Any combination of the components of the hydrogen recirculation pump **110** and the hydrogen recirculation pump **210** described in further detail below may be utilized in an assembly of the present disclosure.

(53) The hydrogen recirculation pump **210** is formed substantially similar to the hydrogen recirculation pump **110**, in particular including a pump motor assembly **210**, a bearing assembly **250**, and an impeller assembly **280**, as shown in FIG. 4A. The hydrogen recirculation pump **210** differs from the hydrogen recirculation pump **110** at least in that, instead of utilizing a heating assembly **140** to remove water from inside the pump cavity **223**, the bearing assembly **250** further includes a lip seal **256** and a grease material **258** arranged within the bearing cavity **253** that is configured to prevent any water from entering the pump cavity **223**. A person skilled in the art will understand that, in some embodiments, heaters, such as those of the heating assembly **140**, may be included along with the lip seal **256** and grease material **258** in order to add a redundancy in cases in which a small amount of water penetrates past the seal **256** and the bearing seal **254** and into the pump cavity **223**.

(54) As can be seen in greater detail in FIG. 4B, the lip seal **256**, which may be an annular seal that extends circumferentially around the drive shaft **231**, is arranged within the bearing cavity **253**

adjacent to the bearing seal **254**. In particular, the lip seal **256** may be arranged between the bearing seal **254** and an opening **259** of the bearing cavity **253** that opens into the impeller cavity **283**. In some embodiments, the lip seal **256** may include a circumferential outer surface **256A** that contacts an inner surface **253S** of the bearing cavity **253**, and a circumferential inner surface **256B** that contacts the drive shaft **231** so as to form the seal. The bearing cavity **253** can be stepped such that a first, larger portion **253A** of the stepped bearing cavity **253** has a greater diameter than a second, smaller portion **253B** of the stepped bearing cavity **253**. Because the bearing seal **254** is arranged in the larger portion **253A**, the lip seal **256** may be arranged in the smaller portion **253B**.

(55) In some embodiments, as shown in FIG. **4C**, the lip seal **256** may include a lip **257** that is located slightly beyond the opening **259** and extends radially and slightly onto the bearing housing **252**. As a result, the axial surface **257A** of the lip **257** facing the bearing housing **252** is securely pressed against the first side **252A** of the bearing housing **252**, while the remainder of the body **256C** of the seal **256** is arranged within the bearing cavity **253**. In some embodiments, the lip **257** is axially spaced apart from the impeller **284**. In either arrangement of the lip seal **256**, as shown in FIGS. **4B** and **4C**, as well as any other embodiments conceivable to a person skilled in the art, the lip seal **256** is oriented and configured to retain grease material **258** and allow pressure to escape towards the impeller assembly **280** while also sealing against incoming pressure from the impeller assembly **280**.

(56) Illustratively, the grease material **258**, which serves as a lubricant between the bearing seal **254** and the lip seal **258**, is arranged axially between the bearing seal **254** and the lip seal **258** and contacts both the bearing seal **254** and the lip seal **258**, as shown in FIG. **4B** and FIG. **4C**. The grease material **258** may also contact the drive shaft **231** and may also contact the inner surface **253S** of the bearing cavity **253**.

(57) In some embodiments, the lip seal **256** is comprised of a fluoroelastomeric material and the grease material **258** is comprised of a hydrogen resistant material. In some embodiments, the grease material **228** is comprised of perfluoropolyether. These materials provide high resistance to chemical damage caused by the hydrogen flowing within the pump **210**, in particular within the impeller cavity **283**. These materials provide significant improvements in chemical damage resistance over the types of materials typically used for seals and corresponding lubricant/grease in lip seal and bearing seal arrangements.

(58) Another embodiment of a hydrogen recirculation pump **310** in accordance with the present disclosure is shown in FIG. **5**. The hydrogen recirculation pump **310** is substantially similar to the hydrogen recirculation pumps **110**, **210** described herein. Accordingly, similar reference numbers in the **300** series indicate features that are common between the hydrogen recirculation pump **310** and the hydrogen recirculation pumps **110**, **210**. The description of the hydrogen recirculation pumps **110**, **210** are incorporated by reference to apply to the hydrogen recirculation pump **310**, except in instances when they conflict with the specific description and the drawings of the hydrogen recirculation pump **310**. Any combination of the components of the hydrogen recirculation pumps **110**, **210** and the hydrogen recirculation pump **310** described in further detail below may be utilized in an assembly of the present disclosure.

(59) The hydrogen recirculation pump **310** is formed substantially similar to the hydrogen recirculation pumps **110**, **210**, in particular including a pump motor assembly **310**, a bearing assembly **350**, and an impeller assembly **380**, as shown in FIG. **5**. The hydrogen recirculation pump **310** differs from the hydrogen recirculation pumps **110**, **210** at least in that the pump **310** includes a heating assembly **340** that does not include heaters, but instead utilizes a fluidic heating circuit **342** to pump warm water **341** through the pump cavity **323**. The warm water **341** warms the condensed water **392** that has leaked into the pump cavity **323**, thus heating the condensed water **392** and forcing it toward the impeller **384** and out of the pump cavity **323**.

(60) Illustratively, the heating assembly **340** may include a first conduit **344** formed in the bearing housing **352**, as shown in FIG. **5**. The first conduit **344** is a fluidic line, which may be a pipe, tube,

or similar cavity formed in the housing **352**. The first conduit **344** is configured to transport fluid, in particular warm water **341**, from an inlet **345** of the first conduit **344** and into the pump cavity **323**. The warm water **341** may then flow through the pump cavity **323** so as to heat the condensed water **392** residing in the pump cavity **323**. In some embodiments, the warm water **341** is sufficiently hotter than the condensed water **392** so as to cause the condensed water **392** to heat enough so as to move toward the impeller **384** and out of the pump cavity **323**.

(61) In some embodiments, an outlet **346** of the first conduit **344** that opens into the pump cavity **323** is arranged underneath the drive shaft **331** and oriented so as to direct the warm water **341** toward the condensed water **392** resting on a bottommost inner surface **323B** of the pump cavity **323**. The warm water **341** may be pumped through the first conduit **344** and into the pump cavity **323** via a pump **370**. In some embodiments, as will be described in more detail below, the pump **370** can be controlled via the controller **510** based on specific operating parameters and operating conditions of the pump **110**.

(62) Illustratively, the heating assembly **340** may include a second conduit **347** formed in the bearing housing **352**, as shown in FIG. 5. The second conduit **347** is a fluidic line, which may be a pipe, tube, or similar cavity formed in the housing **352**. The second conduit **347** opens into the pump cavity **323** at an opening **348** and is configured to transport the warm water **341** from the pump cavity **323** to an outlet **349** of the second conduit **347**. In some embodiments, the opening **348** is arranged such that a maximum amount of the heated water **392** flows through the opening **348**, through the conduit **347**, and exits the conduit **347** via the outlet **349**.

(63) In some embodiments, both the warmed water **341** and the heated water **392**, which can mix together, will be forced toward the impeller **384** due to the heating of the water **392** via the warm water **341** and the flow path of the warm water **341** as it is pumped through the pump cavity **323**, as shown in FIG. 5. As a result, in some embodiments, a portion of the warmed water **341** and the heated water **392** will exit the pump cavity **323** via the second conduit **347**, while another portion of the warmed water **341** and the heated water **392** will exit via the bearing cavity **353** and into the impeller cavity **383**. In some embodiments, the heating assembly **340** does not include the second conduit **347**, and all of the warmed water **341** and the heated water **392** exits the pump cavity **323** via the bearing cavity **353** and into the impeller cavity **383**. In some embodiments, the pump **310** may include heaters, such as the heaters **142**, **144**, **146**, **147**, **148** described above in addition to the fluidic heating circuit **342**, so as to provide a redundancy in the event of failure of one or more of the components.

(64) In some embodiments, the warm water **341** may be provided to the first conduit **344** from a reservoir or other water source separate from the fuel cell stack **12**. In some embodiments, the warm water **341** may be any other fluid that may not mix with the condensed water **392** but nevertheless is hot enough to heat the condensed water **392** so as to cause it to flow towards the impeller **384** and out of the pump cavity **323**. In some embodiments, the cooling fluid **36** flowing through the bipolar plates (BPP) **28**, **30** in order to cool the plates **28**, **30** may be bled from that flow and used as the warm water **341** or warm fluid to heat the condensed water **392**.

(65) According to a further aspect of the present disclosure, a method of recirculating fluid (such as condensed water **192** formed from humidified hydrogen **190**) in a fuel cell system, such as via a pump **110** of the fuel cell system **10** described above, includes a first operation of providing a pump motor assembly, such as the pump motor assembly **120** described above, including a pump housing **122** having a pump cavity **123** therein and a pump motor **130** arranged in the pump cavity **123**. The method includes a second operation of arranging at least one heater, such as the heaters **142**, **144**, **146**, **147**, **148** described above, on or in the pump housing **122** and spaced apart from an impeller, such as the impeller **184** described above, and a third operation of rotating the impeller **184** via the pump motor **130** such that the impeller **184** impels the fluid from an inlet **187** of the impeller **184** to an outlet **188** of the impeller **184**. The pump housing **122** can be arranged axially away from the impeller **184**.

(66) The method can further include a fourth operation of, in response to the fuel cell system **10** being shut off, activating the at least one heater **142, 144, 146, 147, 148** and increasing a temperature of any portion of the fluid **192** that leaks from the impeller **184** into the pump cavity **123** and resides in the pump cavity **123** with the controller **510**. Increasing the temperature causes the fluid **192** residing in the pump cavity **123** to flow toward the impeller **184** and exit the pump cavity **123**. The method can further include a fifth operation of, in response to the at least one heater **142, 144, 146, 147, 148** having been active for a first amount of time based on a first operating condition of the fuel cell system **10**, deactivating the at least one heater **142, 144, 146, 147, 148** via the controller **510**. In some embodiments, the first operating condition of the fuel cell system **10** is when all fluid **192** residing in the pump cavity **123** has exited the pump cavity **123** via the increase in temperature caused by the at least one heater **142, 144, 146, 147, 148**.

(67) A person skilled in the art will understand that other operating conditions and timings of when to activate and deactivate the at least one heater can be utilized. Moreover, the method may further include pumping water through the pump cavity, such as in embodiments similar to the pump **310** described above including the fluidic heating circuit **342**, based on certain operating conditions of the fuel cell system **10**. By way of a non-limiting example, the controller **510** can be configured to activate the heaters **142, 144, 146, 147, 148** and/or the pump **370** of the fluidic heating circuit **342** immediately after the fuel cell system **10** is shut off. In some embodiments, the controller **510** can be configured to activate the heaters **142, 144, 146, 147, 148** and/or the pump **370** of the fluidic heating circuit **342** after a certain predetermined amount of time since the fuel cell system **10** has been shut off. In some embodiments, the controller **510** can be configured to activate the heaters **142, 144, 146, 147, 148** and/or the pump **370** of the fluidic heating circuit **342** in response to an operating parameter being detected within the recirculation pump **110, 310**.

(68) The controller **510**, as described above, is shown in FIG. **6**. The controller **510** may include a memory **511**, and a processor **512**. The memory **511** and processor **512** are in communication with each other. The processor **512** may be embodied as any type of computational processing tool or equipment capable of performing the functions described herein. For example, the processor **512** may be embodied as a single or multi-core processor(s), digital signal processor, microcontroller, or other processor or processing/controlling circuit.

(69) The memory **511** may be embodied as any type of volatile or non-volatile memory or data storage capable of performing the functions described herein, and may include additional storage **513**. Moreover, the controller **510** may also include additional or alternative components, such as those commonly found in a computer (e.g., various input/output devices, resistors, capacitors, etc.). In other embodiments, one or more of the illustrative controllers **510** or components may be incorporated in, or otherwise form a portion of, another component. For example, the memory **511**, or portions thereof, may be incorporated in the processor **512**.

(70) In operation, the memory **511** may store various data and software used during operation of the controller **510** such as operating systems, applications, programs, libraries, and drivers. The memory **511** is communicatively coupled to the processor **512** via an I/O subsystem, which may be embodied as circuitry and/or components to facilitate input/output operations with the processor **512**, the memory **511**, and other components of the controller **510**. In one embodiment, the memory **511** may be directly coupled to the processor **512**, for example via an integrated memory controller hub. Additionally, in some embodiments, the I/O subsystem may form a portion of a system-on-a-chip (SoC) and be incorporated, along with the processor **512**, the memory **511**, and/or other components of the controller **510**, on a single integrated circuit chip (not shown).

(71) The components of the communication network **516** may be configured to use any one or more communication technologies (e.g., wired, wireless and/or power line communications) and associated protocols (e.g., Ethernet, InfiniBand®, Bluetooth®, Wi-Fi®, WiMAX, 3G, 4G LTE, 5G, etc.) to effect such communication among and between system components and devices as described above, including but not limited to between a user interface **518** and the heaters **142, 144,**

146, 147, 148, between the interface **518** and the pump **370**, between the individual heaters **142, 144, 146, 147, 148**, and other communications within the fuel cell system **10** as would be understood by a person skilled in the art.

(72) The following described aspects of the present disclosure are contemplated and non-limiting:
(73) A first aspect of the present disclosure relates to a recirculation pump for a fuel cell system. The recirculation pump includes an impeller, a pump motor assembly, and at least one heater. The impeller is configured to rotate and impel a fluid from an inlet to an outlet. The pump motor assembly includes a pump housing having a pump cavity therein and a pump motor arranged in the pump cavity. The pump motor is configured to drive the impeller, and the pump housing is arranged axially away from the impeller. The at least one heater is disposed on or in the pump housing and is spaced apart from the impeller. The at least one heater is configured to increase a temperature of any portion of the fluid that leaks from the impeller into the pump cavity and resides in the pump cavity. The increase in the temperature causes the fluid that resides in the pump cavity to flow toward the impeller and exit the pump cavity.

(74) A second aspect of the present disclosure relates to a recirculation pump for a fuel cell system. The recirculation pump includes an impeller and a bearing assembly. The impeller includes a drive shaft centrally coupled to the impeller and is configured to rotate and impel a fluid from an inlet of the impeller to an outlet of the impeller. The bearing assembly is arranged axially away from the impeller, and includes a bearing housing having a bearing cavity defined therein and a bearing seal arranged in the bearing cavity. The drive shaft extends from the impeller and through the bearing cavity, and is arranged within and rotatably supported by the bearing seal. The bearing assembly further includes a lip seal disposed within the bearing cavity and a grease material disposed within the bearing cavity between the lip seal and the bearing seal.

(75) A third aspect of the present disclosure relates to a method of recirculating fluid in a fuel cell system. The method includes providing a pump motor assembly including a pump housing having a pump cavity therein and a pump motor arranged in the pump cavity; arranging at least one heater on or in the pump housing and spaced apart from an impeller; and rotating the impeller via the pump motor such that the impeller impels the fluid from an inlet of the impeller to an outlet of the impeller. The pump housing is arranged axially away from the impeller. The method also includes, in response to the fuel cell system being shut off, via a controller, activating the at least one heater and increasing a temperature of any portion of the fluid that leaks from the impeller into the pump cavity and resides in the pump cavity. Increasing the temperature causes the fluid residing in the pump cavity to flow toward the impeller and exit the pump cavity. The method further includes, in response to the at least one heater having been active for a first amount of time based on a first operating condition of the fuel cell system, via the controller, deactivating the at least one heater.

(76) In the first aspect of the present disclosure, the recirculation pump may further comprise an impeller assembly. The impeller assembly may include an impeller housing having an impeller cavity therein and have the inlet and the outlet. The inlet may be spaced apart from the outlet on a first side of the impeller housing. Each of the inlet and outlet may open into the impeller cavity. The impeller assembly may further include the impeller arranged in the impeller cavity and configured to impel the fluid entering the impeller cavity from the inlet to the outlet such that the fluid exits the impeller housing via the outlet.

(77) In the first aspect of the present disclosure, the pump housing may be disposed on a second side of the impeller housing opposite the first side. A first heater of the at least one heater may be arranged on a second side of the pump housing opposite a first side of the pump housing facing the impeller housing. In the first aspect of the present disclosure, a second heater of the at least one heater may be arranged on an outer surface of the pump housing axially between the first side and the second side of the pump housing. In the first aspect of the present disclosure, the second heater may be located axially closer to the second side of the pump housing than the first side of the pump housing. In the first aspect of the present disclosure, at least one additional heater of the at least one

heater and the second heater may be arranged on the outer surface of the pump housing axially between the first side and the second side of the pump housing.

(78) In the first aspect of the present disclosure, the pump motor may be coupled to the impeller via a drive shaft, and the pump motor may drive rotation of the drive shaft and rotation of the impeller. In the first aspect of the present disclosure, the recirculation pump may further comprise a bearing assembly arranged axially between the pump motor assembly and the impeller assembly. The bearing assembly may include including a bearing housing having a first side arranged on a second side of the impeller housing opposite the first side of the impeller housing and having a bearing cavity defined therein. The bearing assembly may further include a bearing seal arranged in the bearing cavity. The drive shaft may extend from the pump motor through the bearing cavity and to the impeller. The drive shaft may be arranged within and rotatably supported by the bearing seal. In the first aspect of the present disclosure, the bearing assembly may further include a lip seal disposed within the bearing cavity between the bearing seal and the impeller and a grease material disposed within the bearing cavity between the lip seal and the bearing seal. The grease material may be arranged adjacent to and abutting the bearing seal and arranged around a circumferential outer surface of the drive shaft. In the first aspect of the present disclosure, the lip seal may be arranged so as to retain the grease material in position abutting the bearing seal, so as to allow pressure to escape the pump cavity, and so as to seal against pressure from the impeller cavity. In the first aspect of the present disclosure, the lip seal may be comprised of a fluoroelastomeric material and the grease material may be comprised of a hydrogen resistant material. In the first aspect of the present disclosure, the grease material may be comprised of perfluoropolyether.

(79) In the second aspect of the present disclosure, the lip seal may be arranged so as to retain the grease material between the lip seal and the bearing seal, so as to allow pressure to escape the pump cavity, and so as to seal against pressure from the impeller cavity.

(80) In the second aspect of the present disclosure, the lip seal may be comprised of a fluoroelastomeric material, and the grease material may be comprised of a hydrogen resistant material. In the second aspect of the present disclosure, the grease material may be comprised of perfluoropolyether.

(81) In the second aspect of the present disclosure, the recirculation pump may further comprise a pump motor assembly and at least one heater. The pump motor assembly may include a pump housing having a pump cavity therein and a pump motor arranged in the pump cavity. The drive shaft may be coupled to the pump motor such that the pump motor is configured to drive the impeller. The pump housing may be arranged adjacent to the bearing housing on a side of the bearing housing opposite the impeller. The at least one heater may be on or in the pump housing and spaced apart from the bearing housing. The at least one heater may be configured to increase a temperature of any portion of the fluid that leaks from the impeller, through the bearing cavity, and into the pump cavity and resides in the pump cavity. The increase in the temperature may cause the fluid that resides in the pump cavity to flow toward the impeller and exit the pump cavity. In the second aspect of the present disclosure, a first heater of the at least one heater may be arranged on a second side of the pump housing opposite a first side of the pump housing facing the bearing housing. A second heater of the at least one heater may be arranged on an outer surface of the pump housing axially between the first side and the second side of the pump housing.

(82) In the third aspect of the present disclosure, the first operating condition may be when all fluid residing in the pump cavity has exited the pump cavity via the increase in temperature caused by the at least one heater. In the third aspect of the present disclosure, the method may further include arranging the impeller including an impeller housing having a first side and a second side opposite the first side; arranging a first side of the pump housing on the second side of the impeller housing; and arranging a first heater of the at least one heater on a second side of the pump housing opposite the first side of the pump housing facing the impeller housing.

(83) While the disclosure has been illustrated and described in detail in the drawings and foregoing

description, such as an illustration and description is to be considered as exemplary and not restrictive in character, it being understood that only illustrative embodiments have been shown and described and that all changes and modifications that come within the spirit of the disclosure are desired to be protected.

(84) There are a plurality of advantages of the present disclosure arising from the various features of the method, apparatus, and system described herein. It will be noted that alternative embodiments of the method, apparatus, and system of the present disclosure may not include all of the features described yet still benefit from at least some of the advantages of such features. Those of ordinary skill in the art may readily devise their own implementations of the method, apparatus, and system that incorporate one or more of the features of the present invention and fall within the spirit and scope of the present disclosure as defined by the appended claims.

(85) The features illustrated or described in connection with one exemplary embodiment may be combined with any other feature or element of any other embodiment described herein. Such modifications and variations are intended to be included within the scope of the present disclosure. Further, a person skilled in the art will recognize that terms commonly known to those skilled in the art may be used interchangeably herein.

(86) The above embodiments are described in sufficient detail to enable those skilled in the art to practice what is claimed and it is to be understood that logical, mechanical, and electrical changes may be made without departing from the spirit and scope of the claims. The detailed description is, therefore, not to be taken in a limiting sense.

(87) As used herein, an element or step recited in the singular and proceeded with the word “a” or “an” should be understood as not excluding plural of said elements or steps, unless such exclusion is explicitly stated. Furthermore, references to “one embodiment” of the presently described subject matter are not intended to be interpreted as excluding the existence of additional embodiments that also incorporate the recited features. Specified numerical ranges of units, measurements, and/or values comprise, consist essentially of, or consist of all the numerical values, units, measurements, and/or ranges including or within those ranges and/or endpoints, whether those numerical values, units, measurements, and/or ranges are explicitly specified in the present disclosure or not.

(88) Unless defined otherwise, technical and scientific terms used herein have the same meaning as is commonly understood by one of ordinary skill in the art to which this disclosure belongs. The terms “first,” “second,” “third” and the like, as used herein do not denote any order or importance, but rather are used to distinguish one element from another. The term “or” is meant to be inclusive and mean either or all of the listed items. In addition, the terms “connected” and “coupled” are not restricted to physical or mechanical connections or couplings, and can include electrical connections or couplings, whether direct or indirect.

(89) Moreover, unless explicitly stated to the contrary, embodiments “comprising,” “including,” or “having” an element or a plurality of elements having a particular property may include additional such elements not having that property. The term “comprising” or “comprises” refers to a composition, compound, formulation, or method that is inclusive and does not exclude additional elements, components, and/or method steps. The term “comprising” also refers to a composition, compound, formulation, or method embodiment of the present disclosure that is inclusive and does not exclude additional elements, components, or method steps.

(90) The phrase “consisting of” or “consists of” refers to a compound, composition, formulation, or method that excludes the presence of any additional elements, components, or method steps. The term “consisting of” also refers to a compound, composition, formulation, or method of the present disclosure that excludes the presence of any additional elements, components, or method steps.

(91) The phrase “consisting essentially of” or “consists essentially of” refers to a composition, compound, formulation, or method that is inclusive of additional elements, components, or method steps that do not materially affect the characteristic(s) of the composition, compound, formulation, or method. The phrase “consisting essentially of” also refers to a composition, compound,

formulation, or method of the present disclosure that is inclusive of additional elements, components, or method steps that do not materially affect the characteristic(s) of the composition, compound, formulation, or method steps.

(92) Approximating language, as used herein throughout the specification and claims, may be applied to modify any quantitative representation that could permissibly vary without resulting in a change in the basic function to which it is related. Accordingly, a value modified by a term or terms, such as “about,” and “substantially” is not to be limited to the precise value specified. In some instances, the approximating language may correspond to the precision of an instrument for measuring the value. Here and throughout the specification and claims, range limitations may be combined and/or interchanged. Such ranges are identified and include all the sub-ranges contained therein unless context or language indicates otherwise.

(93) As used herein, the terms “may” and “may be” indicate a possibility of an occurrence within a set of circumstances; a possession of a specified property, characteristic or function; and/or qualify another verb by expressing one or more of an ability, capability, or possibility associated with the qualified verb. Accordingly, usage of “may” and “may be” indicates that a modified term is apparently appropriate, capable, or suitable for an indicated capacity, function, or usage, while taking into account that in some circumstances, the modified term may sometimes not be appropriate, capable, or suitable.

(94) It is to be understood that the above description is intended to be illustrative, and not restrictive. For example, the above-described embodiments (and/or aspects thereof) may be used individually, together, or in combination with each other. In addition, many modifications may be made to adapt a particular situation or material to the teachings of the subject matter set forth herein without departing from its scope. While the dimensions and types of materials described herein are intended to define the parameters of the disclosed subject matter, they are by no means limiting and are exemplary embodiments. Many other embodiments will be apparent to those of skill in the art upon reviewing the above description. The scope of the subject matter described herein should, therefore, be determined with reference to the appended claims, along with the full scope of equivalents to which such claims are entitled.

(95) This written description uses examples to disclose several embodiments of the subject matter set forth herein, including the best mode, and also to enable a person of ordinary skill in the art to practice the embodiments of disclosed subject matter, including making and using the devices or systems and performing the methods. The patentable scope of the subject matter described herein is defined by the claims, and may include other examples that occur to those of ordinary skill in the art. Such other examples are intended to be within the scope of the claims if they have structural elements that do not differ from the literal language of the claims, or if they include equivalent structural elements with insubstantial differences from the literal languages of the claims.

(96) While only certain features of the invention have been illustrated and described herein, many modifications and changes will occur to those skilled in the art. It is, therefore, to be understood that the appended claims are intended to cover all such modifications and changes as fall within the true spirit of the invention.

Claims

1. A recirculation pump for a fuel cell system, comprising: an impeller configured to rotate and impel a fluid from an inlet to an outlet; a pump motor assembly including a pump housing having a pump cavity therein and a pump motor arranged in the pump cavity and configured to drive the impeller, the pump housing arranged axially away from the impeller; and at least one heater disposed on or in the pump housing and spaced apart from the impeller, the at least one heater being configured to increase a temperature of any portion of the fluid that leaks from the impeller into the pump cavity and resides in the pump cavity, wherein the increase in the temperature causes

- the fluid that resides in the pump cavity to flow toward the impeller and exit the pump cavity.
2. The recirculation pump of claim 1, further comprising: an impeller assembly including an impeller housing having an impeller cavity therein and having the inlet and the outlet, the inlet spaced apart from the outlet on a first side of the impeller housing, each of the inlet and outlet opening into the impeller cavity, the impeller assembly further including the impeller arranged in the impeller cavity and configured to impel the fluid entering the impeller cavity from the inlet to the outlet such that the fluid exits the impeller housing via the outlet.
 3. The recirculation pump of claim 2, wherein the pump housing is disposed on a second side of the impeller housing opposite the first side, and wherein a first heater of the at least one heater is arranged on a second side of the pump housing opposite a first side of the pump housing facing the impeller housing.
 4. The recirculation pump of claim 3, wherein a second heater of the at least one heater is arranged on an outer surface of the pump housing axially between the first side and the second side of the pump housing.
 5. The recirculation pump of claim 4, wherein the second heater is located axially closer to the second side of the pump housing than the first side of the pump housing.
 6. The recirculation pump of claim 4, wherein at least one additional heater of the at least one heater and the second heater are arranged on the outer surface of the pump housing axially between the first side and the second side of the pump housing.
 7. The recirculation pump of claim 2, wherein the pump motor is coupled to the impeller via a drive shaft, and wherein the pump motor drives rotation of the drive shaft and rotation of the impeller.
 8. The recirculation pump of claim 7, further comprising: a bearing assembly arranged axially between the pump motor assembly and the impeller assembly, the bearing assembly including a bearing housing having a first side arranged on a second side of the impeller housing opposite the first side of the impeller housing and having a bearing cavity defined therein, the bearing assembly further including a bearing seal arranged in the bearing cavity, wherein the drive shaft extends from the pump motor through the bearing cavity and to the impeller, and wherein the drive shaft is arranged within and rotatably supported by the bearing seal.
 9. The recirculation pump of claim 8, wherein the bearing assembly further includes a lip seal disposed within the bearing cavity between the bearing seal and the impeller and a grease material disposed within the bearing cavity between the lip seal and the bearing seal, the grease material being arranged adjacent to and abutting the bearing seal and arranged around a circumferential outer surface of the drive shaft.
 10. The recirculation pump of claim 9, wherein the lip seal is arranged so as to retain the grease material in position abutting the bearing seal, so as to allow pressure to escape the pump cavity, and so as to seal against pressure from the impeller cavity.
 11. The recirculation pump of claim 9, wherein the lip seal is comprised of a fluoroelastomeric material and the grease material is comprised of a hydrogen resistant material.
 12. The recirculation pump of claim 11, wherein the grease material is comprised of perfluoropolyether.
 13. The recirculation pump of claim 1, wherein the at least one heater is disposed on an outer surface of the pump housing.
 14. The recirculation pump of claim 13, further comprising: an impeller assembly including an impeller housing having the inlet and the outlet, the inlet spaced apart from the outlet on a first side of the impeller housing, and wherein the at least one heater is a first heater, and the pump housing is disposed on a second side of the impeller housing opposite the first side, and wherein a second heater of the at least one heater is arranged on an axial end surface of the pump housing opposite a first side of the pump housing facing the impeller housing.
 15. The recirculation pump of claim 14, wherein the outer surface of the pump housing extends axially between the first side and the axial end surface of the pump housing.

16. A method of recirculating fluid in a fuel cell system, comprising: providing a pump motor assembly including a pump housing having a pump cavity therein and a pump motor arranged in the pump cavity; arranging at least one heater on or in the pump housing and spaced apart from an impeller; rotating the impeller via the pump motor such that the impeller impels the fluid from an inlet of the impeller to an outlet of the impeller, wherein the pump housing is arranged axially away from the impeller; in response to the fuel cell system being shut off, via a controller, activating the at least one heater and increasing a temperature of any portion of the fluid that leaks from the impeller into the pump cavity and resides in the pump cavity, wherein increasing the temperature causes the fluid residing in the pump cavity to flow toward the impeller and exit the pump cavity; and in response to the at least one heater having been active for a first amount of time based on a first operating condition of the fuel cell system, via the controller, deactivating the at least one heater.

17. The method of claim 16, wherein the first operating condition is when all fluid residing in the pump cavity has exited the pump cavity via the increase in temperature caused by the at least one heater.

18. The method of claim 16, wherein the at least one heater is a first heater, and wherein the step of arranging includes arranging the at least one heater on an outer surface of the pump housing.

19. The method of claim 18, further comprising: arranging the impeller in an impeller housing having a first side and a second side opposite the first side; arranging a first side of the pump housing on the second side of the impeller housing; and arranging a second heater on an axial end surface of the pump housing opposite the first side of the pump housing facing the impeller housing.

20. The method of claim 19, wherein the first heater is located axially closer to the axial end surface of the pump housing than the first side of the pump housing.
