

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12411440
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Adachi; Tomoya et al.

Heating device, fixing device, and image forming apparatus

Abstract

A heating device includes a first rotator, a heater including a base having a slide face over which an inner face of the first rotator slides, a second rotator forming an outer face nip between the first rotator and the second rotator and a slide nip between the heater and the inner face, and a lubricant holder disposed between the first rotator and the heater to hold a lubricant. The first rotator, the lubricant holder, and the lubricant satisfy a formula of $H \times X1 \times R \times G \leq A \leq V \times G$, where H is a height of a roughness of the inner face, X1 is a longitudinal length of the first rotator, R is a circumference of the first rotator, G is a specific density of the lubricant, A is an application amount of the lubricant on the slide face or the inner face, and V is a volume of the lubricant holder.

Inventors:	Adachi; Tomoya (Kanagawa, JP), Furuichi; Yuusuke (Kanagawa, JP)
Applicant:	Adachi; Tomoya (Kanagawa, JP); Furuichi; Yuusuke (Kanagawa, JP)
Family ID:	88877191
Assignee:	Ricoh Company, Ltd. (Tokyo, JP)
Appl. No.:	18/319595
Filed:	May 18, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230384717 A1	Nov. 30, 2023

Foreign Application Priority Data

JP	2022-088501	May. 31, 2022
----	-------------	---------------

Publication Classification

Int. Cl.: G03G15/20 (20060101)

U.S. Cl.:

CPC G03G15/2025 (20130101);

Field of Classification Search

CPC: G03G (15/2025)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6456819	12/2001	Abe	399/329	G03G 15/2064
2003/0170054	12/2002	Suzuki	399/328	G03G 15/2064
2012/0230742	12/2011	Nakagawa	399/329	B32B 27/34
2012/0275831	12/2011	Ishida	399/329	G03G 15/2025
2013/0336672	12/2012	Mizuta	439/700	G03G 21/1867
2015/0139708	12/2014	Shimura	399/329	G03G 15/2042
2019/0179243	12/2018	Hara	N/A	G03G 15/2053
2020/0004182	12/2019	Yabuki	N/A	G03G 15/2053
2020/0409292	12/2019	Fujimoto	N/A	G03G 15/2025
2021/0157257	12/2020	Imaizumi	N/A	G03G 15/2025
2022/0179338	12/2021	Seshita et al.	N/A	N/A
2022/0283530	12/2021	Adachi et al.	N/A	N/A
2022/0291610	12/2021	Seki et al.	N/A	N/A
2022/0299919	12/2021	Inoue et al.	N/A	N/A
2022/0299920	12/2021	Shimada et al.	N/A	N/A
2022/0308511	12/2021	Someya et al.	N/A	N/A
2022/0357697	12/2021	Furuichi	N/A	N/A
2022/0382191	12/2021	Furuichi et al.	N/A	N/A
2022/0382192	12/2021	Inoue et al.	N/A	N/A
2022/0390894	12/2021	Saito et al.	N/A	N/A
2023/0004108	12/2022	Furuichi et al.	N/A	N/A
2023/0010218	12/2022	Shoji et al.	N/A	N/A
2023/0063779	12/2022	Shimada et al.	N/A	N/A
2023/0081075	12/2022	Someya et al.	N/A	N/A
2023/0110956	12/2022	Furuichi	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2003-282230	12/2002	JP	N/A
2008-275756	12/2007	JP	N/A
2010-204587	12/2009	JP	N/A
2015-118365	12/2014	JP	N/A
WO-2023166360	12/2022	WO	N/A

OTHER PUBLICATIONS

U.S. Appl. No. 18/060,566, filed Nov. 30, 2022, Yuusuke Furuichi, et al. cited by applicant

Primary Examiner: Therrien; Carla J

Attorney, Agent or Firm: Harness, Dickey & Pierce, P.L.C.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This patent application is based on and claims priority pursuant to 35 U.S.C. § 119(a) to Japanese Patent Application No. 2022-088501, filed on May 31, 2022, in the Japan Patent Office, the entire disclosure of which is hereby incorporated by reference herein.

BACKGROUND

Technical Field

(2) Embodiments of this disclosure relate to a heating device, a fixing device, and an image forming apparatus.

Related Art

(3) Related-art image forming apparatuses, such as copiers, facsimile machines, printers, and multifunction peripherals (MFP) having two or more of copying, printing, scanning, facsimile, plotter, and other functions, typically form an image on a recording medium according to image data.

(4) Such image forming apparatuses include a fixing device including a fixing belt and a heater. The fixing belt serving as a rotator is an endless belt that rotates. The heater is a laminated heater that is disposed opposite an inner face of the fixing belt, thus heating the fixing belt. In order to decrease sliding friction between the heater and the fixing belt that slides over the heater, a lubricant is applied to the inner face of the fixing belt.

(5) The lubricant in a proper amount is interposed between the fixing belt and the heater to suppress abrasion of the fixing belt and retain a proper value of driving torque of a pressure roller that drives and rotates the fixing belt.

SUMMARY

(6) This specification describes below an improved heating device. In one embodiment, the heating device includes a first rotator that rotates in a rotation direction. A heater is disposed opposite an inner face of the first rotator. The heater includes a resistive heat generator that heats the first rotator and a base having a slide face over which the inner face of the first rotator slides and an opposite face being opposite to the slide face and mounting the resistive heat generator. One of the slide face of the base of the heater and the inner face of the first rotator is applied with a lubricant. A second rotator is disposed opposite the heater via the first rotator to form an outer face nip between the first rotator and the second rotator and a slide nip between the heater and the inner face of the first rotator. A lubricant holder is disposed outboard from the slide nip in the rotation direction of the first rotator and disposed between the first rotator and the heater. The lubricant holder holds the lubricant. The first rotator, the lubricant holder, and the lubricant satisfy a formula of $H \times X1 \times R \times G \leq A \leq V \times G$, where H is a height of a roughness of the inner face of the first rotator, X1 is a length of the first rotator in a longitudinal direction of the first rotator, R is a circumference of the first rotator, G is a specific density of the lubricant, A is an application amount of the lubricant on the one of the slide face of the base of the heater and the inner face of the first rotator, and V is a volume of the lubricant holder.

(7) This specification further describes an improved fixing device. In one embodiment, the fixing device includes a fixing belt that rotates. A heater is disposed opposite an inner face of the fixing belt. The heater includes a resistive heat generator that heats the fixing belt and a base having a slide face over which the inner face of the fixing belt slides and an opposite face being opposite to the slide face and mounting the resistive heat generator. One of the slide face of the base of the heater and the inner face of the fixing belt is applied with a lubricant. A pressure rotator is disposed opposite the heater via the fixing belt to form an outer face nip between the fixing belt and the pressure rotator and a slide nip between the heater and the inner face of the fixing belt. The pressure rotator rotates and conveys a recording medium in a recording medium conveyance direction. A lubricant holder is disposed outboard from the slide nip in the recording medium conveyance direction and disposed between the fixing belt and the heater. The lubricant holder

holds the lubricant. The fixing belt, the lubricant holder, and the lubricant satisfy a formula of $H \times X1 \times R \times G \leq A \leq V \times G$, where H is a height of a roughness of the inner face of the fixing belt, X1 is a length of the fixing belt in a longitudinal direction of the fixing belt, R is a circumference of the fixing belt, G is a specific density of the lubricant, A is an application amount of the lubricant on the one of the slide face of the base of the heater and the inner face of the fixing belt, and V is a volume of the lubricant holder.

(8) This specification further describes an improved image forming apparatus. In one embodiment, the image forming apparatus includes an image bearer that bears an image and the fixing device described above that fixes the image on a recording medium.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) A more complete appreciation of embodiments of the present disclosure and many of the attendant advantages and features thereof can be readily obtained and understood from the following detailed description with reference to the accompanying drawings, wherein:

(2) FIG. 1 is a schematic cross-sectional view of an image forming apparatus according to an embodiment of the present disclosure;

(3) FIG. 2 is a schematic side cross-sectional view of a fixing device according to an embodiment of the present disclosure, that is incorporated in the image forming apparatus depicted in FIG. 1;

(4) FIG. 3 is a plan view of a heater incorporated in the fixing device depicted in FIG. 2, illustrating resistive heat generators incorporated in the heater;

(5) FIG. 4 is a diagram of a power supply circuit that supplies power to the heater depicted in FIG. 3;

(6) FIG. 5 is a plan view of a heater including resistive heat generators having a shape that is different from a shape of the resistive heat generators of the heater depicted in FIG. 3;

(7) FIG. 6 is a plan view of a heater including resistive heat generators having a shape that is different from the shapes of the resistive heat generators of the heaters depicted in FIGS. 3 and 5;

(8) FIG. 7 is a plan view of a heater including resistive heat generators having a shape that is different from the shapes of the resistive heat generators of the heaters depicted in FIGS. 3, 5, and 6;

(9) FIG. 8 is a diagram of the heater depicted in FIG. 7 and a first thermal conductor that contacts the heater, illustrating lengths of the heater and the first thermal conductor, respectively;

(10) FIG. 9 is a cross-sectional view of a fixing device according to another embodiment of the present disclosure, that is installable in the image forming apparatus depicted in FIG. 1, illustrating a slide nip and a fixing nip of the fixing device;

(11) FIG. 10 is a graph illustrating a relation between a width of the slide nip and a width of the fixing nip depicted in FIG. 9;

(12) FIG. 11 is a plan view of the heater depicted in FIG. 3, illustrating a temperature profile of a fixing belt in a longitudinal direction thereof, that is incorporated in the fixing device depicted in FIG. 2;

(13) FIG. 12 is a diagram of the heater depicted in FIG. 5, illustrating a dividing region between the resistive heat generators;

(14) FIG. 13 is a diagram of a heater incorporating resistive heat generators that define a dividing region different from the dividing region depicted in FIG. 12;

(15) FIG. 14 is a diagram of the heater depicted in FIG. 6, illustrating a dividing region between the resistive heat generators;

(16) FIG. 15 is a perspective view of the heater, the first thermal conductor, and a heater holder incorporated in the fixing device depicted in FIG. 2;

(17) FIG. 16 is a plan view of the heater depicted in FIG. 15, illustrating an arrangement of a first thermal conductor as a variation of the first thermal conductor depicted in FIG. 15;

(18) FIG. 17 is a plan view of the heater depicted in FIG. 12, illustrating a first thermal conductor as another variation of the first thermal conductor depicted in FIG. 15;

(19) FIG. 18 is a plan view of the heater depicted in FIG. 17, illustrating a first thermal conductor as yet another variation of the first thermal conductor depicted in FIG. 15;

(20) FIG. 19 is a schematic side cross-sectional view of a fixing device according to yet another embodiment of the present disclosure, that is installable in the image forming apparatus depicted in FIG. 1;

(21) FIG. 20 is a perspective view of the heater, the first thermal conductor, second thermal conductors, and a heater holder incorporated in the fixing device depicted in FIG. 19;

(22) FIG. 21 is a plan view of the heater depicted in FIG. 20, illustrating an arrangement of the first thermal conductor and the second thermal conductors;

(23) FIG. 22 is a plan view of the heater depicted in FIG. 17, illustrating the first thermal conductor depicted in FIG. 17 and a second thermal conductor that are arranged with an arrangement different from the arrangement depicted in FIG. 21;

(24) FIG. 23 is a diagram of a crystalline structure of atoms of graphene;

(25) FIG. 24 is a diagram of a crystalline structure of atoms of graphite;

(26) FIG. 25 is a plan view of the heater depicted in FIG. 21, illustrating an arrangement of second thermal conductors as a variation of the second thermal conductors depicted in FIG. 21;

(27) FIG. 26 is a schematic side cross-sectional view of a fixing device according to yet another embodiment of the present disclosure, that is installable in the image forming apparatus depicted in FIG. 1;

(28) FIG. 27 is a schematic side cross-sectional view of a fixing device according to yet another embodiment of the present disclosure, that is installable in the image forming apparatus depicted in FIG. 1;

(29) FIG. 28 is a schematic cross-sectional view of an image forming apparatus according to another embodiment of the present disclosure, that is different from the image forming apparatus depicted in FIG. 1;

(30) FIG. 29 is a schematic side cross-sectional view of a fixing device according to yet another embodiment of the present disclosure, that is incorporated in the image forming apparatus depicted in FIG. 28;

(31) FIG. 30 is a plan view of a heater incorporated in the fixing device depicted in FIG. 29;

(32) FIG. 31 is a perspective view of the heater depicted in FIG. 30 and a heater holder incorporated in the fixing device depicted in FIG. 29;

(33) FIG. 32 is a perspective view of the heater depicted in FIG. 31 and a connector to be attached to the heater;

(34) FIG. 33 is a diagram of thermistors, thermostats, and flanges incorporated in the fixing device depicted in FIG. 29, illustrating an arrangement of the thermistors and the thermostats; and

(35) FIG. 34 is a diagram of the flange depicted in FIG. 33, illustrating a slide groove of the flange.

(36) The accompanying drawings are intended to depict embodiments of the present disclosure and should not be interpreted to limit the scope thereof. The accompanying drawings are not to be considered as drawn to scale unless explicitly noted. Also, identical or similar reference numerals designate identical or similar components throughout the several views.

DETAILED DESCRIPTION

(37) In describing embodiments illustrated in the drawings, specific terminology is employed for the sake of clarity. However, the disclosure of this specification is not intended to be limited to the specific terminology so selected and it is to be understood that each specific element includes all technical equivalents that have a similar function, operate in a similar manner, and achieve a similar result.

(38) Referring now to the drawings, embodiments of the present disclosure are described below. As used herein, the singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise.

(39) Referring to attached drawings, the following describes embodiments of the present disclosure. In the drawings for explaining the embodiments of the present disclosure, identical reference numerals are assigned to elements such as members and parts that have an identical function or an identical shape as long as differentiation is possible and a description of those elements is omitted once the description is provided.

(40) FIG. 1 is a schematic cross-sectional view of an image forming apparatus **100** according to an embodiment of the present disclosure. The image forming apparatus **100** according to the embodiment includes a fixing device **9** that fixes a toner image on a sheet. The fixing device **9** serves as a heating device according to an embodiment of the present disclosure.

(41) As illustrated in FIG. 1, the image forming apparatus **100** includes four image forming units **1Y**, **1M**, **1C**, and **1Bk** that are installed in an apparatus body of the image forming apparatus **100** such that the image forming units **1Y**, **1M**, **1C**, and **1Bk** are attached to and removed from the apparatus body of the image forming apparatus **100**. The image forming units **1Y**, **1M**, **1C**, and **1Bk** have a similar construction. However, the image forming units **1Y**, **1M**, **1C**, and **1Bk** contain developers in different colors, that is, yellow, magenta, cyan, and black, respectively. The developers correspond to color separation components for a color image. Each of the image forming units **1Y**, **1M**, **1C**, and **1Bk** includes a photoconductor **2**, a charger **3**, a developing device **4**, and a cleaner **5**. The photoconductor **2** is drum-shaped and serves as an image bearer. The charger **3** charges a surface of the photoconductor **2**. The developing device **4** supplies toner as the developer to the surface of the photoconductor **2** to form a toner image. The cleaner **5** cleans the surface of the photoconductor **2**.

(42) The image forming apparatus **100** further includes an exposure device **6**, a sheet feeder **7**, a transfer device **8**, the fixing device **9** serving as a heating device, and an output device **10**. The exposure device **6** exposes the surface of each of the photoconductors **2** and forms an electrostatic latent image thereon. The image forming apparatus **100** further includes a sheet conveyance path **14**. The sheet feeder **7** supplies a sheet **P** serving as a recording medium to the sheet conveyance path **14**. The transfer device **8** transfers the toner image formed on each of the photoconductors **2** onto the sheet **P**. The fixing device **9** fixes the toner image transferred onto a surface of the sheet **P** thereon. The output device **10** ejects the sheet **P** onto an outside of the image forming apparatus **100**. Each of the image forming units **1Y**, **1M**, **1C**, and **1Bk**, that includes the photoconductor **2** and the charger **3**, the exposure device **6**, the transfer device **8**, and the like construct an image forming device that forms the toner image on the sheet **P**.

(43) The transfer device **8** includes an intermediate transfer belt **11**, four primary transfer rollers **12**, and a secondary transfer roller **13**. The intermediate transfer belt **11** is an endless belt serving as an intermediate transferor. The primary transfer rollers **12** serve as primary transferors. The secondary transfer roller **13** serves as a secondary transferor. The intermediate transfer belt **11** is stretched taut across a plurality of rollers. The primary transfer rollers **12** transfer yellow, magenta, cyan, and black toner images formed on the photoconductors **2** onto the intermediate transfer belt **11**, respectively, thus forming a full color toner image on the intermediate transfer belt **11**. The secondary transfer roller **13** transfers the full color toner image formed on the intermediate transfer belt **11** onto the sheet **P**. The plurality of primary transfer rollers **12** is pressed against the photoconductors **2**, respectively, via the intermediate transfer belt **11**. Accordingly, the intermediate transfer belt **11** contacts each of the photoconductors **2**, forming a primary transfer nip therebetween. On the other hand, the secondary transfer roller **13** is pressed against a roller **16**, that is, one of the plurality of rollers across which the intermediate transfer belt **11** is stretched taut, via the intermediate transfer belt **11**. Thus, a secondary transfer nip is formed between the secondary transfer roller **13** and the intermediate transfer belt **11**.

(44) The sheet conveyance path **14** is provided with a timing roller pair **15** at a position between the sheet feeder **7** and the secondary transfer nip defined by the secondary transfer roller **13**.

(45) Referring to FIG. **1**, a description is provided of printing processes performed by the image forming apparatus **100** having the construction described above.

(46) When the image forming apparatus **100** receives an instruction to start printing, a driver disposed inside the apparatus body of the image forming apparatus **100** drives and rotates the photoconductor **2** clockwise in FIG. **1** in each of the image forming units **1Y**, **1M**, **1C**, and **1Bk**. The charger **3** charges the surface of the photoconductor **2** uniformly at a high electric potential. The exposure device **6** exposes the charged surfaces of the photoconductors **2**, respectively, according to image data (e.g., print data) sent from a terminal. Alternatively, if the image forming apparatus **100** is a copier, the exposure device **6** exposes the charged surfaces of the photoconductors **2**, respectively, according to image data created by a scanner that reads an image on an original. Accordingly, the electric potential of an exposed portion on the surface of each of the photoconductors **2** decreases, forming an electrostatic latent image on the surface of each of the photoconductors **2**. The developing device **4** of each of the image forming units **1Y**, **1M**, **1C**, and **1Bk** supplies toner to the electrostatic latent image formed on the photoconductor **2**, forming a toner image thereon.

(47) The toner images formed on the photoconductors **2** move and reach the primary transfer nips defined by the primary transfer rollers **12** in accordance with rotation of the photoconductors **2**, respectively. The primary transfer rollers **12** transfer the toner images formed on the photoconductors **2** onto the intermediate transfer belt **11** driven and rotated counterclockwise in FIG. **1** successively such that the toner images are superimposed on the intermediate transfer belt **11**, thus forming a full color toner image thereon. The full color toner image formed on the intermediate transfer belt **11** is conveyed to the secondary transfer nip defined by the secondary transfer roller **13** in accordance with rotation of the intermediate transfer belt **11**. The secondary transfer roller **13** transfers the full color toner image onto a sheet **P** conveyed through the secondary transfer nip. The sheet **P** is supplied from the sheet feeder **7**. The timing roller pair **15** temporarily halts the sheet **P** supplied from the sheet feeder **7**. Thereafter, the timing roller pair **15** conveys the sheet **P** to the secondary transfer nip at a time when the full color toner image formed on the intermediate transfer belt **11** reaches the secondary transfer nip. The secondary transfer roller **13** transfers the full color toner image onto the sheet **P**. Thus, the sheet **P** bears the full color toner image. After the toner image is transferred onto the intermediate transfer belt **11**, the cleaner **5** removes residual toner remained on the photoconductor **2** therefrom.

(48) The sheet **P** transferred with the full color toner image is conveyed to the fixing device **9** that fixes the full color toner image on the sheet **P**. Thereafter, the output device **10** ejects the sheet **P** onto the outside of the image forming apparatus **100**, thus finishing a series of printing processes.

(49) A description is provided of a construction of the fixing device **9**.

(50) As illustrated in FIG. **2**, the fixing device **9** according to the embodiment includes a fixing belt **20**, a pressure roller **21**, a heater **22**, a heater holder **23**, a stay **24**, thermistors **25**, and a first thermal conductor **28**. The heater holder **23** serves as a holder. The stay **24** serves as a support. The thermistors **25** serve as temperature detectors. The fixing belt **20** is an endless belt. The pressure roller **21** contacts an outer circumferential face **20a** of the fixing belt **20** to form a fixing nip **N2**, serving as an outer face nip, between the fixing belt **20** and the pressure roller **21**. The heater **22** heats the fixing belt **20**. The heater holder **23** holds or supports the heater **22**. The stay **24** supports the heater holder **23**. Each of the thermistors **25** detects a temperature of the first thermal conductor **28**.

(51) The fixing belt **20**, the pressure roller **21** serving as a pressure rotator, the heater **22**, the heater holder **23**, the stay **24**, the first thermal conductor **28**, and the like extend in a longitudinal direction that is perpendicular to a paper surface in FIG. **2** and is parallel to a width direction of a sheet **P** conveyed through the fixing nip **N2**, a belt width direction of the fixing belt **20**, and an axial

direction of the pressure roller **21**. A fixing device includes a fixing rotator as one example of a rotator incorporated in a heating device (e.g., the fixing device **9**) according to an embodiment of the present disclosure. The fixing device **9** according to the embodiment includes the fixing belt **20** as one example of the fixing rotator. As the fixing belt **20** and the pressure roller **21** rotate in rotation directions **D20** and **D21**, respectively, the fixing belt **20** and the pressure roller **21** convey the sheet **P** in a sheet conveyance direction **DP** serving as a recording medium conveyance direction.

(52) The fixing belt **20** includes a tubular base layer that is made of polyimide (PI) and has an outer diameter of 25 mm and a thickness in a range of from 50 μm to 75 μm , for example. The fixing belt **20** further includes a release layer serving as an outermost surface layer. The release layer is made of fluororesin, such as perfluoroalkoxy alkane (PFA) and polytetrafluoroethylene (PTFE), and has a thickness in a range of from 7 μm to 20 μm to enhance durability of the fixing belt **20** and facilitate separation of the sheet **P** and a foreign substance from the fixing belt **20**. Optionally, an elastic layer that is made of rubber or the like and has a thickness in a range of from 100 micrometers to 300 micrometers may be interposed between the base layer and the release layer. The base layer of the fixing belt **20** may be made of heat-resistant resin such as polyetheretherketone (PEEK) or metal such as nickel (Ni) and stainless used steel (SUS), instead of polyimide. The fixing belt **20** may include an inner circumferential face **20b** that is coated with polyimide, PTFE, or the like to produce a sliding layer.

(53) The pressure roller **21** has an outer diameter in a range of from 20 mm to 22 mm, for example. The pressure roller **21** includes a core metal **21a** as an inner layer, an elastic layer **21b** disposed on the core metal **21a**, and a surface layer **21c** disposed on the elastic layer **21b**. The core metal **21a** is solid and made of a conductive material. According to the embodiment, the core metal **21a** is made of iron. The elastic layer **21b** is made of a non-conductive material. According to the embodiment, the elastic layer **21b** has a thickness in a range of from 3.5 mm to 4.0 mm and is made of silicone rubber. Since the elastic layer **21b** is a non-conductive layer, the elastic layer **21b** is elastic and stretchy without being added with a material that applies conductivity such as a filler. The surface layer **21c** is made of fluororesin and has a thickness in a range of from 30 μm to 50 μm .

(54) The fixing device **9** further includes a biasing member that biases and moves the pressure roller **21** toward the fixing belt **20**, pressing the pressure roller **21** against the heater **22** via the fixing belt **20**. Thus, the fixing nip **N2** is formed between the fixing belt **20** and the pressure roller **21**. The fixing device **9** further includes a driver that drives and rotates the pressure roller **21**. As the pressure roller **21** rotates in the rotation direction **D21**, the pressure roller **21** drives and rotates the fixing belt **20** in the rotation direction **D20**.

(55) The heater **22** is a laminated heater that extends in the longitudinal direction thereof throughout an entire span of the fixing belt **20** in the longitudinal direction thereof. The heater **22** includes a base **30** (e.g., a substrate) that is platy, resistive heat generators **31** that are disposed on the base **30**, and an insulating layer **32** that coats the resistive heat generators **31**. The base **30** has a back face **30b** that mounts the resistive heat generators **31** and a front face **30a** (e.g., an opposite face) that is opposite to the back face **30b**. The front face **30a** of the base **30** contacts the inner circumferential face **20b** of the fixing belt **20**. The resistive heat generators **31** generate heat that is conducted to the fixing belt **20** through the base **30**. According to the embodiment, the base **30** is made of alumina. The heater **22** may contact the inner circumferential face **20b** of the fixing belt **20** directly or indirectly. For example, the heater **22** may be disposed opposite the inner circumferential face **20b** of the fixing belt **20** via a conductor such as a slide sheet. As a power supply **200** depicted in FIG. 4 applies an alternating current (AC) voltage to the heater **22**, the resistive heat generators **31** generate heat mainly.

(56) The heater holder **23** and the stay **24** are disposed within a loop formed by the fixing belt **20**. The stay **24** includes a channel made of metal. The stay **24** has both lateral ends in the longitudinal direction thereof, that are supported by side plates of the fixing device **9**, respectively. Since the

stay **24** supports the heater holder **23** and the heater **22**, in a state in which the pressure roller **21** is pressed against the fixing belt **20**, the heater **22** receives pressure from the pressure roller **21** precisely. Thus, the fixing nip N2 is formed between the fixing belt **20** and the pressure roller **21** stably. According to the embodiment, the heater holder **23** has a thermal conductivity that is smaller than a thermal conductivity of the base **30**.

(57) Since the heater holder **23** is subject to high temperatures by heat from the heater **22**, the heater holder **23** is preferably made of a heat-resistant material. For example, if the heater holder **23** is made of heat-resistant resin having a decreased thermal conductivity, such as liquid crystal polymer (LCP), the heater holder **23** suppresses conduction of heat thereto from the heater **22**. Accordingly, the heater **22** heats the fixing belt **20** efficiently.

(58) The fixing device **9** further includes a plurality of guides **26** that is mounted on the heater holder **23** and guides the fixing belt **20**. The guides **26** are disposed upstream from and below the heater **22** and disposed downstream from and above the heater **22** in FIG. 2, respectively, in the rotation direction D20 of the fixing belt **20**. The plurality of guides **26** disposed upstream and downstream from the heater **22** in the rotation direction D20 of the fixing belt **20** is arranged in the longitudinal direction of the heater **22** with a gap between the adjacent guides **26**. Each of the guides **26** is substantially fan-shaped. Each of the guides **26** includes a fixing belt opposed face **260** that is disposed opposite the inner circumferential face **20b** of the fixing belt **20** and defines an arc or a projecting curved face that extends in a circumferential direction of the fixing belt **20**.

(59) The heater holder **23** includes a plurality of openings **23a** arranged in the longitudinal direction of the heater holder **23**. Each of the openings **23a** is a slot penetrating through the heater holder **23** in a thickness direction thereof. The thermistors **25** and thermostats described below are placed in the openings **23a**, respectively. The fixing device **9** further includes springs **29** that bias and press the thermistors **25** and the thermostats against a back face of the first thermal conductor **28**. Alternatively, each of the first thermal conductor **28** and a second thermal conductor described below may also include an opening similarly so that the thermistors **25** and the thermostats are pressed against a back face of the insulating layer **32** of the heater **22** through the openings.

(60) The first thermal conductor **28** is made of a material having a thermal conductivity greater than a thermal conductivity of the base **30**. According to the embodiment, the first thermal conductor **28** is a plate made of aluminum. Alternatively, the first thermal conductor **28** may be made of copper, silver, graphene, or graphite, for example. Since the first thermal conductor **28** is platy, the first thermal conductor **28** improves accuracy of positioning of the heater **22** with respect to the heater holder **23** and the first thermal conductor **28**. The first thermal conductor **28** contacts the insulating layer **32** of the heater **22**.

(61) A description is provided of a method for calculating the thermal conductivity described above.

(62) A thermal diffusivity of a target object was measured and a thermal conductivity was calculated based on the thermal diffusivity.

(63) The thermal diffusivity was measured with a thermal diffusivity-thermal conductivity measurement device, ai-Phase Mobile 1u, manufactured by ai-Phase Co., Ltd.

(64) The thermal diffusivity was converted into the thermal conductivity based on a density and a specific heat capacity. The density was measured with a dry-process pycnometer, Accupyc 1330, manufactured by Shimadzu Corporation. The specific heat capacity was measured with a differential scanning calorimeter, DSC-60, manufactured by Shimadzu Corporation. Sapphire was used as a reference material having a known specific heat capacity. According to an embodiment, the specific heat capacity was measured five times to obtain an average at 50 degrees Celsius. Based on a density ρ , a specific heat capacity S , and a thermal diffusivity a obtained by the above-described measurement of the thermal diffusivity, a thermal conductivity k is obtained by a formula (1) below.

$$\lambda = \rho \times S \times a \dots (1)$$

In the fixing device **9** according to the embodiment, when printing starts, the driver drives and rotates the pressure roller **21** and the fixing belt **20** starts rotation in accordance with rotation of the pressure roller **21**. Since the inner circumferential face **20b** of the fixing belt **20** is contacted and guided by the fixing belt opposed face **260** of each of the guides **26**, the fixing belt **20** rotates stably and smoothly. Additionally, as power is supplied to the resistive heat generators **31** of the heater **22**, the heater **22** heats the fixing belt **20**. In a state in which the temperature of the fixing belt **20** reaches a predetermined target temperature (e.g., a fixing temperature), as a sheet P bearing an unfixed toner image is conveyed through the fixing nip N2 formed between the fixing belt **20** and the pressure roller **21** as illustrated in FIG. 2, the fixing belt **20** and the pressure roller **21** fix the unfixed toner image on the sheet P under heat and pressure. The fixing belt **20** serves as a heated member that is heated by the heater **22**.

(65) A detailed description is provided of a construction of the heater **22** of the fixing device **9**.

(66) FIG. 3 is a plan view of the heater **22** according to the embodiment. FIG. 3 illustrates conductors such as the resistive heat generators **31** that are disposed on the left of the base **30** in FIG. 2. In a description below, the base **30** has the front face **30a** and the back face **30b**. The back face **30b** is opposite to the front face **30a** and is a left face of the base **30** in FIG. 2. The front face **30a** is opposite to the back face **30b** and is disposed opposite the fixing nip N2 and a slide nip described below.

(67) As illustrated in FIG. 3, the base **30** that is platy has the back face **30b** (e.g., a surface) depicted in FIG. 2 that mounts the plurality of resistive heat generators **31** (e.g., the four resistive heat generators **31**). The back face **30b** also mounts feeders **33A** and **33B** serving as conductors, and electrodes **34A** and **34B** serving as a first electrode and a second electrode, respectively. The number of the resistive heat generators **31** is not limited to four.

(68) FIG. 3 illustrates a longitudinal direction X (e.g., a horizontal direction in FIG. 3) that defines the longitudinal direction of the heater **22** and the like and an arrangement direction in which the plurality of resistive heat generators **31** is arranged. The arrangement direction is parallel to the longitudinal direction of the fixing belt **20** and the axial direction of the pressure roller **21**. FIG. 3 illustrates a short direction Y (e.g., a vertical direction in FIG. 3) that is parallel to the sheet conveyance direction DP serving as the recording medium conveyance direction depicted in FIG. 2. The short direction Y is a short direction of the heater **22**. The short direction Y is an orthogonal direction that intersects the arrangement direction in which the resistive heat generators **31** are arranged. According to the embodiment, the short direction Y is perpendicular to the arrangement direction in which the resistive heat generators **31** are arranged. The short direction Y is different from a thickness direction of the base **30**. The longitudinal direction X and the short direction Y are hereinafter also referred to as the longitudinal direction and the short direction, respectively.

(69) The heater **22** includes a heat generation portion **35** that is divided into the plurality of resistive heat generators **31** arranged in the longitudinal direction X of the heater **22**. The resistive heat generators **31** are electrically connected in parallel to a pair of electrodes **34A** and **34B** through the feeders **33A** and **33B**. The electrodes **34A** and **34B** are mounted on one lateral end (e.g., a left end in FIG. 3) of the base **30** in the longitudinal direction X thereof. Each of the feeders **33A** and **33B** is made of a conductor having a resistance value smaller than a resistance value of the resistive heat generator **31**. The adjacent resistive heat generators **31** define a gap therebetween, that is 0.2 mm or greater, preferably 0.4 mm or greater, in view of ensuring insulation between the adjacent resistive heat generators **31**. If the gap between the adjacent resistive heat generators **31** is excessively great, the fixing belt **20** is subject to temperature decrease at an opposed portion thereof that is disposed opposite the gap. Hence, the gap is 5 mm or smaller, preferably 1 mm or smaller, in view of suppressing uneven temperature of the fixing belt **20** in the longitudinal direction thereof.

(70) The resistive heat generators **31** are made of a material having a positive temperature coefficient (PTC) property that is characterized in that the resistance value increases, that is, a heater output decreases, as the temperature increases. The resistive heat generator **31** has a

temperature coefficient of 500 ppm, for example.

(71) Since the resistive heat generators **31** have the PTC property and the heat generation portion **35** is divided into the plurality of resistive heat generators **31** in the longitudinal direction X of the heater **22**, the heater **22** prevents overheating of the fixing belt **20** when sheets P having a decreased size are conveyed over the fixing belt **20**. For example, if a sheet P having a decreased width that is smaller than an entire length of the heat generation portion **35** in the longitudinal direction X of the heater **22** is conveyed through the fixing nip N2, since the sheet P does not draw heat from the fixing belt **20** in an outboard span that is outboard from the sheet P in the longitudinal direction X of the fixing belt **20**, the resistive heat generators **31** in the outboard span are subject to temperature increase. Since a constant voltage is applied to the resistive heat generators **31**, when the temperature of the resistive heat generators **31** in the outboard span increases and the resistance value thereof increases, conversely, an output (e.g., a heat generation amount) of heat from the resistive heat generators **31** decreases relatively, suppressing temperature increase of the resistive heat generators **31** that are disposed in both lateral end spans of the heat generation portion **35** in the longitudinal direction X thereof. Additionally, the plurality of resistive heat generators **31** is electrically connected in parallel, suppressing temperature increase in a non-conveyance span where the sheet P is not conveyed over the fixing belt **20** while retaining the printing speed.

Alternatively, the heat generation portion **35** may include heat generators other than the resistive heat generators **31** having the PTC property. The resistive heat generators **31** may be arranged in a plurality of columns in the short direction Y of the heater **22**.

(72) For example, the resistive heat generator **31** is produced as below. Silver-palladium (AgPd), glass powder, and the like are mixed into paste. The paste coats the base **30** by screen printing or the like. Thereafter, the base **30** is subject to firing. According to the embodiment, the resistive heat generator **31** has a resistance value of 80Ω at an ambient temperature. Alternatively, the resistive heat generator **31** may be made of a resistive material such as a silver alloy (AgPt) and ruthenium oxide (RuO_{sub}.2). The feeders **33A** and **33B** and the electrodes **34A** and **34B** are made of a material prepared with silver (Ag) or silver-palladium (AgPd) by screen printing or the like. Each of the feeders **33A** and **33B** is made of a conductor having a resistance value smaller than a resistance value of the resistive heat generator **31**.

(73) The base **30** is preferably made of ceramics, such as alumina and aluminum nitride, or a nonmetallic material, such as glass and mica, having an enhanced heat resistance and an enhanced insulation. According to the embodiment, the base **30** is made of alumina and has a short width of 8 mm, a longitudinal length of 270 mm, and a thickness of 1.0 mm. Alternatively, the base **30** may include a conductive layer made of metal or the like and an insulating layer disposed on the conductive layer. The metal of the base **30** is preferably aluminum, stainless steel, or the like that is available at reduced costs. The base **30** made of a stainless steel plate suppresses breakage due to thermal stress. In order to improve evenness of heat conducted from the heater **22** so as to enhance quality of an image formed on a sheet P, the base **30** may be made of a material that has an increased thermal conductivity such as copper, graphite, and graphene.

(74) The insulating layer **32** is made of heat-resistant glass and has a thickness of 75 μm, for example. The insulating layer **32** covers the resistive heat generators **31** and the feeders **33A** and **33B** and insulates and protects the resistive heat generators **31** and the feeders **33A** and **33B**.

(75) FIG. 4 is a diagram of the heater **22** according to the embodiment, illustrating a power supply circuit that supplies power to the heater **22**.

(76) As illustrated in FIG. 4, according to the embodiment, the power supply circuit for supplying power to the resistive heat generators **31** includes the alternating current power supply **200** that is electrically connected to the electrodes **34A** and **34B** of the heater **22**. The power supply circuit further includes a triac **210** that controls an amount of power supplied to the resistive heat generators **31**. The power supply circuit further includes a controller **220** that controls the amount of power supplied to each of the resistive heat generators **31** through the triac **210** based on

temperatures of the resistive heat generators **31**, that are detected by the thermistors **25**, respectively. The controller **220** includes a microcomputer that includes a central processing unit (CPU), a read only memory (ROM), a random access memory (RAM), and an input-output (I/O) interface.

(77) According to the embodiment, the thermistors **25** are disposed opposite a center span of the heater **22** in the longitudinal direction thereof, that is, a minimum sheet conveyance span where a minimum size sheet **P** available in the fixing device **9** is conveyed, and one lateral end span of the heater **22** in the longitudinal direction thereof, respectively. The fixing device **9** further includes a thermostat **27** that is disposed at one lateral end of the heater **22** in the longitudinal direction thereof. The thermostat **27** serves as a power breaker that interrupts supplying power to the resistive heat generators **31** when a temperature of the resistive heat generator **31** is a predetermined temperature or higher. The thermistors **25** and the thermostat **27** contact the first thermal conductor **28** to detect a temperature of the first thermal conductor **28**.

(78) According to the embodiment, the electrodes **34A** and **34B** are disposed in an identical lateral end span of the heater **22** in the longitudinal direction thereof. Alternatively, the electrodes **34A** and **34B** may be disposed in one lateral end span and another lateral end span of the heater **22** in the longitudinal direction thereof, respectively. The resistive heat generator **31** has shapes that are not limited to a shape according to the embodiment. FIG. 5 illustrates a heater **22A** that includes resistive heat generators **31A** each of which is rectangular. FIG. 6 illustrates a heater **22B** that includes resistive heat generators **31B** each of which includes a linear portion. The linear portion turns to define a parallelogram substantially. As illustrated in FIG. 5, the heater **22A** includes an extension that extends from the resistive heat generator **31A** having a block shape to the feeder **33A** or **33B** in the short direction **Y**. The extension may be a part of the resistive heat generator **31A** or may be made of a material equivalent to a material of the feeder **33A** or **33B**.

(79) Alternatively, a heater may include a plurality of resistive heat generators that is not divided in a longitudinal direction of the heater. For example, FIG. 7 illustrates a heater **22C** that includes two resistive heat generators **31C** that are extended in the longitudinal direction **X** of the heater **22C** and are connected in series. The two resistive heat generators **31C** are connected to the electrodes **34A** and **34B** through the feeders **33A** and **33B**, respectively, at one lateral end of each of the resistive heat generators **31C** in the longitudinal direction **X** thereof. The two resistive heat generators **31C** are connected in series through a feeder **33C** at another lateral end of each of the resistive heat generators **31C** in the longitudinal direction **X** thereof.

(80) A description is provided of a construction of the heater **22C** depicted in FIG. 7 as one example.

(81) The heater **22C** has dimensions in the short direction **Y**, that are defined by a dimension of 8.0 mm of the base **30**, a dimension of 1.5 mm of each of the resistive heat generators **31C**, and a dimension of 3.0 mm of a gap between the resistive heat generators **31C**. The heater **22C** has a heating region having a width **Y2** of 6.0 mm in the short direction **Y** of the heater **22C**. The heating region of the heater **22C** defines a main heat generation region thereof where the resistive heat generators **31C** are disposed. The heating region encompasses the gap between the resistive heat generators **31C**.

(82) As illustrated in FIG. 8, the heating region of the heater **22C** has a length **X2** of 216 mm in the longitudinal direction **X** of the heater **22C**. The first thermal conductor **28** has a thickness of 0.3 mm, a length **X3** of 222 mm in the longitudinal direction of the first thermal conductor **28**, and a width of 10 mm in a short direction of the first thermal conductor **28**. The length **X3** of the first thermal conductor **28** in the longitudinal direction thereof is greater than the length **X2** of the heating region of the heater **22C** in the longitudinal direction **X** thereof. Thus, the first thermal conductor **28** covers an entirety of the heating region of the heater **22C**. Accordingly, the first thermal conductor **28** prevents the resistive heat generators **31C** of the heater **22C** from overheating locally, thus preventing breakage of the heater **22C**.

(83) A description is provided of a construction of a comparative fixing device.

(84) The comparative fixing device includes a fixing belt including a rough surface portion disposed on an inner circumferential face of the fixing belt in a center span of the fixing belt in an axial direction thereof. The rough surface portion improves retention of a lubricant by the fixing belt.

(85) However, the comparative fixing device may suffer from degradation in retention of the lubricant due to an application amount of the lubricant applied between the fixing belt, serving as a rotator, and a heater, a construction of the heater, and a construction of a holder that holds the heater.

(86) FIG. 9 illustrates a fixing device 9A that includes the fixing belt 20 that contacts the pressure roller 21 to form the fixing nip N2 that extends in the sheet conveyance direction DP (e.g., a horizontal direction in FIG. 9). The inner circumferential face 20b of the fixing belt 20 contacts the heater 22C to form a slide nip N1 that extends in the sheet conveyance direction DP. FIG. 9 illustrates, in a lower part in FIG. 9, a temperature profile of the front face 30a, serving as the slide face, of the base 30 in the sheet conveyance direction DP with an alternate long and short dash line.

(87) The inner circumferential face 20b of the fixing belt 20 slides over the heater 22C with constant pressure therebetween at the slide nip N1. For example, as a measurement method for measuring the slide nip N1, a lead-free mold inspection agent, Shinmyotan N-Red, available from Nakatani Co., Ltd. is applied on a surface of the heater 22C and the pressure roller 21 is pressed against the fixing belt 20. While the fixing belt 20 has a surface temperature of 190 degrees Celsius, the fixing device 9A is driven for ten minutes. Thereafter, the fixing device 9A is dismantled. The surface of the heater 22C is checked and a peel-off portion of the heater 22C, where the Shinmyotan is peeled off, is observed. The peel-off portion is photographed. Based on a width of the heater 22C in the short direction Y thereof, that has been measured, the peel-off portion is measured as the slide nip N1.

(88) In the fixing device 9A incorporating the heater 22C, as the fixing belt 20 rotates, the inner circumferential face 20b of the fixing belt 20 may slide over the front face 30a, serving as the slide face, of the base 30 of the heater 22C with sliding friction, resulting abrasion of the fixing belt 20. In order to suppress the sliding friction and the abrasion of the fixing belt 20, a lubricant is applied onto the inner circumferential face 20b of the fixing belt 20 or the front face 30a (e.g., the slide face) of the base 30, over which the fixing belt 20 slides. According to the embodiment, fluorine grease is used as the lubricant. The fluorine grease is hereinafter also referred to as the grease.

(89) According to the embodiment, the heater holder 23 includes a recess 23b that holds the heater 22C. The heater holder 23 further includes protrusions 23e disposed at both ends of the heater holder 23 in the sheet conveyance direction DP, respectively. The protrusions 23e protrude beyond the base 30 of the heater 22C held inside the recess 23b toward the fixing belt 20. The inner circumferential face 20b of the fixing belt 20 slides over the protrusions 23e.

(90) The pressure roller 21 presses the fixing belt 20 against the front face 30a of the base 30. Accordingly, in a center span of the heater 22C in the short direction Y thereof (e.g., the horizontal direction in FIG. 9), the inner circumferential face 20b of the fixing belt 20 contacts the front face 30a of the base 30, thus forming the slide nip N1. The fixing device 9A further includes grease reservoirs 40 disposed opposite both ends of the base 30 in the short direction Y of the heater 22C, respectively. Each of the grease reservoirs 40 defines space produced between the front face 30a of the base 30 and the inner circumferential face 20b of the fixing belt 20. Each of the grease reservoirs 40 serves as a lubricant holder. The grease reservoirs 40 store the grease. According to the embodiment, each of the grease reservoirs 40 stores grease 90 at a portion of the grease reservoir 40, that abuts on the slide nip N1. The grease 90 accumulated in each of the grease reservoirs 40 is supplied to the slide nip N1 little by little. Thus, the grease 90 retains proper sliding of the inner circumferential face 20b of the fixing belt 20 over the front face 30a of the base 30 for an extended period of time.

(91) In order to attain proper sliding of the inner circumferential face **20b** of the fixing belt **20** over the base **30** of the heater **22C**, an amount of the grease **90** interposed between the fixing belt **20** and the front face **30a** of the base **30** of the heater **22C** and a viscosity of the grease **90** are retained at appropriate values, respectively. For example, if the amount of the grease **90** decreases excessively, the grease **90** does not attain proper sliding of the fixing belt **20** over the heater **22C**. Conversely, if the amount of the grease **90** increases excessively, the grease **90** may have an excessively increased film thickness, increasing a slide load imposed on the fixing belt **20** and increasing an amount of the grease **90** that leaks from each lateral end of the fixing belt **20** in the longitudinal direction thereof. Thus, neither an excessively increased viscosity nor an excessively decreased viscosity of the grease **90** attains proper sliding of the fixing belt **20** over the heater **22C**. Additionally, surface roughness of the inner circumferential face **20b** of the fixing belt **20** and the front face **30a** of the base **30** of the heater **22C**, that retain the grease **90**, changes capacity of the inner circumferential face **20b** and the front face **30a** for retaining the grease **90**.

(92) According to the embodiment, the base **30** is made of ceramics having enhanced smoothness. The front face **30a** has an arithmetic average roughness Ra of 0.2 μm or smaller. Alternatively, the front face **30a** may be coated with thin film made of polyimide or a glass layer. Accordingly, the inner circumferential face **20b** of the fixing belt **20** slides over the front face **30a** of the base **30** without abrasion. If the front face **30a** is smooth like in the embodiment, roughness of the inner circumferential face **20b** of the fixing belt **20** affects retention of the grease **90** substantially. For example, the inner circumferential face **20b** of the fixing belt **20** includes recesses that retain PTFE as a thickener for the fluorine grease. Accordingly, base oil of the fluorine grease is supplied to the slide nip N1 over time, preventing shortage of oil film.

(93) According to the embodiment, the grease **90** is supplied to the inner circumferential face **20b** of the fixing belt **20** in an amount that is great enough to fill the recesses. For example, the roughness on the inner circumferential face **20b** of the fixing belt **20** has a height H. The fixing belt **20** has the length X1 in the longitudinal direction of the fixing belt **20**. The fixing belt **20** has a circumference R. The grease **90** has a specific density G. The grease **90** may move round to a back face of the heater **22C** or may adhere to the heater holder **23**. Hence, an application amount A of the grease **90** satisfies a formula (2) below.

$$H \times X1 \times R \times G \leq A \dots (2)$$

The height H of the roughness on the inner circumferential face **20b** of the fixing belt **20** is obtained by measuring a surface profile with a laser microscope VK series available from Keyence Corporation and calculating a ten-point mean roughness of peak-to-peak values. The ten-point mean roughness is calculated as below. Measurement is performed on ten points on the inner circumferential face **20b** of the fixing belt **20**. For example, the ten points include one point at a center position on the fixing belt **20** in the longitudinal direction thereof, two points separated from the center position by plus and minus 50 mm in the longitudinal direction of the fixing belt **20**, respectively, and two points separated from the center position by plus and minus 100 mm in the longitudinal direction of the fixing belt **20**, respectively. The above described five points are located on two points shifted from each other in the circumferential direction of the fixing belt **20**. The peak-to-peak values obtained at the ten points are averaged. For example, according to the embodiment, the roughness has a height of 1.67 μm.

(94) The fixing belt **20** according to the embodiment has an outer diameter of 25 mm. The base layer of the fixing belt **20** has a thickness of 60 μm. The elastic layer of the fixing belt **20**, that is made of silicone rubber, has a thickness of 250 μm. The release layer of the fixing belt **20**, that is made of PFA, has a thickness of 12 μm. The fixing belt **20** has the length X1 of 234 mm in the longitudinal direction of the fixing belt **20**. The fixing belt **20** has the circumference R (e.g., an inner circumference) of 76.5 mm. The inner circumferential face **20b** of the fixing belt **20** has an entire area of 17,901 mm.² obtained by multiplying 234 mm by 76.5 mm. The fluorine grease has the specific density G of 2.0 kg/m.³.

(95) Based on the above-described values, according to the formula (2), the application amount A of the grease **90** is approximately 6×10^{-5} g or greater. Accordingly, the recesses on the inner circumferential face **20b** of the fixing belt **20**, especially, the grease reservoirs **40**, retain the grease **90**. Hence, the grease **90** in a proper amount is supplied to a gap between the front face **30a** of the base **30** and the inner circumferential face **20b** of the fixing belt **20** over time, preventing shortage of the oil film.

(96) The application amount A of the grease **90** is not greater than a volume of the grease reservoirs **40** disposed upstream and downstream from the slide nip N1 in the sheet conveyance direction DP, respectively. If the grease **90** is applied in an amount greater than a volume of the space of the grease reservoirs **40**, the grease **90** may leak from each lateral end of the fixing belt **20** in the longitudinal direction thereof. Sliding friction may increase due to an excessive amount of the grease **90**. Each of the grease reservoirs **40** defines space that is produced between the inner circumferential face **20b** of the fixing belt **20** and the front face **30a** of the base **30**. The space has a width Y1 and is disposed outboard from the slide nip N1 in the sheet conveyance direction DP as illustrated in FIG. 9.

(97) Each of the grease reservoirs **40** disposed outboard from the slide nip N1 in the sheet conveyance direction DP has the width Y1. Each of the protrusions **23e** of the heater holder **23** protrudes beyond the front face **30a** of the base **30** for a protrusion amount Z1. Hence, the application amount A of the grease **90** satisfies a formula (3) below. According to the formula (3), the width Y1 multiplied by 2 is multiplied by the protrusion amount Z1 and the length X1 of the fixing belt **20** in the longitudinal direction thereof to obtain a volume V in a unit of m^3 of the grease reservoirs **40**.

$$A \leq Y1 \times 2 \times Z1 \times X1 \times \dots \quad (3)$$

(98) As described above, the slide nip N1 has a width of 5.1 mm. The heater **22C** has a width of 8.0 mm in the short direction Y thereof. Hence, the width Y1 multiplied by 2 is 2.9 mm. The protrusion **23e** has a height of 1.57 mm. The first thermal conductor **28** has a thickness of 0.3 mm. The heater **22C** has a thickness of 1.07 mm. Hence, the protrusion amount Z1 is 0.2 mm. The length X1 of the fixing belt **20** in the longitudinal direction thereof is 234 mm. Thus, according to the formula (3), the volume V of the grease reservoir **40** is 135.72 mm^3 that is obtained by multiplying 2.9 mm by 0.2 mm and 234 mm. The volume V is multiplied by the specific density G of the grease **90** to obtain 2.7×10^{-4} g. The application amount A of the grease **90** is not greater than 2.7×10^{-4} g. Thus, the grease **90** does not leak from each lateral end of the fixing belt **20** in the longitudinal direction thereof. Further, the grease **90** prevents increase in initial torque of the fixing belt **20** when driving of the fixing belt **20** starts and prevents resultant slippage of the fixing belt **20**.

(99) A description is provided of one example of a calculation method for calculating the protrusion amount Z1 (e.g., a height) of the protrusion **23e**.

(100) The heater **22C** and the first thermal conductor **28** are removed from the fixing device **9A**. In a state in which the pressure roller **21** presses the fixing belt **20** against the heater **22C**, a height from a bottom face of the recess **23b** to a peak of the protrusion **23e** that protrudes toward the fixing belt **20** is measured with a height gauge. The bottom face of the recess **23b**, that is measured, is horizontal with respect to a floor. The heights are measured at an upstream position and a downstream position on the recess **23b** in the sheet conveyance direction DP, respectively, and averaged to obtain an average. A thickness of the heater **22C** and a thickness of the first thermal conductor **28**, that are measured, are subtracted from the average to obtain the protrusion amount Z1 (e.g., the height) of the protrusion **23e**.

(101) Since the back face **30b** of the base **30** mounts the resistive heat generators **31C**, compared to a configuration in which the front face **30a** of the base **30** mounts the resistive heat generators **31C**, the heater **22C** suppresses temperature increase of the front face **30a** of the base **30**, that serves as the slide face over which the fixing belt **20** slides. Accordingly, the heater **22C** prevents the resistive heat generators **31C** from heating the grease **90** accumulated in the grease reservoirs **40**,

suppressing decrease in viscosity of the grease **90** and volatilization of fluorine oil. Hence, the grease reservoirs **40** retain the grease **90** in a proper condition and supply a base oil component of the grease **90** to the slide nip N1. Consequently, the inner circumferential face **20b** of the fixing belt **20** slides over the heater **22C** properly.

(102) As described above, the back face **30b** of the base **30** mounts the resistive heat generators **31C**. Additionally, the application amount A of the grease **90** (e.g., the fluorine grease) is in a range from a lower limit to an upper limit of the values described above. Accordingly, the inner circumferential face **20b** of the fixing belt **20** slides over the heater **22C** properly for an extended period of time. Consequently, the inner circumferential face **20b** of the fixing belt **20** slides over the front face **30a** of the base **30** without abrasion and noise. Further, the grease **90** prevents slippage of the fixing belt **20** while the fixing belt **20** rotates.

(103) The first thermal conductor **28** is disposed opposite the back face **30b** of the base **30**, preventing local overheating in an opposed portion of the heater **22C**, that is disposed opposite the resistive heat generators **31C**. Accordingly, the first thermal conductor **28** prevents the heater **22C** from heating the grease **90** accumulated in the grease reservoirs **40**, suppressing decrease in viscosity of the grease **90** and volatilization of the fluorine oil. Hence, the grease reservoirs **40** supply the grease **90** in the proper condition to the slide nip N1, improving sliding of the inner circumferential face **20b** of the fixing belt **20** over the heater **22C**.

(104) The resistive heat generators **31C** are disposed in the slide nip N1 in the sheet conveyance direction DP. Thus, the resistive heat generators **31C** do not heat the grease **90** accumulated in the grease reservoirs **40** disposed outside the slide nip N1, suppressing decrease in viscosity of the grease **90** and volatilization of the fluorine oil. Hence, the grease reservoirs **40** supply the grease **90** in the proper condition to the slide nip N1, causing the inner circumferential face **20b** of the fixing belt **20** to slide over the heater **22C** properly.

(105) According to the embodiment, the application amount A of the grease **90** is 0.15 g. Even if the application amount A of the grease **90** has an error of approximately plus or minus 30 percent, the application amount A of the grease **90** is preferably in the range from the lower limit to the upper limit of the values described above.

(106) The fluorine grease is preferably used as the lubricant like in the embodiment. Accordingly, the thickener made of PTFE attains viscosity of the grease **90**, preventing shortage of the oil film between the fixing belt **20** and the heater **22C** and retaining the lubricant. Consequently, the fixing belt **20** slides over the heater **22C** properly for an extended period of time.

(107) According to the embodiment, the fixing belt **20** may include the elastic layer. Hence, the fixing belt **20** has an increased rigidity, decreasing the slide nip N1. The fixing belt **20** may have an outer diameter that is smaller than an outer diameter of the pressure roller **21**. Accordingly, the fixing belt **20** decreases the slide nip N1.

(108) The front face **30a**, serving as the slide face, of the base **30** of the heater **22C** preferably has a surface roughness of 0.2 μm or smaller. Since the front face **30a** of the base **30** has decreased capacity for retaining the grease **90**, in order to suppress sliding friction with which the inner circumferential face **20b** of the fixing belt **20** slides over the front face **30a** of the base **30**, the front face **30a** preferably has a decreased surface roughness. The inner circumferential face **20b** of the fixing belt **20** preferably has a surface roughness of 0.5 μm or smaller. The inner circumferential face **20b** of the fixing belt **20**, that has the decreased surface roughness, prevents the roughness on the inner circumferential face **20b** of the fixing belt **20** from trapping the grease **90** and inhibiting the grease **90** from being supplied to a gap between the inner circumferential face **20b** of the fixing belt **20** and the heater **22C**.

(109) The surface roughness described above is measured with a surface roughness tester, Surfcom 1400A, available from Tokyo Seimitsu Co., Ltd. by a method conforming to JIS B0601-2001 of the Japanese Industrial Standards. The arithmetic average roughness Ra is measured under a measurement condition of an evaluation length Ln of 1.5 mm, a reference length Lr of 0.25 mm,

and a cutoff value of 0.8 mm.

(110) In order to improve quality of a toner image fixed on a sheet P and extend a life of the fixing device **9A**, the fixing belt **20** improves rigidity by incorporating a thickened base layer, a metallic base layer, a thickened elastic layer, or the like. However, if the fixing belt **20** has an increased rigidity, the fixing belt **20** is deformed by pressure from the pressure roller **21** with a decreased deformation amount, decreasing the slide nip N1 compared to the fixing nip N2. If the fixing belt **20** has a decreased outer diameter or has an outer diameter that is smaller than an outer diameter of the pressure roller **21**, the slide nip N1 is smaller than the fixing nip N2.

(111) A description is provided of results of an experiment, that indicate a relation between the slide nip N1 and the fixing nip N2.

(112) The experiment uses fixing devices of two types, that is, a first fixing device having a first configuration and a second fixing device having a second configuration.

(113) The first fixing device includes the fixing belt **20** having an outer diameter of 25 mm. The fixing belt **20** includes the base layer that has a thickness of 60 μm and is made of polyimide, the elastic layer that has a thickness of 250 μm and is made of silicone rubber, and the release layer, serving as the outermost surface layer, that has a thickness of 12 μm and is made of PFA. The pressure roller **21** has an outer diameter of 20 mm. The pressure roller **21** includes the core metal **21a**, the elastic layer **21b** that has a thickness of 3.5 mm and is made of silicone rubber, and the surface layer **21c**, serving as an outermost surface layer or a release layer, that has a thickness of 50 μm and is made of PFA.

(114) The second fixing device includes the fixing belt **20** having an outer diameter of 25 mm. The fixing belt **20** includes the base layer that has a thickness of 40 μm and is made of nickel, the elastic layer that has a thickness of 120 μm and is made of silicone rubber, and the release layer, serving as the outermost surface layer, that has a thickness of 7 μm and is made of PFA. The pressure roller **21** of the second fixing device has a construction equivalent to the construction of the pressure roller **21** of the first fixing device.

(115) With the first fixing device and the second fixing device, as a hardness (e.g., Asker C hardness) on an axis of the pressure roller **21** changes, a width of the slide nip N1 and a width of the fixing nip N2 in the sheet conveyance direction DP are measured to obtain results of measurement illustrated in FIG. **10**. FIG. **10** illustrates a result of the first fixing device with a solid line. FIG. **10** illustrates a result of the second fixing device with a broken line.

(116) The width of the fixing nip N2 is measured as below. While the fixing belt **20** has a surface temperature of 190 degrees Celsius, the fixing device **9A** (e.g., the first fixing device or the second fixing device) is driven for five minutes or longer. After an overhead projector (OHP) transparency starts passing through the fixing nip N2 until the fixing belt **20** rotates for one rotation, the fixing device **9A** stops and halts a leading edge of the OHP transparency. The fixing belt **20** and the pressure roller **21** sandwich the OHP transparency at the fixing nip N2. After the OHP transparency is left for 20 seconds, the OHP transparency is removed. An imprint of the width of the fixing nip N2, that is produced on the OHP transparency, is measured precisely with a vernier caliper. Thus, the width of the fixing nip N2 of the fixing device **9A** is measured.

(117) As illustrated in FIG. **10**, with the fixing nip N2 having a width in a range of from 6.5 mm to 8.0 mm, the slide nip N1 of the first fixing device is smaller than the fixing nip N2 by a width in a range of from 1.4 mm to 2.0 mm approximately. Conversely, the slide nip N1 of the second fixing device is smaller than the fixing nip N2 by a width in a range of from 2.4 mm to 3.0 mm approximately. Thus, the second fixing device employing the fixing belt **20** incorporating the base layer made of nickel having an increased rigidity decreases the width of the slide nip N1.

(118) If the resistive heat generators **31C** are disposed outside the slide nip N1 in the sheet conveyance direction DP, the temperature of the heater **22C** increases in an outside of the slide nip N1, decreasing viscosity of the grease **90** in the grease reservoirs **40** and volatilizing the fluorine oil. Hence, the second fixing device employing the fixing belt **20** having an increased rigidity

increases the fixing nip N2 and the slide nip N1. For example, the second fixing device employs the fixing nip N2 spotted at an upper right position in FIG. 10. Hence, in view of downsizing the fixing device 9A and suppressing driving torque, the fixing belt 20 of the first fixing device is preferably employed.

(119) FIG. 11 is a diagram illustrating a temperature profile of the fixing belt 20 in the longitudinal direction thereof. FIG. 11 illustrates, in a section (a), arrangement of the resistive heat generators 31 of the heater 22. FIG. 11 illustrates, in a section (b), a vertical axis that represents a temperature T of the fixing belt 20 and a horizontal axis that represents the longitudinal direction X of the fixing belt 20.

(120) As illustrated in the sections (a) and (b) in FIG. 11, the heater 22 includes the plurality of resistive heat generators 31 divided and arranged in the longitudinal direction X of the heater 22 to produce a gap B (e.g., a dividing region) between the adjacent resistive heat generators 31 in the longitudinal direction X of the heater 22. In other words, the plurality of resistive heat generators 31 of the heater 22 is arranged with the gap B between the adjacent resistive heat generators 31. The gap B defines a dividing region or a dividing span. An opposed portion of the resistive heat generators 31, that is disposed opposite the gap B, occupies an area smaller than an area of other portion of each of the resistive heat generators 31, thus generating a decreased amount of heat. Accordingly, an opposed portion of the fixing belt 20, that is disposed opposite the gap B, has a lower temperature compared to other portion of the fixing belt 20, causing uneven temperature of the fixing belt 20 in the longitudinal direction X thereof. The adjacent resistive heat generators 31 define an enlarged gap region C (e.g., an enlarged dividing region) encompassing the gap B, serving as the dividing region, and a peripheral region thereof. The heater 22 and the fixing belt 20 suffer from temperature decrease also in opposed portions thereof, that are disposed opposite the enlarged gap region C, respectively. Similarly, the heater 22 suffers from temperature decrease also in an opposed portion thereof, that is disposed opposite the gap B. As illustrated in an enlarged view in the section (a) in FIG. 11, the gap B indicates a region encompassing an entirety of the dividing region between the adjacent resistive heat generators 31 serving as a main heat generation portion of the heater 22 in the longitudinal direction thereof. The resistive heat generator 31 includes a joint 311 that is coupled with the feeder 33A or 33B. The enlarged gap region C encompasses the joints 311 in addition to the gap B. The joint 311 defines a part of the resistive heat generator 31, that extends substantially in the short direction Y of the heater 22 and is coupled with the feeder 33A or 33B.

(121) FIG. 12 illustrates the heater 22A depicted in FIG. 5 that includes the resistive heat generators 31A that are rectangular. In the heater 22A also, a temperature of an opposed portion of the heater 22A, that is disposed opposite the gap B, is lower than a temperature of other portion of the heater 22A. FIG. 13 illustrates a heater 22D that includes a plurality of resistive heat generators 31D that is zigzag. In the heater 22D also, a temperature of an opposed portion of the heater 22D, that is disposed opposite the gap B, is lower than a temperature of other portion of the heater 22D. FIG. 14 illustrates the heater 22B depicted in FIG. 6 that includes the resistive heat generators 31B including the linear portion that defines the parallelogram. In the heater 22B also, a temperature of an opposed portion of the heater 22B, that is disposed opposite the gap B, is lower than a temperature of other portion of the heater 22B. As illustrated in FIGS. 11, 13, and 14, the adjacent resistive heat generators 31, 31D, and 31B overlap each other in a longitudinal direction of the heaters 22, 22D, and 22B, suppressing temperature decrease of the opposed portion of each of the heaters 22, 22D, and 22B, that is disposed opposite the gap B, compared to other portion of each of the heaters 22, 22D, and 22B.

(122) The fixing device 9 according to the embodiment incorporates the first thermal conductor 28 that suppresses temperature decrease at the gap B and thereby suppresses uneven temperature of the fixing belt 20 in the longitudinal direction thereof.

(123) A description is provided of a configuration of the first thermal conductor 28 in detail.

(124) As illustrated in FIG. 2, the first thermal conductor **28** is interposed between the heater **22** and the stay **24** in a horizontal direction in FIG. 2. Specifically, the first thermal conductor **28** is sandwiched between the heater **22** and the heater holder **23**. For example, the first thermal conductor **28** has one face that is disposed opposite the back face **30b** of the base **30** of the heater **22** and another face that contacts the heater holder **23**.

(125) The stay **24** includes two perpendicular portions **24a** that extend in a thickness direction of the heater **22** and the like. Each of the perpendicular portions **24a** has a contact face **24a1** that contacts the heater holder **23**, supporting the heater holder **23**, the first thermal conductor **28**, and the heater **22**. The contact faces **24a1** are disposed outboard from the resistive heat generators **31** in the short direction Y (e.g., a vertical direction in FIG. 2) of the heater **22**. Thus, the stay **24** suppresses conduction of heat thereto from the heater **22**, causing the heater **22** to heat the fixing belt **20** efficiently.

(126) As illustrated in FIG. 15, the first thermal conductor **28** is a plate. According to the embodiment, the first thermal conductor **28** is constructed of a single plate. Alternatively, the first thermal conductor **28** may be constructed of a plurality of members. FIG. 15 omits illustration of the guides **26** depicted in FIG. 2.

(127) The first thermal conductor **28** is fitted to the recess **23b** of the heater holder **23**. The heater **22** is attached to the heater holder **23** from above the first thermal conductor **28**. Thus, the heater holder **23** and the heater **22** sandwich and hold the first thermal conductor **28**. According to the embodiment, the first thermal conductor **28** has a length in the longitudinal direction thereof, which is equivalent to a length of the heater **22** in the longitudinal direction thereof. The heater holder **23** includes side walls **23b1**, serving as longitudinal direction restrictors, that are disposed at both lateral ends of the heater holder **23** in the longitudinal direction thereof, respectively, and define the recess **23b**. The side walls **23b1** restrict motion of the first thermal conductor **28** and the heater **22** in the longitudinal direction thereof. Thus, the side walls **23b1** restrict shifting of the first thermal conductor **28** in the longitudinal direction thereof inside the fixing device **9**, improving efficiency in thermal conduction in a target span in the longitudinal direction of the first thermal conductor **28**. The heater holder **23** further includes side walls **23b2**, serving as short direction restrictors, that are disposed at both ends of the heater holder **23** in a short direction thereof, respectively, and define the recess **23b**. The side walls **23b2** restrict motion of the first thermal conductor **28** and the heater **22** in the short direction thereof.

(128) The first thermal conductor **28** may extend in a span other than a span in which the first thermal conductor **28** extends in the longitudinal direction thereof as illustrated in FIG. 15. For example, FIG. 16 illustrates a fixing device **9B** incorporating a first thermal conductor **28A** that extends in a span hatched in FIG. 16 and defined by the heat generation portion **35** in the longitudinal direction X of the heater **22**. FIG. 17 illustrates a fixing device **9C** incorporating first thermal conductors **28B**. Each of the first thermal conductors **28B** is disposed opposite and spans an entire span of the gap B in a longitudinal direction of the heater **22A** in which the resistive heat generators **31A** are arranged. FIG. 17 illustrates the resistive heat generators **31A** shifted from the first thermal conductors **28B** vertically in FIG. 17 for convenience. Practically, the resistive heat generators **31A** are substantially leveled with the first thermal conductors **28B** in a short direction of the heater **22A**. Alternatively, the first thermal conductors **28B** may be disposed with respect to the resistive heat generators **31A** with other arrangement. For example, the first thermal conductor **28B** may span or cover a part of the resistive heat generator **31A** in the short direction of the heater **22A**. FIG. 18 illustrates a fixing device **9D** incorporating a first thermal conductor **28C** that spans or covers an entirety of the resistive heat generator **31A** in the short direction Y of the heater **22A**. As illustrated in FIG. 18, the first thermal conductor **28C** is disposed opposite and spans the gap B in the longitudinal direction X of the heater **22A**. Additionally, the first thermal conductor **28C** bridges the adjacent resistive heat generators **31A** that sandwich the gap B. A state in which the first thermal conductor **28C** bridges the adjacent resistive heat generators **31A** denotes a state in which

the first thermal conductor **28C** overlaps the adjacent resistive heat generators **31A** at least partially in the longitudinal direction X of the heater **22A**. Alternatively, the first thermal conductors **28C** may be disposed opposite the gaps B of the heater **22A**, respectively. Yet alternatively, for example, as illustrated in FIG. **18**, the first thermal conductor **28C** may be disposed opposite a part of the gaps B, for example, one of the gaps B. A state in which the first thermal conductor **28C** spans the gap B in the longitudinal direction X of the heater **22A** denotes that at least a part of the first thermal conductor **28C** overlaps the gap B in the longitudinal direction X of the heater **22A**.

(129) As illustrated in FIGS. **2** and **9**, as the pressure roller **21** applies pressure to a heater (e.g., the heaters **22**, **22A**, **22B**, **22C**, and **22D**), the heater and the heater holder **23** sandwich a first thermal conductor (e.g., the first thermal conductors **28**, **28A**, **28B**, and **28C**) such that the first thermal conductor contacts the heater and the heater holder **23**. As the first thermal conductor contacts the heater, the first thermal conductor conducts heat generated by the heater in a longitudinal direction thereof with improved efficiency. The first thermal conductor is disposed opposite at least one gap B between adjacent resistive heat generators (e.g., the resistive heat generators **31**, **31A**, **31B**, **31C**, and **31D**) arranged in a longitudinal direction of the heater. Thus, the first thermal conductor improves efficiency in conduction of heat at the gaps B, increases an amount of heat conducted to the gaps B, and increases the temperature of the heater at the gaps B arranged in the longitudinal direction of the heater, thus suppressing uneven temperature of the heater in the longitudinal direction thereof. Accordingly, the first thermal conductor suppresses uneven temperature of the fixing belt **20** in the longitudinal direction thereof. Consequently, the fixing belt **20** suppresses uneven fixing and uneven gloss of a toner image fixed on a sheet P. The heater does not heat the fixing belt **20** redundantly to attain sufficient fixing performance at the gaps B, causing a fixing device (e.g., the fixing devices **9**, **9A**, **9B**, **9C**, and **9D**) to save energy. The first thermal conductor extends throughout an entire span of the heat generating portion **35** in the longitudinal direction of the heater. Accordingly, the first thermal conductor improves efficiency in conduction of heat of the heater in an entirety of a main heating span of the heater disposed opposite an imaging span of a toner image formed on a sheet P conveyed through the fixing nip N2. Accordingly, the first thermal conductor suppresses uneven temperature of the heater and the fixing belt **20** in the longitudinal direction thereof.

(130) According to the embodiment, the first thermal conductor is coupled with the resistive heat generators having the PTC property described above, suppressing overheating of the fixing belt **20** in the non-conveyance span where a sheet P having a decreased size is not conveyed effectively. For example, the PTC property suppresses an amount of heat generated by the resistive heat generators in the non-conveyance span. Additionally, the first thermal conductor efficiently conducts heat from the non-conveyance span on the fixing belt **20** that suffers from temperature increase to a sheet conveyance span on the fixing belt **20**, where the sheet P is conveyed, thus suppressing overheating of the fixing belt **20** in the non-conveyance span effectively.

(131) Since the heater generates heat in a decreased amount at the gap B between the adjacent resistive heat generators, the heater has a decreased temperature also in a periphery of the gap B. To address the circumstance, the first thermal conductor is preferably disposed also in the periphery of the gap B. For example, according to the embodiment illustrated in FIG. **11**, the first thermal conductor **28** is disposed opposite the enlarged gap region C. Hence, the first thermal conductor **28** improves efficiency in conduction of heat at the gap B and the periphery thereof in the longitudinal direction X of the heater **22**, suppressing uneven temperature of the heater **22** in the longitudinal direction X thereof. According to the embodiment, the first thermal conductor **28** extends throughout the entire span of the heat generation portion **35** in the longitudinal direction X of the heater **22**. Accordingly, the first thermal conductor **28** suppresses uneven temperature of the heater **22** and the fixing belt **20** in the longitudinal direction X thereof more effectively.

(132) A description is provided of a construction of a fixing device **9E** according to an embodiment of the present disclosure.

(133) As illustrated in FIG. 19, the fixing device 9E according to the embodiment includes second thermal conductors 36 and a heater holder 23A. The second thermal conductors 36 are sandwiched between the heater holder 23A and the first thermal conductor 28. Each of the second thermal conductors 36 is disposed at a position different from a position of the first thermal conductor 28 in a laminating direction (e.g., a horizontal direction in FIG. 19) in which the stay 24, the heater holder 23A, the second thermal conductor 36, the first thermal conductor 28, and the heater 22 are arranged. Specifically, the second thermal conductors 36 are superimposed on the first thermal conductor 28. Unlike FIG. 2 illustrating the fixing device 9, FIG. 19 illustrates a cross section, that crosses a longitudinal direction of the fixing device 9E in which the second thermal conductors 36 are arranged, where the second thermal conductor 36 is disposed and the thermistor 25 is not disposed in the laminating direction.

(134) The second thermal conductor 36 is made of a material having a thermal conductivity greater than a thermal conductivity of the base 30. For example, the second thermal conductor 36 is made of graphene or graphite. According to the embodiment, the second thermal conductor 36 is a graphite sheet having a thickness of 1 mm. Alternatively, the second thermal conductor 36 may be a plate made of aluminum, copper, silver, or the like.

(135) As illustrated in FIG. 20, the plurality of second thermal conductors 36 is arranged on a plurality of parts on the heater holder 23A in a longitudinal direction thereof, respectively. The heater holder 23A includes a recess 23bA that includes cavities placed with the second thermal conductors 36, respectively. The cavities are stepped down by one step from other portion of the recess 23bA. The second thermal conductor 36 and the heater holder 23A define a gap therebetween at both lateral ends of the second thermal conductor 36 in the longitudinal direction of the heater holder 23A. Thus, the second thermal conductor 36 suppresses conduction of heat therefrom to the heater holder 23A, causing the heater 22 to heat the fixing belt 20 efficiently. FIG. 20 omits illustration of the guides 26 depicted in FIG. 2.

(136) As illustrated in FIG. 21, the second thermal conductor 36 that is hatched is disposed opposite the gap B between the adjacent resistive heat generators 31 and overlaps at least a part of the adjacent resistive heat generators 31 in the longitudinal direction X of the heater 22. According to the embodiment, the second thermal conductor 36 extends throughout the entire span of the gap B. FIG. 21 and FIG. 25 referred to in a description below illustrate the first thermal conductor 28 that is disposed opposite and spans the heat generation portion 35 in the longitudinal direction X of the heater 22. Alternatively, the first thermal conductor 28 may span differently as described above.

(137) The fixing device 9E according to the embodiment includes, in addition to the first thermal conductor 28, the second thermal conductors 36 each of which is disposed opposite the gap B and overlaps at least a part of the adjacent resistive heat generators 31 in the longitudinal direction X of the heater 22. The second thermal conductors 36 improve efficiency in conduction of heat at the gaps B in the longitudinal direction X of the heater 22, suppressing uneven temperature of the heater 22 in the longitudinal direction X thereof more effectively.

(138) FIG. 22 illustrates a fixing device 9F including the first thermal conductors 28B, second thermal conductors 36D, and a heater 22A including the resistive heat generators 31A. The first thermal conductor 28B and the second thermal conductor 36D are preferably disposed opposite the entire span of the gap B in the longitudinal direction of the heater 22A. Accordingly, the first thermal conductor 28B and the second thermal conductor 36D improve efficiency in conduction of heat at the gap B compared to an outboard region of the heater 22A, which is other than the gap B. FIG. 22 illustrates the resistive heat generators 31A shifted from the first thermal conductors 28B and the second thermal conductors 36D vertically in FIG. 22 for convenience. Practically, the resistive heat generators 31A are substantially leveled with the first thermal conductors 28B in the short direction of the heater 22A. Alternatively, the first thermal conductors 28B may be disposed with respect to the resistive heat generators 31A with other arrangement. For example, the first thermal conductor 28B and the second thermal conductor 36D may span a part of the resistive heat

generator **31A** in the short direction of the heater **22A**. The first thermal conductor **28B** and the second thermal conductor **36D** may span or cover the entirety of the resistive heat generator **31A** in the short direction of the heater **22A**.

(139) Unlike the embodiment described above, according to an embodiment of the present disclosure, each of a first thermal conductor (e.g., the first thermal conductors **28**, **28A**, **28B**, and **28C**) and a second thermal conductor (e.g., the second thermal conductors **36** and **36D**) is made of a graphene sheet. Hence, each of the first thermal conductor and the second thermal conductor has an enhanced thermal conductivity in a predetermined direction along a surface of the graphene sheet, that is, a longitudinal direction of a heater (e.g., the heaters **22**, **22A**, **22B**, **22C**, and **22D**), not a thickness direction of the first thermal conductor and the second thermal conductor.

Accordingly, the first thermal conductor and the second thermal conductor suppress uneven temperature of the heater and the fixing belt **20** in the longitudinal direction thereof effectively.

(140) Graphene is thin powder. As illustrated in FIG. **23**, graphene is constructed of a plane of carbon atoms arranged in a two-dimensional honeycomb lattice. The graphene sheet is graphene in a sheet form and is usually constructed of a single layer. The graphene sheet may contain impurities in the single layer of carbon atoms. The graphene sheet may have a fullerene structure. The fullerene structure is generally recognized as a polycyclic compound constructed of an identical number of carbon atoms bonded to form a cage with fused rings of five and six atoms. For example, the fullerene structure is a closed cage structure formed of fullerene C.sub.60, C.sub.70, and C.sub.80, 3-coordinated carbon atoms, or the like.

(141) The graphene sheet is artificial and is produced by chemical vapor deposition (CVD), for example.

(142) The graphene sheet is commercially available. A size and a thickness of the graphene sheet and a number of layers and the like of the graphite sheet described below are measured with a transmission electron microscope (TEM), for example.

(143) Graphite is constructed of stacked layers of graphene and is highly anisotropic in thermal conduction. As illustrated in FIG. **24**, graphite has a plurality of layers, each of which is constructed of hexagonal fused rings of carbon atoms, that are bonded planarly. The plurality of layers defines a crystalline structure. In the crystalline structure, adjacent carbon atoms in the layer are bonded with each other by a covalent bond. Bonding between layers of carbon atoms is established by the van der Waals bond. The covalent bond achieves bonding greater than bonding by the van der Waals bond. Graphite is highly anisotropic with bonding within the layer and bonding between the layers. For example, a first thermal conductor (e.g., the first thermal conductors **28**, **28A**, **28B**, and **28C**) or a second thermal conductor (e.g., the second thermal conductors **36** and **36D**) is made of graphite. Accordingly, the first thermal conductor or the second thermal conductor attains an efficiency in conduction of heat in the longitudinal direction of a heater (e.g., the heaters **22**, **22A**, **22B**, **22C**, and **22D**), which is greater than an efficiency in conduction of heat in a thickness direction, that is, the laminating direction (e.g., the horizontal direction in FIG. **19**) in which the stay **24**, the heater holder **23A**, the second thermal conductor **36**, the first thermal conductor **28**, and the heater **22** are arranged, thus suppressing conduction of heat to the heater holder **23A**. Consequently, the first thermal conductor or the second thermal conductor suppresses uneven temperature of the heater in the longitudinal direction X thereof efficiently. Additionally, the first thermal conductor or the second thermal conductor minimizes heat conducted to the heater holder **23A**. The first thermal conductor or the second thermal conductor that is made of graphite attains enhanced heat resistance that inhibits oxidation at approximately 700 degrees Celsius.

(144) The graphite sheet has a physical property and a dimension that are adjusted properly according to a function of the first thermal conductor or the second thermal conductor. For example, the graphite sheet is made of graphite having enhanced purity or single crystal graphite. The graphite sheet has an increased thickness to enhance anisotropic thermal conduction. In order

to perform high speed fixing, a fixing device (e.g., the fixing devices **9E** and **9F**) employs the graphite sheet having a decreased thickness to decrease thermal capacity of the fixing device. If the fixing nip **N2** and the heater have an increased length in the longitudinal direction **X** thereof, the first thermal conductor or the second thermal conductor also has an increased length in the longitudinal direction **X** of the heater.

(145) In view of increasing mechanical strength, the graphite sheet preferably has a number of layers that is not smaller than 11 layers. The graphite sheet may include a part constructed of a single layer and another part constructed of a plurality of layers.

(146) The second thermal conductor **36** is disposed opposite the gap **B** between the adjacent resistive heat generators **31** and the enlarged gap region **C** depicted in FIG. **11** and overlaps at least a part of the adjacent resistive heat generators **31** in the longitudinal direction **X** of the heater **22**. Hence, the second thermal conductor **36** may be positioned with respect to the resistive heat generators **31** differently from the second thermal conductor **36** depicted in FIG. **21**. For example, FIG. **25** illustrates a fixing device **9G** including a second thermal conductor **36A** that protrudes beyond the base **30** bidirectionally in the short direction **Y** of the heater **22**. The fixing device **9G** further includes a second thermal conductor **36B** that is disposed in a span of the resistive heat generator **31** in the short direction **Y** of the heater **22**. The fixing device **9G** further includes a second thermal conductor **36C** that spans a part of the gap **B**.

(147) FIG. **26** illustrates a fixing device **9H** according to an embodiment of the present disclosure that includes the heater holder **23A** including a retracted portion **23c** (e.g., a clearance) that is interposed between the first thermal conductor **28** and a body of the heater holder **23A** in a thickness direction of the heater holder **23A** (e.g., a horizontal direction in FIG. **26**). For example, the retracted portion **23c** is disposed in a part of the recess **23bA** of the heater holder **23A** depicted in FIG. **20**, which accommodates the heater **22**, the first thermal conductor **28**, and the second thermal conductors **36**. The retracted portion **23c** is disposed outboard from the second thermal conductor **36** in the longitudinal direction **X** of the heater **22**. The retracted portion **23c** spans a part of the recess **23bA** in the short direction **Y** of the heater **22**. A part of the recess **23bA** is stepped down from other part of the recess **23bA**, that accommodates the first thermal conductor **28**, to produce the retracted portion **23c** serving as a thermal insulation layer. Accordingly, the heater holder **23A** contacts the first thermal conductor **28** with a decreased contact area, thus suppressing conduction of heat from the first thermal conductor **28** to the heater holder **23A** and causing the heater **22** to heat the fixing belt **20** efficiently. On a cross section that intersects a longitudinal direction of the fixing device **9H** and is provided with the second thermal conductor **36**, the second thermal conductor **36** contacts the heater holder **23A** as illustrated in FIG. **19** illustrating the fixing device **9E** according to the embodiment described above.

(148) According to the embodiment, the retracted portion **23c** spans an entirety of the resistive heat generator **31** in the short direction **Y** (e.g., a vertical direction in FIG. **26**) of the heater **22**. Thus, the retracted portion **23c** suppresses conduction of heat from the first thermal conductor **28** to the heater holder **23A**, causing the heater **22** to heat the fixing belt **20** efficiently. Alternatively, instead of the retracted portion **23c** that defines the clearance, the fixing device **9H** may incorporate a thermal insulator that has a thermal conductivity smaller than a thermal conductivity of the heater holder **23A**, as the thermal insulation layer.

(149) According to the embodiments described above, the second thermal conductor **36** is provided separately from the first thermal conductor **28**. Alternatively, the fixing device **9H** may have other configuration. For example, the first thermal conductor **28** may include an opposed portion that is disposed opposite the gap **B** and has a thickness greater than a thickness of an outboard portion of the first thermal conductor **28**, which is other than the opposed portion.

(150) According to the embodiments depicted in FIGS. **19** and **26** also, like in the embodiments described above, the resistive heat generators **31** are mounted on the back face **30b** of the base **30**, that is opposite to the front face **30a** of the base **30**, that is disposed opposite the slide nip **N1**.

Additionally, the lubricant is applied in a proper amount. Thus, the fixing belt **20** slides over the heater **22** properly.

(151) The embodiments of the present disclosure are also applied to a fixing device **9I** illustrated in FIG. **27**, other than the fixing devices **9**, **9A**, **9B**, **9C**, **9D**, **9E**, **9F**, **9G**, and **9H** described above.

(152) Referring to FIG. **27**, a description is provided of a construction of the fixing device **9I** according to an embodiment of the present disclosure.

(153) As illustrated in FIG. **27**, the fixing device **9I** includes a heating assembly **92**, a fixing roller **93** serving as a pressure rotator, and a pressure assembly **94** serving as an opposed rotator. The heating assembly **92** includes the heater **22**, the first thermal conductor **28**, the heater holder **23**, and the stay **24** that are described in the embodiments above and a heating belt **120** serving as a rotator. The fixing roller **93** presses against the heating belt **120** to form a heating nip N3 therebetween, thus serving as the pressure rotator. The fixing roller **93** includes a core metal **93a**, an elastic layer **93b**, and a surface layer **93c**. The pressure assembly **94** is disposed opposite the heating assembly **92** via the fixing roller **93**. The pressure assembly **94** includes a nip formation pad **95**, a stay **96**, and a pressure belt **97**. The pressure belt **97** rotates and is formed into a loop within which the nip formation pad **95** and the stay **96** are disposed. The pressure belt **97** and the fixing roller **93** define the fixing nip N2 therebetween. As a sheet P is conveyed through the fixing nip N2, the fixing roller **93** heated at the heating nip N3 and the pressure belt **97** fix a toner image formed on the sheet P thereon under heat and pressure.

(154) According to the embodiment depicted in FIG. **27** also, like in the embodiments described above, the resistive heat generators **31** are mounted on the back face **30b** of the base **30**, that is opposite to the front face **30a** of the base **30**, that is disposed opposite the slide nip N1.

Additionally, the lubricant is applied in a proper amount. Thus, the heating belt **120** slides over the heater **22** properly.

(155) Application of the technology of the present disclosure is not limited to the fixing devices **9**, **9A**, **9B**, **9C**, **9D**, **9E**, **9F**, **9G**, **9H**, and **9I** according to the embodiments described above. The technology of the present disclosure is also applied to a heating device such as a dryer that dries ink applied onto a sheet. Further, the technology of the present disclosure is also applied to a heating device such as a thermocompression bonding device including a laminator and a heat sealer. The laminator bonds film as a coating member onto a surface of a sheet by thermocompression. The heat sealer bonds sealing portions of a packaging material by thermocompression. As the embodiments of the present disclosure are also applied to the heating device incorporating a rotator and a heater, the rotator slides over the heater properly.

(156) Application of the technology of the present disclosure is not limited to the color image forming apparatus **100** depicted in FIG. **1** that forms a color toner image. The technology of the present disclosure is also applied to a monochrome image forming apparatus that forms a monochrome toner image, a copier, a printer, a facsimile machine, a multifunction peripheral (MFP) having at least two of copying, printing, facsimile, scanning, and plotter functions, or the like.

(157) For example, as illustrated in FIG. **28**, an image forming apparatus **100A** according to an embodiment of the present disclosure includes an image forming device **50** including a photoconductive drum, a sheet conveyance device including the timing roller pair **15**, the sheet feeder **7**, a fixing device **9J**, the output device **10**, and a scanner **51**. The sheet feeder **7** includes a plurality of sheet trays (e.g., paper trays) that loads a plurality of sheets P having different sizes, respectively.

(158) The scanner **51** reads an image on an original Q into image data. The sheet feeder **7** loads the plurality of sheets P and feeds the sheets P to a sheet conveyance path one by one. The timing roller pair **15** conveys the sheet P conveyed through the sheet conveyance path to the image forming device **50**.

(159) The image forming device **50** forms a toner image on the sheet P. For example, the image

forming device **50** includes the photoconductive drum, a charging roller, an exposure device, a developing device, a replenishing device, a transfer roller, a cleaner, and a discharger. The toner image is a reproduction of the image on the original Q, for example. The fixing device **9J** fixes the toner image on the sheet P under heat and pressure. The sheet P bearing the fixed toner image is conveyed to the output device **10** by a conveyance roller and the like. The output device **10** ejects the sheet P onto an outside of the image forming apparatus **100A**.

(160) A description is provided of a construction of the fixing device **9J** according to an embodiment of the present disclosure.

(161) A description of elements of the fixing device **9J**, which are common to the fixing device **9** depicted in FIG. **2**, is omitted properly.

(162) As illustrated in FIG. **29**, the fixing device **9J** includes the fixing belt **20**, the pressure roller **21**, a heater **22E**, a heater holder **23B**, the stay **24**, the thermistors **25**, the guides **26**, and the first thermal conductor **28**.

(163) The fixing belt **20** and the pressure roller **21** define the fixing nip N2 therebetween. The fixing nip N2 has a nip width of 10 mm in the sheet conveyance direction DP. The fixing belt **20** and the pressure roller **21** convey the sheet P at a linear velocity of 240 mm/s.

(164) The fixing belt **20** includes the base layer made of polyimide and the release layer and does not include an elastic layer. The release layer is heat-resistant film made of fluororesin, for example. The fixing belt **20** has an outer diameter of approximately 24 mm.

(165) The pressure roller **21** includes the core metal **21a**, the elastic layer **21b**, and the surface layer **21c**. The pressure roller **21** has an outer diameter in a range of from 24 mm to 30 mm. The elastic layer **21b** has a thickness in a range of from 3 mm to 4 mm.

(166) The heater **22E** includes the base **30**, a thermal insulation layer, a conductor layer including the resistive heat generators **31A**, and an insulating layer. The heater **22E** has a total thickness of 1 mm. The heater **22E** has a width of 13 mm in the short direction Y thereof.

(167) As illustrated in FIG. **30**, the conductor layer of the heater **22E** includes the plurality of resistive heat generators **31A**, the feeders **33**, the electrodes **34A** and **34B**, and an electrode **34C**. According to the embodiment also, as illustrated in an enlarged view in FIG. **30**, the gap B serving as the dividing region is interposed between the adjacent resistive heat generators **31A** arranged in a longitudinal direction of the heater **22E**. FIG. **30** illustrates the two gaps B in the enlarged view. However, the gap B is disposed at each interval between the adjacent resistive heat generators **31A** depicted in FIG. **30**. The heater **22E** further includes three heat generation portions **35A**, **35B**, and **35C** each of which is constructed of the resistive heat generators **31A**. As the electrodes **34A** and **34B** are energized, the heat generation portions **35A** and **35C** generate heat. As the electrodes **34A** and **34C** are energized, the heat generation portion **35B** generates heat. For example, in order to fix a toner image on a sheet P having a decreased size not greater than a predetermined size, the heat generation portion **35B** generates heat. In order to fix a toner image on a sheet P having an increased size greater than the predetermined size, the heat generation portions **35A**, **35B**, and **35C** generate heat.

(168) As illustrated in FIG. **31**, the heater holder **23B** includes a recess **23d** that holds the heater **22E** and the first thermal conductor **28**. The recess **23d** is disposed on a heater opposed face of the heater holder **23B**, that is disposed opposite the heater **22E**. The recess **23d** includes a bottom face **23d1** and walls **23d2** and **23d3**. The bottom face **23d1** is substantially parallel to the base **30** and recessed with respect to the heater **22E** compared to other faces of the heater holder **23B**. The wall **23d2** is disposed at at least one of both lateral ends of the heater holder **23B** in a longitudinal direction thereof and serves as an interior wall of the heater holder **23B**. The walls **23d3** are disposed at both ends of the heater holder **23B** in a short direction thereof and serve as interior walls of the heater holder **23B**, respectively. The heater holder **23B** mounts the guides **26**. The heater holder **23B** is made of LCP.

(169) As illustrated in FIG. **32**, the fixing device **9J** further includes a connector **60** that includes a

housing made of resin such as LCP and a plurality of contact terminals disposed in the housing.

(170) The connector **60** is attached to the heater **22E** and the heater holder **23B** such that the connector **60** sandwiches the heater **22E** and the heater holder **23B** together at a front face and a back face of the heater **22E** and the heater holder **23B**. In a state in which the connector **60** sandwiches and holds the heater **22E** and the heater holder **23B**, as the contact terminals of the connector **60** contact and press against the electrodes **34A**, **34B**, and **34C** of the heater **22E** depicted in FIG. **30**, the heat generation portions **35A**, **35B**, and **35C** are electrically connected to a power supply disposed in the image forming apparatus **100A** through the connector **60**. Thus, the power supply is ready to supply power to the heat generation portions **35A**, **35B**, and **35C**. At least a part of each of the electrodes **34A**, **34B**, and **34C** is not coated with the insulating layer and is exposed so that each of the electrodes **34A**, **34B**, and **34C** is coupled with the connector **60**.

(171) The fixing device **9J** further includes a flange **53** that is disposed on each lateral end of the fixing belt **20** in the longitudinal direction thereof. The flange **53** contacts the inner circumferential face **20b** of the fixing belt **20** and holds or supports the fixing belt **20** at each lateral end of the fixing belt **20** in the longitudinal direction thereof. The flanges **53** are secured to a frame of the fixing device **9J**. The flange **53** is inserted into each lateral end of the stay **24** in the longitudinal direction thereof in an insertion direction **153** illustrated in FIG. **32**.

(172) The connector **60** is attached to the heater **22E** and the heater holder **23B** in an attachment direction **A60** illustrated in FIG. **32** that is parallel to the short direction **Y** of the heater **22E**. Alternatively, in order to attach the connector **60** to the heater holder **23B**, one of the connector **60** and the heater holder **23B** may include a projection that engages a recess disposed in another one of the connector **60** and the heater holder **23B** such that the projection moves inside the recess relatively. The connector **60** is attached to one lateral end of the heater **22E** and the heater holder **23B** in the longitudinal direction of the heater **22E**. The one lateral end of the heater **22E** and the heater holder **23B** is opposite to another lateral end of the heater **22E** and the heater holder **23B**, with which the driver (e.g., a motor) that drives the pressure roller **21** is coupled.

(173) As illustrated in FIG. **33**, the thermistors **25** are disposed opposite the inner circumferential face **20b** of the fixing belt **20** at a position in proximity to a center line **L** and a position in one lateral end span of the fixing belt **20** in the longitudinal direction thereof, respectively. The controller **220** depicted in FIG. **4** controls the heater **22E** based on a temperature of the fixing belt **20**, that is detected by the thermistor **25** disposed at the position in proximity to the center line **L**, and a temperature of the fixing belt **20**, that is detected by the thermistor **25** disposed opposite the one lateral end span of the fixing belt **20** in the longitudinal direction thereof, respectively.

(174) The thermostats **27** are disposed opposite the inner circumferential face **20b** of the fixing belt **20** at a position in proximity to the center line **L** and a position in another lateral end span of the fixing belt **20** in the longitudinal direction thereof, respectively. If the thermostat **27** detects a temperature of the fixing belt **20**, that is higher than a preset threshold, the thermostat **27** breaks power to the heater **22E**.

(175) The flanges **53** contact and support both lateral ends of the fixing belt **20** in the longitudinal direction thereof, respectively. Each of the flanges **53** is made of LCP.

(176) As illustrated in FIG. **34**, the flange **53** includes a slide groove **53a**. The slide groove **53a** extends in a contact-separation direction in which the fixing belt **20** comes into contact with and separates from the pressure roller **21**. The slide groove **53a** engages an engagement mounted on the frame of the fixing device **9J**. As the engagement moves relatively inside the slide groove **53a**, the fixing belt **20** moves in the contact-separation direction with respect to the pressure roller **21**.

(177) Also in the fixing device **9J**, like in the embodiments described above, the resistive heat generators **31A** are mounted on the back face **30b** of the base **30**, that is opposite to the front face **30a** of the base **30**, that is disposed opposite the slide nip **N1**. Additionally, the lubricant is applied in a proper amount. Thus, the fixing belt **20** slides over the heater **22E** properly.

(178) The above describes the embodiments of the present disclosure. However, the technology of

the present disclosure is not limited to the embodiments described above. The embodiments of the present disclosure may be modified variously within the scope of the present disclosure.

(179) Application of the technology of the present disclosure is not limited to the color image forming apparatus **100** depicted in FIG. **1** that forms a color toner image. The technology of the present disclosure is also applied to a monochrome image forming apparatus that forms a monochrome toner image, a copier, a printer, a facsimile machine, a multifunction peripheral (MFP) having at least two of copying, printing, facsimile, scanning, and plotter functions, or the like.

(180) The recording media include, in addition to plain paper as a sheet P, thick paper, a postcard, an envelope, thin paper, coated paper, art paper, tracing paper, an overhead projector (OHP) transparency, plastic film, prepreg, and copper foil.

(181) A description is provided of aspects of the embodiments of the present disclosure.

(182) A description is provided of a first aspect of the embodiments of the present disclosure.

(183) As illustrated in FIG. **9**, a heating device (e.g., the fixing devices **9**, **9A**, **9B**, **9C**, **9D**, **9E**, **9F**, **9G**, **9H**, **9I**, and **9J**) includes a rotator (e.g., the fixing belt **20** and the heating belt **120**) serving as a first rotator, a pressure rotator (e.g., the pressure roller **21** and the fixing roller **93**) serving as a second rotator, a heater (e.g., the heaters **22**, **22A**, **22B**, **22C**, **22D**, and **22E**), a heater holder (e.g., the heater holders **23**, **23A**, and **23B**), and a lubricant holder (e.g., the grease reservoir **40**).

(184) The rotator rotates in a rotation direction (e.g., the rotation direction **D20**). The pressure rotator presses against the heater via the rotator to form an outer face nip (e.g., the fixing nip **N2** depicted in FIGS. **2**, **9**, **19**, **26**, and **29** and the heating nip **N3** depicted in FIG. **27**) between the pressure rotator and the rotator. The heater is disposed opposite an inner face (e.g., the inner circumferential face **20b**) of the rotator. The heater includes a base (e.g., the base **30**) and a resistive heat generator (e.g., the resistive heat generators **31**, **31A**, **31B**, **31C**, and **31D**). The heater holder includes a recess (e.g., the recess **23b**) that holds the heater. The base includes a slide face (e.g., the front face **30a**) over which the inner face of the rotator slides. One of the slide face of the base of the heater and the inner face of the rotator is applied with a lubricant (e.g., the grease **90**). The pressure rotator presses against the heater via the rotator to form a slide nip (e.g., the slide nip **N1**) between the heater and the inner face of the rotator. The pressure rotator rotates and conveys a recording medium (e.g., a sheet P) in a recording medium conveyance direction (e.g., the sheet conveyance direction **DP**). The lubricant holder is disposed outboard from the slide nip in the recording medium conveyance direction or the rotation direction of the rotator and disposed between the rotator and the heater. The lubricant holder holds the lubricant. The resistive heat generator is mounted on an opposite face (e.g., the back face **30b**) of the base, that is opposite to the slide face of the base, that defines the slide nip. The lubricant is applied in an application amount A. The inner face of the rotator has a roughness having a height H. The rotator has a length **X1** in a longitudinal direction of the rotator. The rotator has a circumference **R**. The lubricant has a specific density **G**. The lubricant holder has a volume **V**. The rotator, the lubricant holder, and the lubricant satisfy a formula of $H \times X1 \times R \times G \leq A \leq V \times G$.

(185) A description is provided of a second aspect of the embodiments of the present disclosure.

(186) In the heating device of the first aspect, the lubricant includes fluorine grease.

(187) A description is provided of a third aspect of the embodiments of the present disclosure.

(188) The heating device of the first aspect or the second aspect further includes a thermal conductor (e.g., the thermal conductors **28**, **28A**, **28B**, and **28C**) that contacts the opposite face of the base of the heater.

(189) A description is provided of a fourth aspect of the embodiments of the present disclosure.

(190) In the heating device of any one of the first aspect to the third aspect, the base is made of ceramics having enhanced smoothness.

(191) A description is provided of a fifth aspect of the embodiments of the present disclosure.

(192) In the heating device of any one of the first aspect to the fourth aspect, the slide face of the

base of the heater, over which the rotator slides, has a surface roughness not greater than 0.2 μm .
 (193) A description is provided of a sixth aspect of the embodiments of the present disclosure.
 (194) In the heating device according to any one of the first aspect to the fifth aspect, the inner face of the rotator has a surface roughness not greater than 0.5 μm .
 (195) A description is provided of a seventh aspect of the embodiments of the present disclosure.
 (196) The heating device of any one of the first aspect to the sixth aspect includes a fixing device that heats and fixes an image on the recording medium.
 (197) A description is provided of an eighth aspect of the embodiments of the present disclosure.
 (198) An image forming apparatus (e.g., the image forming apparatuses **100** and **100A**) includes the fixing device of the seventh aspect.
 (199) Accordingly, the rotator slides over the heater properly.
 (200) According to the embodiments described above, the fixing belt **20** serves as a fixing rotator. Alternatively, a fixing film, a fixing sleeve, or the like may be used as a fixing rotator. Further, the pressure roller **21** serves as a pressure rotator. Alternatively, a pressure belt or the like may be used as a pressure rotator.
 (201) The above-described embodiments are illustrative and do not limit the present invention. Thus, numerous additional modifications and variations are possible in light of the above teachings. For example, elements and/or features of different illustrative embodiments may be combined with each other and/or substituted for each other within the scope of the present invention.

Claims

1. A heating device comprising: a first rotator configured to rotate in a rotation direction; a heater opposite an inner face of the first rotator, the heater including: a planar resistive heat generator configured to heat the first rotator, at least one electrode, at least one feeder configured to electrically connect the at least one electrode with the planar resistive heat generator, an insulating layer, and a base having a slide face over which the inner face of the first rotator slides and an opposite face being opposite to the slide face, the planar resistive heat generator, the at least one electrode, the at least one feeder, and the insulating layer mounted on the opposite face, one of the slide face of the base of the heater and the inner face of the first rotator being applied with a lubricant; a second rotator opposite the heater via the first rotator to form an outer face nip between the first rotator and the second rotator and a slide nip between the heater and the inner face of the first rotator; a heater holder configured to hold the heater, the heater holder including a protrusion protruding beyond the slide face of the base of the heater toward the second rotator, the protrusion causing the first rotator to protrude towards the second rotator such that an outer face of the first rotator is in contact with a curved portion of an outer face of the second rotator away from the base; and a lubricant holder outboard from the slide nip in the rotation direction of the first rotator and between the first rotator and the heater, the lubricant holder included in a space between the slide face of the base and the inner face of the first rotator, the lubricant holder configured to hold the lubricant, the first rotator, the lubricant holder, and the lubricant configured to satisfy a formula of $H \times X1 \times R \times G \leq A \leq V \times G$, and where H is a height of a roughness of the inner face of the first rotator, X1 is a length of the first rotator in a longitudinal direction of the first rotator, R is a circumference of the first rotator, G is a specific density of the lubricant, A is an application amount of the lubricant on the one of the slide face of the base of the heater and the inner face of the first rotator, and V is a volume of the lubricant holder.
2. The heating device according to claim 1, wherein the heater holder includes a recess, the heater holder configured to hold the heater in the recess.
3. The heating device according to claim 1, wherein the lubricant includes fluorine grease.
4. The heating device according to claim 3, wherein the lubricant holder includes a grease reservoir configured to hold the fluorine grease.

5. The heating device according to claim 1, further comprising: a thermal conductor configured to contact the opposite face of the base of the heater.
6. The heating device according to claim 1, wherein the base of the heater is made of ceramics having enhanced smoothness.
7. The heating device according to claim 1, wherein the slide face of the base of the heater has a surface roughness not greater than $0.2\text{ }\mu\text{m}$.
8. The heating device according to claim 1, wherein the inner face of the first rotator has a surface roughness not greater than $0.5\text{ }\mu\text{m}$.
9. The heating device according to claim 1, wherein the first rotator includes a belt.
10. The heating device according to claim 1, wherein the second rotator includes a roller.
11. The heating device of claim 1, wherein the lubricant holder is further configured to store the lubricant at a portion of the lubricant holder which abuts the slide nip.
12. A fixing device comprising: a fixing belt configured to rotate; a heater opposite an inner face of the fixing belt, the heater including: a planar resistive heat generator configured to heat the fixing belt, at least one electrode, at least one feeder configured to electrically connect the at least one electrode with the planar resistive heat generator, an insulating layer, and a base having a slide face over which the inner face of the fixing belt slides and an opposite face being opposite to the slide face, the planar resistive heat generator, the at least one electrode, the at least one feeder, and the insulating layer mounted on the opposite face, one of the slide face of the base of the heater and the inner face of the fixing belt being applied with a lubricant; a pressure rotator opposite the heater via the fixing belt to form an outer face nip between the fixing belt and the pressure rotator and a slide nip between the heater and the inner face of the fixing belt, the pressure rotator configured to rotate and convey a recording medium in a recording medium conveyance direction; a heater holder configured to hold the heater, the heater holder including a protrusion protruding beyond the slide face of the base of the heater toward the pressure rotator, the protrusion causing the fixing belt to protrude towards the pressure rotator such that an outer face of the fixing belt is in contact with a curved portion of an outer face of the pressure rotator away from the base; and a lubricant holder outboard from the slide nip in the recording medium conveyance direction and between the fixing belt and the heater, the lubricant holder included in a space between the slide face of the base and the inner face of the fixing belt, the lubricant holder configured to hold the lubricant, the fixing belt, the lubricant holder, and the lubricant configured to satisfy a formula of $H \times X1 \times R \times G \leq A \leq V \times G$, and where H is a height of a roughness of the inner face of the fixing belt, X1 is a length of the fixing belt in a longitudinal direction of the fixing belt, R is a circumference of the fixing belt, G is a specific density of the lubricant, A is an application amount of the lubricant on the one of the slide face of the base of the heater and the inner face of the fixing belt, and V is a volume of the lubricant holder.
13. An image forming apparatus comprising: an image bearer configured to bear an image; and a fixing device configured to fix the image on a recording medium, the fixing device including, a fixing belt configured to rotate; a heater opposite an inner face of the fixing belt, the heater including: a planar resistive heat generator configured to heat the fixing belt, at least one electrode, at least one feeder configured to electrically connect the at least one electrode with the planar resistive heat generator, an insulating layer, and a base having a slide face over which the inner face of the fixing belt slides and an opposite face being opposite to the slide face, the planar resistive heat generator, the at least one electrode, the at least one feeder, and the insulating layer mounted on the opposite face, one of the slide face of the base of the heater and the inner face of the fixing belt being applied with a lubricant; a pressure rotator opposite the heater via the fixing belt to form an outer face nip between the fixing belt and the pressure rotator and a slide nip between the heater and the inner face of the fixing belt, the pressure rotator configured to rotate and convey the recording medium in a recording medium conveyance direction; a heater holder configured to hold the heater, the heater holder including a protrusion protruding beyond the slide face of the base of

the heater toward the pressure rotator, the protrusion causing the fixing belt to protrude towards the pressure rotator such that an outer face of the fixing belt is in contact with a curved portion of an outer face of the pressure rotator away from the base; and a lubricant holder outboard from the slide nip in the recording medium conveyance direction and between the fixing belt and the heater, the lubricant holder included in a space between the slide face of the base and the inner face of the fixing belt, the lubricant holder configured to hold the lubricant, the fixing belt, the lubricant holder, and the lubricant configured to satisfy a formula of $H \times X1 \times R \times G \leq A \leq V \times G$, and where H is a height of a roughness of the inner face of the fixing belt, X1 is a length of the fixing belt in a longitudinal direction of the fixing belt, R is a circumference of the fixing belt, G is a specific density of the lubricant, A is an application amount of the lubricant on the one of the slide face of the base of the heater and the inner face of the fixing belt, and V is a volume of the lubricant holder.

14. The image forming apparatus according to claim 13, wherein the heater holder includes a recess, the heater holder configured to hold the heater in the recess.

15. The image forming apparatus according to claim 13, wherein the lubricant includes fluorine grease.

16. The image forming apparatus according to claim 15, wherein the lubricant holder includes a grease reservoir configured to hold the fluorine grease.

17. The image forming apparatus according to claim 13, further comprising: a thermal conductor configured to contact the opposite face of the base of the heater.

18. The image forming apparatus according to claim 13, wherein the base of the heater is made of ceramics having enhanced smoothness.

19. The image forming apparatus according to claim 13, wherein the slide face of the base of the heater has a surface roughness not greater than 0.2 μm .

20. The image forming apparatus of claim 13, wherein the lubricant holder is further configured to store the lubricant at a portion of the lubricant holder which abuts the slide nip.
