

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12411763
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Porzio; Luca et al.

Data defragmentation control

Abstract

Methods, systems, and devices for data defragmentation control are described. A memory system may include one or more regions of logical addresses and a plurality of memory cells arranged according to a plurality of physical addresses. In some instances, data may be stored to one or more discontinuous physical addresses and it may be desirable rearrange the data to be within continuous physical addresses (e.g., it may be desirable to defragment the data). Accordingly, the data stored to the one or more discontinuous physical addresses may be arranged (e.g., rearranged) to be within continuous physical addresses based at least in part on a value stored to one or more registers of the memory system.

Inventors:	Porzio; Luca (Casalnuovo, IT), Bi; Yanhua (Shanghai, CN)
Applicant:	Micron Technology, Inc. (Boise, ID)
Family ID:	88698946
Assignee:	Micron Technology, Inc. (Boise, ID)
Appl. No.:	18/197469
Filed:	May 15, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230367710 A1	Nov. 16, 2023

Related U.S. Application Data

us-provisional-application US 63342431 20220516

Publication Classification

Int. Cl.: G06F12/06 (20060101)

U.S. Cl.:

CPC G06F12/0607 (20130101);

Field of Classification Search

CPC: G06F (12/06); G06F (12/0607); G06F (12/0615); G06F (12/0638)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8904137	12/2013	Zhang	711/165	G06F 3/067
2015/0347296	12/2014	Kotte	711/103	G06F 3/0679
2018/0217926	12/2017	Ogawa	N/A	G06F 3/0679
2022/0197562	12/2021	Wada	N/A	G06F 12/10
2023/0195617	12/2022	Cheng	711/154	G06F 12/0246
2023/0236966	12/2022	Yarimi	711/170	G06F 3/0638

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
WO-2014049678	12/2013	WO	G06F 12/0246
WO-2017023458	12/2016	WO	H04L 47/34

Primary Examiner: Bataille; Pierre Michel

Attorney, Agent or Firm: Holland & Hart LLP

Background/Summary

CROSS REFERENCE (1) The present application for patent claims priority to U.S. Patent Application No. 63/342,431 by Porzio et al., entitled “DATA DEFRAGMENTATION CONTROL,” filed May 16, 2022, which is assigned to the assignee hereof, and which is expressly incorporated by reference herein.

FIELD OF TECHNOLOGY

(1) The following relates to one or more systems for memory, including data defragmentation control.

BACKGROUND

(2) Memory devices are widely used to store information in various electronic devices such as computers, user devices, wireless communication devices, cameras, digital displays, and the like. Information is stored by programming memory cells within a memory device to various states. For example, binary memory cells may be programmed to one of two supported states, often corresponding to a logic 1 or a logic 0. In some examples, a single memory cell may support more than two possible states, any one of which may be stored by the memory cell. To access information stored by a memory device, a component may read, or sense, the state of one or more memory cells within the memory device. To store information, a component may write, or

program, one or more memory cells within the memory device to corresponding states.

(3) Various types of memory devices exist, including magnetic hard disks, random access memory (RAM), read-only memory (ROM), dynamic RAM (DRAM), synchronous dynamic RAM (SDRAM), static RAM (SRAM), ferroelectric RAM (FeRAM), magnetic RAM (MRAM), resistive RAM (RRAM), flash memory, phase change memory (PCM), 3-dimensional cross-point memory (3D cross point), not-or (NOR) and not-and (NAND) memory devices, and others. Memory devices may be volatile or non-volatile. Volatile memory cells (e.g., DRAM cells) may lose their programmed states over time unless they are periodically refreshed by an external power source. Non-volatile memory cells (e.g., NAND memory cells) may maintain their programmed states for extended periods of time even in the absence of an external power source.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 illustrates an example of a system that supports data defragmentation control in accordance with examples as disclosed herein.
- (2) FIG. 2 illustrates an example of a system that supports data defragmentation control in accordance with examples as disclosed herein.
- (3) FIG. 3 illustrates an example of a block diagram that supports data defragmentation control in accordance with examples as disclosed herein.
- (4) FIG. 4 illustrates an example of a process flow diagram that supports data defragmentation control in accordance with examples as disclosed herein.
- (5) FIG. 5 shows a block diagram of a memory system that supports data defragmentation control in accordance with examples as disclosed herein.
- (6) FIG. 6 shows a flowchart illustrating a method or methods that support data defragmentation control in accordance with examples as disclosed herein.

DETAILED DESCRIPTION

- (7) Some memory systems use logical-to-physical (L2P) tables to map logical block addresses (LBAs) with physical addresses. The LBAs may be used by the host system to address stored data at a memory system, and the physical address may be used by the memory system to identify the corresponding physical location for the stored data. In some cases, data may be associated with a continuous LBA that is associated with discontinuous corresponding physical addresses of the memory system. For example, the memory may support a first granularity for writes to addresses that have been erased, but a second granularity (e.g., a block of physical addresses) for erase operations. Because data is constantly written and overwritten to logical addresses of the memory device-resulting in the overwritten data being written to a new physical address-data may ultimately become spread out over several physical addresses (e.g., data may become fragmented).
- (8) Memory devices may be configured to rearrange the discontinuous data by reading it from the discontinuous physical addresses and writing it to one or more continuous physical addresses (e.g., the memory system may defragment the data) to improve the overall performance of the associated device. However, because defragmentation mainly affects the associated device's performance, it may be undesirable to perform defragmentation on some devices. For example, it may be less desirable to perform defragmentation on a memory device reaching its end of life (EOL) or a memory device included in a mobile system that is low on battery to preserve endurance or power. Accordingly, a memory system configured to provide control over when a defragmentation operation occurs, based on one or more characteristics of the system, may be desirable.
- (9) A memory system configured to provide control over when a defragmentation operation occurs is described herein. In some examples, the memory system may include one or more registers (e.g., mode registers, status registers, or other types of registers) for managing defragmentation

operations. The memory device may include a first register configured to store one or more values that indicate whether or not to initiate a defragmentation operation (or whether a defragmentation operation is ongoing). The memory device may also include a second register configured to store one or more values indicating whether to perform a defragmentation operation based on the endurance (or another characteristic) of the memory system, and a third register configured to store one or more values indicating the amount of defragmentation to conduct (e.g., if a defragmentation operation is performed). Utilizing the registers described herein to perform (or to refrain from performing) a defragmentation operation may prolong the life or power of the associated memory system, among other benefits, which may be desirable.

(10) Features of the disclosure are initially described in the context of systems, devices, and circuits with reference to FIGS. 1 and 2. Features of the disclosure are described in the context of a block diagram and a process flow diagram with reference to FIGS. 3 and 4. These and other features of the disclosure are further illustrated by and described in the context of an apparatus diagram and flowchart that relate to data defragmentation control with reference to FIGS. 5 and 6.

(11) FIG. 1 illustrates an example of a system **100** that supports data defragmentation control in accordance with examples as disclosed herein. The system **100** includes a host system **105** coupled with a memory system **110**.

(12) A memory system **110** may be or include any device or collection of devices, where the device or collection of devices includes at least one memory array. For example, a memory system **110** may be or include a Universal Flash Storage (UFS) device, an embedded Multi-Media Controller (eMMC) device, a flash device, a universal serial bus (USB) flash device, a secure digital (SD) card, a solid-state drive (SSD), a hard disk drive (HDD), a dual in-line memory module (DIMM), a small outline DIMM (SO-DIMM), or a non-volatile DIMM (NVDIMM), among other possibilities.

(13) The system **100** may be included in a computing device such as a desktop computer, a laptop computer, a network server, a mobile device, a vehicle (e.g., airplane, drone, train, automobile, or other conveyance), an Internet of Things (IoT) enabled device, an embedded computer (e.g., one included in a vehicle, industrial equipment, or a networked commercial device), or any other computing device that includes memory and a processing device.

(14) The system **100** may include a host system **105**, which may be coupled with the memory system **110**. In some examples, this coupling may include an interface with a host system controller **106**, which may be an example of a controller or control component configured to cause the host system **105** to perform various operations in accordance with examples as described herein. The host system **105** may include one or more devices and, in some cases, may include a processor chipset and a software stack executed by the processor chipset. For example, the host system **105** may include an application configured for communicating with the memory system **110** or a device therein. The processor chipset may include one or more cores, one or more caches (e.g., memory local to or included in the host system **105**), a memory controller (e.g., NVDIMM controller), and a storage protocol controller (e.g., peripheral component interconnect express (PCIe) controller, serial advanced technology attachment (SATA) controller). The host system **105** may use the memory system **110**, for example, to write data to the memory system **110** and read data from the memory system **110**. Although one memory system **110** is shown in FIG. 1, the host system **105** may be coupled with any quantity of memory systems **110**.

(15) The host system **105** may be coupled with the memory system **110** via at least one physical host interface. The host system **105** and the memory system **110** may, in some cases, be configured to communicate via a physical host interface using an associated protocol (e.g., to exchange or otherwise communicate control, address, data, and other signals between the memory system **110** and the host system **105**). Examples of a physical host interface may include, but are not limited to, a SATA interface, a UFS interface, an eMMC interface, a PCIe interface, a USB interface, a Fiber Channel interface, a Small Computer System Interface (SCSI), a Serial Attached SCSI (SAS), a Double Data Rate (DDR) interface, a DIMM interface (e.g., DIMM socket interface that supports

DDR), an Open NAND Flash Interface (ONFI), and a Low Power Double Data Rate (LPDDR) interface. In some examples, one or more such interfaces may be included in or otherwise supported between a host system controller **106** of the host system **105** and a memory system controller **115** of the memory system **110**. In some examples, the host system **105** may be coupled with the memory system **110** (e.g., the host system controller **106** may be coupled with the memory system controller **115**) via a respective physical host interface for each memory device **130** included in the memory system **110**, or via a respective physical host interface for each type of memory device **130** included in the memory system **110**.

(16) The memory system **110** may include a memory system controller **115** and one or more memory devices **130**. A memory device **130** may include one or more memory arrays of any type of memory cells (e.g., non-volatile memory cells, volatile memory cells, or any combination thereof). Although two memory devices **130-a** and **130-b** are shown in the example of FIG. **1**, the memory system **110** may include any quantity of memory devices **130**. Further, if the memory system **110** includes more than one memory device **130**, different memory devices **130** within the memory system **110** may include the same or different types of memory cells.

(17) The memory system controller **115** may be coupled with and communicate with the host system **105** (e.g., via the physical host interface) and may be an example of a controller or control component configured to cause the memory system **110** to perform various operations in accordance with examples as described herein. The memory system controller **115** may also be coupled with and communicate with memory devices **130** to perform operations such as reading data, writing data, erasing data, or refreshing data at a memory device **130**—among other such operations—which may generically be referred to as access operations. In some cases, the memory system controller **115** may receive commands from the host system **105** and communicate with one or more memory devices **130** to execute such commands (e.g., at memory arrays within the one or more memory devices **130**). For example, the memory system controller **115** may receive commands or operations from the host system **105** and may convert the commands or operations into instructions or appropriate commands to achieve the desired access of the memory devices **130**. In some cases, the memory system controller **115** may exchange data with the host system **105** and with one or more memory devices **130** (e.g., in response to or otherwise in association with commands from the host system **105**). For example, the memory system controller **115** may convert responses (e.g., data packets or other signals) associated with the memory devices **130** into corresponding signals for the host system **105**.

(18) The memory system controller **115** may be configured for other operations associated with the memory devices **130**. For example, the memory system controller **115** may execute or manage operations such as wear-leveling operations, garbage collection operations, error control operations such as error-detecting operations or error-correcting operations, encryption operations, caching operations, media management operations, background refresh, health monitoring, and address translations between logical addresses (e.g., logical block addresses (LBAs)) associated with commands from the host system **105** and physical addresses (e.g., physical block addresses) associated with memory cells within the memory devices **130**.

(19) The memory system controller **115** may include hardware such as one or more integrated circuits or discrete components, a buffer memory, or a combination thereof. The hardware may include circuitry with dedicated (e.g., hard-coded) logic to perform the operations ascribed herein to the memory system controller **115**. The memory system controller **115** may be or include a microcontroller, special purpose logic circuitry (e.g., a field programmable gate array (FPGA), an application specific integrated circuit (ASIC), a digital signal processor (DSP)), or any other suitable processor or processing circuitry.

(20) The memory system controller **115** may also include a local memory **120**. In some cases, the local memory **120** may include read-only memory (ROM) or other memory that may store operating code (e.g., executable instructions) executable by the memory system controller **115** to

perform functions ascribed herein to the memory system controller **115**. In some cases, the local memory **120** may additionally or alternatively include static random access memory (SRAM) or other memory that may be used by the memory system controller **115** for internal storage or calculations, for example, related to the functions ascribed herein to the memory system controller **115**.

(21) A memory device **130** may include one or more arrays of non-volatile memory cells. For example, a memory device **130** may include NAND (e.g., NAND flash) memory, ROM, phase change memory (PCM), self-selecting memory, other chalcogenide-based memories, ferroelectric random access memory (RAM) (FeRAM), magneto RAM (MRAM), NOR (e.g., NOR flash) memory, Spin Transfer Torque (STT)-MRAM, conductive bridging RAM (CBRAM), resistive random access memory (RRAM), oxide based RRAM (OxRAM), electrically erasable programmable ROM (EEPROM), or any combination thereof. Additionally or alternatively, a memory device **130** may include one or more arrays of volatile memory cells. For example, a memory device **130** may include RAM memory cells, such as dynamic RAM (DRAM) memory cells and synchronous DRAM (SDRAM) memory cells.

(22) In some examples, a memory device **130** may include (e.g., on a same die or within a same package) a local controller **135**, which may execute operations on one or more memory cells of the respective memory device **130**. A local controller **135** may operate in conjunction with a memory system controller **115** or may perform one or more functions ascribed herein to the memory system controller **115**. For example, as illustrated in FIG. 1, a memory device **130-a** may include a local controller **135-a** and a memory device **130-b** may include a local controller **135-b**.

(23) In some cases, a memory device **130** may be or include a NAND device (e.g., NAND flash device). A memory device **130** may be or include a memory die **160**. For example, in some cases, a memory device **130** may be a package that includes one or more dies **160**. A die **160** may, in some examples, be a piece of electronics-grade semiconductor cut from a wafer (e.g., a silicon die cut from a silicon wafer). Each die **160** may include one or more planes **165**, and each plane **165** may include a respective set of blocks **170**, where each block **170** may include a respective set of pages **175**, and each page **175** may include a set of memory cells.

(24) In some cases, a NAND memory device **130** may include memory cells configured to each store one bit of information, which may be referred to as single level cells (SLCs). Additionally or alternatively, a NAND memory device **130** may include memory cells configured to each store multiple bits of information, which may be referred to as multi-level cells (MLCs) if configured to each store two bits of information, as tri-level cells (TLCs) if configured to each store three bits of information, as quad-level cells (QLCs) if configured to each store four bits of information, or more generically as multiple-level memory cells. Multiple-level memory cells may provide greater density of storage relative to SLC memory cells but may, in some cases, involve narrower read or write margins or greater complexities for supporting circuitry.

(25) In some cases, planes **165** may refer to groups of blocks **170**, and in some cases, concurrent operations may take place within different planes **165**. For example, concurrent operations may be performed on memory cells within different blocks **170** so long as the different blocks **170** are in different planes **165**. In some cases, an individual block **170** may be referred to as a physical block, and a virtual block **180** may refer to a group of blocks **170** within which concurrent operations may occur. For example, concurrent operations may be performed on blocks **170-a**, **170-b**, **170-c**, and **170-d** that are within planes **165-a**, **165-b**, **165-c**, and **165-d**, respectively, and blocks **170-a**, **170-b**, **170-c**, and **170-d** may be collectively referred to as a virtual block **180**. In some cases, a virtual block may include blocks **170** from different memory devices **130** (e.g., including blocks in one or more planes of memory device **130-a** and memory device **130-b**). In some cases, the blocks **170** within a virtual block may have the same block address within their respective planes **165** (e.g., block **170-a** may be “block 0” of plane **165-a**, block **170-b** may be “block 0” of plane **165-b**, and so on). In some cases, performing concurrent operations in different planes **165** may be subject to one

or more restrictions, such as concurrent operations being performed on memory cells within different pages **175** that have the same page address within their respective planes **165** (e.g., related to command decoding, page address decoding circuitry, or other circuitry being shared across planes **165**).

(26) In some cases, a block **170** may include memory cells organized into rows (pages **175**) and columns (e.g., strings, not shown). For example, memory cells in a same page **175** may share (e.g., be coupled with) a common word line, and memory cells in a same string may share (e.g., be coupled with) a common digit line (which may alternatively be referred to as a bit line).

(27) For some NAND architectures, memory cells may be read and programmed (e.g., written) at a first level of granularity (e.g., at the page level of granularity) but may be erased at a second level of granularity (e.g., at the block level of granularity). That is, a page **175** may be the smallest unit of memory (e.g., set of memory cells) that may be independently programmed or read (e.g., programmed or read concurrently as part of a single program or read operation), and a block **170** may be the smallest unit of memory (e.g., set of memory cells) that may be independently erased (e.g., erased concurrently as part of a single erase operation). Further, in some cases, NAND memory cells may be erased before they can be re-written with new data. Thus, for example, a used page **175** may, in some cases, not be updated until the entire block **170** that includes the page **175** has been erased.

(28) In some cases, L2P mapping tables may be maintained and data may be marked as valid or invalid at the page level of granularity, and a page **175** may contain valid data, invalid data, or no data. Invalid data may be data that is outdated due to a more recent or updated version of the data being stored in a different page **175** of the memory device **130**. Invalid data may have been previously programmed to the invalid page **175** but may no longer be associated with a valid logical address, such as a logical address referenced by the host system **105**. Valid data may be the most recent version of such data being stored on the memory device **130**. A page **175** that includes no data may be a page **175** that has never been written to or that has been erased.

(29) In some cases, a memory system controller **115** or a local controller **135** may perform operations (e.g., as part of one or more media management algorithms) for a memory device **130**, such as wear leveling, background refresh, garbage collection, scrub, block scans, health monitoring, or others, or any combination thereof. For example, within a memory device **130**, a block **170** may have some pages **175** containing valid data and some pages **175** containing invalid data. To avoid waiting for all of the pages **175** in the block **170** to have invalid data in order to erase and reuse the block **170**, an algorithm referred to as “garbage collection” may be invoked to allow the block **170** to be erased and released as a free block for subsequent write operations. Garbage collection may refer to a set of media management operations that include, for example, selecting a block **170** that contains valid and invalid data, selecting pages **175** in the block that contain valid data, copying the valid data from the selected pages **175** to new locations (e.g., free pages **175** in another block **170**), marking the data in the previously selected pages **175** as invalid, and erasing the selected block **170**. As a result, the quantity of blocks **170** that have been erased may be increased such that more blocks **170** are available to store subsequent data (e.g., data subsequently received from the host system **105**).

(30) The system **100** may include any quantity of non-transitory computer readable media that support data defragmentation control. For example, the host system **105**, the memory system controller **115**, or a memory device **130** (e.g., a local controller **135**) may include or otherwise may access one or more non-transitory computer readable media storing instructions (e.g., firmware) for performing the functions ascribed herein to the host system **105**, memory system controller **115**, or memory device **130**. For example, such instructions, if executed by the host system **105** (e.g., by the host system controller **106**), by the memory system controller **115**, or by a memory device **130** (e.g., by a local controller **135**), may cause the host system **105**, memory system controller **115**, or memory device **130** to perform one or more associated functions as described herein.

- (31) In some cases, a memory system **110** may utilize a memory system controller **115** to provide a managed memory system that may include, for example, one or more memory arrays and related circuitry combined with a local (e.g., on-die or in-package) controller (e.g., local controller **135**). An example of a managed memory system is a managed NAND (MNAND) system.
- (32) As described herein, the memory device **130-a** may include one or more logical regions (e.g., regions associated with LBAs) and a plurality of memory cells arranged according to a plurality of physical addresses. In some instances, data associated with a single command or operation (e.g., data associated with a continuous LBA) may be stored to one or more discontinuous physical addresses. Accordingly, the host system **105** may initiate a defragmentation operation to rearrange the data to be within a continuous physical address. The host system **105** may initiate the defragmentation operation based on a value stored to one or more registers (not shown) of the memory system **110** that are managed and/or maintained by the memory system controller **115**.
- (33) For example, the memory system **110** may include a first register (not shown), a second register (not shown), and a third register (not shown). The registers may be mode registers (or status registers or other types of registers) that are accessible by the memory system controller **115** (e.g., the registers may be write-only registers, read-only registers, or read/write registers). In some examples, the first register may store a value indicating whether a defragmentation operation is to be performed (or whether a defragmentation operation is ongoing). The second register may store a value indicating whether to perform a defragmentation operation based on the endurance (or another characteristic) of the memory device **130-a**, and a third register may be configured to store one or more values indicating the amount of defragmentation to conduct (e.g., a size or quantity of data to rearrange into continuous physical addresses, if a defragmentation operation is to occur).
- (34) The memory system controller **115** may write the values to the respective registers (or update the values stored to the respective registers) based on one or more characteristics of the memory system **110**. For example, the memory system controller **115** may write a value to the third register based on one or more heuristics, such as a quantity (or a size) of frequently-accessed LBAs of the memory device **130-a**. In other examples, the memory system controller **115** may write a value to one or more registers based on a command received from the host system **105**. Moreover, the memory system controller **115** may read one or more values from the registers and may transmit the values to the host system **105**, which may use the values to determine whether to initiate a defragmentation operation. By utilizing the registers described herein to perform (or to refrain from performing) a defragmentation operation, the life or power of the memory system **110** may be prolonged, among other benefits.
- (35) FIG. 2 illustrates an example of a system **200** that supports data defragmentation control in accordance with examples as disclosed herein. The system **200** may be an example of a system **100** as described with reference to FIG. 1 or aspects thereof. The system **200** may include a memory system **210** configured to store data received from the host system **205** and to send data to the host system **205**, if requested by the host system **205** using access commands (e.g., read commands or write commands). The system **200** may implement aspects of the system **100** as described with reference to FIG. 1. For example, the memory system **210** and the host system **205** may be examples of the memory system **110** and the host system **105**, respectively.
- (36) The memory system **210** may include memory devices **240** to store data transferred between the memory system **210** and the host system **205**, e.g., in response to receiving access commands from the host system **205**, as described herein. The memory devices **240** may include one or more memory devices as described with reference to FIG. 1. For example, the memory devices **240** may include NAND memory, PCM, self-selecting memory, 3D cross point, other chalcogenide-based memories, FERAM, MRAM, NOR (e.g., NOR flash) memory, STT-MRAM, CBRAM, RRAM, or OxRAM.
- (37) The memory system **210** may include a storage controller **230** for controlling the passing of data directly to and from the memory devices **240**, e.g., for storing data, retrieving data, and

determining memory locations in which to store data and from which to retrieve data. The storage controller **230** may communicate with memory devices **240** directly or via a bus (not shown) using a protocol specific to each type of memory device **240**. In some cases, a single storage controller **230** may be used to control multiple memory devices **240** of the same or different types. In some cases, the memory system **210** may include multiple storage controllers **230**, e.g., a different storage controller **230** for each type of memory device **240**. In some cases, a storage controller **230** may implement aspects of a local controller **135** as described with reference to FIG. **1**.

(38) The memory system **210** may additionally include an interface **220** for communication with the host system **205** and a buffer **225** for temporary storage of data being transferred between the host system **205** and the memory devices **240**. The interface **220**, buffer **225**, and storage controller **230** may be for translating data between the host system **205** and the memory devices **240**. e.g., as shown by a data path **250**, and may be collectively referred to as data path components.

(39) Using the buffer **225** to temporarily store data during transfers may allow data to be buffered as commands are being processed, thereby reducing latency between commands and allowing arbitrary data sizes associated with commands. This may also allow bursts of commands to be handled, and the buffered data may be stored or transmitted (or both) once a burst has stopped. The buffer **225** may include relatively fast memory (e.g., some types of volatile memory, such as SRAM or DRAM) or hardware accelerators or both to allow fast storage and retrieval of data to and from the buffer **225**. The buffer **225** may include data path switching components for bi-directional data transfer between the buffer **225** and other components.

(40) The temporary storage of data within a buffer **225** may refer to the storage of data in the buffer **225** during the execution of access commands. That is, upon completion of an access command, the associated data may no longer be maintained in the buffer **225** (e.g., may be overwritten with data for additional access commands). In addition, the buffer **225** may be a non-cache buffer. That is, data may not be read directly from the buffer **225** by the host system **205**. For example, read commands may be added to a queue without an operation to match the address to addresses already in the buffer **225** (e.g., without a cache address match or lookup operation).

(41) The memory system **210** may additionally include a memory system controller **215** for executing the commands received from the host system **205** and controlling the data path components in the moving of the data. The memory system controller **215** may be an example of the memory system controller **115** as described with reference to FIG. **1**. A bus **235** may be used to communicate between the system components.

(42) In some cases, one or more queues (e.g., a command queue **260**, a buffer queue **265**, and a storage queue **270**) may be used to control the processing of the access commands and the movement of the corresponding data. This may be beneficial, e.g., if more than one access command from the host system **205** is processed concurrently by the memory system **210**. The command queue **260**, buffer queue **265**, and storage queue **270** are depicted at the interface **220**, memory system controller **215**, and storage controller **230**, respectively, as examples of a possible implementation. However, queues, if used, may be positioned anywhere within the memory system **210**.

(43) Data transferred between the host system **205** and the memory devices **240** may take a different path in the memory system **210** than non-data information (e.g., commands, status information). For example, the system components in the memory system **210** may communicate with each other using a bus **235**, while the data may use the data path **250** through the data path components instead of the bus **235**. The memory system controller **215** may control how and if data is transferred between the host system **205** and the memory devices **240** by communicating with the data path components over the bus **235** (e.g., using a protocol specific to the memory system **210**).

(44) If a host system **205** transmits access commands to the memory system **210**, the commands may be received by the interface **220**, e.g., according to a protocol (e.g., a UFS protocol or an

eMMC protocol). Thus, the interface **220** may be considered a front end of the memory system **210**. Upon receipt of each access command, the interface **220** may communicate the command to the memory system controller **215**, e.g., via the bus **235**. In some cases, each command may be added to a command queue **260** by the interface **220** to communicate the command to the memory system controller **215**.

(45) The memory system controller **215** may determine that an access command has been received based on the communication from the interface **220**. In some cases, the memory system controller **215** may determine the access command has been received by retrieving the command from the command queue **260**. The command may be removed from the command queue **260** after it has been retrieved therefrom, e.g., by the memory system controller **215**. In some cases, the memory system controller **215** may cause the interface **220**, e.g., via the bus **235**, to remove the command from the command queue **260**.

(46) Upon the determination that an access command has been received, the memory system controller **215** may execute the access command. For a read command, this may mean obtaining data from the memory devices **240** and transmitting the data to the host system **205**. For a write command, this may mean receiving data from the host system **205** and moving the data to the memory devices **240**.

(47) In either case, the memory system controller **215** may use the buffer **225** for, among other things, temporary storage of the data being received from or sent to the host system **205**. The buffer **225** may be considered a middle end of the memory system **210**. In some cases, buffer address management (e.g., pointers to address locations in the buffer **225**) may be performed by hardware (e.g., dedicated circuits) in the interface **220**, buffer **225**, or storage controller **230**.

(48) To process a write command received from the host system **205**, the memory system controller **215** may first determine if the buffer **225** has sufficient available space to store the data associated with the command. For example, the memory system controller **215** may determine, e.g., via firmware (e.g., controller firmware), an amount of space within the buffer **225** that may be available to store data associated with the write command.

(49) In some cases, a buffer queue **265** may be used to control a flow of commands associated with data stored in the buffer **225**, including write commands. The buffer queue **265** may include the access commands associated with data currently stored in the buffer **225**. In some cases, the commands in the command queue **260** may be moved to the buffer queue **265** by the memory system controller **215** and may remain in the buffer queue **265** while the associated data is stored in the buffer **225**. In some cases, each command in the buffer queue **265** may be associated with an address at the buffer **225**. That is, pointers may be maintained that indicate where in the buffer **225** the data associated with each command is stored. Using the buffer queue **265**, multiple access commands may be received sequentially from the host system **205** and at least portions of the access commands may be processed concurrently.

(50) If the buffer **225** has sufficient space to store the write data, the memory system controller **215** may cause the interface **220** to transmit an indication of availability to the host system **205** (e.g., a “ready to transfer” indication), e.g., according to a protocol (e.g., a UFS protocol or an eMMC protocol). As the interface **220** subsequently receives from the host system **205** the data associated with the write command, the interface **220** may transfer the data to the buffer **225** for temporary storage using the data path **250**. In some cases, the interface **220** may obtain from the buffer **225** or buffer queue **265** the location within the buffer **225** to store the data. The interface **220** may indicate to the memory system controller **215**, e.g., via the bus **235**, if the data transfer to the buffer **225** has been completed.

(51) Once the write data has been stored in the buffer **225** by the interface **220**, the data may be transferred out of the buffer **225** and stored in a memory device **240**. This may be done using the storage controller **230**. For example, the memory system controller **215** may cause the storage controller **230** to retrieve the data out of the buffer **225** using the data path **250** and transfer the data

to a memory device **240**. The storage controller **230** may be considered a back end of the memory system **210**. The storage controller **230** may indicate to the memory system controller **215**, e.g., via the bus **235**, that the data transfer to a memory device of the memory devices **240** has been completed.

(52) In some cases, a storage queue **270** may be used to aid with the transfer of write data. For example, the memory system controller **215** may push (e.g., via the bus **235**) write commands from the buffer queue **265** to the storage queue **270** for processing. The storage queue **270** may include entries for each access command. In some examples, the storage queue **270** may additionally include a buffer pointer (e.g., an address) that may indicate where in the buffer **225** the data associated with the command is stored and a storage pointer (e.g., an address) that may indicate the location in the memory devices **240** associated with the data. In some cases, the storage controller **230** may obtain from the buffer **225**, buffer queue **265**, or storage queue **270** the location within the buffer **225** from which to obtain the data. The storage controller **230** may manage the locations within the memory devices **240** to store the data (e.g., performing wear-leveling, garbage collection, and the like). The entries may be added to the storage queue **270**, e.g., by the memory system controller **215**. The entries may be removed from the storage queue **270**, e.g., by the storage controller **230** or memory system controller **215** upon completion of the transfer of the data.

(53) To process a read command received from the host system **205**, the memory system controller **215** may again first determine if the buffer **225** has sufficient available space to store the data associated with the command. For example, the memory system controller **215** may determine, e.g., via firmware (e.g., controller firmware), an amount of space within the buffer **225** that may be available to store data associated with the read command.

(54) In some cases, the buffer queue **265** may be used to aid with buffer storage of data associated with read commands in a similar manner as discussed above with respect to write commands. For example, if the buffer **225** has sufficient space to store the read data, the memory system controller **215** may cause the storage controller **230** to retrieve the data associated with the read command from a memory device **240** and store the data in the buffer **225** for temporary storage using the data path **250**. The storage controller **230** may indicate to the memory system controller **215**, e.g., via the bus **235**, when the data transfer to the buffer **225** has been completed.

(55) In some cases, the storage queue **270** may be used to aid with the transfer of read data. For example, the memory system controller **215** may push the read command to the storage queue **270** for processing. In some cases, the storage controller **230** may obtain from the buffer **225** or storage queue **270** the location within the memory devices **240** from which to retrieve the data. In some cases, the storage controller **230** may obtain from the buffer queue **265** the location within the buffer **225** to store the data. In some cases, the storage controller **230** may obtain from the storage queue **270** the location within the buffer **225** to store the data. In some cases, the memory system controller **215** may move the command processed by the storage queue **270** back to the command queue **260**.

(56) Once the data has been stored in the buffer **225** by the storage controller **230**, the data may be transferred out of the buffer **225** and sent to the host system **205**. For example, the memory system controller **215** may cause the interface **220** to retrieve the data out of the buffer **225** using the data path **250** and transmit the data to the host system **205**, e.g., according to a protocol (e.g., a UFS protocol or an eMMC protocol). For example, the interface **220** may process the command from the command queue **260** and may indicate to the memory system controller **215**, e.g., via the bus **235**, that the data transmission to the host system **205** has been completed.

(57) The memory system controller **215** may execute received commands according to an order (e.g., a first-in, first-out order, according to the order of the command queue **260**). For each command, the memory system controller **215** may cause data corresponding to the command to be moved into and out of the buffer **225**, as discussed above. As the data is moved into and stored within the buffer **225**, the command may remain in the buffer queue **265**. A command may be

removed from the buffer queue **265**, e.g., by the memory system controller **215**, if the processing of the command has been completed (e.g., if data corresponding to the access command has been transferred out of the buffer **225**). If a command is removed from the buffer queue **265**, the address previously storing the data associated with that command may be available to store data associated with a new command.

(58) The memory system controller **215** may additionally be configured for operations associated with the memory devices **240**. For example, the memory system controller **215** may execute or manage operations such as wear-leveling operations, garbage collection operations, error control operations such as error-detecting operations or error-correcting operations, encryption operations, caching operations, media management operations, background refresh, health monitoring, and address translations between logical addresses (e.g., LBAs) associated with commands from the host system **205** and physical addresses (e.g., physical block addresses) associated with memory cells within the memory devices **240**. That is, the host system **205** may issue commands indicating one or more LBAs and the memory system controller **215** may identify one or more physical block addresses indicated by the LBAs. In some cases, one or more contiguous LBAs may correspond to noncontiguous physical block addresses. In some cases, the storage controller **230** may be configured to perform one or more of the above operations in conjunction with or instead of the memory system controller **215**. In some cases, the memory system controller **215** may perform the functions of the storage controller **230** and the storage controller **230** may be omitted.

(59) As described herein, the memory devices **240** may include one or more logical regions (e.g., regions associated with LBAs) and a plurality of memory cells arranged according to a plurality of physical addresses. In some instances, data associated with a single command or a set of commands (e.g., data associated with one or more continuous LBAs) may be stored to one or more discontinuous physical addresses. Accordingly, the host system **205** may initiate a defragmentation operation to rearrange the data to be within a continuous physical address. The host system **205** may initiate the defragmentation operation based on a value stored to one or more registers (not shown) of the memory system **210** that are managed by the memory system controller **215**.

(60) For example, the memory system **210** may include register(s) **245** that may include a first register, a second register, and a third register. The register(s) **245** may be mode registers (or status registers or other types of registers) that are accessible by the memory system controller **215** (e.g., the registers may be read-only registers, write-only registers, or read/write registers) via the bus **235**. In some examples, the first register may store a value indicating whether a defragmentation operation is to be performed (or whether a defragmentation operation is ongoing). The second register may store a value indicating whether to perform a defragmentation operation based on the endurance (or another characteristic) of the memory devices **240**, and a third register may be configured to store one or more values indicating the amount of defragmentation to conduct (e.g., a size or quantity of data to rearrange into continuous physical addresses, if a defragmentation operation is to occur).

(61) The memory system controller **215** may write the values to the respective register(s) **245** (or update the values stored to the respective register(s) **245**) based on one or more characteristics of the memory system **210**. For example, the memory system controller **215** may write a value to the third register based on one or more heuristics, such as a quantity (or a size) of frequently-accessed LBAs of the memory devices **240**. In other examples, the memory system controller **215** may write a value to one or more registers based on a command received from the host system **205**. Moreover, the memory system controller **215** may read one or more values from the registers and may transmit the values to the host system **205**, which may use the values to determine whether to initiate a defragmentation operation. By utilizing the registers described herein to perform (or to refrain from performing) a defragmentation operation, the life or power of the memory system **210** may be prolonged, among other benefits.

(62) FIG. 3 illustrates an example of a block diagram **300** that supports data defragmentation

control in accordance with examples as disclosed herein. The block diagram 300 may include a host system 305 and a memory system 310. The memory system 310 may include a memory system controller 315, an interface 320, a memory device 325, a first register 340, a second register 345, and a third register 350. In some examples, the memory device 325 may include a memory 330 and an L2P table 335. The host system 305, the memory system 310, the memory system controller 315, the memory device 325, the first register 340, the second register 345, and the third register 350 may be respective examples of a host system, a memory system, a memory system controller, a memory device, a first register, a second register, and a third register as described with reference to FIGS. 1 and 2. The first register 340, the second register 345, and the third register 350 may each be configured to store one or more values for performing (or not performing) a defragmentation operation on the memory 330 of the memory device 325. By utilizing the registers to perform (or to refrain from performing) a defragmentation operation, the life or power of the memory system 310 may be prolonged, among other benefits. Although illustrated as a single memory device 325, the memory system 310 may include multiple memory devices 325, in some cases.

(63) The memory system 310 may receive commands from the host system 305, via the interface 320, and write data to the memory 330 of the memory device 325. In some cases, the memory system controller 315 may receive the commands from the host system 305 and may determine physical addresses of the memory 330 that correspond to LBAs addressed by the command. The memory system controller 315 may determine the physical addresses of the memory 330 using the L2P table 335 and may subsequently write data to or read data from the physical addresses of the memory 330 to execute the commands.

(64) In some examples, the memory device 325 may support a first granularity for writes to addresses that have been erased, but a second granularity (e.g., a block of physical addresses) for erase operations. Because data is constantly written and overwritten to logical addresses of the memory device 325—resulting in the overwritten data being written to a new physical address of memory 330—data may ultimately become spread out over several physical addresses (e.g., data may become fragmented). Fragmentation of the data may degrade the overall performance of the memory system 310. As described herein, it may be desirable to defragment the data (e.g., rearrange the data to be within continuous physical addresses that correspond to the continuous LBAs) to improve the performance of the memory system 310. However, instances may occur where it may be less desirable to perform a defragmentation operation, thus the first register 340, the second register 345, and the third register 350 may be utilized to perform (or to refrain from performing) a defragmentation operation based on one or more characteristics of the memory system 310.

(65) The first register 340, which may be an example of a mode register or another type of register, may store one or more values that indicate whether a defragmentation operation is to be performed on the memory 330. For example, the first register 340 may store a first value (e.g., a “1”) that indicates a defragmentation operation will start during the next duration that the memory system 310 is idle. The first register 340 may also store a second value (e.g., a “0”) that indicates a defragmentation operation will not start. That is, a defragmentation operation will not start even if the memory system 310 is idle for a duration. The first register 340 may also store a third value (e.g., a “2”) that indicates a defragmentation operation is presently ongoing.

(66) In some instances, the host system 305 may be configured to write the first and second values to the first register 340. For example, if it is desirable to improve the overall performance of the memory system 310, the host system 305 may transmit signaling to the memory system 310 to write the first value to the first register 340. In other examples (e.g., if it is undesirable to perform a defragmentation operation at a particular time), the host system 305 may transmit signaling to the memory system 310 to write the second value to the first register 340. The second value may be a default value of the first register 340—meaning that, as a default—a defragmentation operation will

not occur unless the host system **305** transmits signaling for the memory system **310** (e.g., for the memory system controller **315**) to write the first value to the first register **340**. Additionally or alternatively, the memory system controller **315** may be configured to write the third value to the first register **340** when a defragmentation operation on the memory **330** is initiated.

(67) The second register **345**, which may be an example of a mode register or another type of register, may store one or more values associated with an endurance of the memory system **310** (e.g., of the memory device **325** of the memory system). For example, the second register **345** may store a value (e.g., a threshold or a threshold value) indicating a maximum quantity of program/erase (P/E) cycles performed on the memory **330** before defragmentation operations are no longer performed. If the quantity of P/E cycles performed on the memory **330** satisfies (e.g., exceeds, or meets or exceeds) the threshold value stored to the second register then a defragmentation operation may not be performed on the memory **330**. In some instances, the default value stored to the second register **345** may be “0” such that a defragmentation operation may not be performed if any P/E cycles have been performed on the memory **330**. The default value may be set at “0” so that defragmentation is an optional feature to be performed. However, the value (e.g., the threshold value) stored to the second register **345** may be configurable, thus defragmentation may be performed on the memory **330** of the memory system **310** if desirable.

(68) Additionally or alternatively, the threshold quantity stored by the second register **345** may be set based on an expected lifecycle (e.g., an expected endurance) of the memory **330**. Moreover, the memory system controller **315** may track the quantity of P/E cycles performed on the memory **330** using a counter or other component of the memory system **310**. Thus, when the host system **305** transmits signaling to the memory system **310** to initiate a defragmentation operation, the memory system controller **315** may compare the quantity of P/E cycles performed on the memory **330** to the threshold before initiating the defragmentation operation. If the quantity of P/E cycles does not satisfy the threshold, then the defragmentation operation may be performed. However, if the quantity of P/E cycles satisfies the threshold, then signaling may be transmitted to the host system **305** and, in some examples, the host system may transmit return signaling to write a second value to the first register **340**. Although the second register **345** is described as storing a threshold value associated with a quantity of P/E cycles, the second register may store a threshold value associated with any metric or characteristic of the memory system **310**.

(69) The third register **350**, which may be an example of a mode register or another type of register, may store one or more values indicating a size or quantity of the memory **330** that needs to be defragmented. For example, the third register **350** may store a value indicating a total quantity of megabits (MBs) of the memory **330** that need to be defragmented. The value stored to the third register **350** may be determined by (and written to the third register **350** by) the memory system controller **315** using one or more algorithms. For example, the memory system controller **315** may determine, using an algorithm, the most-frequently-accessed portions of a logical space of the memory **330**. Based on which portions are most-frequently accessed, the memory system controller **315** may determine a size of the memory **330** needing to undergo a defragmentation operation and may store a value indicative of the size to the third register **350**. Thus, before initiating a defragmentation operation, the host system **305** may read the value from the third register **350** and may initiate a defragmentation operation on a subset of the memory **330** based on a value stored to the third register **350**.

(70) The host system **305** may initiate a defragmentation operation when the memory system **310** is in an idle state when no access operations are performed on the memory device **325**. For example, the memory system **310** may perform one or more background operations (e.g., BKOPS) while in an idle state, and may also defragment data during this duration. In some examples, the background operations performed on the memory system **310** may be manual BKOPS or automatic BKOPS, which may be defined by a standard such as a Joint Electron Device Engineering Council (JEDEC) standard. Moreover, the host system **305** may stop the background operations performed on the

memory **330** at any time without accessing the first register **340**, the second register **345**, or the third register **350**. However, once a defragmentation operation begins, the host system **305** may only be able to stop the operation by writing the second value (e.g., a “1”) to the first register **340**. (71) To perform a defragmentation operation, the memory system controller **315** (or another component of the memory system **310**) may read data from discontinuous physical addresses of the memory **330** and may write (e.g., rewrite, rearrange) the data to be within continuous physical addresses. In some instances, the memory system controller **315** may identify one or more blocks of continuous physical addresses of the memory **330** before reading the data from the discontinuous physical addresses. Additionally or alternatively, after rearranging the data to be within the continuous physical addresses, the memory system controller **315** may update one or more mappings stored to the L2P table **335**. The updated mappings may reflect the association between LBAs and the physical addresses to which the data was written to. By utilizing the registers to perform (or to refrain from performing) a defragmentation operation, the life or power of the memory system **310** may be prolonged, among other benefits.

(72) FIG. **4** illustrates an example of a process flow diagram **400** that supports data defragmentation control in accordance with examples as disclosed herein. The process flow diagram **400** may include a host system **405** and a memory system **410**. The memory system **410** may include a memory controller **415** (e.g., a memory system controller **415**), a first register **420**, a second register **425**, or a third register **430**. The host system **405** and the memory system **410** may be respective examples of the host system and the memory system described with reference to FIG. **3**, thus the memory system **410** may also include an interface and a memory device that includes a memory and a L2P table, among other components. The first register **420**, the second register **425**, and the third register **430** may each be configured to store one or more values for performing (or not performing) a defragmentation operation on a memory (e.g., the memory **330** as described with reference to FIG. **3**) of a memory device (e.g., a memory device **325** as described with reference to FIG. **3**). By utilizing the registers to perform (or to refrain from performing) a defragmentation operation, the life or power of the memory system **410** may be prolonged, among other benefits.

(73) At **432**, initial values may be written to the first register **420**, the second register **425**, or both. In some examples, the initial values may be written to the first register **420** and the second register **425** by the memory controller **415**, whereas in other examples the initial values may be programmed during manufacturing of the memory system **410**. For example, a second value (e.g., a “0”) may be initially written to the first register **420**. As described herein, the second value may indicate that no defragmentation operations are to be performed on the memory device associated with the memory system **410** (e.g., until a different value is programmed to the first register **420**). Additionally or alternatively, a “0” (or a value indicating that a defragmentation operation may not be performed if any P/E cycles have been performed on the associated memory) may be written to the second register **425**. As described herein, a “0” or corresponding value may be the default value such that, if a customer or user of the memory system **410** desires that defragmentation is to be performed on the associated memory, the default value may be overwritten.

(74) At **434**, a threshold value may be written to the second register **425**. For example, the threshold value may be written to the second register **425** by the host device (e.g., via the memory controller **415**). In some examples, the threshold value may be written upon the memory system **410** being installed or booted for a first time. Moreover, the threshold value may be written to the second register **425** due to the second register **425** storing an initial value of “0” (e.g., at **432**) or a value that is otherwise undesirable. For example, the threshold value may be set as a quantity of P/E cycles that is less than an anticipated lifetime quantity of P/E cycles for the associated memory. In other words, the threshold may be set based on the expected life of the associated memory.

(75) At **436**, a plurality of commands may be transmitted from the host system **405**. For example, the commands may include access commands such as write commands, read commands, erase commands, and the like, and may each include a LBA of the memory of the memory system **410**.

At **438**, the commands may be received. For example, the commands may be received by the memory controller **415**. At **440**, the commands may be processed. For example, the commands may be processed by the memory controller **415** such that the memory controller **415** accesses one or more memory cells having physical addresses associated with the LBAs included in the command(s).

(76) As described herein, multiple commands may be transmitted from the host system **405** to the memory system **410** over a duration. The commands may write and overwrite various LBAs. Because overwriting an LBA containing previous data may result in writing the new data to a different physical address (and corresponding update of the L2P table), data associated with a continuous set of LBAs may be broken up into discontinuous corresponding physical addresses. That is, the data may become fragmented, which may degrade the overall performance of the memory system **410**. Thus, it may be desirable to perform one or more defragmentation operations on the memory system **410**.

(77) At **442**, it may be desirable to perform a defragmentation operation on the memory system **410** (e.g., on a memory of the memory system **410**). For example, the host system **405** may determine to perform a defragmentation operation on the memory system **410** based on one or more performance characteristics of the memory system **410**. The performance characteristics may include the memory system **410** having a relatively low latency or bandwidth or having a relatively high battery supply (or being connected to a power source) if the memory system **410** is implemented in a mobile device or mobile application.

(78) At **444**, a first value may be written to the first register **420** of the memory system **410**. For example, the host system **405** may write the first value to the first register **420** (e.g., via the memory controller **415**) based on determining to perform a defragmentation operation on the memory system **410**. As described herein, the first value may indicate for a defragmentation operation to be performed when the memory system **410** is idle for a duration.

(79) At **446**, an amount of defragmentation to be performed on the memory system **410** (e.g., on the memory associated with the memory system **410**) may be determined. For example, the memory controller **415** may determine the amount of defragmentation to be performed. The memory controller **415** may determine the amount (e.g., the quantity, the size) of data to defragment based on one or more heuristics, such as a quantity of frequently-accessed LBAs. That is, if a particular LBA or set of LBAs is frequently accessed, then a value representative of an amount of data associated with the LBA or LBAs may be written to the third register **430**.

(80) At **448**, a value indicating the quantity of defragmentation to be performed on the memory system **410** may be written to the third register **430**. For example, the memory controller **415** may write the value (e.g., a third value) to the third register **430** based on determining the amount of defragmentation to be performed on the memory system **410**.

(81) At **450**, the memory system **410** may be idle for a duration. For example, during the duration, access operations may be performed on the memory associated with the memory system **410**. Other operations such as maintenance operations (e.g., BKOPS) or defragmentation operations, however, may be performed during the duration. At **452**, one or more commands may be transmitted from the host system **405** to the memory system **410**. In some examples, the command(s) may initiate one or more maintenance operations (e.g., BKOPS) to be performed on the memory system.

(82) At **454**, values stored to the first register **420**, the second register **425**, and the third register **430** may be read and analyzed. For example, the memory controller **415** may read and analyze the values stored to each of the registers based on receiving the command (e.g., at **452**) and/or based on the memory system **410** being idle for a duration.

(83) For example, the memory controller **415** may read a first value from the first register **420**. The first value (e.g., a "1") may indicate that a defragmentation operation is to occur based on the maintenance operations (e.g., the BKOPS) being performed.

(84) The memory controller **415** may read a second value from the second register **425**. As

described herein, the second value may be a threshold value associated with a quantity of P/E cycles performed on the memory associated with the memory system **410**. The memory controller **415** may then compare a quantity of P/E cycles performed on the memory (e.g., which may be tracked by the memory controller **415** using a counter or other component as described herein) to the threshold value. If the quantity of P/E cycles does not satisfy the threshold value, then the defragmentation operation may be performed based on the first register **420** storing the first value. However, if the quantity of P/E cycles satisfies the threshold value, the defragmentation operation may not be performed because the memory system **410** may be undesirably close to EOL. In some instances, if the quantity of P/E cycles satisfies the threshold value, signaling may be transmitted to the host system **405** and the host system **405** may write the second value to the first register **420** based on receiving the signaling. In other examples, the memory controller **415** may write the second value to the first register **420** based on the quantity of P/E cycles satisfying the threshold value.

(85) The memory controller **415** may also read the value indicating the quantity of defragmentation to perform (e.g., the third value) from the third register **430**. As described herein, the third value may indicate the quantity of defragmentation to perform. At **456**, a defragmentation operation may be initiated. For example, the memory controller **415** may initiate the defragmentation operation based on the values stored to the first register **420** and the second register **425** and the amount of data to be defragmented may be based on the third value stored to the third register **430**. The defragmentation operation may be performed during the duration in which the memory system **410** is idle and may be performed either serially or in parallel with the maintenance operations that were initiated based on the command transmitted from the host system **405** (e.g., at **452**).

(86) In some instances, before initiating the defragmentation operation (e.g., at **456**), the memory controller **415** (or another component of the memory system **410**) may identify portions of memory to defragment. For example, the memory controller **415** may perform a scan or other type of operation to identify data that is associated with one or more continuous LBAs but that is stored to one or more associated, discontinuous physical addresses. The memory controller **415** may identify such data using an L2P table (e.g., an L2P table **335** as described with reference to FIG. 3) or other source of mappings between logical space and physical addresses. An identification of the data (e.g., a LBA associated with the discontinuous physical addresses or the actual discontinuous physical addresses) may be stored to a portion of the memory system **410** and the memory controller **415** may access the identification of the data for the defragmentation operation. Such an identification, although not illustrated in FIG. 4, may occur at any time before the defragmentation operation is initiated (e.g., at any time before **456**).

(87) At **458**, it may be desirable to stop the defragmentation operation. For example, the host system **405** may determine to stop the defragmentation operation based on one or more characteristics of the memory system **410**, such as a power supply of associated with the memory system **410** running low. At **460**, the second value may be written to the first register **420**. For example, the host system **405** may write the second value to the first register **420** (e.g., via the memory controller **415**), which may result in the defragmentation operation being stopped. That is, the memory controller **415** may stop the ongoing defragmentation operation (not shown) based on the second value being written to the first register **420**. By utilizing the registers to perform (or to refrain from performing) a defragmentation operation, the life or power of the memory system **410** may be prolonged, among other benefits.

(88) FIG. 5 shows a block diagram **500** of a memory system **520** that supports data defragmentation control in accordance with examples as disclosed herein. The memory system **520** may be an example of aspects of a memory system as described with reference to FIGS. 1 through 4. The memory system **520**, or various components thereof, may be an example of means for performing various aspects of data defragmentation control as described herein. For example, the memory system **520** may include an identification component **525**, a reception component **530**, a

defragmentation component **535**, a determination component **540**, a writing component **545**, a maintenance component **550**, a storing component **555**, or any combination thereof. Each of these components may communicate, directly or indirectly, with one another (e.g., via one or more buses).

(89) The identification component **525** may be configured as or otherwise support a means for identifying, for a memory system including a plurality of regions of logical addresses and a plurality of memory cells arranged according to a plurality of physical addresses, a region of the plurality of regions having one or more continuous logical addresses associated with discontinuous corresponding physical addresses of the plurality of physical addresses. In some examples, the identification component **525** may be configured as or otherwise support a means for identifying, after rearranging the information, a second region of the plurality of regions having one or more logical addresses associated with discontinuous corresponding physical addresses of the plurality of physical addresses.

(90) The reception component **530** may be configured as or otherwise support a means for receiving, at a first register of the memory system, a first value enabling rearranging of information associated with continuous logical addresses that are associated with discontinuous corresponding physical addresses. In some examples, the reception component **530** may be configured as or otherwise support a means for receiving, at a second register of the memory system, a second value. In some examples, the reception component **530** may be configured as or otherwise support a means for receiving, from a host device, a first command for performing the one or more maintenance operations on the memory system.

(91) The defragmentation component **535** may be configured as or otherwise support a means for rearranging, during a duration for performing one or more maintenance operations on the memory system, information stored within the discontinuous corresponding physical addresses to be within continuous physical addresses of the plurality of physical addresses based at least in part on the first value of the first register. In some examples, the defragmentation component **535** may be configured as or otherwise support a means for refraining, during a second duration for performing one or more maintenance operations on the memory system, from defragmenting third information stored within discontinuous corresponding physical addresses from being within continuous physical addresses of the plurality of physical addresses based at least in part on the second value of the first register.

(92) In some examples, to support rearranging the information stored within the discontinuous corresponding physical addresses to be within continuous physical addresses of the plurality of physical addresses, the defragmentation component **535** may be configured as or otherwise support a means for reading data from the discontinuous corresponding physical addresses. In some examples, to support rearranging the information stored within the discontinuous corresponding physical addresses to be within continuous physical addresses of the plurality of physical addresses, the defragmentation component **535** may be configured as or otherwise support a means for writing the data associated with the plurality of physical addresses to the continuous physical addresses of the plurality of physical addresses based at least in part on reading the data, where rearranging the information is based at least in part on reading the data and writing the data.

(93) In some examples, the determination component **540** may be configured as or otherwise support a means for determining that a quantity of access operations performed on the plurality of memory cells of the memory system does not satisfy the second value, where rearranging the information is based at least in part on determining that the quantity of access operations does not satisfy the second value. In some examples, the determination component **540** may be configured as or otherwise support a means for determining that the quantity of access operations performed on the plurality of memory cells of the memory system satisfies the second value, where second information stored within the discontinuous corresponding physical addresses to be within continuous physical addresses of the plurality of physical addresses is not rearranged based at least

in part on determining that the quantity of access operations satisfies the second value.

(94) In some examples, the writing component **545** may be configured as or otherwise support a means for writing a third value to a third register of the memory system based at least in part on reading the first value from the first register of the memory system, where a quantity of the information rearranged is based at least in part on the third value read from the third register of the memory system. In some examples, the writing component **545** may be configured as or otherwise support a means for writing a second value to the first register based at least in part on receiving the second value from a host device.

(95) In some examples, the maintenance component **550** may be configured as or otherwise support a means for performing, during the duration, the one or more maintenance operations on the memory system based at least in part on receiving the first command.

(96) In some examples, the storing component **555** may be configured as or otherwise support a means for storing a first physical address of the plurality of physical addresses in a logical-to-physical table of the memory system based at least in part on rearranging the information.

(97) In some examples, the plurality of memory cells are not accessed during the duration.

(98) FIG. **6** shows a flowchart illustrating a method **600** that supports data defragmentation control in accordance with examples as disclosed herein. The operations of method **600** may be implemented by a memory system or its components as described herein. For example, the operations of method **600** may be performed by a memory system as described with reference to FIGS. **1** through **5**. In some examples, a memory system may execute a set of instructions to control the functional elements of the device to perform the described functions. Additionally or alternatively, the memory system may perform aspects of the described functions using special-purpose hardware.

(99) At **605**, the method may include identifying, for a memory system including a plurality of regions of logical addresses and a plurality of memory cells arranged according to a plurality of physical addresses, a region of the plurality of regions having one or more continuous logical addresses associated with discontinuous corresponding physical addresses of the plurality of physical addresses. The operations of **605** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **605** may be performed by an identification component **525** as described with reference to FIG. **5**.

(100) At **610**, the method may include receiving, at a first register of the memory system, a first value enabling rearranging of information associated with continuous logical addresses that are associated with discontinuous corresponding physical addresses. The operations of **610** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **610** may be performed by a reception component **530** as described with reference to FIG. **5**.

(101) At **615**, the method may include rearranging, during a duration for performing one or more maintenance operations on the memory system, information stored within the discontinuous corresponding physical addresses to be within continuous physical addresses of the plurality of physical addresses based at least in part on the first value of the first register. The operations of **615** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **615** may be performed by a defragmentation component **535** as described with reference to FIG. **5**.

(102) In some examples, an apparatus as described herein may perform a method or methods, such as the method **600**. The apparatus may include features, circuitry, logic, means, or instructions (e.g., a non-transitory computer-readable medium storing instructions executable by a processor), or any combination thereof for performing the following aspects of the present disclosure:

(103) Aspect 1: A method, apparatus, or non-transitory computer-readable medium including operations, features, circuitry, logic, means, or instructions, or any combination thereof for identifying, for a memory system including a plurality of regions of logical addresses and a

plurality of memory cells arranged according to a plurality of physical addresses, a region of the plurality of regions having one or more continuous logical addresses associated with discontinuous corresponding physical addresses of the plurality of physical addresses; receiving, at a first register of the memory system, a first value enabling rearranging of information associated with continuous logical addresses that are associated with discontinuous corresponding physical addresses; and rearranging, during a duration for performing one or more maintenance operations on the memory system, information stored within the discontinuous corresponding physical addresses to be within continuous physical addresses of the plurality of physical addresses based at least in part on the first value of the first register.

(104) Aspect 2: The method, apparatus, or non-transitory computer-readable medium of aspect 1, further including operations, features, circuitry, logic, means, or instructions, or any combination thereof for receiving, at a second register of the memory system, a second value and determining that a quantity of access operations performed on the plurality of memory cells of the memory system does not satisfy the second value, where rearranging the information is based at least in part on determining that the quantity of access operations does not satisfy the second value.

(105) Aspect 3: The method, apparatus, or non-transitory computer-readable medium of aspect 2, further including operations, features, circuitry, logic, means, or instructions, or any combination thereof for identifying, after rearranging the information, a second region of the plurality of regions having one or more logical addresses associated with discontinuous corresponding physical addresses of the plurality of physical addresses and determining that the quantity of access operations performed on the plurality of memory cells of the memory system satisfies the second value, where second information stored within the discontinuous corresponding physical addresses to be within continuous physical addresses of the plurality of physical addresses is not rearranged based at least in part on determining that the quantity of access operations satisfies the second value.

(106) Aspect 4: The method, apparatus, or non-transitory computer-readable medium of any of aspects 1 through 3, further including operations, features, circuitry, logic, means, or instructions, or any combination thereof for writing a third value to a third register of the memory system based at least in part on reading the first value from the first register of the memory system, where a quantity of the information rearranged is based at least in part on the third value read from the third register of the memory system.

(107) Aspect 5: The method, apparatus, or non-transitory computer-readable medium of any of aspects 1 through 4, further including operations, features, circuitry, logic, means, or instructions, or any combination thereof for receiving, from a host device, a first command for performing the one or more maintenance operations on the memory system and performing, during the duration, the one or more maintenance operations on the memory system based at least in part on receiving the first command.

(108) Aspect 6: The method, apparatus, or non-transitory computer-readable medium of any of aspects 1 through 5, further including operations, features, circuitry, logic, means, or instructions, or any combination thereof for writing a second value to the first register based at least in part on receiving the second value from a host device and refraining, during a second duration for performing one or more maintenance operations on the memory system, from defragmenting third information stored within discontinuous corresponding physical addresses from being within continuous physical addresses of the plurality of physical addresses based at least in part on the second value of the first register.

(109) Aspect 7: The method, apparatus, or non-transitory computer-readable medium of any of aspects 1 through 6 where rearranging the information stored within the discontinuous corresponding physical addresses to be within continuous physical addresses of the plurality of physical addresses includes operations, features, circuitry, logic, means, or instructions, or any combination thereof for reading data from the discontinuous corresponding physical addresses and

writing the data associated with the plurality of physical addresses to the continuous physical addresses of the plurality of physical addresses based at least in part on reading the data, where rearranging the information is based at least in part on reading the data and writing the data.

(110) Aspect 8: The method, apparatus, or non-transitory computer-readable medium of any of aspects 1 through 7, further including operations, features, circuitry, logic, means, or instructions, or any combination thereof for storing a first physical address of the plurality of physical addresses in a logical-to-physical table of the memory system based at least in part on rearranging the information.

(111) Aspect 9: The method, apparatus, or non-transitory computer-readable medium of any of aspects 1 through 8 where the plurality of memory cells are not accessed during the duration.

(112) It should be noted that the methods described above describe possible implementations, and that the operations and the steps may be rearranged or otherwise modified and that other implementations are possible. Further, portions from two or more of the methods may be combined.

(113) Information and signals described herein may be represented using any of a variety of different technologies and techniques. For example, data, instructions, commands, information, signals, bits, symbols, and chips that may be referenced throughout the above description may be represented by voltages, currents, electromagnetic waves, magnetic fields or particles, optical fields or particles, or any combination thereof. Some drawings may illustrate signals as a single signal; however, the signal may represent a bus of signals, where the bus may have a variety of bit widths.

(114) The terms “electronic communication,” “conductive contact,” “connected,” and “coupled” may refer to a relationship between components that supports the flow of signals between the components. Components are considered in electronic communication with (or in conductive contact with or connected with or coupled with) one another if there is any conductive path between the components that can, at any time, support the flow of signals between the components. At any given time, the conductive path between components that are in electronic communication with each other (or in conductive contact with or connected with or coupled with) may be an open circuit or a closed circuit based on the operation of the device that includes the connected components. The conductive path between connected components may be a direct conductive path between the components or the conductive path between connected components may be an indirect conductive path that may include intermediate components, such as switches, transistors, or other components. In some examples, the flow of signals between the connected components may be interrupted for a time, for example, using one or more intermediate components such as switches or transistors.

(115) The term “coupling” refers to a condition of moving from an open-circuit relationship between components in which signals are not presently capable of being communicated between the components over a conductive path to a closed-circuit relationship between components in which signals are capable of being communicated between components over the conductive path. If a component, such as a controller, couples other components together, the component initiates a change that allows signals to flow between the other components over a conductive path that previously did not permit signals to flow.

(116) The term “isolated” refers to a relationship between components in which signals are not presently capable of flowing between the components. Components are isolated from each other if there is an open circuit between them. For example, two components separated by a switch that is positioned between the components are isolated from each other if the switch is open. If a controller isolates two components, the controller affects a change that prevents signals from flowing between the components using a conductive path that previously permitted signals to flow.

(117) The term “layer” or “level” used herein refers to a stratum or sheet of a geometrical structure (e.g., relative to a substrate). Each layer or level may have three dimensions (e.g., height, width, and depth) and may cover at least a portion of a surface. For example, a layer or level may be a

three-dimensional structure where two dimensions are greater than a third, e.g., a thin-film. Layers or levels may include different elements, components, and/or materials. In some examples, one layer or level may be composed of two or more sublayers or sublevels.

(118) The terms “if,” “when,” “based on,” or “based at least in part on” may be used interchangeably. In some examples, if the terms “if,” “when,” “based on,” or “based at least in part on” are used to describe a conditional action, a conditional process, or connection between portions of a process, the terms may be interchangeable.

(119) The term “in response to” may refer to one condition or action occurring at least partially, if not fully, as a result of a previous condition or action. For example, a first condition or action may be performed and second condition or action may at least partially occur as a result of the previous condition or action occurring (whether directly after or after one or more other intermediate conditions or actions occurring after the first condition or action).

(120) Additionally, the terms “directly in response to” or “in direct response to” may refer to one condition or action occurring as a direct result of a previous condition or action. In some examples, a first condition or action may be performed and second condition or action may occur directly as a result of the previous condition or action occurring independent of whether other conditions or actions occur. In some examples, a first condition or action may be performed and second condition or action may occur directly as a result of the previous condition or action occurring, such that no other intermediate conditions or actions occur between the earlier condition or action and the second condition or action or a limited quantity of one or more intermediate steps or actions occur between the earlier condition or action and the second condition or action. Any condition or action described herein as being performed “based on,” “based at least in part on,” or “in response to” some other step, action, event, or condition may additionally or alternatively (e.g., in an alternative example) be performed “in direct response to” or “directly in response to” such other condition or action unless otherwise specified.

(121) The devices discussed herein, including a memory array, may be formed on a semiconductor substrate, such as silicon, germanium, silicon-germanium alloy, gallium arsenide, gallium nitride, etc. In some examples, the substrate is a semiconductor wafer. In some other examples, the substrate may be a silicon-on-insulator (SOI) substrate, such as silicon-on-glass (SOG) or silicon-on-sapphire (SOP), or epitaxial layers of semiconductor materials on another substrate. The conductivity of the substrate, or sub-regions of the substrate, may be controlled through doping using various chemical species including, but not limited to, phosphorous, boron, or arsenic. Doping may be performed during the initial formation or growth of the substrate, by ion-implantation, or by any other doping means.

(122) A switching component or a transistor discussed herein may represent a field-effect transistor (FET) and comprise a three terminal device including a source, drain, and gate. The terminals may be connected to other electronic elements through conductive materials, e.g., metals. The source and drain may be conductive and may comprise a heavily-doped, e.g., degenerate, semiconductor region. The source and drain may be separated by a lightly-doped semiconductor region or channel. If the channel is n-type (i.e., majority carriers are electrons), then the FET may be referred to as an n-type FET. If the channel is p-type (i.e., majority carriers are holes), then the FET may be referred to as a p-type FET. The channel may be capped by an insulating gate oxide. The channel conductivity may be controlled by applying a voltage to the gate. For example, applying a positive voltage or negative voltage to an n-type FET or a p-type FET, respectively, may result in the channel becoming conductive. A transistor may be “on” or “activated” if a voltage greater than or equal to the transistor's threshold voltage is applied to the transistor gate. The transistor may be “off” or “deactivated” if a voltage less than the transistor's threshold voltage is applied to the transistor gate.

(123) The description set forth herein, in connection with the appended drawings, describes example configurations and does not represent all the examples that may be implemented or that

are within the scope of the claims. The term “exemplary” used herein means “serving as an example, instance, or illustration” and not “preferred” or “advantageous over other examples.” The detailed description includes specific details to providing an understanding of the described techniques. These techniques, however, may be practiced without these specific details. In some instances, well-known structures and devices are shown in block diagram form to avoid obscuring the concepts of the described examples.

(124) In the appended figures, similar components or features may have the same reference label. Further, various components of the same type may be distinguished by following the reference label by a hyphen and a second label that distinguishes among the similar components. If just the first reference label is used in the specification, the description is applicable to any one of the similar components having the same first reference label irrespective of the second reference label.

(125) The functions described herein may be implemented in hardware, software executed by a processor, firmware, or any combination thereof. If implemented in software executed by a processor, the functions may be stored on or transmitted over, as one or more instructions or code, a computer-readable medium. Other examples and implementations are within the scope of the disclosure and appended claims. For example, due to the nature of software, functions described above can be implemented using software executed by a processor, hardware, firmware, hardwiring, or combinations of any of these. Features implementing functions may also be physically located at various positions, including being distributed such that portions of functions are implemented at different physical locations.

(126) For example, the various illustrative blocks and components described in connection with the disclosure herein may be implemented or performed with a general-purpose processor, a DSP, an ASIC, an FPGA or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general-purpose processor may be a microprocessor, but in the alternative, the processor may be any processor, controller, microcontroller, or state machine. A processor may be implemented as a combination of computing devices (e.g., a combination of a DSP and a microprocessor, multiple microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration).

(127) As used herein, including in the claims, “or” as used in a list of items (for example, a list of items prefaced by a phrase such as “at least one of” or “one or more of”) indicates an inclusive list such that, for example, a list of at least one of A, B, or C means A or B or C or AB or AC or BC or ABC (i.e., A and B and C). Also, as used herein, the phrase “based on” shall not be construed as a reference to a closed set of conditions. For example, an exemplary step that is described as “based on condition A” may be based on both a condition A and a condition B without departing from the scope of the present disclosure. In other words, as used herein, the phrase “based on” shall be construed in the same manner as the phrase “based at least in part on.”

(128) Computer-readable media includes both non-transitory computer storage media and communication media including any medium that facilitates transfer of a computer program from one place to another. A non-transitory storage medium may be any available medium that can be accessed by a general purpose or special purpose computer. By way of example, and not limitation, non-transitory computer-readable media can comprise RAM, ROM, electrically erasable programmable read-only memory (EEPROM), compact disk (CD) ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other non-transitory medium that can be used to carry or store desired program code means in the form of instructions or data structures and that can be accessed by a general-purpose or special-purpose computer, or a general-purpose or special-purpose processor. Also, any connection is properly termed a computer-readable medium. For example, if the software is transmitted from a website, server, or other remote source using a coaxial cable, fiber optic cable, twisted pair, digital subscriber line (DSL), or wireless technologies such as infrared, radio, and microwave, then the coaxial cable, fiber optic

cable, twisted pair, DSL, or wireless technologies such as infrared, radio, and microwave are included in the definition of medium. Disk and disc, as used herein, include CD, laser disc, optical disc, digital versatile disc (DVD), floppy disk, and Blu-ray disc, where disks usually reproduce data magnetically, while discs reproduce data optically with lasers. Combinations of the above are also included within the scope of computer-readable media.

(129) The description herein is provided to enable a person skilled in the art to make or use the disclosure. Various modifications to the disclosure will be apparent to those skilled in the art, and the generic principles defined herein may be applied to other variations without departing from the scope of the disclosure. Thus, the disclosure is not limited to the examples and designs described herein but is to be accorded the broadest scope consistent with the principles and novel features disclosed herein.

Claims

1. A method, comprising: identifying, for a memory system comprising a plurality of regions of logical addresses and a plurality of memory cells arranged according to a plurality of physical addresses, a region of the plurality of regions having one or more continuous logical addresses associated with discontinuous corresponding physical addresses of the plurality of physical addresses; receiving, at a first register of the memory system, a first value enabling rearranging of information associated with continuous logical addresses that are associated with discontinuous corresponding physical addresses; and rearranging, during a duration for performing one or more maintenance operations on the memory system, information stored within the discontinuous corresponding physical addresses to be within continuous physical addresses of the plurality of physical addresses based at least in part on the first value of the first register, wherein rearranging the information stored within the discontinuous corresponding physical addresses to be within continuous physical addresses of the plurality of physical addresses comprises: reading data from the discontinuous corresponding physical addresses; and writing the data associated with the plurality of physical addresses to the continuous physical addresses of the plurality of physical addresses based at least in part on reading the data, wherein rearranging the information is based at least in part on reading the data and writing the data.
2. The method of claim 1, further comprising: receiving, at a second register of the memory system, a second value; and determining that a quantity of access operations performed on the plurality of memory cells of the memory system does not satisfy the second value, wherein rearranging the information is based at least in part on determining that the quantity of access operations does not satisfy the second value.
3. The method of claim 2, further comprising: identifying, after rearranging the information, a second region of the plurality of regions having one or more logical addresses associated with discontinuous corresponding physical addresses of the plurality of physical addresses; and determining that the quantity of access operations performed on the plurality of memory cells of the memory system satisfies the second value, wherein second information stored within the discontinuous corresponding physical addresses to be within continuous physical addresses of the plurality of physical addresses is not rearranged based at least in part on determining that the quantity of access operations satisfies the second value.
4. The method of claim 1, further comprising: writing a third value to a third register of the memory system based at least in part on reading the first value from the first register of the memory system, wherein a quantity of the information rearranged is based at least in part on the third value read from the third register of the memory system.
5. The method of claim 1, further comprising: receiving, from a host device, a first command for performing the one or more maintenance operations on the memory system; and performing, during the duration, the one or more maintenance operations on the memory system based at least in part

on receiving the first command.

6. The method of claim 1, further comprising: writing a second value to the first register based at least in part on receiving the second value from a host device; and refraining, during a second duration for performing one or more maintenance operations on the memory system, from defragmenting third information stored within discontinuous corresponding physical addresses from being within continuous physical addresses of the plurality of physical addresses based at least in part on the second value of the first register.

7. An apparatus, comprising: a memory system comprising a plurality of regions of logical addresses and a plurality of memory cells arranged according to a plurality of physical addresses; a first register associated with the memory system; and processing circuitry associated with the memory system, wherein the processing circuitry is configured to cause the apparatus to: identify a region of the plurality of regions having one or more continuous logical addresses associated with discontinuous corresponding physical addresses of the plurality of physical addresses; receive, at the first register of the memory system, a first value enabling rearranging of information associated with continuous logical addresses that are associated with discontinuous corresponding physical addresses; and rearrange, during a duration for performing one or more maintenance operations on the memory system, information stored within the discontinuous corresponding physical addresses to be within continuous physical addresses of the plurality of physical addresses based at least in part on the first value of the first register, wherein, to rearrange the information stored within the discontinuous corresponding physical addresses to be within continuous physical addresses of the plurality of physical addresses, the processing circuitry is configured to cause the apparatus to: read data from the discontinuous corresponding physical addresses; and write the data associated with the plurality of physical addresses to the continuous physical addresses of the plurality of physical addresses based at least in part on reading the data, wherein rearranging the information is based at least in part on reading the data and writing the data.

8. The apparatus of claim 7, further comprising: a second register associated with the memory system, wherein the processing circuitry is further configured to cause the apparatus to: receive, at the second register, a second value; and determine that a quantity of access operations performed on the plurality of memory cells of the memory system does not satisfy the second value, wherein rearranging the information is based at least in part on determining that the quantity of access operations does not satisfy the second value.

9. The apparatus of claim 8, wherein the processing circuitry is further configured to cause the apparatus to: identify, after rearranging the information, a second region of the plurality of regions having one or more logical addresses associated with discontinuous corresponding physical addresses of the plurality of physical addresses; and determine that the quantity of access operations performed on the plurality of memory cells of the memory system satisfies the second value, wherein second information stored within the discontinuous corresponding physical addresses to be within continuous physical addresses of the plurality of physical addresses is not rearranged based at least in part on determining that the quantity of access operations satisfies the second value.

10. The apparatus of claim 7, further comprising: a third register associated with the memory system, wherein the processing circuitry is further configured to cause the apparatus to: write a third value to the third register based at least in part on reading the first value from the first register of the memory system, wherein a quantity of the information rearranged is based at least in part on the third value read from the third register of the memory system.

11. The apparatus of claim 7, wherein the processing circuitry is further configured to cause the apparatus to: receive, from a host device, a first command for performing the one or more maintenance operations on the memory system; and perform, during the duration, the one or more maintenance operations on the memory system based at least in part on receiving the first command.

12. The apparatus of claim 7, wherein the processing circuitry is further configured to cause the apparatus to: write a second value to the first register based at least in part on receiving the second value from a host device; and refrain, during a second duration for performing one or more maintenance operations on the memory system, from defragmenting third information stored within discontinuous corresponding physical addresses from being within continuous physical addresses of the plurality of physical addresses based at least in part on the second value of the first register.

13. The apparatus of claim 7, wherein the processing circuitry is further configured to cause the apparatus to: store a first physical address of the plurality of physical addresses in a logical-to-physical table of the memory system based at least in part on rearranging the information.

14. The apparatus of claim 7, wherein the plurality of memory cells are not accessed during the duration.

15. A non-transitory computer-readable medium storing code comprising instructions which, when executed by one or more processors of an electronic device, cause the electronic device to: identify, for a memory system comprising a plurality of regions of logical addresses and a plurality of memory cells arranged according to a plurality of physical addresses, a region of the plurality of regions having one or more continuous logical addresses associated with discontinuous corresponding physical addresses of the plurality of physical addresses; receive, at a first register of the memory system, a first value enabling rearranging of information associated with continuous logical addresses that are associated with discontinuous corresponding physical addresses; and rearrange, during a duration for performing one or more maintenance operations on the memory system, information stored within the discontinuous corresponding physical addresses to be within continuous physical addresses of the plurality of physical addresses based at least in part on the first value of the first register, wherein, to rearrange the information stored within the discontinuous corresponding physical addresses to be within continuous physical addresses of the plurality of physical addresses, the instructions, when executed by the one or more processors of the electronic device, cause the electronic device to: read data from the discontinuous corresponding physical addresses; and write the data associated with the plurality of physical addresses to the continuous physical addresses of the plurality of physical addresses based at least in part on reading the data, wherein rearranging the information is based at least in part on reading the data and writing the data.

16. The non-transitory computer-readable medium of claim 15, wherein the instructions, when executed by the one or more processors of the electronic device, further cause the electronic device to: receive, at a second register of the memory system, a second value; and determine that a quantity of access operations performed on the plurality of memory cells of the memory system does not satisfy the second value, wherein rearranging the information is based at least in part on determining that the quantity of access operations does not satisfy the second value.

17. The non-transitory computer-readable medium of claim 16, wherein the instructions, when executed by the one or more processors of the electronic device, further cause the electronic device to: identify, after rearranging the information, a second region of the plurality of regions having one or more logical addresses associated with discontinuous corresponding physical addresses of the plurality of physical addresses; and determine that the quantity of access operations performed on the plurality of memory cells of the memory system satisfies the second value, wherein second information stored within the discontinuous corresponding physical addresses to be within continuous physical addresses of the plurality of physical addresses is not rearranged based at least in part on determining that the quantity of access operations satisfies the second value.

18. The non-transitory computer-readable medium of claim 15, wherein the instructions, when executed by the one or more processors of the electronic device, further cause the electronic device to: write a third value to a third register of the memory system based at least in part on reading the first value from the first register of the memory system, wherein a quantity of the information

rearranged is based at least in part on the third value read from the third register of the memory system.

19. The non-transitory computer-readable medium of claim 15, wherein the instructions, when executed by the one or more processors of the electronic device, further cause the electronic device to: receive, from a host device, a first command for performing the one or more maintenance operations on the memory system; and perform, during the duration, the one or more maintenance operations on the memory system based at least in part on receiving the first command.

20. The non-transitory computer-readable medium of claim 15, wherein the instructions, when executed by the one or more processors of the electronic device, further cause the electronic device to: write a second value to the first register based at least in part on receiving the second value from a host device; and refrain, during a second duration for performing one or more maintenance operations on the memory system, from defragmenting third information stored within discontinuous corresponding physical addresses from being within continuous physical addresses of the plurality of physical addresses based at least in part on the second value of the first register.

21. The non-transitory computer-readable medium of claim 1, wherein the instructions, when executed by the one or more processors of the electronic device, further cause the electronic device to: store a first physical address of the plurality of physical addresses in a logical-to-physical table of the memory system based at least in part on rearranging the information.

22. The non-transitory computer-readable medium of claim 15, wherein the plurality of memory cells are not accessed during the duration.
