

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12412698
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Yoshioka; Yoshimasa

Passive component, three-dimensional device, and method for manufacturing passive component

Abstract

A passive component includes a body portion having a first main surface and a passive element at least a part of which is provided inside the body portion. The first main surface at least partially includes a flat surface made of an inorganic substance and having a surface roughness of equal to or less than 1/1000 of a thickness of the body portion in a direction orthogonal to the first main surface or equal to or less than 10 nm.

Inventors:	Yoshioka; Yoshimasa (Nagaokakyo, JP)
Applicant:	Murata Manufacturing Co., Ltd. (Kyoto-fu, JP)
Family ID:	88934326
Assignee:	Murata Manufacturing Co., Ltd. (Kyoto-fu, JP)
Appl. No.:	18/321401
Filed:	May 22, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230395312 A1	Dec. 07, 2023

Foreign Application Priority Data

JP	2022-090324	Jun. 02, 2022
----	-------------	---------------

Publication Classification

Int. Cl.: H01F27/32 (20060101); H01F27/28 (20060101); H01F41/04 (20060101); H01L25/16 (20230101); H01L25/18 (20230101); H10D86/85 (20250101)

U.S. Cl.:

CPC **H01F27/324** (20130101); **H01F27/2804** (20130101); **H01F41/043** (20130101);
H01L25/16 (20130101); **H01L25/18** (20130101); **H10D86/85** (20250101);

Field of Classification Search

CPC: H01F (27/324); H10D (86/85)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9460996	12/2015	Zang	N/A	H01L 23/5227
2008/0023219	12/2007	Yoshizawa	174/260	H10D 1/20
2020/0294908	12/2019	Haba	N/A	H01L 23/5223
2021/0305231	12/2020	Oba	N/A	H10D 1/20

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
H04-284612	12/1991	JP	N/A
H11-243033	12/1998	JP	N/A
5448393	12/2013	JP	N/A
2020-503692	12/2019	JP	N/A

Primary Examiner: Bauer; Scott

Attorney, Agent or Firm: Studebaker Brackett PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application claims benefit of priority to Japanese Patent Application No. 2022-090324, filed Jun. 2, 2022, the entire content of which is incorporated herein by reference.

BACKGROUND

Technical Field

(2) The present disclosure relates to a passive component, a three-dimensional device and a method for manufacturing a passive component.

Background Art

(3) In recent years, with miniaturization and high performance of stacked semiconductor packages, integration of electronic circuits has been further advanced. An existing stacked semiconductor package is disclosed in Japanese Patent No. 5448393. The stacked semiconductor package includes a first semiconductor package, a second semiconductor package stacked on the first semiconductor package, and a capacitor provided between the first semiconductor package and the second semiconductor package and connected to the first semiconductor package and the second semiconductor package. The capacitor is an example of a passive component. By stacking the first semiconductor package, the second semiconductor package, and the capacitor, a footprint (an area of a circuit or a component) is reduced in size.

SUMMARY

- (4) However, in the existing stacked semiconductor package described above, since the first semiconductor package, the second semiconductor package, and the capacitor are connected using solder balls or solder paste, the thickness of the entire stacked semiconductor package becomes thick, and then it is difficult to realize a reduction in thickness.
- (5) In view of the above, the present disclosure provides a passive component and a three-dimensional device in which reducing the thickness of an entire device such as a stacked semiconductor package can be achieved and a method for manufacturing a passive component.
- (6) A passive component according to an aspect of the present disclosure includes a body portion having a first main surface; and a passive element at least a part of which is provided inside the body portion. The first main surface at least partially includes a flat surface made of an inorganic substance and having a surface roughness of equal to or less than $1/1000$ of a thickness of the body portion in a direction orthogonal to the first main surface or equal to or less than 10 nm.
- (7) According to the aspect, since the first main surface of the body portion at least partially includes a flat surface made of an inorganic substance, when the passive component is bonded to another electronic component or the like having a flat surface, the flat surfaces can be bonded in a state of being in contact with each other. Therefore, it is possible to reduce the thickness of the entire device such as a stacked semiconductor package.
- (8) Preferably, an embodiment of a three-dimensional device includes: the passive component; and a semiconductor integrated circuit component bonded to the flat surface of the passive component.
- (9) According to the above embodiment, a thin-type three-dimensional device can be obtained.
- (10) An embodiment of a method for manufacturing a passive component includes preparing an inorganic layer made of an inorganic substance and having a first main surface and a second main surface facing each other; forming a body portion including the inorganic layer and at least a part of a passive element by providing the passive element on the second main surface side of the inorganic layer; and providing a flat surface having a surface roughness of equal to or less than $1/1000$ of a thickness of the body portion in a direction orthogonal to the first main surface or equal to or less than 10 nm by polishing the first main surface of the inorganic layer.
- (11) According to the embodiment, since the first main surface of the inorganic layer includes a flat surface, when the passive component is bonded to another electronic component or the like having a flat surface, the flat surfaces can be bonded in a state of being in contact with each other. Therefore, it is possible to reduce the thickness of the entire device such as a stacked semiconductor package.
- (12) According to a passive component, a three-dimensional device, and a method for manufacturing a passive component according to an aspect of the present disclosure, it is possible to reduce the thickness.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a schematic bottom view illustrating a first embodiment of a passive component viewed from a bottom surface side;
- (2) FIG. 2 is a cross-sectional view taken along a line II-II of FIG. 1;
- (3) FIG. 3 is a cross-sectional view taken along a line III-III of FIG. 1;
- (4) FIG. 4A is a schematic cross-sectional view illustrating a method for manufacturing a passive component;
- (5) FIG. 4B is a schematic cross-sectional view illustrating the method for manufacturing the passive component;
- (6) FIG. 4C is a schematic cross-sectional view illustrating the method for manufacturing the

passive component;

(7) FIG. 4D is a schematic cross-sectional view illustrating the method for manufacturing the passive component;

(8) FIG. 4E is a schematic cross-sectional view illustrating the method for manufacturing the passive component;

(9) FIG. 4F is a schematic cross-sectional view illustrating the method for manufacturing the passive component;

(10) FIG. 4G is a schematic cross-sectional view illustrating the method for manufacturing the passive component;

(11) FIG. 4H is a schematic cross-sectional view illustrating the method for manufacturing the passive component;

(12) FIG. 4I is a schematic cross-sectional view illustrating the method for manufacturing the passive component;

(13) FIG. 4J is a schematic cross-sectional view illustrating the method for manufacturing the passive component;

(14) FIG. 4K is a schematic cross-sectional view illustrating the method for manufacturing the passive component;

(15) FIG. 5 is a schematic top view illustrating a second embodiment of a passive component viewed from a top surface side;

(16) FIG. 6 is a cross-sectional view taken along a line VI-VI of FIG. 5;

(17) FIG. 7 is an enlarged view of part A of FIG. 6;

(18) FIG. 8A is a schematic cross-sectional view illustrating a method for manufacturing a passive component;

(19) FIG. 8B is a schematic cross-sectional view illustrating the method for manufacturing the passive component;

(20) FIG. 8C is a schematic cross-sectional view illustrating the method for manufacturing the passive component;

(21) FIG. 8D is a schematic cross-sectional view illustrating the method for manufacturing the passive component;

(22) FIG. 8E is a schematic cross-sectional view illustrating the method for manufacturing the passive component;

(23) FIG. 8F is a schematic cross-sectional view illustrating the method for manufacturing the passive component;

(24) FIG. 8G is a schematic cross-sectional view illustrating the method for manufacturing the passive component;

(25) FIG. 8H is a schematic cross-sectional view illustrating the method for manufacturing the passive component;

(26) FIG. 8I is a schematic cross-sectional view illustrating the method for manufacturing the passive component;

(27) FIG. 9 is a schematic top view illustrating a third embodiment of a passive component viewed from a top surface side;

(28) FIG. 10 is a cross-sectional view taken along a line X-X of FIG. 9;

(29) FIG. 11A is a schematic cross-sectional view illustrating a method for manufacturing a passive component;

(30) FIG. 11B is a schematic cross-sectional view illustrating the method for manufacturing the passive component;

(31) FIG. 11C is a schematic cross-sectional view illustrating the method for manufacturing the passive component;

(32) FIG. 11D is a schematic cross-sectional view illustrating the method for manufacturing the passive component;

- (33) FIG. 11E is a schematic cross-sectional view illustrating the method for manufacturing the passive component;
- (34) FIG. 11F is a schematic cross-sectional view illustrating the method for manufacturing the passive component;
- (35) FIG. 11G is a schematic cross-sectional view illustrating the method for manufacturing the passive component;
- (36) FIG. 11H is a schematic cross-sectional view illustrating the method for manufacturing the passive component;
- (37) FIG. 11I is a schematic cross-sectional view illustrating the method for manufacturing the passive component;
- (38) FIG. 11J is a schematic cross-sectional view illustrating the method for manufacturing the passive component;
- (39) FIG. 12 is a schematic cross-sectional view illustrating a stacked semiconductor package; and
- (40) FIG. 13 is a schematic cross-sectional view illustrating a modification of a three-dimensional device.

DETAILED DESCRIPTION

(41) Hereinafter, a passive component, a three-dimensional device, and a method for manufacturing a passive component according to an aspect of the present disclosure will be described in detail with reference to embodiments illustrated in the accompanying drawings. Note that the accompanying drawings are partially schematic and do not reflect actual dimensions or ratios in some cases.

First Embodiment

1. Schematic Configuration of Passive Component 1

(42) FIG. 1 is a schematic bottom view of a passive component 1 viewed from the bottom surface side. FIG. 2 is a cross-sectional view taken along a line II-II of FIG. 1. FIG. 3 is a cross-sectional view taken along a line III-III of FIG. 1. Note that for the sake of convenience, in FIG. 1, an element body 10 is drawn to be transparent so that the structure can be easily understood, but may be translucent or opaque. Further, in FIG. 1, an insulator and an inorganic layer are omitted.

(43) The passive component 1 is, for example, a surface-mount passive component used in a high-frequency signal transmission circuit. The passive component 1 is an electronic component such as a resistor, a capacitor, or an inductor, and does not include an active element such as a transistor. In this embodiment, the passive component 1 is an inductor. As illustrated in FIG. 1 to FIG. 3, the passive component 1 includes a body portion 41 having a first main surface 41a and a second main surface 41b facing each other, and a passive element at least a part of which is provided inside the body portion 41. The passive element is an inductor element L. That is, the passive component includes the element body, the internal wiring, and the like, and the passive element represents, for example, a coil or the like in the passive component and does not include the element body or the like. The passive element includes an inductor element, a capacitor element, and a resistor element, and one of the inductor elements which includes a conductor winding around a central axis in a specific direction is defined as a coil.

(44) The body portion 41 holds the inductor element L. The shape of the body portion 41 is not particularly limited, and is a substantially rectangular parallelepiped shape in this embodiment. The body portion 41 has a length, a width, and a height. The body portion 41 has a first end surface and a second end surface on both end sides in the length direction, a first side surface and a second side surface on both end sides in the width direction, and a bottom surface and a top surface on both end sides in the height direction. In this embodiment, the bottom surface of the body portion 41 is the first main surface 41a of the body portion 41, and the top surface of the body portion 41 is the second main surface 41b of the body portion 41.

(45) The first main surface 41a of the body portion 41 at least partially includes a flat surface FS. The flat surface FS is made of an inorganic substance. In this embodiment, the entire first main

surface **41a** is the flat surface FS made of an inorganic substance. However, the present disclosure is not limited thereto, and only a part of the first main surface **41a** may be the flat surface FS made of an inorganic substance. The other part of the first main surface **41a** may be made of, for example, an organic substance and need not be the flat surface FS. Preferably, the area of the flat surface FS is equal to or greater than half the area of the first main surface **41a** of the body portion **41**. Thus, when the passive component **1** is bonded to another electronic component or the like via the flat surface FS, the bonding strength can be increased.

(46) In this specification, the term “flat” of the “flat surface” refers to a state in which the surface roughness of the flat surface is smaller than any one of equal to or less than 1/1000 of the thickness of the body portion of the passive component (the thickness of the body portion in a direction orthogonal to the first main surface of the body portion) and equal to or less than 10 nm. The “surface roughness” is Sa (arithmetic average height). “Flat” means, for example, a state in which Sa is 0.2 nm. An atomic force microscope (AFM) is used for measurement of Sa. The surface roughness is an average value of Sa at five points on the component surface.

(47) Examples of the “inorganic substance” include Si, SiN, SiO₂, Ge, GaN, GaP, GaAs, InP, Ti, TiN, Al, Au, Sn, Ta, Cu, and the like. According to this, the first main surface **41a** of the body portion **41** is easily flattened compared with a case where the first main surface **41a** of the body portion **41** is made of an organic substance. In addition, the hardness of the flat surface FS is high and the strength of the passive component **1** can be increased.

(48) According to the passive component **1**, since the first main surface **41a** of the body portion **41** at least partially includes the flat surface FS made of an inorganic substance, when the passive component **1** is bonded to another electronic component or the like having the flat surface FS, the flat surfaces FS can be bonded in a state of being in contact with each other. Therefore, it is possible to reduce the thickness of the entire device such as a stacked semiconductor package.

(49) Note that in this specification, “bonding in a state where the flat surfaces FS are in contact with each other” refers to room-temperature direct bonding by atomic diffusion or ionic bonding, hybrid bonding to which heat is applied, or the like. In addition, “bonding” may indicate a chemical bonding state such as a covalent bond, an ionic bond, or a metallic bond, or may refer to a mechanical bonding state.

2. Method for Manufacturing Passive Component **1**

(50) Next, a method for manufacturing the passive component **1** will be described.

(51) As illustrated in FIG. 2, an inorganic substrate **21** made of an inorganic substance and having a first main surface **21a** and a second main surface **21b** facing each other is prepared. Thereafter, the inductor element L is provided as a passive element on the second main surface **21b** side of the inorganic substrate **21** to form the body portion **41** including the inorganic substrate **21** and a part of the inductor element L. Thereafter, the first main surface **21a** of the inorganic substrate **21** is polished to provide the flat surface FS.

(52) According to this, since the first main surface **21a** of the inorganic substrate **21** includes the flat surface FS made of an inorganic substance, when the passive component **1** is bonded to another electronic component or the like having the flat surface FS, the flat surfaces FS can be bonded in a state of being in contact with each other. Therefore, it is possible to reduce the thickness of the entire device such as a stacked semiconductor package.

3. Preferred Embodiment

(53) Passive Component **1**

(54) The passive component **1** includes the element body **10**, a coil **110** provided on the element body **10** and spirally wound along an axis AX, the inorganic layer **21** provided on a first main surface (bottom surface **100b**) of the element body **10**, a first via wiring **121v** and a second via wiring **122v** penetrating the inorganic layer **21**, and an insulator **22** provided on a second main surface (top surface **100t**) of the element body **10**. The coil **110** constitutes the inductor element L. The element body **10**, the inorganic layer **21**, the first via wiring **121v**, and the second via wiring

122v constitute the body portion **41**. The first via wiring **121v** and the second via wiring **122v** correspond to “through-wirings” described in the claims.

(55) The element body **10** has a length, a width, and a height. The element body **10** has a first end surface **100e1** and a second end surface **100e2** on both end sides in the length direction, a first side surface **100s1** and a second side surface **100s2** on both end sides in the width direction, and the bottom surface **100b** and the top surface **100t** on both end sides in the height direction. In other words, an outer surface **100** of the element body **10** includes the first end surface **100e1** and the second end surface **100e2**, the first side surface **100s1** and the second side surface **100s2**, and the bottom surface **100b** and the top surface **100t**. The first end surface **100e1**, the second end surface **100e2**, the first side surface **100s1**, and the second side surface **100s2** constitute a part of the first end surface, a part of the second end surface, a part of the first side surface, and a part of the second side surface of the body portion **41** described above, respectively. The top surface **100t** constitutes the top surface of the body portion **41** described above.

(56) Note that as illustrated in the accompanying drawings, hereinafter, for convenience of description, the length direction (longitudinal direction) of the element body **10** is referred to as an X direction, a direction from the first end surface **100e1** toward the second end surface **100e2** is referred to as a forward X direction, and a direction opposite to the forward X direction is referred to as a reverse X direction. In addition, the width direction of the element body **10** is referred to as a Y direction, a direction from the first side surface **100s1** toward the second side surface **100s2** is referred to as a forward Y direction, and a direction opposite to the forward Y direction is referred to as a reverse Y direction. In addition, a height direction of the element body **10** is referred to as a Z direction, a direction from the bottom surface **100b** toward the top surface **100t** is referred to as a forward Z direction, and a direction opposite to the forward Z direction is referred to as a reverse Z direction. In this specification, the forward Z direction is defined as the upper side and the reverse Z direction is defined as the lower side. The X direction, the Y direction, and the Z direction are directions orthogonal to each other, and constitute a right-handed system when arranged in the order of X, Y, and Z.

(57) In this specification, the “outer surface **100** of the element body” including the first end surface **100e1**, the second end surface **100e2**, the first side surface **100s1**, the second side surface **100s2**, the bottom surface **100b**, and the top surface **100t** of the element body **10** does not simply mean a surface facing the outer peripheral side of the element body **10** but is a surface serving as a boundary between the outer side portion and the inner side portion of the element body **10**. In addition, “above the outer surface **100** of the element body **10**” does not refer to one absolute direction such as vertically above defined in the gravity direction, but refers to a direction toward the outer side portion, of the outer side portion and the inner side portion with the outer surface **100** as a boundary, with reference to the outer surface **100**. Therefore, “above the outer surface **100**” is a relative direction determined by an orientation of the outer surface **100**. In addition, the expression “above” an element includes not only a position above the element at a distance, that is, a position above the element via another object or a position above the element with a space therebetween, but also a position (on) immediately above the element in contact with the element.

(58) The axis AX of the coil **110** is arranged parallel to the bottom surface **100b**. In other words, the coil **110** has the central axis AX parallel to the first main surface **41a** of the body portion **41**. According to this configuration, when the first main surface **41a** of the body portion **41** is set as a mounting surface, the magnetic flux generated from the coil **110** is not directed to the mounting surface, and thus the inductor element L having a high Q value can be obtained.

(59) The coil **110** includes a plurality of first coil wirings (bottom surface wirings **11b**) provided on the bottom surface **100b** side with respect to the axis AX and arranged along the axis AX on a plane parallel to the bottom surface **100b**, a plurality of second coil wirings (top surface wirings **11t**) provided on the top surface **100t** side with respect to the axis AX and arranged along the axis AX on a plane parallel to the top surface **100t**, a plurality of first through-wirings **13** extending from the

bottom surface wiring **11b** toward the top surface wiring **11t** and arranged along the axis AX, and a plurality of second through-wirings **14** extending from the bottom surface wiring **11b** toward the top surface wiring **11t**, provided on the side opposite to the first through-wiring **13** with respect to the axis AX, and arranged along the axis AX. The bottom surface wiring **11b**, the first through-wiring **13**, the top surface wiring **11t**, and the second through-wiring **14** are connected in this order to form at least a part of a spiral shape.

(60) The axis AX is a line of intersection between a first plane passing through the center between the bottom surface wiring **11b** and the top surface wiring **11t** and a second plane passing through the center between the first through-wiring **13** and the second through-wiring **14**. That is, the axis AX is a straight line passing through the center of the inner diameter portion of the coil **110**. The axis AX of the coil **110** does not have a dimension in a direction orthogonal to the axis AX.

(61) The volume of the passive component **1** is equal to or less than 0.08 mm³, and the size of the long side of the passive component **1** is equal to or less than 0.65 mm. The size of the long side of the passive component **1** refers to the largest value of the length, the width, and the height of the passive component **1**, and refers to the length in the X direction in this embodiment. According to the above configuration, since the volume of the passive component **1** is small and the long side of the passive component **1** is also short, the weight of the passive component **1** can be reduced. In addition, the thickness of the passive component **1** is preferably equal to or less than 200 nm. Thus, the passive component **1** can be made thin.

(62) To be specific, the size (length (X direction)×width (Y direction)×height (Z direction)) of the passive component **1** is 0.6 mm×0.3 mm×0.3 mm, 0.4 mm×0.2 mm×0.2 mm, 0.25 mm×0.125 mm×0.120 mm or the like. Further, the width and the height need not be equal to each other, and may be, for example, 0.4 mm×0.2 mm×0.3 mm or the like.

(63) Element Body **10**

(64) The element body **10** is made of an insulating resin. As the insulating resin, for example, a photosensitive permanent film (permanent photoresist) or an insulating resin containing an inorganic filler is used. A photosensitive permanent film is a photoresist that is not removed after processing.

(65) Note that the element body **10** may be made of, for example, a glass sintered body or a glass substrate. The glass substrate may be a single-layer glass substrate, and since most of the element body is made of glass, loss such as eddy current loss at high frequencies can be suppressed.

(66) Coil **110**

(67) The coil **110** includes a plurality of bottom surface wirings **11b**, a plurality of top surface wirings **11t**, a plurality of first through-wirings **13**, and a plurality of second through-wirings **14**. The bottom surface wiring **11b**, the first through-wiring **13**, the top surface wiring **11t**, and the second through-wiring **14** are connected in order and constitute at least a part of the coil **110** wound in the axis AX direction.

(68) According to the above-described configuration, since the coil **110** is the coil **110** having a so-called helical shape, it is possible to reduce a region in which the bottom surface wiring **11b**, the top surface wiring **11t**, the first through-wiring **13**, and the second through-wiring **14** run in parallel along the winding direction of the coil **110** in the cross section orthogonal to the axis AX, and it is possible to reduce stray capacitance in the coil **110**.

(69) Here, the helical shape refers to a shape in which the number of turns of the entire coil is greater than one turn and the number of turns of the coil in a cross section orthogonal to the axis is less than one turn. The term “one turn or more” refers to a state having a portion in which the wirings of the coil adjacent to each other in the radial direction run in parallel in the winding direction when viewed in the axial direction in a cross section orthogonal to the axis, and the term “less than one turn” refers to a state that does not have a portion in which the wirings of the coil adjacent to each other in the radial direction run in parallel in the winding direction when viewed in the axial direction in a cross section orthogonal to the axis.

(70) The bottom surface wiring **11b** extends in the Y direction while being slightly inclined in the X direction. The bottom surface wiring **11b** is embedded in the element body **10** so as to be exposed from the bottom surface **100b**. The plurality of bottom surface wirings **11b** is arranged in parallel along the X direction. When viewed from a direction orthogonal to the bottom surface **100b**, the bottom surface wirings **11b** at both ends in the axis AX direction are formed in a triangular shape, and the other bottom surface wirings **11b** are formed in a linear shape.

(71) The top surface wiring **11t** has a shape extending in the Y direction. The top surface wiring **11t** is provided on the top surface **100t**. The plurality of top surface wirings **11t** is arranged in parallel along the X direction. When viewed from a direction orthogonal to the bottom surface **100b**, the top surface wirings **11t** at both ends in the axis AX direction are formed in a quadrangular shape, and the other top surface wirings **11t** are formed in a linear shape.

(72) The bottom surface wiring **11b** and the top surface wiring **11t** are made of a good conductor material such as Cu, Ag, Au, or alloys thereof. The bottom surface wiring **11b** and the top surface wiring **11t** may be a metallic film formed by plating, vapor deposition, sputtering, or the like, or may be a metallic sintered body obtained by applying and sintering conductive paste. Further, the bottom surface wiring **11b** and the top surface wiring **11t** may have a multilayer structure in which a plurality of metallic layers is stacked. The thicknesses of the bottom surface wiring **11b** and the top surface wiring **11t** are preferably equal to or more than 5 μm and equal to or less than 50 μm (i.e., from 5 μm to 50 μm).

(73) The first through-wiring **13** is arranged on the first side surface **100s1** side with respect to the axis AX in a through-hole V of the element body **10**, and the second through-wiring **14** is arranged on the second side surface **100s2** side with respect to the axis AX in the through-hole V of the element body **10**. The first through-wiring **13** and the second through-wiring **14** extend in a direction orthogonal to the bottom surface **100b** and the top surface **100t**, respectively. According to this configuration, since the lengths of the first through-wiring **13** and the second through-wiring **14** can be shortened, the direct-current resistance (R_{dc}) can be suppressed. All the first through-wirings **13** and all the second through-wirings **14** are arranged parallel to each other along the X direction. The first through-wiring **13** and the second through-wiring **14** are made of the same material as the bottom surface wiring **11b** and the top surface wiring **11t**.

(74) Inorganic Layer **21**

(75) The inorganic layer **21** is provided on the bottom surface **100b** of the element body **10** and covers the exposed portion of the bottom surface wiring **11b** from the bottom surface **100b**. Thus, the bottom surface wiring **11b** is protected from an external force, the bottom surface wiring **11b** is prevented from being damaged, and the insulating property of the bottom surface wiring **11b** is improved. The inorganic layer **21** is made of an inorganic substance. The inorganic substance is, for example, Si, SiN, SiO.sub.2, Ge, GaN, GaP, GaAs, InP, Ti, TiN, Al, Au, Sn, Ta, Cu, or the like, similar to the above-described inorganic substance of the flat surface FS. The inorganic layer **21** has the first main surface **21a** and the second main surface **21b** facing each other. The first main surface **21a** of the inorganic layer **21** constitutes a part of the first main surface **41a** of the body portion **41**. The second main surface **21b** is in contact with the bottom surface **100b** of the element body **10**.

(76) Insulator **22**

(77) The insulator **22** is provided on the top surface **100t** of the element body **10** and covers the top surface wiring **11t**. Thus, the top surface wiring **11t** is protected from an external force, the top surface wiring **11t** is prevented from being damaged, and the insulating property of the top surface wiring **11t** is improved. The insulator **22** is preferably an organic insulator. For example, the insulator **22** may be a resin film such as an epoxy-based or a polyimide-based resin film that can be easily formed.

(78) First Via Wiring **121v** and Second Via Wiring **122v**

(79) The first via wiring **121v** is connected to a first end portion of the coil **110**, and the second via

wiring **122v** is connected to a second end portion of the coil **110**. That is, the first via wiring **121v** and the second via wiring **122v** are not included in the coil **110**. The first via wiring **121v** is provided on the first end surface **100e1** side with respect to the center of the element body **10** in the X direction. The second via wiring **122v** is provided on the second end surface **100e2** side with respect to the center of the element body **10** in the X direction.

(80) The first via wiring **121v** is embedded in the inorganic layer **21** and exposed from the first main surface **21a** of the inorganic layer **21**. The first via wiring **121v** penetrates the inorganic layer **21** from the first main surface **21a** to the second main surface **21b** of the inorganic layer **21**. The first via wiring **121v** is connected to an end portion of the bottom surface wiring **11b** located on the first end surface **100e1** side in the axis AX direction.

(81) The second via wiring **122v** is embedded in the inorganic layer **21** and exposed from the first main surface **21a** of the inorganic layer **21**. The second via wiring **122v** penetrates the inorganic layer **21** from the first main surface **21a** to the second main surface **21b** of the inorganic layer **21**. The second via wiring **122v** is connected to an end portion of the bottom surface wiring **11b** located on the second end surface **100e2** side in the axis AX direction.

(82) Preferably, the first main surface **21a** of the inorganic layer **21**, the exposed surface **121a** of the first via wiring **121v** exposed from the first main surface **21a** of the inorganic layer **21**, and an exposed surface of the second via wiring **122v** (not illustrated) exposed from the first main surface **21a** of the inorganic layer **21** constitute the first main surface **41a** of the body portion **41**.

According to this configuration, an electric signal can be extracted from the passive component **1** through the first via wiring **121v** and the second via wiring **122v**.

(83) Preferably, the first via wiring **121v** and the second via wiring **122v** are made of an inorganic substance, and an exposed surface **121a** of the first via wiring **121v** exposed from the first main surface **21a** of the inorganic layer **21** and an exposed surface (not illustrated) of the second via wiring **122v** exposed from the first main surface **21a** of the inorganic layer **21** constitute at least a part of the flat surface FS. The inorganic substance in the first via wiring **121v** and the second via wiring **122v** is, for example, a conductive material selected from Si, SiN, SiO.sub.2, Ge, GaN, GaP, GaAs, InP, Ti, TiN, Al, Au, Sn, Ta, Cu, and the like. When the first via wiring **121v** and the second via wiring **122v** are made of an inorganic substance, it is preferable that the first via wiring **121v** and the second via wiring **122v** do not include a void from the viewpoint of reducing the electrical resistance.

(84) According to the above-described configuration, since the exposed surfaces of the first via wiring **121v** and the second via wiring **122v** are flat surfaces, when it is bonded to another electronic component or the like having a flat surface, in the case where a part of the wiring is exposed from the flat surface in the other electronic component and the exposed surface is also a flat surface, the wiring of the other electronic component can be directly connected to the first via wiring **121v** and the second via wiring **122v**.

(85) Preferably, the inorganic layer **21** is amorphous or single crystal. A scanning transmission electron microscope (STEM), an X-ray diffractometer (XRD), or the like is used to determine whether it is amorphous or single crystal. According to this configuration, the flat surface FS can be easily obtained. In the case where the inorganic layer **21** is a sintered body of ferrite or the like, unevenness may occur on the first main surface **21a** of the inorganic layer **21**.

(86) Preferably, the body portion **41** includes the inorganic layer **21** made of an inorganic substance and having the first main surface **21a** and the second main surface **21b** facing each other and an organic insulating layer provided on the second main surface **21b** of the inorganic layer **21**, the first main surface **21a** of the inorganic layer **21** constitutes at least a part of the first main surface **41a** of the body portion **41**, the passive element includes the inductor element L having the coil **110**, and the coil **110** is in contact with both the inorganic layer **21** and the organic insulating layer.

Specifically, as illustrated in FIG. 2, preferably, the element body **10** is made of an organic insulating layer, and the coil **110** is in contact with both the inorganic layer **21** and the organic

insulating layer of the element body **10**.

(87) According to the above-described configuration, since the organic insulating layer of the element body **10** can support the coil **110**, the diameter of the coil **110** can be increased. In addition, since the inorganic layer **21** has a coefficient of linear expansion smaller than that of the organic insulating layer of the element body **10**, the stress of the body portion **41** can be relaxed as compared with the case where the coil **110** is in contact with only the organic insulating layer of the element body **10**.

(88) Preferably, the body portion **41** includes the inorganic layer **21** having the first main surface **21a** and the second main surface **21b** facing each other, the first main surface **21a** of the inorganic layer **21** constitutes at least a part of the first main surface **41a** of the body portion **41**, and the thickness of the inorganic layer **21** in the direction (Z direction) orthogonal to the first main surface **41a** of the body portion **41** is smaller than the thickness of the passive element in the direction orthogonal to the first main surface **41a** of the body portion **41**. According to this configuration, the passive component **1** can be made thinner.

(89) Preferably, as illustrated in FIG. 2, the body portion **41** includes the inorganic layer **21** made of an inorganic substance and having the first main surface **21a** and the second main surface **21b** facing each other, the first main surface **21a** of the inorganic layer **21** constitutes at least a part of the first main surface **41a** of the body portion **41**, the passive element includes the coil **110** having the central axis parallel to the first main surface **41a** of the body portion **41**, and a thickness $t2$ of the inorganic layer **21** in a direction orthogonal to the first main surface **41a** of the body portion **41** is smaller than a thickness $t1$ of the coil **110** in a direction orthogonal to the first main surface **41a** of the body portion **41**. According to this configuration, the passive component **1** including the inductor element **L** can be made thinner.

(90) Preferably, the body portion **41** has the second main surface **41b** opposed to the first main surface **41a**, and further includes the insulator **22** which is made of an organic insulating resin and provided on the second main surface **41b** of the body portion **41**, at least a part of the passive element is exposed from the second main surface **41b** of the body portion **41**, and an exposed portion of the passive element exposed from the second main surface **41b** of the body portion **41** is covered with the insulator **22**. Specifically, as illustrated in FIG. 2, the insulator **22** is made of an organic insulating resin, and the top surface wiring **11t** of the coil **110** of the inductor element **L** is exposed from the second main surface **41b** of the body portion **41** and is covered with the insulator **22**. According to this configuration, since the insulating member **22** is made of an organic insulating resin, adhesion of the insulator **22** to the top surface wiring **11t** is improved, and the inductor element **L** can be more effectively protected from the external environment.

(91) Method for Manufacturing Passive Component **1**

(92) Next, a method for manufacturing the passive component **1** will be described with reference to FIG. 4A to FIG. 4K. FIG. 4A, FIG. 4B, FIG. 4C, FIG. 4J, and FIG. 4K are views corresponding to the III-III cross section of FIG. 1. FIG. 4D to FIG. 4I are views corresponding to the II-II cross section of FIG. 1.

(93) As illustrated in FIG. 4A, an inorganic substrate **1021** corresponding to the inorganic layer **21** is prepared. The inorganic substrate **1021** is, for example, an Si substrate. A first resist layer **1001** is applied to the upper surface of the inorganic substrate **1021**, and a cavity **1001a** having a predetermined pattern is formed in the first resist layer **1001** by a photolithography process.

(94) As illustrated in FIG. 4B, the inorganic substrate **1021** is etched through the cavity **1001a** to form a groove **1021a**. The etching may be either dry etching or wet etching. In the present embodiment, since an Si substrate is used as the inorganic substrate **1021**, plasma etching using a fluorine-based gas is used.

(95) Thereafter, the first resist layer **1001** is peeled off, a seed layer (not illustrated) is formed on the upper surface of the inorganic substrate **1021** as illustrated in FIG. 4C and FIG. 4D, a second resist layer **1002** is applied on the upper surface of the seed layer, and a cavity **1002a** having a

predetermined pattern is formed in the second resist layer **1002** by the photolithography process. Then, by electrolytic plating, a bottom surface conductor layer **1011b** corresponding to the bottom surface wiring **11b** is provided in the cavity **1002a**, and a first via conductor layer **1121v** corresponding to the first via wiring **121v** is provided in the groove **1021a**. In addition, although not illustrated, a second via conductor layer corresponding to the second via wiring **122v** is provided in the same manner as the first via conductor layer **1121v**.

(96) Although a semi-additive method is used as a method of forming the bottom surface conductor layer and the via conductor layer in the present embodiment, a known method such as a subtractive method, a full additive method, a damascene method, a dual damascene method, or a printing method of conductive paste may be used. In the present embodiment, Ti/Cu is used for the seed layer, but a seed species such as W, TiW, or Ag and a combination thereof may be selected as necessary.

(97) Thereafter, the second resist layer **1002** is peeled off, and the seed layer is etched to provide an insulating resin layer **1010** corresponding to the element body **10** on the upper surface of the inorganic substrate **1021** as illustrated in FIG. 4E. A cavity **1010a** having a predetermined pattern is formed in the insulating resin layer **1010** by a photolithography process, a part of the bottom surface conductor layer **1011b** is exposed from the cavity **1010a**, and the insulating resin layer **1010** is cured. In the present embodiment, a photosensitive permanent film is used as the insulating resin layer **1010**, but for example, an insulating resin containing an inorganic filler may be used to form a cavity by a laser method or a blast method, or an inorganic insulating layer may be deposited by CVD or the like and a cavity may be formed by an etching method or the like.

(98) As illustrated in FIG. 4F, a second through-conductor layer **1014** corresponding to the second through-wiring **14** is formed in the cavity **1010a** of the insulating resin layer **1010**. In addition, although not illustrated, a first through-conductor layer corresponding to the first through-wiring **13** is provided similar to the second through-conductor layer **1014**. To be specific, in the present embodiment, a seed layer of Ti/Cu is formed on the upper surface of the insulating resin layer **1010** and the inner surface of the cavity **1010a** by anisotropic sputtering. Thereafter, filling plating is performed, and the upper surface of the insulating resin layer **1010** is planarized by chemical mechanical polishing (CMP), mechanical polishing, or the like. In the case of mechanical polishing, the upper surface of the insulating resin layer **1010** is planarized by processing with dry etching or chemical etching after mechanical polishing in order to keep the surface roughness within a predetermined range. Note that as another method of forming the through-conductor layer, a conductive portion may be provided in the bottom surface conductor layer in advance, and power may be supplied from the conductive portion to form the through-conductor layer by an electrolytic plating method.

(99) Thereafter, a seed layer (not illustrated) is formed on the upper surface of the insulating resin layer **1010**, a resist layer (not illustrated) is applied on the upper surface of the seed layer, and a cavity having a predetermined pattern is formed in the resist layer by a photolithography process. Then, a top surface conductor layer **1011t** corresponding to the top surface wiring **11t** is provided in the cavity by electrolytic plating, the resist layer is peeled off, and the seed layer is etched as illustrated in FIG. 4G.

(100) As illustrated in FIG. 4H, an insulating layer **1022** corresponding to the insulator **22** is provided on the upper surface of the insulating resin layer **1010** so as to cover the top surface conductor layer **1011t**, and the insulating layer **1022** is cured. The insulating layer **1022** may be the same resin as the insulating resin layer **1010**, or may be different resin. Since the insulating layer **1022** is in contact with the outside, it is preferable to use resin having excellent water resistance or resin having high hardness as compared with the insulating resin layer **1010**, and it is further preferable to use resin containing an inorganic filler or the like, whereby the insulating property is improved. Furthermore, the insulating layer **1022** is preferably formed using resin having the higher light-blocking property (shielding property) than the insulating resin layer **1010**.

(101) As illustrated in FIG. 4I and FIG. 4J, the inorganic substrate **1021** is polished to expose the end surface of the first via conductor layer **1121v** and the end surface of the second via conductor layer. CMP is preferred for polishing the inorganic substrate **1021**. Note that when necessary, the insulating layer **1022** may be polished for adjustment of thickness.

(102) As illustrated in FIG. 4K, singulation is performed along a cut line C. Thus, as illustrated in FIG. 3, the passive component **1** is manufactured.

Second Embodiment

(103) Configuration of Passive Component **1A**

(104) FIG. 5 is a schematic top view illustrating a second embodiment of the passive component viewed from the top surface side. FIG. 6 is a cross-sectional view taken along a line VI-VI of FIG. 5. FIG. 7 is an enlarged view of part A of FIG. 6. The second embodiment is different from the first embodiment in the configuration of the coil and the configuration of the element body. This different configuration will be described below. The other configurations are the same as those of the first embodiment, and are denoted by the same reference signs as those of the first embodiment, and description thereof is omitted.

(105) As illustrated in FIG. 5 to FIG. 7, a passive component **1A** includes the element body **10**, a coil **110A**, an organic insulating portion **23**, a first connection wiring **51**, and a second connection wiring **52** provided inside the element body **10**, and the inorganic layer **21** provided on the bottom surface **100b** of the element body **10**. The element body **10** includes a first magnetic layer **101** and a second magnetic layer **102** stacked in the forward Z direction. The lower surface of the second magnetic layer **102** corresponds to the bottom surface **100b** of the element body **10**. In this embodiment, the element body **10** corresponds to the “magnetic portion” recited in the claims.

(106) The coil **110A** is provided on an upper surface **101u** of the first magnetic layer **101** and has a planar spiral shape. The coil **110A** is spirally wound in the clockwise direction from an outer peripheral end **110e1** toward an inner peripheral end **110e2** when viewed from the Z direction. In other words, the coil **110A** is wound along a plane parallel to the first main surface **41a** of the body portion **41**. The coil **110A** has the central axis AX orthogonal to the first main surface **41a** of the body portion **41**. According to this configuration, the inductor element L can be made thinner than in the case where the coil **110A** has the central axis parallel to the first main surface **41a** of the body portion **41**. As a result, the passive component **1A** can be made thinner.

(107) The number of turns of the coil **110A** is preferably more than one. Thus, the inductance can be improved. The outer peripheral end **110e1** has a substantially rectangular shape. The inner peripheral end **110e2** has a substantially circular shape. Each of the width of the outer peripheral end **110e1** in the X direction and the diameter of the inner peripheral end **110e2** is larger than the wiring width of the winding portion of the coil **110A** excluding the outer peripheral end **110e1** and the inner peripheral end **110e2**. Accordingly, the outer peripheral end **110e1** and the inner peripheral end **110e2** function as pad portions, and the connection reliability with the first connection wiring **51** and the second connection wiring **52** is improved. The coil **110A** does not include the first connection wiring **51**, the second connection wiring **52**, the first via wiring **121v**, and the second via wiring **122v**.

(108) The coil **110A** is covered with the element body **10** (magnetic portion). According to this configuration, the inductance of the inductor element L can be improved. The conductive material of the coil **110A** may be the same as the conductive material of the bottom surface wiring **11b** and the top surface wiring **11t** in the first embodiment.

(109) The organic insulating portion **23** is provided at least on a side surface **110s** orthogonal to the first main surface **41a** of the body portion **41** in the coil **110A**. In this embodiment, the organic insulating portion **23** is provided on the outer peripheral surface of a portion of the coil **110A** constituting one turn of the coil **110A** including the outer peripheral end **110e1**, on the inner peripheral surface of a portion of the coil **110A** constituting one turn of the coil **110A** including the inner peripheral end **110e2**, and between respective turns of the coil **110A**. The material of the

organic insulating portion **23** is, for example, a photosensitive permanent film.

(110) The element body **10** covers the coil **110A** and the organic insulating portion **23**. The coil **110A** is in contact with the organic insulating portion **23** and the element body **10**. To be specific, an upper surface **110u** of the coil **110A** is in contact with the second magnetic layer **102**, a lower surface **110b** of the coil **110A** is in contact with the first magnetic layer **101**, and the side surface **110s** of the coil **110A** is in contact with the organic insulating portion **23**. According to this configuration, the inductance of the inductor element **L** can be improved by the element body **10**, and the inter-wiring leakage in the XY plane can be suppressed by the organic insulating portion **23** provided on the side surface **110s** of the coil **110A**. In particular, since the organic insulating portion **23** is provided between the respective turns of the coil **110A**, it is possible to suppress the inter-wiring leakage that may occur between the respective turns.

(111) The first magnetic layer **101** and the second magnetic layer **102** are, for example, a composite material containing an epoxy resin, an Fe-based metal filler, and a glass filler. Whereby, it is possible to obtain high DC superposition characteristics while improving inductance, and it is possible to suppress cracks that may occur in the element body **10** by the epoxy resin. The resin of the first magnetic layer **101** and the second magnetic layer **102** is not limited to the epoxy resin, and may be imide-based resin, phenol-based resin, or the like. The Fe-based metal filler may be FeSi-based metal filler, FeCo-based metal filler, FeNi-based metal filler, or the like. In addition, for the first magnetic layer **101** and the second magnetic layer **102**, magnetic materials formed by sputtering or the like may be used, or a magnetic block may be inserted into the core portion of the coil **110A**.

(112) The first connection wiring **51** penetrates the first magnetic layer **101** in the Z direction and connects the outer peripheral end **110e1** of the coil **110A** and the first via wiring **121v**. The second connection wiring **52** penetrates the first magnetic layer **101** in the Z direction and connects the inner peripheral end **110e2** of the coil **110A** and the second via wiring **122v**. According to this configuration, an electric signal of the coil **110A** can be extracted via the first connection wiring **51** and the second connection wiring **52**. The conductive material of the first connection wiring **51** and the second connection wiring **52** is not particularly limited, but is the same as the conductive material of the coil **110A**, for example.

(113) In this embodiment, the first main surface **41a** of the body portion **41** includes the first main surface **21a** of the inorganic layer **21** and the exposed surfaces of the first via wiring **121v** and the second via wiring **122v** from the first main surface **21a** of the inorganic layer **21**, and the entire first main surface **41a** of the body portion **41** is the flat surface FS made of an inorganic substance. According to this configuration, when it is bonded to another electronic component or the like having the flat surface FS, the flat surfaces FS can be bonded in a state of being in contact with each other. Therefore, it is possible to reduce the thickness of the entire device such as a stacked semiconductor package.

(114) Preferably, as illustrated in FIG. 7, a thickness **t3** of the organic insulating portion **23** in a direction orthogonal to the first main surface **41a** of the body portion **41** is greater than a thickness **t4** of the coil **110A** in a direction orthogonal to the first main surface **41a** of the body portion **41**. According to this configuration, the inter-wiring leakage in the XY plane can be further suppressed. In particular, the inter-wiring leakage that may occur between the respective turns can be further suppressed. The thickness **t3** is, for example, 35 μm . The thickness **t4** is, for example, 30 μm . A thickness **t5** of the inorganic layer **21** is, for example, 1 μm . A thickness **t6** of the first magnetic layer **101** is, for example, 20 μm . A thickness **t7** of the second magnetic layer **102** is, for example, 50 μm .

(115) Method for Manufacturing Passive Component **1A**

(116) Next, a method for manufacturing the passive component **1A** will be described with reference to FIG. 8A to FIG. 8I. FIG. 8A to FIG. 8I are views corresponding to the VI-VI cross section of FIG. 5.

(117) As illustrated in FIG. 8A, the inorganic substrate **1021** corresponding to the inorganic layer **21** is prepared. The inorganic substrate **1021** is, for example, an Si substrate. A first resist layer **1001** is applied to the upper surface of the inorganic substrate **1021**, and the cavity **1001a** having a predetermined pattern is formed in the first resist layer **1001** by a photolithography process.

(118) As illustrated in FIG. 8B, the inorganic substrate **1021** is etched through the cavity **1001a** to form the groove **1021a**. The etching may be either dry etching or wet etching. In the present embodiment, since an Si substrate is used as the inorganic substrate **1021**, plasma etching using a fluorine-based gas is used.

(119) As illustrated in FIG. 8C, the first resist layer **1001** is peeled off, a seed layer (not illustrated) is formed on the upper surface of the inorganic substrate **1021**, and a conductive material of the first via wiring **121v** and the second via wiring **122v** is used to form a film (solid coating) on the upper surface of the seed layer by electrolytic plating so as to cover the groove **1021a**. As a result, the first via conductor layer **1121v** corresponding to the first via wiring **121v** and a second via conductor layer **1122v** corresponding to the second via wiring **122v** are formed in the groove **1021a**. Further, a solid film **1020** is formed on the upper surface of the inorganic substrate **1021**. In the present embodiment, Ti/Cu is used for the seed layer, but a seed species such as W, TiW, or Ag and a combination thereof may be selected as necessary.

(120) As illustrated in FIG. 8D, the solid film **1020** is removed by etching. The solid film **1020** may be removed by CMP or polishing.

(121) As illustrated in FIG. 8E, a first magnetic sheet **1101** corresponding to the first magnetic layer **101** is performed thermocompression bonding to the upper surface of the inorganic substrate **1021**. Thereafter, the first magnetic sheet **1101** is ground as necessary. The first magnetic sheet **1101** may be formed by printing, sputtering, or the like. Thereafter, an opening **1101a** is formed at a predetermined position of the first magnetic sheet **1101** by using a laser. The predetermined position is a position corresponding to a connection portion between the first connection wiring **51** and the first via wiring **121v** and a connection portion between the second connection wiring **52** and the second via wiring **122v**. The opening **1101a** may be formed by photolithography, an etching method, or the like.

(122) As illustrated in FIG. 8F, a seed layer is formed on the upper surface of the first magnetic sheet **1101** and the inner surface of the opening **1101a** using a sputtering method. Thereafter, a resist layer (not illustrated) is applied, and a cavity having a predetermined pattern is formed in the resist layer by a photolithography process. The seed layer is then etched to form a patterned seed layer **600**. The seed layer **600** is formed at a predetermined position on the upper surface of the first magnetic sheet **1101** and on the inner surface of the opening **1101a**. The predetermined position is a position at which the coil **110A** is provided. Thereafter, a photosensitive permanent film is applied, and an organic insulating layer **1023** corresponding to the organic insulating portion **23** is formed by a photolithography process.

(123) Here, when the above seed layer is etched, the resin or the magnetic powder on the upper surface of the first magnetic sheet **1101** may be intentionally dissolved by the etching liquid. Accordingly, it is possible to form a boundary portion with a small amount of magnetic powder between the first magnetic sheet **1101** and the wiring layer, between the first magnetic sheet **1101** and a second magnetic sheet **1102** to be described later, or the like. An air gap can be formed by the boundary portion, and DC superposition characteristics can be improved. The boundary portion is preferably formed at least in a contact portion between the first magnetic layer **101** and the second magnetic layer **102** in FIG. 6, for example.

(124) As illustrated in FIG. 8G, a first connection wiring conductor layer **1051** corresponding to the first connection wiring **51**, a second connection wiring conductor layer **1052** corresponding to the second connection wiring **52**, and a coil conductor layer **1110** corresponding to the coil **110A** are formed on the upper surface of the seed layer **600** by electrolytic plating. The conductive material of the first connection wiring conductor layer **1051**, the second connection wiring conductor layer

1052, and the coil conductor layer **1110** is, for example, Cu. Here, as in the etching of the above seed layer, a boundary portion having a small amount of magnetic powder may be formed between the first magnetic sheet **1101** and the wiring layer, between the first magnetic sheet **1101** and the second magnetic sheet **1102**, or the like by the above electrolytic plating.

(125) As illustrated in FIG. **8H**, the second magnetic sheet **1102** corresponding to the second magnetic layer **102** is performed thermocompression bonding so as to cover the coil conductor layer **1110** and the organic insulating portion **23**. Thereafter, the second magnetic sheet **1102** is ground as necessary. Thereafter, the inorganic substrate **1021** is polished to expose the end surface of the first via conductor layer **1121v** and the end surface of the second via conductor layer **1122v**. CMP is preferred for polishing the inorganic substrate **1021**.

(126) As illustrated in FIG. **8I**, singulation is performed along the cut line C. Thus, as illustrated in FIG. **6**, the passive component **1A** is manufactured.

Third Embodiment

(127) Configuration of Passive Component **1B**

(128) FIG. **9** is a schematic top view illustrating a third embodiment of the passive component viewed from the top surface side. FIG. **10** is a cross-sectional view taken along a line X-X of FIG. **9**. The third embodiment is different from the second embodiment mainly in the configuration of the element body, in that the capacitor element and the resistor element are further provided, and in that the second main surface of the body portion is a flat surface. This different configuration will be described below. The other configurations are the same as those of the second embodiment, and are denoted by the same reference signs as those of the second embodiment, and description thereof is omitted.

(129) A passive component **1B** is an electronic component including passive elements such as the inductor element L, a capacitor element C, and a resistor element R. The inductor element L and the capacitor element C are electrically connected in series to each other. The resistor element R is electrically independent from the inductor element L and the capacitor element C. As illustrated in FIG. **9** and FIG. **10**, when viewed from the Z direction, the inductor element L and the capacitor element C are arranged on the first end surface **100e1** side with respect to the center of the element body **10**, and the resistor element R is arranged on the second end surface **100e2** side with respect to the center of the element body **10**.

(130) The body portion **41** includes the element body **10** and the inorganic layer **21** provided on the bottom surface **100b** of the element body **10**. The element body **10** includes a first insulating layer **111** provided on the second main surface **21b** of the inorganic layer, the capacitor element C, a third connection wiring **53**, and a fourth connection wiring **54** provided inside the first insulating layer **111**, a second insulating layer **112** provided on the first insulating layer **111**, and the inductor element L, a fifth connection wiring **55**, and a sixth connection wiring **56** provided inside the second insulating layer **112**.

(131) The first insulating layer **111** electrically insulates the capacitor element C and the resistor element R from each other. The material of the first insulating layer **111** is not particularly limited, but is, for example, SiO₂. The capacitor element C includes a first capacitor electrode **71** and a second capacitor electrode **72** opposed to each other in the Z direction, and a dielectric layer **73** arranged between the first capacitor electrode **71** and the second capacitor electrode **72**. The first capacitor electrode **71** is provided on the second main surface **21b** of the inorganic layer **21** so as to cover the first via wiring **121v**, and is connected to the first via wiring **121v**. The dielectric layer **73** is provided so as to cover the first capacitor electrode **71**. An end portion of the dielectric layer **73** on the forward X direction side extends to the vicinity of the second end surface **100e2** of the element body **10**. The second capacitor electrode **72** is provided on the dielectric layer **73**. The second capacitor electrode **72** is arranged so as to overlap the first capacitor electrode **71** when viewed from the Z direction.

(132) The conductive material of the first capacitor electrode **71** and the second capacitor electrode

72 is not particularly limited and is, for example, **Al**. Preferably, the conductive material of the first and second capacitor electrodes **71** and **72** is different from the conductive material of each of the first and second via wirings **121v** and **122v** and the coil **110A**. Thus, by using different conductive materials for the first and second capacitor electrodes **71** and **72** through which no direct current flows and the first and second via wirings **121v** and **122v** and the coil **110A** through which a direct current flows, it is possible to reduce the manufacturing cost without deteriorating the characteristics of the passive component **1B**. More specifically, since **Al** has low electrical conductivity but is inexpensive, it is preferable to use **Al** for the first and second capacitor electrodes **71** and **72** of the capacitor element **C** which is a voltage element. In addition, **Cu** having high electrical conductivity is preferably used for the coil **110A** of the inductor element **L** which is a current element, and the first and second via wirings **121v** and **122v**. Thus, the manufacturing cost can be reduced without deteriorating the characteristics of the passive component **1B**.

(133) The material of the dielectric layer **73** is not particularly limited and is, for example, **SiO.sub.2**. The material of the dielectric layer **73** may be, for example, a high-k material such as **HfO.sub.2** or **Y.sub.2O.sub.3**. Thus, the capacitance of the capacitor element **C** can be increased. Preferably, the material of the dielectric layer **73** is the same as the material of the second insulating layer **112**. Accordingly, since the material of the dielectric layer **73** is the same as the material of the second insulating layer **112** that covers at least the coil **110A**, the manufacturing cost of the passive component **1B** can be reduced. In addition, it is possible to reduce residual stresses that may occur in the passive component **1B**.

(134) The second insulating layer **112** electrically insulates the inductor element **L** and the resistor element **R** from each other. The material of the second insulating layer **112** is an insulating inorganic substance, such as **SiO.sub.2**. The second insulating layer **112** may be made of a magnetic material.

(135) The third connection wiring **53** penetrates the first insulating layer **111** in the **Z** direction and connects the second capacitor electrode **72** and the outer peripheral end **110e1** of the coil **110A**. The fourth connection wiring **54** passes through the first insulating layer **111** and the dielectric layer **73** in the **Z** direction and connects the second via wiring **122v** and the sixth connection wiring **56**. The fifth connection wiring **55** penetrates the second insulating layer **112** in the **Z** direction. The end surface on the reverse **Z** direction side of the fifth connection wiring **55** is connected to the inner peripheral end **110e2** of the coil **110A**, and the end surface on the forward **Z** direction side of the fifth connection wiring **55** is exposed from the upper surface of the second insulating layer **112** (the top surface **100t** of the element body **10**). The coil **110A** does not include the third connection wiring **53** and the fifth connection wiring **55**. The sixth connection wiring **56** penetrates the second insulating layer **112** in the **Z** direction. The end surface of the sixth connection wiring **56** on the reverse **Z** direction side is connected to the upper surface of the fourth connection wiring **54**, and the end surface of the sixth connection wiring **56** on the forward **Z** direction side is exposed from the upper surface of the second insulating layer **112**.

(136) The conductive material of the third connection wiring **53** and the fourth connection wiring **54** is not particularly limited, but is the same as the conductive material of the coil **110A**, for example. The conductive material of the fifth connection wiring **55** and the sixth connection wiring **56** is a conductive inorganic substance.

(137) By connecting the first via wiring **121v**, the capacitor element **C**, the third connection wiring **53**, the coil **110A**, and the fifth connection wiring **55** in this order, the capacitor element **C** and the inductor element **L** are electrically connected in series.

(138) The second via wiring **122v**, the fourth connection wiring **54**, and the sixth connection wiring **56** are connected in this order to form a conduction wiring **81**. The conduction wiring **81** extends from the first main surface **41a** to the second main surface **41b** of the body portion **41**, and both end portions thereof in the extending direction are exposed from the first main surface **41a** and the second main surface **41b** of the body portion **41**. According to this configuration, since electric

signals can be extracted from both the first main surface **41a** and the second main surface **41b** of the body portion **41** via the conduction wiring **81**, electronic components and the like can be stacked on both the first main surface **41a** side and the second main surface **41b** side of the body portion **41**. The conduction wiring **81** is electrically independent from the inductor element L and the capacitor element C. According to this configuration, an electric signal different from the electric signals of the inductor element L and the capacitor element C can be taken out through the conduction wiring **81**. In this embodiment, the conduction wiring **81** serves as the resistor element R.

(139) At least apart of the second main surface **41b** of the body portion **41** is a flat surface FS made of an inorganic substance. In this embodiment, the entire second main surface **41b** of the body portion **41** is the flat surface FS made of an inorganic substance. To be specific, the upper surface of the second insulating layer **112** (the top surface **100t** of the element body **10**), the exposed surface of the fifth connection wiring **55** from the upper surface of the second insulating layer **112**, and the exposed surface of the sixth connection wiring **56** from the upper surface of the second insulating layer **112** are the flat surfaces FS made of an inorganic substance. According to this configuration, since at least a part of the second main surface **41b** of the body portion **41** is the flat surface FS made of an inorganic substance, when the body portion **41** is bonded to another electronic component or the like having the flat surface FS, the flat surface FS of the second main surface **41b** of the body portion **41** and the flat surface FS of the electronic component or the like can be bonded in a state of being in contact with each other. Therefore, it is possible to further reduce the thickness of the entire device such as a stacked semiconductor package.

(140) Preferably, the passive component **1B** includes one or more passive elements, the one or more passive elements are at least one of the inductor element L, the capacitor element C, and the resistor element R. According to this configuration, since at least one of the inductor element L, the capacitor element C, and the resistor element R can be included in the one passive component **1B**, it is not necessary to prepare a plurality of passive components individually including the respective elements. Therefore, the entire device such as a stacked semiconductor package can be reduced in size.

(141) Preferably, as illustrated in FIG. **10**, a thickness **t9** of the inorganic layer **21** in the direction orthogonal to the first main surface **41a** of the body portion **41** is smaller than a thickness **t8** of the capacitor element C in the direction orthogonal to the first main surface **41a** of the body portion **41**. According to this configuration, the passive component **1B** can be made thinner.

(142) Method for Manufacturing Passive Component **1B**

(143) Next, a method for manufacturing the passive component **1B** will be described with reference to FIG. **11A** to FIG. **11J**. FIG. **11A** to FIG. **11J** are views corresponding to the X-X cross section of FIG. **9**.

(144) As illustrated in FIG. **11A**, the inorganic substrate **1021** corresponding to the inorganic layer **21** is prepared. The inorganic substrate **1021** is, for example, an Si substrate. The first resist layer **1001** is applied to the upper surface of the inorganic substrate **1021**, and the cavity **1001a** having a predetermined pattern is formed in the first resist layer **1001** by a photolithography process.

(145) As illustrated in FIG. **11B**, the inorganic substrate **1021** is etched through the cavity **1001a** to form the groove **1021a**. The etching may be either dry etching or wet etching. In the present embodiment, since an Si substrate is used as the inorganic substrate **1021**, plasma etching using a fluorine-based gas is used.

(146) As illustrated in FIG. **11C**, the first resist layer **1001** is peeled off, a seed layer (not illustrated) is formed on the upper surface of the inorganic substrate **1021**, and a conductive material of the first via wiring **121v** and the second via wiring **122v** is used to form a film (solid coating) on the upper surface of the seed layer by electrolytic plating so as to cover the groove **1021a**. As a result, the first via conductor layer **1121v** corresponding to the first via wiring **121v** and the second via conductor layer **1122v** corresponding to the second via wiring **122v** are formed

in the groove **1021a**. Further, the solid film **1020** is formed on the upper surface of the inorganic substrate **1021**. In the present embodiment, Ti/Cu is used for the seed layer, but a seed species such as W, TiW, or Ag and a combination thereof may be selected as necessary.

(147) As illustrated in FIG. **11D**, the solid film **1020** is removed by etching. The solid film **1020** may be removed by CMP or polishing.

(148) As illustrated in FIG. **11E**, a first capacitor-electrode conductor layer **1071** corresponding to the first capacitor electrode **71** is formed on the inorganic substrate **1021** so as to cover the first via conductor layer **1121v** and the second via conductor layer **1122v**. Specifically, an Al film, for example, is formed on the upper surface of the inorganic substrate **1021** by sputtering. Thereafter, a resist layer (not illustrated) is applied, and a cavity having a predetermined pattern is formed in the resist layer by a photolithography process. Thereafter, the Al film is etched to form a patterned first capacitor-electrode conductor layer **1071**. Thereafter, the resist layer is peeled off.

(149) As illustrated in FIG. **11F**, a dielectric material layer **1073** corresponding to the dielectric layer **73** is formed on the inorganic substrate **1021** so as to cover the first capacitor-electrode conductor layer **1071**, and a second capacitor-electrode conductor layer **1072** corresponding to the second capacitor electrode **72** is formed on the dielectric material layer **1073**. The second capacitor-electrode conductor layer **1072** is formed so as to overlap the first capacitor-electrode conductor layer **1071** when viewed from the Z direction.

(150) Specifically, a dielectric material layer is formed on the inorganic substrate **1021** so as to cover the first capacitor-electrode conductor layer **1071** using a vapor deposition method. The material of the dielectric material layer is for example SiO₂. Thereafter, a resist layer (not illustrated) is applied, and a cavity having a predetermined pattern is formed in the resist layer by a photolithography process. The dielectric material layer is then etched to form a patterned dielectric material layer **1073**. At this time, an opening **1073a** is formed in the dielectric material layer **1073** so that the upper surface of the second via conductor layer **1122v** is exposed. Thereafter, the resist layer is peeled off. Thereafter, an Al film, for example, is formed on the upper surface of the dielectric material layer **1073** and the upper surface of the inorganic substrate **1021** by sputtering. Thereafter, a resist layer (not illustrated) is applied, and a cavity having a predetermined pattern is formed in the resist layer by a photolithography process. Thereafter, the Al film is etched to form the patterned second capacitor-electrode conductor layer **1072**. Thereafter, the resist layer is peeled off. Note that the dielectric material layer **1073** and the second capacitor-electrode conductor layer **1072** may be alternately stacked. Thus, the capacitance of the capacitor element C can be increased.

(151) As illustrated in FIG. **11G**, a first insulating material layer **1111** corresponding to the first insulating layer **111** is formed so as to cover the second capacitor-electrode conductor layer **1072** and the dielectric material layer **1073**. Specifically, the first insulating material layer is formed using a chemical vapor deposition (CVD) method so as to cover the second capacitor-electrode conductor layer **1072** and the dielectric material layer **1073**. The material of the first insulating material layer is, for example, SiO₂. Thereafter, a resist layer (not illustrated) is applied, and a cavity having a predetermined pattern is formed in the resist layer by a photolithography process. Thereafter, the first insulating material layer is etched to form the patterned first insulating material layer **1111**. At this time, an opening **1111a** is formed at a position corresponding to the position where the third connection wiring **53** and the fourth connection wiring **54** are provided.

(152) Thereafter, a third connection wiring conductor layer **1053** corresponding to the third connection wiring **53** and a fourth connection wiring conductor layer **1054** corresponding to the fourth connection wiring **54** are formed in the opening **1111a**, and the coil conductor layer **1110** is formed on the upper surface of the third connection wiring conductor layer **1053** and on the first insulating material layer **1111**. A semi-additive method may be used as a method of forming the third connection wiring conductor layer **1053**, the fourth connection wiring conductor layer **1054**, and the coil conductor layer **1110**. Note that instead of the semi-additive method, a known method such as a subtractive method, a full-additive method, or a printing method of conductive paste may

be used. In the present embodiment, Ti/Cu is used for the seed layer, but a seed species such as W, TiW, or Ag and a combination thereof may be selected as necessary.

(153) As illustrated in FIG. 11H, a second insulating material layer **1112** corresponding to the second insulating layer **112** is formed so as to cover the coil conductor layer **1110**. Specifically, the second insulating material layer is formed by the CVD method so as to cover the coil conductor layer **1110**. Thereafter, a resist layer (not illustrated) is applied, and a cavity having a predetermined pattern is formed in the resist layer by a photolithography process. Thereafter, the second insulating material layer is etched to form the patterned second insulating material layer **1112**. At this time, an opening **1112a** is formed at a position corresponding to the position where the fifth connection wiring **55** and the sixth connection wiring **56** are provided.

(154) Thereafter, a fifth connection wiring conductor layer **1055** corresponding to the fifth connection wiring **55** and a sixth connection wiring conductor layer **1056** corresponding to the sixth connection wiring **56** are formed in the opening **1112a**. Specifically, the fifth connection wiring conductor layer **1055** and the sixth connection wiring conductor layer **1056** are formed by filling plating. At this time, plating is also formed on the second insulating material layer **1112**. The conductive material of the fifth connection wiring conductor layer **1055** and the sixth connection wiring conductor layer **1056** is, for example, Cu.

(155) As illustrated in FIG. 11I, the plating on the second insulating material layer **1112**, the fifth connection wiring conductor layer **1055**, and the sixth connection wiring conductor layer **1056** are polished to expose the second insulating material layer **1112**, the end surface of the fifth connection wiring conductor layer **1055**, and the end surface of the sixth connection wiring conductor layer **1056**. As a result, the upper surface of the second insulating material layer **1112**, the end surface of the fifth connection wiring conductor layer **1055**, and the end surface of the sixth connection wiring conductor layer **1056** are planarized. CMP is preferred for the above polishing. Thereafter, the inorganic substrate **1021** is polished to expose the end surface of the first via conductor layer **1121v** and the end surface of the second via conductor layer **1122v**. As a result, the lower surface of the inorganic substrate **1021**, the end surface of the first via conductor layer **1121v**, and the end surface of the second via conductor layer are planarized. CMP is preferred for polishing the inorganic substrate **1021**.

(156) As illustrated in FIG. 11J, singulation is performed along the cut line C. Thus, as illustrated in FIG. 10, the passive component **1B** is manufactured.

Fourth Embodiment

(157) Configuration of Stacked Semiconductor Package 7

(158) FIG. 12 is a schematic cross-sectional view illustrating a stacked semiconductor package 7. As illustrated in FIG. 12, the stacked semiconductor package 7 includes a second substrate **220**, a first substrate **210** stacked on the second substrate **220** in a first direction **D1**, and a three-dimensional device **4** stacked on the first substrate **210** in the first direction **D1**. The first direction **D1** is an upward direction in the drawing.

(159) The first substrate **210** is, for example, an inorganic substrate made of Si or SiO₂ (so-called silicon interposer substrate or glass interposer substrate), or an organic substrate made of Flame Retardant Type 4 (FR4), epoxy, polyimide, or the like (so-called organic package substrate). Wiring is provided inside or on the main surface of the first substrate **210** and is electrically connected to the three-dimensional device **4**. A conductive member such as an external terminal, a conductor bump, a conductor pillar, or solder may be provided on the main surface of the first substrate **210**. A similar conductive member may also be provided on the main surface of the three-dimensional device **4** facing the first substrate **210**.

(160) Similar to the first substrate **210**, the second substrate **220** is, for example, an inorganic substrate made of Si or SiO₂, or an organic substrate made of FR4, epoxy, polyimide, or the like. The design accuracy of the second substrate **220** is lower than that of the first substrate **210**. Wiring is provided inside or on the main surface of the second substrate **220**, and is electrically

connected to the first substrate **210**. A conductive member such as an external terminal, a conductor bump, a conductor pillar, or solder may be provided on the main surface of the second substrate **220**. A similar conductive member may be provided on the main surface of the first substrate **210** facing the second substrate **220**.

(161) The three-dimensional device **4** includes the passive component **1B** having the flat surface FS made of an inorganic substance, and a first semiconductor integrated circuit component **301** and a second semiconductor integrated circuit component **302** bonded to the flat surface FS. The passive component **1B** is the same as the passive component **1B** described in the third embodiment. The first semiconductor integrated circuit component **301** and the second semiconductor integrated circuit component **302** are, for example, electronic components such as an integrated circuit (IC), a central processing unit (CPU), a power management IC (PMIC), a memory, and a transistor.

(162) A first main surface **301a** of the first semiconductor integrated circuit component **301** facing the passive component **1B** includes the flat surface FS. The second main surface **41b** of the body portion **41** of the passive component **1B** facing the first semiconductor integrated circuit component **301** includes the flat surface FS. The flat surface FS of the first semiconductor integrated circuit component **301** and the flat surface FS of the second main surface **41b** of the passive component **1B** are bonded in contact with each other. Similarly, a first main surface **302a** of the second semiconductor integrated circuit component **302** facing the passive component **1B** includes the flat surface FS. The first main surface **41a** of the body portion **41** of the passive component **1B** facing the second semiconductor integrated circuit component **302** includes the flat surface FS. The flat surface FS of the second semiconductor integrated circuit component **302** and the flat surface FS of the first main surface **41a** of the passive component **1B** are bonded in contact with each other. According to this configuration, the thin-type three-dimensional device **4** can be obtained.

(163) Note that when the flat surface FS of the semiconductor integrated circuit component and the flat surface FS of the passive component cannot be separated from each other, the surface roughness of the flat surface FS may be calculated from the cross section of the three-dimensional device. Specifically, a cross section of the bonding portion of the flat surface FS is exposed by a known method such as ion milling, and an image of the bonding portion is acquired by a transmission electron microscope (TEM) or the like. At this time, the magnification is preferably equal to or more than 300 K. The interface of the bonding portion of the flat surface FS can be recognized from the difference of the grain boundary or the like. Using the acquired image, a straight line (a line drawn by the least squares method) is drawn at a position corresponding to the interface. The surface roughness can be determined by measuring Ra (arithmetic average roughness) with respect to this straight line.

(164) The three-dimensional device **4** is not limited to the configuration illustrated in FIG. **12**, and the number of passive components may be two or more, and the number of semiconductor integrated circuit components may be one or three or more. Further, the stacking order of the semiconductor integrated circuit component and the passive component in the first direction D**1** is not particularly limited.

(165) A first main surface **211** of the first substrate **210** facing the three-dimensional device **4** and a first main surface (a second main surface **302b** of the second semiconductor integrated circuit component **302**) of the three-dimensional device **4** facing the first substrate **210** are connected with a connection member **5** interposed therebetween in a state of being separated from each other. A first main surface **221** of the second substrate **220** facing the first substrate **210** and a second main surface **212** of the first substrate **210** facing the second substrate **220** are connected to each other with a connection member **6** interposed therebetween in a state of being separated from each other. The connection members **5** and **6** are, for example, solder, a conductor bump, a conductor pillar, or the like.

(166) Modification

(167) FIG. 13 is a schematic cross-sectional view illustrating a three-dimensional device 4A according to a modification. As illustrated in FIG. 13, the three-dimensional device 4A consists of only passive components. The three-dimensional device 4A includes the passive component 1B having the flat surface FS made of an inorganic substance and a passive component 1C bonded to the flat surface FS. The passive component 1B and the passive component 1C are stacked. The passive component 1B is the same as the passive component 1B described in the third embodiment. The passive component 1C is different from the passive component 1B described in the third embodiment in the position of the exposed surface of the fifth connection wiring 55 from the second main surface 41b of the body portion 41. To be specific, in the passive component 1C, the fifth connection wiring 55 is exposed from the second main surface 41b of the body portion 41 at a position corresponding to the first via wiring 121v of the stacked passive component 1B. The flat surface FS of the second main surface 41b of the passive component 1C and the flat surface FS of the first main surface 41a of the passive component 1B are bonded to each other in a contact state. Therefore, the thickness of the three-dimensional device 4A can be reduced. Note that the passive components included in the three-dimensional device 4A are not limited to the passive component 1B and the passive component 1C, and may be other passive components having a flat surface. Further, the three-dimensional device 4A may include three or more passive components.

(168) Note that the present disclosure is not limited to the above-described embodiments, and design changes can be made without departing from the gist of the present disclosure. For example, the features of the first to fourth embodiments may be combined in various ways.

(169) Although the entire first main surface of the inorganic layer and the entire exposed surfaces of the first via wiring and the second via wiring from the first main surface of the inorganic layer are flat surfaces in the first to fourth embodiments, at least only a part of the first main surface of the inorganic layer may be a flat surface, at least only a part of the exposed surface may be a flat surface, or only a part of the first main surface of the inorganic layer and only a part of the exposed surface may be flat surfaces.

(170) In the second embodiment, the coil has a planar spiral shape formed of one layer, but may have a plurality of layers of coil wiring in a planar spiral shape. Thus, the inductance can be improved.

(171) In the fourth embodiment, the passive component of the three-dimensional device is the passive component of the third embodiment, but the type of the passive component is not particularly limited.

(172) <1> A passive component comprising a body portion having a first main surface; and a passive element at least a part of which is provided inside the body portion. The first main surface at least partially includes a flat surface made of an inorganic substance and having a surface roughness of equal to or less than 1/1000 of a thickness of the body portion in a direction orthogonal to the first main surface or equal to or less than 10 nm.

(173) <2> The passive component according to <1>, wherein the body portion includes an inorganic layer made of an inorganic substance and having a first main surface and a second main surface facing each other, and a through-wiring penetrating the inorganic layer from the first main surface to the second main surface of the inorganic layer. Also, the first main surface of the inorganic layer and an exposed surface of the through-wiring exposed from the first main surface of the inorganic layer constitute the first main surface of the body portion.

(174) <3> The passive component according to <2>, wherein the through-wiring is made of an inorganic substance, and the exposed surface of the through-wiring constitutes at least a part of the flat surface.

(175) <4> The passive component according to <2> or <3>, wherein the inorganic layer is amorphous or single crystal.

(176) <5> The passive component according to any one of <1> to <4>, wherein the passive element includes a coil, and the coil has a central axis parallel to the first main surface of the body

portion.

(177) <6> The passive component according to any one of <1> to <5>, wherein the body portion includes an inorganic layer made of an inorganic substance and having a first main surface and a second main surface facing each other, and an organic insulating layer provided on the second main surface of the inorganic layer. Also, the first main surface of the inorganic layer constitutes at least a part of the first main surface of the body portion, the passive element includes a coil at least a part of which is provided inside the organic insulating layer, and the coil is in contact with both the inorganic layer and the organic insulating layer.

(178) <7> The passive component according to any one of <1> to <6>, wherein the body portion includes an inorganic layer having a first main surface and a second main surface facing each other, the first main surface of the inorganic layer constitutes at least a part of the first main surface of the body portion, and a thickness of the inorganic layer in a direction orthogonal to the first main surface of the body portion is smaller than a thickness of the passive element in a direction orthogonal to the first main surface of the body portion.

(179) <8> The passive component according to any one of <1> to <7>, wherein the body portion includes an inorganic layer having a first main surface and a second main surface facing each other. Also, the first main surface of the inorganic layer constitutes at least a part of the first main surface of the body portion, the passive element includes a coil having a central axis parallel to the first main surface of the body portion, and a thickness of the inorganic layer in a direction orthogonal to the first main surface of the body portion is smaller than a thickness of the coil in a direction orthogonal to the first main surface of the body portion.

(180) <9> The passive component according to any one of <1> to <8>, wherein the body portion has a second main surface facing the first main surface. Also, an insulator provided on the second main surface of the body portion and made of an organic insulating resin is further provided, at least a part of the passive element is exposed from the second main surface of the body portion, and an exposed portion of the passive element exposed from the second main surface of the body portion is covered with the insulator.

(181) <10> The passive component according to any one of <1> to <4>, wherein the passive element includes a coil, and the coil has a central axis orthogonal to the first main surface of the body portion.

(182) <11> The passive component according to any one of <1> to <4>, wherein the body portion includes an inorganic layer having a first main surface and a second main surface facing each other, and a magnetic portion provided on the second main surface of the inorganic layer. Also, the first main surface of the inorganic layer constitutes at least a part of the first main surface of the body portion, the passive element includes a coil, and the coil is covered with the magnetic portion.

(183) <12> The passive component according to <11>, wherein the coil is wound along a plane parallel to the first main surface. Also, the body portion further includes an organic insulating portion provided at least on a side surface of the coil orthogonal to the first main surface of the body portion, the magnetic portion covers the coil and the organic insulating portion, and the coil is in contact with the organic insulating portion and the magnetic portion.

(184) <13> The passive component according to <12>, wherein a thickness of the organic insulating portion in a direction orthogonal to the first main surface of the body portion is thicker than a thickness of the coil in a direction orthogonal to the first main surface of the body portion.

(185) <14> The passive component according to any one of <1> to <4>, wherein the body portion further includes a second main surface facing the first main surface, and the second main surface at least partially includes a flat surface made of an inorganic substance.

(186) <15> The passive component according to <14>, wherein the at least one passive element includes at least one of an inductor element, a capacitor element, and a resistor element.

(187) <16> The passive component according to <15>, wherein the at least one passive element includes at least an inductor element and a capacitor element. Also, the body portion further

includes a conduction wiring extending from the first main surface to the second main surface of the body portion and having both end portions in the extending direction exposed from the first main surface and the second main surface of the body portion, and the conduction wiring is electrically independent from the inductor element and the capacitor element.

(188) <17> The passive component according to <15> or <16>, wherein the body portion includes an inorganic layer having a first main surface and a second main surface facing each other, and a through-wiring penetrating the inorganic layer from the first main surface to the second main surface of the inorganic layer. Also, the first main surface of the inorganic layer constitutes at least a part of the first main surface of the body portion, the at least one passive element includes at least an inductor element and a capacitor element, the inductor element includes a coil, and the capacitor element includes two capacitor electrodes facing each other and a dielectric layer arranged between the two capacitor electrodes. In addition, a conductive material of the two capacitor electrodes is different from a conductive material of each of the through-wiring and the coil, the body portion includes an insulating layer covering at least the coil, and a material of the dielectric layer is the same as a material of the insulating layer.

(189) <18> A three-dimensional device comprising the passive component according to any one of <1> to <17>; and a semiconductor integrated circuit component bonded to the flat surface of the passive component.

(190) <19> A three-dimensional device comprising the passive component according to any one of <1> to <17>; and a passive component bonded to the flat surface of the passive component.

(191) <20> A method for manufacturing a passive component comprising preparing an inorganic layer made of an inorganic substance and having a first main surface and a second main surface facing each other; forming a body portion including the inorganic layer and at least a part of a passive element by providing the passive element on the second main surface side of the inorganic layer; and providing a flat surface having a surface roughness of equal to or less than 1/1000 of a thickness of the body portion in a direction orthogonal to the first main surface or equal to or less than 10 nm by polishing the first main surface of the inorganic layer.

Claims

1. A passive component comprising: a body portion having a first main surface; and at least one passive element at least a part of which is inside the body portion, wherein the first main surface at least partially includes a flat surface including an inorganic substance and having a surface roughness of equal to or less than 1/1000 of a thickness of the body portion in a direction orthogonal to the first main surface or equal to or less than 10 nm, the body portion includes an inorganic layer including an inorganic substance and having a first main surface and a second main surface facing each other, and an insulating element body on the second main surface of the inorganic layer, the body portion has a second main surface facing the first main surface of the body portion, the second main surface of the body portion being configured by a surface of the element body, the body portion has a conductive through-wiring penetrating the inorganic layer from the first main surface to the second main surface of the inorganic layer and extending through the element body to the second main surface of the body portion, the first main surface of the inorganic layer and an exposed surface of the through-wiring exposed from the first main surface of the inorganic layer configure the first main surface of the body portion, and the conductive through-wiring is part of the at least one passive element.
2. The passive component according to claim 1, wherein the through-wiring includes an inorganic substance, and the exposed surface of the through-wiring configures at least a part of the flat surface.
3. The passive component according to claim 1, wherein the inorganic layer is amorphous or single crystal.

4. The passive component according to claim 1, wherein the passive element includes a coil, and the coil has a central axis parallel to the first main surface of the body portion.
5. The passive component according to claim 1, wherein the element body comprises, the passive element includes a coil at least a part of which is inside the organic insulating layer, and the coil is in contact with both the inorganic layer and the organic insulating layer.
6. The passive component according to claim 1, wherein a thickness of the inorganic layer in a direction orthogonal to the first main surface of the body portion is smaller than a thickness of the passive element in a direction orthogonal to the first main surface of the body portion.
7. The passive component according to claim 1, wherein the passive element includes a coil having a central axis parallel to the first main surface of the body portion, and a thickness of the inorganic layer in a direction orthogonal to the first main surface of the body portion is smaller than a thickness of the coil in a direction orthogonal to the first main surface of the body portion.
8. The passive component according to claim 1, wherein the passive component further includes an insulator on the second main surface of the body portion and including an organic insulating resin, at least a part of the passive element is exposed from the second main surface of the body portion, and an exposed portion of the passive element exposed from the second main surface of the body portion is covered with the insulator.
9. The passive component according to claim 1, wherein the passive element includes a coil, and the coil has a central axis orthogonal to the first main surface of the body portion.
10. The passive component according to claim 1, wherein the second main surface at least partially includes a flat surface including an inorganic substance.
11. The passive component according to claim 10, wherein the at least one passive element includes at least one of an inductor element, a capacitor element, and a resistor element.
12. The passive component according to claim 11, wherein the at least one passive element includes at least an inductor element and a capacitor element, the body portion further includes a conduction wiring extending from the first main surface of the body portion toward the second main surface and exposed from each of the first main surface and the second main surface of the body portion, and the conduction wiring is electrically independent from the inductor element and the capacitor element.
13. A three-dimensional device comprising: the passive component according to claim 1; and a semiconductor integrated circuit component bonded to the flat surface of the passive component.
14. A three-dimensional device comprising: the passive component according to claim 1; and a passive component bonded to the flat surface of the passive component.
15. The passive component of claim 1, wherein the inorganic layer of the body portion is a different material than the element body.
16. A passive component comprising: a body portion having a first main surface; and at least one passive element at least a part of which is inside the body portion, wherein the first main surface at least partially includes a flat surface including an inorganic substance and having a surface roughness of equal to or less than 1/1000 of a thickness of the body portion in a direction orthogonal to the first main surface or equal to or less than 10 nm, the body portion includes an inorganic layer having a first main surface and a second main surface facing each other, and a magnetic portion on the second main surface of the inorganic layer, the first main surface of the inorganic layer configures at least a part of the first main surface of the body portion, the passive element includes a coil, and the coil is covered with the magnetic portion.
17. The passive component according to claim 16, wherein the coil is wound along a plane parallel to the first main surface, the body portion further includes an organic insulating portion at least on a side surface of the coil orthogonal to the first main surface of the body portion, the magnetic portion covers the coil and the organic insulating portion, and the coil is in contact with the organic insulating portion and the magnetic portion.
18. The passive component according to claim 17, wherein a thickness of the organic insulating

portion in a direction orthogonal to the first main surface of the body portion is thicker than a thickness of the coil in a direction orthogonal to the first main surface of the body portion.

19. A passive component comprising: a body portion having a first main surface; and at least one passive element at least a part of which is inside the body portion, wherein the first main surface at least partially includes a flat surface including an inorganic substance and having a surface roughness of equal to or less than $1/1000$ of a thickness of the body portion in a direction orthogonal to the first main surface or equal to or less than 10 nm, the body portion further includes a second main surface facing the first main surface; the second main surface at least partially includes a flat surface including an inorganic substance, the body portion includes an inorganic layer having a first main surface and a second main surface facing each other, and a through-wiring penetrating the inorganic layer from the first main surface to the second main surface of the inorganic layer, the first main surface of the inorganic layer configures at least a part of the first main surface of the body portion, the at least one passive element includes at least an inductor element and a capacitor element, the inductor element includes a coil, the capacitor element includes two capacitor electrodes facing each other and a dielectric layer between the two capacitor electrodes, and a conductive material of the two capacitor electrodes is different from a conductive material of each of the through-wiring and the coil, the body portion includes an insulating layer covering at least the coil, and a material of the dielectric layer is the same as a material of the insulating layer.

20. A passive component comprising: a body portion having a first main surface; and at least one passive element at least a part of which is inside the body portion, wherein the first main surface at least partially includes a flat surface including an inorganic substance and having a surface roughness of equal to or less than $1/1000$ of a thickness of the body portion in a direction orthogonal to the first main surface or equal to or less than 10 nm, the body portion further includes a second main surface facing the first main surface; the second main surface at least partially includes a flat surface including an inorganic substance, the body portion includes an inorganic layer having a first main surface and a second main surface facing each other, and a through-wiring penetrating the inorganic layer from the first main surface to the second main surface of the inorganic layer, the first main surface of the inorganic layer configures at least a part of the first main surface of the body portion, the at least one passive element includes at least a capacitor element, the capacitor element includes two capacitor electrodes facing each other and a dielectric layer between the two capacitor electrodes, and a conductive material of the two capacitor electrodes is different from a conductive material of the through-wiring.
