

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12413588
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Sanchez Rola; Iskander

Systems and methods for dynamically generating fingerprint signatures

Abstract

A computer-implemented method for dynamically generating fingerprint signatures may include (i) detecting data associated with fingerprinting functions called in a target web page, (ii) associating, based on the data, fingerprints generated by the fingerprinting functions with a corresponding action, (ii) identifying, based on the data, callee information associated with each of the fingerprinting functions, and (iv) performing a security action that protects against malicious activity by calculating a cryptographic hash of a list including the fingerprinting functions and the corresponding actions to generate a fingerprint signature for the target web page. Various other methods, systems, and computer-readable media are also disclosed.

Inventors:	Sanchez Rola; Iskander (Antibes, FR)
Applicant:	GEN DIGITAL INC. (Tempe, AZ)
Family ID:	88647672
Assignee:	Gen Digital Inc. (Tempe, AZ)
Appl. No.:	18/509954
Filed:	November 15, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20250047669 A1	Feb. 06, 2025

Publication Classification

Int. Cl.: G06F7/04 (20060101); H04L9/40 (20220101)

U.S. Cl.:

CPC H04L63/0876 (20130101);

Field of Classification Search

CPC: G06F (21/44); G06F (21/554); G06F (21/577); G06F (21/60); G06F (21/6263); H04L (63/0876); H04W (12/02)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5974455	12/1998	Monier	709/217	G06F 16/9014
9514312	12/2015	Antoun	N/A	G06F 16/152
10628630	12/2019	Surace	N/A	H04L 67/02
12019785	12/2023	Bennett	N/A	H04L 63/0407
2004/0128515	12/2003	Rabin	380/231	G06F 21/1064
2018/0114000	12/2017	Taylor	N/A	H04L 9/0643
2021/0203694	12/2020	Paquet	N/A	H04L 63/1483

OTHER PUBLICATIONS

Sedaghat et al, A Dynamic Web Agent for Verifying the Security and Integrity of a Web Site's Contents, IEEE, Jul. 14, 2001, pp. 330-337. (Year: 2001). cited by examiner

Sjosten et al, EssentialIFP: Exposing the Essence of Browser Fingerprinting, IEEE, Sep. 10, 2021, pp. 32-48. (Year: 2021). cited by examiner

Primary Examiner: Chea; Philip J

Assistant Examiner: Jackson; Jenise E

Attorney, Agent or Firm: Greenberg Traurig, LLP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATION

(1) This application claims the benefit of European Patent Application No. EP23306313.0, filed Jul. 31, 2023. The disclosure of this application is hereby incorporated, by reference, in its entirety.

BACKGROUND

(2) Computing device users are increasingly being targeted by sophisticated attacks that capture device and browser fingerprints in malicious websites for a variety of nefarious activities. For example, cybercriminals may reuse stolen browser fingerprint code when creating malicious web pages multiple potential victims and across multiple categories for performing cloaking (e.g., deceiving users into disclosing private data by presenting different/targeted web page content). Additionally or alternatively, captured fingerprints may be sold along with stolen user credentials for enabling other malicious actors to bypass authentication checks, such as two-factor authentication.

(3) Traditional approaches utilized by threat protection software for protecting against attacks performed utilizing malicious web pages fail to provide methods for detecting the misuse of

browser and device fingerprint code. As a result, these approaches often fail to collect sufficient data for analyzing malicious campaigns carried out by threat actors or detect associated web pages utilized by these actors for malicious purposes.

SUMMARY

(4) As will be described in greater detail below, the present disclosure describes various systems and methods for dynamically generating fingerprint signatures.

(5) In one example, a method for dynamically generating fingerprint signatures may include (i) detecting, by one or more computing devices data associated with fingerprinting functions called in a target web page, (ii) associating, based on the data, fingerprints generated by the fingerprinting functions with a corresponding action, (iii) identifying, based on the data, callee information associated with each of the fingerprinting functions, and (iv) performing a security action that protects against malicious activity by calculating a cryptographic hash of a list including the fingerprinting functions and the corresponding actions to generate a fingerprint signature for the target web page. Examples of malicious activity may include malicious fingerprinting or other web-based threats (such as malware, phishing, and scams) where the security action may protect against these threats by identifying matching fingerprint signatures utilized in attacks corresponding to the aforementioned threats.

(6) In some examples, the data associated with the fingerprinting functions may be detected by detecting hypertext markup language (HTML) elements associated with the fingerprinting functions and/or HTML objects associated with the fingerprinting functions. Additionally or alternatively, the fingerprinting functions may be detected by tracking one or more application programming interfaces (APIs) utilized by the fingerprinting functions to dynamically modify the target web page. Additionally or alternatively, the fingerprinting functions may be detected by utilizing a dynamically generated resource tree for finding a connection between scripts in the target web page.

(7) In some examples, associating the fingerprints with the corresponding actions may include identifying a target function that utilizes any of the fingerprints for a content manipulation action and associating the target function with the content manipulation action. Additionally or alternatively, associating the fingerprints with the corresponding actions may include identifying a target function that utilizes any of the fingerprints for a redirection action and associating the target function with the redirection action. Additionally or alternatively, associating the fingerprints with the corresponding actions may include identifying a target function that performs a storage action for any of the fingerprints and associating the target function with the storage action. Additionally or alternatively, associating the fingerprints with the corresponding actions may include identifying a target function that performs an action for sending any of the fingerprints within a request parameter and associating the target function with the action.

(8) In some examples, the callee information may be identified by determining a domain name associated with a third-party callee. Additionally or alternatively, the callee information may be identified by determining (and marking) a first party-callee.

(9) In some examples, the malicious activity may include a cloaking operation that delivers new content to a user of the target web page that is different than native content associated with the target web page. In other examples, the malicious activity may include other web-based threats such as malware, phishing, and scam attacks (where the security action may protect against these threats by identifying matching fingerprint signatures utilized in the attacks). In some examples, the fingerprint signature may be a device fingerprint signature or a browser fingerprint signature generated by one or more of a web browser, a browser extension, or a backend server web crawler.

(10) In one embodiment, a system for dynamically generating fingerprint signatures may include at least one physical processor and physical memory that includes computer-executable instructions and set of modules that, when executed by the physical processor, cause the physical processor to (i) detect, by a detection module, data associated with one or more fingerprinting functions called

in a target web page, (ii) associate, by an association and based on the data, each of one or more fingerprints generated by the fingerprinting functions with a corresponding action, (iii) identify, by an identification module and based on the data, callee information associated with each of the fingerprinting functions, and (iv) perform, by a security module, a security action that protects against malicious activity by calculating a cryptographic hash of a list including the fingerprinting functions and the corresponding actions to generate a fingerprint signature for the target web page. (11) In some examples, the above-described method may be encoded as computer-readable instructions on a non-transitory computer-readable medium. For example, a computer-readable medium may include one or more computer-executable instructions that, when executed by at least one processor of a computing device, may cause the computing device to (i) detect data associated with one or more fingerprinting functions called in a target web page, (ii) associate, based on the data, each of one or more fingerprints generated by the fingerprinting functions with a corresponding action, (iii) identify, based on the data, callee information associated with each of the fingerprinting functions, and (iv) perform a security action that protects against malicious activity by calculating a cryptographic hash of a list including the fingerprinting functions and the corresponding actions to generate a fingerprint signature for the target web page. (12) Features from any of the embodiments described herein may be used in combination with one another in accordance with the general principles described herein. These and other embodiments, features, and advantages will be more fully understood upon reading the following detailed description in conjunction with the accompanying drawings and claims.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The accompanying drawings illustrate a number of example embodiments and are a part of the specification. Together with the following description, these drawings demonstrate and explain various principles of the present disclosure.

(2) FIG. 1 is a block diagram of an example system for dynamically generating fingerprint signatures.

(3) FIG. 2 is a block diagram of an additional example system for dynamically generating fingerprint signatures.

(4) FIG. 3 is a flow diagram of an example method for dynamically generating fingerprint signatures.

(5) FIG. 4 is a block diagram of example fingerprinting function data utilized in the example systems of FIGS. 1 and 2.

(6) FIG. 5 is a block diagram of example fingerprinting function actions utilized in the example systems of FIGS. 1 and 2.

(7) FIG. 6 is a block diagram of an example computing system capable of implementing one or more of the embodiments described and/or illustrated herein.

(8) FIG. 7 is a block diagram of an example computing network capable of implementing one or more of the embodiments described and/or illustrated herein.

(9) Throughout the drawings, identical reference characters and descriptions indicate similar, but not necessarily identical, elements. While the example embodiments described herein are susceptible to various modifications and alternative forms, specific embodiments have been shown by way of example in the drawings and will be described in detail herein. However, the example embodiments described herein are not intended to be limited to the particular forms disclosed. Rather, the present disclosure covers all modifications, equivalents, and alternatives falling within the scope of the appended claims.

DETAILED DESCRIPTION OF EXAMPLE EMBODIMENTS

(10) The present disclosure is generally directed to systems and methods for dynamically generating fingerprint signatures. As will be described in greater detail below, the systems and methods described herein may collect data about fingerprinting functions in web pages, track APIs that can be used to dynamically the fingerprinting functions, and check a web page hierarchy by utilizing a dynamically generated resource tree to find connections between scripts associated with the fingerprinting functions. Additionally, the systems and methods described herein may associate the fingerprinting functions based on their associated intentions/actions such as (i) the utilization of fingerprints for content manipulation/redirection and (ii) the storing of fingerprints in web cookies (or other storage) or the sending of the fingerprints within request parameters. Additionally, the systems and methods described herein may, for generating precise fingerprinting signatures, incorporate information about the callee of the fingerprinting functions, such as including the associated domain name for third-party callees, and further incorporate the order of the actions and the relationship between the actions. Finally, the systems and methods herein may compute a cryptographic hash of an ordered list of the fingerprinting functions (along with their corresponding parameter pairs) to generate the fingerprinting signatures. By generating fine-grained fingerprinting signatures in this way, the detection of malicious web pages that reuse fingerprinting code (e.g., by bypassing authentication checks) for multiple targets and across multiple categories (e.g., malicious cyber campaigns carried out by hacker group clusters) may be realized.

(11) In addition, the systems and methods described herein may improve the technical field of computing device security by protecting against malicious attacks designed to bypass traditional security protections, such as two-factor authentication, for protecting private user data (e.g., digital user credentials).

(12) The following will provide, with reference to FIGS. 1-2, detailed descriptions of example systems for dynamically generating fingerprint signatures. Detailed descriptions of corresponding computer-implemented methods will also be provided in connection with FIG. 3. In addition, a detailed description of example fingerprinting function data utilized in the example systems of FIGS. 1 and 2, will also be provided in connection with FIG. 4. In addition, a detailed description of example fingerprinting function actions utilized in the example systems of FIGS. 1 and 2, will also be provided in connection with FIG. 5. In addition, detailed descriptions of an example computing system and network architecture capable of implementing one or more of the embodiments described herein will be provided in connection with FIGS. 6 and 7, respectively.

(13) FIG. 1 is a block diagram of an example system **100** for dynamically generating fingerprint signatures. As illustrated in this figure, example system **100** may include one or more modules **102** for performing one or more tasks. As will be explained in greater detail below, modules **102** may include a detection module **104** that detects data **116** associated with fingerprinting functions **114** called in a target web page **112**. Example system **100** may additionally include an association module **106** that associate, based on data **116**, fingerprints **118** generated by fingerprinting functions **114** with actions **122** (e.g., a corresponding action). Example system **100** may also include an identification module **108** that identifies, based on data **116**, callee information associated with fingerprinting functions **114**. Example system **100** may additionally include a security module **110** that performs a security action that protects against malicious activity by calculating a cryptographic hash of a list including fingerprinting functions **114** and actions **122** to generate a fingerprint signature **124** for target web page **112**. Although illustrated as separate elements, one or more of modules **102** in FIG. 1 may represent portions of a single module or application.

(14) The term “fingerprinting functions” as used herein, generally refers to any function (e.g., scripts) utilized for generating browser or device fingerprints containing information for identifying users during web browsing sessions. For example, when a user visits a web page, a website may be configured to execute a script for calling an API (e.g., HTMLCanvasElement) that returns encoded pixel data for serving as a user fingerprint during user browsing sessions.

(15) In certain embodiments, one or more of modules **102** in FIG. **1** may represent one or more software applications or programs that, when executed by a computing device, may cause the computing device to perform one or more tasks. For example, and as will be described in greater detail below, one or more of modules **102** may represent modules stored and configured to run on one or more computing devices, such as the devices illustrated in FIG. **2** (e.g., computing device **202** and/or security server **206**). One or more of modules **102** in FIG. **1** may also represent all or portions of one or more special-purpose computers configured to perform one or more tasks.

(16) As illustrated in FIG. **1**, example system **100** may also include one or more memory devices, such as memory **140**. Memory **140** generally represents any type or form of volatile or non-volatile storage device or medium capable of storing data and/or computer-readable instructions. In one example, memory **140** may store, load, and/or maintain one or more of modules **102**. Examples of memory **140** include, without limitation, Random Access Memory (RAM), Read Only Memory (ROM), flash memory, Hard Disk Drives (HDDs), Solid-State Drives (SSDs), optical disk drives, caches, variations or combinations of one or more of the same, and/or any other suitable storage memory.

(17) As illustrated in FIG. **1**, example system **100** may also include one or more physical processors, such as physical processor **130**. Physical processor **130** generally represents any type or form of hardware-implemented processing unit capable of interpreting and/or executing computer-readable instructions. In one example, physical processor **130** may access and/or modify one or more of modules **102** stored in memory **140**. Additionally or alternatively, physical processor **130** may execute one or more of modules **102** to facilitate dynamically generating fingerprint signatures. Examples of physical processor **130** include, without limitation, microprocessors, microcontrollers, Central Processing Units (CPUs), Field-Programmable Gate Arrays (FPGAs) that implement softcore processors, Application-Specific Integrated Circuits (ASICs), portions of one or more of the same, variations or combinations of one or more of the same, and/or any other suitable physical processor.

(18) As illustrated in FIG. **1**, example system **100** may also include a data storage **120** for storing data. In one example, data storage **120** may store target web page **112**, fingerprinting functions **114**, data **116**, fingerprints **118**, actions **122**, and fingerprint signature **124**.

(19) Example system **100** in FIG. **1** may be implemented in a variety of ways. For example, all or a portion of example system **100** may represent portions of example system **200** in FIG. **2**. As shown in FIG. **2**, system **200** may include a computing device **202** in communication with security server **206** via a network **204**. In one example, all or a portion of the functionality of modules **102** may be performed by computing device **202**, security server **206**, and/or any other suitable computing system. As will be described in greater detail below, one or more of modules **102** from FIG. **1** may, when executed by at least one processor of computing device **202** and/or security server **206**, enable computing device **202** and/or security server **206** to dynamically generate fingerprint signatures. For example, and as will be described in greater detail below, detection module **104**, association module **106**, identification module **108**, and security module **110**, may cause computing device **202** and/or backend server **206** to (i) detect data **116** associated with fingerprinting functions **114** called in target web page **112**, (ii) associate, based on data **116**, fingerprints **118** generated by fingerprinting functions **114** with actions **122**, (iii) identify, based data **116**, callee information **210** associated with fingerprinting functions **114**, and (iv) perform a security action that protects against malicious activity by calculating cryptographic hash **212** of a list including fingerprinting functions **114** and actions **122** to generate fingerprint signature **124** for target web page **112**.

(20) Computing device **202** generally represents any type or form of computing device capable of reading and/or executing computer-executable instructions. In some examples, computing device **202** may represent an endpoint device running client-side security software including a browser application or browser extension viewing and accessing websites. Additional examples of computing device **202** include, without limitation, laptops, tablets, desktops, servers, cellular

phones, Personal Digital Assistants (PDAs), multimedia players, embedded systems, wearable devices (e.g., smart watches, smart glasses, etc.), smart vehicles, smart packaging (e.g., active or intelligent packaging), gaming consoles, so-called Internet-of-Things devices (e.g., smart appliances, etc.), variations or combinations of one or more of the same, and/or any other suitable computing device.

(21) Security server **206** generally represents any type or form of computing device that is capable of reading and/or executing computer-executable instructions. In some examples, security server **206** may represent a backend server computing device, running web crawler **214**, that provides threat protection services for web browsers. Additional examples of security server **206** include, without limitation, application servers, web servers, storage servers, and/or database servers configured to run certain software applications and/or provide various security, web, storage, and/or database services. Although illustrated as a single entity in FIG. 2, security server **206** may include and/or represent a plurality of servers that work and/or operate in conjunction with one another.

(22) Network **204** generally represents any medium or architecture capable of facilitating communication or data transfer. In one example, network **204** may facilitate communication between computing device **202** and security server **206**. In this example, network **204** may facilitate communication or data transfer using wireless and/or wired connections. Examples of network **204** include, without limitation, an intranet, a Wide Area Network (WAN), a Local Area Network (LAN), a Personal Area Network (PAN), the Internet, Power Line Communications (PLC), a cellular network (e.g., a Global System for Mobile Communications (GSM) network), portions of one or more of the same, variations or combinations of one or more of the same, and/or any other suitable network.

(23) FIG. 3 is a flow diagram of an example computer-implemented method **300** for dynamically generating fingerprint signatures. The steps shown in FIG. 3 may be performed by any suitable computer-executable code and/or computing system, including system **100** in FIG. 1, system **200** in FIG. 2, and/or variations or combinations of one or more of the same. In one example, each of the steps shown in FIG. 3 may represent an algorithm whose structure includes and/or is represented by multiple sub-steps, examples of which will be provided in greater detail below.

(24) As illustrated in FIG. 3, at step **302** one or more of the systems described herein may detect data associated with fingerprinting functions called in a target web page. For example, detection module **104** may, as part of computing device **202** in FIG. 2, detect data **116** associated with fingerprinting functions **114** called in target web page **112**. In some examples, and as shown in FIG. 4, data **116** may include HTML elements **402**, HTML objects **404**, APIs **406**, and caller information **408** (e.g., first or third-party scripts utilized for calling fingerprinting functions **114**).

(25) Detection module **104** may receive and may detect data **116** in a variety of ways. In some examples, detection module **104** may collect information in HTML elements **402** (e.g., HTMLCanvasElement) and HTML objects **404** (e.g., RTCPeerConnection object) associated with the fingerprinting functions **114**. Additionally or alternatively, detection module **104** may track APIs **406** that may be utilized to dynamically modify target web page **112** (e.g., Element.ReplaceChild and Node.insertBefore). Additionally or alternatively, detection module **104** may track caller information **408** (e.g., first-party or third-party scripts that call fingerprinting functions **114**). Moreover, in some examples, detection module **104** may check a page hierarchy of target web page **112** by utilizing a dynamically generated resource tree to find a connection between the aforementioned scripts.

(26) At step **304**, one or more of the systems described herein may associate, based on the data detected at step **302**, fingerprints generated by the fingerprinting functions with a corresponding action. For example, association module **106** may, as part of computing device **202** in FIG. 2, associate fingerprints **118** with one or more actions **122** based on data **116**. In some examples, and as shown in FIG. 5, actions **122** may include content manipulation **502**, redirection **504**, storage

506, and parameter request **508**.

(27) Association module **106** may associate fingerprints **118** with actions **122** in a variety of ways. In some examples, association module **106** may identify a fingerprinting function **114** that utilizes a fingerprint **118** for content manipulation **502** and then associate fingerprinting function **114** with content manipulation **502**. Additionally or alternatively, association module **106** may identify a fingerprinting function **114** that utilizes a fingerprint **118** for redirection **504** (e.g., redirecting a user of target web page **112** to another web page) and then associate fingerprinting function **114** with redirection **504**. Additionally or alternatively, association module **106** may identify a fingerprinting function **114** that performs storage **506** and then associate fingerprinting function **114** with storage **506**. In this example, a fingerprinting function **114** may be configured to store fingerprints **118** in either HTTP cookies (e.g., web browser cookies) or another device storage utilized by computing device **202**. Additionally or alternatively, association module **106** may identify a fingerprinting function **114** that performs parameter request **508** and then associate fingerprinting function **114** with parameter request **508**. In this example, a fingerprinting function **114** may be configured to send fingerprints **118** in within parameters of requests. In some embodiments, association module **106** may associate a specific set of actions **122** performed in each of the aforementioned examples including the types of data (e.g., data **116**).

(28) At step **306**, one or more of the systems described herein may identify, based on the data detected at step **302**, callee information associated with the fingerprinting functions. For example, identification module **106** may, as part of computing device **202** in FIG. 2, identify callee information **210** based on data **116**.

(29) Identification module **108** may identify callee information **210** in a variety of ways. In some examples, identification module **108** may identify callee information **210** by determining a domain name associated with a third-party callee. For example, identification module **108** (in order to increase the precision of a generated fingerprint signature **124**), may include a domain of a third-party callee of a fingerprinting function **114** in a data structure (e.g., `canvasrenderingcontext2d.measureText, domain.com.`). In some examples, upon identifying a first-party callee from callee information **210**, identification module **108** may identify (e.g., mark) the first-party callee as “first.”

(30) At step **308**, one or more of the systems described herein may perform a security action that protects against malicious activity by calculating a cryptographic hash of a list including the fingerprinting functions and the corresponding actions to generate a fingerprint signature for the target web page. For example, security module **110** may, as part of computing device **202** in FIG. 2, calculate cryptographic hash **212** to generate fingerprint signature **124**.

(31) Security module **110** may generate fingerprint signature **124** in a variety of ways. In some examples, security module **110** may compute a hash of a list of ordered fingerprinting functions **114** and corresponding parameter pairs (e.g., parameter pairs in parameter request **508**). In one example, fingerprinting functions **114** may be ordered based on an order of actions **122** that are performed and the relationship between each action **122**.

(32) As explained in connection with method **300** above, the systems and methods described herein dynamically generating fingerprint signatures. The systems and methods described herein may collect data about fingerprinting functions in web pages, track APIs that can be used to dynamically the fingerprinting functions, and check a web page hierarchy by utilizing a dynamically generated resource tree to find connections between scripts associated with the fingerprinting functions. Additionally, the systems and methods described herein may associate the fingerprinting functions based on their associated intentions/actions such as (i) the utilization of fingerprints for content manipulation/redirection and (ii) the storing of fingerprints in web cookies (or other storage) or the sending of the fingerprints within request parameters. Additionally, the systems and methods described herein may, for generating precise fingerprinting signatures, incorporate information about the callee of the fingerprinting functions, such as including the associated domain name for

third-party callees, and further incorporate the order of the actions and the relationship between the actions. Finally, the systems and methods herein may compute a cryptographic hash of an ordered list of the fingerprinting functions (along with their corresponding parameter pairs) to generate the fingerprinting signatures. By generating fine-grained fingerprinting signatures in this way, the detection of malicious web pages that reuse fingerprinting code (e.g., by bypassing authentication checks) for multiple targets and across multiple categories (e.g., malicious cyber campaigns carried out by hacker group clusters) may be realized.

(33) FIG. 6 is a block diagram of an example computing system **610** capable of implementing one or more of the embodiments described and/or illustrated herein. For example, all or a portion of computing system **610** may perform and/or be a means for performing, either alone or in combination with other elements, one or more of the steps described herein (such as one or more of the steps illustrated in FIG. 3). All or a portion of computing system **610** may also perform and/or be a means for performing any other steps, methods, or processes described and/or illustrated herein.

(34) Computing system **610** broadly represents any single or multi-processor computing device or system capable of executing computer-readable instructions. Examples of computing system **610** include, without limitation, workstations, laptops, client-side terminals, servers, distributed computing systems, handheld devices, or any other computing system or device. In its most basic configuration, computing system **610** may include at least one processor **614** and a system memory **616**.

(35) Processor **614** generally represents any type or form of physical processing unit (e.g., a hardware-implemented central processing unit) capable of processing data or interpreting and executing instructions. In certain embodiments, processor **614** may receive instructions from a software application or module. These instructions may cause processor **614** to perform the functions of one or more of the example embodiments described and/or illustrated herein.

(36) System memory **616** generally represents any type or form of volatile or non-volatile storage device or medium capable of storing data and/or other computer-readable instructions. Examples of system memory **616** include, without limitation, Random Access Memory (RAM), Read Only Memory (ROM), flash memory, or any other suitable memory device. Although not required, in certain embodiments computing system **610** may include both a volatile memory unit (such as, for example, system memory **616**) and a non-volatile storage device (such as, for example, primary storage device **632**, as described in detail below). In one example, one or more of modules **102** from FIG. 1 may be loaded into system memory **616**.

(37) In some examples, system memory **616** may store and/or load an operating system **640** for execution by processor **614**. In one example, operating system **640** may include and/or represent software that manages computer hardware and software resources and/or provides common services to computer programs and/or applications on computing system **610**. Examples of operating system **640** include, without limitation, LINUX, JUNOS, MICROSOFT WINDOWS, WINDOWS MOBILE, MAC OS, APPLE'S IOS, UNIX, GOOGLE CHROME OS, GOOGLE'S ANDROID, SOLARIS, variations of one or more of the same, and/or any other suitable operating system.

(38) In certain embodiments, example computing system **610** may also include one or more components or elements in addition to processor **614** and system memory **616**. For example, as illustrated in FIG. 6, computing system **610** may include a memory controller **618**, an Input/Output (I/O) controller **620**, and a communication interface **622**, each of which may be interconnected via a communication infrastructure **612**. Communication infrastructure **612** generally represents any type or form of infrastructure capable of facilitating communication between one or more components of a computing device. Examples of communication infrastructure **612** include, without limitation, a communication bus (such as an Industry Standard Architecture (ISA), Peripheral Component Interconnect (PCI), PCI Express (PCIe), or similar bus) and a network.

(39) Memory controller **618** generally represents any type or form of device capable of handling memory or data or controlling communication between one or more components of computing system **610**. For example, in certain embodiments memory controller **618** may control communication between processor **614**, system memory **616**, and I/O controller **620** via communication infrastructure **612**.

(40) I/O controller **620** generally represents any type or form of module capable of coordinating and/or controlling the input and output functions of a computing device. For example, in certain embodiments I/O controller **620** may control or facilitate transfer of data between one or more elements of computing system **610**, such as processor **614**, system memory **616**, communication interface **622**, display adapter **626**, input interface **630**, and storage interface **634**.

(41) As illustrated in FIG. 6, computing system **610** may also include at least one display device **624** coupled to I/O controller **620** via a display adapter **626**. Display device **624** generally represents any type or form of device capable of visually displaying information forwarded by display adapter **626**. Similarly, display adapter **626** generally represents any type or form of device configured to forward graphics, text, and other data from communication infrastructure **612** (or from a frame buffer, as known in the art) for display on display device **624**.

(42) As illustrated in FIG. 6, example computing system **610** may also include at least one input device **628** coupled to I/O controller **620** via an input interface **630**. Input device **628** generally represents any type or form of input device capable of providing input, either computer or human generated, to example computing system **610**. Examples of input device **628** include, without limitation, a keyboard, a pointing device, a speech recognition device, variations or combinations of one or more of the same, and/or any other input device.

(43) Additionally or alternatively, example computing system **610** may include additional I/O devices. For example, example computing system **610** may include I/O device **636**. In this example, I/O device **636** may include and/or represent a user interface that facilitates human interaction with computing system **610**. Examples of I/O device **636** include, without limitation, a computer mouse, a keyboard, a monitor, a printer, a modem, a camera, a scanner, a microphone, a touchscreen device, variations or combinations of one or more of the same, and/or any other I/O device.

(44) Communication interface **622** broadly represents any type or form of communication device or adapter capable of facilitating communication between example computing system **610** and one or more additional devices. For example, in certain embodiments communication interface **622** may facilitate communication between computing system **610** and a private or public network including additional computing systems. Examples of communication interface **622** include, without limitation, a wired network interface (such as a network interface card), a wireless network interface (such as a wireless network interface card), a modem, and any other suitable interface. In at least one embodiment, communication interface **622** may provide a direct connection to a remote server via a direct link to a network, such as the Internet. Communication interface **622** may also indirectly provide such a connection through, for example, a local area network (such as an Ethernet network), a personal area network, a telephone or cable network, a cellular telephone connection, a satellite data connection, or any other suitable connection.

(45) In certain embodiments, communication interface **622** may also represent a host adapter configured to facilitate communication between computing system **610** and one or more additional network or storage devices via an external bus or communications channel. Examples of host adapters include, without limitation, Small Computer System Interface (SCSI) host adapters, Universal Serial Bus (USB) host adapters, Institute of Electrical and Electronics Engineers (IEEE) 1394 host adapters, Advanced Technology Attachment (ATA), Parallel ATA (PATA), Serial ATA (SATA), and External SATA (eSATA) host adapters, Fibre Channel interface adapters, Ethernet adapters, or the like. Communication interface **622** may also allow computing system **610** to engage in distributed or remote computing. For example, communication interface **622** may receive

instructions from a remote device or send instructions to a remote device for execution.

(46) In some examples, system memory **616** may store and/or load a network communication program **638** for execution by processor **614**. In one example, network communication program **638** may include and/or represent software that enables computing system **610** to establish a network connection **642** with another computing system (not illustrated in FIG. **6**) and/or communicate with the other computing system by way of communication interface **622**. In this example, network communication program **638** may direct the flow of outgoing traffic that is sent to the other computing system via network connection **642**. Additionally or alternatively, network communication program **638** may direct the processing of incoming traffic that is received from the other computing system via network connection **642** in connection with processor **614**.

(47) Although not illustrated in this way in FIG. **6**, network communication program **638** may alternatively be stored and/or loaded in communication interface **622**. For example, network communication program **638** may include and/or represent at least a portion of software and/or firmware that is executed by a processor and/or Application Specific Integrated Circuit (ASIC) incorporated in communication interface **622**.

(48) As illustrated in FIG. **6**, example computing system **610** may also include a primary storage device **632** and a backup storage device **633** coupled to communication infrastructure **612** via a storage interface **634**. Storage devices **632** and **633** generally represent any type or form of storage device or medium capable of storing data and/or other computer-readable instructions. For example, storage devices **632** and **633** may be a magnetic disk drive (e.g., a so-called hard drive), a solid state drive, a floppy disk drive, a magnetic tape drive, an optical disk drive, a flash drive, or the like. Storage interface **634** generally represents any type or form of interface or device for transferring data between storage devices **632** and **633** and other components of computing system **610**. In one example, data storage **120** from FIG. **1** may be stored and/or loaded in primary storage device **632**.

(49) In certain embodiments, storage devices **632** and **633** may be configured to read from and/or write to a removable storage unit configured to store computer software, data, or other computer-readable information. Examples of suitable removable storage units include, without limitation, a floppy disk, a magnetic tape, an optical disk, a flash memory device, or the like. Storage devices **632** and **633** may also include other similar structures or devices for allowing computer software, data, or other computer-readable instructions to be loaded into computing system **610**. For example, storage devices **632** and **633** may be configured to read and write software, data, or other computer-readable information. Storage devices **632** and **633** may also be a part of computing system **610** or may be a separate device accessed through other interface systems.

(50) Many other devices or subsystems may be connected to computing system **610**. Conversely, all of the components and devices illustrated in FIG. **6** need not be present to practice the embodiments described and/or illustrated herein. The devices and subsystems referenced above may also be interconnected in different ways from that shown in FIG. **6**. Computing system **610** may also employ any number of software, firmware, and/or hardware configurations. For example, one or more of the example embodiments disclosed herein may be encoded as a computer program (also referred to as computer software, software applications, computer-readable instructions, or computer control logic) on a computer-readable medium. The term “computer-readable medium,” as used herein, generally refers to any form of device, carrier, or medium capable of storing or carrying computer-readable instructions. Examples of computer-readable media include, without limitation, transmission-type media, such as carrier waves, and non-transitory-type media, such as magnetic-storage media (e.g., hard disk drives, tape drives, and floppy disks), optical-storage media (e.g., Compact Disks (CDs), Digital Video Disks (DVDs), and BLU-RAY disks), electronic-storage media (e.g., solid-state drives and flash media), and other distribution systems.

(51) The computer-readable medium containing the computer program may be loaded into computing system **610**. All or a portion of the computer program stored on the computer-readable

medium may then be stored in system memory **616** and/or various portions of storage devices **632** and **633**. When executed by processor **614**, a computer program loaded into computing system **610** may cause processor **614** to perform and/or be a means for performing the functions of one or more of the example embodiments described and/or illustrated herein. Additionally or alternatively, one or more of the example embodiments described and/or illustrated herein may be implemented in firmware and/or hardware. For example, computing system **610** may be configured as an Application Specific Integrated Circuit (ASIC) adapted to implement one or more of the example embodiments disclosed herein.

(52) FIG. 7 is a block diagram of an example network architecture **700** in which client systems **710**, **720**, and **730** and servers **740** and **745** may be coupled to a network **750**. As detailed above, all or a portion of network architecture **700** may perform and/or be a means for performing, either alone or in combination with other elements, one or more of the steps disclosed herein (such as one or more of the steps illustrated in FIG. 3). All or a portion of network architecture **700** may also be used to perform and/or be a means for performing other steps and features set forth in the present disclosure.

(53) Client systems **710**, **720**, and **730** generally represent any type or form of computing device or system, such as example computing system **610** in FIG. 6. Similarly, servers **740** and **745** generally represent computing devices or systems, such as application servers or database servers, configured to provide various database services and/or run certain software applications. Network **750** generally represents any telecommunication or computer network including, for example, an intranet, a WAN, a LAN, a PAN, or the Internet. In one example, client systems **710**, **720**, and/or **730** and/or servers **740** and/or **745** may include all or a portion of system **100** from FIG. 1.

(54) As illustrated in FIG. 7, one or more storage devices **760(1)-(N)** may be directly attached to server **740**. Similarly, one or more storage devices **770(1)-(N)** may be directly attached to server **745**. Storage devices **760(1)-(N)** and storage devices **770(1)-(N)** generally represent any type or form of storage device or medium capable of storing data and/or other computer-readable instructions. In certain embodiments, storage devices **760(1)-(N)** and storage devices **770(1)-(N)** may represent Network-Attached Storage (NAS) devices configured to communicate with servers **740** and **745** using various protocols, such as Network File System (NFS), Server Message Block (SMB), or Common Internet File System (CIFS).

(55) Servers **740** and **745** may also be connected to a Storage Area Network (SAN) fabric **780**. SAN fabric **780** generally represents any type or form of computer network or architecture capable of facilitating communication between a plurality of storage devices. SAN fabric **780** may facilitate communication between servers **740** and **745** and a plurality of storage devices **790(1)-(N)** and/or an intelligent storage array **795**. SAN fabric **780** may also facilitate, via network **750** and servers **740** and **745**, communication between client systems **710**, **720**, and **730** and storage devices **790(1)-(N)** and/or intelligent storage array **795** in such a manner that devices **790(1)-(N)** and array **795** appear as locally attached devices to client systems **710**, **720**, and **730**. As with storage devices **760(1)-(N)** and storage devices **770(1)-(N)**, storage devices **790(1)-(N)** and intelligent storage array **795** generally represent any type or form of storage device or medium capable of storing data and/or other computer-readable instructions.

(56) In certain embodiments, and with reference to example computing system **610** of FIG. 6, a communication interface, such as communication interface **622** in FIG. 6, may be used to provide connectivity between each client system **710**, **720**, and **730** and network **750**. Client systems **710**, **720**, and **730** may be able to access information on server **740** or **745** using, for example, a web browser or other client software. Such software may allow client systems **710**, **720**, and **730** to access data hosted by server **740**, server **745**, storage devices **760(1)-(N)**, storage devices **770(1)-(N)**, storage devices **790(1)-(N)**, or intelligent storage array **795**. Although FIG. 7 depicts the use of a network (such as the Internet) for exchanging data, the embodiments described and/or illustrated herein are not limited to the Internet or any particular network-based environment.

(57) In at least one embodiment, all or a portion of one or more of the example embodiments disclosed herein may be encoded as a computer program and loaded onto and executed by server **740**, server **745**, storage devices **760(1)-(N)**, storage devices **770(1)-(N)**, storage devices **790(1)-(N)**, intelligent storage array **795**, or any combination thereof. All or a portion of one or more of the example embodiments disclosed herein may also be encoded as a computer program, stored in server **740**, run by server **745**, and distributed to client systems **710**, **720**, and **730** over network **750**.

(58) As detailed above, computing system **610** and/or one or more components of network architecture **700** may perform and/or be a means for performing, either alone or in combination with other elements, one or more steps of an example method for dynamically generating fingerprint signatures.

(59) While the foregoing disclosure sets forth various embodiments using specific block diagrams, flowcharts, and examples, each block diagram component, flowchart step, operation, and/or component described and/or illustrated herein may be implemented, individually and/or collectively, using a wide range of hardware, software, or firmware (or any combination thereof) configurations. In addition, any disclosure of components contained within other components should be considered example in nature since many other architectures can be implemented to achieve the same functionality.

(60) In some examples, all or a portion of example system **100** in FIG. **1** may represent portions of a cloud-computing or network-based environment. Cloud-computing environments may provide various services and applications via the Internet. These cloud-based services (e.g., software as a service, platform as a service, infrastructure as a service, etc.) may be accessible through a web browser or other remote interface. Various functions described herein may be provided through a remote desktop environment or any other cloud-based computing environment.

(61) In various embodiments, all or a portion of example system **100** in FIG. **1** may facilitate multi-tenancy within a cloud-based computing environment. In other words, the software modules described herein may configure a computing system (e.g., a server) to facilitate multi-tenancy for one or more of the functions described herein. For example, one or more of the software modules described herein may program a server to enable two or more clients (e.g., customers) to share an application that is running on the server. A server programmed in this manner may share an application, operating system, processing system, and/or storage system among multiple customers (i.e., tenants). One or more of the modules described herein may also partition data and/or configuration information of a multi-tenant application for each customer such that one customer cannot access data and/or configuration information of another customer.

(62) According to various embodiments, all or a portion of example system **100** in FIG. **1** may be implemented within a virtual environment. For example, the modules and/or data described herein may reside and/or execute within a virtual machine. As used herein, the term “virtual machine” generally refers to any operating system environment that is abstracted from computing hardware by a virtual machine manager (e.g., a hypervisor). Additionally or alternatively, the modules and/or data described herein may reside and/or execute within a virtualization layer. As used herein, the term “virtualization layer” generally refers to any data layer and/or application layer that overlays and/or is abstracted from an operating system environment. A virtualization layer may be managed by a software virtualization solution (e.g., a file system filter) that presents the virtualization layer as though it were part of an underlying base operating system. For example, a software virtualization solution may redirect calls that are initially directed to locations within a base file system and/or registry to locations within a virtualization layer.

(63) In some examples, all or a portion of example system **100** in FIG. **1** may represent portions of a mobile computing environment. Mobile computing environments may be implemented by a wide range of mobile computing devices, including mobile phones, tablet computers, e-book readers, personal digital assistants, wearable computing devices (e.g., computing devices with a head-

mounted display, smartwatches, etc.), and the like. In some examples, mobile computing environments may have one or more distinct features, including, for example, reliance on battery power, presenting only one foreground application at any given time, remote management features, touchscreen features, location and movement data (e.g., provided by Global Positioning Systems, gyroscopes, accelerometers, etc.), restricted platforms that restrict modifications to system-level configurations and/or that limit the ability of third-party software to inspect the behavior of other applications, controls to restrict the installation of applications (e.g., to only originate from approved application stores), etc. Various functions described herein may be provided for a mobile computing environment and/or may interact with a mobile computing environment.

(64) In addition, all or a portion of example system **100** in FIG. **1** may represent portions of, interact with, consume data produced by, and/or produce data consumed by one or more systems for information management. As used herein, the term “information management” may refer to the protection, organization, and/or storage of data. Examples of systems for information management may include, without limitation, storage systems, backup systems, archival systems, replication systems, high availability systems, data search systems, virtualization systems, and the like.

(65) In some embodiments, all or a portion of example system **100** in FIG. **1** may represent portions of, produce data protected by, and/or communicate with one or more systems for information security. As used herein, the term “information security” may refer to the control of access to protected data. Examples of systems for information security may include, without limitation, systems providing managed security services, data loss prevention systems, identity authentication systems, access control systems, encryption systems, policy compliance systems, intrusion detection and prevention systems, electronic discovery systems, and the like.

(66) According to some examples, all or a portion of example system **100** in FIG. **1** may represent portions of, communicate with, and/or receive protection from one or more systems for endpoint security. As used herein, the term “endpoint security” may refer to the protection of endpoint systems from unauthorized and/or illegitimate use, access, and/or control. Examples of systems for endpoint protection may include, without limitation, anti-malware systems, user authentication systems, encryption systems, privacy systems, spam-filtering services, and the like.

(67) The process parameters and sequence of steps described and/or illustrated herein are given by way of example only and can be varied as desired. For example, while the steps illustrated and/or described herein may be shown or discussed in a particular order, these steps do not necessarily need to be performed in the order illustrated or discussed. The various example methods described and/or illustrated herein may also omit one or more of the steps described or illustrated herein or include additional steps in addition to those disclosed.

(68) While various embodiments have been described and/or illustrated herein in the context of fully functional computing systems, one or more of these example embodiments may be distributed as a program product in a variety of forms, regardless of the particular type of computer-readable media used to actually carry out the distribution. The embodiments disclosed herein may also be implemented using software modules that perform certain tasks. These software modules may include script, batch, or other executable files that may be stored on a computer-readable storage medium or in a computing system. In some embodiments, these software modules may configure a computing system to perform one or more of the example embodiments disclosed herein.

(69) In addition, one or more of the modules described herein may transform data, physical devices, and/or representations of physical devices from one form to another. Additionally or alternatively, one or more of the modules recited herein may transform a processor, volatile memory, non-volatile memory, and/or any other portion of a physical computing device from one form to another by executing on the computing device, storing data on the computing device, and/or otherwise interacting with the computing device.

(70) The preceding description has been provided to enable others skilled in the art to best utilize various aspects of the example embodiments disclosed herein. This example description is not

intended to be exhaustive or to be limited to any precise form disclosed. Many modifications and variations are possible without departing from the spirit and scope of the present disclosure. The embodiments disclosed herein should be considered in all respects illustrative and not restrictive. Reference should be made to the appended claims and their equivalents in determining the scope of the present disclosure.

(71) Unless otherwise noted, the terms “connected to” and “coupled to” (and their derivatives), as used in the specification and claims, are to be construed as permitting both direct and indirect (i.e., via other elements or components) connection. In addition, the terms “a” or “an,” as used in the specification and claims, are to be construed as meaning “at least one of.” Finally, for ease of use, the terms “including” and “having” (and their derivatives), as used in the specification and claims, are interchangeable with and have the same meaning as the word “comprising.”

Claims

1. A computer-implemented method for dynamically generating fingerprint signatures, at least a portion of the method being performed by one or more computing devices comprising at least one processor, the method comprising: detecting, by the one or more computing devices, data associated with one or more fingerprinting functions called in a target web page; associating, by the one or more computing devices and based on the data, each of one or more fingerprints generated by the fingerprinting functions with a corresponding action; identifying, by the one more computing devices and based on the data, callee information associated with each of the fingerprinting functions; and performing, by the one or more computing devices, a security action that protects against malicious activity by calculating a cryptographic hash of a list comprising the fingerprinting functions and the corresponding actions to generate a fingerprint signature for the target web page.
2. The computer-implemented method of claim 1, wherein detecting the data associated with the fingerprinting functions called in the target web page comprises detecting at least one of: hypertext markup language (HTML) elements associated with the fingerprinting functions; and HTML objects associated with the fingerprinting functions.
3. The computer-implemented method of claim 1, wherein detecting the data associated with the fingerprinting functions called in the target web page comprises tracking one or more application programming interfaces (APIs) utilized by the fingerprinting functions to dynamically modify the target web page.
4. The computer-implemented method of claim 1, wherein detecting the data associated with the fingerprinting functions called in the target web page comprises utilizing a dynamically generated resource tree for finding a connection between scripts in the target web page.
5. The computer-implemented method of claim 1, wherein associating, based on the data, the each of one or more the fingerprints generated by the fingerprinting functions with the corresponding action comprises: identifying a target function that utilizes any of the one or more of the fingerprints for a content manipulation action; and associating the target function with the content manipulation action.
6. The computer-implemented method of claim 1, wherein associating, based on the data, the each of one or more the fingerprints generated by the fingerprinting functions with the corresponding action comprises: identifying a target function that utilizes any of the one or more of the fingerprints for a redirection action; and associating the target function with the redirection action.
7. The computer-implemented method of claim 1, wherein associating, based on the data, the each of one or more the fingerprints generated by the fingerprinting functions with the corresponding action comprises: identifying a target function that performs a storage action for any of the one or more of the fingerprints; and associating the target function with the storage action.
8. The computer-implemented method of claim 1, wherein associating, based on the data, the each

of one or more the fingerprints generated by the fingerprinting functions with the corresponding action comprises: identifying a target function that performs an action for sending any of the one or more of the fingerprints within a request parameter; and associating the target function with the action.

9. The computer-implemented method of claim 1, wherein identifying, based on the data, callee information associated with each of the fingerprinting functions comprises determining a domain name associated with a third-party callee based on the callee information.

10. The computer-implemented method of claim 1, wherein the malicious activity comprises a cloaking operation that delivers new content to a user of the target web page that is different than native content associated with the target web page.

11. The computer-implemented method of claim 1, wherein the fingerprint signature is at least one of: a device fingerprint signature; or a browser fingerprint signature.

12. A system for dynamically generating fingerprint signatures, the system comprising: at least one physical processor; physical memory comprising computer-executable instructions and one or more modules that, when executed by the physical processor, cause the physical processor to: detect, by a detection module, data associated with one or more fingerprinting functions called in a target web page; associate, by an association module and based on the data, each of one or more fingerprints generated by the fingerprinting functions with a corresponding action; identify, by an identification module and based on the data, callee information associated with each of the fingerprinting functions; and perform, by a security module, a security action that protects against malicious activity by calculating a cryptographic hash of a list comprising the fingerprinting functions and the corresponding actions to generate a fingerprint signature for the target web page.

13. The system of claim 12, wherein the detection module detects the data associated with the fingerprinting functions called in the target web page by detecting at least one of: hypertext markup language (HTML) elements associated with the fingerprinting functions; and HTML objects associated with the fingerprinting functions.

14. The system of claim 12, wherein the detection module detects the data associated with the fingerprinting functions called in the target web page by tracking one or more application programming interfaces (APIs) utilized by the fingerprinting functions to dynamically modify the target web page.

15. The system of claim 12, wherein the detection module detects the data associated with the fingerprinting functions called in the target web page by utilizing a dynamically generated resource tree for finding a connection between scripts in the target web page.

16. The system of claim 12, wherein the association module associates, based on the data, the each of one or more the fingerprints generated by the fingerprinting functions with the corresponding action by: identifying a target function that utilizes any of the one or more of the fingerprints for a content manipulation action; and associating the target function with the content manipulation action.

17. The system of claim 12, wherein the association module associates, based on the data, the each of one or more the fingerprints generated by the fingerprinting functions with the corresponding action by: identifying a target function that utilizes any of the one or more of the fingerprints for a redirection action; and associating the target function with the redirection action.

18. The system of claim 12, wherein the association module associates, based on the data, the each of one or more the fingerprints generated by the fingerprinting functions with the corresponding action by: identifying a target function that performs a storage action for any of the one or more of the fingerprints; and associating the target function with the storage action.

19. The system of claim 12, wherein the association module associates, based on the data, the each of one or more the fingerprints generated by the fingerprinting functions with the corresponding action by: identifying a target function that performs an action for sending any of the one or more of the fingerprints within a request parameter; and associating the target function with the action.

20. A non-transitory computer-readable medium comprising one or more computer-executable instructions that, when executed by at least one processor of a computing device, cause the computing device to: detect data associated with one or more fingerprinting functions called in a target web page; associate, based on the data, each of one or more fingerprints generated by the fingerprinting functions with a corresponding action; identify, based on the data, callee information associated with each of the fingerprinting functions; and perform a security action that protects against malicious activity by calculating a cryptographic hash of a list comprising the fingerprinting functions and the corresponding actions to generate a fingerprint signature for the target web page.
