

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12414805
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Gault; James A. et al.

Implantable compression screws

Abstract

A compression screw for applying compression at a bone joint. The compression screw includes an axial screw body extending from a distal end to a proximal end with the distal end including a series of bone engaging threads configured to be self-drilling and self-tapping and the proximal end including a head which defines a radially extending shoulder. At least one proximal rotary cutting structure is defined proximally of the bone engaging threads. The at least one proximal rotary cutting structure is configured to be self-drilling such that a proximal portion of the axial screw body cuts into and advances within a bone of the bone joint as the axial screw body is advanced. A method of inserting the compression screw is also provided.

Inventors: Gault; James A. (Philadelphia, PA), Davis; Barclay (Glenmoore, PA)

Applicant: GLOBUS MEDICAL, INC. (Audubon, PA)

Family ID: 1000008822360

Assignee: Globus Medical, Inc. (Audubon, PA)

Appl. No.: 18/310844

Filed: May 02, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230270480 A1	Aug. 31, 2023

Related U.S. Application Data

continuation parent-doc US 16704684 20191205 US 11638600 child-doc US 18310844
division parent-doc US 15132368 20160419 US 10531905 20200114 child-doc US 16704684

Publication Classification

Int. Cl.: A61B17/86 (20060101); A61B17/68 (20060101); A61B17/88 (20060101)

U.S. Cl.:

CPC A61B17/8635 (20130101); A61B17/68 (20130101); A61B17/8605 (20130101); A61B17/863 (20130101); A61B17/864 (20130101); A61B17/8685 (20130101); A61B17/8875 (20130101); A61B17/888 (20130101); A61B2017/8655 (20130101)

Field of Classification Search

CPC: A61B (17/8685); A61B (2017/681)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4175555	12/1978	Herbert	N/A	N/A
4432358	12/1983	Fixel	606/66	A61B 17/742
4858601	12/1988	Glisson	N/A	N/A
5217462	12/1992	Asnis	606/301	A61B 17/888
5498265	12/1995	Asnis	606/53	A61B 17/74
5527312	12/1995	Ray	N/A	N/A
5743912	12/1997	Lahille	606/65	A61B 17/746
5871486	12/1998	Huebner et al.	N/A	N/A
6030162	12/1999	Huebner	N/A	N/A
6074391	12/1999	Metz-Stavenhagen et al.	N/A	N/A
6319269	12/2000	Li	N/A	N/A
6368319	12/2001	Schaefer	N/A	N/A
6485518	12/2001	Cornwall et al.	N/A	N/A
6540747	12/2002	Marino	N/A	N/A
6547795	12/2002	Schneiderman	N/A	N/A
6648893	12/2002	Dudasik	N/A	N/A
6669698	12/2002	Tromanhauser et al.	N/A	N/A
6808526	12/2003	Mageri et al.	N/A	N/A
6887243	12/2004	Culbert	N/A	N/A
6951561	12/2004	Warren et al.	N/A	N/A
6964664	12/2004	Freid et al.	N/A	N/A
7044483	12/2005	Capanni	N/A	N/A
7371238	12/2007	Soboleski et al.	N/A	N/A
7794483	12/2009	Capanni	N/A	N/A
9089371	12/2014	Faulhaber	N/A	A61B 17/7032
9795412	12/2016	Sinha	N/A	N/A
2003/0045881	12/2002	Barouk et al.	N/A	N/A
2004/0068261	12/2003	Fourcault et al.	N/A	N/A
2004/0260298	12/2003	Kaiser et al.	N/A	N/A
2005/0143735	12/2004	Kyle	N/A	N/A
2005/0149030	12/2004	Serhan et al.	N/A	N/A

2005/0203522	12/2004	Vaughan	N/A	N/A
2006/0039772	12/2005	Matthys-Mark	411/5	A61B 17/86
2006/0085068	12/2005	Barry	N/A	N/A
2006/0200137	12/2005	Soboleski et al.	N/A	N/A
2006/0276790	12/2005	Dawson et al.	N/A	N/A
2007/0112428	12/2006	Lancial	N/A	N/A
2007/0118132	12/2006	Culbert et al.	N/A	N/A
2009/0192551	12/2008	Cianfrani et al.	N/A	N/A
2013/0238036	12/2012	Sinha	606/317	A61B 17/88
2013/0338722	12/2012	Yalizis	N/A	N/A
2015/0150615	12/2014	Anapliotis	606/305	A61B 17/8685
2015/0250515	12/2014	Terrill et al.	N/A	N/A
2015/0327902	12/2014	Eekhoff	606/310	A61B 17/8891
2016/0287301	12/2015	Mehl et al.	N/A	N/A
2018/0008317	12/2017	Sinha	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
103054642	12/2012	CN	N/A
200433767	12/2003	JP	N/A
2004008949	12/2003	WO	N/A
2004069031	12/2003	WO	N/A
2004098453	12/2003	WO	N/A

Primary Examiner: Bates; David W

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 16/704,684, filed Dec. 5, 2019, which is a division of U.S. patent application Ser. No. 15/132,368, filed Apr. 19, 2016, all of which are incorporated by reference herein in their entirety for all purposes.

FIELD OF THE INVENTION

(1) The present disclosure relates to implantable screws. More particularly, the disclosure relates to implantable screws configured to provide compression upon a bone into which the screw is implanted.

BACKGROUND OF THE INVENTION

(2) A broken bone must be carefully stabilized and supported until it is strong enough to handle the body's weight and movement. Until the last century, physicians relied on casts and splints to support and stabilize the bone from outside the body. The advent of sterile surgical procedures reduced the risk of infection, allowing doctors to internally set and stabilize fractured bones. During a surgical procedure to set a fracture, the bone fragments are first repositioned (reduced) into their normal alignment. They are held together with special implants, such as plates, screws, nails and wires.

(3) Screws are used for internal fixation more often than any other type of implant. Although the screw is a simple device, there are different designs based on the type of fracture and how the screw will be used. Screws come in different sizes for use with bones of different sizes. Screws can be used alone to hold a fracture, as well as with plates, rods, or nails. After the bone heals, screws

may be either left in place or removed.

(4) In many instances, it is desired that the inserted screw provide compression at the bone joint or fracture line to reduce the incidence of nonunion (improper healing) and malunion (healing in improper position) of broken bones.

SUMMARY OF THE INVENTION

(5) To meet this and other needs, devices, systems, and methods for fixating bone are provided. In particular, bone screws are provided that apply compression to bone fragments or bone portions (for example, fixation of fractures or fusion of joints), are self-tapping and/or self-drilling, minimize or prevent screw toggle and/or back-out, remove bone build-up (for example, from cutting flutes), and the like.

(6) In at least one embodiment, a compression screw is provided for applying compression at a bone joint. The compression screw includes an axial screw body extending from a distal end to a proximal end with the distal end including a series of bone engaging threads configured to be self-drilling and self-tapping and the proximal end including a head which defines a radially extending shoulder. At least one proximal rotary cutting structure is defined proximally of the bone engaging threads. The at least one proximal rotary cutting structure is configured to be self-drilling such that a proximal portion of the axial screw body cuts into and advances within a bone of the bone joint as the axial screw body is advanced.

(7) In at least one embodiment, the compression screw for applying compression at a bone joint includes a bone screw and a compression sleeve. The bone screw extends from a distal end to a proximal end with the bone screw distal end including a series of bone engaging threads configured to be self-drilling and self-tapping and the bone screw proximal end including a series of external threads. The compression sleeve has a tubular body extending from a distal end to a proximal end with the compression sleeve distal end defining a proximal rotary cutting structure and the compression sleeve proximal end including a head which defines a radially extending shoulder. The compression sleeve includes internal threads engaged with the bone screw external threads such that the compression sleeve and bone screw are threadably adjustable relative to one another. The proximal rotary cutting structure is configured to be self-drilling such that a portion of the compression sleeve cuts into and advances within a bone of the bone joint as the compression screw is advanced.

(8) In at least one embodiment, a method of inserting a compression screw into a bone joint includes engaging the compression screw with a driver assembly, the driver assembly including a first driver and a second driver, the first and second drivers co-axial with one another and selectively rotatable together or independently of one another; rotating the first and second drivers simultaneously to advance the compression screw into the bone joint until the compression screw is at a first desired location; and rotating the first driver while maintaining the second driver stationary whereby at least a portion of the compression screw is further advanced into the bone joint such that a compressive force is applied to the bone joint.

(9) According to yet another embodiment, a method for applying compression between a first bone portion and a second bone portion having a gap therebetween includes inserting a compression screw in the first bone portion and the second bone portion, the compression screw comprising an outer sleeve and an inner bone screw, the outer sleeve having a non-threaded head which defines a radially extending shoulder, and the inner bone screw being threadably engaged with the outer sleeve, the compression screw being inserted into the first bone portion and the second bone portion as a single unit; and rotating the outer sleeve to move the inner bone screw toward the outer sleeve and reduce the gap between the first bone portion and the second bone portion. If desired, the entire compression screw may be removed by the outer sleeve.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The accompanying drawings, which are incorporated herein and constitute part of this specification, illustrate the presently preferred embodiments of the invention, and, together with the general description given above and the detailed description given below, serve to explain the features of the invention. In the drawings:
- (2) FIG. 1 is a plan view of a compression screw according to an embodiment of the invention.
- (3) FIG. 2 is an end view of the compression screw of FIG. 1.
- (4) FIG. 3 is a perspective view of a compression sleeve in accordance with another exemplary embodiment.
- (5) FIG. 4 is an expanded view of the cutting end of the compression sleeve of FIG. 3.
- (6) FIG. 5 is an expanded view of the cutting end of a compression sleeve in accordance with another exemplary embodiment.
- (7) FIG. 6 is an expanded view of the cutting end of a compression sleeve in accordance with yet another exemplary embodiment.
- (8) FIG. 7 is a plan view of an exemplary driver assembly configured for implantation of the compression screw of FIG. 1.
- (9) FIG. 8 is a cross-sectional view of the driver assembly of FIG. 7 engaged with the compression screw of FIG. 1.
- (10) FIG. 9 is a plan view of a compression screw according to another embodiment of the invention.
- (11) FIG. 10 is a plan view similar to FIG. 9 with the compression sleeve shown transparently.
- (12) FIG. 11 is a plan view of an exemplary driver assembly configured for implantation of the compression screw of FIG. 9.
- (13) FIG. 12 is a cross-sectional view of the driver assembly of FIG. 11.
- (14) FIG. 13 is a cross-sectional view of the driver assembly of FIG. 11 engaged with the compression screw of FIG. 9.
- (15) FIG. 14 is a plan view of a compression screw according to another embodiment of the invention.
- (16) FIG. 15 is an expanded perspective view of the tip of the compression screw of FIG. 14.
- (17) FIG. 16 is an expanded perspective view of the head of the compression screw of FIG. 14.
- (18) FIG. 17 is a plan view of an exemplary driver assembly engaging the compression screw of FIG. 14.
- (19) FIG. 18 is a cross-sectional view of the driver assembly of FIG. 17 engaged with the compression screw of FIG. 14.

DETAILED DESCRIPTION OF THE INVENTION

- (20) In the drawings, like numerals indicate like elements throughout. Certain terminology is used herein for convenience only and is not to be taken as a limitation on the present invention. The following describes preferred embodiments of the present invention. However, it should be understood, based on this disclosure, that the invention is not limited by the preferred embodiments described herein.
- (21) Devices, systems, and methods for fixating bone are provided. In particular, bone screws are provided that may apply compression to bone fragments or bone portions. This may be particularly effective, for example, in trauma applications for fixation of bone fractures and/or fusion of joints. The disclosed devices and methods may be used for repairing bones including, but not limited to, the femur, tibia, fibula, humerus, ulna, radius, metatarsals, phalanx, phalanges, ribs, spine, vertebrae, clavicle, and other bones. Any of the features described herein may be applied to standalone screws or screws that additionally include a compression sleeve.
- (22) Referring to FIGS. 1-2 and 8, a compression screw 10 in accordance with an embodiment will be described. The compression screw 10 generally comprises a bone screw 12 and a compression

sleeve **30**. The bone screw **12** and the compression sleeve **30** may be constructed from any biocompatible material including, but not limited to, stainless steel alloys, titanium, titanium based alloys, or polymeric materials.

(23) The bone screw **12** includes a shaft **14** extending from a distal end **11** to a proximal end **13**. Referring to FIGS. **2** and **8**, in the illustrated embodiment, a cannula **20** extends from the distal end **11** to the proximal end **13** such that a guide wire may be used for positioning the compression screw **10**. A drive feature **22** is defined in the proximal end **13** of the shaft **14** and is configured and dimensioned to be any shape that corresponds with the end of the driving instrument designed to engage the bone screw **12**. As an example, in the illustrated embodiment, the drive feature **22** has a hexalobular configuration.

(24) A series of bone engaging threads **15** extend radially from the shaft **14** at the distal end **11** and a series of sleeve engaging threads **18** extend radially from the shaft **14** at the proximal end **13**. In the preferred embodiment, the bone engaging threads **15** are dual lead thread type and the sleeve engaging threads **18** are a standard machine thread. However, any type of thread for either thread series **15**, **18** may be used to facilitate the function of the compression screw **10**. The bone screw **12** preferably also includes at least one cutting flute **16** configured to cut into the bone as the bone screw **12** is rotated, defining a self-drilling and self-tapping tip. In a preferred embodiment, a slot **17** is associated with each cutting flute **16** to clear any chips, dust, or debris generated when the compression screw **10** is implanted into bone tissue.

(25) The compression sleeve **30** includes a tubular body **32** extending from a distal end **31** to a proximal end **31** with an internal passage **40** therethrough. The compression sleeve **30** includes a series of internal threads **39** (see FIG. **8**) configured to engage the sleeve engaging threads **18** of the bone screw **12** such that the bone screw **12** and the compression sleeve **30** are threadably adjustable to one another. The proximal end **33** of the compression sleeve **30** defines a radially extending head **34** which defines a shoulder **35** between the tubular body **32** and the head **34**. A drive feature **42** is defined in the head **34** of the compression sleeve **30** and is configured and dimensioned to be any shape that corresponds with the end of the driving instrument designed to engage the compression sleeve **30**. As an example, in the illustrated embodiment, the drive feature **42** has a hexalobular configuration.

(26) As will be described in more detail hereinafter, during insertion of the implant, both drive features **22**, **42** are engaged such that the compression screw **10** maintains its full length. After the tip of the bone screw **12** is at the desired depth, only the drive feature **42** in the compression sleeve **30** is actuated. Since the two components are connected via threads, actuation of only the compression sleeve **30** will act to move the compression sleeve **30** distally toward the tip of the bone screw **12**, which shortens the length of the compression screw **10** and compresses the bone when the shoulder **35** of the compression sleeve **30** is on the near cortex.

(27) To facilitate such shortening of the compression screw **10**, the distal end **31** of the compression sleeve **30** is provided with one or more cutting flutes **36** configured to cut into the bone as the compression sleeve **30** is rotated. The cutting flutes **36** simplify the procedure by removing material without the necessity of drilling to the outer diameter of the compression sleeve tubular body **32**. This also allows the compression screw **10** to be adjusted to any length without the need to predrill to a desired depth to accommodate the compression sleeve **30**. In the present embodiment, the cutting flutes **36** define a proximal rotary cutting structure.

(28) In the alternative embodiment of the compression sleeve **30'** illustrated in FIGS. **3** and **4**, a slot **38** is associated with each cutting flute **36**, with each slot recessed into the surface of the tubular body **32** and configured to guide the aforementioned cut bone into the slots **38**. The mechanism of action for this technology relies on first the cutting flutes **36** to remove material from the substrate that it is being inserted into. This material then follows through the path of the slots **38** by one of two mechanisms: (1) path of least resistance (the material has nowhere else to go) or (2) the trajectory of the slots **38** roughly follows the pitch of the cutting flutes **36** as it is advanced into the

bone, and thus the cutaway material stays close to its original position as the screw advances axially via the screw's helix.

(29) The slots **38** serve two functions: (1) the cut bone that follows the slots **38** acts to enhance the fit between the native bone and the component being inserted into the bone and (2) allows for bony ingrowth to prevent dislodging of the compression screw **10**. The cutting flutes **36** act to remove bone and guide said removed bone into the slots **38**. This is in effect a self-grafting feature of the compression sleeve **30** which enhances purchase. Surgeons will sometimes remove bone and pack it back into the implant to enhance purchase, however, this configuration on the compression sleeve **30** does that for them. Enhanced purchase acts to prevent screw toggle and screw axial motion. Even if the slots **38** are not filled with bone, they can act to prevent both screw toggle and screw axial motion by providing a surface to catch on the native bone. Additionally, the slots **38** provide a surface for bony ingrowth which can also prevent screw toggle and screw axial motion.

(30) While the trajectory of the slots **38** is shown in the embodiment of FIGS. **3** and **4** to roughly follow the pitch of the cutting flutes **36**, the slots may have other configurations. For example, in the compression sleeve **30''** illustrated in FIG. **5**, the slot **38'** has a steeper trajectory than the pitch of the cutting flutes. FIG. **6** illustrates another embodiment of the compression sleeve **30'''** wherein the slot **38''** has an even steeper trajectory, being substantially parallel to the axis of the compression sleeve **30'''**. In addition to having different trajectories, the slots **38**, **38'**, **38''** may have different pitches resulting in the slots being spaced closer together or further apart. Additionally, the slots **38**, **38'**, **38''** may have different configurations, for example, semi-circular, semi-oval, v-shaped, square, rectangular or the like. Furthermore, while the combination of cutting flutes **36** and slots **38**, **38'**, **38''** are illustrated in conjunction with the compression sleeve **30**, it is recognized that such can be applied to a surface of any type of component that is being inserted into bone.

(31) Having generally described the compression screw **10**, an exemplary driver assembly **100** for inserting the compression screw **10** and an exemplary method of insertion will be described with reference to FIGS. **7** and **8**.

(32) The driver assembly **100** has a bone screw driver **110** and a compression sleeve driver **120**. The bone screw driver **110** includes a driver shaft **112** extending from a distal end **111** to a proximal end **113**. A driver tip **114** is defined on the distal end **111** of the driver shaft **112** and is configured to engage the driver feature **22** of the bone screw **12**. A connection key **115** is defined on the proximal end **113** of the driver shaft **112** and is configured to facilitate connection of the bone screw driver **110** to a manual or powered rotation device or a locking device which prevents rotation (not shown). A series of axial splines **116** extend radially from the driver shaft **112** and are configured to be selectively engaged by a connector switch **128** of the compression sleeve driver **120**, as will be described in more detail hereinafter. A series of external threads **119** extend from the driver shaft **112** distally of the splines **116**. The external threads **119** are configured to be selectively engaged by a thread engagement member **132** of the compression sleeve driver **120**, as will be described in more detail hereinafter.

(33) The compression sleeve driver **120** extends from a distal end **121** to a proximal end **123**. The proximal end **121** is defined by a tubular body **125** with a driver tip **124** at the distal most end and an outward housing **130** proximally therefrom. The driver tip **124** is configured to engage the driver feature **42** of the compression sleeve **30**. The housing **130** defines a radial chamber in which the thread engagement member **132** is radially moveable. Upon depression of the thread engagement member **132**, internal threads thereof engage the external threads **119** of the driver shaft **112** such that the driver shaft **112** is caused to move axially with the compression sleeve driver **120** when they are rotated together as will be described.

(34) A handle member **126** extends proximally from the housing **130** to the proximal end **123**. The connector switch **128** extends transversely through the handle member **126** and is moveable between a non-engaged position (see FIG. **8**) and an engaged position (see FIG. **13**). In the non-engaged position, an open area **129** of the connector switch **128** aligns with the splines **116** such

that the switch **128** is not engaged with the splines **116** and the compression sleeve driver **120** rotates independent of the bone screw driver **110**. In the engaged position, a contact portion **127** of the connector switch **128** engages the splines **116** such that rotation of the compression sleeve driver **120** causes simultaneous rotation of the bone screw driver **110**.

(35) To insert the compression screw **10**, the driver assembly **100** is positioned such that the driver tip **114** of the shaft **112** engages with the drive feature **22** of the bone screw **12** and the driver tip **124** of the tubular body **125** engages with the drive feature **42** of the compression sleeve **30**, as shown in FIG. **8**. During initial insertion, the connector switch **128** is moved to the engaged position such that the bone screw driver **110** and the compression sleeve driver **120** rotate together. The driver assembly **100** is rotated with both drivers **110**, **120** rotating and thus the compression screw **10** is advanced as a single unit until the distal end **11** of the bone screw **12** is at a desired location. The thread engagement member **132** may be depressed during such rotation to ensure that the shaft **112** advances axially during the simultaneous rotation. If the distal end **31** of the compression sleeve **30** contacts bone as the compression screw **10** is advanced, the proximal rotary cutting structure, i.e. the cutting flutes **36**, cut into the bone and the compression screw **10** is free to continue to advance as a single unit.

(36) After the distal end **11** of the bone screw **12** has landed at the desired location, compression may be achieved by advancing the compression sleeve **30** while the bone screw **12** remains stationary. The bone screw **12** remains stationary by holding the bone screw driver **110** stationary, for example, by attaching a locking device to the connection key **115**, and by disengaging the connector switch **128**. With the connector switch **128** moved to the disengaged position, the compression sleeve driver **120** rotates freely about the bone screw driver **110**. Rotation of the compression sleeve driver **120** causes the compression sleeve **30** to advance. Since the bone screw **12** is stationary as the compression sleeve driver **120** advances the compression sleeve **30**, the compression screw **10** shortens in length and the shoulder **35** thus applies compression. Again, the cutting flutes **36** on the compression sleeve distal end **31** allow the compression sleeve **30** to cut into and advance into the bone.

(37) Referring to FIGS. **9-10**, a compression screw **10'** in accordance with another exemplary embodiment will be described. The compression screw **10'** is substantially the same as the previous embodiment except with the addition of a self-countersinking head **34'** on the compression sleeve **30**.sup.iv. The self-countersinking head **34'** has a tapered shoulder **35'** and a series of external threads **37**. The threads **37** are configured to be self-drilling and self-tapping. The self-countersinking head **34'** is advantageous in that the head does not protrude from the near cortex, which minimizes soft-tissue irritation and can reduce the reoperation rate. In the present embodiment, the cutting flutes **36** and the threads **37** each define a proximal rotary cutting structure. In all other aspects, the compression screw **10'** is the same as the previously described compression screw **10**.

(38) Referring to FIGS. **11-13**, a driver assembly **100'** and method for inserting the compression screw **10'** will be described. The driver assembly **100'** is substantially the same as in the previous embodiment except for the distal end **121'** of tubular body **125'** of the compression sleeve driver **120'**. Instead of a driver tip, the distal end **121'** defines an internally threaded chamber **122** which threadably engages the threads **137** of the self-countersinking head **34'**.

(39) To insert the compression screw **10'**, the driver assembly **100'** is positioned such that the driver tip **114** of the shaft **112** engages with the drive feature **22** of the bone screw **12** and the threads **137** of the self-countersinking head **34'** are threadably received in the threaded chamber **122** of the compression sleeve driver **120'**, as shown in FIG. **13**. During initial insertion, the connector switch **128** is moved to the engaged position such that the bone screw driver **110** and the compression sleeve driver **120'** rotate together. The driver assembly **100'** is rotated with both drivers **110**, **120'** rotating and thus the compression screw **10'** is advanced as a single unit until the distal end **11** of the bone screw **12** is at a desired location. The thread engagement member **132** may be depressed

during such rotation to ensure that the shaft **112** advances axially during the simultaneous rotation. If the distal end **31** of the compression sleeve **30.sup.iv** contacts bone as the compression screw **10'** is advanced, the cutting flutes **36** cut into the bone and the compression screw **10'** is free to continue to advance as a single unit.

(40) After the distal end **11** of the bone screw **12** has landed at the desired location, compression may be achieved by advancing the compression sleeve **30.sup.iv** while the bone screw **12** remains stationary. The bone screw **12** remains stationary by holding the bone screw driver **110** stationary, for example, by attaching a locking device to the connection key **115**, and by disengaging the connector switch **128**. With the connector switch **128** moved to the disengaged position, the compression sleeve driver **120'** rotates freely about the bone screw driver **110**. Rotation of the compression sleeve driver **120'** causes the compression sleeve **30.sup.iv** to advance. Since the bone screw **12** is stationary as the compression sleeve driver **120'** advances the compression sleeve **30.sup.iv**, the compression screw **10'** shortens in length and the shoulder **35'** and distal end **121'** of the compression sleeve driver **120'** thus apply compression. Again, the cutting flutes **36** on the compression sleeve distal end **31** allow the compression sleeve **30** to cut into and advance into the bone.

(41) After the desired amount of compression has been reached, the head **34'** may be countersunk. Countersinking is done by a third driver component (not shown) that mates with the compression sleeve driver feature **42**. For example, the driver assembly **100** may be exchanged for the driver assembly **100'** such that the driver tip **124** can be used to rotate the compression sleeve **30.sup.iv** while the bone screw **12** is maintained stationary. As the compression sleeve **30.sup.iv** advances over the bone screw **12**, the threads **37** cut into the bone and advance the head **34'** into a countersunk position within the bone.

(42) Referring to FIGS. **14-16**, a compression screw **50** in accordance with another embodiment will be described. The compression screw **50** includes a shaft **52** extending from a distal end **51** to a proximal end **53**. A series of bone engaging threads **55** extend radially from the shaft **52** at the distal end **51**. In the preferred embodiment, the bone engaging threads **55** are dual lead thread type, however, any type of thread may be used to facilitate the function of the compression screw **50**. The distal end **51** preferably also includes at least one cutting flute **56** configured to cut into the bone as the compression screw **12** is rotated, defining a self-drilling and self-tapping tip. In a preferred embodiment, a slot **57** is associated with each cutting flute **56** to clear any chips, dust, or debris generated when the compression screw **50** is implanted into bone tissue.

(43) The proximal end **53** of the shaft **52** includes a self-countersinking head **54**. The self-countersinking head **54** has a tapered shoulder **68** and a series of external threads **64**. The threads **64** may include one or more cutting flutes **66** such that the threads **64** are self-drilling and self-tapping. In the present embodiment, the threads **64** define a proximal rotary cutting structure. A drive feature **62** is defined in the proximal end **53** of the shaft **52** and is configured and dimensioned to be any shape that corresponds with the end of the driving instrument designed to engage the compression screw **50**. As an example, in the illustrated embodiment, the drive feature **62** has a hexalobular configuration.

(44) The shaft **52** between the bone engaging threads **55** and the head **54** is preferably free of threads. With this configuration, a difference in pitch between the bone engaging threads **55** and the threads **64** of the head **54** can provide additional compression control as the compression screw **50** is inserted. That is, if the pitch of the bone engaging threads **55** is larger than the pitch of the threads **64** of the head **54**, and the fracture or joint line lies somewhere in the shaft **52** section of the screw **50**, this configuration will provide compression between the two bones as the distal end **51** tries to advance faster than the head **54** of the screw **50**.

(45) Referring to FIGS. **17** and **18**, a driver assembly **150** which allows the surgeon to further control how much compression is achieved will be described. The driver assembly **150** includes an inner driver member **152** and an outer driver member **160**. The inner driver member **152** extends

from a distal end **151** to a proximal end **153**. A driver tip **154** is defined on the distal end **151** and is configured to engage the driver feature **62** of the compression screw **50**.

(46) The outer driver member **160** includes a tubular body extending from a distal end **161** to a proximal end **163**. The distal end **161** defines a threaded chamber **164** configured to threadably receive the threads **64** of the compression screw head **54**.

(47) To insert the compression screw **50**, the driver assembly **150** is positioned with the driver tip **154** engaged with the driver feature **62** and the threads **64** of the head **54** threadably received in the threaded chamber **164**. The inner and outer driver members **152**, **160** are rotated such that the compression screw **50** is advanced. As the compression screw **50** advances, the distal end **161** of the outer driver member **160** will hit the near cortex and compress the fracture line as the screw **50** is continued to be inserted.

(48) After the desired amount of compression has been reached, the inner driver member **152** is rotated, independent of the outer driver member **160**, such that the compression screw **50** continues to advance with the outer driver member distal end **161** maintaining the compression. As the compression screw **50** advances, the threads **64** of the head **54** will enter the bone and begin to countersink the head **54**. As the head **54** advances and countersinks, it simultaneously threads out of the threaded chamber **164**. As explained before, the pitch of the bone engaging threads **55** and the threads **64** of the head **54** may be configured such that countersinking of the head **54** causes additional compression.

(49) These and other advantages of the present invention will be apparent to those skilled in the art from the foregoing specification. Accordingly, it will be recognized by those skilled in the art that changes or modifications may be made to the above-described embodiments without departing from the broad inventive concepts of the invention. It should therefore be understood that this invention is not limited to the particular embodiments described herein, but is intended to include all changes and modifications that are within the scope and spirit of the invention as defined in the claims.

Claims

1. A method of inserting a compression screw into a bone joint, the method comprising: coupling the compression screw to a driver assembly, the compression screw including a bone screw and a compression sleeve threadably coupled to the bone screw, the driver assembly including a first driver for driving the compression sleeve and a second driver for driving the bone screw, the driver assembly including a connector switch having an unlocking state and a locking state for rotationally locking the first and second drivers together, the compression sleeve having a non-threaded radially extending head which defines a radially extending shoulder, wherein the bone screw at its distal end includes at least one longitudinal slot recessed into an exterior surface to clear any debris generated while the compression screw is being advanced into a bone; rotating the driver assembly with the connector switch in the locking state to simultaneously advance the compression sleeve and the bone screw into the bone to a desired location; switching the connector switch of the driver assembly to the unlocking state; while the connector switch is in the unlocking state, rotating the first driver while maintaining the second driver stationary so as to advance the compression sleeve into the bone over the bone screw such that a compressive force is applied to the bone joint, wherein the first and second drivers are co-axial with one another and selectively rotatable together or independently of one another, wherein rotating the first and second drivers simultaneously advances the compression screw into the bone joint until the compression screw is at a first desired location; and rotating the first driver while maintaining the second driver stationary whereby at least a portion of the compression screw is further advanced into the bone joint such that a compressive force is applied to the bone joint, wherein the longitudinal slot is configured to provide a surface for bony ingrowth to prevent screw toggle and screw axial motion.

2. The method of claim 1, wherein a distal portion of the compression sleeve includes a plurality of cutting flutes, wherein rotating the driver assembly includes cutting into the bone by both the bone screw and the compression sleeve.
3. The method of claim 2, wherein the compression sleeve includes a plurality of slots corresponding to the flutes and recessed into an exterior surface of the compression sleeve.
4. The method of claim 3, wherein the slots are helically shaped slots around the compression sleeve.
5. The method of claim 3, wherein the slots extend substantially parallel to a longitudinal axis of the compression sleeve.
6. The method of claim 1, wherein the head of the compression sleeve includes a drive feature, wherein coupling the compression screw to a driver assembly includes mating the drive feature of the compression sleeve to a drive feature of the driver assembly.
7. The method of claim 1, wherein the second driver of the driver assembly has a plurality of splines that are positioned to be engaged by the connector switch, and switching the connector switch of the driver assembly to the locking state includes moving the switch to engage the splines.
8. The method of claim 1, wherein the head has a flat underside for contacting a surface of the bone and is shaped to remain above the bone surface, and the longitudinal slot crosses at least one of a plurality of threads on the bone screw.
9. The method of claim 1, wherein: a distal portion of the compression sleeve includes a plurality of cutting flutes; the compression sleeve has an internal threading, and the bone screw has a distal threading and a proximal threading threaded with the internal threading of the compression sleeve.
10. The method of claim 9, wherein the distal threading of the bone screw has a coarse pitch relative to the pitch of the proximal threading of the bone screw.
11. A method of inserting a compression screw into a bone joint, the method comprising: coupling the compression screw to a driver assembly, the compression screw including a bone screw and a compression sleeve threadably coupled to the bone screw such that rotation of the compression sleeve translates the compression sleeve relative to the bone screw, the driver assembly including a first driver for driving the compression sleeve and a second driver for driving the bone screw, the driver assembly including a connector switch having an unlocking state and a locking state for rotationally locking the first and second drivers together, the compression sleeve having a non-threaded radially extending head which defines a radially extending shoulder and which includes a flat underside configured to contact the bone without being inserted into the bone, wherein the bone screw at its distal end includes at least one longitudinal slot recessed into an exterior surface to clear any debris generated while the compression screw is being advanced into a bone; rotating the driver assembly with the connector switch in the locking state to simultaneously advance the compression sleeve and the bone screw into the bone to a desired location; switching the connector switch of the driver assembly to the unlocking state; while the connector switch is in the unlocking state, rotating the first driver while maintaining the second driver stationary so as to advance the compression sleeve into the bone over the bone screw such that a compressive force is applied to the bone joint wherein the first and second drivers are co-axial with one another and selectively rotatable together or independently of one another, wherein rotating the first and second drivers simultaneously advances the compression screw into the bone joint until the compression screw is at a first desired location; and rotating the first driver while maintaining the second driver stationary whereby at least a portion of the compression screw is further advanced into the bone joint such that a compressive force is applied to the bone joint, wherein the longitudinal slot is configured to provide a surface for bony ingrowth to prevent screw toggle and screw axial motion.
12. The method of claim 11, wherein a distal portion of the compression sleeve includes a plurality of cutting flutes, wherein rotating the driver assembly includes cutting into the bone by both the bone screw and the compression sleeve.
13. The method of claim 12, wherein the compression sleeve includes a plurality of slots

corresponding to the flutes and recessed into an exterior surface of the compression sleeve.

14. The method of claim 13, wherein the slots are helically shaped slots around the compression sleeve.

15. The method of claim 13, wherein the slots extend substantially parallel to a longitudinal axis of the compression sleeve.

16. The method of claim 11, wherein the head of the compression sleeve includes a drive feature, wherein coupling the compression screw to a driver assembly includes mating the drive feature of the compression sleeve to a drive feature of the driver assembly.

17. The method of claim 11, wherein the second driver of the driver assembly has a plurality of splines that are positioned to be engaged by the connector switch, and switching the connector switch of the driver assembly to the locking state includes moving the switch to engage the splines.

18. The method of claim 11, wherein a proximal end of the bone screw has a drive feature mateable to a drive feature of the second driver.

19. The method of claim 11, wherein: a distal portion of the compression sleeve includes a plurality of cutting flutes; the compression sleeve has an internal threading, and the bone screw has a distal threading and a proximal threading threaded with the internal threading of the compression sleeve.

20. The method of claim 19, wherein the distal threading of the bone screw has a coarse pitch relative to the pitch of the proximal threading of the bone screw.
