

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12415596
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Kurita; Mitsuru et al.

Riblet structure and object

Abstract

A riblet structure according to the present technology includes a plurality of riblets that are arranged in a width direction and each include a first wall portion and a second wall portion, the first wall portion being vertically provided to be substantially perpendicular to a bottom portion, the second wall portion including an inclined portion connected to the first wall portion at an apex portion and inclined with respect to a perpendicular direction at a predetermined angle.

Inventors:	Kurita; Mitsuru (Tokyo, JP), Abe; Hiroyuki (Tokyo, JP), Sasamori; Monami (Tokyo, JP), Koga; Seigo (Tokyo, JP)
Applicant:	JAPAN AEROSPACE EXPLORATION AGENCY (Tokyo, JP)
Family ID:	1000008822330
Assignee:	Japan Aerospace Exploration Agency (Tokyo, JP)
Appl. No.:	18/292034
Filed (or PCT Filed):	May 16, 2022
PCT No.:	PCT/JP2022/020423
PCT Pub. No.:	WO2023/042481
PCT Pub. Date:	March 23, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20250083794 A1	Mar. 13, 2025

Foreign Application Priority Data

JP	2021-149517	Sep. 14, 2021
----	-------------	---------------

Publication Classification

Int. Cl.: B64C3/18 (20060101)

U.S. Cl.:

CPC B64C3/187 (20130101);

Field of Classification Search

CPC: B64C (21/10); B64C (2230/26); F15D (1/0035)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4650138	12/1986	Grose	244/130	B64C 21/10
4759516	12/1987	Grose	244/130	F15D 1/06
4863121	12/1988	Savill	244/130	B63B 1/34
4930729	12/1989	Savill	244/130	B63B 1/34
5133516	12/1991	Marentic	244/130	B05D 5/02
5386955	12/1994	Savill	244/130	B63B 1/34
5542630	12/1995	Savill	N/A	N/A
5971326	12/1998	Bechert	244/130	B64C 21/10
7070850	12/2005	Dietz	428/167	F15D 1/12
8528601	12/2012	Dahm	137/809	F02C 7/04
2006/0060722	12/2005	Choi et al.	N/A	N/A
2010/0159204	12/2009	Van Merksteijn	N/A	N/A
2019/0023379	12/2018	Okabayashi et al.	N/A	N/A
2020/0263704	12/2019	Miyazaki et al.	N/A	N/A
2024/0280122	12/2023	Chiba	N/A	B64C 21/10

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2005-529298	12/2004	JP	N/A
2009-504474	12/2008	JP	N/A
7022238	12/2021	JP	N/A
WO-2012082668	12/2011	WO	B32B 27/08
2017/149837	12/2016	WO	N/A
2018/139049	12/2017	WO	N/A

OTHER PUBLICATIONS

Bai, Xiuqin. Numerical Analysis of Drag Reduction Performance of Different Shaped Riblet Surfaces. Marine Technology Society Journal, 2016. (Year: 2016). cited by examiner

Walsh, Michael. Turbulent Boundary Layer Drag Reduction Using Riblets. AIAA-82-0169. Jan. 1982. (Year: 1982). cited by examiner
Walsh, Michael. Riblets for Aircraft Skin-Friction Reduction. 1986. (Year: 1986). cited by examiner
Lapsa, Andrew. Experimental Study of Passive Ramps for Control of Shock—Boundary Layer Interactions. University of Michigan PhD dissertation. 2009. (Year: 2009). cited by examiner
International Search Report dated Jul. 12, 2022 in International Application No. PCT/JP2022/020423. cited by applicant
Bechert, D. W. et al., “Experiments on drag-reducing surfaces and their optimization with an adjustable geometry,” Cambridge University Press, 1997, 338:59-87. cited by applicant

Primary Examiner: Michener; Joshua J

Assistant Examiner: Kreiner; Michael B.

Attorney, Agent or Firm: Saliwanchik, Lloyd & Eisenschenk

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application is the U.S. national stage application of International Patent Application No. PCT/JP2022/020423, filed May 16, 2022, which claims the benefit under 35 U.S.C. § 119 of Japanese Application No. 2021-149517, filed Sep. 14, 2021, the disclosures of each of which are incorporated herein by reference in their entirety.

TECHNICAL FIELD

(2) The present technology relates to a technology of a riblet structure or the like for reducing surface friction resistance to a fluid.

BACKGROUND ART

(3) Conventionally, it has been known that surface friction resistance to a turbulent flow of a fluid such as gas or liquid can be reduced by providing a predetermined riblet pattern on a surface of an aircraft or the like.

(4) Non-Patent Literature 1 below discloses a structure in which isosceles triangular riblets are arranged along a width direction, and it is disclosed that the isosceles triangular riblets can reduce surface friction resistance by approximately 5% to 6% at a maximum (see FIGS. 19 and 20 of Non-Patent Literature 1 below).

(5) The isosceles triangular riblet has a tendency that as the angle of the apex portion becomes sharper, the surface friction resistance can be reduced. In this regard, Non-Patent Literature 1 below proposes riblets each formed into a plate shape thinned to the limit (linearly as viewed from the front) as a shape in which the angle of the apex portion is sharpened to the limit. Such plate-shaped riblets thinned to the limit can reduce the surface friction resistance by approximately 10% at a maximum (see FIGS. 19 and 20 of Non-Patent Literature 1 below).

(6) The plate-shaped riblets thinned to the limit are known as having a shape capable of reducing the most surface friction resistance at the present.

CITATION LIST

Non-Patent Literature

(7) Non-Patent Literature 1: Bechert, D, W., Bruse, M., Hage, W., Van der Hoeven, J, G, T., and Hoppe, G., “Experiments on drag-reducing surfaces and their optimization with an adjustable geometry,” Journal of fluid mechanics, vol. 338, pp. 59-87, 1997.

DISCLOSURE OF INVENTION

Technical Problem

(8) However, if plate-shaped riblets thinned to an upper processing limit are formed, such riblets have a problem in that they are structurally fragile and are not suitable for practical use.

(9) In view of the circumstances as described above, it is an object of the present technology to provide a technology of a riblet structure or the like that can effectively reduce surface friction resistance while having strength of a certain level or more.

Solution to Problem

(10) A riblet structure according to the present technology includes a plurality of riblets that are arranged in a width direction and each include a first wall portion and a second wall portion, the first wall portion being vertically provided to be substantially perpendicular to a bottom portion, the second wall portion including an inclined portion connected to the first wall portion at an apex portion and inclined with respect to a perpendicular direction at a predetermined angle.

(11) It is possible to provide a riblet structure that can effectively reduce surface friction resistance while having strength of a certain level or more.

(12) In the riblet structure, first wall portion sides of the riblets adjacent to each other in the width direction may face each other, and second wall portion sides thereof may face each other.

(13) In the riblet structure, the second wall portion may further include a perpendicular portion vertically provided to be substantially perpendicular to the bottom portion and connected to the inclined portion.

(14) In the riblet structure, the inclined portion may include a first inclined portion that is inclined with respect to the perpendicular direction at the predetermined angle, and a second inclined portion that is inclined with respect to the perpendicular direction at an angle different from the predetermined angle and is closer to the bottom portion than the first inclined portion.

(15) In the riblet structure, the angle at which the second inclined portion is inclined with respect to the perpendicular direction may be sharper than the angle at which the first inclined portion is inclined with respect to the perpendicular direction.

(16) In the riblet structure, the predetermined angle may be in a range of 20° or more and 60° or less.

(17) In the riblet structure, the predetermined angle may be in a range of 35° or more and 50° or less.

(18) In the riblet structure, when a distance in the width direction between two of the apex portions of the riblets adjacent to each other is denoted by s , a friction velocity is denoted by $u_{\text{sub},\tau}$, and a kinematic viscosity coefficient is denoted by ν , a dimensionless riblet interval $s_{\text{sup},+}$ represented by $s_{\text{sup},+} = s u_{\text{sub},\tau} / \nu$ may be in a range of 10 or more and to 30 or less.

(19) In the riblet structure, the dimensionless riblet interval $s_{\text{sup},+}$ may be in a range of 10 or more and 25 or less.

(20) In the riblet structure, the dimensionless riblet interval $s_{\text{sup},+}$ may be in a range of 15 or more and 22 or less.

(21) In the riblet structure, when a distance in the width direction between two of the apex portions of the riblets adjacent to each other is denoted by s , a height h of the riblet may be in a range of 0.05 times or more and 1.5 times or less the distance s .

(22) In the riblet structure, when a distance in the width direction between two of the apex portions of the riblets adjacent to each other is denoted by s , a distance d in the width direction between lowermost points of two of the inclined portions facing each other in the riblets adjacent to each other may be in a range of 0.1 times or more and 0.98 times or less the distance s .

(23) An object according to the present technology includes a riblet structure on a surface of the object, the riblet structure including a plurality of riblets that are arranged in a width direction and each include a first wall portion and a second wall portion, the first wall portion being vertically provided to be substantially perpendicular to a bottom portion, the second wall portion including an

inclined portion connected to the first wall portion at an apex portion and inclined with respect to a perpendicular direction at a predetermined angle.

Advantageous Effects of Invention

(24) As described above, according to the present technology, it is possible to provide a technology of a riblet structure or the like that can effectively reduce surface friction resistance while having strength of a certain level or more.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a diagram showing a riblet structure according to a first embodiment.
- (2) FIG. 2 is a diagram showing a plate-shaped riblet structure thinned to the limit.
- (3) FIG. 3 is a diagram showing a riblet structure according to a comparative example.
- (4) FIG. 4 is a diagram showing a reduction rate of surface friction resistance with respect to a dimensionless riblet interval s^+ in the riblets according to this embodiment and the riblets according to the comparative example.
- (5) FIG. 5 is a diagram showing a riblet structure according to a second embodiment.
- (6) FIG. 6 is a diagram showing a riblet structure according to a third embodiment.
- (7) FIG. 7 is a diagram showing an example when an inclined portion of a second wall portion includes two or more steps in the third embodiment.
- (8) FIG. 8 is a diagram showing a riblet structure according to a fourth embodiment.

MODE(S) FOR CARRYING OUT THE INVENTION

(9) Hereinafter, embodiments of the present invention will be described with reference to the drawings.

First Embodiment

(10) <Overall Configuration of Riblet Structure **30** and Configuration of Each Portion>

(11) FIG. 1 is a diagram showing a riblet structure **30** according to a first embodiment of the present technology.

(12) The riblet structure **30** according to this embodiment can reduce surface friction resistance to a turbulent flow of a fluid. The riblet structure **30** is provided onto a surface of an object. As the method of providing the riblet structure **30** onto a surface of an object, there are two methods of bonding riblets formed into a sheet shape onto the surface of the object and of directly forming riblets onto the surface of the object, but any one of the methods may be used.

(13) Examples of the object provided with the riblet structure **30** include an aircraft, a ship, a car, a turbine, a fan, and a fluid device. Note that the riblet structure **30** can be provided to any object as long as it is intended to reduce the surface friction resistance to a turbulent flow of a fluid.

(14) The riblet structure **30** is made of various materials such as a resin, a metal, and a coating film, but may be made of any material.

(15) As shown in FIG. 1, the riblet structure **30** includes a base portion **1** (bottom portion) and a plurality of riblets **2** vertically provided on the base portion **1**.

(16) The base portion **1** is formed into a flat plate shape that is thin in a thickness direction (Z-axis direction) and wide in a plane direction (XY directions). The bottom surface of the base portion **1** is bonded to a surface of an object, on which the riblets **2** are to be formed, for example, via an adhesive layer. Typically, the thickness of the base portion **1** is approximately 5 μm or more and several mm or less. Note that the base portion **1** can be omitted, and in such a case, the riblets **2** are directly formed onto the surface (bottom portion) of the object.

(17) Each of the plurality of riblets **2** has a shape that is long in a length direction (X-axis direction), short in a width direction (Y-axis direction), and low in a height direction (Z-axis direction).

(18) The riblet **2** may be formed linearly in the length direction or may be formed in a sinusoidal shape (as viewed from above). When the riblet **2** is formed in a sinusoidal shape in the length direction, a height h of the riblet **2** may be formed in a sinusoidal shape (as viewed from the side-surface side (Y-axis direction)).

(19) Each of the plurality of riblets **2** includes a first wall portion **11** substantially perpendicular to the base portion **1**, and a second wall portion **12** that is opposite to the first wall portion **11** with an apex portion **15** interposed therebetween and includes an inclined portion **13**.

(20) Further, the plurality of riblets **2** are arranged along the width direction such that the first wall portion **11** sides of the riblets **2** adjacent to each other in the width direction (Y-axis direction) face each other, and the second wall portion **12** sides thereof face each other.

(21) The first wall portion **11** is vertically provided to be substantially perpendicular to the base portion **1**. Here, the wording “substantially perpendicular” means approximately $\pm 10^\circ$ with respect to the perpendicular direction (Z-axis direction). In other words, the riblet **2** according to this embodiment has a small size as will be described later, which makes it difficult to form the first wall portion **11** strictly in the perpendicular direction due to a problem of a processing accuracy in some cases. For that reason, it is assumed that the first wall portion **11** is substantially perpendicular as long as it is at approximately $\pm 10^\circ$ with respect to the perpendicular direction.

(22) The second wall portion **12** includes the inclined portion **13** and a perpendicular portion **14**. The inclined portion **13** is connected to the first wall portion **11** at the apex portion **15**, and is inclined with respect to the perpendicular direction (Z-axis direction) at a predetermined angle. The perpendicular portion **14** is vertically provided to be substantially perpendicular to the base portion **1** and is connected to the inclined portion **13**. Note that the wording “substantially perpendicular” in the perpendicular portion **14** also means approximately $\pm 10^\circ$ with respect to the perpendicular direction (Z-axis direction) as described above.

(23) In the second wall portion **12**, an angle θ (angle θ of apex portion **15**) at which the inclined portion **13** is inclined with respect to the perpendicular direction (Z-axis direction) is set from the following viewpoints. First, as the angle θ becomes sharper, surface friction resistance to a turbulent flow of a fluid can be reduced. On the other hand, as the angle θ becomes sharper, the riblet **2** becomes narrower in the width direction and its strength decreases, and further processing becomes difficult to perform.

(24) From such viewpoints, the lower limit value of the angle θ is set to 20° . If the angle θ is set to 20° or more, the riblet **2** can have strength of a certain level or more within a range in which processing is possible, and the surface friction resistance can be reduced. On the other hand, the upper limit value of the angle θ is set to 60° . If the angle θ is set to 60° or less, it is possible to improve the strength while obtaining a reduction effect of a certain level or more with respect to the surface friction resistance, and it is also possible to reduce the difficulty of processing.

(25) In other words, the angle θ at which the inclined portion **13** is inclined with respect to the perpendicular direction is typically in the range of 20° or more and 60° or less, and favorably in the range of 35° or more and 50° or less. Note that the angle θ is set to 45° in the example shown in FIG. 1.

(26) A distance s in the widthwise direction (Y-axis direction) between the two apex portions **15** of the riblets **2** adjacent to each other is typically $10\text{ }\mu\text{m}$ or more and several mm or less. Note that the distance s is set to $100\text{ }\mu\text{m}$ in the example shown in FIG. 1.

(27) Note that there are two types of distance s between the two apex portions **15** in this embodiment. The first is a distance s at a position where the first wall portion **11** sides face each other (at a position of U-shaped first groove portion **22**), and the second is a distance s at a position where the second wall portions **12** face each other (at a position of Y-shaped second groove portion **23**). Those two distances s are typically the same, but may be different from each other.

(28) Further, the height h of the riblet **2** is typically set to 0.05 times or more and 1.5 times or less the distance s . Note that the height h is set to 0.5 times the distance s , $50\text{ }\mu\text{m}$, in the example shown

in FIG. 1.

(29) Further, a distance d in the width direction between the lowermost points of the two inclined portions **13** facing each other in the riblets **2** adjacent to each other (distance d between perpendicular portions **14**) is typically 0.1 times or more and 0.98 times or less the distance s . Note that the distance d is set to 0.5 times the distance s , 50 μm , in the example shown in FIG. 1.

(30) Here, if the distance d in the width direction between the lowermost points of the two inclined portions **13** (distance d between perpendicular portions **14**) is too large, the width of the riblet **2** becomes too small, so that the strength is reduced. From this viewpoint, the upper limit value of the distance d is set to 0.98 times the distance s . On the other hand, if the distance d is too small, a region on the lower side of the Y-shaped second groove portion **23** becomes small, so that the surface friction resistance to a turbulent flow of a fluid increases. Therefore, from this viewpoint, the lower limit value of the distance d is set to 0.1 times the distance s .

(31) The plurality of riblets **2** are constituted by a plurality of groove portions **21** arranged along the width direction (Y-axis direction). The plurality of groove portions **21** include the first groove portions **22** and the second groove portions **23** alternately arranged in the width direction. In this embodiment, the first groove portions **22** and the second groove portions **23** have different shapes.

(32) The first groove portion **22** is formed by a space surrounded by the two first wall portions **11** facing each other and the base portion **1**. The shape of the first groove portion **22** is rectangular and is generally U-shaped.

(33) The second groove portion **23** is formed by a space surrounded by the two second wall portions **12** facing each other and the base portion **1**. The shape of the second groove portion **23** is an inverted trapezoidal shape on the apex portion **15** side and a rectangular shape on the bottom portion side, and is generally Y-shaped.

(34) <Basic Concept>

(35) Next, the basic concept of the present technology will be described. FIG. 2 is a diagram showing a riblet structure **31** including plate-shaped riblets **3** thinned to the limit. As shown in FIG. 2, in the riblet structure **31**, the riblet **3** has a plate shape having a width thinned to the limit. In such a riblet structure **31**, it is known that surface friction resistance to a turbulent flow of a fluid can be reduced to 10% at a maximum.

(36) However, even if the plate-shaped riblets **3** thinned to the upper processing limit are formed, such riblets **3** are structurally fragile and are not suitable for practical use.

(37) Here, the inventors of the present technology have considered that points of improving the performance of reducing surface friction resistance by the riblets **2** are to sharpen the apex portion **15** at which a flow is strong due to a turbulent flow of a fluid and to minimize the surface area of the apex portion **15**, and also to maximize the volume inside the groove portion **21** at which the flow is weak. On the other hand, for practical use, it is necessary to ensure strength of a certain level in the riblets **2** and it is also necessary to consider a range in which processing is possible.

(38) In other words, the following four points are considered for the riblet structure **30** according to this embodiment: 1. Sharpen the apex portion **15** as much as possible; 2. Maximize the volume inside the groove portion **21** as much as possible; 3. Ensure strength of a certain level or more; and 4. Fall within a range in which processing is possible (Facilitate processing). If those four points are satisfied, the surface friction resistance is reduced while ensuring strength of a certain level or more in the riblets **2** within a range in which processing is possible.

(39) Here, the two first wall portions **11** facing each other in the width direction are substantially perpendicular. Thus, the first groove portion **22** is assumed to be rectangular, and the volume thereof is taken as large as possible. Therefore, the surface friction resistance can be effectively reduced.

(40) It is also desired to form the second wall portion **12** side to be substantially perpendicular to form the riblet **2** as a plate thinned to the limit, like the riblet **3** thinned to the limit, if possible. In this case, however, it is not possible to ensure strength of a certain level or more in the riblet **2**. In

this regard, in this embodiment, the inclined portion **13** is provided on the second wall portion **12** side.

(41) As the angle θ (angle θ of apex portion **15**) at which the inclined portion **13** is inclined with respect to the perpendicular direction in the second wall portion **12** becomes sharper, the surface friction resistance can be reduced. However, as the angle θ becomes sharper, the riblet **2** becomes narrower in the width direction and its strength decreases, and further processing becomes difficult to perform. Therefore, as described above, the angle θ is in the range of 20° or more and 60° or less, and favorably in the range of 35° or more and 50° or less.

(42) The lowermost point of the inclined portion **13** in the second wall portion **12** may be in contact with the upper surface of the base portion **1**, and the second groove portion **23** may have a shape of an inverted triangle (in this case, the second groove portion **23** generally has a V-shape). In this case, however, the volume of the second groove portion **23** is slightly reduced. In this regard, the second wall portion **12** is provided with the perpendicular portion **14** on the lower side of the inclined portion **13**, and thus a rectangular portion is formed on the lower side of the inverted trapezoidal shape in the second groove portion **23**. Thus, it is possible to effectively reduce the surface friction resistance also in the second groove portion **23**.

(43) <Evaluation of Performance of Reducing Surface Friction Resistance>

(44) Next, the evaluation of performance of reducing the surface friction resistance of the riblets **2** with respect to a turbulent flow of a fluid will be described.

(45) In this evaluation, the riblet structure **30** according to this embodiment and a riblet structure **32** according to a comparative example were compared in the performance of reducing the surface friction resistance. FIG. **3** is a diagram showing the riblet structure **32** according to the comparative example. A riblet **4** according to the comparative example has an isosceles triangular shape.

(46) In this evaluation, in the riblet **2** according to this embodiment and the riblet **4** according to the comparative example, the reduction rate of the surface friction resistance with respect to a dimensionless riblet interval s^+ was analyzed using a numerical method called direct numerical simulation (DNS). Note that Fortran was used as the language of a calculation program in this DNS analysis.

(47) FIG. **4** is a diagram showing the reduction rate of the surface friction resistance with respect to the dimensionless riblet interval s^+ in the riblet **2** according to this embodiment and the riblet **4** according to the comparative example.

(48) Here, s_{sup}^+ means the Reynolds number based on the distance s between the two apex portions **15** in the riblets **2** adjacent to each other, and $s_{sup}^+ = s_{sub} \cdot u_{\tau} / \nu$ is a dimensionless riblet interval. Note that u_{sub} is a friction velocity, and ν is a kinematic viscosity coefficient of the fluid. The friction velocity u_{sub} is represented by $u_{sub} = (\tau_{sub} \cdot w / \rho)^{1/2}$ using a shear stress τ_{sub} acting on the wall surface and a density ρ of the fluid.

(49) In FIG. **4**, in this embodiment and the comparative example, the dimensionless riblet interval s_{sup}^+ was changed by changing the distance s between the two apex portions **15** of the riblets **2**, **4** adjacent to each other, and what value is taken as the reduction rate of the surface friction resistance was analyzed.

(50) Note that, in this embodiment and the comparative example, the riblets **2**, **4** are formed to be linearly straight in the length direction. Further, in this embodiment and the comparative example, the height h of the riblet **2**, **4** is $1/2$ times the distance s (that is, the height h varies according to the value of the distance s), and further, the angle θ of the apex portion **15** is fixed at 45° . Furthermore, in this embodiment, the distance d between the lowermost points of the two inclined portions **13** is set to $1/2$ times the distance s (that is, the distance d varies according to the value of the distance s).

(51) As is apparent from FIG. **4**, in this embodiment, when the dimensionless riblet interval s_{sup}^+ is set to approximately 10 or more and approximately 30 or less, the reduction rate of the surface friction resistance is improved as compared to that of the comparative example.

(52) Specifically, in the comparative example (refer to cross marks), the reduction rate of the

surface friction resistance is approximately 6% at a maximum. On the other hand, in this embodiment (refer to circle marks), the reduction rate of the surface friction resistance is approximately 8% at a maximum.

(53) In other words, in this embodiment, it is possible to reduce the surface friction resistance by approximately 8% at a maximum while setting the riblets **2** having strength of a certain level or more within a range in which processing is possible, though it does not reach 10% that is the reduction rate of the surface friction resistance of the plate-shaped riblets **3** thinned to the limit.

(54) Here, in this embodiment, the reduction rate of the surface friction resistance varies according to a change in the dimensionless riblet interval $s_{sup.}$, and thus the value of $s_{sup.}$ has an appropriate range. Typically, $s_{sup.}$ is in the range of 10 or more and 30 or less, favorably in the range of 10 or more and 25 or less, and more favorably in the range of 15 or more and 22 or less.

(55) Note that, as shown in FIG. **1**, if the distance s is set to 100 μm in an airflow assuming a case of an aircraft, the dimensionless riblet interval s is approximately 17. In this case, the surface friction resistance can be reduced by approximately 8%.

(56) <Effects and Others>

(57) As described above, the riblet structure **30** according to this embodiment is constituted in a manner that the plurality of riblets **2** are arranged in the width direction, the plurality of riblets **2** each including the first wall portion **11** vertically provided to be substantially perpendicular to the base portion **1**, and the second wall portion **12** including the inclined portion **13** connected to the first wall portion **11** at the apex portion **15** and inclined with respect to the perpendicular direction at a predetermined angle.

(58) This makes it possible to set the riblets **2** to have strength of a certain level or more and effectively reduce the surface friction resistance.

(59) Further, in this embodiment, the first wall portion **11** sides of the riblets **2** adjacent to each other in the width direction face each other, and the second wall portion **12** sides thereof face each other. This makes it possible to increase a region of the first groove portion **22**, which is surrounded by the two first wall portions **11** facing each other, and thus further effectively reduce the surface friction resistance.

(60) Further, in this embodiment, the second wall portion **12** further includes the perpendicular portion **14** that is vertically provided to be substantially perpendicular to the bottom portion and connected to the inclined portion **13**. This makes it possible to form a rectangular portion in the lower region of the second groove portion **23** surrounded by the two second wall portions **12** facing each other. Therefore, the region of the second groove portion **23** can be increased, so that the surface friction resistance can be further effectively reduced.

(61) Further, in this embodiment, the angle θ (angle θ of apex portion **15**) at which the inclined portion **13** is inclined with respect to the perpendicular direction (Z-axis direction) in the second wall portion **12** is typically in the range of 20° or more and 60° or less, and favorably in the range of 35° or more and 50° or less. This makes it possible to set the riblets **2** to have strength of a certain level or more within a range in which processing is possible and effectively reduce the surface friction resistance.

(62) Further, in this embodiment, the height h of the riblet **2** is set in the range of 0.05 times or more and 1.5 times or less the distance s in the width direction between the two apex portions **15** adjacent to each other. This makes it possible to further effectively reduce the surface friction resistance.

(63) Further, in this embodiment, the distance d in the width direction between the lowermost points of the two inclined portions **13** facing each other (width d of rectangular portion in second groove portion **23**) is set in the range of 0.1 times or more and 0.98 times or less the distance s . This makes it possible to further effectively reduce the surface friction resistance by widening the width d of the rectangular portion in the second groove portion **23** as much as possible while setting the riblets **2** to have a certain width or more and have strength of a certain level or more.

(64) Further, in this embodiment, the dimensionless riblet interval s is typically set in the range of 10 or more and 30 or less, favorably in the range of 10 or more and 25 or less, and more favorably in the range of 15 or more and 22 or less. This makes it possible to effectively reduce the surface friction resistance and reduce the surface friction resistance to approximately 8% at a maximum.

Second Embodiment

(65) Next, a second embodiment of the present technology will be described. Note that in the description of the second embodiment and following embodiments, portions including configurations and functions similar to those of the first embodiment described above will be denoted by the same reference symbols and description thereof will be omitted or simplified.

(66) FIG. 5 is a diagram showing a riblet structure **33** according to the second embodiment. The second embodiment is different from the first embodiment described above in that the inclined portion **13** of the second wall portion **12** includes two steps. Therefore, this point will be mainly described.

(67) In a riblet **5**, the inclined portion **13** of the second wall portion **12** includes a first inclined portion **13a** on an apex portion **15** side and a second inclined portion **13b** on a bottom portion side. The first inclined portion **13a** is inclined with respect to the perpendicular direction at a first angle θ_1 . The second inclined portion **13b** is inclined with respect to the perpendicular direction at a second angle θ_2 different from the first angle θ_1 . The second angle θ_2 is an angle sharper than the first angle θ_1 .

(68) As in the range of the angle θ (angle θ of apex portion **15**) at which the inclined portion **13** is inclined in the first embodiment described above, the first angle θ_1 is typically in the range of 20° or more and 60° or less, and favorably in the range of 35° or more and 50° or less. The second angle θ_2 is typically set to 20° or more and to an angle less than the first angle θ_1 .

(69) In the example shown in FIG. 5, an example in which the first angle θ_1 is set to 45° and the second angle θ_2 is set to 30° is shown.

(70) Note that, in the second embodiment, the inclined portion **13** of the second wall portion **12** includes two steps, and thus the shape of a second groove portion **24** surrounded by the second wall portions **12** is different from that of the first embodiment. Specifically, the second groove portion **24** includes a first inverted trapezoidal portion on the apex portion **15** side, a second inverted trapezoidal portion in the middle, and a rectangular portion on the bottom portion side.

(71) Also in the second embodiment, as in the first embodiment described above, it is possible to set the riblets **5** to have strength of a certain level or more within a range in which processing is possible and effectively reduce the surface friction resistance. Furthermore, in the second embodiment, the inclined portion **13** includes two steps and thus the volume of the second groove portion **24** is further increased. This makes it possible to further reduce the surface friction resistance.

(72) Note that, in the second embodiment, the case where the inclined portion **13** includes the two steps has been described, but the inclined portion **13** may include three or more steps.

Third Embodiment

(73) Next, a third embodiment of the present technology will be described. In each of the embodiments described above, the case where the perpendicular portion **14** is provided in the second wall portion **12** has been described. On the other hand, the perpendicular portion **14** can be omitted. In the third embodiment, a shape of the second wall portion **12** from which the perpendicular portion **14** is omitted will be described.

(74) FIG. 6 is a diagram showing a riblet structure **34** according to the third embodiment. As shown in FIG. 6, in the third embodiment, the inclined portion **13** is connected to the base portion **1** and the perpendicular portion **14** is not provided in the second wall portion **12** of a riblet **6**.

(75) In the third embodiment, an angle θ at which the inclined portion **13** is inclined with respect to the perpendicular direction is typically in the range of 20° or more and 60° or less, and favorably in the range of 35° or more and 50° or less as in the embodiments described above. In the example

shown in FIG. 6, the angle θ is set to 30° .

(76) Further, in the example shown in FIG. 6, the distance d in the width direction between the lowermost points of the two inclined portions **13** facing each other is set to $50\text{ }\mu\text{m}$. Note that the distance d can be appropriately changed (may be set to 0.1 times or more and 0.98 times or less the distance s).

(77) Note that, in the third embodiment, the perpendicular portion **14** is omitted in the second wall portion **12**, and thus the shape of a second groove portion **25** surrounded by the second wall portions **12** facing each other is different from that of each embodiment described above.

Specifically, the shape of the second groove portion **25** is an inverted trapezoidal shape.

(78) Also in the third embodiment, as in the embodiments described above, it is possible to set the riblets **6** to have strength of a certain level or more within a range in which processing is possible and effectively reduce the surface friction resistance.

(79) Here, in the third embodiment, as in the second embodiment, the inclined portion **13** of the second wall portion **12** can be provided with two or more steps. FIG. 7 is a diagram showing an example of a case where the inclined portion **13** of the second wall portion **12** includes two or more steps in the third embodiment.

(80) In a riblet structure **35** shown in FIG. 7, the perpendicular portion **14** is omitted in the second wall portion **12** of a riblet **7**, and the inclined portion **13** is connected to the base portion **1**. The inclined portion **13** of the second wall portion **12** includes a first inclined portion **13a** inclined with respect to the perpendicular direction at a first angle θ_1 on the apex portion **15** side, and a second inclined portion **13b** inclined with respect to the perpendicular direction at a second angle θ_2 .

(81) The range of the first angle θ_1 and the second angle θ_2 is similar to that of the second embodiment described above. Note that, in the example shown in FIG. 7, an example in which the first angle θ_1 is set to 45° and the second angle θ_2 is set to 20° is shown.

Fourth Embodiment

(82) Next, a fourth embodiment of the present technology will be described. In each of the embodiments described above, the case where the first wall portion **11** sides face each other and the second wall portion **12** sides face each other in the two riblets **2**, **5**, **6**, **7**, adjacent to each other has been described. On the other hand, in the two riblets **2** adjacent to each other, the first wall portion **11** and the second wall portion **12** may face each other.

(83) FIG. 8 is a diagram showing a riblet structure **36** according to a fourth embodiment. In the riblet structure **36**, in two riblets **8** adjacent to each other, the first wall portion **11** and the second wall portion **12** face each other.

(84) In the example shown in FIG. 8, a distance s between two apex portions **15** adjacent to each other is set to $100\text{ }\mu\text{m}$, a height h of the riblet **8** is set to $50\text{ }\mu\text{m}$, and an angle θ of the apex portion **15** is set to 45° , but those values can be appropriately changed in the ranges described above.

Further, in the example shown in FIG. 8, a distance d between a first wall portion **11** and the lowermost point of the inclined portion **13** of the second wall portion **12** facing the first wall portion **11** is set to $75\text{ }\mu\text{m}$, but such a value can also be appropriately changed.

(85) Note that, in the fourth embodiment, groove portions **27** have the same shape. In the example shown in FIG. 8, the groove portion **27** includes an inverted trapezoidal portion on the apex portion **15** side and a rectangular portion on the bottom portion side.

(86) Also in the fourth embodiment, as in the embodiments described above, it is possible to set the riblets **8** to have strength of a certain level or more within a range in which processing is possible and effectively reduce the surface friction resistance.

(87) Note that, in the fourth embodiment, the inclined portion **13** can also be provided with two or more steps (see the second embodiment), or the perpendicular portion **14** can also be omitted (see the third embodiment).

REFERENCE SIGNS LIST

(88) **1** base portion **2** to **8** riblet **11** first wall portion **12** second wall portion **13** inclined portion **14** perpendicular portion **15** apex portion **30** to **36** riblet structure

Claims

1. A riblet structure, comprising a plurality of riblets that are arranged at intervals in a width direction and each include a first wall portion and a second wall portion, the first wall portion being vertically provided to be substantially perpendicular to a flat bottom portion, the second wall portion being connected to the first wall portion at an apex portion, wherein the first wall portion is vertically provided to be substantially perpendicular from the apex portion to the flat bottom portion to form a groove portion having a right-angled cross section together with an upper surface of the flat bottom portion, and wherein the second wall portion includes an inclined portion that is connected to the first wall portion at the apex portion and inclined with respect to a perpendicular direction at a predetermined angle.
2. The riblet structure according to claim 1, wherein first wall portion sides of the riblets adjacent to each other in the width direction face each other to form a first groove portion having a rectangular cross section, and second wall portion sides thereof face each other to form a second groove portion having a Y-shaped cross section or an inverted trapezoidal cross section.
3. The riblet structure according to claim 2, wherein when a distance in the width direction between two of the apex portions of the riblets adjacent to each other is denoted by s , a distance d in the width direction between lowermost points of two of the inclined portions facing each other in the riblets adjacent to each other is in a range of 0.1 times or more and 0.98 times or less the distance s .
4. The riblet structure according to claim 1, wherein the second wall portion further includes a perpendicular portion vertically provided to be substantially perpendicular to the bottom portion and connected to the inclined portion.
5. The riblet structure according to claim 1, wherein the inclined portion includes a first inclined portion that is inclined with respect to the perpendicular direction at the predetermined angle, and a second inclined portion that is inclined with respect to the perpendicular direction at an angle different from the predetermined angle and is closer to the bottom portion than the first inclined portion.
6. The riblet structure according to claim 5, wherein the angle at which the second inclined portion is inclined with respect to the perpendicular direction is sharper than the angle at which the first inclined portion is inclined with respect to the perpendicular direction.
7. The riblet structure according to claim 1, wherein the predetermined angle is in a range of 20° or more and 60° or less.
8. The riblet structure according to claim 7, wherein the predetermined angle is in a range of 35° or more and 50° or less.
9. The riblet structure according to claim 1, wherein when a distance in the width direction between two of the apex portions of the riblets adjacent to each other is denoted by s , a friction velocity is denoted by $u_{\text{sub}}\tau$, and a kinematic viscosity coefficient is denoted by ν , a dimensionless riblet interval $s_{\text{sup}}+$ represented by $s_{\text{sup}}+=s_{\text{sub}}\tau/\nu$ is in a range of 10 or more and 30 or less.
10. The riblet structure according to claim 9, wherein the dimensionless riblet interval $s_{\text{sup}}+$ is in a range of 10 or more and 25 or less.
11. The riblet structure according to claim 10, wherein the dimensionless riblet interval $s_{\text{sup}}+$ is in a range of 15 or more and 22 or less.
12. The riblet structure according to claim 1, wherein when a distance in the width direction between two of the apex portions of the riblets adjacent to each other is denoted by s , a height h of the riblet is in a range of 0.05 times or more and 1.5 times or less the distance s .
13. An object, comprising a riblet structure on a surface of the object, the riblet structure including a plurality of riblets that are arranged at intervals in a width direction and each include a first wall

portion and a second wall portion, the first wall portion being vertically provided to be substantially perpendicular to a flat bottom portion, the second wall portion being connected to the first wall portion at an apex portion, wherein the first wall portion is vertically provided to be substantially perpendicular from the apex portion to the flat bottom portion to form a groove portion having a right-angled cross section together with an upper surface of the flat bottom portion, and wherein the second wall portion includes an inclined portion that is connected to the first wall portion at the apex portion and inclined with respect to a perpendicular direction at a predetermined angle.
