

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12418509
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Singh; Shailendra

System and method for updating a firewall security configuration in a decentralized network

Abstract

An apparatus may comprise a memory communicatively coupled to a processor. The memory may be configured to store user profiles and security information. The processor may be configured to receive a device profile from a user device. Further, the processor may be configured to validate the device profile against a user profile; determine an entitlement associated with the user profile; generate an initial token indicating that the device profile is entitled to access the entitlement; transmit the initial token to a decentralized network; and receive an updated token from the decentralized network. The updated token may indicate a firewall configuration based at least in part upon the initial token. The firewall configuration may be configured to enable the user device to access the entitlement. The processor may be configured to transmit the firewall configuration to the user device to implement a firewall at the user device.

Inventors:	Singh; Shailendra (Maharashtra, IN)
Applicant:	Bank of America Corporation (Charlotte, NC)
Family ID:	1000008822365
Assignee:	Bank of America Corporation (Charlotte, NC)
Appl. No.:	18/311811
Filed:	May 03, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240372833 A1	Nov. 07, 2024

Publication Classification

Int. Cl.: H04L9/40 (20220101)

U.S. Cl.:

CPC **H04L63/0263** (20130101); **H04L63/102** (20130101);

Field of Classification Search

CPC: G16H (40/20); H04L (9/50); H04L (63/20); H04L (63/102); H04L (63/0227); H04L (63/0245); H04L (63/0263); H04L (63/0272); H04L (67/535); H04L (63/1441); G06Q (30/0277); G06F (21/31)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5968176	12/1998	Nessett	726/11	H04L 63/0227
7441262	12/2007	Hui et al.	N/A	N/A
8228861	12/2011	Nix	N/A	N/A
8353021	12/2012	Satish	709/202	H04L 63/0263
8468244	12/2012	Redlich et al.	N/A	N/A
8498941	12/2012	Felsher	N/A	N/A
8566115	12/2012	Moore	N/A	N/A
8843997	12/2013	Hare	N/A	N/A
9026079	12/2014	Raleigh et al.	N/A	N/A
9419951	12/2015	Felsher et al.	N/A	N/A
10474660	12/2018	Ariel et al.	N/A	N/A
10523657	12/2018	Reddy et al.	N/A	N/A
10785190	12/2019	Saavedra et al.	N/A	N/A
10798165	12/2019	Srinivasan et al.	N/A	N/A
10805332	12/2019	Gunda et al.	N/A	N/A
10880270	12/2019	Rigor et al.	N/A	N/A
11165800	12/2020	Thampy	N/A	N/A
11232125	12/2021	Khante et al.	N/A	N/A
11515032	12/2021	Dormer et al.	N/A	N/A
11575693	12/2022	Muddu et al.	N/A	N/A
2002/0166068	12/2001	Kilgore	726/4	H04L 63/102
2004/0205101	12/2003	Radhakrishnan	709/200	G06Q 30/0277
2007/0234408	12/2006	Burch	726/6	G06F 21/31
2008/0235755	12/2007	Blaisdell	726/1	H04L 63/102
2008/0282336	12/2007	Diaz Cuellar	726/11	H04L 63/20
2016/0099917	12/2015	Glazemakers	726/12	H04L 63/0272
2017/0251013	12/2016	Kirti	N/A	H04L 63/1441
2018/0013722	12/2017	Enos	N/A	G16H 40/20
2018/0131675	12/2017	Sengupta	N/A	H04L 63/0245
2018/0332063	12/2017	Ford	N/A	H04L 67/535
2020/0267138	12/2019	Irwan	N/A	H04L 9/50
2022/0030009	12/2021	Hasan	N/A	N/A
2022/0084087	12/2021	Chapman	N/A	N/A

OTHER PUBLICATIONS

Primary Examiner: Nguyen; Dustin

Background/Summary

TECHNICAL FIELD

(1) The present disclosure relates generally to operation of a system configured to provide a firewall security configuration, and more specifically to a system and method to update a firewall security configuration in a decentralized network.

BACKGROUND

(2) In network security, the term vulnerability refers to a possible point of attack where resources may be attempted to be accessed from a network. In some cases, user devices may be targeted by bad actors to exploit vulnerabilities in security systems of the user devices. To defend against these bad actors, network managers may use firewalls to block unauthorized access to the user device while permitting outward communication. Currently, firewalls need to be reviewed, approved, and set up by a specific network manager before a given firewall is set up in a given user device. As such, several hours of work in security-related operations are needed to implement a firewall.

(3) In situations where configuration information for each firewall is prepared for each user device, several user devices may remain vulnerable in an organization or group of user devices for long periods of time while the network manager sets up a firewall for each user device individually.

SUMMARY OF THE DISCLOSURE

Updating A Firewall Security Configuration

(4) In one or more embodiments, a system and a method disclosed herein generate a firewall security configuration in a decentralized network. The firewall security configuration may be one or more configuration commands to implement a firewall at a user device. In one or more embodiments, the method and the system monitor system interactions of a user device, assign a firewall security configuration to the user device based at least in part upon one or more entitlements corresponding to a user profile associated with the user device, and update the firewall for the user device based at least in part upon changes to the one or more entitlements. To determine the firewall security configuration, the system and the method generate a token representative of the one or more entitlements and provide this token to a decentralized network. In the decentralized network, the token is used to exchange the one or more entitlements to one or more configuration policies and rules corresponding to the entitlements. Once an updated version of the token is received from the decentralized network, the system and the method may extract firewall security information to the user device to be implemented as a firewall at the user device. An improvement provided by using tokens in the decentralized network is that the process of retrieving configuration policies and rules may be automated and may be implemented without the intervention of a network manager while protecting the identity of the user device. The method and the system may update the token to fetch updates to the configuration policies and rules periodically or dynamically every time the system and the method detect a change to the one or more entitlements.

(5) In one or more embodiments, the system and the method described herein are integrated into a practical application of reducing vulnerabilities in a security system, a network, or a group of user devices. In network security, the term vulnerability refers to a possible point of attack where

resources may be attempted to be accessed from the network. In some embodiments, the system and the method are configured to prevent bad actors from exploiting vulnerabilities in security systems of the user devices. To defend against these bad actors, the method and the system are integrated into the practical application of reducing work hours for network managers that configure firewalls to block unauthorized access to the user device while permitting outward communication. In one or more embodiments, the firewalls implemented based at least in part upon the firewall configuration do not need to be reviewed, approved, and set up by any network managers before a given firewall is set up in a given user device. In this regard, several hours of work in security-related operations are reduced or eliminated while implementing a user firewall.

(6) In one or more embodiments, the system and the method described herein are integrated into a practical application of reducing or preventing network security challenges by reducing a possibility of malicious attacks caused by vulnerabilities in the security network. In this regard, the system and the method are integrated into a practical application of upgrading the firewall configuration to implement the firewall in the user device. As a result, the firewall does not need to be approved by network managers or security personnel before the firewall is implemented in the user device. In some embodiments, the system and the method improve operations where configuration information for each firewall is prepared for each user device by acknowledging new possible vulnerabilities, creating tokens to safeguard access to user entitlements via the new possible vulnerabilities, and updating the firewall of the user device to defend against the new possible vulnerabilities. In this regard, safeguarding against the new possible vulnerabilities may refer to updating the firewall of the user device to account for a change in the corresponding user entitlements.

(7) In some embodiments, the system and the method are integrated into a practical application of improving data security by protecting sensitive information associated with a user operating the user device. In particular, the system and the method reduce or eliminate any access from the nodes in the decentralized network to the sensitive information because the initial token comprises initial encrypted firewall configuration that only allows the nodes to identify any entitlements associated with a given user profile. At this stage, the system and method described herein provide updated tokens to the server comprising updated encrypted firewall configuration that the server parses to assign updates to the firewall configuration of the firewall at the user device. As a non-limiting example of technical solutions involving this practical application, the system and the method may identify that a user attempts to access a network resource and generates an update to the firewall such that the user device is enabled to access the network resource with protection against any new possible vulnerabilities without requiring review and approval from security personnel. In turn, security personnel may update the rules and policies at the nodes of the decentralized network, which ensures that the system and the method receive updated tokens updated in accordance with newer security information.

(8) In one or more embodiments, the system and method are directed to improvements in computer systems. Specifically, the system and the method reduce processor and memory usage in user devices by preventing or eliminating queues in a central location in a network. Further, the system and the method reduce the possibility of downtime in the updated firewalls by providing updated tokens via nodes in a decentralized network. In particular, the nodes may be updated individually and may be located at different locations such that rules and policies associated with all security information for an organization is not in a same location. Instead, the system and the method enable nodes located at different locations to provide updated information to the server, generate backups of one another, and remain available for the server to request updated tokens even if one of the node is interrupted or irresponsive. Substantial processing capacity, memory usage, and power consumption is prevented by providing defenses for interactions accessing resources in the network. Another technical solution involves eliminating potential threats dynamically for a given user device.

(9) In one or more embodiments, the system and the method may be performed by an apparatus, such as the server, communicatively coupled to one or more user devices and one or more decentralized networks. Further, the system may be a security system, that comprises the apparatus. In addition, the system and the method may be performed as part of a process performed by the apparatus communicatively coupled to the one or more user devices and the one or more decentralized networks. As a non-limiting example, the apparatus may comprise a memory and a processor communicatively coupled to one another. The memory may be configured to store one or more user profiles associated with one or more user groups and security information comprising one or more firewall configurations. Each user profile may comprise one or more entitlements. Each firewall configuration may be configured to enable each user profile to access the one or more entitlements. The processor may be configured to receive a first device profile from a first user device; validate the first device profile against a first user profile of the one or more user profiles; and determine a first entitlement of the one or more entitlements associated with the first user profile. Further, the processor may be configured to generate a first initial token indicating that the first device profile is entitled to access the first entitlement; transmit the first initial token to a decentralized network; and receive a first updated token from the decentralized network. The first updated token may indicate a first firewall configuration based at least in part upon the first initial token. The first firewall configuration may be configured to enable the first user device to access the first entitlement. Then, the processor may be configured to transmit the first firewall configuration to the first user device to implement a first firewall at the first user device.

Dynamically Aggregating Multiple Firewall Security Configurations

(10) In one or more embodiments, the system and the method disclosed herein dynamically aggregate multiple firewall security configurations in a decentralized network. The firewall security configurations may be configuration commands to implement firewalls at multiple user devices. In one or more embodiments, the method and the system monitor and aggregate multiple tokens of multiple user devices in a group or organization. Each token may be representative of entitlements associated with a user device in the group or organization. In the decentralized network, the token is used to exchange the one or more entitlements to one or more configuration policies and rules corresponding to the entitlements. In some embodiments, the method and the system may parse each token generated for a user device in the group or organization; identify differences among the tokens in the group or organization; and dynamically update the tokens of user devices in the group or organization that include fewer entitlements in their corresponding tokens. An improvement provided by the system and the method is that multiple tokens in a group or organization may be dynamically updated to include the entitlements approved for multiple user devices in the group or organization.

(11) In one or more embodiments, the system and the method described herein are integrated into a practical application of dynamically reduce vulnerabilities in a security system, a network, or a group of user devices. As described above, in network security, the term vulnerability refers to a possible point of attack where resources may be attempted to be accessed from the network. In some embodiments, the system and the method are configured to prevent bad actors from exploiting vulnerabilities in security systems of a group of user devices. To defend against these bad actors, the method and the system are integrated into the practical application of reducing work hours for network managers that configure firewalls to block unauthorized access to the group of user devices while permitting outward communication. In one or more embodiments, the firewalls implemented based at least in part upon the firewall configuration do not need to be reviewed, approved, and set up by any network managers for an entire group of user devices before firewalls are set up in a given group of user device. In this regard, several hours of work in security-related operations are reduced or eliminated while implementing a group firewall.

(12) In one or more embodiments, the system and the method described herein are integrated into a practical application of reducing or preventing network security challenges by reducing a

possibility of malicious attacks caused by vulnerabilities in the security network. In this regard, the system and the method are integrated into a practical application of dynamically aggregating multiple firewall security configurations to implement the firewalls in a given group comprising the user devices. As a result, the firewalls do not need to be approved by network managers or security personnel before the firewalls are aggregated and implemented at each user device in the group. In some embodiments, the system and the method improve operations where configuration information for each firewall is prepared for a group of user devices by acknowledging new possible vulnerabilities, creating tokens to safeguard access to user entitlements via the new possible vulnerabilities, dynamically aggregating tokens for multiple user devices in a group, and updating the firewall of the user device to defend against the new possible vulnerabilities. In this regard, safeguarding against the new possible vulnerabilities may refer to updating the firewall of the group of user devices to account for multiple individual changes in the corresponding user entitlements at each user device.

(13) In some embodiments, the system and the method are integrated into a practical application of improving data security by protecting sensitive information associated with any users operating the group of user devices. In particular, the system and the method reduce or eliminate any access from the nodes in the decentralized network to the sensitive information because the initial token comprises initial encrypted firewall configuration that only allows the nodes to identify any entitlements associated with multiple user profiles. At this stage, the system and method described herein provide updated tokens to the server comprising updated encrypted firewall configuration that the server parses to assign updates to the firewall configuration of the firewall at the user devices in the group. As a non-limiting example of technical solutions involving this practical application, the system and the method may identify that a user in the group attempts to access a network resource and generates an update to the collective firewall such that the user devices in the group are enabled to access the network resource with protection against any new possible vulnerabilities without requiring review and approval from security personnel. In turn, security personnel may update the rules and policies at the nodes of the decentralized network, which ensures that the system and the method receive updated tokens updated in accordance with newer security information.

(14) In one or more embodiments, the system and method are directed to improvements in computer systems. Specifically, the system and the method reduce processor and memory usage in the user devices of a given group by preventing or eliminating queues in a central location in a network. Further, the system and the method reduce the possibility of downtime in the updated firewalls by providing aggregated updated tokens via nodes in a decentralized network. In particular, the nodes may be updated individually and may be located at different locations such that rules and policies associated with all security information for an organization is not in a same location. Instead, the system and the method enable nodes located at different locations to provide updated information to the server, generate backups of one another, and remain available for the server to request updated tokens even if one of the node is interrupted or unresponsive. Substantial processing capacity, memory usage, and power consumption is prevented by dynamically providing defenses for interactions accessing resources in the network. Another technical solution involves eliminating potential threats dynamically for a given group of user devices.

(15) In one or more embodiments, the system and the method may be performed by an apparatus, such as the server, communicatively coupled to one or more user devices and one or more decentralized networks. Further, the system may be a security system, that comprises the apparatus. In addition, the system and the method may be performed as part of a process performed by the apparatus communicatively coupled to the one or more user devices and the one or more decentralized networks. As a non-limiting example, the apparatus may comprise a memory and a processor communicatively coupled to one another. The memory may be configured to store one or more user profiles associated with one or more user groups, security information comprising one or

more firewall configurations, and one or more updated tokens associated with one or more of the user profiles. Each user profile may comprise one or more entitlements. Each firewall configuration may be configured to enable each user profile to access the one or more entitlements. Each updated token may indicate a firewall configuration configured to enable a corresponding user device to access an entitlement of the one or more entitlements. The processor may be configured to identify a first updated token of the one or more updated tokens that is associated with a first user profile of the one or more user profiles; and determine a first entitlement of the one or more entitlements associated with the first user profile. The first user profile may be associated with a first user group of the one or more user groups. Further, the processor may be configured to identify a second updated token of the one or more updated tokens that is associated with a second user profile of the one or more user profiles; and determine a second entitlement of the one or more entitlements associated with the second user profile. The second user profile may be associated with the first user group of the one or more user groups. Then, the processor may be configured to determine a second entitlement of the one or more entitlements associated with the second user profile; generate a first initial token indicating that the first user group is entitled to access the first entitlement and the second entitlement; transmit the first initial token to a decentralized network; and receive a third updated token from the decentralized network. The third updated token may indicate a first firewall configuration based at least in part upon the first initial token. The first firewall configuration may be configured to enable a first user device associated with the first user profile and a second user device associated with the second user profile to access the first entitlement and the second entitlement. In this regard, the processor is configured to transmit the first firewall configuration to the first user device and the second user device to implement a first firewall at the first user device and at the second user device.

(16) Certain embodiments of this disclosure may include some, all, or none of these advantages. These advantages and other features will be more clearly understood from the following detailed description taken in conjunction with the accompanying drawings and claims.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) For a more complete understanding of this disclosure, reference is now made to the following brief description, taken in connection with the accompanying drawings and detailed description, wherein like reference numerals represent like parts.

(2) FIG. 1 illustrates an example security system in accordance with one or more embodiments;

(3) FIG. 2 illustrates example security operations performed by the security system of FIG. 1 in accordance with one or more embodiments;

(4) FIG. 3 illustrates an example flowchart of a method to update a firewall security configuration in accordance with one or more embodiments; and

(5) FIG. 4 illustrates an example flowchart of a method to aggregate multiple firewall security configurations in accordance with one or more embodiments.

DETAILED DESCRIPTION

(6) As described above, this disclosure provides various systems and methods to update a firewall security configuration for a user device in a decentralized network. Further, this disclosure provides various systems and methods to dynamically aggregate multiple firewall security configurations for user devices in a user device group. FIG. 1 illustrates a security system **100** in which a server **102** is configured to determine individual or aggregated firewall configurations **104A-104D** based at least in part upon monitored operations of one or more user devices **110A-110D** in a user device group **112**. FIG. 2 illustrates one or more security operations **200** performed by the security system **100** of FIG. 1. FIG. 3 illustrates a first process **300** to perform one or more of the security operations **200**

of FIG. 2. FIG. 4 illustrates a second process 400 to perform one or more of the security operations 200 of FIG. 2.

Security System Overview

(7) FIG. 1 illustrates a security system 100 configured to update one or more firewall security configuration in accordance with one or more embodiments. Further, the security system 100 is configured to aggregate multiple firewall security configuration in accordance with one or more embodiments. In the security system 100 of FIG. 1, a server 102 monitors one or more operations performed by one or more users (e.g., user 106) operating one or more user devices 110A-110D in a user device group 112 and identifies at least one operation in a first user device 110A that triggers a request for an updated firewall configuration to the server 102. In FIG. 1, the server 102 is communicatively coupled to multiple user devices 110A-110D via a communication link 114 of via a network 120. While FIG. 1 shows the server 102 connected via the communication link 114 to the entire user device group 112, the server 102 may be communicatively coupled to each of the user devices 110A-110D directly or indirectly via one or more additional electronic devices (e.g., routers, gateways, and the like). Further, the server 102 is communicatively coupled to one or more decentralized networks 130 comprising one or more nodes 132-140. While FIG. 1 shows the server 102 connected via the network 120 to the entire one or more decentralized networks 130, the server 102 may be communicatively coupled to each of the nodes 132-140 directly or indirectly via one or more additional electronic devices (e.g., routers, gateways, and the like).

(8) In one or more embodiments, the server 102 is configured to monitor multiple electronic operations of the user devices 110A-110D over a first predetermined amount of time. In reference to user device 110A as a non-limiting example, the electronic operations may comprise input and output communications received and transmitted by the user device 110A. respectively. The server 102 may be configured to identify an electronic operation that triggers a request to update one or more firewall configurations 104A-104D (collectively, firewall configurations 104) associated with the user device 110A. In one example, a trigger electronic operation may be an attempt by the user device 110A to access a specific network resource (e.g., a website) via the network 120. In another example, the trigger electronic operation may the request by the user device 110A to generate a firewall 150A at the user device 110A. At this stage, in response to determining that the user device 110A is entitled to access the network resources, the server 102 may generate an initial token (one of tokens 116, one of the one or more initial tokens 202 shown in FIG. 2) indicating that the user device 110A is allowed to access the one. In some embodiments, the initial token is transmitted to the one or more decentralized networks 130. In the decentralized networks 130, the nodes 132-140 may update the initial token into an updated token (one of tokens 116, one of the one or more updated tokens 204 of FIG. 2) that is then transmitted to the server 102 comprising updated rules and policies. The server 102 may provide a firewall configuration to the user device 110A based at least in part upon the updated token. The firewall configuration may enable the user device 110A to establish the firewall 150A at the user device 110A comprising a secure (i.e., protected) access to the network resources via the network 120.

(9) In one or more embodiments, the server 102 is configured to monitor multiple electronic operations of the user devices 110A-110D over a second predetermined amount of time. In reference to user device 110A and user device 110B as non-limiting examples, the server 102 may be configured to identify electronic operations that triggers a first request to update one or more firewall configurations 104 associated with the user device 110A and a second request to update one or more firewall configurations 104 associated with the user device 110B. Upon generating a corresponding updated token for the user device 110A and the user device 110B, the server 102 may determine whether the respective firewall configurations 104 indicated by the updated tokens provide secure access to different network resources. If the updated tokens enable secure access to different network resources, the server 102 may aggregate the updated tokens to generate a single updated token. The server 102 may provide the user device 110A and the user device 110B with the

single updated token instead of their individual tokens to preemptively enable each of the user device **110A** and the user device **110B** to securely access each other's network resources via the network **120**.

Security System Components

Server

(10) The server **102** is generally any device that is configured to process data and communicate with computing devices (e.g., user devices **110A-110D**), databases, systems, and the like, via one or more interfaces (i.e., user interface **152** or network interface **154**). The server **102** may comprise a processor **156** that is generally configured to oversee operations of a processing engine **158**. The operations of the processing engine **156** are described further below in conjunction with the servicing system **100** described in FIG. 1, the security operations **200** in FIG. 2, process **300** described in FIG. 3, and process **400** described in FIG. 4.

(11) The server **102** comprises the processor **156** communicatively coupled with the user interface **152**, the network interface **154**, a hardware accelerator **160**, a token controller **162**, and a memory **164**. The server **102** may be configured as shown, or in any other configuration.

(12) The processor **156** comprises one or more processors communicatively coupled to the memory **164**. The processor **156** may be any electronic circuitry, including, but not limited to, state machines, one or more central processing unit (CPU) chips, logic units, cores (e.g., a multi-core processor), field-programmable gate arrays (FPGAs), application-specific integrated circuits (ASICs), or digital signal processors (DSPs). The processor **156** may be a programmable logic device, a microcontroller, a microprocessor, or any suitable combination of the preceding. The one or more processors **156** are configured to process data and may be implemented in hardware or software executed by hardware. For example, the processor **156** may be 8-bit, 16-bit, 32-bit, 64-bit or of any other suitable architecture. The processor **156** may include an arithmetic logic unit (ALU) for performing arithmetic and logic operations, processor registers that supply operands to the ALU and store the results of ALU operations, and a control unit that fetches instructions **166** from the memory **164** and executes them by directing the coordinated operations of the ALU, registers and other components. In this regard, the one or more processors **156** are configured to execute various instructions. For example, the one or more processors **156** are configured to execute the instructions **166** to implement the functions disclosed herein, such as some or all of those described with respect to FIGS. 1-4. In some embodiments, the functions described herein are implemented using logic units, FPGAs, ASICs, DSPs, or any other suitable hardware or electronic circuitry.

(13) In one or more embodiments, the user interface **152** and the network interface **154** may be any suitable hardware and/or software to facilitate any suitable type of wireless and/or wired connection. These connections may include, but not be limited to, all or a portion of network connections coupled to the Internet, an Intranet, a private network, a public network, a peer-to-peer network, the public switched telephone network, a cellular network, a local area network (LAN), a metropolitan area network (MAN), a wide area network (WAN), and a satellite network. The user interface **152** and the network interface **154** may be configured to support any suitable type of communication protocol as would be appreciated by one of ordinary skill in the art.

(14) In one or more embodiments, the user interface **152** and the network interface **154** may be configured to enable wired and/or wireless communications. The user interface **152** and the network interface **154** may be configured to communicate data between the server **102** and other user devices (i.e., the user devices **110A-110D**), network devices (i.e., the decentralized networks **130**), systems, or domain(s) via the network **120**. For example, the network interface **154** may comprise a WIFI interface, a LAN interface, a WAN interface, a modem, a switch, or a router. The processor **156** may be configured to send and receive data using the user interface **152** and the network interface **154**. The user interface **152** and the network interface **156** may be configured to use any suitable type of communication protocol. In some embodiments, the communication protocols may be protocols configured in accordance with the non-fungible token (NFT) processing

and aggregating of the EIP-3664 standard. In the EIP-3664 standard, tokens may be aggregated or grouped based at least upon common characteristics, such as general changeability, transferability, upgradeability, and evolvable attributes.

(15) In some embodiments, the hardware accelerator **160** may be any combination of a processing accelerator, signal processing circuitry (e.g., including filters, mixers, oscillators, amplifiers, and the like), or digital processing circuitry (e.g., for digital modulation as well as other digital processing). For example, the hardware accelerator **160** may be configured to allocate power, processing, and memory resources during updates of firewall configurations and during dynamic aggregation of firewall configurations.

(16) In one or more embodiments, the token controller **162** is configured to create, analyze, manage, and update one or more tokens **116**. The token controller **162** may be configured to communicate with the one or more decentralized networks **130** via the network interface **154** and the network **120**. The token controller **162** may be configured to perform one or more of the security operations **200** described below in reference to FIG. 2. In some embodiments, the token controller **162** may be configured to update one or more of the firewall configurations **104** in the security information **176**. In other embodiments, the token controller **162** may be configured to aggregate updated tokens of multiple user devices **110** and obtain a new updated token from the decentralized networks **130** representing an aggregated firewall configuration **104**. In this regard, the token controller **162** may generate user tokens **180** when an updated token is configured to provide a firewall configuration **104** to be implemented as a firewall **150** at one or more of the user devices **110**. In yet other embodiments, the token controller **162** may generate group tokens **178** when an updated token is configured to provide a firewall configuration **104** to be implemented as one or more firewalls **150** at one or more the user devices **110** in a user device group **112**.

(17) The memory **164** may be volatile or non-volatile and may comprise a read-only memory (ROM), random-access memory (RAM), ternary content-addressable memory (TCAM), dynamic random-access memory (DRAM), and static random-access memory (SRAM). The memory **164** may be implemented using one or more disks, tape drives, solid-state drives, and/or the like. The memory **164** is operable to store the instructions **166**, multiple asset names **168** corresponding to names of one or more of the user devices **110**, a server profile **170**, one or more user profiles **172** corresponding to one or more users (e.g., user **106**) of the user devices **110** and comprising one or more entitlements **174** for each user profile, security information **176** comprising the firewall configurations **104**, one or more tokens **177** comprising group tokens **178A** and **178B** (collectively, group tokens **178**) and one or more user tokens **180A** and **180B** (collectively, group tokens **180**), and/or any other data or instructions. The instructions **166** may comprise any suitable set of instructions, logic, rules, or code operable to execute the processor **156**.

(18) In one or more embodiments, the asset names **168** may be the names of the user devices **110** in a given user device group **112**. The asset names may be a string of numbers, alphanumeric characters, one or more words or phrases, one or more letters, and/or symbols. In some embodiments, the server profile **170** may be a profile of the server **102** that is representative of one or more entitlements of the server **102** within an organization. For example, an organization may include multiple versions of the server **102** comprising different levels of clearance or access to network resources. In the example of FIG. 1, the server profile **170** may indicate that the server **102** is entitled to operate the token controller **162** and perform one or more of the security operations described in reference to FIG. 2 in relation to the processor **156** and/or the token controller **162**.

(19) In one or more embodiments, the user profiles **172** may comprise multiple profiles for users (e.g., user **106**). Each user profile may comprise one or more entitlements **174**. As described above, the entitlements **174** may indicate that a given user is allowed to access one or more network resources in accordance with one or more rules and policies **196A-196E** (collectively, rules and policies **196**). The entitlements **174** may indicate that a given user is allowed to perform one or more operations in the network **120** (e.g., access a specific website on the Internet). To secure or

protect operations of the user devices **110** from bad actors, the entitlements may be assigned to a given user profile **172** in accordance with updated security information **198A-198E** (collectively, security information **198**), which may provide guidance parameters to the use of the entitlements **174** based at least upon corresponding rules and policies **196**.

(20) In one or more embodiments, the security information **176** comprises one or more firewall configurations **104**. In FIG. **1**, the security information **176** comprises the firewall configuration **104A**, the firewall configuration **104B**, the firewall configuration **104C**, and the firewall configuration **104D**. In some embodiments, the security information may comprise more or less firewall configurations **104** than those showed in FIG. **1**. As described above, the security information **176** may be established configuration parameters to implement a firewall **150** at a given user device **110**. In this regard, each firewall configuration **104** comprises one or more instructions for implementing the firewalls **150**.

(21) In one or more embodiments, the tokens **116** are comprise the group tokens **178** and the user tokens **180**. The group tokens **178** may be configured to provide one or more firewall configurations **104** from the security information **176** to implement a firewall **150** at multiple user devices **110**. For example, the user device group **112** may receive the group token **178A** from the server **102** indicating that the aggregated updated tokens corresponding to the user devices **110A-110D**. The user tokens **180** may be configured to provide one or more firewall configurations **104** from the security information **176** to implement a firewall **150** at least one user device **110**. For example, the user device **110A** in the user device group **112** may receive the user token **180A** from the server **102** indicating that the updated token corresponding to the user device **110A**.

Network

(22) The network **120** facilitates communication between and amongst the various devices of the security system **100**. The network **120** may be any suitable network operable to facilitate communication between the server **102**, the one or more decentralized networks **130**, and the user devices **110** of the security system **100**. The network **120** may include any interconnecting system capable of transmitting audio, video, signals, data, data packets (e.g., non-fungible tokens (NFT)), messages, or any combination of the preceding. The network **120** may include all or a portion of a public switched telephone network (PSTN), a public or private data network, a LAN, a MAN, a WAN, a local, regional, or global communication or computer network, such as the Internet, a wireline or wireless network, an enterprise intranet, or any other suitable communication link, including combinations thereof, operable to facilitate communication between the devices.

User Device

(23) In one or more embodiments, each of the user devices **110** (e.g., the user devices **110A-110D**) may be any computing device configured to communicate with other devices, such as the server **102**, other user devices **110** in the user device group **112**, databases, and the like in the security system **100**. Each of the user devices **110** may be configured to perform specific functions described herein and interact with one or more user devices **110A-110D** in the user device group **112**. Examples of user device **110** comprise, but are not limited to, a laptop, a computer, a smartphone, a tablet, a smart device, an IoT device, a simulated reality device, an augmented reality device, or any other suitable type of device.

(24) The user devices **110** may be hardware configured to create, transmit, and/or receive information. The user devices **110** may be configured to receive inputs from a user, process the inputs, and generate data information or command information in response. The data information may include documents or files generated using a graphical user interface (GUI). The command information may include input selections/commands triggered by a user using a peripheral component or one or more device peripherals **184** (i.e., a keyboard) or an integrated input system (i.e., a touchscreen displaying the GUI). The user devices **110** may be communicatively coupled to the server **102** via a network connection (i.e., user interface **152** in the server **102**). The user devices **110** may transmit and receive data information, command information, or a combination of

both to and from the server **102** via the user interface **152**. In one or more embodiments, the user devices **110** is configured to exchange data, commands, and signaling with the server **102** via the communication link **114**. In some embodiments, the user devices **110** are configured to receive at least one firewall configuration from the server **102** to implement a firewall (one of the firewalls **150**) at one of the user devices **110**. In other embodiments, the firewalls configurations **104** and the firewalls are explained in further detail below in conjunction with the operational flow of the servicing system **100** described in FIG. **1**, the security operations **200** of FIG. **2**, the process **300** described in FIG. **3**, and the process **400** described in FIG. **4**.

(25) In one or more embodiments, while FIG. **1** shows the user device **110A**, the user device **110B**, the user device **110C**, and the user device **110D**, the user device group **112** may comprise less or more user devices **110**. In FIG. **1**, while the firewall **150A** is implemented at the user device **110A**, the firewall **150B** is implemented at the user device **110B**, the firewall **150C** is implemented at the user device **110A**, and the firewall **150A** is implemented at the user device **110A**, a single firewall **150** may be implemented at two or more user devices **110**. For example, in the case of a firewall to be implemented as a result of aggregating firewall configurations **104** for all user devices **110** in the user device group **112**, a same firewall **150** may be implemented in the user devices **110A-110D** of the user device group **112**.

(26) In one or more embodiments, referring to the user device **110A** as a non-limiting example of the user devices **110**, the user device **110A** may comprise a device interface **182**, the one or more device peripherals **184**, a device processor **186**, and a device memory **188**. The device interface **182** may be any suitable hardware or software (e.g., executed by hardware) to facilitate any suitable type of communication in wireless or wired connections. These connections may comprise, but not be limited to, all or a portion of network connections coupled to additional user devices **110A-110D** in the user device group **112**, the server **102**, the Internet, an Intranet, a private network, a public network, a peer-to-peer network, the public switched telephone network, a cellular network, a LAN, a MAN, a WAN, and a satellite network. The device interface **182** may be configured to support any suitable type of communication protocol.

(27) In one or more embodiments, the one or more device peripherals **184** may comprise audio devices (e.g., speaker, microphones, and the like), input devices (e.g., keyboard, mouse, and the like), or any suitable electronic component that may provide a modifying or triggering input to the user device **110A**. For example, the one or more device peripherals **184** may be speakers configured to release audio signals (e.g., voice signals or commands) during media playback operations. In another example, the one or more device peripherals **184** may be microphones configured to capture audio signals from the user **106**. In one or more embodiments, the one or more device peripherals **184** may be configured to operate continuously, at predetermined time periods or intervals, or on-demand.

(28) The device processor **186** may comprise one or more processors communicatively coupled to and in signal communication with the device interface **182**, the device peripherals **184**, and the device memory **188**. The device processor **186** is any electronic circuitry, including, but not limited to, state machines, one or more CPU chips, logic units, cores (e.g., a multi-core processor), FPGAs, ASICs, or DSPs. The UE processor **164** may be a programmable logic device, a microcontroller, a microprocessor, or any suitable combination of the preceding. The one or more processors in the device processor **186** are configured to process data and may be implemented in hardware or software executed by hardware. For example, the device processor **186** may be an 8-bit, a 16-bit, a 32-bit, a 64-bit, or any other suitable architecture. The device processor **186** comprises an ALU to perform arithmetic and logic operations, processor registers that supply operands to the ALU, and store the results of ALU operations, and a control unit that fetches software instructions such as device instructions **190** from the device memory **188** and executes the device instructions **190** by directing the coordinated operations of the ALU, registers, and other components via a device processing engine (not shown). The device processor **186** may be configured to execute various

instructions. For example, the device processor **186** may be configured to execute the device instructions **190** to implement functions or perform operations disclosed herein, such as some or all of those described with respect to FIGS. **1-4**. In some embodiments, the functions described herein are implemented using logic units, FPGAs, ASICs, DSPs, or any other suitable hardware or electronic circuitry.

Decentralized Network

(29) In one or more embodiments, the decentralized network **130** comprises a peer-to-peer networking protocol that enables development of serverless applications. The decentralized network **130** may include multiple electronic components or devices (i.e., nodes **132-140**) comprising specific node data. The nodes **132-140** may not be required to store or validate all data in the decentralized network **130**. Instead, validation of each node's data may be obtained via peer accountability. The peer accountability is explained in further detail below in conjunction with the operational flow of the servicing system **100** described in FIG. **1**, process **300** described in FIG. **3**, and process **400** described in FIG. **4**.

(30) In some embodiments, the nodes **132-140** may include only their own data and a reference to all other data in the decentralized network **130** in accordance with rules and policies **196** preestablished by an electronic component or device outside the decentralized network **130** (e.g., one or more servers, such as the server **102**). These rules and policies **196** may determine how the nodes **132-140** interact with each other and the server **102**. The rules and policies **196** may be updated dynamically or periodically with additional data received as updates via one or more planning components (e.g., electronic devices or components configured to provide updates to the rules and policies **196**). The updates may be triggered by a perceived lack of knowledge level in the nodes **132-140**. A perceived knowledge level in the nodes **132-140** may be identified via node scores (not shown) received from the server **102** as feedback.

(31) In one or more embodiments, each node (i.e., out of nodes **132-140**) in the decentralized network **130** includes knowledge-specific information and information associated with peer accountability and a perceived knowledge level. Specifically, referencing the node **132** as a non-limiting example, includes rules and policies **196A** and updated security information **198A**. The updated security information **198A** may include expert information corresponding to at least one knowledge domain configured to protect operations of one or more user devices **110**. In one or more embodiments, the node **132** may be configured to receive one or more of initial tokens. Upon receiving the initial tokens **116**, the node **132** may be configured to determine whether any of entitlements **174** of the initial tokens correspond to the knowledge information included in the updated security information **198A**.

(32) In other embodiments, the node **132** includes a processor (not shown) configured to provide updates corresponding to specific updated security information **196**. The processor in the node **132** may be configured to provide updated tokens directly to the token controller **162**. Further, the processor of the node **132** may be configured to route any initial tokens that are not updated to one of the other nodes **134-140** in accordance with one or more rules and policies **194** governing the decentralized network **130**.

(33) In the example of FIG. **1**, the decentralized network **130** includes five nodes **132-140**. However, additional nodes or fewer nodes may be included. In some embodiments, each of the nodes **132-140** includes a corresponding rules and policies **196** and a corresponding security information **198**. In the decentralized network **130** of FIG. **1**, the node **132** includes the rules and policies **196A** and the updated security information **198A**; the node **134** includes the rules and policies **196B** and the updated security information **198B**; the node **136** includes the rules and policies **196C** and the updated security information **198C**; the node **138** includes the rules and policies **196D** and the updated security information **198D**; and the node **140** includes the rules and policies **196E** and the updated security information **198E**.

Operational Flow Overview

(34) FIG. 2 illustrates an example of one or more security operations **200** implemented by the security system **100** of FIG. 1, in accordance with one or more embodiments. While the one or more security operations **200** are shown to be performed by the user devices **110**, the token controller **162**, and the one or more decentralized networks **130**, additional electronic devices or components in the server **102** (e.g., the processor **156** or the hardware accelerator **160**) or in a network element (not shown) may be configured to perform one or more of the security operations **200**. In the example of FIG. 2, the token controller **114** comprise a token generator **210**, a token transceiver **212**, a controller memory **214**, a firewall aggregator **216**, and a token aggregator **218** communicatively coupled to one another.

(35) In one or more embodiments, the token generator **210** is hardware or software (e.g., executed by hardware) configured to generate one or more tokens based at least in part upon one or more characteristics provided by the server **102**. In some embodiments, the token generator **210** is configured to mint a token based at least in part upon a decentralized network protocol (e.g., in applications involving blockchain, holochain, and the like). In some embodiments, the token generator **210** shares operations with the processor **156** or the hardware accelerator **160** such that generating a token may be performed by any one or more of these electronic devices or components.

(36) In one or more embodiments, the token transceiver **212** is hardware (e.g., antenna array configured to exchange wireless communications, an analog or digital switchboard configured to exchange wired communications, and the like) or software (e.g., executed by hardware) configured to receive and transmit one or more tokens based at least in part upon one or more conditions indicated by the server **102**. In some embodiments, the token transceiver **212** is configured to transmit or receive minted tokens based at least in part upon one of the decentralized network protocol. In some embodiments, the token transceiver **212** shares operations with the user interface **154** and the network interface **154** such that transmitting or receiving a token may be performed by any one or more of these electronic devices or components alone or in combination with one another.

(37) The controller memory **214** comprises one or more group members **220** and one or more firewall configurations **104**. The group members **220** may be user profiles **172** that are members of a specific group (e.g., members of the user device group **112**). The group members **220** may comprise the user profiles **172** of the server memory **164** shown as user profile **172A**, user profile **172B**, and user profile **172C**, among others. The firewall configurations **104** may comprise secure access to the entitlements **174** of the server memory **164** shown as entitlement **174A**, entitlement **174B**, and entitlement **174C**, among others.

(38) The firewall aggregator **216** may comprise one or more group firewalls **230A** and **230B** (collectively, group firewalls **230**) comprising one or more firewall configurations **104**. Each of the firewall configurations **104** may comprise secure or protected access to the one or more entitlements **174**. Each firewall configuration **104** may be aggregated to obtain compile multiple firewall configurations **104** associated with a specific user device group **112** in the group firewall **230**. The firewall configurations **104** may be different or similar between group firewalls **230**.

(39) The token aggregator **218** may comprise one or more of the group tokens **178**. In the example of FIG. 2, the token aggregator **218** comprises the group token **178A** and the group token **178B**. Each of the group tokens **178** may comprise one or more user tokens **180**. As described above, each group token **178** may be aggregated to obtain compile multiple firewall configurations associated with a specific user device group **112**.

(40) In some embodiments, one or more user devices **110** send one or more firewall requests **240** from the user device group **112** to the token controller **162**. The token controller **162** may generate and transmit one or more initial tokens **202** with initial encrypted firewall configuration **250** to the one or more decentralized networks **130**. The initial tokens **202** may be one or more initial tokens **202** configured to indicate the entitlements **174** that a user profile or a group of user profiles

request to access. The initial firewall configuration **250** may be configuration information comprising one or more of the entitlements **174** the one or more user devices **110** request to access. At the decentralized network **130**, the nodes **132-140** may perform one or more token updating operations shown as updating token **260** and updating tokens **270-274** in which updated tokens are generated or minted based at least in part upon the initial firewall configuration **250** received from the initial tokens **202**. In some embodiments, the decentralized network **130** transmits one or more updated tokens **204** to the token controller **162** comprising updated encrypted firewall configuration **280**. Upon receiving the updated tokens **204**, the token controller **162** may extract firewall configurations **104** to implement one or more firewalls **150** in the respective user devices **110**. The token controller **162** may parse the updated tokens **204** to determine whether a given updated token is a group token **178** or a user token **180**. In some embodiments, the token controller **162** may transmit one or more group or user tokens **250** to one or more user devices **110** in the user device group **112** based at least in part upon the firewall configurations **104** updated in the one or more updated tokens **204**.

Updating A Firewall Security Configuration

(41) In one or more embodiments, the security operations **200** comprise generating the firewall configuration **104A** based at least in part upon operations performed in the decentralized network **130**. The firewall configuration **104A** may be one or more configuration commands to implement the firewall **150A** at the user device **110A**. In one or more embodiments, the server **102** monitors interactions of the user device **110A** in the user device group **112**, assigns at least one firewall configuration **104A** to the user device **110A** based at least in part upon on one or more entitlements **174** corresponding to a user profile **172A** associated with the user device **110A**, and update the firewall configuration **104A** for the user device **110A** based at least in part upon changes to the one or more entitlements **174**. To determine the firewall configuration **104A**, the token generator **210** generates an initial token **202** representative of the one or more entitlements **174** and provides this initial token **202** to the decentralized network **130**. In the decentralized network **130**, the token is used to exchange the one or more entitlements **174** to one or more configuration policies and rules **196** corresponding to the entitlements **174**.

(42) In FIG. 2, updating token **260** is shown as a representation in which the node **132** forwards the initial token **202** to the node **140** if the node **132** determines that the node **140** comprises the policies and rules **196** corresponding to the initial token **202** received in accordance with a corresponding security information **198**. Once an updated version of the token is created by the decentralized network **130**, the token transceiver **212** receives an updated token **204** from the decentralized network **130**. At this stage, the server **102** may extract firewall configuration **104** to the user device to be implemented as a firewall at the user device. An improvement provided by using tokens in the decentralized network **130** to obtain updated security information **198** is that the process of retrieving configuration policies and rules **196** may be automated and may be dynamically implemented without the intervention of a network manager while protecting the identity of the user **106** operating the user device **110A**. In this regard, the security operations may update the token to fetch updates to the configuration policies and rules **196** periodically or dynamically every time the server **102** detects a change to the one or more entitlements **174** for the user device **110A**.

Dynamically Aggregating Multiple Firewall Security Configurations

(43) In one or more embodiments, the security operations **200** comprise dynamically aggregating multiple firewall configurations **104** based at least in part upon operations performed in the decentralized network **130**. The firewall security configurations **104** may be configuration commands to implement firewalls **150A** and **150B** at the user device **110A** and the user device **110B**, respectively. In one or more embodiments, the server **102** monitors and aggregates multiple user tokens **180** of the user device **110A** and the user device **110B** in the user device group **112**. Each user token **180** may be representative of any entitlements **174** associated with each user

device **110** in the user device group **112**. In one example, the entitlement **174A** may be associated with the user profile **172A** and the user token **180A** of the user device **110A**. In another example, the entitlement **174B** may be associated with the user profile **172B** and the user token **180B** of the user device **110B**. The user token **180A** and the user token **180B** may be tokens previously updated via the decentralized network **130**.

(44) In some embodiments, the token aggregator **218** identifies one or more updated tokens **204** (e.g., user token **180A** and the user token **180B**) in the tokens **116** that may be already prepared for the user device **110A** and the user device **110B** and aggregates the updated tokens **204** to create the group token **178A**. In this regard, the group token **178A** may be transmitted to the decentralized network **130** via the token transceiver **212** as an initial token **202** comprising a corresponding initial encrypted firewall configuration **250**.

(45) In the decentralized network **130**, the token is used to exchange the one or more entitlements **174** with one or more configuration policies and rules **196** corresponding to the entitlements **174** and updated in accordance with updated security information **198**. In the decentralized network **130**, the updates are represented by updating token **270**, updating token **272**, and updating token **274**. The multiple updates may occur under conditions in which the node **132** received the initial token **202** and determines that the nodes **134-138** may comprise relevant updated security information **198B-198D** to update the initial token **202**. In some embodiments, the node **134** may receive the initial token **202** from the node **132** and determines that the node **136** may comprise relevant updated security information **198C** to provide additional updates to the initial token **202**. At this point, the node **136** may receive the initial token **202** from the node **134** and determines that the node **138** may comprise relevant further updated security information **198D** to provide additional updates to the initial token **202**. After an updated token **204** is generated based at least in part upon the updates provided to the initial tokens **202**.

(46) Once an updated version of the token is created by the decentralized network **130**, the token transceiver **212** receives an updated token **204** from the decentralized network **130**. At this stage, the server **102** may extract firewall configuration **104C** to the user device to be implemented as the firewall **150A** at the user device **110A** and the firewall **150B** at the user device **110B**.

(47) In some embodiments, the firewall aggregator **216** identifies one or more firewall configurations **104** from updated tokens **204** (e.g., user token **180A** and the user token **180B**) in the tokens **116** that may be already prepared for the user device **110A** and the user device **110B** and aggregates the firewall configurations **104** to create the group firewall **230A**. In this regard, the group firewall **230A** may be transmitted to the user device group **112** to implement the firewall **150A** and the firewall **150B** at the user device **110A** and the user device **110B**, respectively.

(48) An improvement provided by using tokens in the decentralized network **130** to obtain updated multiple security information **198** to be implemented at multiple user devices **110** in the user device group **112** is that multiple tokens in a group or organization (e.g., the user device group **112**) may be dynamically updated to include the entitlements **174** approved for multiple user devices **110** in the group or organization. In other embodiments, the process of retrieving configuration policies and rules **196** may be automated and may be dynamically implemented without the intervention of a network manager while protecting the identity of the users operating the user device **110A** and the user device **110B**. In this regard, the security operations may update the token to fetch updates to the configuration policies and rules **196** periodically or dynamically every time the server **102** detects a change to the one or more entitlements **174** for the user device **110A**.

Example Processes

(49) FIGS. **3** and **4** illustrate respective example flowcharts of a process **300** and a process **400** in accordance with one or more embodiments. Modifications, additions, or omissions may be made to the processes **300** and **400**. The processes **300** and **400** may comprise more, fewer, or other operations than those shown below. For example, operations may be performed in parallel or in any suitable order. While at times discussed as the server **102**, processor **156**, processing engine **158**,

the hardware accelerator **160**, the token controller **162**, the nodes **132-140** of the decentralized network **130**, or components of any of thereof performing operations described in the operations, any suitable system or components of the security system **100** may perform one or more operations of the processes **300** and **400**. For example, one or more operations of processes **300** and **400** may be implemented, at least in part, in the form of instructions **166** of FIG. **1**, stored on non-transitory, tangible, machine-readable media (e.g., the server memory **164** of FIG. **1**) that when run by one or more processors (e.g., the processor **156** of FIG. **1**) may cause the one or more processors to perform operations described in operations **302-322** or **402-422**.

Example Process to Update a Firewall Security Configuration in a Decentralized Network

(50) FIG. **3** illustrates an example flowchart of the process **300** to update firewall configurations **104** in the decentralized network **130**, in accordance with one or more embodiments.

(51) The process **300** starts at operation **302**, where the server **102** receives a device profile **192** from the user device **110A**. As described above, the server **102** may request the device profile **192** from the user device **110A** upon determining that the user device **110A** attempts to access a new entitlement **174A**. At operation **304**, the server **102** validates the device profile **192** against the user profile **172A**. The server **102** may confirm that the validation profile **192** is associated with the user profile **172A**. At operation **306**, the server **102** determines at least one entitlement **174A** associated with the user profile **172A**.

(52) At operation **310**, the server **102** may determine whether the user device **110A** is allowed to access the entitlement **174A**. If the server **102** determines that the user device **110A** is allowed to access the entitlement **174A** (e.g., YES), then the process **300** proceeds to operation **312**. If the server **102** determines that the user device **110A** is not allowed to access the entitlement **174A** (e.g., NO), then the process **300** proceeds to operation **320**.

(53) At operation **312**, the server **102** generates the initial token **202** indicating that the device profile **172A** is entitled to access the entitlement **174A**. At operation **314**, the server **102** transmit the initial token **202** to the decentralized network **130**. The decentralized network **130** may receive the initial token **202** at a first node **132** of the multiple nodes **132-140**. The first node **132** may be configured to provide a first update (i.e., represented by updating tokens **260-274**) corresponding to rules and policies **196** and updated in accordance with the updated security information **198**. At operation **316**, the server **102** receives the updated token **204** from the decentralized network **130**. At operation **318**, the server **102** identifies the firewall configuration **104A** in the updated token **204**.

(54) At operation **320**, the server **102** identifies the firewall configuration **104A** in security information **176** predefined for the user profile **172A**. In this regard, the server **102** may maintain the existing firewall configuration **104B** previously assigned to user device **110A**. In other embodiments, the server **102** may fetch the firewall configuration **104B** from the security information **176** to implement the firewall **150A** at the user device **110A**.

(55) The process **300** ends at operation **322**, where the server **102** transmits the firewall configuration **104A** to the user device **110A** to implement the firewall **150A** at the user device **110A**.

Example Process to Dynamically Aggregating Multiple Firewall Security Configurations in a Decentralized Network

(56) FIG. **4** illustrates an example flowchart of a process **400** to dynamically aggregate multiple firewall configurations **104** in the decentralized network **130**, in accordance with one or more embodiments.

(57) The process **400** starts at operation **402**, where the server **102** identifies a first updated token (e.g., user token **180A**) associated with the first user profile **172A** of the user device group **112**. At operation **404**, where the server **102** identifies a second updated token (e.g., user token **180B**) associated with the second user profile **172B** of the user device group **112**. At operation **406**, the server **102** determine one or more entitlements **174** associated with the first user profile **172A** and

the second user profile **172B**.

(58) At operation **410**, the server **102** may determine whether the entitlements **174** are different between the first user profile **172A** and the second user profile **172B**. If the server **102** determines that the entitlements **174** are different (e.g., a first entitlement **174A** and a second entitlement **174B**) between the first user profile **172A** and the second user profile **172B** (e.g., YES), then the process **400** proceeds to operation **412**. If the server **102** determines that the entitlements are the same (e.g., not different) (e.g., the first entitlement **174A**) between the first user profile **172A** and the second user profile **172B** (e.g., NO), then the process **400** proceeds to operation **420**.

(59) At operation **412**, the server **102** generates an initial token **202** indicating that the user devices **110** in the user device group **112** are entitled to access the one or more entitlements **174**. The decentralized network **130** may receive the initial token **202** at a first node **132** of the multiple nodes **132-140**. The first node **132** may be configured to provide a first update (i.e., represented by updating tokens **260-274**) corresponding to rules and policies **196** and updated in accordance with the updated security information **198**. At operation **414**, the server **102** transmits the initial token to the decentralized network **130**. At operation **416**, the server **102** receives an updated token **204** from the decentralized network **130**. At operation **418**, the server **102** identifies one or more firewall configurations **104A-104C** in the updated token **204**.

(60) At operation **420**, the server **102** identifies the firewall configuration **104C** for the first user profile **172A** corresponding to the user device **110A** and the second user profile **172B** corresponding to the user device **110B** in the user device group **112**. In this regard, the server **102** may maintain the existing firewall configuration **104C** previously assigned to the user device **110A** or the user device **110B** to be used in all user devices **110** in the user device group **112**.

(61) The process **400** ends at operation **422**, where the server **102** transmits the firewall configurations **104A-104C** to the user devices **110A** and **110B** in the user device group **112** to implement respective firewalls **150A** and **150B** at the user devices **110A** and **110B**.

SCOPE OF THE DISCLOSURE

(62) While several embodiments have been provided in the present disclosure, it should be understood that the disclosed systems and methods might be embodied in many other specific forms without departing from the spirit or scope of the present disclosure. The present examples are to be considered as illustrative and not restrictive, and the intention is not to be limited to the details given herein. For example, the various elements or components may be combined or integrated with another system or certain features may be omitted, or not implemented.

(63) In addition, techniques, systems, subsystems, and methods described and illustrated in the various embodiments as discrete or separate may be combined or integrated with other systems, modules, techniques, or methods without departing from the scope of the present disclosure. Other items shown or discussed as coupled or directly coupled or communicating with each other may be indirectly coupled or communicating through some interface, device, or intermediate component whether electrically, mechanically, or otherwise. Other examples of changes, substitutions, and alterations are ascertainable by one skilled in the art and could be made without departing from the spirit and scope disclosed herein.

(64) To aid the Patent Office, and any readers of any patent issued on this application in interpreting the claims appended hereto, applicants note that they do not intend any of the appended claims to invoke 35 U.S.C. § 112 (f) as it exists on the date of filing hereof unless the words “means for” or “step for” are explicitly used in the particular claim.

Claims

1. An apparatus, comprising: a memory, configured to store: one or more user profiles associated with one or more user groups, each user profile comprising one or more entitlements; and security information comprising one or more firewall configurations, each firewall configuration being

configured to enable each user profile to access the one or more entitlements; a processor communicatively coupled to the memory and configured to: receive a first device profile from a first user device; validate the first device profile against a first user profile of the one or more user profiles; determine a first entitlement of the one or more entitlements associated with the first user profile; generate a first initial token indicating that the first device profile is entitled to access the first entitlement; transmit the first initial token to a decentralized network; receive a first updated token from the decentralized network, wherein: the first updated token indicates a first firewall configuration based at least in part upon the first initial token; and the first firewall configuration is configured to enable the first user device to access the first entitlement; and transmit the first firewall configuration to the first user device to implement a first firewall at the first user device.

2. The apparatus of claim 1, wherein the processor is further configured to: receive a second device profile from a second user device; validate the second device profile against a second user profile of the one or more user profiles; determine a second entitlement of the one or more entitlements associated with the second user profile; generate a second initial token indicating that the second device profile is entitled to access the second entitlement; transmit the second initial token to the decentralized network; receive a second updated token from the decentralized network, wherein: the second updated token indicates a second firewall configuration based at least in part upon the second initial token; and the second firewall configuration is configured to enable the second user device to access the second entitlement; and transmit the second firewall configuration to the second user device to implement a second firewall at the second user device.

3. The apparatus of claim 1, wherein the processor is further configured to: in determining the first entitlement of the one or more entitlements associated with the first user profile, determine whether the first user profile is associated with a first user group of the one or more user groups or a second user group of the one or more user groups, wherein: the first user group is associated with a first plurality of rules and policies in the decentralized network; and the second user group is associated with a second plurality of rules and policies in the decentralized network; in response to determining that the first user profile is associated with the first user group, generate the first initial token indicating that the first device profile is entitled to access the first entitlement in accordance the first plurality of rules and policies; in response to determining that the first user profile is associated with the second user group, generate the first initial token indicating that the first device profile is entitled to access the first entitlement in accordance with the second plurality of rules and policies; and transmit the first initial token to the first node in the decentralized network.

4. The apparatus of claim 1, wherein the processor is further configured to: in conjunction with receiving the first device profile from the first user device, receive a first request for the first firewall configuration from the first user device.

5. The apparatus of claim 1, wherein the processor is further configured to: in conjunction with receiving the first device profile from the first user device, monitor first communication information associated with the first user device; determine whether the communication information comprises a first attempt at accessing the first entitlement; and in response to determining that the communication information comprises the first attempt, indicate to the first user device to transmit the first device profile to the apparatus.

6. The apparatus of claim 5, wherein the processor is further configured to: dynamically monitor second communication information associated with the first user device; determine whether the communication information comprises a second attempt at accessing a second entitlement; in response to determining that the communication information comprises the second attempt, generate a second initial token indicating that the first device profile is entitled to access the first entitlement and the second entitlement; transmit the second initial token to the decentralized network; receive a second updated token from the decentralized network, wherein: the second updated token indicates a second firewall configuration based at least in part upon the second initial token; and the second firewall configuration is configured to enable the first user device to access

the first entitlement and the second entitlement; and transmit the second firewall configuration to the first user device to implement a second firewall at the first user device.

7. The apparatus of claim 5, wherein the processor is further configured to: periodically monitor second communication information associated with the first user device; determine whether the communication information comprises a second attempt at accessing a second entitlement; in response to determining that the communication information comprises the second attempt, generate a second initial token indicating that the first device profile is entitled to access the first entitlement and the second entitlement; transmit the second initial token to the decentralized network; receive a second updated token from the decentralized network, wherein: the first updated token indicates a second firewall configuration based at least in part upon the second initial token; and the second firewall configuration is configured to enable the first user device to access the first entitlement and the second entitlement; and transmit the second firewall configuration to the first user device to implement a second firewall at the first user device.

8. A system, comprising: a decentralized network comprising: a first node configured to: receive a first initial token comprising a first initial encrypted firewall configuration and a second initial token comprising a second initial encrypted firewall configuration; and provide a first updated token comprising a first updated encrypted firewall configuration based at least in part upon the first initial token in accordance with a first security information; and a second node configured to: receive the second initial token from the first node; and provide a second updated token comprising a second updated encrypted firewall configuration based at least in part upon the second initial token in accordance with a second security information; and a server communicatively coupled to the decentralized network and configured to: receive a first device profile from a first user device; validate the first device profile against a first user profile of one or more user profiles, the first user profile being associated with a first user group and comprising a first entitlement; determine the first entitlement associated with the first user profile; generate the first initial token indicating that the first device profile is entitled to access the first entitlement; transmit the first initial token to the decentralized network; receive the first updated token from the decentralized network, wherein: the first updated token indicates a first firewall configuration based at least in part upon the first initial token; and the first firewall configuration is configured to enable the first user device to access the first entitlement; and transmit the first firewall configuration to the first user device to implement a first firewall at the first user device.

9. The system of claim 8, wherein the server is further configured to: receive a second device profile from a second user device; validate the second device profile against a second user profile of the one or more user profiles, the second user profile being associated with a second user group and comprising a second entitlement; determine the second entitlement associated with the second user profile; generate the second initial token indicating that the second device profile is entitled to access the second entitlement; transmit the second initial token to the decentralized network; receive the second updated token from the decentralized network, wherein: the second updated token indicates a second firewall configuration based at least in part upon the second initial token; and the second firewall configuration is configured to enable the second user device to access the second entitlement; and transmit the second firewall configuration to the second user device to implement a second firewall at the second user device.

10. The system of claim 9, wherein the server is further configured to: in determining the first entitlement associated with the first user profile, determine whether the first user profile is associated with the first user group or the second user group, wherein: the first user group is associated with a first plurality of rules and policies in the decentralized network; and the second user group is associated with a second plurality of rules and policies in the decentralized network; in response to determining that the first user profile is associated with the first user group, generate the first initial token indicating that the first device profile is entitled to access the first entitlement in accordance the first plurality of rules and policies; in determining the second entitlement

associated with the second user profile, determine whether the second user profile is associated with the first user group or the second user group; in response to determining that the second user profile is associated with the second user group, generate the second initial token indicating that the second device profile is entitled to access the second entitlement in accordance with the second plurality of rules and policies; and transmit the first initial token and the second initial token to the first node in the decentralized network.

11. The system of claim 8, wherein the server is further configured to: in conjunction with receiving the first device profile from the first user device, receive a first request for the first firewall configuration from the first user device.

12. The system of claim 8, wherein the server is further configured to: in conjunction with receiving the first device profile from the first user device, monitor first communication information associated with the first user device; determine whether the communication information comprises a first attempt at accessing the first entitlement; and in response to determining that the communication information comprises the first attempt, indicate to the first user device to transmit the first device profile to the apparatus.

13. The system of claim 12, wherein the server is further configured to: dynamically monitor second communication information associated with the first user device; determine whether the communication information comprises a second attempt at accessing a second entitlement; in response to determining that the communication information comprises the second attempt, generate a third initial token indicating that the first device profile is entitled to access the first entitlement and the second entitlement; transmit the third initial token to the decentralized network; receive a third updated token from the decentralized network, wherein: the third updated token indicates a third firewall configuration based at least in part upon the third initial token; and the third firewall configuration is configured to enable the first user device to access the first entitlement and the second entitlement; and transmit the third firewall configuration to the first user device to implement a third firewall at the first user device.

14. The system of claim 12, wherein the server is further configured to: periodically monitor second communication information associated with the first user device; determine whether the communication information comprises a second attempt at accessing a second entitlement; in response to determining that the communication information comprises the second attempt, generate a third initial token indicating that the first device profile is entitled to access the first entitlement and the second entitlement; transmit the third initial token to the decentralized network; receive a third updated token from the decentralized network, wherein: the third updated token indicates a third firewall configuration based at least in part upon the third initial token; and the third firewall configuration is configured to enable the first user device to access the first entitlement and the second entitlement; and transmit the third firewall configuration to the first user device to implement a third firewall at the first user device.

15. A method, comprising: receiving a first device profile from a first user device; validating the first device profile against a first user profile of one or more user profiles, the first user profile being associated with a first user group and comprising a first entitlement; determining the first entitlement associated with the first user profile; generating a first initial token indicating that the first device profile is entitled to access the first entitlement; transmitting the first initial token to a decentralized network; receiving the first updated token from the decentralized network, wherein: the first updated token indicates a first firewall configuration based at least in part upon the first initial token; and the first firewall configuration is configured to enable the first user device to access the first entitlement; and transmitting the first firewall configuration to the first user device to implement a first firewall at the first user device.

16. The method of claim 15, further comprising: receiving a second device profile from a second user device; validating the second device profile against a second user profile of the one or more user profiles, the second user profile being associated with a second user group and comprising a

second entitlement; determining a second entitlement associated with the second user profile; generating a second initial token indicating that the second device profile is entitled to access the second entitlement; transmitting the second initial token to the decentralized network; receiving the second updated token from the decentralized network, wherein: the second updated token indicates a second firewall configuration based at least in part upon the second initial token; and the second firewall configuration is configured to enable the second user device to access the second entitlement; and transmitting the second firewall configuration to the second user device to implement a second firewall at the second user device.

17. The method of claim 16, further comprising: in determining the first entitlement associated with the first user profile, determining whether the first user profile is associated with the first user group or the second user group, wherein: the first user group is associated with a first plurality of rules and policies in the decentralized network; and the second user group is associated with a second plurality of rules and policies in the decentralized network; in response to determining that the first user profile is associated with the first user group, generating the first initial token indicating that the first device profile is entitled to access the first entitlement in accordance the first plurality of rules and policies; in determining the second entitlement associated with the second user profile, determining whether the second user profile is associated with the first user group or the second user group; in response to determining that the second user profile is associated with the second user group, generating the second initial token indicating that the second device profile is entitled to access the second entitlement in accordance with the second plurality of rules and policies; and transmitting the first initial token and the second initial token to the first node in the decentralized network.

18. The method of claim 15, further comprising: in conjunction with receiving the first device profile from the first user device, receiving a first request for the first firewall configuration from the first user device.

19. The method of claim 15, further comprising: in conjunction with receiving the first device profile from the first user device, monitoring first communication information associated with the first user device; determining whether the communication information comprises a first attempt at accessing the first entitlement; and in response to determining that the communication information comprises the first attempt, indicating to the first user device to transmit the first device profile to the apparatus.

20. The method of claim 19, further comprising: dynamically monitoring second communication information associated with the first user device; determining whether the communication information comprises a second attempt at accessing a second entitlement; in response to determining that the communication information comprises the second attempt, generating a third initial token indicating that the first device profile is entitled to access the first entitlement and the second entitlement; transmitting the third initial token to the decentralized network; receiving a third updated token from the decentralized network, wherein: the third updated token indicates a third firewall configuration based at least in part upon the third initial token; and the third firewall configuration is configured to enable the first user device to access the first entitlement and the second entitlement; and transmitting the third firewall configuration to the first user device to implement a third firewall at the first user device.
