

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12397906
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Fernandez; Maxime et al.

Device for driving at least one wheel of an aircraft landing gear

Abstract

A device for driving at least one wheel of an aircraft landing gear is provided. The device includes at least one wheel having a rim, an electric motor having a shaft, and a mechanical transmission system for mechanical transmission between the shaft of the motor and the rim. The mechanical transmission system includes a mechanical reduction gear. The mechanical reduction gear includes a sun gear secured in rotation to the shaft and having an external tothing, a stationary ring gear with internal tothing, a movable ring gear secured in rotation to the rim and having an internal tothing, and planet gears that are meshed with the sun gear and each have two external tothing meshed respectively with the tothing of the stationary and movable ring gears.

Inventors: Fernandez; Maxime (Moissy-Cramayel, FR), Douy; Yohan (Moissy-Cramayel, FR), Francois; Loïc (Moissy-Cramayel, FR), Morelli; Boris Pierre Marcel (Moissy-Cramayel, FR), Peltier; Jordane Emile André (Moissy-Cramayel, FR)

Applicant: SAFRAN TRANSMISSION SYSTEMS (Colombes, FR)

Family ID: 1000008779860

Assignee: SAFRAN TRANSMISSION SYSTEMS (Colombes, FR)

Appl. No.: 18/467019

Filed: September 14, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240092480 A1	Mar. 21, 2024

Foreign Application Priority Data

FR	FR2209343	Sep. 16, 2022
----	-----------	---------------

Publication Classification

Int. Cl.: B64C25/32 (20060101); F16H1/28 (20060101); F16H57/08 (20060101)

U.S. Cl.:

CPC B64C25/405 (20130101); F16H1/28 (20130101); F16H2001/2881 (20130101); F16H2057/085 (20130101)

Field of Classification Search

CPC: B64C (25/405); F16H (1/28); F16H (2001/2881); F16H (2001/2872); B60K (7/0007); B60K (17/046)

USPC: 475/342

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2401875	12/1945	Lawler	475/342	F16H 1/46
3421596	12/1968	Livezey	180/65.245	F16H 47/08
3686978	12/1971	Knoblach	475/296	F16H 3/001
3711043	12/1972	Cameron-Johnson	244/50	B64C 25/405
4280376	12/1980	Rosen	74/462	F16H 55/08
5957804	12/1998	Schulz	475/342	F16H 1/46
8342612	12/2012	Sgherri	301/6.5	B60K 17/046
8714481	12/2013	Sweet	244/100R	B64C 25/405
9650131	12/2016	Jaber	N/A	B60B 25/004
11235661	12/2021	Bonny	N/A	F16H 57/082
2003/0139250	12/2002	Bowman	475/342	B60K 17/046
2014/0041619	12/2013	Yamauchi	123/196R	F16H 57/0486
2018/0170527	12/2017	Roques et al.	N/A	N/A
2019/0291575	12/2018	Rotenberg	N/A	N/A
2022/0145769	12/2021	Mouly et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
3116095	12/2009	FR	N/A
2016202909	12/2015	WO	N/A

OTHER PUBLICATIONS

French Search Report mailed Apr. 18, 2023 issued in corresponding French Application No. FR2209343, filed Sep. 16, 2022, 2 pages total. cited by applicant

Primary Examiner: Estremsky; Sherry L

Background/Summary

CROSS-REFERENCE(S) TO RELATED APPLICATION(S)

(1) This application claims priority to FR2209343, filed Sep. 16, 2022, the disclosure of which is hereby expressly incorporated by reference herein in its entirety.

TECHNICAL FIELD

(2) The present disclosure relates to a device for driving at least one wheel of an aircraft landing gear.

BACKGROUND

(3) The technical background includes the documents US-A1-2019/291575, WO-A1-2016/202909 and FR-A1-3 116 095.

(4) An aircraft has landing gear equipped with wheels for moving the aircraft on the ground over a tarmac. This taxiing can be achieved by propelling the aircraft using its turbomachines.

(5) To limit the fuel consumption and the environmental impact, it is known to carry out this taxiing electrically. The electric taxiing is achieved by driving the wheels of a landing gear by an electric motor.

(6) The present application proposes an improvement on existing technologies and thus relates to an electric motor device for driving at least one wheel of an aircraft landing gear.

(7) A solution consisting of using a reduction gear to transmit the power of an electric motor to a wheel of a landing gear was proposed by the Applicant in the document EP-A1-3 882 136.

(8) The role of a mechanical reduction gear is to modify the speed and torque ratio between the input axle and the output axle of a mechanical system.

(9) In the remote field of the aircraft turbomachines, a mechanical reduction gear is used to transmit power between two rotating mechanical shafts.

(10) There are many different types of reduction gears, for example differential, planetary, epicyclic, with intermediate lines, with reduction stages in series, etc.

(11) In the prior art of the dual-flow turbomachines, the reduction gears are of the planetary or epicyclic type. Such a reduction gear comprises a central pinion, referred to as sun gear, a ring gear and pinions referred to as planet gears, which are engaged between the sun gear and the ring gear. The planet gears are maintained by a frame referred to as planet carrier. The sun gear, the ring gear and the planet carrier are planetary because their axes of revolution coincide with the longitudinal axis of the turbomachine. The planet gears each have a different axis of revolution equally distributed on the same operating diameter around the axis of the planetaries. These axes are parallel to the longitudinal axis of the turbomachine.

(12) There are several reduction gear architectures. In other similar applications, there are architectures referred to as differential or “compound.”

(13) In a planetary reduction gear, the planet carrier is stationary and the ring gear is the output shaft of the device which rotates in the opposite orientation of the sun gear.

(14) In an epicyclic reduction gear, the ring gear is stationary and the planet carrier is the output shaft of the device which rotates in the same orientation as the sun gear.

(15) On a compound reduction gear, no element is attached in rotation. The ring gear rotates in the opposite orientation of the sun gear and the planet carrier.

(16) The reduction gears can consist of one or more meshing stages. This meshing is ensured in different ways such as by contact, friction or magnetic field.

(17) In the present application, “stage” or “tooththing” means at least one series of meshing teeth with at least one series of complementary teeth. A tooththing can be internal or external.

(18) A planet gear may comprise one or two meshing stages. A single-stage planet gear comprises a toothing that can be straight, helical or herringbone, and teeth of which are located on a same diameter. This toothing cooperates with both the sun gear and the ring gear.

(19) A double-stage planet gear comprises two toothings that are located on different diameters. A first toothing cooperates with the sun gear and a second toothing generally cooperates with the ring gear.

(20) A reduction gear with a meshing double stage has the advantage of having a higher reduction ratio than a reduction gear with a single meshing stage of the same overall dimensions.

(21) In the context of a device for driving at least one wheel of a landing gear, the use of an electric motor and a reduction gear to drive the wheel generates considerable overall dimensions constraints. The outer diameter of the reduction gear is limited by the size of the rim of the wheel, and the inner diameter of the reduction gear is strongly constrained by the diameter of the hub of the wheel. In addition, the use of an electric motor generally rotating at high speeds requires the use of a reduction gear with a high reduction ratio in order to offer an output speed that corresponds to the low speed of rotation of the wheel. The current epicyclic and planetary gear trains do not offer these levels of reduction in such a small space.

(22) The disclosure proposes a solution to at least part of these problems, which is simple, effective, and economical.

SUMMARY

(23) This summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This summary is not intended to identify key features of the claimed subject matter, nor is it intended to be used as an aid in determining the scope of the claimed subject matter.

(24) Embodiments of the present disclosure relate to a device for driving at least one wheel of an aircraft landing gear. In some embodiments, the device includes: at least one landing gear wheel, this wheel comprising a rim having an axis of rotation, an electric motor comprising a shaft, a mechanical transmission system between the shaft of the motor and the rim, this mechanical transmission system comprising a mechanical reduction gear, wherein the mechanical reduction gear comprises: a sun gear secured in rotation to the shaft of the motor, this sun gear being centered on the axis and comprising an external toothing, a stationary ring gear centered on the axis and that comprises an internal toothing, this stationary ring gear being configured to be secured to a stator of the device, a movable ring gear centered on the axle and that comprises an internal toothing, this movable ring gear being secured in rotation with the rim, and planet gears that are meshed with the sun gear, the planet gears being carried by a planet carrier mobile in rotation around the axis, each of the planet gears comprising two external toothings meshed respectively with the toothings of the stationary and movable ring gears.

(25) Embodiments of the present disclosure include a driving device for at least one wheel of an aircraft landing gear, which is equipped with a reduction gear with two independent ring gears and different functions. One of the ring gears is stationary and the other of the ring gears is mobile in rotation. It is therefore understood that the movable ring gear forms an output (torque) of the reduction gear, the input of the reduction gear being formed by the sun gear. The planet carrier is also mobile in rotation. It can rotate freely and is therefore independent of any rotor of the electric motor.

(26) Embodiments of the present disclosure are compatible with a multi-stage reduction gear as described above. They are also compatible with a reduction gear in which the planet carrier is mobile in rotation, such as the epicyclic or differential reduction gear. They are also compatible with any type of toothings (straight, helical, herringbone, etc.). Some embodiments are further compatible with a planet carrier of the monobloc type or of the cage and cage carrier type. These different types of reduction gear are well known to a person skilled in the relevant art. The solution proposed below is compatible with any type of planet gear bearing, whether it consists of rolling

elements, a hydrodynamic bearing, etc.

(27) The device according to the present disclosure may include one or more of the following characteristics, taken alone or in combination with each other: each of the planet gears is meshed by a first toothing with the toothing of the sun gear and the toothing of the stationary ring gear, and by a second toothing with the toothing of the movable ring gear; each of the planet gears is meshed by a first toothing with the toothing of the sun gear and the toothing of the movable ring gear, and by a second toothing with the toothing of the stationary ring gear; the planet gears are each centered and guided by two roller bearings carried by the planet carrier, the toothing of each of the planet gears being located between these roller bearings; the planet gears are each centered and guided by two needle bearings carried by the planet carrier, each of the needle bearings being radially aligned with one of the toothing of the planet gear; the sun gear is coupled to a shaft or secured to a shaft, the planet gears are arranged around at least part of this shaft or of the shaft of the motor; the toothing of the stationary and movable ring gears have the same diameter; the toothing of the stationary and movable ring gears have different numbers of teeth; all the toothings are selected from straight, helical or herringbone toothing; the motor has an annular shape centered on the axis and is arranged next to the reduction gear; the motor is arranged adjacent to and radially opposite the axis of rotation at the level of the planet gears; the toothing of each of the planet gears have different diameters, the smallest diameter toothing of each of the planet gears meshing with the toothing of the movable ring gear, and the smallest diameter toothing of each of the planet gears meshing with the toothing of the stationary ring gear; the electric motor is arranged on the side of the stationary ring gear and on the opposite side to the movable ring gear; and the planet carrier is arranged on the electric motor side.

Description

DESCRIPTION OF THE DRAWINGS

- (1) The foregoing aspects and many of the attendant advantages of the claimed subject matter will become more readily appreciated as the same become better understood by reference to the following detailed description, when taken in conjunction with the accompanying drawings, wherein:
- (2) FIG. 1 is a schematic perspective view of a wheel of an aircraft landing gear and a device for driving this wheel in accordance with embodiments of the present disclosure;
- (3) FIG. 2 is a partial axial sectional view of a mechanical reduction gear in accordance with embodiments of the present disclosure;
- (4) FIG. 3 is another partial axial sectional view of a mechanical reduction gear in accordance with embodiments of the present disclosure;
- (5) FIG. 4 is a schematic axial section and perspective view of a reduction gear with a double symmetrical meshing stage in accordance with embodiments of the present disclosure;
- (6) FIG. 5 is another schematic axial section view of the reduction gear of FIG. 4;
- (7) FIG. 6 is a schematic partial view in axial section of a reduction gear for a device in accordance with embodiments of the present disclosure;
- (8) FIG. 7 is a schematic partial view in axial section of a reduction gear for a device in accordance with other embodiments of the present disclosure;
- (9) FIG. 8 is a schematic partial view in axial section of a reduction gear for a device in accordance with further embodiments of the present disclosure;
- (10) FIG. 9 is a partial schematic view of a reduction gear in axial section according to the embodiment in FIG. 8;
- (11) FIG. 10 is a partial schematic perspective view of a reduction gear according to the embodiment in FIG. 8;

- (12) FIG. **11** is a partial schematic view of the reduction gear in axial section according to the embodiment in FIG. **8**;
- (13) FIG. **12** is a partial schematic perspective view of an alternative embodiment of the reduction gear;
- (14) FIG. **13** is a schematic axial sectional view of a planet gear and guide bearings for guiding this planet gear in accordance with embodiments of the present disclosure; and
- (15) FIG. **14** is a schematic axial sectional view of a planet gear and guide bearings for guiding this planet gear in accordance with embodiments of the present disclosure.

DETAILED DESCRIPTION

- (16) The detailed description set forth above in connection with the appended drawings, where like numerals reference like elements, are intended as a description of various embodiments of the present disclosure and are not intended to represent the only embodiments. Each embodiment described in this disclosure is provided merely as an example or illustration and should not be construed as preferred or advantageous over other embodiments. The illustrative examples provided herein are not intended to be exhaustive or to limit the disclosure to the precise forms disclosed.
- (17) FIG. **1** shows a device **10** for driving at least one wheel **12** of an aircraft landing gear **14**.
- (18) The wheel **12** comprises a rim **16** with an axis of rotation X. Conventionally, this rim **16** is generally tubular or disc-shaped and carries a tyre **18** on its periphery.
- (19) The device **10** comprises an electric motor **20** and a mechanical transmission system **22** for a mechanical transmission between a shaft of the motor **20** and the rim **16** of the wheel **12**.
- (20) In the illustrated embodiment, the motor **20** and the system **22** each have a generally annular shape and are centered on the axis X. They are arranged next to each other and the system **22** is installed between the motor **20** and the rim **16**. A part of the system **22**, or even part of the motor **20**, could be housed in the rim **16** to optimize the overall dimensions of the device **10**. The motor **20** and the system **22** can be protected by an outer cylindrical cover **26** projecting from one side of the rim **16** or of the tire **18**.
- (21) The mechanical transmission system **22** comprises a mechanical reduction gear **28**, with examples of these embodiments shown in FIGS. **2-5**.
- (22) FIG. **2** shows an epicyclic reduction gear **28**. At the input, the reduction gear **28** is connected to a shaft **30**, for example by means of internal splines **32a**. The shaft **30** drives a planetary pinion referred to as the sun gear **32**. In some embodiments, the sun gear **32** drives a series of pinions referred to as planet gears **34**, which are equally spaced on the same diameter around the axis X of rotation of the sun gear **32**. This diameter is equal to twice the operating center distance between the sun gear **32** and the planet gears **34**. The number of planet gears **34** is generally defined as between three and seven.
- (23) The assembly of the planet gears **34** is held by a frame referred to as planet carrier **36**. Each planet gear **34** rotates about its own axis Y and meshes with a ring gear **38**.
- (24) In the output we have: (1) In this epicyclic configuration, the assembly of the planet gears **34** drive in rotation the planet carrier **36** about the axis X. The ring gear **38** is attached to a stator via a ring gear carrier **40** and the planet carrier **36** is attached to another shaft **42**. (2) In another planetary configuration, the assembly of the planet gears **34** is held by a planet carrier **36** which is attached to a stator. Each planet gear drives the ring gear **38** which is connected to the shaft **42** via a ring gear carrier **40**. (3) In another differential configuration, the assembly of the planet gears **34** is held by a planet carrier **36** which is connected to the shaft **30**. Each planet gear **34** drives the ring gear **38** which is fitted to the shaft **42** via a ring gear carrier **40**.
- (25) Each planet gear **34** is mounted free in rotation by means of a bearing **44**, for example of the rolling or hydrodynamic bearing type. Each bearing **44** is mounted on one of the axles **36b** of the planet carrier **36** and all the axles **36b** are positioned relative to each other using one or more structural frames **36a** of the planet carrier **36**. The number of axles **36b** and bearings **44** is equal to

the number of planet gears **34**. For reasons of operation, assembly, manufacture, inspection, repair or replacement, the axles **36b** and the frame **36a** may be separated into several parts.

(26) For the same reasons mentioned above, the toothing **34a** of a planet gear **34** can be separated into several helices or teeth each having a median plane P, P'. In the example shown, each planet gear **34** comprises two series of herringbone teeth cooperating with a ring gear **38** separated into two half-ring gears: (1) An upstream annulus **38a** consisting of a rim **38aa** and an attachment half-flange **38ab**. On the rim **38aa** is the front helix meshed with a helix of the toothing **34a** of each planet gear **34**. The helix of the toothing **34a** also meshes with that of the sun gear **32**. (2) A downstream annulus **38b** consisting of a rim **38ba** and an attachment half-flange **38bb**. The rear helix is located on the rim **38ba** and is meshed with a helix of the toothing **34a** of each planet gear **34**. The helix of the toothing **34a** also meshes with that of the sun gear **32**.

(27) If the helix widths vary between the sun gear **32**, the planet gears **34** and the ring gear **38** because of the toothing overlaps, they are all centered on a median plane P for the upstream teeth and on another median plane P' for the downstream teeth.

(28) FIG. 2 illustrates the case of a reduction gear with a single meshing stage, i.e., the same toothing **34a** of each planet gear **34** cooperates with both the sun gear **32** and the ring gear **38**. Although the toothing **34a** comprises two sets of teeth, these teeth have the same average diameter and form a single toothing referred to as herringbone.

(29) The attachment half-flange **38ab** of the upstream annulus **38a** and the attachment half-flange **38bb** of the downstream annulus **38b** form the attachment flange **38c** of the ring gear. The ring gear **38** is attached to the ring gear carrier **40** by assembling the attachment flange **38c** of the ring gear **38** and an attachment flange **40a** of the ring gear carrier **40** using a bolted assembly, for example.

(30) FIG. 3 shows another example of reduction gear architecture, referred to as a double meshing stage, in which each planet gear **34** comprises two separate toothings **34a1**, **34a2** configured to cooperate respectively with the ring gear **38** and the sun gear **32**.

(31) In this FIG. 3, the elements already described in the foregoing are designated by the same references.

(32) The toothing **34a1** meshing with the ring gear **38** has an average diameter D2 and is located in a median plane P. The toothing **34a2** meshing with the sun gear **32** has an average diameter D1 and is located in another median plane P'. The median planes P, P' are parallel to each other and perpendicular to the axis X. The diameter D2 is smaller than the diameter D1. Finally, each toothing **34a1**, **34a2** comprises a single helix.

(33) FIGS. 4 and 5 show a reduction gear **28** with symmetrical double toothing, comprising: a sun gear **32** having an axis of rotation X; a ring gear **38** which extends around the sun gear **32** and which is configured so that it cannot rotate about the axis X; and planet gears **34** which are meshed with the sun gear **32** and the ring gear **38** and which are maintained by a planet carrier **36** which is configured to be mobile in rotation about the axis X.

(34) The plane H is defined as a median plane perpendicular to the axis X and passing substantially through the middle of the reduction gear **28** (see FIG. 5).

(35) The sun gear **32** comprises internal splines **32b** for coupling with the shaft **30** and external toothing **32a** for meshing with the planet gears **34**. The toothing **32a** has two series of adjacent chevron-shaped teeth, separated from each other by an annular groove **46** oriented outwards. The toothing **32a** is symmetrical with respect to the plane H, its teeth being located on either side of the plane H which passes through the groove **46**.

(36) The ring gear **38** is formed by two independent annulus **38a**, **38b** and comprises a toothing separated into two series of chevron-shaped teeth **38d1**, **38d2** carried respectively by the two annuluses.

(37) The annulus **38a**, **38b** are arranged symmetrically with respect to the plane H, which therefore extends between these annuluses. The annuluses **38a**, **38b** are connected and secured to a ring gear carrier **40** by means of annular connecting flasks **48**. The flasks **48** are independent of each other,

each flask having a general S-shape in axial half-section providing it with a certain radial flexibility by elastic deformation during operation.

(38) Each annulus **38a**, **38b** extends around the axis X and is secured to the corresponding flask **48** by its external periphery. Its inner periphery comprises one of the teeth **38d1**, **38d2**.

(39) The ring gear carrier **40** has a generally annular shape about the axis X and more particularly is biconical. It thus comprises a first upstream or left-hand segment in the drawing, with an upstream end of smaller diameter, and a downstream end of larger diameter which is connected to the upstream end of larger diameter of the other, downstream or right-hand segment in the drawing. The larger diameter ends of the segments are therefore connected together, and their smaller diameter ends form the axial ends of the ring gear carrier **40**.

(40) The upstream end of the ring gear carrier **40** extends around the planet carrier **36** or a shaft **42** connected to this planet carrier, and is centered and guided in rotation on the planet carrier or shaft via at least one bearing **50**. Similarly, the downstream end of the ring gear carrier **40** extends around the planet carrier **36** or a shaft connected to this planet carrier, and is centered and guided in rotation on the planet carrier or the shaft by means of at least one further bearing **52**.

(41) As with the ring gear **38**, the ring gear carrier **40** is symmetrical with respect to the plane H which cuts the ring gear carrier **40** in the middle and therefore passes through the ends of the aforementioned segments with the largest diameter.

(42) Each planet gear **34** comprises a first toothing **34a** of mean diameter D1 for meshing with the sun gear **32**, and a second toothing **54aa** of mean diameter D2, different from D1 and in particular smaller than D1, for meshing with the ring gear **38**. The average diameters are measured from the axis Y of each planet gear **34** and represent the average between the maximum diameter and the minimum diameter of a toothing of this planet gear.

(43) Each planet gear **34** comprises a cylindrical sleeve **58** and an annular web **60** extending substantially radially outwards from the middle of this sleeve **58**. The toothing **54aa** is separated into two series of chevron-shaped teeth **54a1**, **54a2** which are located respectively on the axial ends of the sleeve **58**. The toothing **34aa** comprise two series of chevron-shaped teeth **34a1**, **34a2** which are located at the external periphery of the web **60** and which are separated from each other by an annular groove **55** opening radially outwards with respect to the axis Y.

(44) The toothing **34aa** is crossed at its center by the plane H which passes through the groove **55**, the teeth **34a1**, **34a2** therefore being arranged on either side of the plane H. The teeth **54a1**, **54a2** are also arranged symmetrically with respect to the plane H.

(45) The toothing **34aa** and the external periphery of the web **60** have an axial dimension which is smaller than the axial distance between the annulus **38a**, **38b** and between the flasks **48**, so that each planet gear **34** can rotate freely in the ring gear carrier **40** and between the annulus **38a**, **38b** and the flasks **48**.

(46) Each of the planet gears **34** is guided in rotation by a hydrodynamic bearing **44** which comprises a cylindrical body **44a** which passes through the planet gear **34**, and in particular its sleeve **58**, and which is configured to form a film of guiding oil inside the planet gear.

(47) The body **44a** of a bearing **44** extends along the axis Y and comprises at its longitudinal ends extensions **44b** housed in orifices forming seats in the planet carrier **36**.

(48) The body **44a** is generally tubular and comprises an internal bore of oil circulation which generally communicates with oil supply conduits to an external cylindrical surface of the body for the formation of the oil film between this surface and an internal cylindrical surface of the planet gear **34**.

(49) Embodiments of the present disclosure can increase the reduction ratio of a mechanical reduction gear in the context of a device **10** for driving at least one wheel of an aircraft landing gear, as illustrated in FIG. 1.

(50) The reduction gear **28** of the device **10** according to embodiments of the present disclosure comprises all the characteristics described above in relation to FIGS. 3, 4, and 5 insofar as they are

not contrary to or do not contradict what follows.

(51) The references used in FIG. 6 and following and already used in FIGS. 3, 4, and 5 therefore designate identical or similar elements.

(52) FIGS. 6 to 8 illustrate embodiments of a reduction gear 28 according to the present disclosure, which comprises: a sun gear 32 which is mobile in rotation about the axis X and comprises an external toothing 32a; a stationary ring gear 38 which extends around the axis X and which comprises an internal toothing 38d, this stationary ring gear being con to be secured to a stator of the device 10; a movable ring gear 56 which extends around the axis X and which comprises an internal toothing 56a, this movable ring gear 56 being independent of the stationary ring gear 38; and planet gears 34 which are meshed with the sun gear 32 and the ring gears 38 and 56, the planet gears being carried by a planet carrier (not shown) which is mobile in rotation about the axis X.

(53) In the context of the present disclosure, the sun gear 32 is coupled to the shaft 30 of the electric motor 20. The movable ring gear 56 is coupled to the shaft 42 of the rim or to the rim 16 directly.

(54) Each of the planet gears 34 is meshed with the sun gear 32 and the ring gears 38, 56 and comprises a first external toothing 34a with an average diameter D1, and a second external toothing 54a with an average diameter D2, different from D1. In the example shown, D1 is greater than D2. Alternatively, the toothings 34a and 54a could have equal diameters D1 and D2 and different numbers of teeth, so as to have different modules.

(55) The reference 44a refers to the cylindrical body 44a of the hydrodynamic guide bearing for each planet gear 34, as described above.

(56) In the embodiment shown in FIG. 6, the toothing 54a of diameter D2 of each planet gear 34 is meshed with the toothing 32a of the sun gear 32 and the toothing 56a of the movable ring gear 56. The toothings 32a, 54a and 56a are thus in the same plane P1 perpendicular to the axis X. The toothing 34a of diameter D1 of each planet gear 34 is meshed with the toothing 38d of the stationary ring gear 38.

(57) In the embodiment shown in FIG. 7, the toothing 34a of diameter D1 of each planet gear 34 are meshed with the toothing 56a of the movable ring gear 56. The toothing 54a of diameter D2 of each planet gear 34 is meshed with the toothing 32a of the sun gear 32 and the toothing 38d of the stationary ring gear 38. The toothings 32a, 54a and 38d are thus in the same plane P1 perpendicular to the axis X.

(58) In the embodiment shown in FIG. 8, the toothing 34a of diameter D1 of each planet gear 34 are meshed with the toothing 56a of the movable ring gear 56 and with the toothing 32a of the sun gear 32. The toothings 32a, 34a and 56a are thus in the same plane P1 perpendicular to the axis X. The toothing 54a of diameter D2 of each planet gear 34 is meshed with the toothing 38d of the stationary ring gear 38.

(59) In the embodiments of FIGS. 6 and 8 where the sun gear 32 and the movable ring gear 56 mesh with the same toothing of the planet gears 34, the (torque) output of the reduction gear can be said to be aligned with its input. In the configuration shown in FIG. 7, where the sun gear 32 and the movable ring gear 56 mesh with different toothings of the planet gears 34, the (torque) output of the reduction gear can be said to be opposite to its input.

(60) In some embodiments, the number of teeth on the movable ring gear 56 is different from the number of teeth on the stationary ring gear 38, so that the two ring gears have different diameters. Alternatively, the diameters can be equal, provided that the two ring gears have different moduli. The direction of rotation of the movable ring gear 56 may depend on the relative diameter of the two ring gears 38, 56. For example, when the number of teeth of the movable ring gear 56 is greater than that of the stationary ring gear 38, the reduction gear 28 is contra-rotating, i.e., the movable ring gear 56 rotates in the opposite direction to the sun gear 32. When the number of teeth of the movable ring gear 56 is less than that of the stationary ring gear 38, the reduction gear 28 is co-rotating, i.e., the ring gear 56 and the sun gear 32 rotate in the same direction.

(61) FIG. 9 provides a partial schematic view of the reduction gear 28 shown in FIG. 8.

(62) The reference 30 refers to the shaft, one end of which comprises splines complementary to the splines 32b of the sun gear 32. FIG. 9 shows that the planet gears 34 are arranged around the shaft 30 or part of the shaft. In some embodiments, this is the case when the stationary ring gear 38 is located downstream of the movable ring gear 56. As the shaft 30 comes from downstream of the electric motor, it is coupled to the upstream toothing 34a of the planet gears 34 and the toothing 54a of these planet gears are located around the shaft 30.

(63) FIGS. 10 and 11 also provide partial illustrations of the reduction gear 28 shown in FIG. 8.

(64) The reference 36 refers to the planet carrier which carries the cylindrical bodies 44a of the hydrodynamic bearings of the planet gears 34.

(65) In the embodiments shown in FIGS. 8-11, D1 is less than D2. The number of planet gears 34 in the reduction gear shown in FIGS. 10 and 11 is three.

(66) FIG. 11 also shows the position of the motor 20 (shown in dotted lines) next to reduction gear 28. The motor 20 is annular in shape and is positioned next to the planet gears 34. The planet gears 34 and the motor 20 are therefore located on circumferences of the same or close diameter. The references 20a and 20b refer respectively to the rotor and the stator of the motor 20, both of which are annular. The stator 20b is connected to the stationary ring gear 38 and the rotor 20a is connected to the sun gear 32.

(67) The rim 16 is shown in dotted lines and the reduction gear 28 is at least partly housed axially in the rim 16.

(68) In the alternative embodiment shown in FIG. 12, the diameters of the toothings 34a, 54a of the planet gears 34 are different and the number of planet gears 34 is five.

(69) FIG. 13 shows another example of how the planet gears 34 of the reduction gear 28 are guided. The planet gears 34 are guided by rolling bearings 45, which in this case are roller bearings. There are two guide bearings 45 for guiding each planet gear 34, mounted around the longitudinal ends of this planet gear, between these ends and the planet carrier 36. Each of the bearings 45 comprises an internal ring 45a carried by the planet gear 34 or integrated into it, and an external ring 45b carried by the planet carrier 36. The rollers 45c are mounted between the rings 45a, 45b.

(70) FIG. 13 shows that the toothings 34a, 54a of the planet gears are located between the bearings 45. This arrangement allows the moments applied to the planet gears 34 by the meshing to be balanced as effectively as possible.

(71) Alternatively, as shown in FIG. 14, the planet gears 34 are guided by needle bearings 47. These bearings 47 are two in number and are mounted radially between the planet gears 34 and the bodies 44a. Each of the bearings 47 is radially aligned with one of the toothing 34a, 54a of the planet gear 34. This assembly allows to reduce the axial overall dimension.

(72) Each of the bearings 47 may have an axial length or dimension L1, L2 measured along the axis Y, which is at least 80% of the axial length or dimension L3, L4 of the corresponding toothing 34a, 54a.

(73) In the foregoing description, specific details are set forth to provide a thorough understanding of exemplary embodiments of the present disclosure. It will be apparent to one skilled in the art, however, that the embodiments disclosed herein may be practiced without embodying all of the specific details. In some instances, well-known process steps have not been described in detail in order not to unnecessarily obscure various aspects of the present disclosure. Further, it will be appreciated that embodiments of the present disclosure may employ any combination of features described herein.

(74) The present application may reference quantities and numbers. Unless specifically stated, such quantities and numbers are not to be considered restrictive, but exemplary of the possible quantities or numbers associated with the present application. Also in this regard, the present application may use the term “plurality” to reference a quantity or number. In this regard, the term “plurality” is

meant to be any number that is more than one, for example, two, three, four, five, etc. The terms “about,” “approximately,” “near,” etc., mean plus or minus 10% of the stated value. For the purposes of the present disclosure, the phrase “at least one of A and B” is equivalent to “A and/or B” or vice versa, namely “A” alone, “B” alone or “A and B.”. Similarly, the phrase “at least one of A, B, and C,” for example, means (A), (B), (C), (A and B), (A and C), (B and C), or (A, B, and C), including all further possible permutations when greater than three elements are listed.

(75) It should be noted that for purposes of this disclosure, terminology such as “upper,” “lower,” “vertical,” “horizontal,” “fore,” “aft,” “inner,” “outer,” “front,” “rear,” etc., should be construed as descriptive and not limiting the scope of the claimed subject matter. Further, the use of “including,” “comprising,” or “having” and variations thereof herein is meant to encompass the items listed thereafter and equivalents thereof as well as additional items. Unless limited otherwise, the terms “connected,” “coupled,” and “mounted” and variations thereof herein are used broadly and encompass direct and indirect connections, couplings, and mountings.

(76) Throughout this specification, terms of art may be used. These terms are to take on their ordinary meaning in the art from which they come, unless specifically defined herein or the context of their use would clearly suggest otherwise.

(77) The principles, representative embodiments, and modes of operation of the present disclosure have been described in the foregoing description. However, aspects of the present disclosure, which are intended to be protected, are not to be construed as limited to the particular embodiments disclosed. Further, the embodiments described herein are to be regarded as illustrative rather than restrictive. It will be appreciated that variations and changes may be made by others, and equivalents employed, without departing from the spirit of the present disclosure. Accordingly, it is expressly intended that all such variations, changes, and equivalents fall within the spirit and scope of the present disclosure as claimed.

Claims

1. A device for driving at least one wheel of an aircraft landing gear, the device comprising: at least one landing gear wheel including a rim having an axis of rotation; an electric motor including a shaft; and a mechanical transmission system for mechanical transmission between the shaft of the motor and the rim, the mechanical transmission system including a mechanical reduction gear, the mechanical reduction gear comprising: a sun gear secured in rotation to the shaft of the motor, the sun gear being centered on the axis of rotation and having an external toothing; a stationary ring gear centered on the axis of rotation and having an internal toothing, the stationary ring gear being configured to be secured to a stator of the device; a movable ring gear centered on the axis of rotation and having an internal toothing, the movable ring gear being secured in rotation to the rim; and planet gears which are meshed with the sun gear, the planet gears being carried by a planet carrier which is mobile in rotation about the axis of rotation, each of the planet gears having two external toothings meshed respectively with the toothing of the stationary and movable ring gears, wherein the toothing of the stationary and movable ring gears have the same diameter.
2. The device of claim 1, wherein the planet gears are each centered and guided by: two roller bearings carried by the planet carrier, wherein the toothing of each of the planet gears is located between these roller bearings; or two needle bearings carried by the planet carrier, wherein each of the needle bearings is radially aligned with one of the toothing of the planet gear.
3. The device of claim 1, wherein the toothing of the stationary and movable ring gears have different numbers of teeth.
4. The device of claim 1, wherein all the toothings are selected from straight, helical, or herringbone toothings.
5. The device of claim 1, wherein the motor has an annular shape centered on the axis of rotation and arranged next to the reduction gear.

6. The device of claim 1, wherein the motor is arranged aside the planet gears along the axis of rotation.

7. The device of claim 1, wherein: the two external toothings of each of the planet gears comprise a first external toothing having a smallest diameter and a second external toothing having a greatest diameter which is different from the smallest diameter; the first external toothing having the smallest diameter meshing with the toothing of the stationary ring gear; and the second external toothing having the greatest diameter meshing with the toothing of the movable ring gear.

8. The device of claim 1, wherein the electric motor is arranged on the side of the stationary ring gear and on the opposite side to the movable ring gear.

9. The device of claim 1, wherein the planet carrier is arranged on the side of the electric motor.

10. The device of claim 1, wherein each of the planet gears is meshed by a first toothing with the toothing of the sun gear and the toothing of the stationary ring gear, and by a second toothing with the toothing of the movable ring gear.

11. The device of claim 1, wherein each of the planet gears is meshed by a first toothing with the toothing of the sun gear and the toothing of the movable ring gear, and by a second toothing with the toothing of the stationary ring gear.

12. The device of claim 1, wherein the planet gears are arranged around at least part of the shaft of the motor.
