

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12401840
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Aoi; Shosuke et al.

Information processing device and information processing method

Abstract

An information processing device includes a processing unit. The processing unit selects one communication section from a plurality of communication sections having different communication schemes, on the basis of broadcast information indicating a broadcast use of a video to be transferred and broadcast status information indicating a status of utilization of the video when the broadcast information indicates live streaming for providing an optimal communication environment while suppressing power consumption.

Inventors:	Aoi; Shosuke (Tokyo, JP), Inui; Tasuku (Tokyo, JP), Horiuchi; Kohta (Tokyo, JP)
Applicant:	SONY GROUP CORPORATION (Tokyo, JP)
Family ID:	1000008779899
Assignee:	SONY GROUP CORPORATION (Tokyo, JP)
Appl. No.:	18/548217
Filed (or PCT Filed):	January 26, 2022
PCT No.:	PCT/JP2022/002833
PCT Pub. No.:	WO2022/185795
PCT Pub. Date:	September 09, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240305843 A1	Sep. 12, 2024

Foreign Application Priority Data

JP 2021-035215 Mar. 05, 2021

Publication Classification

Int. Cl.: H04N21/238 (20110101); H04N21/2187 (20110101)

U.S. Cl.:

CPC H04N21/238 (20130101); H04N21/2187 (20130101);

Field of Classification Search

CPC: H04N (21/238); H04N (21/2187)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
11451864	12/2021	Mittal	N/A	H04N 21/8456
2012/0284421	12/2011	Xiao	709/231	H04N 21/4316
2013/0226979	12/2012	Caruso	707/827	G06F 16/116

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
11-069325	12/1998	JP	N/A
2001-251258	12/2000	JP	N/A
2002-344654	12/2001	JP	N/A
2016-032160	12/2015	JP	N/A
2018-085678	12/2017	JP	N/A
2019/073802	12/2018	WO	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion of PCT Application No. PCT/JP2022/002833, issued on Apr. 12, 2022, 09 pages of ISRWO. cited by applicant

Primary Examiner: Ekpo; Nnenna N

Attorney, Agent or Firm: CHIP LAW GROUP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

(1) This application is a U.S. National Phase of International Patent Application No. PCT/JP2022/002833 filed on Jan. 26, 2022, which claims priority benefit of Japanese Patent Application No. JP 2021-035215 filed in the Japan Patent Office on Mar. 5, 2021. Each of the

above-referenced applications is hereby incorporated herein by reference in its entirety.

FIELD

(2) The present invention relates to an information processing device, an information processing method, and a program.

BACKGROUND

(3) In recent years, larger communication capacity has been provided for transmission and reception using a wireless communication system, and practical use of a fifth generation mobile communication system (5G) has recently started. In such an environment, a system that transmits a captured video using an information processing device as a relay and uses the captured video for video production has also been studied.

(4) In general, a communication unit having a large communicable capacity consumes a large amount of power but a communication device is not always in an environment where power supply can be always received. Therefore, a system is required that provides an optimal communication environment while suppressing power consumption.

CITATION LIST

Patent Literature

(5) Patent Literature 1: JP 2016-32160 A

SUMMARY

Technical Problem

(6) Patent Literature 1 discloses selection of any of communication sections consuming different amounts of power (communication capacities) to be used, according to information about an operation time of a relay device and a result of determination whether a (predicted) remaining battery level reaches a predetermined threshold when an identical operation is performed in communication by a certain communication section. However, there is no disclosure of control of communication for a video to be transferred, depending on the broadcast use thereof, while suppressing power consumption.

(7) Therefore, the present disclosure proposes an information processing device, an information processing method, and a program that are configured to perform control of communication for a video to be transferred, depending on broadcast use thereof, while suppressing power consumption.

Solution to Problem

(8) According to the present disclosure, an information processing device is provided that comprises a processing unit that selects one communication section from a plurality of communication sections having different communication schemes, based on broadcast information indicating a broadcast use of a video to be transferred. According to the present disclosure, an information processing method in which an information process of the information processing device is executed by a computer, and a program for causing the computer to execute the information process of the information processing device, are provided.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a diagram illustrating an example of a video production system using video streaming.

(2) FIG. 2 is a diagram illustrating a process of production and distribution of a video.

(3) FIG. 3 is a diagram illustrating an exemplary network environment.

(4) FIG. 4 is a diagram illustrating an exemplary configuration of a communication unit.

(5) FIG. 5 is a diagram illustrating an exemplary configuration of an imaging device.

(6) FIG. 6 is a block diagram illustrating an exemplary functional configuration of a video acquisition unit.

(7) FIG. 7 is a diagram illustrating an overview of video stream transmission between a

transmission-side device and a reception-side device.

(8) FIG. 8 is a flowchart illustrating an example of an information processing method performed by the communication unit.

(9) FIG. 9 is a flowchart illustrating an example of the information processing method performed by the communication unit.

(10) FIG. 10 is a flowchart illustrating an example of the information processing method performed by the communication unit.

(11) FIG. 11 is a flowchart illustrating an example of the information processing method performed by the communication unit.

(12) FIG. 12 is a block diagram illustrating an exemplary hardware configuration of the communication unit.

DESCRIPTION OF EMBODIMENTS

(13) Embodiments of the present disclosure will be described in detail below with reference to the drawings. In the following embodiments, the same portions are denoted by the same reference numerals, and repetitive description thereof will be omitted.

(14) Note that the description will be given in the following order. [1. Video production system] [2. Communication network] [3. Configuration of communication unit] [4. Configuration of imaging device] [5. Video streaming] [6. Information processing method] [7. Exemplary hardware configuration] [8. Effects] [9. Modification]

1. Video Production System

(15) FIG. 1 is a diagram illustrating an example of a video production system SY using video streaming.

(16) The video production system SY is a system that transmits a video captured by a camera operator to a production site where a broadcast program is produced, by using a wireless communication channel. The video production system SY includes an imaging device CM, a communication unit CU, and a reception-side device RD.

(17) The imaging device CM is, for example, a digital video camera for business use or consumer use. The imaging device CM may be a mobile terminal device such as a digital still camera, a smartphone, or a tablet terminal, capable of capturing a moving image or the like. The imaging device CM performs network communication by using a communication scheme such as 5G via the communication unit CU.

(18) The communication unit CU receives a video captured by the imaging device CM through a wired or wireless connection, and transfers the video to the production site. The communication unit CU may be provided separately from the imaging device CM or may be incorporated in the imaging device CM. In the present disclosure, for example, a communication device separate from the imaging device CM is used as the communication unit CU.

(19) The communication unit CU performs video streaming transmission to the reception-side device RD via a network NW. As the network NW, for example, the Internet, a home network, a local area network (LAN), a satellite communication network, and the other various networks are assumed.

(20) Various devices are assumed as the reception-side device RD. For example, a cloud server, a network distribution server, a video server, a video editor, a video reproducing apparatus, a video recording apparatus, and a television apparatus, or an information processing apparatus such as a personal computer or mobile terminal having video processing functions equivalent thereto is assumed.

(21) FIG. 2 is a diagram illustrating a process of production and distribution of the video.

(22) The camera operator connects the communication unit CU to the imaging device CM as a relay. The communication unit CU is connected to the network NW via a base station BS. The video captured by the imaging device CM is transmitted to the production site (control room) via wireless communication.

(23) At the production site, an editor PR processes the transmitted videos and generates processed videos for broadcasting. The editor PR performs switching control of the processed videos by using a switcher SW or the like, for TV broadcast output or over-the-top (OTT) distribution. The distributed processed videos are each viewed by a viewer AU, via a communication terminal TM such as a television or a smartphone.

(24) Note that, in pre-recorded broadcasting, the video transmitted to the production site is used only for confirming the contents of the video or performing pre-editing work, in some cases. In this case, a video actually used for broadcasting is separately recorded on a tape, disk, or the like and delivered.

2. Communication Network

(25) FIG. 3 is a diagram illustrating an exemplary network environment used in the present disclosure.

(26) In recent years, the specifications of 5G-NR that is the next-generation wireless communication system have been studied in the Third Generation Partnership Project (3GPP). Specifically, 5G-NR includes enhanced mobile broadband (eMBB), massive machine type communication (mMTC), and ultra-reliable and low latency communications (URLLC) as the scope of standardization.

(27) In particular, in order to achieve high-speed communication in eMBB, it is necessary to extend the frequency band used for wireless communication. Therefore, in 5G-NR, use of a high frequency band represented by, for example, a millimeter wave band has been studied. Specifically, in 5G-NR, a frequency band definitions enabling allocation to 24 GHz or more has been added. In use of a high frequency band, it is possible to perform high-speed communication than in a frequency band having been used before.

(28) Meanwhile, when different frequency bands are used for communication, radio property changes. For example, in communication in a high frequency band, transmission power is higher than that in a frequency band used in 4G or earlier wireless communication systems, and thus, increasing power consumption upon transmitting a radio wave signal. In addition, for example, in communication in a high frequency band, it is assumed that a processing load on a modem of the terminal device increases and results in an increase in power consumption as compared with that in other frequency bands.

(29) Meanwhile, depending on the amount of data of the cellular communication by the terminal device, speed as fast as the communication speed in the high frequency band is not necessarily required in some cases. For example, the amount of data communicated is small in the transmission and reception of a text message, and therefore, it is assumed that there is no problem even if the communication speed is not high as in the high frequency band.

(30) In view of the above, it is desired to reduce power consumption by determining a frequency band according to a state of the terminal device or the purpose of communication.

(31) Therefore, the communication unit CU according to an embodiment of the present disclosure has a function of determining a frequency band (communication scheme) to be used for communication on the basis of a state of the communication unit CU. This configuration allows for communication suitable for the state of the communication unit CU, and power consumption can be suppressed according to the state.

(32) FIG. 3 illustrates a communication system CS that includes the communication unit CU, a plurality of the base stations BS, and the network NW. The plurality of the base stations BS includes, for example, a 5G-NR base station BS1 and an LTE base station BS2. Hereinafter, an example of communication scheme selection between 4G/LTE and 5G will be described. In a 5G-NR communication system, for example, a non-standalone (NSA) mode is adopted. The NSA mode is a mode that uses a long term evolution (LTE) network, for implementing 5G-NR communication. Specifically, the NSA mode is a mode in which a control signal is transmitted and received through the LTE network and a data signal is transmitted and received through a 5G-NR

network.

(33) Meanwhile, the technology according to the present disclosure is also applicable to a standalone (SA) mode of the 5G-NR communication system. The SA mode is a mode that transmits and receives both of the control signal and the data signal through the 5G-NR network. As a matter of course, the 5G-NR communication system is merely an example, and the present technology is also applicable to other communication systems.

(34) The 5G NR base station BS1 is a base station that provides 5G-NR wireless communication. The 5G NR base station BS1 is connected to a core network CN. Here, the core network CN is connected to a data network DN via a gateway device (not illustrated). In addition, a cell of the 5G NR base station BS1 can have a range smaller than that of a cell of the LTE base station BS2.

(35) The communication unit CU is connected to the 5G NR base station BS1 or the LTE base station BS2 to enjoy a wireless communication service. The communication unit CU may be, for example, a smartphone. Note that the communication unit CU transmits and receives the control signal to and from the LTE base station BS2, and transmits and receives the data signal to and from the 5G NR base station BS1.

(36) The communication unit CU determines a frequency band used for communication, from a plurality of independent frequency bands (communication schemes), on the basis of the positioning of the video to be transferred, in the broadcast program. Here, the positioning of the video in the broadcast program means the broadcast use of the video, a status of utilization of the video in live streaming, and the like. Examples of the broadcast use include live streaming, pre-recorded broadcasting, and the like. The status of utilization in the live streaming means whether the video is used as the distribution video or used only for the editor PR to confirm the contents of the video.

(37) For example, in the pre-recorded broadcasting, the transmitted video is used only for the editor PR to confirm the contents of the video or to perform pre-editing work, in some cases. Such a video often has no problem even if the image quality is coarse. Even a video captured for live streaming is not always used entirely for the distribution video. A portion not used for the distribution video is only used for confirmation by the editor PR, and thus, high communication performance is not required. Therefore, the communication unit CU selects an appropriate communication scheme according to the communication performance required for the video, for each video to be transferred so as not to increase the power consumption due to excessive specifications.

(38) The LTE base station BS2 is a base station that provides LTE wireless communication. The LTE base station BS2 is connected to the core network CN as in the 5G NR base station BS1.

3. Configuration of Communication Unit

(39) FIG. 4 is a diagram illustrating an exemplary configuration of the communication unit CU.

(40) The communication unit CU is an information processing device that processes various information. The communication unit CU performs wired or wireless data communication with the imaging device CM, and transfers the video acquired from the imaging device CM to the production site by wireless communication. The communication unit CU includes, for example, a plurality of communication sections **10**, antenna units AT, a processing unit **20**, a video acquisition unit **30**, a power supply unit **40**, and a storage unit **50**.

(41) The plurality of communication sections **10** uses different communication schemes. The plurality of communication sections **10** includes, for example, a first communication section **11** and a second communication section **12**. The first communication section **11** uses a communication scheme such as 5G having a large communication capacity (communication speed) and consuming a large amount of power. The second communication section **12** uses a communication scheme such as 4G/LTE having a smaller communication capacity and consuming a smaller amount of power, as compared with the first communication section **11**. In general, as the communication capacity increases, the communication performance increases, but the power consumption also increases. The communication performance and the power consumption are a trade-off. The

communication sections **10** each transmit and receive an image, voice information, and the like to and from an external device via each of the antenna units AT.

(42) The video acquisition unit **30** performs wired or wireless data communication with the imaging device CM, and acquires the video captured by the imaging device CM. The video acquisition unit **30** supplies the video acquired from the imaging device CM to the processing unit **20**.

(43) The processing unit **20** provides various functions of the communication unit CU. The processing unit **20** includes, for example, a determination unit **21**, a communication control unit **22**, and a broadcast status information acquisition unit **23**.

(44) The determination unit **21** determines whether to perform communication by using which communication scheme, on the basis of broadcast-related information **51** acquired from the storage unit **50**, broadcast status information acquired from the broadcast status information acquisition unit **23**, external power supply information acquired from the power supply unit **40**, and the like. The communication control unit **22** controls each communication section **10** corresponding to the communication scheme determined by the determination unit **21**, and performs communication.

(45) The broadcast-related information **51** includes various pieces of information indicating the positioning of the video to be transmitted, in the broadcast program. For example, the broadcast-related information **51** includes broadcast information indicating the broadcast use of the video to be transferred. The broadcast use includes the live streaming and the pre-recorded broadcasting. The broadcast-related information **51** may include information indicating the broadcasting time of the broadcast program, a video shooting location (the position of the shooting location), and the like.

(46) For example, the broadcast-related information **51** may be recorded as planning meta-information. The planning meta-information is information that describes a shooting plan. When the item name of interview/record, the name of reporter/director, the name of the camera operator, and the like are recorded in advance on a disk as the planning meta information, and loaded and recorded on the imaging device CM, recording is performed in association with the meta-information. The imaging device CM is allowed to perform imaging by using a title defined in advance in the planning meta-information, as the name of a video clip.

(47) The broadcast status information is information indicating the status of utilization of the video in live streaming. The broadcast status information includes information (“PGM OUT”) indicating that the video is currently broadcasted and information (“Next”) indicating that the video is to be switched as a next video broadcasted. The broadcast status information is supplied from the production site to the broadcast status information acquisition unit **23** via any of the communication sections **10**.

(48) Videos whose broadcast status information indicating “PGM OUT” and “Next” are videos that are to be distributed to the viewer AU. Therefore, high image quality is required. A video whose broadcast status information is other than “PGM OUT” or “Next” is a video that is used only for the editor PR to confirm the contents of the video. Therefore, high image quality is not required.

(49) For example, the determination unit **21** selects one communication section **10** from the plurality of communication sections **10** having different communication schemes, on the basis of the broadcast information. For example, when the broadcast information indicates live streaming, the determination unit **21** is configured to select the first communication section **11** having higher communication performance in order to provide a high-quality video to the production site.

(50) However, even when the broadcast information indicates the live streaming, the communication section **10** can be selected, on the basis of the status of utilization (current broadcast status) of the video to be transferred. In other words, the determination unit **21** is configured to acquire the broadcast status information indicating the status of utilization of the video from the broadcast status information acquisition unit **23**, and select the communication section **10** on the basis of the broadcast status information. For example, when the broadcast status

information indicates “PGM OUT” or “Next”, high image quality is required for the video to be transferred. Therefore, the determination unit **21** selects the communication section **10** having a higher communication performance than that when the video whose broadcast status information indicates a state other than “PGM OUT” or “Next”.

(51) Note that, in the present disclosure, the same communication section **10** (first communication section **11**) is selected for both of the video whose broadcast status information indicates “Next” and the video whose broadcast status information indicates “PGM OUT”. However, the highest-priority video is a video currently broadcasted. Therefore, the first communication section **11** may be selected only when the broadcast status information indicates “PGM OUT”, and the second communication section **12** may be selected when the broadcast status information indicates “Next”. In other words, when the broadcast status information indicates “PGM OUT”, the determination unit **21** may select the communication section **10** having the higher communication performance than that when the broadcast status information indicates a state other than “PGM OUT”.

(52) When the broadcast information indicates pre-recorded broadcasting, the determination unit **21** is configured to select the second communication section **12**. In some cases, the video for the pre-recorded broadcasting is used only for confirming the contents of the video or performing pre-editing work. In such a case, high image quality is not required, and therefore, it is preferable to select the second communication section **12** that is configured to suppress power consumption although communication performance is low.

(53) However, in some cases, even when the broadcast information indicates the pre-recorded broadcasting, wireless acquisition of the video from the shooting location is desired for immediate editing, due to tight schedule of editing. Therefore, the determination unit **21** is configured to select the communication section **10** on the basis of a time available for editing of the video for recording, even when the broadcast information indicates the pre-recorded broadcasting. For example, in an urgent case where the time available for editing is equal to or less than a predetermined amount of time, the determination unit **21** selects the communication section **10** having the higher communication performance than that in a non-urgent case where the time available for editing is larger than the predetermined amount of time.

(54) The determination unit **21** is configured to determine the time available for editing, on the basis of the information indicating the position of the shooting location and broadcasting time of a recorded video. Information indicating the position of the shooting location and broadcasting time of the recorded video is included in the broadcast-related information **51**.

(55) The power supply unit **40** manages a battery of the communication unit CU. The power supply unit **40** notifies the processing unit **20** of a remaining power supply capacity. The determination unit **21** selects the communication section **10** based on the broadcast status information, according to a remaining battery capacity. For example, if the first communication section **11** consuming a large amount of power is continuously used under a low remaining capacity condition where the remaining battery capacity is equal to or less than a predetermined value, there is a possibility that the battery runs out during communication and video cannot be transmitted. Therefore, under the low remaining capacity condition, the determination unit **21** preferentially selects the second communication section **12**, as much as possible. The determination unit **21** performs selection of the communication section **10** based on the broadcast status information, when the remaining battery capacity satisfies the low remaining capacity condition.

(56) The low remaining capacity condition is defined, for example, as a condition where a remaining battery capacity $V_{sub.c}$ satisfies $V_{sub.c} - V_{sub.Est} \leq V_{sub.th}$. A symbol $V_{sub.Est}$ indicates an estimated battery capacity that is estimated to be used until the end of live streaming. A symbol $V_{sub.th}$ is a preset threshold. The threshold $V_{sub.th}$ has a value of 0 or more.

(57) The storage unit **50** stores, for example, the broadcast-related information **51** and a program **59** executed by the processing unit **20**. The program **59** is a program that causes a computer to perform information processing according to the present disclosure. The processing unit **20** performs

various processing in accordance with the program **59** stored in the storage unit **50**. Furthermore, the storage unit **50** may be used as a work area that temporarily stores a result of the processing by the processing unit **20**. The storage unit **50** includes, for example, any non-transitory storage medium such as a semiconductor storage medium and a magnetic storage medium. The storage unit **50** includes, for example, a magnetic disk, an optical disk, a magneto-optical disk, a flash memory, or the like. The program **59** is stored, for example, in a non-transitory computer-readable storage medium.

(58) The processing unit **20** is, for example, a computer that includes a processor and a memory. The memory of the processing unit **20** includes a random access memory (RAM) and a read only memory (ROM). The processing unit **20** executes the program **59** to function as the determination unit **21**, the communication control unit **22**, and the broadcast status information acquisition unit **23**.

4. Configuration of Imaging Device

(59) FIG. 5 is a diagram illustrating an exemplary configuration of the imaging device CM.

(60) The imaging device CM includes an imaging unit **110**, an image signal processing unit **120**, a storage unit **130**, a control unit **150**, an operation unit **160**, a display control unit **170**, a display unit **180**, and a communication section **140**.

(61) The imaging unit **110** includes an imaging optical system and an image sensor, for imaging. Furthermore, the image sensor is an imaging element, such as a charge coupled device (CCD) sensor, a complementary metal oxide semiconductor (CMOS) sensor, and the image sensor receives light incident from a subject via the imaging optical system, converts the light to an electric signal, and outputs the electric signal. The image sensor performs, for example, correlated double sampling (CDS) processing, automatic gaincontrol (AGC) processing, and the like on the electric signal obtained by photoelectrically converting the received light, and further performs analog/digital (A/D) conversion processing. Then, image data as digital data is output to the image signal processing unit **120** on the downstream side.

(62) The image signal processing unit **120** is constituted, as an image processing processor, for example, by a digital signal processor (DSP) or the like. The image signal processing unit **120** performs various processing on the image data input from the imaging unit **110**.

(63) For example, when an image signal is assumed as a normal visible light image, the image signal processing unit **120** performs clamp processing of clamping the black levels of red (R), green (G), and blue (B) to a predetermined signal level, correction processing between color channels of R, G, and B, color separation processing (or demosaicing when a mosaic color filter such as a Bayer filter is used) of allocating all color components of R, G, and B to the image data for each pixel, or processing of generating (separating) a brightness (Y) signal and a color (C) signal, and the like.

(64) The image signal processing unit **120** performs necessary resolution conversion processing, for example, resolution conversion for storage, communication output, or monitor image, on the image signal subjected to various signal processing, in some cases. The image signal processing unit **120** performs, for example, compression encoding processing for storage, on the image data whose resolution has been converted, in some cases. When the compression encoding processing is performed on the image data, a compression rate may be changed according to the communication performance of the selected communication section **10**. For example, when the second communication section **12** is selected by the determination unit **21**, the compression encoding processing is performed at a higher compression rate than that when the first communication section **11** is selected.

(65) The control unit **150** includes a microcomputer (arithmetic processing device) including a central processing unit (CPU), a ROM, a RAM, a flash memory, and the like.

(66) The CPU executes a program stored in the ROM, the flash memory, or the like to integrally control the imaging device CM as a whole. The RAM is used for temporary storage of data,

programs, and the like, as a work area to process various data of the CPU. The ROM and the flash memory (nonvolatile memory) are used to store an operating system (OS) for the CPU to control each unit, content files such as image files, application programs for various operations, firmware, and the like.

(67) The control unit **150** performs control of imaging operation such as shutter speed, exposure adjustment, and frame rate in the imaging unit **110**, control of parameters of various signal processing in the image signal processing unit **120**, and the like. Furthermore, the control unit **150** performs setting processing, imaging operation control, display operation control, and the like, according to a user's operation.

(68) The operation unit **160** is assumed to be an operation element such as a key, switch, or dial, a touch panel, or the like that are provided in a device housing. The operation unit **160** transmits a signal according to an input operation, to the control unit **150**.

(69) The display unit **180** is a display unit that provides various displays for the user (camera operator or the like), and that includes, for example, a display device such as a liquid crystal display (LCD) or organic electro-luminescence (EL) display.

(70) The display control unit **170** performs processing of causing the display unit **180** to perform a display operation. For example, the display control unit **170** includes a character generator, a display driver, and the like, and causes the display unit **180** to present various displays under the control of the control unit **150**. For example, the display control unit **170** causes the display unit **180** to display a through-image or reproduce and display a still image or moving image recorded on a recording medium, or to display various operation menus, icons, messages, or the like, that is, a graphical user interface (GUI), on a screen.

(71) The storage unit **130** includes, for example, a nonvolatile memory, and stores, for example, an image file such as still image data or moving image data captured by the imaging unit **110**, attribute information of the image file, a thumbnail image, and the like.

(72) Various actual modes of the storage unit **130** can be considered. For example, the storage unit **130** may be a flash memory incorporated in the imaging device CM, or may be a memory card (e.g., portable flash memory) attachable to and detachable from the imaging device CM to have a mode in which a card recording/reproducing unit performs recording/reproducing/access to the memory card. In addition, as a mode of the storage unit **130** incorporated in the imaging device CM, the storage unit **130** may be implemented as a hard disk drive (HDD) or the like.

(73) The communication section **140** transmits a captured image data (video) to the video acquisition unit **30** through a wired or wireless connection.

(74) FIG. **6** is a block diagram illustrating an exemplary functional configuration of the video acquisition unit **30**.

(75) The video acquisition unit **30** includes a video capture unit **60**, a packet transmission module **70**, a video encoder **80**, a memory **81**, and a network interface unit **90**.

(76) For example, image data (frame data) V_{in} of each frame processed by the image signal processing unit **120** is input to the video capture unit **60**. For example, uncompressed frame data are input at predetermined time intervals (frame intervals according to the frame rate of the imaging operation of the imaging device CM). "Frame data" refers to image data per frame.

(77) The video capture unit **60** transfers the input image data V_{in} per frame to the video encoder **80** via a bus BL. The bus BL is, for example, a bus such as a peripheral component interconnect express (PCIe).

(78) The video encoder **80** performs encoding processing for compression encoding per frame data, and transfers the encoded frame data to the packet transmission module **70** via the bus BL. The packet transmission module **70** performs packet fragmentation processing for transmission, and performs processing to cause the network interface unit **90** to transmit and output video stream data per frame.

5. Video Streaming

(79) FIG. 7 is a diagram illustrating an overview of video stream transmission between a transmission-side device TD and the reception-side device RD. The transmission-side device TD includes the imaging device CM and communication unit CU.

(80) In the communication unit CU, the image data Vin input to the video capture unit **60** is encoded by the video encoder **80** and packetized by the packet transmission module **70**. This video data packet VDPK is transmitted to the network NW through the network interface unit **90**.

(81) The reception-side device RD includes a reception unit RU. In the reception unit RU, the video data packet VDPK is received through a network interface unit **210** and taken into a packet receiving module **220**. Then, frame data having been compressed is extracted from each packet and subjected to decoding processing in a video decoder **230** against compressing. Then, video stream data VRX received is output via a video renderer **240**.

(82) In such a transmission/reception system, a transmission delay may occur. Therefore, the reception unit RU sequentially transmits a control packet CPK to the communication unit CU and transmits status information. For example, the control packet CPK includes information that helps to notify of the current reception rate, delay amount, and packet loss rate in the reception unit RU.

(83) Receiving the control packet CPK makes it possible to control the packet transmission module **70** of the communication unit CU to recognize the current state of the network, to change (decrease or increase) a transmittable rate, to instruct the video encoder **80** to change (decrease or increase) an encoding rate (i.e., increase or decrease the compression rate).

6. Information Processing Method

(84) FIGS. **8** to **11** are a flowchart illustrating an example of an information processing method performed by the communication unit CU. In the communication unit CU, for example, the communication scheme (second communication section **12**) having a lower communication performance is adopted as a default communication scheme.

(85) In Step **S101**, the determination unit **21** acquires the broadcast information indicating the broadcast use of the video captured by the imaging device CM. Then, in Step **S102**, the determination unit **21** determines whether the broadcast use is for live streaming, on the basis of the acquired broadcast information.

(86) In Step **S102**, when it is determined that the broadcast use is for live streaming (Step **S102**: Yes), the process proceeds to Step **S103**. In Step **S103**, the determination unit **21** acquires the current remaining battery capacity of the communication unit CU. Then, in Step **S104**, the determination unit **21** determines whether the remaining battery capacity satisfies the low remaining capacity condition.

(87) In Step **S104**, when it is determined that the remaining battery capacity does not satisfy the low remaining capacity condition (Step **S104**: No), the process proceeds to Step **S105**. In Step **S105**, the determination unit **21** selects the first communication section **11**.

(88) Next, in Step **S106**, the determination unit **21** determines whether imaging is finished. When operation information about an imaging end button or the like is acquired from the imaging device CM, the determination unit **21** determines that the imaging is finished. In Step **S106**, when it is determined that the imaging is finished (Step **S106**: Yes), the process is finished. In Step **S106**, when it is determined that the imaging is not finished (Step **S106**: No), the process returns to Step **S106**, and the processing described above is repeated until the imaging is finished.

(89) In step **S104**, when it is determined that the remaining battery capacity satisfies the low remaining capacity condition (Step **S104**: Yes), the process proceeds to Step **S107**. In Step **S107**, the determination unit **21** acquires the broadcast status information indicating the status of utilization of the video to be transferred. Then, in Step **S108**, the determination unit **21** determines whether the video to be transferred is used as a video corresponding to “PGM OUT” or “Next”, on the basis of the broadcast status information.

(90) In Step **S108**, when it is determined that the video to be transferred is the video corresponding to “PGM OUT” or “Next” (Step **S108**: Yes), the process proceeds to Step **S109**. In Step **S109**, the

determination unit **21** selects the second communication section **12**, and the process proceeds to Step **S111**. In Step **S108**, when it is determined that the video to be transferred is a video other than “PGM OUT” or “Next” (Step **S108**: No), the process proceeds to Step **S110**. In Step **S110**, the determination unit **21** selects the first communication section **11**, and the process proceeds to Step **S111**.

(91) In Step **S111**, the determination unit **21** determines whether the imaging is finished. In Step **S111**, when it is determined that the imaging is finished (Step **S111**: Yes), the process is finished. In Step **S111**, when it is determined that the imaging is not finished (Step **S111**: No), the process returns to Step **S107**, and the processing described above is repeated until imaging is finished.

(92) In Step **S102**, when it is determined that the broadcast use is for pre-recorded broadcasting (Step **S102**: No), the process proceeds to Step **S112**. In Step **S112**, the determination unit **21** acquires the information about a time until the broadcasting of a broadcast program using the captured video and the position of the shooting location. Then, in Step **S113**, the determination unit **21** determines whether the time available for editing the video is larger than the predetermined amount of time (urgent case or non-urgent case). The time available for editing is calculated from, for example, the arrival time to the production site from the shooting location and the time until the broadcasting time.

(93) In Step **S113**, when it is determined that the time available for editing the video is equal to or less than the predetermined amount of time (urgent case) (Step **S113**: No), the process proceeds to Step **S114**. In Step **S114**, the determination unit **21** selects the first communication section **11**, and the process is finished. In Step **S113**, when it is determined that the time available for editing the video is larger than the predetermined amount of time (non-urgent case) (Step **S113**: Yes), the process proceeds to Step **S115**. In Step **S115**, the determination unit **21** selects the second communication section **12** and the process is finished.

7. Exemplary Hardware Configuration

(94) FIG. **12** is a block diagram illustrating an exemplary hardware configuration of the communication unit CU.

(95) The communication unit CU includes, for example, a processor **871**, ROM **872**, RAM **873**, a host bus **874**, a bridge **875**, an external bus **876**, an interface **877**, an input device **878**, an output device **879**, a storage **880**, a drive **881**, a connection port **882**, and a communication device **883**. Note that the hardware configuration shown here is merely an example, and some of the component elements may be omitted. In addition, a component element other than the component elements shown here may be further included.

(96) The processor **871** functions, for example, as an arithmetic processing device or a control device, and controls all or some of the operations of the component elements, on the basis of various programs recorded in the ROM **872**, the RAM **873**, the storage **880**, on a removable recording medium **901**.

(97) The ROM **872** is a unit that stores a program read by the processor **871**, data used for calculation, and the like. The RAM **873** temporarily or permanently stores, for example, a program read by the processor **871**, various parameters appropriately changing upon running the program, and the like.

(98) The processor **871**, the ROM **872**, and the RAM **873** are connected to each other, for example, via the host bus **874** configured to transmit data at high speed. Meanwhile, the host bus **874** is connected to, for example, the external bus **876** configured to transmit data at relatively low speed, via the bridge **875**. In addition, the external bus **876** is connected to various component elements via the interface **877**.

(99) For the input device **878**, for example, a mouse, a keyboard, a touch screen, a button, a switch, a lever, and the like are used. Furthermore, for the input device **878**, a remote controller configured to transmit the control signal by using an infrared ray or other radio waves is used, in some cases. Furthermore, the input device **878** includes a voice sound input device such as a microphone.

(100) The output device **879** is a device, such as a display device including a cathode ray tube (CRT), LCD, or organic EL, an audio output device including a speaker or headphone, a printer, a mobile phone, or a facsimile, that is configured to visually or audibly notify the user of acquired information. Furthermore, the output device **879** according to the present disclosure includes various vibrating devices configured to output tactile stimulation.

(101) The storage **880** is a device for storing various data. For the storage **880**, for example, a magnetic storage device such as a hard disk drive (HDD), a semiconductor storage device, an optical storage device, a magneto-optical storage device, or the like is employed.

(102) The drive **881** is, for example, a device that reads information recorded on the removable recording medium **901** such as a magnetic disk, optical disk, magneto-optical disk, or semiconductor memory, and writes information on the removable recording medium **901**.

(103) The removable recording medium **901** is, for example, a DVD medium, a Blu-ray (registered trademark) medium, an HD DVD medium, various semiconductor storage media, or the like. As a matter of course, the removable recording medium **901** may be, for example, an IC card with a non-contact IC chip, an electronic device, or the like.

(104) The connection port **882** is, for example, a port for connecting an externally connected device **902**, such as a universal serial bus (USB) port, IEEE1394 port, small computer system interface (SCSI), RS-232C port, or optical audio terminal.

(105) The externally connected device **902** includes, for example, a printer, a portable music player, a digital camera, a digital camcorder, or an IC recorder.

(106) The communication device **883** is a communication device for connection to a network, and is, for example, a communication card for wired or wireless LAN, Bluetooth (registered trademark), or wireless USB (WUSB), an optical communication router, an asymmetric digital subscriberline (ADSL) router, various communication modems, or the like.

(107) Furthermore, the communication device **883** includes a communication interface that supports wireless communication schemes such as 5G-NR, LTE, and LTE-Advanced. Specifically, the communication device **883** may include a baseband processor that performs signal processing such as encoding, decoding, and modulation/demodulation. Furthermore, the communication device **883** may include an RF circuit. Furthermore, the communication device **883** may include an antenna that radiates a radio wave into space and converts a radio wave in space into a signal.

8. Effects

(108) The communication unit CU includes the processing unit **20**. The processing unit **20** selects one communication section **10** from the plurality of communication sections **10** having different communication schemes, on the basis of the broadcast information indicating the broadcast use of the video to be transferred. In the information processing method of the present embodiment, the processing of the communication unit CU described above is performed by the computer. The program of the present embodiment causes a computer to implement the above processing of the communication unit CU.

(109) This configuration makes it possible to suppress power consumption while securing sufficient communication quality.

(110) When the broadcast information indicates the live streaming, the processing unit **20** selects the communication section **10**, on the basis of the broadcast status information indicating the status of utilization of the video.

(111) This configuration makes it possible to select an appropriate communication section **10**, on the basis of the status of utilization of the video.

(112) When the broadcast status information is the information (“PGM OUT”) indicating that the video is currently broadcasted, the processing unit **20** selects the communication section **10** having the higher communication performance than that when the broadcast status information indicates a state other than “PGM OUT”.

(113) This configuration makes it also possible to suppress power consumption while improving

the communication quality of the video currently broadcasted.

(114) When the broadcast status information is the information (“PGM OUT”) indicating that the video is currently broadcasted or the information (“Next”) indicating that the video is to be switched as a next video broadcasted, the processing unit **20** selects the communication section **10** having the higher communication performance than that when the broadcast status information indicates a state other than “PGM OUT” or “Next”.

(115) This configuration also makes it also possible to suppress the power consumption while improving the communication quality of the video currently broadcasted or the video scheduled to be broadcasted next.

(116) The processing unit **20** selects the communication section **10** based on the broadcast status information, according to the remaining battery capacity.

(117) This configuration selects an appropriate communication section **10** according to battery endurance.

(118) The processing unit **20** performs selection of the communication section **10** based on the broadcast status information, when the low remaining capacity condition is satisfied in which the remaining battery capacity is equal to or less than the predetermined value.

(119) This configuration makes it possible to maximize the communication quality.

(120) When the broadcast information indicates the pre-recorded broadcasting, the processing unit **20** selects the communication section **10** on the basis of the time available for editing of the video for recording.

(121) This configuration makes it possible to transfer the video in a high-quality communication environment according to the urgency of editing, even in the pre-recorded broadcasting, prompting the editor PR to perform editing early.

(122) In the urgent case where the time available for editing is equal to or less than the predetermined amount of time, the processing unit selects the communication section **10** having the higher communication performance than that in the non-urgent case where time available for editing is larger than the predetermined amount of time.

(123) This configuration makes it possible to immediately start the editing by using the video transferred in the high-quality communication environment, even in a tight schedule of editing.

(124) The processing unit **20** determines the time available for editing, on the basis of the information indicating the position of the shooting location and broadcasting time of the recorded video.

(125) This configuration makes it possible to accurately estimate the time available for editing.

(126) Note that the effects described herein are merely examples and are not limited to the description, and other effects may be provided.

9. Modification

(127) In the embodiments described above, 5G and 4G/LTE are exemplified as a combination of communication schemes having different communication performances. Although the communication schemes have been switched between 5G and 4G/LTE, the combination of the communication schemes is not limited thereto. The communication schemes may be switched between Wireless Fidelity (Wi-Fi) (registered trademark) and 3G.

Supplementary Note

(128) Note that the present technology can also have the following configurations.

(129) (1)

(130) An information processing device comprising a processing unit that selects one communication section from a plurality of communication sections having different communication schemes, based on broadcast information indicating a broadcast use of a video to be transferred.

(131) (2)

(132) The information processing device according to (1), wherein the processing unit selects the

communication section, based on broadcast status information indicating a status of utilization of the video when the broadcast information indicates live streaming.

(3)

(133) The information processing device according to (2), wherein when the broadcast status information is information indicating that the video is currently broadcasted, the processing unit selects the communication section having a higher communication performance than that when the broadcast status information is other than the information indicating that the video is currently broadcasted.

(4)

(134) The information processing device according to (2), wherein when the broadcast status information is information indicating that the video is currently broadcasted, the processing unit selects the communication section having the higher communication performance than that when the broadcast status information is other than the information indicating that the video is currently broadcasted or information indicating that the video is to be switched as a next video broadcasted.

(5)

(135) The information processing device according to (2), wherein when the broadcast status information is information indicating that the video is to be switched as a next video broadcasted, the processing unit selects the communication section having the higher communication performance than that when the broadcast status information is other than information indicating that the video is currently broadcasted or the information indicating that the video is to be switched as a next video broadcasted.

(6)

(136) The information processing device according to any one of (2) to (5), wherein the processing unit selects the communication section based on the broadcast status information, according to a remaining battery capacity.

(7)

(137) The information processing device according to (6), wherein the processing unit selects the communication section based on the broadcast status information, when a low remaining capacity condition that the remaining battery capacity is equal to or less than a predetermined value is satisfied.

(8)

(138) The information processing device according to (1), wherein the processing unit selects the communication section based on a time available for editing the video for recording, when the broadcast information indicates pre-recorded broadcasting.

(9)

(139) The information processing device according to (8), wherein in an urgent case where the time available for editing is equal to or less than a predetermined amount of time, the processing unit selects the communication section having the higher communication performance than that in a non-urgent case where the time available for editing is larger than the predetermined amount of time.

(10)

(140) The information processing device according to (8) or (9), wherein the processing unit determines the time available for editing, based on information indicating a position of a shooting location and broadcasting time of a recorded video.

(11)

(141) An information processing method executed by a computer, the method comprising selecting one communication section from a plurality of communication sections having different communication schemes, based on broadcast information indicating a broadcast use of a video to be transferred.

(142) (12)

(143) A program for causing a computer to implement selection of one communication section from a plurality of communication sections having different communication schemes, based on broadcast information indicating a broadcast use of a video to be transferred.

REFERENCE SIGNS LIST

(144) **10** COMMUNICATION SECTION **20** PROCESSING UNIT CU COMMUNICATION UNIT (INFORMATION PROCESSING DEVICE)

Claims

1. An information processing device, comprising: a processing unit configured to: select one communication section from a plurality of communication sections having a plurality of communication schemes, based on broadcast information, wherein the broadcast information indicates a broadcast use of a video that is transferred; select a first communication section of the plurality of communication sections based on a time available to edit the video and based on a determination that the broadcast information indicates pre-recorded broadcast; and select a second communication section of the plurality of communication sections based on communication performance of the second communication section, wherein the communication performance of the second communication section is higher at a first time available to edit the video than at a second time available to edit the video, the first time available is equal to or less than a threshold, and the second time available is more than the threshold.
2. The information processing device according to claim 1, wherein the processing unit is further configured to select a third communication section of the plurality of communication sections based on first broadcast status information, and the first broadcast status information indicating a status of utilization of the video based on a determination that the broadcast information indicates live streaming.
3. The information processing device according to claim 2, wherein the processing unit is further configured to select a fourth communication section of the plurality of communication sections based on communication performance of the fourth communication section and second broadcast status information which indicates that the video is currently broadcasted, and the communication performance of the fourth communication section is higher with the second broadcast status information than from an alternate broadcast status information which is different from the second broadcast status information.
4. The information processing device according to claim 2, wherein the processing unit is further configured to select a fifth communication section of the plurality of communication sections based on communication performance of the fifth communication section and second broadcast status information which indicates that the video is currently broadcasted, and the communication performance of the fifth communication section is higher with the second broadcast status information than with third broadcast status information which is different from the second broadcast status information and which indicates that the video is switched as a next video broadcasted.
5. The information processing device according to claim 2, wherein the processing unit is further configured to select a sixth communication section of the plurality of communication sections based on communication performance of the sixth communication section and third broadcast status information which indicates that the video is switched as a next video broadcasted, and the communication performance of the sixth communication section is higher with the third broadcast status information than with a fourth broadcast status information which is different from a second broadcast status information and the third broadcast status information, the second broadcast status information indicating that the video is currently broadcasted.
6. The information processing device according to claim 2, wherein the processing unit is further configured to select a seventh communication section from the plurality of communication sections

based on the first broadcast status information and remaining battery capacity of the information processing device.

7. The information processing device according to claim 6, wherein the seventh communication section is selected based on the first broadcast status information and based on satisfaction of a low remaining battery capacity condition, and the low remaining battery capacity condition indicates that the remaining battery capacity of the information processing device is equal to or less than a specific value.

8. The information processing device according to claim 1, wherein the processing unit is further configured to determine the time available to edit, based on information indicating a position of a shooting location and broadcasting time of a recorded video.

9. An information processing method, comprising: selecting one communication section from a plurality of communication sections having a plurality of communication schemes, based on broadcast information, wherein the broadcast information indicates a broadcast use of a video that is transferred; selecting a first communication section of the plurality of communication sections based on a time available to edit the video and based on a determination that the broadcast information indicates pre-recorded broadcast; and selecting a second communication section of the plurality of communication sections based on communication performance of the second communication section, wherein the communication performance of the second communication section is higher at a first time available to edit the video than at a second time available to edit the video, the first time available is equal to or less than a threshold, and the second time available is more than the threshold.

10. A non-transitory computer-readable medium having stored thereon, computer-executable instructions which, when executed by a computer, cause the computer to execute operations, the operations comprising: selecting one communication section from a plurality of communication sections having a plurality of communication schemes, based on broadcast information, wherein the broadcast information indicates a broadcast use of a video that is transferred; selecting a first communication section of the plurality of communication sections based on a time available to edit the video and based on a determination that the broadcast information indicates pre-recorded broadcast; and selecting a second communication section of the plurality of communication sections based on communication performance of the second communication section, wherein the communication performance of the second communication section is higher at a first time available to edit the video than at a second time available to edit the video, the first time available is equal to or less than a threshold, and the second time available is more than the threshold.
