

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12401856
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Satou; Hirokazu

Reception device and transmission system

Abstract

An object is to efficiently display pieces of image data of some regions of interest (ROI) cut from a captured image on a display device. A reception device includes: a reception unit that receives a transmission signal in which image data of a predetermined number of regions of interest (ROIs) cut from a predetermined captured image is included in payload data and ROI information corresponding to a predetermined number of the ROIs is included in embedded data; and a processing unit that is configured to perform restoration processing of restoring the image data of the ROI so as to be displayable on a predetermined display device on the basis of the ROI information extracted from the embedded data.

Inventors:	Satou; Hirokazu (Kanagawa, JP)
Applicant:	Sony Semiconductor Solutions Corporation (Kanagawa, JP)
Family ID:	1000008779918
Assignee:	Sony Semiconductor Solutions Corporation (Kanagawa, JP)
Appl. No.:	17/802735
Filed (or PCT Filed):	February 19, 2021
PCT No.:	PCT/JP2021/006374
PCT Pub. No.:	WO2021/192764
PCT Pub. Date:	September 30, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20230129052 A1	Apr. 27, 2023

Foreign Application Priority Data

JP2020-054537

Mar. 25, 2020

Publication Classification

Int. Cl.: G06V10/25 (20220101); G06T5/00 (20240101)

U.S. Cl.:

CPC G06V10/25 (20220101); G06T5/00 (20130101);

Field of Classification Search

CPC: G06V (10/25); G06T (5/001)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2008/0285789	12/2007	Kimura	382/100	H04N1/32347
2015/0016504	12/2014	Auyeung	375/240.02	H04N19/33
2017/0372675	12/2016	Cho	N/A	G09G5/005
2020/0186841	12/2019	Yoshimochi	N/A	H04N23/665

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2012209831	12/2011	JP	N/A
2013164834	12/2012	JP	N/A
2014039219	12/2013	JP	N/A
2016504890	12/2015	JP	N/A
2016506669	12/2015	JP	N/A
2016529789	12/2015	JP	N/A
2016201756	12/2015	JP	N/A
2019049705	12/2018	JP	N/A
2019091967	12/2018	JP	N/A
2017131806	12/2016	KR	G09G 3/20
WO-2006008787	12/2005	WO	N/A
WO-2018225449	12/2017	WO	H04N21/23418

OTHER PUBLICATIONS

Primary Examiner: Cadeau; Wednel

Attorney, Agent or Firm: Michael Best & Friedrich LLP

Background/Summary

TECHNICAL FIELD

(1) The present disclosure relates to a reception device and a transmission system.

BACKGROUND ART

(2) In recent years, transmission of a large amount of massive data is increasing. A large load is likely to be applied to a transmission system, and in the worst case, there is a possibility that the transmission system is down and data transmission cannot be performed.

(3) It is known that an object to be imaged is specified and only an image of a cut part of the specified object is transmitted instead of, for example, transmitting all captured images in order to prevent the transmission system from being down (for example, Patent Documents 1 to 4).

CITATION LIST

Patent Document

(4) Patent Document 1: Japanese Patent Application Laid-Open No. 2016-201756 Patent Document 2: Japanese Patent Application Laid-Open No. 2014-39219 Patent Document 3: Japanese Patent Application Laid-Open No. 2013-164834 Patent Document 4: Japanese Patent Application Laid-Open No. 2012-209831

SUMMARY OF THE INVENTION

Problems to be Solved by the Invention

(5) Processing for efficiently displaying some regions of interest (ROIs) cut from a captured image and transmitted on a display device has not been studied at all.

(6) An object of the present disclosure is to provide a reception device and a transmission system that enable efficient display of some regions of interest (ROIs) cut from a captured image on a display device.

Solutions to Problems

(7) A reception device according to one aspect of the present disclosure includes: a reception unit that receives a transmission signal in which image data of a predetermined number of regions of interest (ROIs) cut from a predetermined captured image is included in payload data and ROI information corresponding to a predetermined number of the ROIs is included in embedded data; and a processing unit that is configured to perform restoration processing of restoring the image data of the ROI so as to be displayable on a predetermined display device on the basis of the ROI information extracted from the embedded data.

(8) A transmission system according to one aspect of the present disclosure includes: a transmission device that sends image data of a region of interest (ROI) as payload data and sends ROI information as embedded data; and a reception device that includes a reception unit that receives a transmission signal in which the image data of a predetermined number of the ROIs cut from a predetermined captured image is included in the payload data and the ROI information corresponding to a predetermined number of the ROIs is included in the embedded data, and a processing unit that is configured to perform restoration processing of restoring the image data of a

predetermined number of the ROIs so as to be displayable on a predetermined display device on the basis of the ROI information extracted from the embedded data.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a diagram illustrating a schematic configuration example of a video transmission system.
- (2) FIG. 2 is a diagram illustrating a schematic configuration example of a video transmission device of FIG. 1.
- (3) FIG. 3 is a diagram illustrating an example of a transmission data generation procedure in a case where two regions of interest (ROIs) are included in a captured image.
- (4) FIG. 4 is a diagram illustrating a configuration example of a packet header.
- (5) FIG. 5 is a diagram illustrating a configuration example of transmission data.
- (6) FIG. 6 is a diagram illustrating a configuration example of the transmission data.
- (7) FIG. 7 is a diagram illustrating a configuration example of payload data of a long packet.
- (8) FIG. 8 is a diagram illustrating a schematic configuration example of a video reception device of FIG. 1.
- (9) FIG. 9 is a diagram illustrating an example of a procedure of generating two ROI images included in a captured image in a case where two images are included in transmission data.
- (10) FIG. 10 is a diagram schematically illustrating a region in which a specified object is arranged in a captured image.
- (11) FIG. 11 is a diagram illustrating an example of an ROI set for a specified object.
- (12) FIG. 12 is a diagram illustrating a configuration example of transmission data in which position information of each ROI image is included in payload data of a long packet.
- (13) FIG. 13 is a diagram schematically illustrating an example of a captured image according to an embodiment of the present disclosure.
- (14) FIG. 14 is a diagram illustrating coordinates and image sizes of regions of interest illustrated in FIG. 13.
- (15) FIG. 15 is a diagram illustrating an example of payload data including image data of the regions of interest illustrated in FIG. 13.
- (16) FIG. 16 is a diagram for describing first coordinate data and second coordinate data included in ROI restoration information according to an embodiment of the present disclosure.
- (17) FIG. 17 is a diagram illustrating an example of X-coordinate order data and Y-coordinate order data according to an embodiment of the present disclosure.
- (18) FIG. 18 is a block diagram illustrating a schematic configuration of a video transmission system according to an embodiment of the present disclosure.
- (19) FIG. 19 is a diagram illustrating a schematic configuration example of a video reception device according to an embodiment of the present disclosure.
- (20) FIG. 20 is a flowchart illustrating an example of a flow of restoration processing in the video reception device according to the present embodiment of the present disclosure.
- (21) FIG. 21 is a flowchart illustrating an example of a flow of image data replacement processing in the video reception device 200a according to an embodiment of the present disclosure.

MODE FOR CARRYING OUT THE INVENTION

- (22) Hereinafter, modes for carrying out the present disclosure will be described in detail with reference to the drawings. The following description is a specific example of the present disclosure, and the present disclosure is not limited to the following aspects.
- (23) Hereinafter, a mode for carrying out the technology according to the present disclosure (hereinafter, referred to as “embodiment”) will be described in the following order. 1. Underlying

Technology 1 of Present Disclosure (Technology for Transmitting Some Regions of Interest (ROIs) (Having Rectangular Shape) Cut from Captured Image) 2. Underlying Technology 2 of Present Disclosure (Technology for Transmitting Some Regions of Interest (ROIs) (Having Non-Rectangular Shape) Cut from Captured Image) 3. Principle of Restoration Processing in Embodiment of Present Disclosure 4. Video Reception Device and Video Transmission System According to Embodiment of Present Disclosure 5. Processing for Displaying Image Data in Video Reception According to Embodiment of Present Disclosure 6. Modified Example of Restoration Processing in Embodiment of Present Disclosure

1. Underlying Technology 1 of Present Disclosure

(24) [Configuration]

(25) In recent years, in portable devices such as smartphones, camera devices, and the like, the capacity of handled image data has been increased, and there has been a demand for higher speed and lower power consumption for data transmission in the devices or between different devices. In order to meet such requirements, high-speed interface standards such as a C-PHY standard and a D-PHY standard set by the MIPI Alliance are being standardized as connection interfaces for portable devices and camera devices. The C-PHY standard and the D-PHY standard are interface standards of a physical layer (PHY) of a communication protocol. In addition, a display serial interface (DSI) for display of a portable device and a camera serial interface (CSI) for a camera device exist as higher protocol layers of the C-PHY standard and the D-PHY standard.

(26) A video transmission system **1** according to the underlying technology of the present disclosure is a system that can transmit and receive a signal according to various standards, and can transmit and receive a signal according to, for example, an MIPI CSI-2 standard, an MIPI CSI-3 standard, or an MIPI DSI standard. FIG. **1** illustrates an outline of the video transmission system **1** according to the underlying technology of the present disclosure. The video transmission system **1** is applied to transmission of a data signal, a clock signal, and a control signal, and includes a video transmission device **100** and a video reception device **200**. The video transmission system **1** includes a data lane DL for transmitting a data signal such as image data, a clock lane CL for transmitting a clock signal, and a camera control interface CCI for transmitting a control signal across the video transmission device **100** and the video reception device **200**. Although FIG. **1** illustrates an example in which one data lane DL is provided, a plurality of data lanes DL may be provided. The camera control interface CCI is a bidirectional control interface compatible with an inter-integrated circuit (I2C) standard.

(27) The video transmission device **100** is a device that sends a signal according to the MIPI CSI-2 standard, the MIPI CSI-3 standard, or the MIPI DSI standard. A CSI transmitter **100A** and a CCI slave **100B** are provided. The video reception device **200** includes a CSI receiver **200A** and a CCI master **200B**. In the clock lane CL, a clock signal line connects between the CSI transmitter **100A** and the CSI receiver **200A**. In the data lane DL, a clock signal line connects between the CSI transmitter **100A** and the CSI receiver **200A**. In the camera control interface CCI, a control signal line connects between the CCI slave **100B** and the CCI master **200B**.

(28) The CSI transmitter **100A** is, for example, a differential signal transmission circuit that generates a differential clock signal as a clock signal and outputs the differential clock signal to the clock signal line. The CSI transmitter **100A** can be configured to be able to transmit not only the differential clock signal but also a single-ended signal or a three-phase signal. The CSI transmitter **100A** is also a differential signal transmission circuit that generates a differential data signal as a data signal and outputs the differential data signal to a data signal line. The CSI receiver **200A** is a differential signal reception circuit that receives a differential clock signal as a clock signal via the clock signal line and performs predetermined processing on the received differential clock signal. The CSI receiver **200A** is also a differential signal reception circuit that receives a differential data signal as a data signal via the data signal line and performs predetermined processing on the received differential data signal.

(29) (Video Transmission Device **100**)

(30) FIG. 2 illustrates an example of a configuration of the video transmission device **100**. The video transmission device **100** corresponds to a specific example of the CSI transmitter **100A**. The video transmission device **100** includes, for example, an imaging unit **110**, image processing units **120** and **130**, and a transmission unit **140**. The video transmission device **100** transmits transmission data **147A** generated by performing predetermined processing on a captured image **111** obtained by the imaging unit **110** to the video reception device **200** via the data lane DL. FIG. 3 illustrates an example of a procedure of generating the transmission data **147A**.

(31) The imaging unit **110** converts, for example, an optical image signal obtained through an optical lens or the like into image data. The imaging unit **110** includes, for example, an image sensor such as a charge coupled device (CCD) image sensor, a complementary metal oxide semiconductor (CMOS) image sensor, or the like. The imaging unit **110** includes an analog-digital conversion circuit, and converts analog image data into digital image data. A data format after the conversion may be a YCbCr format in which the color of each pixel is expressed by a luminance component Y and chrominance components Cb and Cr, an RGB format, or the like. The imaging unit **110** outputs the captured image **111** (digital image data) obtained by imaging to the image processing unit **120**.

(32) The image processing unit **120** is a circuit that performs predetermined processing on the captured image **111** input from the imaging unit **110**. In Underlying Technology 1, a case where the image processing unit **120** performs predetermined processing on the captured image **111** input from the imaging unit **110** in a case where a control signal for instructing cutting of an ROI is input from the video reception device **200** via the camera control interface CCI will be described. However, Underlying Technology 1 can also be applied to a case where the video transmission device **100**, that is, a transmission side, specifies the coordinates of an ROI to be cut. In this case, for example, the transmission side is configured to receive information such as a “person” or an “object” to be acquired in the ROI sent from a reception side, and determine and specify the coordinates of the cutting. As a result, the image processing unit **120** generates various pieces of data (**120A**, **120B**, and **120C**) and outputs the various pieces of data to the transmission unit **140**. The image processing unit **130** is a circuit that performs predetermined processing on the captured image **111** input from the imaging unit **110**. The image processing unit **130** performs predetermined processing on the captured image **111** input from the imaging unit **110** in a case where a control signal for instructing outputting of a normal image is input from the video reception device **200** via the camera control interface CCI. As a result, the image processing unit **130** generates image data **130A** and outputs the image data **130A** to the transmission unit **140**.

(33) The image processing unit **130** includes, for example, an encoding unit **131**. The encoding unit **131** encodes the captured image **111** to generate compressed image data **130A**. For example, the image processing unit **130** compresses the captured image **111** in a compression format conforming to the joint photographic experts group (JPEG) standard or the like as the format of the compressed image data **130A**.

(34) The image processing unit **120** includes, for example, an ROI cutting unit **121**, an ROI analysis unit **122**, an overlapping detection unit **123**, a priority setting unit **124**, an encoding unit **125**, and an image processing control unit **126**.

(35) The ROI cutting unit **121** specifies one or more objects to be imaged included in the captured image **111** input from the imaging unit **110**, and sets a region of interest ROI for each specified object. The region of interest ROI is, for example, a square-shaped region including the specified object. The ROI cutting unit **121** cuts an image of each region of interest ROI (for example, an ROI image **112** in FIG. 3) from the captured image **111**. The ROI cutting unit **121** further assigns a region number as an identifier to each set region of interest ROI. For example, in a case where two regions of interest ROI are set in the captured image **111**, the ROI cutting unit **121** assigns a region number **1** to one region of interest ROI (for example, a region of interest ROI1 in FIG. 3), and

assigns a region number **2** to the other region of interest ROI (for example, a region of interest ROI2 in FIG. 3). For example, the ROI cutting unit **121** stores the assigned identifier (region number) in a storage unit. For example, the ROI cutting unit **121** stores each ROI image **112** cut from the captured image **111** in the storage unit. The ROI cutting unit **121** further stores, for example, the identifier (region number) assigned to each region of interest ROI in the storage unit in association with the ROI image **112**.

(36) The ROI analysis unit **122** derives position information **113** of a region of interest ROI in the captured image **111** for each region of interest ROI. The position information **113** includes, for example, the upper-left end coordinates (Xa,Ya) of a region of interest ROI, the length of a region of interest ROI in an X-axis direction, and the length of a region of interest ROI in a Y-axis direction. The length of a region of interest ROI in the X-axis direction is, for example, a physical region length XLa of a region of interest ROI in the X-axis direction. The length of a region of interest ROI in the Y-axis direction is, for example, a physical region length YLa of a region of interest ROI in the Y-axis direction. The physical region length indicates a physical length (data length) of a region of interest ROI. The position information **113** may include coordinates of a position different from the upper-left end of a region of interest ROI. The ROI analysis unit **122** stores, for example, the derived position information **113** in the storage unit. For example, the ROI analysis unit **122** stores, in the storage unit, the position information **113** in association with the identifier (region number) assigned to the region of interest ROI.

(37) The ROI analysis unit **122** may further derive, for example, an output region length XLc of a region of interest ROI in the X-axis direction and an output region length YLc of a region of interest ROI in the Y-axis direction as the position information **113** for each region of interest ROI. The output region length is, for example, a physical length (data length) of a region of interest ROI after resolution of a region of interest ROI is changed by thinning processing, pixel addition, or the like. For example, the ROI analysis unit **122** may derive, in addition to the position information **113**, for example, sensing information, exposure information, gain information, an analog-digital (AD) word length, an image format, and the like for each region of interest ROI, and store the derived information in the storage unit.

(38) The sensing information refers to a computation content for an object included in a region of interest ROI, supplementary information for post-stage signal processing for the ROI image **112**, and the like. The exposure information refers to an exposure time of a region of interest ROI. The gain information refers to gain information of a region of interest ROI. The AD word length refers to a word length of data per pixel subjected to AD conversion in a region of interest ROI. The image format refers to the format of an image of a region of interest ROI. For example, the ROI analysis unit **122** may derive the number of regions of interest ROI (the number of ROIs) included in the captured image **111** and store the number in the storage unit.

(39) In a case where a plurality of objects to be imaged is specified in the captured image **111**, the overlapping detection unit **123** detects a region of overlap (ROO) in which two or more regions of interest ROI overlap each other on the basis of the position information **113** of the plurality of regions of interest ROI in the captured image **111**. That is, the overlapping detection unit **123** derives position information **114** of a region of overlap ROO in the captured image **111** for each region of overlap ROO. For example, the overlapping detection unit **123** stores the derived position information **114** in the storage unit. For example, the overlapping detection unit **123** stores the derived position information **114** in the storage unit in association with the region of overlap ROO. The region of overlap ROO is, for example, a square-shaped region having the same size as or smaller than the smallest region of interest ROI among two or more regions of interest ROI overlapping each other. The position information **114** includes, for example, the upper-left end coordinates (Xb,Yb) of a region of overlap ROO, the length of a region of overlap ROO in the X-axis direction, and the length of a region of overlap ROO in the Y-axis direction. The length of a region of overlap ROO in the X-axis direction is, for example, a physical region length XLb. The

length of a region of overlap ROO in the Y-axis direction is, for example, a physical region length YLb. The position information **114** may include coordinates of a position different from the upper-left end of a region of interest ROI.

(40) The priority setting unit **124** assigns a priority **115** to each region of interest ROI in the captured image **111**. The priority setting unit **124** stores, for example, the assigned priority **115** in the storage unit. For example, the priority setting unit **124** stores the assigned priority **115** in the storage unit in association with the region of interest ROI. The priority setting unit **124** may assign the priority **115** to each region of interest ROI separately from the region number assigned to each region of interest ROI, or may substitute the region number assigned to each region of interest ROI for the priority **115**. For example, the priority setting unit **124** may store the priority **115** in the storage unit in association with the region of interest ROI, or may store the region number assigned to each region of interest ROI in the storage unit in association with the region of interest ROI.

(41) The priority **115** is an identifier of each region of interest ROI, and is determination information that enables determination of from which one of a plurality of regions of interest ROI in the captured image **111** a region of overlap ROO has been omitted. For example, for two regions of interest ROI each including a region of overlap ROO, the priority setting unit **124** assigns **1** as the priority **115** to one region of interest ROI, and assigns **2** as the priority **115** to the other region of interest ROI. In this case, at the time of creating a transmission image **116** to be described later, the region of overlap ROO is omitted from the region of interest ROI whose priority **115** has a larger value. Note that the priority setting unit **124** may assign, to a region of interest ROI, the same number as a region number assigned to each region of interest ROI as the priority **115**. For example, the priority setting unit **124** stores the priority **115** assigned to each region of interest ROI in the storage unit in association with the ROI image **112**.

(42) The encoding unit **125** encodes each transmission image **116** to generate compressed image data **120A**. For example, the encoding unit **125** compresses each transmission image **116** in a compression format conforming to the JPEG standard or the like as the format of the compressed image data **120A**. The encoding unit **125** generates each transmission image **116** before performing the above-described compression processing. The encoding unit **125** generates a plurality of transmission images **116** obtained by omitting an image **118** of the region of overlap ROO from a plurality of ROI images **112** obtained from the captured image **111** in such a manner that the image **118** is not included redundantly in the plurality of ROI images **112** obtained from the captured image **111**.

(43) For example, the encoding unit **125** determines from which of the plurality of ROI images **112** the image **118** is to be omitted on the basis of the priority **115** assigned to each region of interest ROI. Note that the encoding unit **125** may determine from which of the plurality of ROI images **112** the image **118** is to be omitted by using, for example, the region number assigned to each region of interest ROI as the priority **115**. The encoding unit **125** uses an image obtained by omitting the image **118** from the ROI image **112** specified as described above as the transmission image **116** (for example, a transmission image **116a2** in FIG. 3). In a case of an ROI image **112** that does not include a region of overlap ROO or an ROI image **112** from which the image **118** is not omitted according to the above-described determination, the encoding unit **125** uses the ROI image **112** itself as the transmission image **116** (for example, a transmission image **116a1** in FIG. 3).

(44) The image processing control unit **126** generates ROI information **120B** and frame information **120C**, and transmits the ROI information **120B** and the frame information **120C** to the transmission unit **140**. The ROI information **120B** includes, for example, each piece of position information **113**. The ROI information **120B** further includes, for example, at least one of the data type of each region of interest ROI, the number of regions of interest ROI included in the captured image **111**, the region number (or the priority **115**) of each region of interest ROI, the data length of each region of interest ROI, or the image format of each region of interest ROI. The frame information **120C** includes, for example, a virtual channel number assigned to each frame, the data

type of each region of interest ROI, the payload length of each line, and the like. The data type includes, for example, YUV data, RGB data, RAW data, or the like. The data type further includes, for example, ROI format data or normal format data. The payload length is, for example, the number of pixels included in a payload of a long packet, and is, for example, the number of pixels for each region of interest ROI. Here, the payload refers to main data (application data) transmitted between the video transmission device **100** and the video reception device **200**. The long packet refers to a packet arranged between a packet header PH and a packet footer PF.

(45) The transmission unit **140** is a circuit that generates and sends the transmission data **147A** on the basis of various pieces of data (**120A**, **120B**, **120C**, and **130A**) input from the image processing units **120** and **130**. The transmission unit **140** sends the ROI information **120B** regarding each region of interest ROI in the captured image **111** as embedded data (Embedded Data). Further, in a case where a control signal for instructing cutting of an ROI is input from the video reception device **200** via the camera control interface CCI, the transmission unit **140** sends image data (compressed image data **120A**) of each region of interest ROI as payload data (Payload Data) of the long packet. At this time, the transmission unit **140** sends the image data (compressed image data **120A**) of each region of interest ROI through a common virtual channel. In addition, the transmission unit **140** sends the image data (compressed image data **120A**) of each region of interest ROI by an image data frame, and sends the ROI information **120B** regarding each region of interest ROI by a header of the image data frame. Further, in a case where a control signal for instructing outputting of a normal image is input from the video reception device **200** via the camera control interface CCI, the transmission unit **140** sends normal image data (compressed image data **130A**) as the payload data of the long packet.

(46) The transmission unit **140** includes, for example, a LINK control unit **141**, an ECC generation unit **142**, a PH generation unit **143**, an EBD buffer **144**, an ROI data buffer **145**, a normal image data buffer **146**, and a combining unit **147**. The LINK control unit **141**, the ECC generation unit **142**, the PH generation unit **143**, the EBD buffer **144**, and the ROI data buffer **145** perform outputting to the combining unit **147** in a case where a control signal for instructing cutting of an ROI is input from the video reception device **200** via the camera control interface CCI. In a case where a control signal for instructing outputting of a normal image is input from the video reception device **200** via the camera control interface CCI, the normal image data buffer **146** outputs a normal image to the combining unit **147**.

(47) Note that the ROI data buffer **145** may also serve as the normal image data buffer **146**. In this case, the transmission unit **140** may include a selector that selects an output of any one of the ROI data buffer **145** and the ROI data buffer **145** between an output terminal of each of the ROI data buffer **145** and the ROI data buffer **145** and an input terminal of the combining unit **147**.

(48) For example, the LINK control unit **141** outputs the frame information **120C** to the ECC generation unit **142** and the PH generation unit **143** for each line. The ECC generation unit **142** generates an error correction code of one line on the basis of data (for example, a virtual channel number, the data type of each region of interest ROI, the payload length of each line, and the like) of the line in the frame information **120C**, for example. The ECC generation unit **142** outputs the generated error correction code to the PH generation unit **143**, for example. The PH generation unit **143** generates the packet header PH for each line by using, for example, the frame information **120C** and the error correction code generated by the ECC generation unit **142**. At this time, for example, as illustrated in FIG. 4, the packet header PH is a packet header of payload data of a long packet. The packet header PH includes, for example, DI, WC, and ECC. The WC is a region for indicating an end of a packet by the number of words for the video reception device **200**. The WC includes, for example, the payload length, and includes, for example, the number of pixels of each region of interest ROI. The ECC is a region for storing a value for correcting a bit error. The ECC includes an error correction code. The DI is a region for storing a data identifier. The DI includes a virtual channel (VC) number and DataType (the data type of each region of interest ROI). The

virtual channel (VC) is a concept introduced for packet flow control, and is a mechanism for supporting a plurality of independent data streams sharing the same link. The PH generation unit **143** outputs the generated packet header PH to the combining unit **147**.

(49) The EBD buffer **144** primarily stores the ROI information **120B** and outputs the ROI information **120B** to the combining unit **147** as the embedded data at a predetermined timing. The embedded data refers to additional information that can be embedded in a header or footer of an image data frame (see FIG. 5 as described later). The embedded data includes, for example, the ROI information **120B**.

(50) The ROI data buffer **145** primarily stores the compressed image data **120A** and outputs the compressed image data **120A** to the combining unit **147** as the payload data of the long packet at a predetermined timing. In a case where a control signal for instructing cutting of an ROI is input from the video reception device **200** via the camera control interface CCI, the ROI data buffer **145** outputs the compressed image data **120A** to the combining unit **147** as the payload data of the long packet. The normal image data buffer **146** primarily stores the compressed image data **130A** and outputs the compressed image data **130A** to the combining unit **147** as the payload data of the long packet at a predetermined timing. In a case where a control signal for instructing outputting of a normal image is input from the video reception device **200** via the camera control interface CCI, the normal image data buffer **146** outputs the compressed image data **130A** to combining unit **147** as the payload data of the long packet.

(51) In a case where a control signal for instructing outputting of a normal image is input from the video reception device **200** via the camera control interface CCI, the combining unit **147** generates the transmission data **147A** on the basis of input data (compressed image data **130A**). The combining unit **147** outputs the generated transmission data **147A** to the video reception device **200** via the data lane DL. Meanwhile, in a case where a control signal for instructing cutting of an ROI is input from the video reception device **200** via the camera control interface CCI, the combining unit **147** generates the transmission data **147A** on the basis of various pieces of input data (the packet header PH, the ROI information **120B**, and the compressed image data **120A**). The combining unit **147** outputs the generated transmission data **147A** to the video reception device **200** via the data lane DL. That is, the combining unit **147** includes, in the packet header PH of the payload data of the long packet, DataType (the data type of each region of interest ROI) and sends the packet. In addition, the combining unit **147** sends the image data (compressed image data **120A**) of each region of interest ROI through a common virtual channel.

(52) The transmission data **147A** includes, for example, the image data frame as illustrated in FIG. 5. The image data frame usually includes a header region, a packet region, and a footer region. The footer region is omitted in FIG. 5 for convenience. A frame header region R1 of the transmission data **147A** includes the embedded data. At this time, the embedded data includes the ROI information **120B**. In FIG. 5, a packet region R2 of the transmission data **147A** includes the payload data of the long packet for each line, and further includes the packet header PH and the packet footer PF at positions sandwiching the payload data of the long packet therebetween. Moreover, low power modes LP are included at positions sandwiching the packet header PH and the packet footer PF therebetween.

(53) At this time, the packet header PH includes, for example, the DI, the WC, and the ECC. The WC includes, for example, the payload length, and includes, for example, the number of pixels of each region of interest ROI. The ECC includes an error correction code. The DI includes a virtual channel number (VC) and DataType (the data type of each region of interest ROI). In the present embodiment, the VC of each line is assigned with a common virtual channel number. Furthermore, in FIG. 5, compressed image data **147B** is included in the packet region R2 of the transmission data **147A**. The compressed image data **147B** includes one piece of compressed image data **120A** or a plurality of pieces of compressed image data **120A**. Here, in FIG. 5, a packet group closer to the packet header PH includes, for example, the compressed image data **120A** (**120A1**) of the

transmission image **116a1** in FIG. 3, and a packet group away from the packet header PH includes, for example, the compressed image data **120A** (**120A2**) of the transmission image **116a2** in FIG. 3. The two pieces of compressed image data **120A1** and **120A2** constitute the compressed image data **147B**. The payload data of the long packet of each line includes pixel data for one line in the compressed image data **147B**.

(54) FIG. 6 illustrates a configuration example of the transmission data **147A**. The transmission data **147A** includes, for example, the frame header region R1 and the packet region R2. Note that FIG. 6 illustrates contents of the frame header region R1 in detail. Furthermore, in FIG. 6, the low power modes LP are omitted.

(55) The frame header region R1 includes, for example, a frame number F1 as the identifier of the transmission data **147A**. The frame header region R1 includes information regarding the compressed image data **147B** included in the packet region R2. The frame header region R1 includes, for example, the number of pieces of compressed image data **120A** (the number of ROIs) included in the compressed image data **147B** and information regarding the ROI image **112** corresponding to each piece of compressed image data **120A** included in the compressed image data **147B** (the ROI information **120B**).

(56) For example, the combining unit **147** arranges the compressed image data **147B** separately for each pixel row of the compressed image data **120A** in the packet region R2 of the transmission data **147A**. Therefore, the compressed image data corresponding to the image **118** of the region of overlap ROO is not redundantly included in the packet region R2 of the transmission data **147A**. Further, for example, the combining unit **147** omits a pixel row of the captured image **111** that does not correspond to each transmission image **116** in the packet region R2 of the transmission data **147A**. Therefore, the packet region R2 of the transmission data **147A** does not include a pixel row of the captured image **111** that does not correspond to each transmission image **116**. Note that a portion surrounded by a broken line in the packet region R2 in FIG. 6 corresponds to the compressed image data of the image **118** of the region of overlap ROO.

(57) A boundary between a packet group (for example, 1(n) in FIG. 6) closer to the packet header PH and a packet group (for example, 2(1) in FIG. 6) away from the packet header PH is specified by a physical region length XLa1 of the ROI image **112** corresponding to the compressed image data of the packet group (for example, 1(n) in FIG. 6) closer to the packet header PH. In the compressed image data corresponding to the image **118** of the region of overlap ROO included in the packet group (for example, 1(n) in FIG. 6) closer to the packet header PH, a start position of the packet is specified by a physical region length XLa2 of the ROI image **112** corresponding to the packet group (for example, 2(1) in FIG. 6) away from the packet header PH.

(58) For example, the combining unit **147** may include, in the payload data of the long packet, the ROI information **120B** in addition to, for example, the pixel data of one line in the compressed image data **147B** as illustrated in FIG. 7 at the time of generating the payload data of the long packet for each line, in the packet region R2 of the transmission data **147A**. That is, the combining unit **147** may include the ROI information **120B** in the payload data of the long packet and send the payload data. At this time, for example, as illustrated in FIG. 7(A) to 7(K), the ROI information **120B** includes, for example, at least one of the data type of each region of interest ROI, the number of regions of interest ROI (the number of ROIs) included in the captured image **111**, the region number (or the priority **115**) of each region of interest ROI, the data length of each region of interest ROI, or the image format of each region of interest ROI. The ROI information **120B** is preferably arranged at an end portion (that is, the head of the payload data of the long packet) on the packet header PH side in the payload data of the long packet.

(59) (Video Reception Device **200**)

(60) Next, the video reception device **200** will be described. FIG. 8 illustrates an example of a configuration of the video reception device **200**. FIG. 9 illustrates an example of a procedure for generating an ROI image **223A** in the video reception device **200**. The video reception device **200**

is a device that receives a signal according to a common standard (for example, the MIPI CSI-2 standard, the MIPI CSI-3 standard, or the MIPI DSI standard) with the video transmission device **100**. The video reception device **200** includes, for example, the reception unit **210** and an information processing unit **220**. The reception unit **210** is a circuit that receives the transmission data **147A** output from the video transmission device **100** via the data lane DL, generates various pieces of data (**214A**, **215A**, and **215B**) by performing predetermined processing on the received transmission data **147A**, and outputs the various pieces of data to the information processing unit **220**. The information processing unit **220** is a circuit that generates the ROI image **223A** on the basis of the various pieces of data (**214A** and **215A**) received from the reception unit **210** and generates a normal image **224A** on the basis of the data (**215B**) received from the reception unit **210**.

(61) The reception unit **210** includes, for example, a header separation unit **211**, a header interpretation unit **212**, a payload separation unit **213**, an EBD interpretation unit **214**, and an ROI data separation unit **215**.

(62) The header separation unit **211** receives the transmission data **147A** from the video transmission device **100** via the data lane DL. That is, the header separation unit **211** receives the transmission data **147A** in which the ROI information **120B** regarding each region of interest ROI in the captured image **111** is included in the embedded data and the image data (compressed image data **120A**) of each region of interest ROI is included in the payload data of the long packet. The header separation unit **211** separates the received transmission data **147A** into the frame header region R1 and the packet region R2. The header interpretation unit **212** specifies the position of the payload data of the long packet included in the packet region R2 on the basis of the data (specifically, the embedded data) included in the frame header region R1. The payload separation unit **213** separates the payload data of the long packet included in the packet region R2 from the packet region R2 on the basis of the position of the payload data of the long packet specified by the header interpretation unit **212**.

(63) The EBD interpretation unit **214** outputs the embedded data as EBD data **214A** to the information processing unit **220**. The EBD interpretation unit **214** further determines whether the image data included in the payload data of the long packet is compressed image data **120A** of image data **116** of an ROI or compressed image data **130A** of normal image data on the basis of the data type included in the embedded data. The EBD interpretation unit **214** outputs the determination result to the ROI data separation unit **215**.

(64) In a case where the image data included in the payload data of the long packet is the compressed image data **120A** of the image data **116** of the ROI, the ROI data separation unit **215** outputs the payload data of the long packet as payload data **215A** to the information processing unit **220** (specifically, an ROI decoding unit **222**). In a case where the image data included in the payload data is the compressed image data **130A** of the normal image data, the ROI data separation unit **215** outputs the payload data of the long packet as payload data **215B** to the information processing unit **220** (specifically, a normal image decoding unit **224**). In a case where the ROI information **120B** is included in the payload data of the long packet, the payload data **215A** includes the ROI information **120B** and pixel data of one line of the compressed image data **147B**.

(65) The information processing unit **220** extracts the ROI information **120B** from the embedded data included in the EBD data **214A**. The information processing unit **220** extracts, on the basis of the ROI information **120B** extracted by the information extraction unit **221**, an image of each region of interest ROI (ROI image **112**) in the captured image **111** from the payload data of the long packet included in the transmission data **147A** received by the reception unit **210**. The information processing unit **220** includes, for example, an information extraction unit **221**, the ROI decoding unit **222**, an ROI image generation unit **223**, and the normal image decoding unit **224**.

(66) The normal image decoding unit **224** decodes the payload data **215B** to generate the normal image **224A**. The ROI decoding unit **222** decodes the compressed image data **147B** included in the

payload data **215A** to generate image data **222A**. The image data **222A** includes one or more transmission images **116**.

(67) The information extraction unit **221** extracts the ROI information **120B** from the embedded data included in the EBD data **214A**. For example, the information extraction unit **221** extracts the number of regions of interest ROI included in the captured image **111**, the region number (or the priority **115**) of each region of interest ROI, the data length of each region of interest ROI, and the image format of each region of interest ROI from the embedded data included in the EBD data **214A**. That is, the transmission data **147A** includes the region number (or the priority **115**) of the region of interest ROI corresponding to each transmission image **116** as determination information that enables determination of from which one of the plurality of transmission images **116** obtained from the transmission data **147A** the image **118** of the region of overlap ROO has been omitted.

(68) The ROI image generation unit **223** detects a region of overlap ROO in which two or more regions of interest ROI overlap each other on the basis of the ROI information **120B** obtained by the information extraction unit **221**.

(69) For example, the information extraction unit **221** extracts the coordinates (for example, the upper-left end coordinates (Xa1,Ya1)), the lengths (for example, the physical region lengths XLa1 and YLa1), and the region number **1** (or the priority **115** (=1)) of the region of interest ROI corresponding to an ROI image **112a1** from the embedded data included in the EBD data **214A**. The information extraction unit **221** further extracts the coordinates (for example, the upper-left end coordinates (Xa2,Ya2)), the lengths (for example, the physical region lengths XLa2 and YLa2), and the region number **2** (or the priority **115** (=2)) of the region of interest ROI corresponding to an ROI image **112a2** from the embedded data included in the EBD data **214A**.

(70) At this time, the ROI image generation unit **223** derives the position information **114** of the region of overlap ROO on the basis of these pieces of extracted information (hereinafter, referred to as “extracted information **221A**”). The ROI image generation unit **223** derives, for example, the coordinates (for example, the upper-left end coordinates (Xb1,Yb1)) and the lengths (for example, the physical region lengths XLb1 and YLb1) of the region of overlap ROO as the position information **114** of the region of overlap ROO described above.

(71) Note that the ROI image generation unit **223** may acquire the ROI information **120B** from the payload data **215A** instead of acquiring the ROI information **120B** from the embedded data included in the EBD data **214A**. In this case, the ROI image generation unit **223** may detect a region of overlap ROO in which two or more regions of interest ROI overlap each other on the basis of the ROI information **120B** included in the payload data **215A**. Furthermore, the ROI image generation unit **223** may extract the extracted information **221A** from the ROI information **120B** included in the payload data **215A**, and may derive the position information **114** of the region of overlap ROO on the basis of the extracted information **221A** extracted in this manner.

(72) The ROI image generation unit **223** further generates images (ROI images **112a1** and **112a2**) of respective regions of interest ROI in the captured image **111** on the basis of image data **222A**, the extracted information **221A**, and the position information **114** of the region of overlap ROO. The ROI image generation unit **223** outputs the generated image as the ROI image **223A**.

(73) [Procedure]

(74) Next, an example of a procedure for data transmission in the video transmission system **1** will be described with reference to FIGS. **3** and **9**.

(75) First, the imaging unit **110** outputs the captured image **111** (digital image data) obtained by imaging to the image processing unit **120**. The ROI cutting unit **121** specifies two regions of interest ROI1 and ROI2 included in the captured image **111** input from the imaging unit **110**. The ROI cutting unit **121** cuts images (ROI images **112a1** and **112a2**) of the respective regions of interest ROI1 and ROI2 from the captured image **111**. The ROI cutting unit **121** assigns the region number **1** as the identifier to the region of interest ROI1, and assigns the region number **2** as the identifier to the region of interest ROI2.

(76) The ROI analysis unit **122** derives position information **113** of a region of interest ROI in the captured image **111** for each region of interest ROI. The ROI analysis unit **122** derives the upper-left end coordinates (Xa1,Ya1) of the region of interest ROI1, the length (XLa1) of the region of interest ROI1 in the X-axis direction, and the length (YLa1) of the region of interest ROI1 in the Y-axis direction on the basis of the region of interest ROI1. The ROI analysis unit **122** derives the upper-left end coordinates (Xa2,Ya2) of the region of interest ROI2, the length (XLa2) of the region of interest ROI2 in the X-axis direction, and the length (YLa2) of the region of interest ROI2 in the Y-axis direction on the basis of the region of interest ROI2.

(77) The overlapping detection unit **123** detects a region of overlap ROO in which the two regions of interest ROI1 and ROI2 overlap each other on the basis of the position information **113** of the two regions of interest ROI1 and ROI2 in the captured image **111**. That is, the overlapping detection unit **123** derives the position information **114** of the region of overlap ROO in the captured image **111**. The overlapping detection unit **123** derives the upper-left end coordinates (Xb1,Yb1) of the region of overlap ROO, the length (XLb1) of the region of overlap ROO in the X-axis direction, and the length (YLb1) of the region of overlap ROO in the Y-axis direction as the position information **114** of the region of overlap ROO in the captured image **111**.

(78) For two regions of interest ROI1 and ROI2, the priority setting unit **124** assigns **1** as the priority **115** to one region of interest ROI1, and assigns **2** as the priority **115** to the other region of interest ROI2.

(79) The encoding unit **125** generates two transmission images **116a1** and **116a2** obtained by omitting an image **118** of a region of overlap ROO from the two ROI images **112a1** and **112a2** obtained from the captured image **111** in such a manner that the image **118** is not included redundantly in the two regions of interest ROI1 and ROI2.

(80) The encoding unit **125** determines from which of the two ROI images **112a1** and **112a2** the image **118** is to be omitted on the basis of the region numbers (or the priorities **115**) of the two regions of interest ROI1 and ROI2. The encoding unit **125** omits the image **118** from the ROI image **112a2** corresponding to the region of interest ROI2 having the larger region number (or higher priority **115**) among the two regions of interest ROI1 and ROI2, thereby generating the transmission image **116a2**. In a case of the ROI image **112a1** corresponding to the region of interest ROI1 having the smaller region number (or lower priority **115**) among the two regions of interest ROI1 and ROI2, the encoding unit **125** uses the ROI image **112a1** itself as the transmission image **116a1**.

(81) The image processing control unit **126** generates ROI information **120B** and frame information **120C**, and transmits the ROI information **120B** and the frame information **120C** to the transmission unit **140**. The transmission unit **140** generates and sends the transmission data **147A** on the basis of various pieces of data (**120A**, **120B**, **120C**, and **130A**) input from the image processing units **120** and **130**. The transmission unit **140** sends the generated transmission data **147A** to the video reception device **200** via the data lane DL.

(82) The reception unit **210** receives the transmission data **147A** output from the video transmission device **100** via the data lane DL. The reception unit **210** performs predetermined processing on the received transmission data **147A** to generate the EBD data **214A** and the payload data **215A**, and outputs the generated data to the information processing unit **220**.

(83) The information extraction unit **221** extracts the ROI information **120B** from the embedded data included in the EBD data **214A**. The information extraction unit **221** extracts the coordinates (for example, the upper-left end coordinates (Xa1,Ya1)), the lengths (for example, the physical region lengths XLa1 and YLa1), and the region number **1** (or the priority **115** (=1)) of the region of interest ROI corresponding to an ROI image **112a1** from the embedded data included in the EBD data **214A**. The information extraction unit **221** further extracts the coordinates (for example, the upper-left end coordinates (Xa2,Ya2)), the lengths (for example, the physical region lengths XLa2 and YLa2), and the region number **2** (or the priority **115** (=2)) of the region of interest ROI

corresponding to the ROI image **112a2**. The ROI decoding unit **222** decodes the compressed image data **147B** included in the payload data **215A** to generate image data **222A**.

(84) The ROI image generation unit **223** derives the position information **114** of the region of overlap ROO on the basis of these pieces of extracted information (extracted information **221A**). The ROI image generation unit **223** derives, for example, the coordinates (for example, the upper-left end coordinates (Xb1,Yb1)) and the lengths (for example, the physical region lengths XLb1 and YLb1) of the region of overlap ROO as the position information **114** of the region of overlap ROO described above. The ROI image generation unit **223** further generates images (ROI images **112a1** and **112a2**) of respective regions of interest ROI in the captured image **111** on the basis of image data **222A**, the extracted information **221A**, and the position information **114** of the region of overlap ROO.

(85) [Effects]

(86) Next, effects of the video transmission system **1** according to the present embodiment will be described.

(87) In recent years, transmission of a large amount of massive data is increasing. A large load is likely to be applied to a transmission system, and in the worst case, there is a possibility that the transmission system is down and data transmission cannot be performed.

(88) Conventionally, an object to be imaged is specified and only an image of a cut part of the specified object is transmitted instead of, for example, transmitting all captured images in order to prevent the transmission system from being down.

(89) Meanwhile, the MIPI CSI-2 may be used as a method used for transmission from an image sensor to an application processor. In a case where an attempt is made to transmit an ROI using this method, the transmission of the ROI is not easy due to various restrictions in some cases.

(90) On the other hand, in the present embodiment, the ROI information **120B** regarding each region of interest ROI in the captured image **111** is sent as the embedded data, and the image data of each region of interest ROI is sent as the payload data of the long packet. As a result, the device (video reception device **200**) that has received the transmission data **147A** transmitted from the video transmission device **100** can easily extract the image data (ROI image **112**) of each region of interest ROI from the transmission data **147A**. As a result, the region of interest ROI can be sent even under various constraints.

(91) Furthermore, in the present embodiment, the image data (compressed image data **120A**) of each region of interest ROI is sent through a common virtual channel. As a result, a plurality of ROI images **112** can be sent in the same packet, and it is thus not necessary to enter the LP mode while sending the plurality of ROI images **112**, as a result of which high transmission efficiency can be obtained.

(92) Furthermore, in the present embodiment, the data type of each region of interest ROI is included in the packet header PH of the payload data of the long packet and sent. As a result, the data type of each region of interest ROI can be obtained only by accessing the packet header PH of the payload data of the long packet without accessing the embedded data. Therefore, a processing speed in the video reception device **200** can be increased, as a result of which high transmission efficiency can be obtained.

(93) Furthermore, in the present embodiment, in a case where the ROI information **120B** is included in the payload data of the long packet and sent, the ROI information **120B** can be obtained only by accessing the payload data of the long packet without accessing the embedded data. Therefore, a processing speed in the video reception device **200** can be increased, as a result of which high transmission efficiency can be obtained.

(94) Furthermore, in the present embodiment, the ROI information **120B** regarding each region of interest ROI is extracted from the embedded data included in the transmission data **147A**, and the image (ROI image **112**) of each region of interest ROI is extracted from the payload data of the long packet included in the transmission data **147A** on the basis of the extracted ROI information

120B. As a result, the image (ROI image **112**) of each region of interest ROI can be easily extracted from the transmission data **147A**. As a result, the region of interest ROI can be sent even under various constraints.

2. Underlying Technology 2 of Present Disclosure

(95) A technology for transmitting some (non-rectangular) regions of interest (ROIs) cut from a captured image will be described with reference to FIGS. **1** to **9** and FIGS. **10** to **12**. That is, a technology for transmitting and receiving an image of an object to be captured having a shape other than a square shape (rectangular shape) will be described. FIG. **10** is a diagram schematically illustrating a region in which a specified object is arranged in the captured image **111**. Note that FIG. **10** schematically illustrates the captured image **111** captured in an imaging region including 15 rows×23 columns of imaging elements in order to facilitate understanding. FIG. **11** is a diagram illustrating an example of an ROI set for a specified object.

(96) In Underlying Technology 2, similarly to Underlying Technology 1, a case where predetermined processing is performed on the captured image **111** input from the imaging unit **110** in a case where a control signal for instructing cutting of an ROI is input from the video reception device **200** to the video transmission device **100** via the camera control interface CCI will be described. However, Underlying Technology 2 can also be applied to a case where the video transmission device **100**, that is, a transmission side, specifies the coordinates of an ROI to be cut. In this case, for example, the transmission side is configured to receive information such as a “person” or an “object” to be acquired in the ROI sent from a reception side, and determine and specify the coordinates of the cutting.

(97) The control signal for instructing cutting of an ROI is input from the video reception device **200** via the camera control interface CCI. As a result, as illustrated in FIG. **10**, the ROI cutting unit **121** specifies four objects **1** to **4** to be captured included in the captured image **111**. The object **1** has, for example, a rectangular shape that occupies a part of the upper-left region in the captured image **111**. The object **2** occupies, for example, a partial region on the right side of the object **1** in the captured image **111**, and has a shape in which opposite upper side corners of a rectangle and a part of the lower edge of the rectangle are missing. The object **3** occupies, for example, a partial region below the object **2** in the captured image **111**, and has a shape in which four corners of a rectangle are missing. The object **4** occupies, for example, a partial region under the object **3** in the captured image **111**, and has a shape in which opposite upper side corners of a rectangle are missing. The object **3** and the object **4** partially overlap each other.

(98) As illustrated in FIG. **11**, the ROI cutting unit **121** (see FIG. **2**) sets the smallest rectangles including the specified objects **1** to **4** as regions of interest ROI1 to ROI4, respectively. The ROI cutting unit **121** sets the region of interest ROI1 for the object **1** and cuts an ROI image **112a1**. In addition, the ROI cutting unit **121** sets the region of interest ROI2 for the object **2** and cuts an ROI image **112a2**. In addition, the ROI cutting unit **121** sets the region of interest ROI3 for the object **3** and cuts an ROI image **112a3**. Moreover, the ROI cutting unit **121** sets the region of interest ROI4 for the object **4** and cuts an ROI image **112a4**.

(99) The ROI cutting unit **121** stores the region of interest ROI1 and the region number “1” assigned to the region of interest ROI1 in the storage unit in association with each other. The ROI cutting unit **121** stores the region of interest ROI2 and the region number “2” assigned to the region of interest ROI2 in the storage unit in association with each other. The ROI cutting unit **121** stores the region of interest ROI3 and the region number “3” assigned to the region of interest ROI3 in the storage unit in association with each other. The ROI cutting unit **121** stores the region of interest ROI4 and the region number “4” assigned to the region of interest ROI4 in the storage unit in association with each other.

(100) The ROI analysis unit **122** (see FIG. **2**) derives the position information of each of the regions of interest ROI1 to ROI4. The ROI analysis unit **122** derives, for example, a physical region length XLa1 in the X-axis direction and a physical region length YLa1 in the Y-axis

direction as the position information of the region of interest ROI1. The ROI analysis unit **122** derives, for example, a physical region length XLa2 in the X-axis direction and a physical region length YLa2 in the Y-axis direction as the position information of the region of interest ROI2. The ROI analysis unit **122** derives, for example, a physical region length XLa3 in the X-axis direction and a physical region length YLa3 in the Y-axis direction as the position information of the region of interest ROI3. The ROI analysis unit **122** derives, for example, a physical region length XLa4 in the X-axis direction and a physical region length YLa4 in the Y-axis direction as the position information of the region of interest ROI4. The ROI analysis unit **122** may further derive, for example, an output region length XLc of a region of interest ROI in the X-axis direction and an output region length YLc of a region of interest ROI in the Y-axis direction as the position information **113** for each region of interest ROI.

(101) The ROI analysis unit **122** derives the lengths of each region of interest ROI in the X-axis direction and the Y-axis direction, thereby deriving the size and the total data amount of each of the regions of interest ROI1 to ROI4 as information for the subsequent stage. As a result, the video reception device **200** corresponding to the subsequent stage can secure a memory region.

(102) The ROI analysis unit **122** is configured to derive the position information of the ROI images **112a1** to **112a4** instead of the position information of the regions of interest ROI in a case where the shapes of the object to be captured and the region of interest do not match. The ROI analysis unit **122** derives the left end coordinates (xn,yn) of each row and a physical region length XLn in the X-axis direction as the position information of the ROI images **112a1** to **112a4**. In addition, in a case where the ROI images are separated as in the second row of the ROI image **112a2**, the ROI analysis unit **122** derives the position information of each of the separated portions. The ROI analysis unit **122** stores the region numbers of the regions of interest ROI1 to ROI4 and the position information of the ROI images **112a1** to **112a4** in the storage unit in association with each other.

(103) Furthermore, the ROI analysis unit **122** may derive, in addition to the position information, for example, sensing information, exposure information, gain information, an AD word length, an image format, and the like for each of the regions of interest ROI1 to ROI4, and store the derived information in the storage unit in association with the region number.

(104) In a case where the object to be captured has a rectangular shape, the overlapping detection unit **123** (see FIG. 2) derives a region where the ROI images overlap each other as a region of overlap, instead of a region where the regions of interest overlap each other. As illustrated in FIG. **11**, the overlapping detection unit **123** derives a region of overlap ROO as a region where the ROI image **112a3** and the ROI image **123a4** overlap each other. The overlapping detection unit **123** stores the derived region of overlap ROO in the storage unit in association with the position information of each of the regions of interest ROI3 and ROI4.

(105) The priority setting unit **124** (see FIG. 2) assigns the priority “1” to the region of interest ROI1, and stores the priority (1) in the storage unit in association with the region of interest ROI1. The priority setting unit **124** assigns the priority “2” lower than the priority “1” to the region of interest ROI2, and stores the priority (2) in the storage unit in association with the region of interest ROI2. The priority setting unit **124** assigns the priority “3” lower than the priority “2” to the region of interest ROI3, and stores the priority (3) in the storage unit in association with the region of interest ROI3. The priority setting unit **124** assigns the priority “4” lower than the priority “3” to the region of interest ROI4, and stores the priority (4) in the storage unit in association with the region of interest ROI4.

(106) The encoding unit **125** (see FIG. 2) generates a transmission image for each of the ROI images **112a1** to **112a4**. Since the region of interest ROI4 is lower in priority than the region of interest ROI3, the encoding unit **125** generates the transmission image by omitting the region of overlap ROO from the ROI image **112a4**.

(107) The image processing control unit **126** (see FIG. 2) generates ROI information and frame

information, and transmits the ROI information and the frame information to the transmission unit **140** (see FIG. 2). The ROI information includes, for example, the position information of each of the ROI images **112a1** to **112a4**. The ROI information further includes information similar to that in the case where the object to be captured has a rectangular shape (for example, the data type of each of the regions of interest ROI1 to ROI4, the number of the regions of interest ROI1 to ROI4 included in the captured image **111**, the region numbers and priorities of the regions of interest ROI1 to ROI4, and the like). The frame information includes, for example, information similar to that in the case where the object to be imaged has a rectangular shape, such as the data types of the regions of interest ROI1 to ROI4.

(108) The LINK control unit **141** provided in the transmission unit **140** (see FIG. 2) outputs the frame information and the ROI information input from the image processing control unit **126** to the ECC generation unit **142** and the PH generation unit **143** (see FIG. 2) for each line. The ECC generation unit **142** generates an error correction code of one line on the basis of data (for example, a virtual channel number, the data type of each of the regions of interest ROI1 to ROI4, the payload length of each line, and the like) of the line in the frame information, for example. The ECC generation unit **142** outputs the generated error correction code to the PH generation unit **143**, for example. The PH generation unit **143** generates the packet header PH (see FIG. 4) for each line by using, for example, the frame information and the error correction code generated by the ECC generation unit **142**.

(109) The EBD buffer **144** (see FIG. 2) primarily stores the ROI information and outputs the ROI information to the combining unit **147** (see FIG. 2) as embedded data at a predetermined timing.

(110) The ROI data buffer **145** (see FIG. 2) primarily stores compressed image data input from the encoding unit **125**, and outputs, in a case where a control signal for instructing cutting of an ROI is input from the video reception device **200** via the camera control interface CCI, outputs the compressed image data **120A** to the combining unit **147** as payload data of a long packet, for example.

(111) In a case where a control signal for instructing cutting of an ROI is input from the video reception device **200** via the camera control interface CCI, the combining unit **147** generates transmission data **147A** on the basis of various pieces of input data (the packet header PH, the ROI information, and the compressed image data that is input from the encoding unit **125** via the ROI data buffer **145**). The combining unit **147** outputs the generated transmission data **147A** to the video reception device **200** via the data lane DL. That is, the combining unit **147** includes, in the packet header PH of the payload data of the long packet, the data type of each of the regions of interest ROI1 to ROI4 and sends the packet. In addition, the combining unit **147** sends the image data (compressed image data) of each of the regions of interest ROI1 to ROI4 through a common virtual channel.

(112) In a case where the object to be captured does not have rectangular shape, the position information of each of the ROI images **112a1** to **112a4** is included in the packet header PH or the payload data of the long packet. The position information of each of the ROI images **112a1** to **112a4** is included in the packet header PH by the PH generation unit **143**. Meanwhile, the position information of each of the ROI images **112a1** to **112a4** is included in the payload data of the long packet by the combining unit **147**.

(113) FIG. 12 is a diagram illustrating a configuration example of the transmission data **147A** in which the position information of each of the ROI images **112a1** to **112a4** is included in the payload data of the long packet. As illustrated in FIG. 12, the transmission data **147A** includes, for example, a frame header region R1 and a packet region R2. Note that FIG. 12 illustrates contents of the frame header region R1 in detail. Furthermore, in FIG. 12, the low power modes LP are omitted.

(114) The frame header region R1 includes, for example, a frame number F1 as the identifier of the transmission data **147A**. The frame header region R1 includes information regarding compressed image data included in the packet region R2. The frame header region R1 includes, for example,

the number of pieces of compressed image data (the number of ROIs) and information regarding each of the ROI images **112a1** to **112a4** corresponding to the respective compressed image data (ROI information). The ROI information includes a region number, a physical region length, a rectangular output region size, a priority, exposure information, gain information, an AD word length, and an image format. The physical region length is the maximum length of an ROI image, and the rectangular output region size is the size of a region of interest ROI.

(115) “Info” illustrated in FIG. **12** indicates region information stored in the payload of the long packet. The position information of each of the ROI images **112a1** to **112a4** is stored in “Info”, for example. The position information of each of the ROI images **112a1** to **112a4** is stored in the head portion of the payload of the long packet. In a case where the physical region lengths of the respective consecutive pixel rows included in the ROI image in the X-axis direction are the same and the ROI images having different region numbers are not included in the respective pixel rows, the region information “info” does not have to be stored in the payload of the long packet including the image data of the second and subsequent pixel rows among the respective pixel rows. In this example, in the ROI image **112a1**, the physical region lengths of the first to fourth consecutive pixel rows among all the pixel rows in the X-axis direction are the same, and the ROI images having different region numbers are not included in the first to fourth pixel rows. Therefore, the region information “info” is not stored in the payload of each long packet including the image data of the second to fourth pixel rows corresponding to the second and subsequent pixel rows among the first to fourth consecutive pixel rows included in the ROI image **112a1**. Furthermore, in this example, in the ROI image **112a4**, the physical region lengths of the second and third consecutive pixel rows among all the pixel rows in the X-axis direction are the same, and the ROI images having different region numbers are not included in the second and third pixel rows. Therefore, the region information “info” is not stored in the payload of the long packet including the image data of the third pixel row corresponding to the second and subsequent pixel rows among the second and third consecutive pixel rows included in the ROI image **112a4**. Note that even in a case where the physical region lengths in the X-axis direction are the same and the ROI images having different region numbers are not included in each pixel row, the region information “info” may be stored in the payload of each row.

(116) For example, the combining unit **147** divides and arranges compressed image data generated by compressing each of the ROI images **112a1** to **112a4** for each pixel row in the packet region R2 of the transmission data **147A**. “1” illustrated in FIG. **12** indicates the compressed image data of the ROI image **112a1** stored in the payload of the long packet. “2” illustrated in FIG. **12** indicates the compressed image data of the ROI image **112a2** stored in the payload of the long packet. “3” illustrated in FIG. **12** indicates the compressed image data of the ROI image **112a3**. “4” illustrated in FIG. **12** indicates the compressed image data of the ROI image **112a4** stored in the payload of the long packet. Note that, in FIG. **12**, each piece of compressed image data is illustrated in a divided manner for easy understanding, but there is no division in data stored in a payload of a long packet. Compressed image data **112b** corresponding to the image of the region of overlap ROO is not redundantly included in the packet region R2 of the transmission data **147A**. Further, for example, the combining unit **147** omits a pixel row of the captured image **111** that does not correspond to each transmission image in the packet region R2 of the transmission data **147A**. Therefore, the packet region R2 of the transmission data **147A** does not include a pixel row of the captured image **111** that does not correspond to each transmission image.

(117) Next, an operation of the video reception device **200** in a case where the transmission data **147A** is received will be described.

(118) The header separation unit **211** (see FIG. **8**) provided in the reception unit **210** receives the transmission data **147A** from the video transmission device **100** via the data lane DL. That is, the header separation unit **211** receives the transmission data **147A** in which the ROI information regarding each of the regions of interest ROI1 to ROI4 in the captured image **111** is included in the

embedded data and the image data (compressed image data) of each of the regions of interest ROI1 to ROI4 is included in the payload data of the long packet. The header separation unit **211** separates the received transmission data **147A** into the frame header region R1 and the packet region R2.

(119) The header interpretation unit **212** (see FIG. 8) specifies the position of the payload data of the long packet included in the packet region R2 on the basis of the data (specifically, the embedded data) included in the frame header region R1.

(120) The payload separation unit **213** (see FIG. 8) separates the payload data of the long packet included in the packet region R2 from the packet region R2 on the basis of the position of the payload data of the long packet specified by the header interpretation unit **212**.

(121) The EBD interpretation unit **214** outputs the embedded data as EBD data to the information processing unit **220** (see FIG. 8). The EBD interpretation unit **214** further determines whether the image data included in the payload data of the long packet is compressed image data of image data **116** of an ROI or compressed image data of normal image data on the basis of the data type included in the embedded data. The EBD interpretation unit **214** outputs the determination result to the ROI data separation unit **215** (see FIG. 8).

(122) In a case where image data of an ROI as the image data included in the payload data of the long packet is input, the ROI data separation unit **215** outputs the payload data of the long packet as the payload data to the information processing unit **220** (specifically, the ROI decoding unit **222** (see FIG. 8)). The payload data of the long packet including the ROI information includes pixel data of one line of the ROI information and the compressed image data.

(123) The information extraction unit **221** (see FIG. 8) provided in the information processing unit **220** extracts the number of regions of interest ROI1 to ROI4 included in the captured image **111** (four in this example), the region numbers **1** to **4** and the priorities **1** to **4** of the regions of interest ROI1 to ROI4, the data length of each of the regions of interest ROI1 to ROI4, and the image format of each of the regions of interest ROI1 to ROI4 from the embedded data included in the EBD data input from the EBD interpretation unit **214**. Moreover, the information extraction unit **221** extracts the position information of each of the ROI images **112a1** to **112a4** from the embedded data.

(124) The ROI decoding unit **222** decodes the compressed image data **147B** included in the payload data, extracts the position information of each of the ROI images **112a1** to **112a4**, and generates the image data (generated from the transmission image). For example, in a case where the payload data corresponding to the sixth pixel row is input, the ROI decoding unit **222** extracts one piece of position information of the ROI image **112a1** and two pieces of position information of the ROI image **112a2** from the payload data, and generates the image data (transmission image) of each of the ROI images **112a1** and **112b1** corresponding to the sixth pixel row.

(125) For example, in a case where the payload data corresponding to the tenth pixel row is input, the ROI decoding unit **222** extracts one piece of position information of the ROI image **112a3** and one piece of position information of the ROI image **112a4** from the payload data, and generates the image data (transmission image) of each of the ROI images **112a3** and **112b4**.

(126) The ROI image generation unit **223** (see FIG. 8) generates the ROI images **112a1** to **112a4** of the regions of interest ROI1 to ROI4 in the captured image **111** on the basis of the ROI information obtained by the information extraction unit **221**, the position information of each of the ROI images **112a1** to **112a4** extracted by the ROI decoding unit **222**, and the transmission image generated by the ROI decoding unit **222**. For example, in a case where one piece of position information of the ROI image **112a1** and two pieces of position information of the ROI image **112a2** extracted from the payload data corresponding to the sixth pixel row, and the transmission images thereof are input, the ROI image generation unit **223** generates the ROI image **112a1** corresponding to five pixels and extending in the X-axis direction, the ROI image **112a2** corresponding to four pixels and extending in the X-axis direction at a position separated from the ROI image **112a1** by five pixels, and the ROI image **112a2** corresponding to two pixels and extending in the X-axis direction at a

position separated from the ROI image **112a2** by two pixels (see FIG. **10**).

(127) In addition, the ROI image generation unit **223** detects the region of overlap ROO in which the region of interest ROI3 and the region of interest ROI4 overlap each other on the basis of the ROI information obtained by the information extraction unit **221**. The ROI image generation unit **223** generates, on the basis of the detected region of overlap ROO, the position information of each of the ROI images **112a3** and **112a4** extracted from the payload data corresponding to the tenth pixel row, and the transmission image, the ROI image **112a3** corresponding to four pixels and extending in the X-axis direction and the ROI image **112a4** corresponding to three pixels and extending in the X-axis direction in a state where one pixel overlaps with the ROI image **112a3** (see FIG. **10**).

(128) The ROI image generation unit **223** outputs the generated image as an ROI image to a device in the subsequent stage (not illustrated).

(129) In this manner, the video transmission device **100** and the video reception device **200** can transmit and receive an ROI image even in a case where an object to be captured has a shape other than a rectangular shape.

3. Principle of Restoration Processing in Embodiment of Present Disclosure

(130) Next, the principle of restoration processing in an embodiment of the present disclosure will be described with reference to FIGS. **13** to **17**. The restoration processing in the embodiment of the present disclosure (hereinafter, referred to as the present embodiment) is processing of restoring image data of a region of interest (ROI) input from a video transmission device to a video reception device so as to be displayable on a predetermined display device. For example, various types of processing (for example, writing in a frame memory, outputting image data of a region of interest to a predetermined display device, and the like) related to display of the image data of the region of interest can be efficiently performed by executing the restoration processing in the video reception device and restoring the image data of the region of interest.

(131) 3-1. Sending of Image Data of Region of Interest in Video Transmission Device

(132) First, as a pre-stage of the restoration processing, processing until the image data of the region of interest is input to the video reception device will be described. As described above, image data of a region of interest cut from a captured image is sent as payload data from the video transmission device. FIG. **13** is a view schematically illustrating an example of a captured image obtained by the imaging unit of the video transmission device. In FIG. **13**, a captured image α is illustrated in association with pixel coordinates. In this example, a plurality of (three in this example) regions of interest (ROI0, ROI1, and ROI2) is set in the captured image α . Hereinafter, the restoration processing will be described using the regions of interest ROI0 to ROI2 illustrated in FIG. **13** as a specific example.

(133) In this example, a coordinate system of the captured image α is an XY orthogonal coordinate system formed in the X-axis direction (horizontal direction) and the Y-axis direction (vertical direction) of the captured image α with a pixel at an upper-left end portion as an origin α_o . Furthermore, as illustrated in FIG. **13**, the coordinates of a lower-right end portion (end point) α_e of the captured image α are (1759,989). That is, the captured image α of this example is a rectangular image having a width (a length in the X-axis direction) of 1760 pixels and a height (a length in the Y-axis direction) of 990 pixels. In this example, for example, it is assumed that three regions of interest (ROI0, ROI1, and ROI2) set on the basis of an instruction by a control signal from the video reception device are cut from the captured image α . Each of the regions of interest ROI0 to ROI2 is a rectangular region. In addition, each of the regions of interest ROI0 to ROI2 is arranged at a predetermined interval without overlapping each other. Further, in the captured image α , a region where the region of interest ROI is not arranged is set as a non-region of interest OE.

(134) FIG. **14** is a diagram illustrating coordinates and an image size of each of three regions of interest (ROI1, ROI2, and ROI3) included in the captured image α , in the captured image α . As for the coordinates of the regions of interest, coordinates closest to the origin α_o of the captured

image α are upper-left end coordinates (start point coordinates), and coordinates farthest from the origin α_o are lower-right end coordinates (end point coordinates). Furthermore, the size of the region of interest includes the length in the X-axis direction indicating the width of the region of interest and the length in the Y-axis direction indicating the height of the region of interest. The arrangement state in the captured image, that is, the position in the captured image and the image size, can be obtained by using at least the start point coordinates, the X-axis direction length, and the Y-axis direction length of the rectangular region of interest.

(135) As illustrated in FIG. 14, in this example, the region of interest ROI0 is arranged at a position where the start point coordinates are the start point X coordinate $i0=520$ and the start point Y coordinate $j0=300$, and the end point coordinates are the end point X coordinate $k0=919$ and the end point Y coordinate $l0=899$ in the captured image α . In addition, the region of interest ROI1 is arranged at a coordinate position where the start point coordinates are the start point X coordinate $i1=1040$ and the start point Y coordinate $j1=140$, and the end point coordinates are the end point X coordinate $k1=1439$ and the end point Y coordinate $l1=739$. In addition, the region of interest ROI2 is arranged at a coordinate position where the start point coordinates are the start point X coordinate $i2=100$ and the start point Y coordinate $j2=100$, and the end point coordinates are the end point X coordinate $k2=499$ and the end point Y coordinate $l2=699$. Furthermore, in this example, each of the regions of interest ROI0 to ROI2 has the length of 400 pixels in the X-axis direction and the length of 600 pixels in the Y-axis direction.

(136) As illustrated in FIGS. 13 and 14, in this example, among the start point coordinates of the regions of interest ROI0 to ROI2, the X coordinate $i2$ (100) of the region of interest ROI2 is closest to the origin α_o , followed by the start point X coordinate $i0$ (520) of the region of interest ROI0 and the start point X coordinate $i1$ (1040) of ROI1. Therefore, the relative positions of the regions of interest ROI0 to ROI2 in the X-axis direction in the captured image α are arranged in the order of the region of interest ROI2, the region of interest ROI0, and the region of interest ROI1. Furthermore, in this example, among the Y coordinates of the start point coordinates of the regions of interest ROI0 to ROI2, the Y coordinate of the region of interest ROI2 is closest to the origin α_o , followed by the Y coordinate of the region of interest ROI1 and the Y coordinate of the region of interest ROI0. Therefore, as illustrated in FIG. 13, the relative positions of the regions of interest ROI0 to ROI2 in the Y-axis direction in the captured image α are arranged in the order of the region of interest ROI2, the region of interest ROI1, and the region of interest ROI0.

(137) In the video transmission device, for example, in a case where a control signal for instructing cutting of ROI0 to ROI2 illustrated in FIG. 13 is input from the video reception device, a cutting position at which an image is cut from an imaging region of the imaging unit 31, that is, the start point coordinates and the image size (the lengths in the X-axis direction and the Y-axis direction) of each of the regions of interest ROI0 to ROI2 are determined. The determined start point coordinates and image size are included in the ROI information as position information and size information, respectively. That is, the ROI information includes the position information and the size information corresponding to a predetermined number of regions of interest (ROIs) cut from the captured image. The ROI information is set as the embedded data in the frame header region of the transmission data and sent from the video transmission device.

(138) The ROI information set in the embedded data may be limited by a transmission standard specification or the like. In the present embodiment, the ROI information is generated by using the start point coordinates and the image size as the position information and the size information, respectively, as the minimum data that enables determination of the position and the size of the region of interest in the captured image in the video reception device. In the present embodiment, the end point coordinates indicating the lower-right end of the region of interest are not included in the ROI information, but in FIG. 14, the end point coordinates are displayed together with the start point coordinates for easy understanding. Note that the present disclosure may be configured to include the end point coordinates of the region of interest as the position information in the ROI

information. The position information in the present disclosure may be coordinates indicating any one of four corners in a case where the region of interest has a rectangular shape.

(139) FIG. 15 is a diagram illustrating an example of the payload data including the image data of each of the regions of interest ROI0 to ROI2. The payload data is set in a packet region of the transmission data and sent from the video transmission device. In the present embodiment, in each line of the payload data, the image data of the region of interest is stored in units of pixel rows, that is, in units of Y-axis coordinates in the captured image.

(140) In the present embodiment, the payload data that stores the region of interest includes only the image data of the region of interest in the captured image, and does not store the image data of the non-region of interest OE. Therefore, a pixel row including only the image data of the non-region of interest OE in the captured image is not included in the payload data. Furthermore, the image data of the region of interest in the payload data is stored in the payload data in a state of being left aligned adjacent to a payload header PH (corresponding to the “packet header PH” in Underlying Technologies 1 and 2 described above). As illustrated in FIG. 15, the image data of the region of interest in the captured image is stored in the payload data in a state of being aligned in the upper-left direction, that is, a direction toward the origin (the origin α_o in this example) of the captured image. In this example, the respective pieces of image data of the regions of interest ROI0 to ROI2 correspond to pixel rows corresponding to 800 Y-axis coordinates in the captured image α . Therefore, in this example, the payload data that stores the respective pieces of image data of the regions of interest ROI0 to ROI2 includes total 800 lines including lines PL1 to PL800 in order from the top and forms a data group that stores pixel rows corresponding to 800 Y-axis coordinates in the captured image α .

(141) In this example, among the three regions of interest (ROIs) in the captured image α , a region having the smallest Y coordinate of the start point coordinates is the region of interest ROI2. Therefore, as illustrated in FIG. 15, the image data (image data ROI2(L1) in this example) of the first row among the pixel rows of the region of interest ROI2 is stored in the left-aligned manner in the line PL1 which is the top row of the payload data. Furthermore, in this example, a region having the largest Y coordinate of the start point coordinates among the three regions of interest in the captured image α is the region of interest ROI0. Therefore, as illustrated in FIG. 15, the image data (image data ROI0(L600) in this example) of the last row among the pixel rows of the region of interest ROI0 is stored in the left-aligned manner in the line PL800 which is the last row of the payload data.

(142) As described above, the pieces of image data of the regions of interest ROI0 to ROI2 in the captured image α of this example are left-aligned in order from the image data of the region having the smaller Y coordinate (Y coordinates j_0 to j_2) of the start point coordinates, and are stored in each line of the payload data. For example, pieces of image data ROI2(L1) to ROI2(L40) corresponding to the Y coordinate j_2 of the start point coordinates of the region of interest ROI2 from the first pixel row (Y coordinate=100) to the 140-th pixel row (Y coordinate=139) are stored in the left-aligned manner in the lines PL1 to PL40 of the payload data illustrated in FIG. 15.

(143) Furthermore, as described above, the image data of the region of interest is stored in each line of the payload data in units of Y-axis coordinates (in units of pixel rows) in the captured image. The image data of the region of interest in units of pixel rows stored in the payload data is referred to as ROI pixel row data. The ROI pixel row data includes a packet group including compressed image data of the region of interest. In a case where a plurality of regions of interest is arranged at the same Y coordinate in the captured image, a plurality of packet groups each including image data of each of the plurality of regions of interest I is continuously stored in the left-aligned manner in the ROI pixel row data.

(144) Furthermore, for example, as illustrated in FIG. 13, the region of interest ROI2 also exists at the same Y coordinate as the Y coordinate $i_1(140)$ of the start point coordinates of the region of interest ROI1 in the captured image α . Therefore, as illustrated in FIG. 15, as the image data of the

pixel row corresponding to the Y coordinate **140** in the captured image α , image data **ROI2(L41)** of the 41-th pixel row of the region of interest **ROI2** and image data **ROI1(L1)** of the first image row of the region of interest **ROI1** are stored in the left-aligned manner in this order in the line **PL41** of the payload data in this example. Similarly, the pieces of image data of the two regions of interest **ROI2** and **ROI1** are stored in the left-aligned manner in this order also from the line **PL42** (not illustrated) to the line **PL200** after the line **PL41** of the payload data.

(145) Furthermore, for example, as illustrated in FIG. **13**, the regions of interest **ROI2** and **ROI1** also exist at the same Y coordinate as the Y coordinate **i1(300)** of the start point coordinates of the region of interest **ROI0** in the captured image α . Therefore, as illustrated in FIG. **15**, as the image data of the pixel row corresponding to the Y coordinate **300** in the captured image α , image data **ROI2(L201)** of the 201-th pixel row of the region of interest **ROI2**, image data **ROI0(L1)** of the first pixel row of the region of interest **ROI0**, and image data **ROI1(L161)** of the 161-th image row of the region of interest **ROI1** are stored in the left-aligned manner in this order in the line **PL201** of the payload data in this example. Similarly, the pieces of image data of the three regions of interest **ROI2**, **ROI0**, and **ROI1** are stored in the left-aligned manner in this order also from the line **PL202** (not illustrated) to the line **PL600** after the line **PL201** of the payload data.

(146) In addition, the payload data line **PL600** includes image data **ROI2(L600)** of the 600-th pixel row, which is the last row of the region of interest **ROI2**, as the image data of the Y coordinate **l2** (Y coordinate=699 in the captured image α) of the end point coordinates of the region of interest **ROI2**. Then, the pieces of image data of the two regions of interest **ROI0** and **ROI1** are stored in the left-aligned manner in this order in the lines **PL601** to **PL640** of the payload data. In addition, the payload data line **PL640** includes image data **ROI1(L600)** of the 600-th pixel row, which is the last row of the region of interest **ROI1**, as the image data of the Y coordinate **l1** (Y coordinate=739 in the captured image α) of the end point coordinates of the region of interest **ROI1**. Then, the image data of one region of interest **ROI0** is stored in the left-aligned manner in this order in the lines **PL641** to **PL800** of the payload data. The payload data line **PL800** includes image data **ROI0(L600)** of the 600-th pixel row, which is the last row of the region of interest **ROI0**, as the image data of the Y coordinate **l0** (Y coordinate=899 in the captured image α) of the end point coordinates of the region of interest **ROI0**. In this way, the pieces of payload data corresponding to 800 lines including the pieces of image data of the regions of interest **ROI0** to **ROI2** of this example are generated.

(147) In this way, payload data in which pieces of image data of a predetermined number of (three in this example) regions of interest (ROIs) cut from a predetermined captured image (the captured image α in this example) are stored is sent from the video transmission device to the video reception device together with embedded data including ROI information corresponding to the predetermined number of cut ROIs.

(148) 3-2. Restoration Processing in Video Reception Device

(149) In the present embodiment, once transmission data including image data of a region of interest is received, the video reception device performs the restoration processing on the image data of the region of interest included in the received transmission data. The transmission data including the image data is communicated between the video transmission device and the video reception device in units of image data frames. For example, data in each of the header region and the packet region of the image data frame is transmitted to the video reception device in units of transactions. The video reception device receives a packet (start of frame (SOF)) indicating a start of the image data frame to perform various types of processing related to the image data included in the transmission data, and the restoration processing is also an example thereof.

(150) In the restoration processing in the present embodiment, ROI information corresponding to the region of interest is extracted from the received transmission data, and ROI restoration information used for the restoration processing is generated on the basis of the extracted ROI information. The image data of the region of interest is decoded from the compressed state in the

video transmission device, restored so as to be displayable on the basis of the ROI restoration information, and written in the frame memory.

(151) The image data of the region of interest is restored so as to be displayable (displayable state) on a predetermined display device on the basis of the ROI information corresponding to a predetermined number of regions of interest extracted from the embedded data by performing the restoration processing. As a result, the image data of the region of interest cut at an arbitrary position and image size in the captured image can be efficiently displayed on the display device. Hereinafter, for easy understanding, the restoration processing will be described separately for an information extraction process and a writing process. The information extraction process is a process of generating the ROI restoration information used for the restoration processing from the extracted ROI information, and the writing process is a process of writing the image data of the region of interest in the frame memory on the basis of the ROI restoration information.

(152) [Information Extraction Process]

(153) In the information extraction process, first, the embedded data in the transmission data is analyzed, and the ROI information corresponding to the predetermined number of regions of interest (ROIs) cut from the captured image is extracted from the embedded data. In the information extraction process, the position information and size information of the region of interest are extracted as the ROI information from the embedded data.

(154) In the present embodiment, the position information is information indicating the position of the region of interest in the captured image, and corresponds to, for example, start point coordinates (X coordinate and Y coordinate) indicating the upper-left end portion of the region of interest. Furthermore, in the present embodiment, the size information is information indicating the size (the number of pixels) of the region of interest in the captured image, and corresponds to, for example, the length of the region of interest in the X-axis direction and the length of the region of interest in the Y-axis direction. Therefore, in the information extraction process in the present embodiment, the start point coordinates of the region of interest are extracted as the position information in the ROI information. In addition, the length of the region of interest in the X-axis direction and the length of the region of interest in the Y-axis direction are extracted as the size information in the ROI information.

(155) In this example, as illustrated in FIG. 13, three regions of interest ROI0 to ROI2 are cut from the captured image α . Therefore, in this example, in the information extraction process, the start point coordinates of each of the regions of interest ROI0 to ROI2, and the lengths of each of the regions of interest ROI0 to ROI2 in the X-axis direction and the Y-axis direction (see FIG. 14) are extracted as the ROI information from the embedded data.

(156) (ROI Restoration Information)

(157) In the information extraction process, once the ROI information (the position information and the size information) is extracted, the ROI restoration information used to restore the image data of the region of interest is generated on the basis of the extracted ROI information. Here, the ROI restoration information will be described in detail with reference to FIG. 16. FIG. 16 is a diagram for describing first coordinate data and second coordinate data included in the ROI restoration information. In the information extraction process, in generating the ROI restoration information, the first coordinate data and the second coordinate data illustrated in FIG. 16 are generated for each region of interest on the basis of the extracted ROI information (the position information and the size information). For example, in this example, three regions of interest ROI0 to ROI2 are restoration processing targets. Therefore, in generating the ROI restoration information in this example, the first coordinate data and the second coordinate data corresponding to each of the three regions of interest ROI0 to ROI2 are generated.

(158) The first coordinate data includes ROI identification data for identifying the region of interest and relative coordinate data indicating a relative position of the region of interest in the captured image. The first coordinate data is data in which the ROI identification data and the relative

coordinate data are associated with each other. The ROI identification information is information that enables identification of each of a plurality of regions of interest in the transmission data that is a restoration processing target, and is, for example, an arbitrary numerical value or character string. (159) Further, as illustrated in FIG. 16, the relative coordinate data includes start point coordinates indicating the upper-left end of the region of interest in the captured image and end point coordinates indicating the lower-right end of the region of interest. Specifically, the relative coordinate data included in the first coordinate data includes four numerical values indicating an X coordinate of the start point coordinates (start point X coordinate), a Y coordinate of the start point coordinates (start point Y coordinate), an X coordinate of the end point coordinates (end point X coordinate), and a Y coordinate of the end point coordinates (end point Y coordinate). The relative coordinate data in the first coordinate data is, for example, a numerical array in which numerical values indicating the start point coordinates (X,Y) and the end point coordinates (X,Y) are arranged in the order illustrated in the upper part of FIG. 16 in a comma-delimited manner.

(160) As described above, in the present embodiment, the ROI information sent from the video transmission device includes the information of the start point coordinates as the position information, but does not include the information of the end point coordinates. Therefore, in the information extraction process, at the time of generating the first coordinate data, the end point coordinates are calculated from the start point coordinates included in the position information and the lengths in the X-axis direction and the Y-axis direction included in the size information.

(161) Similarly to the first coordinate data, the second coordinate data includes ROI identification data and relative coordinate data. However, as illustrated in FIG. 16, the relative coordinate data of the second coordinate data is different from that of the first coordinate data in that the relative coordinate data of the second coordinate data includes the start point Y coordinate and the end point Y coordinate and does not include the start point X coordinate and the end point X coordinate. The relative coordinate data of the second coordinate data is, for example, a numerical array in which numerical values indicating the start point Y coordinate and the end point Y coordinate are arranged in the order illustrated in the lower part of FIG. 16 in a comma-delimited manner.

(162) In the information extraction process according to the present embodiment, once the first coordinate data and the second coordinate data corresponding to the region of interest (ROI) that is the restoration processing target are generated, X-coordinate order data in which the first coordinate data of each region of interest is rearranged in ascending order of the start point X coordinates is generated. In addition, Y-coordinate order data in which the pieces of second coordinate data are rearranged in ascending order of the start point Y coordinates is generated. In the present embodiment, the X-coordinate order data and the Y-coordinate order data correspond to the ROI restoration information.

(163) As described above, the ROI restoration information is information generated by rearranging the position information and the size information in the ROI information. More specifically, the ROI restoration information is information generated by rearranging data (the first coordinate data and the second coordinate data) generated from the position information and the size information. In the information extraction process in the present embodiment, the X-coordinate order data and the Y-coordinate order data are generated as the ROI restoration information as described above. The generated X-coordinate order data and Y-coordinate order data are temporarily stored in a predetermined storage region (for example, a register or the like) of the video reception device, and are used in a subsequent process (for example, the writing process) of the restoration processing.

(164) Here, specific examples of the X-coordinate order data and the Y-coordinate order data will be described with reference to FIG. 17. FIG. 17 is a diagram illustrating an example of the X-coordinate order data and the Y-coordinate order data corresponding to the regions of interest ROI0 to ROI2 that are the restoration processing targets in this example.

(165) In the information extraction process in this example, the end point coordinates of the regions

of interest ROI0 to ROI2 are calculated in generating the first coordinate data and the second coordinate data constituting the X-coordinate order data and the Y-coordinate order data. The end point X coordinate of the region of interest is obtained by “start point X coordinate+X-axis direction length-1”. As illustrated in FIG. 14, the value of the start point X coordinate i0 of the region of interest ROI0 is “520”, and the length in the X-axis direction is “400”. Therefore, the value of the end point X coordinate k0 is calculated as “919”=“start point X coordinate i0 (520)+X-axis direction length (400)-1”. Similarly, the value “1439” of the end point X coordinate k1 of the region of interest ROI1 and the value “499” of the end point X coordinate k2 of the region of interest ROI2 are calculated.

(166) Further, the end point Y coordinate of the region of interest is obtained by “start point Y coordinate+Y-axis direction length-1”. As illustrated in FIG. 14, the value of the start point Y coordinate j0 of the region of interest ROI0 is “300”, and the length in the Y-axis direction is “600”. Therefore, the value of the end point Y coordinate l0 is calculated as “899”=“start point Y coordinate i0 (300)+Y-axis direction length (600)-1”. Similarly, the value “739” of the end point Y coordinate l1 of the region of interest ROI1 and the value “699” of the end point Y coordinate l2 of the region of interest ROI2 are calculated. In this manner, the end point coordinates of each region of interest are calculated.

(167) In the information extraction process in this example, once the end point coordinates are calculated, the first coordinate data and the second coordinate data of the regions of interest ROI0 to ROI2 are generated using the start point coordinate information included in the ROI information and the calculated end point coordinates.

(168) In this example, the first coordinate data of the region of interest ROI0 is represented by “R0(520,300,919,899)”. Here, “R0” is the ROI identification information indicating the region of interest ROI0. Similarly, the first coordinate data of the region of interest ROI1 is represented by “R1(1040,140,1439,739)”, and the first coordinate data of the region of interest ROI2 is represented by “R2(100,100,499,699)”. In a case where the start point X coordinates of the regions of interest ROI0 to ROI2 are arranged in ascending order, a value “100” indicating the start point X coordinate i2 of the region of interest ROI2, a value “520” indicating the start point X coordinate i0 of the region of interest ROI0, and a value “1040” indicating the start point X coordinate i1 of the region of interest ROI1 are arranged in this order. Therefore, the X-coordinate order data corresponding to the regions of interest ROI0 to ROI2 illustrated on the left side of FIG. 17 is generated by rearranging the pieces of first coordinate data of the regions of interest ROI0 to ROI2 in ascending order of the start point X coordinates (in the order of the regions of interest ROI2, ROI0, and ROI1).

(169) Further, in this example, the second coordinate data of the region of interest ROI0 is represented by “R0(300,899)”. Similarly, the second coordinate data of the region of interest ROI1 is represented by “R1(140,739)”, and the second coordinate data of the region of interest ROI2 is represented by “R2(100,699)”. In a case where the start point Y coordinates of the regions of interest ROI0 to ROI2 are arranged in ascending order, a value “100” indicating the start point Y coordinate l2 of the region of interest ROI2, a value “140” indicating the start point Y coordinate l1 of the region of interest ROI1, and a value “899” indicating the start point Y coordinate l0 of the region of interest ROI0 are arranged in this order. Therefore, the Y-coordinate order data corresponding to the regions of interest ROI0 to ROI2 illustrated on the right side of FIG. 17 is generated by rearranging the pieces of second coordinate data of the regions of interest ROI0 to ROI2 in ascending order of the start point Y coordinates (in the order of the regions of interest ROI2, ROI1, and ROI0). In this example, the generated X-coordinate order data and Y-coordinate order data corresponding to the regions of interest ROI0 to ROI2 are stored in the register while maintaining the order illustrated in FIG. 17.

(170) Note that, in FIG. 17, the arrangement order in the X-coordinate order data and the Y-coordinate order data is indicated by a numerical value of 1 to 3 at the left end for easy

understanding. Further, in FIG. 17, the X-coordinate order data is displayed in a table format in which the pieces of first coordinate data of the regions of interest ROI0 to ROI2 are stored in ascending order of the start point X coordinates in units of rows, and the Y-coordinate order data is displayed in a table format in which the pieces of second coordinate data of the regions of interest ROI0 to ROI2 are stored in ascending order of the start point Y coordinates in units of rows for easy understanding. However, the storage manner of the X-coordinate order data and the Y-coordinate order data is not limited thereto. In the present embodiment, the X-coordinate order data and the Y-coordinate order data may be stored in such a way that the order of a predetermined number of regions of interest is maintained.

(171) For example, the X-coordinate order data may store the first coordinate data of each region of interest together with a numerical value indicating an order in a case of rearrangement in ascending order of the start point X coordinates. Further, similarly, the Y-coordinate order data may store the second coordinate data of each region of interest together with a numerical value indicating an order in a case of rearrangement in ascending order of the start point Y coordinates. Furthermore, the X-coordinate order data may be stored as an array obtained by dividing the first coordinate data of each of the regions of interest by a predetermined delimiter (for example, comma). Similarly, the Y-coordinate order data may be stored as an array obtained by dividing the second coordinate data of each of the regions of interest by a predetermined delimiter (for example, comma).

(172) In the information extraction process of this example, it is possible to determine the relative positions of the regions of interest ROI0 to ROI2 that are the restoration processing targets in the captured image α (see FIG. 13) by generating the X-coordinate order data and the Y-coordinate order data corresponding to the regions of interest ROI0 to ROI2. As a result, in the process (writing process) of the restoration processing after the information extraction process, processing using the relative positions of the regions of interest ROI0 to ROI2 can be performed.

(173) As described above, the X-coordinate order data is data obtained by rearranging the position information and the size information of a predetermined number of regions of interest (ROIs) cut from the captured image in ascending order of the values of the X coordinates (start point X coordinates) of the start point coordinates corresponding to the position information. More specifically, the X-coordinate order data is data obtained by rearranging the pieces of relative coordinate information generated from the position information and the size information of the regions of interest in ascending order of the start point X coordinates. Furthermore, the Y-coordinate order data is data obtained by rearranging the position information and the size information of a predetermined number of regions of interest cut from the captured image in ascending order of the values of the Y coordinates of the start point coordinates corresponding to the position information. More specifically, the Y-coordinate order data is data obtained by rearranging the Y coordinates in the relative coordinate information generated from the position information and the size information of the regions of interest in ascending order of the start point Y coordinates.

(174) The relative positions of the regions of interest in the captured image can be determined by generating the ROI restoration information in the information extraction process in the restoration processing. As a result, the subsequent processes (for example, the writing process) of the restoration processing can be smoothly performed using the relative positions. As will be described in detail later, the stored X-coordinate order data and Y-coordinate order data are updated each time the video reception device receives the transmission data and a new information extraction process is started.

(175) [Writing Process]

(176) Next, the writing process in the restoration processing will be described. The writing process is a process of writing the image data of the region of interest to a memory device in the video reception device on the basis of the ROI restoration information generated in the information extraction process. In the present embodiment, for example, the frame memory is assumed as the

memory device for writing image data of an ROI. The frame memory is a memory IC capable of holding image data to be displayed on a display device (for example, a display or the like) in units of screens.

(177) In the present embodiment, once a frame for communicating transmission data is started by the reception of the SOF as described above and the transmission data is received in the video transmission device, the embedded data is first input, and then the respective lines of the payload data are sequentially input from the top. The above-described information extraction process is on the basis of the input of the embedded data, but the writing process in the restoration processing is performed on the basis of the input of each line of the payload data. In the writing process in the present embodiment, the image data of the region of interest is written in the frame memory in units of payload data on the basis of the ROI restoration information. In the writing process, the ROI pixel row data of each line of the payload data is written in the frame memory.

(178) In the present embodiment, in the writing process of the restoration processing, the image data of the region of interest in the payload data, that is, the ROI pixel row data, is divided for each region of interest on the basis of the ROI restoration information. That is, the ROI pixel row data is divided as a packet group for each region of interest, that is, image data of the region of interest (ROI) on the basis of the ROI restoration information. Furthermore, in the writing process, an address indicating a write destination of the image data of the region of interest (ROI) in the frame memory is generated on the basis of the ROI restoration information. The image data of each region of interest divided from the ROI pixel row data is written to the address in the frame memory.

(179) As will be described in detail later, in the present embodiment, a restoration position in the frame memory corresponding to the relative position of each region of interest in the captured image is specified as the write destination of the image data of the region of interest on the basis of the ROI restoration information, and an address indicating the restoration position is generated. As a result, the relative position of the region of interest in the captured image is restored in the frame memory. Therefore, the image data of the region of interest can be displayed at the display position corresponding to the relative position in the captured image on the screen of the display.

(180) (Analysis of ROI Restoration Information)

(181) In the writing process in the present embodiment, the ROI restoration information (the X-coordinate order data and the Y-coordinate order data) is analyzed, information corresponding to the ROI pixel row data in each line of the payload data is extracted on the basis of the ROI restoration information, and information (writing information) used for writing is generated. The division of the ROI pixel row data and generation of the address indicating the write destination in the frame memory for the divided ROI pixel row data are performed on the basis of the writing information generated from the ROI restoration information. In the present embodiment, for example, a writing Y coordinate, a writing start X coordinate, and a writing size are generated as the writing information. In the writing process of the restoration processing, the X-coordinate order data and the Y-coordinate order data are extracted for each input of each line of the payload data to generate the writing information. The writing information (the writing Y coordinate, the writing start X coordinate, and the writing size) will be specifically described below.

(182) (Writing Y Coordinate)

(183) The writing Y coordinate is a Y coordinate of the ROI pixel row data in the captured image. The writing Y coordinate is used to determine the position in the Y-axis direction in the frame memory at the time of writing the ROI pixel row data. The ROI pixel row data stored in each line of the payload data includes the image data of the region of interest having the same Y coordinate in the captured image. Therefore, the writing Y coordinate has a common value in units of lines of the payload data. The writing Y coordinate is generated from the Y-coordinate order data in the ROI restoration information. For example, once each line of the payload data is input, the second coordinate data is extracted from the Y-coordinate order data in the storage order (in ascending

order of the start point X coordinates). The writing Y coordinate corresponding to each line of the input payload data is generated using the extracted second coordinate data.

(184) In this example, in a case where the line PL1 (see FIG. 15) of the payload data is input, the second coordinate data related to the first region of interest ROI2 of the Y-coordinate order data (see the right side of FIG. 17) is extracted, and the writing Y coordinate indicating the start point Y coordinate (100) of the region of interest ROI2 is generated. That is, in a case where the top line (first line) of the payload data is input, it is sufficient if the first second coordinate data of the Y-coordinate order data is extracted, and the start point Y coordinate in the second coordinate data, that is, the start point Y coordinate having the smallest value in the Y-coordinate order data is determined as the writing Y coordinate.

(185) After the inputting of the top line, the value of the writing Y coordinate is updated by being incremented by 1 every time a new line of the payload data is input. Furthermore, in a case where the updated value of the writing Y coordinate exceeds the value of the end point Y coordinate, the next second coordinate data is extracted from the Y-coordinate order data. In this example, in a case where the line PL601 of the 601-th row of the payload data is input, the updated value of the writing Y coordinate becomes “700”, and exceeds the value “699” of the end point Y coordinate of the region of interest ROI2. Therefore, the second coordinate data related to the second region of interest ROI1 is extracted from the Y-coordinate order data (see the right side of FIG. 17).

(186) Once new second coordinate data is extracted, it is determined whether or not the updated value of the writing Y coordinate is included within a range from the start point Y coordinate to the end point Y coordinate of the newly extracted second coordinate data. If the updated value of the writing Y coordinate is within the range, the updated value of the writing Y coordinate is used as the writing Y coordinate corresponding to the input line. In this example, it is determined that the updated value “700” of the writing Y coordinate is within the range from the value “140” of the start point Y coordinate to the value “739” of the end point Y coordinate of the region of interest ROI1. Therefore, the updated value “700” of the writing Y coordinate is used as the writing Y coordinate of the ROI pixel row data of the line PL601 of the payload data.

(187) On the other hand, in a case where the updated value of the writing Y coordinate is not within the range, the updated value of the writing Y coordinate does not correspond to the Y coordinate of the ROI pixel row data in the input line. Therefore, the writing Y coordinate is generated on the basis of the newly extracted second coordinate data. For example, in a case where the updated value of the writing Y coordinate is smaller than the value of the start point Y coordinate of the newly extracted second coordinate data, it is sufficient if the writing Y coordinate is generated with the value of the start point Y coordinate of the second coordinate data. Furthermore, in a case where the updated value of the writing Y coordinate is larger than the value of the end point Y coordinate of the newly extracted second coordinate data, it is sufficient if the next second coordinate data is extracted from the Y-coordinate order data to generate the writing Y coordinate. As a result, the Y-coordinate position of each region of interest in the captured image can be reflected on the writing Y coordinate.

(188) (Writing Start X Coordinate and Writing Size)

(189) Next, the generation of the writing start X coordinate and the writing size will be described. The writing start X coordinate and the writing size are generated for each region of interest with respect to the writing Y coordinate generated in units of ROI pixel rows. The writing start X coordinate indicates the X coordinate of each packet group included in the ROI pixel row data, that is, the image data of each region of interest, in the captured image. Furthermore, the writing size indicates the image size (here, the length in the X-axis direction) of the image data of each region of interest. The ROI pixel row data is divided for each region of interest on the basis of the writing start X coordinate and the writing size at the time of writing in the frame memory. Therefore, the writing size is also referred to as a “division size”.

(190) Furthermore, the writing start X coordinate is used to calculate a writing start position (head

address) corresponding to each region of interest in the X-axis direction in the frame memory at the time of writing the image data of each region of interest. Further, the writing size is used to calculate consecutive addresses in the frame memory for storing the image data of the region of interest divided from the ROI pixel row data.

(191) The writing start X coordinate and the writing size are generated from the X-coordinate order data in the ROI restoration information. For example, once each line of the payload data is input, the second coordinate data is extracted from the X-coordinate order data in the storage order (in ascending order of the start point X coordinates). For the extracted first coordinate data, it is determined whether or not the value of the current writing Y coordinate is included within a range from the start point Y coordinate to the end point Y coordinate of the extracted first coordinate data. As a result, it is determined whether or not the image data of each region of interest is included in the ROI pixel row data of each line. Here, the region of interest associated with the image data included in the ROI pixel row data is referred to as a writing target ROI. Note that, in the present embodiment, in a case where a predetermined line of the payload data is input, first, the value of the writing Y coordinate is generated (updated), and then, the writing start X coordinate and the writing size are generated.

(192) In this example, in a case where the line PL1 (see FIG. 15) of the first row of the payload data is input, the first coordinate data related to the first region of interest ROI2 of the X-coordinate order data (see the right side of FIG. 17) is first extracted. At this time, as described above, the value of the writing Y coordinate is “100”, and is included within a range from the value “100” of the start point Y coordinate to the value “699” of the end point Y coordinate of the region of interest ROI2. Therefore, the ROI pixel row data of the line PL1 includes the image data of the region of interest ROI2, and the region of interest ROI2 is determined to be the writing target ROI. On the other hand, the value “100” of the writing Y coordinate is not included in the range from the value “140” of the start point Y coordinate to the value “739” of the end point Y coordinate of the first coordinate data related to the second region of interest ROI1 of the X-coordinate order data. Similarly, the value “100” of the writing Y coordinate is not included in the range from the value “300” of the start point Y coordinate to the value “899” of the end point Y coordinate of the first coordinate data related to the third region of interest ROI0 of the X-coordinate order data. Therefore, it is determined that the regions of interest ROI0 and ROI1 are not the writing target ROIs.

(193) In the present embodiment, the writing start X coordinate and the writing size are generated for each region of interest (ROI) determined to be the writing target ROI. Specifically, the start point X coordinate of the writing target ROI is generated as the writing start X coordinate. In this example, the writing start X coordinate of the region of interest ROI2 is generated as the value “100” of the start point X coordinate. Further, the writing size is generated by adding 1 to a difference between the value of the start point X coordinate and the value of the end point X coordinate in the first coordinate data of the writing target ROI. In this example, the writing size of the region of interest ROI2 is “400 pixels (=end point X coordinate (499)–start point X coordinate (100)+1)”.

(194) In a case where it is determined that the region of interest ROI0 is the writing target ROI, the writing start X coordinate of the region of interest ROI0 is generated as the value “300” of the start point X coordinate, and the writing size of the region of interest ROI0 is “400 pixels (=end point X coordinate (919)–start point X coordinate (520)+1)”. Further, in a case where it is determined that the region of interest ROI1 is the writing target ROI, the writing start X coordinate of the region of interest ROI1 is generated as the value “1040” of the start point X coordinate, and the writing size of the region of interest ROI1 is “400 pixels (=end point X coordinate (1439)–start point X coordinate (1040)+1)”.

(195) In this example, in a case where the lines PL1 to PL40 of the payload data are input, only the region of interest ROI2 is the writing target ROI. Therefore, the writing start X coordinate and the

writing size of the region of interest ROI2 are generated. Furthermore, in a case where the lines PL41 to PL200 of the payload data are input, the regions of interest ROI2 and ROI1 are the writing target ROIs. Therefore, the writing start X coordinate and the writing size of each of the regions of interest ROI2 and ROI1 are generated. Moreover, in a case where the lines PL201 to PL600 of the payload data are input, the regions of interest ROI2, ROI0, and ROI1 are the writing target ROIs. Therefore, the writing start X coordinate and the writing size of each of the regions of interest ROI2, ROI0, and ROI1 are generated.

(196) Furthermore, after the inputting of the line PL601 of the payload data, the region of interest ROI2 does not correspond to the writing target ROI. Therefore, the writing start X coordinate and the writing size of each of the regions of interest ROI0 and ROI1 are generated. Furthermore, after the inputting of the line PL641 of the payload data, the region of interest ROI1 does not correspond to the writing target ROI. Therefore, only the writing start X coordinate and the writing size of the region of interest ROI0 are generated. As described above, in the present embodiment, the writing size of the image data of the region of interest (ROI) to be written in the frame memory is calculated on the basis of the position information (the X-coordinate order data in this example) in the ROI restoration information.

(197) (Generation of Address in Frame Memory)

(198) In the writing process in the restoration processing of the present embodiment, once the writing information (the writing Y coordinate, the writing start X coordinate, and the writing size) is generated from the ROI restoration information, an address for writing, in the frame memory, the image data of the region of interest (writing target ROI) included in the ROI pixel row data is specified on the basis of the writing information. In the present embodiment, as described above, the address corresponding to the restoration position indicating the relative position of the region of interest in the captured image is generated in the frame memory. Furthermore, for the image data of the writing target ROI, the address is generated in the storage order of the X-coordinate order data (in ascending order of the start point X coordinates).

(199) For example, a position in the Y-axis direction in the frame memory among the restoration positions of the regions of interest (here, the writing target ROIs) is specified on the basis of the writing Y coordinate common in units of ROI pixel rows. Furthermore, the head position in the X-axis direction in the frame memory among the restoration positions of the respective writing target ROIs is specified on the basis of the writing start X coordinate of each writing target ROI. As a result, the writing start position of the image data of the writing target ROI in the frame memory is specified.

(200) In this example, it is assumed that the writing Y coordinate “140” for the ROI pixel row data, the writing start X coordinate “100” of the region of interest ROI2, and the writing start X coordinate “140” of the region of interest ROI1 are generated in a case where the line PL41 (see FIG. 15) of the first row of the payload data is input. In this case, a position corresponding to the pixel coordinates “100,140 (X coordinate, Y coordinate)” in the captured image α (see FIG. 13) is determined as the writing start position of the image data of the region of interest ROI2 included in the ROI pixel row data in PL41 in the frame memory. Further, a position corresponding to the pixel coordinates “520,140 (X coordinate, Y coordinate)” in the captured image α is determined as the writing start position of the image data of the region of interest ROI1 included in the ROI pixel row data in the frame memory.

(201) As described above, the writing start position is determined for each writing target ROI in the ROI pixel row data, whereby the head address in the frame memory that indicates the writing start position is calculated. In the present embodiment, for example, equivalent pixel coordinates to those of the captured image can be applied to a writing region of the image data in the frame memory. In this case, for example, an address indicating the coordinates in the frame memory can be calculated by specifying the coordinates of the writing start position. Note that it is sufficient if specific address calculation method (calculation formula) is appropriately designed according to

specifications of the frame memory or the like.

(202) Moreover, consecutive addresses corresponding to the number of pixels indicated by the writing size are calculated using the head address of each region of interest and the writing size generated for each region of interest. For example, the value of the head address is added (incremented) by 1 up to the number of pixels indicated by the writing size. As a result, consecutive addresses corresponding to the number of pixels indicated by the writing size are calculated. The image data of a series of writing target ROIs can be written in the frame memory by writing each pixel of the image data of the writing target ROI to each of the consecutive addresses. In the frame memory, a region corresponding to the writing size from the writing start position corresponds to the restoration position of the writing target ROI in units of pixel rows.

(203) In this example, in a case where the line PL41 (see FIG. 15) of the 41-th row of the payload data is input, addition for calculating addresses corresponding the writing size “400 pixels” is repeated for the head address of the region of interest ROI2. As a result, consecutive addresses corresponding to 400 pixels from the head address of the region of interest ROI2 are generated in the frame memory. Similarly, the consecutive addresses for 400 pixels from the head address of the region of interest ROI1 are generated. As a result, image data for 400 pixels of each of the regions of interest ROI2 and ROI1 is written in the frame memory.

(204) (Division of Image Data)

(205) In the writing process in the present embodiment, the image data (ROI pixel row data) of the region of interest (ROI) in the payload data is divided and transferred for each region of interest on the basis of the ROI restoration information, and is written in the frame memory. Specifically, the ROI pixel row data in each line of the payload data is divided for each region of interest (writing target ROI) on the basis of the writing information (the writing Y coordinate, the writing start X coordinate, and the writing size) generated from the ROI restoration information. In the writing process in the restoration processing of the present embodiment, the ROI pixel row data is divided for each region of interest on the basis of the writing size in the writing information.

(206) For example, the image data of the writing target ROI is divided from the ROI pixel row data in the storage order of the X-coordinate order data (in ascending order of the start point X coordinates). That is, the ROI pixel row data is divided into the image data of each writing target ROI in order from a payload header side. The divided image data in units of writing target ROIs is separated from the ROI pixel row data for each writing target ROI, and writing target image data is generated. The writing target image data is transferred to the frame memory and written to an address generated on the basis of the writing information. Therefore, the ROI pixel row data is written in the frame memory by the number of times of writing corresponding to the number of divisions for each writing target ROI.

(207) In this example, in a case where the line PL41 (see FIG. 15) of the 41-th row of the payload data is input, the ROI pixel row data is divided on the basis of the writing size of each of the regions of interest ROI2 and ROI1 which are the writing target ROIs. The pixel row data of the line PL41 is divided into two pieces of image data including the image data (ROI2(L41)) of the region of interest ROI2 and the image data (ROI1(L1)) of the region of interest ROI1 starting from the head of the ROI pixel row data, that is, the payload header PH side of the line PL41. Therefore, the number of times the ROI pixel row data of the line PL41 is written in the frame memory is 2. Specifically, in the line PL41 of the 41-th row of the payload data, the division size (writing size) of the region of interest ROI2 is 400 pixels, and the division size of the region of interest ROI1 is 400 pixels. Therefore, the image data corresponding to 400 pixels from the head in the ROI pixel row data is divided to generate the writing target image data of the region of interest ROI2. Further, the writing target image data of the region of interest ROI1 is generated from the image data corresponding to the remaining 400 pixels in the ROI pixel row data.

(208) The writing target image data generated for each region of interest (writing target ROI) is transferred to the frame memory in the order of division from the ROI pixel row data (in ascending

order of the writing start X coordinates), for example, and is written to an address indicating the restoration position corresponding to each region of interest (ROI). As a result, the writing target image data of the writing target ROI is written to the restoration position corresponding to the writing target ROI in the frame memory. Note that, in a case where there is one writing target ROI (for example, in a case where the line PL1 of the first row of the payload data is input), the pixel row data can be transferred to the frame memory without being divided, but may be divided if appropriate in view of a bus specification and the number of pixels of the pixel row data.

(209) The writing process in the restoration processing of the present embodiment has been described above. As described above, each time each line of the payload data is input, the generation of the address of the writing target ROI and the division of the ROI pixel row data are performed, and the pieces of ROI pixel row data of all lines of the payload data are written in the frame memory. As a result, each of the regions of interest cut from the captured image is written to the restoration position in the frame memory. Therefore, in the video reception device, the image data of the region of interest is restored so as to be displayable on a predetermined display device. In this example, in the frame memory, the regions of interest ROI0 to ROI2 are written to the restoration positions corresponding to the relative positions in the captured image α (see FIG. 13). That is, the regions of interest ROI0 to ROI2 are restored so as to be displayable at display positions corresponding to the relative positions in the captured image α (see FIG. 13) on the screen of the predetermined display device.

(210) As described above, in the present embodiment, the image data of the region of interest is restored so as to be displayable and is written in the frame memory through the information extraction process and the writing process in the restoration processing, whereby the image data can be efficiently displayed on the display device such as the display.

4. Video Transmission System of Present Disclosure

(211) 4-1. Outline of Video Transmission System

(212) Next, a video transmission system and a video reception device according to the present embodiment will be described with reference to FIGS. 18 and 19. First, a schematic configuration of the video transmission system according to the present embodiment will be described with reference to FIG. 18. FIG. 18 is a block diagram illustrating a schematic configuration of a video transmission system (an example of a transmission system) 2. Furthermore, FIG. 19 is a block diagram illustrating an example of a configuration of a video reception device 200a according to the present embodiment.

(213) As illustrated in FIG. 18, the video transmission system 2 includes a video transmission device (an example of a transmission device) 100 and the video reception device (an example of a reception device) 200a. Note that components that implement the same operations and functions as those of the video transmission system 1 (see FIG. 1) according to Underlying Technologies 1 and 2 described above are denoted by the same reference signs, and a description thereof is omitted.

(214) In the video transmission system 2, the video transmission device 100 generates transmission data including embedded data and payload data in which image data of a region of interest and data of a normal image are stored. The transmission data generated by the video transmission device 100 is sent to the video reception device 200a via a data lane DL. Once the transmission data is received, the video reception device 200a performs predetermined processing on the transmission data. Once the transmission data including the image data of the region of interest is received, the video reception device 200a according to the present embodiment performs the restoration processing on the image data of the region of interest.

(215) Further, in the present embodiment, the video reception device 200a is connected to a display device 300. The display device 300 is, for example, a display device including a screen capable of displaying an image. The video reception device 200a outputs the image data (the data of the normal image and the image data of the region of interest (ROI)) included in the transmission data to the display device 300. As a result, for example, the image data of the region of interest cut from

the captured image and sent as the transmission data in the video transmission device **100** is subjected to the restoration processing in the video reception device **200a** and then displayed on the screen of the display device **300**.

(216) Next, the video reception device **200a** according to the present embodiment will be described. The video reception device **200a** is different from the video reception device **200** (see FIG. **8**) according to Underlying Technologies 1 and 2 in that the video reception device **200a** is configured to be able to perform the restoration processing. Note that, components that implement the same operations and functions in the video reception device **200a** as those of the video reception device **200** according to Underlying Technologies 1 and 2 are denoted by the same reference signs, and a description thereof is omitted if appropriate.

(217) As illustrated in FIG. **19**, the video reception device **200a** includes, for example, a reception unit **210**, an information processing unit (an example of a processing unit) **230**, and a frame memory **250**. As will be described in detail later, in the present embodiment, the information processing unit **230** includes a first information processing unit **230a** and a second information processing unit **230b**. The information processing unit **230** (the first information processing unit **230a** and the second information processing unit **230b**) and the frame memory **250** are connected via a bus **240** so as to be able to transfer image data. Furthermore, the second information processing unit **230b** and the frame memory **250** are connected so as to be able to transfer image data via the bus **240** under the control of a direct memory access (DMA) controller **20**.

(218) The reception unit **210** in the video reception device **200a** receives a transmission signal (transmission data **147A** in this example) in which image data of a predetermined number of regions of interest (ROIs) cut from a predetermined captured image is included in the payload data, and ROI information corresponding to the predetermined number of regions of interest is included in the embedded data. Similarly to the video transmission device **100** in Underlying Technologies 1 and 2, the video transmission device **100** (see FIG. **18**) included in the transmission system **2** according to the present embodiment sends image data of each region of interest (ROI) in a captured image **111** as payload data of a long packet, and sends ROI information **120B** regarding the region of interest as embedded data. As a result, the device (video reception device **200**) that has received the transmission data **147A** transmitted from the video transmission device **100** can easily extract the image data (ROI image **112**) of each region of interest ROI from the transmission data **147A**. The reception unit **210** is a circuit that generates various pieces of data (**214A**, **215A**, and **215B**) by performing predetermined processing on the received transmission data **147A** and outputs the various pieces of data to the information processing unit **220**. In the present embodiment, once a packet (SOF) indicating that communication of an image data frame with the video transmission device **100** is started is received, the reception unit **210** outputs a predetermined signal indicating the reception of the SOF to the first information processing unit **230a**.

(219) Similarly to the video reception device **200** in Underlying Technologies 1 and 2 described above, also in the video reception device **200a**, the reception unit **210** includes, for example, a header separation unit **211**, a header interpretation unit **212**, a payload separation unit **213**, an EBD interpretation unit **214**, and an ROI data separation unit **215**. Among these, the header separation unit **211** and the header interpretation unit **212** have similar configurations to those of the video reception device **200**, and a description thereof is thus omitted.

(220) The EBD interpretation unit **214** determines whether the image data included in the payload data of the transmission data **147A** is image data of an ROI (the compressed image data **120A** of the image data **116** of the region of interest in Underlying Technologies 1 and 2) or data of a normal image (the compressed image data **130A**), on the basis of the data type included in embedded data **213A** input from the payload separation unit **213**. Further, the EBD interpretation unit **214** outputs the data type determination result to the ROI data separation unit **215**. Furthermore, the EBD interpretation unit **214** outputs the embedded data including ROI information (indicating that the image data of the region of interest is included in the payload data) to the first information

processing unit **230a** (specifically, a first information extraction unit **231**) as EBD data **214A**.
(221) In a case where it is determined that the image data included in the payload data of the transmission data **147A** is image data of a region of interest (the compressed image data **120A** of the image data **116**) on the basis of the data type determination result from the EBD interpretation unit **214**, the ROI data separation unit **215** outputs each line of the payload data as payload data **215A** to the first information processing unit **230a** (specifically, an ROI decoding unit **232**) for each line. The payload data **215A** includes pixel data (ROI pixel row data) for one line of compressed image data **147B**.

(222) In the present embodiment, for example, each line of the payload data is transmitted to the video reception device **200a** in units of transactions constituting an image data frame related to the transmission data **147A** sent from the video transmission device **100**. Once a header of each line of the payload data of the long packet is detected in the header interpretation unit **212** of the reception unit **210**, each line of the payload data is separated from a packet region R2 in the payload separation unit **213**, and the payload data **215A** including a payload header PH, ROI pixel row data, and a payload footer PF of each line is generated in the ROI data separation unit **215**.

(223) For example, in a case where an image data frame including the payload data illustrated in FIG. **15** in the packet region is transmitted from the video transmission device **100**, the payload data **215A** generated by the ROI data separation unit **215** includes pixel data for one line of lines PL1 to PL800 of the payload data. Furthermore, at this time, the ROI data separation unit **215** sequentially outputs, as the payload data **215A** to the ROI decoding unit **232**, the pieces of payload data of the lines PL1 to PL800 constituting the packet region of the image data frame from the line PL1. Note that, in a case where the ROI information **120B** is included in the payload data of the long packet, the ROI information **120B** may be included in the payload data **215A**.

(224) On the other hand, in a case where the image data included in the payload data is the compressed image data **130A** which is data of a normal image, the ROI data separation unit **215** outputs the payload data to the first information processing unit **230a** (specifically, a normal image decoding unit **236**) as payload data **215B**. In addition, the ROI data separation unit **215** outputs the data type determination result (the determination result indicating that the image data is data of a normal image) input from the EBD interpretation unit **214** to the first information processing unit **230a** (specifically, a normal image address generation unit **235**).

(225) The first information processing unit **230a** is a circuit that performs the restoration processing of restoring the image data (payload data **215A**) of the region of interest so as to be displayable on the display device **300** on the basis of the ROI information corresponding to the predetermined number of regions of interest (ROIs) extracted from the embedded data. Furthermore, the first information processing unit **230a** performs predetermined processing (normal image processing) on the data of the normal image (payload data **215B**).

(226) The first information processing unit **230a** includes the first information extraction unit **231**, the ROI decoding unit **232**, an ROI image address generation unit **233**, and an ROI image generation unit **234** as components related to the execution of the restoration processing. First, these components for performing the restoration processing will be described.

(227) The first information processing unit **230a** extracts the ROI information from the embedded data (EBD data **214A**). The first information processing unit **230a** performs the above-described information extraction process and writing process in the restoration processing, and performs a series of processing of restoring the image data of the region of interest (ROI) and writing the image data in the frame memory **250**.

(228) The first information extraction unit **231** performs the information extraction process in the restoration processing. Specifically, the first information extraction unit **231** extracts position information and size information of each of the predetermined number of regions of interest in the captured image as the ROI information from the ROI information (ROI information **120B**) included in the embedded data (EBD data **214A**). In this example, the first information extraction

unit **231** extracts the start point coordinates of each of three regions of interest ROI0 to ROI2 in the captured image α as the position information, and extracts the lengths of each of the regions of interest ROI0 to ROI2 in the X-axis direction and the Y-axis direction as the size information. (229) The first information extraction unit **231** generates ROI restoration information (X-coordinate order data and Y-coordinate order data) used to restore the image data of the region of interest on the basis of the extracted ROI information. Specifically, the position information in the ROI information includes an X coordinate and a Y coordinate that indicate the upper-left end portion of the region of interest (ROI). The first information extraction unit **231** generates the X-coordinate order data in which the position information and the size information of the predetermined number of regions of interest cut from the captured image are rearranged in ascending order of the values of the start point X coordinates. In this example, the first information extraction unit **231** generates the first coordinate data (see FIG. **16**) corresponding to each of the regions of interest ROI0 to ROI2, and generates the X-coordinate order data (see the left side of FIG. **17**) in which the pieces of generated first coordinate data are rearranged in ascending order of the values of the start point X coordinates (in the order of the regions of interest ROI2, ROI0, and ROI1).

(230) Furthermore, the first information extraction unit **231** generates the Y-coordinate order data in which the position information and the size information of the predetermined number of regions of interest cut from the captured image are rearranged in ascending order of the values of the start point Y coordinates. In this example, the first information extraction unit **231** generates the second coordinate data (see FIG. **16**) corresponding to each of the regions of interest ROI0 to ROI2, and generates the Y-coordinate order data (see the right side of FIG. **17**) in which the pieces of generated second coordinate data are rearranged in ascending order of the values of the start point Y coordinates (in the order of the regions of interest ROI2, ROI1, and ROI0). Once the X-coordinate order data and the Y-coordinate order data are generated, the first information extraction unit **231** stores, for example, the generated X-coordinate order data and Y-coordinate order data in the register as the ROI restoration information.

(231) The first information extraction unit **231** may generate final line determination information when generating the ROI restoration information. The final line determination information is generated on the basis of, for example, the Y-coordinate order data. For example, the first information extraction unit **231** may compare the end point Y coordinates in the second coordinate data in the Y-coordinate order data, and store a Y coordinate having the largest value in the register as final line Y coordinate. As a result, the first information extraction unit **231** can determine whether or not writing of the pieces of image data of the regions of interest for all lines in the payload data has been completed by using the final line determination information.

(232) Furthermore, once generation of the restoration information in the information extraction process is performed, the first information extraction unit **231** then analyzes the ROI restoration information and generates the writing information (the writing Y coordinate, the writing start X coordinate, and the writing size) in the writing process. The first information extraction unit **231** generates the writing information for the input payload data **215A** every time the payload data **215A** is input to the first information processing unit **230a** (specifically, the ROI decoding unit **232**). That is, the first information extraction unit **231** generates the writing information in units of payload data. Once the payload data **215A** is input from the ROI data separation unit **215** on the basis of detection of the header of each line of the payload data in the header interpretation unit **212**, the ROI decoding unit **232** outputs a predetermined signal indicating the input to the first information extraction unit **231**. As a result, the first information extraction unit **231** can detect that each line of the payload data has been input.

(233) In this example, the first information extraction unit **231** generates the writing information for the payload data **215A** corresponding to each line every time the payload data **215A** for each of the lines PL1 to PL800 of the payload data illustrated in FIG. **15** is input to the ROI decoding unit

232.

(234) The first information extraction unit **231** generates the writing Y coordinate corresponding to the payload data **215A** from the Y-coordinate order data in the ROI restoration information as the writing information. The method of generating the writing Y coordinate is as described above. For example, in a case where the inputting of the payload data **215A** corresponding to the line PL**1** (see FIG. **15**) of the payload data is detected, the first information extraction unit **231** extracts the second coordinate data related to the first region of interest ROI**2** of the Y-coordinate order data (see the right side of FIG. **17**), and determines the value “100” of the start point Y coordinate of the region of interest ROI**2** as the writing Y coordinate. Thereafter, the first information extraction unit **231** updates (increments) the value of the writing Y coordinate every time the payload data **215A** is input. In a case where the line PL**601** of the 601-th row of the payload data is input, the first information extraction unit **231** extracts the second coordinate data related to the second region of interest ROI**1** from the Y-coordinate order data, and uses the updated value “700” of the writing Y coordinate as the writing Y coordinate.

(235) Furthermore, the first information extraction unit **231** generates the writing start X coordinate and the writing size corresponding to the image data of each region of interest (writing target ROI) included in the payload data **215A** from the X-coordinate order data in the ROI restoration information as the writing information. The method of generating the writing start X coordinate and the writing size is as described above.

(236) For example, it is assumed that the inputting of the payload data **215A** corresponding to the line PL**1** of the payload data is detected, and the first information extraction unit **231** generates the writing Y coordinate (Y=100). In this case, the writing Y coordinate is included within a range from the value “100” of the start point Y coordinate to the value “699” of the end point Y coordinate in the first coordinate data of the first region of interest ROI**2** of the X-coordinate order data. Therefore, the first information extraction unit **231** determines that the region of interest ROI**2** is the writing target ROI, and sets the start point X coordinate (X=100) of the region of interest ROI**2** as the writing start X coordinate of the image data of the region of interest ROI**2**. In addition, the first information extraction unit **231** calculates “400 pixels (=end point X coordinate (499)–start point X coordinate (100)+1)” as the writing size of the region of interest ROI**2**.

(237) Once the writing target ROI in the payload data **215A** is determined on the basis of the X-coordinate order data, the first information extraction unit **231** generates the writing information (the writing Y coordinate, the writing start X coordinate, and the writing size) for each writing target ROI, and outputs the generated writing information to the ROI image address generation unit **233** and the ROI image generation unit **234**.

(238) The writing information for each writing target ROI is input from the first information extraction unit **23** to the ROI image address generation unit **233** and the ROI image generation unit **234** in the storage order (in ascending order of the start point X coordinates) in the X-coordinate order data. For example, in a case where the inputting of the payload data **215A** corresponding to the line PL**41** (see FIG. **15**) of the payload data is detected, the first information extraction unit **231** outputs the writing information for the writing target ROI to the ROI image address generation unit **233** and the ROI image generation unit **234** in the order of the regions of interest ROI**2** and ROI**1**. As a result, the ROI image address generation unit **233** and the ROI image generation unit **234** can perform the processing (the address generation and the division of the ROI image row data) related to the writing process of the restoration processing in the order of the regions of interest ROI**2** and ROI**1**, that is, in the storage order in the X-coordinate order data (in ascending order of the start point X coordinates (writing start X coordinates)).

(239) The ROI image address generation unit **233** performs address generation processing in the writing process of the restoration processing. The ROI image address generation unit **233** generates an address indicating a write destination of the image data of the region of interest (ROI) in the frame memory **250** on the basis of the ROI restoration information. The ROI image address

generation unit **233** generates an address for writing the image data of the region of interest (writing target ROI) included in the ROI pixel row data in the payload data **215A** in the frame memory **250** on the basis of the inputting of the writing information generated from the ROI restoration information from the first information extraction unit **231**.

(240) In the present embodiment, the address generated by the ROI image address generation unit **233** is an address corresponding to a restoration position indicating the relative position of the region of interest in the captured image in the frame memory **250**. The ROI image address generation unit **233** calculates an address corresponding to a restoration position of the writing target ROI on the basis of the writing information for the writing target ROI input from the first information extraction unit **231**. As described above, the ROI image address generation unit **233** specifies coordinates indicating a writing start position of the writing target ROI on the basis of the writing Y coordinate and the writing start X coordinate, and calculates a head address from the writing start position.

(241) In addition, as described above, the ROI image address generation unit **233** calculates consecutive addresses corresponding to the number of pixels of the image data of the writing target ROI on the basis of the head address and the writing size. As described above, the ROI image address generation unit **233** specifies the restoration position of the image data of the writing target ROI in units of pixel rows in the frame memory **250** by using the coordinates of the writing start position and the writing size, and generates the address corresponding to the restoration position. Note that a specific address value calculation method is designed according to allocation of an address region of the frame memory **250** as appropriate.

(242) As described above, the writing information for each writing target ROI is input from the first information extraction unit **231** to the ROI image address generation unit **233** in ascending order of the start point X coordinates (writing start X coordinates). Therefore, the ROI image address generation unit **233** generates an address for each writing target ROI in ascending order of the writing start X coordinates.

(243) The ROI image address generation unit **233** issues an address command including the generated address. The issued address command is transferred to the frame memory **250** via the bus. In addition, at the time of issuing the address command, the ROI image address generation unit **233** outputs the writing size of the writing target ROI, that is, the number of pixels (the number of transfers) of the image data of the writing target ROI to be written in the frame memory **250** to the ROI image generation unit **234**.

(244) The ROI image generation unit **234** writes the image data of the region of interest in the frame memory **250** in units of payload data on the basis of the ROI restoration information. More specifically, the ROI image generation unit **234** divides and writes the ROI pixel row data in the writing process of the restoration processing. The ROI image generation unit **234** divides the ROI pixel row data in the payload data **215A** for each region of interest (writing target ROI) on the basis of the ROI restoration information, and writes the divided ROI pixel row data in the frame memory **250**. Once the writing information generated from the ROI restoration information is input from the first information extraction unit **231**, the ROI image generation unit **234** divides the ROI pixel row data in the payload data on the basis of the writing information. The ROI image generation unit **234** generates writing target image data **234A** which is image data of the writing target ROI divided from the ROI pixel row data, and writes the writing target image data **234A** in the frame memory **250**.

(245) ROI decoded image data **232A** obtained by decoding the ROI pixel row data in the payload data **215A** is input from the ROI decoding unit **232** to the ROI image generation unit **234**. The ROI decoding unit **232** decodes the ROI pixel row data (compressed image data **147B**) in the payload data **215A** input from the ROI data separation unit **215** to generate the ROI decoded image data **232A**. Note that, in the present embodiment, the ROI decoded image data **232A** includes a payload header PH and a payload footer PF (see FIG. 15).

(246) The ROI image generation unit **234** divides the ROI decoded image data **232A** in units of writing target ROIs on the basis of the writing information for the writing target ROI input from the first information extraction unit **231**. The ROI image generation unit **234** divides the ROI decoded image data **232A** for each writing target ROI on the basis of the writing size in the writing information. As described above, the writing information for each writing target ROI is input from the first information extraction unit **231** to the ROI image generation unit **234** in ascending order of the start point X coordinates (writing start X coordinates). Therefore, the ROI image generation unit **234** divides the image data for each writing target ROI in ascending order of the writing start X coordinates, that is, in order from the payload header side of the ROI decoded image data **232A**. For example, the ROI image generation unit **234** separates the image data in units of the writing target ROIs from the ROI decoded image data **232A**, and generates the writing target image data for each writing target ROI.

(247) For example, in a case where the line PL**41** (see FIG. **15**) of the 41-th row of the payload data is input, the ROI image generation unit **234** divides the ROI decoded image data **232A** for 400 pixels on the basis of the writing size (400 pixels) of each of the regions of interest ROI**2** and ROI**1** which are the writing target ROIs. Specifically, the ROI image generation unit **234** divides the ROI decoded image data **232A** for 400 pixels from the head (payload header PH side) of the ROI decoded image data **232A** as the image data of the region of interest ROI**2**, and divides the ROI decoded image data **232A** for the remaining 400 pixels as the image data of the region of interest ROI**1**. The ROI image generation unit **234** separates the divided image data of the region of interest ROI**2** from the ROI decoded image data **232A** to generate the writing target image data **234A** of the region of interest ROI**2**, and similarly generates the writing target image data **234A** of the region of interest ROI**1**.

(248) Once the writing target image data **234A** is generated, the ROI image generation unit **234** issues a data command including the writing target image data **234A**. The issued data command is transferred to the frame memory **250** via the bus **240**. As a result, the writing target image data **234A** of the writing target ROI is written in the frame memory **250**. The ROI image generation unit **234** may compress the writing target image data **234A** and generate a data command including the compressed writing target image data **234A**. In this case, the writing target image data **234A** is written in the frame memory **250** in a compressed state.

(249) In the present embodiment, as described above, the number of transfers is input to the ROI image generation unit **234** when the ROI image address generation unit **233** issues the address command. In addition, the ROI image address generation unit **233** generates the address in ascending order of the writing start X coordinates of the writing target ROI. Therefore, in the present embodiment, the address command and the data command related to the same writing target ROI are transferred to the frame memory **250** at substantially the same timing. That is, in the video reception device **200a**, issuance of the address command and issuance of the data command are synchronized with each other. Therefore, the ROI image generation unit **234** can write the writing target image data **234A** of one writing target ROI to the address indicating the write destination of the one writing target ROI by issuing the data command in response to the inputting of the number of transfers from the ROI image address generation unit **233**. That is, each pixel of the writing target image data **234A** of the writing target ROI included in the data command is written in the frame memory **250** for each address of the writing target ROI indicated by the address command.

(250) Furthermore, once all pieces of the image data of the writing target ROI are separated from the ROI decoded image data **232A** and the generation of the writing target image data **234A** in units of payload data of the writing target image data **234A** is completed, the ROI image generation unit **234** generates a writing termination signal and outputs the writing termination signal to the first information extraction unit **231**. For example, the ROI image generation unit **234** separates all pieces of image data of the writing target ROI from the ROI decoded image data **232A**, and

outputs, once the payload footer PF (see FIG. 15) indicating the end of the image data is detected, the writing termination signal to the first information extraction unit **231**. As the writing termination signal is input, the first information extraction unit **231** can recognize that the writing of the pieces of image data of all the regions of interest in each line (payload data **215A**) of the payload data has been completed.

(251) As described above, the first information processing unit **230a** in the video reception device **200a** according to the present embodiment writes the image data of the region of interest in the frame memory **250** on the basis of the generated ROI restoration information. In addition, the first information processing unit **230a** (specifically, the ROI image address generation unit **233**) specifies the restoration position corresponding to the relative position of the region of interest in the captured image in the frame memory **250** on the basis of the ROI restoration information. Moreover, the first information processing unit **230a** (specifically, the ROI image generation unit **234**) writes the image data of the region of interest (writing target image data **234A**) to the restoration position in the frame memory **250**. As described above, the video reception device **200a** can restore the image data of the region of interest so as to be displayable on a predetermined display device by performing the restoration processing.

(252) In the present embodiment, the first information processing unit **230a** of the video reception device **200a** performs the information extraction process and the writing process in the restoration processing, restores the image data of the region of interest so as to be displayable, and writes the image data in the frame memory **250**, as a result of which it is possible to efficiently display the image data on the display device **300** (see FIG. 18). Furthermore, in the present embodiment, the first information processing unit **230a** is configured as hardware (for example, a restoration processing circuit) capable of performing the information extraction process and the writing process in the restoration processing. As a result, the video reception device **200a** can speed up the processing related to the restoration of the image data of the region of interest, and can increase the number of image data frames processed per unit time in the transmission system **2**. That is, it is possible to implement the processing performed at a high frame rate. Furthermore, the entire video reception device **200a** according to the present embodiment may be configured as hardware (for example, a video reception circuit). In this case, the reception unit **210** that receives the transmission data **147A** including the embedded data and the payload data is also configured as hardware (for example, a reception circuit). As a result, the entire processing performed by the video reception device **200a** can be speeded up, and the number of image data frames processed per unit time in the transmission system **2** can be further increased. That is, it is possible to implement the processing performed at a higher frame rate.

(253) Here, the frame memory **250** in which the image data of the writing target ROI is written will be described. The frame memory **250** can store, for example, image data (one byte) of one pixel in a region indicated by one address. Note that, for example, in a case of full-color image data, data of one pixel has a memory size of one byte for each of RGB elements, that is, a total of three bytes. Therefore, the frame memory **250** may be provided for each of the RGB elements, and may be configured to write one pixel (three bytes) of full-color image data byte by byte. At this time, for example, the frame memory **250** for each of R, G, and B may have a common address, and image data for one pixel may be writable at an equivalent position of each frame memory by designating one common address.

(254) Furthermore, for example, the content of the transmission data **147A** transmitted from the video transmission device **100** in one frame can be written in a region different from that for the image data in the frame memory **250**. In the present embodiment, the content of the embedded data (EBD data **214A**) set in a frame header region of the transmission data **147A** is also written in the frame memory **250**. For example, the first information extraction unit **231** outputs the EBD data **214A** to the ROI image generation unit **234** in response to the completion of writing of the pieces of image data of all the regions of interest (ROIs) in the payload data **215A** (inputting of the writing

termination signal). The ROI image generation unit **234** transfers the input EBD data **214A** to the frame memory **250**. The EBD data **214A** is stored as additional image information in the frame memory. As a result, the image data of the region of interest and the embedded data transmitted in one image data frame are stored in the frame memory **250**.

(255) When outputting the image data of the region of interest to the display device **300**, the video reception device **200a** according to the present embodiment performs processing using the embedded data stored in the frame memory **250** together with the image data. As a result, display data including the image data of the region of interest written in the frame memory **250** can be displayed on the display device **300** in a more easily recognizable state.

(256) Furthermore, as will be described in detail later, the image data of the region of interest written in the frame memory **250** is read in units of frame memories, output from the video reception device **200a** to the display device **300** (see FIG. **18**), and displayed in the screen of the display device **300**. Therefore, the image data of the region of interest restored by the first information processing unit **230a** and written in the frame memory **250** can be displayed in the screen of the predetermined display device while maintaining the relative position in the captured image. As a result, the image data of the region of interest can be efficiently displayed on the display device **300**. Note that processing related to display of the image data of the eye region ROI read from the frame memory **250** will be described later.

(257) Next, a flow of the restoration processing in the video reception device **200a** according to the present embodiment will be described with reference to FIG. **20**. FIG. **20** is a flowchart illustrating an example of a flow of the restoration processing in the video reception device **200a** according to the present embodiment.

(258) (Step **S101**)

(259) Once a predetermined packet is received from the video transmission device **100**, the reception unit **210** included in the video reception device **200a** determines whether or not the packet is a packet (SOF) indicating a start of a frame (an image data frame in this example). In a case where it is determined that the SOF has been received, the reception unit **210** outputs a control signal indicating that the SOF has been received to the first information processing unit **230a**. The first information processing unit **230a** performs the processing of Step **S103** on the basis of the control signal. On the other hand, in a case where it is determined that the received packet is not the SOF, the reception unit **210** repeats the processing of Step **S101** at predetermined intervals and waits for the reception of the SOF.

(260) (Step **S103**)

(261) The first information processing unit **230a** resets information (ROI restoration information or the like) used for the restoration processing in the previous image data frame, and proceeds to Step **S105**. The first information processing unit **230a** erases the ROI restoration information (the X-coordinate order data and the Z-coordinate order data) stored in the register or sets a predetermined value in the register, thereby resetting the ROI restoration information and the like in the previous image data frame.

(262) (Step **S105**)

(263) The first information processing unit **230a** determines whether or not embedded data has been input. Specifically, the first information extraction unit **231** included in the first information processing unit **230a** determines whether or not the embedded data (EBD data **214A**) including ROI information has been input from the EBD interpretation unit **214** included in the reception unit **210**. In a case where it is determined that the EBD data **214A** has been input, the first information extraction unit **231** proceeds to Step **S107**. On the other hand, in a case where it is determined that the EBD data **214A** has not been input, the first information extraction unit **231** repeats the processing of Step **S105** at predetermined intervals, and waits for the execution of the processing of Step **S107** and subsequent steps until the EBD data **214A** is input.

(264) (Step **S107**)

(265) The first information extraction unit **231** extracts the ROI information (position information and size information) from the embedded data (EBD data **214A**), and proceeds to Step **S109**. For example, the first information extraction unit **231** extracts, from the EBD data **214A**, start point coordinates as the position information corresponding to the regions of interest ROI0 to ROI2 cut from the captured image α , and extracts the lengths in the X-axis direction and the Y-axis direction as the size information.

(266) (Step **S109**)

(267) The first information extraction unit **231** rearranges the extracted ROI information to generate ROI restoration information (X-coordinate order data and Y-coordinate order data), and proceeds to Step **S111**. Specifically, the first information extraction unit **231** generates the ROI restoration information (the X-coordinate order data and the Y-coordinate order data) by rearranging the first coordinate data and the second coordinate data (see FIG. **16**) generated on the basis of the extracted ROI information as described above. In addition, the first information extraction unit **231** generates final line determination information together with the ROI restoration information. For example, the first information extraction unit **231** generates the X-coordinate order data (see the left side of FIG. **17**) by rearranging the pieces of first coordinate data of the regions of interest ROI0 to ROI2 in ascending order of the start point X coordinates, and generates the Y-coordinate order data (see the right side of FIG. **17**) by rearranging the pieces of second coordinate data of the regions of interest ROI0 to ROI2 in ascending order of the start point Y coordinates. In addition, the first information extraction unit **231** generates the end point Y coordinate (899) of the region of interest ROI0 having the largest value in the Y-coordinate order data as the final line determination information.

(268) (Step **S111**)

(269) The first information extraction unit **231** determines whether or not a header of the payload data has been input. In the present embodiment, in a case where a signal indicating that the payload data **215A** has been input is detected in the ROI decoding unit **232**, the first information extraction unit **231** determines that the header of the payload data has been input, and proceeds to Step **S113**. On the other hand, in a case where the signal indicating that the payload data **215A** has been input is not detected, the first information extraction unit **231** repeats the processing of Step **S111** at predetermined intervals until the input of the signal is detected, that is, until the header of the payload data is input.

(270) (Step **S113**)

(271) The first information extraction unit **231** generates writing information (writing Y coordinate, writing start X coordinate, and writing size) to be used for writing the image data of the region of interest (writing target ROI) from the ROI restoration information, and proceeds to Step **S115**. The first information extraction unit **231** generates the writing Y coordinate from the Y-coordinate order data, and generates the writing start X coordinate and the writing size from the X-coordinate order data by using the generated writing Y coordinate. The first information extraction unit **231** outputs the writing information generated for each writing target ROI to the ROI image address generation unit **233** and the ROI image generation unit **234** in ascending order of the writing start X coordinates. On the basis of the input writing information, the ROI image address generation unit **233** performs the processing of Step **S115**, and the ROI image generation unit **234** performs the processing of Steps **S117** and **S119**.

(272) (Step **S115**)

(273) The ROI image address generation unit **233** calculates an address corresponding to a restoration position of the writing target ROI in the frame memory **250** on the basis of the input writing information. The calculated address is issued as an address command and transferred to the frame memory **250**. In addition, the ROI image address generation unit **233** outputs the number of transfers indicating the number of pixels of the writing target ROI to the ROI image generation unit **234** in response to the light emission of the address command.

(274) (Step S117)

(275) The ROI image generation unit **234** generates the writing target image data **234A** on the basis of the writing information input from the first information extraction unit **231**, and proceeds to Step **S119**. The ROI image generation unit **234** divides the ROI decoded image data **232A** input from the ROI decoding unit **232** in units of writing target ROIs on the basis of the input writing information, and generates the writing target image data **234A**.

(276) (Step S119)

(277) The ROI image generation unit **234** issues a data command including the writing target image data **234A**, and writes the writing target image data **234A** in the frame memory **250** via the bus **240**. The ROI image generation unit **234** issues the data command at a timing when the number of transfers is input from the ROI image address generation unit **233**. Further, the ROI image generation unit **234** outputs a predetermined signal indicating that the data command has been issued to the first information extraction unit **231**. Once the signal is input, the first information extraction unit **231** performs the processing of Step **S121**. In a case where the payload footer PF of the ROI decoded image data **232A** is detected, the ROI image generation unit **234** outputs a writing termination signal to the first information extraction unit **231**.

(278) (Step S121)

(279) The first information extraction unit **231** determines whether or not all pieces of image data (ROI pixel row data in the ROI decoded image data **232A**) of the writing target ROI in the input payload data (payload data **215A**) for one line have been written in the frame memory **250**. Once the predetermined signal indicating that the data command has been issued is input from the ROI image generation unit **234**, the first information extraction unit **231** performs the determination. In a case where the writing termination signal is input from the ROI image generation unit **234**, the first information extraction unit **231** determines that the writing of the image data of the writing target ROI in the payload data for one line has been terminated, and proceeds to Step **S123**. On the other hand, in a case where the writing termination signal is not input, the first information extraction unit **231** determines that image data of the writing target ROI that has not been written in the frame memory **250** remains, and returns to Step **S115**.

(280) In this way, in the restoration processing in the present embodiment, the processing from Step **S115** to Step **S119** is repeated by the number of writing target ROIs in each line of the payload data. As a result, the pieces of image data of all the writing target ROIs in each line of the payload data can be written in the frame memory **250** in ascending order of the writing start X coordinates. For example, all pieces of image data of the regions of interest ROI2, ROI0, and ROI1 which are the writing target ROIs of the line PL600 (see FIG. 15) of the payload data can be written in the frame memory **250** in this order.

(281) (Step S123)

(282) The first information extraction unit **231** determines whether or not the processing is performed for the final line of the payload data. The first information extraction unit **231** compares the value of the writing Y coordinate in the current writing information with the value of the final line determination information on the basis of the inputting of the writing termination signal, and determines that the processing is performed for the final line of the payload data in a case where the value of the writing Y coordinate is equal to the value of the final line determination information. On the other hand, in a case where the value of the writing Y coordinate is not equal to the value of the final line determination information, the first information extraction unit **231** determines that the processing is not performed for the final line of the payload data and returns to Step **S111**. As a result, the restoration processing can be performed on the pieces of image data of the regions of interest of the payload data of all lines stored in the packet region R2 in the transmission data **147A**.

(283) For example, in a case where the restoration processing for the lines PL1 to PL800 of the payload data illustrated in FIG. 15 is performed, the first information extraction unit **231**

determines that the processing is performed for the final line of the payload data in a case where the value of the writing Y coordinate is equal to the value “899” of the final line determination information. As a result, in the video reception device **200a**, the restoration processing for the image data of the region of interest is performed for all 800 lines, the lines **PL1** to **PL800**, and the pieces of image data of the regions of interest **ROI0** to **ROI2** are written in the frame memory **250**. (284) As described above, the video reception device **200a** and the video transmission system **2** according to the present embodiment can perform the restoration processing for the image data of the region of interest.

(285) Next, a configuration related to normal image processing in the first information processing unit **230a** will be described. The first information processing unit **230a** includes the normal image address generation unit **235**, a normal image decoding unit **236**, and a normal image generation unit **237** as components for performing the normal image processing.

(286) The normal image decoding unit **236** decodes the payload data **215B** input from the ROI data separation unit **215**, and generates a normal image **224A**. The normal image decoding unit **236** decodes the compressed image data **147B** included in the payload data **215A** and outputs the decoded data to the normal image generation unit **237**. In addition, the normal image address generation unit **235** generates a normal image address for writing data of a normal image in the frame memory **250** in units of pixel rows on the basis of the inputting of the determination result indicating that the image data included in the payload data is the normal image data (the payload data **215B** including the data of the normal image has been output to the normal image decoding unit **236**) from the ROI data separation unit **215**.

(287) In the present embodiment, the frame memory **250** is configured to be able to store image data of the entire region of a captured image (for example, the captured image α). Therefore, it is sufficient if the normal image address generation unit **235** generates the address of the captured image in units of pixel rows (from the left end to the right end in the X-axis direction) every time the above-described determination result is input from the ROI data separation unit **215**. In this example, in a case of generating an address of the data of the normal image corresponding to the top pixel row of the captured image α , the normal image address generation unit **235** first calculates an address of the frame memory **250** corresponding to the coordinates “0,0 (X,Y)” indicating the origin α_o of the captured image α as a head address. Moreover, once the head address is calculated, the normal image address generation unit **235** generates consecutive addresses for storing the pixels of the top pixel row of the captured image α on the basis of the writing size (1760 pixels) of the captured image α in units of pixel rows in the X-axis direction, similarly to the address generation in the ROI image address generation unit **233**. Thereafter, it is sufficient if the address of the data of the normal image is generated and the address command is issued, similarly to the address of the top pixel row while incrementing the Y coordinates by 1.

(288) Note that the data of the normal image may be divided and transferred to the frame memory **250** according to the specification of the bus **240** or the like. In this case, the normal image address generation unit **235** may generate and issue the address command by performing division for each predetermined number of pixels of the captured image in units of pixel rows. In this case, it is sufficient if the normal image address generation unit **235** outputs the number of pixels (the number of transfers) at the time of transfer of the data of the normal image based on the number of divisions of the addresses to the normal image generation unit **237**.

(289) The normal image generation unit **237** generates and issues the data command for writing the data in the frame memory **250** on the basis of the data of the decoded normal image input from the normal image decoding unit **236**. In addition, the normal image generation unit **237** may divide the data of the normal image on the basis of the number of transfers input from the normal image address generation unit **235**, and generate and issue the data command including the divided data of the normal image. Furthermore, the normal image generation unit **237** may compress the data of the normal image and generate the data command including the compressed data of the normal

image. In this case, the data of the compressed normal image is written in the frame memory **250**.
(290) In addition, the normal image address generation unit **235** issues a predetermined command and transfers the result of determining the data type of the image data input from the ROI data separation unit **215** to the frame memory **250**. The determination result is stored as the additional image information in the frame memory. As a result, the data of the normal image and the determination result indicating the data type corresponding to the data of the normal image transmitted in one image data frame are stored in the frame memory **250**.

5. Processing Related to Display of Image Data in Video Reception Device

(291) Next, processing related to display of image data stored in the frame memory **250** will be described. Returning to FIG. **19**, the video reception device **200a** according to the present embodiment includes the second information processing unit **230b** as a component for performing the processing related to display of image data stored in the frame memory **250**. The second information processing unit **230b** performs image data replacement processing, for example, as processing related to display of image data of a region of interest.

(292) 5-1. Configuration Related to Image Data Replacement Processing

(293) As will be described in detail later, the image data replacement processing is processing of, in a case where image data of a region of interest is displayed on the display device **300**, replacing non-ROI image data which does not correspond to the image data of the region of interest among pieces of image data in units of screens of the display device **300** stored in the frame memory **250** with fixed value image data. Hereinafter, the image data replacement processing in the second information processing unit **230b** will be described.

(294) In the present embodiment, for example, in a case where image data (image data of a region of interest (ROI) and data of a normal image) transmitted in units of image data frames from the video transmission device **100** (see FIG. **18**) is written in the frame memory **250**, data (additional information and image data) in the frame memory **250** is sequentially read by the DMA controller **260** written on the basis of the image data frame. The read data is output to the second information processing unit **230b**.

(295) The DMA controller **260** according to the present embodiment controls transfer of data between the frame memory **250** and the second information processing unit **230b**. Note that the DMA controller **260** in the present disclosure is not limited thereto, and may be configured to control transfer of data between the frame memory **250** and the first information processing unit **230a**.

(296) The DMA controller **260** is a controller for transferring data between the frame memory **250** and the second information processing unit **230b** via the bus **240** by direct memory access (DMA). The DMA controller **260** outputs the additional information read from the frame memory **250** to the second information extraction unit **271**. Further, the DMA controller **260** outputs display target image data RD, which is display target image data read from the frame memory **250**, to the image data replacement unit **272**. For example, once each pixel of image data in the frame memory **250** is read for each address, the DMA controller **260** outputs the image data to the image data replacement unit **272** as the display target image data RD in units of pixel rows in the frame memory **250**.

(297) For example, in a case where the frame memory **250** can store image data of 1760 pixels (X coordinate=0 to 1759) per pixel row, the display target image data RD includes image data corresponding to 1760 pixels. Note that the display target image data RD output from the DMA controller **260** to the image data replacement unit **272** is not limited to being output in units of pixel rows, and may be output in units of pixels (for each pixel), for example. Further, the DMA controller **260** may divide the image data in units of pixel rows into a plurality of pieces of display target image data RD and output the plurality of pieces of display target image data RD to the image data replacement unit **272**.

(298) The second information extraction unit **271** in the second information processing unit **230b**

analyzes the additional information input from the DMA controller **260**. Specifically, the second information extraction unit **271** determines whether or not the input additional information is the embedded data (EBD data **214A**), and generates the ROI restoration information on the basis of the ROI information (ROI information **120B**) included in the embedded data in a case where the additional information is the embedded data.

(299) Similarly to the first information extraction unit **231** in the first information processing unit **230a**, the second information extraction unit **271** extracts the position information (start point coordinates) and the size information (lengths in the X-axis direction and the Y-axis direction) of the region of interest from the ROI information (ROI information **120B**) included in the embedded data (EBD data **214A**), and generates the ROI restoration information (X-coordinate order data and Y-coordinate order data). The second information extraction unit **271** stores the generated ROI restoration information in a predetermined register. In addition, the second information extraction unit **271** may output a signal indicating that the ROI restoration information has been generated to the image data replacement unit **272**. In the present embodiment, the generation of the ROI restoration information by the second information extraction unit **271** corresponds to an information extraction process in the image data replacement processing.

(300) In a case where image data of a region of interest is displayed on the display device **300** (see FIG. **18**), the image data replacement unit **272** in the second information processing unit **230b** replaces non-ROI image data which does not correspond to the image data of the region of interest among the pieces of image data in units of screens of the display device **300** stored in the frame memory **250** with the fixed value image data. In the present embodiment, the replacement of the non-ROI image data in the image data replacement unit **272** corresponds to a replacement process in the image data replacement processing.

(301) Here, the fixed value image data is, for example, image data having a fixed mode. In the present embodiment, the fixed value image data is, for example, image data of a fixed color (for example, white). Therefore, once the image data replacement processing in the present embodiment is performed, non-ROI image data is replaced with white image data. Generally, image data transmitted in an image data frame is sequentially overwritten in each address region of a frame memory. Furthermore, in a case where image data is written in units of image data frames, initialization of a frame memory is usually not performed. Therefore, in a case where image data of a region of interest is newly overwritten in a frame memory, image data transmitted in the previous image data frame remains in an address other than the address to which the image data is overwritten.

(302) In a case where image data of a region of interest is displayed, the video reception device **200a** according to the present embodiment performs the image data replacement processing to replace non-ROI image data, that is, image data remaining in an address other than the address to which the image data is overwritten with the fixed value image data. As a result, the video reception device **200a** can improve the visibility of image data of a region of interest to be displayed on the display device **300**. Note that, in a case where the image data of the region of interest is written to the restoration position (a position corresponding to the relative position in the captured image) in the frame memory **250**, the fixed value image data is displayed on the display device **300** as an image indicating the non-region of interest OE in the captured image.

(303) Once the signal indicating that the ROI restoration information has been generated is input from the second information extraction unit **271**, the image data replacement unit **272** determines that the image data of the region of interest is the display target and the image data of the region of interest is included in the display target image data RD input from the DMA controller **260**. As a result, the image data replacement unit **272** performs replacement (replacement process) of the non-ROI image data for the display target image data RD on the basis of the ROI restoration information generated by the second information extraction unit **271**.

(304) The image data replacement unit **272** specifies the non-ROI image data on the basis of the

ROI restoration information generated by the second information extraction unit **271** in the replacement process of the image data replacement processing. The image data replacement unit **272** specifies the non-ROI image data among the pieces of image data in units of screens stored in the frame memory **250** on the basis of the X-coordinate order data and the Y-coordinate order data. In addition, the image data replacement unit **272** determines whether each pixel of the image data in units of screens in the frame memory **250** is included in the image data of the region of interest or in the non-ROI image data on the basis of the ROI restoration information.

(305) Specifically, the image data replacement unit **272** acquires a coordinate position of each pixel of the image data in units of screens (image data in the frame memory **250**), and determines whether or not the coordinate position is included in the region of interest. For example, once the display target image data RD in units of pixel rows read from the frame memory **250** is input, the image data replacement unit **272** acquires the coordinate position of each pixel of the display target image data RD. For example, the image data replacement unit **272** acquires the coordinate position of each pixel in order from the head (X coordinate=0) of the display target image data RD (for example, X coordinate=0 to 1759).

(306) In the present embodiment, the image data replacement unit **272** acquires the coordinate position of the image data (display target image data RD) read using a counter. In the present embodiment, the second information processing unit **230b** includes a counter unit used for various types of measurement processing. In the present embodiment, the second information processing unit **230b** includes a horizontal counter Xct and a vertical counter Yct as the counter units. The horizontal counter Xct is a counter that measures a position (horizontal position) of the display target image data RD in the X-axis direction in the captured image read from the frame memory **250**. A counter value of the horizontal counter Xct corresponds to an X coordinate in a captured image (for example, the captured image α). Furthermore, the vertical counter Yct is a counter that measures a position (vertical position) of the display target image data RD in the Y-axis direction in the captured image. A value of the vertical counter Yct corresponds to a Y coordinate in a captured image, and indicates the position of a pixel row in the captured image. For example, in a case where the values of the horizontal counter Xct and the vertical counter Yct are “0”, the origin α_o (0,0) in the captured image is indicated.

(307) Once the display target image data RD is input, the image data replacement unit **272** sequentially acquires the coordinates of each pixel of the display target image data RD from the head by referring to the value of the horizontal counter Xct. In the present embodiment, the video reception device **200a** performs each processing in the device in synchronization with a predetermined clock signal. Therefore, the counter value of the horizontal counter Xct is updated (incremented) by 1 in synchronization with the clock signal. Furthermore, in the present embodiment, once the counter value of the horizontal counter Xct reaches the end of the X coordinates of the captured image, that is, a value indicating the right end of the captured image, the value of the vertical counter Yct is updated (incremented by 1). For example, the X coordinate of the right end portion of the captured image α is “1759”. Therefore, once the counter value of the horizontal counter Xct reaches “1759”, the counter value of the horizontal counter Xct is reset to “0”. At this time, the value of the vertical counter Yct is updated (incremented by 1).

(308) Once the coordinate position of each pixel of the display target image data RD is acquired, the image data replacement unit **272** determines whether or not the coordinate position acquired on the basis of the ROI restoration information (the X-coordinate order data and the Y-coordinate order data) is included in the region of interest. The image data replacement unit **272** outputs image data of a pixel included in the region of interest among the pixels of the display target image data RD to the display device **300**. On the other hand, the image data replacement unit **272** determines data of a pixel that is not included in the region of interest among the pixels of the display target image data RD as the non-ROI image data, replaces the image data of the pixel with the fixed value image data, and outputs the fixed value image data to the display device **300**.

(309) For example, in order to specify the non-ROI image data, the image data replacement unit 272 determines whether or not the Y coordinate (pixel Y coordinate) and the X coordinate (pixel X coordinate) of each pixel of the display target image data RD in the captured image are included in the region of interest. For example, the image data replacement unit 272 first determines the pixel Y coordinate by using the Y-coordinate order data of the ROI restoration information.

(310) Here, an example of determination of the pixel Y coordinate in the replacement process of the image data replacement processing will be described. The image data replacement unit 272 determines the pixel Y coordinate by using, for example, the counter value of the vertical counter Yct indicating the pixel Y coordinate and the Y-coordinate order data. The image data replacement unit 272 extracts the second coordinate data in order from the head of the Y-coordinate order data (in ascending order of the start point Y coordinates), and determines whether or not the counter value of the vertical counter Yct is included in a range (vertical ROI range) from the start point Y coordinate to the end point Y coordinate in the extracted second coordinate data (first determination condition).

(311) Furthermore, in a case where it is determined that the counter value of the vertical counter Yct is included in the vertical ROI range (the first determination condition is satisfied), the image data replacement unit 272 extracts the first coordinate data of the region of interest (ROI) associated with the second coordinate data from the X-coordinate order data, and determines the pixel X-coordinate. On the other hand, in a case where it is determined that the counter value of the vertical counter Yct is not included in the vertical ROI range in any second coordinate data of the Y-coordinate order data (the first determination condition is not satisfied), the image data replacement unit 272 determines that a pixel that is being processed in the display target image data RD is not included in the image data of the region of interest and is included in the non-ROI image data.

(312) Next, an example of determination of the pixel X coordinate in the replacement process of the image data replacement processing will be described. The image data replacement unit 272 extracts, from the X-coordinate order data, the first coordinate data associated with the second coordinate data in a case where the first determination condition is satisfied, and determines whether or not the counter value of the horizontal counter Xct is included in a range (horizontal ROI range) from the start point X coordinate to the end point X coordinate in the extracted first coordinate data (second determination condition). In this manner, the image data replacement unit 272 determines the pixel X coordinates by using, for example, the counter value of the horizontal counter Xct indicating the pixel X coordinates and the X-coordinate order data.

(313) In a case where it is determined that the counter value of the horizontal counter Xct is included in the horizontal ROI range (the second determination condition is satisfied), the image data replacement unit 272 determines that a pixel that is being processed in the display target image data RD is included in the region of interest and is included in the image data of the region of interest. That is, in a case where both the first determination condition and the second determination condition described above are satisfied and it is determined that the coordinate position of the processing target pixel (a target of determination as to whether or not the pixel is within the region of interest) in the display target image data RD is included in the region of interest, the image data replacement unit 272 determines that the pixel that is being processed is included in the image data of the region of interest.

(314) On the other hand, in a case where it is determined that the counter value of the horizontal counter Xct is not included in the horizontal ROI range (the second determination condition is not satisfied), the image data replacement unit 272 determines that the pixel that is being processed in the display target image data RD is not included in the image data of the region of interest and is included in the non-ROI image data. As described above, in a case where any one of the first determination condition and the second determination condition is not satisfied and it is determined that the coordinate position of the pixel that is being processed is not included in the region of

interest, the image data replacement unit **272** determines that the pixel is included in the non-ROI image data.

(315) In a case where it is determined that the coordinate position of the pixel that is being processed in the display target image data RD is included in the region of interest in the replacement process of the image data replacement processing, the image data replacement unit **272** outputs (sends) the pixel as the display target image data to the display device **300**. On the other hand, in a case where it is determined that the coordinate position of the pixel that is being processed in the display target image data RD is included not in the region of interest but in the non-ROI image data in the replacement process of the image data replacement processing, the image data replacement unit **272** replaces the data of the pixel (display target image data) with the fixed value image data and outputs (sends) the fixed value image data to the display device **300**.

(316) 5-2. Image Data Replacement Processing Method

(317) Next, a flow of the image data replacement processing (image data replacement processing method) in the video reception device **200a** according to the present embodiment will be described with reference to FIG. **22**. FIG. **21** is a flowchart illustrating an example of the flow of the image data replacement processing in the video reception device **200a** according to the present embodiment.

(318) (Step **S201**)

(319) In the second information processing unit **230b** included in the video reception device **200a**, the second information extraction unit **271** determines whether or not an image data frame has been started. In the present embodiment, the image data frame in the image data replacement processing indicates a series of data read from the frame memory **250** by the DMA controller **26**. That is, a series of read data including the additional information and the image data sequentially read from the frame memory **250** corresponds to the image data frame in the image data replacement processing.

(320) In Step **S201**, the second information extraction unit **271** determines whether or not the DMA controller **260** has started reading the data from the frame memory **250**. In a case where it is determined that reading of the data from the frame memory **250** has been started (the image data frame has been started) in response to an input of a predetermined signal or command from the DMA controller **260**, for example, the second information extraction unit **271** proceeds to Step **S203**. On the other hand, in a case where it is determined that reading of the data from the frame memory **250** has not been started (the image data frame has not been started), the second information extraction unit **271** repeats the processing of Step **S201** at predetermined intervals until the reading is started.

(321) (Step **S203**)

(322) The second information extraction unit **271** resets various pieces of information generated at the time of reading the previous image data frame in the image data replacement processing, and proceeds to Step **S205**. The second information extraction unit **271** erases the ROI restoration information (the X-coordinate order data and the Z-coordinate order data) stored in the register or sets a predetermined value in the register, thereby resetting the ROI restoration information and the like in the previous image data frame.

(323) (Step **S205**)

(324) The second information extraction unit **271** determines whether or not embedded data has been input. Specifically, the second information extraction unit **271** determines whether or not the embedded data (EBD data **214A**) including the ROI information as the additional information has been input from the DMA controller **260**. In a case where it is determined that the EBD data **214A** read from the frame memory **250** has been input, the first information extraction unit **231** proceeds to Step **S207**. On the other hand, in a case where it is determined that the EBD data **214A** has not been input, the second information extraction unit **271** repeats the processing of Step **S205** at predetermined intervals, and waits for the execution of the processing of Step **S207** and subsequent

steps until the EBD data **214A** is input.

(325) Note that, in a case where a determination result indicating the data type corresponding to a normal image has been input as the additional information from the DMA controller **260** to the second information extraction unit **271**, it is sufficient if the second information processing unit **230b** performs the processing related to display of data of a normal image. The processing will be described later.

(326) (Step **S207**)

(327) The second information extraction unit **271** extracts the ROI information (the position information and the size information) from the embedded data (EBD data **214A**) in a similar manner to the processing performed by the first information extraction unit **231** in Step **S107** (see FIG. **20**) in the restoration processing, and proceeds to Step **S209**.

(328) (Step **S209**)

(329) The second information extraction unit **271** rearranges the extracted ROI information to generate the ROI restoration information (the X-coordinate order data and the Y-coordinate order data) similarly to the processing performed by the first information extraction unit **231** in Step **S109** (see FIG. **20**) in the restoration processing, and proceeds to Step **S211**. Further, at this time, the second information extraction unit **271** stores the ROI restoration information in the register, and outputs a signal indicating that the ROI restoration information has been generated to the image data replacement unit **272**. Note that, for example, the register in which the ROI restoration information generated by the second information extraction unit **271** in the image data replacement processing is stored is different from the register in which the ROI restoration information generated by the first information extraction unit **231** in the restoration processing is stored.

(330) (Step **S211**)

(331) In the second information processing unit **230b** included in the video reception device **200a**, the image data replacement unit **272** determines whether or not payload data has been input. The payload data in the image data replacement processing indicates the display target image data RD in units of pixel rows read from the frame memory **250** for each address by the DMA controller **260**. In a case where the display target image data RD has been input from the DMA controller **260**, the second information extraction unit **271** determines that the payload data has been input, and proceeds to Step **S213**. On the other hand, in a case where display target image data RD has not been input from the DMA controller **260**, the second information extraction unit **271** determines that the payload data has not been input, and repeats the processing in Step **S211** at predetermined intervals (for example, a cycle synchronized with the clock signal) until the display target image data RD is input.

(332) Hereinafter, the processing of Step **S213** and Step **S215** and the processing of Step **S217** or Step **S219** are processing performed for all the pixels in the payload data (display target image data RD), that is, processing performed so as to cover each pixel. Therefore, the image data replacement unit **272** repeats the processing in Steps **S213** and **S215** until the processing in the replacement process of the image data replacement processing ends for all the pixels in the display target image data RD (YES in Step **S221**), and performs the processing in Step **S217** or **S219** according to the result of Step **S215**.

(333) (Step **S213**)

(334) The image data replacement unit **272** acquires the display target image data, that is, the coordinates of the display target pixel in the display target image data RD read from the frame memory **250**, and proceeds to Step **S215**. The image data replacement unit **272** acquires the counter value of the vertical counter Yct as the pixel Y coordinate. Furthermore, the image data replacement unit **272** acquires the counter value of the horizontal counter Xct as the pixel X coordinate. As a result, the coordinates of each pixel are acquired. In the image data replacement processing, the image data replacement unit **272** sequentially acquires the coordinates from the head (X coordinate=0) for each pixel in the display target image data RD, for example, every time

Step S213 is performed at a cycle synchronized with the clock signal.

(335) The image data replacement unit **272** determines whether or not the coordinate position of the display target pixel acquired in Step S213 is included in the region of interest (ROI). As described above, the image data replacement unit **272** determines the value (pixel Y coordinate) of the vertical counter Yct on the basis of the Y-coordinate order data, and determines the value (pixel X coordinate) of the horizontal counter Xct on the basis of the X-coordinate order data. In a case where it is determined that the pixel Y coordinate is included in the vertical ROI range (the first determination condition is satisfied) and the pixel X coordinate is included in the horizontal ROI range (the second determination condition is satisfied), the image data replacement unit **272** determines that the display target pixel is included in the region of interest (ROI), and proceeds to Step S217. On the other hand, in a case where it is determined that any one of the first determination condition and the second determination condition is not satisfied, the image data replacement unit **272** determines that the display target pixel is included not in the region of interest but in the non-ROI image data, and proceeds to Step S219.

(336) (Step S217)

(337) The image data replacement unit **272** outputs the pixel to the display device **300** (see FIG. **18**) on the basis of the determination that the display target pixel is included in the region of interest, and proceeds to Step S221.

(338) (Step S219)

(339) The image data replacement unit **272** replaces the display target pixel with the fixed value image data on the basis of the determination that the display target pixel is included in the non-ROI image data. Specifically, the image data replacement unit **272** outputs the fixed value image data to the display device **300** instead of the display target pixel, and proceeds to Step S221.

(340) (Step S221)

(341) The image data replacement unit **272** determines whether or not all pieces of image data in a line that is being processed in the payload data, that is, all pixels in the display target image data RD in units of pixel rows, have been output. In a case where the counter value (pixel X coordinate) of the horizontal counter Xct has reached the value of an end X coordinate (an end coordinate in the X-axis direction) corresponding to the right end portion in the captured image, the image data replacement unit **272** determines that all the pixels in the display target image data RD have been output, and proceeds to Step S223. At this time, the image data replacement unit **272** resets the counter value of the horizontal counter Xct (sets the counter value to "0"). For example, it is assumed that the X coordinate of the right end portion of the captured image α is "1759", and the frame memory **250** can store image data of 1760 pixels (X coordinate=0 to 1759) per pixel row. In this case, in a case where the counter value of the horizontal counter Xct is "1759", the image data replacement unit **272** determines that all the pixels in the display target image data RD have been output. As described above, once the horizontal counter Xct is reset, the counter value of the vertical counter Yct is updated (incremented by 1). As a result, the value of the pixel Y coordinate common in the display target image data RD in units of pixel rows is updated.

(342) On the other hand, in a case where it is determined that the counter value of the horizontal counter Xct is less than the value of the end X coordinate in the frame memory **250**, the image data replacement unit **272** returns to Step S213. As a result, the replacement process in the image data replacement processing is performed for all the pixels in the display target image data RD in units of pixel rows.

(343) (Step S223)

(344) The image data replacement unit **272** determines whether or not processing for the last line of the payload data, that is, processing (processing in the replacement process of the image data replacement processing) for all pieces of image data in the frame memory has ended. The image data replacement unit **272** updates (increments by 1) the value (counter value) of the vertical counter Yct. For example, in a case where the value (pixel Y coordinate) of the vertical counter Yct

has reached the value of the Y coordinate corresponding to the lower end portion of the captured image, the image data replacement unit **272** determines that the processing for all pieces of display target image data RD read from the frame memory **250** has ended, and ends the image data replacement processing. At this time, the image data replacement unit **272** resets the horizontal counter Xct and the vertical counter Yct in this order (sets the counter values to “0”). As a result, both the counter values of the horizontal counter Xct and the vertical counter Yct become “0”. (345) For example, it is assumed that the Y coordinate of the lower end portion of the captured image α is “989”, and the frame memory **250** can store image data of 989 pixel rows. In this case, in a case where the value of the vertical counter Yct is “989”, the image data replacement unit **272** determines that the processing for all pieces of image data read from the frame memory **250** has ended, and ends the image data replacement processing. On the other hand, in a case where it is determined that the counter value of the vertical counter Yct is less than the value of the Y coordinate of the lower end portion of the captured image α , the image data replacement unit **272** returns to Step S211. As a result, the replacement process in the image data replacement processing is performed for all the pixels in the display target image data RD corresponding to all the pixel rows in the frame memory **250**, that is, all pieces of image data in the frame memory **250**. (346) As described above, the video reception device **200a** (see FIG. **19**) according to the present embodiment includes: the reception unit **210** that receives a transmission signal in which image data of a predetermined number of regions of interest (ROI) cut from a predetermined captured image is included in payload data, and ROI information is included in embedded data; and the information processing unit **230** (specifically, the first information processing unit **230a**) capable of performing restoration processing of restoring the image data of the region of interest so as to be displayable on the display device **300** (see FIG. **18**) on the basis of the ROI information corresponding to the predetermined number of regions of interest extracted from the embedded data. As a result, the image data of the region of interest can be efficiently displayed on the display device **300**.

(347) In addition, in a case where the image data of the region of interest is displayed on the display device **300**, the information processing unit **230** (specifically, the second information processing unit **230b**) in the video reception device **200a** according to the present embodiment replaces non-ROI image data which does not correspond to the image data of the region of interest, among the pieces of image data in units of screens of the display device **300** stored in the frame memory **250** with fixed value image data. As a result, it is possible to improve the visibility of image data of a region of interest to be displayed on the display device **300**.

(348) Furthermore, in the video reception device **200a** according to the present embodiment, the reception unit **210** and the information processing unit **230** (the first information processing unit **230a** and the second information processing unit **230b**) are configured as hardware. As a result, the video reception device **200a** can speed up the processing related to the restoration of the image data of the region of interest in the first information processing unit **230a** and the processing of replacing the image data in the second information processing unit **230b**, and can increase the number of image data frames processed per unit time.

(349) 5-3. Processing Related to Display of Data of Normal Image

(350) Next, an outline of processing related to display of data of a normal image in the second information processing unit **230b** (normal image display processing) will be described. The second information processing unit **230b** performs the normal image display processing in a case where a determination result indicating the data type corresponding to a normal image has been input as the additional information from the DMA controller **260** to the second information extraction unit **271**.

(351) Specifically, in a case where the input additional information is a determination result indicating the data type corresponding to the data of the normal image, the second information extraction unit **271** outputs the determination result to the image data replacement unit **272**. Once the determination result is input, the image data replacement unit **272** determines that the display

target image data RD input from the DMA controller **260** is data of a normal image. In this case, the image data replacement unit **272** outputs the display target image data RD including the data of the normal image to the display device **300** without performing the image data replacement processing. For example, the image data replacement unit **272** may divide the display target image data RD including the data of the normal image in units of pixels (for each pixel) and output the divided display target image data RD to the display device **300**, or may output the display target image data RD in units of pixel rows. As described above, the image data replacement unit **272** functions as an output unit that outputs image data to the display device **300**.

6. Modified Example of Restoration Processing

6-1. Modified Example 1

(352) Although the ROI image generation unit **234** performing the writing process in the restoration processing of the present embodiment divides the ROI pixel row data for each region of interest (ROI) and writes the divided ROI pixel row data in the frame memory **250**, the present disclosure is not limited thereto. Various methods are assumed for writing the ROI pixel row data in the payload data **215A** in the frame memory.

(353) For example, the ROI image generation unit **234** in the first information processing unit **230a** may transfer the image data (ROI pixel row data) of the region of interest in the payload data **215A** to the frame memory **250** by burst transfer on the basis of the ROI restoration information and write the image data. For example, in a case where a predetermined condition is satisfied in the writing process, the ROI image generation unit **234** inserts dummy image data between pieces of image data of two or more regions of interest in the payload data, and generates inserted dummy image data **234B** obtained by connecting the pieces of image data of the two or more regions of interest. Then, for example, the ROI image generation unit **234** may continuously write the generated inserted dummy image data **234B** in the frame memory by one instruction (for example, a data command is issued once).

(354) That is, the ROI image generation unit **234** may transfer the generated inserted dummy image data **234B** to the frame memory **250** by the burst transfer, and continuously write the inserted dummy image data **234B** in the frame memory **250**. Here, dummy image data included in the inserted dummy image data **234B** may be, for example, predetermined image data (for example, image data similar to the fixed value image data in the image data replacement processing or the like) that fills a gap between the two or more regions of interest.

(355) In the present modified example, for example, in a case where pieces of image data of two writing target ROIs are included in one piece of ROI pixel row data in the payload data **215A**, the first information extraction unit **231** may determine whether or not the above-described burst transfer can be performed according to a distance between the pieces of image data of the writing target ROIs, that is, the length of the gap. For example, the first information extraction unit **231** may determine that the burst transfer can be performed in a case where the gap between the pieces of image data of the writing target regions of interest (writing target ROIs) is narrow and a memory size (the number of bytes) of the dummy image data inserted into the gap is equal to or smaller than a predetermined size (an example of a predetermined condition). In this case, the first information extraction unit **231** generates a dummy image size in addition to a writing size of each piece of image data of the writing target ROIs as the writing information based on the ROI restoration information.

(356) For example, in a case where the memory size of the dummy image data is equal to or smaller than 128 bytes, the first information extraction unit **231** may determine that the burst transfer can be performed and generate the dummy image size as the writing information. Note that the memory size of the dummy image data used to determine whether or not the burst transfer can be performed and the size of the image data that can be subjected to the burst transfer are appropriately selected according to, for example, the specification of bus **240** used to transfer the image data in the video reception device **200a**. Note that in a case where the memory size of the

dummy image data exceeds 128 bytes and the burst transfer cannot be performed, it is sufficient if the first information extraction unit **231** determines to write the image data for each writing target ROI as in the above-described embodiment.

(357) Once the writing information including the dummy image size is input from the first information extraction unit **231**, the ROI image generation unit **234** generates dummy image data having the dummy image size, and for example, generates the inserted dummy image data **234B** by inserting the dummy image data between the pieces of image data of the two writing target ROIs. At this time, it is sufficient if the ROI image generation unit **234** determines an insertion position of the dummy image data on the basis of the writing size (division size) of each region of interest ROI. Once the inserted dummy image data **234B** is generated, the ROI image generation unit **234** issues a data command including the generated inserted dummy image data **234B**, and writes pieces of image data of a plurality of (for example, two) writing target ROIs in the frame memory **250** by the burst transfer.

(358) In a case where the ROI image generation unit **234** performs the burst transfer on pieces of image data of two or more writing target ROIs, the size of the image data (burst transfer size) transferred to the frame memory **250** by one data command, that is, the image size of the inserted dummy image data **234B**, is a size obtained by adding the size of the dummy image data (dummy image size) to the sum of the writing sizes of the pieces of image data of the writing target ROIs to be subjected to the burst transfer.

(359) Furthermore, in a case where the first information extraction unit **231** determines to perform the burst transfer for pieces of image data of a plurality of (for example, two) writing target ROIs, the ROI image address generation unit **233** generates an address of the frame memory **250** in units of burst transfers on the basis of the writing information including the dummy image size. In a case where the burst transfer of the inserted dummy image data **234B** is performed, the ROI image address generation unit **233** generates an address indicating a write destination of the inserted dummy image data **234B** in the frame memory **250** on the basis of the ROI restoration information. Specifically, the ROI image address generation unit **233** generates an address indicating the write destination of the inserted dummy image data **234B** on the basis of the writing information including the dummy image size generated by the first information extraction unit **231**.

(360) In this case, the ROI image address generation unit **233** generates a head address of the inserted dummy image data **234B** on the basis of the writing start X coordinate and the writing Y coordinate included in the writing information. Moreover, the ROI image address generation unit **233** performs addition on the head address according to the writing size of the inserted dummy image data **234B** (a size obtained by adding the dummy image size to the sum of the writing sizes of the pieces of image data of the writing target ROIs). As a result, consecutive addresses serving as write destinations in units of inserted dummy image data are generated.

(361) In addition, the ROI image address generation unit **233** outputs the image size (the number of pixels) of the inserted dummy image data **234B** written by the burst transfer to the ROI image generation unit **234** as the number of burst transfers. Once the number of burst transfers is input, the ROI image generation unit **234** issues a data command including the writing inserted dummy image data **234B** having a size corresponding to the number of burst transfers. In this way, the inserted dummy image data **234B** is transmitted to the frame memory **250** and written by the burst transfer.

(362) Furthermore, in a case where three or more writing target ROIs are included in the payload data **215A** and the number of gaps between the regions of interest is two or more, it is sufficient if the first information extraction unit **231** determines the memory size of the dummy image data for each of the gaps. In a case where the first information extraction unit **231** determines that the inserted dummy image data **234B** including the pieces of image data of all the writing target ROIs in the payload data **215A** can be transferred to the frame memory **250** (in a case where the dummy image sizes related to all the gaps are equal to or smaller than a predetermined number), the

inserted dummy image data **234B** including the pieces of image data of all the writing target ROIs is written in the frame memory **250** by issuing a data command once. That is, the number of times the inserted dummy image data **234B** is written in the frame memory **250** is 1.

(363) Meanwhile, for example, it is assumed that a wide gap for which the dummy image size exceeds a predetermined number (for example, 128 bytes) is included in a plurality of gaps between pieces of image data of writing target ROIs (for example, three gaps between pieces of image data of four writing target ROIs). In this case, the first information extraction unit **231** may determine to perform the burst transfer by dividing the ROI pixel row data in the payload data **215A** into data in front of the wide gap and data behind the wide gap. For example, inserted dummy image data **234B-1** including pieces of image data of two writing target ROIs from the head among four writing target ROIs and inserted dummy image data **234B-2** including pieces of image data of the remaining writing target ROIs (third and fourth writing target ROIs from the head) may be generated. In this case, the number of times the inserted dummy image data **234B** is written in the frame memory **250** is 2.

(364) In addition, for pieces of image data of a plurality of writing target ROIs in the payload data **215A**, the first information extraction unit **231** may determine to perform the burst transfer on a predetermined number (two or more) of writing target ROIs and write pieces of image data of the remaining writing target ROIs in units of regions of interest as usual.

(365) As described above, by performing the burst transfer in units of ROI pixel row data, the number of times of writing can be reduced and the writing process can be speeded up as compared with a case where the image data is written in the frame memory in units of regions of interest (ROIs).

6-2. Modified Example 2

(366) In the present embodiment, an address generated by the ROI image address generation unit **233** is an address corresponding to a restoration position indicating a relative position of a region of interest in a captured image in the frame memory **250**, but the present disclosure is not limited thereto. For example, the ROI image address generation unit **233** may be configured to generate addresses indicating arbitrary positions (an example of a predetermined position) at which pieces of image data of a predetermined number of regions of interest can be displayed without overlapping each other in the screen of the display device **300**. That is, the ROI image generation unit **234** may be configured to write the image data of the region of interest so that the image data of a predetermined number of regions of interest can be displayed without overlapping in the screen of the display device **300**.

(367) For example, the ROI image address generation unit **233** may generate addresses indicating arbitrary positions (arbitrary Y-axis positions) at which the pieces of image data of the predetermined number of regions of interest can be displayed in order in the Y-axis direction of the display device **300** so as not to overlap each other. Furthermore, the ROI image generation unit **234** may be configured to write the image data of the region of interest at an arbitrary Y-axis position in the screen of the display device **300**. In this case, the first information extraction unit **231** generates the writing information that enables the address generation according to the arbitrary Y-axis position by using the Y-coordinate order data and the Y-coordinate order data of the ROI restoration information. For example, the first information extraction unit **231** uses the X-axis coordinate order data and the Y-axis coordinate order data (see FIG. 17) to generate the writing information used for the address generation for displaying each of the regions of interest ROI0 to ROI2 (see FIG. 13) at the arbitrary Y-axis position in the display device **300**.

(368) For example, the first information extraction unit **231** determines the display order of the regions of interest ROI0 to ROI2 on the display device **300** on the basis of the Y-axis coordinate order data. For example, the first information extraction unit **231** determines the storage order of the Y-axis coordinate order data, that is, the ascending order of the start point Y coordinates as the display order of the regions of interest ROI0 to ROI2. In this example, the order of the regions of

interest ROI2, ROI1, and ROI0 is the display order in the Y-axis direction in the screen of the display device **300**.

(369) Once the display order is determined, the first information extraction unit **231** determines, for example, a display start Y coordinate which is a head Y coordinate when the image data of each region of interest (ROI) is displayed on the display device **300**. As described above, the image data in units of screens of the display device **300** is written in the frame memory **250**. Therefore, the display position (coordinates) in the screen of the display device **300** corresponds to the writing position in the frame memory **350**.

(370) For example, the image data of the region of interest ROI2 that is displayed at the head position is displayed from the top pixel row of the display device **300**. Therefore, the first information extraction unit **231** sets the writing start Y coordinate of the image data of the region of interest ROI2 to “0”. Furthermore, the image data of the region of interest ROI1 is displayed below the image data of the region of interest ROI2 so as not to overlap the image data of the region of interest ROI2. Therefore, the first information extraction unit **231** sets the display start Y coordinate of the image data of the region of interest ROI1 to “600 (=0+600 (length in Y-axis direction of region of interest ROI2))”. Note that the length in the Y-axis direction is calculated by “end point Y coordinate–start point Y coordinate” in the Y-coordinate order data. Similarly, the first information extraction unit **231** sets the display start Y coordinate of the image data of the region of interest ROI0 displayed below the image data of the region of interest ROI1 to “1200 (=600 (display start Y coordinate of image data of region of interest ROI1)+600 (length of region of interest ROI1 in Y-axis direction))”.

(371) Once the display start Y coordinate of the image data of each region of interest is determined, the first information extraction unit **231** then adds 1 to the value of the display start Y coordinate corresponding to each region of interest and updates the value every time the image data of each region of interest is input as the payload data. As a result, the display start Y coordinate corresponding to the arbitrary Y-axis position can be generated.

(372) Further, a display start X coordinate which is a head X coordinate when the image data of the region of interest is displayed on the display device **300** at the arbitrary Y-axis position in the screen of the display device **300** is determined. In the present modified example, the writing start X coordinates of the pieces of image data of the respective regions of interest have a uniform value. For example, it is assumed that the pieces of image data of the respective regions of interest are displayed in a left-aligned manner on the screen of the display device **300** in a case where the pieces of image data of the respective regions of interest are displayed at the arbitrary Y-axis positions. In this case, the first information extraction unit **231** generates a common value “0” for each region of interest as the display start X coordinate. That is, in a case where the pieces of image data of the regions of interest are displayed at the arbitrary Y-axis positions, the pieces of image data of the respective regions of interest are displayed while being arranged in the Y-axis direction in order from the upper end of the screen in a left-aligned manner starting from the upper-left end (origin position) of the screen of the display device **300**. In addition, the first information extraction unit **231** generates the writing size in a manner similar to that in the above-described embodiment.

(373) Once the writing information corresponding to display of the image data of the region of interest at the arbitrary Y-axis position is input from the first information extraction unit **231**, the ROI image address generation unit **233** generates an address for writing the image data of the region of interest in the frame memory **250** on the basis of the writing information. The ROI image address generation unit **233** can generate an address corresponding to the arbitrary Y-axis position in the frame memory **250** by generating an address on the basis of the input writing information similarly to the above-described embodiment. Further, similarly to the above-described embodiment, the ROI image generation unit **234** generates the writing target image data **234A**, and issues a data command at a timing synchronized with the address issuance of the ROI image address generation unit **233**. As a result, the ROI image generation unit **234** can write the pieces of

image data of the regions of interest (ROIs) to the arbitrary Y-axis positions at which the pieces of image data of the predetermined number of regions of interest can be sequentially displayed in the Y-axis direction without overlapping each other in the screen of the display device **300**.

(374) Note that the present modified example is not limited thereto, and for example, the ROI image address generation unit **233** may generate addresses indicating arbitrary positions (arbitrary X-axis positions) at which the pieces of image data of the predetermined number of regions of interest can be sequentially displayed in the X-axis direction of the display device **300** so as not to overlap each other. Furthermore, the ROI image generation unit **234** may be configured to write the image data of the region of interest at an arbitrary X-axis position in the screen of the display device **300**. In this case, the first information extraction unit **231** generates the writing information that enables the address generation according to the arbitrary X-axis position by using the X-coordinate order data and the Y-coordinate order data of the ROI restoration information. At this time, the first information extraction unit **231** determines the display order of each region of interest as the storage order of the X-coordinate order data, that is, the ascending order of the start point X coordinates (in the order of the regions of interest **ROI2**, **ROI0**, and **ROI1**).

(375) In a case where the pieces of image data of the regions of interest are displayed at the arbitrary X-axis positions, the pieces of image data of the respective regions of interest are displayed in the X-axis direction in order from the left end of the screen starting from the upper-left end of the screen of the display device **300**.

(376) Once the display order is determined, the first information extraction unit **231** determines the display start X coordinate. For example, the region of interest **ROI2** that is displayed at the head position is displayed from the upper-left end position in the display device **300**. Therefore, the first information extraction unit **231** sets the display start X coordinate of the region of interest **ROI2** to “0”. In addition, the region of interest **ROI0** is displayed on the right side of the region of interest **ROI2** so as not to overlap the region of interest **ROI2**. Therefore, the first information extraction unit **231** sets the writing start X coordinate of the region of interest **ROI0** to “400 (=0+400 (length in X-axis direction of region of interest **ROI2**))”. Note that the length in the X-axis direction is calculated by “end point X coordinate–start point X coordinate” in the X-coordinate order data. Similarly, the first information extraction unit **231** sets the display start X coordinate of the region of interest **ROI1** displayed on the right side of the region of interest **ROI0** to “800 (=400 (display start X coordinate of image data of region of interest **ROI0**)+400 (length of region of interest **ROI0** in X-axis direction))”.

(377) In addition, in a case where the pieces of image data of the regions of interest are displayed at the arbitrary X-axis positions on the screen of the display device **300**, the display start Y coordinates of the pieces of image data of the respective regions of interest have a uniform value. For example, it is assumed that the pieces of image data of the respective regions of interest are displayed in a top-aligned manner on the screen of the display device **300** in a case where the pieces of image data of the regions of interest are displayed at the arbitrary X-axis positions. In this case, the first information extraction unit **231** generates a common value “0” for each region of interest as the display start Y coordinate. Furthermore, the first information extraction unit **231** adds 1 to the value of the display start Y coordinate corresponding to each region of interest and updates the value every time the image data of each region of interest is input as the payload data. As a result, the display start Y coordinate corresponding to the arbitrary X-axis position can be generated. In addition, the first information extraction unit **231** generates the writing size in a manner similar to that in the above-described embodiment.

(378) Once the writing information corresponding to the display of the image data of the region of interest at the arbitrary X-axis position is input from the first information extraction unit **231**, the ROI image address generation unit **233** generates an address on the basis of the input writing information, similarly to the above-described embodiment. As a result, an address corresponding to the arbitrary X-axis position in the frame memory **250** can be generated. Furthermore, the ROI

image generation unit **234** can write the pieces of image data of the regions of interest to the arbitrary X-axis positions at which the pieces of image data of the predetermined number of regions of interest can be sequentially displayed in the X-axis direction without overlapping each other in the screen of the display device **300**.

(379) As described above, the video reception device **200a** can restore the image data of the region of interest (ROI) so as to be displayable at an arbitrary position (for example, the X-axis arbitrary position or Y-axis arbitrary position) in the display device **300** by performing the restoration processing in the present modified example. As a result, the image data of the region of interest can be efficiently displayed on the display device **300** (see FIG. **18**). In addition, the pieces of image data of the predetermined number of regions of interest are displayed while being arranged so as not to overlap each other in one direction (the X-axis direction or Y-axis direction), as a result of which, for example, recognition processing and comparison processing for the image data of each region of interest can be efficiently performed.

6-3. Other Modified Examples

(380) Further, in the above-described embodiment, the first information extraction unit **231** of the first information processing unit **230a** of the video reception device **200a** performs the information extraction process in the restoration processing (generation of the ROI restoration information from the extracted ROI information), but the present disclosure is not limited thereto. For example, in the video reception device **200a** according to the present disclosure, the EBD interpretation unit **214** of the reception unit **210** may extract the ROI information (the position information and the size information) from the embedded data in the information extraction process. In this case, it is sufficient if the EBD interpretation unit **214** outputs the extracted ROI information to the first information extraction unit **231**. In addition, it is sufficient if the first information extraction unit **231** generates the ROI restoration information on the basis of the input ROI information.

(381) Furthermore, in the above-described embodiment, as an example, the region of interest in the captured image has a rectangular shape, but the present disclosure is not limited thereto. Even in a case where the region of interest ROI is not rectangular, the video reception device **200a** can perform the restoration processing and the image data replacement processing in the above-described embodiment.

(382) Although the present disclosure has been described above with reference to the underlying technologies, the embodiment, and the modified examples thereof, the present disclosure is not limited to the above-described embodiment and the like, and various modifications can be made. Note that the effects described in the present specification are merely examples. The effects of the present disclosure are not limited to the effects described herein. The present disclosure may have effects other than those described herein.

(383) Furthermore, for example, the present disclosure can have the following configuration. (1)

(384) A reception device including: a reception unit that receives a transmission signal in which image data of a predetermined number of regions of interest (ROIs) cut from a predetermined captured image is included in payload data and ROI information corresponding to a predetermined number of the ROIs is included in embedded data; and a processing unit that is configured to perform restoration processing of restoring the image data of the ROI so as to be displayable on a predetermined display device on the basis of the ROI information extracted from the embedded data. (2)

(385) The reception device according to (1), in which the processing unit extracts position information and size information of each of a predetermined number of the ROIs in the captured image as the ROI information. (3)

(386) The reception device according to (2), in which the processing unit rearranges the extracted position information and size information to generate ROI restoration information used for restoration of the image data of the ROI. (4)

(387) The reception device according to (3), in which the position information includes an X

coordinate and a Y coordinate indicating an upper-left end portion of the ROI in the captured image, and the processing unit generates, as the ROI restoration information, X-coordinate order data obtained by rearranging the position information and the size information in ascending order of values of the X coordinates and Y-coordinate order data obtained by rearranging the position information and the size information in ascending order of values of the Y coordinates. (5)

(388) The reception device according to any one of (1) to (4), further including a frame memory that is configured to store the image data of the ROI, in which the processing unit writes the image data of the ROI in the frame memory on the basis of the ROI restoration information generated from the ROI information. (6)

(389) The reception device according to (5), in which the processing unit writes the image data of the ROI in the frame memory in units of the payload data on the basis of the ROI restoration information. (7)

(390) The reception device according to (6), in which the processing unit divides the image data of the ROI in the payload data for each ROI on the basis of the ROI restoration information and writes the divided image data in the frame memory. (8)

(391) The reception device according to (6), in which in a case where a predetermined condition is satisfied, the processing unit inserts dummy image data between pieces of image data of two or more of the ROIs in the payload data to generate inserted dummy image data in which the pieces of image data of the two or more of the ROIs are connected, and writes the generated inserted dummy image data in the frame memory continuously by one instruction. (9)

(392) The reception device according to any one of (5) to (8), in which the processing unit specifies a restoration position corresponding to a relative position of the ROI in the captured image in the frame memory on the basis of the ROI restoration information, and writes the image data of the ROI to the restoration position. (10)

(393) The reception device according to any one of (5) to (8), in which the processing unit writes pieces of image data of a predetermined number of the ROIs in the frame memory so as to be displayable without overlapping each other in a screen of the display device on the basis of the ROI restoration information. (11)

(394) The reception device according to any one of (5) to (10), in which the processing unit generates an address indicating a write destination of the image data of the ROI in the frame memory on the basis of the ROI restoration information. (12)

(395) The reception device according to (8), in which the processing unit generates an address indicating a write destination of the inserted dummy image data in the frame memory on the basis of the ROI restoration information. (13)

(396) The reception device according to any one of (5) to (12), in which in a case where the image data of the ROI is displayed on the display device, the processing unit replaces non-ROI image data which does not correspond to the image data of the ROI among pieces of image data in units of screens of the display device stored in the frame memory with fixed value image data. (14)

(397) The reception device according to (13), in which the processing unit specifies the non-ROI image data on the basis of the ROI restoration information. (15)

(398) The reception device according to (14), in which the processing unit determines whether each pixel of the image data in the units of screens is included in the image data of the ROI or in the non-ROI image data on the basis of the ROI restoration information. (16)

(399) A transmission system including: a transmission device that sends image data of a region of interest (ROI) as payload data and sends ROI information as embedded data; and a reception device that includes a reception unit that receives a transmission signal in which the image data of a predetermined number of the ROIs cut from a predetermined captured image is included in the payload data and the ROI information corresponding to a predetermined number of the ROIs is included in the embedded data, and a processing unit that is configured to perform restoration processing of restoring the image data of a predetermined number of the ROIs so as to be

displayable on a predetermined display device on the basis of the ROI information extracted from the embedded data. (17)

(400) The transmission system according to (16), in which the reception device rearranges, by the processing unit, position information and size information of each of a predetermined number of the ROIs in the captured image extracted as the ROI information to generates ROI restoration information used for restoration of the image data of the ROI. (18)

(401) The transmission system according to (17), in which the reception device further includes a frame memory that is configured to store the image data of the ROI, and writes, by the processing unit, the image data of the ROI in the frame memory on the basis of the ROI restoration information. (19)

(402) The transmission system according to (18), in which in a case where the image data of the ROI is displayed on the display device, the reception device replaces, by the processing unit, non-ROI image data which does not correspond to the image data of the ROI among pieces of image data in units of screens of the display device stored in the frame memory with fixed value image data.

REFERENCE SIGNS LIST

(403) **1, 2** Video transmission system **31, 110** Imaging unit **32, 41** Control unit **42** Image processing unit **100** Video transmission device **100A** CSI transmitter **100B** CCI slave **111** Captured image **112, 112a1, 112a2, 112a3, 112a4, 112b1, 112b4, 123a4, 223A** ROI image **112b** Compressed image data **113, 114** Position information **115** Priority **116, 116a1, 116a2** Transmission image **118** Image **120, 130** Image processing unit **120A, 120A1, 120A2, 130A, 147B** Compressed image data **120B** ROI information **120C** Frame information **121** ROI cutting unit **122** ROI analysis unit **123** Detection unit **124** Priority setting unit **125, 131** Encoding unit **126** Image processing control unit **140** Transmission unit **141** LINK control unit **142** ECC generation unit **143** PH generation unit **144** EBD buffer **145** ROI data buffer **146** Normal image data buffer **147** Combining unit **147A** Transmission data **200, 200a** Video reception device **200A** CSI receiver **200B** CCI master **210** Reception unit **211** Header separation unit **212** Header interpretation unit **213** Payload separation unit **214** EBD interpretation unit **214A** EBD data **215** ROI data separation unit **215A, 215B** Payload data **220** Information processing unit **221** Information extraction unit **221A** Extracted information **222, 232** ROI decoding unit **222A** Image data **223** ROI image generation unit **224** Normal image decoding unit **224A** Normal image **230** Information processing unit **230a** First information processing unit **230b** Second information processing unit **231** First information extraction unit **232A** ROI decoded image data **233** ROI image address generation unit **234** ROI image generation unit **234A** Writing target image data **235** Normal image address generation unit **236** Normal image decoding unit **237** Normal image generation unit **240** Bus **250** Frame memory **260** DMA controller **271** Second information extraction unit **272** Image data replacement unit **300** Display device Cb Chrominance component CCI Camera control interface CL Clock lane RD Display target image data

Claims

1. A reception device comprising: a reception circuitry configured to receive a transmission signal from a transmission device, wherein the transmission signal includes payload data and embedded data, wherein the payload data includes image data of a predetermined number of regions of interest (ROIs) cut from a predetermined captured image, wherein one or more of the predetermined number of the ROIs have a non-rectangular shape and do not overlap with any other of the predetermined number of the ROIs, wherein the non-rectangular shape has a plurality of sides, wherein two of the plurality of sides intersect with each other at approximately a ninety-degree angle, and wherein the embedded data includes ROI information corresponding to the predetermined number of the ROIs; and a processing circuitry configured to extract the image data

of the predetermined number of the ROIs from the payload data and the ROI information from the embedded data, and restore the image data of the predetermined number of the ROIs so as to be displayable on a predetermined display device on a basis of the ROI information extracted from the embedded data, wherein the image data that is restored is less than all of the predetermined captured image, and wherein the image data that is restored includes one or more ROI images that each have a shape other than a rectangular shape that corresponds to the one or more of the predetermined number of the ROIs that each have the non-rectangular shape.

2. The reception device according to claim 1, wherein the processing circuitry is further configured to extract position information and size information of each of a predetermined number of the ROIs in the predetermined captured image as the ROI information.

3. The reception device according to claim 1, further comprising a frame memory that is configured to store the image data of the ROI, wherein the processing circuitry is further configured to write the image data of the ROI in the frame memory on a basis of ROI restoration information generated from the ROI information.

4. The reception device according to claim 1, wherein the predetermined number of the ROIs includes four or more ROIs, a first ROI of the four or more ROIs has a rectangular shape that does not overlap with any other ROIs, a second ROI of the four or more ROIs has a first non-rectangular shape that does not overlap with the any other ROIs, wherein the first non-rectangular shape has a first plurality of sides, and wherein two of the first plurality of sides intersect with each other at approximately a ninety-degree angle, a third ROI of the four or more ROIs has a second non-rectangular shape, wherein the second non-rectangular shape has a second plurality of sides, and wherein two of the second plurality of sides intersect with each other at approximately a ninety-degree angle, and a fourth ROI of the four or more ROIs has a third non-rectangular shape, the fourth ROI being directly adjacent to the third ROI, wherein the second non-rectangular shape has a second plurality of sides, and wherein two of the second plurality of sides intersect with each other at approximately a ninety-degree angle.

5. The reception device according to claim 2, wherein the processing circuitry is further configured to rearrange the extracted position information and size information to generate ROI restoration information used for restoration of the image data of the ROI.

6. The reception device according to claim 3, wherein the processing circuitry is further configured to write the image data of the ROI in the frame memory in units of the payload data on a basis of the ROI restoration information.

7. The reception device according to claim 3, wherein the processing circuitry is further configured to specify a restoration position corresponding to a relative position of the ROI in the predetermined captured image in the frame memory on a basis of the ROI restoration information, and writes the image data of the ROI to the restoration position.

8. The reception device according to claim 3, wherein the processing circuitry is further configured to write pieces of image data of a predetermined number of the ROIs in the frame memory so as to be displayable without overlapping each other in a screen of the predetermined display device on a basis of the ROI restoration information.

9. The reception device according to claim 3, wherein the processing circuitry is further configured to generate an address indicating a write destination of the image data of the ROI in the frame memory on a basis of the ROI restoration information.

10. The reception device according to claim 3, wherein in a case where the image data of the ROI is displayed on the predetermined display device, the processing circuitry is further configured to replace non-ROI image data which does not correspond to the image data of the ROI among pieces of image data in units of screens of the predetermined display device stored in the frame memory with fixed value image data.

11. The reception device according to claim 5, wherein the position information includes an X coordinate and a Y coordinate indicating an upper-left end portion of the ROI in the predetermined

captured image, and the processing circuitry is further configured to generate, as the ROI restoration information, X-coordinate order data obtained by rearranging the position information and the size information in ascending order of values of the X coordinates and Y-coordinate order data obtained by rearranging the position information and the size information in ascending order of values of the Y coordinates.

12. The reception device according to claim 6, wherein the processing circuitry is further configured to divide the image data of the ROI in the payload data for each ROI on a basis of the ROI restoration information and writes the divided image data in the frame memory.

13. The reception device according to claim 6, wherein in a case where a predetermined condition is satisfied, the processing circuitry is further configured to insert dummy image data between pieces of image data of two or more of the ROIs in the payload data to generate inserted dummy image data in which the pieces of image data of the two or more of the ROIs are connected, and writes the generated inserted dummy image data in the frame memory continuously by one instruction.

14. The reception device according to claim 10, wherein the processing circuitry is further configured to specify the non-ROI image data on a basis of the ROI restoration information.

15. The reception device according to claim 13, wherein the processing circuitry is further configured to generate an address indicating a write destination of the inserted dummy image data in the frame memory on a basis of the ROI restoration information.

16. The reception device according to claim 14, wherein the processing circuitry is further configured to determine whether each pixel of the image data in the units of screens is included in the image data of the ROI or in the non-ROI image data on a basis of the ROI restoration information.

17. A transmission system comprising: a transmission device including a transmission circuitry configured to send a transmission signal including payload data and embedded data, wherein the payload data includes image data of a predetermined number of regions of interest (ROIs) that are cut from a predetermined captured image, wherein one or more of the predetermined number of the ROIs have a non-rectangular shape and do not overlap with any other of the predetermined number of the ROIs, wherein the non-rectangular shape has a plurality of sides, wherein two of the plurality of sides intersect with each other at approximately a ninety-degree angle, and wherein the embedded data includes ROI information; and a reception device including a reception circuitry configured to receive the transmission signal, and a processing circuitry configured to extract the image data of the predetermined number of the ROIs from the payload data and the ROI information from the embedded data, and restore the image data of the predetermined number of the ROIs so as to be displayable on a predetermined display device on a basis of the ROI information extracted from the embedded data, wherein the image data that is restored is less than all of the predetermined captured image, and wherein the image data that is restored includes one or more ROI images that each have a shape other than a rectangular shape that corresponds to the one or more of the predetermined number of the ROIs that each have the non-rectangular shape wherein one or more of the predetermined number of ROIs have a non rectangular shape.

18. The transmission system according to claim 17, wherein wherein the processing circuitry is further configured to rearrange position information and size information of each of a predetermined number of the ROIs in the predetermined captured image extracted as the ROI information to generate ROI restoration information used for restoration of the image data of the ROI.

19. The transmission system according to claim 18, wherein the reception device further includes a frame memory that is configured to store the image data of the ROI, and wherein the processing circuitry is further configured to write the image data of the ROI in the frame memory on a basis of the ROI restoration information.

20. The transmission system according to claim 19, wherein in a case where the image data of the

ROI is displayed on the predetermined display device, the processing circuitry is further configured to replace non-ROI image data which does not correspond to the image data of the ROI among pieces of image data in units of screens of the predetermined display device stored in the frame memory with fixed value image data.
