

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12408752
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Farjamrad; Bobby

Cabinet hanging system

Abstract

The invention is generally a cabinet hanging system that, in exemplary embodiments, includes a wall cleat hanger and at least one cabinet. The at least one cabinet has a plurality of recesses on its rear exterior edge that are substantially similar to the same shape of the wall cleat hanger. The recesses allow a user to hang the cabinets on their wall without needing to fasten the cabinets to the wall cleat hanger or the wall. This invention alleviates the burden of complicated cabinet systems installations while simultaneously allowing the user to install the cabinet system without the assistance of another person. In an exemplary embodiment, the cabinet has a first elongated recess and a second elongated recess. Terminal cabinets replace one elongated recess with a finished panel and a wall cleat. The wall cleat allows terminal cabinets to securely rest on the wall cleat hanger.

Inventors:	Farjamrad; Bobby (Santa Ana, CA)
Applicant:	PRIME TECH CABINETS, INC. (Santa Ana, CA)
Family ID:	67106222
Assignee:	PRIME TECH CABINETS, INC. (Santa Ana, CA)
Appl. No.:	17/346088
Filed:	June 11, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20210298475 A1	Sep. 30, 2021

Related U.S. Application Data

continuation parent-doc US 16445591 20190619 US 11058222 child-doc US 17346088
continuation parent-doc US 16027079 20180703 US 10342345 child-doc US 16445591

Publication Classification

Int. Cl.: A47B95/00 (20060101); A47B96/06 (20060101)

U.S. Cl.:

CPC A47B95/008 (20130101); A47B96/067 (20130101);

Field of Classification Search

CPC: A47B (95/008); A47B (96/067); A47B (96/06); A47B (47/0041); A47B (95/002); A47B (47/042); A47B (97/001); A47B (2220/0052); A47B (47/0075); A47B (47/0091); A47B (85/00); A47B (96/1441); A47B (83/045); A47B (77/00); A47B (96/14); A47B (2230/06); A47F (5/08); A47F (5/0838); A47F (5/0846); A47F (5/00)

USPC: 312/245; 312/198; 312/257.1; 312/246; 312/263; 312/265.5; 211/94.01; 211/90.01; 211/90.04; 211/90.02; 211/87.01; 211/105.1; 211/189; 211/175; 211/85.3; 211/118; 211/186; 211/187; 211/86.01; 108/152; 248/225.51; 248/225.2; 248/225.21; 248/222.11; 248/225.11; 248/214; 248/215; 248/216.1; 248/227.4; 248/250; 248/501; 248/500; 248/223.41; 248/339; 248/224.61

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2521134	12/1949	Stanitz	N/A	N/A
2708147	12/1954	Duggan	N/A	N/A
3241850	12/1965	Porpst	N/A	N/A
3669035	12/1971	Grossman	N/A	N/A
3698565	12/1971	Weber	N/A	N/A
3885845	12/1974	Krieks	N/A	N/A
3899228	12/1974	Schreiber	312/107	A47B 47/042
3908831	12/1974	Brendgord	N/A	N/A
3950049	12/1975	Drass	N/A	N/A
4165852	12/1978	Chervenak	N/A	N/A
4228906	12/1979	Jones	N/A	N/A
4329003	12/1981	Manchester	N/A	N/A
4342439	12/1981	Bruner	N/A	N/A
4629076	12/1985	Amstutz	N/A	N/A
4928833	12/1989	Huizenga	211/187	A47B 95/008
5050832	12/1990	Lee	248/222.51	A47B 95/008
5222611	12/1992	Wood	N/A	N/A
5392934	12/1994	Fox	248/220.31	A47F 5/0846
5412912	12/1994	Alves	N/A	N/A
5582306	12/1995	Balter	211/187	A47B 61/00
5624168	12/1996	Licciardello	N/A	N/A
5819958	12/1997	Dement	N/A	N/A
5951127	12/1998	Smith	248/909	A47B 87/007
6113201	12/1999	Bauer	N/A	N/A

8444235	12/2012	Gmerek	N/A	N/A
9526336	12/2015	Wells	N/A	N/A
2006/0091271	12/2005	Nowak	N/A	N/A
2006/0283822	12/2005	Jacques	N/A	N/A
2008/0173778	12/2007	Mertens	N/A	N/A
2010/0308702	12/2009	Apgood	N/A	N/A
2011/0025180	12/2010	Ilich	N/A	N/A
2011/0147551	12/2010	Richard	N/A	N/A
2013/0134849	12/2012	Menzel	312/265.5	A47B 95/008
2015/0053635	12/2014	Ahart	211/206	A47B 96/06
2015/0351538	12/2014	Wells	N/A	N/A
2016/0045026	12/2015	Trunkle	N/A	N/A
2016/0235195	12/2015	Ahart	N/A	A47B 96/024
2017/0079426	12/2016	Davis	N/A	N/A
2018/0098629	12/2017	Knepper	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
4114378	12/1991	DE	N/A
2404411	12/1978	FR	N/A
2444897	12/2007	GB	N/A

Primary Examiner: Tefera; Hiwot E

Attorney, Agent or Firm: Jafari Law Group, Inc.

Background/Summary

TECHNICAL FIELD OF THE INVENTION

(1) The present invention relates generally to storage systems, and more specifically, to a wall-mounted storage system capable of being installed by an individual.

COPYRIGHT AND TRADEMARK NOTICE

(2) A portion of the disclosure of this patent application may contain material that is subject to copyright protection. The owner has no objection to the facsimile reproduction by anyone of the patent document or the patent disclosure, as it appears in the Patent and Trademark Office patent file or records, but otherwise reserves all copyrights whatsoever.

(3) Certain marks referenced herein may be common law or registered trademarks of third parties affiliated or unaffiliated with the applicant or the assignee. Use of these marks is by way of example and should not be construed as descriptive or to limit the scope of this invention to material associated only with such marks.

BACKGROUND OF THE INVENTION

(4) Storage systems capable of being mounted to walls, such as the walls in a kitchen, garage, or office, are well known in the art. However, the wall-mounted storage systems described in the prior art are cumbersome and difficult to install, especially when said storage systems are being installed by an individual. The challenge in solo-installing wall-mounted storage systems is particularly present when various tools and fasteners are required because at least one person is needed to hold the storage system level and at the desired height while at least one additional person is needed to fasten and secure the cabinet to the wall.

(5) Additionally, once the storage system is mounted to the wall, it is often equally as cumbersome

to uninstall and reinstall the cabinets. For example, changes to a person's walls or personal preferences may leave said person inclined to change which direction the doors on the cabinets open. In order to facilitate this change, the doors would have to be removed from their hinges or other fasteners, flipped, and reattached to said hinges or fasteners. As is all too common, getting the doors to perfectly realign is no easy feat. Also, removing and reattaching the doors may require the efforts of multiple people because one person may need to hold the door steady while another person detaches and reattaches the door.

(6) There have been attempts to solve this and other related wall-mounted storage system problems. For example, U.S. Pat. No. 9,526,336 to Wells (the "336 Patent") describes a storage system wherein the cabinets have notches on the upper back portion of the cabinet which are used to slide the cabinet over the alignment rail. However, the storage members of the '336 Patent are attached to the wall via at least one fastener that extends through a first rail and a second rail. The use of fasteners to attach the cabinets to the wall is not only less cost effective but also decreases the ease with which a solo installer may install the storage system because more tools and people are required to complete installation. Furthermore, the '336 Patent only has notches on the upper back portion of the cabinets, and thus the cabinets are only capable of being installed in a single orientation; such a design limits how doors on the cabinet may open

(7) The prior art illuminates a clear deficiency in existing wall-mounted storage systems. Therefore, there exists a previously unappreciated need for a new and improved wall-mounted storage system that can easily be installed by an individual without needing to use fasteners to attach the cabinets to a wall cleat hanger. The present invention overcomes the above-described disadvantages of presently existing wall-mounted storage systems. It is to these ends that the present invention has been developed.

SUMMARY OF THE INVENTION

(8) To minimize the limitations in the prior art, and to minimize other limitations that will be apparent upon reading and understanding the present specification, the present invention describes a wall-mounted storage system, such as cabinets for use in a kitchen, garage, or office, which can be easily and quickly installed by an individual. A wall-mounted storage system in accordance with the present invention may incorporate a plurality of cabinets with a plurality of hanger cutouts, or recesses, located on a rear exterior edge of said cabinets, the hanger cutouts being designed to receive a wall cleat hanger that is fastened to a wall.

(9) An apparatus in accordance with one embodiment of the present invention may be comprised of a wall cleat hanger and a plurality of cabinets, each cabinet further comprising at least two pairs of recesses located on upper and lower portions of a rear exterior edge of said cabinets, the recesses being formed to receive and rest on the wall cleat hanger. The recesses may have an upper and lower boundary to securely receive and rest on the wall cleat hanger, thereby mounting the cabinets to a wall and preventing said cabinets from falling off the wall.

(10) Another apparatus in accordance with one embodiment of the present invention may be comprised of a wall cleat hanger and a plurality of cabinets, each cabinet further comprising an at least single pair of recesses located on a rear exterior edge of said cabinets, the recesses being formed to receive and rest on the wall cleat hanger. The at least single pair of recesses may be elongated and allow a user to mount the cabinets to a wall, thereby preventing said cabinets from falling off the wall. Furthermore, having an elongated recess may allow a user to install the cabinets on bumpy, uneven, and/or warped walls. This is because the elongated recesses would be able to accommodate the wall's protrusions without forcing the cabinet to extend away from the wall.

(11) A method of installing a plurality of cabinets on a wall cleat hanger in accordance with one embodiment of the present invention may comprise the steps of fastening the wall cleat hanger to a wall and attaching the cabinet to said wall cleat hanger by lining up a plurality of recesses on a rear exterior edge of said cabinet and sliding said cabinet along the wall cleat hanger until the cabinet

reaches a desired position.

(12) A method of installing a plurality of cabinets on a wall cleat hanger in accordance with another embodiment of the present invention may comprise the steps of fastening the wall cleat hanger to a wall and attaching the cabinet with an at least one pair of recesses to said wall cleat hanger by placing an upper surface of the at least one pair of recesses superior to the wall cleat hanger and lowering the cabinet onto the wall cleat hanger until the upper surface of the at least one pair of recesses is resting on the wall cleat hanger.

(13) These and other advantages and features of the present invention are described herein with specificity in order to make the present invention understandable to one of ordinary skill in the art.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Elements in the figures have not necessarily been drawn to scale in order to enhance their clarity and improve understanding of the various embodiments of the invention. Furthermore, elements that are known to be common and well understood to those in the industry are not depicted in order to provide a clear view of the various embodiments of the invention.

(2) FIG. 1 is a perspective view of one embodiment of a cabinet hanging system in accordance with the present invention.

(3) FIG. 2 is a rear perspective view of a cabinet used in the cabinet hanging system in accordance with the present invention.

(4) FIG. 3 is a side view of a cabinet used in the cabinet hanging system in accordance with the present invention, showing the right side of the cabinet.

(5) FIG. 4(a) is an enhanced view of an upper recess on the right side of a cabinet used in the cabinet hanging system, showing more detail of a first upper recess.

(6) FIG. 4(b) is a cross-sectional view of the mounting rail in accordance with the present invention.

(7) FIG. 5 is a perspective view of one embodiment of a cabinet hanging system in accordance with the present invention.

(8) FIG. 6 is a rear perspective view of a cabinet used in the cabinet hanging system in accordance with the present invention.

(9) FIG. 7 is a side view of a cabinet used in the cabinet hanging system in accordance with the present invention, showing the right side of the cabinet.

(10) FIG. 8(a) is an enhanced view of the right side of the cabinet used in the cabinet hanging system in accordance with the present invention, showing more detail of a first elongated recess.

(11) FIG. 8(b) is a cross-sectional view of the wall cleat hanger in accordance with the present invention.

(12) FIG. 9(a) is a rear perspective view of a terminal left cabinet in accordance with the present invention.

(13) FIG. 9(b) is a rear perspective view of a terminal right cabinet installed on a wall in accordance with the present invention.

(14) FIG. 10 is a cross-sectional view of a cabinet cleat in accordance with the present invention.

(15) FIG. 11 is a perspective view of one embodiment of a cabinet hanging system in accordance with the present invention.

DETAILED DESCRIPTION OF THE INVENTION

(16) In the following discussion that addresses a number of embodiments and applications of the present invention, reference is made to the accompanying drawings, which form a part thereof. Depictions are made, by way of illustration, of specific embodiments in which the invention may be practiced; however, it is to be understood that other embodiments may be utilized, and changes

may be made without departing from the scope of the present invention. Wherever possible, the same reference numbers are used in the drawings and the following description to refer to the same or similar elements.

(17) In the following detailed description, numerous specific details are set forth by way of examples in order to provide a thorough understanding of the relevant teachings. However, it should be apparent to those skilled in the art that the present teachings may be practiced without such details. In other instances, well-known structures, components, and/or functional or structural relationship thereof, etc., have been described at a relatively high level, without detail, in order to avoid unnecessarily obscuring aspects of the present teachings.

(18) Throughout the specification and claims, terms may have nuanced meanings suggested or implied in context beyond an explicitly stated meaning. Likewise, the phrase “in one embodiment/example,” as used herein, does not necessarily refer to the same embodiment, and the phrase “in another embodiment/example,” as used herein, does not necessarily refer to a different embodiment. It is intended, for example, that the claimed subject matter include combinations of example embodiments in whole or in part.

(19) Conditional language used herein, such as, among others, “can,” “could,” “might,” “may,” “e.g.,” and the like, unless specifically stated otherwise, or otherwise understood within the context as used, is generally intended to convey that certain embodiments include, while other embodiments do not include, certain features, elements, and/or steps. Thus, such conditional language is not generally intended to imply that features, elements, and/or steps are in any way required for one or more embodiments, whether these features, elements, and/or steps are included or are to be performed in any particular embodiment.

(20) The terms “comprising,” “including,” “having,” and the like are synonymous and are used inclusively, in an open-ended fashion, and do not exclude additional elements, features, acts, operations, and so forth. Also, the term “or” is used in its inclusive sense (and not in its exclusive sense) so that when used, for example, to connect a list of elements, the term “or” means one, some, or all of the elements in the list. Conjunctive language such as the phrase “at least one of X, Y, and Z,” unless specifically stated otherwise, is otherwise understood with the context as used in general to convey that an item, term, etc., may be either X, Y, or Z. Thus, such conjunctive language is not generally intended to imply that certain embodiments require at least one of X, at least one of Y, and at least one of Z to each be present.

(21) The term “and/or” means that “and” applies to some embodiments and “or” applies to some embodiments. Thus, A, B, and/or C can be replaced with A, B, and C written in one sentence and A, B, or C written in another sentence. A, B, and/or C means that some embodiments can include A and B, some embodiments can include A and C, some embodiments can include B and C, some embodiments can include only A, some embodiments can include only B, some embodiments can include only C, and some embodiments can include A, B, and C. The term “and/or” is used to avoid unnecessary redundancy. Similarly, terms such as “a,” “an,” or “the,” again, may be understood to convey a singular usage or to convey a plural usage, depending at least in part upon context. In addition, the term “based on” may be understood as not necessarily intended to convey an exclusive set of facts and may, instead, allow of the existence of additional factors not necessarily expressly described, again, depending at least in part on context.

(22) While exemplary embodiments of the disclosure may be described, modifications, adaptations, and other implementations are possible. For example, substitutions, additions, or modifications may be made to the elements illustrated in the drawings, and the methods described herein may be modified by substituting, reordering, or adding stages to the disclosed methods. Thus, nothing in the foregoing description is intended to imply that any particular feature, characteristic, step, module, or block is necessary or indispensable. Indeed, the novel methods and systems described herein may be embodied in a variety of other forms; furthermore, various omissions, substitutions, and changes in the form of the methods and systems described herein may be made without

departing from the spirit of the invention or inventions disclosed herein. Accordingly, the following detailed description does not limit the disclosure. Instead, the proper scope of the disclosure is defined by the appended claims.

(23) Generally, the invention is a cabinet hanging system that, in exemplary embodiments, may include a wall cleat hanger, or mounting rail, and at least one cabinet. The cabinet may have a plurality of recesses on its rear exterior edge that may be substantially the same shape as the mounting rail. The recesses may allow a user to hang the cabinets on a wall without needing to fasten the cabinets to the mounting rail. This may be accomplished because the recesses on the cabinet may catch and rest on the mounting rail. This invention alleviates the burden of complicated cabinet system installations while simultaneously allowing the user to install the cabinet system without the assistance of another person.

(24) Turning now to the figures, FIG. 1 is a perspective view of a cabinet hanging system in accordance with one embodiment of the present invention, wherein the system includes a mounting rail and a cabinet with recesses designed to receive and rest on the mounting rail. Specifically, FIG. 1 illustrates cabinet hanging system **100**, which includes mounting rail **102** and cabinet **103**. Mounting rail **102** may be comprised of plurality of holes **113** for receiving fasteners. Cabinet **103** may include right panel **104**, left panel **105**, door **106**, first upper recess **107**, first lower recess **108**, upper panel **109**, lower panel **110**, and rear panel **122**. First upper recess **107** and first lower recess **108** may be on a rear exterior edge of right panel **104**. Not shown in FIG. 1 is the left side of cabinet **103**, which may include second upper recess **111** and second lower recess **112** on a rear exterior edge of left panel **105**. Second upper recess **111** and second lower recess **112** may be substantially similar to first upper recess **107** and first lower recess **108**, respectively.

(25) Mounting rail **102** may be attached to wall **101**. It is envisioned that wall **101** is in a kitchen, but any wall suitable for cabinets is contemplated by the present invention, such as the walls in a garage or office. Mounting rail **102** may be affixed to wall **101** using any fastening method known in the art. By way of example and not limitation, mounting rail **102** may be affixed to wall **101** by hammering nails through plurality of holes **113** on mounting rail **102**. Alternatively, other fasteners, such as screws, bolts, and/or adhesives, may be used without deviating from the scope or spirit of the present invention. A level (not shown) may be implemented to ensure mounting rail **102** is level; this may help maintain cabinet **103** in place and keep the contents of cabinet **103** from falling.

(26) In one embodiment, plurality of holes **113** may be spaced along mounting rail **102** such that each individual hole corresponds to a stud located within wall **101** on which the user wants to install cabinet hanging system **100**.

(27) In some embodiments of the present invention, mounting rail **102** may be extendable in order to reach across at least a portion of wall **101**. It may be desired to have mounting rail **102** be a length longer than the width of one cabinet **103** in order to allow multiple cabinets **103** to be attached to wall **101**. For example, and without limiting the scope of the present invention, mounting rail **102** may be a quarter-inch shorter than the sum of the widths of upper panel **109** of at least one cabinet **103**. It is envisioned that more than one cabinet **103** may be installed on mounting rail **102**. Having more than one cabinet **103** may allow a user to store more items and may be more aesthetically pleasing to the user. It is also contemplated by the present invention that mounting rail **102** may be a predetermined length based on the user's or a manufacturer's specifications.

(28) The material from which mounting rail **102** may be constructed is not to be limited. For example, and without limitation, mounting rail **102** may be comprised of any metal, such as aluminum, suitable for supporting cabinet **103** and its contents. Alternative materials, such as wood and/or plastic, may also be used.

(29) After installing mounting rail **102** to a desired height on wall **101**, the user may attach cabinet **103** to mounting rail **102** by positioning first upper recess **107** and second upper recess **111** (See FIG. 2) in such a way so that first upper recess **107** and second upper recess **111** align with a

terminal end of mounting rail **102**. As is explained in more detail below, first upper recess **107**, first lower recess **108**, second upper recess **111**, and second lower recess **112** may each be of such a width that each recess can receive, be flush with, and rest on mounting rail **102**. Once first upper recess **107** and second upper recess **111** are lined up with mounting rail **102**, the user can slide cabinet **103** along mounting rail **102** until cabinet **103** reaches a desired position. As is apparent, no fasteners are required to attach cabinet **103** to mounting rail **102**. Rather, the recesses support cabinet **103** and keep it attached to mounting rail **102**.

(30) In some embodiments, a user may attach cabinet **103** to mounting rail **102** by positioning first upper recess upper surface **114** and the upper surface of second upper recess **111** (See FIGS. 2 and 3) superior to mounting rail **102** and lowering cabinet **103** until first upper recess upper surface **114** and the upper surface of second upper recess **111** catch mounting rail **102**. This may allow cabinet **103** to securely rest on mounting rail **102**.

(31) Right panel **104**, left panel **105**, upper panel **109**, lower panel **110**, and rear panel **122** of cabinet **103** may be formed in such a shape so as to define a cavity therein. It is envisioned that cabinet **103** is rectangularly shaped, though other shapes, including but not limited to square, circle, and oval, are contemplated by the present invention. Said cavity may be used to store any number of items.

(32) Right panel **104**, left panel **105**, upper panel **109**, lower panel **110**, rear panel **122**, and door **106** of cabinet **103** may be constructed out of any material suitable for making cabinets. By way of example and not limitation, cabinet **103** may be constructed out of wood, metal, and/or plastic. This list of materials is non-exhaustive and other materials known in the art are contemplated by the present invention.

(33) Cabinet **103** may also be comprised of door **106**. Door **106** may be useful in preventing the contents of cabinet **103** from falling out of the cavity defined by cabinet **103**. In one embodiment of the present invention, door **106** may be fastened to an interior surface of left panel **105** using any fastener suitable for fastening doors to cabinets, such as but not limited to, hinges or magnetic catches. Door **106**, however, may be fastened to the interior surface of any of the panels of cabinet **103**. In other embodiments of the present invention, cabinet **103** may be a framed cabinet. In such embodiments, door **106** may attach to the frame of cabinet **103**.

(34) There may be situations that call for door **106**, after it is attached to cabinet **103**, to be oriented differently so as to allow door **106** to open in a different direction. Rather than having to detach and reattach door **106**, which can be tedious, difficult, and time consuming, a user need merely slide cabinet **103** off mounting rail **102**, rotate cabinet **103** 180 degrees along its X-axis, and replace cabinet **103** onto mounting rail **102**. Doing so flips cabinet **103** such that door **106** may now open in an orientation opposite from the orientation door **106** opened before the 180-degree rotation (i.e., door **106** opens towards the user's left-hand side instead of their right-hand side, or vice versa depending on door **106**'s pre-rotation orientation). This means first lower recess **108** and second lower recess **112** may be used to receive mounting rail **102**.

(35) In some embodiments of the present invention, a rightmost (from the wall's perspective) and a leftmost cabinet (from the wall's perspective) attached to mounting rail **102** may each have a removable panel that covers the upper and lower recesses that would otherwise be exposed and observable to passersby. For example, and without limitation, if cabinet **103** is a rightmost cabinet, in such embodiments cabinet **103** may have a removable and separate panel that can be placed over right panel **104**. Hiding the recesses with removable panels on the terminal cabinets **103** may be preferred in order to enhance the aesthetics of cabinet hanging system **100** while still allowing cabinet **103** to be rotated should the user decide they want or need door **106** to open in the opposite direction.

(36) The removable panel may be attachable to right panel **104** or left panel **105** by any means known in the art for removably attaching one panel to another panel. By way of example and not limitation, the removable panel may attach to right panel **104** and left panel **105** by using magnets

placed on an interior surface of the removable panel and an exterior or interior surface of right panel **104** and left panel **105**. Alternatively, other methods of attaching the removable panel to cabinet **103** may be implemented and are contemplated by the present invention, such as a peg located on either the removable panel or right panel **104** and left panel **105** and a corresponding peg-receiving hole located at substantially the same position on the panel that does not have the peg.

(37) FIG. 2 is a rear perspective view of a cabinet used in cabinet hanging system **100** in accordance with the present invention. As may be better illustrated by this figure, cabinet **103** may have a plurality of recesses suitable for receiving mounting rail **102** (not shown). In some embodiments, cabinet **103** may be comprised of first upper recess **107**, first lower recess **108**, second upper recess **111**, and second lower recess **112**. A greater or fewer number of recesses may be implemented without deviating from the spirit or scope of the present invention.

(38) As can be seen by FIG. 2, first upper recess **107** may align with second upper recess **111** along a first horizontal axis, and first lower recess **108** may align with second lower recess **112** along a second horizontal axis. Having upper recesses **107** and **111** located on the first horizontal axis and lower recesses **108** and **112** located on the second horizontal axis may facilitate installation of cabinet **103** onto mounting rail **102** because cabinet **103** will more easily slide and rest on mounting rail **102**, which is envisioned to be straight in preferred embodiments.

(39) First upper recess **107** and first lower recess **108** may be cutout from a rear exterior edge of right panel **104**. Similarly, second upper recess **111** and second lower recess **112** may be cutout from a rear exterior edge of left panel **105**. Having the recesses **107**, **108**, **111**, and **112** be a part of cabinet **103**, as opposed to separate pieces attached to cabinet **103**, makes cabinet hanging system **100** less expensive, lighter, stronger, and easier for a user to install by him- or herself.

(40) Rear panel **122** may be offset into the cavity of cabinet **103** by a distance sufficient to allow first upper recess **107**, first lower recess **108**, second upper recess **111**, and second lower recess **112** to receive and rest on mounting rail **102**. For example, and not limitation, if first upper recess **107**, first lower recess **108**, second upper recess **111**, and second lower recess **112** are each seven-eighths of an inch deep, rear panel **122** may be offset into the cavity of cabinet **103** by one inch. It is contemplated that rear panel **122** may be offset into the cavity of cabinet **103** by other distances without deviating from the present invention.

(41) Turning now to the next figure, FIG. 3 depicts a side view of the right side of cabinet **103** in accordance with the present invention. As can be seen, first upper recess **107** may be further comprised of first upper recess upper surface **114** and first upper recess lower surface **115**.

Likewise, first lower recess **108** may be further comprised of first lower recess upper surface **116** and first lower recess lower surface **117**. Though not shown, second upper recess **111** and second lower recess **112** may be designed similarly to first upper recess **107** and first lower recess **108**, respectively.

(42) In some embodiments, first upper recess upper surface **114** may be angled diagonally up and toward the cavity defined by cabinet **103**, and first upper recess lower surface **115** may extend perpendicularly toward the cavity defined by cabinet **103**. Thus, first upper recess **107** may be convex, and the opening defined by first upper recess **107** may extend along an inward side of right panel **104**. First upper recess **107** may be designed this way so as to more easily receive and retain mounting rail **102** (not shown). As shown in FIG. 4(b), the shape of mounting rail **102** may substantially match the shape of first upper recess **107**. Alternatively, first upper recess **107** may be differently shaped to retain mounting rail **102** without departing from the scope and spirit of the present invention. First upper recess upper surface **114** may be angled in this manner in order to allow first upper recess **107** to securely catch and rest on mounting rail **102**.

(43) First lower recess **108** may mirror first upper recess **107** along a horizontal axis of cabinet **103**. First lower recess **108** may be a mirrored reflection of first upper recess **107** because, as described above, a user may desire to rotate cabinet **103** 180 degrees along its X-axis so that door **106** (not

shown) opens in the opposite direction. To facilitate such rotations, first lower recess upper surface **116** may extend perpendicularly toward the cavity, and first lower recess lower surface **117** may be angled diagonally down and toward the cavity defined by cabinet **103**. Thus, when a user rotates cabinet **103** 180 degrees along its X-axis, naturally leading to first lower recess being superior to first upper recess, cabinet **103** can securely rest on mounting rail **102**.

(44) Though not shown, second upper recess **111** may be substantially similar to first upper recess **107**. Furthermore, second lower recess **112** may be substantially similar to first lower recess **108**.

(45) FIG. 4(a) is an enhanced view of first upper recess **107** in accordance with the present invention. First upper recess upper surface **114** may be located substantially near upper panel **109**. In a preferred embodiment, it is envisioned that, for example and not limitation, first upper recess upper surface **114** may be located four inches inferior to upper panel **109**, the recess formed by first upper recess upper surface **114** and first upper recess lower surface **115** may be three inches, and the angled portion of first upper recess upper surface **114** may extend into right panel **104** seven-eighths of an inch. These measurements may be slightly larger than the measurements of mounting rail **102** (See FIG. 4(b)), thus allowing mounting rail **102** to snugly fit within first upper recess **107**. The measurements of first upper recess **107** may be augmented or decreased without deviating from the scope or spirit of the present invention.

(46) Though not shown, it is envisioned that first lower recess lower surface **117** may be located substantially near lower panel **110**. In a preferred embodiment, first lower recess lower surface **117** may be located, for example and not limitation, four inches superior to lower panel **110**, and the angled portion of first lower recess lower surface **117** may extend into right panel **104** seven-eighths of an inch. These measurements may be slightly larger than the measurements of mounting rail **102** (See FIG. 4(b)), thus allowing mounting rail **102** to snugly fit within first lower recess lower surface **117**. The measurements of first lower recess lower surface **117** may be augmented or decreased without deviating from the scope or spirit of the present invention.

(47) Though not shown, second upper recess **111** and second lower recess **112** may have measurements substantially similar to the measurements of first upper recess **107** and first lower recess **108**, respectively.

(48) Turning to the next figure, FIG. 4(b) illustrates a cross-sectional view of mounting rail **102** in accordance with the present invention. Mounting rail **102** may be comprised of mounting rail upper surface **118**, mounting rail lower surface **119**, mounting rail wall surface **120**, and mounting rail cabinet surface **121**. In preferred embodiments, mounting rail upper surface **118** may abut first upper recess upper surface **114** of first upper recess **107** (and the upper surface of second upper recess **111**), mounting rail lower surface **119** may abut first upper recess lower surface **115** of first upper surface **107** (and the lower surface of second upper recess **111**), mounting rail wall surface **120** may abut wall **101**, and mounting rail cabinet surface **121** may abut the rear exterior surfaces of right panel **104** and left panel **105**.

(49) The measurements of mounting rail **102** may be slightly less the measurements of first upper recess **107**, first lower recess **108**, second upper recess **111**, and second lower recess **112**. Having the measurements of mounting rail **102** be similar to the measurements of the recesses may allow cabinet **103** to lay flush against wall **101** and thus increase stability and allow cabinet **103** to snugly rest on mounting rail **102**.

(50) Turning to the next figure, FIG. 5 depicts a perspective view of one embodiment of a cabinet hanging system in accordance with the present invention, wherein the cabinet hanging system includes a wall cleat hanger and a cabinet with an elongated recess designed to receive the wall cleat hanger. Specifically, FIG. 5 illustrates cabinet hanging system **200**, which includes wall cleat hanger **202** and cabinet **203**. Wall cleat hanger **202** may be comprised of plurality of holes **211** for receiving fasteners. Cabinet **203** may include right panel **204**, left panel **205**, door **206**, first elongated recess **207**, upper panel **208**, lower panel **209**, and rear panel **219**. First elongated recess **207** may be on the rear exterior edge of right panel **204**. Cabinet **203** may also include second

elongated recess **210** (not shown) on the rear exterior edge of left panel **205**. Second elongated recess **210** may be substantially similar to first elongated recess **207**.

(51) Wall cleat hanger **202** may be attached to wall **201**. It is envisioned that wall **201** is in a kitchen, but any wall suitable for cabinets is contemplated by the present invention, such as the walls in a garage or office. Wall cleat hanger **202** may be affixed to wall **201** using any fastening method known in the art. By way of example and not limitation, wall cleat hanger **202** may be affixed to wall **201** by hammering nails through plurality of holes **211** on wall cleat hanger **202**. Alternatively, other fasteners, such as screws, bolts, and/or adhesives, may be used. A level (not shown) may be implemented to ensure wall cleat hanger **202** is level; this may help maintain cabinet **203** in place and keep the contents of cabinet **203** from falling.

(52) In one embodiment, plurality of holes **211** may be spaced along wall cleat hanger **202** such that each individual hole may correspond to a stud located within the wall on which the user wants to install cabinet hanging system **200**.

(53) In some embodiments of the present invention, wall cleat hanger **202** may be extendable in order to reach across at least a portion of wall **201**. For example, and not limitation, wall cleat hanger **202** may be a quarter-inch shorter than the sum of the width of upper panel **208** of cabinet **203**. It may be desired to have wall cleat hanger **202** be extendable to allow more than one cabinet **203** to be attached to wall **201**. Having more than one cabinet **203** may allow a user to store more items and may be more aesthetically pleasing. It is also contemplated by the present invention that wall cleat hanger **202** may be a predetermined length based on the user's or a manufacturer's specifications.

(54) The material from which wall cleat hanger **202** may be constructed is not to be limited. For example, and without limitation, wall cleat hanger **202** may be comprised of any materials suitable for supporting cabinet **203** and its contents, such as wood, plastic or metal including a light metal such as aluminum. In an exemplary embodiment, wall cleat hanger **202** is a wooden cleat without pre-existing holes and may be simply screwed into studs on the wall.

(55) After installing wall cleat hanger **202** to a desired height on wall **201**, the user may attach cabinet **203** to wall cleat hanger **202** by positioning first elongated recess **207** and second elongated recess **210** (See FIG. 6) so that first elongated recess **207** and second elongated recess **210** may align with a terminal end of wall cleat hanger **202**. As explained below in more detail, first elongated recess **207** and second elongated recess **210** may each be of such a width that each can receive, and be flush with, wall cleat hanger **202**. Once first elongated recess **207** and second elongated recess **210** are lined up with wall cleat hanger **202**, the user can easily slide cabinet **203** along wall cleat hanger **202** until cabinet **203** reaches a desired position on wall **201**. As is apparent, no fasteners are required to attach cabinet **203** to wall cleat hanger **202**.

(56) In some embodiments, a user may, instead of sliding cabinet **203** along wall cleat hanger **202**, attach cabinet **203** to wall cleat hanger **202** by positioning first recess upper surface **212** and the upper surface of second elongated recess **210** (See FIGS. 6 and 7) superior to wall cleat hanger **202** and lowering cabinet **203** until first recess upper surface **212** and the upper surface of second elongated recess **210** catch wall cleat hanger **202**. This installation method is possible because neither first elongated recess **207** nor second elongated recess **210** have a lower boundary.

(57) Right panel **204**, left panel **205**, upper panel **208**, lower panel **209**, and rear panel **219** of cabinet **203** may be formed in such a shape so as to define a cavity therein. It is envisioned that cabinet **203** is rectangularly shaped, though other shapes, including but not limited to square, circle, and oval, may be implemented and are contemplated by the present invention. Said cavity may be used to store any number of items.

(58) Cabinet **203** may also be comprised of door **206**. Door **206** may be useful in preventing the contents of cabinet **203** from falling out of the cavity defined by cabinet **203**. In one embodiment of the present invention, door **206** may be fastened to an interior surface of left panel **205** using any fastener suitable for fastening doors to cabinets, such as but not limited to, hinges or magnetic

catches. Door **206** may be fastened to the interior surface of any of the panels of cabinet **203**. In other embodiments of the present invention, cabinet **203** may be a framed cabinet. In such embodiments, door **206** may attach to the frame of cabinet **203**.

(59) There may be situations that call for door **206**, after it is attached to cabinet **203**, to be oriented differently so as to allow door **206** to open in a different direction. Rather than having to detach and reattach door **206**, which can be tedious, difficult, and time consuming, a user need merely remove cabinet **203** from wall cleat hanger **202**, rotate cabinet **203** 180 degrees along its X-axis, and replace cabinet **203** on wall cleat hanger **202**. Doing so effectively flips cabinet **203** such that door **206** may now open in an orientation opposite from the orientation door **206** opened before the 180-degree rotation (i.e., door **206** opens towards the user's left-hand side instead of their right-hand side, or vice versa depending on door **206**'s pre-rotation orientation).

(60) Right panel **204**, left panel **205**, upper panel **208**, lower panel **209**, rear panel **219**, and door **206** of cabinet **203** may be constructed out of any material suitable for cabinets. By way of example and not limitation, cabinet **203** may be constructed out of wood, metal, and/or plastic. This list of materials is non-exhaustive as other materials known in the art are contemplated by the present invention.

(61) FIG. **6** is a rear perspective view of cabinet **203** in accordance with the present invention. Cabinet **203** may have a first elongated recess **207** and a second elongated recess **210** suitable for receiving wall cleat hanger **202** (not shown). First elongated recess **207** may comprise an opening that vertically extends from substantially near upper panel **208** to substantially near lower panel **209** along a rear exterior edge of right panel **204**, and second elongated recess **210** may also comprise an opening that vertically extends from substantially near upper panel **208** to substantially near lower panel **209** along a rear exterior edge of left panel **205**. By way of example and not limitation, first elongated recess upper surface **212** and first elongated recess lower surface **213** (See FIG. **7**) may be located three and one-half inches inferior to upper panel **208** and superior to lower panel **209**, respectively. These measurements are only for example as first elongated recess upper surface **212** and first elongated recess lower surface **213** may be located other distances from upper panel **208** and lower panel **209**, respectively, without deviating from the scope or spirit of the present invention. Having first elongated recess **207** and second elongated recess **210** be elongated may help cabinet **203** lay flush against an unlevel wall. For example, if wall **201** is warped, bumpy, or generally uneven, the non-smooth portion of wall **201** can be received by first elongated recess **207** and second elongated recess **210** such that the wall distortion does not disrupt the flushness of cabinet **203** since there are fewer points of contact between wall **201** and cabinet **203**.

(62) First elongated recess **207** may align with second elongated recess **210** along a horizontal axis of cabinet **203**. Having first recess **207** and second elongated recess **210** aligned with each other on the horizontal axis may facilitate installation of cabinet **203** onto wall cleat hanger **202** because cabinet **203** will more easily slide onto wall cleat hanger **202**, which is envisioned to be parallel to a floor in preferred embodiments.

(63) Rear panel **219** may be offset into the cavity of cabinet **203** by a distance sufficient to allow first elongated recess **207** and second elongated recess **210** to receive and rest on wall cleat hanger **202**. For example, and not limitation, if first elongated recess **207** and second elongated recess **210** are both seven-eighths of an inch deep, rear panel **219** may be offset into the cavity of cabinet **203** by one inch. It is contemplated by the present invention that rear panel **219** may be offset into the cavity of cabinet **203** by other distances.

(64) First elongated recess **207** may be cutout from a rear exterior edge of right panel **204**. Similarly, second elongated recess **210** may be cutout from a rear exterior edge of left panel **205**. Having first elongated recess **207** and second elongated recess **210** be a part of cabinet **203**, as opposed to separate pieces that are attached to cabinet **203**, makes cabinet hanging system **200** less expensive, lighter, stronger, and easier for a user to install by him- or herself.

(65) First elongated recess **207** may be in proximity to a terminal rear end of right panel **204** and

second elongated recess **210** may be in proximity to a terminal rear end of left panel **205**. Thus, when cabinet **203** is mounted on wall cleat hanger **202**, first elongated recess **207** and second elongated recess **210** may be adjacent to wall **201**. Furthermore, first elongated recess **207** and second elongated recess **210** may each vertically extend between upper panel **208** and lower panel **209**. However, in other embodiments of the present invention, first elongated recess **207** and second elongated recess **210** may be located on upper panel **208** and lower panel **209**, respectively; in such an embodiment, first elongated recess **207** and second elongated recess **210** may horizontally extend between right panel **204** and left panel **205**.

(66) Turning now to the next figure, FIG. 7 depicts a side view of the right side of a cabinet used in cabinet hanging system **200** in accordance with the present invention. First elongated recess **207** may be further comprised of first recess upper surface **212** and first recess lower surface **213**. Though not shown, second elongated recess **210** may be designed similarly to first elongated recess **207**.

(67) In some embodiments, first recess upper surface **212** may be angled diagonally up and toward the cavity defined by cabinet **203**, and first recess lower surface **213** may be angled diagonally down and toward the cavity defined by cabinet **203**. Thus, first elongated recess **207** may be convex, and the opening defined by first elongated recess **207** may extend along an inward side of right panel **204**. The angled surfaces of first elongated recess **207** may be angled in order to allow first elongated recess **207** to easily catch and rest on wall cleat hanger **202**. As shown in FIG. 8(b), the shape of wall cleat hanger **202** may substantially match the shape of first elongated recess **207**. First elongated recess **207** may be any shape sufficient to retain wall cleat hanger **202** without departing from the scope and spirit of the present invention.

(68) As can be seen from FIG. 7, first recess lower surface **213** may mirror first recess upper surface **212** along a horizontal axis. First recess lower surface **213** may be a mirrored reflection of first recess upper surface **212** because, as described above, a user may desire to rotate cabinet **203** 180 degrees along its X-axis so that door **206** (not shown) opens in the opposite direction. To facilitate such rotations, first recess lower surface **213** may be angled diagonally down and toward the cavity defined by cabinet **203**. Thus, when a user rotates cabinet **203** 180 degrees along its X-axis, naturally leading to first recess lower surface **213** being superior to first recess upper surface **212**, the user can still attach cabinet **203** to wall **201** using wall cleat hanger **202**.

(69) Though not shown, second elongated recess **210** may be substantially identical to first elongated recess **207**, i.e., the upper surface of second elongated recess **210** may be angled diagonally up and toward the cavity defined by cabinet **203**, and the lower surface of second elongated recess **210** may be angled diagonally down and toward the cavity defined by cabinet **203**. Thus, second elongated recess **210** may be convex, and the opening defined by second elongated recess **210** may extend along an inward side of left panel **205**. Second elongated recess **210** may be designed this way in order to more easily receive and retain wall cleat hanger **202**.

(70) FIG. 8(a) is an enhanced view of first elongated recess upper surface **212** in accordance with the present invention. First elongated recess upper surface **212** may be located substantially near upper panel **208**. For example, and not limitation, first elongated recess upper surface **212** may be located four inches inferior to upper panel **208**, and the angled portion of first elongated recess upper surface **212** may extend into right panel **204** seven-eighths of an inch. These measurements may be slightly larger than the measurements of wall cleat hanger **202** (See FIG. 8(b)), thus allowing wall cleat hanger **202** to snugly fit within first elongated recess **207**. The measurements of first elongated recess upper surface **212** may be augmented or decreased without deviating from the scope or spirit of the present invention.

(71) Though not shown, it is envisioned that first elongated recess lower surface **213** may be located substantially near lower panel **209**. For example, and not limitation, first elongated recess lower surface may be located four inches superior to lower panel **209**, and the angled portion of first elongated recess lower surface **213** may extend into right panel **204** seven-eighths of an inch.

These measurements may be slightly larger than the measurements of wall cleat hanger **202** (See FIG. **8(b)**), thus allowing wall cleat hanger **202** to snugly fit within first elongated recess **207**. The measurements of first elongated recess lower surface **213** may be augmented or decreased without deviating from the scope or spirit of the present invention.

(72) Additionally, the corresponding upper and lower surfaces of second elongated recess **210** may have measurements substantially similar to the measurements of first elongated recess **207**.

(73) Turning to the next figure, FIG. **8(b)** illustrates a cross-sectional view of wall cleat hanger **202** in accordance with the present invention. Wall cleat hanger **202** may be comprised of wall cleat hanger upper surface **214**, wall cleat hanger lower surface **215**, wall cleat hanger wall surface **216**, and wall cleat hanger cabinet surface **217**. In preferred embodiments, wall cleat hanger upper surface **214** may abut and interact with first recess upper surface **212** of first recess **207** (and the upper surface of second recess **210**), wall cleat hanger wall surface **216** may be adjacent to wall **201**, and wall cleat hanger cabinet surface **217** may abut and interact with the rear exterior surfaces of right panel **204** and left panel **205**.

(74) The measurements of wall cleat hanger **202** may be similar to the measurements of first elongated recess **207** and second elongated recess **210**. Having the measurements of wall cleat hanger **202** be similar to the measurements of first elongated recess **207** and second elongated recess **210** may allow cabinet **203** to lay flush against wall **201** and thus increase the stability and aesthetics of cabinet hanging system **200**.

(75) Turning to the next figures, FIG. **9(a)** is a rear perspective view of a terminal left cabinet with a finished panel in accordance with the present invention, FIG. **9(b)** is a rear perspective view of a terminal right cabinet with a finished panel attached to a wall cleat hanger, and FIG. **10** is a cross-sectional view of a cabinet cleat in accordance with the present invention.

(76) It is envisioned in some embodiments of the present invention that wall cleat hanger **202** may be used to support more than one cabinet **203**. In such embodiments, cabinet hanging system **200** may comprise terminal left cabinet **203 (a)**, terminal right cabinet **203 (b)**, and at least one cabinet **203** between terminal left cabinet **203 (a)** and terminal right cabinet **203 (b)**. Other embodiments may comprise only a terminal left cabinet **203 (a)** or terminal right cabinet **203 (b)**, such as in situations where the terminal cabinet is placed against a wall. In other embodiments, a user may install only terminal left cabinet **203 (a)** and terminal right cabinet **203 (b)** without cabinet **203** in between terminal left cabinet **203 (a)** and terminal right cabinet **203 (b)**. As will be appreciated by a person of ordinary skill in the art, many configurations are possible without deviating from the scope of the present invention.

(77) Terminal left cabinet **203 (a)** may be comprised of finished left panel **220**, cabinet cleat **221**, upper panel **225**, lower panel **226**, elongated recess **227**, rear panel **228**, and right panel **233**. Terminal left cabinet **203 (b)** may be comprised of cabinet cleat **221**, finished right panel **224**, upper panel **229**, lower panel **230**, elongated recess **231**, and rear panel **232**.

(78) As shown in FIG. **9(a)**, which depicts terminal left cabinet **203 (a)**, there may be only elongated recess **227** on right panel **233**. Instead of an elongated recess on the left-hand side of terminal left cabinet **203 (a)**, there may be finished left panel **220**. Finished left panel **220** may not be comprised of an elongated recess. By not including an elongated recess on finished left panel **220**, wall cleat hanger **202** is hidden from view.

(79) As seen in FIG. **9(b)**, which depicts terminal right cabinet **203 (b)**, there may be only elongated recess **231** on left panel **234**. Instead of an elongated recess on the righthand side of terminal right cabinet **203 (b)**, there may be finished right panel **224**. Finished right panel **224** may not be comprised of an elongated recess. By not including an elongated recess on finished right panel **224**, wall cleat hanger is hidden from view.

(80) As illustrated by FIG. **9(b)**, terminal right cabinet **203 (b)** may rest on wall cleat hanger **202** via cabinet cleat **221**. Cabinet cleat **221** may be comprised of cabinet cleat upper surface **222** and cabinet cleat lower surface **223** (See FIG. **10**). Cabinet cleat upper surface may extend

perpendicularly from wall **201** and terminal right cabinet **203 (b)**. Cabinet cleat lower surface **223** may extend diagonally downward from terminal right cabinet **203 (b)** and wall **201**. Specifically, cabinet cleat lower surface **223** may be angled in such a way in order to rest on wall cleat hanger **202** (See FIG. **8(b)**). Though not shown, cabinet cleat **221** of terminal left cabinet **203 (a)** may interact with and rest on wall cleat hanger **202** similar to how terminal right cabinet **203 (b)** interacts with and rests on wall cleat hanger **202**.

(81) Cabinet cleat **221** may be located on rear panel **232** of terminal right cabinet **203 (b)**. Specifically, cabinet cleat **221** may be located on the terminal side of rear panel **232** of terminal right cabinet **203 (b)** and positioned where upper panel **229** abuts finished right panel **224**. Some embodiments of the present invention may include more than one cabinet cleat **221** on rear panel **232** of terminal right cabinet **203 (b)**. In such embodiments, cabinet cleat **221** may be positioned on rear panel **232** where upper panel **229** abuts finished right panel **224** and where lower panel **230** abuts finished right panel **224**. Having more than one cabinet cleat **221** may allow a user to rotate terminal right cabinet **203 (b)** horizontally around its center point and have door **235** open in a different orientation.

(82) Referring back to FIG. **9(a)**, cabinet cleat **221** may be located on rear panel **228** of terminal left cabinet **203 (a)**. Specifically, cabinet cleat **221** may be located on the terminal side of rear panel **228** of terminal left cabinet **203 (a)** and positioned where upper panel **225** abuts finished left panel **220**. Some embodiments of the present invention may include more than one cabinet cleat **221** on rear panel **228** of terminal left cabinet **203 (a)**. In such embodiments, cabinet cleat **221** may be positioned on rear panel **228** where upper panel **225** abuts finished left panel **220** and where lower panel **226** abuts finished left panel **220**. Having more than one cabinet cleat **221** may allow a user to rotate terminal left cabinet **203 (a)** horizontally around its center point and have door **235** (not shown) open in a different orientation.

(83) Terminal left cabinet **203 (a)** and terminal right cabinet **203 (b)** may be installed in a manner similar to how cabinet **203** is installed. For instance, and without limitation, a user may hold terminal left cabinet **203 (a)** and terminal right cabinet **203 (b)** above wall cleat hanger **202** and slide terminal left cabinet **203 (a)** and terminal right cabinet **203 (b)** down wall **201** until elongated recess **227**, elongated recess **231**, respectively, and cabinet cleat **221** catch and are able to rest on wall cleat hanger **202**. Terminal left cabinet **203 (a)** and terminal right cabinet **203 (b)** may also be installed by aligning elongated recess **227** and elongated recess **231**, respectively, with wall cleat hanger **202** and sliding terminal left cabinet **203 (a)** and terminal right cabinet **203 (b)** along wall cleat hanger **202** until a desired position is reached.

(84) Turning to the next figure, FIG. **11** depicts a perspective view of one embodiment of a cabinet hanging system in accordance with the present invention. Specifically, FIG. **11** illustrates cabinet hanging system **300**, which includes upper wall cleat hanger **302**, upper terminal right cabinet **304**, lower wall cleat hanger **311**, and lower terminal right cabinet **313**. Upper wall cleat hanger **302** may be comprised of plurality of holes **303** and lower wall cleat hanger **311** may be comprised of a plurality of holes **312**, both of which may be used for receiving fasteners. Upper terminal right cabinet **304** may include finished right panel **305**, upper panel **306**, lower panel **307**, left panel **308**, rear panel **309**, and door **310**. Lower terminal right cabinet **313** may include finished right panel **314**, upper panel **315**, lower panel **316**, left panel **317**, rear panel **321**, and door **318**. It is envisioned that at least one cabinet **203** may be installed on upper wall cleat hanger **302** and/or lower wall cleat hanger **311**.

(85) Upper wall cleat hanger **302** and lower wall cleat hanger **311** may be attached to wall **301**. It is envisioned that wall **301** is in a kitchen, but any wall suitable for cabinets is contemplated by the present invention, such as the walls in a garage or office. Upper wall cleat hanger **302** and lower wall cleat hanger **311** may be affixed to wall **301** using any fastening method known in the art. By way of example and not limitation, upper wall cleat hanger **302** may be affixed to wall **301** by hammering nails through plurality of holes **303**. Similarly, lower wall cleat hanger **311** may be

affixed to wall **301** by hammering nails through plurality of holes **312**. Alternatively, other fasteners, such as screws, bolts, and/or adhesives, may be used without deviating from the scope or spirit of the present invention. A level (not shown) may be implemented to ensure upper wall cleat hanger **302** and lower wall cleat hanger **311** are level; this may help maintain upper terminal right cabinet **304** and lower terminal right cabinet **313** in place.

(86) In one embodiment, plurality of holes **303** may be spaced along upper wall cleat hanger **302** such that each individual hole corresponds to a stud located within wall **301**. The spacing of plurality of holes **312** may be similarly spaced along lower wall cleat hanger **311**.

(87) In some embodiments of the present invention, upper wall cleat hanger **302** and lower wall cleat hanger **311** may each be extendable in order to reach across at least a portion of wall **301**. For example, and not limitation, upper wall cleat hanger **302** and lower wall cleat hanger **311** may each be a quarter-inch shorter than the sum of the width of upper panel **306** and/or upper panel **315**. It is also contemplated by the present invention that upper wall cleat hanger **302** and lower wall cleat hanger **311** may each be a predetermined length based on the user's or a manufacturer's specifications.

(88) The material from which upper wall cleat hanger **302** may be constructed is not to be limited. For example, and without limitation, upper wall cleat hanger **302** may be comprised of any metal, such as aluminum, suitable for supporting upper terminal right cabinet **304** and/or at least one cabinet **203**. Alternative materials, such as wood and/or plastic, are also comprehended by the present invention and may be used to construct upper wall cleat hanger **302** and lower wall cleat hanger **311**. Lower wall cleat hanger **311** may be similarly constructed.

(89) In some embodiments of the present invention, upper terminal right cabinet **304** and lower terminal right cabinet **313** may each have elongated recesses that may be used to attach upper terminal right cabinet **304** and lower terminal right cabinet **313** to upper wall cleat hanger **302** and lower wall cleat hanger **311**, respectively. These elongated recesses may be similar to first elongated recess **207**, as shown in FIG. 6. Other embodiments of the present invention may also incorporate separate upper and lower recesses similar to first upper recess **107** and first lower recess **108**, as seen in FIG. 2.

(90) After installing upper wall cleat hanger **302** to a desired height on wall **301**, a user may attach upper terminal right cabinet **304** to upper wall cleat hanger **302** by positioning the elongated recess located on a rear exterior edge of the left panel **308** (See FIG. 6) in such a way that the elongated recess may align with a terminal end of upper wall cleat hanger **302**. As explained herein in more detail, the elongated recess may be of such a width that it can receive, and be flush with, upper wall cleat hanger **302**. Once the elongated recess is aligned with upper wall cleat hanger **302**, the user can easily slide upper terminal right cabinet **304** along upper wall cleat hanger **302** until upper terminal right cabinet **304** reaches a desired position on wall **301**. As is apparent, no fasteners are required to attach upper terminal right cabinet **304** to upper wall cleat hanger **302**.

(91) In some embodiments, a user may attach upper terminal right cabinet **304** to upper wall cleat hanger **302** by positioning an upper surface of the elongated recess (See FIGS. 6 and 7) superior to upper wall cleat hanger **302** and lowering upper terminal right cabinet **304** until the upper surface of the elongated recess catches upper wall cleat hanger **302**. This installation method is possible because the elongated recess does not have a lower boundary.

(92) The installation method of lower terminal right cabinet **313** onto lower wall cleat hanger **311** may be similar to the methods used to install upper terminal right cabinet **304** onto upper wall cleat hanger **302**.

(93) Upper panel **306**, lower panel **307**, left panel **308**, rear panel **309**, and finished right panel **305** of upper terminal right cabinet **304** may be formed in such a shape to define a cavity therein. It is envisioned that upper terminal right cabinet **304** may be rectangularly shaped, though other shapes, including but not limited to square, circle, and oval, may be implemented and are contemplated by the present invention. Said cavity may be used to store any number of items. Upper panel **315**,

lower panel **316**, left panel **317**, rear panel **321**, and finished right panel **314** of lower terminal right cabinet **313** may be formed similar to upper terminal right cabinet **304**.

(94) In some embodiments, upper terminal right cabinet **304** may be comprised of door **310**, and lower terminal right cabinet **313** may be comprised door **318**. Door **310** and door **318** may be useful in preventing the contents of upper terminal right cabinet **304** and lower terminal right cabinet **313** from falling out of the defined cavity. In one embodiment of the present invention, door **310** and door **318** may be fastened to an interior surface of left panel **308** and left panel **317**, respectively, using any fastener suitable for fastening doors to cabinets, such as but not limited to, hinges and/or magnetic catches. Door **310** and door **318** may be fastened to the interior surface of any of the panels of upper terminal right cabinet **304** and lower terminal right cabinet **313**, respectively. In other embodiments of the present invention, the cabinets may be framed cabinets. In such embodiments, door **310** and door **318** may attach to the cabinet frame.

(95) There may be situations that call for door **310**, after it is attached to upper terminal right cabinet **304**, to be oriented differently to allow door **310** to open in a different direction. Rather than having to detach and reattach door **310**, which can be tedious, difficult, and time consuming, a user need merely slide and/or lift upper terminal right cabinet **304** off upper wall cleat hanger **302**, rotate upper terminal right cabinet **304** 180 degrees along its X-axis, and slide and/or lower upper terminal right cabinet **304** onto upper wall cleat hanger **302**. Doing so effectively flips upper terminal right cabinet **304** such that door **310** may now open in an orientation opposite from the orientation door **310** opened before the 180-degree rotation (i.e., door **310** opens towards the user's left-hand side instead of their right-hand side, or vice versa depending on door **310**'s pre-rotation orientation). Door **318** may be similarly rotated. In some embodiments, the orientation of lower terminal right cabinet **313** may be fixed such that lower terminal cabinet **313** cannot be flipped; for example, because some cabinets such as base cabinets are built so that a base panel does not match a top panel.

(96) In some embodiments of the present invention, upper terminal right cabinet **304** and lower terminal right cabinet **313** may be empty. In other embodiments, upper terminal right cabinet **304** and lower terminal right cabinet **313** may each be comprised of at least one shelf **319**. It is envisioned that more than one shelf **319** may be implemented. Shelf **319** may be installed via methods known in the art, such as, for example, by having pegs located on the interior of the side panels that extend into the interior of upper terminal right cabinet **304** and/or lower terminal right cabinet **313**. Shelf **319** may rest on and be supported by the pegs. The pegs may attach to the side panels of upper terminal right cabinet **304** and/or lower terminal right cabinet **313** via a series of peg-receiving holes extending from the upper and lower panels (**306**, **307**, **315**, and **316**) of upper terminal right cabinet **304** and/or lower terminal right cabinet **313**, respectively. Having a series of peg-receiving holes allows the user to adjust the height of where shelf **319** is placed. In still other embodiments, upper terminal right cabinet **304** and/or lower terminal right cabinet **313** may be comprised of drawer **320**. Drawer **320** may be located on a track attached to the side panels of upper terminal right cabinet **304** and/or lower terminal right cabinet **313**, thus allowing the user to pull out and push in the drawer **320**. Other drawer systems known in the art are also contemplated by the present invention.

(97) Upper panels **306** and **315**, lower panels **307** and **316**, left panels **308** and **317**, finished right panels **305** and **314**, rear panels **309** and **321**, and doors **310** and **318**, may be constructed out of any material suitable for cabinets. By way of example and not limitation, wood, metal, and/or plastic may be used. This list of materials is non-exhaustive as other materials known in the art are contemplated by the present invention.

(98) Upper wall cleat hanger **302** and lower wall cleat hanger **311** may be similar to wall cleat hanger **202**, as seen in FIG. **8(b)**. Upper wall cleat hanger **302** and lower wall cleat hanger **311** may each be comprised of a wall cleat hanger upper surface, a wall cleat hanger lower surface, a wall cleat hanger wall surface, and a wall cleat hanger cabinet surface. In preferred embodiments, the

wall cleat hanger upper surface may abut and interact with the upper surfaces of the elongated recesses of upper terminal right cabinet **304** and lower terminal right cabinet **313**, respectively, the wall cleat hanger wall surface may be adjacent to wall **301**, and the wall cleat hanger cabinet surface may abut and interact with the rear exterior surfaces of the finished right panels **305** and **314**, respectively, and left panels **308** and **317**, respectively, of upper terminal right cabinet **304** and lower terminal right cabinet **313**.

(99) The measurements of upper wall cleat hanger **302** and lower wall cleat hanger **311** may be similar to the measurements of the elongated recesses of upper terminal right cabinet **304** and lower terminal right cabinet **313**. Having the measurements of upper wall cleat hanger **302** and lower wall cleat hanger **311** be similar to the measurements of the elongated recesses may allow upper terminal right cabinet **304** and lower terminal right cabinet **313** to lay flush against wall **301**, thus increasing the stability and aesthetics of the cabinet hanging system **300**.

(100) Upper terminal right cabinet **304** and lower terminal right cabinet **313** may each only be comprised of a single elongated recess. Instead of an elongated recess on the righthand side of upper terminal right cabinet **304** and the righthand side of lower terminal right cabinet **313**, there may be finished right panel **305** and finished right panel **314**, respectively. Finished right panel **305** and finished right panel **314** may not be comprised of an elongated recess. By not including an elongated recess on finished right panel **305** and finished right panel **314**, upper wall cleat hanger **302** and lower wall cleat hanger **313**, respectively, are hidden from view. Though not shown, the leftmost upper terminal cabinet and the leftmost lower terminal cabinet may each have an elongated recess on a right panel and a finished terminal panel on a left panel.

(101) Upper terminal right cabinet **304** and lower terminal right cabinet **313** may rest on upper wall cleat hanger **302** and lower terminal right cabinet **313**, respectively, via a cabinet cleat similar to cabinet cleat **221** (See FIGS. **9(b)** and **10**). The cabinet cleat may be comprised of a cabinet cleat upper surface and a cabinet cleat lower surface. The cabinet cleat upper surface may extend perpendicularly from wall **301** and upper terminal right cabinet **304** and lower terminal right cabinet **313**. The cabinet cleat lower surface may extend diagonally downward from wall **301** and upper terminal right cabinet **304** and lower terminal right cabinet **313**. The cabinet cleat lower surface may be angled in such a way to rest on upper wall cleat hanger **302** and lower wall cleat hanger **311**, respectively.

(102) The cabinet cleat may be located on rear panel **309** of upper terminal right cabinet **304** similar to cabinet cleat **221** (See FIG. **9(a)**). Specifically, the cabinet cleat may be located on the exterior side of rear panel **309** of upper terminal right cabinet **304** and positioned where upper panel **306** abuts finished right panel **305**. Some embodiments of the present invention may include more than one cabinet cleat on rear panel **309** of upper terminal right cabinet **304**. In such embodiments, the cabinet cleat may be positioned on an exterior side of rear panel **309** where upper panel **306** abuts finished right panel **305** and where lower panel **307** abuts finished right panel **305**. Having multiple cabinet cleats may allow a user to rotate upper terminal right cabinet **304** horizontally around its center point and have door **310** open in a different orientation. The cabinet cleat may be similarly located on lower terminal right cabinet **313**.

(103) Though not shown, it is envisioned by the present invention that cabinet hanging system **300** may also comprise an upper terminal left cabinet and a lower terminal left cabinet, which may be similar to upper terminal right cabinet and lower terminal right cabinet, respectively.

(104) A cabinet hanging system has been described. The foregoing description of the various exemplary embodiments of the invention has been presented for the purposes of illustration and disclosure. It is not intended to be exhaustive or to limit the invention to the precise form disclosed. Many modifications and variations are possible in light of the above teaching without departing from the spirit of the invention.

Claims

1. A cabinet hanging system for mounting cabinets to a wall, comprising: a wall cleat hanger; and an at least one cabinet comprising a right panel opposite a left panel, an upper panel, a lower panel, and a rear panel which define a cavity: a rear exterior edge on the right panel that comprises a first elongated recess that vertically extends from substantially near the upper panel to substantially near the lower panel; and a rear exterior edge on the left panel that comprises a second elongated recess that vertically extends from substantially near the upper panel to substantially near the lower panel, wherein the rear exterior edge on the right panel and the rear exterior edge on the left panel extend beyond a posterior surface of the rear panel to preclude the posterior surface of the rear panel from making contact with a wall adapted with the wall cleat hanger; and wherein the first elongated recess and second elongated recess each comprise an upper surface that is angled diagonally up and toward the cavity and a lower surface that is angled diagonally down and toward the cavity, the first elongated recess and the second elongated recess adapted to be installed on the wall cleat hanger on a first position along an x-axis of the at least one cabinet and to be installed on the wall cleat hanger on a second position by rotating the at least one cabinet 180 (degrees) along the x-axis of the at least one cabinet.
2. The cabinet hanging system of claim 1, further comprising a terminal left cabinet including: a rear exterior edge of a right panel of the terminal left cabinet comprising a first elongated recess that vertically extends from substantially near an upper panel of the terminal left cabinet to substantially near a lower panel of the terminal left cabinet; and a rear exterior surface of a left panel of the terminal left cabinet comprising a finished left panel.
3. The cabinet hanging system of claim 1, further comprising a terminal right cabinet including: a rear exterior edge of a left panel of the terminal right cabinet comprising a first elongated recess that vertically extends from substantially near an upper panel of the terminal right cabinet to substantially near a lower panel of the terminal right cabinet; and a rear exterior surface of a right panel of the terminal right cabinet comprising a finished right panel.
4. The cabinet hanging system of claim 2, wherein the terminal left cabinet further includes a first cabinet cleat located on an exterior surface of a rear panel of the terminal left cabinet where the upper panel intersects the finished left panel.
5. The cabinet hanging system of claim 2, wherein the terminal left cabinet further includes a second cabinet cleat located on the exterior surface of a rear panel of the terminal left cabinet where the lower panel intersects the finished left panel.
6. The cabinet hanging system of claim 3, wherein the terminal right cabinet further includes a first cabinet cleat located on an exterior surface of a rear panel of the terminal cabinet where the upper panel intersects the finished right panel.
7. The cabinet hanging system of claim 3, wherein the terminal right cabinet further includes a second cabinet cleat located on an exterior surface of a rear panel of the terminal right cabinet where the lower panel intersects the finished right panel.
8. The cabinet hanging system of claim 1, wherein the cabinet comprises at least one cabinet door, wherein the at least one cabinet door is attached to an interior surface of a cabinet panel and wherein the at least one cabinet door opens outward.
9. A cabinet, comprising: a right panel, a left panel, an upper panel at a first terminal end of the cabinet, a lower panel at second terminal end of the cabinet, and a rear panel which define a cavity, wherein: a rear exterior edge of the right panel comprises a first elongated recess that vertically extends from substantially near the upper panel to substantially near the lower panel; and a rear exterior edge of the left panel comprises a second elongated recess that vertically extends from substantially near the upper panel to substantially near the lower panel; and wherein the first and second elongated recess are adapted to register with a wall cleat hanger affixed to a wall; and

wherein the rear exterior edge on the right panel and the rear exterior edge on the left panel extend beyond a posterior surface of the rear panel to preclude the posterior surface of the rear panel from making contact with the wall adapted with the wall cleat hanger; and wherein the first elongated recess and second elongated recess each comprise an upper surface that is angled diagonally up and toward the cavity and a lower surface that is angled diagonally down and toward the cavity, the first elongated recess and the second elongated recess adapted to be installed on the wall cleat hanger on a first position along an x-axis of the cabinet and to be installed on the wall cleat hanger on a second position by rotating the cabinet 180 (degrees) along the x-axis of the cabinet.

10. The cabinet of claim 9, wherein the cabinet comprises at least one cabinet door, wherein the at least one cabinet door is attached to an interior surface of a cabinet panel and wherein the at least one cabinet door opens outward.

11. The cabinet of claim 10, wherein the rear panel of the cabinet is offset into the cabinet by a distance sufficient to allow the first elongated recess and the second elongated recess to receive and rest on the wall cleat hanger.

12. The cabinet of claim 9, wherein the rear panel of the cabinet is offset into the cabinet by a distance sufficient to allow the first elongated recess and the second elongated recess to receive and rest on the wall cleat hanger.
