

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12408968
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Horner; Shawn K. et al.

Smoke evacuation device

Abstract

A smoke evacuation device that evacuates smoke from a surgical site and filters the smoke from the air. The smoke evacuation device can include a fluid trap for removing moisture from the smoke. The smoke evacuation device can also include a filter with a compression mechanism for compressing a filter medium. The smoke evacuation device can also include features for controlling flow parameters, noise, and vibrations of the device. A remote activation device can also be used to activate the smoke evacuation device upon detection of certain system parameters.

Inventors: Horner; Shawn K. (Woods Cross, UT), Harris; Jason L (Lebanon, OH), Shelton; Frederick (Hillsboro, OH), Frampton; Chad S. (American Fork, UT), Andrews; Steven D. (West Jordan, UT), Danziger; Benjamin J. (Seattle, WA), Glassett; Mark D. (Sandy, UT), Greep; Darcy W. (Herriman, UT), Millis; Roger (West Jordan, UT), Yates; David C. (West Chester, OH)

Applicant: Megadyne Medical Products, Inc. (Draper, UT)

Family ID: 66634169

Assignee: MEGADYNE MEDICAL PRODUCTS, INC. (Draper, UT)

Appl. No.: 17/572217

Filed: January 10, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220409261 A1	Dec. 29, 2022

Related U.S. Application Data

continuation parent-doc US 15826376 20171129 US 11234754 child-doc US 17572217

Publication Classification

Int. Cl.: A61B18/14 (20060101); A61B18/00 (20060101); A61B90/00 (20160101)

U.S. Cl.:

CPC A61B18/1402 (20130101); A61B2018/00017 (20130101); A61B2018/00702 (20130101); A61B2018/00827 (20130101); A61B2090/034 (20160201); A61B2218/008 (20130101)

Field of Classification Search

CPC: A61B (2218/008); A61B (2218/006); B01D (2253/102)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1165288	12/1914	Rimmer	N/A	N/A
1789194	12/1930	Rockwell	N/A	N/A
2577606	12/1950	Conley	N/A	N/A
3815752	12/1973	Hoffman et al.	N/A	N/A
3841490	12/1973	Hoffman et al.	N/A	N/A
4116649	12/1977	Cullen et al.	N/A	N/A
4157234	12/1978	Shaffer et al.	N/A	N/A
4166649	12/1978	Scholl	294/65.5	B66C 1/06
4396206	12/1982	Tsuge et al.	N/A	N/A
4619672	12/1985	Robertson	N/A	N/A
4642128	12/1986	Solorzano	N/A	N/A
D291353	12/1986	Conero et al.	N/A	N/A
4701193	12/1986	Robertson et al.	N/A	N/A
4786298	12/1987	Billiet et al.	N/A	N/A
4788298	12/1987	Wang	N/A	N/A
4810269	12/1988	Stackhouse et al.	N/A	N/A
4826513	12/1988	Stackhouse et al.	N/A	N/A
4986839	12/1990	Wertz et al.	N/A	N/A
4988839	12/1990	Kennicott	N/A	N/A
D315410	12/1990	Aten	N/A	N/A
5108389	12/1991	Cosmescu	N/A	N/A
5144176	12/1991	Popper	N/A	N/A
5144178	12/1991	Sugiura	N/A	N/A
5160334	12/1991	Billings et al.	N/A	N/A
5221192	12/1992	Heflin et al.	N/A	N/A
5226939	12/1992	Nicolas et al.	N/A	N/A
5228939	12/1992	Chu	N/A	N/A
5242474	12/1992	Herbst et al.	N/A	N/A
5288469	12/1993	Skalla	261/DIG.2	B01D 46/0036
5288489	12/1993	Reich et al.	N/A	N/A
5318516	12/1993	Cosmescu	N/A	N/A

5328478	12/1993	McVay	604/65	A61M 3/0233
5336218	12/1993	Linhares	N/A	N/A
5342349	12/1993	Kaufman	N/A	N/A
D357738	12/1994	Kaufman	N/A	N/A
5423779	12/1994	Yeh	N/A	N/A
5431650	12/1994	Cosmescu	N/A	N/A
5456248	12/1994	Holian et al.	N/A	N/A
5507859	12/1995	Kaiser	N/A	N/A
5522808	12/1995	Skalla	N/A	N/A
5536254	12/1995	McVay	604/135	A61M 3/022
5597385	12/1996	Moerke	N/A	N/A
5619992	12/1996	Guthrie et al.	N/A	N/A
5620441	12/1996	Greff et al.	N/A	N/A
5674219	12/1996	Monson et al.	N/A	N/A
5690480	12/1996	Suzuki et al.	N/A	N/A
5853410	12/1997	Greff et al.	N/A	N/A
5874052	12/1998	Holland	N/A	N/A
5910291	12/1998	Skalla et al.	N/A	N/A
5947694	12/1998	Hablanian	N/A	N/A
5992413	12/1998	Martin et al.	N/A	N/A
D420140	12/1999	Noble et al.	N/A	N/A
6050792	12/1999	Shaffer	N/A	N/A
6089527	12/1999	Utterberg	N/A	N/A
6110259	12/1999	Schultz et al.	N/A	N/A
6129530	12/1999	Shaffer	N/A	N/A
6145509	12/1999	Tanner	N/A	N/A
6203590	12/2000	Byrd et al.	N/A	N/A
6203762	12/2000	Skalla et al.	N/A	N/A
6331246	12/2000	Beckham et al.	N/A	N/A
6439864	12/2001	Shaffer	N/A	N/A
D467654	12/2001	Klug et al.	N/A	N/A
6511308	12/2002	Shaffer	N/A	N/A
6524307	12/2002	Palmerton et al.	N/A	N/A
6544210	12/2002	Trudel et al.	N/A	N/A
6576033	12/2002	Booth	428/36.1	B01D 46/0038
6585791	12/2002	Garito et al.	N/A	N/A
6589316	12/2002	Schultz et al.	N/A	N/A
6589318	12/2002	El-Shoubary et al.	N/A	N/A
6592543	12/2002	Wortrich et al.	N/A	N/A
6616722	12/2002	Cartellone	N/A	N/A
6663698	12/2002	Mishin et al.	N/A	N/A
D485339	12/2003	Klug et al.	N/A	N/A
6709248	12/2003	Fujioka et al.	N/A	N/A
6736620	12/2003	Satoh	N/A	N/A
6758885	12/2003	Leffel et al.	N/A	N/A
6786707	12/2003	Kim	N/A	N/A
D513314	12/2004	Iddings et al.	N/A	N/A

7014434	12/2005	Fujioka et al.	N/A	N/A
D521137	12/2005	Khalil	N/A	N/A
D545955	12/2006	Arias	N/A	N/A
7258712	12/2006	Schultz et al.	N/A	N/A
D553228	12/2006	Virr et al.	N/A	N/A
7276052	12/2006	Kobayashi et al.	N/A	N/A
D555803	12/2006	Garito et al.	N/A	N/A
7294116	12/2006	Ellman et al.	N/A	N/A
D568991	12/2007	Schweikert et al.	N/A	N/A
D574323	12/2007	Waalder	N/A	N/A
7465156	12/2007	Lee	N/A	N/A
7497340	12/2008	Hershberger et al.	N/A	N/A
7597731	12/2008	Palmerton et al.	N/A	N/A
D608447	12/2009	Meyer et al.	N/A	N/A
D616986	12/2009	Biegen et al.	N/A	N/A
D625399	12/2009	Horiguchi	N/A	N/A
D626204	12/2009	Morgan	N/A	N/A
7819957	12/2009	Roberts et al.	N/A	N/A
7942655	12/2010	Shaffer	N/A	N/A
D646368	12/2010	Osendorf et al.	N/A	N/A
8033798	12/2010	Suh et al.	N/A	N/A
D648841	12/2010	Lam	N/A	N/A
8142175	12/2011	Duppert et al.	N/A	N/A
D657468	12/2011	Held	N/A	N/A
8147577	12/2011	Palmerton	55/482	A61B 18/00
8190398	12/2011	Kitaguchi et al.	N/A	N/A
D666704	12/2011	Osendorf et al.	N/A	N/A
8298420	12/2011	Burrows	N/A	N/A
8556570	12/2012	Ishihara	N/A	N/A
8608816	12/2012	Palmerton et al.	N/A	N/A
8684705	12/2013	Magoon et al.	N/A	N/A
8727744	12/2013	Magoon et al.	N/A	N/A
8974569	12/2014	Matula et al.	N/A	N/A
9011366	12/2014	Dean et al.	N/A	N/A
9028230	12/2014	Shaffer	N/A	N/A
9067030	12/2014	Stearns et al.	N/A	N/A
9074598	12/2014	Shaffer et al.	N/A	N/A
D736933	12/2014	Qiu et al.	N/A	N/A
D737449	12/2014	Zheng et al.	N/A	N/A
D739770	12/2014	Scampoli et al.	N/A	N/A
9199047	12/2014	Stearns et al.	N/A	N/A
9215964	12/2014	Loske	N/A	N/A
9215984	12/2014	Hattery et al.	N/A	N/A
9366254	12/2015	Murakami	N/A	N/A
9387295	12/2015	Mastri et al.	N/A	N/A
9387296	12/2015	Mastri et al.	N/A	N/A
D764649	12/2015	Ko et al.	N/A	N/A
9415160	12/2015	Bonano et al.	N/A	N/A
9435339	12/2015	Calhoun et al.	N/A	N/A

9474512	12/2015	Blackhurst et al.	N/A	N/A
9532843	12/2016	Palmerton et al.	N/A	N/A
9549849	12/2016	Charles	N/A	N/A
9579428	12/2016	Reasoner et al.	N/A	N/A
D783178	12/2016	Mead et al.	N/A	N/A
D799055	12/2016	Kennedy et al.	N/A	N/A
D802024	12/2016	Aoki	N/A	N/A
9867914	12/2017	Bonano	N/A	A61M 5/165
9943355	12/2017	Babini et al.	N/A	N/A
D844333	12/2018	Maynard	N/A	N/A
D868236	12/2018	Frampton et al.	N/A	N/A
D868287	12/2018	Frampton	N/A	N/A
10631916	12/2019	Horner et al.	N/A	N/A
D886976	12/2019	Horner et al.	N/A	N/A
D890900	12/2019	Bink et al.	N/A	N/A
10758293	12/2019	Horner	N/A	F04B 39/06
10758855	12/2019	Horner et al.	N/A	N/A
10758856	12/2019	Horner	N/A	A61B 18/00
D912762	12/2020	Horner et al.	N/A	N/A
D943058	12/2021	Horner et al.	N/A	N/A
11305223	12/2021	Horner et al.	N/A	N/A
11389225	12/2021	Frampton et al.	N/A	N/A
D967384	12/2021	Horner	N/A	N/A
2004/0223859	12/2003	Sharp	N/A	N/A
2005/0000196	12/2004	Schultz	N/A	N/A
2005/0189283	12/2004	Smit et al.	N/A	N/A
2005/0263004	12/2004	Arsen et al.	N/A	N/A
2006/0099096	12/2005	Shaffer et al.	N/A	N/A
2006/0224150	12/2005	Arts et al.	N/A	N/A
2007/0066970	12/2006	Ineson	N/A	N/A
2009/0022613	12/2008	Dai et al.	N/A	N/A
2010/0185139	12/2009	Stearns et al.	N/A	N/A
2011/0067699	12/2010	Caruso et al.	N/A	N/A
2011/0203585	12/2010	Cozean et al.	N/A	N/A
2013/0023160	12/2012	Healey et al.	N/A	N/A
2013/0115122	12/2012	Lee	N/A	N/A
2013/0231606	12/2012	Stearns et al.	N/A	N/A
2013/0251514	12/2012	Oakman	N/A	N/A
2014/0303576	12/2013	Schultz	604/319	A61M 1/74
2014/0356207	12/2013	Yang	N/A	N/A
2015/0133750	12/2014	White et al.	N/A	N/A
2015/0224237	12/2014	Reasoner et al.	N/A	N/A
2015/0273381	12/2014	Stoner et al.	N/A	N/A
2016/0000494	12/2015	Cosmescu	N/A	N/A
2016/0001102	12/2015	Huh	N/A	N/A
2016/0169941	12/2015	Fukui	N/A	N/A
2016/0287817	12/2015	Mastri et al.	N/A	N/A
2016/0367266	12/2015	Palmerton et al.	N/A	N/A
2017/0014557	12/2016	Minskoff et al.	N/A	N/A
2017/0014560	12/2016	Minskoff et al.	N/A	N/A

2017/0095603	12/2016	Cho	N/A	N/A
2017/0165725	12/2016	Hersey et al.	N/A	N/A
2017/0181768	12/2016	Galley	N/A	N/A
2017/0181788	12/2016	Dastjerdi et al.	N/A	N/A
2017/0274125	12/2016	Minskoff et al.	N/A	N/A
2018/0221599	12/2017	Hiraga	N/A	A61B 17/3474
2019/0001029	12/2018	Davie et al.	N/A	N/A
2019/0001078	12/2018	Kane	N/A	B01D 46/0008
2019/0159825	12/2018	Frampton et al.	N/A	N/A
2019/0159826	12/2018	Horner et al.	N/A	N/A
2019/0159827	12/2018	Horner et al.	N/A	N/A
2019/0159830	12/2018	Horner et al.	N/A	N/A
2019/0160409	12/2018	Horner et al.	N/A	N/A
2019/0160410	12/2018	Horner et al.	N/A	N/A
2019/0162186	12/2018	Frampton et al.	N/A	N/A
2020/0214760	12/2019	Horner et al.	N/A	N/A
2020/0324238	12/2019	Jones et al.	N/A	N/A
2020/0353399	12/2019	Horner et al.	N/A	N/A
2021/0199136	12/2020	Tulett et al.	N/A	N/A
2022/0040419	12/2021	Silver	N/A	A61M 13/006
2022/0080136	12/2021	Teh	N/A	A61M 1/88

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1283952	12/1990	CA	A61B 18/20
204312376	12/2014	CN	N/A
304909540	12/2017	CN	N/A
2117982	12/1982	GB	N/A
2016-148281	12/2015	JP	N/A
20170096058	12/2016	KR	N/A
220478	12/2014	PL	N/A
94/08698	12/1993	WO	N/A
WO-9423657	12/1993	WO	A61B 18/00
2016/142690	12/2015	WO	N/A
2017/003712	12/2016	WO	N/A
2017/066720	12/2016	WO	N/A
2017/112684	12/2016	WO	N/A
2017/177069	12/2016	WO	N/A

OTHER PUBLICATIONS

Notice of Allowance received for U.S. Appl. No. 15/826,370, mailed on Apr. 14, 2023, 6 pages.
cited by applicant

Non-Final Office Action received for U.S. Appl. No. 15/826,370, mailed on Jan. 26, 2023, 9 pages.
cited by applicant

“Megadyne Surgical Smoke Evacuation System found online [Sep. 11, 2018]—<http://www.hcp-austria.com/Minivac%20Smoke%20Evacuators.html>”. cited by applicant

Bovie 35 hour filter found online [Sep. 11, 2018]—<http://www.boviemedical.com/smoke-shark-ii/>. cited by applicant

Chinese Patent Application No. 201830176822, filed on Apr. 2018. cited by applicant

Chinese Patent Application No. 304909540, filed Apr. 25, 2018. cited by applicant

Exam Report for MX/f/2018/001583 mailed Jan. 20, 2020. cited by applicant

Examiner Interview Summary received for U.S. Appl. No. 15/826,370, mailed on Nov. 27, 2020, 2 pages. cited by applicant

Final Office Action for U.S. Appl. No. 15/826,287 mailed Dec. 20, 2019. cited by applicant

Final Office Action for U.S. Appl. No. 15/826,342 mailed Nov. 5, 2019. cited by applicant

Final Office Action received for U.S. Appl. No. 15/826,289, mailed on Oct. 5, 2021, 10 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 15/826,370, mailed on Feb. 24, 2021, 31 pages. cited by applicant

International Search and Written Opinion for PCT/IB2018/059376 mailed May 7, 2019. cited by applicant

International Search Report and Written Opinion for PCT/IB2018/059371 mailed Feb. 15, 2019. cited by applicant

International Search Report and Written Opinion for PCT/IB2018/059375 mailed May 7, 2019. cited by applicant

International Search Report and Written Opinion for PCT/IB2018/059377 mailed Mar. 6, 2019. cited by applicant

International Search Report and Written Opinion for PCT/IB2018/059378 mailed May 10, 2019. cited by applicant

Non-Final Office Action for U.S. Appl. No. 15/826,287 mailed Jul. 17, 2019. cited by applicant

Non-Final Office Action for U.S. Appl. No. 15/826,325 mailed Aug. 1, 2019. cited by applicant

Non-Final Office Action for U.S. Appl. No. 15/826,342 mailed Jul. 16, 2019. cited by applicant

Non-Final Office Action for U.S. Appl. No. 15/826,344 mailed Sep. 12, 2019. cited by applicant

Non-Final Office Action for U.S. Appl. No. 29/627,788 mailed Feb. 19, 2019. cited by applicant

Non-Final Office Action for U.S. Appl. No. 29/627,793 mailed on Oct. 29, 2018. cited by applicant

Non-Final Office Action for U.S. Appl. No. 29/627,794 mailed Feb. 19, 2020. cited by applicant

Non-Final Office Action for U.S. Appl. No. 29/627,794 mailed Jul. 10, 2019. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 15/826,289, mailed on May 28, 2021, 12 pages. cited by applicant

Non-Final Office Action Received for U.S. Appl. No. 15/826,370, Mailed on Aug. 18, 2020, 24 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 15/826,370, mailed on Nov. 23, 2021, 35 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 15/826,376, mailed on Apr. 26, 2021, 7 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/825,998, mailed on Feb. 2, 2021, 9 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/937,000, mailed on Aug. 31, 2021, 8 pages. cited by applicant

Notice of Allowance for U.S. Appl. No. 15/826,287 mailed Feb. 12, 2020. cited by applicant

Notice of Allowance for U.S. Appl. No. 15/826,325 mailed Dec. 26, 2019. cited by applicant

Notice of Allowance for U.S. Appl. No. 15/826,342 mailed Apr. 23, 2020. cited by applicant

Notice of Allowance for U.S. Appl. No. 15/826,342 mailed Jan. 31, 2020. cited by applicant

Notice of Allowance for U.S. Appl. No. 15/826,344 mailed Jan. 23, 2020. cited by applicant

Notice of Allowance for U.S. Appl. No. 29/627,788 mailed Jul. 23, 2019. cited by applicant

Notice of Allowance for U.S. Appl. No. 29/627,793 mailed Feb. 21, 2020. cited by applicant

Notice of Allowance for U.S. Appl. No. 15/826,344 dated Apr. 22, 2020. cited by applicant

Notice of Allowance received for U.S. Appl. No. 29/760,171, mailed on Feb. 24, 2022, 6 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 15/826,289, mailed on Mar. 18, 2022, 8 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 15/826,376, mailed on Mar. 3, 2021, 9 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 15/826,376, mailed on Oct. 1, 2021, 8 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 16/825,998, mailed on Apr. 6, 2021, 9 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 16/825,998, mailed on Jul. 27, 2021, 10 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 16/825,998, mailed on Oct. 22, 2021, 2 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 29/733,877, mailed on Dec. 27, 2021, 2 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 29/733,877, mailed on Sep. 2, 2021, 9 pages. cited by applicant

Requirement for Restriction/Election received for U.S. Appl. No. 15/826,289, mailed on Dec. 15, 2020, 8 pages. cited by applicant

Requirement for Restriction/Election received for U.S. Appl. No. 15/826,376, mailed on Sep. 30, 2020, 6 pages. cited by applicant

Requirement for Restriction/Election received for U.S. Appl. No. 29/760,171, mailed on Jan. 13, 2022, 5 pages. cited by applicant

U.S. Appl. No. 16/825,998, filed Mar. 20, 2020. cited by applicant

U.S. Appl. No. 29/627,793, filed Nov. 29, 2017. cited by applicant

U.S. Appl. No. 29/627,794, filed Nov. 29, 2017. cited by applicant

Final Office Action received for U.S. Appl. No. 15/826,370, mailed on Jul. 22, 2022, 40 pages. cited by applicant

Notice of Allowance for U.S. Appl. No. 15/826,344 mailed May 21, 2020. cited by applicant

Notice of Allowance for U.S. Appl. No. 29/627,794 mailed Aug. 14, 2020. cited by applicant

Notice of Allowance for U.S. Appl. No. 16/937,000 mailed Dec. 17, 2021. cited by applicant

Notice of Allowance received for U.S. Appl. No. 29/760,171, mailed on Jun. 10, 2022, 6 pages. cited by applicant

Examiner Interview Summary Record (PTOL-413) Mailed on Mar. 17, 2022 for U.S. Appl. No. 15/826,370, 2 page(s). cited by applicant

Examiner Interview Summary Record (PTOL-413) Mailed on Nov. 27, 2020 for U.S. Appl. No. 15/826,370, 2 page(s). cited by applicant

Final Rejection Mailed on Feb. 24, 2021 for U.S. Appl. No. 15/826,370, 29 page(s). cited by applicant

Final Rejection Mailed on Jul. 22, 2022 for U.S. Appl. No. 15/826,370, 39 page(s). cited by applicant

List of references cited by examiner Mailed on Aug. 18, 2020 for U.S. Appl. No. 15/826,370, 1 page(s). cited by applicant

List of references cited by examiner Mailed on Jul. 22, 2022 for U.S. Appl. No. 15/826,370, 1 page(s). cited by applicant

List of references cited by examiner Mailed on Mar. 3, 2021 for U.S. Appl. No. 15/826,376, 1 page(s). cited by applicant

Non-Final Rejection Mailed on Apr. 26, 2021 for U.S. Appl. No. 15/826,376, 7 page(s). cited by

applicant
Non-Final Rejection Mailed on Aug. 18, 2020 for U.S. Appl. No. 15/826,370, 24 page(s). cited by applicant
Non-Final Rejection Mailed on Jan. 26, 2023 for U.S. Appl. No. 15/826,370, 9 page(s). cited by applicant
Non-Final Rejection Mailed on Nov. 23, 2021 for U.S. Appl. No. 15/826,370, 35 page(s). cited by applicant
Notice of Allowance and Fees Due (PTOL-85) Mailed on Apr. 14, 2023 for U.S. Appl. No. 15/826,370, 6 page(s). cited by applicant
Notice of Allowance and Fees Due (PTOL-85) Mailed on Dec. 15, 2021 for U.S. Appl. No. 15/826,376, 4 page(s). cited by applicant
Notice of Allowance and Fees Due (PTOL-85) Mailed on Mar. 3, 2021 for U.S. Appl. No. 15/826,376, 8 page(s). cited by applicant
Notice of Allowance and Fees Due (PTOL-85) Mailed on Mar. 29, 2023 for U.S. Appl. No. 15/826,370, 9 page(s). cited by applicant
Notice of Allowance and Fees Due (PTOL-85) Mailed on Oct. 1, 2021 for U.S. Appl. No. 15/826,376, 8 page(s). cited by applicant
Office Action Appendix Mailed on Mar. 17, 2022 for U.S. Appl. No. 15/826,370, 1 page(s). cited by applicant
Requirement for Restriction/Election Mailed on Feb. 13, 2020 for U.S. Appl. No. 15/826,370, 9 page(s). cited by applicant
Requirement for Restriction/Election Mailed on Sep. 30, 2020 for U.S. Appl. No. 15/826,376, 6 page(s). cited by applicant

Primary Examiner: Eisenberg; Rebecca E

Assistant Examiner: Yang; Ted

Attorney, Agent or Firm: Workman Nydegger

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 15/826,376, filed Nov. 29, 2017, and entitled Smoke Evacuation Device, the entire content of which is incorporated herein by reference.

BACKGROUND

1. Technical Field

(1) The present disclosure relates to smoke evacuation systems.

2. The Relevant Technology

(2) As is known to those skilled in the art, modern surgical techniques typically employ radio frequency (RF) power to cut tissue and coagulate bleeding encountered in performing surgical procedures. Such electrosurgery is widely used and offers many advantages including the use of a single surgical instrument for both cutting and coagulation. A monopolar electrosurgical generator system has an active electrode, such as in the form of an electrosurgical instrument having a hand piece and a conductive electrode or tip, which is applied by the surgeon to the patient at the surgical site to perform surgery and a return electrode to connect the patient back to the generator.

(3) The electrode or tip of the electrosurgical instrument is small at the point of contact with the patient to produce an RF current with a high current density in order to produce a surgical effect of

cutting or coagulating tissue through cauterization. The return electrode carries the same RF signal provided to the electrode or tip of the electrosurgical instrument, after it passes through the patient, thus providing a path back to the electrosurgical generator.

(4) Electrosurgical instruments communicate electrical energy to a target tissue of a patient to cut the tissue and/or cauterize blood vessels within and/or near the target tissue. This cutting and cauterization results in smoke released into the air that can be distracting or otherwise unpleasant. Many electrosurgical systems may therefore employ an evacuation system that captures the resulting smoke and directs it through a filter and exhaust port, away from practitioners and/or patients. A smoke evacuation system typically creates suction directed at the smoke using fans to draw the smoke through a tube connecting the surgical instrument to an exhaust port.

(5) Smoke evacuation systems typically comprise a pump and a filter. The pump creates suction that draws smoke through a vacuum tube into the filter. A vacuum tube may terminate at the hand piece that includes the electrode tip so that the smoke is sucked in at the hand piece. Other electrosurgical systems may include separate hand pieces that are used to suck the smoke into the system. The smoke travels to the filter via a vacuum tube and offensive smells and particulate are filtered out as the smoke moves through the filter. Filtered air may then exit the smoke evacuation system as exhaust. Periodically replacing the filters is necessary for the smoke evacuation system to remain effective.

(6) The subject matter claimed herein is not limited to embodiments that solve any disadvantages or that operate only in environments such as those described above. Rather, this background is only provided to illustrate one exemplary technology area where some embodiments described herein may be practiced.

BRIEF SUMMARY

(7) The present disclosure relates to smoke evacuation systems used in electrosurgical systems.

(8) In one embodiment, a smoke evacuation system includes a housing surrounding an enclosure and an airflow path extending inside the enclosure from an inlet port to an outlet port of the smoke evacuation system. The system also includes a motor and pump disposed within the enclosure. A cooling mechanism is configured to induce airflow through the enclosure to cool the enclosure. The induce airflow is proportionate to the work output of the motor.

(9) In one embodiment, a smoke evacuation system includes an inlet port, outlet port, an airflow path extending between the inlet port and the outlet port, and one or more cooling vents. The smoke evacuation system also includes an exhaust mechanism near the outlet port. The exhaust mechanism is configured to diffuse air exiting at the outlet port.

(10) In one embodiment, a smoke evacuation system includes an airflow control mechanism, an exhaust diffuser, and a rotary mechanism. The airflow control mechanism reduces a pressure within the smoke evacuation system when abnormal flow or high pressures are detected. The exhaust diffuser reduces the exit noise of the filtered air without baffling or redirecting flow causing an exit head pressure. The rotary mechanism induces an airflow through the smoke evacuation system at a flow rate that is proportional to the rate at which a pump is pumping filtered air through the smoke evacuation system.

(11) In one embodiment, a filter connection for a smoke evacuation system includes a filter canister and a socket. The filter canister comprises first and second ends, a body extending between the first and second ends, a connection nipple, a seal disposed around the connection nipple, and a first electronic connector. The socket comprises a first recess configured to receive the canister body, a second recess configured to receive the connection nipple, and a second electronic connector. The longitudinal distance between the seal and the first electronic connector is greater than the longitudinal distance between the second recess of the socket and the second electronic connector.

(12) In one embodiment, a filter canister for a smoke evacuation system includes a first end having an inlet port, a second end, an electronic connector, and a connection nipple disposed at the second end. The cross-sectional shape of the second end of the filter canister has only one line of

symmetry. The electronic connector is disposed at the second end of the filter canister.

(13) In one embodiment, a method for connecting a filter in a smoke evacuation system includes the following steps: providing a filter canister; providing a socket in the smoke evacuation system; inserting the filter canister a first distance into the socket so that the filter canister creates an airtight boundary between the filter canister and the socket; and inserting the filter canister a second distance into the socket so that an electronic connection is made between the filter canister and the socket. The second distance is greater than the first distance.

(14) In one embodiment, a smoke evacuation system includes a filter, a pump that has a sealed positive displacement airflow path, and a motor that drives the pump. The sealed positive displacement airflow path of the pump may comprise one or more circulation paths of a gas within the pump. In one embodiment, the pump has a first operating pressure and a second operating pressure. The flow rate of a gas being pumped may be the same regardless of the operating pressure. The pump may compress incoming gas to create a pressure difference between various zones of airflow within the smoke evacuation system.

(15) In one embodiment, a smoke evacuation system may include various vibration absorption mechanisms. The system may have a first housing enclosing the motor and the pump and a second housing enclosing the entire system. Vibration mechanisms may be disposed between the two housings and outside the second housing. Flexible tubing may also be incorporated to absorb vibrations.

(16) A method of reducing the vibrations and noise of a smoke evacuation system may include regulating the motor engaged with the pump. The regulation of the motor may include varying a supply of current to the motor in order to operate the motor in at least two distinct operating levels. Regulation of the motor may depend on sensory inputs, such as temperature or pressure. Orifices may also be provided within the airflow path that allow communication with ambient surroundings of the system in order to relieve excessive resistance pressures in the system caused by blockages or clogging of the airflow path.

(17) In an embodiment, a fluid trap for minimizing the escape of contaminated fluids from the fluid trap when an orientation of the fluid trap changes during removal or transport includes (i) a front cover defining an inlet port that extends a first distance into an interior chamber of the fluid trap, (ii) a rear cover coupled to the front cover and which defines an exhaust port extending a second distance away from the rear cover of the fluid trap and positioned above the inlet port when the fluid trap is in an upright position, and (iii) an interior chamber defined by the front and rear covers. The interior chamber includes a maximum fluid volume at least partially defined by the lesser of a fluid reservoir volume, a front cover volume, and a rear cover volume.

(18) In one or more embodiments, the fluid reservoir volume is the volume defined by the interior sidewalls of the fluid trap below the inlet port, the front cover volume is equivalent to a product of the surface area of the front cover and an average depth of the front cover with respect to the first distance of the inlet port, and the rear cover volume is the volume of the interior chamber defined by interior sidewalls of the fluid trap and bounded by a line tangent to a lowest interior-facing sidewall of the exhaust port that is parallel with a surface upon which the exhaust port lies.

(19) In an embodiment, a fluid trap for minimizing the escape of contaminated fluids includes an interior chamber defined by sidewalls of the fluid trap, an inlet port extending into the interior chamber that is or includes a notched cylindrical body that directs smoke in a defined direction, and an exhaust port positioned opposite and above the inlet port. The exhaust port defines an open channel between the interior chamber of the fluid trap and an area outside the fluid trap.

Additionally, the fluid trap can include a splash canopy positioned between the inlet port and the exhaust and extending laterally across a width of the inlet port, and in an embodiment, the fluid trap additionally includes a splash wall spanning opposing sidewalls of the interior chamber and extending vertically from a first point coplanar with at least a portion of the splash canopy to a second point coplanar with at least a portion of the exhaust port. The splash canopy and/or the

splash wall can, in some embodiments, include a fibrous fluid wicking material that enables removal of aerosols and/or small droplet fluids and additionally, or alternatively, act as condensation promoting surfaces.

(20) In an embodiment, a smoke evacuation system includes a suction pump, a filter connected to the suction pump, and a fluid trap connected to the filter. The fluid trap includes an interior chamber, a sensor disposed within the interior chamber for monitoring a fluid level within the fluid trap, and a visual indicator in electrical communication with the sensor that represents the fluid level within the fluid trap. Additionally, in an embodiment, the sensor is an optical emitter and detector pair, an ultrasonic detector, a resistive strip, or a combination thereof that senses the amount of fluid in the fluid trap and activates a corresponding visual indicator to communicate the fill status of the fluid trap, such as the fluid trap reaching a maximum fill state.

(21) In an embodiment, a filter includes (i) a filter body, (ii) a front cap associated with a first end of the filter body and coupled to and receiving smoke from a vacuum hose, (iii) a back cap associated with a second end of the filter body and having a filter exhaust sized and shaped to associate with and communicate suction from a smoke evacuation system, (iv) a compressed carbon reservoir disposed within the filter body between the front cap and the back cap, and (v) a flexible porous barrier disposed on at least a first side of the compressed carbon reservoir.

(22) In an embodiment, a replaceable filter for processing smoke derived from electrosurgery includes (i) a filter body, (ii) a front cap associated with a first end of the filter body, (iii) a back cap associated with a second end of the filter body and configured to receive suction, (iv) one or more particulate filters disposed within the filter body between the front cap and the back cap, (v) a compressed carbon reservoir disposed within the filter body between the one or more particulate filters and the back cap, and (vi) a flexible porous barrier disposed on at least a first side of the compressed carbon reservoir.

(23) In an embodiment, a three-stage filter for processing smoke derived from electrosurgery includes a first stage for removing one or more fluids from the smoke, a second stage for removing particulates, and a third stage having a compressed carbon reservoir. The first stage can include a fluid trap having a fluid trap inlet port and a fluid trap exhaust port. The fluid trap inlet port extends into an interior chamber of the fluid trap and couples to and receives smoke from a vacuum hose. The fluid trap exhaust port is positioned opposite and above the fluid trap inlet port and defines an open channel between an interior chamber of the fluid trap, where one or more fluids extracted from the smoke are retained, and the second stage of the three-stage filter. In some embodiments, the second-stage removes particulates using one or more particulate filters, such as a coarse media filter and an ultra-low penetration air (ULPA) filter in series. In some embodiments, the third stage can be under a compressive bias by a flexible porous barrier. The flexible porous barrier can transition from a flexed state to a partially relaxed state in response to the compressed carbon reservoir reducing in volume, which in some embodiments is caused by settling of the compressed carbon reservoir or pressure from suction applied to the compressed carbon reservoir.

(24) In an embodiment, an RF current sensor is configured to operate in at least two modes—a first mode and a second mode—and includes (i) a sensor body having at least a cable interfacing sidewall and a retaining member, the cable interfacing sidewall and the retaining member defining a retention pocket configured to receive a cable communicating RF current, (ii) a sensor element for detecting RF current in the cable, and (iii) a sensor cable in electrical communication with the sensor element, the sensor cable communicating one or more of an activation signal or a current signal derived from the detected RF current to the smoke evacuation device.

(25) The RF sensor can operate in the first mode when the sensor element identifies a single RF current in the cable. The single RF current in the cable can be communicated between a signal generator and an active electrode of a monopolar electrosurgical instrument or between a return electrode and the signal generator, and the activation signal and/or the current signal are derived from the single RF current when the RF current sensor operates in the first mode. The RF sensor

can operate in the second mode when the sensor element identifies two RF currents—a first RF current flowing in an opposite direction as a second RF current—in the cable. Operating in the second mode causes the RF current sensor to detect the first RF current with respect to the second RF current and to derive the activation signal and/or the current signal from the first RF current.

(26) In an embodiment, a method for remote activation of a smoke evacuation device includes (i) generating an RF current at a signal generator, (ii) communicating the RF current through a source cable to an electrosurgical instrument, (iii) detecting an activation of RF current with an RF current sensor communicatively coupled to a smoke evacuation device, (iv) communicating an activation signal from the RF current sensor to the smoke evacuation device in response to detecting the activation of RF current, (v) receiving the activation signal at the smoke evacuation device, and (vi) activating a vacuum source for one or more of a defined period of time or to generate a defined smoke evacuation flow rate in response to receiving the activation signal.

(27) In some embodiments, the method for remote activation of a smoke evacuation device can additionally include (i) detecting the RF current with the RF current sensor subsequent to detecting the activation of RF current, (ii) periodically or continuously communicating a current signal from the RF current sensor to the smoke evacuation device in response to detecting the RF current, the signal current including data associated with the RF current, (iii) receiving the current signal at the smoke evacuation device, and (iv) in response to receiving the current signal, adjusting the defined period of time and/or the defined smoke evacuation flow rate of the vacuum source.

(28) In some embodiments, the method for remote activation of a smoke evacuation device can additionally include deriving a treatment power based on the activation signal and/or the current signal and calculating an estimated smoke production based on the treatment power, and the defined period of time and/or the defined smoke evacuation flow rate can be based on the estimated smoke production.

(29) In an embodiment, an electrosurgical system includes (i) a signal generator producing an RF current, (ii) a source cable electrically coupled to the signal generator and to an electrosurgical instrument, the source cable communicating the RF current from the signal generator to the electrosurgical instrument, (iii) a smoke evacuation device that includes a vacuum hose positioned proximate the electrosurgical instrument and configured to evacuate smoke generated by the electrosurgical instrument, and (iv) an RF current sensor communicatively coupled to the smoke evacuation device, the RF current sensor activating the smoke evacuation device in response to identifying the RF current.

(30) In some embodiments, the RF current sensor is removably coupled to the source cable or the return cable and detects RF current flowing therethrough. In some embodiments, the RF current sensor is integrally formed within the return electrode or within the smoke evacuation device.

(31) This Summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used as an aid in determining the scope of the claimed subject matter.

(32) Additional features and advantages of the disclosed embodiments will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by the practice of the disclosure. These and other features will become more fully apparent from the following description and appended claims, or may be learned by the practice of the present disclosure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) To further clarify the above and other advantages and features of the present invention, a more

particular description of the invention will be rendered by reference to specific embodiments thereof which are illustrated in the appended drawings. It is appreciated that these drawings depict only illustrated embodiments of the invention and are therefore not to be considered limiting of its scope. The invention will be described and explained with additional specificity and detail through the use of the accompanying drawings in which:

- (2) FIG. 1 illustrates an embodiment of an electrosurgical system;
- (3) FIG. 2 illustrates a schematic of a smoke evacuation system;
- (4) FIG. 3A illustrates a perspective view of an embodiment of a smoke evacuation system;
- (5) FIG. 3B illustrates a partial cross-sectional view of the smoke evacuation system illustrated in FIG. 3A;
- (6) FIG. 4 illustrates a partial cross-sectional view of an embodiment of a cooling mechanism;
- (7) FIG. 5A illustrates a cross-sectional view of an embodiment of a cooling mechanism;
- (8) FIG. 5B illustrates a front view of an embodiment of an airflow path;
- (9) FIG. 5C illustrates a front view of the cooling mechanism illustrated in FIG. 5A;
- (10) FIG. 6 illustrates an embodiment of an exhaust mechanism and a pressure relief mechanism disposed at an outlet port of a smoke evacuation system;
- (11) FIG. 7A illustrates a perspective view of a diffuser;
- (12) FIG. 7B illustrates a schematic of the diffuser illustrated in FIG. 7A;
- (13) FIG. 8A illustrates a perspective view of an embodiment of a smoke evacuation system;
- (14) FIG. 8B illustrates a cross-sectional view of the system illustrated in FIG. 8A, wherein an embodiment of a socket is shown;
- (15) FIG. 9A illustrates a perspective view of an embodiment of a filter canister assembly;
- (16) FIG. 9B illustrates a perspective view of an embodiment of a filter canister assembly;
- (17) FIG. 10A illustrates a schematic of a cross-sectional shape of one end of a filter canister assembly and an opening of a socket;
- (18) FIG. 10B illustrates a schematic of a cross-sectional shape of one end of a filter canister assembly and an opening of a socket;
- (19) FIG. 10C illustrates a perspective view of an embodiment of a filter canister;
- (20) FIG. 10D illustrates a perspective view of an embodiment of a socket of a smoke evacuation system;
- (21) FIG. 11A illustrates a cross-sectional view of a filter canister assembly partially inserted into a socket;
- (22) FIG. 11B illustrates a cross-sectional view of a filter canister assembly fully inserted into a socket;
- (23) FIG. 12 illustrates a flow chart describing a method for connecting a canister to a smoke evacuation system;
- (24) FIG. 13 illustrates a schematic of an embodiment of a smoke evacuation system;
- (25) FIG. 14 illustrates resistance pressure vs. air flow for a sealed positive displacement pump and a fan;
- (26) FIG. 15 illustrates a table comparing various specifications of a fan, blower, and compressor.
- (27) FIG. 16A illustrates an exploded view of a hybrid regenerative blower;
- (28) FIG. 16B illustrates a cross-sectional view of the hybrid regenerative blower illustrated in FIG. 16A;
- (29) FIGS. 17A through 17C illustrate cross-sectional views of various stages of a claw pump;
- (30) FIG. 18A illustrates one embodiment of a lobe compressor having two lobes;
- (31) FIG. 18B illustrates one embodiment of a lobe compressor having three lobes;
- (32) FIG. 18C illustrates one embodiment of a lobe compressor having five lobes;
- (33) FIG. 19 illustrates a cross-sectional view of one embodiment of a scroll compressor;
- (34) FIG. 20 illustrates one embodiment of a dual, in-line scroll compressor;
- (35) FIG. 21A illustrates one embodiment of a high flow and a low flow scroll;

(36) FIG. 21B illustrates the relationship of time vs. airflow for both the low flow scroll and the high flow scroll illustrated in FIG. 21A;

(37) FIG. 22 illustrates an embodiment of a smoke evacuation system including inner and outer housings;

(38) FIG. 23 illustrates an embodiment of vibration absorption mechanisms disposed between inner and outer housings;

(39) FIG. 24A illustrates one embodiment of vibration absorption mechanisms disposed between inner and outer housings;

(40) FIGS. 24B and 24C illustrate various cross-sectional views of the vibration absorption mechanisms illustrated in FIG. 24A;

(41) FIG. 25A illustrates one embodiment of a vibration absorption mechanism;

(42) FIG. 25B illustrates a cross-sectional view of the vibration absorption mechanism illustrated in FIG. 25A;

(43) FIG. 26 illustrates one embodiment of a vibration absorption mechanism;

(44) FIGS. 27A through 27C illustrate various embodiments of vibration absorption mechanisms;

(45) FIG. 28A illustrates one embodiment of a vibration absorption mechanism;

(46) FIG. 28B illustrates a cross-sectional view of one of the vibration absorption mechanisms illustrated in FIG. 28A;

(47) FIG. 28C illustrates one embodiment of a vibration absorption mechanism;

(48) FIG. 29A illustrates one embodiment of a vibration absorption mechanism;

(49) FIG. 29B illustrates a cross-sectional view of the vibration absorption mechanisms illustrated in FIG. 29A;

(50) FIG. 30A illustrates a cross-sectional view of one embodiment of a vibration absorption mechanism;

(51) FIG. 30B illustrates the vibration absorption mechanism illustrated in FIG. 30A, but undergoing deformation due to vibrations;

(52) FIG. 31 illustrates a flowchart showing a method of reducing noise and vibration of a smoke evacuation system;

(53) FIG. 32 illustrates a smoke evacuation system associated with an exemplary fluid trap;

(54) FIG. 33 illustrates a front perspective view of an exemplary fluid trap;

(55) FIG. 34 illustrates a rear perspective view of the exemplary fluid trap of FIG. 33;

(56) FIG. 35 illustrates a side view of the exemplary fluid trap of FIG. 33;

(57) FIG. 36 illustrates a vertical cross-section of the exemplary fluid trap depicted in FIG. 35;

(58) FIG. 37 illustrates a simplified vertical cross-section of the exemplary fluid trap depicted in FIG. 35 and an embodiment of air flow through therethrough;

(59) FIG. 38 illustrates a simplified vertical cross-section of the exemplary fluid trap depicted in FIG. 35 having fluid collected therein and in an upright position;

(60) FIG. 39 illustrates a simplified vertical cross-section of the exemplary fluid trap depicted in FIG. 35 having fluid collected therein and positioned on a surface inlet-side down;

(61) FIG. 40 illustrates a simplified vertical cross-section of the exemplary fluid trap depicted in FIG. 35 having fluid collected therein and positioned on a surface inlet side up;

(62) FIG. 41 illustrates a simplified vertical cross-section of another exemplary fluid trap having fluid collected therein that is positioned on a surface inlet-side up with the fluid shown as being agitated;

(63) FIG. 42 illustrates a partial cross section, perspective view of a fluid trap having baffles;

(64) FIG. 43 illustrates a partial cross section, perspective view of a fluid trap having a plurality of interior condensation surfaces;

(65) FIG. 44 illustrates a perspective view of a fluid trap with transparent viewing windows;

(66) FIG. 45 illustrates a partial cross section, perspective view of a fluid trap having a fill detector and indicator light;

(67) FIG. **46** illustrates a partial cross section, front view of a fluid trap having a graded fill sensor and indicator light;

(68) FIG. **47** illustrates a partial perspective view of a fluid trap with a drain valve;

(69) FIG. **48** illustrates an exemplary smoke filter for use with a smoke evacuation system;

(70) FIG. **49** illustrates a cross-section along the longitudinal axis of the exemplary smoke filter of FIG. **48**, revealing various components therein;

(71) FIG. **50** illustrates a simplified view of the cross-section illustrated in FIG. **49** that emphasizes the carbon reservoir;

(72) FIG. **51** illustrates the simplified view of FIG. **50** with a volumetric decrease in the carbon reservoir;

(73) FIG. **52** illustrates cross-sections before and after a volumetric shift within a filter having a flexible porous barrier;

(74) FIG. **53** illustrates cross-sections before and after a volumetric shift within another filter having a flexible porous barrier;

(75) FIG. **54** illustrates a cross-section after a volumetric shift within a filter having a flexible porous barrier;

(76) FIG. **55** illustrates cross-sections before and after a volumetric shift within a filter having a ratcheting porous barrier;

(77) FIG. **56** illustrates a perspective view of an exemplary remote activation clip;

(78) FIG. **57** illustrates an elevation view of the exemplary remote activation clip of FIG. **56**;

(79) FIG. **58** illustrates a partial cross-sectional view of the exemplary remote activation clip of FIG. **56**;

(80) FIG. **59** illustrates a remote activation clip associated with a cable leading to the electrosurgical instrument of the depicted electrosurgical system;

(81) FIG. **60** illustrates a remote activation clip associated with a cable extending from the return electrode of the depicted electrosurgical system;

(82) FIG. **61** illustrates a current sensor associated with the return electrode of the depicted electrosurgical system;

(83) FIG. **62** illustrates a current sensor associated with the smoke evacuation device of the depicted electrosurgical system;

(84) FIG. **63** illustrates an exemplary graph depicting a potential smoke evacuation flow rate with respect to the sensed treatment current from current sensors described herein; and

(85) FIG. **64** illustrates an exemplary graph depicting potential smoke evacuation flow rates with respect to an estimated amount or volume of generated smoke.

DETAILED DESCRIPTION

(86) The present disclosure relates to smoke evacuation systems used in electrosurgical systems. Some embodiments of the present disclosure relate to methods and apparatuses for managing noise and vibrations of smoke evacuation systems. Noise and vibrations produced by smoke evacuation systems can be distracting and irritating to practitioners performing surgery. Some embodiments relate to apparatuses and methods for controlling air flow parameters to cool the smoke evacuation system in order to avoid overheating. Still other embodiments relate to a filter connection for a smoke evacuation device. It may be difficult to determine when filters need to be replaced in smoke evacuation systems, and current filter connections can lead to faulty installations. The filter connection of the present disclosure may enable easy installation of filters, as well as other features to electronically detect and communicate when filters need to be replaced or when an incorrect filter has been installed. Further embodiments relate to fluid traps used to remove fluids and other materials evacuated from a surgical site. Embodiments disclosed herein also relate to remote activation devices that activate a smoke evacuation system upon detection of certain system parameters.

(87) Reference is made herein to the evacuation of smoke and components that facilitate such

function. It will be appreciated that references to “smoke” is merely for simplicity and convenience, and is not intended to limit the disclosed and claimed embodiments to evacuation of only smoke. Rather, the disclosed and claimed embodiments may be used to evacuate substantially any type of fluid, including liquids, gases, vapors, smoke, or combinations thereof. Additionally, rather than simply evacuating fluid, it is contemplated that at least some of the embodiments may be used to deliver fluids to a desired location, such as a surgical site. As used herein, the term “fluid” includes bulk liquids and/or liquid vapor, which can include liquids-biologic in origin or otherwise-obtained from or introduced into a surgical site (e.g., water, saline, lymph, blood, exudate, pyogenic discharge, and/or other fluid). A “fluid” is additionally intended to include cellular matter or debris that is transported through a vacuum hose and into the fluid reservoir of a mechanically coupled fluid trap.

(88) General

(89) FIG. 1 illustrates an exemplary electrosurgical system **100**. The illustrated embodiment includes a signal generator **102**, an electrosurgical instrument **104**, a return electrode **106**, and a smoke evacuation system **120**. Generator **102**, in one embodiment, is an RF wave generator that produces RF electrical energy. Connected to electrosurgical instrument **104** is a utility conduit **108**. In the illustrated embodiment, utility conduit **108** includes a cable **110** that communicates electrical energy from generator **102** to electrosurgical instrument **104**. The illustrated utility conduit **108** also includes a vacuum hose **112** that conveys captured/collected smoke and/or fluid away from a surgical site.

(90) Generally, electrosurgical instrument **104** includes a hand piece or pencil **114** and an electrode tip **116**. Electrosurgical instrument **104** communicates electrical energy to a target tissue of a patient to cut the tissue and/or cauterize blood vessels within and/or near the target tissue. Specifically, an electrical discharge is delivered from electrode tip **116** to the patient in order to cause heating of cellular matter of the patient that is in close contact with or adjacent to electrode tip **116**. The tissue heating takes place at an appropriately high temperature to allow electrosurgical instrument **104** to be used to perform electrosurgery. Return electrode **106** is connected to generator **102** by a cable **118**, and is either applied to or placed in close proximity to the patient (depending on the type of return electrode), in order to complete the circuit and provide a return electrical path to wave generator **102** for energy that passes into the patient's body.

(91) The heating of cellular matter of the patient by the electrode tip **116**, or cauterization of blood vessels to prevent bleeding, results in smoke being released where the cauterization takes place. The electrosurgical instrument **104** may comprise a smoke evacuation conduit opening **122** near the electrode tip **116** so as to be able to capture the smoke that is released during a procedure. Vacuum suction may draw the smoke into the conduit opening **122**, through the electrosurgical instrument **104**, and into the vacuum hose **112** toward the smoke evacuation system **120**.

(92) FIG. 2 illustrates an embodiment of a smoke evacuation system **200**. The smoke evacuation system **200** may include a filter **206** and an airflow path **208**. The airflow path **208** may comprise a pump **210** disposed in-line with the airflow path **208** producing a pressure difference within the airflow path **208** by mechanical action. The term “pump” as used herein refers to blowers, compressors, and other mechanical means of moving a fluid/gas while increasing the pressure of the fluid/gas. This pressure difference may cause movement of a gas through the airflow path **208**. The gas drawn through the airflow path **208** may be smoke **202**, or the filtered air remaining after the smoke **202** has passed through the filter **206**. A motor **212** drives the pump **210**. The smoke evacuation system **200** may also include an exhaust mechanism **214** that may also be disposed in-line with the airflow path **208**.

(93) The airflow path **208** may be disposed between an inlet port **222** and an outlet port **224**. The smoke **202** may flow into the filter **206** at the inlet port **222**, be pumped through the airflow path **208** by the pump **210** so that the smoke **202** is drawn through the filter **206**, through the exhaust mechanism **214**, and out the outlet port **224** of the smoke evacuation system **200**. The air exiting

the smoke evacuation system **200** at the outlet port **224** may be the exhaust **204**. The exhaust **204** may consist of filtered air/gas that has passed through the smoke evacuation system **200** and exits through the outlet port **224**.

(94) The airflow path **208** may comprise a first zone **216** and a second zone **218**. The first zone **216** may be upstream from the pump **205** and the second zone **218** may be downstream from the pump **205**. The pump **205** may pressurize the air in the airflow path **208** so that the air in the second zone **218** has a higher pressure than the air in the first zone **216**. This pressure difference causes air to flow through the airflow path **208** from the inlet port **222** to the outlet port **224**.

(95) The smoke evacuation system **200** may also include a housing **220**. FIG. 2 illustrates a schematic view of a smoke evacuation system **200** to show the various components within the housing **220**. An enclosure **226** may be defined by the space inside the housing **220** but outside the airflow path **208**. The housing **220** may completely or partially encompass or enclose the smoke evacuation system **200**. The airflow path **208** may be at least partially comprised of a tube or other conduit that substantially contains and/or isolates the air moving through the airflow path **208** air outside the airflow path **208**.

(96) For example, the first zone **216** of the airflow path **208** may comprise a tube through which the airflow path **208** extends between the filter **206** and the pump **210**. The second zone **218** of the airflow path **208** may also comprise a tube through which the airflow path **208** extends between the pump **210** and the exhaust mechanism **214**. The airflow path **208** also extends through the filter **206**, pump **210**, and exhaust mechanism **214** so that a continuous airflow path **208** extends from the inlet port **222** to the outlet port **224**.

(97) Controlling Flow Parameters

(98) FIG. 3A illustrates a smoke evacuation system **200** that includes a cooling mechanism **230**. The cooling mechanism **230** may include a plurality of openings **232** in the outer housing **220** of the smoke evacuation system **200**. The embodiment illustrated in FIG. 3A includes ten square-shaped openings **232** disposed together in a group. Air may flow into the smoke evacuation system **200** through the openings **232** in the outer housing **220**. Air that enters through the openings **232** may cool internal components of the smoke evacuation system **200**, such as the motor and/or pump, by convective heat transfer.

(99) Other embodiments of a smoke evacuation system **200** may include cooling mechanisms **230** that have more or less than ten openings **232**. For example, one embodiment may include only one opening **232**. Other embodiments may include more than ten openings **232**. It will be appreciated that a large number of variations in the openings **232** in the outer housing **220**, including the size, shape, and number of openings **232**, may be employed in other embodiments to achieve the same or similar cooling effects of the openings **232**.

(100) The openings **232** may be positioned in the outer housing **220** to facilitate cooling of certain components within the outer housing **220**. For example, in the embodiment illustrated in FIG. 3A, the openings **232** are positioned such that they may be directly over a motor (e.g., motor **212** in FIG. 2) inside the outer housing **220**. In other embodiments, the openings **232** may be positioned elsewhere to correspond with a motor that may be at a different location inside the outer housing **220**. The openings may be place on the top, bottom and/or side surfaces of the outer housing **220**. One will appreciate that the openings **232** may be strategically place anywhere in the outer housing **220** to facilitate convective cooling of the various components inside the outer housing **220**.

(101) FIG. 3B illustrates a partial cross-sectional view of the smoke evacuation system **200** of FIG. 3A on plane **228**. The arrows in FIG. 3B indicate airflow. Air may flow inside the airflow path **208** of the smoke evacuation system **200** through a tube **234** and the various components that form or define the airflow path **208**, such as the filter **206**, pump **210**, and exhaust mechanism **214**. Air from outside the outer housing **220** may flow into the enclosure **226** of the smoke evacuation system **200** through the openings **232**, as indicated by the arrows through the openings **232**. In the illustrated embodiment, the air flowing through airflow path **208** may be sealed off from the air

entering through the openings **232** so that no mixing occurs. The air entering through the openings **232** may cool the motor **215**, pump **210**, exhaust mechanism **214**, tube **234** or other components the air comes into contact with by convective heat transfer. These components may also be cooled when hot air within the enclosure escapes out of the openings **232**.

(102) Alternatively, in another embodiment illustrated in FIG. **4**, the air flowing through the airflow path **208** may not be sealed off from air entering the smoke evacuation system **200** through the openings **232** in the outer housing **220**. In this embodiment, the air entering through the openings **232** may enter into the airflow path **208** to mix with the air flowing through the airflow path **208**. This mixing may cause the air flowing inside the airflow path **208** to be cooled by the air flowing into the airflow path **208** through the openings **232** in the outer housing **220**.

(103) One or more airflow path openings **236** may be provided in the airflow path **208** so that air from outside the airflow path **208** may enter into the airflow path **208**. In one embodiment, the opening may be an open juncture **236** between a first portion of the airflow path **242** and a second portion of the airflow path **430**. The first portion **242** may extend into a second portion **244**. The first portion **242** may have a first diameter **238** and the second portion **244** may have a second diameter **240**. The first diameter **236** may be smaller than the second diameter **240**. The first portion **242** may extend at least partially into the second portion **244** so that the second portion **244** at least partially receives the first portion **242**. In this configuration, substantially all of the air flowing through the airflow path **208** may remain inside the airflow path **208** as it flows from the first portion **242** to the second portion **244**.

(104) As the air within the airflow path **208** flows from the first portion **242** to the second portion **244**, a suction may be created that draws air from outside the airflow path **208** into the airflow path **208**. In this way, air from outside the outer housing **220** may enter into the outer housing **220** through the openings **232** in the outer housing **220** and enter the airflow path **208** through the one or more open junctures **236** to mix with air flowing inside the airflow path **208**. This mixing may cause the airflow path **208** or other components, such as the pump **210** and/or motor **212**, to be cooled.

(105) For example, after the air is mixed and cooled within the airflow path **208** according to the embodiment illustrated in FIG. **4**, the cooled air may then pass through the pump **210**. Also for example, air that enters the smoke evacuation system **200**, but does not mix with the air inside the airflow path **208**, may freely flow within the outer housing **220** so that it flows over/around the motor **212**, causing the motor **212** to be cooled.

(106) The embodiment illustrated in FIG. **4** illustrates an airflow path **208** that includes one open juncture **236** in the airflow path **208** through which air may enter. Other embodiments may include more than one airflow path openings **210**. For example, one embodiment may include two or more open junctures **236** disposed in series along the airflow path **208**. Increasing the number of open junctures **236** may increase the mixing of air from outside the airflow path **208** with air inside the airflow path **208** to increase cooling capacity.

(107) FIG. **5A** illustrates an embodiment of an airflow path **208** that has a cooling mechanism **230**. The airflow path **208** may be comprised of a tube **234** or other conduit through which air may flow. The air is indicated by the arrows in the airflow path **208**. The airflow path may also include one or more interior walls **246** configured to straighten or direct the airflow. Air exiting the filter **206**, indicated by arrows **248**, may be flowing turbulently. The one or more walls **246** may create channels that direct air **250** in the downstream direction, as indicated by arrows **250**, resulting in more laminar flow.

(108) FIG. **5B** illustrates a cross sectional view of the airflow path **208** where the one or more walls **246** are located in FIG. **5A**. The one or more walls **246** may create one or more channels **252** through which the air **250** may flow. The channels may be bounded by the one or more walls **252** and the tube **234** or other conduit of the airflow path **208**. Other embodiments may include one or more walls **246** that create more or less than the four channels **252** illustrated in FIG. **5B**. Other

embodiments may also include one or more walls **246** that create channels **252** having various shaped cross-sections, such as circular, square, or other shaped cross-sections.

(109) Referring back to FIG. 5A, the cooling mechanism **230** may include a first rotary element **254** coupled to a second rotary element **256** via a rotary element coupler **258**. The first rotary element **254** may comprise a plurality of first rotary element blades **260** and the second rotary element **256** may comprise a plurality of second rotary element blades **262**. The second rotary element **256** may be disposed outside and surrounding the tube **234** of the airflow path **208** and inside the enclosure **226** of the smoke evacuation system **200**. The first rotary element **254** may be disposed within the tube **234** of the airflow path **208**.

(110) As noted, the first and second rotary elements **254**, **256** may be coupled by a rotary element coupler **258** so that rotation of the first rotary element **254** causes the rotation of the second rotary element **256**. For example, air **250** flowing through the airflow path **208** may push against the first rotary element blades **260** causing the first rotary element **254** to rotate. The rotation of the first rotary element **254**, which is coupled to the second rotary element **256**, may cause the second rotary element **256** to rotate as well.

(111) The rotary element coupler **258** may be disposed in-line with the airflow path **208** so that air does not escape the airflow path **208** at the rotary element coupler **258**. The rotary element coupler **258** may rotate with the first rotary element **254** and therefore may comprise a plurality of ball bearings **264** to reduce frictional resistance to rotation while maintaining a tight fit within the airflow path **208** to avoid leaking. In this way, the rotary element coupler **258** may also be integrated into the tube **234** of the airflow path **208** to maintain a sealed path for air to flow within the airflow path **208**. FIG. 5C illustrates a front cross-sectional view of the first rotary element **254**, second rotary element **256**, and rotary element coupler **258** with ball bearings **264** for further reference.

(112) The second rotary element blades **262** may move air in the enclosure **226** to flow to and/or around other components inside the enclosure **226**. For example, a motor **212** may be disposed within the enclosure **226**. The motor may drive the pump **210** to create a flow of air **248**, **250** through the airflow path **208**. The air **248** may flow through the first rotary element **254**, causing the first and second rotary elements **254**, **256** to rotate as discussed above. The second rotary element **256** may move air that has been drawn into the enclosure **226** from outside the enclosure **226**, as described above, and circulate the air throughout the enclosure **226**. The circulating air may cool the motor **212** by convective heat transfer.

(113) Therefore, the cooling capacity of the circulated air pushed by the second rotary element **256** may be proportional to the work of the motor **212**. For example, the more work output by the motor **212**, the greater the rate of the airflow through the airflow path **208** may be. A greater rate of airflow may result in a greater velocity of circulated air pushed throughout the enclosure **226** by the second rotary element **256**. Therefore, the more work produced by the motor **212**, the greater the cooling capacity of the cooling mechanism **230** may be. The cooling mechanism **230** may also be configured to cool other components within the enclosure **226**, such as the pump **210**.

(114) FIG. 6 illustrates an embodiment of an exhaust mechanism **214** disposed within the outer housing **220** near or at the outlet port **224**. The exhaust mechanism **214** may include a pressure relief mechanism **266** disposed at the outlet port **224** of the smoke evacuation system **200**. The exhaust port **266** may be connected with the tube **230** or other conduit through which air flows in the airflow path **208**. The air flowing through the airflow path **208** may be pressurized by the pump **210** illustrated in FIG. 2. The pressure relief mechanism **266** may limit the suction of the smoke evacuation system **200** when abnormal flow or high pressure is detected within the airflow path **208**.

(115) The pressure release mechanism **266** may comprise an outlet port cover **268** disposed over the outlet port **224**. The cover **268** may be secured over the outlet port **224** via one or more biasing members **270**. In the illustrated embodiment, the one or more biasing members **272** are coil

springs. Other types of biasing members **270** may be used in other embodiments or in combination with the springs illustrated in FIG. **6**. The biasing springs **268** may hold the cover **268** away from the outlet port **224** so that filtered air **272** may exit out of the outlet port **224**. As pressure within the airflow path **208** increases, the one or more biasing members **270** may extend so that the cover is further away from the outlet port **224** to increase airflow out of the outlet port **224**. Increasing airflow out of the outlet port may decrease a pressure within the airflow path **208**.

(116) In this way, the pressure release mechanism **266** may limit the pressure within the airflow path **208** by increasing airflow out of the outlet port **224**. A pressure limit, which depends on the biasing force of the biasing members **270**, may therefore not be exceeded within the airflow path **208**. A similar pressure release mechanism may also be disposed at the inlet port **222** of the smoke evacuation system **200** to regulate a pressure within the airflow path **208**. It will also be appreciated that a similar pressure release mechanism may be disposed anywhere along the airflow path **208** to accomplish the same objective of relieving pressure in the system. For example, a pressure release mechanism may be disposed at an inlet or outlet of the pump **210**.

(117) It will be appreciated that other embodiments of a pressure relief mechanism may be employed to ensure that a pressure limit is not exceeded within the smoke evacuation system **200**. For example, any mechanism that increases airflow out of the outlet port **224** or pump outlet, proportional to an increased pressure in the airflow path **208**, may be suitable. Likewise, any mechanism that decreases airflow into the system at the inlet port **222** or pump inlet, proportional to an increase in pressure detected within the airflow path **208**, may also be suitable.

(118) For example, one embodiment of a pressure relief mechanism may include a controller and a pressure sensor. The pressure sensor may signal the controller to activate a mechanism that increases or decreases flow in or out of the smoke evacuation system similar to the pressure relief mechanisms described above. A pressure limit may be pre-determined and set so that when the sensor senses a pressure within the smoke evacuation system that is equal to or greater than the pressure limit, the pressure relief mechanism is activated by the controller.

(119) FIGS. **7A** and **7B** illustrate an embodiment of an exhaust mechanism **214**. The exhaust mechanism **214** may be configured to control or reduce the velocity of filtered air from the airflow path **208** exiting the smoke evacuation system **200** at the outlet port **224**. The exhaust mechanism **214** may also be configured to decrease noise associated with high velocity filtered air exiting the outlet port **224**. The exhaust mechanism **214** may help to reduce exit noise of the filtered air without baffling or redirecting flow causing an exit head pressure.

(120) FIG. **7A** illustrates a perspective view of an exhaust mechanism **214**. The exhaust mechanism may be a diffuser **225**. The diffuser **225** may include a plurality of vanes **274**. The vanes **274** may be spaced apart and angled such that filtered air may flow out through the diffuser **225** between the vanes **274**. The vanes **274** may be angled such that the vanes **274** force the air in a variety of directions upon exiting. FIG. **7B** further illustrates how the diffuser **225** may decrease the velocity and noise of the filtered air exiting the system **200**.

(121) FIG. **7B** illustrates a schematic of the diffuser illustrated in FIG. **7A**. High velocity filtered air **276** may enter the diffuser in a substantially laminar flow pattern. The cross-sectional area of the diffuser **225** increases to expand the filtered air. The filtered air **278** exiting at the expanded cross-sectional area of the diffuser **225** decreases the velocity of the filtered air **278**. The filtered air **280** then exits the diffuser through the plurality of vanes **274** shown in FIG. **7A** so that the air is pushed in a variety of directions. Thus, the flow of the exiting filtered air **280** is no longer laminar. In this way, the diffuser **225** may reduce the velocity of the filtered air exiting the smoke evacuation system **200** at the outlet port **224**, which in turn may reduce the noise of the exiting filtered air **280**.

(122) Filter Connection

(123) FIG. **8A** illustrates a perspective view of a smoke evacuation system **300**. The smoke evacuation system **300** may include a socket **326** configured to receive a filter **306**. The filter **306** is

not shown in FIG. 3 in order to illustrate the socket 326. The socket 326 may have a first recess 328 and a second recess 332. A transition surface 330 extends between the first recess 328 and the second recess 332. The socket 326 may be shaped to receive a filter 306 into the socket so that the filter 306 fits snugly into the socket 326.

(124) FIG. 8B illustrates a cross-sectional view of the smoke evacuation system 300 of FIG. 8A. FIG. 8B illustrates a cross-sectional view of plane 334 illustrated in FIG. 8A that passes through the socket 326. As shown in FIG. 8B, the socket comprises a first end 336 that is open to receive a filter 306 and a second end 338 in communication with the airflow path 308. A filter 306 may be inserted and removed from the first end 336 of the socket 326.

(125) The socket 326 may also include a transition surface 330 configured to receive a second end of a filter canister assembly, a second recess 332 configured to receive a connection nipple, and an electronic connector 340. More details regarding filter canister assembly, including the body, second end, connection nipple, and electronic connector will be given hereafter.

(126) FIGS. 9A through 4C illustrate various views of an embodiment of a filter canister assembly 342. FIG. 9A illustrates a perspective view of the filter canister assembly 342. The filter canister assembly 342 may include a first end 344 and a second end 346. The second end 346 of the filter canister 342 may be at least partially conical. A canister body 348 may be disposed between the first end 344 and the second end 346 of the canister assembly 342. The filter canister assembly 342 may be configured to be inserted into the socket 326 of the smoke evacuation system 300.

(127) A plate 350 may be disposed on the first end 344 of the canister assembly 342 so that the canister assembly 342 may not be inserted too far into the socket 326. When the canister assembly 342 has been fully inserted into the socket 326, the plate 350 makes contact with the outer housing 320 and/or the second end 346 of the canister assembly 342 abuts the transition surface 330 of the socket 326 so that the canister assembly 342 may not be inserted further. The second end 346 and the body 348 of the canister assembly 342 may be able to fit into the socket 326, but the plate 350 may not. The canister assembly 342 may be inserted until the plate 350 comes into contact with the outer housing 320 of the smoke evacuation system 300. The plate 350 may include an inlet port 322 such as the inlet port 322 discussed above with reference to FIG. 2. The vacuum hose 112 illustrated in FIG. 1 may connect to the inlet port 322 so that smoke may travel through the vacuum hose 112 and into the filter canister assembly 342 at the inlet port 322.

(128) Smoke may enter at the inlet port 322 and move through an inner pathway of the filter 306 disposed within the body 348 of the filter canister assembly 342. Potentially harmful and/or unpleasant toxins and particulates may become trapped in the filter 306 as the smoke moves through the filter 306. The filtered gas remaining after filtration may exit the filter canister assembly 342 through the canister outlet 352 illustrated in FIG. 9B. The filter canister assembly 342 may be inserted into the socket 326 of the smoke evacuation system 300 so that the canister outlet 352 communicates with the airflow path 308.

(129) FIG. 9B illustrates a perspective view of the second end 346 of the filter canister assembly 342. The second end 346 may include a connection nipple 354 surrounding the canister outlet 352 and a first electronic connector 356. In one embodiment, the first electronic connector may be an erasable programmable read-only memory (EPROM) connector. The first electronic programmable connector 356 may be a male connector. Other embodiments may include a first electronic programmable connector that is a female connector. The second end 346 of the canister assembly 342 may also include a seal 358 disposed around the connection nipple 354. More details regarding the connection nipple 354, seal 358, and electronic programmable connector 356 will be given hereafter in reference to FIG. 11A and FIG. 11B.

(130) FIG. 10A illustrates the cross-sectional shape of the second end of a filter canister 360 and the cross-sectional shape of the first recess of a socket 361. The cross-sectional shape of the second end of the filter canister 360 may be similar to the cross-sectional shape of the first recess of the socket 361 and only slightly smaller so that the filter canister assembly 360 may fit snugly into the

socket **361** when inserted. The cross-sectional shape of the second end of the canister assembly **360** may be slightly smaller than the cross-sectional shape of the first recess of the socket **361** so that the filter canister **360** may be inserted therein.

(131) FIG. **10A** illustrates teardrop shaped cross-sections **360**, **361**. A teardrop cross sectional shape **360**, **361** may ensure that the filter canister **360** may only be inserted in a particular orientation so that the filter canister **360** fits into the socket **361**. Other embodiments may include cross-sectional shapes that are different from the teardrop shape illustrated in FIG. **10A**. Other embodiments may include any other cross-sectional shapes so long as the cross-sectional shape limits the canister assembly **360** to being inserted into the socket **361** in only one orientation.

(132) For example, in one embodiment, the cross-sectional shape **360**, **361** may be a triangle having only one line of symmetry. Other embodiments may include other cross-sectional shapes that only have one line of symmetry. Limiting the canister assembly **342** to a single orientation may assure that the filter canister **360** is inserted correctly into the socket **361**.

(133) FIG. **10B** illustrates another cross-sectional shape of a filter canister **362**. The shape **362** shown in FIG. **10B** is similar to the shape **360**, **361** shown in FIG. **10A**, except the cross-sectional shape **362** includes a key notch **364**. The socket cross-sectional shape has a corresponding key groove **365**. FIG. **10C** illustrates a canister assembly **342** that includes a second end **346** having a cross-sectional shape **362** as shown in FIG. **10B**. FIG. **10D** illustrates a smoke evacuation system **300** that includes a socket **326** having a first recess **328** with a cross-sectional shape **362** as shown in FIG. **10B**. The key notch **366** of the second end **346** of the canister assembly **342** must align with a key groove **368** of the first recess **328** of the socket **326** in order to be inserted. The key notch **366** and groove **368** may further assure that the canister assembly **342** is properly inserted into the socket **326**. Other embodiments of shapes **360** and **362** are contemplated herein. For example, a circular or square shape with a key notch **364** may also be used.

(134) Other embodiments may include more than one key notch **366** and groove **368** at various locations around the cross sectional shape **362** so that multiple key notches **366** and grooves **368** on the canister assembly **342** and socket **326** must be aligned before the canister assembly **342** is inserted into the socket **326**. Some embodiments of a canister assembly **342** may also include a body **348** that also has a cross-sectional shape shown in FIGS. **10A** and **10B** and described herein so that the shape of the body **348** corresponds to the socket **326** when it is inserted.

(135) In some embodiments, the key notch **366** may extend along the whole length of the body **348** of the canister assembly **342** and the key groove **368** may not extend along the whole length of the first recess **328** of the socket **326**. In other embodiments, the key notch **366** may extend along the whole length of the body **348** of the canister assembly **342** and the key groove **368** may extend along the whole length of the first recess **328** of the socket **326**. In any of the embodiments described herein, the key notch **366** and groove **368** may be configured such that the canister assembly **342** may not be rotated/twisted within the socket **326** once the canister assembly **342** has been inserted into the socket **326**.

(136) One of the reasons it is important to ensure that the canister assembly **342** is inserted in the correct orientation is so that the first and second electronic connectors **356**, **340** come into contact with each other. In one embodiment, the second electronic connector **340** may be an EPROM connector. The second electronic connector **340** may be disposed within the socket **326** as illustrated in FIG. **8B**. The first electronic memory **356** may be disposed at the second end **346** of the canister assembly **342** as shown in FIG. **9B**. The first and second electronic connectors **356**, **340** may be thus disposed so that when the canister assembly **346** and the first recess **328** of the socket **326** are aligned properly, the first and second electronic connectors **356**, **340** meet when the canister assembly **342** is fully inserted into the socket **326**.

(137) In the illustrated embodiment of FIG. **9B**, the first electronic connector **356** is disposed at an upper edge of the second end **346** of the canister assembly **342**. This location corresponds to the location of the second electronic connector **340** disposed within the socket **326** as shown in FIG.

11A. Other embodiments may include first and second electronic connectors **356, 340** that are positioned at various locations on the second end **346** of the canister assembly **342** and in the socket **326**. Any location is suitable so long as the first and second electronic connectors **356, 340** make contact when the canister assembly **342** is inserted into the socket **326**.

(138) Once the first and second electronic connectors **356, 340** contact each other, the electronic memory may relay information to a user or other components of the smoke evacuation system **342** regarding the filter. Such information may include, but is not limited to, the number of times the filter has been used, whether it is the correct filter, whether the filter is still functioning properly, how much life/filtration capacity is left in the filter, and so forth. This connection enables safe, reliable, and efficient use of filters that need to be periodically replaced. The electronic memory may also be used to signal that a filter has been inserted properly and activate the smoke evacuation system **300**.

(139) FIGS. **11A** and **11B** illustrate an embodiment of canister assembly **342** inserted into socket **326**. FIG. **11A** illustrates canister assembly **342** partially inserted into the socket **326** and FIG. **11B** illustrates a canister assembly **342** fully inserted into the socket **326**. Referring to FIG. **11A**, the canister assembly **342** is partially inserted into the socket **326** so that the connection nipple **354** is received by the second recess **332** of the socket **326**. The seal **358** surrounding the connection nipple **354** makes contact with the inner surface of the second recess **332**, creating a sealed path for a filtered gas exiting the canister assembly **342** at the canister outlet **352** to enter the airflow path **308** of the smoke evacuation system **300**. In one embodiment, the seal **358** may be an O-ring. Other embodiments may include other seals **358**.

(140) The seal **358** makes contact with the inner walls of the second recess **332** to create a seal between the connection nipple **354** and the second recess **332** before the canister assembly **342** has been fully inserted into the socket **326**. In this partially inserted configuration, the plate **350** does not contact the outer housing **320** of the smoke evacuation system **300** and the first and second electronic connectors **356, 340** do not make contact with one another.

(141) FIG. **11B** illustrates a canister assembly **342** fully inserted into the socket **326**. When the canister assembly **342** is fully inserted into the socket **326**, the seal **358** maintains a seal around the connection nipple **354** within the second recess **332**. Additionally, when the canister assembly **342** has been fully inserted into the socket **326**, the plate **350** makes contact with the outer housing **320** and/or the second end **346** of the canister assembly **342** abuts the transition surface **330** of the socket **326** so that the canister assembly **342** may not be inserted further. Furthermore, when the canister assembly **342** is fully inserted, the first and second electronic connectors **356, 340** contact one another. The electronic connection may then function as described above.

(142) As discussed above, the electronic connection may activate or allow for activation of the smoke evacuation system **300** so that a suction begins drawing smoke into the filter **306** through the vacuum tube **112**. In the embodiments illustrated herein, the seal creates an airtight boundary between the connection nipple **354** and the second recess **332** of the socket **326** before the first and second electronic connectors **356, 340** meet. In other words, the longitudinal distance **D1** between the seal **358** and the first electronic connector **356** may be greater than the longitudinal distance **D2** between the second recess **332** of the socket **326** and the second electronic connector **340**.

Longitudinal distances **D1** and **D2** are labeled in FIG. **11A**.

(143) Alternatively, the first electronic connector **356** may be disposed at the first end **344** of the filter canister **342** and the second electronic connector **340** may be disposed at or near the plate **350**. In this configuration, the longitudinal distance between the seal **458** and the first electronic connector **356** may still be greater than the longitudinal distance between the second recess **332** of the socket **326** and the second electronic connector **340** so that a seal is created for smoke to pass through into the airflow path **308** before the first and second electronic connectors **356, 340** meet. It will be appreciated that both the first and second electronic connectors **356, 340** may be disposed at various locations on the filter canister **342** and in the socket **326** so long as the relationship

between the longitudinal distances mentioned above remain the same.

(144) These configurations ensure that the smoke evacuation system **300** will not be activated until the seal has been created so that filtered gas may not exit the canister outlet **352** until a closed path in communication with the airflow path **308** has been established. These configurations may prevent leakage of filtered gas exiting the canister assembly **342** at the canister outlet **352**. These configurations may also ensure that the smoke evacuation system **300** does not begin drawing smoke through the filter **306** until the filter canister assembly **342** is inserted fully and properly into the socket **326**.

(145) FIG. **12** illustrates a method for connecting a filter canister to a smoke evacuation system **370**. In a first step **372**, a filter canister is provided. The filter canister may include a body disposed between first and second ends, a connection nipple disposed at the second end, a seal disposed around the connection nipple, a key notch, a cross-sectional shape, and a first electronic connector.

(146) A second step **374** may include aligning the cross-sectional shape of the filter canister with a cross-sectional shape of the socket. The socket may comprise a first recess configured to receive the body of the filter canister, a second recess configured to receive the connection nipple, a transition surface connecting the first and second recesses, and a second electronic connector.

(147) A third step **376** may include inserting the filter canister partially into the socket until the seal creates an airtight boundary between the connection nipple of the filter canister and the second recess of the socket. A fourth step **378** may include inserting the filter canister further into the socket until the second end of the filter canister makes contact with the transition surface of the socket and until the first and second electronic connectors come into contact with one another.

(148) The method of inserting the filter canister described herein creates an airtight boundary between the connection nipple of the canister and the second recess of the socket before the electronic connection is made. In this way, the electronic memory, which may be configured to activate the smoke evacuation system, will not be connected until a sealed path that leads from the connection nipple to the airflow path of the smoke evacuation system has been established. This method may thus prevent filtered gas from leaking out of the filter canister before it is fully installed into the socket of the smoke evacuation system.

(149) Noise and Vibration Management

(150) FIG. **13** illustrates a schematic of an embodiment of a smoke evacuation system **400**. The smoke evacuation system **400** may include a filter **406** and an airflow path **408**. The airflow path **408** may comprise a pump **410** disposed in-line with the airflow path **408** producing a pressure difference within the airflow path **408** by mechanical action. This pressure difference may cause movement of a gas through the airflow path **408**.

(151) The airflow path **408** may be at least partially comprised of a tube or other conduit that substantially contains and/or isolates the air moving through the airflow path **408** from air outside the airflow path. For example, the first zone **416** of the airflow path **408** may comprise a tube through which the airflow path **408** extends between the filter **406** and the pump **410**. The second zone **418** of the airflow path **408** may also comprise a tube through which the airflow path **408** extends between the pump **410** and the exhaust mechanism **414**. The airflow path **408** also extends through the filter **406**, pump **410**, and exhaust mechanism **414** so that a continuous airflow path **408** extends through the smoke evacuation system **400**.

(152) The gas drawn through the airflow path **408** may be smoke **402**, or the filtered air remaining after the smoke **402** has passed through the filter **406**. A motor **412** drives the pump **410**. The smoke evacuation system **400** may also include an exhaust mechanism **414** that may also be disposed in-line with the airflow path **408**. The airflow path **408** may extend from the inlet port **245** to the outlet port **250** and pass through the filter **406**, pump **410** and exhaust mechanism **414**.

(153) Pumps

(154) The pump **410** may cause a suction of smoke **402** that has travelled through the vacuum tube **112** illustrated in FIG. **1** to the filter illustrated in FIG. **13**. The smoke **402** may be drawn to the

filter **406** via a suction created by the pump **410** as discussed above. The pump **410** may create a pressure difference between a first zone **416** and a second zone **418** of the airflow path **408**. This pressure difference causes the smoke **402** to travel into the filter **406**, which is disposed at an inlet of the airflow path **408**, through the airflow path **408**, and out the exhaust mechanism **414**, which is disposed at an outlet of the airflow path **408**. The filter **406** may extract potentially harmful, foul, or otherwise unwanted particulates from the smoke **402**.

(155) The pump **410** may be disposed in-line with the airflow path **408**, meaning the gas flowing through the system enters the pump **410** at one end and exits the pump **410** at the other end. The pump **410** may provide a sealed positive displacement airflow path. The pump **410** may produce the sealed positive displacement airflow path by trapping (sealing) a first volume of gas and decreasing that volume to a second smaller volume as the gas moves through the pump **410**. Decreasing the volume of the trapped gas increases the pressure of the gas. The second pressurized volume of gas may then be released from the pump at a pump outlet. The pump releases the pressurized outlet gas into the airflow path **408** and on towards the exhaust mechanism **414**. More details regarding various embodiments of pumps that may provide a sealed positive displacement airflow path are described herein.

(156) The pump **410** may have more than one operating pressure. The pump **410** may operate at various operating pressures while maintaining a similar flow rate through the airflow path **408**. For example, the pump **410** may operate at a first operating pressure resulting in a first flow rate of gas through the airflow path **408**. The pump **410** may also operate at a second operating pressure resulting in a second flow rate. The first and second flow rates of gas through the airflow path **408** may be the same or substantially similar regardless of the difference in the first and second operating pressures of the pump **410**. For example, if blockage or clogging occurs in the airflow path **408**, causing a higher pressure within the path **408**, the pump **410** may operate at that higher pressure while still maintaining a constant flow rate of air/gas through the airflow path **408**.

(157) The terms “pump” and “sealed positive displacement pump” as used herein may refer to mechanisms that may transfer or cause movement of a gas by mechanical action and substantially increase the pressure of that gas as the gas is moved. For instance, as used herein, a pump may refer to any number of different blowers or compressors. Fans, on the other hand, are not considered “pumps” for purposes of this disclosure. Fans may only operate at a pressure ratio of about 1:1. This pressure ratio does not provide a substantial increase in pressure of the gas being moved.

(158) Fans and pumps differ in many respects. A fan may include rotating blades that create a current or flow of gas from one side of the fan to the other. Fans typically operate at a pressure ratio of about 1:1 and move a relatively high volume of air. Typical fans used in smoke evacuation systems may have an operational pressure between atmospheric pressure to about 1.5 psig. The volumetric airflow capacity of a fan decreases dramatically when blockages increase a pressure resistance inside the airflow path **408**, as shown in FIG. **14**. A sealed positive displacement pump, as described above, is affected less by such blockages and performs well against high resistance pressures, as seen in FIG. **14**.

(159) Fans may create suction that draws air through the smoke evacuation system, but they are typically very noisy. The noise can be distracting to practitioners performing surgery. Fans used in typical systems can create sufficient suction but struggle to maintain consistent suction when resistance pressures increase in the system due to airflow obstructions or clogging. Fans are prone to create weak and inconsistent airflow rates through the system.

(160) Blowers differ from fans in that they operate at a higher pressure ratio (e.g., between about 1:1 to 1:2). Essentially, a blower is a high-speed and/or high-volume fan. For example, a blower may be a centrifugal fan that uses rotating impellers to increase the speed and volume of a gas passing through it. Blowers typically have an operational pressure between 1.5 and 1.72 psig and transfer a very high volume of gas relative to fans and compressors.

(161) Compressors are pumps that move relatively low volumes of gas with much higher pressure

ratios than fans and blowers. A typical pressure ratio for a compressor, such as those described in various embodiments herein, may be greater than about 2:1. Compressors may operate at a pressure of greater than about 2.72 psig. The various compressors described herein, particularly embodiments that include positive displacement compressors, may be advantageous for a number of reasons. Positive displacement pumps may be much quieter than typical fans used in smoke evacuation systems. Positive displacement pumps also operate well against resistance pressures due to blockages in the airflow path **408** of the smoke evacuation system **400**.

(162) Blockages may include unwanted particulate build-up or other clogging due to objects from the ambient air being sucked into the airflow path **408**. FIG. **14** illustrates the relationship between pressure resistance and airflow for a positive displacement pump vs. a typical fan. As shown, a sealed positive displacement pump may maintain a relatively steady airflow regardless of the pressure resistance in the system due to clogging. In contrast, the airflow capability of a fan decreases dramatically as the pressure resistance rises. In practice, this indicates that sealed positive displacement pumps, such as the various embodiments described herein, may still create a suction through the smoke evacuation system **400** even when the system clogs or becomes blocked. This is typically not the case if a fan is used.

(163) FIG. **15** is a table showing the pressure increase, operational pressure, pressure ratio, and air volume transferred by a fan, blower, and compressor for comparison. As shown, compressors are able to produce a pressure ratio of greater than 2:1 between a low-pressure gas entering the pump **410** from a first zone **416** of the airflow path **408** and a pressurized gas exiting the pump **410** into a second zone **418** of the airflow path **408**.

(164) FIG. **15** also shows the relative air volume moved by the fans, blowers, and compressors. Compressors move the lowest volume of air relative to fans and blowers, and fans move the highest volume of air when air flow path conditions are equivalent. FIG. **15** also shows that compressors operate at a pressure ratio of greater than 2:1, as opposed to fans and blowers that operate at pressure ratios closer to 1:1. This means that air/gas exiting a compressor is typically pressurized at twice the pressure of the air/gas entering the compressor at a compressor inlet.

(165) The various embodiments of the smoke evacuation system, as described herein, may include one or more various types of pumps. The various pumps may be incorporated into the system in order to reduce noise and vibrations, which can be irritating to users and damaging to the system. For example, typical fans used in current systems may be very noisy and cause significant vibrations. These vibrations can cause the system to travel along a surface where it is placed, thus requiring a secure connection to that surface. This secure connection diminishes the portability of the system and increases the difficulty of installation. Vibrations can also be damaging to internal components of the system, which may not be designed to withstand such vibrations.

(166) The following description includes various embodiments of a smoke evacuation system, including various types of pumps, vibration absorption mechanisms, and motor control methods aimed at reducing the noise and vibration of the system in order to solve these problems.

(167) In one embodiment of a smoke evacuation system **400**, the pump **410** shown in FIG. **13** may be a blower **420**, as illustrated in FIGS. **16A-16B**. FIG. **16A** illustrates an exploded view of blower **420**. The blower **420** may be a hybrid regenerative blower with impeller features that compress the gas **402** passing there through. The blower **420** may include a top cover **422**, a bottom cover **424**, and an impeller assembly **426**. A rotary shaft **428** may be secured to the center of the impeller assembly **426** and cause the impeller assembly **426** to rotate. A motor **412** that may engage the rotary shaft **428** is not illustrated in FIG. **16A**, but is shown in FIG. **13**.

(168) The top cover **422** may be secured to the bottom cover **424** to create a sealed circulation path **430** having an inlet **432** and an outlet **434**. The circulation path **430** may also be referred to as an airflow path **430** of the blower. The impeller assembly **426** may be disposed between the top cover **422** and bottom cover **424** so that the impeller blades **436** reside within the sealed circulation path **430**. A motor drives the impeller assembly **426** to rotate about the rotary shaft **428** so that the

impeller blades **436** travel in a circular path through the sealed circulation path **430**. This circular motion of the impeller blades **436** creates a suction so that a gas **402** is drawn into the inlet **432**, travels around the sealed circulation path **430**, and exits the blower **420** out of the outlet **434**.

(169) FIG. **16B** illustrates the flow path **438** of a gas **402** flowing through the sealed circulation path **430** of the blower **420**. FIG. **16B** illustrates a cross-sectional view of the blower **420** showing impeller assembly **426** inside sealed circulation path **430**. The impeller assembly **426** is driven clockwise in this embodiment. As the impeller blades **436** rotate through the sealed circulation path **430**, centrifugal force moves gas molecules from the blade root **440** to its tip **442**. The gas molecules then leave the blade tip **442** and enter the portion of the sealed circulation path **430** not occupied by the impeller blades **436**. The gas molecules are then drawn back down a succeeding impeller blade **436** in repeated fashion.

(170) This repeated flow path **438** of the gas provides a quasi-staging effect that may increase a pressure differential capability of the blower **420**. This type of regenerative blower **420** passes the gas through many compression cycles as the gas molecules pass up and down various impeller blades **436** with each revolution of the impeller assembly **426**. Thus, a gas exiting the outlet **434** may have a higher pressure than the gas entering at the inlet **432**. The speed of the rotating impeller assembly **426** is proportional to the pressure differential of the gas. For example, a higher rotational speed of the impeller assembly **426** increases the pressure differential between the gas at the inlet **432** compared to the gas exiting at the outlet **434**. A lower rotational speed results in a lower pressure differential.

(171) The number of impeller blades **436** may be odd so as to limit resonance, which can create noise and vibrations. An odd number of blades **436** reduces the chance of elastic frequencies from the blades **436** becoming tuned to a resonant frequency of the rotary shaft **428**. Natural frequencies of the top and bottom covers **422**, **424** are also offset from the frequencies of the blades **436** and rotary shaft **428** to limit noise and vibrations of the blower **420** due to the harmonics of the blower **420**.

(172) In one embodiment of a smoke evacuation system **400**, the pump **410** shown in FIG. **13** may be a claw pump **444**. Various cross-sectional views of the claw pump **444** are illustrated in FIGS. **17A-17C**. The claw pump **444** may be a cooperative dual drive shaft claw pump. FIGS. **17A-17C** illustrate a top cross-sectional view of the claw pump **444** in three different stages of rotation. The claw pump **444** is a positive displacement pump that compresses gas by decreasing the volume of an initial volume of gas that enters the pump.

(173) The claw pump **444** may have first and second counter-rotating rotary elements, or claws **446**, **448** disposed within a single circulation path of the pump **444**. For example, the first claw **446** may rotate clockwise and the second claw **448** may rotate counter-clockwise, as indicated by the arrows in FIG. **17B**. FIG. **17A** shows an initial state of the claw pump **444** where a gas **450** resides in a sealed space between the claws **446**, **448** and the pump housing **452**. The gas **450** is illustrated in gray. As the claws **446**, **448** rotate, the volume of the sealed space in which the gas **450** resides decreases due to the geometry of the claws **446**, **448**. FIG. **17C** illustrates the gas **450** in a compressed state, where the volume of the sealed space in which the gas **450** resides has been reduced due to the rotation of the claws **446**, **448**.

(174) Decreasing the volume of the gas **450** pressurizes the gas. The inlet and outlet ports of the claw pump **444** are not shown in detail because of the top cross-sectional view of FIGS. **17A-17C**. An inlet **456** may, for example, be disposed below the claw pump **444** and an outlet **454** may be disposed above the claw pump **444** so that the compressed volume of gas **450** shown in FIG. **17C** may enter and exit via the inlet **456** and outlet **454** perpendicular to the viewing plane. In other words, the inlet **456** and outlet **454** may be configured so that the inlet **456** is disposed below the viewing plane and the outlet **454** is disposed above the viewing plane, or vice versa, so that the gas travels through the claw pump **444** perpendicular to the viewing plane.

(175) Embodiments of the smoke evacuation system **400** that may include a cooperative dual drive

shaft claw pump **444** such as the one illustrated in FIGS. **17A-C** may enjoy reduced noise and vibrations. Pumps with single shaft rotary elements may suffer from vibrations due to slight imbalances of components that rotate around a central drive shaft. In the cooperative dual drive shaft claw pump **444** illustrated, the two rotating claws **446**, **448** rotate in opposite directions and may balance each other out. This balance may minimize vibrations.

(176) In one embodiment, the pump **410** of the smoke evacuation system **400** may also be a lobe compressor **458**. FIG. **18A** illustrates a cross-sectional view of a lobe compressor **458** including two counter-rotating rotary elements **460**, **462**. Each rotary element **460**, **462** may have two or more lobes **478**. The lobe compressor **700** functions similarly to the claw pump **444** described herein, in that the two rotary elements **460**, **462** rotate in opposite directions, as indicated by the arrows marked on the two rotary shafts **470**, **472**, in order to create a sealed positive displacement airflow path through the compressor **458**.

(177) The rotation of the rotary elements **460**, **462** draws in a low-pressure gas **474** through an inlet **466** and moves the gas **474** through the compressor **458** to an outlet **468**. As the gas **474** moves through the compressor **458**, as indicated by the arrows, the volume of the gas **474** decreases, which pressurizes the gas. The pressurized gas **476** then exits the compressor **458** via the outlet **468**.

(178) Other embodiments of the smoke evacuation system **400** may include lobe compressors **700** having more than two lobes **478** on each rotary element **460**, **462**. For example, FIG. **18B** illustrates a lobe compressor **480** that comprises two rotary elements **460**, **462** having three lobes **478** each. In this embodiment, a low-pressure gas is drawn into the inlet **466**, driven through the compressor **480** via the rotating lobes **478**, after which the volume of the inlet gas is reduced and pressurized before it exits out the outlet **468** of the compressor **480**.

(179) FIG. **18C** illustrates yet another embodiment of a lobe compressor **482** that operates similar to the other lobe compressors described herein. The lobe compressor **482** illustrated in FIG. **18C** includes two rotary elements **460**, **462** that have five lobes each. Other embodiments may include lobe compressors with rotary elements that have four lobes, or more than five lobes.

(180) In the various embodiments of lobe compressors illustrated in FIGS. **18A-7C**, the two rotary elements maintain consistent contact with each other while rotating. For instance, each lobe **478** of one rotary element extends between two lobes of the other rotary element so that contact is maintained as the rotary elements rotate. Thus, air may not escape from between the lobes. Instead, the air is trapped within sealed compartments as the air moves through the lobe compressors.

(181) Other embodiments of a smoke evacuation system **400** may include multiple rotary elements that cooperatively counter-rotate to produce a sealed circulation path that traps and compresses gas by positive displacement action. These other pumps may include, but are not limited to, two stage rotary vane pumps and dual screw eccentric pumps. The various counter rotating dual drive shaft pumps with multiple rotary elements described herein may provide a pressure differential of at least 1.5 psig between a low-pressure inlet gas entering the pump **410** from a first zone **416** of the airflow path **408** and a high-pressure outlet gas exiting the pump **410** into a second zone **418** of the airflow path **408**. Other embodiments may include similar pumps that produce a pressure differential of between 1 and 2 psig. Yet other embodiments may produce a pressure differential of greater than 2 psig.

(182) The various counter rotating dual drive shaft pumps with multiple rotary elements may also reduce vibration and noise within the smoke evacuation system **400** for the same reasons as discussed above in reference to the claw pump **444**. The two rotary elements rotate in opposite directions and balance each other out. This balance may cancel out vibrations and resulting noise.

(183) In one embodiment of the smoke evacuation system **400**, the pump **410** may be a scroll compressor. Scroll compressors are positive displacement compressors. The various embodiments of a scroll compressor described herein may achieve all the advantages of the pumps described above, including but not limited to the same compression ratios, operating pressures, vibration

reduction, and noise reduction of the smoke evacuation system **400**.

(184) FIG. **19** illustrates a cross-sectional view of a scroll compressor **800**. The scroll compressor may include a stator scroll **484** and a moving scroll **486**. The stator scroll **484** is fixed in position while the moving scroll **486** orbits eccentrically without rotating. The moving scroll **486** may orbit eccentrically such that the moving scroll **486** does not rotate about its own central longitudinal axis, but the central longitudinal axis of the moving scroll **486** would orbit about a central longitudinal axis of the stator scroll **484**. The central longitudinal axes of the stator and moving scrolls **484**, **486** extend perpendicular to the viewing plane of the scrolls **484**, **486**. The stator scroll **484** and the moving scroll **486** may be interleaved with each other to form discreet sealed compression chambers **488**.

(185) A gas may enter the scroll compressor **483** at an inlet **490**. As the moving scroll **486** orbits, the inlet gas is first trapped in a compression chamber **488**. The compression chamber **488** moves a discreet volume of gas along the spiral contour of the scrolls **484**, **486** toward the center of the scroll compressor **483**. The compression chamber **488**, or sealed space in which the gas resides, decreases in volume as the gas moves toward the center of the stator scroll **484**. This decrease in volume increases the pressure of the gas inside the compression chamber **488**. The gas inside the sealed compression chamber **488** is trapped while the volume decreases, thus pressurizing the gas. Once the pressurized gas reaches the center of the scroll compressor **483** it is released through an outlet **492**.

(186) Two or more scroll compressors may be disposed in series in order to counterbalance vibrations that may be caused by the orbiting of the moving scroll **486**. FIG. **20** illustrates a perspective view of two scroll compressors **494**, **496** disposed in series. Only the moving scrolls **498**, **500** are shown for illustrative purposes. The first moving scroll **498** may be oriented at 180-degrees from the second moving scroll **500**. The first moving scroll **498** of the first scroll pump **494** may orbit in an opposite direction of the second moving scroll **500** of the second scroll pump **496**. For example, the first moving scroll **498** may orbit counterclockwise and the second moving scroll **500** may orbit clockwise. Other embodiments may include first and second scroll pumps **494**, **496** that are oriented opposite of the scrolls illustrated.

(187) The two scroll pumps **494**, **496** may be disposed in series within a sealed airflow path **408**. In such a configuration, compressed gas exiting the first scroll pump **494** at an outlet of the first scroll pump **494** may enter an inlet of the second scroll pump **496** to be further compressed. A single scroll pump, such as those described above, orbits eccentrically and therefore inherently shifts its weight around while orbiting to produce vibrations. The opposite orbiting movement of the two scrolls **498**, **500** in series, illustrated in FIG. **20**, may counterbalance one another in order to limit vibrations in the system **400**.

(188) Alternatively, another dual scroll pump embodiment may include two scroll pumps **494**, **496** aligned parallel to one another so that parallel flow paths pass through each scroll pump **494**, **496**. Each scroll pump **494**, **496** may have an inlet from a common airflow path **408** and an outlet communicating with a common airflow path **408**. Dual scroll pumps **494**, **496** aligned parallel in this manner may provide twice as much airflow through the system **400** than other embodiments described herein.

(189) In one embodiment of the smoke evacuation system **400**, the pump **410** may comprise two scroll pumps of different sizes. FIG. **21A** illustrates a perspective view of first and second scroll pumps **502**, **504**. For the sake of simplicity in illustration, stator scrolls of the scroll pumps **502**, **504** are not shown. Rather, only the moving scrolls **502**, **504** are shown for illustrative purposes. The first scroll **502** may be a low flow-capacity scroll that orbits at a relatively low revolutions-per-minute ("RPM") compared to the other pumps described herein. The second scroll **504** may be a high flow-capacity scroll that also orbits at a relatively low RPM. The high flow scroll **504** may have a higher flow-capacity than the low flow-capacity scroll **502** even when the two are orbiting at the same RPM due to a larger diameter **506** compared to a diameter of the low flow-capacity scroll

502.

(190) The low-flow scroll **502** and the high flow scroll **504** may be disposed in series, as described previously in reference to the dual in-line scroll pump illustrated in FIG. **20**. The two scrolls **502**, **504** may also be disposed next to each other as illustrated in FIG. **21A**. Arrows **508** and **510** indicate the orbiting direction of the low flow and high flow scrolls **502**, **504**, respectively. FIG. **21A** illustrates both scrolls orbiting in a counter-clockwise direction. Other embodiments may include scrolls that orbit clockwise. Yet other embodiments may include scrolls that orbit in opposite directions to one another.

(191) Pairing a low flow scroll **502** with a high flow scroll **504** as described above has a number of advantages. The configuration illustrated in FIG. **21A** may allow for variable selectable flow rates without increasing the RPM of the scrolls. For example, as illustrated in FIG. **21B**, the low flow scroll **502** may produce a constant low-level airflow **512** over time. The high flow scroll **504** may provide higher flows over time. The high flow scroll **504** may be selectively turned on and off to provide discrete higher flows **514** when needed. Such a need may arise, for example, to overcome a temporarily increased pressure resistance (e.g., due to clogging) within the airflow path **408** of the smoke evacuation system **400**.

(192) Thus, variable flow rates can be accomplished while maintaining a low RPM of the orbiting scrolls. Maintaining low RPMs of the scrolls may decrease vibrations and noise of the pump **410**.

(193) Vibration Absorption Mechanisms

(194) Components of typical smoke evacuation systems, such as pumps and motors, may create unwanted or even damaging vibrations. Vibrations can damage components of the system or shorten their useful lifespan. Vibrations can even cause components of the system to move across the surfaces on which they rest, requiring that they be fixed to the surface. This decreases the portability of the system and increases the difficulty of installation. Vibration absorption mechanisms may be incorporated into the smoke evacuation system **400** to further limit vibrations. These absorption mechanisms can be used in conjunction with the various pumps described herein, or they may be incorporated separately into various other embodiments of the system **400**.

(195) FIG. **22** illustrates in schematic form an embodiment of a smoke evacuation system **516** that includes an inner housing **518** and an outer housing **520**. The inner housing **518** may house the motor **412** and pump **410** of the smoke evacuation system **516**. In some embodiments, the inner housing **518** may house various other components of the smoke evacuation system **516**. For example, the inner housing **518** may house the motor **412**, pump **410**, and exhaust mechanism **414**. Also, for example, the inner housing **518** may only house the pump **410** or the motor **412**. In the illustrated embodiment of FIG. **22**, the inner housing **518** also includes portions of the first zone **416** and second zone **418** of the airflow path **408** (See FIG. **13**).

(196) The first zone **416** of the airflow path **408** may be an inlet to the pump **410** that may pass through the inner housing **518**. Likewise, the second zone **418** of the airflow path **408** may be an outlet from the pump that may pass through the inner housing **518** as well. Other embodiments of a smoke evacuation system may include an inner housing **518** that houses all or none of the first and second zones **416**, **418** of the airflow path **408**.

(197) FIG. **22** illustrates a cross-sectional view of smoke evacuation system **516** in order to show the configurations of the inner and outer housings **518**, **520**. In some embodiments, the inner housing **518** may completely encapsulate various components of the system **516**, such as the pump **410** and the motor **412**, thus totally isolating them from other components of the system **516**, such as the filter **406** and exhaust mechanism **414**. In other embodiments, the inner housing **518** may only partially surround or encapsulate these or other components.

(198) The outer housing **520** may house other components of the smoke evacuation system **516** that are not housed within the inner housing **518**. For example, the embodiment illustrated in FIG. **22** shows outer housing **520** that houses the filter **406**, exhaust mechanism **414**, and portions of the first and second zones **416**, **418** of the airflow path **408**. The outer housing **520** may also house the

entire system, including the inner housing **518** and components therein.

(199) FIG. **22** illustrates a cross-sectional view of a smoke evacuation system **516** in order to show the configurations of the inner and outer housings **518**, **520**. In some embodiments, the outer housing **520** may completely encapsulate various components of the system **516**, such as the filter **406** and the exhaust mechanism **414**, thus totally isolating them from an exterior environment surrounding the system **516**. The outer housing **520** may also encapsulate the inner housing **518**. The outer housing **520** may completely encapsulate components of the smoke evacuation system **516** not encapsulated by the inner housing **518**, such as the filter **406** and exhaust mechanism **414**. In other embodiments, the outer housing **520** may only partially surround or encapsulate these or other components.

(200) Vibration absorption mechanisms may be disposed, and serve as interfaces, between the inner and outer housings **518**, **520**. FIG. **23** illustrates an inner housing **518** interfacing with an outer housing **520** via various vibration absorption mechanisms **522**. Only a portion of the outer housing **520** is shown for illustrative purposes. Various components of a smoke evacuation system **400** are also shown, including first and second zones **416**, **418** of the airflow path **408**, which may serve as an inlet and outlet of the pump disposed within inner housing **518**. The filter **406** (illustrated in FIG. **22**), motor **412**, and first and second zones **416**, **418** of the airflow path **408** may be disposed within the outer housing **520** but outside the inner housing **518**. The pump **410** may be enclosed inside the inner housing **518** and therefore not shown in FIG. **23**.

(201) In the embodiment illustrated in FIG. **23**, vibration absorption mechanisms **522** may comprise springs disposed between inner and outer housings **518**, **520**. The pump and/or motor enclosed/housed within the inner housing **518** may create vibrations that result in unwanted movement or noise of the system. The vibration absorption mechanisms **522** may absorb these vibrations so that a substantial portion of the vibrations are not transferred to the outer housing **520**.

(202) For example, the springs **522** illustrated in FIG. **23** may compress, stretch, or laterally flex due to vertical or horizontal vibrational forces acting on the springs **522**. These forces may be a result of the inner housing **518** vibrating up and down, or laterally. These movements caused by the vibrating motor and/or pump within the inner housing **518** may be transferred into the springs **522**. As the springs **522** compress, stretch, or laterally flex, the spring may absorb a substantial portion of the vibrations. Thus, the vibrations may not be substantially transferred from the inner housing **518** to the outer housing **520**.

(203) FIG. **23** illustrates an embodiment wherein four vibration absorption mechanisms **522** are disposed between the inner housing **518** and the outer housing **520**. Other embodiments may include more or less than four vibration absorption mechanisms **522** disposed between the inner housing **518** and the outer housing **520**. The location of the vibration absorption mechanisms **522** may also vary in other embodiments. For example, a vibration absorption mechanism **522** may be disposed at the bottom center of the inner housing **518**, rather than just at the bottom four corners of the inner housing **518** as illustrated.

(204) In the embodiment illustrated in FIG. **23**, a number of plates **524** may be secured to or integrally formed with the inner housing **518** and the vibration absorption mechanisms **522** may be secured directly or indirectly to the plates **524**. Other embodiments may or may not include plates **524**. For example, other embodiments may have vibration absorption mechanisms **522** that are secured directly to the inner housing **518**. Other embodiments may include more or less than two plates **524** secured to both the inner housing **518** and vibration absorption mechanism **522** as illustrated in FIG. **23**.

(205) FIG. **24A** shows an inner housing **518** secured to an outer housing **520** via plates **524** and vibration absorption mechanisms **526**. The vibration absorption mechanisms **526** of the embodiment illustrated in FIG. **24A** may be ring isolators **526**. Similar to the springs **522** disposed between the plates **524** and outer housing **520** illustrated in FIG. **23**, the ring isolators **526** may absorb vibrations from the pump **410** and/or motor **412** housed within the inner housing **518** so that

a substantial portion of those vibrations are not transferred to the outer housing 520.

(206) FIG. 24B illustrates how the ring isolators 526 may be secured to the housings 518, 520 and/or plates 524. The ring isolators 526 may be configured in a circular ring shape and be disposed between the plate 524 and outer housing 520 so that the ring isolator 526 acts as a barrier between the two, as illustrated in FIGS. 24B and 24C. Two or more securing mechanisms 528 may secure the plate 524 and outer housing 520 to the ring isolator 526 on opposing sides of the ring isolator 526 as shown. The securing mechanisms 528 illustrated in FIGS. 24B and 24C comprise a nut and bolt assembly. Other embodiments may include other securing mechanisms 528. For example, other embodiments may include securing mechanisms 528 that comprise nails, screws, adhesives, clips, hooks, and the like.

(207) FIG. 24C illustrates how a ring isolator 526 may absorb vibrations. The ring isolator may be comprised of a flexible material such as an elastomer. For example, one embodiment of the ring isolator 526 may be made of silicone. Other embodiments may include ring isolators 526 that comprise other elastomeric materials, such as rubber. The ring isolator 526 may flex when acted upon by a force, such as the forces created by vibrations 530. FIG. 24C illustrates vibrations 530 pushing down on the plate 524. These vibrations 530 push down on the plate 524, which pushes down on the ring isolator 526, which may cause the ring isolator 526 to flex in such a way so as to compress the ring isolator 526. The compressed ring isolator 526 may absorb the movement of the plate 524 due to the vibrations 530 without transferring a substantial portion of that movement into the outer housing 520.

(208) Vibrations 530 may be oscillatory movements that create forces that may push downward, pull upward, or pull sideways on the plate 524. As will be appreciated, the ring isolator 526 may absorb all of these potential movements of the plate 524 by deforming and/or flexing in all different directions. For example, the ring isolator 526 may expand and stretch taller, or shift side to side in response to various vibrational forces. In this way, ring isolators 526 may absorb the vibrations 530 of the inner housing 518 so the vibrations 530 are not substantially transferred to the outer housing 520.

(209) FIG. 25A illustrates an embodiment where the vibration absorption mechanism comprises an elastomeric sheet 532. The elastomeric sheet 532 may be disposed between the plates 524 and outer housing 520 similar to the springs 522 and ring isolators 526 described herein. The elastomeric sheet 532 may be a single sheet covering an entire area between the first housing 518 and the second housing 520 as shown in FIG. 25A. Other embodiments may include multiple sheets 532. For example, in one embodiment, the sheet 532 may comprise four separate sections disposed at the four bottom corners of the inner housing 518 and/or plates 524, similar to where the ring isolators 526 are disposed according to the embodiment illustrated in FIG. 24A. Other embodiments may include two separate sheets 532, each connecting two corners of the inner housing 518 and/or plates 524 to the outer housing 520.

(210) FIG. 25B shows one way in which the elastomeric sheet 532 may be secured between the plate 524 and the outer housing 520. In the illustrated embodiment, two nuts molded into the sheet 532 provide a fixture through which two screws/bolts may be threaded from above the plate 524 and below the outer housing 520. Other embodiments may include other securing mechanisms, such as nails, hooks, adhesives, and so forth. Once secured, the sheet 532 may absorb vibrations from the inner housing 518 due to the pump 410 or motor 412 and substantially prevent those vibrations from being transferred to the outer housing 520.

(211) In addition to the various vibration absorption mechanisms described herein, additional vibration absorption mechanisms may be employed in conjunction with those described in other embodiments. FIG. 26 shows a tube configuration that may enhance the vibration absorption capabilities of various tubes. More specifically, FIG. 26 shows bent tubes 536, 537 that may absorb vibrations due to their bent configuration. The tubes 536, 537 may be inlet and/or outlet tubes to the pump 410 residing within the inner housing 518. The motor 412 may be disposed outside the

inner housing **518** and engage the pump **410** through the housing **518**. The motor **412** and/or pump **412** may create vibrations in the system that may travel into the inner housing **518** and through the tubes **536**, **537**.

(212) The tubes **536**, **537** may include a U-shaped portion **538** at one or more locations along the length of the tubes **536**, **537**. The U-shaped portions **538** of the tubes **536**, **537** may allow the tubes **536**, **537** to flex in response to vibrations to a greater degree than straight tubes having no U-shaped portions **538**. The U-shaped portions **538** of the tubes **537** also may increase the total length of the tubes **536**, **537** to increase the amount of tube material available to absorb and dampen vibrations. In the embodiment shown in FIG. **26**, each tube **536**, **537** has one U-shaped portion **538**. Other embodiments may include more than one U-shaped portion **538**. Some embodiments may include tubes **536**, **537** bent into other shapes, such as S-shaped portions or the like.

(213) The U-shaped portions **538** of the tubes **536**, **537** may be made of material that is the same or similar to the rest of the tubes **536**, **537**. Some embodiments may include U-shaped portions **538** that are made of a different material than the rest of the tubes **536**, **537**. For example, some embodiments may include U-shaped portions **538** that are made of an elastomeric material. A U-shaped portion **538** made of an elastomeric material, for example rubber, may absorb vibrations to a greater degree than more rigid materials such as plastics and the like.

(214) Three different configurations of tubes **540** configured to absorb vibrations are illustrated in FIGS. **27A** through **27C**. FIG. **27A** illustrates a tube **540** having a flexible portion **542**. The flexible portion **542** may be made of an elastomeric material such as silicone, rubber, or the like. FIG. **27B** illustrates a tube **540** that includes a U-shaped portion **544** similar to those U-shaped portions **538** illustrated in FIG. **26**. The U-shaped portion **544** may be made of material similar to the rest of the tube **540** or it may be made of elastomeric material such as silicone, rubber, or the like. FIG. **27C** illustrates a tube **540** that includes 90-degree bent portions **546**, in order to accomplish the same vibration absorption capacity of the tubes **540** described above. Again, the bent portions **546** may be made of material similar to the rest of the tube **540** or may be made of elastomeric material such as silicone, rubber, or the like.

(215) In addition to the absorption mechanisms described above, which may be disposed between the inner housing **518** and outer housing **520**, additional absorption mechanisms may be disposed on an outside surface of the outer housing **520**. The smoke evacuation system **400** may be placed on a support surface, such as a table or countertop when in use. Vibration of the outer housing, due to the operation of internal components of the system **400** such as the motor **412** and/or pump **410**, may cause the entire system **400** to bounce/travel along the support surface.

(216) Additional vibration absorption mechanisms may be disposed on a bottom outside surface of the outer housing **520** to act as an interface between the smoke evacuation system **400** and the support surface on which the outer housing **520** is placed in order to reduce this effect. The vibration absorption mechanisms may act to absorb the vibrations so the vibrations are not substantially transferred to the support surface. The vibrations absorption mechanisms may also provide greater friction between the outer housing **520** and a support surface to reduce travel along the surface due to vibrations.

(217) FIG. **28A** shows an outer housing **520** that includes a number of feet **548**. These feet **548** are vibration absorption mechanisms. The feet **548** are disposed on a bottom surface **550** of the outer housing **520** and may act as an interface between the outer housing **520** and a support surface on which the outer housing **520** is placed. The embodiment illustrated in FIG. **28A** includes four feet **548** disposed on the bottom surface **550**. Other embodiments may include more or less than four feet **548** that may be arranged in any number of configurations. For example, one embodiment may include only three feet **548**. Other embodiments may include five or more feet **548** with some of the feet **548** disposed near the center of the bottom surface **550** as well as the corners.

(218) FIG. **28B** illustrates a cross-sectional view of one of the feet **548** illustrated in FIG. **28A**. The foot **548** may be comprised of a flexible matrix **554** secured to the bottom surface **550** via a rigid or

semi-rigid bolt **552**. The bolt **552** may be threaded or otherwise secured to the bottom surface **550**. The bolt **552** may protrude beyond the bottom surface **550** and the flexible matrix **554** may be molded around the protrusion of the bolt **552**.

(219) The flexible matrix **554** of the foot **548** may have a first diameter $D_{sub.1}$ and a second diameter $D_{sub.2}$. The first diameter $D_{sub.1}$ and the second diameter $D_{sub.2}$ may vary in size. The first diameter $D_{sub.1}$ may be smaller than the second diameter $D_{sub.2}$. A contact pressure between the foot **548** and a support surface may increase as the diameter of the foot **548** decreases. Also, certain diameters may absorb a given range of vibrational frequencies better than others. It may therefore be advantageous to vary the diameter of the foot **548** as shown in FIG. **17B**.

(220) For example, $D_{sub.1}$ may absorb a first frequency of vibrations, or first range of frequencies, and $D_{sub.2}$ may absorb a second frequency of vibrations, or second range of frequencies. Therefore, having a foot **548**, such as the foot **548** illustrated in FIG. **17C**, with various diameters $D_{sub.1}$. $D_{sub.2}$ may enable the foot **548** to substantially absorb both the first and second frequencies, or ranges thereof. One will appreciate that other embodiments may include feet with any number and combination of different diameters to meet the specific range of frequencies being absorbed.

(221) FIG. **17C** shows another embodiment of a foot **548** that includes a first diameter $D_{sub.1}$ that is smaller than a second diameter $D_{sub.2}$. In this embodiment, the edge profile **556** of the foot **548** is straight so that the foot **548** substantially resembled an inverse cone. Other embodiments may include edge profiles **556** that result in various other shapes.

(222) It will be appreciated that the feet **548** may be secured to the bottom surface **550** in a variety of ways. For example, in one embodiment, the feet **548** may be secured via hooks, nails, adhesives, or the like, without the need for a bolt **552** as shown in FIG. **28B**. The feet **548**, including other embodiments of feet described herein, may be made of an elastomeric material, such as rubber, silicone, or the like. The elastomeric material of the flexible matrix **554** may absorb vibrations from the outer housing **520** and provide added friction between the bottom surface **550** of the outer housing **520** and a support surface on which the outer housing **520** is placed.

(223) FIG. **29A** illustrates a number of feet **558** disposed on the bottom surface **560** of an outer housing **520**. In this embodiment, nine feet **558** serve as an interface between the bottom surface **560** and a support surface. Increasing the number of feet **558** may increase the vibration absorption capacity of the system. It may also increase the friction between the bottom surface **560** of the outer housing **520** and a support surface to minimize vibrational travel. Other embodiments may include more than nine feet **558** disposed on the bottom surface **560** in order to increase friction and vibration absorption capacity.

(224) FIG. **29B** illustrates a cross-sectional view of two of the feet **558** shown in FIG. **29A**. There may be slight variations in the bottom surface **560** of the outer housing **520** and/or the support surface **564** that cause the surfaces **560**, **564** to be uneven. This may result in inconsistent contact between some of the feet **558** and the support surface **564**. Flexible spacers **562** may be disposed on the feet **558** to compensate for uneven surfaces **560**, **564** so that all the feet **558** may be in contact with the support surface **564** despite unevenness.

(225) As shown in FIG. **29B**, the spacers **562** may compress from a first thickness $X_{sub.1}$ to a second thickness $X_{sub.2}$. The spacers **562** may be made of an elastomeric material, such as silicone or rubber, so that the thickness X of the spacer **562** may vary depending on the unevenness of the support surface **564** on which the outer housing **520** is placed. In this way, all of the feet **558** may be in contact with the support surface **564** in order to increase vibration absorption capability and friction between the bottom surface **560** and the support surface **564**. The spacers **562** may also prevent the outer housing **520** from rocking due to a space or gap between the feet and the support surface.

(226) FIG. **30A** shows a cross-sectional view of one embodiment of a foot **566** for absorbing vibrations. This embodiment is similar to the embodiment illustrated in FIG. **28C**, except here the

first diameter D.sub.1 is greater than the second diameter D.sub.2. FIG. 30B illustrates how the foot 566, which may be comprised of an elastomeric material, may deform due to vibrations in the outer housing 520. As shown, vibrational movements of the outer housing 520, illustrated by arrows 576, are transferred to the foot 566. The foot 566 may laterally deform, as illustrated by arrows 578, from a first shape 572 to a second shape 568. This lateral deformation and/or change in shape of the foot 566 may occur while the interface 574 between the foot 566 and the support surface remains substantially constant. In this way, the foot 566 may absorb vibrations without substantially transferring them to the support surface 570 or traveling across the support surface 570.

(227) The various embodiments of vibration absorption mechanisms described herein, including vibration absorption mechanisms disposed between inner and outer housings, flexible tubing, U-shaped tubing, and feet disposed on a bottom surface of the outer housing, may be employed singly or together in a multitude of combinations. These embodiments may also be included within various embodiments of a smoke evacuation system that includes various types of pumps, blowers, and/or compressors. The vibration absorption mechanisms described herein, combined with pumps that reduce vibrations and noise, may provide a substantial decrease in vibrations and noise inherent in typical smoke evacuation systems.

(228) Motors and Methods of Control

(229) The smoke evacuation system 400 illustrated in FIG. 13 includes motor 412 engaging the pump 410. The motor may rotate a rotary shaft of the various pumps 410 described herein. In one embodiment, the motor 412 may be a permanent magnet synchronous motor. Other embodiments may include a brushless DC motor. Brushless motors may have large starting torques from a fully stopped condition for use with the various pumps described herein. Brushless motors may also have less noise, greater dynamic response, and better speed-vs.-torque characteristics than brushed motors.

(230) The pump 410 may create a pressure differential between a gas entering the pump 410 and a gas exiting the pump 410, as described above. This pressure differential, or compression ratio of the pump 410 may result in a high starting torque of the motor 412 in order to initiate the motor 412 rotating the pump 410.

(231) Motor control methods may be employed to reduce the vibrations and increase motor efficiency and lifespan. Unwanted debris from the outside environment may inadvertently enter the airflow path 408 and cause clogging and/or blockages. These blockages within the system can cause pump and airflow path resistance pressures to rise as airflow is impeded. In order to maintain necessary airflow while blockages are present, pumps and/or motors may need more power and/or speed in order to compensate. Increased speed and/or power may diminish the efficiency of the motor and pump as well as decrease their lifespan. Various control methods of a smoke evacuation system, particularly methods of motor regulation, as described herein, may maintain airflow rates, increase motor efficiency, and preserve the lifespan of the motor and/or pump, especially when blockages and/or clogging of the system occurs.

(232) A method 580 for regulating the motor to reduce noise and vibration in a smoke evacuation system is shown in FIG. 31. In a first step 586, the system may sense or detect whether smoke is present to be evacuated or not. This detection may be done automatically when the practitioner begins cutting a patient during electrosurgery, or a separate smoke sensor may be employed to detect smoke present at cutting site. If smoke is present to be evacuated, then a next step 582 of the method may be to regulate the motor so that the rotational speed of the motor results in full smoke evacuation. If no smoke is present to be evacuated, then the next step may be to regulate the motor to operate at a rotational speed so that the motor is in sleep mode 584.

(233) In one embodiment, a method of regulating the motor may include varying a supply of electrical current to the motor. For instance, the method 580 may include supplying a first amount of current to the motor to cause the motor to operate at a first performance level. Alternatively, a

second amount of current may be supplied to the motor to cause the motor to operate at a second performance level. The supply of current may be accomplished by varying a pulse width modulation (PWM) duty cycle of an electrical input to the motor. In other embodiments, the current may be varied by adjusting the frequency of the current supplied to the motor. The motor may be engaged with a rotary mechanism, such as the compressors and blowers described above, so that reducing the duty cycle or frequency of a current input to the motor decreases the rotational speed of the rotary mechanism.

(234) In one embodiment, a regulation of the motor may depend on an initial condition, such as the rotational speed of the rotary mechanism. For example, once the system is running, the regulation of the motor may operate the motor at a constant speed that equals the initial rotational speed of the motor. In one embodiment, the first performance level of the motor may result in a first rotational speed of a rotary shaft of the motor engaging a rotary mechanism. The first performance level therefore, may result in a faster rotation of the rotary mechanism. This first performance level, and corresponding rotation speed of the rotary mechanism, may be the speed needed for normal suction of a gas through the airflow path. A second performance level may be slower than the first so that the second performance level causes the rotary mechanism to operate at a speed lower than the first level.

(235) The first performance level may be employed when there is no smoke produced by the electrosurgical instrument, but it is advantageous to keep the smoke evacuation system active. For example, a practitioner performing electro-surgery may temporarily have no need to suck smoke into the system to be filtered because the practitioner is not currently cutting the flesh of the patient and producing smoke. Instead of completely turning off the smoke evacuation system every time smoke is not being produced, and suction is temporarily not needed, the motor may switch to the second, slower performance level.

(236) When the practitioner begins cutting again with the electrosurgical instrument, producing unwanted smoke, the motor may be switched back to the first, higher performance level, thus creating a higher vacuum pressure necessary to suck smoke into the system to be filtered. This lower second performance level may be thought of as a sleep mode. In sleep mode, the motor may still run, but not to its full or usual strength/rotational speed. The sleep mode may preserve the lifespan of the motor, and/or rotary mechanism with which it is engaged, by reducing the stress and wear caused by running the motor at full capacity at all times.

(237) The second, lower performance level of the motor may be more advantageous than turning the motor completely off when suction is not needed, and switching the motor on when suction is needed. This is because a practitioner may need to use the suction only intermittently during long periods of surgery. Turning a motor on from a completely turned-off state requires high start-up torques in order to overcome the standstill inertia of the motor. Repeatedly turning the motor on from a completely off mode in this manner is inefficient and may decrease the lifespan of the motor. Alternatively, employing a sleep mode as described above, with a first and second performance level, allows the motor to remain on during intermittent non-use of the system during surgery, so that activation of the first performance level when suction is needed can be done without the higher torques needed to overcome standstill inertia.

(238) In one embodiment, a method of motor control may be employed to limit substantial overheating of the motor. The motor may overheat if a blockage in the airflow path of the smoke evacuation system causes an overworking of the motor and/or rotary mechanism as they attempt to compensate for the blockage and maintain a constant airflow rate. Therefore, in the method **580** for regulating the motor, a further step may include detecting an operational parameter. The operational parameter may be, but is not limited to, the temperature of the motor and/or rotary mechanism and/or the pressure in the airflow path of the smoke evacuation system.

(239) In one embodiment, the next step **590** may be to compare the detected operational parameter to an operational parameter limit. This parameter limit may be preset. If the detected operational

parameter is greater than or equal to the operational parameter limit, the next step 592 of the method may include altering the operational parameter to be less than the operational parameter limit. In one embodiment, the method may include setting a temperature limit and sensing a temperature of the motor and/or rotary mechanism. When the temperature of the motor and/or the rotary mechanism is equal to or greater than the temperature limit, the motor may be shut off or its performance level reduced.

(240) In one embodiment, the method may include defining a pressure limit and sensing a pressure within the circulation path of the rotary mechanism and/or the airflow path of the smoke evacuation system. A pressure inside the airflow path or rotary mechanism may increase when blockage occurs inside the airflow path as described above. In order to prevent the motor from overextending itself to overcome these higher pressures, the motor may be shut off or its performance level reduced, as described above, when the sensed pressure is equal to or greater than the set pressure limit. In one embodiment, the method may include disengaging the motor from the rotary mechanism. The motor may disengage from the rotary mechanism via a clutch.

(241) In one embodiment, the method may include manipulating one or more orifices disposed near the motor within the airflow path of the smoke evacuation system. This method may also include defining a pressure limit and sensing a pressure within the airflow path as described above. When the sensed pressure is equal to or greater than the pressure limit, the one or more orifices may be opened to allow air to flow from inside the otherwise closed airflow path of the system to the surrounding environment, or vice versa. Opening the one or more orifices may reduce the pressure within the system, thus preventing the motor and/or rotary mechanism from attempting to compensate for the higher pressure.

(242) The various methods of regulating the motor and or smoke evacuation system described herein may be employed in conjunction with any of the embodiments of a smoke evacuation system described above. These methods may also be employed independent of the various other embodiments.

(243) Smoke Evacuation System Fluid Traps

(244) In some embodiments, a smoke evacuation system includes a fluid trap that directs smoke from a vacuum hose and into a filter and removes and collects at least a portion of the fluid content from the smoke. In some embodiments, the fluid trap includes an inlet port with an inlet body extending into an interior chamber of the fluid trap and oriented to initially direct incoming smoke into a bottom, interior chamber of the fluid trap. The fluid trap additionally includes an exhaust port for directing smoke from the interior chamber of the fluid trap to an area outside the fluid trap (e.g., into a filter associated with the smoke evacuation system). In some embodiments, the exhaust port is sized and shaped to mechanically couple to a smoke filter and can additionally, or alternatively, be sized and shaped to prevent the fluid trap from spilling its contents when, for example, the fluid trap is placed on a surface contacting the exhaust-port-side of the fluid trap.

(245) In some embodiments, the fluid trap is sized and shaped to prevent spillage of stored fluid when the fluid trap is detached from the smoke evacuation system and positioned on a surface in any of a variety of different orientations. In some embodiments, the fluid trap includes a protrusion in a sidewall that increase the volume of the fluid reservoir of the fluid trap and which may additionally, or alternatively, prevent collected fluid from spilling when the fluid trap is positioned on a surface. Fluid traps disclosed herein can, in some embodiments, include a plurality of baffles or condensation surfaces to promote retention and/or extraction of fluid from smoke.

(246) One or more embodiments beneficially enable identification of the relative or absolute fluid volume within the fluid trap, and in some embodiments, fluid traps can include visual or auditory indicators of the fluid level within the fluid trap. In some embodiments, the fluid trap can include a drain valve for quickly and/or easily accessing the contents of fluid trap and which can further enable emptying or draining the contents of the fluid trap. Beneficially, the fluid traps disclosed herein reduce the amount of fluid entering the filter or other components of smoke evacuation

devices and safely retain such fluids collected by preventing or reducing the likelihood an inadvertent spill can occur. By reducing the total fluid content of the smoke and removing bulk liquid from the smoke, the usable life of mechanically coupled filters can be increased. Additionally, or alternatively, the reduced fluid content within the smoke can protect the electrical components within or associated with the smoke evacuation device.

(247) Illustrated in FIG. 32 is the smoke evacuation system 120 of FIG. 1, and as shown, the smoke evacuation system 120 is coupled to a vacuum hose 112. The smoke evacuation system 120 is configured to produce suction and thereby draw smoke from the distal end of the vacuum hose 112 into the smoke evacuation system 120 for processing. Instead of the vacuum hose 112 being connected to the smoke evacuation system 120 through a smoke filter end cap (as shown in FIG. 1), the smoke evacuation system 120 of FIG. 32 is connected to the vacuum hose 112 through a fluid trap 600.

(248) In some embodiments, the fluid trap 600 is a first smoke processing point that extracts and retains at least a portion of the fluid from the smoke before relaying the partially processed smoke to the smoke evacuation system 120 for further processing and filtration. The smoke evacuation system 120 beneficially enables smoke to be processed, filtered, or otherwise cleaned, reducing or eliminating unpleasant odors or other problems associated with smoke generation in the surgical theater (or other operating environment), and by extracting fluid from the smoke before it is processed by the smoke evacuation system 120, the fluid trap, among other things, increases the efficiency of the smoke evacuation system and increases the life of filters associated therewith.

(249) Referring now to FIGS. 33-35, illustrated are various views of a fluid trap 600 that is detached from or has yet to be associated with a smoke evacuation system, such as the smoke evacuation system 120 of FIG. 32. FIG. 33 illustrates a front perspective view of the fluid trap 600, and as shown, the fluid trap 600 includes an inlet port 602 that is defined by the front cover or surface of fluid trap 600. In some embodiments, the inlet port 602 is configured to releasably receive a vacuum hose. For example, an end of a vacuum hose can be inserted at least partially within the inlet port 602 and form an interference fit therewith. The interference fit can, in some embodiments, be a fluid tight and/or airtight fit so that substantially all of the smoke passing through the vacuum hose is transferred into the fluid trap 600. In some embodiments, other mechanisms of coupling or joining the hose with the inlet are employed such as, for example, a latch-based compression fitting, an O-ring, threadedly coupling the hose with the inlet, or other coupling mechanism known in the art.

(250) A fluid tight and/or airtight fit between the vacuum hose and the fluid trap 600 can beneficially prevent fluids or other contents within the smoke from leaking at or near the junction of these two components. In some embodiments, the vacuum hose can be associated with the inlet port through an intermediate coupling device (e.g., an O-ring, adaptor, etc.) to further ensure an airtight and/or fluid tight connection between the vacuum hose and the fluid trap.

(251) As shown in the rear perspective view of the fluid trap 600 illustrated in FIG. 34, the fluid trap 600 additionally includes an exhaust port 604 extending away from a rear cover or surface of the fluid trap 600. The exhaust port 604 defines an open channel between an interior chamber of the fluid trap 600 and the exterior environment. In some embodiments, the exhaust port 604 is sized and shaped to tightly associate with a smoke evacuation system or components thereof. For example, exhaust port 604 can be sized and shaped to associate with and communicate at least partially processed smoke from the fluid trap 600 to a smoke filter housed within smoke evacuation system 120. In some embodiments, the exhaust port extends away from a front, top, or side surface of the fluid trap.

(252) In some embodiments, the exhaust port 604 includes or is spaced apart from the smoke evacuation system by a membrane (not shown). The membrane can act to prevent water or other liquid collected in the fluid trap from passing through the exhaust port and into the smoke evacuation system while permitting air, water vapor and/or evaporate to freely pass. For example, a

high flow rate microporous polytetrafluoroethylene (PTFE) can be positioned downstream of the exhaust port and upstream of the smoke evacuation system components (e.g., a vacuum pump inlet) to protect the smoke evacuation system from damage and/or contamination.

(253) Referring back to FIG. 34, fluid trap 600 can additionally include a gripping region 606 to assist a user in handling the fluid trap and/or connecting it with a vacuum hose and/or smoke evacuation system. The gripping region 606 is depicted as being an elongate recess. However, it should be appreciated that the gripping region 606, in some embodiments, can include a plurality of recesses or grooves, any of which can be sized and shaped to accommodate a user's digits or to otherwise provide a gripping surface. In some embodiments, the gripping regions are protrusions, rings, or tassels instead of recesses.

(254) Referring now to FIG. 35, illustrated is a side view of the fluid trap 600 depicted in FIGS. 33 and 34. As shown, the front cover or surface of the fluid trap 600 is tapered from a wider upper region to a narrower lower region when viewing the fluid trap 600 in an upright position. In some embodiments, the front cover or surface does not taper, but rather, it maintains substantially uniform dimensions between the upper and lower regions of the fluid trap 600.

(255) As also shown in FIG. 35, the exhaust port 604 is positioned proximate the upper end of the rear cover or surface of fluid trap 600 when the fluid trap 600 is viewed in an upright position. The inlet port 602 can be positioned substantially within the center of the fluid trap 600, as shown in the vertical cross-section of the fluid trap 600 depicted in FIG. 36, or it can be positioned higher or lower along the front surface. In some embodiments, the inlet port is positioned laterally off-center and/or proximate an outer edge of the front cover or surface. The respective positioning of the exhaust port 604 can mimic the lateral and/or vertical positioning of the inlet port, but in some embodiments, the exhaust port 604 remains in the position shown in FIGS. 32-36 so that its placement does not functionally impair the fluid trap 600 from associating with the smoke evacuation system 120 (or components thereof).

(256) With continued reference to FIG. 36, the inlet port 602 is defined by a notched cylindrical body that extends into the interior chamber of the fluid trap 600. The notched cylindrical shape of the inlet port 602 is defined by an upper sidewall 608 and a lower sidewall 610. The upper sidewall 608 extends into the interior chamber of the fluid trap 600 farther than the shorter, lower sidewall 610 such that a cross-sectional slice transecting the longitudinal axis of the inlet port 602 yields a circle (or similar arcuate shape) where the cross-section includes both the upper and lower sidewalls 608, 610, and a cross-sectional slice transecting the longitudinal axis of the inlet port 602 yields a semi-circle where the cross-section includes only that portion of the upper sidewall 608 that extends beyond the lower sidewall 610.

(257) As also shown in FIG. 36, the exhaust port 604 is positioned above the inlet port 602. In some embodiments, the exhaust port 604 is positioned lower on the rear cover of the fluid trap 600 than what is illustrated in FIGS. 34-36. In such embodiments, the exhaust port 604 is preferentially positioned above an associated inlet port 602. As used herein, the relative positioning of the exhaust port being “above” the inlet port or the inlet port being positioned “below” the exhaust port is intended to preferentially include embodiments where any portion of the openings defined by the inlet port and exhaust port, respectively, are in different horizontal planes. Additionally, in some embodiments, the exhaust port is understood to be “above” the inlet port when the exhaust port is more proximate an upper edge or surface of the fluid trap than the inlet port and/or the inlet port is more proximate a lower edge or surface of the fluid trap than the exhaust port. Additionally, the exhaust port can be “above” the inlet port if a portion of the respective openings (e.g., less than 50%, less than 40%, less than 30%, less than 20%, less than 10%, less than 5%, etc.) coexist within the same horizontal plane (or sets of horizontal planes) but there is at least one horizontal plane that includes an upper surface of the exhaust port that does not include any portion of the inlet port.

(258) In some embodiments, the relative positioning of the inlet port 602 and the exhaust port 604 promote extraction and retention of fluid from the smoke as it passes into the fluid trap 600. In

some embodiments, the notched cylindrical shape of the inlet port **602** can beneficially act to initially direct smoke and the accompanying airflow towards a fluid reservoir of the fluid trap **600** or otherwise directionally away from the exhaust port. Such an exemplary airflow is depicted in FIG. 37.

(259) As shown, smoke enters the fluid trap **600** through inlet port **602** (illustrated by arrow A) and exits the fluid trap through exhaust port **604** (illustrated by arrow E). At least partially due to the geometry of the inlet port (e.g., a longer, upper sidewall **608** and a shorter, lower sidewall **610**), the smoke entering the inlet port **602** is initially directed downward into the fluid reservoir of the fluid trap **600** (illustrated by arrows B). As smoke continues to be pulled into the fluid trap **600** along arrows A and B, the smoke that was initially directed downward tumbles and is directed laterally away from its source to travel in an opposite but parallel path towards the upper portion of the fluid trap **600** and out of the exhaust port **604** (illustrated by arrows D and E).

(260) In some embodiments, the directional flow of air/smoke through the fluid trap **600** (as illustrated in FIG. 37, for example) enables fluids within the smoke to be extracted and retained within the lower portion of the fluid trap **600**. Further, the relative positioning of the exhaust port **604** with respect to the inlet port **602** discourages liquid from inadvertently being carried through the exhaust port **604** by the flow of smoke while not substantially hindering airflow into and out of the fluid trap **600**. Additionally, the configuration of the inlet and exhaust ports **602**, **604** and/or the size and shape of the fluid trap, itself, can enable the fluid trap **600** to be spill resistant.

(261) For example, in an upright position, fluid **612** that is extracted from smoke is retained within the bottom portion of the fluid trap **600**, as shown, for example, in FIG. 38. If the fluid trap **600** falls or is moved or its orientation changed from an upright position such that it becomes oriented on a surface inlet port side down, as shown in FIG. 39, the fluid trap **600** can still retain the fluid **612** within the interior chamber owing to its size and shape. For example, the upper sidewall **608** and the lower sidewall **610** of the inlet port **602** protrude deep enough into the interior chamber of the fluid trap **602** to create a front cover volume that is bounded by the surface area of the interior surface of the front cover and the sidewalls **608**, **610** of the inlet port **602**.

(262) It should be appreciated that although the fluid **612** in FIG. 39 appears to be separated into two distinct portions, FIG. 39 illustrates a cross-sectional view of the fluid trap **600**. As described above, the inlet port **602** can be defined by a notched cylindrical sidewall (or cylindrical sidewall) that does not transact the entire front cover or surface. Accordingly, when the fluid trap **600** is positioned on a surface with the inlet side down, as shown in FIG. 39, fluid **612** can pass around the intrusive sidewalls of inlet **602** and be distributed along the interior surface of the cover.

Accordingly, in some embodiments, the front cover of the fluid trap is dimensioned such that the volume of the front cover is equal to or greater than the maximum fluid volume of the fluid reservoir. The volume of the front cover can, for example, be calculated as the product of the surface area of the front cover and the average depth of the front cover with respect to the lowest intrusive sidewall of the inlet port. In some embodiments, the maximum volume of the fluid reservoir is determined by the volume of the front cover. As used herein, a “fluid reservoir” includes a subset of the interior chamber of the fluid trap, particularly the interior volume of the fluid trap defined by the interior sidewalls of the fluid trap below the inlet port.

(263) In some embodiments, the fluid trap **600** can be considered full when the volume of fluid **612** contained therein rises as high as the terminal end of the lower sidewall **610** when the fluid trap is positioned on a surface with the inlet side down (i.e., at a maximum front cover volume). In some embodiments, the fluid trap **600** can be considered full when the volume of fluid **612** contained therein rises a particular distance below the terminal end of the lower sidewall **610** when positioned on the surface with the inlet side down. In some embodiments, the foregoing particular distance is about 1/16", 1/8", about 1/4", about 3/8", about 1/2", about 5/8", about 3/4", about 7/8", or about 1".

(264) In some embodiments, the fluid trap **600** is additionally spill resistant owing at least partially to its size and shape when oriented on a surface with the exhaust port side down, as shown in FIG.

40. The sidewalls defining the exhaust port **604** extend a length **616** away from the rear surface of the fluid trap **600** such that the exhaust port acts like a kickstand to stably support the fluid trap **600** in an inclined position, directing the fluid **612** away from the exhaust port **604**. As shown in FIG. **40**, the fluid **612** is retained within the fluid reservoir of the fluid trap **600** and at least partially along the rear cover of the fluid trap. The fluid **612** is retained within the fluid trap **600** when the fluid trap is oriented exhaust port **604** side down because, in some embodiments, the rear cover volume is greater than the volume of fluid **612** contained therein. The rear cover volume can, in some embodiments, be calculated as the volume of the interior chamber defined by the interior sidewalls of the fluid trap that is bounded by a line tangent to a lowest interior-facing sidewall of the exhaust port and parallel with the surface upon which the exhaust port lies. In some embodiments, the line parallel with the surface upon which the exhaust port lies is a line normal to the force of gravity.

(265) In some embodiments, the volume of the rear cover is expanded by a protrusion or protruding sidewall **618**. The protruding sidewall **618** can be sized proportionally with the length **616** of the exhaust port **604**, or it can have defined dimensions regardless of the length **616** of the exhaust port **604**. For example, in embodiments where the protruding sidewall **618** is sized proportionally with the length **616** of the exhaust port **604**, as the length **616** of the exhaust port **604** decreases, the angle of incline experienced by the fluid trap **600** can similarly decrease. A decreased incline causes a decreased rear cover volume. By increasing the width or depth of the protrusion **618**, the protrusion **618** effectively increases the rear cover volume. Alternatively, as the length **616** of the exhaust port **604** increases, the angle of incline experienced by the fluid trap **600** can similarly increase. The increased incline causes an increase in the rear cover volume. The protrusion **618** can be proportionally shrunk or removed as the rear cover volume increases to prevent fluid **612** from spilling out of the exhaust port **604**.

(266) It should be appreciated that in some embodiments, the fluid reservoir volume can additionally be increased by the same protrusion **618** shown in at least FIGS. **38-40** (or a different protrusion). For example, an increase in the size of the protrusion **618** can proportionally increase the fluid reservoir volume, and a decrease in the size of the protrusion **618** can proportionally decrease the fluid reservoir volume. Additionally, although the protrusion **618** is shown in at least FIGS. **38-40** as being located on the rear cover, a protrusion may additionally, or alternatively, be located on the front cover.

(267) In some embodiments, the fluid trap **600** can be considered full when the volume of fluid **612** contained therein rises as high as but not into the exhaust port **604** when the fluid trap is positioned on a surface with the exhaust port **604** side down (i.e., at a maximum rear cover volume).

(268) As described above with respect to at least FIGS. **38-40**, embodiments of the present disclosure include fluid traps that are spill resistant. In such embodiments, the maximum volume of fluid that can be extracted and retained while maintaining the fluid trap's spill resistant feature is dependent upon the volume of the fluid reservoir of the fluid trap, the volume of the front cover, and the volume of the rear cover. In some embodiments, the maximum volume is the lesser of the fluid reservoir volume, the front cover volume, and the rear cover volume. For example, in some embodiments, the front cover volume is less than the fluid reservoir volume and the rear cover volume. Accordingly, the maximum volume for the foregoing exemplary fluid trap is at most the front cover volume.

(269) Referring now to FIG. **44**, the exhaust port **604** can be adapted to include upper and lower sidewalls **622**, **624** that extend into the interior chamber of the fluid trap **620**. The upper and lower sidewalls **622**, **624** can similarly form a notched cylinder (as described above with respect to upper and lower sidewalls **608**, **610** of the inlet port **602**). Alternatively, the upper and lower sidewalls of the exhaust port can define a cylindrical channel. Regardless, by extending upper and lower sidewalls **622**, **624** of the exhaust port **604** into the interior chamber of the fluid trap **620**, the fluid trap **620** becomes more resistant to spilling or at least reduces the likelihood that splashes or

sloshing of the fluid **612** inside the fluid trap **620** results in spillage when the fluid trap **620** is positioned on a surface inlet side up-even when agitated. In some embodiments, extending upper and lower sidewalls **622**, **624** into the interior chamber of the fluid trap **620** may also allow for a shorter exterior length **616** of the exhaust port **604** without appreciably risking spilling liquid **612**. In some embodiments, the length **626** of the upper sidewall **622**, which is shorter than the lower sidewall **624** in some embodiments, can be proportional to the length **616** of the exhaust port **604**. For example, the length **626** of the upper sidewall **622** can increase to compensate for a decreased length **616** of the exhaust port **604**. Similarly, as the length **616** of the exhaust port **604** increases, the length **626** of the upper sidewall **622** can decrease.

(270) In some embodiments, the exhaust port **604** protrudes into the interior chamber of the fluid trap **620**, as illustrated in FIG. **44**. This can, in some embodiments, decrease the likelihood that fluid can freely or accidentally transit between the inlet **602** and the exhaust **604**. In some embodiments, having the exhaust port protrude into the interior chamber of the fluid trap increases the rear cover volume. Additionally, or alternatively, the exhaust port **604** protrudes into the interior chamber of the fluid trap **620** with the lower sidewall **624** being longer than the upper sidewall **622** so as to further manipulate the airflow through the fluid trap **620**. As it should be appreciated, the configuration of sidewalls having a staggered length, as shown in FIG. **44**, can increase the flow rate of air or smoke proximate the upper sidewall **622** (similar to the flow described above for inlet port **602**).

(271) In some embodiments, it may be advantageous to include physical barriers within the fluid trap to reduce the likelihood that splashes or sloshing of the fluid inside the fluid trap results in spillage. Referring now to FIG. **42**, illustrated is a partial cross-section, perspective view of a fluid trap **630** having a plurality of baffles **632** disposed within an interior chamber thereof. The plurality of baffles **632** can be disposed along baffle securing members **634**, as shown in FIG. **42**. The baffle securing member **634** can attach to one or more interior surfaces of the fluid trap **630** and act to hold the plurality of baffles **632** stationary. In some embodiments, the baffles, themselves, are attached to one or more interior surfaces of the fluid trap, and the baffles securing members can be optionally omitted.

(272) As illustrated by FIG. **42**, smoke can enter inlet port **602** and be similarly directed downward owing to the shorter, lower sidewall **610** and the longer, upper sidewall **608** that form a notched cylindrical projection (as discussed above with respect to at least FIG. **37**). Accordingly, liquid within the smoke can be directed to the fluid reservoir of the fluid trap **630** along angled baffles **632**. Once the liquid **612** passes beneath the baffles **632**, the angled arrangement of the baffles **634** acts to catch upward moving splashes or droplets and redirect them down towards the fluid reservoir. In such a manner, the plurality of baffles can minimize fluid motion during handling of the fluid trap **630**. In some embodiments, the angled baffles **634** can additionally act as condensation surfaces to promote the condensation of liquid vapor in the smoke, which is similarly directed towards the interior chamber of the fluid trap **630** after condensing into droplets (not shown). In some embodiments, the baffles are made of absorptive material and can act to wick fluid from the smoke.

(273) In some embodiments, additional measures can be taken to reduce and/or control aerosols and small droplet fluids that are moving at higher velocities by, for example, removing them from the airflow path. Referring now to FIG. **43**, illustrated is a fluid trap **640** that includes a splash canopy **644** positioned within the collection chamber of the fluid trap **640**, above the inlet port **602** and providing a physical barrier between the exhaust port **604** and the inlet port **602**. As shown in FIG. **43**, the splash canopy **644** spans the interior sidewall of the front cover to the interior sidewall of the rear cover and extends laterally across and past the width of the inlet port **602**. In some embodiments, the splash canopy is attached to the sidewall of the rear cover, extends over the upper sidewall of the inlet port and towards the interior sidewall of the front cover but does not attach thereto.

(274) The splash canopy **644** is also illustrated as having a downwardly concave arcuate shape. Additionally, or alternatively, the splash canopy can be planar and/or extend over the width of the inlet port. In some embodiments, the contour and position of the splash canopy **644** can advantageously act to direct incoming airflow (shown by arrow A) and any splashing fluid downward toward the bottom, interior chamber of the fluid trap **640** (shown by arrow B). Similar to the airflow described above with respect to FIG. **37**, the downwardly directed air can flow laterally and upward (shown by arrow C) where it passes over and around a vertically oriented splash wall **642**. As shown in FIG. **43**, the splash wall **642** can span the distance between the interior sidewall of the front cover to the interior sidewall of the rear cover and can extend vertically a distance from at least the lower terminal edge of the splash canopy **644** (or lower) to the bottom of the exhaust port **604**.

(275) In some embodiments, the vertical distance spanned by the splash wall **642** can be different. For example, the splash wall can begin at a point coplanar to the bottom of the inlet port and extend vertically upward, terminating in at a point coplanar with the top of the splash canopy, the bottom of the exhaust port, or the top of the exhaust port. Additionally, as shown in FIG. **43**, the splash wall **642** can be spaced apart from the splash canopy **644**. However, in some embodiments, the splash canopy and the splash wall are connected to form a W-shaped or U-shaped splash wall that partially surrounds the exhaust port **604**.

(276) In some embodiments, the splash canopy **644** and/or the splash wall **642** can include or be made of a fibrous fluid wicking material (e.g., glass borosilicate or similar) which can enable the splash canopy **644** and/or splash wall **642** to remove aerosols and small droplet fluids from the inbound smoke. In some embodiments, the splash walls **642** and/or the splash canopy **644** can act as condensation promoting surfaces where aerosols and small droplets of fluids can condense and accumulate into droplets **646** that fall into the bottom, interior chamber.

(277) In some embodiments, the fluid trap contains a plurality of splash walls and/or splash canopies, which can be tiered, stacked, or aligned in series. In some embodiments the splash walls and splash canopies are made of or include heat conductive materials that promote condensation.

(278) In some embodiments, it may be advantageous to monitor the total volume of fluid collected within the fluid trap. As shown in FIG. **44**, a fluid trap **650** can include a horizontal viewing window **652** and/or a vertical viewing window **654**. The viewing windows **652**, **654** can be an integral part of the fluid trap sidewalls. As shown in FIG. **4**, the horizontal viewing window **652** can wrap circumferentially around fluid trap **650** at a position below the inlet port **602**. The positioning of the horizontal window may, in some embodiments, indicate a maximum fill line for the fluid reservoir **650**. Alternatively, a plurality of horizontal viewing windows can be positioned along the fluid trap (e.g., in tiers) so the volume of fluid within the fluid trap can be progressively monitored and/or observed. Additionally, or alternatively, the vertical viewing window **654** can join with one or more horizontal viewing windows at at least one point and extend to the bottom of the fluid trap **650**, as illustrated in FIG. **4**.

(279) Although illustrated as being positioned on a side of the fluid trap **650**, it should be appreciated that the vertical viewing window **654** may be positioned on a front surface and/or rear surface of the fluid trap **650**. In some embodiments, placing the horizontal and/or vertical viewing windows on the front surface can beneficially enable a user to quickly identify the volume level of fluid contained within the fluid trap without disassociating or otherwise removing the fluid trap from the smoke evacuation system. In some embodiments, the viewing windows are made of a transparent and/or translucent material that allow a user to readily view the contents of the fluid trap through the viewing window. For example, the viewing window may include glass or plastic, or in some embodiments, the viewing window may include frosted glass or plastic to better indicate dark blood within the fluid trap.

(280) In some embodiments, a visual indicator coupled to a sensor can additionally, or alternatively, indicate the amount or volume of fluid within the fluid trap. For example, as shown in

FIG. 45, the fluid trap **660** includes a horizontal viewing window **662** that indicates a maximum fill line for the fluid trap **660**. The fluid trap **660** additionally includes an optical emitter and detector pair **666** positioned at or adjacently below the maximum fill line. The emitter and detector pair **666** can beneficially identify via optics whether fluid **612** within the fluid trap **660** has risen to a level at or above the emitter and detector pair **666**. Upon determining that fluid **612** is at or above the level of the emitter and detector pair **666**, an electrical signal can be sent to activate a status light **664** that indicates the fluid trap **660** is full.

(281) Additionally, or alternatively, the fluid trap **660** can include an ultrasonic detector **668** that identifies a change in signal and causes an electrical signal to be sent to activate the status light **664**, indicating the fluid trap **660** is full. For example, an identified change in signal can include the ultrasonic signal being consistently received at the ultrasonic detector **668** more quickly than previously observed. As an additional example, an identified change in signal can include the ultrasonic signal being received at the ultrasonic detector **668** within a threshold time that is indicative of the ultrasonic waves passing through a liquid medium.

(282) In some embodiments, the volume of fluid within a fluid trap can be progressively monitored and/or indicated electronically, as shown, for example, in FIG. 46. The fluid trap **670** of FIG. 46 includes a resistive strip **674** having a plurality of nodes that are sequentially activated upon detection of liquid at the node. Each node of the resistive strip **674** can correspond to one or more status lights **676** such that upon activation of each node on the resistive strip, the corresponding status light is activated. For example, as shown in FIG. 46, the fluid level **612** is activating nodes **1** and **2**, and the corresponding status lights—25% and 50% respectively—are turned on. In some embodiments, one of the nodes on the resistive strip can correspond to an audio signal or alarm that provides an audible cue—in addition to or separate from the visual cue(s) provided by the status light(s)—that the fluid trap is full and needs to be replaced or drained.

(283) Although the embodiment of FIG. 45 is illustrated as having a single optical emitter and detector pair and a single ultrasonic detector, it should be appreciated that in some embodiments, a fluid trap can include a plurality of optical emitter and detector pairs and/or a plurality of ultrasonic detectors—and in any combination—to achieve an analogous progressive status light activation corresponding to the amount of fluid within the fluid trap like that depicted and described in FIG. 46.

(284) In some embodiments, upon an indication that the fluid trap is full, the fluid trap is discarded. Alternatively, the fluid can be drained from the fluid trap for continued use. For example, as shown in FIG. 47, a fluid trap **680** can include a drain **682** for draining fluid **612** from the fluid trap **680**. The drain **682** can be associated with a removable drain plug **684**, as shown in FIG. 47, or alternatively, the drain can include a lever or valve for opening and/or closing the drain. The drain **682** may be positioned at a lower side edge of the fluid trap **660**, or in some embodiments, the drain may be positioned on the lower front face of the fluid trap. In some embodiments, it is advantageous for the drain to be located near the bottom of the fluid trap so that opening the drain (e.g., by removing a drain plug or opening a drain valve) causes immediate drainage of fluid from the fluid trap. In other embodiments, however, it may be advantageous to position the drain near the top of the fluid trap so that opening the drain does not immediately cause fluid to be expelled. Instead, a user can pour the fluid at a rate that is more easily controlled by the user.

(285) Filter Medium Compression Systems

(286) In some embodiments, after at least a portion of a fluid has been removed from the smoke using fluid traps (as described above), the partially processed smoke can be further filtered within the smoke evacuation system **120** (as illustrated, for example, in FIG. 32). Alternatively, in some embodiments, smoke is transferred directly from the vacuum hose **112** into the smoke evacuation system **120** (as shown, for example, in FIG. 1). Regardless of whether the smoke is preprocessed at a fluid trap or directly transferred to the smoke evacuation system **120** from vacuum hose **112**, a smoke filter (e.g., smoke filter **700** illustrated in FIG. 48) can be used to remove particulate matter

and gaseous pollutants from the smoke.

(287) However, it can be difficult to process and/or filter smoke, as it can contain particulate matter of various sizes, volatile organic compounds, water vapor, and potentially other noxious chemicals and compounds. Traditionally, particulate matter can be removed from smoke using particulate filters, which have a wide range of airflow resistance and efficiency. For example, coarse media filters, which broadly include low air resistant filters such as fiberglass, polyester, and pleated filters, can be used to remove the majority of large particulate matter (e.g., greater than 10 μm). In some instances, coarse media filters can be used to remove at least 85% of large particulate matter (e.g., greater than 10 μm) and between 50%-95% of small particulate matter (e.g., between 1-3 μm). Some coarse media filters can remove greater than 95% of small particulate matter.

(288) High efficiency particulate air (HEPA) filters and ultra-low penetration air (ULPA) filters can be used for filtering fine particulate matter. HEPA filters, for example, are defined by the U.S. Department of Energy as filters capable of removing at least 99.97% of airborne particulate matter up to 0.3 μm in diameter. HEPA filters typically have a minimal airflow resistance compared to the higher efficiency ULPA filters. Although ULPA filters are typically associated with higher airflow resistance, ULPA filters are generally more efficient at filtering fine particulate matter. Most ULPA filters can remove at least 99.9995% of airborne particulate matter up to 0.12 μm in diameter.

(289) Particulate filters are, for the most part, not very effective at removing other contaminants, particularly those gaseous pollutants found within smoke like volatile organic compounds. Sorbent-based filters can remove a number of gaseous pollutants from air and smoke, including volatile organic compounds, by chemically cross-linking the gaseous pollutant to the surface of the sorbent, and because adsorption is dependent upon the surface area of the sorbent, activated carbon is an ideal sorbent. Activated carbon is highly microporous and offers a significant amount of surface area per unit volume.

(290) Filters employing sorbents like activated carbon require surface exposure of the air or smoke to be filtered with the sorbent in order for adsorption to occur. As it can be appreciated, therefore, the amount of surface area exposed to the air or smoke to be filtered is generally proportional to the amount or efficiency of filtration, and it is desirable to limit any gaps or routes through a sorbent-based filter that minimize surface area exposure thereto.

(291) Referring now to FIG. 48, illustrated is a smoke filter **700**, which can be used with smoke evacuation systems disclosed herein. The smoke filter **700** includes a front cap **702** and a back cap **704** and a filter body **706** disposed of therebetween. As shown, the front cap **702** can include a filter inlet **708**, which in some embodiments, receives smoke directly from a vacuum hose or other smoke source, or alternatively, the smoke inlet may associate with a fluid trap exhaust port to communicate partially processed smoke into the smoke filter **700**. In some embodiments, the front cap **702** is replaced by a fluid trap that communicates smoke directly from the smoke source, and after removing at least a portion of the fluid therefrom, passes the partially processed smoke into the filter body **706** for further processing.

(292) Regardless of the source, once smoke enters the filter **700**, it is filtered by components housed within the filter body **706**, and exits the filter **700** through the filter exhaust **710** defined by the back cap **704**. As shown in FIG. 48, the filter body **706** of smoke filter **700** is cylindrical. It should be appreciated, however, that the size and/or shape of the filter body can be different. For example, the filter body can be a rectangular solid or other polygonal solid. Similarly, the front cap **702** and back cap **704** are shown as having arcuate cross-sections complementary to the shape of the filter body **706** where the front and back caps **702**, **704** are coupled to the filter body **706**, and the cross-sectional geometry of the front and back caps can be changed to match the shape of the filter body. In some embodiments, the filter exhaust **710** is sized and shaped to communicate with the smoke evacuation system, and the shape and/or placement of the filter exhaust **710** can remain unchanged, regardless of the size and shape the front cap **702** and/or filter body **706**.

(293) When the filter **700** is associated with a smoke evacuation system, suction generated at the

smoke evacuation system can be communicated to the filter **700** through the filter exhaust **710** to pull smoke through each of the internal filtering components of the filter **700**. An exemplary embodiment of filtering components contained within smoke filter **700** is illustrated in FIG. **49**. As shown, smoke entering the smoke filter **700** is initially drawn through a coarse media filter **714** followed by a fine particulate filter **716**. The smoke is then drawn through a carbon reservoir **722** where gaseous contaminants such as volatile organic compounds are removed. The filtered smoke, which is now substantially free of particulate matter and gaseous contaminants, is drawn through the filter exhaust **710** and into the smoke evacuation system for further processing and/or elimination.

(294) In some embodiments, the filter **700** can include a plurality of defined sections which can be cordoned off by one or more dams and/or dividers. As shown in FIG. **49**, the smoke filter **700** can include a particulate filtration section that includes the coarse media filter **714** and the fine particulate filter **716** flanked by dams **712**, **718**. The initial dam **712** of the particulate filtration section can be secured to an inner wall of the filter body **706** at a first end of the filter **700** proximate the front cap **702** and a first particulate filter (e.g., the coarse media filter **714**) within the filter body **706**. As shown in FIG. **49**, the initial dam can be shaped as a gasket or O-ring and can act to prevent movement of downstream filters towards the first end or front cap **702** of the filter **700**. The particulate filtration section of the filter **700** can be defined at an intermediate position within the filter body **706** by intermediate dam **718**, which prevents movement of the upstream particulate filters **714**, **716** toward the back cap **704**. As shown in FIG. **49**, the intermediate dam **718** can be shaped as a perforated disc that allows filtered smoke to freely pass through the perforations while the non-perforated sections act as a physical barrier to prevent upstream filters from moving further downstream and/or distending in the direction of applied suction.

(295) In some embodiments, the initial dam **712** and the intermediate dam **718** are spaced apart such that the particulate filters placed therebetween are secure. In some instances, the particulate filters being secured between the initial and intermediate dams **712**, **718** results in a substantial lack of lateral mobility. For example, as shown in FIG. **49**, the coarse media filter **714** and fine particulate filter **716** are disposed between the initial dam **712** and intermediate dam **718** such that the filters **714**, **716** cannot move laterally (e.g., directionally towards or away from dams **712**, **718**). The size and shape of the dams, particularly intermediate dam **718** can, in some embodiments, be chosen to further prevent distention of the filters in the direction of applied suction.

(296) The coarse media filter **714** illustrated in FIG. **49** can include any low air resistant filter, such as fiberglass, polyester, and pleated filters, that remove the majority of particulate matter larger than 10 μm . In some embodiments, this includes filters that remove at least 85% of particulate matter larger than 10 μm , greater than 90% of particulate matter larger than 10 μm , greater than 95% of particulate matter larger than 10 μm , greater than 99% of particulate matter larger than 10 μm , greater than 99.9% particulate matter larger than 10 μm , or greater than 99.99% particulate matter larger than 10 μm .

(297) Additionally, or alternatively, the coarse media filter **714** can include any low air resistant filter that removes the majority of particulate matter greater than 1 μm . In some embodiments, this includes filters that remove at least 85% particulate matter larger than 1 μm , greater than 90% of particulate matter larger than 1 μm , greater than 95% of particulate matter larger than 1 μm , greater than 99% of particulate matter larger than 1 μm , greater than 99.9% particulate matter larger than 1 μm , or greater than 99.99% particulate matter larger than 1 μm .

(298) The fine particulate filter **716** illustrated in FIG. **49** can include any filter of higher efficiency than the coarse media filter **714**. This includes, for example, filters that are capable of filtering a higher percentage of the same sized particles as the coarse media filter **714** and/or capable of filtering smaller sized particles than the coarse media filter **714**. In some embodiments, the fine particulate filter **716** can include a HEPA filter or an ULPA filter. Additionally, or alternatively, the fine particulate filter **716** can be pleated (as shown in FIG. **49**) to increase the surface area of the

fine particulate filter. In some embodiments, the coarse media filter **714** include a pleated HEPA filter and the fine particulate filter **716** includes a pleated ULPA filter.

(299) Subsequent to particulate filtration, smoke enters a downstream section of the filter **700** that includes a carbon reservoir **722**. In some embodiments, the carbon reservoir **722** is flanked by the intermediate dam **718** and a terminal dam **728**. The terminal dam **728** can, in some embodiments, have the same shape and/or properties described above with respect to the intermediate dam **718**. The carbon reservoir **722** can additionally be bounded by porous dividers **720**, **726** disposed between the intermediate and terminal dams **718**, **728**. In some embodiments, the porous dividers **720**, **726** are rigid and/or inflexible and define a constant spatial volume for the carbon reservoir **722**.

(300) In some embodiments, the carbon reservoir includes additional sorbents that act cumulatively with or independently from the carbon particles to remove gaseous pollutants. The additional sorbents can include, for example, sorbents such as magnesium oxide and/or copper oxide, which can act to adsorb gaseous pollutants such as carbon monoxide, ethylene oxide, and/or ozone. In some embodiments, the additional sorbents are dispersed throughout the reservoir or are positioned in distinct layers above, below, or within the reservoir.

(301) Referring now to FIGS. **50-55**, illustrated are simplified cross-sectional illustrations of smoke filters which can be in many respects similar to the smoke filter **700** described above. Many of the internal components of the smoke filters illustrated in FIGS. **50-55**, however, have been removed for ease of illustration and discussion. It should be appreciated that the smoke filters shown in FIGS. **50-55** can include any number or combination of filter components illustrated in FIG. **49** or otherwise known in the art.

(302) FIG. **50**, for example, illustrates the smoke filter **700** with the carbon reservoir **722** bounded on opposite ends by porous dividers **720**, **726**. In some embodiments, the carbon reservoir **722** is compressed within the volume defined by the porous dividers **720**, **726** when manufactured. Problematically however, the carbon reservoir **722** can settle to a smaller spatial volume over time, or when suction is applied through the carbon reservoir **722** from the filter exhaust **710**, the carbon reservoir may be compacted to a smaller spatial volume. The settling or compacting of the carbon reservoir into a smaller spatial volume can create a gap within the reservoir that was previously occupied by carbon particles. In some embodiments, this can result in a nonuniform distribution of carbon particles within the reservoir, which can reduce the efficiency of adsorption and thereby reduce the effectiveness of the filter. In extreme instances, the carbon particles can settle to create a route through the reservoir that is devoid of carbon particles, allowing smoke to transit a portion or the entire length of the carbon reservoir without being adequately filtered.

(303) FIG. **51** illustrates a smoke filter **730** having a compacted carbon reservoir **724** that has settled over time or in response to pressure from suction communicated to the filter from a smoke evacuation system. As shown, a gap **732** is present between the compacted carbon reservoir **724** and an upstream divider **720**. In some embodiments, the compacted carbon reservoir **724** filled the gap **732** before the carbon particles settled or were otherwise compacted. As shown in FIG. **51**, the porous divider **720** does not move from its originally installed location as the carbon particles reorient because the porous divider **720** was fixed to the sidewalls of the smoke filter to define the carbon reservoir and/or to maintain the compressed state of the carbon reservoir.

(304) In some embodiments, the porous divider can be replaced by a flexible porous barrier that enables the flexible porous barrier to maintain interaction with the carbon reservoir as it decreases in volume due to settling or a result of suction pressure. In doing so, the flexible porous barrier prevents gaps or channels from forming within the carbon reservoir that would otherwise decrease the efficiency or effectiveness of the carbon reservoir as a filter for gaseous contaminants.

(305) For example, as shown in FIG. **52**, a smoke filter **725-1** includes a carbon reservoir **722** bounded on at least one end by a flexible porous barrier. The carbon reservoir **722** can be bounded on an opposing end by an inflexible porous divider **726**, or in some embodiments, the carbon

reservoir **722** can be bounded on an opposing end by a second flexible porous barrier (not shown). The carbon reservoir **722** is shown as occupying a first spatial volume **742**—denoted $V_{sub.1}$. Smoke filter **752-2** of FIG. **52** illustrates a compacted carbon reservoir **724** after settling of the carbon reservoir **722**. The compacted carbon reservoir **724** now occupies a second spatial volume **744**—denoted $V_{sub.2}$ —which is less than the first spatial volume **742**. At the first spatial volume **742**, the flexible porous barrier **734** is flexed and applying a compressive bias **738** against the carbon reservoir **722**. As the carbon particles shift to form the compacted carbon reservoir **724**, the flexed, flexible porous barrier **734** moves from a first position **739** to a second position **740** maintaining contact with the carbon particles to prevent gap formation. The partially relaxed, flexible porous barrier **736** can continue to apply a compressive bias **738** against the compacted carbon reservoir **724**, and in some embodiments, the partially relaxed, flexible porous barrier **736** can move to a third position (or a plurality of subsequent positions) while continuing to apply a compressive bias against the carbon particles within the reservoir in preventing gap formation. (306) In some embodiments, the flexible porous barrier can flex outward, opposite the compressive bias in response to an unsettling force within the carbon reservoir. For example, the carbon particles may settle or become compacted through continuous pressure applied by suction from the smoke evacuation system. The associated flexible porous barrier may remain associated with the carbon particles as they settle, preventing gap formation (as described above). However, upon release of suction (e.g., turning the power off of the smoke evacuation system), the carbon particles may exert an outward force against the flexible porous barrier and causing it to flex toward its original position and/or return to its original position.

(307) FIG. **52** illustrates the flexible porous barrier **734** applying a compressive bias **738** against the carbon reservoir **722** at a first side of the carbon reservoir. In some embodiments, the flexible porous barrier **734** is proximate the particulate filtration section of the smoke filter, or alternatively, the flexible porous barrier **734** is proximate the back cap. In yet other embodiments, the porous divider **726** of FIG. **52** is replaced with a second flexible porous barrier such that a flexible porous barrier defines two opposing ends of the carbon reservoir **722**. It should be appreciated that regardless of the positioning or location of a flexible porous barrier with respect to the carbon reservoir, the carbon particles within the carbon reservoir may shift or settle at any position therein, and the compressive bias applied against the carbon reservoir can cause any gap or channel formed by the shifting particles to be successively filled by carbon particles disposed between the flexible porous barrier and the shifting particles.

(308) In some embodiments, and as illustrated in FIG. **53**, a smoke filter **735-1** can include a flexible sleeve **746** that is flexed or otherwise applying an inward compressive bias against the carbon reservoir **722**. Upon the carbon particles shifting from a first spatial volume **742** to a second spatial volume **744**, the flexible sleeve **746** moves to a partially relaxed state, creating a gap **750** between the interior sidewall of the filter body **706** and the sleeve **748**. Although FIG. **53** is illustrated as a cross-section, it should be appreciated that the sleeve **748** may, in some embodiments, wrap circumferentially around the carbon reservoir **722**, **724**.

(309) In some embodiments, and as illustrated in FIG. **54**, a smoke filter **745** can include a flexible sleeve **752** that is positioned on one side and/or only partially around the carbon reservoir **724**. In such an embodiment, the flexible sleeve **752** may be positioned such that when the smoke filter **745** is associated with the smoke evacuation device, the compressive bias exerted by the flexible sleeve **752** is against the carbon reservoir **724** in a direction parallel to the force of gravity. In some embodiments, the flexible sleeve **752** can be positioned about at least a portion of the carbon reservoir **724** irrespective of the directional force of gravity.

(310) In some embodiments, a smoke filter **755-1** includes a rigid, porous barrier **756** associated with an outermost portion of the carbon reservoir **722** distal to the source of suction, as illustrated in FIG. **55**. Upon shifting of carbon particles within the carbon reservoir **722** and moving from a first spatial volume **742** to a second spatial volume **744**, the rigid, porous barrier ratchets down a

plurality of ridges associated with the interior sidewall of the filter body **706**, thereby decreasing the volume of the carbon reservoir. In some embodiments, the energy from moving the rigid, porous barrier **756** along the ridges **758** is at least partially obtained from a lack of pressure beneath the rigid, porous barrier **756**—as a result of the particles shifting away from or being capable of shifting away from the barrier **756** to form a smaller, second spatial volume **744**.

(311) Additionally, or alternatively, the rigid, porous barrier **756** can be weighted more heavily such that the force of gravity causes the barrier **756** to automatically lower itself along the ridges **758** when there is sufficient space to do so. In some embodiments, the suction pressure can act to pull the barrier **756** along the ridges as there is sufficient space to do so. In some embodiments, an additional flexible member (not shown) is positioned between the barrier and another component of the filter (e.g., a dam or cap) and biases against the barrier, causing the barrier to maintain contact with the carbon particles within the reservoir as the spatial volume decreases. In some embodiments, the flexible member is a spring member that forces the barrier **756** to maintain contact with the carbon particles within the reservoir and lowers the barrier **756** along the ridges **758** when there is sufficient space to do so.

(312) Embodiments described herein can provide a number of benefits. For example, during an electrosurgical procedure, a portion of the generated smoke can be captured and transited to a smoke evacuation system for processing and filtration. As the smoke may include particulates and gaseous pollutants, which can potentially be toxic if inhaled, decrease visibility, or at the very least be potentially odoriferous, it is advantageous to filter the smoke to a more purified state. The smoke filters described above can enable smoke to be adequately filtered.

(313) Additionally, the smoke filters described above can prevent inefficiencies associated with gap formation when the charcoal reservoir is compacted from a starting volume to a smaller settled volume. For example, the carbon reservoir of smoke filter may compress to a smaller settled volume when under constant pressure of suction from the smoke evacuation device. This may cause gaps to form within the carbon reservoir, and smoke entering into the carbon reservoir to be filtered can pass around or through the gaps minimizing the surface area contact within the carbon reservoir. This reduced surface area contact can result in less adsorption of contaminants, and in some extreme instances, a channel may be formed partially or entirely around the carbon reservoir preventing filtration therethrough. In some embodiments, settling of the carbon particles within the reservoir may cause the carbon particles to fill a smaller spatial volume regardless of pressure. The addition of one or more flexible porous barriers and/or flexible sleeves can provide a compression bias against the particles within the carbon reservoir such that any decrease in volume causes the flexible porous barrier and/or flexible sleeve to contract inward, preventing gaps from forming.

(314) By maintaining a solid carbon reservoir without gaps, the efficiency of the filter can be maintained or increased. Smoke being filtered through the carbon reservoir maintains contact with the surface area of carbon particles more consistently as it traverses the reservoir in beneficially increasing the efficiency of the filter.

(315) Remote Activation

(316) As explained in greater detail below, embodiments of electrosurgical systems according to the present disclosure enable efficient activation and dynamic capture of smoke generated during an electrosurgical procedure. For example, vacuum suction originating from the smoke evacuation device **120** can be activated and/or adjusted by a sensor that detects activation of RF current and turns on the vacuum suction in response to detecting activation of RF current and that monitors the RF current, adjusting the flow rate and/or temporal duration of vacuum suction based on the monitored RF current.

(317) Current smoke evacuation devices are inefficient and unresponsive to user interaction with components of electrosurgical systems. For example, current smoke evacuation devices are typically turned on or activated before the electrosurgical procedure begins, and the smoke evacuation device is left running for the duration of the electrosurgical procedure. In doing so, any

smoke generated during the procedure can be captured and collected from the surgical site and conveyed to the smoke evacuation device for filtering and processing. However, smoke is not continually generated, leaving the smoke evacuation device to convey and filter/process environmental air during non-smoke-generating periods.

(318) In some instances, the smoke filter associated with the smoke evacuation device is monitored for a total number of hours used. That is, the total amount of time the smoke evacuation device is on and providing suction—and therefore pulling air through the smoke filter—is the determinative factor for calculating the life span of the smoke filter, regardless of how many hours the smoke filter was actually being used to filter smoke. Even if the smoke filter was processing relatively clean environmental air for 90% of its temporal life span and would otherwise be deemed clean/useable, many regulations and protocols require the smoke filter to be replaced after so many hours of use. These precautions are intended to guard against the use of clogged or dirty filters, but in practice, it typically results in a tremendous amount of product waste, increased costs, and other inefficiencies within electrosurgical systems.

(319) Additionally, most smoke evacuation devices are not responsive to the variable amount of smoke that can be created throughout an electrosurgical procedure. For example, a great deal of smoke may be generated at various interspersed times during the procedure such as when first cutting tissue at the surgical site or during excision or repair of tissue, whereas at other times, there may be little or no smoke generated such as when the surgeon is performing small delicate incisions or when the surgeon is not using the electrosurgical instrument at all. Regardless of the smoke generation, the smoke evacuation device is likely to be providing constant suction.

(320) In some embodiments, the amount of suction can be manually adjusted, but doing so may detract from the task at hand and can be burdensome to continually monitor and adjust. Further, it may be the case that by the time the user realizes that additional suction is required due to an increased production of smoke, it is likely too late. By the time the suction is adjusted, the smoke will have likely dissipated, making it difficult—if not impossible—to adequately capture and convey to the smoke evacuation device.

(321) One or more embodiments disclosed herein beneficially enable the detection of electrical current within an electrosurgical system and initiate a corresponding activation or modulation of vacuum suction at the smoke evacuation device. Additionally, in some embodiments, a treatment power is derived from the detected current, and based on the derived treatment power, the smoke evacuation device is activated for a defined duration and/or at a defined smoke evacuation flow rate. In some embodiments, the derived treatment power is used to calculate an estimated smoke production, and the smoke evacuation device is activated for a defined duration and/or at a defined smoke evacuation flow rate based on the estimated smoke production.

(322) In some embodiments, an RF current sensor is configured to operate in at least two modes—a first mode and a second mode—and includes a sensor body having at least a cable interfacing sidewall and a retaining member. The cable interfacing sidewall and the retaining member define a retention pocket configured to receive a cable communicating RF current. The RF current sensor additionally includes a sensor element for detecting RF current in the cable and a sensor cable in electrical communication with the sensor element. The sensor cable communicates one or more of an activation signal or a current signal derived from the detected RF current to the smoke evacuation device.

(323) In some embodiments, a method for remote activation of a smoke evacuation device includes generating an RF current at a signal generator, communicating the RF current through a source cable to an electrosurgical instrument, detecting an activation of RF current with an RF current sensor communicatively coupled to a smoke evacuation device, communicating an activation signal from the RF current sensor to the smoke evacuation device in response to detecting the activation of RF current, receiving the activation signal at the smoke evacuation device, and activating a vacuum source for one or more of a defined period of time or to generate a defined smoke

evacuation flow rate in response to receiving the activation signal.

(324) In some embodiments, an electrosurgical system includes a signal generator producing an RF current, a source cable electrically coupled to the signal generator and to an electrosurgical instrument, the source cable communicating the RF current from the signal generator to the electrosurgical instrument, a smoke evacuation device that includes a vacuum hose positioned proximate the electrosurgical instrument and configured to evacuate smoke generated by the electrosurgical instrument, and an RF current sensor communicatively coupled to the smoke evacuation device, the RF current sensor activating the smoke evacuation device in response to identifying the RF current.

(325) Such foregoing embodiments of the present disclosure along with additional, or alternative, embodiments described herein can provide a number of benefits. For example, during an electrosurgical procedure, an electrosurgical instrument can be activated for a variable amount of time and/or for variable durations, and this can directly affect the amount and timing of smoke generated during the electrosurgical procedure. Implementations of the present application beneficially enable an associated smoke evacuation device to be activated in response to activation of the electrosurgical instrument and concomitant smoke generation instead of being run constantly. This will reduce the overall time the smoke evacuation device is activated during individual procedures and thereby provide energy savings and increase the life of the smoke evacuation device and/or its components. For example, smoke filters associated with the smoke evacuation device can benefit from an increased life span and/or be more efficiently used by predominantly filtering smoke instead of passively filtering air from a constantly running smoke evacuation device.

(326) In another example, the ability to detect current activation, intensity, and/or duration allows implementations of the present disclosure to adjust the flow rate to accommodate an estimated increase or decrease in smoke generation, thereby providing automatic, dynamic, and responsive smoke evacuation without burdensome oversight, monitoring, or manual adjustments. This can beneficially reduce any visibility reduction, odor, and other problems associated with smoke generation. In some instances, this can enable electrosurgical procedures that generate greater amounts of smoke to be performed or to be performed with less ancillary equipment (e.g., less additional independent vacuum hoses, fans, and other air management equipment) as it can dynamically respond to the smoke generated during the electrosurgical procedure.

(327) Referring now to FIGS. 56 and 57, illustrated are perspective and elevation views, respectively, of an exemplary RF current sensor **800**. As shown, the RF current sensor **800** includes a sensor body **802** defining most of the visible exterior surfaces of the RF current sensor **800**. The RF sensor **800** is associated with a sensor cable **806** at a first end thereof and is retained in place or coupled to the RF sensor **800** by grommet **808**. Although depicted as being disposed on a short side of the RF current sensor **800**, in some embodiments, the grommet **808** and/or the sensor cable **806** can be disposed on/through any front, side, top, or bottom surface of the RF current sensor **800**.

(328) As perhaps best shown in FIG. 57, the sensor body **802** includes a cable interfacing sidewall **804** that at least partially defines a retention pocket **810**. The retention pocket is also at least partially defined by the retaining member **812**. The retaining member **812** is configured to flex or bend, and in some embodiments—and as illustrated in FIGS. 56 and 57—the RF current sensor **800** can be shaped to accommodate the bending or flexing of the retaining member **812**. For example, the sensor body **802** includes a recess sidewall **814** that together with the retaining member **812** and protruding ridge **818** at least partially define a recess **816** into which the retaining member **812** can bend or flex.

(329) The retaining member **812** is illustrated as having a substantially linear lower body that is substantially parallel with the opposing cable interfacing sidewall **804** followed by an arcuate upper body that initially creates a concavity directed towards the retention pocket **810** and narrowing the distance between the cable interfacing sidewall **804** and the retaining member **812**. The narrowed

distance can serve to prevent unintentional attachment of the RF current sensor **800** to other objects and can also serve to prevent the RF current sensor **800** from unintentionally detaching from an object (e.g., a cable) disposed within the retention pocket **810**.

(330) In some embodiments, the retaining member **812** can be biased or flexed towards the recess sidewall **814** and/or into the recess **816**, widening the distance between the upper body of the retaining member **812** and the cable interfacing sidewall **804**. By doing so, an object can be passed into the retention pocket **810**, wherein upon release of the flexed retaining member **812**, the object is secured within the retention pocket **810** (e.g., the retaining member **812** mechanically blocks egress of the object from the retention pocket **810**).

(331) Additionally, the protruding ridge **818** alone, or in combination with the stop member **815** running substantially parallel thereto, can act to prevent unintentional insertion of an object within the recess **816**, which could prevent the retaining member **812** from flexing into the recess **816**. Additionally, the length of the stop member **815** and/or the corresponding depth of the recess **816** can act to autoregulate the diameter of cable that can be inserted into the retention pocket **810**. For example, a shorter stop member (assuming the same recess **816** depth) will allow the retaining member to flex more, widening the opening and allowing larger diameter cables to enter the retention pocket **810**. On the other hand, a longer stop member (again assuming the same recess **816** depth) will prevent the retaining member from flexing and provide a narrower opening through which only smaller diameter cables can pass and enter the retention pocket **810**. It should be appreciated that the depth of the corresponding recess **816** can similarly affect the diameter of cable that may enter the retention pocket **810**. For example, a deeper recess (assuming the same stop member **815**) will allow the retaining member to flex more, widening the opening and allowing larger diameter cables to enter the retention pocket **810** while a shallower recess (again assuming the same stop member **815**) will prevent the retaining member from flexing and provide a narrower opening through which only smaller diameter cables can pass and enter the retention pocket **810**.

(332) In some embodiments, the stop member **815** and/or the recess **816** are sized to allow a source cable **110** or a return cable **118** to enter the retention pocket **810**. Additionally, or alternatively, the stop member **815** and/or the recess **816** are sized to prevent admission of other cables into the retention pocket **810**, such as a power cable for the generator **102** or a power cable for the smoke evacuation device **120** or to prevent admission of cable-like objects such as the vacuum hose **112**.

(333) The length and configuration of the retaining member **812** and stop member **815** with respect to other features of the RF current sensor **800** can provide additional benefits. For example, the retaining member **812** is contained within the six spatial planes that define the generally box-shaped RF current sensor **800** (e.g., as shown in FIG. 56). That is, the retaining member **812** does not extend or protrude in any direction outside of body of the RF current sensor **800**, and this configuration beneficially protects the retaining member from catching on other cables, which could break the retaining member **812**. This configuration also protects the retaining member **812** from impact damage if the RF current sensor **800** is dropped or stepped on. Further, because the retaining member **812** is not confluent with any of the six structural sidewalls that make up the box-like dimensions of the RF current sensor **800**, it is protected from breakage resulting from a forceful extraction or insertion of a cable into the retention pocket. Additionally, the hard stop relationship between the stop member **812** and the recess **815** allow elastic deformations to the retaining member **812** while preventing plastic deformations or fracturing.

(334) It should be appreciated that the retaining member **812** should not be limited to the exemplary illustration provided in FIGS. 56 and 57. Rather, in some embodiments, the retaining member can include any type or combination of geometries and spatial association with the cable interfacing sidewall. As a non-limiting example, the retaining member can include a horizontal member that encloses the retention pocket similar in form and function to a lid or latch.

Additionally, the recess and/or protruding ridge may be omitted, in some embodiments-such as in the foregoing example. It should be noted, however, that embodiments including a horizontal

member or that remove the horizontal member or the stop member may not benefit from all of the aforementioned advantages afforded to retaining member **812** of FIG. **57**.

(335) In some embodiments, the object retained within the retention pocket **810** is a cable. The cable can be any cable but preferably, the cable includes a source cable **110** or a return cable **118** associated with an electrosurgical system. The cable can serve as a conduit for transmitting RF current from a signal generator **102** to an electrosurgical instrument **104**. In the case of a bipolar electrosurgical instrument, the cable can serve as both a source cable and a return cable. In the case of a monopolar electrosurgical instrument, the cable can be one or both of the source cable **110** electrically coupled between the signal generator **102** and the electrosurgical instrument **104** or the return cable **118** electrically coupled between the return electrode **106** and the signal generator **102**.

(336) When the cable is disposed within the retention pocket **810**, the RF current sensor **800** can detect activation of the RF current through the cable and/or the RF current passing through the cable. In some embodiments, and as shown in FIG. **58**, the RF current sensor **800** can include a sensor element **820** housed within the sensor body **802** that detects the activation and/or current of the RF current passing through the cable retained within the retention pocket **810**. The sensor element **820** can be any sensor that can detect current within the cable, including, for example, an RF current sensor.

(337) In some embodiments, it may be difficult to detect activation of RF current and/or RF current with a single pass of the cable through the retention pocket **810**. In a monopolar system, the RF current signal from the cable can be amplified by looping the cable multiple times through the retention pocket **810**. In a bipolar system, the RF current signal can be amplified by separating the source and return strands and looping one of the source or return strands—but not the other—multiple times through the retention pocket **810**.

(338) Additionally, or alternatively, it may be advantageous for the sensor element to register detection of RF current above a lower or baseline threshold. For example, a cable may include a low base level of current passing therethrough, even when the electrosurgical instrument is not being used, which could give a false positive indication of RF current passing therethrough. In some embodiments, the baseline threshold is at least 1 mA, at least 5 mA, at least 10 mA, at least 25 mA, at least 50 mA, at least 75 mA, at least 100 mA, at least 150 mA, at least 200 mA, at least 300 mA, at least 400 mA, at least 500 mA, at least 600 mA, at least 700 mA, at least 800 mA, or at least 900 mA.

(339) In addition to the sensor element **820**, the sensor body **802** can house various additional internal components of the sensor **800**. For example, as illustrated in FIG. **58**, the RF current sensor **800** can include a printed circuit board (or similar electronic medium) in electrical communication with the sensor element **820** and which is also in electrical communication with a lead **824**. The lead **824** can, in some embodiments, transmit analog data detected and transmitted by the sensor element **820**. Additionally, or alternatively, the lead **824** can transmit digital data representative of the signal data (e.g., an activation signal and/or a current signal) detected by the sensor element **820**.

(340) In some embodiments, the sensor cable **806** communicates an activation signal or a current signal derived from the detected RF current to a smoke evacuation device. When received by the smoke evacuation device, the activation signal and/or current signal, can cause a vacuum source to be activated for a period of time and/or cause the vacuum source to generate a defined smoke evacuation flow rate. In some embodiments, the activation signal and/or the current signal are proportional to the detected RF current and thereby cause an effect at the smoke evacuation device that is commensurate with the detected signal.

(341) For example, if the RF current sensor detects activation of the RF current, the sensor cable can communicate instructions to the smoke evacuation device to turn on the vacuum system to a low setting. If the RF current sensor fails to detect RF current thereafter, the sensor cable can communicate instructions to the smoke evacuation device to deactivate the vacuum system. In

some embodiments, the deactivation is immediate. In other embodiments, the vacuum system runs for a defined period of time to ensure capture and conveyance of any smoke generated at the surgical site. It should be appreciated that the sensor cable can communicate any pre-defined (e.g., turn vacuum system on high) or user-defined instruction in response to the RF current sensor detecting activation of the RF current through the associated cable.

(342) As an additional example, the if the RF current sensor detects activation of the RF current followed by sustained RF current, the sensor cable can communicate instructions to the smoke evacuation device to create a high smoke evacuation flow rate (e.g., by turning the vacuum system on its highest setting).

(343) In some embodiments, the sensor cable **806** is physically coupled to the RF current sensor **800** and can electrically communicate with the RF current sensor **800** and the smoke evacuation device **120**. In some embodiments, the sensor cable **806** is also physically coupled to the smoke evacuation device **120**. In yet other embodiments, the sensor cable communicates wirelessly with the smoke evacuation device.

(344) As provided above, the RF current sensor **800** can, in some embodiments, selectively clip onto a source cable **110** and/or a return cable **118** and be retained thereon, detecting RF activation events and/or RF current through the cable **110**, **118**. For example, as illustrated in FIG. 59, an electrosurgical system **830** can include a signal generator **102** that generates an RF current and communicates the RF current to an electrosurgical instrument **104** (illustrated as a monopolar electrosurgical instrument) through a source cable **110**. The RF current is transmitted through the patient and received at the return electrode **106**, completing the circuit to the signal generator **102** through return cable **118**. As illustrated, a vacuum hose **112** extends from the smoke evacuation device **120** to the surgical site proximate the electrosurgical instrument **104** and is positioned to extract smoke generated by the electrosurgical instrument **104** and convey the smoke to the smoke evacuation device **120** for filtering/processing.

(345) The electrosurgical system **830** additionally includes an RF current sensor **800** removably associated with the source cable **110** and connected to the smoke evacuation device **120** by sensor cable **806**. The RF current sensor **800** can detect an activation of RF current passing through the source cable **110**, and in response to detecting the activation of RF current, the RF current sensor **800** can communicate an activation signal to the smoke evacuation device **120**. In response to receiving the activation signal, the smoke evacuation device **120** can activate a vacuum source for a defined period of time or to generate a defined smoke evacuation flow rate. In some embodiments, the defined period of time or the defined smoke evacuation flow rate is proportional to the activation signal or a plurality of previously detected activation signals. For example, if the RF current sensor **800** detects a series of RF activation events in close temporal proximity, the RF current sensor **800** can instruct the smoke evacuation device **120** to activate the vacuum system for a prolonged period of time, as the plurality of detected activation signals can be indicative of successive electrosurgical events that can in the aggregate generate sufficient smoke to warrant prolonged smoke evacuation.

(346) It should be appreciated that the RF current sensor **800** can additionally, or alternatively, detect RF current through source cable **110** and communicate instructions to the smoke evacuation device **120** in a similar fashion as described above.

(347) As shown in FIG. 60, an electrosurgical system **840** can include a similar setup as described above with respect to electrosurgical system **830**. That is, an electrical circuit for transmitting RF current can be formed from the signal generator **102**, to a source cable **110**, electrosurgical instrument **104**, return electrode **106**, and return cable **118**, completing the electrical circuit at the signal generator **102**. Instead of the RF current sensor **800** being positioned on the source cable **110**, as described above with respect to FIG. 59, the RF current sensor **800** is removably attached to the return cable **118**. However, similar to the RF current sensor **800** of FIG. 59, the RF current sensor **800** of FIG. 60 is connected to the smoke evacuation device **120** by sensor cable **806**.

(348) The RF current sensor **800** of FIG. **60** can detect an activation of RF current passing through the return cable **118**, and in response to detecting the activation of RF current, the RF current sensor **800** can communicate an activation signal to the smoke evacuation device **120**. Similarly, it should be appreciated that the RF current sensor **800** can additionally, or alternatively, detect RF current through return cable **118** and communicate instructions to the smoke evacuation device **120** in a similar fashion as described above.

(349) As shown in FIG. **61**, an electrosurgical system **850** can include a similar setup as described above with respect to electrosurgical systems **830** and **840**. That is, an electrical circuit for transmitting RF current can be formed from the signal generator **102**, to a source cable **110**, electrosurgical instrument **104**, return electrode **852**, and return cable **118**, completing the electrical circuit at the signal generator **102**. However, instead of the RF current sensor **800** being releasably connected to the source cable **110** (as in FIG. **59**) or to the return cable **118** (as in FIG. **60**), the RF current sensor **854** is integrally formed within the return electrode **852**. The return electrode **852** includes pigtails or other electrical outlets that electrically couple the return electrode **852** to the signal generator **102**, thereby completing the circuit, and also allow electrical coupling of the return electrode **852** with the smoke evacuation device **120** through a sensor cable **856**.

(350) The RF current sensor **854** within the return electrode **852** detects RF current activation as the RF current is received and passes through the return electrode **852**. Additionally, the RF current sensor **854** can detect RF current passing through return electrode **852**. In response to the current sensor **854** detecting RF current activation and/or the RF current passing through the return electrode **852**, the current sensor **854** can communicate with the smoke evacuation device **120** to activate and modulate smoke evacuation flow rate and/or a period of time the smoke evacuation device **120** is activated, as described herein.

(351) In some embodiments, and as illustrated in FIG. **62**, a smoke evacuation device **662** can include an RF current sensor integrally formed therein. In the electrosurgical system **860** incorporating the smoke evacuation device **862**, a signal generator **102** can generate an RF current and communicate the RF current to an electrosurgical instrument **104** (again illustrated as a monopolar electrosurgical instrument) through the resource cable **110**. The RF current is transmitted through the patient and received at the return electrode **106** and completes the circuit to the signal generator **102** by passing through the smoke evacuation device **862** along a series of return cables **864**, **866**. More particularly, the RF current is passed between the return electrode **106** and the smoke evacuation device **862** via first return cable **864**, and the RF current is passed between the smoke evacuation device **862** and the signal generator **102** via second return cable **866**. As the RF current passes through the smoke evacuation device **862**, the integrally formed RF current sensor can detect one or both of an RF activation event or RF current passing therethrough. Upon detecting activation of RF current and/or RF current passing through the smoke evacuation device **862**, the integrally formed RF current sensor can communicate directly or indirectly with the vacuum system to activate and/or modulate airflow into the smoke evacuation device for a defined or dynamic period of time.

(352) In some embodiments, the RF current sensor can dynamically adjust the smoke evacuation flow rate in response to a sensed treatment current. For example, as shown in the graph **870** illustrated in FIG. **63**, the smoke evacuation flow rate can be dynamically adjusted based on the current detected by the RF current sensor. As the current increases, the flow rate increases, and as the current decreases, the flow rate decreases.

(353) It should be appreciated that although graph **870** illustrates a smoke evacuation curve **872** having a linear relationship between the sensed treatment current in the smoke evacuation flow rate, other relationships are possible. For example, the smoke evacuation flow rate may increase logarithmically or exponentially with respect to a sensed treatment current. In some embodiments, it may be advantageous to increase the smoke evacuation flow rate rapidly at the lower end of the sensed treatment current to ensure that any smoke generated at the surgical site has sufficient

suction port extraction and conveyance to the smoke evacuation device.

(354) In some embodiments, it may be advantageous to increase the smoke evacuation flow rate slowly at the lower end of the sensed treatment current within a rapid increase in the smoke evacuation flow rate before, at, or after the predefined treatment current or smoke generation is known to occur. In doing so, the smoke evacuation device is not activated until smoke is presumed to be generated, thereby preserving the life of the smoke evacuation device or components thereof, such as the smoke filter.

(355) In some embodiments, the detected current can be used to derive an estimate of the treatment power delivered to tissue, and in turn, the estimated treatment power delivered to tissue can be correlated with a tissue effect and the smoke generated as a result of such a tissue effect.

Accordingly, in some embodiments, the detected current can be used to infer an estimated amount or volume of smoke, and that information can be used to dynamically adjust the smoke evacuation flow rate. For example, as illustrated in the graph **880** of FIG. **64**, an amount or volume of estimated smoke generation can be derived based on the detected current, and the smoke evacuation flow rate can be adjusted accordingly.

(356) In one embodiment, and as represented by the first smoke evacuation curve **882**, the smoke evacuation flow rate can correlate with an estimated smoke generation in a logarithmic fashion. In another embodiment, and as represented by the second smoke evacuation curve **884**, smoke evacuation flow rate can correlate with an estimated smoke generation in a polynomial or exponential fashion. In some embodiments, the smoke evacuation flow rate can correlate with an estimated smoke generation linearly (not shown).

(357) Thus, implementations of the present disclosure enable a smoke evacuation flow rate to be dynamically modified in a way that is proportional to and/or dependent upon the current detected by the current sensor. In some embodiments, however, the direct correlation between the detected current in the smoke evacuation flow rate may not be optimal. For example, different currents may affect tissue differently and thereby cause differential smoke production that is difficult to account for when only correlating the detected current and the smoke evacuation flow rate. Furthermore, continued exposure to single or different currents may result in a smoke plume that would be unaccounted for when only correlating the detected current in the smoke evacuation flow rate.

(358) Accordingly, implementations of the present disclosure further enable a smoke evacuation flow rate to be dynamically modified in a way that is proportional to and/or dependent upon a tissue effect and resulting smoke generation that is caused by a given treatment power. In some embodiments, the energy associated with an activation of RF current can be estimated by multiplying the treatment power by the activation time. The estimated energy can be correlated with an amount or volume of smoke produced from exposure to the estimated energy, and the smoke evacuation flow rate can be adjusted based on this amount or volume of smoke.

(359) Similarly, the energy associated with a plurality of activations of RF current and/or energy associated with continuous RF current can be estimated by multiplying the treatment power by the activation time for each activation of RF current and/or exposure to continuous RF current. The total estimated energy can be correlated with an amount or volume of smoke produced from exposure to the total estimated energy, and the smoke evacuation flow rate can be adjusted based on this amount or volume of smoke.

(360) While the embodiments described herein have been directed to electrosurgical instruments with smoke evacuation features, the present disclosure is not intended to be so limited. Rather, the present disclosure is broadly directed to any hand-held instrument that includes fluid (e.g., liquids, gases, vapors, smoke, or combinations thereof) evacuation or delivery features as described herein. By way of non-limiting example, such hand-held instruments may include dental instruments (e.g., drills, polishing tools, scalers, compressed air tools, suction tools, irrigation tools, carries detection tools, water flossing tool (e.g., waterpik)), soldering tools (e.g., heated tools, smoke collection tools, de-soldering tools), high speed grinding and polishing tools (e.g., Dremel tools, carving

tools, manicure tools, dental lab grinders/polishers), laser treatment instruments, laser surgical instruments, light probes, suction handles (e.g., Yankauer), blasting tools (e.g., sandblast, gritblast), shockwave therapy tools, ultrasonic therapy tools, ultrasonic probe tools, ultrasonic surgical tools, adhesive application instruments, glue guns, pneumatic pipettes, welding tools, RF wrinkle therapy hand pieces, phaco hand pieces, shears, shaver, or razor hand pieces, micro drill hand pieces, vacuum hand pieces, small parts handling hand pieces, tattoo needle handles, small torch hand pieces, electrology hand pieces, low speed grinding, polishing and carving tools, permanent makeup hand pieces, electrical probe hand pieces, ferromagnetic surgical hand pieces, surgical plasma hand pieces, argon beam surgical hand pieces, surgical laser hand pieces, surgical suction instruments (e.g., liposuction cannulas), surgical suction cannulas, microdermabrasion hand pieces, fiberoptic camera handles, microcamera hand pieces, pH probe hand pieces, fiberoptic and LED light source hand pieces, hydrosurgery hand pieces, orthopedic shaver, cutter, burr hand pieces, wood burning tools, electric screwdrivers, electronic pad styluses, and the like.

(361) The present invention may be embodied in other specific forms without departing from its spirit or essential characteristics. The described embodiments are to be considered in all respects only as illustrative and not restrictive. The scope of the invention is, therefore, indicated by the appended claims rather than by the foregoing description. All changes which come within the meaning and range of equivalency of the claims are to be embraced within their scope.

Claims

1. A filter, comprising: a filter body; a front cap associated with a first end of the filter body, the front cap being configured to couple to and receive smoke from a vacuum hose; a back cap associated with a second end of the filter body, the back cap having a filter exhaust that is sized and shaped to associate with and communicate suction from a smoke evacuation system; a compressed carbon reservoir disposed within the filter body between the front cap and the back cap; and a flexible sleeve extending at least partially between the front and back caps and at least partially around the compressed carbon reservoir, the flexible sleeve being biased towards the compressed carbon reservoir to compress the carbon reservoir.
2. The filter of claim 1, wherein the flexible sleeve extends circumferentially about the compressed carbon reservoir.
3. The filter of claim 2, wherein the flexible sleeve is configured to compress the compressed carbon reservoir towards a center thereof.
4. The filter of claim 1, wherein the flexible sleeve extends circumferentially about only a portion of the compressed carbon reservoir.
5. The filter of claim 4, wherein the flexible sleeve is configured to compress the compressed carbon reservoir towards a side of the filter opposite the flexible sleeve.
6. The filter of claim 1, further comprising first and second porous dividers disposed at opposing ends of the compressed carbon reservoir.
7. A filter, comprising: a filter body having a first end and an opposing second end; a front cap associated with the first end of the filter body, the front cap being configured to couple to and receive smoke from a vacuum hose; a back cap associated with the second end of the filter body, the back cap having a filter exhaust that is sized and shaped to associate with and communicate suction from a smoke evacuation system; a compressed carbon reservoir disposed within the filter body between the front cap and the back cap; a first porous divider disposed between the compressed carbon reservoir and the back cap; and a second porous divider disposed between the compressed carbon reservoir and the front cap, the second porous divider being formed of a rigid material and being configured to move towards the first porous divider when the volume of the compressed carbon reservoir decreases.
8. The filter of claim 7, wherein the second porous divider is configured to successively engage a

- plurality of ridges associated with the interior of the filter body when the volume of the compressed carbon reservoir decreases.
9. The filter of claim 8, wherein the second porous divider is weighted such that it successively engages the plurality of ridges associated with the interior of the filter body when the volume of the compressed carbon reservoir decreases.
10. The filter of claim 8, wherein the second porous divider is configured to successively engage the plurality of ridges associated with the interior of the filter body in response to a negative pressure within the compressed carbon reservoir.
11. The filter of claim 7, further comprising a biasing member configured to move the second porous divider towards the first porous divider when the volume of the compressed carbon reservoir decreases.
12. The filter of claim 11, wherein the biasing member comprises a flexible member.
13. The filter of claim 12, wherein the flexible member comprises a spring member that forces the second porous member to maintain contact with carbon particles within the compressed carbon reservoir.
14. The filter of claim 13, wherein spring member is configured to move the second porous member successively along a plurality of ridges associated with the interior of the filter body when the volume of the compressed carbon reservoir decreases.
-