

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409051
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Beyer; Morten

Spine cage holder

Abstract

A cage holder includes an elongated body having a proximal end and a distal end, the elongated body extending from the proximal end to the distal end. The cage holder further includes means for transferring energy centrally from the proximal end to the distal end through the elongated body.

Inventors:	Beyer; Morten (Rødkaersbro, DK)
Applicant:	Neo Medical SA (Villette, CH)
Family ID:	66102723
Assignee:	Neo Medical SA (Villette, CH)
Appl. No.:	18/191383
Filed:	March 28, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230225882 A1	Jul. 20, 2023

Foreign Application Priority Data

WO	PCT/IB2018/051188	Feb. 26, 2018
----	-------------------	---------------

Related U.S. Application Data

continuation parent-doc US 16969212 US 11628070 WO PCT/IB2019/051520 20190226 child-doc US 18191383

Publication Classification

Int. Cl.: A61F2/46 (20060101); **A61F2/44** (20060101)

U.S. Cl.:

CPC **A61F2/4611** (20130101); **A61F2/4455** (20130101); A61F2002/4681 (20130101);
A61F2310/00017 (20130101); A61F2310/00023 (20130101); A61F2310/00047
(20130101); A61F2310/00107 (20130101); A61F2310/00131 (20130101);
A61F2310/00149 (20130101)

Field of Classification Search

CPC: A61F (2/46); A61F (2/4603); A61F (2/4611); A61F (2002/4625); A61F (2002/4627);
A61F (2002/4629)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5913860	12/1998	Scholl	N/A	N/A
8088163	12/2011	Kleiner	N/A	N/A
9107768	12/2014	Schell	N/A	A61F 2/4455
9226835	12/2015	Schell	N/A	A61B 17/7064
9265622	12/2015	Schell	N/A	A61F 2/447
9566170	12/2016	Schell	N/A	A61B 17/1757
11628070	12/2022	Beyer	623/17.11	A61F 2/4455
2002/0016592	12/2001	Branch	606/279	A61F 2/4611
2005/0240197	12/2004	Kmiec	N/A	N/A
2010/0298941	12/2009	Hes	623/17.16	A61F 2/4425
2011/0230965	12/2010	Schell	606/86A	A61B 17/7064
2013/0226186	12/2012	Burgi	606/91	A61F 2/4609
2014/0194993	12/2013	Schell	623/17.16	A61B 17/1757
2014/0214164	12/2013	Schell	623/17.11	A61F 2/4611
2014/0214165	12/2013	Schell	623/17.11	A61F 2/4455
2015/0045892	12/2014	Lynn	623/17.16	A61B 17/1671
2015/0238327	12/2014	Cheng	623/17.16	A61F 2/447
2016/0135963	12/2015	Kerboul	606/91	A61F 2/4609
2016/0235448	12/2015	Seex	N/A	A61B 17/808
2016/0374825	12/2015	Kleiner	N/A	N/A
2017/0042696	12/2016	Larsson	N/A	N/A
2017/0100260	12/2016	Duffield	N/A	A61F 2/4611
2017/0340358	12/2016	Bullard	N/A	A61B 17/1757

2019/0374350	12/2018	Milz	N/A	B25B 23/1427
2020/0352739	12/2019	Ouidja	N/A	A61F 2/30749
2020/0405504	12/2019	Beyer	N/A	A61F 2/4455
2021/0015630	12/2020	Wall	N/A	A61F 2/4603
2021/0393408	12/2020	Ginn	N/A	A61F 2/4611
2021/0393409	12/2020	Ginn	N/A	A61B 6/032
2022/0031472	12/2021	Bruffey	N/A	A61F 2/4455
2022/0151800	12/2021	Huh	N/A	A61F 2/4611
2023/0225882	12/2022	Beyer	623/17.11	A61F 2/4455

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
105662662	12/2015	CN	N/A
1124510	12/2000	EP	N/A
2016511082	12/2015	JP	N/A
WO-2014088521	12/2013	WO	A61F 2/442
2014/159739	12/2013	WO	N/A
2014159027	12/2013	WO	N/A
2015/162514	12/2014	WO	N/A

OTHER PUBLICATIONS

International Search Report dated Jun. 11, 2019 for Application N° PCT/IB2019/051520. cited by applicant

Written Opinion of the ISA dated Jun. 11, 2019 for Application N° PCT/IB2019/051520. cited by applicant

Office Action, issued in Japanese Patent Application No. 2020-543280 dated Feb. 28, 2023. cited by applicant

Office Action, issued in Japanese Patent Application No. 2020-543280 dated Oct. 17, 2023. cited by applicant

Primary Examiner: Gibson; Eric S

Attorney, Agent or Firm: NIXON & VANDERHYE

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation application of U.S. patent application Ser. No. 16/969,212 filed on Aug. 12, 2020, which is the U.S. national phase of International Application No. PCT/IB2019/051520 filed on Feb. 26, 2019, which designated the U.S. and claims priority to international patent application PCT/IB2018/051188 filed on Feb. 26, 2018, the entire contents of each of which are hereby incorporated herein by reference.

FIELD OF THE INVENTION

(1) The present invention concerns a cage holder and more particularly a spine cage holder. The device can be used for handling or manipulating, for example, a spine cage used for spinal fusion between two or more vertebrae of the spine.

BACKGROUND

(2) During the insertion or placement of a spine cage between vertebrae of a patient it is often necessary to force the cage into a desired position between vertebrae thus requiring a force, such as a mechanical force, to be applied by for example hammering on the end of a cage holder to which a spinal cage is attached.

(3) Known cage holders require repeated application of such a force to be applied to the cage holder to achieve a correct placement or positioning of the spine cage and thus complicates the surgical procedure or increases the risk of injury to the surgeon or patient.

(4) WO2015162514 discloses an example of a spine cage.

SUMMARY

(5) The goal of the present invention is to provide a cage holder that overcomes the above-mentioned inconvenience. In particular, a goal of the present invention is to assure that repeated application of such a force is avoided or at least minimized.

(6) The present invention is thus a cage holder including an elongated body comprising a proximal end and a distal end, the elongated body extending from the proximal end to the distal end; and means for transferring energy centrally from the proximal end to the distal end through the elongated body.

(7) The means for transferring energy centrally can be at least partially enclosed by the elongated body (3).

(8) The cage holder according to the present invention advantageously includes means for transferring energy centrally from a proximal end to a distal end through the cage holder. This permits mechanical energy to be channeled through the core of the cage holder and guided directly to the cage for an efficient transfer of energy thus assuring that a repeated application of a force is not required or at least minimized.

(9) Other advantageous features can be found in the dependent claims.

(10) According to an aspect of the present disclosure, the means for transferring energy is configured to transfer energy centrally through the cage holder in a longitudinal direction of the cage holder.

(11) According to another aspect of the present disclosure, the means for transferring energy is configured to transfer energy centrally through the cage holder in a longitudinal direction of the cage holder from an outer extremity of the proximal end of the cage holder to an outer extremity of the distal end of the cage holder.

(12) According to another aspect of the present disclosure, the means for transferring energy centrally includes a cage holding or cage attachment means at a distal end.

(13) According to an aspect of the present disclosure, the means for transferring energy centrally includes a member extending from the proximal end to the distal end of the elongated body, the member comprising or consisting of a first material and the elongated body comprising or consisting of a second material different to the first material.

(14) According to an aspect of the present disclosure, the first material has a higher material density than the second material.

(15) According to another aspect of the present disclosure, the member has a higher rigidity or a lower flexibility than the elongated body.

(16) According to another aspect of the present disclosure, the means for transferring energy centrally includes a tube extending from the proximal end to the distal end of the elongated body.

(17) According to another aspect of the present disclosure, the means for transferring energy centrally includes a tube extending from the proximal end of the cage holder to the distal end of the cage holder.

(18) According to another aspect of the present disclosure, the tube extends from an outer extremity of the proximal end of the cage holder to an outer extremity of the distal end of the cage holder.

(19) According to another aspect of the present disclosure, the elongated body delimits a passage in

which the tube is located and/or held therein.

(20) According to another aspect of the present disclosure, the passage extends from an outer extremity of the proximal end of the elongated body to an outer extremity of the distal end of the elongated body.

(21) According to another aspect of the present disclosure, the tube is or defines a hollow tube; or the tube is a non-hollow solid tube or solid rod.

(22) According to another aspect of the present disclosure, an external wall of the tube is located at a distance of at least 0.1 mm from the central longitudinal axis of the cage holder.

(23) According to another aspect of the present disclosure, an external wall of the tube is located at a distance of between 0.5 mm and 5 mm from a central longitudinal axis of the cage holder.

(24) According to another aspect of the present disclosure, the central longitudinal axis of the cage holder is located at a geometric center or center of symmetry of the cage holder and/or the elongated body.

(25) According to another aspect of the present disclosure, the means for transferring energy centrally from the proximal end to the distal end through the elongated body further includes an elongated shaft removably held in the cage holder.

(26) According to another aspect of the present disclosure, the elongated shaft is configured to movably slide within the cage holder from an outer extremity of the proximal end of the cage holder to an outer extremity of the distal end of the cage holder.

(27) According to another aspect of the present disclosure, the elongated shaft is configured to be received by the tube; or is removably held by the tube.

(28) According to another aspect of the present disclosure, the elongated shaft is configured to movably slide within the tube from an outer extremity of a proximal end of the tube to an outer extremity of a distal end of the tube.

(29) According to another aspect of the present disclosure, the elongated shaft is a solid rod or a hollow rod or shaft.

(30) According to another aspect of the present disclosure, the elongated shaft includes a knob at a first end.

(31) According to another aspect of the present disclosure, the elongated shaft includes a cage holding or cage attachment means at a second end.

(32) According to another aspect of the present disclosure, the distal end of the cage holder is configured to hold or attach a spinal cage.

(33) According to another aspect of the present disclosure, the elongated body includes a handle and the proximal end of the elongated body is located at the end of the handle.

(34) According to another aspect of the present disclosure, the cage holder is a spine cage holder.

(35) According to another aspect of the present disclosure, the means for transferring energy centrally is configured to transfer mechanical energy.

(36) According to another aspect of the present disclosure, said means is configured to transfer energy centrally from the proximal end to the distal end of the elongated body and centrally through the full length of the elongated body.

(37) According to another aspect of the present disclosure, the elongated body comprises or consist of a plastic; and the means for transferring energy centrally from the proximal end to the distal end through the elongated body and/or the member comprises or consists of a metal, and/or the tube comprises or consists of a metal.

(38) According to another aspect of the present disclosure, the elongated shaft comprises or consists of a metal.

(39) The present invention also concerns a kit of instruments including the above-mentioned cage holder.

Description

A BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

- (1) The above object, features and other advantages of the present disclosure will be best understood from the following detailed description in conjunction with the accompanying drawings, in which:
- (2) FIGS. 1 to 11 show non-limiting and exemplary embodiments of the present disclosure.
- (3) FIG. 1 shows a cage holder according to an exemplary embodiment of the present disclosure.
- (4) FIG. 2 shows the cage holder of FIG. 1 in which a central shaft is fully inserted.
- (5) FIG. 3 shows a view of a proximal end of a cage holder of the present disclosure.
- (6) FIG. 4 shows the cage holder of FIG. 1 in which a central shaft is partially inserted.
- (7) FIG. 5 shows a shaft and knob at one end of a cage holder of the present disclosure, the being shaft is partially removed from a body of the cage holder.
- (8) FIG. 6A shows an opposite extremity to that of FIG. 5 of a cage holder of the present disclosure.
- (9) FIG. 6B shows the same extremity to that of FIG. 6A with the shaft of FIG. 5 being fully inserted.
- (10) FIG. 7 shows the extremity of a cage holder attached to a spine cage.
- (11) FIG. 8 shows a cage holder according to an exemplary embodiment of the present disclosure in which a central shaft is not present.
- (12) FIG. 9 shows a sectional view (along A1-A1 of FIG. 8) and top view of the cage holder of FIG. 8.
- (13) FIG. 10 shows a cage holder according to an exemplary embodiment of the present disclosure in which a central shaft is present.
- (14) FIG. 11 shows a sectional (along A-A of FIG. 10) and top view of the cage holder of FIG. 10.
- (15) Herein, identical reference numerals are used, where possible, to designate identical elements that are common to the Figures.

DETAILED DESCRIPTION OF THE SEVERAL EMBODIMENTS

- (16) An exemplary cage holder 1 according to the present disclosure is shown, for example, in FIGS. 1 and 2.
- (17) The cage holder 1 includes an elongated body 3 comprising a proximal end 5 and a distal end 7, the elongated body 3 extending from the proximal end 5 to the distal end 7.
- (18) The elongated body 3 is for example made of, comprises or consists of a plastic or a polymer. The elongated body 3 is for example made of, comprises or consists of a polyvinyl chloride (PVC), polyethylene, a polyester, polycarbonate, polyetherether ketone (PEEK), ultra-high molecular weight polyethylene (UHMWPE) or polyarylamide.
- (19) The elongated body 3 may include, for example, a handle 8A and the proximal end 5 of the elongated body 3 is located at the end of the handle 8. The elongated body 3 may also include, for example, a sleeve 8B.
- (20) The cage holder 1 further includes means 9 for transferring energy centrally from the proximal end 5 to the distal end 7 and centrally through the full length of the elongated body. The means 9 for transferring energy is configured to transfer energy centrally through the cage holder 1 in a longitudinal direction of the cage holder 1. The means 9 for transferring energy is configured to transfer energy centrally through the cage holder in a longitudinal direction L (see FIG. 1) of the cage holder 1 from a proximal end 11 of the cage holder 1 to a distal end 15 of the cage holder 1. The longitudinal direction L extends in a direction running along or parallel to the length or extension of the elongated body 3.
- (21) The means 9 for transferring energy is, for example, partially or fully enclosed by the elongated body 3.

(22) The means **9** for transferring energy is configured to transfer energy centrally through the cage holder **1** in the longitudinal direction **L** from an outer extremity of the proximal end **11** of the cage holder **1** to an outer extremity of the distal end **15** of the cage holder **1**. As a result, this energy or force is efficiently transferred to a spine cage when located or attached at the extremity of the cage holder **1** to allow an easier insertion of the cage into a desired position between vertebrae.

(23) The distal end **15** of the cage holder **1** is configured to hold or attach a spinal cage.

(24) The means **9** for transferring energy centrally includes a cage holder, or a cage holding means or a cage attachment means **17** at the distal end (see in particular FIG. **6**). The cage holding means or cage attachment means **17** can include, for example, one or more projections configured to, for example, cooperate with or be received by corresponding sockets of the cage (for example a spine cage, for example, as shown in FIG. **7**). The cage can be, for example, attached by sliding or inserting the projections into the sockets of the cage.

(25) The means **9** can be or include a core or central member located centrally in the cage holder and extending from the proximal end **11** to the distal end **15** of the cage holder **1**. The core or central member is configured to transfer or guide energy centrally in the core of the cage holder **1** from the proximal end **11** to the distal end **15** of the cage holder **1**. Mechanical energy applied at the proximal end **11** is channeled through the core of the cage holder to the proximal end. Dissipation or loss of the energy in non-central regions of the device is avoided permitting an optimum quantity of energy to be transferred to the cage.

(26) The means **9** for transferring energy centrally includes a member **9** extending from the proximal end **5** to the distal end **7** of the elongated body **3**. The member **9** comprises or consists of a first material and the elongated body **3** comprises or consists of a second material that, in a preferred embodiment, is different to the first material. Alternatively, the first and second material may also be the same material.

(27) The first material, may for example, have a higher material density than the second material. Alternatively or additionally, the member **9** may have a higher rigidity or a lower flexibility than the elongated body **3**.

(28) The member **9** or the means **9** for transferring energy centrally (or the core or central member) includes or is, for example, a tube **9**. The tube **9** is, for example, partially or fully enclosed by the elongated body **3**.

(29) The tube **9** extends from the proximal end **5** to the distal end **7** of the elongated body **3**, and can extend beyond the distal end **7** of the body **3**.

(30) The tube **9** can extend from the proximal end **11** of the cage holder **1** to the distal end **15** of the cage holder **1**. The tube **9** can extend from an outer extremity of the proximal end **11** of the cage holder **1** to an outer extremity of the distal end **15** of the cage holder **1**.

(31) The elongated body **3** delimits a passage in which the tube is located and/or held therein (see for example FIG. **3**). The passage extends from an outer extremity of the proximal end **5** of the elongated body **3** to an outer extremity of the distal end **7** of the elongated body **3**.

(32) The tube **9** can define a hollow tube. Alternatively, the tube can be a non-hollow solid tube or solid rod.

(33) The tube **9** can be, for example, a metallic tube. The tube **9** can be made of, comprises or consists of, for example, stainless steel, or titanium, or tantalum, or platinum, or palladium or aluminum.

(34) The tube **9** can be discontinuous in parts but extends continuously from the proximal end to the distal end for efficient energy transfer.

(35) The tube **9** is preferably cylindric but may also have other shapes.

(36) The tube **9** is preferably located in proximity to the central longitudinal axis **L** of the cage holder **1**.

(37) The tube **9**, for example, encircles the central longitudinal axis **L** of the cage holder **1** or the central longitudinal axis **L** extends longitudinally through the tube.

- (38) An external wall of the tube is, for example, located at a distance of at least 0.1 mm from the central longitudinal axis L of the cage holder **1**.
- (39) An external wall of the tube is, for example, located at a distance between 0.1 mm and 5 mm from a central longitudinal axis L of the cage holder **1**.
- (40) The central longitudinal axis L of the cage holder **1** is located, for example, at a geometric center or center of symmetry of the cage holder **1** and/or the elongated body **3**.
- (41) The external wall of the tube **9** directly contacts a wall of the elongated body **3** defining the passage in the elongated body **3**.
- (42) The means **9** for transferring energy centrally may further include an elongated shaft **19** removably held in the cage holder **1**. The elongated shaft **19** is configured to movably slide within the cage holder **1** from an outer extremity of the proximal end **11** of the cage holder to an outer extremity of the distal end **15** of the cage holder.
- (43) The cage holder **1** can thus further include the elongated shaft **19** or elongated central shaft **19** (see for example FIG. **4**) configured to be received by the means **9** for transferring energy centrally, for example, the member or tube **9**. In such a case the tube **9** is hollow.
- (44) The elongated shaft **19** is configured to be received by the tube (**9**) and is removably held by the tube **9**. The elongated shaft **19** is configured to movably slide within the tube **9** from an outer extremity of a proximal end of the tube **9** to an outer extremity of a distal end of the tube **9**.
- (45) The elongated shaft **19** can be for example a solid rod or a hollow shaft. The shaft **19** can be made of, comprises or consists of, for example, stainless steel, or titanium, or tantalum, or platinum, or palladium or aluminum.
- (46) The elongated shaft has, for example, a complementary shape to that of the means (tube) **9** to fit snugly therein for an efficient transfer of energy.
- (47) The elongated shaft **19** may include a knob **21** at a first end. The elongated shaft **19** can include a cage holding means or cage attachment means **23** at a second end. The second end is opposite the first end.
- (48) The cage holding means or cage attachment means **23** can include, for example, a threaded extremity or a projection configured to, for example, cooperate with or be received by corresponding sockets or threaded sockets of the cage (for example, a cage as shown on the left in FIG. **7**).
- (49) A force may be applied to the shaft **19** via, for example, the knob **21**, and the energy is transferred from the proximal end to the distal end of the cage holder **1** via both the shaft **19** and the tube **9**. The means for transferring energy centrally may thus additionally include the shaft **9**.
- (50) The cage holder may be part of an instrument kit.
- (51) While the invention has been disclosed with reference to certain preferred embodiments, numerous modifications, alterations, and changes to the described embodiments, and equivalents thereof, are possible without departing from the sphere and scope of the invention. The features of any one of the described embodiments may be included in any other of the described embodiments. Accordingly, it is intended that the invention not be limited to the described embodiments and be given the broadest reasonable interpretation in accordance with the language of the appended claims.

Claims

1. A cage holder comprising: an elongated body comprising a proximal end and a distal end, the elongated body extending from the proximal end to the distal end of the elongated body; and a tube configured to transfer energy centrally from a proximal end to a distal end of the cage holder, said tube being at least partially enclosed by the elongated body, the tube extending through the elongated body and from the proximal end to the distal end of the cage holder, the tube comprising or consisting of a first material, the tube configured to transfer energy centrally from the proximal

end to the distal end through the elongated body, the tube including an elongated shaft removably held in the cage holder, the elongated shaft including a knob at a first end thereof, wherein the elongated body comprises or consists of a second material different from the first material, the first material having a greater material density than a material density of the second material, the tube having a greater rigidity or a lower flexibility than a rigidity or a flexibility of the elongated body, wherein the elongated shaft is removably held inside the tube, and wherein the elongated shaft has a complementary shape to a shape of the tube to fit snugly inside the tube for a transfer of energy, the elongated shaft being a hollow rod or hollow shaft.

2. The cage holder according to claim 1, wherein the tube is configured to transfer energy centrally through the cage holder in a longitudinal direction of the cage holder from the proximal end of the cage holder to the distal end of the cage holder.

3. The cage holder according to claim 1, wherein the tube configured to transfer energy centrally includes a cage holding or cage attachment system at the distal end of the cage holder.

4. The cage holder according to claim 1, wherein the elongated shaft is configured to movably slide within the cage holder from an outer extremity of the proximal end of the cage holder to an outer extremity of the distal end of the cage holder.

5. The cage holder according to claim 4, wherein the elongated shaft is configured to be received by the tube.

6. The cage holder according to claim 1, wherein the elongated shaft includes a cage holding or cage attachment device at a second end thereof.

7. The cage holder according to claim 1, wherein the distal end of the cage holder is configured to hold or attach a spinal cage.

8. The cage holder according to claim 1, wherein the elongated body includes a handle and the proximal end of the elongated body is located at an end of the handle.

9. The cage holder according to claim 1, wherein the cage holder is a spine cage holder.

10. The cage holder according to claim 1, wherein the tube configured to transfer energy centrally is configured to transfer mechanical energy.

11. The cage holder according to claim 1, wherein the elongated body includes a handle and the proximal end of the elongated body is located at an end of the handle, wherein the elongated shaft includes a cage holding or cage attachment system at a distal end of the elongated shaft.

12. The cage holder according to claim 11, wherein the elongated body includes a sleeve disposed as the distal end of the elongated body.

13. The cage holder according to claim 1, wherein the elongated shaft has a complementary shape to a shape of the tube to fit snugly inside the tube for a transfer of energy, the elongated shaft being a solid rod elongated shaft.

14. The cage holder according to claim 13, wherein the elongated shaft includes a cage holding or cage attachment system at a distal end of the elongated shaft.

15. The cage holder according to claim 1, wherein the knob is disposed at a proximal end of the elongated shaft and the elongated shaft includes a cage holding or cage attachment system at a distal end of the elongated shaft.
