

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12412348
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Richter; Ian M. et al.

Method and devices for presenting and manipulating conditionally dependent synthesized reality content threads

Abstract

In one implementation, a method includes presenting, via a display device, a first synthesized reality (SR) view of an event that includes SR content associated with the event. The SR content includes a plurality of related layers of SR content that perform actions associated with the event. The method includes detecting, via one or more input devices, selection of a respective layer among the plurality of related layers of SR content associated with the event. The method includes presenting, via the display device, a second SR view of the event that includes the respective layer of SR content in response to the selection of the respective layer. The second SR view corresponds to a point-of-view of the respective layer.

Inventors: Richter; Ian M. (Los Angeles, CA), Rockwell; Michael J. (Palo Alto, CA), Saini; Amritpal Singh (San Jose, CA), Soares; Olivier (Oakland, CA)

Applicant: Apple Inc. (Cupertino, CA)

Family ID: 65729427

Assignee: Apple Inc. (Cupertino, CA)

Appl. No.: 18/679836

Filed: May 31, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240320937 A1	Sep. 26, 2024

Related U.S. Application Data

continuation parent-doc US 18233867 20230814 US 12033290 child-doc US 18679836
continuation parent-doc US 17557739 20211221 US 11769305 20230926 child-doc US 18233867

continuation parent-doc US 16965139 US 11238661 20220201 WO PCT/US2019/018303
20190215 child-doc US 17557739
us-provisional-application US 62679201 20180601
us-provisional-application US 62632378 20180219

Publication Classification

Int. Cl.: G06T19/00 (20110101); G06N3/04 (20230101); G06N3/08 (20230101)

U.S. Cl.:

CPC G06T19/006 (20130101); G06N3/04 (20130101); G06N3/08 (20130101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2006/0122884	12/2005	Graham et al.	N/A	N/A
2011/0098056	12/2010	Rhoads et al.	N/A	N/A
2013/0176334	12/2012	Boldyrev et al.	N/A	N/A
2013/0259238	12/2012	Xiang et al.	N/A	N/A
2013/0289998	12/2012	Eller et al.	N/A	N/A
2014/0104394	12/2013	Yanai et al.	N/A	N/A
2014/0120887	12/2013	Huang	N/A	N/A
2014/0285519	12/2013	Uusitalo et al.	N/A	N/A
2015/0375103	12/2014	George	N/A	N/A
2016/0131761	12/2015	Yates et al.	N/A	N/A
2017/0124626	12/2016	Barnett et al.	N/A	N/A
2017/0216675	12/2016	Goslin et al.	N/A	N/A
2019/0279425	12/2018	Yin	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1020130137968	12/2012	KR	N/A
1020170018930	12/2016	KR	N/A
2017096096	12/2016	WO	N/A
2018/005596	12/2017	WO	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion dated May 22, 2019, International Application No. PCT/US2019/018303, pp. 1-11. cited by applicant

Robin Baumgarten et al., “Combining AI Methods for Learning Bots in a Real-Time Strategy Game”, International Journal of Computer Games Technology, vol. 2009, Article ID 129075, pp. 1-10. cited by applicant

PCT International Search Report and Written Opinion dated Sep. 13, 2019, International Application No. PCT/US2019/034142, pp. 1-11. cited by applicant

Primary Examiner: Craddock; Robert J

Attorney, Agent or Firm: Fernando & Partners, LLP

Background/Summary

CROSS-REFERENCES TO RELATED APPLICATIONS (1) This application is a continuation application of U.S. Non-Provisional patent application Ser. No. 18/233,867, filed on Aug. 14, 2023, which is a national phase entry of Intl. Patent App. No. PCT/US2019/018303, filed on Feb. 15, 2019, which claims priority to U.S. Provisional Patent App. No. 62/679,201, filed on Jun. 1, 2018 and to U.S. Provisional Patent App. No. 62/632,378, filed on Feb. 19, 2018, all of which are hereby incorporated by reference in their entireties.

TECHNICAL FIELD

(1) The present disclosure generally relates to objective-effectuators (OEs) within synthesized reality (SR) settings and, more specifically, to presenting and manipulating OEs within conditionally dependent SR content threads.

BACKGROUND

(2) Some devices are capable of generating and presenting synthesized reality settings. Some synthesized reality settings include virtual settings that are simulated replacements of physical settings. Some synthesized reality settings include augmented settings that are modified versions of physical settings. Some devices that present synthesized reality settings include mobile communication devices such as smartphones, head-mountable displays (HMDs), eyeglasses, heads-up displays (HUDs), head-mountable enclosures, and optical projection systems. Most previously available devices that present synthesized reality setting are ineffective at presenting representations of certain objects. For example, some previously available devices that present synthesized reality settings are unsuitable for presenting representations of objects that are associated with an action.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) So that the present disclosure can be understood by those of ordinary skill in the art, a more detailed description may be had by reference to aspects of some illustrative implementations, some of which are shown in the accompanying drawings.

(2) FIGS. 1A and 1B are diagrams of example operating environments in accordance with some implementations.

(3) FIG. 2 is a block diagram of an example system in accordance with some implementations.

(4) FIG. 3A is a block diagram of an example emergent content engine in accordance with some implementations.

(5) FIG. 3B is a block diagram of an example neural network in accordance with some implementations.

(6) FIGS. 4A-4E are flowchart representations of a method of generating content for SR settings in

accordance with some implementations.

(7) FIG. 5 is a block diagram of a server system enabled with various components of the emergent content engine in accordance with some implementations.

(8) FIG. 6A is a block diagram of conditionally dependent synthesized reality (SR) content threads in accordance with some implementations.

(9) FIGS. 6B and 6C illustrate timelines associated with objective-effectuator (OE) encapsulations in accordance with some implementations.

(10) FIGS. 7A-7C illustrate example SR presentation scenarios in accordance with some implementations.

(11) FIGS. 8A-8C are block diagrams of emergent content architectures in accordance with some implementations.

(12) FIG. 9 is a flowchart representation of a method of instantiating an OE encapsulation within an SR setting in accordance with some implementations.

(13) FIG. 10 is a flowchart representation of a method of initializing and generating content for an OE encapsulation within an SR setting in accordance with some implementations.

(14) FIG. 11 is a flowchart representation of a method of initializing and generating content for an OE within an SR setting in accordance with some implementations.

(15) FIG. 12 is a flowchart representation of a method of selecting a point-of-view within an SR setting (e.g., a conditionally dependent SR content threads environment) in accordance with some implementations.

(16) In accordance with common practice the various features illustrated in the drawings may not be drawn to scale. Accordingly, the dimensions of the various features may be arbitrarily expanded or reduced for clarity. In addition, some of the drawings may not depict all of the components of a given system, method or device. Finally, like reference numerals may be used to denote like features throughout the specification and figures.

SUMMARY

(17) Various implementations disclosed herein include devices, systems, and methods for instantiating an OE encapsulation within an SR setting. In various implementations, a device includes a non-transitory memory and one or more processors coupled with the non-transitory memory. In some implementations, a method includes: instantiating a first objective-effectuator (OE) associated with a first set of attributes and a second OE associated with a second set of attributes into a synthesized reality (SR) setting, wherein the first OE is encapsulated within the second OE; providing a first objective to the first OE based on the first and second sets of attributes; providing a second objective to the second OE based on the second set of attributes, wherein the first and second objectives are associated with a first time period between a first temporal point and a second temporal point; generating a first set of actions associated with the first time period for the first OE based on the first objective; generating a second set of actions associated with the first time period for the second OE based on the second objective; and rendering for display the SR setting including the first set of actions performed by the first OE and the second set of actions performed by the second OE.

(18) Various implementations disclosed herein include devices, systems, and methods for initializing and generating content for an OE encapsulation within an SR setting. In various implementations, a device includes a non-transitory memory and one or more processors coupled with the non-transitory memory. In some implementations, a method includes: synthesizing an initial set of objectives for an objective-effectuator (OE) encapsulation based on a set of actions extracted from source assets associated with an event, wherein the OE encapsulation includes a first OE encapsulated within a second OE, and wherein the initial set of objectives includes a first objective for the first OE that is consistent with a second objective for the second OE; instantiating the OE encapsulation into a virtual, wherein the OE encapsulation is characterized by the initial set of objectives and a set of visual rendering attributes; generating updated objectives for the OE

encapsulation based on a function of the initial set of objectives, contextual information associated with the event, and the set of actions; and modifying the OE encapsulation based on the updated set of objectives.

(19) Various implementations disclosed herein include devices, systems, and methods for initializing and generating content for an OE within an SR setting. In various implementations, a device includes a non-transitory memory and one or more processors coupled with the non-transitory memory. In some implementations, a method includes: synthesizing an initial set of objectives for a first objective-effectuator (OE) based on a set of actions extracted from source assets associated with an event; instantiating the first OE into an SR setting, wherein the first OE is characterized by the initial set of objectives and a set of visual rendering attributes; generating updated objectives for the first OE based on a function of the initial set of objectives, contextual information associated with the event, and the set of actions; and modifying the first OE based on the updated set of objectives.

(20) Various implementations disclosed herein include devices, systems, and methods for selecting a point-of-view within an SR setting (e.g., a conditionally dependent SR content threads environment). In various implementations, a device includes a non-transitory memory and one or more processors coupled with the non-transitory memory. In some implementations, a method includes: presenting a first SR view of an event that includes SR content associated with the event, wherein the SR content includes a plurality of related layers of SR content that perform actions associated with the event; detecting selection of a respective layer among the plurality of related layers of SR content associated with the event; and presenting a second SR view of the event that includes the respective layer of SR content in response to the selection of the respective layer, wherein the second SR view corresponds to a point-of-view of the respective layer.

(21) In accordance with some implementations, a device includes one or more processors, a non-transitory memory, and one or more programs. In some implementations, the one or more programs are stored in the non-transitory memory and are executed by the one or more processors. In some implementations, the one or more programs include instructions for performing or causing performance of any of the methods described herein. In accordance with some implementations, a non-transitory computer readable storage medium has stored therein instructions that, when executed by one or more processors of a device, cause the device to perform or cause performance of any of the methods described herein. In accordance with some implementations, a device includes one or more processors, a non-transitory memory, and means for performing or causing performance of any of the methods described herein.

DESCRIPTION

(22) Numerous details are described in order to provide a thorough understanding of the example implementations shown in the drawings. However, the drawings merely show some example aspects of the present disclosure and are therefore not to be considered limiting. Those of ordinary skill in the art will appreciate that other effective aspects and/or variants do not include all of the specific details described herein. Moreover, well-known systems, methods, components, devices and circuits have not been described in exhaustive detail so as not to obscure more pertinent aspects of the example implementations described herein.

(23) A physical setting refers to a world that individuals can sense and/or with which individuals can interact without assistance of electronic systems. Physical settings (e.g., a physical forest) include physical elements (e.g., physical trees, physical structures, and physical animals). Individuals can directly interact with and/or sense the physical setting, such as through touch, sight, smell, hearing, and taste.

(24) In contrast, a synthesized reality (SR) setting refers to an entirely or partly computer-created setting that individuals can sense and/or with which individuals can interact via an electronic system. In SR, a subset of an individual's movements is monitored, and, responsive thereto, one or more attributes of one or more virtual objects in the SR setting is changed in a manner that

conforms with one or more physical laws. For example, an SR system may detect an individual walking a few paces forward and, responsive thereto, adjust graphics and audio presented to the individual in a manner similar to how such scenery and sounds would change in a physical setting. Modifications to attribute(s) of virtual object(s) in an SR setting also may be made responsive to representations of movement (e.g., audio instructions).

(25) An individual may interact with and/or sense an SR object using any one of his senses, including touch, smell, sight, taste, and sound. For example, an individual may interact with and/or sense aural objects that create a multi-dimensional (e.g., three dimensional) or spatial aural setting, and/or enable aural transparency. Multi-dimensional or spatial aural settings provide an individual with a perception of discrete aural sources in multi-dimensional space. Aural transparency selectively incorporates sounds from the physical setting, either with or without computer-created audio. In some SR settings, an individual may interact with and/or sense only aural objects.

(26) One example of SR is virtual reality (VR). A VR setting refers to a simulated setting that is designed only to include computer-created sensory inputs for at least one of the senses. A VR setting includes multiple virtual objects with which an individual may interact and/or sense. An individual may interact and/or sense virtual objects in the VR setting through a simulation of a subset of the individual's actions within the computer-created setting, and/or through a simulation of the individual or his presence within the computer-created setting.

(27) Another example of SR is mixed reality (MR). An MR setting refers to a simulated setting that is designed to integrate computer-created sensory inputs (e.g., virtual objects) with sensory inputs from the physical setting, or a representation thereof. On a reality spectrum, a mixed reality setting is between, and does not include, a VR setting at one end and an entirely physical setting at the other end.

(28) In some MR settings, computer-created sensory inputs may adapt to changes in sensory inputs from the physical setting. Also, some electronic systems for presenting MR settings may monitor orientation and/or location with respect to the physical setting to enable interaction between virtual objects and real objects (which are physical elements from the physical setting or representations thereof). For example, a system may monitor movements so that a virtual plant appears stationery with respect to a physical building.

(29) One example of mixed reality is augmented reality (AR). An AR setting refers to a simulated setting in which at least one virtual object is superimposed over a physical setting, or a representation thereof. For example, an electronic system may have an opaque display and at least one imaging sensor for capturing images or video of the physical setting, which are representations of the physical setting. The system combines the images or video with virtual objects, and displays the combination on the opaque display. An individual, using the system, views the physical setting indirectly via the images or video of the physical setting, and observes the virtual objects superimposed over the physical setting. When a system uses image sensor(s) to capture images of the physical setting, and presents the AR setting on the opaque display using those images, the displayed images are called a video pass-through. Alternatively, an electronic system for displaying an AR setting may have a transparent or semi-transparent display through which an individual may view the physical setting directly. The system may display virtual objects on the transparent or semi-transparent display, so that an individual, using the system, observes the virtual objects superimposed over the physical setting. In another example, a system may comprise a projection system that projects virtual objects into the physical setting. The virtual objects may be projected, for example, on a physical surface or as a holograph, so that an individual, using the system, observes the virtual objects superimposed over the physical setting.

(30) An augmented reality setting also may refer to a simulated setting in which a representation of a physical setting is altered by computer-created sensory information. For example, a portion of a representation of a physical setting may be graphically altered (e.g., enlarged), such that the altered portion may still be representative of but not a faithfully reproduced version of the originally

captured image(s). As another example, in providing video pass-through, a system may alter at least one of the sensor images to impose a particular viewpoint different than the viewpoint captured by the image sensor(s). As an additional example, a representation of a physical setting may be altered by graphically obscuring or excluding portions thereof.

(31) Another example of mixed reality is augmented virtuality (AV). An AV setting refers to a simulated setting in which a computer-created or virtual setting incorporates at least one sensory input from the physical setting. The sensory input(s) from the physical setting may be representations of at least one characteristic of the physical setting. For example, a virtual object may assume a color of a physical element captured by imaging sensor(s). In another example, a virtual object may exhibit characteristics consistent with actual weather conditions in the physical setting, as identified via imaging, weather-related sensors, and/or online weather data. In yet another example, an augmented reality forest may have virtual trees and structures, but the animals may have features that are accurately reproduced from images taken of physical animals.

(32) Many electronic systems enable an individual to interact with and/or sense various SR settings. One example includes head mounted systems. A head mounted system may have an opaque display and speaker(s). Alternatively, a head mounted system may be designed to receive an external display (e.g., a smartphone). The head mounted system may have imaging sensor(s) and/or microphones for taking images/video and/or capturing audio of the physical setting, respectively. A head mounted system also may have a transparent or semi-transparent display. The transparent or semi-transparent display may incorporate a substrate through which light representative of images is directed to an individual's eyes. The display may incorporate LEDs, OLEDs, a digital light projector, a laser scanning light source, liquid crystal on silicon, or any combination of these technologies. The substrate through which the light is transmitted may be a light waveguide, optical combiner, optical reflector, holographic substrate, or any combination of these substrates. In one implementation, the transparent or semi-transparent display may transition selectively between an opaque state and a transparent or semi-transparent state. In another example, the electronic system may be a projection-based system. A projection-based system may use retinal projection to project images onto an individual's retina. Alternatively, a projection system also may project virtual objects into a physical setting (e.g., onto a physical surface or as a holograph). Other examples of SR systems include heads up displays, automotive windshields with the ability to display graphics, windows with the ability to display graphics, lenses with the ability to display graphics, headphones or earphones, speaker arrangements, input mechanisms (e.g., controllers having or not having haptic feedback), tablets, smartphones, and desktop or laptop computers.

(33) The present disclosure provides methods, systems, and/or devices for presenting and manipulating SR settings. An emergent content engine generates objectives for objective-effectuators, and provides the objectives to corresponding objective-effectuator engines so that the objective-effectuator engines can generate actions that satisfy the objectives. The objectives generated by the emergent content engine indicate plots or story lines for which the objective-effectuator engines generate actions. Generating objectives enables presentation of dynamic objective-effectuators that perform actions as opposed to presenting static objective-effectuators, thereby enhancing the user experience and improving the functionality of the device presenting the SR setting.

(34) FIG. 1A is a block diagram of an example operating environment **100A** in accordance with some implementations. While pertinent features are shown, those of ordinary skill in the art will appreciate from the present disclosure that various other features have not been illustrated for the sake of brevity and so as not to obscure more pertinent aspects of the example implementations disclosed herein. To that end, as a non-limiting example, the operating environment **100A** includes a controller **102** and an electronic device **103**. In the example of FIG. 1A, the electronic device **103** is being held by a user **10**. In some implementations, the electronic device **103** includes a smartphone, a tablet, a laptop, or the like.

(35) As illustrated in FIG. 1A, the electronic device **103** presents a synthesized reality setting **106**. In some implementations, the synthesized reality setting **106** is generated by the controller **102** and/or the electronic device **103**. In some implementations, the synthesized reality setting **106** includes a virtual setting that is a simulated replacement of a physical setting. In other words, in some implementations, the synthesized reality setting **106** is simulated by the controller **102** and/or the electronic device **103**. In such implementations, the synthesized reality setting **106** is different from the physical setting where the electronic device **103** is located. In some implementations, the synthesized reality setting **106** includes an augmented setting that is a modified version of a physical setting. For example, in some implementations, the controller **102** and/or the electronic device **103** modify (e.g., augment) the physical setting where the electronic device **103** is located in order to generate the synthesized reality setting **106**. In some implementations, the controller **102** and/or the electronic device **103** generate the synthesized reality setting **106** by simulating a replica of the physical setting where the electronic device **103** is located. In some implementations, the controller **102** and/or the electronic device **103** generate the synthesized reality setting **106** by removing and/or adding items from the simulated replica of the physical setting where the electronic device **103** is located.

(36) In some implementations, the synthesized reality setting **106** includes various SR representations of objective-effectuators, such as a boy action figure representation **108a**, a girl action figure representation **108b**, a robot representation **108c**, and a drone representation **108d**. In some implementations, the objective-effectuators represent characters from fictional materials, such as movies, video games, comics, and novels. For example, the boy action figure representation **108a** represents a 'boy action figure' character from a fictional comic, and the girl action figure representation **108b** represents a 'girl action figure' character from a fictional video game. In some implementations, the synthesized reality setting **106** includes objective-effectuators that represent characters from different fictional materials (e.g., from different movies/games/comics/novels). In various implementations, the objective-effectuators represent things (e.g., tangible objects). For example, in some implementations, the objective-effectuators represent equipment (e.g., machinery such as planes, tanks, robots, cars, etc.). In the example of FIG. 1A, the robot representation **108c** represents a robot and the drone representation **108d** represents a drone. In some implementations, the objective-effectuators represent things (e.g., equipment) from fictional materials. In some implementations, the objective-effectuators represent things from a physical setting, including things located inside and/or outside of the synthesized reality setting **106**.

(37) In various implementations, the objective-effectuators perform one or more actions in order to effectuate (e.g., complete/satisfy/achieve) one or more objectives. In some implementations, the objective-effectuators perform a sequence of actions. In some implementations, the controller **102** and/or the electronic device **103** determine the actions that the objective-effectuators are to perform. In some implementations, the actions of the objective-effectuators are within a degree of similarity to actions that the corresponding characters/things perform in the fictional material. In the example of FIG. 1A, the girl action figure representation **108b** is performing the action of flying (e.g., because the corresponding 'girl action figure' character is capable of flying, and/or the 'girl action figure' character frequently flies in the fictional materials). In the example of FIG. 1A, the drone representation **108d** is performing the action of hovering (e.g., because drones in physical settings are capable of hovering). In some implementations, the controller **102** and/or the electronic device **103** obtain the actions for the objective-effectuators. For example, in some implementations, the controller **102** and/or the electronic device **103** receive the actions for the objective-effectuators from a remote server that determines (e.g., selects) the actions.

(38) In various implementations, an objective-effectuator performs an action in order to satisfy (e.g., complete or achieve) an objective. In some implementations, an objective-effectuator is associated with a particular objective, and the objective-effectuator performs actions that improve

the likelihood of satisfying that particular objective. In some implementations, SR representations of the objective-effectuators are referred to as object representations, for example, because the SR representations of the objective-effectuators represent various objects (e.g., real objects, or fictional objects). In some implementations, an objective-effectuator representing a character is referred to as a character objective-effectuator. In some implementations, a character objective-effectuator performs actions to effectuate a character objective. In some implementations, an objective-effectuator representing an equipment is referred to as an equipment objective-effectuator. In some implementations, an equipment objective-effectuator performs actions to effectuate an equipment objective. In some implementations, an objective-effectuator representing an environment is referred to as an environmental objective-effectuator. In some implementations, an environmental objective-effectuator performs environmental actions to effectuate an environmental objective.

(39) In some implementations, the synthesized reality setting **106** is generated based on an input from the user **10**. For example, in some implementations, the electronic device **103** receives an input indicating a terrain for the synthesized reality setting **106**. In such implementations, the controller **102** and/or the electronic device **103** configure the synthesized reality setting **106** such that the synthesized reality setting **106** includes the terrain indicated via the input. In some implementations, the input indicates environmental conditions for the synthesized reality setting **106**. In such implementations, the controller **102** and/or the electronic device **103** configure the synthesized reality setting **106** to have the environmental conditions indicated by the input. In some implementations, the environmental conditions include one or more of temperature, humidity, pressure, visibility, ambient light level, ambient sound level, time of day (e.g., morning, afternoon, evening, or night), and precipitation (e.g., overcast, rain, or snow).

(40) In some implementations, the actions for the objective-effectuators are determined (e.g., generated) based on an input from the user **10**. For example, in some implementations, the electronic device **103** receives an input indicating placement of the SR representations of the objective-effectuators. In such implementations, the controller **102** and/or the electronic device **103** position the SR representations of the objective-effectuators in accordance with the placement indicated by the input. In some implementations, the input indicates specific actions that the objective-effectuators are permitted to perform. In such implementations, the controller **102** and/or the electronic device **103** select the actions for the objective-effectuator from the specific actions indicated by the input. In some implementations, the controller **102** and/or the electronic device **103** forgo actions that are not among the specific actions indicated by the input. In some implementations, the controller **102** and/or the electronic device **103** include at least a portion of the emergent content architectures in FIGS. 8A-8C.

(41) FIG. 1B is a block diagram of an example operating environment **100B** in accordance with some implementations. While pertinent features are shown, those of ordinary skill in the art will appreciate from the present disclosure that various other features have not been illustrated for the sake of brevity and so as not to obscure more pertinent aspects of the example implementations disclosed herein. To that end, as a non-limiting example, the operating environment **100B** includes the controller **102** and a head-mountable device (HMD) **104**. In the example of FIG. 1B, the HMD **104** is worn by the user **10**. In various implementations, the HMD **104** operates in substantially the same manner as the electronic device **103** shown in FIG. 1A. In some implementations, the HMD **104** performs substantially the same operations as the electronic device **103** shown in FIG. 1A. In some implementations, the HMD **104** includes a head-mountable enclosure. In some implementations, the head-mountable enclosure is shaped to form a receptacle for receiving an electronic device with a display (e.g., the electronic device **103** shown in FIG. 1A). For example, in some implementations, the electronic device **103** shown in FIG. 1A can be slid into the HMD **104**. In some implementations, the HMD **104** includes an integrated display for presenting a synthesized reality experience to the user **10**. In some implementations, the controller **102** and/or the HMD **104** include at least a portion of the emergent content architectures in FIGS. 8A-8C.

(42) FIG. 2 is a block diagram of an example system **200** that generates objectives for various objective-effectuators in an SR setting. For example, the system **200** generates objectives for the boy action figure representation **108a**, the girl action figure representation **108b**, the robot representation **108c**, and/or the drone representation **108d** shown in FIGS. 1A and 1B. In the example of FIG. 2, the system **200** includes a boy action figure character engine **208a**, a girl action figure character engine **208b**, a robot equipment engine **208c**, and a drone equipment engine **208d** that generate actions **210** for the boy action figure representation **108a**, the girl action figure representation **108b**, the robot representation **108c**, and the drone representation **108d**, respectively. In some implementations, the system **200** also includes an environmental engine **208e**, an emergent content engine **250**, and a display engine **260**.

(43) In various implementations, the emergent content engine **250** generates respective objectives **254** for objective-effectuators that are in the SR setting and/or for the environment of the SR setting. In the example of FIG. 2, the emergent content engine **250** generates boy action figure objectives **254a** for the boy action figure representation **108a**, girl action figure objectives **254b** for the girl action figure representation **108b**, robot objectives **254c** for the robot representation **108c**, drone objectives **254d** for the drone representation **108d**, and/or environmental objectives **254e** (e.g., environmental conditions) for the environment of the SR setting **106**. As illustrated in FIG. 2, the emergent content engine **250** provides the objectives **254** to corresponding character/equipment/environmental engines. In the example of FIG. 2, the emergent content engine **250** provides the boy action figure objectives **254a** to the boy action figure character engine **208a**, the girl action figure objectives **254b** to the girl action figure character engine **208b**, the robot objectives **254c** to the robot equipment engine **208c**, the drone objectives **254d** to the drone equipment engine **208d**, and the environmental objectives **254e** to the environmental engine **208e**.

(44) In various implementations, the emergent content engine **250** generates the objectives **254** based on a function of possible objectives **252** (e.g., a set of predefined objectives), contextual information **258** characterizing the SR setting, and actions **210** provided by the character/equipment/environmental engines. For example, in some implementations, the emergent content engine **250** generates the objectives **254** by selecting the objectives **254** from the possible objectives **252** based on the contextual information **258** and/or the actions **210**. In some implementations, the possible objectives **252** are stored in a datastore. In some implementations, the possible objectives **252** are obtained from corresponding fictional source material (e.g., by scraping video games, movies, novels, and/or comics). For example, in some implementations, the possible objectives **252** for the girl action figure representation **108b** include saving lives, rescuing pets, fighting crime, etc.

(45) In some implementations, the emergent content engine **250** generates the objectives **254** based on the actions **210** provided by the character/equipment/environmental engines. In some implementations, the emergent content engine **250** generates the objectives **254** such that, given the actions **210**, a probability of completing the objectives **254** satisfies a threshold (e.g., the probability is greater than the threshold, for example, the probability is greater than 80%). In some implementations, the emergent content engine **250** generates objectives **254** that have a high likelihood of being completed with the actions **210**.

(46) In some implementations, the emergent content engine **250** ranks the possible objectives **252** based on the actions **210**. In some implementations, a rank for a particular possible objective **252** indicates the likelihood of completing that particular possible objective **252** given the actions **210**. In such implementations, the emergent content engine **250** generates the objective **254** by selecting the highest N ranking possible objectives **252**, where N is a predefined integer (e.g., 1, 3, 5, 10, etc.).

(47) In some implementations, the emergent content engine **250** establishes initial/end states **256** for the SR setting based on the objectives **254**. In some implementations, the initial/end states **256** indicate placements (e.g., locations) of various character/equipment representations within the SR

setting. In some implementations, the SR setting is associated with a time duration (e.g., a few seconds, minutes, hours, or days). For example, the SR setting is scheduled to last for the time duration. In such implementations, the initial/end states **256** indicate placements of various character/equipment representations at/towards the beginning and/or at/towards the end of the time duration. In some implementations, the initial/end states **256** indicate environmental conditions for the SR setting at/towards the beginning/end of the time duration associated with the SR setting.

(48) In some implementations, the emergent content engine **250** provides the objectives **254** to the display engine **260** in addition to the character/equipment/environmental engines. In some implementations, the display engine **260** determines whether the actions **210** provided by the character/equipment/environmental engines are consistent with the objectives **254** provided by the emergent content engine **250**. For example, the display engine **260** determines whether the actions **210** satisfy objectives **254**. In other words, in some implementations, the display engine **260** determines whether the actions **210** improve the likelihood of completing/achieving the objectives **254**. In some implementations, if the actions **210** satisfy the objectives **254**, then the display engine **260** modifies the SR setting in accordance with the actions **210**. In some implementations, if the actions **210** do not satisfy the objectives **254**, then the display engine **260** forgoes modifying the SR setting in accordance with the actions **210**.

(49) FIG. 3A is a block diagram of an example emergent content engine **300** in accordance with some implementations. In some implementations, the emergent content engine **300** implements the emergent content engine **250** shown in FIG. 2. In various implementations, the emergent content engine **300** generates the objectives **254** for various objective-effectuators that are instantiated in an SR setting (e.g., character/equipment representations such as the boy action figure representation **108a**, the girl action figure representation **108b**, the robot representation **108c**, and/or the drone representation **108d** shown in FIGS. 1A and 1B). In some implementations, at least some of the objectives **254** are for an environmental engine (e.g., the environmental engine **208e** shown in FIG. 2) that affects an environment of the SR setting.

(50) In various implementations, the emergent content engine **300** includes a neural network system **310** (“neural network **310**”, hereinafter for the sake of brevity), a neural network training system **330** (“a training module **330**”, hereinafter for the sake of brevity) that trains (e.g., configures) the neural network **310**, and a scraper **350** that provides possible objectives **360** to the neural network **310**. In various implementations, the neural network **310** generates the objectives **254** (e.g., the objectives **254a** for the boy action figure representation **108a**, the objectives **254b** for the girl action figure representation **108b**, the objectives **254c** for the robot representation **108c**, the objectives **254d** for the drone representation **108d**, and/or the environmental objectives **254e** shown in FIG. 2).

(51) In some implementations, the neural network **310** includes a long short-term memory (LSTM) recurrent neural network (RNN). In various implementations, the neural network **310** generates the objectives **254** based on a function of the possible objectives **360**. For example, in some implementations, the neural network **310** generates the objectives **254** by selecting a portion of the possible objectives **360**. In some implementations, the neural network **310** generates the objectives **254** such that the objectives **254** are within a degree of similarity to the possible objectives **360**.

(52) In various implementations, the neural network **310** generates the objectives **254** based on the contextual information **258** characterizing the SR setting. As illustrated in FIG. 3A, in some implementations, the contextual information **258** indicates instantiated equipment representations **340**, instantiated character representations **342**, user-specified scene/environment information **344**, and/or actions **210** from objective-effectuator engines.

(53) In some implementations, the neural network **310** generates the objectives **254** based on the instantiated equipment representations **340**. In some implementations, the instantiated equipment representations **340** refer to equipment representations that are located in the SR setting. For example, referring to FIGS. 1A and 1B, the instantiated equipment representations **340** include the

robot representation **108c** and the drone representation **108d** in the SR setting **106**. In some implementations, the objectives **254** include interacting with one or more of the instantiated equipment representations **340**. For example, referring to FIGS. **1A** and **1B**, in some implementations, one of the objectives **254a** for the boy action figure representation **108a** includes destroying the robot representation **108c**, and one of the objectives **254b** for the girl action figure representation **108b** includes protecting the robot representation **108c**.

(54) In some implementations, the neural network **310** generates the objectives **254** for each character representation based on the instantiated equipment representations **340**. For example, referring to FIGS. **1A** and **1B**, if the SR setting **106** includes the robot representation **108c**, then one of the objectives **254a** for the boy action figure representation **108a** includes destroying the robot representation **108c**. However, if the SR setting **106** does not include the robot representation **108c**, then the objective **254a** for the boy action figure representation **108a** includes maintaining peace within the SR setting **106**.

(55) In some implementations, the neural network **310** generates objectives **254** for each equipment representation based on the other equipment representations that are instantiated in the SR setting. For example, referring to FIGS. **1A** and **1B**, if the SR setting **106** includes the robot representation **108c**, then one of the objectives **254d** for the drone representation **108d** includes protecting the robot representation **108c**. However, if the SR setting **106** does not include the robot representation **108c**, then the objective **254d** for the drone representation **108d** includes hovering at the center of the SR setting **106**.

(56) In some implementations, the neural network **310** generates the objectives **254** based on the instantiated character representations **342**. In some implementations, the instantiated character representations **342** refer to character representations that are located in the SR setting. For example, referring to FIGS. **1A** and **1B**, the instantiated character representations **342** include the boy action figure representation **108a** and the girl action figure representation **108b** in the SR setting **106**. In some implementations, the objectives **254** include interacting with one or more of the instantiated character representations **342**. For example, referring to FIGS. **1A** and **1B**, in some implementations, one of the objectives **254d** for the drone representation **108d** includes following the girl action figure representation **108b**. Similarly, in some implementations, one of the objectives **254c** for the robot representation **108c** include avoiding the boy action figure representation **108a**.

(57) In some implementations, the neural network **310** generates the objectives **254** for each character representation based on the other character representations that are instantiated in the SR setting. For example, referring to FIGS. **1A** and **1B**, if the SR setting **106** includes the boy action figure representation **108a**, then one of the objectives **254b** for the girl action figure representation **108b** includes catching the boy action figure representation **108a**. However, if the SR setting **106** does not include the boy action figure representation **108a**, then the objective **254b** for the girl action figure representation **108b** includes flying around the SR setting **106**.

(58) In some implementations, the neural network **310** generates objectives **254** for each equipment representation based on the character representations that are instantiated in the SR setting. For example, referring to FIGS. **1A** and **1B**, if the SR setting **106** includes the girl action figure representation **108b**, then one of the objectives **254d** for the drone representation **108d** includes following the girl action figure representation **108b**. However, if the SR setting **106** does not include the girl action figure representation **108b**, then the objective **254d** for the drone representation **108d** includes hovering at the center of the SR setting **106**.

(59) In some implementations, the neural network **310** generates the objectives **254** based on the user-specified scene/environment information **344**. In some implementations, the user-specified scene/environment information **344** indicates boundaries of the SR setting. In such implementations, the neural network **310** generates the objectives **254** such that the objectives **254** can be satisfied (e.g., achieved) within the boundaries of the SR setting. In some implementations, the neural network **310** generates the objectives **254** by selecting a portion of the possible

objectives **252** that are better suited for the environment indicated by the user-specified scene/environment information **344**. For example, the neural network **310** sets one of the objectives **254d** for the drone representation **108d** to hover over the boy action figure representation **108a** when the user-specified scene/environment information **344** indicates that the skies within the SR setting are clear. In some implementations, the neural network **310** forgoes selecting a portion of the possible objectives **252** that are not suitable for the environment indicated by the user-specified scene/environment information **344**. For example, the neural network **310** forgoes the hovering objective for the drone representation **108d** when the user-specified scene/environment information **344** indicates high winds within the SR setting.

(60) In some implementations, the neural network **310** generates the objectives **254** based on the actions **210** provided by various objective-effectuator engines. In some implementations, the neural network **310** generates the objectives **254** such that the objectives **254** can be satisfied (e.g., achieved) given the actions **210** provided by the objective-effectuator engines. In some implementations, the neural network **310** evaluates the possible objectives **360** with respect to the actions **210**. In such implementations, the neural network **310** generates the objectives **360** by selecting the possible objectives **360** that can be satisfied by the actions **210** and forgoing selecting the possible objectives **360** that cannot be satisfied by the actions **210**.

(61) In various implementations, the training module **330** trains the neural network **310**. In some implementations, the training module **330** provides neural network (NN) parameters **312** to the neural network **310**. In some implementations, the neural network **310** includes model(s) of neurons, and the neural network parameters **312** represent weights for the model(s). In some implementations, the training module **330** generates (e.g., initializes or initiates) the neural network parameters **312**, and refines (e.g., adjusts) the neural network parameters **312** based on the objectives **254** generated by the neural network **310**.

(62) In some implementations, the training module **330** includes a reward function **332** that utilizes reinforcement learning to train the neural network **310**. In some implementations, the reward function **332** assigns a positive reward to objectives **254** that are desirable, and a negative reward to objectives **254** that are undesirable. In some implementations, during a training phase, the training module **330** compares the objectives **254** with verification data that includes verified objectives. In such implementations, if the objectives **254** are within a degree of similarity to the verified objectives, then the training module **330** stops training the neural network **310**. However, if the objectives **254** are not within the degree of similarity to the verified objectives, then the training module **330** continues to train the neural network **310**. In various implementations, the training module **330** updates the neural network parameters **312** during/after the training.

(63) In various implementations, the scraper **350** scrapes content **352** to identify the possible objectives **360**. In some implementations, the content **352** includes movies, video games, comics, novels, and fan-created content such as blogs and commentary. In some implementations, the scraper **350** utilizes various methods, systems and/or, devices associated with content scraping to scrape the content **352**. For example, in some implementations, the scraper **350** utilizes one or more of text pattern matching, HTML (Hyper Text Markup Language) parsing, DOM (Document Object Model) parsing, image processing and audio analysis to scrape the content **352** and identify the possible objectives **360**.

(64) In some implementations, an objective-effectuator is associated with a type of representation **362**, and the neural network **310** generates the objectives **254** based on the type of representation **362** associated with the objective-effectuator. In some implementations, the type of representation **362** indicates physical characteristics of the objective-effectuator (e.g., color, material type, texture, etc.). In such implementations, the neural network **310** generates the objectives **254** based on the physical characteristics of the objective-effectuator. In some implementations, the type of representation **362** indicates behavioral characteristics of the objective-effectuator (e.g., aggressiveness, friendliness, etc.). In such implementations, the neural network **310** generates the

objectives **254** based on the behavioral characteristics of the objective-effectuator. For example, the neural network **310** generates an objective of being destructive for the boy action figure representation **108a** in response to the behavioral characteristics including aggressiveness. In some implementations, the type of representation **362** indicates functional and/or performance characteristics of the objective-effectuator (e.g., strength, speed, flexibility, etc.). In such implementations, the neural network **310** generates the objectives **254** based on the functional characteristics of the objective-effectuator. For example, the neural network **310** generates an objective of always moving for the girl action figure representation **108b** in response to the behavioral characteristics including speed. In some implementations, the type of representation **362** is determined based on a user input. In some implementations, the type of representation **362** is determined based on a combination of rules.

(65) In some implementations, the neural network **310** generates the objectives **254** based on specified objectives **364**. In some implementations, the specified objectives **364** are provided by an entity that controls (e.g., owns or created) the fictional material from where the character/equipment originated. For example, in some implementations, the specified objectives **364** are provided by a movie producer, a video game creator, a novelist, etc. In some implementations, the possible objectives **360** include the specified objectives **364**. As such, in some implementations, the neural network **310** generates the objectives **254** by selecting a portion of the specified objectives **364**.

(66) In some implementations, the possible objectives **360** for an objective-effectuator are limited by a limiter **370**. In some implementations, the limiter **370** restricts the neural network **310** from selecting a portion of the possible objectives **360**. In some implementations, the limiter **370** is controlled by the entity that owns (e.g., controls) the fictional material from where the character/equipment originated. For example, in some implementations, the limiter **370** is controlled by a movie producer, a video game creator, a novelist, etc. In some implementations, the limiter **370** and the neural network **310** are controlled/operated by different entities. In some implementations, the limiter **370** restricts the neural network **310** from generating objectives that breach a criterion defined by the entity that controls the fictional material.

(67) FIG. 3B is a block diagram of the neural network **310** in accordance with some implementations. In the example of FIG. 3B, the neural network **310** includes an input layer **320**, a first hidden layer **322**, a second hidden layer **324**, a classification layer **326**, and an objective selection module **328**. While the neural network **310** includes two hidden layers as an example, those of ordinary skill in the art will appreciate from the present disclosure that one or more additional hidden layers are also present in various implementations. Adding additional hidden layers adds to the computational complexity and memory demands, but may improve performance for some applications.

(68) In various implementations, the input layer **320** receives various inputs. In some implementations, the input layer **320** receives the contextual information **258** as input. In the example of FIG. 3B, the input layer **320** receives inputs indicating the instantiated equipment **340**, the instantiated characters **342**, the user-specified scene/environment information **344**, and the actions **210** from the objective-effectuator engines. In some implementations, the neural network **310** includes a feature extraction module (not shown) that generates a feature stream (e.g., a feature vector) based on the instantiated equipment **340**, the instantiated characters **342**, the user-specified scene/environment information **344**, and/or the actions **210**. In such implementations, the feature extraction module provides the feature stream to the input layer **320**. As such, in some implementations, the input layer **320** receives a feature stream that is a function of the instantiated equipment **340**, the instantiated characters **342**, the user-specified scene/environment information **344**, and the actions **210**. In various implementations, the input layer **320** includes a number of LSTM logic elements **320a**, which are also referred to as neurons or models of neurons by those of ordinary skill in the art. In some such implementations, an input matrix from the features to the

LSTM logic elements **320a** includes rectangular matrices. The size of this matrix is a function of the number of features included in the feature stream.

(69) In some implementations, the first hidden layer **322** includes a number of LSTM logic elements **322a**. As illustrated in the example of FIG. 3B, the first hidden layer **322** receives its inputs from the input layer **320**.

(70) In some implementations, the second hidden layer **324** includes a number of LSTM logic elements **324a**. In some implementations, the number of LSTM logic elements **324a** is the same as or similar to the number of LSTM logic elements **320a** in the input layer **320** or the number of LSTM logic elements **322a** in the first hidden layer **322**. As illustrated in the example of FIG. 3B, the second hidden layer **324** receives its inputs from the first hidden layer **322**. Additionally or alternatively, in some implementations, the second hidden layer **324** receives its inputs from the input layer **320**.

(71) In some implementations, the classification layer **326** includes a number of LSTM logic elements **326a**. In some implementations, the number of LSTM logic elements **326a** is the same as or similar to the number of LSTM logic elements **320a** in the input layer **320**, the number of LSTM logic elements **322a** in the first hidden layer **322** or the number of LSTM logic elements **324a** in the second hidden layer **324**. In some implementations, the classification layer **326** includes an implementation of a multinomial logistic function (e.g., a soft-max function) that produces a number of outputs that is approximately equal to the number of possible actions **360**. In some implementations, each output includes a probability or a confidence measure of the corresponding objective being satisfied by the actions **210**. In some implementations, the outputs do not include objectives that have been excluded by operation of the limiter **370**.

(72) In some implementations, the objective selection module **328** generates the objectives **254** by selecting the top N objective candidates provided by the classification layer **326**. In some implementations, the top N objective candidates are likely to be satisfied by the actions **210**. In some implementations, the objective selection module **328** provides the objectives **254** to a rendering and display pipeline (e.g., the display engine **260** shown in FIG. 2). In some implementations, the objective selection module **328** provides the objectives **254** to one or more objective-effectuator engines (e.g., the boy action figure character engine **208a**, the girl action figure character engine **208b**, the robot equipment engine **208c**, the drone equipment engine **208d**, and/or the environmental engine **208e** shown in FIG. 2).

(73) FIG. 4A is a flowchart representation of a method **400** of generating content for SR settings. In various implementations, the method **400** is performed by a device with a non-transitory memory and one or more processors coupled with the non-transitory memory (e.g., the controller **102**, the electronic device **103** shown in FIG. 1A, and/or the HMD **104** shown in FIG. 1B). In some implementations, the method **400** is performed by processing logic, including hardware, firmware, software, or a combination thereof. In some implementations, the method **400** is performed by a processor executing code stored in a non-transitory computer-readable medium (e.g., a memory). Briefly, in some implementations, the method **400** includes instantiating an objective-effectuator into an SR setting, obtaining contextual information for the SR setting, generating an objective for the objective-effectuator, setting environmental conditions for the SR setting, establishing initial conditions for the objective-effectuator based on the objective, and modifying the objective-effectuator based on the objective.

(74) As represented by block **410**, in various implementations, the method **400** includes instantiating an objective-effectuator into an SR setting (e.g., instantiating the boy action figure representation **108a**, the girl action figure representation **108b**, the robot representation **108c**, and/or the drone representation **108d** into the SR setting **106** shown in FIGS. 1A and 1B). In some implementations, the objective-effectuator is characterized by a set of predefined objectives (e.g., the possible objectives **360** shown in FIG. 3A) and a set of visual rendering attributes.

(75) As represented by block **420**, in various implementations, the method **400** includes obtaining

contextual information characterizing the SR setting (e.g., the contextual information **258** shown in FIGS. 2-3B). In some implementations, the method **400** includes receiving the contextual information (e.g., from a user).

(76) As represented by block **430**, in various implementations, the method **400** includes generating an objective for the objective-effectuator based on a function of the set of predefined objectives, the contextual information, and a set of predefined actions for the objective-effectuator. For example, referring to FIG. 2, the method **400** includes generating the objectives **254** based on the possible objectives **252**, the contextual information **258**, and the actions **210**.

(77) As represented by block **440**, in various implementations, the method **400** includes setting environmental conditions for the SR setting based on the objective for the objective-effectuator. For example, referring to FIG. 2, the method **400** includes generating the environmental objectives **254e** (e.g., the environmental conditions).

(78) As represented by block **450**, in various implementations, the method **400** includes establishing initial conditions and a current set of actions for the objective-effectuator based on the objective for the objective-effectuator. For example, referring to FIG. 2, the method **400** include establishing the initial/end states **256** for various objective-effectuators (e.g., character representations, equipment representations and/or the environment).

(79) As represented by block **460**, in various implementations, the method **400** includes modifying the objective-effectuator based on the objective. For example, referring to FIG. 2, in some implementations, the method **400** includes providing the objectives **254** to the display engine **260** and/or to one or more objective-effectuator engines.

(80) Referring to FIG. 4B, as represented by block **410a**, in various implementations, the method **400** includes obtaining a set of predefined objectives (e.g., the possible objectives **360** shown in FIG. 3A) from source material (e.g., the content **352** shown in FIG. 3A, for example, movies, books, video games, comics, and/or novels). As represented by block **410b**, in various implementations, the method **400** includes scraping the source material for the set of predefined objectives.

(81) As represented by block **410c**, in some implementations, the method **400** includes determining the set of predefined objectives based on a type of representation (e.g., the type of representation **362** shown in FIG. 3A). As represented by block **410d**, in some implementations, the method **400** includes determining the set of predefined objectives based on user-specified configuration (e.g., the type of representation **362** shown in FIG. 3A is determined based on a user input).

(82) As represented by block **410e**, in some implementations, the method **400** includes determining the predefined objectives based on a limit specified by an object owner. For example, referring to FIG. 3A, in some implementations, the method **400** includes limiting the possible objectives **360** selectable by the neural network **310** by operation of the limiter **370**.

(83) As represented by block **410f**, in some implementations, the SR setting (e.g., the SR setting **106** shown in FIGS. 1A and 1B) include an SR setting that is a simulated replacement of a real-world scene.

(84) As represented by block **410g**, in some implementations, the SR setting (e.g., the SR setting **106** shown in FIGS. 1A and 1B) includes an augmented scene that is a modified version of a real-world scene.

(85) As represented by block **410h**, in some implementations, the objective-effectuator is a representation of a character (e.g., the boy action figure representation **108a** and/or the girl action figure representation **108b** shown in FIGS. 1A and 1B) from one or more of a movie, a video game, a comic, a novel, or the like.

(86) As represented by block **410i**, in some implementations, the objective-effectuator is a representation of an equipment (e.g., the robot representation **108c** and/or the drone representation **108d** shown in FIGS. 1A and 1B) from one or more of a movie, a video game, a comic, a novel, or the like.

(87) As represented by block **410j**, in some implementations, the method **400** includes obtaining a set of visual rendering attributes from an image. For example, in some implementations, the method **400** includes capturing an image and extracting the visual rendering attributes from the image (e.g., by utilizing devices, methods, and/or systems associated with image processing).

(88) Referring to FIG. 4C, as represented by block **420a**, in various implementations, the contextual information indicates whether objective-effectuators have been instantiated in the SR setting. As represented by block **420b**, in some implementations, the contextual information indicates which character representations have been instantiated in the SR setting (e.g., the contextual information includes the instantiated characters representation **342** shown in FIGS. 3A-3B). As represented by block **420c**, in some implementations, the contextual information indicates equipment representations that have been instantiated in the SR setting (e.g., the contextual information includes the instantiated equipment representations **340** shown in FIGS. 3A-3B).

(89) As represented by block **420d**, in various implementations, the contextual information includes user-specified scene information (e.g., user-specified scene/environment information **344** shown in FIGS. 3A-3B). As represented by block **420e**, in various implementations, the contextual information indicates a terrain (e.g., a landscape, for example, natural artifacts such as mountains, rivers, etc.) of the SR setting. As represented by block **420f**, in various implementations, the contextual information indicates environmental conditions within the SR setting (e.g., the user-specified scene/environmental information **344** shown in FIGS. 3A-3B).

(90) As represented by block **420g**, in some implementations, the contextual information includes a mesh map of a real-world scene (e.g., a detailed representation of the real-world scene where the device is located). In some implementations, the mesh map indicates positions and/or dimensions of real-world artifacts that are located at the real-world scene.

(91) Referring to FIG. 4D, as represented by block **430a**, in some implementations, the method **400** includes utilizing a neural network (e.g., the neural network **310** shown in FIGS. 3A-3B) to generate the objectives. As represented by block **430b**, in some implementations, the neural network generates the objectives based on a set of neural network parameters (e.g., the neural network parameters **312** shown in FIG. 3A). As represented by block **430c**, in some implementations, the method **400** includes adjusting the neural network parameters based on the objectives generated by the neural network (e.g., adjusting the neural network parameters **312** based on the objectives **254** shown in FIG. 3A).

(92) As represented by block **430d**, in some implementations, the method **400** includes determining neural network parameters based on a reward function (e.g., the reward function **332** shown in FIG. 3A) that assigns a positive reward to desirable objectives and a negative reward to undesirable objectives. As represented by block **430e**, in some implementations, the method **400** includes configuring (e.g., training) the neural network based on reinforcement learning. As represented by block **430f**, in some implementations, the method **400** includes training the neural network based on content scraped (e.g., by the scraper **350** shown in FIG. 3A) from videos such as movies, books such as novels and comics, and video games.

(93) As represented by block **430g**, in some implementations, the method **400** includes generating a first objective if a second objective-effectuator is instantiated in the SR setting. As represented by block **430h**, in some implementations, the method **400** includes generating a second objective if a third objective-effectuator is instantiated in the SR setting. More generally, in various implementations, the method **400** includes generating different objectives for an objective-effectuator based on the other objective-effectuators that are present in the SR setting.

(94) As represented by block **430i**, in some implementations, the method **400** includes selecting an objective if, given a set of actions, the likelihood of the objective being satisfied is greater than a threshold. As represented by block **430j**, in some implementations, the method **400** includes forgoing selecting an objective if, given the set of actions, the likelihood of the objective being satisfied is less than the threshold.

(95) Referring to FIG. 4E, as represented by block **440a**, in some implementations, the method **400** includes setting one or more of a temperature value, a humidity value, a pressure value and a precipitation value within the SR setting. In some implementations, the method **400** includes making it rain or snow in the SR setting. As represented by block **440b**, in some implementations, the method **400** includes setting one or more of an ambient sound level value (e.g., in decibels) and an ambient lighting level value (e.g., in lumens) for the SR setting. As represented by block **440c**, in some implementations, the method **400** includes setting states of celestial bodies within the SR setting (e.g., setting a sunrise or a sunset, setting a full moon or a partial moon, etc.).

(96) As represented by block **450a**, in some implementations, the method **400** includes establishing initial/end positions of objective-effectuators. In some implementations, the SR setting is associated with a time duration. In such implementations, the method **400** includes setting initial positions that the objective-effectuators occupy at or near the beginning of the time duration, and/or setting end positions that the objective-effectuators occupy at or near the end of the time duration.

(97) As represented by block **450b**, in some implementations, the method **400** includes establishing initial/end actions for objective-effectuators. In some implementations, the SR setting is associated with a time duration. In such implementations, the method **400** includes establishing initial actions that the objective-effectuators perform at or near the beginning of the time duration, and/or establishing end actions that the objective-effectuators perform at or near the end of the time duration.

(98) As represented by block **460a**, in some implementations, the method **400** includes providing the objectives to a rendering and display pipeline (e.g., the display engine **260** shown in FIG. 2). As represented by block **460b**, in some implementations, the method **400** includes modifying the objective-effectuator such that the objective-effectuator can be seen as performing actions that satisfy the objectives.

(99) FIG. 5 is a block diagram of a server system **500** enabled with one or more components of a device (e.g., the controller **102**, the electronic device **103** shown in FIG. 1A, and/or the HMD **104** shown in FIG. 1B) in accordance with some implementations. While certain specific features are illustrated, those of ordinary skill in the art will appreciate from the present disclosure that various other features have not been illustrated for the sake of brevity, and so as not to obscure more pertinent aspects of the implementations disclosed herein. To that end, as a non-limiting example, in some implementations, the server system **500** includes one or more processing units (CPUs) **501**, a network interface **502**, a programming interface **503**, a memory **504**, and one or more communication buses **505** for interconnecting these and various other components.

(100) In some implementations, the network interface **502** is provided to communicate with one or more local devices (e.g., via near-field communication or a local network) and/or one or more remote devices (e.g., WiFi, Ethernet, etc.). In some implementations, the one or more communication buses **505** include circuitry that interconnects and controls communications between system components. The memory **504** includes high-speed random-access memory, such as DRAM, SRAM, DDR RAM or other random-access solid-state memory devices, and may include non-volatile memory, such as one or more magnetic disk storage devices, optical disk storage devices, flash memory devices, or other non-volatile solid-state storage devices. The memory **504** optionally includes one or more storage devices remotely located from the one or more CPUs **501**. The memory **504** comprises a non-transitory computer readable storage medium.

(101) In some implementations, the memory **504** or the non-transitory computer readable storage medium of the memory **504** stores the following programs, modules and data structures, or a subset thereof including an optional operating system **506**, the neural network **310**, the training module **330**, the scraper **350**, and the possible objectives **360**. As described herein, the neural network **310** is associated with the neural network parameters **312**. As described herein, the training module **330** includes a reward function **332** that trains (e.g., configures) the neural network **310** (e.g., by determining the neural network parameters **312**). As described herein, the neural network **310**

determines objectives (e.g., the objectives **254** shown in FIGS. 2-3B) for objective-effectuators in an SR setting and/or for the environment of the SR setting. In some implementations, the memory **504** include at least a portion of the emergent content architectures in FIGS. 8A-8C.

(102) In some implementations, the electronic device **500** optionally includes one or more input devices such as an eye tracker, touch-sensitive surface, keypad or keyboard, accelerometer, gyroscope, inertial measurement unit (IMU), grip sensor, one or more microphones, one or more buttons, one or more interior-facing image sensors, one or more exterior-facing image sensors, one or more depth sensors, one or more physiological sensors (e.g., heartbeat sensor, glucose level detector, etc.), one or more environmental sensors (e.g., barometer, humidity sensor, thermometer, ambient light detector, etc.), and/or the like. In some implementations, the electronic device **500** optionally includes one or more output/feedback devices such as a haptics engine, skin shear engine, one or more displays, one or more speakers, and/or the like.

(103) FIG. 6A is a block diagram of conditionally dependent SR content threads **600** in accordance with some implementations. While certain specific features are illustrated, those of ordinary skill in the art will appreciate from the present disclosure that various other features have not been illustrated for the sake of brevity, and so as not to obscure more pertinent aspects of the implementations disclosed herein. To that end, as a non-limiting example, in some implementations, the conditionally dependent SR content threads **600** correspond to a mesh of related content threads (e.g., stories, narratives, etc.) associated with a movie, TV episode, novel, theatrical play, or event such as an athletic event, ritual, coronation, inauguration, concert, opera, theatrical performance, battle, or other large-scale occurrence.

(104) According to some implementations, the conditionally dependent SR content threads **600** includes a plurality of content threads (sometime also referred to herein as “stories” or “story nodes” for the sake of brevity) that are linked together in a tree, mesh, or web of inter-related stories. In some implementations, each of the plurality of stories within the conditionally dependent SR content threads **600** corresponds to a particular point-of-view of the event. In some implementations, each of the plurality of stories within the conditionally dependent SR content threads **600** is based on source assets/materials including, for example, plans for the event such as battle plans or an order of battle, ground truth for the event such as the course and outcomes of the battle, historical accounts and books, movies, video games, novels, and/or the like.

(105) According to some implementations, the root of the conditionally dependent SR content threads **600** includes a super-macro story **610**, which is, in turn, associated with one or more macro stories **620a**, **620b**, . . . , **620n** (sometimes collectively referred to herein as macro stories **620**). As shown in FIG. 6A, in some implementations, each of the macro stories **620** is associated with one or more sub-macro stories. For example, the macro story **620a** is associated with sub-macro stories **632a**, **632b**, . . . , **632n** (sometimes collectively referred to herein as sub-macro stories **632**), and the macro story **620n** is associated with sub-macro stories **634a**, **634b**, . . . , **634n** (sometimes collectively referred to herein as sub-macro stories **634**).

(106) As shown in FIG. 6A, in some implementations, each of the sub-macro stories is associated with one or more micro stories. For example, the sub-macro story **634a** is associated with micro stories **640a**, . . . , **640n** (sometimes collectively referred to herein as micro stories **640**). In some implementations, each of the micro stories **640** is associated with one or more sub-micro stories and, in turn, each of the sub-micro stories is associated with one or more super-micro stories. As shown in FIGS. 6, for example, the micro story **640a** is associated with a sub-micro story **650**, and the sub-micro story **650** is associated with a super-micro story **660**.

(107) As one example, the super-macro story **610** corresponds to the overall story associated with a particular battle of a war in the historical records. Continuing with this example, the macro stories **620** correspond to various military branches for the countries involved in a particular battle. As such, in this example, the macro story **620n** corresponds to a naval military branch. Continuing with this example, the sub-macro stories **634** correspond to individual ships. As such, in this

example, the sub-macro story **634a** corresponds to a particular transport ship.

(108) As shown in FIG. **6A**, there is a relationship **635** between the sub-macro story **632n** corresponding to a squadron of aircraft and the sub-macro story **634a**. In this example, the squadron of aircraft are providing air support and defense for the particular transport ship (among other transport ships).

(109) Continuing with this example, the micro stories **640** correspond to a plurality of amphibious landing craft being transported by the particular transport ship. Continuing with this example, the sub-micro story **650** corresponds to a platoon of infantry or marines assigned to respective amphibious landing craft among the plurality of amphibious landing craft being transported by the particular transport ship. Continuing with this example, the super-micro story **660** corresponds to a particular infantryman or marine assigned to the respective amphibious landing craft.

(110) In some implementations, a user is presented SR content associated with an omniscient third-person view of the super-macro story **610** (e.g., a particular battle). The user may switch to another point-of-view within the conditionally dependent SR content threads **600** in order to view SR content associated with the selected point-of-view within the conditionally dependent SR content threads **600** such as the perspective of the naval military branch associated with macro story **620n**, the perspective of the particular transport ship associated with the sub-macro story **634a**, the perspective of the respective amphibious landing craft, the perspective of the platoon of infantry or marines associated with sub-micro story **650**, or the perspective the particular infantryman or marine assigned to the respective amphibious landing craft associated with the super-micro story **660**.

(111) According to some implementations, a node of the conditionally dependent SR content threads **600** may be removed by the user in order to view a simulation of the event that excludes the particular node and associated child nodes. According to some implementations, a node may be added to the conditionally dependent SR content threads **600** by the user in order to view a simulation of the event that includes the particular node and associated child nodes.

(112) FIG. **6B** is a block diagram of a timeline **675** associated with an objective-effectuator (OE) encapsulation in accordance with some implementations. While certain specific features are illustrated, those of ordinary skill in the art will appreciate from the present disclosure that various other features have not been illustrated for the sake of brevity, and so as not to obscure more pertinent aspects of the implementations disclosed herein. To that end, as a non-limiting example, as shown in FIG. **6B**, the timeline **675** illustrates the state of an OE encapsulation from the point-of-view of a lowest-level OE **684** at a plurality of time periods or temporal points **T0**, **T1**, **T2**, and **T3**.

(113) In some implementations, an OE encapsulation includes a plurality of conditional, related, correlated, associated, or dependent OEs that are encapsulated or nested based on contextual information. In some implementations, each OE corresponds to a character within a synthesized reality (SR) setting. As one example, an OE encapsulation corresponds to a set of related characters or entities such as a transport ship including N amphibious landing crafts each with M marines. In this example, the lowest-level OE is an individual marine that is encapsulated/nested within his company, which, in turn, is encapsulated/nested within the amphibious land craft. Continuing with this example, the amphibious land craft is encapsulated/nested within the transport ship.

(114) In some implementations, when the first OE is encapsulated within the second OE, the first OE is associated with the second OE. In some implementations, when the first OE is encapsulated within the second OE, the first OE is correlated with the second OE. In some implementations, when the first OE is encapsulated within the second OE, the first OE is related to the second OE. In some implementations, when the first OE is encapsulated within the second OE, the first OE is dependent on the second OE. In other words, the first OE is provided objectives and performs actions that are consistent with the context and attributes of the second OE because the first OE is encapsulated within the second OE.

(115) As shown in FIG. 6B, at time T0, the OE encapsulation **685a** includes an OE **684** encapsulated/nested within an OE **682**, which, in turn, is encapsulated/nested within an OE **680**. For example, at time T0, while approaching a beach to make an amphibious landing, the OE encapsulation **685a** includes the OE **684** (e.g., an individual marine) encapsulated/nested within the OE **682** (e.g., a company of marines), which, in turn, is encapsulated/nested within an OE **680** (e.g., an amphibious landing craft).

(116) In some implementations, when a first OE is encapsulated/nested within a second OE, the first OE is provided an objective based on the context of the second OE within which it is encapsulated and, in turn, the first OE performs actions that are consistent with that context. As an example, a marine on a transport ship is not given a scouting objective to perform scouting patrols or a fire suppression objective to mortar a target while on the transport ship. In some implementations, the lower-level OE performs actions consistent with higher-level OEs in its encapsulation. In some implementations, one or more other lower-level OEs are encapsulated within the first OE. In some implementations, the second OE is encapsulated within one or more other higher-level OEs.

(117) In some implementations, the system determines a set of OE encapsulations for each time period of the event. As such, an OE encapsulation may change over the course of the event such as OEs (layers) being stripped away or added. As one example, a particular battle encapsulation starts as transport ship->amphibious assault vehicle->company of marines->individual marine while in transport (T0). Continuing with this example, the OE encapsulation changes to amphibious assault vehicle->company of marines->individual marine while approaching the beach (T1). Continuing with this example, the OE encapsulation changes again to company of marines->individual marine while storming the beach (T2). Continuing with this example, the OE encapsulation changes again when the marines may find and enter a vehicle after reaching the beach (T3) which changes the encapsulation to vehicle->subset of company of marines->individual marine.

(118) As shown in FIG. 6B, at time T1, the OE encapsulation **685b** includes the OE **684** encapsulated/nested within the OE **682**. For example, at time T1, after landing on a beach, the OE encapsulation **685b** includes the OE **684** (e.g., the individual marine) encapsulated/nested within the OE **682** (e.g., the company of marines).

(119) As shown in FIG. 6B, at time T2, the OE encapsulation **685c** includes the OE **684**. For example, at time T2, after landing on a beach and completing a mission, the OE encapsulation **685c** includes the OE **684** (e.g., the individual marine) apparat from the OE **682**.

(120) As shown in FIG. 6B, at time T3, the OE encapsulation **685d** includes the OE **684** encapsulated/nested within the OE **686**. For example, at time T3, after landing on a beach and reaching a rendezvous point, the OE encapsulation **685d** includes the OE **684** (e.g., the individual marine) encapsulated/nested within the OE **686** (e.g., an evacuation helicopter or truck).

(121) FIG. 6C is a block diagram of a timeline **695** associated with an objective-effectuator (OE) encapsulation in accordance with some implementations. While certain specific features are illustrated, those of ordinary skill in the art will appreciate from the present disclosure that various other features have not been illustrated for the sake of brevity, and so as not to obscure more pertinent aspects of the implementations disclosed herein. To that end, as a non-limiting example, the timeline **695** is related to the timeline **675** in FIG. 6B. The time **695** illustrates the parallel functioning of the OEs even after the OE encapsulation changes over the time periods or temporal points T0, T1, T2, and T3. In other words, FIG. 6C illustrates the OEs **680** and **682** that are stripped away from the OE encapsulation **685a** and **685b** over time continuing to function in parallel with the OE **684**.

(122) FIGS. 7A-7C illustrate example SR settings **700a** and **700b** in accordance with some implementations. While pertinent features are shown, those of ordinary skill in the art will appreciate from the present disclosure that various other features have not been illustrated for the sake of brevity and so as not to obscure more pertinent aspects of the example implementations

disclosed herein.

(123) FIG. 7A illustrates an example SR setting **700a**. As shown in FIG. 7A, the physical setting **706** includes a table **702**. In this example, a portion of the physical setting **706** is within the field-of-view **704** of the electronic device **103**, where the field-of-view **704** is associated with an external facing image sensor of the electronic device **103** (e.g., a tablet or mobile phone). In other words, the user is looking at the table **702** from a side or perspective orientation through the electronic device **103**. As such, the portion of the physical setting **706**, including the table **702**, is displayed on the display **705** of the electronic device **103** (e.g., a live video stream or video pass-through of the physical setting **706**). As shown in FIG. 7A, the electronic device **103** displays an SR setting **106** on the display **705** that includes SR content superimposed on or composited with the table **702** and the wall.

(124) As shown in FIG. 7A, for example, the SR content (e.g., associated with a particular battle) overlaid or superimposed on the table **702** includes a first SR content layer **710a** (e.g., an underwater layer) with SR content elements **712** (e.g., sunken ships, sunken amphibious landing craft, underwater mines, and/or the like), a second AR content layer **710b** (e.g., a water surface layer) with SR content elements **714** (e.g., amphibious landing craft with platoons of infantrymen or marines, transport ships, and/or the like), and a third SR content layer **710c** (e.g., an aerial layer) with SR content elements **716** (e.g., aircraft, dirigibles, shells, and/or the like). As shown in FIG. 7A, for example, the SR content **720** overlaid on the wall includes SR content elements **722** (e.g., defensive position, stationary guns, and/or the like on land). One of ordinary skill in the art will appreciate that the number, structure, dimensions, and placement of the SR content layers and associated SR content elements in FIG. 7A is arbitrary and may be changed in various other implementations.

(125) FIGS. 7B and 7C illustrate an example SR setting **700b**. As shown in FIGS. 7B and 7C, as one example, the user **10** wears the HMD **104** his/her head (e.g., AR-enabled glasses) with optical see-through of the physical setting **706** (e.g., the user's living room). As shown in FIGS. 7B and 7C, as another example, the user **10** wears the HMD **104** on his/her head (e.g., an SR-enabled headset) with video pass-through of the physical setting **706** (e.g., the user's living room).

(126) As shown in FIG. 7B, in state **725** (e.g., associated with time period **T1**), the HMD **104** superimposes or overlays SR content on the table **702** and the walls of the physical setting **706**. In this example, with reference to state **725**, the SR content (e.g., associated with a particular battle) overlaid on the table **702** includes a first SR content layer **710a** (e.g., an underwater layer) with SR content elements **712** (e.g., sunken ships, sunken amphibious landing craft, underwater mines, and/or the like), a second SR content layer **710b** (e.g., a water surface layer) with SR content elements **714** (e.g., amphibious landing craft with platoons of infantrymen or marines, transport ships, and/or the like), and a third SR content layer **710c** (e.g., an aerial layer) with SR content elements **716** (e.g., aircraft, dirigibles, shells, and/or the like). As shown in FIG. 7B, with reference to state **725**, the SR content elements **720** overlaid on the front wall includes SR content elements **722** (e.g., defensive position, stationary guns, and/or the like on land), and the SR content elements **730** overlaid on the side wall includes peripheral or environment details. One of ordinary skill in the art will appreciate that the number, structure, dimensions, and placement of the SR content layers and associated SR content elements in FIG. 7B is arbitrary and may be changed in various other implementations.

(127) As shown in FIG. 7B, state **725** corresponds to a first SR view of the event such as an omniscient third-person view of the overall event (e.g., a particular battle). In response to receiving an input from the user **10** (e.g., a voice command, gesture, or the like) selecting the third AR content layer **710c** (e.g., an aerial layer), the HMD **104** presents a second SR view of the event associated with the third SR content layer **710c** (e.g., an aerial layer).

(128) As shown in FIG. 7C, in state **735** (e.g., associated with time period **T2**), the HMD **104** updates the SR content superimposed or overlaid on the table **702** in response to the selectin of the

third AR content layer **710c**. As shown in FIG. 7C, in state **735**, the HMD **104** superimposes or overlays SR content on the table **702** that corresponds to the third SR content layer **710c**. In this example, with reference to state **735**, the SR content (e.g., associated with a particular battle) overlaid on the table **702** includes the third SR content layer **710c** (e.g., an aerial layer) with SR content elements **716** (e.g., aircraft, dirigibles, shells, and/or the like). For example, in FIG. 7C, the third SR content layer **710c** corresponds to a center of gravity of a squadron of aircraft on approach to attack the defensive positions on within a battle site. As another example, in state **735**, the user **10** may be presented the point-of-view of a particular pilot among the squadron of aircraft on approach to attack the defensive positions on a battle site (not shown).

(129) FIG. **8A** is a block diagram of an emergent content architecture **800** in accordance with some implementations. While certain specific features are illustrated, those of ordinary skill in the art will appreciate from the present disclosure that various other features have not been illustrated for the sake of brevity, and so as not to obscure more pertinent aspects of the implementations disclosed herein. To that end, as a non-limiting example, in some implementations, an objective-effectuator (OE) encapsulation of related (e.g., encapsulated/nested) OE engines **810a**, **810b**, **810c**, and **810d** (sometimes collectively referred to herein as the OE engines **810**) (e.g., similar to character engines **208a-e** in FIG. 2) perform actions based on objectives derived from the objective generator **807**.

(130) As one example, the OE encapsulation includes a top-level OE engine **810a** associated with a transport ship, a second-level OE engine **810b** associated with an amphibious landing craft being transported by the transport ship, a third-level OE engine **810c** associated a platoon of infantrymen or marine assigned to the amphibious landing craft, and a bottom-level OE engine **810d** associated with a particular infantryman or marine. As such, the various OE engines within the OE encapsulation are related in some manner as they correspond to connected nodes within a conditionally dependent SR content threads associated with the event (e.g., as described with reference to the story nodes in FIG. 6A). According to some implementations, the emergent content architecture **800** is structured to produce concurrent actions for the various OE engines within the OE encapsulation for consistent content. In various implementations, one of ordinary skill in the art will appreciate that emergent content architecture **800** may include an arbitrary number of OE encapsulations. In some implementations, a same OE engine may be shared between two or more OE encapsulations due to the related nature of OEs to OE encapsulations.

(131) According to some implementations, the objective generator **807** (e.g., a neural network or other AI construct) produces objectives for each OE per time period based on a bank of predetermined objectives, previous objectives, source assets, and/or other information (e.g., similar to the emergent content engine **250** in FIG. 2). According to some implementations, the encapsulation manager **825** determines the OE encapsulation (e.g., the nesting or layering of related OEs). For example, the encapsulation manager **825** determines the OE encapsulation based on the connections between the story nodes within conditionally dependent SR content threads associated with the event. In some implementations, the encapsulation manager **825** modifies the OE encapsulation over time (e.g., adding or removing layers of OEs) based on the objectives, source assets, and/or other information.

(132) In some implementations, the demultiplexer **845** routes the objectives on a per OE basis to their respective OE engines **810**. In some implementations, the OE engines **810** perform actions based on their objectives. According to some implementations, the actions for a time period are captured and provided to a display pipeline **855** for rendering and display in order to present the SR content associated with the event to a user (e.g., an SR reconstruction or simulation of a battle or other event based on the source assets then emergent content). According to some implementations, the actions for a time period are captured and provided to the OE engines **810** as training feedback **865**. According to some implementations, the actions are provided to the objective generator **807** which in turn produces updated objective for each OE per time period (e.g., as described above

with reference to the emergent content engine **250** in FIG. 2).

(133) FIG. **8B** is a block diagram of an emergent content architecture **850** in accordance with some implementations. While certain specific features are illustrated, those of ordinary skill in the art will appreciate from the present disclosure that various other features have not been illustrated for the sake of brevity, and so as not to obscure more pertinent aspects of the implementations disclosed herein. To that end, as a non-limiting example, in some implementations, an objective-effectuator (OE) encapsulation of related (e.g., encapsulated/nested) OE engines **810a**, **810b**, **810c**, and **810d** (sometimes collectively referred to herein as the OE engines **810**) (e.g., similar to character engines **208a-e** in FIG. 2) perform actions based on initial objectives derived from source assets **805** at time **T0** and based on updated objectives derived from the emergent content engine **250** at times **T1** and on.

(134) According to some implementations, the encapsulation manager **825** determines the OE encapsulation (e.g., the nesting or layering of related OEs). For example, the encapsulation manager **825** determines the OE encapsulation based on the connections between the story nodes within a conditionally dependent SR content threads associated with the event. In some implementations, the encapsulation manager **825** modifies the OE encapsulation over time (e.g., adding or removing layers of OEs) based on the objectives, source assets, and/or other information.

(135) As one example, the OE encapsulation includes a top-level OE engine **810a** associated with a transport ship, a second-level OE engine **810b** associated with an amphibious landing craft being transported by the transport ship, a third-level OE engine **810c** associated a platoon of infantrymen or marine assigned to the amphibious landing craft, and a bottom-level OE engine **810d** associated with a particular infantryman or marine. As such, the various OE engines within the OE encapsulation are related in some manner as they correspond to connected nodes within a conditionally dependent SR content threads associated with the event (e.g., as described with reference to the story nodes in FIG. **6A**). According to some implementations, the emergent content architecture **850** is structured to produce concurrent actions for the various OE engines within the OE encapsulation for consistent emergent content. In various implementations, one of ordinary skill in the art will appreciate that emergent content architecture **850** may include an arbitrary number of OE encapsulations. In some implementations, a same OE engine may be shared between two or more OE encapsulations due to the related nature of OEs to OE encapsulations.

(136) According to some implementations, the initial objectives are produced by the operations of a scraper engine **820** and an objective generator **830** based on source assets **805** associated with an event (e.g., plans **810a**, ground truth **810b**, and personal accounts or the like **810c** for the event). In some implementations, the scraper engine **820** performs parsing and understanding operations on the source assets **805** in order to produce extracted actions for each OE (e.g., characters identified in the source assets **805**) per time period. For example, in some implementations, the scraper engine **820** extracts the actions from the source assets **805**. Thereafter, in some implementations, the objective generator **830** (e.g., a neural network or other AI construct) produces initial objectives for each OE per time period.

(137) According to some implementations, a multiplexer **835** enables one of the initial objectives or the updated objectives as inputs to the OE encapsulation. In some implementations, the demultiplexer **845** routes the objectives on a per OE basis to their respective OE engines **810**. In some implementations, the OE engines **810** perform actions based on their objectives. According to some implementations, the actions for a time period are captured and provided to a display pipeline **855** for rendering and display in order to present the SR content associated with the event to a user (e.g., an SR reconstruction or simulation of a battle or other event based on the source assets then emergent content). According to some implementations, the actions for a time period are captured and provided to the emergent content engine **250** and the OE engines **810** as training feedback **865**. According to some implementations, the actions are provided to the emergent content engine **250** which in turn produces updated objective for each OE per time period (e.g., as described above

with reference to the emergent content engine **250** in FIG. 2).

(138) FIG. **8C** is a block diagram of an emergent content architecture **875** in accordance with some implementations. While certain specific features are illustrated, those of ordinary skill in the art will appreciate from the present disclosure that various other features have not been illustrated for the sake of brevity, and so as not to obscure more pertinent aspects of the implementations disclosed herein. To that end, as a non-limiting example, in some implementations, OE engines **860a**, **860b**, **860c**, and **860d** (sometimes collectively referred to herein as the OE engines **860**) (e.g., similar to character engines **208a-e** in FIG. 2) perform actions based on initial objectives derived from source assets **805** at time **T0** and based on updated objectives derived from the emergent content engine **250** at times **T1** and on.

(139) According to some implementations, the initial objectives are produced by the operations of a scraper engine **820** and an objective generator **830** based on source assets **805** (e.g., a movie, TV episode, audio book, novel, magazine article, etc.). In some implementations, the scraper engine **820** performs parsing and understanding operations on the source assets **805** in order to produce extracted actions for each OE (e.g., characters identified in the source assets **805**) per time period. For example, in some implementations, the scraper engine **820** extracts the actions from the source assets **805**. Thereafter, in some implementations, the objective generator **830** (e.g., a neural network or other AI construct) produces initial objectives for each OE per time period.

(140) According to some implementations, the multiplexer **835** enables one of the initial objectives or the updated objectives as inputs to the OE engines **860**. In some implementations, the demultiplexer **845** routes the objectives on a per OE basis to their respective OE engines **860**. In some implementations, the OE engines **860** perform actions based on their objectives. According to some implementations, the actions for a time period are captured and provided to a display pipeline **855** for rendering and display in order to present the SR content associated with the event to a user (e.g., an SR reconstruction or simulation of a battle or other event based on the source assets then emergent content). According to some implementations, the actions for a time period are captured and provided to the emergent content engine **250** and the OE engines **860** as training feedback **865**. According to some implementations, the actions are provided to the emergent content engine **250** which in turn produces updated objective for each OE per time period (e.g., as described above with reference to the emergent content engine **250** in FIG. 2).

(141) FIG. **9** is a flowchart representation of a method **900** of instantiating an objective-effectuator (OE) encapsulation within an SR setting in accordance with some implementations. In various implementations, the method **900** is performed by a device with a non-transitory memory and one or more processors coupled with the non-transitory memory (e.g., the controller **102**, the electronic device **103** shown in FIG. **1A**, and/or the HMD **104** shown in FIG. **1B**). In some implementations, the method **900** is performed by processing logic, including hardware, firmware, software, or a combination thereof. In some implementations, the method **900** is performed by a processor executing code stored in a non-transitory computer-readable medium (e.g., a memory).

(142) The method **900**, for example, generates objectives for OEs in an OE encapsulation, which result in related plots in an SR setting that are consistent with the context of the encapsulation (e.g., while on the transport ship, a marine performs actions consistent with the transport ship context). As one example, the OE encapsulation associated with an event (e.g., a particular battle) corresponds to navy->transport ship->amphibious assault vehicle->company of marines->individual marine.

(143) As represented by block **9-1**, the method **900** includes instantiating a first OE associated with a first set of attributes (e.g., visual rendering attributes, possible actions, contextual information, etc.) and a second OE associated with a second set of attributes into an SR setting, wherein the first OE is encapsulated within the second OE. In some implementations, when the first OE is encapsulated within the second OE, the first OE is associated with the second OE. In some implementations, when the first OE is encapsulated within the second OE, the first OE is correlated

with the second OE. In some implementations, when the first OE is encapsulated within the second OE, the first OE is related to the second OE. In some implementations, when the first OE is encapsulated within the second OE, the first OE is dependent on the second OE. In other words, the first OE is provided objectives and performs actions that are consistent with the context and attributes of the second OE because the first OE is encapsulated within the second OE. In some implementations, the lower-level OE performs actions consistent with higher-level OEs in which it is encapsulated. In some implementations, the one or more other lower-level OEs are encapsulated within the first OE. In some implementations, the second OE is encapsulated within one or more other higher-level OEs.

(144) In some implementations, the attributes are extracted from source material/assets associated with the event including, for example, plans for the event such as battle plans, ground truth for the event such as the course and outcomes of the battle, historical accounts or memoirs, screenplays, scripts, text or audio books, movies, video games, novels, etc. In some implementations, the system determines a set of OE encapsulations for each time period (e.g., as shown in FIGS. 6B and 6C). As such, an OE encapsulation may change over the course of the event such as OEs (layers) being stripped away or added. As one example, a particular battle encapsulation starts as transport ship->amphibious assault vehicle->company of marines->individual marine while in transport (TO). Continuing with this example, the OE encapsulation changes to amphibious assault vehicle->company of marines->individual marine while approaching the beach (T1). Continuing with this example, the OE encapsulation changes again to company of marines->individual marine while storming the beach (T2). Continuing with this example, the OE encapsulation changes again when the marines may find and enter a vehicle after reaching the beach (T3) which changes the encapsulation to vehicle->subset of company of marines->individual marine.

(145) As represented by block 9-2, the method 900 includes providing a first objective to the first OE based on the first and second sets of attributes. In some implementations, the first OE is provided an objective based on the context of the second OE within which it is encapsulated and, in turn, the first OE performs actions that are consistent with that context. For example, a marine on a transport ship is not given a scouting objective to perform scouting patrols or a fire suppression objective to mortar a target while on the transport ship.

(146) As represented by block 9-3, the method 900 includes providing a second objective to the second OE based on the second set of attributes, wherein the first and second objectives are associated with a first time period between a first temporal point and a second temporal point (e.g., the objectives are valid or active for the particular time period). In some implementations, the objectives correspond to initial objectives synthesized from the source assets. In some implementations, the objectives are updated every time period by the emergent content engine. In some implementations, the OE encapsulations are updated every time period by an encapsulation manager such as adding or removing OEs (layers) from an encapsulation. In one example, the first and second temporal points correspond to start and end times for a scene within source content. As another example, the first and second temporal points correspond to natural break points in an instruction set or the like. As yet another example, the first and second temporal points correspond to start and end states for an event (e.g., the state of troops before and after a battle). Thus, according to some implementations, the first and second temporal points provide book ends or guide posts for the objectives.

(147) In some implementations, the method 900 includes synthesizing the first and second objectives based on source assets/materials (e.g., a movie, book, historical account associated with an event or the like). For example, the source assets correspond to plans for the event such as battle plans, ground truth for the event such as the course and outcomes of the battle, historical accounts or memoirs, screenplays, scripts, text or audio books, movies, video games, novels, etc. For example, the source assets also include 3D models of terrain, infrastructure, vehicles, humanoids, animals, etc. associated with the story or event.

(148) In some implementations, the method **900** includes extracting a set of actions associated with an event from the source assets, and wherein the first and second objectives are derived from the set of actions (e.g., the set of actions include basic plot points associated with a book, movie, event, or the like such as its start and end situations). In some implementations, the first and second objectives are consistent with the set of actions. For example, if the predefined set of actions does not include killing, then the objective cannot be to kill. For example, if the set of actions includes at least start and end points (e.g., book-ends) for the event, the objective is derived to get a character from the start to the end point. For example, characters cannot perform actions “outside” of intellectual property (IP) or digital rights management (DRM)-limited bounds.

(149) In some implementations, the first and second objectives are generated by utilizing a neural network. For example, the neural network generates the first and second objectives based on a set of neural network parameters (e.g., weights). For example, the neural network parameters are determined by a reward function. In some implementations, the first and second objectives are provided to a training module that adjusts parameters of a neural network that generates the objectives. For example, the training module includes a reward function that assigns positive rewards to desirable actions and negative rewards to undesirable actions. For example, the training module utilizes reinforcement learning to configure the neural network. For example, the training module utilizes fan-created content (e.g., blog posts), canon video, novels, books, comics and/or video games to train the neural network.

(150) As represented by block **9-4**, the method **900** includes generating a first set of actions associated with the first time period for the first OE based on the first objective. As represented by block **9-5**, the method **900** includes generating a second set of actions associated with the first time period for the second OE based on the second objective. For example, with reference to FIG. **8A**, the OE engines **810** perform actions based on objectives from the objective generator **807**.

(151) As represented by block **9-6**, the method **900** includes rendering for display the SR setting including the first set of actions performed by the first OE and the second set of actions performed by the second OE. In some implementations, the SR setting is associated with an event. For example, the event corresponds to an athletic event, a concert, a battle, or another large-scale occurrence. For example, with reference to FIG. **8A**, the display pipeline **855** renders the actions performed by the OEs for the first time period in order to present the SR content to a user.

(152) In some implementations, the method **900** includes obtaining contextual information characterizing the SR setting. For example, the contextual information includes all OEs and OE encapsulations instantiated within the SR setting. For example, the contextual information includes user-specified scene/environment info. For example, the contextual information includes instantiated characters and equipment assets. For example, the contextual information includes identities of other characters that are to be instantiated. For example, the contextual information includes mesh maps for objects present in the user's environment (e.g., a desk).

(153) In some implementations, the method **900** includes setting virtual environmental conditions for the SR setting based on the source assets. In some implementations, the virtual environment conditions include one or more of terrain conditions, weather conditions, lighting conditions and environment sounds. In some implementations, the method **900** includes changing the terrain and/or environmental conditions based on user inputs to test different simulations of the SR setting. For example, the terrain and/or weather associated with an event may be changed from its historical parameters to see how the outcome of the event may have changed with the changed terrain and/or weather (e.g., simulated winter weather in place of summer weather for the historical event, or simulated flat terrain replacing sloped rugged terrain for the historical event).

(154) In some implementations, the method **900** includes receiving user selection of a specific OE and, in response, displaying SR content associated with the actions performed by the specific OE. For example, the user is able to “look through the eyes” of the selected OE and optionally control at least some aspects of the selected OE such as its movements.

(155) In some implementations, the method **900** includes updating the objective for first OE for a next time period based on the first and second sets of attributes and also attributes of a new OE. For example, a third OE layer is added to the OE encapsulation, which further constrains the actions and objectives for the first OE. In some implementations, the new layer is a high-level layer than the first OE which is higher or equal to the second OE. For example, with reference to FIG. **8A**, the encapsulation manager **825** updates the OE encapsulation by adding an additional OE engine within the OE encapsulation.

(156) In some implementations, the method **900** includes updating the objective for first OE for a next time period to be a function of the first set of attributes. For example, the second OE layer is removed, opening new actions and objectives for the first OE. For example, with reference to FIG. **8A**, the encapsulation manager **825** updates the OE encapsulation by removing one of the OE engines **810** within the OE encapsulation.

(157) In some implementations, the method **900** includes adding/removing OEs to test different simulations within the SR setting. For example, if the transport ship typically has N amphibious landing craft, run a simulation within N-1 or N+1 amphibious landing craft to see how a battle's macro or micro outcome may change. For example, remove entire OE encapsulations and/or individual OEs within the SR setting. In some implementations, one of the OEs performs actions inconsistent with its objective when a predetermined criterion is satisfied (e.g., a morale criterion, self-preservation criterion, etc.). For example, a soldier forgoes performing actions consistent with his/her objective and instead deserts his/her post if the predetermined criterion is satisfied.

(158) In some implementations, the method **900** includes instantiating a second OE encapsulation including a third OE and a fourth OE. For example, at least one of the third or fourth OEs is included in both the first and second OE encapsulations.

(159) FIG. **10** is a flowchart representation of a method **1000** of initializing and generating content for an objective-effectuator (OE) encapsulation within SR setting in accordance with some implementations. In various implementations, the method **1000** is performed by a device with a non-transitory memory and one or more processors coupled with the non-transitory memory (e.g., the controller **102**, the electronic device **103** shown in FIG. **1A**, and/or the HMD **104** shown in FIG. **1B**). In some implementations, the method **1000** is performed by processing logic, including hardware, firmware, software, or a combination thereof. In some implementations, the method **1000** is performed by a processor executing code stored in a non-transitory computer-readable medium (e.g., a memory).

(160) As represented by block **10-1**, the method **1000** includes obtaining source assets associated with an event. For example, the event corresponds to an athletic event, a concert, a battle, or another large-scale occurrence. For example, the source assets correspond to plans for the event such as battle plans, ground truth for the event such as the course and outcomes of the battle, historical accounts and books, movies, video games, novels, etc. For example, the source assets also include 3D models of terrain, infrastructure, vehicles, humanoids, animals, etc. associated with the story or event.

(161) As represented by block **10-2**, the method **1000** includes identifying an OE encapsulation based on the source assets, the OE encapsulation including a first OE and a second OE. For example, the OE encapsulation corresponds to a set of related characters or entities such as a transport ship including N amphibious landing crafts each with M marines. In some implementations, the OEs corresponds to characters associated with the event such as humanoids, vehicles, androids, robots, animals, etc. For example, with reference to FIG. **8B**, the encapsulation manager **825** determines the OE encapsulation including the OE engines **810** based on the source assets associated with the event.

(162) As represented by block **10-3**, the method **1000** includes extracting a set of actions performed by the first and second OEs during the event based on the source assets. For example, the set of actions correspond actions sequences for each OE derived from a screenplay or script for the event.

In some implementations, the device synthesizes a screenplay for the event. In some implementations, the device receives a sequence of actions or a set of potential actions for the OEs from a character engine that generates the sequence of actions. In some implementations, the device receives a user input that indicates a sequence of actions. For example, the set of actions includes movement trajectory, operation of weapons or other related equipment, dialogue, etc. for the set of related characters. For example, with reference to FIG. 8B, the scraper engine **820** extracts a set of actions performed by the OEs during the event.

(163) As represented by block **10-4**, the method **1000** includes synthesizing an initial set of objectives for the OE encapsulation based on the set of actions extracted from source assets associated with an event, wherein the initial set of objectives includes a first objective for the first OE that is consistent with a second objective for the second OE. For example, with reference to FIG. 8B, the objective generator **830** synthesizes an initial set of objectives based on the extracted set of actions.

(164) For example, the initial set of objectives are such that OEs within the OE encapsulation act in concert and do not conflict-cannot act to break from the related grouping. In some implementations, the initial set of objectives includes an objective for each OE within the OE encapsulation. In some implementations, the initial set of objectives is consistent with the set of actions. For example, if the predefined set of actions does not include killing, then the objective cannot be to kill. For example, if the set of actions includes at least start and end points (e.g., book-ends) for the event, the objective is derived to get a character from the start to the end point. For example, characters cannot perform actions “outside” of intellectual property (IP) or digital rights management (DRM)-limited bounds.

(165) In some implementations, synthesizing the initial set of objectives includes utilizing a neural network. For example, a neural network generates the initial set of objectives based on a set of neural network parameters (e.g., weights). For example, the neural network parameters are determined by a reward function

(166) In some implementations, the initial set of objectives is provided to a training module that adjusts parameters of a neural network that generates the objective. For example, the training module includes a reward function that assigns positive rewards to desirable actions and negative rewards to undesirable actions. For example, the training module utilizes reinforcement learning to configure the neural network. For example, the training module utilizes fan-created content (e.g., blog posts), canon video, novels, books, comics and/or video games to train the neural network.

(167) As represented by block **10-5**, the method **1000** includes instantiating (e.g., at time **T0**) the OE encapsulation into an SR setting (e.g., an SR setting), wherein the OE encapsulation is characterized by the initial set of objectives (e.g., synthesized from the source assets) and a set of visual rendering attributes. For example, with reference to FIG. 8B, at time **T0**, the emergent content architecture **850** is initialized with initial objectives derived from source assets **805**.

(168) In some implementations, the method **1000** includes setting virtual environmental conditions for the SR setting based on the initial set of objectives. For example, the virtual environment conditions include one or more of terrain conditions, weather conditions, lighting conditions, environment sounds, and/or the like.

(169) In some implementations, the method **1000** includes obtaining contextual information characterizing the SR setting. For example, the contextual information includes all OEs and OE encapsulations instantiated within the SR setting. For example, the contextual information includes user-specified scene/environment info. For example, the contextual information includes instantiated characters and equipment assets. For example, the contextual information includes identities of other characters that are to be instantiated. For example, the contextual information includes mesh maps for objects present in the user's environment (e.g., a desk).

(170) As represented by block **10-6**, the method **1000** includes generating updated objectives for the OE encapsulation based on a function of the initial set of objectives, contextual information

associated with the event, and the set of actions. For example, the set of revised objectives cannot conflict due to their encapsulation. In some implementations, generating the updated set of objectives includes utilizing a neural network. For example, parameters of the neural network are provided by a reward function. For example, with reference to FIG. 8B, the emergent content engine **250** generates an updated set of objectives based at least in part on the previous actions performed by the OE engine **810**.

(171) As represented by block **10-7**, the method **1000** includes modifying the OE encapsulation based on the updated set of objectives (e.g., at time **T1**). For example, with reference to FIG. 8B, at time **T1** and on, the emergent content architecture **850** operates with updated objectives from the emergent content engine **250**. In some implementations, the modified objective is provided to a character engine that generated the OE representation, and ultimately to a rendering and display pipeline in order to output SR content showing the OE performing the sequence of actions within the SR setting, and potentially in combination with one or more other OEs. For example, the OE performs actions that achieve the objective or improve the likelihood of achieving the objective.

(172) FIG. **11** is a flowchart representation of a method **1100** of initializing and generating content for an objective-effectuator (OE) within SR setting in accordance with some implementations. In various implementations, the method **1100** is performed by a device with a non-transitory memory and one or more processors coupled with the non-transitory memory (e.g., the controller **102**, the electronic device **103** shown in FIG. **1A**, and/or the HMD **104** shown in FIG. **1B**). In some implementations, the method **1100** is performed by processing logic, including hardware, firmware, software, or a combination thereof. In some implementations, the method **1100** is performed by a processor executing code stored in a non-transitory computer-readable medium (e.g., a memory).

(173) As represented by block **11-1**, the method **1100** includes obtaining source assets associated with an event. For example, the event corresponds to an athletic event, a concert, a battle, or another large-scale occurrence. For example, the source assets correspond to plans for the event such as battle plans, ground truth for the event such as the course and outcomes of the battle, historical accounts and books, movies, video games, novels, etc. For example, the source assets also include 3D models of terrain, infrastructure, vehicles, humanoids, animals, etc. associated with the story or event.

(174) As represented by block **11-2**, the method **1100** includes extracting a set of actions performed by the first OE during the event based on the source assets. For example, the set of actions correspond actions sequences for each OE derived from a screenplay or script for the event. In some implementations, the device synthesizes a screenplay for the event. In some implementations, the device receives a sequence of actions or a set of potential actions for the OEs from a character engine that generates the sequence of actions. In some implementations, the device receives a user input that indicates a sequence of actions. For example, the set of actions includes movement trajectory, operation of weapons or other related equipment, dialogue, etc. for the OEs. For example, with reference to FIG. 8C, the scraper engine **820** extracts a set of actions performed by the OEs during the event.

(175) As represented by block **11-3**, the method **1100** includes synthesizing an initial set of objectives for the first OE based on the set of actions extracted from source assets associated with an event. For example, with reference to FIG. 8C, the objective generator **830** synthesizes an initial set of objectives based on the extracted set of actions. In some implementations, the initial set of objectives is consistent with the set of actions. For example, if the predefined set of actions does not include killing, then the objective cannot be to kill. For example, if the set of actions includes at least start and end points (e.g., book-ends) for the event, the objective is derived to get a character from the start to the end point. For example, characters cannot perform actions “outside” of intellectual property (IP) or digital rights management (DRM)-limited bounds.

(176) In some implementations, synthesizing the initial set of objectives includes utilizing a neural network. For example, a neural network generates the initial set of objectives based on a set of

neural network parameters (e.g., weights). For example, the neural network parameters are determined by a reward function.

(177) In some implementations, the initial set of objectives is provided to a training module that adjusts parameters of a neural network that generates the objective. For example, the training module includes a reward function that assigns positive rewards to desirable actions and negative rewards to undesirable actions. For example, the training module utilizes reinforcement learning to configure the neural network. For example, the training module utilizes fan-created content (e.g., blog posts), canon video, novels, books, comics and/or video games to train the neural network.

(178) As represented by block **11-4**, the method **1100** includes instantiating (e.g., at time **T0**) the first OE into an SR setting (e.g., an SR setting), wherein the first OE encapsulation is characterized by the initial set of objectives (e.g., synthesized from the source assets) and a set of visual rendering attributes. As such, with reference to FIG. **8C**, at time **T0**, the OE engines **860** within the emergent content architecture **875** are initialized with initial objectives derived from source assets **805**.

(179) In some implementations, the method **1100** includes setting virtual environmental conditions for the SR setting based on the initial set of objectives. For example, the virtual environment conditions include one or more of terrain conditions, weather conditions, lighting conditions, environment sounds, and/or the like.

(180) In some implementations, the method **1100** includes obtaining contextual information characterizing the SR setting. For example, the contextual information includes all OEs instantiated within the SR setting. For example, the contextual information includes user-specified scene/environment info. For example, the contextual information includes instantiated characters and equipment assets. For example, the contextual information includes identities of other characters that are to be instantiated. For example, the contextual information includes mesh maps for objects present in the user's environment (e.g., a desk).

(181) As represented by block **11-5**, the method **1100** includes generating updated objectives for the first OE based on a function of the initial set of objectives, contextual information associated with the event, and the set of actions. In some implementations, generating the updated set of objectives includes utilizing a neural network. For example, parameters of the neural network are provided by a reward function. For example, with reference to FIG. **8C**, the emergent content engine **250** generates an updated set of objectives based at least in part on the previous actions performed by the OE engine **860**.

(182) As represented by block **11-6**, the method **1100** includes modifying the first OE based on the updated set of objectives (e.g., at time **T1**). For example, with reference to FIG. **8C**, at time **T1** and on, the OE engines **860** within the emergent content architecture **875** operate with updated objectives from the emergent content engine **250**. In some implementations, the modified objective is provided to a character engine that generated the OE representation, and ultimately to a rendering and display pipeline in order to output SR content showing the OE performing the sequence of actions within the SR setting, and potentially in combination with one or more other OEs. For example, the OE performs actions that achieve the objective or improve the likelihood of achieving the objective.

(183) FIG. **12** is a flowchart representation of a method **1200** of selecting a point-of-view within an SR setting (e.g., a conditionally dependent SR content threads environment) in accordance with some implementations. In various implementations, the method **1200** is performed by a device with a non-transitory memory and one or more processors coupled with the non-transitory memory (e.g., the controller **102**, the electronic device **103** shown in FIG. **1A**, and/or the HMD **104** shown in FIG. **1B**). In some implementations, the method **1200** is performed by processing logic, including hardware, firmware, software, or a combination thereof. In some implementations, the method **1200** is performed by a processor executing code stored in a non-transitory computer-readable medium (e.g., a memory).

(184) The method **1200**, for example, enables a user to select between different points of view within the multi-level conditionally dependent SR content threads such as an omniscient third-person view of an overall battlefield, a squadron view for a group of planes, a captain view for a destroyer, a first-person view for a specific marine within an amphibious landing craft, or the like (185) As represented by block **12-1**, the method **1200** includes presenting a first SR view of an event with SR content associated with the event that includes a plurality of inter-related layers of SR content that perform actions associated with an event. For example, the event corresponds to an athletic event, a concert, a battle, or another large-scale occurrence. In some implementations, the SR content is synthesized based on source material/assets associated with the event including, for example, plans for the event such as battle plans, ground truth for the event such as the course and outcomes of the battle, historical accounts or memoirs, screenplays, scripts, text or audio books, movies, video games, novels, etc.

(186) In some implementations, as represented by block **12-1a**, the method **1200** includes panning around or zooming in/out within the first SR view based on user inputs. As such, the user is able to view the event from a nearly infinite number of perspectives. In some implementations, as represented by block **12-1b**, the method **1200** includes adding and/or removing layers and/or SR content elements based on user inputs. As such, the user is able to play-out various “what if” simulations of the event with modified layers and/or changed numbers of elements.

(187) In some implementations, SR content includes the environmental conditions (e.g., weather) and/or terrain associated with the event based on source assets associated with the event. In some implementations, the method **1200** includes modifying the environmental conditions and/or terrain associated with the event based on user inputs. As such, the user is able to play-out various “what if” simulations of the event with modified environmental conditions (e.g., weather) and/or terrain.

(188) As represented by block **12-2**, the method **1200** includes detecting selection of a respective layer among the plurality of inter-related layers of SR content. For example, the selection corresponds to a voice command, a gestural command, selection of an affordance associated with the respective layer, or the like.

(189) As represented by block **12-3**, the method **1200** includes presenting a second SR view of the event that includes the respective layer of SR content, where the second SR view corresponds to a point-of-view of the respective layer. According to some implementations, the first SR view corresponds to an omniscient third-person view of the event (e.g., a virtual view of a battlefield commander), and the second SR view corresponds to a first-person view of an individual character within the event (e.g., a soldier on the battlefield or a pilot in an aircraft). As one example, state **725** in FIG. 7B shows a first SR view of the event (e.g., a particular battle from an overall multi-dimensional view), and state **735** in FIG. 7C shows a second SR view of the event e.g., a particular battle from an aerial view).

(190) In some implementations, while presenting the second SR view, the method **1200** includes presenting lower level layers in addition to the respective layer. For example, if the respective layer corresponds to a specific transport ship, also show the amphibious landing craft each including a company of marines riding on the transport ship.

(191) In some implementations, while presenting the second SR view, the method **1200** includes presenting directly related higher level layers in addition to the respective layer. For example, if the respective layer corresponds to a specific marine, also show the balance of his company and the amphibious landing ship on which the specific marine is riding.

(192) In some implementations, while presenting the second SR view, the method **1200** includes excluding presentation of higher-level layers. For example, if the respective layer corresponds to a specific pilot of an aircraft, exclude the other crew on the airplane and the other aircraft in the squadron.

(193) In some implementations, while presenting the second SR view, the method **1200** includes excluding presentation of orthogonal equal level layers. For example, if the respective layer

corresponds to a specific marine, also show the balance of his company and the amphibious landing ship on which the specific marine is riding but no other amphibious landing craft from the same transport ship.

(194) In some implementations, as represented by block **12-3a**, the method **1200** includes controlling the SR content element associated with the second SR view based on user inputs. In some implementations, at run-time, the layers continue to payout concurrently whether they are currently presented or not.

(195) While various aspects of implementations within the scope of the appended claims are described above, it should be apparent that the various features of implementations described above may be embodied in a wide variety of forms and that any specific structure and/or function described above is merely illustrative. Based on the present disclosure one skilled in the art should appreciate that an aspect described herein may be implemented independently of any other aspects and that two or more of these aspects may be combined in various ways. For example, an apparatus may be implemented and/or a method may be practiced using any number of the aspects set forth herein. In addition, such an apparatus may be implemented and/or such a method may be practiced using other structure and/or functionality in addition to or other than one or more of the aspects set forth herein.

(196) It will also be understood that, although the terms “first,” “second,” etc. may be used herein to describe various elements, these elements should not be limited by these terms. These terms are only used to distinguish one element from another. For example, a first node could be termed a second node, and, similarly, a second node could be termed a first node, which changing the meaning of the description, so long as all occurrences of the “first node” are renamed consistently and all occurrences of the “second node” are renamed consistently. The first node and the second node are both nodes, but they are not the same node.

(197) The terminology used herein is for the purpose of describing particular implementations only and is not intended to be limiting of the claims. As used in the description of the implementations and the appended claims, the singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will also be understood that the term “and/or” as used herein refers to and encompasses any and all possible combinations of one or more of the associated listed items. It will be further understood that the terms “comprises” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

(198) As used herein, the term “if” may be construed to mean “when” or “upon” or “in response to determining” or “in accordance with a determination” or “in response to detecting,” that a stated condition precedent is true, depending on the context. Similarly, the phrase “if it is determined [that a stated condition precedent is true]” or “if [a stated condition precedent is true]” or “when [a stated condition precedent is true]” may be construed to mean “upon determining” or “in response to determining” or “in accordance with a determination” or “upon detecting” or “in response to detecting” that the stated condition precedent is true, depending on the context.

Claims

1. A method comprising: at a computing system including non-transitory memory and one or more processors, wherein the computing system is communicatively coupled to a display device and one or more input devices coupled with the non-transitory memory: presenting, via the display device, a first synthesized reality (SR) view of a segment of an event that includes SR content associated with the event, wherein the SR content includes a plurality of related layers of SR content that perform actions associated with the segment of the event, wherein the plurality of related layers is concurrently played out whether they are presented or not; detecting, via the one or more input

devices during presentation of the first SR view, selection of a respective layer among the plurality of related layers of SR content associated with the segment of the event; and presenting, via the display device, a second SR view of the segment of the event that includes the respective layer of SR content in response to the selection of the respective layer, wherein the second SR view corresponds to a point-of-view of the respective layer.

2. The method of claim 1, wherein the first SR view corresponds to an omniscient third-person view of the segment of the event, and the second SR view corresponds to a first-person view of a specific element within the segment of the event.

3. The method of claim 1, further comprising: while presenting the first SR view of the segment of the event, receiving a user input to modify perspective of the first SR view; and in response to receiving the user input, modifying the perspective of the first SR view of the segment of the event based on the user input.

4. The method of claim 3, wherein modifying the perspective of the first SR view of the segment of the event includes panning around the SR content associated with the first SR view of the segment of the event based on the user input.

5. The method of claim 3, wherein modifying the perspective of the first SR view of the segment of the event includes zooming in or out the SR content associated with the first SR view of the segment of the event based on the user input.

6. The method of claim 1, further comprising: while presenting the second SR view of the segment of the event, receiving a user input to control an element associated with the respective layer; and in response to receiving the user input, controlling the element associated with the respective layer based on the user input.

7. The method of claim 1, further comprising: while presenting the first SR view of the segment of the event, receiving a user input to remove one or more layers from the SR content; and in response to receiving the user input, removing the one or more layers from the SR content while maintaining display of the first SR view of the segment of the event.

8. The method of claim 1, further comprising: while presenting the first SR view of the segment of the event, receiving a user input to add one or more layers from the SR content; and in response to receiving the user input, adding the one or more layers from the SR content while maintaining display of the first SR view of the segment of the event.

9. The method of claim 1, further comprising: while presenting the first SR view of the segment of the event, receiving a user input to modify environmental conditions associated with the segment of the event; and in response to receiving the user input, modifying the environmental conditions associated with the segment of the event while maintaining display of the first SR view of the segment of the event.

10. The method of claim 1, further comprising: while presenting the first SR view of the segment of the event, receiving a user input to modify terrain associated with the segment of the event; and in response to receiving the user input, modifying the terrain associated with the segment of the event while maintaining display of the first SR view of the segment of the event.

11. A computing system comprising: one or more processors; a non-transitory memory; an interface for communicating with a display device and one or more input devices; and one or more programs stored in the non-transitory memory, which, when executed by the one or more processors, cause the computing system to: present, via the display device, a first synthesized reality (SR) view of a segment of an event that includes SR content associated with the segment of the event, wherein the SR content includes a plurality of related layers of SR content that perform actions associated with the segment of the event, wherein the plurality of related layers is concurrently played out whether they are presented or not; detect, via the one or more input devices during presentation of the first SR view, selection of a respective layer among the plurality of related layers of SR content associated with the segment of the event; and present, via the display device, a second SR view of the segment of the event that includes the respective layer of SR content in response to the

selection of the respective layer, wherein the second SR view corresponds to a point-of-view of the respective layer.

12. The computing system of claim 11, wherein the first SR view corresponds to an omniscient third-person view of the segment of the event, and the second SR view corresponds to a first-person view of a specific element within the segment of the event.

13. The computing system of claim 11, wherein the one or more programs further cause the computing system to: while presenting the first SR view of the segment of the event, receive a user input to modify perspective of the first SR view; and in response to receiving the user input, modify the perspective of the first SR view of the segment of the event based on the user input.

14. The computing system of claim 13, wherein modifying the perspective of the first SR view of the segment of the event includes panning around the SR content associated with the first SR view of the segment of the event based on the user input.

15. The computing system of claim 13, wherein modifying the perspective of the first SR view of the segment of the event includes zooming in or out the SR content associated with the first SR view of the segment of the event based on the user input.

16. The computing system of claim 11, wherein the one or more programs further cause the computing system to: while presenting the second SR view of the segment of the event, receive a user input to control an element associated with the respective layer; and in response to receiving the user input, control the element associated with the respective layer based on the user input.

17. The computing system of claim 11, wherein the one or more programs further cause the computing system to: while presenting the first SR view of the segment of the event, receive a user input to remove one or more layers from the SR content; and in response to receiving the user input, remove the one or more layers from the SR content while maintaining display of the first SR view of the segment of the event.

18. The computing system of claim 11, wherein the one or more programs further cause the computing system to: while presenting the first SR view of the segment of the event, receive a user input to add one or more layers from the SR content; and in response to receiving the user input, add the one or more layers from the SR content while maintaining display of the first SR view of the segment of the event.

19. The computing system of claim 11, wherein the one or more programs further cause the computing system to: while presenting the first SR view of the segment of the event, receive a user input to modify environmental conditions associated with the segment of the event; and in response to receiving the user input, modify the environmental conditions associated with the segment of the event while maintaining display of the first SR view of the segment of the event.

20. A non-transitory memory storing one or more programs, which, when executed by one or more processors of a computing system with an interface for communicating with a display device and one or more input devices, cause the computing system to: present, via the display device, a first synthesized reality (SR) view of a segment of an event that includes SR content associated with the segment of the event, wherein the SR content includes a plurality of related layers of SR content that perform actions associated with the segment of the event, wherein the plurality of related layers is concurrently played out whether they are presented or not; detect, via the one or more input devices during presentation of the first SR view, selection of a respective layer among the plurality of related layers of SR content associated with the segment of the event; and present, via the display device, a second SR view of the segment of the event that includes the respective layer of SR content in response to the selection of the respective layer, wherein the second SR view corresponds to a point-of-view of the respective layer.
