

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12412547
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Yamazaki; Shunpei et al.

Flexible display panel

Abstract

A novel display panel that is highly convenient or reliable is provided. The display panel includes a first region and a second region. The second region is provided with a first component, and the second region can be bent with the first component facing outward. The first component includes a first elastic body and a second elastic body. The second elastic body includes an end portion part or the whole of which is covered with the first elastic body. The second elastic body has a higher elastic modulus than the first elastic body.

Inventors: Yamazaki; Shunpei (Tokyo, JP), Adachi; Hiroki (Tochigi, JP), Eguchi; Shingo (Kanagawa, JP)

Applicant: Semiconductor Energy Laboratory Co., Ltd. (Kanagawa-ken, JP)

Family ID: 66663867

Assignee: Semiconductor Energy Laboratory Co., Ltd. (N/A, JP)

Appl. No.: 18/244676

Filed: September 11, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240074227 A1	Feb. 29, 2024

Foreign Application Priority Data

JP	2017-229894	Nov. 30, 2017
----	-------------	---------------

Related U.S. Application Data

continuation parent-doc US 17719702 20220413 US 11758759 child-doc US 18244676
continuation parent-doc US 16766418 US 11309523 20220419 WO PCT/IB2018/059085

Publication Classification

Int. Cl.: **G09G5/00** (20060101); **G09G5/14** (20060101); **H10K50/844** (20230101); **H10K59/80** (20230101); **H10K77/10** (20230101); H10K59/12 (20230101); H10K59/131 (20230101)

U.S. Cl.:

CPC **G09G5/006** (20130101); **G09G5/14** (20130101); **H10K50/844** (20230201); **H10K59/873** (20230201); **H10K77/111** (20230201); G09G2354/00 (20130101); G09G2380/02 (20130101); H10K59/12 (20230201); H10K59/131 (20230201)

Field of Classification Search

CPC: H10K (50/844); H10K (77/111); H10K (59/12); H10K (50/00); H10K (59/00); G09G (5/14); G09G (2354/00); G09G (2380/02); G09G (3/2092); G09G (2300/0426); G09G (5/006); G09G (5/003); Y02E (10/549); G09F (9/00); G09F (9/30); H05B (33/02); H05B (33/04); H05B (33/14)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6377324	12/2001	Katsura	N/A	N/A
8816977	12/2013	Rothkopf et al.	N/A	N/A
8934228	12/2014	Franklin et al.	N/A	N/A
9176535	12/2014	Bohn	N/A	G06F 1/1681
9178970	12/2014	Lynch	N/A	N/A
9189027	12/2014	Lee et al.	N/A	N/A
9285835	12/2015	Lee et al.	N/A	N/A
9377817	12/2015	Eguchi	N/A	N/A
9395070	12/2015	Endo	N/A	N/A
9429999	12/2015	Lee et al.	N/A	N/A
9588549	12/2016	Endo et al.	N/A	N/A
9710033	12/2016	Yamazaki et al.	N/A	N/A
9756158	12/2016	Lynch	N/A	N/A
9818961	12/2016	Hiroki et al.	N/A	N/A
9857844	12/2017	Tsukamoto	N/A	N/A
9866660	12/2017	Myers et al.	N/A	N/A
9882179	12/2017	Tajima	N/A	N/A
10013027	12/2017	Sun	N/A	N/A
10088927	12/2017	Rothkopf et al.	N/A	N/A
10142547	12/2017	Yamazaki et al.	N/A	N/A
10271438	12/2018	Hirakata	N/A	H01F 1/14791
10348875	12/2018	Lynch	N/A	N/A

10488887	12/2018	Yamazaki	N/A	H04M 1/0216
10735569	12/2019	Lynch	N/A	N/A
10771705	12/2019	Yamazaki et al.	N/A	N/A
10931802	12/2020	Myers et al.	N/A	N/A
11309523	12/2021	Yamazaki et al.	N/A	N/A
2007/0097014	12/2006	Solomon	345/1.1	G06F 1/1616
2008/0018631	12/2007	Hioki	345/206	G02F 1/133526
2011/0286157	12/2010	Ma	361/679.01	G06F 1/1652
2012/0008267	12/2011	Watanabe	361/679.01	H05B 33/02
2014/0145977	12/2013	Kang	N/A	N/A
2014/0321074	12/2013	Chida	361/749	G09F 9/35
2015/0036269	12/2014	Kim	361/679.01	H05K 7/00
2015/0049428	12/2014	Lee et al.	N/A	N/A
2015/0062525	12/2014	Hirakata	349/158	G06F 1/1641
2015/0325804	12/2014	Lindblad	313/511	H10K 59/40
2015/0370287	12/2014	Ko	361/749	H04M 1/0268
2016/0118616	12/2015	Hiroki	257/40	H10K 50/8428
2016/0240817	12/2015	Cho et al.	N/A	N/A
2017/0038641	12/2016	Yamazaki	N/A	G02F 1/133308
2017/0170417	12/2016	Myung	N/A	H10K 59/12
2017/0279073	12/2016	Nagata et al.	N/A	N/A
2017/0280531	12/2016	Tada	N/A	H10K 50/8445
2017/0307929	12/2016	Nakazawa et al.	N/A	N/A
2019/0042041	12/2018	Rothkopf et al.	N/A	N/A
2020/0344341	12/2019	Lynch	N/A	N/A
2020/0365827	12/2019	Yamazaki	N/A	G09F 9/30
2021/0132653	12/2020	Yamazaki et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
103416043	12/2012	CN	N/A
104021734	12/2013	CN	N/A
104424851	12/2014	CN	N/A
104916230	12/2014	CN	N/A
105874525	12/2015	CN	N/A
105911618	12/2015	CN	N/A
106462197	12/2016	CN	N/A
106601130	12/2016	CN	N/A
107195253	12/2016	CN	N/A
107230429	12/2016	CN	N/A
107301821	12/2016	CN	N/A
107331795	12/2016	CN	N/A

2772826	12/2013	EP	N/A
2840460	12/2014	EP	N/A
2960747	12/2014	EP	N/A
3364636	12/2017	EP	N/A
3863265	12/2020	EP	N/A
2336460	12/1998	GB	N/A
2012-103444	12/2011	JP	N/A
2016-081051	12/2015	JP	N/A
2016-0000109	12/2015	KR	N/A
2017-0070309	12/2016	KR	N/A
WO-1999/034348	12/1998	WO	N/A
WO-2012/129247	12/2011	WO	N/A
WO-2015/079356	12/2014	WO	N/A
WO-2015/199427	12/2014	WO	N/A

OTHER PUBLICATIONS

International Search Report (Application No. PCT/IB2018/059085) dated Feb. 19, 2019. cited by applicant

Written Opinion (Application No. PCT/IB2018/059085) dated Feb. 19, 2019. cited by applicant

Chinese Office Action (Application No. 201880074988.2) dated Nov. 12, 2021. cited by applicant

Chinese Office Action (Application No. 201880074988.2) dated Sep. 15, 2022. cited by applicant

Primary Examiner: Davis; David D

Attorney, Agent or Firm: Husch Blackwell LLP

Background/Summary

(1) This application is a continuation of copending U.S. application Ser. No. 17/719,702, filed on Apr. 13, 2022 which is a continuation of U.S. application Ser. No. 16/766,418, filed on May 22, 2020 (now U.S. Pat. No. 11,309,523 issued Apr. 19, 2022) which is 371 of international application PCT/IB2018/059085 filed on Nov. 19, 2018 which are all incorporated herein by reference.

FIELD OF THE INVENTION

(1) One embodiment of the present invention relates to a display panel, a display device, an input/output device, a data processing device, or a semiconductor device.

(2) Note that one embodiment of the present invention is not limited to the above technical field. The technical field of one embodiment of the invention disclosed in this specification and the like relates to an object, a method, or a manufacturing method. Another embodiment of the present invention relates to a process, a machine, manufacture, or a composition of matter. Thus, more specifically, examples of the technical field of one embodiment of the present invention disclosed in this specification include a semiconductor device, a display device, a light-emitting device, a power storage device, a memory device, a driving method thereof, and a manufacturing method thereof.

BACKGROUND OF THE INVENTION

(3) A functional panel that includes a first surface, a second surface facing the first surface, and a neutral surface between the first surface and the second surface and has a structure in which part of a functional layer that has a thickness greater than or equal to half of the thickness of the functional layer is positioned in a region between the first surface and the neutral surface is known (Patent

SUMMARY OF THE INVENTION

(4) An object of one embodiment of the present invention is to provide a novel display panel that is highly convenient or reliable. Another object is to provide a novel display device that is highly convenient or reliable. Another object is to provide a novel input/output device that is highly convenient or reliable. Another object is to provide a novel data processing device that is highly convenient or reliable. Another object is to provide a novel display panel, a novel display device, a novel input/output device, a novel data processing device, or a novel semiconductor device.

(5) Note that the description of these objects does not disturb the existence of other objects. One embodiment of the present invention does not need to achieve all of these objects. Other objects will be apparent from the description of the specification, the drawings, the claims, and the like, and other objects can be derived from the description of the specification, the drawings, the claims, and the like. (1) One embodiment of the present invention is a display panel including a first region **700A**, a second region **700B**, and a display region **231**.

(6) The first region **700A** includes part of the display region **231**.

(7) The second region **700B** includes another part of the display region **231**, the second region **700B** is provided with a first component **791**, and the second region **700B** can be bent with the first component **791** facing outward.

(8) The first component **791** includes a first elastic body **791A** and a second elastic body **791C**.

(9) The second elastic body **791C** includes an end portion part or the whole of which is covered with the first elastic body **791A**, and the second elastic body **791C** has a higher elastic modulus than the first elastic body **791A**.

(10) Thus, the degree of easiness in bending the second region **700B** can be adjusted. Alternatively, the second region **700B** can be bent with a curvature radius larger than the predetermined one. Alternatively, the second region **700B** can be bent such that the curvature radius does not become smaller than the predetermined one. Alternatively, a plurality of bent portions with different curvature radii can be formed in the second region **700B**. Alternatively, the second region **700B** can be bent into a U shape. Alternatively, the second region **700B** can be bent repeatedly. Alternatively, the formation of an irreversible fold can be suppressed. Alternatively, the display region overlapping with the second region **700B** can be protected. Alternatively, the strength of the second region **700B** can be increased. As a result, a novel display panel that is highly convenient or reliable can be provided. (2) Another embodiment of the present invention is the display panel in which the display region **231** has a function of performing display in the direction in which the first component **791** is not provided.

(11) Thus, display can be performed without being blocked by the first component **791**.

Alternatively, the formation of a wrinkle in the second region **700B** can be suppressed. As a result, a novel display panel that is highly convenient or reliable can be provided. (3) Another embodiment of the present invention is the display panel in which the second region **700B** can be bent with a curvature radius larger than 2 mm.

(12) Thus, the display panel can be bent repeatedly without having a defect. Alternatively, the thickness of the bent display panel can be reduced. For example, the display panel can be bent with a curvature radius larger than or equal to 5 mm, preferably larger than or equal to 2 mm, further preferably larger than 2 mm. Specifically, the display panel can be bent repeatedly more than 50000 times. As a result, a novel display panel that is highly convenient or reliable can be provided. (4) Another embodiment of the present invention is the display panel in which the thickness of the second region **700B** is smaller than a thickness obtained by addition of 100 μm to the thickness of the first component **791**, preferably smaller than a thickness obtained by addition of 80 μm to the thickness of the first component **791**, further preferably smaller than a thickness obtained by addition of 50 μm to the thickness of the first component **791**.

(13) Thus, the thickness of the display panel can be reduced. As a result, a novel display panel that

is highly convenient or reliable can be provided. (5) Another embodiment of the present invention is the display panel in which the first component **791** becomes thinner toward the end portions in the cross section.

(14) Thus, the rigidity of the first component **791** can be gradually reduced toward the end portions. Alternatively, the second region **700B** can be bent such that the curvature radius becomes gradually smaller toward the end portions. As a result, a novel display panel that is highly convenient or reliable can be provided. (6) Another embodiment of the present invention is the display panel in which the first component **791** has a belt-like shape to cross the display region **231**.

(15) Thus, the display region can be folded in half along the first component **791**. Alternatively, part of the display region **231** can face another part thereof. Alternatively, the outer size of the display panel can be reduced. As a result, a novel display panel that is highly convenient or reliable can be provided. (7) Another embodiment of the present invention is the display panel including a sealant **705**, a first base **510**, a second base **770**, and a third region **700C**.

(16) The sealant **705** is positioned between the first base **510** and the second base **770**.

(17) The second base **770** includes a region overlapping with the first base **510**.

(18) The first region **700A** includes part of the overlapping region, and the second region **700B** includes another part of the overlapping region.

(19) The third region **700C** includes the overlapping region, an end portion of the first base **510**, the second base **770**, and a second component **792**.

(20) In the display panel, the second component **792** covers the end portion of the first base **510**, and the second component **792** has lower moisture permeability than the sealant **705**.

(21) Thus, diffusion of impurities from the outside into a functional layer **520** or a display element **550(i, j)** between the first base **510** and the second base **770** can be inhibited. Alternatively, the end portions of the first base **510** and the second base **770** can be protected. As a result, a novel display panel that is highly convenient or reliable can be provided. (8) Another embodiment of the present invention is the display panel including a pixel **702(i, j)**.

(22) The pixel **702(i, j)** includes the functional layer **520** and the display element **550(i, j)**.

(23) The functional layer **520** includes a pixel circuit **530(i, j)**, and the pixel circuit **530(i, j)** is electrically connected to the display element **550(i, j)**.

(24) Thus, electronic data can be displayed. As a result, a novel display panel that is highly convenient or reliable can be provided. (9) Another embodiment of the present invention is the display panel in which the display region **231** includes a group of pixels **702(i, 1)** to **702(i, n)**, a different group of pixels **702(1, j)** to **702(m, j)**, a scan line **G2(i)**, and a signal line **S2(j)**.

(25) The group of pixels **702(i, 1)** to **702(i, n)** include the pixel **702(i, j)**, and the group of pixels **702(i, 1)** to **702(i, n)** are provided in the row direction.

(26) The different group of pixels **702(1, j)** to **702(m, j)** include the pixel **702(i, j)**, and the different group of pixels **702(1, j)** to **702(m, j)** are provided in the column direction that intersects the row direction.

(27) The scan line **G2(i)** is electrically connected to the group of pixels **702(i, 1)** to **702(i, n)**.

(28) The signal line **S2(j)** is electrically connected to the different group of pixels **702(1, j)** to **702(m, j)**.

(29) Thus, image data can be supplied to a plurality of pixels. As a result, a novel display panel that is highly convenient or reliable can be provided. (10) Another embodiment of the present invention is a display device including the display panel **700** and a control portion **238**.

(30) The control portion **238** is supplied with image data **V1** and control data **CI**, the control portion **238** generates data **V11** on the basis of the image data **V1**, the control portion **238** generates a control signal **SP** on the basis of the control data **CI**, and the control portion **238** supplies the data **V11** and the control signal **SP**.

(31) The display panel **700** is supplied with the data **V11** or the control signal **SP**, and the pixel performs display on the basis of the data.

(32) Thus, the image data can be displayed using the display element. As a result, a novel display device that is highly convenient or reliable can be provided. (11) Another embodiment of the present invention is an input/output device including an input portion **240** and a display portion **230**.

(33) The display portion **230** includes the display panel **700**.

(34) The input portion **240** includes a sensing region **241**, and the input portion **240** senses an object approaching the sensing region **241**. The sensing region **241** includes a region overlapping with the pixel **702(i, j)**.

(35) Thus, the object approaching the region overlapping with the display portion can be sensed while image data is displayed by the display portion. Alternatively, a finger or the like that approaches the display portion can be used as a pointer to input positional data. Alternatively, positional data can be associated with image data displayed on the display portion. As a result, a novel input/output device that is highly convenient or reliable can be provided. (12) Another embodiment of the present invention is a data processing device including an arithmetic device **210** and an input/output device **220**.

(36) The arithmetic device **210** is supplied with input data II or sensing data DS, and the arithmetic device **210** supplies the control data CI and the image data V1.

(37) The input/output device **220** supplies the input data II and the sensing data DS, the input/output device **220** is supplied with the control data CI and the image data V1, and the input/output device **220** includes the display portion **230**, the input portion **240**, and a sensing portion **250**.

(38) The display portion **230** includes the display panel **700**, and the display portion **230** displays the image data V1 on the basis of the control data CI.

(39) The input portion **240** generates the input data II, and the sensing portion **250** generates the sensing data DS. (13) Another embodiment of the present invention is a data processing device including one or more of a keyboard, a hardware button, a pointing device, a touch sensor, an illuminance sensor, an imaging device, an audio input device, an eye-gaze input device, and an attitude sensing device, and the display panel.

(40) Thus, an arithmetic device can generate image data or control data on the basis of data supplied using a variety of input devices. As a result, a novel data processing device that is highly convenient or reliable can be provided.

(41) In the drawings attached to this specification, the block diagram in which components are classified according to their functions and shown as independent blocks is illustrated; however, it is difficult to separate actual components according to their functions completely and it is possible for one component to relate to a plurality of functions.

(42) In this specification, the names of a source and a drain of a transistor interchange with each other depending on the polarity of the transistor and the levels of potentials applied to the terminals. In general, in an n-channel transistor, a terminal to which a lower potential is applied is called a source, and a terminal to which a higher potential is applied is called a drain. In a p-channel transistor, a terminal to which a lower potential is applied is called a drain, and a terminal to which a higher potential is applied is called a source. In this specification, for the sake of convenience, the connection relation of a transistor is sometimes described assuming that the source and the drain are fixed; in reality, the names of the source and the drain interchange with each other depending on the above relation of the potentials.

(43) In this specification, a source of a transistor means a source region that is part of a semiconductor film functioning as an active layer or a source electrode connected to the semiconductor film. Similarly, a drain of a transistor means a drain region that is part of the semiconductor film or a drain electrode connected to the semiconductor film. Moreover, a gate means a gate electrode.

(44) In this specification, a state in which transistors are connected in series means, for example, a

state in which only one of a source and a drain of a first transistor is connected to only one of a source and a drain of a second transistor. In addition, a state in which transistors are connected in parallel means a state in which one of a source and a drain of a first transistor is connected to one of a source and a drain of a second transistor and the other of the source and the drain of the first transistor is connected to the other of the source and the drain of the second transistor.

(45) In this specification, connection means electrical connection and corresponds to a state in which current, voltage, or a potential can be supplied or transmitted. Accordingly, a state of being connected does not necessarily mean a state of being directly connected and also includes, in its category, a state of being indirectly connected through a circuit element such as a wiring, a resistor, a diode, or a transistor such that current, voltage, or a potential can be supplied or transmitted.

(46) In this specification, even when independent components are connected to each other in a circuit diagram, there is actually a case where one conductive film has functions of a plurality of components such as a case where part of a wiring functions as an electrode, for example.

Connection in this specification also includes such a case where one conductive film has functions of a plurality of components in its category.

(47) Furthermore, in this specification, one of a first electrode and a second electrode of a transistor refers to a source electrode and the other refers to a drain electrode.

(48) According to one embodiment of the present invention, a novel display panel that is highly convenient or reliable can be provided. Alternatively, a novel display device that is highly convenient or reliable can be provided. Alternatively, a novel input/output device that is highly convenient or reliable can be provided. Alternatively, a novel data processing device that is highly convenient or reliable can be provided. Alternatively, a novel display panel, a novel display device, a novel input/output device, a novel data processing device, or a novel semiconductor device can be provided.

(49) Note that the description of these effects does not disturb the existence of other effects. One embodiment of the present invention does not necessarily achieve all of these effects. Other effects will be apparent from the description of the specification, the drawings, the claims, and the like, and other effects can be derived from the description of the specification, the drawings, the claims, and the like.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIGS. 1A-1C are diagrams showing a structure of a display panel of an embodiment.

(2) FIGS. 2A-2C are diagrams showing a structure of a display panel of an embodiment.

(3) FIGS. 3A and 3B are diagrams showing a structure of a display panel of an embodiment.

(4) FIGS. 4A-4C are diagrams showing a structure of a display panel of an embodiment.

(5) FIGS. 5A-5E are top views showing structures of a display panel of an embodiment.

(6) FIGS. 6A and 6B are a cross-sectional view and a circuit diagram showing a structure of a display panel of an embodiment.

(7) FIGS. 7A and 7B are cross-sectional views showing a structure of a display panel of an embodiment.

(8) FIGS. 8A-8C are cross-sectional views showing a structure of a display panel of an embodiment.

(9) FIG. 9 is a block diagram showing a structure of a display panel of an embodiment.

(10) FIG. 10 is a diagram showing a structure of a display device of an embodiment.

(11) FIG. 11 is a block diagram showing a structure of an input/output device of an embodiment.

(12) FIGS. 12A and 12B are a block diagram and a projection view showing a structure of a data processing device of an embodiment.

(13) FIGS. 13A and 13B are flow charts showing a method for driving a data processing device of an embodiment.

(14) FIGS. 14A-14C are diagrams showing a method for driving a data processing device of an embodiment.

(15) FIGS. 15A-15C are diagrams showing an artificial intelligence portion of a data processing device of an embodiment.

(16) FIGS. 16A and 16B are diagrams showing the characteristics of transistors of an example.

DETAILED DESCRIPTION OF THE INVENTION

(17) One embodiment of the present invention is a display panel including a first region, a second region, and a display region; the second region includes part of the display region; the second region is provided with a first component; the second region can be bent with the first component facing outward; the first component includes a first elastic body and a second elastic body; the second elastic body includes an end portion part or the whole of which is covered with the first elastic body; and the second elastic body has a higher elastic modulus than the first elastic body.

(18) Thus, the second region can be bent with a curvature radius larger than the predetermined one. Alternatively, the second region can be bent such that the curvature radius does not become smaller than the predetermined one. Alternatively, the second region can be bent repeatedly. Alternatively, the formation of an irreversible fold can be suppressed. As a result, a novel display panel that is highly convenient or reliable can be provided.

(19) Embodiments will be described in detail with reference to the drawings. Note that the present invention is not limited to the following description, and it will be readily appreciated by those skilled in the art that modes and details of the present invention can be modified in various ways without departing from the spirit and scope of the present invention. Thus, the present invention should not be construed as being limited to the description in the following embodiments. Note that in structures of the invention described below, the same portions or portions having similar functions are denoted by the same reference numerals in different drawings, and the description thereof is not repeated.

Embodiment 1

(20) In this embodiment, a structure of a display panel of one embodiment of the present invention will be described with reference to FIG. 1 to FIG. 4.

(21) FIG. 1 shows the structure of the display panel of one embodiment of the present invention. FIG. 1(A) is a perspective view of the display panel of one embodiment of the present invention, FIG. 1(B) is a side view of FIG. 1(A), and FIG. 1(C) is a top view of FIG. 1(A).

(22) FIG. 2 shows the structure of the display panel of one embodiment of the present invention. FIG. 2(A) is a top view of the display panel of one embodiment of the present invention, FIG. 2(B) is a cross-sectional view along the cutting line A1-A2 in FIG. 2(A), and FIG. 2(C) is a cross-sectional view showing a bent state.

(23) FIG. 3(A) is a cross-sectional view showing part of FIG. 2(B), and FIG. 3(B) is a cross-sectional view of a state where part of FIG. 2(B) is bent.

(24) FIG. 4 shows the structure of the display panel of one embodiment of the present invention. FIG. 4(A) is a top view of the display panel of one embodiment of the present invention, FIG. 4(B) is a cross-sectional view along the cutting line A1-A2 in FIG. 4(A), and FIG. 4(C) is a diagram showing part of FIG. 4(B).

(25) Note that in this specification, an integer variable of 1 or more is sometimes used for reference numerals. For example, (p) where p is an integer variable of 1 or more is sometimes used for part of a reference numeral that specifies any one of components (p components at a maximum). For another example, (m, n) where m and n are each an integer variable of 1 or more is sometimes used for part of a reference numeral that specifies any one of components (m×n components at a maximum).

(26) <<Structure Example 1 of Display Panel>>

(27) The display panel **700** described in this embodiment includes the region **700A**, the region **700B**, and the display region **231** (see FIG. 1(A) and FIG. 1(C)).

(28) <<Structure Example 1 of Display Region **231**>>

(29) The display region **231** has a function of displaying an image.

(30) <<Region **700A**>>

(31) The region **700A** includes part of the display region **231**.

(32) <<Structure Example 1 of Region **700B**>>

(33) The region **700B** includes another part of the display region **231**.

(34) The region **700B** is provided with the component **791**, and the region **700B** can be bent with the component **791** facing outward.

(35) <<Structure Example 1 of Component **791**>>

(36) The component **791** includes the elastic body **791A** and the elastic body **791C** (see FIG. 1(B)).

(37) The elastic body **791C** includes an end portion part or the whole of which is covered with the elastic body **791A**, and the elastic body **791C** has a higher elastic modulus than the elastic body **791A**. Alternatively, the elastic body **791C** has a lower breaking elongation rate than the elastic body **791A**. A breaking elongation rate refers to a ratio of the length of a sample at the time when the breakage occurs to the original length in a tension test.

(38) <<Structure Example of Elastic Body **791A** and Elastic Body **791C**>>

(39) For example, a resin, rubber, urethane rubber, or silicone rubber can be used as the elastic body **791A** and the elastic body **791C**.

(40) Specifically, a material with an elastic modulus of 0.1 MPa or higher and 0.8 MPa or lower can be used for the elastic body **791A**. A material with an elastic modulus of 0.8 MPa or higher and 1.2 MPa or lower can be used for the elastic body **791C**. Alternatively, a material with a breaking elongation rate of 350% can be used for the elastic body **791A**. A material with a breaking elongation rate of 200% can be used for the elastic body **791C**.

(41) The elastic body **791C** is less likely to be bent than the elastic body **791A**. Thus, when the region **700B** is bent, a curvature radius **R3** of a portion **P3** overlapping with the elastic body **791C** is larger than a curvature radius **R1** of a portion **P1** overlapping with the elastic body **791A** (see FIG. 3(A) and FIG. 3(B)). A curvature radius **R2** of a portion overlapping with a boundary **P2** between the elastic body **791C** and the elastic body **791A** is larger than the curvature radius **R1** and smaller than the curvature radius **R3**.

(42) Thus, the degree of easiness in bending the region **700B** can be adjusted. Alternatively, the region **700B** can be bent with a curvature radius larger than the predetermined one. Alternatively, the region **700B** can be bent such that the curvature radius does not become smaller than the predetermined one. Alternatively, a plurality of bent portions with different curvature radii can be formed in the region **700B**. Alternatively, the region **700B** can be bent into a U shape. Alternatively, the region **700B** can be bent repeatedly. Alternatively, the formation of an irreversible fold can be suppressed. Alternatively, the display region **231** overlapping with the region **700B** can be protected. Alternatively, the strength of the region **700B** can be increased. As a result, a novel display panel that is highly convenient or reliable can be provided.

(43) <<Structure Example 2 of Display Region **231**>>

(44) The display region **231** has a function of performing display in the direction in which the component **791** is not provided (see FIG. 1(A)).

(45) Thus, display can be performed without being blocked by the component **791**. Alternatively, the formation of a wrinkle in the second region **700B** can be suppressed. As a result, a novel display panel that is highly convenient or reliable can be provided.

(46) <<Structure Example 2 of Region **700B**>>

(47) The region **700B** can be bent with a curvature radius larger than 2 mm (see FIG. 1(B)).

(48) Thus, the display panel can be bent repeatedly without having a defect. Alternatively, the thickness of the bent display panel can be reduced. For example, the display panel can be bent with

a curvature radius larger than or equal to 5 mm, preferably larger than or equal to 2 mm, further preferably larger than 2 mm. Specifically, the display panel can be bent repeatedly more than 50000 times. As a result, a novel display panel that is highly convenient or reliable can be provided.

(49) <<Structure Example 3 of Region **700B**>>

(50) The thickness of the region **700B** is smaller than a thickness **T21** obtained by addition of 100 μm to a thickness **T22** of the component **791** (see FIG. 3(A)). Note that the thickness of the region **700B** is preferably smaller than a thickness obtained by addition of 80 μm to the thickness **T22** of the component **791**, further preferably smaller than a thickness obtained by addition of 50 μm to the thickness **T22**.

(51) Thus, the thickness of the display panel can be reduced. As a result, a novel display panel that is highly convenient or reliable can be provided.

(52) <<Structure Example 2 of Component **791**>>

(53) The component **791** becomes thinner toward the end portions in the cross section ((see FIG. 3(A) and FIG. 3(B)).

(54) Thus, the rigidity of the component **791** can be gradually reduced toward the end portions. Alternatively, the region **700B** can be bent such that the curvature radius becomes gradually smaller toward the end portions. As a result, a novel display panel that is highly convenient or reliable can be provided.

(55) <<Structure Example 3 of Component **791**>>

(56) The component **791** has a belt-like shape to cross the display region **231** (see FIG. 2(A) and FIG. 2(B)).

(57) Thus, the display region can be folded in half along the first component (see FIG. 2(C)). Alternatively, part of the display region can face another part thereof. Alternatively, the outer size of the display panel can be reduced. As a result, a novel display panel that is highly convenient or reliable can be provided.

(58) <Structure Example 2 of Display Panel>

(59) The display panel **700** described in this embodiment includes the sealant **705**, the base **510**, the base **770**, and the region **700C** (see FIG. 4(A) and FIG. 4(B)). The component **791** includes the elastic body **791A**, an elastic body **791B**, and the elastic body **791C**. The elastic body **791C** includes an end portion part of which is covered with the elastic body **791B**, and the elastic body **791C** has a higher elastic modulus than the elastic body **791B**. Alternatively, the elastic body **791C** has a lower breaking elongation rate than the elastic body **791B**. For example, a material that can be used for the elastic body **791A** can be used for the elastic body **791B**.

(60) <<Structure Example of Sealant **705**>>

(61) The sealant **705** is positioned between the first base **510** and the second base **770**.

(62) <<Structure Example of Base **510** and Base **770**>>

(63) The base **770** includes a region overlapping with the base **510**.

(64) The region **700A** includes part of the overlapping region, and the region **700B** includes another part of the overlapping region.

(65) The base **510** and the base **770** have flexibility.

(66) For example, an organic material such as a resin, a resin film, or plastic can be used for the base **510** or the base **770**. Specifically, a resin film or a resin plate of polyester, polyolefin, polyamide, polyimide, polycarbonate, an acrylic resin, or the like can be used. As a result, the weight can be reduced. Alternatively, for example, the frequency of occurrence of breakage due to dropping or the like can be reduced.

(67) For example, a composite material formed by attaching a metal plate, a thin glass plate, or a film of an inorganic material or the like to a resin film or the like can be used for the base **510** or the base **770**. For example, a composite material formed by dispersing a fibrous or particulate metal, glass, an inorganic material, or the like into a resin film can be used. For example, a composite material formed by dispersing a fibrous or particulate resin, an organic material, or the

like into an inorganic material can be used.

(68) Furthermore, a single-layer material or a material in which a plurality of layers are stacked can be used for the base **510** or the base **770**. For example, a material in which a base and an insulating film or the like that prevents diffusion of impurities contained in the base are stacked can be used. Specifically, a material in which glass and one or more films selected from a silicon oxide layer, a silicon nitride layer, a silicon oxynitride layer, and the like that prevent diffusion of impurities contained in the glass are stacked can be used. Alternatively, a material in which a resin and a silicon oxide film, a silicon nitride film, a silicon oxynitride film, or the like that prevents diffusion of impurities that penetrate the resin are stacked can be used.

(69) Specifically, a material containing polyester, polyolefin, polyamide (nylon, aramid, or the like), polyimide, polycarbonate, polyurethane, an acrylic resin, an epoxy resin, or a resin having a siloxane bond, such as silicone, can be used for the base **510** or the base **770**. For example, a resin film, a resin plate, a stacked-layer material, or the like containing any of these resins can be used.

(70) Specifically, polyethylene terephthalate (PET), polyethylene naphthalate (PEN), polyethersulfone (PES), a cycloolefin polymer (COP), a cycloolefin copolymer (COC), or the like can be used for the base **510** or the base **770**.

(71) Furthermore, paper, wood, or the like can be used for the base **510** or the base **770**.

(72) For example, a flexible material can be used for the base **510** or the base **770**.

(73) Note that a method in which a transistor, a capacitor, or the like is directly formed on a substrate can be used. Alternatively, a method in which a transistor, a capacitor, or the like is formed on a substrate that is for use in the process and has resistance to heat applied in the manufacturing process, and the formed transistor, capacitor, or the like is transferred to the base **510** or the base **770**, for example, can be used. Accordingly, a transistor, a capacitor, or the like can be formed on a flexible substrate, for example.

(74) <<Region **700C**>>

(75) The region **700C** includes the overlapping region, an end portion of the base **510**, the base **770**, and the component **792** (see FIG. 4(C)).

(76) <<Component **792**>>

(77) The component **792** covers the end portion of the base **510**, and the component **792** has lower moisture permeability than the sealant **705**.

(78) For example, part of the component **791** can be used as the component **792**. Specifically, the elastic body **791A** or the elastic body **791B** can be used as the component **792**.

(79) Alternatively, a film or a stacked-layer film can be used as the component **792**. Specifically, a material with a moisture permeability of 10^{-5} g/(m²·day) or lower, preferably 10^{-6} g/(m²·day) or lower can be used for the component **792**. For example, a material including an inorganic film or an organic film can be used for the component **792**.

Specifically, a metal film, a film containing a metal and oxygen, a film containing a metal and nitrogen, a film containing a crosslinked polymer, or the like can be used as the component **792**.

(80) Alternatively, a material with an elastic modulus higher than or equal to that of the elastic body **791A** can be used for the component **792**. Alternatively, a material with an elastic modulus higher than or equal to that of the elastic body **791B** can be used for the component **792**. A material with a breaking elongation rate lower than or equal to that of the elastic body **791A** can be used for the component **792**. Alternatively, a material with a breaking elongation rate lower than or equal to that of the elastic body **791B** can be used for the component **792**. Alternatively, a material with rigidity higher than or equal to that of the component **791** can be used for the component **792**.

(81) Thus, diffusion of impurities from the outside into the functional layer **520** or the display element **550(i, j)** between the first base **510** and the second base **770** can be inhibited. Alternatively, the end portions of the first base **510** and the second base **770** can be protected. As a result, a novel display panel that is highly convenient or reliable can be provided.

(82) Note that this embodiment can be combined with other embodiments in this specification as

appropriate.

Embodiment 2

(83) In this embodiment, a structure of the display panel of one embodiment of the present invention will be described with reference to FIG. 5 to FIG. 7.

(84) FIG. 5 shows the structure of the display panel of one embodiment of the present invention. FIG. 5(A) is a top view of the display panel, and FIG. 5(B) and FIG. 5(C) are top views showing part of the pixel of the display panel shown in FIG. 5(A).

(85) FIG. 6(A) is a cross-sectional view along the cutting line X1-X2, the cutting line X3-X4, and the cutting line X9-X10 in FIG. 5(A). FIG. 6(B) is a circuit diagram showing a structure of the pixel circuit included in the display panel.

(86) FIG. 7(A) is a diagram showing a structure of the pixel of the display panel of one embodiment of the present invention. FIG. 7(B) is a cross-sectional view showing part of the pixel shown in FIG. 7(A).

(87) <Structure Example 3 of Display Panel>

(88) The display panel **700** described in this embodiment includes the pixel **702**(*i*, *j*) (see FIG. 5(A)).

(89) <<Structure Example 1 of Pixel **702**(*i*, *j*)>>

(90) The pixel **702**(*i*, *j*) includes the functional layer **520** and the display element **550**(*i*, *j*) (see FIG. 6(A)).

(91) <<Structure Example 1 of Functional Layer **520**>>

(92) The functional layer **520** includes the pixel circuit **530**(*i*, *j*).

(93) <<Structure Example 1 of Pixel Circuit **530**(*i*, *j*)>>

(94) The pixel circuit **530**(*i*, *j*) is electrically connected to the display element **550**(*i*, *j*) (see FIG. 6(A) and FIG. 6(B)).

(95) For example, the pixel circuit **530**(*i*, *j*) is electrically connected to the display element **550**(*i*, *j*) in an opening portion **591A** (see FIG. 7(A)).

(96) A switch, a transistor, a diode, a resistor, an inductor, a capacitor, or the like can be used in the pixel circuit **530**(*i*, *j*), for example.

(97) The pixel circuit **530**(*i*, *j*) includes a switch SW2, a transistor M, and a capacitor C21.

(98) For example, a transistor can be used as the switch SW2 (see FIG. 6(B), FIG. 7(A), and FIG. 7(B)).

(99) <<Structure Example 1 of Display Element **550**(*i*, *j*)>>

(100) The display element **550**(*i*, *j*) has a function of emitting light.

(101) The display element **550**(*i*, *j*) includes a layer **553**(*j*) containing a light-emitting material (see FIG. 7(A)).

(102) A display element having a function of emitting light, for example, can be used as the display element **550**(*i*, *j*). Specifically, an organic electroluminescence element, an inorganic electroluminescence element, a light-emitting diode, a QDLED (Quantum Dot LED), or the like can be used as the display element **550**(*i*, *j*).

(103) <<Structure Example 1 of Layer **553**(*j*) Containing Light-Emitting Material>>

(104) A belt-like layered material that is long in the column direction along the signal line S2(*j*) can be used for the layer **553**(*j*) containing a light-emitting material, for example.

(105) Specifically, materials emitting light with different hues can be used for the layer **553**(*j*) containing a light-emitting material, a layer **553**(*j*+1) containing a light-emitting material, and a layer **553**(*j*+2) containing a light-emitting material. Thus, for example, the hue of the light emitted from the display element **550**(*i*, *j*) can be different between columns.

(106) For example, a material that emits blue light, a material that emits green light, and a material that emits red light can be used as the materials emitting light with different hues.

(107) <<Structure Example 2 of Layer **553**(*j*) Containing Light-Emitting Material>>

(108) A layered material for emitting white light can be used for the layer **553**(*j*) containing a light-

emitting material, for example.

(109) Specifically, materials that emit light with different hues can be used for the layer 553(j) containing a light-emitting material.

(110) For example, a layered material in which a layer containing a light-emitting material including a fluorescent material that emits blue light, and a layer containing materials that are other than a fluorescent material and that emit green light and red light are stacked can be used for the layer 553(j) containing a light-emitting material. Alternatively, a layered material in which a layer containing a light-emitting material including a fluorescent material that emits blue light, and a layer containing a material that is other than a fluorescent material and that emits yellow light are stacked can be used for the layer 553(j) containing a light-emitting material.

(111) A light-emitting unit can be used for the layer 553(j) containing a light-emitting material, for example. The light-emitting unit includes one region where electrons injected from one side are recombined with holes injected from the other side. The light-emitting unit contains a light-emitting material, and the light-emitting material releases energy generated by recombination of electrons and holes as light.

(112) A plurality of light-emitting units and an intermediate layer can be used for the layer 553(j) containing a light-emitting material, for example. The intermediate layer includes a region positioned between two light-emitting units. The intermediate layer includes a charge-generation region and has functions of supplying holes to the light-emitting unit provided on the cathode side and supplying electrons to the light-emitting unit provided on the anode side. Furthermore, a structure including a plurality of light-emitting units and an intermediate layer is referred to as a tandem light-emitting element in some cases.

(113) For example, a light-emitting unit including a material emitting light with one hue and a light-emitting unit including a material emitting light with a different hue can be used for the layer 553(j) containing a light-emitting material.

(114) For example, a high molecular compound (e.g., an oligomer, a dendrimer, or a polymer), a middle molecular compound (a compound between a low molecular compound and a high molecular compound with a molecular weight greater than or equal to 400 and less than or equal to 4000), or the like can be used for the layer 553(j) containing a light-emitting material.

(115) <<Electrode 551(i, j) and Electrode 552>>

(116) An electrode 551(i, j) is electrically connected to the pixel circuit 530(i, j) in the opening portion 591A(i, j) (see FIG. 7(A)).

(117) For example, the material that can be used for the wiring or the like can be used for the electrode 551(i, j) or an electrode 552. Specifically, a material that has a visible light-transmitting property can be used for the electrode 551(i, j) or the electrode 552.

(118) For example, a conductive oxide, a conductive oxide containing indium, indium oxide, indium tin oxide, indium zinc oxide, zinc oxide, zinc oxide to which gallium is added, or the like can be used. Alternatively, a metal film thin enough to transmit light can be used. Alternatively, a material that has a visible light-transmitting property can be used.

(119) For example, a metal film that transmits part of light and reflects another part of the light can be used for the electrode 551(i, j) or the electrode 552. Thus, for example, the distance between the electrode 551(i, j) and the electrode 552 can be adjusted. Alternatively, a microcavity structure can be provided in the display element 550(i, j). Alternatively, light of a predetermined wavelength can be extracted more efficiently than other light. Alternatively, light with a narrow half width of a spectrum can be extracted. Alternatively, light of a bright color can be extracted.

(120) For example, a film that reflects light efficiently can be used for the electrode 551(i, j) or the electrode 552. Specifically, a material containing silver, palladium, and the like or a material containing silver, copper, and the like can be used for the metal film.

(121) <<Structure Example 2 of Pixel Circuit 530(i, j)>>

(122) The pixel circuit 530(i, j) includes the switch SW2, the transistor M, and the capacitor C21.

For example, a transistor can be used as the switch SW2.

(123) <<Structure Example 1 of Switch SW2>>

(124) The transistor used as the switch SW2 includes a semiconductor (see FIG. 7(B)).

(125) The transistor includes a semiconductor film 508, a conductive film 504, a conductive film 512A, and a conductive film 512B (see FIG. 7(B)).

(126) The semiconductor film 508 includes a region 508A electrically connected to the conductive film 512A and a region 508B electrically connected to the conductive film 512B. The semiconductor film 508 includes a region 508C between the region 508A and the region 508B.

(127) The conductive film 504 includes a region overlapping with the region 508C, and the conductive film 504 has a function of a gate electrode.

(128) An insulating film 506 includes a region positioned between the semiconductor film 508 and the conductive film 504. The insulating film 506 has a function of a gate insulating film.

(129) The conductive film 512A has one of a function of a source electrode and a function of a drain electrode, and the conductive film 512B has the other of the function of the source electrode and the function of the drain electrode.

(130) <<Structure Example 1 of Transistor M>>

(131) For example, semiconductor films that can be formed in the same step can be used for the transistor used as the switch SW2 and the transistor M. The same structure can be employed for the transistor used as the switch SW2 and the transistor M.

(132) A conductive film 524 can be used for the transistor. The semiconductor film 508 is positioned between the conductive film 504 and a region included in the conductive film 524. The conductive film 524 has a function of a second gate electrode. The conductive film 524 can be electrically connected to the conductive film 504, for example.

(133) Note that semiconductor films that can be formed in the same step can be used for transistors in the driver circuit and the pixel circuit, for example.

(134) A bottom-gate transistor or a top-gate transistor can be used in the pixel circuit 530(i, j), for example. Alternatively, these transistors can be used as the transistors in the driver circuit.

(135) <<Structure Example 1 of Semiconductor Film 508>>

(136) A semiconductor containing a Group 14 element can be used for the semiconductor film 508, for example. Specifically, a semiconductor containing silicon can be used for the semiconductor film 508.

(137) [Hydrogenated Amorphous Silicon]

(138) For example, hydrogenated amorphous silicon can be used for the semiconductor film 508. Alternatively, microcrystalline silicon or the like can be used for the semiconductor film 508. Thus, a display panel having less display unevenness than a display panel using polysilicon for the semiconductor film 508, for example, can be provided. Alternatively, the size of the display panel can be easily increased.

(139) [Polysilicon]

(140) For example, polysilicon can be used for the semiconductor film 508. Thus, for example, the field-effect mobility of the transistor can be higher than that of a transistor using hydrogenated amorphous silicon for the semiconductor film 508. For another example, the drive capability can be higher than that of a transistor using hydrogenated amorphous silicon for the semiconductor film 508. For another example, the aperture ratio of the pixel can be higher than that in the case of a transistor using hydrogenated amorphous silicon for the semiconductor film 508.

(141) For another example, the reliability of the transistor can be higher than that of a transistor using hydrogenated amorphous silicon for the semiconductor film 508.

(142) Alternatively, the temperature required for manufacture of the transistor can be lower than that required for manufacture of a transistor using single crystal silicon, for example.

(143) Alternatively, the semiconductor film used for the transistor in the driver circuit can be formed in the same step as the semiconductor film used for the transistor in the pixel circuit.

Alternatively, the driver circuit can be formed over the same substrate as the substrate over which the pixel circuit is formed. Alternatively, the number of components included in an electronic device can be reduced.

(144) [Single Crystal Silicon]

(145) For example, single crystal silicon can be used for the semiconductor film **508**. Thus, for example, the resolution can be higher than that of a display panel using hydrogenated amorphous silicon for the semiconductor film **508**. For another example, a display panel having less display unevenness than a display panel using polysilicon for the semiconductor film **508** can be provided. For another example, smart glasses or a head-mounted display can be provided.

(146) <<Structure Example 2 of Semiconductor Film **508**>>

(147) For example, a metal oxide can be used for the semiconductor film **508**. Thus, the pixel circuit can hold an image signal for a longer time than a pixel circuit utilizing a transistor that uses amorphous silicon for the semiconductor film **508**. Specifically, a selection signal can be supplied at a frequency lower than 30 Hz, preferably lower than 1 Hz, further preferably less than once per minute while occurrence of flickers is suppressed. Consequently, fatigue accumulation in a user of a data processing device can be reduced. Moreover, power consumption associated with driving can be reduced.

(148) A transistor using an oxide semiconductor can be used, for example. Specifically, an oxide semiconductor containing indium or an oxide semiconductor containing indium, gallium, and zinc can be used for the semiconductor film **508**.

(149) A transistor having a lower leakage current in an off state than a transistor using amorphous silicon for the semiconductor film **508** can be used, for example. Specifically, a transistor using an oxide semiconductor for the semiconductor film **508** can be used.

(150) A 25-nm-thick film containing indium, gallium, and zinc can be used as the semiconductor film **508**, for example.

(151) A conductive film in which a 10-nm-thick film containing tantalum and nitrogen and a 300-nm-thick film containing copper are stacked can be used as the conductive film **504**. Note that the film containing tantalum and nitrogen is positioned between the insulating film **506** and a region included in the film containing copper.

(152) A stacked-layer film in which a 400-nm-thick film containing silicon and nitrogen and a 200-nm-thick film containing silicon, oxygen, and nitrogen are stacked can be used as the insulating film **506**, for example. Note that the film containing silicon, oxygen, and nitrogen is positioned between the semiconductor film **508** and a region included in the film containing silicon and nitrogen.

(153) A conductive film in which a 50-nm-thick film containing tungsten, a 400-nm-thick film containing aluminum, and a 100-nm-thick film containing titanium are stacked in this order can be used as the conductive film **512A** or the conductive film **512B**, for example. Note that the film containing tungsten includes a region in contact with the semiconductor film **508**.

(154) A manufacturing line for a bottom-gate transistor using amorphous silicon as a semiconductor can be easily remodeled into a manufacturing line for a bottom-gate transistor using an oxide semiconductor as a semiconductor, for example. Furthermore, for example, a manufacturing line for a top-gate transistor using polysilicon as a semiconductor can be easily remodeled into a manufacturing line for a top-gate transistor using an oxide semiconductor as a semiconductor. In either remodeling, a conventional manufacturing line can be effectively utilized.

(155) This can suppress flickering. Alternatively, the power consumption can be reduced.

Alternatively, a moving image that moves quickly can be smoothly displayed. Alternatively, a photograph and the like can be displayed in a wide range of grayscale. As a result, a novel display panel that is highly convenient or reliable can be provided.

(156) <<Structure Example 3 of Semiconductor Film **508**>>

(157) For example, a compound semiconductor can be used as a semiconductor of the transistor.

Specifically, a semiconductor containing gallium arsenide can be used.

(158) For example, an organic semiconductor can be used as a semiconductor of the transistor. Specifically, an organic semiconductor containing polyacene or graphene can be used for the semiconductor film.

(159) <<Structure Example 2 of Pixel **702**(i, j)>>

(160) The display region **231** includes a plurality of pixels. For example, pixels having a function of representing colors with different hues can be used for the display region **231**. Alternatively, colors with hues that cannot be represented by each of the pixels can be represented by additive color mixture or subtractive color mixture with the use of the plurality of pixels.

(161) Note that when a plurality of pixels capable of representing colors with different hues are used for color mixture, each of the pixels can be rephrased as a subpixel. In addition, a set of subpixels can be rephrased as a pixel.

(162) For example, the pixel **702**(i, j) can be rephrased as a subpixel, and a set of the pixel **702**(i, j), a pixel **702**(i, j+1), and a pixel **702**(i, j+2) can be rephrased as a pixel **703**(i, k) (see FIG. 5(C)).

(163) Alternatively, the pixel **702**(i, j) can be rephrased as a subpixel, and a set of the pixel **702**(i, j), the pixel **702**(i, j+1), a pixel **702**(i+1, j), and a pixel **702**(i+1, j+1) can be rephrased as the pixel **703**(i, k) (see FIG. 5(E)).

(164) Specifically, a set of a subpixel that represents blue, a subpixel that represents green, and a subpixel that represents red can be used as the pixel **703**(i, k). A set of a subpixel that represents cyan, a subpixel that represents magenta, and a subpixel that represents yellow can be used as the pixel **703**(i, k).

(165) Furthermore, the above set to which a subpixel that represents white or the like is added can be used as the pixel, for example.

(166) <<Structure Example 2 of Functional Layer **520**>>

(167) The functional layer **520** includes the pixel circuit **530**(i, j) and an insulating film **516**. For example, an insulating film having a bottom surface and a top surface that faces the bottom surface can be used as the insulating film **516**.

(168) Specifically, an insulating film having a bottom surface that is in contact with the semiconductor film **508** and a top surface that is in contact with a semiconductor film **508**(2) can be used as the insulating film **516** (see FIG. 8(B) and FIG. 8(C)).

(169) For example, a stacked-layer film can be used as the insulating film **516**. Specifically, part of the insulating film **516** can be formed over the semiconductor film **508**, a different part of the insulating film **516** can be formed over the part, and the semiconductor film **508**(2) can be formed over the different part.

(170) <<Structure Example 3 of Pixel Circuit **530**(i, j)>>

(171) The pixel circuit **530**(i, j) includes the switch SW2, the transistor M, and the capacitor C21.

(172) A transistor including a semiconductor film formed in a step different from a step of forming the semiconductor film used in the transistor M can be used as the switch SW2, for example (see FIG. 8(A), FIG. 8(B), and FIG. 8(C)). Alternatively, a transistor including a semiconductor film that has a composition different from the composition of the semiconductor film used in the transistor M can be used as the switch SW2.

(173) Specifically, a transistor including the semiconductor film **508** can be used as the switch SW2, and a transistor including the semiconductor film **508**(2) can be used as the transistor M.

(174) Thus, the current drive capability of the transistor M can be higher than that of the transistor used as the switch SW2, for example. Alternatively, a source electrode or a drain electrode of the transistor used as the switch SW2 can be used as a gate electrode of the transistor M. Alternatively, the distance between the semiconductor film **508** of the transistor used as the switch SW2 and the semiconductor film **508**(2) of the transistor M can be shortened. Alternatively, the area occupied by the transistor used as the switch SW2 and the transistor M can be reduced. Alternatively, the aperture ratio of the pixel can be increased. Alternatively, the pixel can be miniaturized.

Alternatively, a high-resolution display panel can be provided. Alternatively, the flexibility in the layout of the pixel circuit can be increased. Alternatively, the number of transistors provided in the minute pixel can be increased.

(175) Although not illustrated, another structure may be employed in which the transistor including the semiconductor film **508(2)** is used as the switch SW2 and the transistor including the semiconductor film **508** is used as the transistor M, for example.

(176) <Structure Example 4 of Display Panel>

(177) The display panel **700** also includes the display region **231** (see FIG. 5(A)).

(178) The display region **231** includes the scan line G2(i) and the signal line S2(j).

(179) <<Structure Example 3 of Display Region **231**>>

(180) The display region **231** includes the pixel **702(i, j)**, the pixel **702(i, j+1)**, and the pixel **702(i, j+2)** (see FIG. 5(C)).

(181) The pixel **702(i, j)** emits light of a color that has a chromaticity x of greater than 0.680 and less than or equal to 0.720 and a chromaticity y of greater than or equal to 0.260 and less than or equal to 0.320 in the CIE 1931 chromaticity coordinates.

(182) The pixel **702(i, j+1)** emits light of a color that has a chromaticity x of greater than or equal to 0.130 and less than or equal to 0.250 and a chromaticity y of greater than 0.710 and less than or equal to 0.810 in the CIE 1931 chromaticity coordinates.

(183) The pixel **702(i, j+2)** emits light of a color that has a chromaticity x of greater than or equal to 0.120 and less than or equal to 0.170 and a chromaticity y of greater than or equal to 0.020 and less than 0.060 in the CIE 1931 chromaticity coordinates.

(184) The pixel **702(i, j)**, the pixel **702(i, j+1)**, and the pixel **702(i, j+2)** are provided such that the area ratio of their color gamut to the BT.2020 color gamut in the CIE chromaticity diagram (x, y) is higher than or equal to 80%, or the color gamut coverage is higher than or equal to 75%.

Preferably, they are provided such that the area ratio is higher than or equal to 90%, or the coverage is higher than or equal to 85%.

(185) <Structure Example 5 of Display Panel>

(186) The display panel **700** includes the base **510**, the base **770**, and an insulating film **501C** (see FIG. 7(A)).

(187) The insulating film **501C** includes a region positioned between the base **510** and the base **770**, and the functional layer **520** includes a region positioned between the insulating film **501C** and the base **770**.

(188) <<Structure Example 3 of Functional Layer **520**>>

(189) The functional layer **520** includes an insulating film **521**, an insulating film **518**, the insulating film **516**, the insulating film **506**, the insulating film **501C**, and the like.

(190) [Insulating Film **521**]

(191) The insulating film **521** includes a region positioned between the pixel circuit **530(i, j)** and the display element **550(i, j)** (see FIG. 7(A)).

(192) An insulating inorganic material, an insulating organic material, or an insulating composite material containing an inorganic material and an organic material, for example, can be used for the insulating film **521**.

(193) Specifically, an inorganic oxide film, an inorganic nitride film, an inorganic oxynitride film, or the like, or a layered material in which a plurality of films selected from these films are stacked can be used as the insulating film **521**.

(194) For example, a film including a silicon oxide film, a silicon nitride film, a silicon oxynitride film, an aluminum oxide film, or the like, or a film including a layered material in which a plurality of films selected from these films are stacked can be used as the insulating film **521**. Note that the silicon nitride film is a dense film and has an excellent function of inhibiting diffusion of impurities.

(195) For example, for the insulating film **521**, polyester, polyolefin, polyamide, polyimide,

polycarbonate, polysiloxane, an acrylic resin, or the like, or a layered material, a composite material, or the like of a plurality of resins selected from these resins can be used. Alternatively, a photosensitive material may be used. Thus, the insulating film **521** can planarize a level difference due to various components overlapping with the insulating film **521**, for example.

(196) Note that polyimide is excellent in thermal stability, insulating property, toughness, low dielectric constant, low coefficient of thermal expansion, chemical resistance, and other properties compared with other organic materials. Accordingly, in particular, polyimide can be suitably used for the insulating film **521** or the like.

(197) For example, a film formed using a photosensitive material can be used as the insulating film **521**. Specifically, a film formed using photosensitive polyimide, a photosensitive acrylic resin, or the like can be used as the insulating film **521**.

(198) For example, a light-transmitting material can be used for the insulating film **521**. Specifically, silicon nitride can be used for the insulating film **521**.

(199) [Insulating Film **518**]

(200) The insulating film **518** includes a region positioned between the pixel circuit **530**(*i, j*) and the insulating film **521** (see FIG. 7(B)). Note that a stacked-layer film can be used as the insulating film **518**.

(201) The material that can be used for the insulating film **521**, for example, can be used for the insulating film **518**.

(202) For example, a material that has a function of inhibiting diffusion of oxygen, hydrogen, water, an alkali metal, an alkaline earth metal, and the like can be used for the insulating film **518**. Specifically, a nitride insulating film can be used as the insulating film **518**. For example, silicon nitride, silicon nitride oxide, aluminum nitride, aluminum nitride oxide, or the like can be used for the insulating film **518**. Thus, diffusion of impurities to a semiconductor film of a transistor can be inhibited.

(203) [Insulating Film **516**]

(204) The insulating film **516** includes a region positioned between the pixel circuit **530**(*i, j*) and the insulating film **518** (see FIG. 7(B)). Note that a stacked-layer film can be used as the insulating film **516**. Specifically, an insulating film in which an insulating film **516A** and an insulating film **516B** are stacked can be used as the insulating film **516**.

(205) The material that can be used for the insulating film **521**, for example, can be used for the insulating film **516**. Specifically, a film formed by a manufacturing method different from that of the insulating film **518** can be used as the insulating film **516**.

(206) [Insulating Film **506** and Insulating Film **501D**]

(207) The insulating film **506** includes a region positioned between the semiconductor film **508** and a conductive film **504E** (see FIG. 7(B)). An insulating film **501D** includes a region positioned between the semiconductor film **508** and the conductive film **524**.

(208) The material that can be used for the insulating film **521**, for example, can be used for the insulating film **506** or the insulating film **501D**. Specifically, a film including a silicon oxide film, a silicon oxynitride film, a silicon nitride oxide film, a silicon nitride film, an aluminum oxide film, a hafnium oxide film, an yttrium oxide film, a zirconium oxide film, a gallium oxide film, a tantalum oxide film, a magnesium oxide film, a lanthanum oxide film, a cerium oxide film, or a neodymium oxide film can be used as the insulating film **506**.

(209) [Insulating Film **501C**]

(210) The insulating film **501C** includes a region positioned between the pixel circuit **530**(*i, j*) and the base **510** (see FIG. 7(A)).

(211) The material that can be used for the insulating film **521**, for example, can be used for the insulating film **501C**. Specifically, a material containing silicon and oxygen can be used for the insulating film **501C**. Thus, diffusion of impurities into the pixel circuit, the display element, or the like can be inhibited.

(212) [Insulating Film **528**]

(213) An insulating film **528** includes a region positioned between the insulating film **521** and the base **770** and has an opening portion in a region overlapping with the display element **550**(*i, j*) (see FIG. 7(A)). The insulating film **528** formed along the periphery of the electrode **551**(*i, j*) prevents a short circuit between the electrode **551**(*i, j*) and the electrode **552**.

(214) The material that can be used for the insulating film **521**, for example, can be used for the insulating film **528**. Specifically, a silicon oxide film, a film containing an acrylic resin, or a film containing polyimide can be used as the insulating film **528**.

(215) <<Sealant **705**>>

(216) The sealant **705** includes a region positioned between the functional layer **520** and the base **770** and has a function of bonding the functional layer **520** and the base **770** together.

(217) An inorganic material, an organic material, a composite material of an inorganic material and an organic material, or the like can be used for the sealant **705**.

(218) For example, an organic material such as a thermally fusible resin or a curable resin can be used for the sealant **705**.

(219) For example, an organic material such as a reactive curable adhesive, a photocurable adhesive, a thermosetting adhesive, and/or an anaerobic adhesive can be used for the sealant **705**.

(220) Specifically, an adhesive containing an epoxy resin, an acrylic resin, a silicone resin, a phenol resin, a polyimide resin, an imide resin, a PVC (polyvinyl chloride) resin, a PVB (polyvinyl butyral) resin, an EVA (ethylene vinyl acetate) resin, or the like can be used for the sealant **705**.

(221) <<Functional Layer **720**>>

(222) A functional layer **720** includes a coloring film CF**1**, an insulating film **771**, and a light-blocking film BM.

(223) The coloring film CF**1** includes a region positioned between the base **770** and the display element **550**(*i, j*).

(224) The light-blocking film BM has an opening portion in a region overlapping with the pixel **702**(*i, j*).

(225) <<Functional Film **770P** and the Like>>

(226) A functional film **770P** includes a region overlapping with the display element **550**(*i, j*).

(227) An anti-reflection film, a polarizing film, a retardation film, a light diffusion film, a condensing film, or the like can be used as the functional film **770P**, for example.

(228) Specifically, a circularly polarizing film can be used as the functional film **770P**.

(229) Furthermore, an antistatic film suppressing the attachment of a dust, a water repellent film suppressing the attachment of a stain, an antireflective film (anti-reflection film), a non-glare film (anti-glare film), a hard coat film suppressing generation of a scratch in use, or the like can be used as the functional film **770P**.

(230) Note that this embodiment can be combined with other embodiments in this specification as appropriate.

Embodiment 3

(231) Described in this embodiment is a metal oxide that can be used for a semiconductor film of a transistor disclosed in one embodiment of the present invention. Note that in the case where a metal oxide is used for a semiconductor film of a transistor, the metal oxide may be rephrased as an oxide semiconductor.

(232) Oxide semiconductors are classified into a single crystal oxide semiconductor and a non-single-crystal oxide semiconductor. Examples of the non-single-crystal oxide semiconductor include a CAAC-OS (c-axis-aligned crystalline oxide semiconductor), a polycrystalline oxide semiconductor, an nc-OS (nanocrystalline oxide semiconductor), an amorphous-like oxide semiconductor (a-like OS), and an amorphous oxide semiconductor.

(233) An example of the non-single-crystal oxide semiconductor is an oxide semiconductor called a semi-crystalline oxide semiconductor. The semi-crystalline oxide semiconductor has an

intermediate structure between the single crystal oxide semiconductor and the amorphous oxide semiconductor. The structure of the semi-crystalline oxide semiconductor is more stable than that of the amorphous oxide semiconductor. An example of the semi-crystalline oxide semiconductor is an oxide semiconductor having a CAAC structure and a CAC (Cloud-Aligned Composite) composition. The details of the CAC will be described below.

(234) A CAC-OS (Cloud-Aligned Composite oxide semiconductor) may be used for a semiconductor film of a transistor disclosed in one embodiment of the present invention.

(235) The aforementioned non-single-crystal oxide semiconductor or CAC-OS can be suitably used for a semiconductor film of a transistor disclosed in one embodiment of the present invention. As the non-single-crystal oxide semiconductor, the nc-OS or the CAAC-OS can be suitably used.

(236) In one embodiment of the present invention, a CAC-OS is preferably used for a semiconductor film of a transistor. The use of the CAC-OS allows the transistor to have high electrical characteristics or high reliability.

(237) The CAC-OS will be described in detail below.

(238) A CAC-OS or a CAC-metal oxide has a conducting function in a part of the material and has an insulating function in a part of the material and has a function of a semiconductor as a whole. Note that in the case where the CAC-OS or the CAC-metal oxide is used in a channel formation region of a transistor, the conducting function is to allow electrons (or holes) serving as carriers to flow, and the insulating function is to not allow electrons serving as carriers to flow. By the complementary action of the conducting function and the insulating function, the CAC-OS or the CAC-metal oxide can have a switching function (On/Off function). In the CAC-OS or the CAC-metal oxide, separation of the functions can maximize each function.

(239) Furthermore, the CAC-OS or the CAC-metal oxide includes conductive regions and insulating regions. The conductive regions have the above-described conducting function, and the insulating regions have the above-described insulating function. Furthermore, in some cases, the conductive regions and the insulating regions in the material are separated at the nanoparticle level. Furthermore, in some cases, the conductive regions and the insulating regions are unevenly distributed in the material. Furthermore, the conductive regions are observed to be coupled in a cloud-like manner with their boundaries blurred, in some cases.

(240) Furthermore, in the CAC-OS or the CAC-metal oxide, the conductive regions and the insulating regions each have a size greater than or equal to 0.5 nm and less than or equal to 10 nm, preferably greater than or equal to 0.5 nm and less than or equal to 3 nm, and are dispersed in the material, in some cases.

(241) Furthermore, the CAC-OS or the CAC-metal oxide includes components having different bandgaps. For example, the CAC-OS or the CAC-metal oxide includes a component having a wide gap due to the insulating region and a component having a narrow gap due to the conductive region. When carriers flow in this composition, carriers mainly flow in the component having a narrow gap. Furthermore, the component having a narrow gap complements the component having a wide gap, and carriers also flow in the component having a wide gap in conjunction with the component having a narrow gap. Therefore, in the case where the above-described CAC-OS or CAC-metal oxide is used in a channel formation region of a transistor, the transistor in the on state can achieve high current drive capability, that is, a high on-state current and high field-effect mobility.

(242) In other words, the CAC-OS or the CAC-metal oxide can also be called a matrix composite or a metal matrix composite.

(243) A CAC-OS refers to one composition of a material in which elements constituting a metal oxide are unevenly distributed with a size greater than or equal to 0.5 nm and less than or equal to 10 nm, preferably greater than or equal to 1 nm and less than or equal to 2 nm, or a similar size, for example. Note that a state in which one or more metal elements are unevenly distributed and regions including the metal element(s) are mixed with a size greater than or equal to 0.5 nm and

less than or equal to 10 nm, preferably greater than or equal to 1 nm and less than or equal to 2 nm, or a similar size in a metal oxide is hereinafter referred to as a mosaic pattern or a patch-like pattern.

(244) Note that the metal oxide preferably contains at least indium. It is particularly preferable that the metal oxide contain indium and zinc. In addition to them, one kind or a plurality of kinds selected from aluminum, gallium, yttrium, copper, vanadium, beryllium, boron, silicon, titanium, iron, nickel, germanium, zirconium, molybdenum, lanthanum, cerium, neodymium, hafnium, tantalum, tungsten, magnesium, and the like may be contained.

(245) For instance, a CAC-OS in an In—Ga—Zn oxide (an In—Ga—Zn oxide in the CAC-OS may be particularly referred to as CAC-IGZO) has a composition in which materials are separated into indium oxide (hereinafter, InO.sub.X1 ($X1$ is a real number greater than 0)) or indium zinc oxide (hereinafter, $\text{In.sub.X2Zn.sub.Y2O.sub.Z2}$ ($X2$, $Y2$, and $Z2$ are real numbers greater than 0)) and gallium oxide (hereinafter, GaO.sub.X3 ($X3$ is a real number greater than 0)) or gallium zinc oxide (hereinafter, $\text{Ga.sub.X4Zn.sub.Y4O.sub.Z4}$ ($X4$, $Y4$, and $Z4$ are real numbers greater than 0)), for example, so that a mosaic pattern is formed, and mosaic-like InO.sub.X1 or $\text{In.sub.X2Zn.sub.Y2O.sub.Z2}$ is evenly distributed in the film (which is hereinafter also referred to as cloud-like).

(246) That is, the CAC-OS is a composite metal oxide having a composition in which a region including GaO.sub.X3 as a main component and a region including $\text{In.sub.X2Zn.sub.Y2O.sub.Z2}$ or InO.sub.X1 as a main component are mixed. Note that in this specification, for example, when the atomic ratio of In to an element M in a first region is larger than the atomic ratio of In to the element M in a second region, the first region is regarded as having a higher In concentration than the second region.

(247) Note that IGZO is a commonly known name and sometimes refers to one compound formed of In, Ga, Zn, and O. A typical example is a crystalline compound represented by $\text{InGaO.sub.3(ZnO).sub.m1}$ ($m1$ is a natural number) or $\text{In.sub.(1+x0)Ga.sub.(1-x0)O.sub.3(ZnO).sub.m0}$ ($-1 \leq x0 \leq 1$; $m0$ is a given number).

(248) The above crystalline compound has a single crystal structure, a polycrystalline structure, or a CAAC (c-axis aligned crystal) structure. Note that the CAAC structure is a crystal structure in which a plurality of IGZO nanocrystals have c-axis alignment and are connected in the a-b plane direction without alignment.

(249) On the other hand, the CAC-OS relates to the material composition of a metal oxide. The CAC-OS refers to a composition in which, in the material composition containing In, Ga, Zn, and O, some regions that include Ga as a main component and are observed as nanoparticles and some regions that include In as a main component and are observed as nanoparticles are randomly dispersed in a mosaic pattern. Therefore, the crystal structure is a secondary element for the CAC-OS.

(250) Note that the CAC-OS is regarded as not including a stacked-layer structure of two or more kinds of films with different compositions. For example, a two-layer structure of a film including In as a main component and a film including Ga as a main component is not included.

(251) Note that a clear boundary cannot sometimes be observed between the region including GaO.sub.X3 as a main component and the region including $\text{In.sub.X2Zn.sub.Y2O.sub.Z2}$ or InO.sub.X1 as a main component.

(252) Note that in the case where one kind or a plurality of kinds selected from aluminum, yttrium, copper, vanadium, beryllium, boron, silicon, titanium, iron, nickel, germanium, zirconium, molybdenum, lanthanum, cerium, neodymium, hafnium, tantalum, tungsten, magnesium, and the like are contained instead of gallium, the CAC-OS refers to a composition in which some regions that include the metal element(s) as a main component and are observed as nanoparticles and some regions that include In as a main component and are observed as nanoparticles are randomly dispersed in a mosaic pattern.

(253) The CAC-OS can be formed by a sputtering method under a condition where a substrate is not heated intentionally, for example. Moreover, in the case of forming the CAC-OS by a sputtering method, any one or more selected from an inert gas (typically, argon), an oxygen gas, and a nitrogen gas are used as a film formation gas. Furthermore, the ratio of the flow rate of an oxygen gas to the total flow rate of the film formation gas at the time of film formation is preferably as low as possible, and for example, the ratio of the flow rate of the oxygen gas is preferably higher than or equal to 0% and lower than 30%, further preferably higher than or equal to 0% and lower than or equal to 10%.

(254) The CAC-OS is characterized in that no clear peak is observed in measurement using $\theta/2\theta$ scan by an Out-of-plane method, which is one of X-ray diffraction (XRD) measurement methods. That is, it is found from the X-ray diffraction measurement that no alignment in the a-b plane direction and the c-axis direction is observed in a measured region.

(255) In addition, in an electron diffraction pattern of the CAC-OS which is obtained by irradiation with an electron beam with a probe diameter of 1 nm (also referred to as a nanobeam electron beam), a ring-like high-luminance region and a plurality of bright spots in the ring region are observed. It is therefore found from the electron diffraction pattern that the crystal structure of the CAC-OS includes an nc (nano-crystal) structure with no alignment in the plan-view direction and the cross-sectional direction.

(256) Moreover, for example, it can be checked by EDX mapping obtained using energy dispersive X-ray spectroscopy (EDX) that the CAC-OS in the In—Ga—Zn oxide has a composition in which regions including GaO.sub.X3 as a main component and regions including In.sub.X2Zn.sub.Y2O.sub.Z2 or InO.sub.X1 as a main component are unevenly distributed and mixed.

(257) The CAC-OS has a composition different from that of an IGZO compound in which the metal elements are evenly distributed, and has characteristics different from those of the IGZO compound. That is, the CAC-OS has a composition in which regions including GaO.sub.X3 or the like as a main component and regions including In.sub.X2Zn.sub.Y2O.sub.Z2 or InO.sub.X1 as a main component are phase-separated from each other and form a mosaic pattern.

(258) Here, a region including In.sub.X2Zn.sub.Y2O.sub.Z2 or InO.sub.X1 as a main component is a region whose conductivity is higher than that of a region including GaO.sub.X3 or the like as a main component. In other words, when carriers flow through the regions including In.sub.X2Zn.sub.Y2O.sub.Z2 or InO.sub.X1 as a main component, the conductivity of an oxide semiconductor is exhibited. Accordingly, when the regions including In.sub.X2Zn.sub.Y2O.sub.Z2 or InO.sub.X1 as a main component are distributed in an oxide semiconductor like a cloud, high field-effect mobility (μ) can be achieved.

(259) By contrast, a region including GaO.sub.X3 or the like as a main component is a region whose insulating property is higher than that of a region including In.sub.X2Zn.sub.Y2O.sub.Z2 or InO.sub.X1 as a main component. In other words, when regions including GaO.sub.X3 or the like as a main component are distributed in an oxide semiconductor, leakage current can be suppressed and favorable switching operation can be achieved.

(260) Accordingly, when the CAC-OS is used for a semiconductor element, the insulating property derived from GaO.sub.X3 or the like and the conductivity derived from In.sub.X2Zn.sub.Y2O.sub.Z2 or InO.sub.X1 complement each other, whereby a high on-state current ($I_{\text{sub.on}}$) and high field-effect mobility (μ) can be achieved.

(261) Moreover, a semiconductor element using the CAC-OS has high reliability. Thus, the CAC-OS is most suitable for a variety of semiconductor devices such as display panels.

(262) This embodiment can be combined with other embodiments as appropriate.

Embodiment 4

(263) In this embodiment, the structure of the display panel of one embodiment of the present invention will be described with reference to FIG. 5 and FIG. 9.

(264) FIG. 9 is a diagram showing the structure of the display panel of one embodiment of the present invention.

(265) <Structure Example 6 of Display Panel>

(266) The display panel **700** described in this embodiment includes the display region **231** (see FIG. 9).

(267) <<Structure Example 5 of Display Region **231**>>

(268) The display region **231** includes the group of pixels **702**(*i*, **1**) to **702**(*i*, *n*), the different group of pixels **702**(**1**, *j*) to **702**(*m*, *j*), the scan line **G2**(*i*), and the signal line **S2**(*j*) (see FIG. 9). Note that *i* is an integer greater than or equal to 1 and less than or equal to *m*, *j* is an integer greater than or equal to 1 and less than or equal to *n*, and *m* and *n* are each an integer greater than or equal to 1.

(269) The display region **231** includes a conductive film **VCOM2** and a conductive film **ANO**, which are not illustrated.

(270) The group of pixels **702**(*i*, **1**) to **702**(*i*, *n*) include the pixel **702**(*i*, *j*), and the group of pixels **702**(*i*, **1**) to **702**(*i*, *n*) are provided in the row direction (the direction indicated by an arrow **R1** in the drawing).

(271) The different group of pixels **702**(**1**, *j*) to **702**(*m*, *j*) include the pixel **702**(*i*, *j*), and the different group of pixels **702**(**1**, *j*) to **702**(*m*, *j*) are provided in the column direction (the direction indicated by an arrow **C1** in the drawing) that intersects the row direction.

(272) The scan line **G2**(*i*) is electrically connected to the group of pixels **702**(*i*, **1**) to **702**(*i*, *n*) provided in the row direction.

(273) The signal line **S2**(*j*) is electrically connected to the different group of pixels **702**(**1**, *j*) to **702**(*m*, *j*) provided in the column direction.

(274) Thus, image data can be supplied to a plurality of pixels. As a result, a novel display panel that is highly convenient or reliable can be provided.

(275) The display region **231** includes 600 or more pixels per inch.

(276) Thus, the aperture ratio can be increased with the pixel resolution maintained. Alternatively, the pixel resolution can be increased with the aperture ratio maintained. As a result, a novel display panel that is highly convenient or reliable can be provided.

(277) <<Structure Example 6 of Display Region **231**>>

(278) The display region **231** includes 7600 or more pixels in the row direction, and the display region **231** includes 4300 or more pixels in the column direction. For example, 7680 pixels are provided in the row direction and 4320 pixels are provided in the column direction.

(279) <Structure Example 7 of Display Panel>

(280) The display region **231** includes the pixel **702**(*i*, *j*), the pixel **702**(*i*, *j*+1), and the pixel **702**(*i*, *j*+2) (see FIG. 5(C)).

(281) The pixel **702**(*i*, *j*) represents a color that has a chromaticity *x* of greater than 0.680 and less than or equal to 0.720 and a chromaticity *y* of greater than or equal to 0.260 and less than or equal to 0.320 in the CIE 1931 chromaticity coordinates.

(282) The pixel **702**(*i*, *j*+1) represents a color that has a chromaticity *x* of greater than or equal to 0.130 and less than or equal to 0.250 and a chromaticity *y* of greater than 0.710 and less than or equal to 0.810 in the CIE 1931 chromaticity coordinates.

(283) The pixel **702**(*i*, *j*+2) represents a color that has a chromaticity *x* of greater than or equal to 0.120 and less than or equal to 0.170 and a chromaticity *y* of greater than or equal to 0.020 and less than 0.060 in the CIE 1931 chromaticity coordinates.

(284) The pixel **702**(*i*, *j*), the pixel **702**(*i*, *j*+1), and the pixel **702**(*i*, *j*+2) are provided such that the area ratio of their color gamut to the BT.2020 color gamut in the CIE chromaticity diagram (*x*, *y*) is higher than or equal to 80%, or the color gamut coverage is higher than or equal to 75%.

Preferably, they are provided such that the area ratio is higher than or equal to 90%, or the coverage is higher than or equal to 85%.

(285) <Structure Example 8 of Display Panel>

(286) The display panel **700** described in this embodiment can include a plurality of driver circuits. For example, a driver circuit GDA, a driver circuit GDB, or a driver circuit SD can be included (see FIG. **9**).

(287) <<Driver Circuit GDA and Driver Circuit GDB>>

(288) The driver circuit GDA and the driver circuit GDB each have a function of supplying a selection signal on the basis of control data.

(289) For example, the driver circuit GDA and the driver circuit GDB each have a function of supplying a selection signal to one scan line at a frequency of 30 Hz or higher, preferably 60 Hz or higher, on the basis of the control data. Accordingly, a moving image can be smoothly displayed.

(290) For example, the driver circuit GDA and the driver circuit GDB each have a function of supplying a selection signal to one scan line at a frequency lower than 30 Hz, preferably lower than 1 Hz, further preferably less than once a minute, on the basis of the control data. Accordingly, a still image can be displayed while flickering is suppressed.

(291) In the case where a plurality of driver circuits are provided, for example, the frequency at which the driver circuit GDA supplies a selection signal and the frequency at which the driver circuit GDB supplies a selection signal can be made different from each other. Specifically, the selection signal can be supplied at a higher frequency to a region on which a moving image is displayed than to a region on which a still image is displayed. Accordingly, a still image can be displayed on a region with reduced flickering, and a moving image can be smoothly displayed on another region.

(292) Alternatively, display can be performed at a frame frequency of 120 Hz by a progressive method. Alternatively, extremely high-resolution display satisfying Recommendation ITU-R BT.2020-2, which is an international standard, can be performed. Alternatively, extremely high-resolution display can be performed.

(293) <<Driver Circuit SD(**1**)>>

(294) A driver circuit SD(**1**) has a function of supplying an image signal on the basis of the data **V11** (see FIG. **9**).

(295) The driver circuit SD(**1**) has a function of generating an image signal and a function of supplying the image signal to a pixel circuit electrically connected to a display element.

(296) A variety of sequential circuits such as a shift register, or the like can be used as the driver circuit SD(**1**), for example.

(297) For example, an integrated circuit formed on a silicon substrate can be used as the driver circuit SD(**1**).

(298) An integrated circuit can be mounted on a terminal by a COG (Chip on glass) method or a COF (Chip on Film) method, for example. Specifically, an anisotropic conductive film can be used to mount an integrated circuit on a terminal.

(299) Note that this embodiment can be combined with other embodiments in this specification as appropriate.

Embodiment 5

(300) In this embodiment, a structure of a display device of one embodiment of the present invention will be described with reference to FIG. **10**.

(301) FIG. **10** is a block diagram showing the structure of the display device of one embodiment of the present invention.

(302) <Structure Example of Display Device>

(303) The display device described in this embodiment includes the control portion **238** and the display panel **700** (see FIG. **10**).

(304) <<Structure Example of Control Portion **238**>>

(305) The control portion **238** is supplied with the image data **V1** and the control data **CI**. For example, a clock signal, a timing signal, or the like can be used as the control data **CI**.

(306) The control portion **238** generates the data **V11** on the basis of the image data **V1** and

generates the control signal SP on the basis of the control data CI. The control portion **238** supplies the data V**11** and the control signal SP. The data V**11** includes a grayscale of 8 bits or more, preferably 12 bits or more, for example.

(307) Specifically, the control portion **238** includes a control circuit **233**, a decompression circuit **234**, and an image processing circuit **235**.

(308) <<Control Circuit **233**>>

(309) The control circuit **233** has a function of generating and supplying the control signal SP.

(310) The control circuit **233** has a function of supplying the control signal SP. For example, a clock signal, a timing signal, or the like can be used as the control signal SP. Specifically, a start pulse for starting operation of the driver circuit GDA(**1**), the driver circuit SDA(**1**), or the like can be used as the control signal SP. Thus, operations of a plurality of driver circuits can be synchronized with each other.

(311) A timing controller can be used as the control circuit **233**, for example.

(312) Note that the control circuit **233** can be included in the display panel. For example, the control circuit **233** mounted on a rigid substrate can be used for the display panel. The control circuit **233** mounted on the rigid substrate can be electrically connected to the driver circuit with the use of a flexible printed circuit.

(313) Specifically, the control circuit **233** can be electrically connected to the driver circuit GDA(**1**), a driver circuit GDB(**1**), a driver circuit GDA(**2**), and a driver circuit GDB(**2**). In addition, the control circuit **233** can be electrically connected to the driver circuit SDA(**1**), a driver circuit SDB(**1**), a driver circuit SDC(**1**), a driver circuit SDA(**2**), a driver circuit SDB(**2**), and a driver circuit SDC(**2**).

(314) <<Decompression Circuit **234**>>

(315) The decompression circuit **234** has a function of decompressing the image data V**1** supplied in a compressed state. The decompression circuit **234** includes a memory portion. The memory portion has a function of storing decompressed image data, for example.

(316) <<Image Processing Circuit **235**>>

(317) The image processing circuit **235** includes a memory region, for example. The memory region has a function of storing data included in the image data V**1**, for example.

(318) The image processing circuit **235** has a function of generating the data V**11** by correcting the image data V**1** on the basis of a predetermined characteristic curve and a function of supplying the data V**11**, for example.

(319) <<Structure Example of Display Panel>>

(320) The display panel **700** is supplied with the data V**11** or the control signal SP. The driver circuit operates on the basis of the control signal SP, and the pixel **702**(*i*, *j*) performs display on the basis of the data V**11**.

(321) For example, the display panel described in Embodiment 1 to Embodiment 4 can be used.

(322) For example, the driver circuit GDA(**1**), the driver circuit GDB(**1**), the driver circuit GDA(**2**), and the driver circuit GDB(**2**) each have a function of supplying a selection signal on the basis of the control signal SP.

(323) For example, each of the driver circuit SDA(**1**), the driver circuit SDB(**1**), the driver circuit SDC(**1**), the driver circuit SDA(**2**), the driver circuit SDB(**2**), and the driver circuit SDC(**2**) is supplied with the control signal SP and supplies the data V**11**.

(324) Thus, the image data can be displayed using the display element. As a result, a novel display device that is highly convenient or reliable can be provided.

(325) Note that this embodiment can be combined with other embodiments in this specification as appropriate.

Embodiment 6

(326) In this embodiment, a structure of an input/output device of one embodiment of the present invention will be described with reference to FIG. **11**.

(327) FIG. 11 is a block diagram showing the structure of the input/output device of one embodiment of the present invention.

(328) <Structure Example of Input/Output Device>

(329) The input/output device described in this embodiment includes the input portion **240** and the display portion **230** (see FIG. 11).

(330) <<Display Portion **230**>>

(331) For example, the display panel **700** described in Embodiment 1 or Embodiment 2 can be used for the display portion **230**. Note that a structure including the input portion **240** and the display portion **230** can be referred to as an input/output panel **700TP**.

(332) <<Structure Example 1 of Input Portion **240**>>

(333) The input portion **240** includes the sensing region **241**. The input portion **240** has a function of sensing an object approaching the sensing region **241**.

(334) The sensing region **241** includes a region overlapping with the pixel **702(i, j)**.

(335) Thus, the object approaching the region overlapping with the display portion can be sensed while image data is displayed by the display portion. Alternatively, a finger or the like that approaches the display portion can be used as a pointer to input positional data. Alternatively, positional data can be associated with image data displayed on the display portion. As a result, a novel input/output device that is highly convenient or reliable can be provided.

(336) <<Structure Example 2 of Input Portion **240**>>

(337) The input portion **240** can include an oscillation circuit OSC and a sensing circuit DC (see FIG. 11).

(338) <<Sensing Region **241**>>

(339) The sensing region **241** includes one or more sensing elements, for example.

(340) The sensing region **241** includes a group of sensing elements **775(g, 1)** to **775(g, q)** and a different group of sensing elements **775(1, h)** to **775(p, h)**. Note that g is an integer greater than or equal to 1 and less than or equal to p , h is an integer greater than or equal to 1 and less than or equal to q , and p and q are each an integer greater than or equal to 1.

(341) The group of sensing elements **775(g, 1)** to **775(g, q)** include a sensing element **775(g, h)** and are provided in the row direction (the direction indicated by an arrow R2 in the drawing). Note that the direction indicated by the arrow R2 may be the same as or different from the direction indicated by the arrow R1.

(342) The different group of sensing elements **775(1, h)** to **775(p, h)** include the sensing element **775(g, h)** and are provided in the column direction (the direction indicated by an arrow C2 in the drawing) that intersects the row direction.

(343) <<Sensing Element>>

(344) The sensing element has a function of sensing an approaching pointer. For example, a finger, a stylus pen, or the like can be used as the pointer. For example, a piece of metal, a coil, or the like can be used for the stylus pen.

(345) Specifically, a capacitive proximity sensor, an electromagnetic inductive proximity sensor, an optical proximity sensor, a resistive proximity sensor, or the like can be used as the sensing element.

(346) A plurality of types of sensing elements can be used in combination. For example, a sensing element that senses a finger and a sensing element that senses a stylus pen can be used in combination.

(347) This allows determination of the kind of a pointer. Alternatively, different instructions can be associated with pieces of sensing data depending on the kind of a pointer that has been determined. Specifically, in the case where it is determined that a finger is used as a pointer, sensing data can be associated with a gesture. Alternatively, in the case where it is determined that a stylus pen is used as a pointer, sensing data can be associated with drawing processing.

(348) Specifically, a capacitive proximity sensor or an optical proximity sensor can be used to

sense a finger. Alternatively, an electromagnetic inductive proximity sensor or an optical proximity sensor can be used to sense a stylus pen.

(349) Note that this embodiment can be combined with other embodiments in this specification as appropriate.

Embodiment 7

(350) In this embodiment, a structure of a data processing device of one embodiment of the present invention will be described with reference to FIG. 12 to FIG. 15.

(351) FIG. 12(A) is a block diagram showing the structure of the data processing device of one embodiment of the present invention. FIG. 12(B) is a projection view showing an example of an external view of the data processing device.

(352) FIG. 13 is a flow chart showing a program of one embodiment of the present invention. FIG. 13(A) is a flow chart showing main processing of the program of one embodiment of the present invention, and FIG. 13(B) is a flow chart showing interrupt processing.

(353) FIG. 14 shows the program of one embodiment of the present invention. FIG. 14(A) is a flow chart showing interrupt processing of the program of one embodiment of the present invention. FIG. 14(B) is a schematic view showing operation of the data processing device, and FIG. 14(C) is a timing chart showing operation of the data processing device of one embodiment of the present invention.

(354) FIG. 15 shows an artificial intelligence portion of one embodiment of the present invention. FIG. 15(A) is a block diagram showing the artificial intelligence portion of one embodiment of the present invention. FIG. 15(B) is a block diagram showing a neural network of one embodiment of the present invention. FIG. 15(C) is a block diagram showing a neuron circuit of one embodiment of the present invention.

(355) <Structure Example 1 of Data Processing Device>

(356) A data processing device **200** described in this embodiment includes the arithmetic device **210** and the input/output device **220** (see FIG. 12(A)). Note that the input/output device **220** is electrically connected to the arithmetic device **210**. The data processing device **200** can also include a housing (see FIG. 12(B)).

(357) <<Structure Example 1 of Arithmetic Device **210**>>

(358) The arithmetic device **210** is supplied with the input data **II** or the sensing data **DS**. The arithmetic device **210** supplies the control data **CI** and the image data **V1**.

(359) The arithmetic device **210** includes an arithmetic portion **211** and a memory portion **212**. The arithmetic portion **211** includes a transmission path **214** and an input/output interface **215**.

(360) The transmission path **214** is electrically connected to the arithmetic portion **211**, the memory portion **212**, and the input/output interface **215**.

(361) <<Arithmetic Portion **211**>>

(362) The arithmetic portion **211** has a function of executing a program, for example.

(363) <<Memory Portion **212**>>

(364) The memory portion **212** has a function of storing, for example, the program executed by the arithmetic portion **211**, initial data, setting data, an image, or the like.

(365) Specifically, a hard disk, a flash memory, a memory using a transistor including an oxide semiconductor, or the like can be used.

(366) <<Input/Output Interface **215** and Transmission Path **214**>>

(367) The input/output interface **215** includes a terminal or a wiring and has a function of supplying data and being supplied with data. The input/output interface **215** can be electrically connected to the transmission path **214**, for example. The input/output interface **215** can also be electrically connected to the input/output device **220**.

(368) The transmission path **214** includes a wiring and has a function of supplying data and being supplied with data. The transmission path **214** can be electrically connected to the input/output interface **215**, for example. The transmission path **214** can also be electrically connected to the

arithmetic portion **211**, the memory portion **212**, or the input/output interface **215**.

(369) <<Structure Example of Input/Output Device **220**>>

(370) The input/output device **220** supplies the input data **II** and the sensing data **DS**. The input/output device **220** is supplied with the control data **CI** and the image data **V1** (see FIG. **12(A)**).

(371) As the input data **II**, for example, a scan code of a keyboard, positional data, operation data of buttons, sound data, image data, or the like can be used. Alternatively, for example, illuminance data, attitude data, acceleration data, bearing data, pressure data, temperature data, humidity data, or the like of an environment where the data processing device **200** is used, or the like can be used as the sensing data **DS**.

(372) As the control data **CI**, for example, a signal controlling the luminance of display of the image data **V1**, a signal controlling the chroma of display of the image data **V1**, or a signal controlling the hue of display of the image data **V1** can be used. Alternatively, a signal that changes display of part of the image data **V1** can be used as the control data **CI**.

(373) The input/output device **220** includes the display portion **230**, the input portion **240**, and the sensing portion **250**. For example, the input/output device described in Embodiment 6 can be used.

(374) The display portion **230** displays the image data **V1** on the basis of the control data **CI**.

(375) The input portion **240** generates the input data **II**.

(376) The sensing portion **250** generates the sensing data **DS**.

(377) <<Display Portion **230**>>

(378) The display portion **230** has a function of displaying an image on the basis of the image data **V1**. The display portion **230** has a function of displaying an image on the basis of the control data **CI**.

(379) The display portion **230** includes the control portion **238**, the driver circuit **GDA(1)**, the driver circuit **SDA(1)**, and the display panel **700** (see FIG. **10**). For example, the display device described in Embodiment 5 can be used for the display portion **230**.

(380) <<Input Portion **240**>>

(381) The input portion **240** has a function of supplying positional data. A variety of human interfaces or the like can be used for the input portion **240** (see FIG. **12(A)**).

(382) For example, a keyboard, a hardware button, a pointing device, a touch sensor, an imaging device, an audio input device, an eye-gaze input device, an attitude sensing device, a microphone, a camera, or the like can be used for the input portion **240**. Note that a touch sensor including a region overlapping with the display portion **230** can be used. An input/output device including the display portion **230** and a touch sensor including a region overlapping with the display portion **230** can be referred to as a touch panel or a touch screen.

(383) A user can make various gestures (tap, drag, swipe, pinch in, and the like) using his/her finger touching the touch panel as a pointer, for example.

(384) The arithmetic device **210**, for example, analyzes data on the position, path, or the like of the finger in contact with the touch panel and can determine that a specific gesture is supplied when the analysis results meet predetermined conditions. Thus, the user can supply a predetermined operation instruction associated with the predetermined gesture in advance by using the gesture.

(385) For instance, the user can supply a “scroll instruction” for changing the display position of image data by using a gesture of moving the finger in contact with the touch panel along the touch panel.

(386) <<Sensing Portion **250**>>

(387) The sensing portion **250** has a function of supplying the sensing data **DS**. The sensing portion **250** has a function of sensing the illuminance of the usage environment of the data processing device **200** and a function of supplying illuminance data, for example.

(388) The sensing portion **250** has a function of sensing the ambient conditions and supplying the sensing data. Specifically, the sensing portion **250** can supply illuminance data, attitude data,

acceleration data, bearing data, pressure data, temperature data, humidity data, or the like.

(389) For example, a photosensor, an illuminance sensor, an attitude sensor, an acceleration sensor, a direction sensor, a GPS (Global positioning System) signal receiving circuit, a pressure sensor, a temperature sensor, a humidity sensor, a camera, or the like can be used as the sensing portion **250**.

(390) <<Communication Portion **290**>>

(391) A communication portion **290** has a function of supplying data to a network and obtaining data from the network.

(392) <<Housing>>

(393) Note that the housing has a function of storing the input/output device **220** or the arithmetic device **210**. Alternatively, the housing has a function of supporting the display portion **230** or the arithmetic device **210**.

(394) Thus, the data processing device can determine the intensity of light received by the housing of the data processing device and operate under the usage environment of the data processing device. Alternatively, a user of the data processing device can select a display method. As a result, a novel data processing device that is highly convenient or reliable can be provided.

(395) Note that in some cases, these components cannot be clearly distinguished from each other and one component may also serve as another component or include part of another component. For example, a touch panel in which a touch sensor overlaps with a display panel is an input portion as well as a display portion.

(396) <<Structure Example 2 of Arithmetic Device **210**>>

(397) The arithmetic device **210** includes an artificial intelligence portion **213** (see FIG. 12(A)).

(398) <<Structure Example 1 of Artificial Intelligence Portion **213**>>

(399) The artificial intelligence portion **213** generates the control data CI on the basis of the input data II or the sensing data DS (see FIG. 15(A)).

(400) The artificial intelligence portion **213** includes a semiconductor device **90**.

(401) [Natural Language Processing on Input Data II]

(402) Specifically, the artificial intelligence portion **213** can perform natural language processing on the input data II to extract one feature from the whole input data II. For example, the artificial intelligence portion **213** can infer emotion or the like put in the input data II, which can be a feature. The artificial intelligence portion **213** can infer the color, design, font, or the like empirically felt suitable for the feature. The artificial intelligence portion **213** can generate data specifying the color, design, or font of a letter or data specifying the color or design of the background, and the data can be used as the control data CI.

(403) Specifically, the artificial intelligence portion **213** can perform natural language processing on the input data II to extract some words included in the input data II. For example, the artificial intelligence portion **213** can extract expressions including a grammatical error, a factual error, emotion, and the like. The artificial intelligence portion **213** can generate the control data CI for display of extracted part in the color, design, font, or the like different from those of another part, and the data can be used as the control data CI.

(404) [Image Processing on Input Data II]

(405) Specifically, the artificial intelligence portion **213** can perform image processing on the input data II to extract one feature from the input data II. For example, the artificial intelligence portion **213** can infer the age where an image of the input data II is taken, whether the image of the input data II is taken indoors or outdoors, whether the image of the input data II is taken in the daytime or at night, or the like, which can be a feature. The artificial intelligence portion **213** can infer the color tone empirically felt suitable for the feature and generate the control data CI for use of the color tone for display. Specifically, data specifying color (e.g., full color, monochrome, or sepia) used for expression of a gradation can be used as the control data CI.

(406) Specifically, the artificial intelligence portion **213** can perform image processing on the input data II to extract some images included in the input data II. For example, the artificial intelligence

portion **213** can generate the control data CI for display of a boundary between extracted part of the image and another part. Specifically, the artificial intelligence portion **213** can generate the control data CI for display of a rectangle surrounding the extracted part of the image.

(407) [Inference Using Sensing Data DS]

(408) Specifically, the artificial intelligence portion **213** can generate an inference RI with the use of the sensing data DS as data IN. Alternatively, the artificial intelligence portion **213** can generate the control data CI on the basis of the inference RI so that the user of the data processing device **200** can feel comfortable.

(409) Specifically, the artificial intelligence portion **213** can generate the control data CI for adjustment of display brightness on the basis of the ambient illuminance or the like so that the display brightness can be felt comfortable. Alternatively, the artificial intelligence portion **213** can generate the control data CI for adjustment of volume on the basis of the ambient noise or the like so that the volume can be felt comfortable.

(410) As the control data CI, a clock signal, a timing signal, or the like that is supplied to the control portion **238** included in the display portion **230** can be used. Alternatively, a clock signal, a timing signal, or the like that is supplied to a control portion included in the input portion **240** can be used as the control data CI.

(411) <<Semiconductor Device **90**>>

(412) The semiconductor device **90** supplies the control data CI on the basis of the input data II or the sensing data DS.

(413) The semiconductor device **90** is supplied with the data IN and supplies the inference RI (see FIG. **15(A)** and FIG. **15(B)**). For example, the input data II or the sensing data DS can be used as the data IN. Alternatively, for example, the inference RI can be used as the control data CI.

(414) For example, the semiconductor device **90** can extract a feature from the input data II or the sensing data DS. The semiconductor device **90** can generate the control data CI on the basis of the extracted feature.

(415) For example, the semiconductor device **90** can extract part of the input data II or the sensing data DS. The semiconductor device **90** can generate the control data CI such that the extracted part is displayed to be different from another part.

(416) In this manner, the control data for display that can be felt suitable can be generated. Alternatively, display that can be felt suitable is possible. Alternatively, the control data for display that can be felt comfortable can be generated. Alternatively, display that can be felt comfortable is possible. As a result, a novel data processing device that is highly convenient or reliable can be provided.

(417) <<Structure Example 2 of Semiconductor Device **90**>>

(418) The semiconductor device **90** includes a neural network **80** (see FIG. **15(A)**).

(419) <<Neural Network **80**>>

(420) The neural network **80** includes an input layer **81**, an intermediate layer **82**, and an output layer **83** (see FIG. **15(B)**). For example, a convolutional neural network can be used as the neural network **80**. Alternatively, a recurrent neural network can be used as the neural network **80**.

(421) The input layer **81** includes a first group of neuron circuits.

(422) The intermediate layer **82** includes a second group of neuron circuits.

(423) The output layer **83** includes a third group of neuron circuits.

(424) The second group of neuron circuits include a first neuron circuit **71** and a second neuron circuit **72**.

(425) The first neuron circuit **71** is electrically connected to the first group of neuron circuits.

(426) The second neuron circuit **72** is electrically connected to the third group of neuron circuits.

(427) The first group of neuron circuits are supplied with the data IN. For example, the input data II or the sensing data DS can be used as the data IN.

(428) The third group of neuron circuits supply the inference RI. For example, the inference RI can

be used as the control data CI.

(429) <<Neuron Circuit **71**>>

(430) The neuron circuit **71** includes a product-sum operation unit **10** and a converter **30** (see FIG. **15(C)**).

(431) <<Product-Sum Operation Unit **10**>>

(432) The product-sum operation unit **10** is supplied with a group of input signals X[**1**] to X[N]. The product-sum operation unit **10** is supplied with a group of weight data W[**1**] to W[N]. The product-sum operation unit **10** is also supplied with a bias signal B.

(433) By the product-sum operation unit **10**, a product-sum signal u is generated on the basis of the bias signal B and the product-sum value of the group of input signals X[**1**] to X[N] and the group of weight data W[**1**] to W[N] and supplied. For example, a memory using a transistor including an oxide semiconductor, or the like can be used as a memory for storing the weight data W[**1**] to the weight data W[N]. Specifically, a transistor that includes an oxide semiconductor containing indium or an oxide semiconductor containing indium, gallium, and zinc can be used for the memory. An analog arithmetic circuit can be used for the product-sum operation unit **10**, for example. In this manner, the circuit scale can be small as compared with that of a digital arithmetic circuit. Alternatively, the power consumption can be reduced.

(434) <<Converter **30**>>

(435) The converter **30** is electrically connected to the product-sum operation unit **10**. By the converter **30**, an output signal f(u) is generated on the basis of the product-sum signal u and supplied.

(436) <Structure Example 3 of Data Processing Device>

(437) Another structure of the data processing device of one embodiment of the present invention is described with reference to FIG. **13(A)** and FIG. **13(B)**.

(438) <<Program>>

(439) The program of one embodiment of the present invention has the following steps (see FIG. **13(A)**).

(440) [First Step]

(441) In a first step, setting is initialized (see (S1) in FIG. **13(A)**).

(442) For example, predetermined image data which is to be displayed on start-up and data for determining a predetermined mode of displaying the image data and a predetermined display method for displaying the image data are acquired from the memory portion **212**. Specifically, one still image data or another moving image data can be used as the predetermined image data. Furthermore, a first mode or a second mode can be used as the predetermined mode.

(443) [Second Step]

(444) In a second step, interrupt processing is allowed (see (S2) in FIG. **13(A)**). Note that an arithmetic device allowed to execute the interrupt processing can perform the interrupt processing in parallel with the main processing. The arithmetic device that has returned from the interrupt processing to the main processing can reflect the results obtained through the interrupt processing in the main processing.

(445) The arithmetic device may execute the interrupt processing when a counter has an initial value, and the counter may be set at a value other than the initial value when the arithmetic device returns from the interrupt processing. Thus, the interrupt processing can always follow the start-up of the program.

(446) [Third Step]

(447) In a third step, image data is displayed by a predetermined mode or a predetermined display method selected in the first step or the interrupt processing (see (S3) in FIG. **13(A)**). Note that the predetermined mode determines a mode of displaying the data, and the predetermined display method determines a method for displaying the image data. For example, the image data V1 can be used as data to be displayed.

(448) One method for displaying the image data **V1** can be associated with the first mode, for example. Alternatively, another method for displaying the image data **V1** can be associated with the second mode. Thus, a display method can be selected on the basis of the selected mode.

(449) <<First Mode>>

(450) Specifically, a method for supplying selection signals to a scan line at a frequency of 30 Hz or higher, preferably 60 Hz or higher, and performing display on the basis of the selection signals can be associated with the first mode.

(451) For example, when selection signals are supplied at a frequency of 30 Hz or higher, preferably 60 Hz or higher, the movement of a moving image can be smoothly displayed.

(452) For example, when an image is refreshed at a frequency of 30 Hz or higher, preferably 60 Hz or higher, an image that changes so as to smoothly follow the user's operation can be displayed on the data processing device **200** which is being operated by the user.

(453) <<Second Mode>>

(454) Specifically, a method for supplying selection signals to a scan line at a frequency lower than 30 Hz, preferably lower than 1 Hz, further preferably less than once a minute, and performing display on the basis of the selection signals can be associated with the second mode.

(455) The supply of selection signals at a frequency lower than 30 Hz, preferably lower than 1 Hz, further preferably less than once a minute enables display with a flicker or flickering suppressed. Furthermore, the power consumption can be reduced.

(456) For example, when the data processing device **200** is used for a clock, the display can be refreshed at a frequency of once a second, once a minute, or the like.

(457) Note that when a light-emitting element is used as the display element, for example, the light-emitting element can be configured to emit light in a pulsed manner so that image data is displayed. Specifically, an organic EL element can be configured to emit light in a pulsed manner, and its afterglow can be used for display. The organic EL element has excellent frequency characteristics; thus, time for driving the light-emitting element can be shortened, and thus the power consumption can be reduced in some cases. Alternatively, heat generation is inhibited; thus, the deterioration of the light-emitting element can be suppressed in some cases.

(458) [Fourth Step]

(459) In a fourth step, selection is performed such that the program proceeds to a fifth step when a termination instruction has been supplied, whereas the program proceeds to the third step when the termination instruction has not been supplied (see (S4) in FIG. 13(A)).

(460) For example, the termination instruction supplied in the interrupt processing may be used for the determination.

(461) [Fifth Step]

(462) In the fifth step, the program terminates (see (S5) in FIG. 13(A)).

(463) <<Interrupt Processing>>

(464) The interrupt processing includes a sixth step to an eighth step described below (see FIG. 13(B)).

(465) [Sixth Step]

(466) In the sixth step, the illuminance of the environment where the data processing device **200** is used is sensed using the sensing portion **250**, for example (see (S6) in FIG. 13(B)). Note that color temperature or chromaticity of ambient light may be sensed instead of the illuminance of the environment.

(467) [Seventh Step]

(468) In the seventh step, a display method is determined on the basis of the sensed illuminance data (see (S7) in FIG. 13(B)). For example, a display method is determined such that the brightness of display is not too dark or too bright.

(469) Note that in the case where the color temperature of the ambient light or the chromaticity of the ambient light is sensed in the sixth step, the color of display may be adjusted.

(470) [Eighth Step]

(471) In the eighth step, the interrupt processing terminates (see (S8) in FIG. 13(B)).

(472) <Structure Example 3 of Data Processing Device>

(473) Another structure of the data processing device of one embodiment of the present invention is described with reference to FIG. 14.

(474) FIG. 14(A) is a flow chart showing a program of one embodiment of the present invention. FIG. 14(A) is a flow chart showing interrupt processing different from the interrupt processing shown in FIG. 13(B).

(475) Note that the structure example 3 of the data processing device is different from the interrupt processing described with reference to FIG. 13(B) in that the interrupt processing includes a step of changing a mode on the basis of a supplied predetermined event. Different portions will be described in detail here, and refer to the above description for portions that can use similar structures.

(476) <<Interrupt Processing>>

(477) The interrupt processing includes a sixth step to an eighth step described below (see FIG. 14(A)).

(478) [Sixth Step]

(479) In the sixth step, the program proceeds to the seventh step when a predetermined event has been supplied, whereas the program proceeds to the eighth step when the predetermined event has not been supplied (see (U6) in FIG. 14(A)). For example, whether the predetermined event is supplied in a predetermined period or not can be used as a condition. Specifically, the predetermined period can be longer than 0 seconds, and shorter than or equal to 5 seconds, shorter than or equal to 1 second, or shorter than or equal to 0.5 seconds, preferably shorter than or equal to 0.1 seconds.

(480) [Seventh Step]

(481) In the seventh step, the mode is changed (see (U7) in FIG. 14(A)). Specifically, the second mode is selected in the case where the first mode has been selected, and the first mode is selected in the case where the second mode has been selected.

(482) For example, it is possible to change the display mode of a region that is part of the display portion 230. Specifically, the display mode of a region where one driver circuit in the display portion 230 including the driver circuit GDA, the driver circuit GDB, and a driver circuit GDC supplies a selection signal can be changed (see FIG. 14(B)).

(483) For example, the display mode of the region where a selection signal is supplied from the driver circuit GDB can be changed when a predetermined event is supplied to the input portion 240 in a region overlapping with the region where a selection signal is supplied from the driver circuit GDB (see FIG. 14(B) and FIG. 14(C)). Specifically, the frequency of supply of the selection signal from the driver circuit GDB can be changed in accordance with a “tap” event supplied to a touch panel with a finger or the like.

(484) A signal GCLK is a clock signal controlling the operation of the driver circuit GDB, and a signal PWC1 and a signal PWC2 are pulse width control signals controlling the operation of the driver circuit GDB. The driver circuit GDB supplies selection signals to a scan line $G2(m+1)$ to a scan line $G2(2m)$ on the basis of the signal GCLK, the signal PWC1, the signal PWC2, and the like.

(485) Thus, for example, the driver circuit GDB can supply a selection signal without supply of selection signals from the driver circuit GDA and the driver circuit GDC. Alternatively, the display of the region where a selection signal is supplied from the driver circuit GDB can be refreshed without any change in the display of regions where selection signals are supplied from the driver circuit GDA and the driver circuit GDC. Alternatively, power consumed by the driver circuits can be reduced.

(486) [Eighth Step]

(487) In the eighth step, the interrupt processing terminates (see (U8) in FIG. 14(A)). Note that in a period in which the main processing is executed, the interrupt processing may be repeatedly executed.

(488) <<Predetermined Event>>

(489) For example, it is possible to use events supplied using a pointing device such as a mouse, such as “click” and “drag”, and events supplied to a touch panel with a finger or the like used as a pointer, such as “tap”, “drag”, and “swipe”.

(490) For example, the position of a slide bar pointed by a pointer, the swipe speed, and the drag speed can be used to assign arguments to an instruction associated with a predetermined event.

(491) For example, data sensed by the sensing portion 250 is compared with a predetermined threshold value, and the compared results can be used for the event.

(492) Specifically, a pressure sensor or the like in contact with a button or the like that can be pushed in a housing can be used for the sensing portion 250.

(493) <<Instruction Associated with Predetermined Event>>

(494) For example, the termination instruction can be associated with a predetermined event.

(495) For example, “page-turning instruction” for switching display from one displayed image data to another image data can be associated with a predetermined event. Note that an argument determining the page-turning speed or the like, which is used when the “page-turning instruction” is executed, can be supplied using the predetermined event.

(496) For example, “scroll instruction” for moving the display position of displayed part of image data and displaying another part continuing from that part, or the like can be associated with a predetermined event. Note that an argument determining the moving speed of display, or the like, which is used when the “scroll instruction” is executed, can be supplied using the predetermined event.

(497) For example, an instruction for setting the display method, an instruction for generating image data, or the like can be associated with a predetermined event. Note that an argument determining the brightness of a generated image can be associated with a predetermined event. An argument determining the brightness of a generated image may be determined on the basis of ambient brightness sensed by the sensing portion 250.

(498) For example, an instruction for acquiring data distributed via a push service using the communication portion 290 or the like can be associated with a predetermined event.

(499) Note that positional data sensed by the sensing portion 250 may be used for the determination of the presence or absence of a qualification for acquiring data. Specifically, it may be determined that there is a qualification for acquiring data in the case of presence in a predetermined class room, school, conference room, company, building, or the like or in a predetermined region. Thus, for example, educational materials distributed in a classroom of a school, a university, or the like can be received, so that the data processing device 200 can be used as a schoolbook or the like (see FIG. 12(B)). Alternatively, materials distributed in a conference room in, for example, a company can be received and used for a conference material.

(500) Note that this embodiment can be combined with other embodiments in this specification as appropriate.

Example

(501) In this example, fabrication results of transistors that can be used in the display panel of one embodiment of the present invention will be described with reference to FIG. 8 and FIG. 16.

(502) FIG. 16 shows the characteristics of the fabricated transistors. The fabricated transistors have the structures similar to the structure of the transistor shown in FIG. 8.

(503) <Fabrication Method>

(504) First, the insulating film 501C was formed, and the conductive film 504 was formed over the insulating film 501C. Next, the insulating film 506 was formed over the conductive film 504, the semiconductor film 508 was formed over the insulating film 506, and the opening portion was

formed in the insulating film **506**. Next, the conductive film **512A** and the conductive film **512B** were formed in contact with the semiconductor film **508**, and the insulating film **516** was formed. A conductive film **512C** was formed in the step of forming the conductive film **512A**. In this manner, the transistor used as the switch SW2 was formed. Note that the channel width W and the channel length of the transistor used as the switch SW2 were 3 μm .

(505) Next, the semiconductor film **508(2)** was formed over the insulating film **516**, and the opening portion was formed in the insulating film **516**. Next, a conductive film **512D** and a conductive film **512E** were formed in contact with the semiconductor film **508(2)**, and an insulating film **516(2)** was formed. In this manner, the transistor M was formed. The channel width W and the channel length of the transistor M were 50 μm and 3 μm , respectively.

(506) Note that an oxide semiconductor film was used as the semiconductor film **508** and the semiconductor film **508(2)**.

(507) <Evaluation>

(508) The characteristics of the fabricated transistor M are shown. Specifically, the drain current-gate voltage (ID-VG) characteristics in the cases where the source-drain voltage (Vds) was set to 0.1 V and 20 V are shown (see FIG. **16(a)**).

(509) The characteristics of the fabricated transistor used as the switch SW2 are shown. Specifically, the drain current-gate voltage (ID-VG) characteristics in the cases where the source-drain voltage (Vds) was set to 0.1 V and 20 V are shown (see FIG. **16(b)**).

(510) Both transistors had favorable characteristics.

(511) In the case where there is an explicit description, X and Y are connected, in this specification and the like, for example, the case where X and Y are electrically connected, the case where X and Y are functionally connected, and the case where X and Y are directly connected are disclosed in this specification and the like. Accordingly, without being limited to a predetermined connection relationship, for example, a connection relationship shown in drawings or texts, a connection relationship other than one shown in drawings or texts is disclosed in the drawings or the texts.

(512) Here, X and Y each denote an object (e.g., a device, an element, a circuit, a wiring, an electrode, a terminal, a conductive film, or a layer).

(513) An example of the case where X and Y are directly connected is the case where an element that allows electrical connection between X and Y (e.g., a switch, a transistor, a capacitor, an inductor, a resistor, a diode, a display element, a light-emitting element, or a load) is not connected between X and Y, and is the case where X and Y are connected without an element that allows electrical connection between X and Y (e.g., a switch, a transistor, a capacitor, an inductor, a resistor, a diode, a display element, a light-emitting element, or a load) placed therebetween.

(514) For example, in the case where X and Y are electrically connected, one or more elements that allow electrical connection between X and Y (e.g., a switch, a transistor, a capacitor, an inductor, a resistor, a diode, a display element, a light-emitting element, or a load) can be connected between X and Y. Note that a switch has a function of being controlled to be turned on or off. That is, a switch has a function of being in a conduction state (on state) or a non-conduction state (off state) to control whether or not current flows. Alternatively, a switch has a function of selecting and changing a current path. Note that the case where X and Y are electrically connected includes the case where X and Y are directly connected.

(515) An example of the case where X and Y are functionally connected is the case where one or more circuits that allow functional connection between X and Y (for example, a logic circuit (an inverter, a NAND circuit, a NOR circuit, or the like), a signal converter circuit (a DA converter circuit, an AD converter circuit, a gamma correction circuit, or the like), a potential level converter circuit (a power supply circuit (a step-up circuit, a step-down circuit, or the like), a level shifter circuit for changing the potential level of a signal, or the like), a voltage source, a current source, a switching circuit, an amplifier circuit (a circuit capable of increasing signal amplitude, the amount of current, or the like, an operational amplifier, a differential amplifier circuit, a source follower

circuit, a buffer circuit, or the like), a signal generator circuit, a memory circuit, a control circuit, or the like) can be connected between X and Y. For example, even when another circuit is interposed between X and Y, X and Y are functionally connected when a signal output from X is transmitted to Y. Note that the case where X and Y are functionally connected includes the case where X and Y are directly connected and the case where X and Y are electrically connected.

(516) Note that in the case where there is an explicit description, X and Y are electrically connected, the case where X and Y are electrically connected (i.e., the case where X and Y are connected with another element or another circuit provided therebetween), the case where X and Y are functionally connected (i.e., the case where X and Y are functionally connected with another circuit provided therebetween), and the case where X and Y are directly connected (i.e., the case where X and Y are connected without another element or another circuit provided therebetween) are disclosed in this specification and the like. That is, in the case where there is an explicit description, being electrically connected, the same contents as the case where there is only an explicit description, being connected, are disclosed in this specification and the like.

(517) For example, any of the following expressions can be used for the case where a source (or a first terminal or the like) of a transistor is electrically connected to X through (or not through) Z1 and a drain (or a second terminal or the like) of the transistor is electrically connected to Y through (or not through) Z2, or the case where a source (or a first terminal or the like) of a transistor is directly connected to one part of Z1 and another part of Z1 is directly connected to X while a drain (or a second terminal or the like) of the transistor is directly connected to one part of Z2 and another part of Z2 is directly connected to Y.

(518) It can be expressed as, for example, “X, Y, a source (or a first terminal or the like) of a transistor, and a drain (or a second terminal or the like) of the transistor are electrically connected to each other, and X, the source (or the first terminal or the like) of the transistor, the drain (or the second terminal or the like) of the transistor, and Y are electrically connected to each other in this order”. Alternatively, the expression “a source (or a first terminal or the like) of a transistor is electrically connected to X, a drain (or a second terminal or the like) of the transistor is electrically connected to Y, and X, the source (or the first terminal or the like) of the transistor, the drain (or the second terminal or the like) of the transistor, and Y are electrically connected to each other in this order” can be used. Alternatively, the expression “X is electrically connected to Y through a source (or a first terminal or the like) and a drain (or a second terminal or the like) of a transistor, and X, the source (or the first terminal or the like) of the transistor, the drain (or the second terminal or the like) of the transistor, and Y are provided in this connection order” can be used. When the connection order in a circuit configuration is defined by an expression similar to the above examples, a source (or a first terminal or the like) and a drain (or a second terminal or the like) of a transistor can be distinguished from each other to specify the technical scope.

(519) Alternatively, as another expression, the expression “a source (or a first terminal or the like) of a transistor is electrically connected to X through at least a first connection path, the first connection path does not include a second connection path, the second connection path is a path through the transistor, between the source (or the first terminal or the like) of the transistor and a drain (or a second terminal or the like) of the transistor, the first connection path is a path through Z1, the drain (or the second terminal or the like) of the transistor is electrically connected to Y through at least a third connection path, the third connection path does not include the second connection path, and the third connection path is a path through Z2” can be used, for example. Alternatively, the expression “a source (or a first terminal or the like) of a transistor is electrically connected to X by at least a first connection path through Z1, the first connection path does not include a second connection path, the second connection path includes a connection path through the transistor, a drain (or a second terminal or the like) of the transistor is electrically connected to Y by at least a third connection path through Z2, and the third connection path does not include the second connection path” can be used. Alternatively, the expression “a source (or a first terminal or

the like) of a transistor is electrically connected to X by at least a first electrical path through Z1, the first electrical path does not include a second electrical path, the second electrical path is an electrical path from the source (or the first terminal or the like) of the transistor to a drain (or a second terminal or the like) of the transistor, the drain (or the second terminal or the like) of the transistor is electrically connected to Y by at least a third electrical path through Z2, the third electrical path does not include a fourth electrical path, and the fourth electrical path is an electrical path from the drain (or the second terminal or the like) of the transistor to the source (or the first terminal or the like) of the transistor” can be used. When the connection path in a circuit configuration is defined by an expression similar to the above examples, a source (or a first terminal or the like) and a drain (or a second terminal or the like) of a transistor can be distinguished from each other to specify the technical scope.

(520) Note that these expressions are examples and there is no limitation on the expressions. Here, X, Y, Z1, and Z2 each denote an object (e.g., a device, an element, a circuit, a wiring, an electrode, a terminal, a conductive film, or a layer).

(521) Even when independent components are electrically connected to each other in a circuit diagram, one component has functions of a plurality of components in some cases. For example, when part of a wiring also functions as an electrode, one conductive film has functions of both components: a function of the wiring and a function of the electrode. Thus, electrical connection in this specification includes, in its category, such a case where one conductive film has functions of a plurality of components.

REFERENCE NUMERALS

(522) ANO: conductive film, B: bias signal, C21: capacitor, CI: control data, DS: sensing data, G2: scan line, GDA: driver circuit, GDB: driver circuit, GDC: driver circuit, GCLK: signal, II: input data, IN: data, P1: portion, P2: boundary, P3: portion, PWC1: signal, PWC2: signal, R1: curvature radius, R2: curvature radius, R3: curvature radius, S2: signal line, SD: driver circuit, SDA: driver circuit, SDB: driver circuit, SDC: driver circuit, SP: control signal, SW2: switch, U: product-sum signal, V1: image data, V11: data, VCOM2: conductive film, W: data, 10: product-sum operation unit, 30: converter, 71: neuron circuit, 72: neuron circuit, 80: neural network, 81: input layer, 82: intermediate layer, 83: output layer, 90: semiconductor device, 200: data processing device, 210: arithmetic device, 211: arithmetic portion, 212: memory portion, 213: artificial intelligence portion, 214: transmission path, 215: input/output interface, 220: input/output device, 230: display portion, 231: display region, 233: control circuit, 234: decompression circuit, 235: image processing circuit, 238: control portion, 240: input portion, 241: sensing region, 248: control portion, 250: sensing portion, 290: communication portion, 400: molecular weight, 501C: insulating film, 504: conductive film, 506: insulating film, 508: semiconductor film, 508A: region, 508B: region, 508C: region, 510: base, 512A: conductive film, 512B: conductive film, 512C: conductive film, 512D: conductive film, 512E: conductive film, 516: insulating film, 516A: insulating film, 516B: insulating film, 518: insulating film, 520: functional layer, 521: insulating film, 524: conductive film, 528: insulating film, 530: pixel circuit, 550: display element, 551: electrode, 552: electrode, 553: layer, 591A: opening portion, 700: display panel, 700A: region, 700B: region, 700C: region, 700TP: input/output panel, 702: pixel, 703: pixel, 720: functional layer, 770: base, 770P: functional film, 771: insulating film, 775: sensing element, 791: component, 791A: elastic body, 791B: elastic body, 791C: elastic body, 792: component

(523) This application is based on Japanese Patent Application Serial No. 2017-229894 filed with Japan Patent Office on Nov. 30, 2017, the entire contents of which are hereby incorporated herein by reference.

Claims

1. A display panel comprising: a first region, a second region, a third region, and a first component, wherein the first region comprises a first part of a display region, wherein the second region comprises a second part of the display region, wherein the third region comprises a third part of the display region, wherein the first component is provided on and in contact with an opposite side of a display surface of the display panel, wherein the first component is in contact with at least the second region, wherein the second region is capable of being bent with the first component facing outward, wherein the first component comprises a first elastic body and a second elastic body, wherein an elastic modulus of the second elastic body is different from an elastic modulus of the first elastic body, wherein the first elastic body is in contact with a first surface of the second elastic body, wherein a second surface of the second elastic body is in contact with the second region, the entire second surface which is in contact with the second region being continuous both when the second region is bent and the second region is not bent, and wherein the second surface of the second elastic body is an opposite surface of the first surface of the second elastic body.
2. The display panel according to claim 1, wherein the display region is configured to perform display in a direction in which the first component is not provided.
3. The display panel according to claim 1, wherein the second region is capable of being bent with a curvature radius larger than 2 mm.
4. The display panel according to claim 1, wherein a thickness of the second region is smaller than a thickness obtained by addition of 100 mm to a thickness of the first component.
5. The display panel according to claim 1, wherein the first component becomes thinner toward end portions in a cross section.
6. The display panel according to claim 1, wherein the first elastic body is in contact with the entire first surface of the second elastic body.
7. A display panel comprising: a first region, a second region, a third region, and a first component, wherein the first region comprises a first part of a display region, wherein the second region comprises a second part of the display region, wherein the third region comprises a third part of the display region, wherein the first component is provided on and in contact with an opposite side of a display surface of the display panel, wherein the first component is in contact with at least the second region, wherein the second region is capable of being bent with the first component facing outward, wherein the first component comprises a first elastic body and a second elastic body, wherein the second elastic body has a higher elastic modulus than the first elastic body, wherein the first elastic body is in contact with a first surface of the second elastic body, wherein a second surface of the second elastic body is in contact with the second region, the entire second surface which is in contact with the second region being continuous both when the second region is bent and the second region is not bent, and wherein the second surface of the second elastic body is an opposite surface of the first surface of the second elastic body.
8. The display panel according to claim 7, wherein the display region is configured to perform display in a direction in which the first component is not provided.
9. The display panel according to claim 7, wherein the second region is capable of being bent with a curvature radius larger than 2 mm.
10. The display panel according to claim 7, wherein a thickness of the second region is smaller than a thickness obtained by addition of 100 mm to a thickness of the first component.
11. The display panel according to claim 7, wherein the first component becomes thinner toward end portions in a cross section.
12. The display panel according to claim 7, wherein the first elastic body is in contact with the entire first surface of the second elastic body.
13. A display panel comprising: a first region, a second region, a third region, and a first component, wherein the first region comprises a first part of a display region, wherein the second region comprises a second part of the display region, wherein the third region comprises a third

part of the display region, wherein the first component is provided on and in contact with an opposite side of a display surface of the display panel, wherein the first component is in contact with at least the second region, wherein the first component comprises a first elastic body and a second elastic body, wherein an elastic modulus of the second elastic body is different from an elastic modulus of the first elastic body, wherein the second elastic body comprises a first surface and a side surface, wherein the first elastic body comprises a first surface and a second surface, wherein the first surface of the first elastic body is in contact with at least the side surface of the second elastic body when the second region is bent and when the second region is not bent, wherein the first surface of the second elastic body is a continuous surface, and wherein the first surface of the second elastic body is in contact with the second region.

14. The display panel according to claim 13, wherein the display region is configured to perform display in a direction in which the first component is not provided.

15. The display panel according to claim 13, wherein the second region is capable of being bent with a curvature radius larger than 2 mm.

16. The display panel according to claim 13, wherein a thickness of the second region is smaller than a thickness obtained by addition of 100 mm to a thickness of the first component.

17. The display panel according to claim 13, wherein the first component becomes thinner toward end portions in a cross section.

18. The display panel according to claim 13, wherein the second elastic body has a higher elastic modulus than the first elastic body.
