

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12412760
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Lee; Chien-Fa et al.

EFEM robot auto teaching methodology

Abstract

The present disclosure relates to a method of programming an EFEM. The method includes placing an automatic teaching element within an EFEM chamber at a first time. The automatic teaching element is operated at a second time to measure one or more parameters corresponding to an initial position of an EFEM robot within the EFEM chamber. The automatic teaching element is removed from the EFEM chamber at a third time and then placed within the EFEM chamber at a fourth time. The automatic teaching element is operated at a fifth time to determine positional parameters describing a difference between the initial position and a new position of the EFEM robot. A second plurality of steps are determined based upon the positional parameters. The EFEM robot is configured to move along the second plurality of steps that extend along a path between first and second positions.

Inventors: Lee; Chien-Fa (Hsinchu, TW), Liu; Hsu-Shui (Pingjhen, TW), Pai; Jiun-Rong (Jhubei, TW), Kuo; Shou-Wen (Hsinchu, TW)

Applicant: Taiwan Semiconductor Manufacturing Company, Ltd. (Hsinchu, TW)

Family ID: 65084571

Assignee: Taiwan Semiconductor Manufacturing Company, Ltd. (Hsinchu, TW)

Appl. No.: 18/625330

Filed: April 03, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240249961 A1	Jul. 25, 2024

Related U.S. Application Data

continuation parent-doc US 15822865 20171127 US 10861723 20201208 child-doc US 17082213
division parent-doc US 17082213 20201028 US 11984331 child-doc US 18625330

Publication Classification

Int. Cl.: B25J9/16 (20060101); H01L21/67 (20060101); H01L21/677 (20060101); H01L21/68 (20060101); H01L21/687 (20060101)

U.S. Cl.:

CPC H01L21/67201 (20130101); H01L21/67259 (20130101); H01L21/67766 (20130101); H01L21/67775 (20130101); H01L21/681 (20130101); H01L21/68707 (20130101)

Field of Classification Search

USPC: 700/245-264; 414/281

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5483138	12/1995	Shmookler et al.	N/A	N/A
5742393	12/1997	Landau et al.	N/A	N/A
6198976	12/2000	Sundar et al.	N/A	N/A
6353312	12/2001	Farnworth et al.	N/A	N/A
6401554	12/2001	Mori	73/1.81	H01L 21/67288
6428673	12/2001	Ritzdorf et al.	N/A	N/A
6453214	12/2001	Bacchi	414/730	H01L 21/68707
6502054	12/2001	Mooring	702/149	G05B 19/4083
6629053	12/2002	Mooring	N/A	N/A
6856863	12/2004	Sundar	N/A	N/A
7066707	12/2005	Bonora et al.	N/A	N/A
7604449	12/2008	Kaveh	414/411	H01L 21/67775
2002/0068992	12/2001	Hine	700/229	H01L 21/67259
2002/0102754	12/2001	Fujimori	438/22	C23C 14/042
2002/0125446	12/2001	Vanderpot	250/492.21	H01L 21/68764
2003/0202092	12/2002	Sadighi	348/87	B25J 9/1697
2004/0031779	12/2003	Cahill	257/E23.179	B23K 26/0853
2004/0151574	12/2003	Lu	414/936	H01L 21/681
2004/0207836	12/2003	Chhibber	356/237.4	G01N 21/8806
2005/0111938	12/2004	van der Meulen	414/217	H01L 21/67184

2005/0113976	12/2004	van der Meulen	700/264	H01L 21/67742
2006/0100740	12/2005	Sakiya	700/121	B25J 9/1692
2006/0130750	12/2005	Ishikawa	118/663	H01L 21/67754
2007/0009345	12/2006	Hall	156/345.31	H01L 21/67265
2007/0180676	12/2006	Hwang	29/407.01	H01L 21/681
2007/0206170	12/2006	Ebihara	355/53	G03F 7/70833
2009/0062959	12/2008	Sakhare	700/254	H01L 21/67742
2009/0118862	12/2008	Genetti	901/3	B25J 9/1694
2009/0225160	12/2008	Shah	348/E5.025	H01L 21/681
2009/0279989	12/2008	Wong	414/217	H01L 21/68
2010/0121487	12/2009	Kawaguchi	414/222.01	H01L 21/68707
2011/0134235	12/2010	Tsumura	348/87	H01L 23/544
2012/0002216	12/2011	Shibata et al.	N/A	N/A
2012/0305024	12/2011	Kang	134/76	H01L 21/67742
2012/0321417	12/2011	Bonora	414/217	H01L 21/67265
2013/0230369	12/2012	Hofmeister	414/217	H01L 21/67724
2013/0325179	12/2012	Liao	700/254	B25J 9/1697
2014/0072397	12/2013	Mooring	118/500	H01L 21/67161
2014/0202921	12/2013	Babbs	206/710	H01L 21/67376
2015/0013910	12/2014	Krupyshev	118/500	H01L 21/67184
2015/0130794	12/2014	Katsuda	345/419	G06T 15/20
2015/0179491	12/2014	Katsuda	414/590	B25J 9/1679
2015/0253765	12/2014	Katsuda	700/121	B25J 9/163
2016/0126128	12/2015	Bonora	414/749.6	H01L 21/6715
2016/0133502	12/2015	Won	901/46	B25J 9/1679
2017/0113344	12/2016	Schoemberg	N/A	N/A
2017/0170044	12/2016	Okabe	N/A	H01L 21/67017
2017/0190053	12/2016	Xu	N/A	B25J 9/1664
2017/0194183	12/2016	Xu	N/A	B25J 9/1692
2017/0194187	12/2016	Xu	N/A	H01L 21/67778
2018/0012789	12/2017	Handa	N/A	B25J 9/042
2018/0053319	12/2017	Kakuma	N/A	H01L 21/67259
2019/0051546	12/2018	Lee	N/A	H01L 21/681

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
H11243131	12/1998	JP	N/A
3208467	12/2000	JP	N/A

OTHER PUBLICATIONS

FALA Technologies. "Introduction to EFEM." Retrieved online on Jul. 31, 2017 from <http://www.falatech.com/page.asp?pageid=45>. cited by applicant

Non-Final Office Action dated Jan. 23, 2020 for U.S. Appl. No. 15/822,865. cited by applicant

Notice of Allowance dated Jul. 29, 2020 for U.S. Appl. No. 15/822,865. cited by applicant

Non-Final Office Action dated Jul. 5, 2023 for U.S. Appl. No. 17/082,213. cited by applicant

Notice of Allowance dated Jan. 10, 2024 for U.S. Appl. No. 17/082,213. cited by applicant

Primary Examiner: Sample; Jonathan L

Attorney, Agent or Firm: Eschweiler & Potashnik, LLC

Background/Summary

REFERENCE TO RELATED APPLICATIONS (1) This Application is a Divisional of U.S. application Ser. No. 17/082,213, filed on Oct. 28, 2020, which is a Continuation of U.S. application Ser. No. 15/822,865, filed on Nov. 27, 2017 (now U.S. Pat. No. 10,861,723, issued on Dec. 8, 2020), which claims the benefit of U.S. Provisional Application No. 62/542,468, filed on Aug. 8, 2017. The contents of the above-referenced Patent Applications are hereby incorporated by reference in their entirety.

BACKGROUND

(1) Semiconductor fabrication facilities (FABs) are factories where integrated chips are manufactured. The fabrication of integrated chips is performed by operating upon a semiconductor wafer with a plurality of fabrication processes (e.g., etching steps, patterning steps, deposition steps, implantation steps, etc.) to form millions or billions of semiconductor devices on and within the semiconductor wafer.

(2) During such fabrication processes, contact between an integrated chip and the outside world is minimized to reduce contaminants that come into contact with the integrated chip and to thereby improve yield. For example, integrated chips are fabricated in clean rooms that have low levels of contaminant particles (e.g., dust) that could be harmful to an integrated chip. Furthermore, human contact with an integrated chip is minimized during fabrication processes by using wafer transfer robots to transfer semiconductor substrates from one location to another (e.g., between a wafer cassette and a processing tool, or vice versa).

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Aspects of the present disclosure are best understood from the following detailed description when read with the accompanying figures. It is noted that, in accordance with the standard practice in the industry, various features are not drawn to scale. In fact, the dimensions of the various features may be arbitrarily increased or reduced for clarity of discussion.

(2) FIG. 1 illustrates a cross-sectional view of some embodiments of a block diagram of a semiconductor processing system comprising an equipment front end module (EFEM) having an

EFEM robot.

(3) FIGS. 2A-2B illustrate block diagrams showing some embodiments of the operation of the semiconductor processing system of FIG. 1 before and after occurrence of an event that modifies a position of an EFEM robot.

(4) FIG. 3 illustrates a block diagram of some embodiments of an automatic teaching element configured to determine positional parameters describing a position of an EFEM robot.

(5) FIGS. 4A-4B illustrate some embodiments of an application of the automatic teaching element of FIG. 3 to determine positional parameters describing a position of an EFEM robot.

(6) FIGS. 5A-5B illustrate some embodiments of an EFEM in which an automatic teaching element is located at various locations on an EFEM robot.

(7) FIG. 6 illustrates a top-view of some additional embodiments of a semiconductor processing system having an EFEM robot within an EFEM having multiple load ports and semiconductor tools.

(8) FIG. 7 illustrates a flow diagram of some embodiments of a method of generating a set of movement commands to account for positional changes of an EFEM robot.

(9) FIGS. 8A-8D illustrate some embodiments of block diagrams showing a method of using a portable automatic teaching element to automatically re-program an EFEM robot to account for positional changes of the EFEM robot.

(10) FIG. 9 illustrates a flow diagram of some embodiments of a method of using a portable automatic teaching element to automatically re-program an EFEM robot to account for positional changes of the EFEM robot.

DETAILED DESCRIPTION

(11) The following disclosure provides many different embodiments, or examples, for implementing different features of the provided subject matter. Specific examples of components and arrangements are described below to simplify the present disclosure. These are, of course, merely examples and are not intended to be limiting. For example, the formation of a first feature over or on a second feature in the description that follows may include embodiments in which the first and second features are formed in direct contact, and may also include embodiments in which additional features may be formed between the first and second features, such that the first and second features may not be in direct contact. In addition, the present disclosure may repeat reference numerals and/or letters in the various examples. This repetition is for the purpose of simplicity and clarity and does not in itself dictate a relationship between the various embodiments and/or configurations discussed.

(12) Further, spatially relative terms, such as “beneath,” “below,” “lower,” “above,” “upper” and the like, may be used herein for ease of description to describe one element or feature's relationship to another element(s) or feature(s) as illustrated in the figures. The spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. The apparatus may be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein may likewise be interpreted accordingly.

(13) To prevent contamination of integrated chips, substrate transfer robots are often used to move semiconductor substrates within semiconductor processing systems. One common type of substrate transfer robot is an equipment front end module (EFEM) robot. EFEM robots are arranged within an EFEM and are configured to transfer semiconductor substrates and/or photo-masks within semiconductor processing systems. For example, an EFEM robot may transfer a semiconductor substrate between a storage carrier (e.g., a pod cassette, a FOUP, etc.) and a variety of processing, measurement, and/or testing tools. EFEM robots are generally installed for each tool in a FAB, so that in a large FAB the number of EFEM robots may be in the hundreds (e.g., 500 or more).

(14) Over time, EFEM robots are subjected to preventive maintenance to maintain reliable operation. EFEM robots also are subjected to repairs when they do fail to operate properly.

Preventive maintenance and repairs may change a position of an EFEM robot within an EFEM chamber. Since the movements of an EFEM robot are fixed with respect to a position of the EFEM robot, such positional changes may result in substrate damage since they also change a path along which the EFEM robot moves substrates. To avoid such damage, an EFEM robot must be re-programmed after a positional change occurs. The re-programming process typically consists of an engineer operating an EFEM robot to slowly move a substrate so as to find new movement commands that define a path of the EFEM robot. However, the re-programming of hundreds of EFEM robots within a FAB can be a costly operation. For example, re-programming often requires a significant time investment (e.g., two or more hours each) by one or more engineers. Furthermore, the re-programming also allows for human errors that can lead to damage of semiconductor substrates.

(15) The present disclosure relates, in some embodiments, to a method of automatically re-programming an EFEM robot to account for positional changes of the EFEM robot, and an associated apparatus. The method comprises determining an initial position of an EFEM robot. When at the initial position, the EFEM robot is configured to operate according to a set of initial movement commands defining a first plurality of steps fixed relative to the initial position. The first plurality of steps move the EFEM robot along a path that extends between first and second positions. After a position of the EFEM robot has changed, positional parameters are determined. The positional parameters describe a change between the initial position and a new position of the EFEM robot that is different than the initial position. A set of new movement commands are generated based upon the positional parameters, and define a second plurality of steps fixed relative to the new position. The EFEM robot is configured to operate according to the set of new movement commands to move along the path between the first position and the second position. By generating new movement commands based upon the positional parameters, positional changes of an EFEM robot (e.g., between the initial position and the new position) can be accounted for without the need for human re-programming, thereby saving time and avoiding damage to substrates.

(16) FIG. 1 illustrates a cross-sectional view of some embodiments of a block diagram of a semiconductor processing system **100** comprising an EFEM robot.

(17) The semiconductor processing system **100** comprises a semiconductor tool **102** coupled to an EFEM (equipment front end module) **103**. The semiconductor tool **102** is configured to perform an operation on a substrate. For example, in various embodiments, the semiconductor tool **102** may be a processing tool (e.g., an etching tool, a lithography tool, etc.) configured to perform a fabrication operation (e.g., an etch, a patterning operation, etc.) on a substrate, a measurement tool configured to perform a measurement operation on a substrate, and/or a testing tool configured to perform a testing operation on a substrate. The EFEM **103** comprises an EFEM chamber **104** and an EFEM robot **112**. The EFEM chamber **104** comprises an enclosed housing in communication with the semiconductor tool **102**. The EFEM chamber **104** is coupled to a load port **106** configured to receive a carrier **108** holding one or more substrates **110**. In various embodiments, the carrier **108** may comprise a FOUP (a front opening unified pod), a wafer cassette, or the like. In some embodiments, the one or more substrates **110** may comprise semiconductor wafers (e.g., 200 mm wafers, 300 mm wafers, 450 mm wafers, etc.).

(18) The EFEM robot **112** is arranged within the EFEM chamber **104**. The EFEM robot **112** includes a robotic arm **114** having a substrate reception element **116** (e.g., a wafer blade) configured to hold one of the one or more substrates **110**. The robotic arm **114** is coupled to a controller **118** that controls movement of the robotic arm **114** within the EFEM chamber **104**. The controller **118** is configured to move the substrate reception element **116** along a series of steps **119** defining a path **120** between a first position and a second position. In some embodiments, the path **120** extends between the carrier **108** and an inlet **122** of the semiconductor tool **102**. The series of steps **119** are fixed within respect to the EFEM robot **112**. Since the series of steps **119** are fixed

with respect to the EFEM robot **112**, a positional change of the EFEM robot **112** will cause a change in the path **120** defined by the series of steps **119**. In some embodiments, the series of steps **119** are defined by a series of movement commands that operate the controller **118** to move the robotic arm **114**.

(19) An automatic teaching element **124** is also arranged within the EFEM chamber **104**. The automatic teaching element **124** comprises one or more sensors that are configured to determine positional parameters describing a change in location of the EFEM robot **112** between an initial position and a new position. In some embodiments, the positional parameters may describe the change in location of the EFEM robot **112** by determining a change in a position of a same component of the EFEM robot **112** relative to a position of an alignment mark **126** disposed on the EFEM chamber **104**.

(20) The positional parameters may be used to adjust the steps **119** that define the path **120** in a manner that accounts for changes in the position of the EFEM robot **112** (e.g., due to crashes, preventive maintenance, etc.). For example, the positional parameters may be used to adjust a series of movement commands defining the steps **119** to account for the changes in position. By using the positional parameters to adjust the steps **119** defining the path **120**, the EFEM robot **112** can be automatically re-programmed to account for positional changes of the EFEM robot **112** without expending the time resources and/or risking product damage associated with human re-programming of the EFEM robot **112**.

(21) FIGS. 2A-2B illustrate block diagrams showing some embodiments of the operation of the semiconductor processing system **100** of FIG. 1 before and after occurrence of an event that modifies a position of an EFEM robot.

(22) FIG. 2A illustrates a block diagram **200** showing operation of an EFEM robot **112** prior to occurrence of an event that modifies a position of the EFEM robot **112** (e.g., a crash, earthquake, preventive maintenance, etc.). As shown in block diagram **200**, during operation the EFEM robot **112** is configured to move a substrate **110** (e.g., semiconductor wafer) along a path **120** extending between a first position **202** and a second position **204**, which are fixed with respect to a fixed reference point (0, 0) tied to an EFEM chamber **104**.

(23) In some embodiments, the EFEM robot **112** is configured to move the substrate **110** according to a series of initial movement commands that move a robotic arm **114** of the EFEM robot **112** along a first plurality of steps **206** that are fixed with respect to a point **201** on the EFEM robot **112**. For example, if the EFEM robot **112** has an initial position **208** of (x.sub.0, z.sub.0) with reference to the fixed reference point (0,0), the series of initial movement commands will cause the EFEM robot **112** to move the robotic arm **114** along a first plurality of steps **206** that are fixed relative to the initial position of (x.sub.0, z.sub.0). In some embodiments, during a first one of the first plurality of steps **206** the EFEM robot **112** will receive the substrate **110** at a first position of (x.sub.1, z.sub.1). During a second one of the first plurality of steps **206**, the EFEM robot **112** will move the substrate **110** to a second position of (x.sub.2, z.sub.1). The first position of (x.sub.1, z.sub.1) is separated from the initial position **208** of (x.sub.0, z.sub.0) by a first distance of (x.sub.1-x.sub.0, z.sub.1-z.sub.0) and the second position of (x.sub.2, z.sub.1) is separated from the initial position **208** of (x.sub.0, z.sub.0) by a second distance of (x.sub.2-x.sub.0, z.sub.1-z.sub.0). In some embodiments, the first plurality of steps **206** will move the substrate **110** along the path **120** from the carrier **108** located at the first position **202** of (x.sub.1, z.sub.1) to an inlet **122** of a semiconductor tool **102** located at the second position **204** of (x.sub.5, z.sub.2) without damaging the substrate **110** (e.g., scraping the substrate).

(24) FIG. 2B illustrates a block diagram **210** of the EFEM robot **112** after an event has changed a position of the EFEM robot **112** from the initial position of (x.sub.0, z.sub.0) to a new position of (x.sub.0+ δ , z.sub.0). The series of initial movement commands are still configured to cause the EFEM robot **112** to move the robotic arm **114** of the EFEM robot **112** along the first plurality of steps **206** that are fixed with respect to the point **201** on the EFEM robot **112**. However, because the

position of the EFEM robot **112** has changed, the series of initial movement commands will no longer move the substrate **110** along the path **120** that extends between the first position **202** of (x.sub.1, z.sub.1) and the second position **204** of (x.sub.5, z.sub.2). Rather, if the EFEM robot **112** is at the new position **212** of (x.sub.0+ δ , z.sub.0), the series of initial movement commands will cause the EFEM robot **112** to move a substrate **110** along a path extending between (x.sub.0+ δ , z.sub.0) and (x.sub.0+ δ , z.sub.0), thereby resulting in an error in the movement of the substrate **110**. The error can cause costly damage (e.g., scrapping) to the substrate **110**.

(25) To account for this error, an automatic teaching element **124** is configured to determine positional parameters describing a change between the initial position (**208** of FIG. 2A) and the new position **212** of the EFEM robot **112**. The automatic teaching element **124** is further configured to use the positional parameters to generate a series of new movement commands. In some embodiments, the automatic teaching element **124** may additionally use the initial position (**208** of FIG. 2A) of the EFEM robot **112** to generate the series of new movement commands. The series of new movement commands take into account positional changes of the EFEM robot **112** to change separations (i.e., distances) between the point **201** on the EFEM robot **112** and steps of the EFEM robot **112**.

(26) In some embodiments, the series of initial movement commands may define the first plurality of steps **206** separated from the point **201** of the EFEM robot having the initial position **208** of (x.sub.0, z.sub.0) by a first plurality of distances, while the series of new movement commands may define a second plurality of steps **214** separated from the point **201** of the EFEM robot **112** having the new position of (x.sub.0+ δ , z.sub.0) by a second plurality of distances different than the first plurality of distances. The changes in the separation between the point **201** on the EFEM robot **112** and the steps causes the second plurality of steps **214** to move the substrate **110** along the path **120** that will not damage the substrate **110**.

(27) For example, during a first one of the second plurality of steps **214**, the EFEM robot **112** will receive the substrate **110** at the first position **202** of (x.sub.1, z.sub.1). The first position **202** of (x.sub.1, z.sub.1) is separated from the new position **212** of (x.sub.0+ δ , z.sub.0) by a first distance of (x.sub.1-(x.sub.0+ δ), z.sub.1-z.sub.0)=(x.sub.1-x.sub.0- δ , z.sub.1-z.sub.0). During a second one of the second plurality of steps **214**, the EFEM robot **112** will move the substrate **110** to a second position **204** of (x.sub.2, z.sub.1). The second position **204** is separated from the new position **212** of (x.sub.0+ δ , z.sub.0) by a second distance of (x.sub.2-(x.sub.0+ δ), z.sub.1-z.sub.0)=(x.sub.2-x.sub.0- δ , z.sub.1-z.sub.0).

(28) Therefore, by operating the automatic teaching element **124** to determine positional changes of the EFEM robot **112**, the automatic teaching element **124** is able to automatically generate a set of new movement commands (i.e., without manual adjustment) that are able to change operation of the EFEM robot **112** to account for changes that may occur during an event that modifies a position of the EFEM robot **112**.

(29) FIG. 3 illustrates a block diagram of some embodiments of an automatic teaching element **300** (e.g., corresponding to automatic teaching element **124**) configured to determine positional parameters describing a position of an EFEM robot.

(30) The automatic teaching element **300** comprises a housing **302** surrounding a position measurement unit **303** configured to take measurements describing positions of an EFEM robot (e.g., **112** of FIG. 1) at different positions within an EFEM chamber (e.g., **104** of FIG. 1). The measurements can be used to determine an initial position of the EFEM robot within the EFEM chamber and positional parameters describing a change between the initial position and a new position of the EFEM robot within the EFEM chamber.

(31) In some embodiments, the position measurement unit **303** may comprise an imaging device **304** and a distance measurement device **306**. The imaging device **304** is configured to capture one or more images corresponding to the EFEM chamber from different positions of the EFEM robot within the EFEM chamber. From the images, a first positional parameter p.sub.1 and a second

positional parameter p.sub.2 can be determined. The first positional parameter p.sub.1 describes a change in the location of the EFEM robot in a first direction (e.g., in an x-coordinate). The second positional parameter p.sub.2 describes a change in the location of the EFEM robot in a second direction (e.g., in a z-coordinate). The first direction is perpendicular to the second direction.

(32) The distance measurement device **306** is configured to measure one or more distances between the distance measurement device **306** and the EFEM chamber at different positions of the EFEM robot within the EFEM chamber. From the one or more distances, a third positional parameter p.sub.3 can be determined to describe a positional change of the EFEM robot in a third direction (e.g., in a y-coordinate) perpendicular to the first direction and to the second direction. In some embodiments, a fourth positional parameter p.sub.4 describing a change in an orientation of the EFEM robot can also be determined from the one or more distances. In other embodiments, the automatic teaching element **300** may comprise an orientation measuring device (not shown) that is arranged within the housing **302** and that is separate and distinct from the distance measurement device **306**.

(33) In some embodiments, the imaging device **304** may comprise a CCD (charge coupled device) camera. In some embodiments, the distance measurement device **306** may comprise a pair of lasers, **308a** and **308b**, and associated sensors, **310a** and **310b**. The pair of lasers comprise a first laser **308a** and a second laser **308b** configured to generate laser beams extending along the third direction. The first laser **308a** and the second laser **308b** are separated along the first direction and/or the second direction.

(34) In some embodiments, the automatic teaching element **300** may further comprise a memory element **312** and a processing element **314**. The memory element **312** is configured to store data describing one or more positions of the EFEM robot. In some embodiments, the memory element **312** may store data describing an initial position of the EFEM robot and/or a new position of the EFEM robot. In various embodiments, the memory element **312** may comprise a volatile memory (e.g., SRAM, DRAM, etc.) and/or a non-volatile memory (e.g., flash, etc.).

(35) The processing element **314** is configured to receive the images from the imaging device **304**, the distances from the distance measurement device **306**, and/or the data describing the initial position of the EFEM robot from the memory element **312**. From the images, the distances, and/or the data, the processing element **314** is configured to determine the positional parameters p.sub.1-p.sub.4. The processing element **314** is further configured to generate a new set of movement commands based upon the positional parameters p.sub.1-p.sub.4. The new set of movement commands are used to modify operation of the EFEM robot to account for changes in the position of the EFEM robot. In some embodiments, the new set of movement commands may be generated by modifying the set of initial movement commands based on the positional parameters. In other embodiments, the new set of movement commands may be generated from the initial position and the positional parameters.

(36) The set of new movement commands may describe a new plurality of steps defining a path between a first position (e.g., carrier **108** of FIG. 1) and a second position (e.g., inlet **122** of semiconductor tool **102** of FIG. 1). In some embodiments, the set of new movement commands may be provided by a communication interface **316** to a controller (e.g., controller **118** of FIG. 1) configured to control movement of the EFEM robot. In other embodiments, the set of new movement commands may be provided by the communication interface **316** to a teaching pendant that is configured to interface with the controller. In some embodiments, the communication interface **316** may be a wireless interface having a transceiver element configured to wirelessly transmit data. In some embodiments, the automatic teaching element **300** may further comprise a coupling element **318** configured to couple the housing **302** to a surface of an EFEM chamber.

(37) Although, the automatic teaching element **300** of FIG. 3 has been described as having a processing element **314** configured to generate the positional parameters and/or movement commands, in other embodiments, the positional parameters and/or movement commands may be

determined by a processing element that is outside of the automatic teaching element **300**. For example, in some alternative embodiments, the automatic teaching element **300** may be configured to provide the image and the one or more distances to a teaching pendant or a controller configured to determine the new set of movement commands therefrom. In such embodiments, the teaching pendant or the controller may comprise a memory element configured to store data describing the initial position of the EFEM robot.

(38) FIGS. **4A-4B** illustrate diagrams, **400** and **406**, showing some embodiments of an application of the automatic teaching element of FIG. **3** to determine positional parameters of an EFEM robot.

(39) As shown in diagram **400** of FIG. **4A**, an automatic teaching element **300** comprises an imaging device **304** configured to capture images of an EFEM chamber **104**. In some embodiments, the imaging device **304** is configured to capture the images from a direction perpendicular to a surface of the EFEM chamber **104** that an alignment mark is on, resulting in a top-view of the alignment mark within a plane extending in an x-direction and a z-direction. Within the top-view of the alignment mark, an image showing a position of the alignment mark **402** at an initial position of an EFEM robot (relative to EFEM chamber **104**) can be compared to an image showing the alignment mark **404** at a new position of the EFEM robot (relative to EFEM chamber **104'**) to determine a first positional parameter $p_{sub.1}$ describing a change in position of the EFEM robot along the x-direction and a second positional parameter $p_{sub.2}$ describing a change in position of the EFEM robot along the z-direction.

(40) As shown in diagram **406** of FIG. **4B**, the automatic teaching element **300** further comprises a distance measurement device **306** configured to measure distances, $d_{sub.1}$ and $d_{sub.2}$, along a y-direction. Distances between the automatic teaching element **300** and the EFEM chamber **104** at an initial position of the EFEM robot (relative to EFEM chamber **104**) can be compared to distances between the automatic teaching element **300** and the EFEM chamber **104** at a new position of the EFEM robot (relative to EFEM chamber **104'**) to determine a third positional parameter $p_{sub.3}$ describing a change in position of the EFEM robot along the y-direction.

(41) In some embodiments, the distance measurement device **306** may comprise a first laser **308a** separated from a second laser **308b** by a separation s . In such embodiments, the first laser **308a** is configured to send a first laser beam **309a** that strikes the EFEM chamber **104** when the EFEM robot is at a first position. The first laser beam **309a** is reflected from the EFEM chamber **104** to a first sensor **310a**, which is configured to determine a first distance $d_{sub.1}$ to the EFEM chamber **104**. The second laser **308b** is configured to send a second laser beam **309b** that strikes the EFEM chamber **104** when the EFEM robot is at a second position. The second laser beam **309b** is reflected from the EFEM chamber **104** to a second sensor **310b**, which is configured to determine a second distance $d_{sub.2}$ to the EFEM chamber **104**.

(42) Furthermore, a difference between the first distance $d_{sub.1}$ and the second distance $d_{sub.2}$ implies that the EFEM robot is rotated (shown as a relative orientation θ of the EFEM chamber). Therefore, in some embodiments, an orientation θ of the EFEM robot may be calculated as a function of the first distance $d_{sub.1}$ and the second distance $d_{sub.2}$. For example, if the first distance $d_{sub.1}$ is equal to a second distance $d_{sub.2}$, the EFEM robot is oriented at an orientation of $\theta=0^\circ$. If a difference of the first distance $d_{sub.1}$ and the second distance $d_{sub.2}$ is equal to the separation s , the EFEM robot **112** is oriented at an orientation of $\theta=45^\circ$. In some embodiments, the orientation θ may be equal to $\tan^{-1}((d_{sub.1}-d_{sub.2})/s)$.

(43) In various embodiments, the automatic teaching element may be configured to be located at different positions in the EFEM chamber and/or on the EFEM robot. FIGS. **5A-5B** illustrate some examples of positions at which the automatic teaching element may be located on an EFEM robot. It will be appreciated that the positions shown in FIG. **5A-5B** are not limiting but rather are merely examples of the many positions at which the automatic teaching element may be located on an EFEM robot.

(44) FIGS. **5A-5B** illustrate some embodiments of a semiconductor processing system **500** in

which the automatic teaching element is located on an EFEM robot.

(45) The semiconductor processing system **500** comprises an EFEM robot **112** within an EFEM chamber **104**. The EFEM robot **112** has a robotic arm **114** coupled to a controller **118**. The robotic arm **114** has a plurality of arm segments **504a-504c** configured to move around a plurality of different axes **506a-506c**. For example, a first arm segment **504a** may move along a first axis **506a**, while a second arm segment **504b** may move along a second axis **506b** that is offset from the first axis **506a**. The plurality of arm segments **504a-504c** are coupled to a base **502** configured to move along the z-direction.

(46) An alignment mark **126** is disposed to an interior surface of the EFEM chamber **104**. In various embodiments, the automatic teaching element **124** may be located along a floor, a sidewall, or a ceiling of the EFEM chamber **104**. The automatic teaching element **124** is located on the EFEM robot **112** and faces the alignment mark **126** on the EFEM chamber **104**. In various embodiments, the automatic teaching element **124** may be located at various location on the EFEM robot **112**. For example, in some embodiments shown in the semiconductor processing system **500** of FIG. 5A, the automatic teaching element **124** may be located on a substrate reception element **116** (e.g., a wafer blade) of the EFEM robot **112**. In another embodiment shown in the semiconductor processing system **508** of FIG. 5B, the automatic teaching element **124** may be located on one of a plurality of arm segments **504a-504c** of the EFEM robot **112**. In yet another embodiment (not shown), the automatic teaching element **124** may be located on the controller **118** of the EFEM robot **112**.

(47) Although FIGS. 1-5B have described the automatic teaching element as adjusting movement commands for a single substrate path, it will be appreciated that the automatic teaching element may be configured to adjust movement commands for multiple paths within a single EFEM chamber. For example, FIG. 6 illustrates a top-view of some additional embodiments of a semiconductor processing system having an EFEM robot configured to move substrates along multiple paths extending between different semiconductor tools and load ports.

(48) The semiconductor processing system **600** comprises a plurality of semiconductor tools **102a-102b** coupled to an EFEM chamber **104** having a plurality of load ports **106a-106c** respectively configured to receive one of a plurality of carriers **108a-108c** holding one or more substrates **110**. An EFEM robot **112** is arranged within the EFEM chamber **104**. The EFEM robot **112** is configured to move the one or more substrates **110** along different paths **120a-120c** extending between the plurality of carriers **108a-108c** and a plurality of semiconductor tools **102a-102b**. For example, the EFEM robot **112** may be configured to move substrates along a first path **120a** extending between a first carrier **108a** and a first semiconductor tool **102a**, a second path **120b** extending between a second carrier **108b** and the first semiconductor tool **102a**, and/or a third path **120c** extending between a third carrier **108c** and a second semiconductor tool **102b**.

(49) The different paths **120a-120c** are defined by different sets of movement commands. For example, the first path **120a** is defined by a first set of movement commands, the second path **120b** is defined by a second set of movement commands that is different than the first set of movement commands, and the third path **120c** is defined by a third set of movement commands that is different than the first set or the second set of movement commands. The different sets of movement commands respectively define a series of steps that are fixed with respect to a position of the EFEM robot **112**.

(50) The automatic teaching element **124** is configured to determine positional parameters describing positional changes of the EFEM robot **112**. The positional parameters may be used to adjust the first set of movement commands defining the path **120** to account positional changes of the EFEM robot **112** (e.g., due to crashes, preventive maintenance). The positional parameters may also be used to adjust the second set of movement commands defining the second path **120b** and the third set of movement commands defining the third path **120c** to account for positional changes of the EFEM robot **112**.

(51) FIG. 7 illustrates a flow diagram of some embodiments of a method **700** of generating a set of movement commands to account for positional changes of an EFEM robot.

(52) While the disclosed methods (e.g., methods **700** and **900**) are illustrated and described herein as a series of acts or events, it will be appreciated that the illustrated ordering of such acts or events are not to be interpreted in a limiting sense. For example, some acts may occur in different orders and/or concurrently with other acts or events apart from those illustrated and/or described herein. In addition, not all illustrated acts may be required to implement one or more aspects or embodiments of the description herein. Further, one or more of the acts depicted herein may be carried out in one or more separate acts and/or phases.

(53) At **702**, an initial position of an EFEM robot is determined. The initial position corresponds to a set of initial movement commands corresponding to a first plurality of steps defining a path between a first position and a second position. The first plurality of steps are fixed with respect to the initial position. FIG. 2A illustrates a cross-sectional view of some embodiments of a block diagram **200** showing an initial position of an EFEM robot corresponding to a first plurality of steps defining a path between first and second positions, according to act **702**.

(54) At **704**, positional parameters are determined. The positional parameters describe positional changes between the initial position and a new position of the EFEM robot. FIGS. 2A-2B illustrates cross-sectional views of some embodiments of block diagrams, **200** and **210**, showing a difference between initial and new positions of an EFEM robot.

(55) In some embodiments, the new positional parameters may be determined based upon acts **706-710**.

(56) At **706**, first and second positional parameters are determined from an alignment mark offset (i.e., an offset between an alignment mark associated with the initial position and an alignment mark associated with the new position). In some embodiments, the first and second positional parameters may describe positional changes in an x-direction and a z-direction. FIG. 4A illustrates a diagram showing some embodiments of determining first and second positional parameters from an alignment mark offset, according to act **706**.

(57) At **708**, a third positional parameter is determined from a plurality of distance offsets (i.e., offsets between distances associated with the initial position and distances associated with the new position). In some embodiments, the third positional parameter may describe positional changes in a y-direction. FIG. 4B illustrates a diagram showing some embodiments of determining a third positional parameter from a plurality of distance offsets, according to act **708**.

(58) At **710**, a difference in a fourth positional parameter is determined from the plurality of distance offsets. In some embodiments, the fourth positional parameters may describe a change in orientation of the EFEM robot. FIG. 4B illustrates a diagram showing some embodiments of determining a fourth positional parameter from a plurality of distance offsets, according to act **710**.

(59) At **712**, a second plurality of steps are determined from the positional parameters. In some embodiments, the second plurality of steps may be determined from the initial position also. The second plurality of steps extend along the path between the first and second positions and are fixed with respect to the new position. FIG. 2B illustrates a cross-sectional view of some embodiments of a block diagram **210** showing a second plurality of steps within the path between first and second positions, according to act **712**.

(60) In some embodiments, the disclosed automatic teaching element may be a portable device that can be moved between different EFEMs. In such embodiments, the automatic teaching element may be used to re-program different EFEM robots within different EFEMs. In some embodiments, the automatic teaching element may be used to re-program different types of EFEM robots (e.g., different EFEM robots made by different manufacturers) within the different EFEMs. By using positional parameters determined by the automatic teaching element to perform EFEM robot re-programming, the different types of EFEM robots can be re-programmed without additional effort.

(61) FIGS. 8A-8D illustrate block diagrams of some embodiments of a method of using a portable

automatic teaching element to account for positional changes in an EFEM robot.

(62) FIG. 8A illustrates a block diagram of a cross-sectional view **800** of some embodiments of a semiconductor processing system during a first time frame comprising first and second times (i.e., t.sub.1–t.sub.2).

(63) As shown in cross-sectional view **800** of FIG. 8A, an automatic teaching element **124** is placed at a first location **802** on an EFEM robot **112** within an EFEM chamber **104** at the first time t.sub.1. The automatic teaching element **124** is operated at the second time t.sub.2 to determine an initial position **208** of (x.sub.1, 0) of the EFEM robot **112** with respect to a fixed reference point (e.g., fixed reference point (0, 0)), which is tied to the EFEM chamber **104**.

(64) FIG. 8B illustrates a block diagram of a cross-sectional view **804** of some embodiments of a semiconductor processing system during a second time frame comprising third and fourth times (i.e., t.sub.3–t.sub.4).

(65) As shown in cross-sectional view **804** of FIG. 8B, the automatic teaching element **124** is removed from the EFEM chamber **104** at the third time t.sub.3. The EFEM robot **112** is subsequently operated to move along a path **120** extending between a first position **202** within a carrier **108** and a second position **204** within a semiconductor tool **102** at the fourth time t.sub.4. The path **120** is defined by a first plurality of steps **206** fixed with respect to the initial position **208** of (x.sub.1, 0) of the EFEM robot **112**.

(66) FIG. 8C illustrates a block diagram of a cross-sectional view **806** of some embodiments of a semiconductor processing system during a third time frame comprising fifth, sixth, and seventh times (i.e., t.sub.5–t.sub.7).

(67) As shown in cross-sectional view **806** of FIG. 8C, after the EFEM robot **112** has moved from the initial position **208** of (x.sub.1, 0) to a new position **212** of (x.sub.1+ δ , 0), the automatic teaching element **124** is placed at the first location **802** on the EFEM robot **112** at the fifth time t.sub.5. The automatic teaching element **124** is operated at the sixth time t.sub.6 to determine the new position of (x.sub.1+ δ , 0) of the EFEM robot **112** with respect to the fixed reference point (e.g., fixed reference point (0, 0)). The automatic teaching element **124** subsequently uses the initial position of (x.sub.1, 0) and the new position of (x.sub.1+ δ , 0) to determine positional parameters describing the positional change of the EFEM robot **112**. From the positional parameters, the automatic teaching element is configured to generate a set of new movement commands at the seventh time t.sub.7. The set of new movement commands are provided to the EFEM robot **112**.

(68) FIG. 8D illustrates a block diagram of a cross-sectional view **808** of some embodiments of a semiconductor processing system during a fourth time frame comprising eighth and ninth times (i.e., t.sub.8–t.sub.9).

(69) As shown in cross-sectional view **808** of FIG. 8D, the automatic teaching element **124** is removed from the EFEM chamber **104** at the eighth time t.sub.8. The EFEM robot **112** is subsequently operated to move along the path **120** according to the set of new movement commands at the ninth time t.sub.9. The path **120** is defined by a second plurality of steps **214** fixed with respect to the new position of (x.sub.1+ δ , 0) of the EFEM robot **112** and extends between the carrier **108** and the semiconductor tool **102**.

(70) FIG. 9 illustrates a flow diagram of some embodiments of a method **900** of using an automatic teaching element to automatically re-program an EFEM robot to account for positional changes of the EFEM robot.

(71) At **902**, an automatic teaching element is placed on an EFEM robot within an EFEM chamber. In some embodiments, the automatic teaching element is placed at a first location on the EFEM robot. FIG. 8A illustrates a cross-sectional view **800** of a block diagram showing an automatic teaching element being placed at a first location within an EFEM chamber, according to some embodiments of act **902**.

(72) At **904**, the automatic teaching element is operated to measure an initial position of an EFEM robot within the EFEM chamber. When the EFEM robot is at the initial position, the EFEM robot is

configured to move along a first plurality of steps that are fixed with respect to the initial position and that extend along a path between a first position and a second position.

(73) At **906**, the automatic teaching element is removed from the EFEM chamber. FIG. **8B** illustrates a cross-sectional view **804** of a block diagram showing an automatic teaching element being removed from an alignment chamber, according to some embodiments of act **906**.

(74) At **908**, the EFEM robot is operated according to set of initial movement commands to move along a first plurality of steps fixed with respect to the initial position and extending between first and second positions. FIG. **8B** illustrates a cross-sectional view **804** of a block diagram showing an EFEM robot moving along a first plurality of steps, according to some embodiments of act **908**.

(75) At **910**, the automatic teaching element is placed on the EFEM robot after operating the EFEM robot according to the set of initial movement commands. In some embodiments, the automatic teaching element is placed at the first location on the EFEM robot. FIG. **8C** illustrates a cross-sectional view **806** of a block diagram showing the automatic teaching element being placed at the first location within an EFEM, according to some embodiments of act **910**.

(76) At **912**, the automatic teaching element is operated to determine positional parameters describing a difference between the initial position and a new position of the EFEM robot.

(77) At **914**, a set of new movement commands are generated based on the positional parameters. In some embodiments, the set of new movement commands may also be generated based on the initial position. The set of new movement commands define a second plurality of steps within the path between first and second positions with respect to the new positional parameters.

(78) At **916**, the automatic teaching element is removed from within the EFEM chamber. FIG. **8C** illustrates a cross-sectional view **806** of a block diagram showing an automatic teaching element being removed from an alignment chamber, according to some embodiments of act **916**.

(79) At **918**, the EFEM robot is operated according to a set of new movement commands to move along second plurality of steps fixed with respect to the new position and extending between the first and second positions. FIG. **8D** illustrates a cross-sectional view **808** of a block diagram showing an EFEM robot moving along a second plurality of steps, according to act **918**.

(80) Although the method **900** describes the reprogramming of a single EFEM robot, it will be appreciated that the method may be applied to use a same teaching device (e.g., comprising a portable unit) to automatically re-program different EFEM robots associated with different EFEMs. For example, after the automatic teaching element is removed from within the EFEM chamber at the sixth time, the automatic teaching element may be placed within an additional EFEM chamber, where the automatic teaching element is configured to determine an additional position of an additional EFEM robot within the additional EFEM chamber.

(81) Accordingly, in various embodiments the present disclosure relates to a method of automatically programming an EFEM robot to account for positional changes of the EFEM robot, and an associated apparatus.

(82) In some embodiments, the present disclosure relates to a method of programming an EFEM robot. The method includes determining an initial position of an EFEM robot within an EFEM chamber, the EFEM robot at the initial position is configured to move along a first plurality of steps that are defined relative to the initial position and that extend along a path between a first position and a second position; determining positional parameters describing a change between the initial position and a new position of the EFEM robot within the EFEM chamber that is different than the initial position; and determining a second plurality of steps based upon the positional parameters, the EFEM robot at the new position is configured to move along the second plurality of steps that are defined relative to the new position and that extend along the path between the first position and the second position. In some embodiments, the positional parameters include a first positional parameter describing a first difference between the initial position and the new position along a first direction, a second positional parameter describing a second difference between the initial position and the new position along a second direction perpendicular to the first direction, a third

positional parameter describing a third difference between the initial position and the new position along a third direction perpendicular to the first direction and to the second direction, and a fourth positional parameter describing a change in an orientation of the EFEM robot between the initial position and the new position. In some embodiments, determining the positional parameters includes determining the first positional parameter and the second positional parameter based on an offset of an alignment mark coupled to the EFEM chamber between the initial position and the new position, wherein the alignment mark is disposed along a plane extending in the first direction and the second direction. In some embodiments, the offset of the alignment mark is determined by comparison of a first image of the alignment mark corresponding to the initial position and a second image of the alignment mark corresponding to the new position. In some embodiments, one or more of the positional parameters is a distance offset along the third direction between the initial position and the new position determined by using one or more lasers. In some embodiments, one or more of the positional parameters is calculated as a function of a first distance measured using a first laser and a second distance measured using a second laser. In some embodiments, one or more of the positional parameters is an orientation of the EFEM robot calculated as a function of a first distance measured using a first laser and a second distance measured using a second laser. In some embodiments, the EFEM robot is configured to operate according to a set of initial movement commands that move the EFEM robot along the first plurality of steps. In some embodiments, the method further includes generating a set of new movement commands based upon the positional parameters, the EFEM robot is configured to operate according to the set of new movement commands to move the EFEM robot along the second plurality of steps. In some embodiments, the method further includes providing the set of new movement commands to a controller configured to operate the EFEM robot according to the set of new movement commands to move the EFEM robot along the second plurality of steps. In some embodiments, the method further includes placing an automatic teaching element within the EFEM chamber, the automatic teaching element is configured to determine the positional parameters; and removing the automatic teaching element from the EFEM chamber prior to using a semiconductor tool coupled to the EFEM chamber to perform a fabrication process on a substrate. In some embodiments, the method further includes placing the automatic teaching element within an additional EFEM chamber after removing the automatic teaching element from the EFEM chamber, the automatic teaching element is configured to determine an additional position of an additional EFEM robot within the additional EFEM chamber. In some embodiments, the first plurality of steps are separated from a point on the EFEM robot by a first plurality of distances, and the second plurality of steps are separated from the point on the EFEM robot by a second plurality of distances different than the first plurality of distances.

(83) In other embodiments, the present disclosure relates to a method of programming an EFEM robot. The method includes determining an initial position of an EFEM robot, the EFEM robot at the initial position is configured to operate according to a set of initial movement commands to move along a first plurality of steps that are defined relative to the initial position and that extend between a first position and a second position; determining positional parameters describing a change between the initial position and a new position of the EFEM robot that is different than the initial position; and generating a set of new movement commands based upon the positional parameters, the EFEM robot at the new position is configured to operate according to the new set of movement commands to move along a second plurality of steps that are defined relative to the new position and that extend between the first position and the second position. In some embodiments, distances between the first plurality of steps and the initial position are different than distances between the second plurality of steps and the new position.

(84) In yet other embodiments, the present disclosure relates to an EFEM robot automatic teaching element. The automatic teaching element includes a position measurement unit configured to determine an initial position of an EFEM robot within an EFEM chamber and a new position of the EFEM robot within the EFEM chamber that is different than the initial position; and a processing

element configured to determine positional parameters describing a difference between the initial position and the new position, and to further determine a second plurality of steps from the positional parameters, which move the EFEM robot along a path extending between a first position and a second position. In some embodiments, the EFEM robot is configured to move along a first plurality of steps that are fixed relative to the initial position and that extend along the path between the first position and the second position. In some embodiments, the first plurality of steps are separated from a point on the EFEM robot by a first plurality of distances, and the second plurality of steps are separated from the point on the EFEM robot by a second plurality of distances different than the first plurality of distances. In some embodiments, the processing element is further configured to determine a set of new movement commands describing the path based upon the positional parameters. In some embodiments, the automatic teaching element further includes a communication interface configured to provide the set of new movement commands to the EFEM robot to change operation of the EFEM robot.

(85) In yet other embodiments, the present disclosure relates to a method of programming an EFEM robot. The method includes placing an automatic teaching element within an EFEM chamber at a first time; operating the automatic teaching element at a second time, after the first time, to measure an initial position of an EFEM robot within the EFEM chamber; removing the automatic teaching element from within the EFEM chamber at a third time after the second time; placing the automatic teaching element within the EFEM chamber at a fourth time after the third time; operating the automatic teaching element at a fifth time, after the fourth time, to measure positional parameters describing a difference between the initial position and a new position of the EFEM robot within the EFEM chamber; and determining a second plurality of steps based upon the positional parameters, wherein the EFEM robot is configured to move along the second plurality of steps that extend along a path between a first position and a second position. In some embodiments, the method further includes placing the automatic teaching element at a first location within the EFEM chamber at the first time, and placing the automatic teaching element at the first location within the EFEM chamber at the fourth time. In some embodiments, the method further includes placing the automatic teaching element within an additional EFEM chamber after removing the automatic teaching element from the EFEM chamber, wherein the automatic teaching element is configured to determine an additional position of an additional EFEM robot within the additional EFEM chamber. In some embodiments, the EFEM robot is configured to move along a first plurality of steps between the third time and the fourth time, which extend along the path between the first position and the second position, and distances between the first plurality of steps and the initial position are different than distances between the second plurality of steps and the new position. In some embodiments, the EFEM robot is configured to operate according to a set of initial movement commands that move the EFEM robot along the first plurality of steps between the third time and the fourth time. In some embodiments, the method further includes generating a set of new movement commands based upon the positional parameters, wherein the EFEM robot is configured to operate according to the set of new movement commands to move the EFEM robot along the second plurality of steps after the fifth time. In some embodiments, the first position is within a carrier configured to hold one or more substrates and the second position is within a semiconductor tool

(86) In yet other embodiments, the present disclosure relates to an EFEM robot automatic teaching element. The automatic teaching element includes a memory element configured to store data describing an initial position of an EFEM robot within an EFEM chamber; a position measurement unit configured to take measurements describing a new position of the EFEM robot within the EFEM chamber that is different than the initial position of the EFEM robot; and a processing element is configured to determine a set of new movement commands describing a path of the EFEM robot based upon the data describing the initial position of the EFEM robot and the measurements. In some embodiments, the automatic teaching element further includes a housing

surrounding the position measurement unit, the memory element, and the processing element. In some embodiments, the automatic teaching element further includes a coupling element fixed to the housing and configured to couple the housing to a surface of the EFEM robot. In some embodiments, the automatic teaching element further includes a communication interface configured to provide the set of new movement commands to a controller configured to control movement of a robotic arm of the EFEM robot or a teaching pendant in communication with the controller. In some embodiments, the position measurement unit includes an imaging device configured to capture an image of an alignment mark disposed on the EFEM chamber, and a distance measurement device configured to measure a first distance and a second distance between the automatic teaching element and the EFEM chamber. In some embodiments, the imaging device comprises a charge coupled device (CCD) camera. In some embodiments, the distance measurement device includes one or more lasers. In some embodiments, the distance measurement device includes a first laser configured to generate a first laser beam extending in a third direction; a second laser configured to generate a second laser beam extending in the third direction, the first laser is separated from the second laser along a first direction or a second direction by a non-zero separation; a first sensor configured to receive a reflection of the first laser beam from the EFEM chamber and to determine the first distance between the first laser and the EFEM chamber; and a second sensor configured to receive a reflection of the second laser beam from the EFEM chamber and to determine the second distance between the second laser and the EFEM chamber.

(87) In yet other embodiments, the present disclosure relates to an EFEM robot automatic teaching element. The automatic teaching element includes an imaging device configured to capture images of an alignment mark disposed on an EFEM chamber at an initial position and at a new position of an EFEM robot (112), the images correspond to a first positional parameter describing a first positional change of the EFEM robot in a first direction and second positional parameter describing a second positional change of the EFEM robot in a second direction; and a distance measurement device configured to measure distances between the distance measurement device and the EFEM chamber at the initial position and at the new position, the distances correspond to a third positional parameter describing a third positional change of the EFEM robot in a third direction and fourth positional parameter describing a change in orientation of the EFEM robot. In some embodiments, the automatic teaching element further includes a processing element configured to receive the images from the imaging device and the first distance and the second distance from the distance measurement device, wherein the processing element is configured to determine the first positional parameter and the second positional parameter from the images and to determine the third positional parameter and the fourth positional parameter from the first distance and the second distance. In some embodiments, the processing element is configured to determine a set of new movement commands describing a path along which the EFEM robot moves between a first position and a second position based upon the first positional parameter, the second positional parameter, the third positional parameter, and the fourth positional parameter. In some embodiments, the automatic teaching element further includes a memory element configured to store data describing an initial position of the EFEM robot, wherein the first positional parameter describes at the first positional change between the initial position of the EFEM robot and at the new position of the EFEM robot. In some embodiments, the distance measurement device includes a first laser configured to generate a first laser beam extending in the third direction; a second laser configured to generate a second laser beam extending in the third direction, the first laser is separated from the second laser along the first direction or the second direction by a non-zero separation; a first sensor configured to receive a reflection of the first laser beam from the EFEM chamber and to determine the first distance from the reflection; and a second sensor configured to receive a reflection of the second laser beam from the EFEM chamber and to determine the second distance from the reflection, the first sensor is separated from the second sensor along the first direction or the second direction.

(88) The foregoing outlines features of several embodiments so that those skilled in the art may better understand the aspects of the present disclosure. Those skilled in the art should appreciate that they may readily use the present disclosure as a basis for designing or modifying other processes and structures for carrying out the same purposes and/or achieving the same advantages of the embodiments introduced herein. Those skilled in the art should also realize that such equivalent constructions do not depart from the spirit and scope of the present disclosure, and that they may make various changes, substitutions, and alterations herein without departing from the spirit and scope of the present disclosure.

Claims

1. A method of programming an equipment front end module (EFEM), comprising: placing an automatic teaching element within an EFEM chamber at a first time; operating the automatic teaching element at a second time, after the first time, to measure one or more parameters corresponding to an initial position of an EFEM robot within the EFEM chamber; removing the automatic teaching element from within the EFEM chamber at a third time after the second time; placing the automatic teaching element within the EFEM chamber at a fourth time after the third time; operating the automatic teaching element at a fifth time, after the fourth time, to determine positional parameters describing a difference between the initial position and a new position of the EFEM robot within the EFEM chamber; and determining a second plurality of steps based upon the positional parameters, wherein the EFEM robot is configured to move along the second plurality of steps that extend along a path between a first position and a second position.
2. The method of claim 1, further comprising: placing the automatic teaching element at a first location within the EFEM chamber at the first time; and placing the automatic teaching element at the first location within the EFEM chamber at the fourth time.
3. The method of claim 1, further comprising: placing the automatic teaching element within an additional EFEM chamber after removing the automatic teaching element from the EFEM chamber, wherein the automatic teaching element is configured to determine an additional position of an additional EFEM robot within the additional EFEM chamber.
4. The method of claim 1, wherein the EFEM robot is configured to move along a first plurality of steps, before the third time, wherein the first plurality of steps extend along the path between the first position and the second position; and wherein distances between the first plurality of steps and the initial position are different than distances between the second plurality of steps and the new position.
5. The method of claim 4, wherein the EFEM robot is configured to operate according to a set of initial movement commands that move the EFEM robot along the first plurality of steps.
6. The method of claim 5, further comprising: generating a set of new movement commands based upon the positional parameters, wherein the EFEM robot is configured to operate according to the set of new movement commands to move the EFEM robot along the second plurality of steps after the fifth time.
7. The method of claim 5, wherein the first position is within a carrier configured to hold one or more substrates and the second position is within a semiconductor tool.
8. A method of programming an EFEM robot, comprising: operating an EFEM at an initial position to move a first substrate along a first plurality of steps that extend between a first position and a second position; determining positional parameters describing a change in position between the initial position and a new position of the EFEM that is different than the initial position, the positional parameters being determined using an offset of an alignment mark between the initial position and the new position; determining a second plurality of steps based upon the positional parameters; and operating the EFEM at the new position to move a second substrate along the second plurality of steps that extend between the first position and the second position.

9. The method of claim 8, wherein the initial position and the new position are within a chamber.
 10. The method of claim 8, further comprising: measuring the change in position between the initial position and the new position along an x-direction, a y-direction, a z-direction, and an angular orientation; and determining the positional parameters based upon the change in position.
 11. The method of claim 8, further comprising: moving the EFEM from the initial position to the new position during maintenance of the EFEM.
 12. The method of claim 8, wherein the EFEM is in the initial position for an entire movement of the first substrate between the first position and the second position along the first plurality of steps.
 13. The method of claim 12, wherein the EFEM is in the new position for an entire movement of the second substrate between the first position and the second position along the second plurality of steps.
 14. A method of programming an EFEM robot, comprising: operating an EFEM at an initial position according to an initial set of movement commands to move a first substrate along a first path between a first position and a second position, wherein the EFEM is in the initial position when the first substrate is in the first position and when the first substrate is in the second position; determining positional parameters that describe a change between the initial position and a new position of the EFEM; determining a second set of movement commands using the positional parameters; and operating the EFEM according to the second set of movement commands, so that at the new position the EFEM moves a second substrate along a second path between the first position and the second position.
 15. The method of claim 14, wherein the EFEM is in the initial position for an entirety of the movement of the first substrate between the first position and the second position along the first path.
 16. The method of claim 14, further comprising: performing maintenance on the EFEM, wherein during the performance of maintenance the EFEM is moved from the initial position to the new position.
 17. The method of claim 14, wherein the initial position is within a carrier and the second position is within a semiconductor tool.
 18. The method of claim 14, wherein the positional parameters describe a change between the initial position and the new position of the EFEM along a first direction, along a second direction, and along a third direction, and further describe a change in an orientation of the EFEM.
 19. The method of claim 14, wherein the positional parameters are determined after the first substrate has been moved between the first position and the second position and prior to moving the second substrate between the first position and the second position.
 20. The method of claim 14, wherein the second set of movement commands are determined from the positional parameters prior to moving the second substrate along the second path between the first position and the second position.
-