

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12413119
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Velderman; Matthew J. et al.

Power tool

Abstract

A power tool is provided comprising: a motor, an output shaft driven by the motor along a longitudinal axis, a fan rotationally coupled to the motor to generate an airflow, and a housing comprising two calm shells mated together to support the motor and forming a back wall behind the motor along the longitudinal axis. The rear wall includes a plurality of air intakes. An end cap is attached to the housing adjacent the rear wall with an air gap therebetween. The airflow generated by the fan enters through the air gap in a substantially radial direction, then passes through the plurality of air intakes to enter the housing in thermal contact with the motor.

Inventors: Velderman; Matthew J. (Baltimore, MD), Seman, Jr.; Andrew E. (Pylesville, MD), White; Daniel J. (Baltimore, MD), Becke; Paul (Stewartstown, PA), Rigdon; William A. (Baltimore, MD)

Applicant: Black & Decker Inc. (New Britain, CT)

Family ID: 65657350

Assignee: BLACK & DECKER INC. (New Britain, CT)

Appl. No.: 18/646102

Filed: April 25, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240275243 A1	Aug. 15, 2024

Related U.S. Application Data

continuation parent-doc US 17411727 20210825 US 11984771 child-doc US 18646102
continuation parent-doc US 16281475 20190221 US 11139722 20211005 child-doc US 17411727
us-provisional-application US 62693564 20180703

Publication Classification

Int. Cl.: **H02K11/215** (20160101); **B23B45/02** (20060101); **B24B23/02** (20060101); **B25F5/00** (20060101); **B26B15/00** (20060101); **H02K5/10** (20060101); **H02K5/15** (20060101); **H02K5/16** (20060101); **H02K5/18** (20060101); **H02K5/20** (20060101); **H02K7/08** (20060101); **H02K7/116** (20060101); **H02K7/14** (20060101); **H02K9/06** (20060101); **H02K9/22** (20060101); **H02K21/16** (20060101)

U.S. Cl.:

CPC **H02K11/215** (20160101); **B23B45/02** (20130101); **B24B23/02** (20130101); **B25F5/008** (20130101); **B26B15/00** (20130101); **H02K5/10** (20130101); **H02K5/15** (20130101); **H02K5/161** (20130101); **H02K5/18** (20130101); **H02K5/207** (20210101); **H02K7/083** (20130101); **H02K7/116** (20130101); **H02K7/145** (20130101); **H02K9/06** (20130101); **H02K9/227** (20210101); **H02K21/16** (20130101);

Field of Classification Search

CPC: H02K (11/215); H02K (5/207); H02K (9/227); H02K (5/10); H02K (7/116)

USPC: 310/50; 310/60R; 310/62-63

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1883288	12/1931	Zubaty	417/423.9	H02K 9/06
5155403	12/1991	Dyke	N/A	N/A
5973428	12/1998	Zakrocki et al.	N/A	N/A
6300697	12/2000	Findeisen et al.	N/A	N/A
6472783	12/2001	Witthohn et al.	N/A	N/A
6674207	12/2003	Blasco Remacha	N/A	N/A
6984909	12/2005	Kadoya et al.	N/A	N/A
7294944	12/2006	Fujii	N/A	N/A
7411326	12/2007	Achor et al.	N/A	N/A
7501730	12/2008	Kimura et al.	N/A	N/A
7622834	12/2008	Fujii et al.	N/A	N/A
7663277	12/2009	Kinoshita et al.	N/A	N/A
7839033	12/2009	Fujii et al.	N/A	N/A
7893578	12/2010	Hayashi et al.	N/A	N/A
8299675	12/2011	Horng et al.	N/A	N/A
8390165	12/2012	Nishiyama et al.	N/A	N/A
8536756	12/2012	Watanabe et al.	N/A	N/A
8653711	12/2013	Burch et al.	N/A	N/A
8796967	12/2013	Sato	N/A	N/A
9033117	12/2014	Ma et al.	N/A	N/A

9272686	12/2015	Chang et al.	N/A	N/A
9287745	12/2015	Akatsu et al.	N/A	N/A
9318932	12/2015	Purohit et al.	N/A	N/A
9331544	12/2015	Okinaga et al.	N/A	N/A
9403505	12/2015	Chang et al.	N/A	N/A
9450472	12/2015	Hatfield et al.	N/A	N/A
9502931	12/2015	Yamada	N/A	N/A
9627934	12/2016	Qin et al.	N/A	N/A
9819241	12/2016	Smith et al.	N/A	N/A
9893576	12/2017	Mikami et al.	N/A	N/A
9966807	12/2017	Yokoyama et al.	N/A	N/A
9966813	12/2017	Nakano et al.	N/A	N/A
10056806	12/2017	Hatfield et al.	N/A	N/A
10063125	12/2017	Jang et al.	N/A	N/A
10205365	12/2018	Beyerl et al.	N/A	N/A
10432065	12/2018	Beyerl et al.	N/A	N/A
10523080	12/2018	Smith et al.	N/A	N/A
10786894	12/2019	Coates et al.	N/A	N/A
11139722	12/2020	Velderman et al.	N/A	N/A
2005/0017591	12/2004	Brewster et al.	N/A	N/A
2006/0152907	12/2005	Rathmann	N/A	N/A
2010/0320880	12/2009	Kamogi	N/A	N/A
2011/0006621	12/2010	Lau	310/64	H02K 5/18
2013/0076195	12/2012	Li et al.	N/A	N/A
2013/0162072	12/2012	Mizutani et al.	N/A	N/A
2013/0264904	12/2012	Taniguchi et al.	N/A	N/A
2013/0342041	12/2012	Ayers et al.	N/A	N/A
2014/0091648	12/2013	Kumagai	310/50	H02K 7/145
2014/0132093	12/2013	Purohit et al.	N/A	N/A
2016/0336838	12/2015	Kouda et al.	N/A	N/A
2017/0106522	12/2016	Coates et al.	N/A	N/A
2017/0288499	12/2016	Beyerl et al.	N/A	N/A
2017/0338726	12/2016	Gandel et al.	N/A	N/A
2018/0148651	12/2017	Koseoglu	N/A	N/A
2018/0294688	12/2017	Smith et al.	N/A	N/A
2019/0023248	12/2018	Yasui	N/A	N/A
2019/0273421	12/2018	Velderman et al.	N/A	N/A
2019/0356197	12/2018	Beyerl et al.	N/A	N/A
2019/0356201	12/2018	Li et al.	N/A	N/A
2020/0091793	12/2019	Smith et al.	N/A	N/A
2020/0162007	12/2019	Sheeks	N/A	N/A
2020/0244127	12/2019	Birkmayer et al.	N/A	N/A
2022/0077750	12/2021	Velderman et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
201918864	12/2010	CN	N/A
203352326	12/2012	CN	N/A
205986473	12/2016	CN	N/A
208046342	12/2017	CN	N/A

210669831	12/2019	CN	N/A
102005039176	12/2006	DE	N/A
102010049682	12/2010	DE	N/A
102012113095	12/2012	DE	N/A
102012215735	12/2013	DE	N/A
102013108118	12/2013	DE	N/A
102016224425	12/2017	DE	N/A
1235327	12/2001	EP	N/A
1385256	12/2003	EP	N/A
1040550	12/2003	EP	N/A
1728414	12/2006	EP	N/A
1863148	12/2006	EP	N/A
1324474	12/2007	EP	N/A
1751837	12/2008	EP	N/A
2670028	12/2012	EP	N/A
2391480	12/2014	EP	N/A
2228886	12/2015	EP	N/A
2739856	12/2015	EP	N/A
3160021	12/2016	EP	N/A
2633618	12/2016	EP	N/A
3007330	12/2016	EP	N/A
3297140	12/2017	EP	N/A
3113336	12/2017	EP	N/A
1384307	12/2018	EP	N/A
2678922	12/2018	EP	N/A
3436221	12/2018	EP	N/A
2195910	12/2018	EP	N/A
2264858	12/2018	EP	N/A
2584672	12/2018	EP	N/A
3203005	12/2018	EP	N/A
3580832	12/2018	EP	N/A
1875586	12/2019	EP	N/A
3603896	12/2019	EP	N/A
2557666	12/2019	EP	N/A
3340440	12/2019	EP	N/A
2002223552	12/2001	JP	N/A
2012050297	12/2011	JP	N/A
2017226025	12/2016	JP	N/A
6453658	12/2018	JP	B25F 5/008
20040032389	12/2003	KR	N/A
20090042597	12/2008	KR	N/A
201230615	12/2011	TW	N/A
2003066262	12/2002	WO	N/A
2011159674	12/2010	WO	N/A
2016177366	12/2015	WO	N/A
2018020650	12/2017	WO	N/A
2018148651	12/2017	WO	N/A
2018176888	12/2017	WO	N/A
2019006452	12/2018	WO	N/A
2019023379	12/2018	WO	N/A

2020038879	12/2019	WO	N/A
2020061756	12/2019	WO	N/A
2020082550	12/2019	WO	N/A

OTHER PUBLICATIONS

Machine Translation JP2017226025 (Year: 2017). cited by examiner

EP EESR, dated May 30, 2022 in corresponding EP Application 21216342.2. cited by applicant

EP EESR, dated May 30, 2022 in corresponding EP Application 21216332.3. cited by applicant

EP EESR, dated May 20, 2022 in corresponding EP Application 21216266.3. cited by applicant

EP EESR, dated May 20, 2022 in corresponding EP Application 21216339.8. cited by applicant

EP EESR, dated May 18, 2022 in corresponding EP Application 21216265.5. cited by applicant

Primary Examiner: Gonzalez Quinones; Jose A

Background/Summary

RELATED APPLICATION (1) This application is a continuation of U.S. patent application Ser. No. 17/411,727 filed Aug. 25, 2021, which is a continuation of U.S. patent application Ser. No. 16/281,475 filed Feb. 21, 2019, now U.S. Pat. No. 11,139,722, which claims the benefit of U.S. Provisional Application No. 62/637,810 filed Mar. 2, 2018; U.S. Provisional Application No. 62/641,008 filed Mar. 9, 2018; and U.S. Provisional Application No. 62/693,564 filed Jul. 3, 2018. The contents of all these applications are incarnated herein by references in their entirety.

FIELD OF THE DISCLOSURE

(1) This disclosure relates to power tools. More particularly, the present invention relates to a power tool with a unique end cap design for improved air flow.

BACKGROUND

(2) Use of brushless DC (BLDC) motors in power tools has increased significantly over the past several years. Examples of such power tool applications are U.S. Pat. No. 9,450,472, US Patent Publication No. 2016/0149463, US Patent Publication No. 2017/0106521, and US Patent Publication No. 2017/0120435, contents of all of which are incorporated herein by reference in their entirety.

(3) As BLDC motors have been used in higher power applications such as grinders, miter saws, etc., a challenge has been to optimize power density so as to keep the power tool as compact and portable as possible while obtaining the desired power output. The goal of power tool manufacturers has been to provide the most amount of power from the motor using the least amount of space possible. The ratio of maximum power output of a motor to the volume of the motor is known as the power density. Power density can be maximized by keeping the size of the motor the same and increasing power, or by keeping the power output the same and reducing the motor volume.

(4) One of the barriers that significantly limit the potential for optimal power density is the motor cooling techniques conventionally used in the industry. Motor coils typically generate a significant amount of heat, particularly for higher power applications. As can be seen in the references cited above, conventional BLDC motors in power tools typically include a cooling fan coupled to the rotor that generates an airflow through the stator windings. This requires a large portion of the volume of the motor stator to be dedicated to providing airflow paths between the motor windings. In most conventional tools, stator slots where stator coils are wound are required to have a maximum slot fill of 50% or less to ensure air gaps between the stator coils can sufficiently cool the coils. This results in large areas of the motor to be wasted for non-magnetic usage.

(5) What is needed is a motor design suitable for power tool applications that provides for maximization of the power density of the motor.

SUMMARY

(6) According to an embodiment of the invention, a motor assembly is provided including a stator and a rotor. The stator includes a stator main body defining a longitudinal axis, stator teeth projecting radially from the stator main body, stator windings wound around the stator teeth, and two winding terminals provided for each stator tooth extending away from the stator main body substantially parallel to the longitudinal axis. The rotor includes a rotor shaft, a rotor core mounted on the shaft, at least one rotor permanent magnet affixed to the rotor core arranged to magnetically interface with the stator windings. In an embodiment, a circuit board is oriented along a radial plane perpendicular to the longitudinal axis adjacent the stator. The circuit board includes a central through-hole through which the rotor shaft extends, at least one magnetic sensor mounted on a surface of the circuit board around the central through-hole configured to magnetically interface with the rotor, peripheral openings arranged to receive the winding terminals of the stator, and conductive routings extending from the peripheral openings to connect the stator windings within each phase of the motor in a series or a parallel configuration and the stator windings within different phases of the motor in a wye or a delta configuration.

(7) In an embodiment, the motor includes axial retainers that axially retain the circuit board relative to an axial end of the stator.

(8) In an embodiment, the peripheral openings include notches formed on a circumference of the circuit board. In an embodiment, the winding terminals are initially positioned at an angle of approximately 5 to 15 degrees relative to the longitudinal axis, are received in radial alignment with the notches, and are radially pressed into the notches to electrically connect to the conductive routings.

(9) In an embodiment, at least one end insulator is located between an axial end of the stator main body and the circuit board and extending radially to insulate at least one of the stator teeth from a corresponding one of the stator windings. For each of the stator teeth, the end insulator includes two legs projecting axially and configured to support the two winding terminals in an axial direction away from the stator main body.

(10) In an embodiment, for each of the stator teeth, the end insulator further includes an axial retainer projecting axially between the two legs configured to attach to and axially retain the circuit board relative to the axial end of the stator main body.

(11) In an embodiment, the stator includes stator segments having segment cores mated together to form the stator main body. The stator teeth project radially from the segment cores.

(12) In an embodiment, end insulators are mounted the stator segments to insulate the stator teeth from the stator windings. Each end insulator includes two legs projecting axially and configured to support the two winding terminals in an axial direction away from the stator main body.

(13) In an embodiment, the motor includes a heat sink having a substantially cylindrical body disposed around the stator, where the circuit board is received inside the heat sink.

(14) In an embodiment, the circuit board includes an outer diameter that is smaller than an outer diameter of the stator main body.

(15) In an embodiment, the motor further includes a sense magnet mounted on the rotor shaft, where the magnetic sensor is positioned proximate the sense magnet along the longitudinal axis.

(16) In an embodiment, a motor end cap is secured to the stator and supporting a bearing therein, where the bearing includes an inner race mounted on the rotor shaft to radially support the rotor relative to the stator.

(17) In an embodiment, the circuit board is disposed between the motor end cap and the stator.

(18) In an embodiment, a power tool is provided including a housing and a BLDC motor according to any of the above embodiments.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 depicts a side view of a power tool **100** constructed in accordance with the teachings of the present disclosure, according to an embodiment;
- (2) FIG. 2 depicts a perspective view of the same power tool;
- (3) FIGS. 3 and 4 respectively depict exploded perspective views of power tool, showing the internal components therein;
- (4) FIGS. 5 and 6 depict perspective partially-exploded front and rear views of the motor assembly, according to an embodiment.
- (5) FIGS. 7 and 8 depict exploded views of the motor assembly, including motor components, according to an embodiment;
- (6) FIG. 9 depicts a cross-sectional side view of the motor, according to an embodiment;
- (7) FIGS. 10 and 11 depict perspective views of the motor, prior to and after assembly of the heat sinks, respectively, according to an embodiment;
- (8) FIG. 12 depicts a perspective cut-off view of the motor, showing the heat sinks in contact with stator lamination stack, according to an embodiment;
- (9) FIG. 13 depicts a perspective view of the motor with heat sinks, showing the path of air flow through air channels, according to an embodiment;
- (10) FIGS. 14 and 15 respectively depict front and rear perspective exploded views of tool housing clam shells around the motor, according to an embodiment;
- (11) FIG. 16 depicts a perspective view of the clam shells assembled around the motor, with end cap shown at a distance, according to an embodiment;
- (12) FIG. 17 depicts a zoomed-in view of the end cap assembled at the end of the tool housing, according to an embodiment;
- (13) FIG. 18 depicts a perspective side view of the motor assembly with heat sinks, according to an embodiment;
- (14) FIG. 19 depicts a cross-sectional side view of the motor assembly without heat sinks, according to an embodiment;
- (15) FIGS. 20-23 depicts various exemplary power tools, including an impact driver, a hammer drill, a cutter, and a reciprocating saw, incorporating the partially-enveloped motor of this disclosure, according to various embodiments;
- (16) FIG. 24 depicts a perspective view of a power tool having a fully-enveloped motor, according to an embodiment;
- (17) FIG. 25 depicts a perspective view of motor assembly of power tool of FIG. 24, according to an embodiment;
- (18) FIG. 26 depicts a top perspective view of power tool, showing an exploded perspective of the motor assembly, according to an embodiment;
- (19) FIG. 27 depicts a bottom exploded view of motor assembly, according to an embodiment;
- (20) FIG. 28 depicts a top cut-off exploded view of the motor assembly from a different angle than that shown in FIG. 26, according to an embodiment;
- (21) FIG. 29 depicts a side cross-sectional view of the motor assembly, according to an embodiment;
- (22) FIGS. 30 and 31 depict partially exploded views of motor assembly following the assembly of rotor and stator within the heat sink, but prior to assembly of module and fan, according to an embodiment;
- (23) FIG. 32 depicts a perspective view of motor assembly, prior to assembly of rear end cap, according to an embodiment;
- (24) FIG. 33 depicts a perspective side view of the motor assembly from a front side of the radial

wall of the heat sink, according to an embodiment;

(25) FIG. **34** depicts a cross-sectional view of the motor assembly from a rear side of the front end cap, according to an embodiment;

(26) FIG. **35** depicts a side view of an exemplary angle grinder including the fully-enveloped motor of this disclosure, according to an embodiment;

(27) FIGS. **36** and **37** depict side views of an exemplary reciprocating saw and an exemplary hammer including the fully-enveloped motor of this disclosure, according to an embodiment;

(28) FIG. **38** depicts a perspective view of a fully-sealed motor assembly, according to an embodiment;

(29) FIG. **39** depicts a bottom exploded view of motor assembly of FIG. **38**, according to an embodiment;

(30) FIG. **40** depicts a top exploded view of the motor assembly without the transmission assembly, according to an embodiment;

(31) FIG. **41** depicts a side cross-sectional view of the motor assembly, according to an embodiment;

(32) FIG. **42** depicts a perspective view of front and rear bearing support structures, according to an embodiment;

(33) FIGS. **43** and **44** depict perspective view of the front and rear bearing support structures received with the heat sink, respectively, according to an embodiment;

(34) FIG. **45** depicts a perspective view of an exemplary motor assembly having an external heat sink, according to an embodiment;

(35) FIG. **46** depicts an axial view of the same motor assembly, according to an embodiment;

(36) FIG. **47** depicts a zoomed-in axial view of the heat sink, showing three of the heat sink fins with coating, according to an embodiment;

(37) FIG. **48** depicts a side view of an exemplary power tool having a fully-enveloped segmented motor assembly, according to an embodiment;

(38) FIGS. **49** and **50** depict front and rear perspective views of an exemplary motor assembly of FIG. **48**, according to an embodiment;

(39) FIGS. **51** and **52** depict front and rear perspective exploded views of the motor assembly, including a stator, a rotor, a heat sink, etc., according to an embodiment;

(40) FIGS. **53** and **54** respectively depict perspective views of the stator of the motor assembly distanced from and within the heat sink, respectively, according to an embodiment;

(41) FIG. **55** depicts an axial cross-sectional view of the heat sink, stator, and rotor, according to an embodiment;

(42) FIG. **56** depicts an axial perspective view of the heat sink and the stator, according to an embodiment;

(43) FIGS. **57-60** depict various views of a stator segment for the stator, according to an embodiment;

(44) FIG. **61** depicts a conventional prior art stator segment design in which the segment core includes inner and outer arched-shaped surfaces, according to an embodiment;

(45) FIG. **62** depicts the stator segment having an improved segment stator segment that significantly improves the slot fill, according to an embodiment;

(46) FIG. **63** depicts an axial view of the heat sink alone, according to an embodiment;

(47) FIG. **64** provides a partial cross-sectional axial view of the stator within the heat sink, according to an embodiment;

(48) FIG. **65** depicts a zoomed-in perspective axial view of two adjacent segment cores within the heat sink, according to an embodiment;

(49) FIG. **66** depicts a perspective view of the stator with a circuit board mounted, according to an embodiment;

(50) FIG. **67** depicts a perspective exploded view of the heat sink, stator, and circuit board,

according to an embodiment;

(51) FIG. **68** depicts a perspective view of the stator and circuit board assembled within the heat sink, according to an embodiment;

(52) FIGS. **69** and **70** depict axial front and back assembled views of the heat sink, stator, and circuit board, according to an embodiment;

(53) FIGS. **71** and **72** depict partial cross-sectional views of motor assembly during the assembly process, immediately prior to and after the insertion of the stator and circuit board into the heat sink, respectively, according to an embodiment;

(54) FIG. **73** depicts a partial perspective view of the motor assembly immediately prior to the insertion of the stator and circuit board into the heat sink, according to an embodiment;

(55) FIGS. **74** and **75** depict power output improvement of an exemplary segmented motor according to the above-described embodiments in comparison to a similarly-sized motor having a conventional stator design, according to an embodiment;

(56) FIG. **76** depicts a power/torque diagram for another exemplary segmented motor according to the above-described embodiments;

(57) FIG. **77** depicts a partially exploded view of a bobbin-wound stator assembly received within a fully-enveloping heat sink, according to an embodiment;

(58) FIG. **78** depicts a partially exploded view of the bobbin-wound stator assembly alone, according to an embodiment;

(59) FIG. **79** depicts another partially exploded view of the bobbin-wound stator assembly, according to an embodiment;

(60) FIGS. **80-83** depict various views of the stator core and the outer ring in a bobbin-wound stator assembly, according to an embodiment;

(61) FIGS. **84** and **85** depict perspective and cross-sectional views of a bobbin-wound stator piece, according to an embodiment;

(62) FIGS. **86** and **87** depict perspective and side views of the bobbin-wound stator piece, according to an embodiment;

(63) FIG. **88** depicts a side view of an exemplary power tool having a motor assembly provided within an outer heatshield, according to an embodiment;

(64) FIGS. **89** and **90** depict front and rear perspective views of an exemplary motor assembly provided within a heatshield, according to an embodiment;

(65) FIGS. **91** and **92** depict front and rear perspective exploded views of the motor assembly with stator and heat sink provided within the heatshield, according to an embodiment;

(66) FIG. **93** depicts a perspective view of heatshield and heat sink housing the stator and circuit board, according to an embodiment;

(67) FIG. **94** depicts an axial view of heatshield alone, according to an embodiment;

(68) FIG. **95** depicts an axial view of heat sink disposed within heatshield, according to an embodiment;

(69) FIG. **96** depicts an axial view of stator and heat sink disposed within heatshield, according to an embodiment;

(70) FIG. **97** depicts a zoomed-in axial view of stator and heat sink disposed within heatshield, according to an embodiment;

(71) FIGS. **98** and **99** depict partially exploded and zoomed-in perspective views of a rear end cap received at an end of the heatshield on one end of the motor assembly, according to an embodiment; and

(72) FIGS. **100** and **101** depict rear zoomed-in axial view and a front axial view of a front end cap of the motor assembly, according to an embodiment.

DETAILED DESCRIPTION

(73) According to an embodiment invention, a BLDC motor design is provided that significantly improves power density for power tool applications. As described below in detail with reference to

the figures, this motor incorporates an external cooling design, where one or more heat carrying elements (heat sinks) are disposed in direct contact with the outer surface of the stator. The power tool housing is shaped and designed so as to expose an outer surface of the heat sink to the outside environment. The heat generated by the coils is conducted through the stator lamination stack and dissipated through the heat sink to the outside environment.

(74) According to an embodiment, the heat sink extends longitudinally along the power tool to make contact with transmission assembly components in addition to the motor components.

(75) According to an embodiment, the motor may be fully sealed via a variety of techniques disclosed in this disclosure. Sealing the motor ensures that motor air flow does not enter the motor, and thus prevents environmental dust and debris from contaminating the motor components.

(76) According to an embodiment, a fan is disposed on the motor shaft that generates cooling air flow for cooling the heat sink. In an embodiment, the fan directs air through a series of channels provided longitudinally on the outer surface of the heat sink to maximize the cooling effect of the air flow. The transmission assembly may include air inlets that align with the heat sink air channels to collect the air passing through the heat sink. Alternatively, the air through the channels may dissipate into the outside environment.

(77) In an embodiment, the fan may be a radial fan with blades arranged opposite the motor. The fan may generate air flow that axially pushes air into the air channels of the heat sink.

(78) In an embodiment, a rear side of the fan facing the motor may house a sense magnet in magnetic communication with positional sensors. This arrangement eliminates the need for placement of sense magnets directly on the rotor shaft or on the lamination stack, thus reducing the size of the motor.

(79) In an embodiment, depending on the motor size and power requirements, the heat sink may be shaped to fully or partially envelope and capsule the motor. For example, for higher-power power tool applications, where motor windings carry higher voltage and are therefore likely to generate more heat, a fully-enveloping heat sink encapsulates the circumference of the stator to maximize heat transfer to the heat sink.

(80) This improved cooling technique eliminates the need to provide large airflow paths within the stator slots for cooling the stator windings and makes that area available for additional slot fill in the form of increased magnet wires with higher number of turns, or thicker magnet wires with the same number of turns. The increased slot fill substantially increases the volumetric power density of the motor.

(81) In an embodiment, a layer of thermally conductive dielectric material may be disposed between the stator laminations to improve thermal conductivity of the stator.

(82) These features are described below in more detail with reference to the accompanying figures.

(83) Partially-Enveloped Motor

(84) A first embodiment of the invention is described herein with reference to FIGS. 1-23.

(85) With reference to the FIG. 1, a side view of a power tool **100** constructed in accordance with the teachings of the present disclosure is shown. FIG. 2 depicts a perspective view of the same power tool **100**. FIGS. 3 and 4 respectively depict exploded perspective views of power tool **100**, showing the internal components therein. The power tool **100** in the particular example provided is an electric cordless drill, but it will be appreciated that the teachings of this disclosure is merely exemplary and the power tool of this invention could be a drill, impact driver, hammer, grinder, circular saw, reciprocating saw, or any similar portable power tool constructed in accordance with the teachings of this disclosure.

(86) Power tool **100**, according to an embodiment, includes a tool housing **102** made up of two clam shells **102a** and **102b** that together form a motor housing **104** for housing a motor assembly **200** and a handle portion **106** for housing an integrated switch module **110**.

(87) In an embodiment, the integrated switch module **110** integrally includes a switch circuit (not shown), such as a three-phase inverter bridge circuit having a series of high-side and low-side

semiconductor switches, arranged to deliver power from a power supply such as battery pack, through terminals **116**, to the motor assembly **200**. The integrated switch module **110** further include a controller (not shown), such as a micro-controller, that controls the switching operation of the switch circuit in order to regulate the voltage being supplied to the motor assembly **200**. The integrated switch module **110** additionally includes an input unit (not shown) coupled to a trigger switch **114** to activate the controller and provide a variable-speed signal to the controller. For detailed examples of the integrated switch module **100**, reference is made to U.S. Pat. No. 9,847,194 filed Mar. 28, 2014, which is incorporated herein by reference in its entirety.

(88) In an embodiment, a transmission assembly **108** having a gear case (not shown) is mounted to the end of the motor housing **104**. The motor assembly **200** may be coupled through the gear case to an output spindle (not shown), which is rotatably coupled to chuck **112**.

(89) In an embodiment, a battery receptacle **118** is disposed at the end of the handle **106** opposite the motor housing **104**. The battery receptacle **118** houses the battery terminals **116** and receives a battery pack couplable to the battery terminals **116** therein. While the motor assembly **200** is powered by a battery pack in this example, it must be understood that power tool **100** may alternatively include a power cord to receive AC power from, for example, a generator or the AC grid, and may include the appropriate circuitry (e.g., a full-wave or half-wave bridge rectifier) to provide positive current to the motor **104**.

(90) In an embodiment, the motor assembly **200** includes a brushless DC (BLDC) motor **202**, a pair of heat sinks **120a** and **120b** disposed on two sides of the motor **202** and held by the clam shells **102a** and **102b** along the outer peripheral surface of the motor **202** to partially envelope an outer periphery of the motor assembly **200**, and a fan **130** disposed at an axial end of the motor **202** opposite the transmission assembly **108**. In an embodiment, the clam shells **102a** and **102b** each includes distal air intakes **140** disposed at the end of the motor housing **104**, radially around a center axial of the motor housing **104**, facing and adjacent the fan **130**. The clam shells **102a** and **102b** also include two longitudinal side openings **142a** and **142b** formed around the heat sinks **120a** and **120b**, through which the heat sinks **120a** and **120b** are exposed to the outside environment. In an embodiment, an end cap **150** is secured to the end of the motor housing **104** in close proximity to the air intakes **140**.

(91) Motor assembly **200** is now described in detail with reference to FIGS. 5-9, according to an embodiment. FIGS. 5 and 6 depict perspective partially-exploded front and rear views of the motor assembly **200**, including the motor **202**, heat sinks **120a** and **120b**, and fan **130**, according to an embodiment. FIGS. 7 and 8 depict exploded views of the motor assembly **200**, including motor **202** components, according to an embodiment. FIG. 9 depicts a cross-sectional side view of the motor **202**, according to an embodiment.

(92) In an embodiment, the motor **202** includes a rotor **210**, a stator **220**, and front and rear bearing support structures **230** and **240**.

(93) Rotor **210**, in an embodiment, includes a rotor shaft **212** on which a rotor lamination stack **202** housing several permanent magnets **218** is mounted. Fan **130** is mounted on the rotor shaft **212** on one side of the rotor lamination stack **214**, and a gear **216** for engagement with the transmission assembly **108** is mounted on the rotor shaft **212** on the other side of the rotor lamination stack **214**. Rotation of the rotor lamination stack **214** causes the rotation of the rotor shaft **212**, the fan **130**, and the gear **216** within the motor assembly **200**. Front and rear rotor bearings **218a**, **218b** are also mounted on the rotor shaft **212**, with front bearing **218a** disposed between the lamination stack **214** and gear **216**, and rear bearing **218b** disposed between the lamination stack **214** and the fan **130**.

(94) Stator **220**, in an embodiment, is disposed around the rotor lamination stack **214** and includes stator windings **222** wound around teeth of a stator lamination stack **224** and two stator end insulators **226**. The stator windings **222** are connected around the stator in, for example, a wye or a delta configuration, and are electrically connected to and energized by integrated switch module **110**. Windings **222** are thereby electrically commutated to generate a magnetic force on the rotor

210, thereby rotating the rotor **210** within the stator **220** in a desired speed and direction of rotation. (95) Front bearing support structure **230**, according to an embodiment, includes a substantially disc-shaped planar radial plate **232** defining a bearing pocket **234** therein. Rear bearing support structure **240**, according to an embodiment, similarly includes a substantially disc-shaped planar radial plate **242** defining a bearing pocket **234** therein. The front and rear bearings **218a** and **218b** are press-fitted inside the bearing pockets **234** and **244** in a way that the outer races of the bearing **218a** and **218b** are non-rotatably supported by the bearing support structures **230** and **240**, respectively.

(96) In an embodiment, a positional sensor board **246**, including a series of positional sensors **248** (e.g., hall sensors), is mounted on the rear bearing support structure **240** facing the rotor **210**. The positional sensor board **246** is positioned in close proximity to a sense magnet ring **250** housed by an end cap **252** of the rotor adjacent the rotor lamination stack **214**. Positional sensors **248** sense the rotational position of the rotor **210** via the sense magnet ring **250**, and the positional sensor board **246** provides the positional information of the to the integrated switch module **110** via connector **254**.

(97) In an embodiment, front bearing support structure **230** includes one or more peripheral arcuate walls **236** that extend longitudinally from radial plate **232** around two opposite sides of the stator **220**. Arcuate walls **236** are sized to form-fittingly receive the stator **220** therein, with the outer surface of the stator lamination stack **224** in contact with, and securely held in place between, the arcuate walls **236**. In an embodiment, rear bearing support structure **240** similarly includes one or more peripheral arcuate walls **256** that extends longitudinally from radial plate **242** along the outer surface of the stator **220** and mates with a corresponding arcuate wall **236** of the front bearing support structure **230**. In the illustrated example, the lower one of the arcuate walls **256** includes a gap to accommodate the positional sensor board **246** and the connector **254**. In an embodiment, a series of fasteners **260** axially secure the front and rear bearing support structures **230** and **240** together around the stator **220**.

(98) In an embodiment, front bearing support structure **230** further includes two side openings **237** peripherally formed between the arcuate walls **236**. Similarly, in an embodiment, rear bearing support structure **240** includes two side openings **257** peripherally formed between the arcuate walls **256**. These peripheral openings **237** and **257** together allow the heat sinks **120a** and **120b** to come into contact with two sides of the outer surface of the stator lamination stack **224** for improved heat transfer from the motor **200**, as described herein.

(99) Fan **130**, in an embodiment, is a high pressure radial fan, which as explained above, is mounted on the rotor shaft **212** to rotate with the rotor **210**. Fan **130** includes a series of blades **270** extending longitudinally around a peripheral portion of a planar fan plate **272**. The fan plate **272** is press-fitted on the rotor shaft **212**. The fan **130** includes a first surface **274** facing the radial plate **242** of the rear bearing support structure **240**, and a second surface **276** from which the blades **270** project longitudinally. The fan blades **270** are oriented such that they suck air from a middle portion of the fan **130** and push air radially out around the fan **130**.

(100) FIGS. **10** and **11** depict perspective views of the motor **200**, prior to and after assembly of the heat sinks **120a** and **120b**, respectively. As shown in these figures, and with continued reference to FIGS. **5-8**, arcuate walls **236** and **256** respectively include guide channels **238** and **258** that align along the axial edges of the peripheral openings **237/257**. The heat sinks **120a** and **120b** include rail guides **261** that are slidably received within the guide channels **238** and **258** in a such a way that an inner surface **162** is in direct contact with the outer surface of the stator **224**.

(101) In an embodiment, outer surfaces **264** of heat sinks **120a** and **120b** opposite the stator **220** include a series of longitudinal fins **266** forming a series of longitudinal air channels **268** therebetween. Air channels **268** are arranged to guide air flow generated by the fan **130** along the outer surfaces **264** of the heat sinks **120a** and **120b**, as discussed below in further detail.

(102) FIG. **12** depicts a perspective cut-off view of the motor **200**, showing the heat sinks **120a** and

120b in contact with the stator lamination stack **224**, according to an embodiment.

(103) FIG. **13** depicts a perspective view of the motor **200** with heat sinks **120a** and **120b** fully inserted into the guide channels **238** and **258**, showing the path of air flow generated by the fan **130** through the air channels **268**.

(104) FIGS. **14** and **15** respectively depict front and rear perspective exploded views of tool housing clam shells **102a** and **102b** around the motor **202**, according to an embodiment.

(105) FIG. **16** depicts a perspective view of the clam shells **102a** and **102b** assembled around the motor **202**, with end cap **150** shown at a distance.

(106) FIG. **17** depicts a zoomed-in view of the end cap **150** assembled at the end of the tool housing **102**.

(107) As shown in these figures, clam shells **102a** and **102b** each includes distal air intakes **140** disposed at the end of the motor housing **104**, radially around a center axial of the motor housing **104**, facing and adjacent the fan **130**. The air intakes **140** are oriented to let air towards a middle portion of the fan **130**. In other words, the air intakes **140** are positioned at a closer radially orientation with respect to the center axis of the motor housing **104** than the fan blades **270**. This allows the fan blades **270** to radially repel the incoming air to the outer periphery of the fan **130**, where air is then pushed into and guided through air channels **268** of the heat sinks **120a** and **120b**.

(108) In an embodiment, clam shells **102a** and **102b** also include two longitudinal side openings **142a** and **142b** formed around the heat sinks **120a** and **120b**, through which the heat sinks **120a** and **120b** are exposed to the outside environment. In an embodiment, side openings **142a** and **142b** are shaped to receive the outermost fins **266** therethrough such that the ends of the fins **266** radially align with, or substantially close to, the outer surfaces **280** of the clam shells **102a** and **102b**. In an embodiment, air inlets **280** are formed between the tool housing **102** and the air channels **268** that guide the air into the air channels **268**. In an embodiment, a radial wall **282** of each of the clam shells **102a** and **102b** that surrounds the fan **130** aligns with the ends of the fins **266** of heat sinks **120a** and **120b** to form the air inlets **280** at the ends of the air channels **268**.

(109) In an embodiment, end cap **150** is attached to the back end of the tool housing **102** in such a way that it maintains a small radial air gap (e.g., approximately 1 mm) between the end cap **150** and the end of the tool housing **102**, as shown in FIG. **17**. This allows air to radially enter through the air gap from outside the tool into the air intakes **140**. In an embodiment, two side caps **284** project axially from the end cap **150** to partially cover the ends of the heat sinks **120a** and **120b**, thus ensuring that the air pushed through the air inlets **280** is properly channeled through air channels **268** of the heat sinks **120a** and **120b**.

(110) It is noted herein that while the cooling mechanism described above includes a radial fan **130** pushing air through the air channels **268** of the heat sinks **120a** and **120b**, the cooling mechanism of this disclosure may employ other types of fan (e.g., a low pressure in-line fan) or other air flow arrangements (e.g., one where the fan pulls air through the air channels of the heat sinks).

(111) Furthermore, while the fan **130** described above is mounted on the rotor shaft **212**, it is envisioned that use of a separately-powered fan, alone or in combination with fan **130**, for cooling the heat sinks **120a** and **120b** is within the scope of this disclosure. In an embodiment, the separately-powered fan may be operated even when the tool is not in use or when the rotor operates at very low speed to continue thermal dissipation and avoid high temperatures that may result from a stalled rotor stall or a low speed operation.

(112) Furthermore, while air is used as the fluid exchange medium in the above-described embodiment, the principle elements of the invention extend to systems cooled with other gases or liquids. For example, in a liquid cooled power tool system, a cooling system include pump, a coolant reservoir, and other elements well known in the art may be incorporated to cool the heat sinks **120a** and **120b**.

(113) It is also noted that while the heat sinks **120a** and **120b** are provided as discrete components in the above-described embodiment, heat sinks **120a** and **120b** may be alternatively provided as

parts of other power tool components, for example, the transmission assembly **108** or the integrated switch module **110**. In an exemplary embodiment, the heat sinks **120a** and **120b** may be integrated into the transmission assembly **108** and later assembled into the motor assembly **200** together with the transmission assembly **108**.

(114) In an embodiment, the heat sinks **120a** and **120b** may be integrally formed with the stator **220**. For example, the heat sinks, including the fins **226** and air channels **268**, may be integrally stamped in the outer geometry of the stator lamination stack **224**.

(115) Furthermore, depending on the motor size and power output requirement, it is envisioned that the motor can be sufficiently cooled without a heat sink and by external cooling of the outer surface of the stator using the methods disclosed herein. Conduction of the heat generated by the stator windings through the stator lamination stack and cooling of the outer surface of the stator outside the motor envelope is thus within the scope of this disclosure.

(116) In an embodiment, in order to enhance the cooling of the motor **200**, particularly the rotor **210** and its components, the fan **130**, including the fan plate **272** and/or the fan blades **270** may be made of thermally conductive material such as metal.

(117) The external end surfaces of the heat sink fins **266** are accessible for contact by the user. Given that the heatsinks may get hot and may exceed permissible limits for user interaction, in an embodiment, additional measures and construction may be employed. Examples of this may include application of a surface coating (such as a polymer) on the end surfaces of the fins **266**. In an embodiment, the surface coating increases the thermal resistance of the end surfaces of the fins **262**, limits direct contact by the user to the end surfaces of the fins **262**, and/or contains airflow directly within the heat sink air channels **268**.

(118) It is also noted that while the heat sinks **120a** and **120b** described above are held in place by motor housing **104** and the motor assembly **200**, the heat sinks may be fully supported by only the enclosure and structural components of the motor assembly **200** alone, or by retention features provided in the motor housing **104** alone.

(119) Additionally, in an embodiment, the boundary thermal resistance between the stator **200** and the heatsinks **120a** and **120b** may be improved by known construction methods, for example, using a thermal bonding compound, via interference and/or compression fits, or using fasteners that securely draw the heatsink against the stator.

(120) In an embodiment, the motor assembly **200** may be fully sealed using a variety of techniques. In an exemplary embodiment, a gasket, adhesive, or other sealant material may be disposed within the mating surfaces of arcuate walls **236** and **256**, and the mating surfaces of guide channels **238** and **258**. In an embodiment, a similar sealant may also be disposed between the edges of the heat sinks **120a**, **120b**, and the guide channels **238**, **258**, and/or the arcuate walls **236**, **256**. In an embodiment, the opening of the rear bearing support structure **240**, through which connector **254** is disposed, is further sealed via a resin or adhesive material, or a plug sized to be fitted within the opening.

(121) Referring now to FIG. **18** a perspective side view of the motor assembly **200** and heat sinks **120a** and **120b** is depicted. FIG. **19** depicts a cross-sectional side view of the motor assembly **200**. As shown in these figures, due to the external cooling of the motor assembly **200**, the number of turns for each winding **222** around stator teeth **292** and through the slots **294** may be significantly increased to a slot fill over 50% or more, preferably to a slot fill of 60% or more, more preferably to a slot fill of 70% or more, more preferably to a slot fill of 80% or more, and even more preferably to a slot fill of 90% or more. This increased slot fill has the effect of increasing the volumetric power density of the motor to levels unachievable with conventional internally-cooled BLDC motors.

(122) According to an embodiment, to improve the thermal bond between the stator winding wires and the stator lamination stack, a variety of techniques may be utilized. These include, but are not limited to, impregnation of the coils with varnish or epoxy, winding the coils in corporation with

thermal adhesives and/or filters, use of bondable wire, or overmolding the stator windings.

(123) According to an embodiment, in order to maximize the slot fill, a variety of winding techniques or stator designs may be utilized. For example, instead of conventional needle winders that require insertion of a winding needle into the stator slots to guide the magnet wires, a precision guide winding machine may be used. A precision guide winding machine guides the wires through the stator slots without the need to insert a winding needle into the slot. This allows more magnet wire to be packed around the stator teeth with the slots.

(124) In an embodiment, the gap **296** between adjacent stator teeth **292** may be significantly reduced for better retention of the stator windings within the slots **294**.

(125) In an embodiment, the thickness of the stator core **290** may be reduced in comparison to conventional BLDC motors to enhance heat transfer between the heat sinks **120a** and **120b** and the stator windings **222**.

(126) According to an embodiment, as shown in FIGS. **18** and **19**, with use of high slot fill as described above, the motor power density can be further improved by increasing the number of stator slots and correspondingly the number of rotor poles. In the illustrated example, nine (9) stator poles are arranged, three of which are commonly coupled to a single phase of the motor **200**, and the rotor is provided with six (6) permanent magnet **218**.

(127) FIGS. **20-23** depicts various exemplary power tools, including an impact driver **295**, a hammer drill **297**, a cutter **298**, and a reciprocating saw **299**, incorporating the partially-enveloped motor **200** of this disclosure. In an embodiment, each of these tools, as well as tool **100** of FIGS. **1-4**, is powered by a battery pack having a maximum voltage of approximately 10V to 30V, preferably approximately 20V.

(128) It should be understood that the partially-enveloped motor design described here is not limited to power tools having aforementioned power tools with the aforementioned voltage ratings, and can be used in various power tool having different power requirements. The size and thickness of the heat sinks **120a** and **120b**, including its fins and air channels, may be varied depending on the motor power requirements and heat dissipation.

(129) Fully-Enveloped Motor

(130) A second embodiment of the invention is described herein with reference to FIGS. **24-37**.

(131) FIG. **24** depicts a perspective view of a power tool **300**, according to an embodiment of the invention. The power tool **300** in the particular example provided is an electric cordless circular saw. Power tool **300**, according to an embodiment, includes a tool housing **302** including a handle portion **304** and a battery receptacle **306** for receiving a battery pack therein. A motor assembly **400**, described below in detail, is provided to drive a saw blade **308**. A saw guard **310** partially enclosing the blade **308** is mounted around a collar (not shown) to protect the blade **308**. For more details of this particular power tool, reference is made to US Patent Publication No. 2014/0366383, which is incorporated herein by reference in its entirety.

(132) In an embodiment, power tool **300** has a higher power output requirement than power tool **100** of the previous embodiment, and thus requires a generally-larger motor assembly that generates more heat as compared to the previous embodiment. It will be appreciated that the power tool **300** of FIG. **24** is merely exemplary and the power tool of this embodiment could be any other type of power tool, particularly medium to high rated voltage power tools receiving 40V to 120V max voltage battery packs, preferably a single 60V max voltage battery pack or two 60V max voltage battery packs arranged in series. Alternatively, the power tool of this embodiment may be one powered by an alternating current (AC) power supply, or a combination of AC and DC power supplies, and include a rectifier circuit to cover AC voltage to DC voltage suitable to energizing the motor **400**. These power tools include, but are not limited to, high power drills and impact drivers, hammer drills, reciprocating saws, table saws, grinders, miter saw, mixers, chain saws, etc., or any similar portable power tool constructed in accordance with the teachings of this disclosure.

(133) FIG. **25** depicts a perspective view of motor assembly **400** of power tool **300**, according to an

embodiment. FIG. 26 depicts a top perspective view of power tool 300, showing an exploded perspective of the motor assembly 400. FIG. 27 depicts a bottom exploded view of motor assembly 400. FIG. 28 depicts a top cut-off exploded view of the motor assembly 400 from a different angle than that shown in FIG. 26, according to an embodiment. FIG. 29 depicts a side cross-sectional view of the motor assembly 400, according to an embodiment. Motor assembly 400 is herein described with reference to these figures.

(134) According to an embodiment, similarly to the previously embodiment, motor assembly 400 includes a rotor 410 having a rotor shaft 412 and a rotor lamination stack 414 housing a series of permanent magnets 418, and a stator 420 having a series of stator windings 422 wound on slots of a lamination stack 424 and two end insulators 426. In an embodiment, a rotary fan 404 is mounted on one end of the rotor shaft 412 to rotate with the rotor shaft 412. It should be noted that motor assembly 400 includes many of the same or similar features as motor assembly 200 previously disclosed, and many of the details and alternative and/or additional embodiments disclosed above with reference to motor assembly 200 are applicable in this embodiment.

(135) In an embodiment, a front end cap 430 is provided on one end of the motor assembly 400 for mounting the motor to a mounting bracket 312 of the power tool 300. Front end cap 430 is sized to be fittingly received within mounting bracket 312, and includes peripheral receptacles 432 for fastening the motor assembly 400 to the mounting bracket 312 via a series of fasteners (not shown). Front end cap 430 also includes a center through-hole 434 through which the rotor shaft 412 extends out.

(136) In an embodiment, a driver 416 is mounted near an end of the rotor shaft 412 extending out of the front end cap 430 through-hole 434. Driver 416, in an embodiment, is press-fitted into a corresponding opening (not shown) of an output spindle (not shown) of the power tool 300 to rotatably drive the saw blade 308. The driver 416 thus radially and axially supports the rotor shaft 412 relative to the front end cap 430, and thus relative to the stator 420. Accordingly, a front side bearing is not provided in this particular example. It should be understood, however, that in an alternative embodiment, through-hole 434 of the front end cap 430 may be as a bearing support pocket and the rotor shaft 412 may be correspondingly provided with a front bearing received within the bearing support pocket.

(137) In an embodiment, a rear end cap 440 is provided on an end of the motor assembly 400 opposite the front end cap 430. Rear end cap 440 is provided with air intakes 442 oriented to let air in towards a middle portion of the fan 404. Fan 404 includes blades 450 facing the rear end cap 440 that generate a radial air flow, as discussed below in detail. Fan 404 also houses a sense magnet ring 452 facing the stator 420 and rotor 410. The sense magnet ring 425 includes one or more magnets corresponding to rotor 410 permanent magnets 418 and rotates with the rotor shaft 412.

(138) In an embodiment, an electronic switch and control module 406 is provided between fan 404 and stator 420. In an embodiment, module 406 may include a disc-shaped printed circuit board on which a controller and power switches for controlling the supply of power to the motor assembly 400 are disposed. Module 406 energizes the stator windings 422 via a series of motor terminals 428 received from the stator 420. Module 406 may also include a series of positional sensors 454 mounted on the printed circuit board facing the fan 404. Positional sensor 454 sense the magnetic position of sense magnet ring 425, and thus the rotor 410, and provide that information to the controller. In an embodiment, module 406 further includes a power terminal 456 that receives battery current from the tool battery receptacle 306. For detailed examples of electronic switch and control module 406, reference is made to US Patent Publication No. 2017/0106522 filed on Oct. 13, 2016, and U.S. patent application Ser. No. 15/708,484 filed on Sep. 19, 2017, contents of both of which are incorporated herein by reference in their entireties.

(139) In an embodiment, motor assembly 400 includes an outer heat sink 402 having a generally cylindrical body surrounding the stator 420. Heat sink 402 includes a cylindrical opening that is sized to fittingly receive the stator 420 therein, the inner surface of the heat sink 402 being in

thermal and physical contact with the outer surface of the stator lamination stack **424**. Since heat sink **402** covers substantially the entire periphery of the stator lamination stack **424**, it provides for optimal heat transfer from the stator **420**.

(140) The outer surface of heat sink **402**, in an embodiment, includes a series of longitudinal fins **460** forming a series of longitudinal air channels **462** therebetween. Air channels **462** are arranged to guide air flow generated by fan **404** along the outer surface of heat sink **402** parallel to the longitudinal axis of the motor **400**. Specifically, as fan **404** rotates, it generates air flow from the air intakes **442** in a radially outwardly direction. Peripheral walls **444** of the rear end cap **440** baffle and guide the air into air channels **462** of the heat sink **402**. In an embodiment, when fully assembled, rear end cap **440** covers the end of the heat sink **402** in contact with the outer edges of fins **460** to guide the air longitudinally into the air channels **462**. Fins **460** increase the outer surface area of the heat sink **402**, while passage of cooling air through the air channels **462** provides for improved heat dissipation from the heat sink **402**.

(141) In an embodiment, air traveling through air channels **462** dissipates into the outside environment at or near the front end cap **430**. In an embodiment, part of the air may be guided through the front end cap **430** and mounting bracket **312** to enter into the spindle assembly (not shown) of the power tool **300** for cooling of the power tool **300** components.

(142) In an embodiment, heat sink **402** may be provided integrally with the stator **420** as a single piece. For example, the heat sink **402**, including the fins **460** and air channels **462**, may be integrally stamped in the outer geometry of the stator lamination stack **424**.

(143) In an embodiment, the inner surface of heat sink **402** is provided with piloting and positioning features **464** for proper of the stator **420** within the heat sink **402**. In an embodiment, stator **420** is provided with corresponding axial ribs or grooves that align with the piloting and positioning features **464** of the heat sink **402**.

(144) In an embodiment, full envelopment of the stator **420** and rotor **410** within the heat sink **402** in the manner described herein provides an arrangement in which the heat sink **402** is the principal enclosure and support structure for the motor **400** while maximizing interfacial contact with the stator **420** and the heat sink **402** for optimal thermal conduction. In an embodiment, the boundary thermal resistance between the stator **420** and the heat sink **402** may be improved by, for example, application of a thermal bonding compound and interference, and/or placement of compression fits, etc., between the outer surface of the stator **420** and the inner surface of the heat sink **402**.

(145) In an embodiment, the inner surface of heat sink **402** is provided with a radial wall **465**. In an embodiment, radial wall **465** is provided to axially fix the relative positions of various motor components. In this example, radial wall **465** spatially separates the rotor **410** and stator **420** from the module **406** and the fan **404**, receiving the stator **420** form-fittingly from one end heat sink **402** and receiving the module **406** form-fittingly from the other end. Additionally, in an embodiment, radial wall **465** may include a bearing pocket **466** for housing a bearing **419** of the rotor **410**. In that manner, heat sink **402**, in cooperation with driver **416**, provides radial and axial support for the rotor **410** with respect to the stator **420**.

(146) In an embodiment, provided peripherally on one end of the heat sink **402** facing the rear end cap **440**, an opening **468** is provided. When module **406** is received within the heat sink **402**, power terminals **456** of module **406** are accessible through the opening **468**.

(147) In an embodiment, one end of the heat sink **402** facing the front end cap **430** is provided with one or more mounting structures **470**. Mounting structure **470** includes through-holes **472** through which fasteners (not shown) secure the heat sink **402** to receptacles **432** of the front end cap **430** and/or the mounting bracket **312**.

(148) Referring to FIGS. **30** and **31**, partially exploded views of motor assembly **400** is depicted following the assembly of rotor **410** and stator **420** within the heat sink **402**, but prior to assembly of module **406** and fan **404**, according to an embodiment. FIG. **32** depicts a perspective view of motor assembly **400**, prior to assembly of rear end cap **440**, according to an embodiment.

(149) As shown in these figures, module **406** may be form-fittingly received within the inner surface of the heat sink **402**. Alternatively and/or additionally, module **406** may include a series of fasteners **474** that securely fasten the module **406** to radial wall **465** of the heat sink **402**.

(150) In an embodiment, fan **404** includes a center receptacle **476** into which the end of the rotor shaft **412** is secured. Once mounted on the end of the rotor shaft **412**, fan **404** substantially aligns with the end of the heat sink **402** with fan blades **450** being disposed outside the envelope of the heat sink **402**. This arrangement allows the fan blades **450** to generate airflow that is directed to air channels **462** on the outer surface of the heat sink **402**, and not into the inner envelope of the heat sink **402**.

(151) In an embodiment, the rotor shaft **412**, the radial wall **465**, and the heat sink **402** are sized to ensure that fan **404** is positioned in close proximity and parallel to the module **406** to facilitate proper magnetic sensing of the sense magnet ring **452** of the fan **404** by positional sensors **454** of module **406**.

(152) In an embodiment, power terminals **456** of module **406** (which in an embodiment is provided as a part of a connector which may include communication signals for other functions in addition to power transfer) are slidably received within opening **468** and covered by peripheral wall **444** of the rear end cap **440**. In an embodiment, the area around the terminals may then be covered by resin or other sealant material.

(153) Referring now to FIG. **33**, a perspective side view of the motor assembly **400** from a front side of the radial wall **465** of the heat sink **402** is depicted. FIG. **34** depicts a cross-sectional view of the motor assembly **400** from a rear side of the front end cap **430**. As shown in these figures, due to the external cooling of the motor assembly **400**, the number of turns for each winding **422** around stator teeth may be significantly increased to a slot fill over 50% or more, preferably to a slot fill of 60% or more, more preferably to a slot fill of 70% or more, more preferably to a slot fill of 80% or more, and even more preferably to a slot fill of 90% or more. This increased slot fill has the effect of increasing the volumetric power density of the motor to levels unachievable with conventional internally-cooled BLDC motors.

(154) According to an embodiment, to improve the thermal bond between the stator winding wires and the stator lamination stack, a variety of techniques may be utilized. These include, but are not limited to, impregnation of the coils with varnish or epoxy, winding the coils in corporation with thermal adhesives and/or filters, use of bondable wire, or overmolding the stator windings.

(155) According to an embodiment, in order to maximize the slot fill, a variety of winding techniques or stator designs may be utilized. For example, instead of conventional needle winders that require insertion of a winding needle into the stator slots to guide the magnet wires, a precision guide winding machine may be used. A precision guide winding machine guides the wires through the stator slots without the need to insert a winding needle into the slot. This allows more magnet wire to be packed around the stator teeth with the slots.

(156) In an embodiment, the gap between adjacent stator teeth may be significantly reduced for better retention of the stator windings within the slots.

(157) In an embodiment, the thickness of the stator core may be reduced in comparison to conventional BLDC motors to enhance heat transfer between the heat sink **402** and the stator windings **422**.

(158) According to an embodiment, with use of high slot fill as described above, the motor power density can be further improved by increasing the number of stator slots and correspondingly the number of rotor poles. In the illustrated example, nine (9) stator poles are arranged, three of which are commonly coupled to a single phase of the motor **400**, and the rotor is provided with six (6) permanent magnet **418**.

(159) FIGS. **35-37** depict various exemplary power tools, including a grinder **500**, a reciprocating saw **520**, and a hammer **522**, incorporating the fully enveloped motor **400** of this disclosure. In an embodiment, each of these tools, as well as tool **300** of FIG. **24**, is powered by a battery pack

having a maximum voltage of approximately 40V to 80V, preferably approximately 60V.

(160) It should be understood that the fully-enveloped motor design described here is not limited to power tools having higher power output requirements, and can be used in various power tool having different power requirements. The size and thickness of the heat sink **402**, including its fins and air channels, may be varied depending on the motor power requirements and heat dissipation.

(161) In an embodiment, as shown in FIG. **35**, motor assembly **400** may be provided along a main axis of the power tool **500** where heat sink **402** is gripped by the user. In this exemplary power tool, a handle portion **502** of the tool is disposed on one side of the motor assembly **400**, and gear case **504** is disposed on the other side of the motor assembly **400** opposite the handle portion **502**. A front end **512** of the handle portion **502**, the heat sink **402**, and a rear end **514** of the gear case **504** are provided with approximately the same girth for a substantially uniform tool body. Instead of a rear end cap **440** with axial air intakes **442**, in this embodiment, a series of radial air intakes **506** are disposed between the front end **512** of handle portion **502** and the heat sink **402**. One of more baffles (not shown) guide the incoming air from the air intakes **506** towards a center portion of the fan, where the air is radially redirected and pushed into the air channels of the heat sink **400** along the tool body. In an embodiment, the front end **514** of the transmission housing may be provided with additional air vents **516** arranged in fluid communication with air channels **462** of the heat sink **402**, through which the air traveling through the air channels **462** enters the gear case **504** for cooling the gear case **504** components.

(162) In an embodiment, a surface coating may be applied to the outer surfaces of the fins **460** to increase the thermal resistance of the outer surface of the heat sink **402**. This prevents the gripping area of the heat sink **402** from getting too much and burning a user's hand. The coating may also assist in containing airflow within the heat channels **462**.

(163) In the embodiments described above, external cooling via the partially-enveloping heat sinks (first embodiment) or fully enveloping heat sink (second embodiment) eliminates the need for air from entering the enclosure of the motor. As a result, in the embodiments of the invention, the motor enclosure may be designed so as to provide total enclosure, i.e., closure or sealing of openings to prevent fluid communication between the inside components of the motor and the outside environment. This is of particular interest with power tool motors as contamination from the environment, e.g., rain, mud, oil, concrete aggregate, metal ingestion, etc., are all common causes of motor failure.

(164) This may be accomplished by providing sealing materials applied or disposed between mating surfaces of various motor components. For example, in the partially-enveloped design of the first embodiment, the mating surfaces of the front and rear bearing support structures and the heat sinks may be provided with sealing material. Similarly, in the fully-enveloped design of the second embodiment, the mating surfaces of the front end cap and the heat sink, and the mating surfaces of the electronic switch and control module and the inner surface of the heat sink, may be provided with sealing material. Such material may include, but are not limited to, adhesives, grease, gaskets, O-rings, compressive fits, etc., provided for increased levels of sealing.

(165) In addition, in an embodiment, various openings such as those provided for disposition of connectors and terminals may be sealed with application of material such as grommets, adhesives, potting, and other gap filling and/or coating measures with the ultimate goal of total motor enclosure.

(166) Fully Enveloped and Sealed Motor

(167) Referring now to FIGS. **38-44**, a third embodiment of the invention is describe herein. In this embodiment, front and rear support structures for the rotor bearings are provided within a sealing material (e.g., O-rings) within a fully-enveloping heat sink. The front and rear bearing support structures, in addition to providing positional support for the rotor relative to the stator, fully seal the axial ends of the rotor and stator assemblies from fluid communication with the outside environment.

(168) FIG. 38 depicts a perspective view of a motor assembly **600**, according to an embodiment. FIG. 39 depicts a bottom exploded view of motor assembly **600**, according to an embodiment. FIG. 40 depicts a top exploded view of the motor assembly **600** without the transmission assembly, according to an embodiment. FIG. 41 depicts a side cross-sectional view of the motor assembly **600**, according to an embodiment. Motor assembly **400** is herein described with reference to these figures.

(169) Similarly to above-described embodiments, motor assembly **600** a rotor **610** having a rotor shaft **612** and a rotor lamination stack **614** housing a series of permanent magnets, and a stator **620** having a series of stator windings wound on slots of a lamination stack **624**. In an embodiment, a rotary fan **650** is mounted on one end of the rotor shaft **612** to rotate with the rotor shaft **612**.

(170) It should be noted that motor assembly **600** includes many of the same or similar features as motor assemblies **200** and **400** previously disclosed, and many of the details and alternative and/or additional embodiments disclosed above with reference to motor assemblies **200** and **400** are applicable in this embodiment.

(171) In an embodiment, similarly to above-described embodiments, motor assembly **600** includes a heat sink **602**, similarly to embodiments described above, is substantially-cylindrical with outer fin **604** defining longitudinal air channels **604** in between formed on the outer surface of the heat sink **602**. Heat sink **602** includes a peripheral opening **608** for disposition of motor connector and/or terminal, as described below.

(172) In an embodiment, heat sink **602** additionally includes a switch receptacle **608** that slidably receives a mode/speed selector switch **680** therein. Switch **680** may be used in some power tool applications such as, for example drills.

(173) In an embodiment, a transmission housing **670** is disposed on a front end of the heat sink **602**, and a rear end cap **660** is disposed on a rear end of heat sink **602**.

(174) In an embodiment, a rear end cap **660** is provided with air intakes **662** oriented to let air in towards a middle portion of the fan **650**. Fan **650** includes blades **652** facing the rear end cap **660** that generate a radial air flow towards away from a center of the fan **650**. Peripheral walls **666** of the rear end cap **660** redirect the air generated by the fan **650** axially into the air channels **606** of the heat sink, similarly to embodiments disclosed above. Fan **650** also houses a sense magnet ring (not shown) facing the stator **620** and rotor **610**, similarly to embodiments disclosed above.

(175) In an embodiment, front and rear bearings **616** and **618** are mounted on the rotor shaft **612** on two sides of the rotor lamination stack **620**. Front and rear bearing support structures **630** and **640** are provided adjacent the ends of the stator **620** and rotor **610** to spatially receive and support the front and rear bearings **616** and **618**, respectively. Front bearing support structure **630** includes a bearing pocket **632** that form-fittingly receives an outer race of the front bearing **616**. Similarly, rear bearing support structure **640** includes a bearing pocket **642** that form-fittingly receives an outer race of the rear bearing **618**. Front and rear bearing support structures **630** and **640** are respectively provided with fasteners **636** and **646** that securely fasten them to the ends of the stator **620**.

(176) In an embodiment, rear bearing support structure **640** includes a positional sensor board **644**, which as described in the embodiments disclosed above, faces the sense magnet ring of the fan **650**.

(177) The stator **626** includes a connector **620** projecting radially from an end of the stator **620**. Connector **626** may accommodate motor terminals or other communication signals to and/or from motor switches and/or the controller (not shown). In an embodiment, front bearing support structure **630** includes a connector tab **634** corresponding to the shape of the connector **626**.

(178) During assembly of motor assembly **600**, stator **610** and rotor **620** are together received from a front end of the heat sink **602** into an inner envelope of the heat sink **602**, with connector **626** received within the opening **608** of the heat sink **602**. Front bearing support structure **630** is also received from the front end of the heat sink **602**, with connector tab **634** received through the opening **608** adjacent or in contact with the connector **626**. Rear bearing support **640** is received

through a rear end of the heat sink **604**.

(179) FIG. **42** depicts a perspective view of front and rear bearing support structures **630** and **640**, according to an embodiment. FIGS. **43** and **44** depict perspective view of the front and rear bearing support structures **630** and **640** received with the heat sink **602**, respectively, according to an embodiment. In an embodiment, as shown in this figure, and with continued reference to FIGS. **38-41**, front and rear bearing support structures **630** and **640** are sized to be form-fittingly received within the inner envelope of the heat sink **602** on the two sides of the rotor **610** and stator **620**. Thus, front and rear bearing support structures **630** and **640**, together with the heat sink **602**, substantially seal the rotor **610** and stator **620**. Additionally, in an embodiment, front and rear bearing support structures **630** and **640** are each provided with a seals **638**, **648** disposed around the outer periphery thereof. Seals **638**, **648** may be adhesives, grease, gaskets, O-rings, compressive fits, or other sealants, that substantially seal any gaps between the support structures **630**, **640** and the heat sink **602**, thus providing an air-tight enclosure around the rotor **610** and stator **620** components.

(180) In an embodiment, a seal may also be applied around the connector **626** and/or connector tab **634**. In an embodiment, the remaining open area of opening **608** may be covered with a plug or other sealant material.

(181) In an embodiment, after assembly of the front and rear bearing support structures **630** and **640**, fan **650** is mounted on an end of the rotor shaft **612**, and rear end cap **660** is secured to the rear end of the heat sink **601**. In an embodiment, peripheral walls **666** of the rear end cap **660** partially covers the end of the heat sink **602** for more efficient baffling of the air flow into the air channels **606** of the heat sink **602**. Rear end cap **660** may be secured to the heat sink **602** via a series of fasteners **664** received into the ends of some of the air channels **606**.

(182) In an embodiment, transmission assembly **670** may be mounted to the front end of the heat sink **602**. Transmission assembly **670** may include air inlets (not shown) that collect and intake air traveling through air channels **606** for cooling of transmission components. In addition, in an embodiment, at least some of the transmission components may be positioned within the inner envelope of the heat sink **602** forward from the front bearing support structure **630** to utilize the heat sink **602** for cooling of these components.

(183) Stator Having Improved Heat Conduction

(184) Conventionally, the steel used in construction of stator lamination has a thermal conductivity of 20 to 25 Watts per meter-Kelvin (W/m-k). This thermal conductivity defines the ability of the motor stator to conduct heat from the interior of the motor to the surface where excess heat may be transferred to the surrounding environment through radiation, conduction or convection. A temperature gradient will form between the inner core of the motor and the outside area of the case of the motor. The magnitude of the temperature gradient is dependent on the thermal conductivity of the stator laminations. It is desirable to reduce the temperature gradient as much as possible in order to increase the efficiency and reliability of the motor. Other materials such as aluminum, copper and carbon have higher thermal conductivities than steel, however they lack the necessary magnetic properties of the steel used in the stator laminations.

(185) Stator laminations are sheets of steel on the order of 100-1000 microns. A protective coating of resin and/or cellulose ester (i.e., lacker material) or other high dielectric material is typically disposed between adjacent layers of the steel lamination to reduce electrical Eddy currents in the steel laminations that contribute motor inefficiency.

(186) According to an embodiment, in order to increase the thermal conductivity of the stator while substantially maintaining its magnetic properties and efficiency, steel laminations of the stator lamination stack are interleaved with materials having high thermal conductivity. Specifically, in an embodiment, the thermal conductivity of the stator is improved by replacing the conventional dielectric materials between adjacent stator laminations with dielectric materials that have high thermal conductivity properties. Various forms of carbon, including graphite, graphene, carbon

Nano tubes, diamonds, and carbon fiber have thermal conductivities as high as 2000 W/m-k. With thermal conductivities nearly 100 times greater than the stator steel, only a relatively thin layer of the carbon-based material between adjacent laminations is sufficient to significantly increase thermal conductivity of the stator.

(187) In an embodiment, since carbon alone does not possess desirable dielectric properties, the layer of carbon-based material is applied to a thin film having dielectric properties.

(188) In an embodiment, carbon material may be dispersed into a resin system and applied through a coating process. Alternatively, in an embodiment, carbon material may be deposited directly as a dry powder. In yet another embodiment, premade sheets of carbon material, such as pyrolytic Graphite, may be provided between adjacent laminations.

(189) It was found by the inventors of this application that with application of thin layers of pyrolytic Graphite between adjacent laminations, thermal conductivity of the stator lamination stack can be significantly improved depending on the thickness of the pyrolytic Graphite sheet (PGS) being applied. In an embodiment, as shown in Table A below, the thickness of a single PGS may be between 2.8% to 28% the thickness of a single steel lamination. Thus, an increase of merely 2.8% to 28% in the lamination stack length results in improved thermal conductivity of between 1.7 times to 4.7 times.

(190) TABLE-US-00001 TABLE A Stator Steel 360.0E-6 360.0E-6 360.0E-6 360.0E-6 360.0E-6 360.0E-6 360.0E-6 360.0E-6 Lamination Thickness (m) Stator Steel 23.0E+0 23.0E+0 23.0E+0 23.0E+0 23.0E+0 23.0E+0 Lamination Thermal conductivity (W/m-k) PSG Sheet 100.0E-6 70.0E-6 50.0E-6 40.0E-6 25.0E-6 17.0E-6 10.0E-6 Thickness (m) PGS Graphite 700.0E+0 1.0E+3 1.3E+3 1.4E+3 1.6E+3 1.9E+3 2.0E+3 Sheets (W/m-k) Thermal 4.7 4.7 4.4 3.8 2.9 2.4 1.7 conductivity Improvement % increase in 27.8% 19.4% 13.9% 11.1% 6.9% 4.7% 2.8% thickness

(191) It will be appreciated that while PGS is used herein by way of example, other carbon-based material and depositing method described above are likely to yield similar results in improved thermal conductivity.

(192) In an embodiment, where materials such as the PGS are used between laminations, the sheets can be oversized so as to provide increased contact area between motor windings on the inside the stator, and heat sinks on the outside of the motor.

(193) The slots for the motor windings are often lined with a material such as paper to help protect the windings during assembly. In an embodiment, constructing the motors using PGS in place of, or in addition to, the paper liners also improves the thermal performance of the motor, as it provides improved thermal conductivity between the motor windings and the stator structure.

(194) Selectively Coated Heat Sink

(195) Another aspect of the invention is described herein with reference to FIGS. 45-47, according to an embodiment.

(196) A motor assembly with an external heat sink, as described in various embodiments of this disclosure, forms the external face of a power tool that is accessible by users. While cooling methods previously described sufficiently cool the heat sink for many applications, in some high-power application, or in applications where power tool is continually used for extended periods of time, the heat sink temperature may reach levels unsafe or uncomfortable for users to touch and operate.

(197) According to an embodiment, in order to reduce thermal transfer to a user's hand, extremities of the external heat sink are selectively coated and/or covered by a layer of thermally-resistive material. In an embodiment, the extremities of the heat sink are coated selectively, for example at the tips of the heat sink fins, such that most of the surface area of the heat sink is left uncoated convectively transfer heat to the outside environment.

(198) In an embodiment, examples of thermally-resistive material may include, but are not limited to, plastic, ceramic, rubber, paint, powder coating, etc. Alternatively, in an embodiment, thermally-

resistive material may be tape, molding, extruded plastic, etc., manufactured separately and attached to the extremities of the heat sink. In yet another embodiment, the coating may be in the form of a process, e.g., anodization, applies to the surface of the heat sink, changing the physical characteristics of the surface properties of the heat sink.

(199) FIG. 45 depicts a perspective view of an exemplary motor assembly 700 having an external heat sink 702 having fins 704, and front and rear bearing support structures 730 and 760. FIG. 46 depicts an axial view of the same motor assembly 700. This motor assembly 700 is depicted here by way of an example, and the principles provided in this section can apply to any of other embodiments of the invention. Motor assembly 700 is not described in great detail herein, and it should be understood that the teachings of the previous embodiments are applicable to motor assembly 700.

(200) In an embodiment, FIG. 47 depicts a zoomed-in axial view of the heat sink 700, showing three of the heat sink fins 704. In an embodiment, the end portion 706 of each fin 704 is provided with recessed side surfaces 708 and a double-humped end surface 709. The coating 710 is applied at the end portion 706 around the recessed side surfaces 708 and the doubled-humped end surface 709. This fin 704 geometry increases the bonding of the coating 710 at the end portion 706, and provides a uniform and consistent perimeter profile between the coating 710 and the rest of the fin 704. In an embodiment, the fin 704 geometry may alternatively and/or additionally include undercuts, scores, texturing/knurling, and/or reliefs to enhance the bonding of the coating 710 to the end portion 706.

(201) In an embodiment, the recessed side surfaces 708 occupy approximately 20-30% of the height, and 10-40% of the width of the fins.

(202) In an embodiment, the coating may be applied by selective masking of the heat sink 702 via, for example, tape or wax, before application of the coating material. Alternatively, the coating may be applied to the entire surface area around the fins and then selectively removed by secondary scraping. In yet another embodiment, coating may be selectively deposited by a known process or material such as ultra-violet curing and/or laser.

(203) Fully-Enveloped Segmented Motor

(204) Another aspect of the invention is described herein with reference to FIGS. 48-76. In an embodiment, as described in detail here, stator assembly of the motor may be provided with a segmented construction. An external heat sink is provided for thermal management of the motor as well as mechanical retention and constraint of the segments.

(205) FIG. 48 depicts a side view of an exemplary power tool 800 having a fully-enveloped segmented motor assembly 900. While power tool 800 in a grinder by way of example, it will be appreciated that the teachings of this disclosure with respect to this embodiment are merely exemplary, and the power tool of this invention could be any type of corded or cordless power tool, such as a drill, impact driver, hammer, hammer drill, circular saw, reciprocating saw, multi-tool, or any similar power tool constructed in accordance with the teachings of this disclosure. In an embodiment, power tool 800 may include a handle 802 disposed on one side of the motor assembly 900, and a gear case 804 disposed on another side of the motor assembly 900 opposite the handle 802. In an embodiment, a battery pack 806 is removably mounted to the end of the handle 802. A trigger mechanism 808 is also mounted on the handle 802. In an embodiment, the handle 802 houses a controller and other electronics (not shown) for driving the motor assembly 900. In an embodiment, the motor assembly 900 rotatably drives a motor spindle (not shown) within the gear case 804, which in turns causes rotation of output spindle 810.

(206) FIGS. 49 and 50 depict front and rear perspective views of an exemplary motor assembly 900, according to an embodiment. FIGS. 51 and 52 depict front and rear perspective exploded views of the motor assembly 900, according to an embodiment.

(207) According to an embodiment, similarly to the previously-described embodiments, motor assembly 900 includes a rotor 910 having a rotor shaft 912 and a rotor lamination stack 914

housing a series of permanent magnets **918**, front and rear beings **916a** and **916b**, and a sense magnet ring **952**. In an embodiment, the motor assembly **900** also includes a stator **920** having segmented windings within an outer heat sink **902** for external cooling and mechanical constraints of the stator **920**, as described later in detail. In an embodiment, a rotary fan **904** having blades **950** is mounted on one end of the rotor shaft **912** to rotate with the rotor shaft **912**.

(208) It should be noted that motor assembly **900** includes many of the same or similar features as motor assemblies **200** and/or **400** previously disclosed, and many of the details and alternative and/or additional embodiments disclosed above with reference to motor assemblies **200** and/or **400** are applicable in this embodiment.

(209) In an embodiment, the outer heat sink **902** may be constructed according to the embodiments described above, particularly a fully-enveloping heat sink include a series of outer longitudinal fins **960** forming longitudinal air channels **962** therebetween on its outer surface. In an embodiment, outer heat sink **902** includes a generally cylindrical body surrounding the stator **920**. Heat sink **902** includes a cylindrical opening that is sized to fittingly receive the stator **920**, with the inner surface of the heat sink **902** being in thermal and physical contact with the outer surface of the stator **920**. Since heat sink **902** covers substantially the entire periphery of the stator **920**, it provides for optimal heat transfer from the stator **920** to the outside environment.

(210) In an embodiment, the outer geometry of the heat sink **902** is sized to provide a substantially uniform profile on the power tool **800** between the handle **802** and the gear case **804**.

(211) In an embodiment, air channels **962** are arranged to guide air flow generated by fan **904** along the outer surface of heat sink **902** parallel to the longitudinal axis of the motor **900**. Fins **960** increase the outer surface area of the heat sink **902**, while passage of cooling air through the air channels **962** provides for improved heat dissipation from the heat sink **902**. In an embodiment, air channels **962** form air inlets with the handle **802** to receive incoming air from inside the handle **802**. In an embodiment, air traveling through air channels **962** dissipates into the outside environment at or near the front end cap **940**. In an embodiment, part of the air may be guided through the front end cap **440** into the gear case **804** for cooling the gear case components.

(212) In an embodiment, heat sink **902** may be constructed of non-ferrous material in order to minimize the impact of eddy current losses and heating from the magnetic operation of the motor assembly **900**. In an embodiment, the heat sink **902** may be constructed of high-thermal conductivity material, such as aluminum, to facilitate the transfer of heat from the stator **920** to the outside environment. In an embodiment, the heat sink **902** may be of an extruded, machined, or die cast construction.

(213) In an embodiment, a rear end cap **930** is provided on one end of the motor assembly **400** for mounting the motor **900** to the power tool handle **802**. An outer periphery **936** of the rear end cap **930** is sized to be fittingly received within an end of the heat sink **902**, i.e., via press-fitting.

Alternatively, in an embodiment, rear end cap **930** includes peripheral receptacles **932** for fastening the rear end cap **930** to the end of the heat sink **902** via a series of fasteners. The fasteners may be fastened into corresponding threaded receptacles in the heat sink **902**, or within the air channels **962**. In an embodiment, front end cap **930** further includes a center bearing pocket **934** that receives the rear bearing **916a** of the rotor shaft **912**.

(214) In an embodiment, a rear portion of the rear end cap **930** is provided with a pair of passthrough bosses **938**. The handle **802** of power tool **800**, which is ordinarily made up on two clam shells, form around the passthrough bosses **938** and includes features that secure the passthrough bosses **938** with respect to the handle **802**.

(215) In an embodiment, a front end cap **940** is provided on an end of the motor assembly **900** opposite the rear end cap **930**. Front end cap **940** is provided with outer receptacles **942** for fastening the front end cap **940** to the gear case **804** of the power tool **800** via fasteners. Front end cap **940** is also provided with inner receptacles **945** for fastening the front end cap **940** to the heat sink **902** via fasteners. The latter fasteners may be fastened into corresponding threaded receptacles

in the heat sink **902**, or within the air channels **962**. Front end cap **940** further includes a through-hole **944** provided as a bearing support for front bearing **916b** of the rotor shaft **912**. Alternatively, through-hole **944** may be a pass-through opening through which the rotor shaft **912** freely extends and is piloted in the gear case **804** via a driver **917**.

(216) In an embodiment, front end cap **940** may also be provided with a series of peripheral openings forming air inlets **946**. Air inlets **946** are aligned with the air channels **962** of the heat sink **902** to receive air traversing through the air channels **962**. A baffle **956** direct air from the air inlets **946** towards a middle portion of the fan **904**. Fan **904** includes blades **955** that generate air flow through the air channels **962**, through the air inlets **946**, in the direction of the fan **904**. In an embodiment, the air flow generated by the fan **904** may be expelled out of air exhaust ports (not shown) in the gear case **804**.

(217) In an embodiment, front end cap **940** may be provided with a series of recesses **948** around the through-hole **944**. Recesses **948** are positioned where the ends of the stator windings **922** facing the front end cap **940** to account with tolerances associated with the stator windings **922**.

(218) In an embodiment, the heat sink **902** and rear and front end caps **930** and **940** together substantially encapsulate and seal the stator **920** and rotor **910** from the outside environment, preventing or at the very least minimizing air flow, and in particular contaminated air flow, from entering the magnetic areas of the motor assembly **900**. In an embodiment, additional sealants, such as for example, gaskets, adhesive, etc. may be applied as needed to the rear and front end caps **930** and **940** to form a water-sealed containment around the magnetic areas of the motor assembly **900**.

(219) In an embodiment, circuit board **906** is received within the heat sink **902**. In an embodiment, circuit **906** may include disc-shaped and include positional sensors for sensing the rotary position of the sense magnet ring **952** are disposed. It should be noted, however, that power switches for powering the phase of the motor **900**, and/or controller for controlling the switching operation of the power switches, may also be disposed on the circuit board **906**. In an embodiment, circuit board **906** may also include metal tracks for connecting the stator windings, as described below in detail. Circuit board **906** electronically communicates with other electronic components disposed in the power tool handle **802** via pins or wires passing through the rear end cap **930**.

(220) Referring now to FIGS. **53-56**, various views of the stator **920** received within the heat sink **902** are provided. FIGS. **53** and **54** respectively depict perspective views of the stator **920** distanced from and within the heat sink **902**, respectively, according to an embodiment. FIG. **55** depicts an axial cross-sectional view of the heat sink **902**, stator **920**, and rotor **910**, according to an embodiment. FIG. **56** depicts an axial perspective view of the heat sink **902** and the stator **920**, according to an embodiment.

(221) In an embodiment, stator **920** includes a series of segmented windings **922** wound over discrete stator segments **924**. The windings **922** are wound on each stator segment **924** independently via a winding machine. The stator segments **924** are shaped to mate in a circular fashion together forming the stator **920** after the windings **922** have been wound. In an embodiment, the heat sink **902** provides radial constraint to securely hold the stator segments **924** together.

(222) FIGS. **57-60** depict various views of the stator segments **924** are depicted. As shown herein, and with continued reference to FIGS. **53-56**, each stator segment **924** includes a segment core **970** arranged to form a segment of the outer periphery of the stator **920**, and a segment pole **972** extending radially inwardly from the segment core **970** on which the windings **922** are disposed. In an embodiment, arched-shaped pole ends **974** extend laterally from the ends of the segment poles **972** around the rotor **910**. In an embodiment, the segment core **970**, segment pole **972**, and pole ends **974** may be made of metal laminations. In an embodiment, two insulating members **976** are disposed on the sides of the segment poles **927** to insulate the windings **922** from the stator segments **924**. Two end insulators **977** and **978** are also disposed at the ends of the of the stator segments **924** for the same purpose. The windings are wound around the end insulators **977**, **978**

and the insulating member **976**. In an embodiment, end insulator **977** further includes two legs **975** that receive two winding terminals **979**, and an axial retainer **980** for attachment of the circuit board **906**, as described later in detail.

(223) Referring to FIGS. **61** and **62**, an embodiment of the invention for increasing the slot fill within each stator segment **924** is described.

(224) FIG. **61** depicts a conventional prior art stator segment design in which the segment core includes inner and outer arched-shaped surfaces. The ends of the segment core are flat and at a normal angle to the inner and outer surfaces of the segment core. When the stator segments are assembled together, the inner and outer surfaces of the stator segments together form circular inner and outer surfaces for the stator core. While this arrangement provides smooth surfaces for easy and high-precision assembly, it limits the number of turns of the windings that can be fitted within each slot. Specifically, the curvature of the inner surface of the segment core limits the opening **982** through which the windings are received, preventing the windings from being fitted into space **986** using commonly-used winding machines.

(225) FIG. **62** depicts the stator segment **924** having an improved segment stator segment that significantly improves the slot fill, according to an embodiment of the invention. In an embodiment, segment core **970** of the stator segment **924** is provided with flat inner surfaces **988** disposed substantially perpendicularly to the segment pole **972**. This construction provides a wider opening **984** compared to the prior art design to allow a higher number of windings to be disposed around the segment pole **972**. This construction optimizes the accessible area for wire fill, and therefore increases power density of the motor.

(226) Furthermore, in an embodiment, to ensure that the thickness of the segment core **970** is not too small around the edges, the outer surface of the segment core **970** is provided with two flat edge portions **992** disposed on two sides of an arch-shaped portion **990**. In an embodiment, arch-shaped portion **990** is aligned with a radial axis of the segment pole **972**, and a notch **994** is provided as a part of the arch-shaped portion **990** for proper piloting and alignment of the stator segments **924** within the heat sink **902**. In an embodiment, flat edge portions **992** are substantially parallel to the flat inner surface **998**. In an embodiment, each flat edge portion **992** extends approximately 10-20% of the width of the segment core **970**. In an embodiment, first and second ends **991** and **993** of the segment core **970** are provided with mating geometric surfaces for improved constraining and retention of the stator segments **924**.

(227) Referring to FIGS. **63-65**, an inner profile of the heat sink **902** optimized for receiving the stator **920** is described herein.

(228) FIG. **63** depicts an axial view of the heat sink **902** alone, according to an embodiment. FIG. **64** provides a partial cross-sectional axial view of the stator **920** within the heat sink **902**. FIG. **65** depicts a zoomed-in perspective axial view of two adjacent segment cores **970** within the heat sink **902**.

(229) As shown in these figures, and with continued reference to FIGS. **53-56**, in an embodiment, heat sink **902** is provided with internal geometry designed for proper radial constraining of the above-described stator segments **924**. Specifically, in an embodiment, instead of a fully circular inner surface, the inner surface of the heat sink **902** includes a series of sectors **996**, one of which is denoted in FIG. **63** within angular position **6**. The sectors **996** correspond to the stator segments **924** in number and surface profile. In an embodiment, each sector **996** includes an arched portion **997** and two flat side portions **998**. Arched portions **997** have the same curvature as the arched-shaped portions **990** of the stator segments **924** and are arranged to form-fittingly receive the arched-shaped portions **990** of the stator segments **924** therein. In an embodiment, each arched portion **997** has a radius of curvature that shares the same center as the center of the heat sink **902** outer surface.

(230) In an embodiment, flat side portions **998** extend laterally from two sides of the arched portion **997**. Abutting flat side portions **998** of adjacent sectors **996** form recessed portions **995**

therebetween in the inner surface of the heat sink **902**. As shown in FIG. **64**, recesses portions **995** receive flat edge portions **992** of adjacent stator segments **924** therein.

(231) In an embodiment, as shown in FIG. **65**, flat side portions **998** are angled to provide a small angular gap (e.g., approximately 1 degrees, up to 0.5 mm in width) between the flat edge portions **992** of the stator segments **924** and flat side portions **998** of the corresponding sectors **996**. This arrangement accounts for tolerances associated with the heat sink **902** and stator segments **924** and ensures that the arched-shaped portions **990** of the stator segments **924** come into contact with the arched portions **997** of the heat sink **902** for proper diametric insertion of the stator segments **924** within the heat sink **902**.

(232) By form-fitting insertion of the stator segments **924** within the sectors **996** of the heat sink **902**, via for example press-fitting, the heat sink **902** provides radial as well as axial constraint to hold the stator segments **924** together around the rotor **910** with a high level of precision.

Furthermore, securing the rear and front end caps **930** and **940** to the ends of the heat sink **902** as previously described provides axial and radial retention between the rotor **910** and the stator **920** with a small radial gap therebetween.

(233) In an embodiment, a series of notches **999** may be provided at different positions on the inner surface of the heat sink **902**. Welding material may be welded inside the notches **999** for enhanced bonding of the stator **920** to the heat sink **902** and increased relief on the arched portions **997** of the heat sink **902**. Notches **999** ensure that the welding material does not interfere with the stator **920** insertion operation.

(234) Referring now to FIGS. **66** to **73**, assembly of circuit board **906** to the stator **920** is described herein, according to an embodiment of the invention.

(235) FIG. **66** depicts a perspective view of the stator **920** with circuit board **906** mounted, in an embodiment. FIG. **67** depicts a perspective exploded view of the heat sink **902**, stator **920**, and circuit board **906**, according to an embodiment. FIG. **68** depicts a perspective view of the stator **920** and circuit board **906** assembled within the heat sink **902**, according to an embodiment. FIGS. **69** and **70** depict axial front and back assembled views of the heat sink **902**, stator **920**, and circuit board **906**, according to an embodiment.

(236) As previously described briefly, circuit board **906** includes a series of positional sensors **908** disposed around a center through-hole **1000**. In addition, circuit board **906** includes conductive routings (not shown) that connect the stator windings **922** of the respective stator segments **924** together. In an embodiment, the conductive routings may be configured to couple corresponding stator windings **922** within each phase of the motor **900** in a series or parallel configuration. Furthermore, the conductive routings may couple stator windings **922** of different phases of the motor **900** in a wye or a delta configuration.

(237) In an embodiment, to facilitate connection of the stator windings **922** to the circuit board **906**, circuit board **906** is peripherally provided with a series of outer notches **1002** positioned to receive the winding terminals **979** of the stator segments **924**. Conductive routings of the circuit board **906** extend into the notches **1002** to facilitate the desired winding connection between the winding terminals **979**. Axial retainers **980** of the stator segments **924**, which may be, for example, elastic snaps, hooks, etc., snap onto the counterpart slots **1004** on outer periphery of the circuit board **906** to securely position and retain the circuit board **906** at the end of the stator **920**.

(238) FIGS. **71** and **72** depict partial cross-sectional views of motor assembly **900** during the assembly process, immediately prior to and after the insertion of the stator **920** and circuit board **906** into the heat sink **902**, respectively, according to an embodiment. FIG. **73** depicts a partial perspective view of the motor assembly **900** immediately prior to the insertion of the stator **920** and circuit board **906** into the heat sink **902**.

(239) As shown in these figures, in an embodiment, during the assembly process, the stator segments **924** are initially held together and inserted partially into the heat sink **902**, with winding terminals **979** and axial retainers **980** protruding outside the heat sink **902** body. In an embodiment,

circuit board **906** is then mounted on the end of the stator **920** with winding terminals **979** disposed within openings of the notches **1002**, and axial retainers **980** making snap connections with the slots **1004**.

(240) In an embodiment, legs **975** of end insulator **977** are positioned at an angle (e.g., approximately 5-15 degrees) from an insertion axis of the stator **920** to ensure that the winding terminals **979** are received into the openings of the notches **1002** with ease and without impeding the insertion process. In an embodiment, legs **975** include outer projections **1006** provided radially outwardly from the winding terminals **979**. In an embodiment, after the circuit board **906** is mounted on the end of the stator **920**, the stator **920** is further slid into the heat sink **902**. During this step, the inner portion of the end surface of the heat sink **902** encounters the outer projections **1006**, applying a radially inward force on the outer projections **1006** that causes the winding terminals **979** to be forced into contact and make an electrical connection with the inner surfaces of the notches **1002**. This arrangement ensures that the winding terminals **979** do not block or interfere with the circuit board **906** during the assembly process, but make a secure electrical connection with the circuit board **906** at the completion of the process.

(241) FIGS. **74** and **75** depict power output improvement of an exemplary segmented motor according to the above-described embodiments in comparison to a similarly-sized motor having a conventional stator design, according to an embodiment. In this example, both motors include 6-pole rotors and 9-slot stators. Both stators are 51 mm in outer diameter (i.e., inner diameter of the heat sink) and 25 mm in length (i.e., length of the segment core). In both simulations, the motor is powered by a 20V max battery pack. As shown, at different conduction band and angle advance commutations, the exemplary segmented motor outputs maximum power greater than 1800 W at 120/30 degrees conduction band/angle advance, and over 2000 W at 150/45 conduction band/angle advance. This power output represents an increase of 23% to 33% over the motor having a conventional stator design.

(242) FIG. **76** depicts a power/torque diagram for another exemplary segmented motor according to the above-described embodiments. In this example, the motor includes a stator that is 30 mm in outer diameter and 25 mm in length, and produces a maximum power output of over 360 W when powered by a 20V max battery pack.

(243) It was further found that an exemplary motor according to the above-described embodiments having a stator that is 61 mm in outer diameter and 45 mm in length produces a maximum power output of approximately 32000 W when powered by a 60V max battery pack.

(244) Bobbin-Wound Motor with External Heat Sink

(245) The above-described embodiment relates to a stator assembly in which the windings are wound directly onto the segment poles. In such a construction, each segment pole is placed into a winding machine and the magnet wires are wound around the segment pole. In an alternative embodiment, as described in this section, the stator assembly may be made of bobbin-wound segments. Bobbin windings refer to coils wound independently of the stator core. The bobbin coils are initially wound onto a bobbin carrier or a mandrel, and the wound coils are thereafter relocated and assembled onto the stator core poles.

(246) According to an embodiment, any of the above-described embodiments, i.e., motor partially enveloped fully enveloped by an external heat sink, may be provided with a bobbin-wound motor as described herein.

(247) FIG. **77** depicts a partially exploded view of a stator assembly **1100** received within a fully-enveloping heat sink **1102**. FIG. **78** depicts a partially exploded view of the stator assembly **1100** alone. FIG. **79** depicts another partially exploded view of the stator assembly **1100**. It is reiterated that heat sink **1102** may be constructed according to any of the above-described embodiments, and disposed as an outer-cooling mechanism for the stator assembly **1100** in any power tool construction previously described. The full motor construction, including details of the rotor assembly and other components, is not described herein to avoid repetition.

(248) In an embodiment, stator assembly **1100** includes an inner stator core **1110** having a central annular body sized to receive a rotor assembly (not shown) with a small air gap therebetween, and a series of stator poles **1112** extending radially outwardly from the stator core **1110**. A series of stator pieces **1120** are mounted on the stator poles **1112**. Stator windings **1122** are wound on the stator pieces **1120**, independently from the rest of the stator assembly **1100**. The windings **1122** may be formed with bondable magnet wire. In an embodiment, the windings **1122** may be wound on a bobbin carrier or a mandrel and later pressed on the stator pieces **1120**. Two winding terminals **1124** are disposed on each stator piece **1120** for attachment to a circuit board (not shown) as previously described. Each stator piece **1120** includes an elongate opening **1126** through which the stator pole **1112** extends after the stator piece **1120** is mounted on the stator pole **1112**.

(249) In an embodiment, an outer ring **1130** may be provided to constrain the stator pieces **1120** on the stator core **1110**. In an embodiment, the outer ring **1130** includes a series of axial inner slots **1132** arranged to received pole tips **1114** of the stator poles **1112** therein when the stator core **1110** and the stator pieces **1120** are inserted inside the inner diameter of the outer ring **1130**. In an embodiment, the outer ring **1130** may be pressed onto the stator pieces **1120** and the stator core **1110**, forming the back iron for the stator assembly **1100** for the magnetic path between the stator poles **1112**. The outer surface of the outer ring **1130** may be provided with appropriate geometry to be received within the heat sink **1102** for external cooling of the stator assembly **1100**.

(250) With the outer ring **1130**, the heat sink **1102** may be provided as a partially-enveloping construction instead of a fully-enveloping construction as shown. It is noted that, in an embodiment, when heat sink **1102** has a fully-enveloping construction as shown in FIG. 77, the stator core **1110** and the stator pieces **1120** maybe received inside the heat sink **1102** directly without the outer ring **1130**. The heat sink **1102** in this embodiment may include axial inner slots similarly to slots **1132** of the outer ring **1130**, and may be sized to provide mechanical radial (and even axial) constraint for the stator pieces **1120** on the stator core **1110**. The heat sink in this embodiment may also form the back iron for the stator assembly **1100** for the magnetic path between the stator poles **1112**.

(251) FIGS. **80-83** depict various views of the stator core **1110** and the outer ring **1130**, according to an embodiment.

(252) FIGS. **84** and **85** depict perspective and cross-sectional views of a stator piece **1120**, according to an embodiment. FIGS. **86** and **87** depict perspective and side views of a stator piece **1120**, according to an embodiment.

(253) According to an embodiment, in order to improve thermal conductivity between the stator windings **1122** and the heat sink **1102**, the stator pieces **1120** are provided with thermal filler material. In an embodiment, radial walls **1127** of each stator piece **1120**, along the sides of the elongate opening **1126**, are provided with side openings **1128**, as shown in FIG. **86**. In an embodiment, the stator pieces **1120** are coated with thermal filler material **1129**, fully or partially within the side openings **1128**. Thermal filler material may be made of thermally conductive but electrically insulating material, such as silicone caulk, grease, etc. The volume of the thermal filler material may be provided in excess of the spaces within the side openings **1128** to ensure proper bonding between stator windings **1122** and the stator poles **1112**.

(254) Outer-Cooled Motor with a Heatshield

(255) Another aspect of the invention is described herein with reference to FIGS. **88-101**, according to an embodiment.

(256) Outer-cooled motor designs with external heat sinks, as described above in embodiments of this disclosure, dissipate heat generated by the motor to the outside environment. In many power tool applications, such designs result in heat sink outer surface temperatures tolerable for users to grip and operate. It has been found by the inventors, however, that in some power tool applications, particularly high voltage/high power applications, and/or power tool applications where the motor is required to run for extended periods of time, the outer surface of the heat sink may reach

temperature levels intolerable or dangerous to users to touch and operate.

(257) As previously discussed, one solution to alleviate this problem is to apply a coating of thermally non-conductive material selectively to outer extremities of the external heat sink. In an alternative embodiment, described herein, a sleeve (also referred to as a heatshield) is provided outside the heat sink with an airgap therebetween. The heatshield shields the user from high temperature of the heat sink, while providing an air gap for proper external cooling of the heat sink, as described herein in detail.

(258) FIG. 88 depicts a side view of an exemplary power tool **1200** having a motor assembly **1300** provided within an outer heatshield **1220**. While power tool **1200** in a grinder by way of example, it will be appreciated that the teachings of this disclosure is merely exemplary, and the power tool of this invention could be any type of cordless or corded power tool, including but not limited to, a drill, impact driver, hammer, hammer drill, circular saw, reciprocating saw, multi-tool, or any similar power tool constructed in accordance with the teachings of this disclosure.

(259) In an embodiment, power tool **1200** may include a handle **1202** disposed on one side of the motor assembly **1300** (and heatshield **1220**), and a gear case **1204** disposed on another side of the motor assembly **1300** (and heatshield **1220**) opposite the handle **1202**. In an embodiment, a battery pack **1206** is removably mounted to the end of the handle **1202**. A trigger mechanism **1208** is also mounted on the handle **1202**. In an embodiment, the handle **1202** houses a controller and other electronics (not shown) for driving the motor assembly **1300**. In an embodiment, the motor assembly **1300** rotatably drives a motor spindle (not shown) within the gear case **1204**, which in turns causes rotation of output spindle **1210**.

(260) FIGS. 89 and 90 depict front and rear perspective views of an exemplary motor assembly **1300** provided within a heatshield **1220**, according to an embodiment. FIGS. 91 and 92 depict front and rear perspective exploded views of the motor assembly **1300** with stator **1320** and heat sink **1302** provided within the heatshield **1220**, according to an embodiment.

(261) According to an embodiment, motor assembly **1300** includes mostly the same features as motor assembly **900** of FIGS. 49-52. In summary, in an embodiment, motor assembly **1300** includes a rotor **1310** having a rotor shaft **1312** and a rotor lamination stack **1314** housing a series of permanent magnets, front and rear bearings **1316a** and **1316b**, and a sense magnet ring **1352**. The motor assembly **1300** also includes a stator **1320** having segmented stator windings **1322** received within an outer heat sink **1302**. In an embodiment, circuit board **1306** includes positional sensors (not shown) for sensing the rotary position of the sense magnet ring **1352**, as well as conductive routings for connecting the stator windings **1322**. In an embodiment, a rotary fan **1304** having blades **1350** is mounted on one end of the rotor shaft **1312** to rotate with the rotor shaft **1312**. Front and rear end caps **1340** and **1330**, and a baffle **1356**, are also provided, as described later in detail.

(262) Referring to FIGS. 93-95, an exemplary arrangement of heat sink **1302** and heatshield **1220** is described herein. FIG. 93 depicts a perspective view of heatshield **1220** and heat sink **1302** housing the stator **1320** and circuit board **1306**. FIG. 94 depicts an axial view of heatshield **1220** alone. FIG. 95 depicts an axial view of heat sink **1302** disposed within heatshield **1220**.

(263) In an embodiment, heat sink **1302** is provided for external cooling of the stator **1320**, as described in previous embodiments. In an embodiment, heat sink **1302** includes a generally cylindrical body surrounding the stator **1320**. Heat sink **1302** includes a cylindrical opening that is sized to fittingly receive the stator **1320** therein, with the inner surface of the heat sink **1302** being in thermal and physical contact with the outer surface of the stator **1320**. Since heat sink **1302** covers substantially the entire periphery of the stator **1320**, it provides for optimal heat transfer from the stator **1320**. Heat sink **1302** may be constructed according to the embodiments described above, particularly a fully-enveloping heat sink include a series of outer longitudinal fins **1360** forming longitudinal air channels **1362** therebetween on its outer surface.

(264) In an embodiment, air channels **1362** are arranged to guide air flow generated by fan **1304** along the outer surface of heat sink **1302** parallel to the longitudinal axis of the motor **1300**. Fins

1360 increase the outer surface area of the heat sink **1302**, while passage of cooling air through the air channels **1362** provides for improved heat dissipation from the heat sink **1302**.

(265) In an embodiment, heatshield **1220** is sized to receive the heat sink **1302** therein with a small airgap in between. The airgap allows cooling air to travel along the outer surface of heat sink **1302**, including inside the air channels **1362** in the direction of the fan **1304**, while the heatshield **1220** shields the user from direct contact with the heat sink **1302**.

(266) In an embodiment, heatshield **1220** may be made of thermally insulating material such as plastic. Alternatively, and preferably, heatshield **1220** may be made of thermally conductive material such as metal to provide some heat transfer through the heatshield **1220**.

(267) In an embodiment, heatshield **1220** may include an annular body with a fully circular inner and outer surface. Alternatively, in an embodiment, heatshield **1220** may include longitudinal extruded channels **1222** projecting inwardly from its main body **1224**. Extruded channels **1222** of heatshield **1220** are sized to project inwardly into air channels **1362** of the heat sink **1302**. This arrangement provides a uniform air gap (i.e., of substantially consistent width) between the heat sink **1302** and heatshield **1220**. In an embodiment, heatshield **1220** may include non-extruded portions **1226** in addition to extruded channels **1222** as needed to improve the power tool **1200** ergonomics. The airgap between non-extruded portions **1226** and the heat sink **1302** is not uniform. In an embodiment, the airgap between the heat sink **1302** and heatshield **1220** results in a temperature differential of at least 10 degrees Celsius between the heat sink **1302** and heatshield **1220**, making the heatshield **1220** more tolerable for a user to touch.

(268) In an embodiment, heatshield **1220** is sized with outer geometry to provide a substantially uniform profile on the power tool **1200** between the handle **1202** and the gear case **1204**.

(269) FIG. **96** depicts an axial view of stator **1320** and heat sink **1302** disposed within heatshield **1220**. FIG. **97** depicts a zoomed-in axial view of stator **1320** and heat sink **1302** disposed within heatshield **1220**. As shown herein, in an embodiment, stator **1320** is provided with segmented design as described earlier in this disclosure, and includes a series of stator windings **1322** wound over discrete stator segments **1324**. Stator segments **1324** are radially constrained and held together by the heat sink **1302**, while the air gap between the heat sink **1302** and heatshield **1220** allows for air flow to cool the stator **1320** externally outside the heat sink **1302**.

(270) It should be noted that, while in this exemplary embodiment, the stator **1320** is segmented and fully enveloped by the heat sink **1302**, the teachings of this embodiment may be applied to other stator/heatsink designs. For example, the stator may be a self-contained assembly having a core, and the heat sink may partially or fully envelope the stator. Furthermore, the heat sink may be provided separately from the stator, or integrally with the stator core. In an embodiment, the heat sink may include outer fins, or may be provided with other geometry. The heatshield **1220** may be provided as an outer sleeve to any such stator/heatsink designs to provide an air channel outside the periphery of the heat sink for cooling the stator.

(271) Referring to the partially exploded view of FIG. **98**, and with continued reference to FIGS. **89-92**, in an embodiment, rear end cap **1330** is provided on one end of the motor assembly **1300** for mounting the motor assembly **1300** to the power tool handle **1202**. Rear end cap **1330** is sized to mate with an end of the heat sink **1302**. Rear end cap **1330** includes peripheral receptacles **1332** that receive a series of fasteners **1333** for fastening the rear end cap **1330** to the end of the heat sink **1302**. The fasteners **1333** may be fastened into corresponding threaded receptacles **1335** in the heat sink **1302**. Alternatively, the fasteners **1333** may be fastened into the heat sink air channels **1362**. Front end cap **1330** further includes a center bearing pocket **1334** that receives the rear bearing **1316a** of the rotor shaft **1312**. In an embodiment, a rear portion of the rear end cap **1330** is provided with a pair of passthrough bosses **1338** for attachment to the tool handle **1202**.

(272) In an embodiment, as shown in FIG. **98** and the zoomed-in perspective view of FIG. **99**, an outer periphery **1336** of the rear end cap **1330** is sized to be fittingly received inside the heatshield **1220** in contact with extruded channels **1222**. In an embodiment, outer periphery **1336** of the rear

end cap **1330** is provided with peripheral teeth **1337** arranged to come into contact with inner radial surfaces of the of the extruded channels **1222**. The diameter of the outer periphery **1336** of the rear end cap **1330**, or at the very least the diameter of the peripheral teeth **1337** of the rear end cap **1330**, is larger than the diameter of the heat sink **1302**. As the rear end cap **1330** is fastened to the heat sink **1302** by fasteners **1333**, the rear end cap **1330** maintains a radial small airgap between the heat sink **1302** and the heatshield **1220** on its end. This airgap, in an embodiment, may be in the range of 0.5 to 10 mm depending on the size of the motor and its thermal requirements. In an embodiment, openings **1339** formed between adjacent peripheral teeth **1337** and extruded channels **1222** form air inlets for airflow generated by the motor fan **1304** to enter the radial airgap between the heat sink **1302** and the heatshield **1220**.

(273) In an embodiment, openings **1339** may be aligned to receive air from within the handle **1202** of the power tool **1200** for improved cooling of the electronic components within the handle **1202**.

Alternatively, openings **1339** may be provided to suction in air from the outside environment.

(274) FIG. **100** depicts a rear zoomed-in axial view of the front end cap **1340**, according to an embodiment. FIG. **101** depicts a front axial view of the front end cap **1340**, according to an embodiment. As shown in these figures, and with continued reference to FIGS. **91** and **92**, in an embodiment, front end cap **1340** is provided on an end of the motor assembly **1300** opposite the rear end cap **1330**. Front end cap **1340** includes a main annular body **1341** provided with outer receptacles **1342** for fastening the front end cap **1340** to the gear case **1204** of the power tool **1200** via fasteners (not shown). Front end cap **1340** also includes a disc-shaped inner body **1343** arranged around a through-hole **1344** of the front end cap **1340**. Inner body **1343** is provided with inner receptacles **1345** for fastening the front end cap **1340** to the heat sink **1302** via fasteners **1347**. Fasteners **1347** may be fastened into corresponding threaded receptacles in the heat sink **1302**, or within the air channels **1362**. In an embodiment, through-hole **1344** is provided as a bearing support for front bearing **1316b** of the rotor shaft **1312**. Alternatively, through-hole **1344** may be a pass-through opening through which the rotor shaft **1312** freely extends and is piloted in the gear case **1204** via a driver **1317**.

(275) In an embodiment, front end cap **1340** may also be provided with a series of peripheral openings forming air inlets **1346a** between the main annular body **1341** and the inner body **1343**. Air inlets **1346a** are aligned with the radial airgap between the heat sink **1302** and the heatshield **1220** to receive air traversing through the radial airgap. Air inlets **1346a** on the rear side of the front end cap **1340** are guided through the front air cap **1340** to air conduits **1346b** on the front side of the front end cap **1340**. A baffle **1356** direct air from the air conduits **1346b** towards a middle portion of the fan **1304**. Fan **1304** includes blades **1355** that generate air flow that enters though the openings **1399** (between the heatshield **1220** and the rear end cap **1330**), passes axially through the radial air gap (between the heatshield **1220** and the heat sink **1302**), and exists the radial air gap through the air inlets **1346a**, and are guided from the air conduits **1346b** in the direction of the fan **1304**. In an embodiment, the air flow generated by the fan **1304** may be expelled out of air exhaust ports (not shown) in the gear case **1204**.

(276) In an embodiment, a rear face of the inner body **1343** may be provided with a series of recesses **1348** around the through-hole **1344**. Recesses **1348** are positioned where the ends of the stator windings **1322** facing the inner body **1343**, to account with tolerances associated with the stator windings **1322**.

(277) In an embodiment, on the rear face of the front end cap **1340** facing the heatshield **1220**, annular area **1357** between the inner body **1343** and the main annular body **1341** is axially recessed to receive the end of the heatshield **1220** therein. This annular area **1357**, which is formed by an outer periphery **1358** of the inner body **1343** and an inner rim **1364** of the main annular body **1341**, is sized to form-fittingly receive the end of the heatshield **1220** therein. The view of FIG. **100** depicts a cut-out portion of the end of the heatshield **1220** received within the annular area **1357** of the front end cap **1340**.

(278) In an embodiment, outer periphery **1358** of the inner body **1343** includes peripheral teeth **1366** arranged to come into contact with inner radial surfaces of the of the extruded channels **1222** of the heatshield **1220**. The diameter of the outer periphery **1358** of the inner body **1343**, or at the very least the diameter of the peripheral teeth **1366** of the inner body **1343**, is larger than the diameter of the heat sink **1302**. As the front end cap **1340** is fastened to the heat sink **1302** by fasteners **1347**, the front end cap **1340**, similarly to the rear end cap **1330**, maintains the radial small airgap between the heat sink **1302** and the heatshield **1220** on its end.

(279) In an embodiment, the heat sink **1302** and rear and front end caps **1330** and **1340** together substantially encapsulate and seal the stator **1320** and rotor **1310** from the outside environment, preventing or at the very least minimizing air flow, and in particular contaminated air flow, from entering the magnetic areas of the motor assembly **1300**. In an embodiment, additional sealants, such as for example, gaskets, adhesive, etc. may be applied as needed to the rear and front end caps **1330** and **1340** to form a water-sealed containment around the magnetic areas of the motor assembly **1300**.

(280) By form-fitting insertion of the stator segments **1324** within the heat sink **1302**, via for example press-fitting, the heat sink **1302** provides radial as well as axial constraint to hold the stator segments **1324** together around the rotor **1310** with a high level of precision. Moreover, securing the rear and front end caps **1330** and **1340** to the ends of the heat sink **1302** provides axial and radial retention between the rotor **1310** and the stator **1320** within the heat sink **1302**, while maintaining a small radial gap between the rotor **1310** and the stator **1320**. Disposition of the rear end cap **1340** and the inner body **1343** of the front end cap **1340** within the two ends of the heatshield **1220** also provides axial and radial retention between the heat sink **1302** and the heatshield **1220**, while maintaining the radial gap therebetween.

(281) The foregoing description of the embodiments has been provided for purposes of illustration and description. It is not intended to be exhaustive or to limit the disclosure. Individual elements or features of a particular embodiment are generally not limited to that particular embodiment, but, where applicable, are interchangeable and can be used in a selected embodiment, even if not specifically shown or described. The same may also be varied in many ways. Such variations are not to be regarded as a departure from the disclosure, and all such modifications are intended to be included within the scope of the disclosure.

(282) Example embodiments are provided so that this disclosure will be thorough, and will fully convey the scope to those who are skilled in the art. Numerous specific details are set forth such as examples of specific components, devices, and methods, to provide a thorough understanding of embodiments of the present disclosure. It will be apparent to those skilled in the art that specific details need not be employed, that example embodiments may be embodied in many different forms and that neither should be construed to limit the scope of the disclosure. In some example embodiments, well-known processes, well-known device structures, and well-known technologies are not described in detail.

(283) The terminology used herein is for the purpose of describing particular example embodiments only and is not intended to be limiting. As used herein, the singular forms “a,” “an,” and “the” may be intended to include the plural forms as well, unless the context clearly indicates otherwise. The terms “comprises,” “comprising,” “including,” and “having,” are inclusive and therefore specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof. The method steps, processes, and operations described herein are not to be construed as necessarily requiring their performance in the particular order discussed or illustrated, unless specifically identified as an order of performance. It is also to be understood that additional or alternative steps may be employed.

LIST OF NUMERICAL REFERENCES

(284) Power Tool **100** Tool Housing **102** Clam Shells **102a**, **102b** Motor housing **104** Handle

portion 106 Transmission assembly 108 Integrated switch module 110 Chuck 112 Trigger switch 114 Battery terminal 116 Battery receptacle 118 Heat Sink 120a, 120b Fan 130 Air intakes 140 Side openings 142a, 142b End cap 150 Motor assembly 200 BLDC motor 202 Rotor 210 Rotor shaft 212 Rotor lamination stack 214 Gear 216 Permeant magnets 218 Rotor bearings 218a, 218b Stator 220 Stator windings 222 Stator lamination stack 224 Stator end insulator 226 Front bearing support str. 230 Radial plate 232 Bearing pocket 234 Arcuate walls 236 Peripheral opening 237 Guide channel 238 Rear bearing support str. 240 Radial plate 242 Bearing pocket 244 Positional sensor board 246 Positional sensors 248 Sense magnet ring 250 Rotor end cap 252 Connector 254 Arcuate wall 256 Peripheral opening 257 Guide channel 258 Fastener 260 Rail guide 261 Inner surface 262 Outer surface 264 Fins 266 Air channels 268 Fan blades 270 Fan plate 272 First fan surface 274 Second fan surface 276 Air inlets 280 Radial wall 282 Side cap 284 Stator core 290 Stator teeth 292 Stator slots 294 Impact Driver 295 Gap 296 Hammer drill 297 Cutter 298 Reciprocating saw 299 Power Tool 300 Tool housing 302 Handle portion 304 Battery receptacle 306 Saw blade 308 Saw guard 310 Motor assembly 400 Heat sink 402 Fan 404 Electronic switch module 406 Rotor 410 Rotor shaft 412 Rotor lamination stack 414 Driver 416 Permeant magnets 418 Rotor bearings 419 Stator 420 Stator windings 422 Stator lamination stack 424 Stator end insulator 426 Motor terminals 428 Front end cap 430 Receptacles 432 Through-hole 434 Rear end cap 440 Air intakes 442 Peripheral wall 444 Fan blades 450 Sense magnet ring 452 Positional sensors 454 Longitudinal fins 460 Air channels 462 Piloting features 464 Radial wall 465 Bearing pocket 466 Opening 468 Mounting structure 470 Through-holes 472 Fasteners 474 Center receptacle 476 Power tool 500 Handle portion 502 Gear case 504 Radial air intakes 506 Front end 512 Rear end 514 Air vents 516 Reciprocating saw 520 Hammer 522 Motor assembly 600 Heat sink 602 Fins 604 Air channels 606 Switch receptacle 608 Rotor 610 Rotor shaft 612 Rotor lamination stack 614 Front bearing 616 Rear bearing 618 Stator 620 Stator lamination 624 Connector 626 Front bearing support str. 630 Front bearing pocket 632 Connector tab 634 Fasteners 636 Front seal 638 Rear bearing support str. 640 Rear bearing pocket 642 Positional sensor board 644 Fasteners 646 Rear seal 648 Fan 650 Fan blades 652 Rear end cap 660 Air inlets 662 Fasteners 664 Peripheral wall 666 Motor assembly 700 Heat sink 702 Fins 704 End portion 706 Recessed side surface 708 Coating 710 Front bearing support str. 730 Rear bearing support str. 760 Power tool 800 Handle 802 Gear case 804 Battery pack 806 Trigger mechanism 808 Output spindle 810 Motor assembly 900 Heat sink 902 Fan 904 Circuit board 906 Positional sensors 908 Rotor 910 Rotor shaft 912 Rotor lamination stack 914 Rotor bearing 916a, 916b Driver 917 Permeant magnets 918 Stator 920 Stator winding 922 Stator segment 924 Rear end cap 930 Receptacles 932 Bearing pocket 934 Outer periphery 936 Passthrough bosses 938 Front end cap 940 Outer receptacles 942 Through-hole 944 Inner receptacles 945 Air inlets 946 Recesses 948 Fan blades 950 Sense magnet ring 952 Longitudinal fins 960 Air channels 962 Segment core 970 Segment pole 972 Pole end 974 Legs 975 Insulating member 976 End insulators 977, 978 Winding terminal 979 Axial retainer 980 Opening 982 Opening 984 Space 986 Flat inner surface 988 Arch-shaped portion 990 First end 991 Flat edge portions 992 Second end 993 Notch 994 Recessed portion 995 Sectors 996 Arched portion 997 Flat side portion 998 Notches 999 Through-hole 1000 Notches 1002 Slots 1004 Stator assembly 1100 Heat sink 1102 Stator core 1110 Stator pole 1112 Pole tip 1114 Stator piece 1120 Stator windings 1122 Winding terminal 1124 Elongate opening 1126 Radial wall 1127 Side openings 1128 Thermal filler material 1129 Outer ring 1130 Slots 1132 Power tool 1200 Handle 1202 Gear case 1204 Battery pack 1206 Trigger mechanism 1208 Output spindle 1210 Heatshield 1220 Extruded channels 1222 Main body 1224 Non-extruded portions 1226 Motor assembly 1300 Heat sink 1302 Fan 1304 Circuit board 1306 Rotor 1310 Rotor shaft 1312 Rotor lamination stack 1314 Rotor bearing 1316a, 916b Driver 1317 Stator 1320 Stator winding 1322 Stator segment 1324 Rear end cap 1330 Receptacles 1332 Fasteners 1333 Bearing pocket 1334 Threaded receptacles 1335 Outer periphery 1336 Peripheral teeth 1337 Passthrough bosses 1338 Openings 1339 Front end cap 1340 Main annular body 1341 Outer receptacles 1342

Inner body **1343** Through-hole **1344** Inner receptacles **1345** Air inlets **1346a** Air conduits **1346b**
Fasteners **1347** Recesses **1348** Blades **1350** Sense magnet ring **1352** Baffle **1356** Annular area **1357**
Outer periphery **1358** Longitudinal fins **1360** Air channels **1362** Inner rim **1364** Peripheral teeth
1366

Claims

1. A power tool comprising: a motor; an output shaft driven by the motor along a longitudinal axis; a fan rotationally coupled to the motor to generate an airflow; a housing comprising two housing halves mated together to support the motor and forming a rear wall behind the motor along the longitudinal axis, wherein the rear wall includes a plurality of air intakes; an end cap attached to the housing adjacent the rear wall with an air gap therebetween, wherein at least a portion of the end cap does not overlap an outer circumferential surface of the housing so as to form a circumferential opening around the air gap, wherein the airflow generated by the fan suctions ambient air from an outside environment directly through the circumferential opening into the air gap in a substantially transverse direction relative to the longitudinal axis, and the airflow then passes through the plurality of air intakes to enter the housing in thermal contact with the motor.
2. The power tool of claim 1, wherein the end cap is oriented substantially along a plane that is perpendicular to the longitudinal axis.
3. The power tool of claim 1, wherein the fan is disposed between the motor and the rear wall of the housing.
4. The power tool of claim 1, wherein the plurality of air intakes is oriented radially around the longitudinal axis.
5. The power tool of claim 4, wherein the fan is located adjacent the rear wall of the housing and includes a plurality of fan blades facing the rear wall, wherein a distance between the plurality of air intakes and the longitudinal axis is less than a distance between the plurality of fan blades and the longitudinal axis, to allow the fan to repel the airflow entering through the plurality of air intakes radially outwardly.
6. The power tool of claim 1, wherein the end cap comprises two side caps extending axially to overlap opposite side portions of the housing.
7. The power tool of claim 1, wherein the motor comprises: a stator including a stator core and a plurality of stator windings connected in phases; a rotor rotatably disposed within the stator to magnetically interact with the plurality of stator windings; and at least one heat sink in contact with the stator core and supported by the housing.
8. The power tool of claim 7, wherein the heat sink comprises a plurality of fins forming a plurality of air channels therebetween extending longitudinally along an outer surface thereof, wherein the plurality of air channels is in fluid communication with the airflow.
9. The power tool of claim 8, wherein the end cap comprises two side caps extending axially to overlap opposite side portions of the heat sink to direct the airflow into the plurality of air channels.
10. The power tool of claim 1, wherein the end cap does not include any air intakes in its rear surface to allow entry of airflow.
11. A power tool comprising: a tool housing including a motor housing defining a longitudinal axis and having a rear wall formed at a rear end thereof, a handle portion extending from the motor housing in a direction traversal to the longitudinal axis, and a battery receptacle formed at an end of the handle portion opposite the motor housing; a motor disposed within the motor housing; an output assembly mounted forward of the motor housing and driven by the motor along the longitudinal axis; a fan rotationally coupled to the motor to generate an airflow; an end cap attached to the motor housing adjacent the rear wall with an air gap therebetween, wherein at least a portion of the end cap includes a diameter that is at most substantially equal to a diameter of the tool housing so as to form a circumferential opening around the air gap, wherein the airflow

generated by the fan enters through the circumferential opening into the air gap in a substantially radial direction, then passes through the plurality of air intakes to enter the housing in thermal contact with the motor.

12. The power tool of claim 11, wherein the end cap is oriented substantially along a plane that is perpendicular to the longitudinal axis.

13. The power tool of claim 11, wherein the fan is disposed between the motor and the rear wall of the housing.

14. The power tool of claim 11, wherein the plurality of air intakes is oriented radially around the longitudinal axis.

15. The power tool of claim 14, wherein the fan is located adjacent the rear wall of the housing and includes a plurality of fan blades facing the rear wall, wherein a distance between the plurality of air intakes and the longitudinal axis is less than a distance between the plurality of fan blades and the longitudinal axis, to allow the fan to repel the airflow entering through the plurality of air intakes radially outwardly.

16. The power tool of claim 11, wherein the end cap comprises two side caps extending axially to overlap opposite side portions of the housing.

17. The power tool of claim 11, wherein the motor comprises: a stator including a stator core and a plurality of stator windings connected in phases; a rotor rotatably disposed within the stator to magnetically interact with the plurality of stator windings; and at least one heat sink in contact with the stator core and supported by the housing.

18. The power tool of claim 17, wherein the heat sink comprises a plurality of fins forming a plurality of air channels therebetween extending longitudinally along an outer surface thereof, wherein the plurality of air channels is in fluid communication with the airflow.

19. The power tool of claim 18, wherein the end cap comprises two side caps extending axially to overlap opposite side portions of the heat sink to direct the airflow into the plurality of air channels.

20. The power tool of claim 11, wherein the end cap does not include any air intakes in its rear surface to allow entry of airflow.
