

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12413725
B2
September 09, 2025
Pfaff; Jonathan et al.

Coding using matrix based intra-prediction and secondary transforms

Abstract

An apparatus configured to select a predetermined intra prediction mode out of a plurality of intra-prediction modes which includes a first set of intra-prediction modes and a second set of matrix-based intra-prediction modes. The apparatus is configured to select a subset of one or more secondary transforms dependent on the predetermined intra prediction mode so that the subset is nonempty in case of the predetermined intra prediction mode being contained in the first set of intra-prediction modes or in the second set of matrix-based intra-prediction modes. The apparatus is configured to derive a transformed version of a prediction residual for a predetermined block, which is related to a spatial domain version of the prediction residual of the predetermined block via a transform defined by a concatenation of a primary transform and a predetermined secondary transform out of the subset of secondary transforms.

Inventors: Pfaff; Jonathan (Berlin, DE), Hinz; Tobias (Berlin, DE), Helle; Philipp (Berlin, DE), Merkle; Philipp (Berlin, DE), Stallenberger; Björn (Berlin, DE), Schäfer; Michael (Berlin, DE), Bross; Benjamin (Berlin, DE), Winken; Martin (Berlin, DE), Siekmann; Mischa (Berlin, DE), Schwarz; Heiko (Berlin, DE), Marpe; Detlev (Berlin, DE), Wiegand; Thomas (Berlin, DE)

Applicant: Fraunhofer-Gesellschaft zur Förderung der angewandten Forschung e.V.
(Munich, DE)

Family ID: 67070686

Assignee: Fraunhofer-Gesellschaft zur Förderung der angewandten Forschung e.V.
(Munich, DE)

Appl. No.: 17/559559

Filed: December 22, 2021

Prior Publication Data

Document Identifier
US 20220116606 A1

Publication Date
Apr. 14, 2022

Foreign Application Priority Data

EP 19182423 Jun. 25, 2019

Related U.S. Application Data

continuation parent-doc WO PCT/EP2020/067446 20200623 PENDING child-doc US 17559559

Publication Classification

Int. Cl.: H04N19/12 (20140101); H04N19/105 (20140101); H04N19/132 (20140101); H04N19/159 (20140101); H04N19/176 (20140101); H04N19/61 (20140101); H04N19/70 (20140101)

U.S. Cl.:

CPC H04N19/12 (20141101); H04N19/105 (20141101); H04N19/132 (20141101); H04N19/159 (20141101); H04N19/176 (20141101); H04N19/61 (20141101); H04N19/70 (20141101);

Field of Classification Search

CPC: H04N (19/12); H04N (19/61); H04N (19/105); H04N (19/132); H04N (19/159); H04N (19/176); H04N (19/70)

USPC: 375/240.02

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9451260	12/2015	Seregin et al.	N/A	N/A
9813727	12/2016	Lee et al.	N/A	N/A
2020/0053365	12/2019	Aono	N/A	H04N 19/18
2022/0030242	12/2021	Toma	N/A	H04N 19/61

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
I558169	12/2015	TW	N/A
I619381	12/2017	TW	N/A
I642299	12/2017	TW	N/A
I659645	12/2018	TW	N/A
2020211765	12/2019	WO	N/A
WO-2020226424	12/2019	WO	H04N 19/159

OTHER PUBLICATIONS

Wang, B. et al., CE3-related: A Unified MPM List for Intra Mode Coding, JVET-N0185 (version 7), ITU, Apr. 4, 2019, pp. 1-3, [online], [retrieved on Apr. 25, 2023], Retrieved from the Internet: URL: https://jvet-experts.org/doc_end_user/documents/14_Geneva/wg11/JVET-N0185-v7.zip , JVET-N0185.pdf. cited by applicant

Bossen, Frank, “JVET common test conditions and software reference configuration for SDR video”, JVET-K1010, Ljubljana, SI, Jul. 2018., 6 pp. cited by applicant

Bossen (Bossentech), F, et al., “Non-CE3: A unified luma intra mode list construction process”, No. JVET-M0528, (Jan. 11, 2019), 13. JVET Meeting; Jan. 9, 2019-Jan. 18, 2019; Marrakech; (The Joint Video Exploration Team of ISO/IEC JTC1/SC29/WG11 and ITU-T SG.16), 4 pp. cited by applicant

Helle, Philipp, et al., “CE3: Non-linear weighted intra prediction (tests 2.2.1 and 2.2.2)”, Joint Video Experts Team (JVET) of ITU-TSG 16 WP 3 and ISO/IEC JTC 1/SC 29/WG11, 12th Meeting: Macao, CN, Oct. 3-12, 2018, Doc> JVET-L0199-v2, 10 pp. cited by applicant

Jang, Hyeongmun, et al., “Adaptive NSST Kernel Size Selection”, 5. JVET Meeting; Jan. 12, 2017-Jan. 20, 2017; Geneva; (The Joint Video Exploration Team of ISO/IEC JTC1/SC29/WG11 and ITU-T SG.16); URL: <http://phenix.int-evry.fr/jvetz> (Jan. 13, 2017), No. JVET-E0047-v3, XP030150519 [A], 6 pp. cited by applicant

Koo, Moonmo, et al., “Reduced Secondary Transform (RST) Algorithm Description (JVET-N0193)”, “CE6: Reduced Secondary Transform (RST) (CE6-3.1)”, No. JVET-N0193, (Mar. 27, 2019), 14. JVET Meeting; Mar. 19, 2019-Mar. 27, 2019; Geneva; (The Joint Video Exploration Team of ISO/IEC JTC1/SC29/WG11 and ITU-T SG.16), 16 pp. cited by applicant

Pfaff, Jonathan, et al., “CE3: Affine linear weighted intra prediction (CE3-4.1, CE3-4.2)”, No. JVET-N0217, (Mar. 19, 2019), 14. JVET Meeting; Mar. 19, 2019-Mar. 27, 2019; Geneva; (The Joint Video Exploration Team of ISO/IEC JTC1/SC29/WG11 and ITU-T SG.16), 18 pp. cited by applicant

Pfaff, Jonathan, “Intra prediction modes based on neural networks”, 10. JVET Meeting; Apr. 10, 2018-Apr. 20, 2018; San Diego; (The Joint Video Exploration Team of ISO/IEC JTC1/SC29/WG11 and ITU-T SG.16); URL: <http://phenix.int-evry.fr/jvet/>, (Apr. 3, 2018), No. JVET-J0037, XP030151210 [X], 14 pp. cited by applicant

Sullivan, Gary J, “Overview of the High Efficiency Video Coding (HEVC) Standard”, IEEE Transactions on Circuits and Systems for Video Technology, US, (Dec. 1, 2012), vol. 22, No. 12, doi:10.1109/TCSVT.2012.2221191, ISSN 1051-8215, pp. 1649-1668, XP055388661 [X] DOI: <http://dx.doi.org/10.1109/TCSVT.2012.2221191>, Dec. 2012, 20 pp. cited by applicant

JVET-J0037-v1 Intra prediction modes based on neural networks, Jonathan Pfaff et. al., Joint Video Experts Team (JVET) of ITU-T SG 16 WP 3 and ISO/IEC JTC 1/SC 29/WG 11 10th Meeting: San Diego, US, Apr. 10-20, 2018. cited by applicant

JVET-N0193 CE6: Reduced Secondary Transform (RST) (CE6-3.1), Moonmo Koo et. al., Joint Video Experts Team (JVET) of ITU-T SG 16 WP 3 and ISO/IEC JTC 1/SC 29/WG 11 14th Meeting: Geneva, CH, Mar. 19-27, 2019. cited by applicant

Primary Examiner: Mung; On S

Attorney, Agent or Firm: Conley Rose, P.C.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of copending International Application No. PCT/EP2020/067446, filed Jun. 23, 2020, which is

incorporated herein by reference in its entirety, and additionally claims priority from European Application No. 19182423.4, filed Jun. 25, 2019, which is also incorporated herein by reference in its entirety.

(1) The present application concerns the field of matrix based intra-prediction and secondary transforms.

BACKGROUND OF THE INVENTION

(2) For the conventional intra prediction modes like the Planar mode, the DC mode and the angular modes, non-separable secondary transform (LFNST) is a tool used to transform the prediction residuals corresponding to these intra prediction modes. Here, a set S of transform sets is given such that each conventional intra prediction mode is associated with one of these transform sets. Then, at the decoder, it can be extracted from the bitstream whether on a given block LFNST is to be applied. If this is the case, one transform set out of the set S is given, depending on the intra prediction mode used on the current block, and, if this transform set consist of more than one transform, it can be extracted from the bitstream which transform T out of this set is to be used. Then, at the decoder, the transform T is applied as a secondary transform, meaning that it is applied to a subset of the residual transform coefficients of a separable primary transform. But the aforementioned secondary transforms are a priori only defined for the conventional intra prediction modes.

SUMMARY

(3) An embodiment may have an apparatus for decoding a predetermined block of a picture using intra-prediction, configured to select, based on the data stream, a predetermined intra prediction mode out of a plurality of intra-prediction modes which includes a first set of intra-prediction modes including a DC intra prediction mode and angular prediction modes, and a second set of matrix-based intra-prediction modes according to each of which a matrix-vector product between a vector derived from reference samples in a neighbourhood of the predetermined block and a prediction matrix associated with the respective matrix-based intra-prediction mode is used to obtain a prediction vector, on the basis of which samples of the predetermined block are predicted, derive a prediction signal for the predetermined block using the predetermined intra-prediction mode, select a subset of one or more secondary transforms out of a set of secondary transforms in a manner dependent on the predetermined intra prediction mode so that the subset is nonempty in case of the predetermined intra prediction mode being contained in the first set of intra-prediction modes and the predetermined intra prediction mode being contained in the second set of matrix-based intra-prediction modes, derive, from the data stream, a transformed version of a prediction residual for the predetermined block, which is related to a spatial domain version of the prediction residual of the predetermined block via a transform defined by a concatenation of a primary transform and a predetermined secondary transform out of the subset of secondary transforms applied onto a subset of coefficients of the primary transform, in case of the predetermined intra prediction mode being contained in the first set of intra-prediction modes and in case of the predetermined intra prediction mode being contained in the second set of matrix-based intra-prediction modes, reconstruct the predetermined block using the prediction signal and the prediction residual for the predetermined block.

(4) Another embodiment may have an apparatus for encoding a predetermined block of a picture using intra-prediction, configured to select a predetermined intra prediction mode out of a plurality of intra-prediction modes which includes a first set of intra-prediction modes including a DC intra prediction mode and angular prediction modes, and a second set of matrix-based intra-prediction modes according to each of which a matrix-vector product between a vector derived from reference samples in a neighbourhood of the predetermined block and a prediction matrix associated with the respective matrix-based intra-prediction mode is used to obtain a prediction vector, on the basis of which samples of the predetermined block are predicted, signal the predetermined intra prediction

mode in the data stream; derive a prediction signal for the predetermined block using the predetermined intra-prediction mode, select a subset of one or more secondary transforms out of a set of secondary transforms in a manner dependent on the predetermined intra prediction mode so that the subset is nonempty in case of the predetermined intra prediction mode being contained in the first set of intra-prediction modes and the predetermined intra prediction mode being contained in the second set of matrix-based intra-prediction modes, encode, into the data stream, a transformed version of a prediction residual for the predetermined block, which is related to a spatial domain version of the prediction residual of the predetermined block via a transform defined by a concatenation of a primary transform and a predetermined secondary transform out of the subset of secondary transforms applied onto a subset of coefficients of the primary transform, in case of the predetermined intra prediction mode being contained in the first set of intra-prediction modes and in case of the predetermined intra prediction mode being contained in the second set of matrix-based intra-prediction modes, wherein the predetermined block is reconstructable using the prediction signal and the prediction residual for the predetermined block.

(5) According to another embodiment, a method for decoding a predetermined block of a picture using intra-prediction may have the steps of: selecting, based on the data stream, a predetermined intra prediction mode out of a plurality of intra-prediction modes which includes a first set of intra-prediction modes including a DC intra prediction mode and angular prediction modes, and a second set of matrix-based intra-prediction modes according to each of which a matrix-vector product between a vector derived from reference samples in a neighbourhood of the predetermined block and a prediction matrix associated with the respective matrix-based intra-prediction mode is used to obtain a prediction vector, on the basis of which samples of the predetermined block are predicted, deriving a prediction signal for the predetermined block using the predetermined intra-prediction mode, selecting a subset of one or more secondary transforms out of a set of secondary transforms in a manner dependent on the predetermined intra prediction mode so that the subset is nonempty in case of the predetermined intra prediction mode being contained in the first set of intra-prediction modes and the predetermined intra prediction mode being contained in the second set of matrix-based intra-prediction modes, deriving, from the data stream, a transformed version of a prediction residual for the predetermined block, which is related to a spatial domain version of the prediction residual of the predetermined block via a transform defined by a concatenation of a primary transform and a predetermined secondary transform out of the subset of secondary transforms applied onto a subset of coefficients of the primary transform, in case of the predetermined intra prediction mode being contained in the first set of intra-prediction modes and in case of the predetermined intra prediction mode being contained in the second set of matrix-based intra-prediction modes, reconstructing the predetermined block using the prediction signal and the prediction residual for the predetermined block.

(6) According to another embodiment, a method for encoding a predetermined block of a picture using intra-prediction may have the steps of: selecting a predetermined intra prediction mode out of a plurality of intra-prediction modes which includes a first set of intra-prediction modes including a DC intra prediction mode and angular prediction modes, and a second set of matrix-based intra-prediction modes according to each of which a matrix-vector product between a vector derived from reference samples in a neighbourhood of the predetermined block and a prediction matrix associated with the respective matrix-based intra-prediction mode is used to obtain a prediction vector, on the basis of which samples of the predetermined block are predicted, signalling the predetermined intra prediction mode in the data stream; deriving a prediction signal for the predetermined block using the predetermined intra-prediction mode, selecting a subset of one or more secondary transforms out of a set of secondary transforms in a manner dependent on the predetermined intra prediction mode so that the subset is nonempty in case of the predetermined intra prediction mode being contained in the first set of intra-prediction modes and the predetermined intra prediction mode being contained in the second set of matrix-based intra-

prediction modes, encoding, into the data stream, a transformed version of a prediction residual for the predetermined block, which is related to a spatial domain version of the prediction residual of the predetermined block via a transform defined by a concatenation of a primary transform and a predetermined secondary transform out of the subset of secondary transforms applied onto a subset of coefficients of the primary transform, in case of the predetermined intra prediction mode being contained in the first set of intra-prediction modes and in case of the predetermined intra prediction mode being contained in the second set of matrix-based intra-prediction modes, wherein the predetermined block is reconstructable using the prediction signal and the prediction residual for the predetermined block.

(7) Another embodiment may have a data stream having a picture encoded therein using the inventive method for encoding.

(8) Another embodiment may have a non-transitory digital storage medium having a computer program stored thereon to perform the inventive methods, when said computer program is run by a computer.

(9) In accordance with a first aspect of the present invention, the inventors of the present application realized that one problem encountered when trying to associate secondary transforms with matrix-based intra prediction modes stems from the fact that a provision of specific secondary transforms for each MIP mode may be too costly in terms of the memory requirement to additionally store extra transforms. According to the first aspect of the present application, this difficulty is overcome by selecting a subset of one or more secondary transforms out of a set of secondary transforms comprising transforms associated with matrix-based intra prediction modes and non-matrix-based intra prediction modes. The secondary transforms in the set of secondary transforms may be defined for one or more prediction modes, which reduces a needed memory capacity for the set of secondary transforms. Transforms defined for planar intra-prediction modes and/or transforms defined for DC intra-prediction modes may also be selectable for matrix-based intra prediction modes. With the specific selection of the subset of secondary transforms for a matrix-based intra prediction mode it is possible to increase a coding efficiency, although a bit stream and thus a signalization cost may be increased due to additional syntax elements needed for blocks associated with matrix-based intra prediction modes to indicate a usage of a secondary transform.

(10) Accordingly, in accordance with a first aspect of the present application, an apparatus, i.e. a decoder, for decoding a predetermined block of a picture using intra-prediction, is configured to select, based on the data stream, a predetermined intra prediction mode out of a plurality of intra-prediction modes which comprises a first set of intra-prediction modes and a second set of matrix-based intra-prediction modes. The first set of intra-prediction modes comprises a DC intra prediction mode and angular prediction modes and optionally a planar intra prediction mode. If a matrix-based intra-prediction mode out of the second set is selected as the predetermined intra prediction mode, the decoder is configured to use a matrix-vector product between a vector derived from reference samples in a neighbourhood of the predetermined block and use a prediction matrix associated with the respective matrix-based intra-prediction mode to obtain a prediction vector, on the basis of which the decoder is configured to predict samples of the predetermined block. The decoder is configured to derive a prediction signal for the predetermined block using the predetermined intra-prediction mode and select a subset of one or more secondary transforms out of a set of secondary transforms in a manner dependent on the predetermined intra prediction mode so that the subset is nonempty in case of the predetermined intra prediction mode being contained in the first set of intra-prediction modes and in case of the predetermined intra prediction mode being contained in the second set of matrix-based intra-prediction modes. The first set and the second set define intra-prediction modes, for which a secondary transform is available. Thus for the predetermined intra-prediction mode selected out of the first set or out of the second set, the decoder is configured to select the subset of one or more secondary transforms out of the set of

secondary transforms specifically associated with the selected predetermined intra-prediction mode. Additionally, the decoder is configured to derive, from the data stream, a transformed version of a prediction residual for the predetermined block, which is related to a spatial domain version of the prediction residual of the predetermined block via a transform defined by a concatenation of a primary transform and a predetermined secondary transform out of the subset of secondary transforms applied onto a subset of coefficients of the primary transform, in case of the predetermined intra prediction mode being contained in the first set of intra-prediction modes and in case of the predetermined intra prediction mode being contained in the second set of matrix-based intra-prediction modes. The primary transform, for example, is set by default and the predetermined secondary transform, for example, is selected out of the subset of secondary transforms by the decoder. The decoder may be configured to select the predetermined secondary transform out of the subset of secondary transforms by deriving a secondary-transform-indicating syntax element from the data stream. The decoder is configured to reconstruct the predetermined block using the prediction signal and the prediction residual for the predetermined block.

(11) In accordance with a first aspect of the present application, parallel to the decoder an apparatus, i.e. an encoder, for encoding a predetermined block of a picture using intra-prediction, is configured to select a predetermined intra prediction mode out of a plurality of intra-prediction modes which comprises a first set of intra-prediction modes comprising a DC intra prediction mode and angular prediction modes and optionally a planar intra prediction mode, and a second set of matrix-based intra-prediction modes according to each of which a matrix-vector product between a vector derived from reference samples in a neighbourhood of the predetermined block and a prediction matrix associated with the respective matrix-based intra-prediction mode is used to obtain a prediction vector, on the basis of which samples of the predetermined block are predicted. The encoder is configured to signal the predetermined intra prediction mode in the data stream and derive a prediction signal for the predetermined block using the predetermined intra-prediction mode. Additionally, the encoder is configured to select a subset of one or more secondary transforms out of a set of secondary transforms in a manner dependent on the predetermined intra prediction mode so that the subset is nonempty in case of the predetermined intra prediction mode being contained in the first set of intra-prediction modes and in case of the predetermined intra prediction mode being contained in the second set of matrix-based intra-prediction modes. The encoder is configured to encode, into the data stream, a transformed version of a prediction residual for the predetermined block, which is related to a spatial domain version of the prediction residual of the predetermined block via a transform defined by a concatenation of a primary transform and a predetermined secondary transform out of the subset of secondary transforms applied onto a subset of coefficients of the primary transform, in case of the predetermined intra prediction mode being contained in the first set of intra-prediction modes and in case of the predetermined intra prediction mode being contained in the second set of matrix-based intra-prediction modes. The predetermined block is reconstructable using the prediction signal and the prediction residual for the predetermined block.

(12) According to an embodiment, the decoder/encoder is configured to select the subset of one or more secondary transforms out of the set of secondary transforms in a manner dependent on the predetermined intra prediction mode so that each secondary transform of the set of secondary transforms is contained in the subset of one or more secondary transforms selected for at least one of the intra-prediction modes within the first and second sets. For one or more intra-prediction modes within the first set or within the second set, the respective selected subset may comprise all secondary transforms of the set of secondary transforms.

(13) According to an embodiment, the decoder/encoder is configured to select a subset of one or more secondary transforms out of a set of secondary transforms in a manner dependent on the predetermined intra prediction mode so that each secondary transform of each subset of secondary transforms selected for any matrix-based intra-prediction mode is contained by a subset of

secondary transforms selected for at least one intra-prediction mode within the first set not belonging to the angular prediction modes. A subset selected for a matrix-based intra-prediction mode may contain secondary transforms associated with one or more non-angular intra-prediction modes within the first set, like the DC intra prediction mode and/or the planar intra prediction mode. Thus the secondary transforms out of the set of secondary transforms can be part of more than one subset of one or more secondary transforms. No additional secondary transforms only usable for blocks with the predetermined intra-prediction mode being a matrix-based intra-prediction mode have to be contained in the set of secondary transforms. For a predetermined block with the predetermined intra-prediction mode being a matrix-based intra-prediction mode, the decoder/encoder is configured to select the same secondary transforms out of the set of secondary transforms as for the predetermined intra-prediction mode being a non-angular prediction mode out of the first set. A subset selected for a matrix-based intra-prediction mode may be equal to a subset selected for an intra-prediction mode within the first set not belonging to the angular prediction modes or may contain some secondary transforms of a subset selected for an intra-prediction mode within the first set not belonging to the angular prediction modes or may contain some or all secondary transforms of two or more subsets selected for intra-prediction modes within the first set not belonging to the angular prediction modes.

(14) Methods for encoding or decoding are based on the same considerations as the above-described apparatuses for encoding or decoding. The methods can, by the way, be completed with all features and functionalities, which are also described with regard to the apparatuses for encoding or decoding.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Embodiments of the present invention will be detailed subsequently referring to the appended drawings, in which:
- (2) FIG. 1 shows an embodiment of an encoding into a data stream;
- (3) FIG. 2 shows an embodiment of an encoder;
- (4) FIG. 3 shows an embodiment of a reconstruction of a picture;
- (5) FIG. 4 shows an embodiment of a decoder;
- (6) FIG. 5 shows schematic diagram of a prediction of a block for encoding and/or decoding, according to an embodiment;
- (7) FIG. 6 shows a matrix operation for a prediction of a block for encoding and/or decoding according to an embodiment;
- (8) FIG. 7.1 shows a prediction of a block with a reduced sample value vector according to an embodiment;
- (9) FIG. 7.2 shows a prediction of a block using an interpolation of samples according to an embodiment;
- (10) FIG. 7.3 shows a prediction of a block with a reduced sample value vector, wherein only some boundary samples are averaged, according to an embodiment;
- (11) FIG. 7.4 shows a prediction of a block with a reduced sample value vector, wherein groups of four boundary samples are averaged, according to an embodiment;
- (12) FIG. 8 shows matrix operations performed by an apparatus according to an embodiment;
- (13) FIG. 9a-c show detailed matrix operations performed by an apparatus according to an embodiment;
- (14) FIG. 10 shows detailed matrix operations performed by an apparatus using offset and scaling parameters, according to an embodiment;
- (15) FIG. 11 shows detailed matrix operations performed by an apparatus using offset and scaling

- parameters, according to a different embodiment;
- (16) FIG. 12 shows a schematic diagram with details of an intra-prediction of a predetermined block using a prediction mode out of a most probable mode list, according to an embodiment;
- (17) FIG. 13 shows a schematic diagram of a decoding of a predetermined block using a secondary transform, according to an embodiment;
- (18) FIG. 14 shows a schematic diagram of an application of a primary transform and a secondary transform, according to an embodiment;
- (19) FIG. 15 shows a schematic diagram of a selection of a subset of secondary transforms, according to an embodiment;
- (20) FIG. 16 shows a schematic diagram of a predetermined block with a non-zero transform domain area, according to an embodiment;
- (21) FIG. 17 shows a block diagram of a method for decoding a predetermined block according to an embodiment;
- (22) FIG. 18 shows a block diagram of a method for encoding a predetermined block according to an embodiment; and
- (23) FIGS. 19a to 19d show a syntax element portion of a data stream.

DETAILED DESCRIPTION OF THE INVENTION

- (24) Equal or equivalent elements or elements with equal or equivalent functionality are denoted in the following description by equal or equivalent reference numerals even if occurring in different figures.
- (25) In the following description, a plurality of details is set forth to provide a more throughout explanation of embodiments of the present invention. However, it will be apparent to those skilled in the art that embodiments of the present invention may be practiced without these specific details. In other instances, well-known structures and devices are shown in block diagram form rather than in detail in order to avoid obscuring embodiments of the present invention. In addition, features of the different embodiments described herein after may be combined with each other, unless specifically noted otherwise.

1 INTRODUCTION

- (26) In the following, different inventive examples, embodiments and aspects will be described. At least some of these examples, embodiments and aspects refer, inter alia, to methods and/or apparatus for video coding and/or for performing intra Predictions e.g. using linear or affine transforms with neighbouring sample reduction and/or for optimizing video delivery (e.g., broadcast, streaming, file playback, etc.), e.g., for video applications and/or for virtual reality applications.
- (27) Further, examples, embodiments and aspects may refer to High Efficiency Video Coding (HEVC) or successors. Also, further embodiments, examples and aspects will be defined by the enclosed claims.
- (28) It should be noted that any embodiments, examples and aspects as defined by the claims can be supplemented by any of the details (features and functionalities) described in the following chapters.
- (29) Also, the embodiments, examples and aspects described in the following chapters can be used individually, and can also be supplemented by any of the features in another chapter, or by any feature included in the claims.
- (30) Also, it should be noted that individual, examples, embodiments and aspects described herein can be used individually or in combination. Thus, details can be added to each of said individual aspects without adding details to another one of said examples, embodiments and aspects.
- (31) It should also be noted that the present disclosure describes, explicitly or implicitly, features of decoding and/or encoding system and/or method.
- (32) Moreover, features and functionalities disclosed herein relating to a method can also be used in an apparatus. Furthermore, any features and functionalities disclosed herein with respect to an

apparatus can also be used in a corresponding method. In other words, the methods disclosed herein can be supplemented by any of the features and functionalities described with respect to the apparatuses.

(33) Also, any of the features and functionalities described herein can be implemented in hardware or in software, or using a combination of hardware and software, as will be described in the section “implementation alternatives”.

(34) Moreover, any of the features described in parentheses (“(. . .)” or “[. . .]”) may be considered as optional in some examples, embodiments, or aspects.

2 ENCODERS, DECODERS

(35) In the following, various examples are described which may assist in achieving a more effective compression when using block-based prediction. Some examples achieve high compression efficiency by spending a set of intra-prediction modes. The latter ones may be added to other intra-prediction modes heuristically designed, for instance, or may be provided exclusively. And even other examples make use of both of the just-discussed specialties. As a variation of these embodiments it may be, however, that intra prediction is turned into an inter prediction by using reference samples in another picture instead.

(36) In order to ease the understanding of the following examples of the present application, the description starts with a presentation of possible encoders and decoders fitting thereto into which the subsequently outlined examples of the present application could be built. FIG. 1 shows an apparatus for block-wise encoding a picture **10** into a datastream **12**. The apparatus is indicated using reference sign **14** and may be a still picture encoder or a video encoder. In other words, picture **10** may be a current picture out of a video **16** when the encoder **14** is configured to encode video **16** including picture **10** into datastream **12**, or encoder **14** may encode picture **10** into datastream **12** exclusively.

(37) As mentioned, encoder **14** performs the encoding in a block-wise manner or block-base. To this, encoder **14** subdivides picture **10** into blocks, units of which encoder **14** encodes picture **10** into datastream **12**. Examples of possible subdivisions of picture **10** into blocks **18** are set out in more detail below. Generally, the subdivision may end-up into blocks **18** of constant size such as an array of blocks arranged in rows and columns or into blocks **18** of different block sizes such as by use of a hierarchical multi-tree subdivision with starting the multi-tree subdivision from the whole picture area of picture **10** or from a pre-partitioning of picture **10** into an array of tree blocks wherein these examples shall not be treated as excluding other possible ways of subdividing picture **10** into blocks **18**.

(38) Further, encoder **14** is a predictive encoder configured to predictively encode picture **10** into datastream **12**. For a certain block **18** this means that encoder **14** determines a prediction signal for block **18** and encodes the prediction residual, i.e. the prediction error at which the prediction signal deviates from the actual picture content within block **18**, into datastream **12**.

(39) Encoder **14** may support different prediction modes so as to derive the prediction signal for a certain block **18**. The prediction modes, which are of importance in the following examples, are intra-prediction modes according to which the inner of block **18** is predicted spatially from neighboring, already encoded samples of picture **10**. The encoding of picture **10** into datastream **12** and, accordingly, the corresponding decoding procedure, may be based on a certain coding order **20** defined among blocks **18**. For instance, the coding order **20** may traverse blocks **18** in a raster scan order such as row-wise from top to bottom with traversing each row from left to right, for instance. In case of hierarchical multi-tree based subdivision, raster scan ordering may be applied within each hierarchy level, wherein a depth-first traversal order may be applied, i.e. leaf nodes within a block of a certain hierarchy level may precede blocks of the same hierarchy level having the same parent block according to coding order **20**. Depending on the coding order **20**, neighboring, already encoded samples of a block **18** may be located usually at one or more sides of block **18**. In case of the examples presented herein, for instance, neighboring, already encoded samples of a block **18**

are located to the top of, and to the left of block **18**.

(40) Intra-prediction modes may not be the only ones supported by encoder **14**. In case of encoder **14** being a video encoder, for instance, encoder **14** may also support inter-prediction modes according to which a block **18** is temporarily predicted from a previously encoded picture of video **16**. Such an inter-prediction mode may be a motion-compensated prediction mode according to which a motion vector is signaled for such a block **18** indicating a relative spatial offset of the portion from which the prediction signal of block **18** is to be derived as a copy. Additionally or alternatively, other non-intra-prediction modes may be available as well such as inter-prediction modes in case of encoder **14** being a multi-view encoder, or non-predictive modes according to which the inner of block **18** is coded as is, i.e. without any prediction.

(41) Before starting with focusing the description of the present application onto intra-prediction modes, a more specific example for a possible block-based encoder, i.e. for a possible implementation of encoder **14**, as described with respect to FIG. 2 with then presenting two corresponding examples for a decoder fitting to FIGS. 1 and 2, respectively.

(42) FIG. 2 shows a possible implementation of encoder **14** of FIG. 1, namely one where the encoder is configured to use transform coding for encoding the prediction residual although this is nearly an example and the present application is not restricted to that sort of prediction residual coding. According to FIG. 2, encoder **14** comprises a subtractor **22** configured to subtract from the inbound signal, i.e. picture **10** or, on a block basis, current block **18**, the corresponding prediction signal **24** so as to obtain the prediction residual signal **26** which is then encoded by a prediction residual encoder **28** into a datastream **12**. The prediction residual encoder **28** is composed of a lossy encoding stage **28a** and a lossless encoding stage **28b**. The lossy stage **28a** receives the prediction residual signal **26** and comprises a quantizer **30** which quantizes the samples of the prediction residual signal **26**. As already mentioned above, the present example uses transform coding of the prediction residual signal **26** and accordingly, the lossy encoding stage **28a** comprises a transform stage **32** connected between subtractor **22** and quantizer **30** so as to transform such a spectrally decomposed prediction residual **26** with a quantization of quantizer **30** taking place on the transformed coefficients where presenting the residual signal **26**. The transform may be a DCT, DST, FFT, Hadamard transform or the like. The transformed and quantized prediction residual signal **34** is then subject to lossless coding by the lossless encoding stage **28b** which is an entropy coder entropy coding quantized prediction residual signal **34** into datastream **12**. Encoder **14** further comprises the prediction residual signal reconstruction stage **36** connected to the output of quantizer **30** so as to reconstruct from the transformed and quantized prediction residual signal **34** the prediction residual signal in a manner also available at the decoder, i.e. taking the coding loss is quantizer **30** into account. To this end, the prediction residual reconstruction stage **36** comprises a dequantizer **38** which perform the inverse of the quantization of quantizer **30**, followed by an inverse transformer **40** which performs the inverse transformation relative to the transformation performed by transformer **32** such as the inverse of the spectral decomposition such as the inverse to any of the above-mentioned specific transformation examples. Encoder **14** comprises an adder **42** which adds the reconstructed prediction residual signal as output by inverse transformer **40** and the prediction signal **24** so as to output a reconstructed signal, i.e. reconstructed samples. This output is fed into a predictor **44** of encoder **14** which then determines the prediction signal **24** based thereon. It is predictor **44** which supports all the prediction modes already discussed above with respect to FIG. 1. FIG. 2 also illustrates that in case of encoder **14** being a video encoder, encoder **14** may also comprise an in-loop filter **46** with filters completely reconstructed pictures which, after having been filtered, form reference pictures for predictor **44** with respect to inter-predicted block.

(43) As already mentioned above, encoder **14** operates block-based. For the subsequent description, the block bases of interest is the one subdividing picture **10** into blocks for which the intra-prediction mode is selected out of a set or plurality of intra-prediction modes supported by predictor **44** or encoder **14**, respectively, and the selected intra-prediction mode performed

individually. Other sorts of blocks into which picture **10** is subdivided may, however, exist as well. For instance, the above-mentioned decision whether picture **10** is inter-coded or intra-coded may be done at a granularity or in units of blocks deviating from blocks **18**. For instance, the inter/intra mode decision may be performed at a level of coding blocks into which picture **10** is subdivided, and each coding block is subdivided into prediction blocks. Prediction blocks with encoding blocks for which it has been decided that intra-prediction is used, are each subdivided to an intra-prediction mode decision. To this, for each of these prediction blocks, it is decided as to which supported intra-prediction mode should be used for the respective prediction block. These prediction blocks will form blocks **18** which are of interest here. Prediction blocks within coding blocks associated with inter-prediction would be treated differently by predictor **44**. They would be inter-predicted from reference pictures by determining a motion vector and copying the prediction signal for this block from a location in the reference picture pointed to by the motion vector. Another block subdivisioning pertains the subdivisioning into transform blocks at units of which the transformations by transformer **32** and inverse transformer **40** are performed. Transformed blocks may, for instance, be the result of further subdivisioning coding blocks. Naturally, the examples set out herein should not be treated as being limiting and other examples exist as well. For the sake of completeness only, it is noted that the subdivisioning into coding blocks may, for instance, use multi-tree subdivisioning, and prediction blocks and/or transform blocks may be obtained by further subdividing coding blocks using multi-tree subdivisioning, as well.

(44) A decoder **54** or apparatus for block-wise decoding fitting to the encoder **14** of FIG. **1** is depicted in FIG. **3**. This decoder **54** does the opposite of encoder **14**, i.e. it decodes from datastream **12** picture **10** in a block-wise manner and supports, to this end, a plurality of intra-prediction modes. The decoder **54** may comprise a residual provider **156**, for example. All the other possibilities discussed above with respect to FIG. **1** are valid for the decoder **54**, too. To this, decoder **54** may be a still picture decoder or a video decoder and all the prediction modes and prediction possibilities are supported by decoder **54** as well. The difference between encoder **14** and decoder **54** lies, primarily, in the fact that encoder **14** chooses or selects coding decisions according to some optimization such as, for instance, in order to minimize some cost function which may depend on coding rate and/or coding distortion. One of these coding options or coding parameters may involve a selection of the intra-prediction mode to be used for a current block **18** among available or supported intra-prediction modes. The selected intra-prediction mode may then be signaled by encoder **14** for current block **18** within datastream **12** with decoder **54** redoing the selection using this signalization in datastream **12** for block **18**. Likewise, the subdivisioning of picture **10** into blocks **18** may be subject to optimization within encoder **14** and corresponding subdivision information may be conveyed within datastream **12** with decoder **54** recovering the subdivision of picture **10** into blocks **18** on the basis of the subdivision information. Summarizing the above, decoder **54** may be a predictive decoder operating on a block-basis and besides intra-prediction modes, decoder **54** may support other prediction modes such as inter-prediction modes in case of, for instance, decoder **54** being a video decoder. In decoding, decoder **54** may also use the coding order **20** discussed with respect to FIG. **1** and as this coding order **20** is obeyed both at encoder **14** and decoder **54**, the same neighboring samples are available for a current block **18** both at encoder **14** and decoder **54**. Accordingly, in order to avoid unnecessary repetition, the description of the mode of operation of encoder **14** shall also apply to decoder **54** as far the subdivision of picture **10** into blocks is concerned, for instance, as far as prediction is concerned and as far as the coding of the prediction residual is concerned. Differences lie in the fact that encoder **14** chooses, by optimization, some coding options or coding parameters and signals within, or inserts into, datastream **12** the coding parameters which are then derived from the datastream **12** by decoder **54** so as to redo the prediction, subdivision and so forth.

(45) FIG. **4** shows a possible implementation of the decoder **54** of FIG. **3**, namely one fitting to the implementation of encoder **14** of FIG. **1** as shown in FIG. **2**. As many elements of the encoder **54**

of FIG. 4 are the same as those occurring in the corresponding encoder of FIG. 2, the same reference signs, provided with an apostrophe, are used in FIG. 4 in order to indicate these elements. In particular, adder 42', optional in-loop filter 46' and predictor 44' are connected into a prediction loop in the same manner that they are in encoder of FIG. 2. The reconstructed, i.e. dequantized and retransformed prediction residual signal applied to adder 42' is derived by a sequence of entropy decoder 56 which inverses the entropy encoding of entropy encoder 28b, followed by the residual signal reconstruction stage 36' which is composed of dequantizer 38' and inverse transformer 40' just as it is the case on encoding side. The decoder's output is the reconstruction of picture 10. The reconstruction of picture 10 may be available directly at the output of adder 42' or, alternatively, at the output of in-loop filter 46'. Some post-filter may be arranged at the decoder's output in order to subject the reconstruction of picture 10 to some post-filtering in order to improve the picture quality, but this option is not depicted in FIG. 4. Again, with respect to FIG. 4 the description brought forward above with respect to FIG. 2 shall be valid for FIG. 4 as well with the exception that merely the encoder performs the optimization tasks and the associated decisions with respect to coding options. However, all the description with respect to block-subdivisioning, prediction, dequantization and retransforming is also valid for the decoder 54 of FIG. 4.

3 ALWIP (AFFINE LINEAR WEIGHTED INTRA PREDICTOR)

(46) Some non-limiting examples regarding ALWIP are herewith discussed, even if ALWIP is not necessary to embody the techniques discussed here.

(47) The present application is concerned, inter alia, with an improved block-based prediction mode concept for block-wise picture coding such as usable in a video codec such as HEVC or any successor of HEVC. The prediction mode may be an intra prediction mode, but theoretically the concepts described herein may be transferred onto inter prediction modes as well where the reference samples are part of another picture.

(48) A block-based prediction concept allowing for an efficient implementation such as a hardware friendly implementation is sought.

(49) This object is achieved by the subject-matter of the independent claims of the present application.

(50) Intra-prediction modes are widely used in picture and video coding. In video coding, intra-prediction modes compete with other prediction modes such as inter-prediction modes such as motion-compensated prediction modes. In intra-prediction modes, a current block is predicted on the basis of neighboring samples, i.e. samples already encoded as far as the encoder side is concerned, and already decoded as far as the decoder side is concerned. Neighboring sample values are extrapolated into the current block so as to form a prediction signal for the current block with the prediction residual being transmitted in the datastream for the current block. The better the prediction signal is, the lower the prediction residual is and, accordingly, a lower number of bits is needed to code the prediction residual.

(51) In order to be effective, several aspects should be taken into account in order to form an effective frame work for intra-prediction in a block-wise picture coding environment. For instance, the larger the number of intra-prediction modes supported by the codec, the larger the side information rate consumption is in order to signal the selection to the decoder. On the other hand, the set of supported intra-prediction modes should be able to provide a good prediction signal, i.e. a prediction signal resulting in a low prediction residual.

(52) In the following, there is disclosed—as a comparison embodiment or basis example—an apparatus (encoder or decoder) for block-wise decoding a picture from a data stream, the apparatus supporting at least one intra-prediction mode according to which the intra-prediction signal for a block of a predetermined size of the picture is determined by applying a first template of samples which neighbours the current block onto an affine linear predictor which, in the sequel, shall be called Affine Linear Weighted Intra Predictor (ALWIP).

(53) The apparatus may have at least one of the following properties (the same may apply to a

method or to another technique, e.g. implemented in a non-transitory storage unit storing instructions which, when executed by a processor, cause the processor to implement the method and/or to operate as the apparatus):

(54) 3.1 Predictors may be Complementary to other Predictors

(55) The intra-prediction modes which might form the subject of the implementational improvements described further below may be complementary to other intra prediction modes of the codec. Thus, they may be complementary to the DC-, Planar-, or Angular-Prediction modes defined in the HEVC codec resp. the JEM reference software. The latter three types of intra-prediction modes shall be called conventional intra prediction modes from now on. Thus, for a given block in intra mode, a flag needs to be parsed by the decoder which indicates whether one of the intra-prediction modes supported by the apparatus is to be used or not.

(56) 3.2 More Than One Proposed Prediction Modes

(57) The apparatus may contain more than one ALWIP mode. Thus, in case that the decoder knows that one of the ALWIP modes supported by the apparatus is to be used, the decoder needs to parse additional information that indicates which of the ALWIP modes supported by the apparatus is to be used.

(58) The signalization of the mode supported may have the property that the coding of some ALWIP modes may involve less bins than other ALWIP modes. Which of these modes involve less bins and which modes involve more bins may either depend on information that can be extracted from the already decoded bitstream or may be fixed in advance.

4 SOME ASPECTS

(59) FIG. 2 shows the decoder 54 for decoding a picture from a data stream 12. The decoder 54 may be configured to decode a predetermined block 18 of the picture. In particular, the predictor 44 may be configured for mapping a set of P neighboring samples neighboring the predetermined block 18 using a linear or affine linear transformation [e.g., ALWIP] onto a set of Q predicted values for samples of the predetermined block.

(60) As shown in FIG. 5, a predetermined block 18 comprises Q values to be predicted (which, at the end of the operations, will be “predicted values”). If the block 18 has M row and N columns, $Q=M \times N$. The Q values of the block 18 may be in the spatial domain (e.g., pixels) or in the transform domain (e.g., DCT, Discrete Wavelet Transform, etc.). The Q values of the block 18 may be predicted on the basis of P values taken from the neighboring blocks 17a-17c, which are in general adjacent to the block 18. The P values of the neighboring blocks 17a-17c may be in the closest positions (e.g., adjacent) to the block 18. The P values of the neighboring blocks 17a-17c have already been processed and predicted. The P values are indicated as values in portions 17'a-17'c, to distinguish them from the blocks they are part of (in some examples, 17'b is not used).

(61) As shown in FIG. 6, in order to perform the prediction, it is possible to operate with a first vector 17P with P entries (each entry being associated to a particular position in the neighboring portions 17'a-17'c), a second vector 18Q with Q entries (each entry being associated with a particular position in the block 18), and a mapping matrix 17M (each row being associated to a particular position in the block 18, each column being associated to a particular position in the neighboring portions 17'a-17'c). The mapping matrix 17M therefore performs the prediction of the P values of the neighboring portions 17'a-17'c into values of the block 18 according to a predetermined mode. The entries in the mapping matrix 17M may be therefore understood as weighting factors. In the following passages, we will refer to the neighboring portions of the boundary using the signs 17a-17c instead of 17'a-17'c.

(62) In the art there are known several conventional modes, such as DC mode, planar mode and 65 directional prediction modes. There may be known, for example, 67 modes.

(63) However, it has been noted that it is also possible to make use of different modes, which are here called linear or affine linear transformations. The linear or affine linear transformation comprises $P=Q$ weighting factors, among which at least $\frac{1}{4} P=Q$ weighting factors are non-zero

weighting values, which comprise, for each of the Q predicted values, a series of P weighting factors relating to the respective predicted value. The series, when being arranged one below the other according to a raster scan order among the samples of the predetermined block, form an envelope which is omnidirectionally non-linear.

(64) It is possible to map the P positions of the neighboring values **17'a-17'c** (template), the Q positions of the neighboring samples **17'a-17'c**, and at the values of the P*Q weighting factors of the matrix **17M**. A plane is an example of the envelope of the series for a DC transformation (which is a plane for the DC transformation). The envelope is evidently planar and therefore is excluded by the definition of the linear or affine linear transformation (ALWIP). Another example is a matrix resulting in an emulation of an angular mode: an envelope would be excluded from the ALWIP definition and would, frankly speaking, look like a hill leading obliquely from top to bottom along a direction in the P/Q plane. The planar mode and the 65 directional prediction modes would have different envelopes, which would however be linear in at least one direction, namely all directions for the exemplified DC, for example, and the hill direction for an angular mode, for example.

(65) To the contrary, the envelope of the linear or affine transformation will not be omnidirectionally linear. It has been understood that such kind of transformation may be optimal, in some situations, for performing the prediction for the block **18**. It has been noted that it is advantageous that at least $\frac{1}{4}$ of the weighting factors are different from zero (i.e., at least the 25% of the P*Q weighting factors are different from 0).

(66) The weighting factors may be unrelated with each other according to any regular mapping rule. Hence, a matrix **17M** may be such that the values of its entries have no apparent recognizable relationship. For example, the weighting factors cannot be described by any analytical or differential function.

(67) In examples, an ALWIP transformation is such that a mean of maxima of cross correlations between a first series of weighting factors relating to the respective predicted value, and a second series of weighting factors relating to predicted values other than the respective predicted value, or a reversed version of the latter series, whatever leads to a higher maximum, may be lower than a predetermined threshold (e.g., 0.2 or 0.3 or 0.35 or 0.1, e.g., a threshold in a range between 0.05 and 0.035). For example, for each couple (i.sub.1,i.sub.2) of rows of the ALWIP matrix **17M**, a cross correlation may be calculated by multiplying the P values of the i.sub.1.sup.th row with by the P values of the i.sub.2.sup.th row. For each obtained cross correlation, the maximum value may be obtained. Hence, a mean (average) may be obtained for the whole matrix **17M** (i.e. the maxima of the cross correlations in all combinations are averaged). After that, the threshold may be e.g., 0.2 or 0.3 or 0.35 or 0.1, e.g., a threshold in a range between 0.05 and 0.035.

(68) The P neighboring samples of blocks **17a-17c** may be located along a one-dimensional path extending along a border (e.g., **18c**, **18a**) of the predetermined block **18**. For each of the Q predicted values of the predetermined block **18**, the series of P weighting factors relating to the respective predicted value may be ordered in a manner traversing the one-dimensional path in a predetermined direction (e.g., from left to right, from top to down, etc.).

(69) In examples, the ALWIP matrix **17M** may be non-diagonal or non-block diagonal.

(70) An example of ALWIP matrix **17M** for predicting a 4×4 block **18** from 4 already predicted neighboring samples may be: { {37, 59, 77, 28}, {32, 92, 85, 25}, {31, 69, 100, 24}, {33, 36, 106, 29}, {24, 49, 104, 48}, {24, 21, 94, 59}, {29, 0, 80, 72}, {35, 2, 66, 84}, {32, 13, 35, 99}, {39, 11, 34, 103}, {45, 21, 34, 106}, {51, 24, 40, 105}, {50, 28, 43, 101}, {56, 32, 49, 101}, {61, 31, 53, 102}, {61, 32, 54, 100} }.

(71) (Here, {37, 59, 77, 28} is the first row; {32, 92, 85, 25} is the second row; and {61, 32, 54, 100} is the 16.sup.th row of the matrix **17M**.) Matrix **17M** has dimension 16×4 and includes 64 weighting factors (as a consequence of 16*4=64). This is because matrix **17M** has dimension Q×P, where Q=M*N, which is the number of samples of the block **18** to be predicted (block **18** is a 4×4 block), and P is the number of samples of the already predicted samples. Here, M=4, N=4, Q=16

(as a consequence of $M \cdot N = 4 \cdot 4 = 16$), $P=4$. The matrix is non-diagonal and non-block diagonal, and is not described by a particular rule.

(72) As can be seen, less than $\frac{1}{4}$ of the weighting factors are 0 (in the case of the matrix shown above, one weighting factor out of sixty-four is zero). The envelope formed by these values, when arranged one below the other one according to a raster scan order, form an envelope which is omnidirectionally non-linear.

(73) Even if the explanation above is mainly discussed with reference to a decoder (e.g., the decoder **54**), the same may be performed at the encoder (e.g., encoder **14**).

(74) In some examples, for each block size (in the set of block sizes), the ALWIP transformations of intra-prediction modes within the second set of intra-prediction modes for the respective block size are mutually different. In addition, or alternatively, a cardinality of the second set of intra-prediction modes for the block sizes in the set of block sizes may coincide, but the associated linear or affine linear transformations of intra-prediction modes within the second set of intra-prediction modes for different block sizes may be non-transferable onto each other by scaling.

(75) In some examples the ALWIP transformations may be defined in such a way that they have “nothing to share” with conventional transformations (e.g., the ALWIP transformations may have “nothing” to share with the corresponding conventional transformations, even though they have been mapped via one of the mappings above).

(76) In examples, ALWIP modes are used for both luma components and chroma components, but in other examples ALWIP modes are used for luma components but are not used for chroma components.

5 AFFINE LINEAR WEIGHTED INTRA PREDICTION MODES WITH ENCODER SPEEDUP (E.G., TEST CE3-1.2.1)

(77) 5.1 Description of a Method or Apparatus

(78) Affine linear weighted intra prediction (ALWIP) modes tested in CE3-1.2.1 may be the same as proposed in JVET-L0199 under test CE3-2.2.2, except for the following changes: Harmonization with multiple reference line (MRL) intra prediction, especially encoder estimation and signaling, i.e. MRL is not combined with ALWIP and transmitting an MRL index is restricted to non-ALWIP blocks. Subsampling now mandatory for all blocks $W \times H \geq 32 \times 32$ (was optional for 32×32 before); therefore, the additional test at the encoder and sending the subsampling flag has been removed. ALWIP for $64 \times N$ and $N \times 64$ blocks (with $N \leq 32$) has been added by downsampling to $32 \times N$ and $N \times 32$, respectively, and applying the corresponding ALWIP modes.

(79) Moreover, test CE3-1.2.1 includes the following encoder optimizations for ALWIP: Combined mode estimation: conventional and ALWIP modes use a shared Hadamard candidate list for full RD estimation, i.e. the ALWIP mode candidates are added to the same list as the conventional (and MRL) mode candidates based on the Hadamard cost. EMT intra fast and PB intra fast are supported for the combined mode list, with additional optimizations for reducing the number of full RD checks. Only MPMs of available left and above blocks are added to the list for full RD estimation for ALWIP, following the same approach as for conventional modes.

5.2 Complexity Assessment

(80) In Test CE3-1.2.1, excluding computations invoking the Discrete Cosine Transform, at most 12 multiplications per sample were needed to generate the prediction signals. Moreover, a total number of 136 492 parameters, each in 16 bits, were needed. This corresponds to 0.273 Megabyte of memory.

(81) 5.3 Experimental Results

(82) Evaluation of the test was performed according to the common test conditions JVET-J1010 [2], for the intra-only (AI) and random-access (RA) configurations with the VTM software version 3.0.1. The corresponding simulations were conducted on an Intel Xeon cluster (E5-2697A v4, AVX2 on, turbo boost off) with Linux OS and GCC 7.2.1 compiler.

(83) TABLE-US-00001 TABLE 1 Result of CE3-1.2.1 for VTM AI configuration Y U V enc time

dec time Class A1 -2.08% -1.68% -1.60% 155% 104% Class A2 -1.18% -0.90% -0.84% 153% 103% Class B -1.18% -0.84% -0.83% 155% 104% Class C -0.94% -0.63% -0.76% 148% 106% Class E -1.71% -1.28% -1.21% 154% 106% Overall -1.36% -1.02% -1.01% 153% 105% Class D -0.99% -0.61% -0.76% 145% 107% Class F -1.38% -1.23% -1.04% 147% 104% (optional)
(84) TABLE-US-00002 TABLE 2 Result of CE3-1.2.1 for VTM RA configuration Y U V enc time
dec time Class A1 -1.25% -1.80% -1.95% 113% 100% Class A2 -0.68% -0.54% -0.21% 111% 100% Class B -0.82% -0.72% -0.97% 113% 100% Class C -0.70% -0.79% -0.82% 113% 99% Class E Overall -0.85% -0.92% -0.98% 113% 100% Class D -0.65% -1.06% -0.51% 113% 102% Class F -1.07% -1.04% -0.96% 117% 99% (optional)

5.4 Affine Linear Weighted Intra Prediction with Complexity Reduction (e.g. Test CE3-1.2.2)

(85) The technique tested in CE2 is related to “Affine Linear Intra Predictions” described in JVET-L0199 [1], but simplifies it in terms of memory requirements and computational complexity: There may be only three different sets of prediction matrices (e.g. S.sub.0, S.sub.1, S.sub.2, see also below) and bias vectors (e.g. for providing offset values) covering all block shapes. As a consequence, the number of parameters is reduced to 14400 10-bit values, which is less memory than stored in a 128×128 CTU. The input and output size of the predictors is further reduced. Moreover, instead of transforming the boundary via DCT, averaging or downsampling may be performed to the boundary samples and the generation of the prediction signal may use linear interpolation instead of the inverse DCT. Consequently, a maximum of four multiplications per sample may be needed for generating the prediction signal.

6. EXAMPLES

(86) It is here discussed how to perform some predictions (e.g., as shown in FIG. 6) with ALWIP predictions.

(87) In principle, with reference to FIG. 6, in order to obtain the $Q=M*N$ values of a $M*N$ block **18** to be predicted, multiplications of the $Q*P$ samples of the $Q*P$ ALWIP prediction matrix **17M** by the P samples of the $P*1$ neighboring vector **17P** should be performed. Hence, in general, in order to obtain each of the $Q=M*N$ values of the $M*N$ block **18** to be predicted, at least $P=M+N$ value multiplications are needed.

(88) These multiplications have extremely unwanted effects. The dimension P of the boundary vector **17P** is in general dependent on the number $M+N$ of boundary samples (bins or pixels) **17a**, **17c** neighbouring (e.g. adjacent to) the $M*N$ block **18** to be predicted. This means that, if the size of block **18** to be predicted is large, the number $M+N$ of boundary pixels (**17a**, **17c**) is accordingly large, hence increasing the dimension $P=M+N$ of the $P*1$ boundary vector **17P**, and the length of each row of the $Q*P$ ALWIP prediction matrix **17M**, and accordingly, also the numbers of multiplications needed (in general terms, $Q=M*N=W*H$, where W (Width) is another symbol for N and H (Height) is another symbol for M ; P , in the case that the boundary vector is only formed by one row and/or one column of samples, is $P=M+N=H+W$).

(89) This problem is, in general, exacerbated by the fact that in microprocessor-based systems (or other digital processing systems), multiplications are, in general, power-consuming operations. It may be imagined that a large number of multiplications carried for an extremely high number of samples for a large number of blocks causes a waste of computational power, which is in general unwanted.

(90) Accordingly, it would be advantageous to reduce the number $Q*P$ of multiplications needed for predicting the $M*N$ block **18**.

(91) It has been understood that it is possible to somehow reduce the computational power needed for each intra-prediction of each block **18** to be predicted by intelligently choosing operations alternative to multiplications and which are easier to be processed.

(92) In particular, with reference to FIGS. 7.1-7.4, it has been understood that an encoder or decoder may predict a predetermined block (e.g. **18**) of the picture using a plurality of neighbouring samples (e.g. **17a**, **17c**), by reducing (e.g. at step **811**), (e.g. by averaging or

downsampling), the plurality of neighbouring samples (e.g. **17a**, **17c**) to obtain a reduced set of samples values lower, in number of samples, than compared to the plurality of neighbouring samples, subjecting (e.g. at step **812**) the reduced set of sample values to a linear or affine linear transformation to obtain predicted values for predetermined samples of the predetermined block. (93) In some cases, the decoder or encoder may also derive, e.g. by interpolation, prediction values for further samples of the predetermined block on the basis of the predicted values for the predetermined samples and the plurality of neighboring samples. Accordingly, an upsampling strategy may be obtained.

(94) In examples, it is possible to perform (e.g. at step **811**) some averages on the samples of the boundary **17**, so as to arrive at a reduced set **102** (FIGS. **7.1-7.4**) of samples with a reduced number of samples (at least one of the samples of the reduced number of samples **102** may be the average of two samples of the original boundary samples, or a selection of the original boundary samples). For example, if the original boundary has $P=M+N$ samples, the reduced set of samples may have $P_{\text{sub.red}}=M_{\text{sub.red}}+N_{\text{sub.red}}$, with at least one of $M_{\text{sub.red}}<M$ and $N_{\text{sub.red}}<N$, so that $P_{\text{sub.red}}<P$. Hence, the boundary vector **17P** which will be actually used for the prediction (e.g. at step **812b**) will not have $P \times 1$ entries, but $P_{\text{sub.red}} \times 1$ entries, with $P_{\text{sub.red}}<P$. Analogously, the ALWIP prediction matrix **17M** chosen for the prediction will not have $Q \times P$ dimension, but $Q \times P_{\text{sub.red}}$ (or $Q_{\text{sub.red}} \times P_{\text{sub.red}}$, see below) with a reduced number of elements of the matrix at least because $P_{\text{sub.red}}<P$ (by virtue of at least one of $M_{\text{sub.red}}<M$ and $N_{\text{sub.red}}<N$).

(95) In some examples (e.g. FIGS. **7.2**, **7.3**), it is even possible to further reduce the number of multiplications, if the block obtained by ALWIP (at step **812**) is a reduced block having size $M'_{\text{sub.red}} \times N'_{\text{sub.red}}$, with $M'_{\text{sub.red}}<M$ and/or $N'_{\text{sub.red}}<N$ (i.e. the samples directly predicted by ALWIP are less in number than the samples of the block **18** to be actually predicted). Thus, setting $Q_{\text{sub.red}}=M'_{\text{sub.red}} \times N'_{\text{sub.red}}$, this will bring to obtain an ALWIP prediction by using, instead of $Q \times P_{\text{sub.red}}$ multiplications, $Q_{\text{sub.red}} \times P_{\text{sub.red}}$ multiplications (with $Q_{\text{sub.red}} \times P_{\text{sub.red}} < Q \times P_{\text{sub.red}} < Q \times P$). This multiplication will predict a reduced block, with dimension $M'_{\text{sub.red}} \times N'_{\text{sub.red}}$. It will be notwithstanding possible to perform (e.g. at a subsequent step **813**) an upsampling (e.g., obtained by interpolation) from the reduced $M'_{\text{sub.red}} \times N'_{\text{sub.red}}$ predicted block into the final $M \times N$ predicted block.

(96) These techniques may be advantageous since, while the matrix multiplication involves a reduced number ($Q_{\text{sub.red}} \times P_{\text{sub.red}}$ or $Q \times P_{\text{sub.red}}$) of multiplications, both the initial reducing (e.g., averaging or downsampling) and the final transformation (e.g. interpolation) may be performed by reducing (or even avoiding) multiplications. For example, downsampling, averaging and/or interpolating may be performed (e.g. at steps **811** and/or **813**) by adopting non-computationally-power-demanding binary operations such as additions and shifting.

(97) Also, the addition is an extremely easy operation which can be easily performed without much computational effort.

(98) This shifting operation may be used, for example, for averaging two boundary samples and/or for interpolating two samples (support values) of the reduced predicted block (or taken from the boundary), to obtain the final predicted block. (For interpolation two sample values are needed. Within the block we have two predetermined values, but for interpolating the samples along the left and above border of the block we only have one predetermined value, as in FIG. **7.2**, therefore we use a boundary sample as a support value for interpolation.)

(99) A two-step procedure may be used, such as: first summing the values of the two samples; then halving (e.g., by right-shifting) the value of the sum.

(100) Alternatively, it is possible to: first halving (e.g., by left-shifting) the each of the samples; then summing the values of the two halved samples.

(101) Even easier operations may be performed when downsampling (e.g., at step **811**), as it is only needed to select one sample amount a group of samples (e.g., samples adjacent to each other).

(102) Hence, it is now possible to define technique(s) for reducing the number of multiplications to

be performed. Some of these techniques may be based, inter alia, on at least one of the following principles: Even if the block **18** to be actually predicted has size $M \times N$, block may be reduced (in at least one of the two dimensions) and an ALWIP matrix with reduced size $Q_{\text{sub.red}} \times P_{\text{sub.red}}$ with $Q_{\text{sub.red}} = M'_{\text{sub.red}} \times N'_{\text{sub.red}}$, $P_{\text{sub.red}} = N_{\text{sub.red}} + M_{\text{sub.red}}$, with $M'_{\text{sub.red}} < M$ and/or $N'_{\text{sub.red}} < N$ and/or $M_{\text{sub.red}} < M$ and/or $N_{\text{sub.red}} < N$) may be applied. Hence, the boundary vector **17P** will have size $P_{\text{sub.red}} \times 1$, implying only $P_{\text{sub.red}} < P$ multiplications (with $P_{\text{sub.red}} = M_{\text{sub.red}} + N_{\text{sub.red}}$ and $P = M + N$). The $P_{\text{sub.red}} \times 1$ boundary vector **17P** may be obtained easily from the original boundary **17**, e.g.: By downsampling (e.g. by choosing only some samples of the boundary); and/or By averaging multiple samples of the boundary (which may be easily obtained by addition and shifting, without multiplications). In addition or alternatively, instead of predicting by multiplication all the $Q = M \times N$ values of the block **18** to be predicted, it is possible to only predict a reduced block with reduced dimensions (e.g., $Q_{\text{sub.red}} = M'_{\text{sub.red}} \times N'_{\text{sub.red}}$ with $M'_{\text{sub.red}} < M$ and/or $N'_{\text{sub.red}} < N$). The remaining samples of the block **18** to be predicted will be obtained by interpolation, e.g. using the $Q_{\text{sub.red}}$ samples as support values for the remaining $Q - Q_{\text{sub.red}}$ values to be predicted.

(103) According to an example illustrated in FIG. 7.1, a 4×4 block **18** ($M=4$, $N=4$, $Q=M \times N=16$) is to be predicted and a neighborhood **17** of samples **17a** (a vertical row column with four already-predicted samples) and **17c** (a horizontal row with four already-predicted samples) have already been predicted at previous iterations (the neighborhoods **17a** and **17c** may be collectively indicated with **17**). A priori, by using the equation shown in FIG. 6, the prediction matrix **17M** should be a $Q \times P = 16 \times 8$ matrix (by virtue of $Q = M \times N = 4 \times 4$ and $P = M + N = 4 + 4 = 8$), and the boundary vector **17P** should have 8×1 dimension (by virtue of $P = 8$). However, this would drive to the necessity of performing 8 multiplications for each of the 16 samples of the 4×4 block **18** to be predicted, hence leading to the necessity of performing $16 \times 8 = 128$ multiplications in total. (It is noted that the average number of multiplications per sample is a good assessment of the computational complexity. For conventional intra-predictions, four multiplications per sample are needed and this increases the computational effort to be involved. Hence, it is possible to use this as an upper limit for ALWIP would ensures that the complexity is reasonable and does not exceed the complexity of conventional intra prediction.)

(104) Notwithstanding, it has been understood that, by using the present technique, it is possible to reduce, at step **811**, the number of samples **17a** and **17c** neighboring the block **18** to be predicted from P to $P_{\text{sub.red}} < P$. In particular, it has been understood that it is possible to average (e.g. at 100 in FIG. 7.1) boundary samples (**17a**, **17c**) which are adjacent to each other, to obtain a reduced boundary **102** with two horizontal rows and two vertical columns, hence operating as the block **18** were a 2×2 block (the reduced boundary being formed by averaged values). Alternatively, it is possible to perform a downsampling, hence selecting two samples for the row **17c** and two samples for the column **17a**. Hence, the horizontal row **17c**, instead of having the four original samples, is processed as having two samples (e.g. averaged samples), while the vertical column **17a**, originally having four samples, is processed as having two samples (e.g. averaged samples). It is also possible to understand that, after having subdivided the row **17c** and the column **17a** in groups **110** of two samples each, one single sample is maintained (e.g., the average of the samples of the group **110** or a simple choice among the samples of the group **110**). Accordingly, a so-called reduced set **102** of sample values is obtained, by virtue of the set **102** having only four samples ($M_{\text{sub.red}}=2$, $N_{\text{sub.red}}=2$, $P_{\text{sub.red}}=M_{\text{sub.red}}+N_{\text{sub.red}}=4$, with $P_{\text{sub.red}} < P$).

(105) It has been understood that it is possible to perform operations (such as the averaging or downsampling **100**) without carrying out too many multiplications at the processor-level: the averaging or downsampling **100** performed at step **811** may be simply obtained by the straightforward and computationally-non-power-consuming operations such as additions and shifts.

(106) It has been understood that, at this point, it is possible to subject the reduced set of sample values **102** to a linear or affine linear (ALWIP) transformation **19** (e.g., using a prediction matrix

such as the matrix **17M** of FIG. 6). In this case, the ALWIP transformation **19** directly maps the four samples **102** onto the sample values **104** of the block **18**. No interpolation is needed in the present case.

(107) In this case, the ALWIP matrix **17M** has dimension $Q \times P_{\text{sub.red}} = 16 \times 4$: this follows the fact that all the $Q=16$ samples of the block **18** to be predicted are directly obtained by ALWIP multiplication (no interpolation needed).

(108) Hence, at step **812a**, a suitable ALWIP matrix **17M** with dimension $Q \times P_{\text{sub.red}}$ is selected. The selection may at least partially be based, for example, on signalling from the datastream **12**. The selected ALWIP matrix **17M** may also be indicated with $A_{\text{sub.k}}$, where k may be understood as an index, which may be signalled in the datastream **12** (in some cases the matrix is also indicated as $A_{\text{sub.idx.sup.m}}$, see below). The selection may be performed according to the following scheme: for each dimension (e.g., pair of height/width of the block **18** to be predicted), an ALWIP matrix **17M** is chosen among, for example, one of the three sets of matrixes $S_{\text{sub.0}}$, $S_{\text{sub.1}}$, $S_{\text{sub.2}}$ (each of the three sets $S_{\text{sub.0}}$, $S_{\text{sub.1}}$, $S_{\text{sub.2}}$ may group a plurality of ALWIP matrixes **17M** of the same dimensions, and the ALWIP matrix to be chosen for the prediction will be one of them).

(109) At step **812b**, a multiplication between the selected $Q \times P_{\text{sub.red}}$ ALWIP matrix **17M** (also indicated as $A_{\text{sub.k}}$) and the $P_{\text{sub.red}} \times 1$ boundary vector **17P** is performed.

(110) At step **812c**, an offset value (e.g., $b_{\text{sub.k}}$) may be added, e.g. to all the obtained values **104** of the vector **18Q** obtained by ALWIP. The value of the offset ($b_{\text{sub.k}}$ or in some cases also indicated with $b_{\text{sub.1,2,3.sup.i}}$, see below) may be associated to the particular selected ALWIP matrix ($A_{\text{sub.k}}$), and may be based on an index (e.g., which may be signalled in the datastream **12**).

(111) Hence, a comparison between using the present technique and non-using the present technique is here resumed: Without the present technique: Block **18** to be predicted, the block having dimensions $M=4$, $N=4$; $Q=M \times N=4 \times 4=16$ values to be predicted; $P=M+N=4+4=8$ boundary samples $P=8$ multiplications for each of the $Q=16$ values to be predicted, a total number of $P \times Q=8 \times 16=128$ multiplications; With the present technique, we have: Block **18** to be predicted, the block having dimensions $M=4$, $N=4$; $Q=M \times N=4 \times 4=16$ values to be predicted at the end; Reduced dimension of the boundary vector: $P_{\text{sub.red}}=P_{\text{sub.red}}+M_{\text{sub.red}}+N_{\text{sub.red}}=2+2=4$; $P_{\text{sub.red}}=4$ multiplications for each of the $Q=16$ values to be predicted by ALWIP, a total number of $P_{\text{sub.red}} \times Q=4 \times 16=64$ multiplications (the half of 128!) the ratio between the number of multiplications and the number of final values to be obtained and is $\text{red } P_{\text{sub.red}} \times Q/Q=4$, i.e. the half than the $P=8$ multiplications for each sample to be predicted!

(112) As can be understood, by relying on straightforward and computationally-non-power-demanding operations such as averaging (and, in case, additions and/or shifts and/or downsampling) it is possible to obtain an appropriate value at step **812**.

(113) With reference to FIG. 7.2, the block **18** to be predicted is here an 8×8 block ($M=8$, $N=8$) of 64 samples. Here, a priori, a prediction matrix **17M** should have size $Q \times P=64 \times 16$ ($Q=64$ by virtue of $Q=M \times N=8 \times 8=64$, $M=8$ and $N=8$ and by virtue of $P=M+N=8+8=16$). Hence, a priori, there would be needed $P=16$ multiplications for each of the $Q=64$ samples of the 8×8 block **18** to be predicted, to arrive at $64 \times 16=1024$ multiplications for the whole 8×8 block **18**!

(114) However, as can be seen in FIG. 7.2, there can be provided a method **820** according to which, instead of using all the 16 samples of the boundary, only 8 values (e.g., 4 in the horizontal boundary row **17c** and 4 in the vertical boundary column **17a** between original samples of the boundary) are used. From the boundary row **17c**, 4 samples may be used instead of 8 (e.g., they may be two-by-two averages and/or selections of one sample out of two). Accordingly, the boundary vector is not a $P \times 1=16 \times 1$ vector, but a $P_{\text{sub.red}} \times 1=8 \times 1$ vector only ($P_{\text{sub.red}}=M_{\text{sub.red}}+N_{\text{sub.red}}=4+4$). It has been understood that it is possible to select or average (e.g., two by two) samples of the horizontal row **17c** and samples of the vertical columns

17a to have, instead of the original $P=16$ samples, only $P_{\text{sub.red}}=8$ boundary values, forming the reduced set **102** of sample values. This reduced set **102** will permit to obtain a reduced version of block **18**, the reduced version having $Q_{\text{sub.red}}=M_{\text{sub.red}} \times N_{\text{sub.red}}=4 \times 4=16$ samples (instead of $Q=M \times N=8 \times 8=64$). It is possible to apply an ALWIP matrix for predicting a block having size $M_{\text{sub.red}} \times N_{\text{sub.red}}=4 \times 4$. The reduced version of block **18** includes the samples indicated with grey in the scheme **106** in FIG. 7.2: the samples indicated with grey squared (including samples **118'** and **118''**) form a 4×4 reduced block with $Q_{\text{sub.red}}=16$ values obtained at the step of subjecting **812**. The 4×4 reduced block has been obtained by applying the linear transformation **19** at the step of subjecting **812**. After having obtain the values of the 4×4 reduced block, it is possible to obtain the values of the remaining samples (samples indicated with white samples in the scheme **106**) for example by interpolation.

(115) In respect to method **810** of FIG. 7.1, this method **820** may additionally include a step **813** of deriving, e.g. by interpolation, prediction values for the remaining $Q - Q_{\text{sub.red}}=64-16=48$ samples (white squares) of the $M \times N=8 \times 8$ block **18** to be predicted. The remaining $Q - Q_{\text{sub.red}}=64-16=48$ samples may be obtained from the $Q_{\text{sub.red}}=16$ directly obtained samples by interpolation (the interpolation may also make use of values of the boundary samples, for example). As can be seen in FIG. 7.2, while the samples **118'** and **118''** have been obtained at step **812** (as indicated by the grey square), the sample **108'** (intermediate to the samples **118'** and **118''** and indicated with white square) is obtained by interpolation between the sample **118'** and **118''** at step **813**. It has been understood that interpolations may also be obtained by operations similar to those for averaging such as shifting and adding. Hence, in FIG. 7.2, the value **108'** may in general be determined as a value intermediate between the value of the sample **118'** and the value of the sample **118''** (it may be the average).

(116) By performing interpolations, at step **813** it is also possible to arrive at the final version of the $M \times N=8 \times 8$ block **18** based on multiple sample values indicated in **104**.

(117) Hence, a comparison between using the present technique and non-using it is: Without the present technique: Block **18** to be predicted, the block having dimensions $M=8$, $N=8$ and $Q=M \times N=8 \times 8=64$ samples in the block **18** to be predicted; $P=M+N=8+8=16$ samples in the boundary **17**; $P=16$ multiplications for each of the $Q=64$ values to be predicted, a total number of $P \times Q=16 \times 64=1028$ multiplications the ratio between the number of multiplications and the number of final values to be obtained is $P \times Q / Q=16$ With the present technique: Block **18** to be predicted, having dimensions $M=8$, $N=8$ $Q=M \times N=8 \times 8=64$ values to be predicted at the end; but an $Q_{\text{sub.red}} \times P_{\text{sub.red}}$ ALWIP matrix to be used, with $P_{\text{sub.red}}=M_{\text{sub.red}}+N_{\text{sub.red}}$, $Q_{\text{sub.red}}=M_{\text{sub.red}} \times N_{\text{sub.red}}$, $M_{\text{sub.red}}=4$, $N_{\text{sub.red}}=4$ $P_{\text{sub.red}}=M_{\text{sub.red}}+N_{\text{sub.red}}=4+4=8$ samples in the boundary, with $P_{\text{sub.red}} < P$ $P_{\text{sub.red}}=8$ multiplications for each of the $Q_{\text{sub.red}}=16$ values of the 4×4 reduced block to be predicted (formed by grey squares in scheme **106**), a total number of $P_{\text{sub.red}} \times Q_{\text{sub.red}}=8 \times 16=128$ multiplications (much less than 1024!) the ratio between the number of multiplications and the number of final values to be obtained is $P_{\text{sub.red}} \times Q_{\text{sub.red}} / Q=128/64=2$ (much less than the 16 obtained without the present technique!).

(118) Accordingly, the herewith presented technique is 8 times less power-demanding than the previous one.

(119) FIG. 7.3 shows another example (which may be based on the method **820**), in which the block **18** to be predicted is a rectangular 4×8 block ($M=8$, $N=4$) with $Q=4 \times 8=32$ samples to be predicted. The boundary **17** is formed by the horizontal row **17c** with $N=8$ samples and the vertical column **17a** with $M=4$ samples. Hence, a priori, the boundary vector **17P** would have dimension $P \times 1=12 \times 1$, while the prediction ALWIP matrix should be a $Q \times P=32 \times 12$ matrix, hence causing the need of $Q \times P=32 \times 12=384$ multiplications.

(120) However, it is possible, for example, to average or downsample at least the 8 samples of the horizontal row **17c**, to obtain a reduced horizontal row with only 4 samples (e.g., averaged

samples). In some examples, the vertical column **17a** would remain as it is (e.g. without averaging). In total, the reduced boundary would have dimension $P_{sub.red}=8$, with $P_{sub.red} < P$. Accordingly, the boundary vector **17P** will have dimension $P_{sub.red} \times 1 = 8 \times 1$. The ALWIP prediction matrix **17M** will be a matrix with dimensions $M \times N_{sub.red} \times P_{sub.red} = 4 \times 4 \times 8 = 64$. The 4×4 reduced block (formed by the grey columns in the schema **107**), directly obtained at the subjecting step **812**, will have size $Q_{sub.red} = M \times N_{sub.red} = 4 \times 4 = 16$ samples (instead of the $Q = 4 \times 8 = 32$ of the original 4×8 block **18** to be predicted). Once the reduced 4×4 block is obtained by ALWIP, it is possible to add an offset value $b_{sub.k}$ (step **812c**) and to perform interpolations at step **813**. As can be seen at step **813** in FIG. 7.3, the reduced 4×4 block is expanded to the 4×8 block **18**, where the values **108'**, non-obtained at step **812**, are obtained at step **813** by interpolating the values **118'** and **118''** (grey squares) obtained at step **812**.

(121) Hence, a comparison between using the present technique and non-using it is: Without the present technique: Block **18** to be predicted, the block having dimensions $M=4$, $N=8$ $Q=M \times N=4 \times 8=32$ values to be predicted; $P=M+N=4+8=12$ samples in the boundary; $P=12$ multiplications for each of the $Q=32$ values to be predicted, a total number of $P \times Q=12 \times 32=384$ multiplications the ratio between the number of multiplications and the number of final values to be obtained is $P \times Q / Q = 12$ With the present technique: Block **18** to be predicted, the block having dimensions $M=4$, $N=8$ $Q=M \times N=4 \times 8=32$ values to be predicted at the end; but a $Q_{sub.red} \times P_{sub.red} = 16 \times 8$ ALWIP matrix can be used, with $M=4$, $N_{sub.red}=4$, $Q_{sub.red} = M \times N_{sub.red} = 16$, $P_{sub.red} = M + N_{sub.red} = 4 + 4 = 8$ $P_{sub.red} = M + N_{sub.red} = 4 + 4 = 8$ samples in the boundary, with $P_{sub.red} < P$ $P_{sub.red} = 8$ multiplications for each of the $Q_{sub.red} = 16$ values of the reduced block to be predicted, a total number of $Q_{sub.red} \times P_{sub.red} = 16 \times 8 = 128$ multiplications (less than 384!) the ratio between the number of multiplications and the number of final values to be obtained is $P_{sub.red} \times Q_{sub.red} / Q = 128 / 32 = 4$ (much less than the 12 obtained without the present technique!).

(122) Hence, with the present technique, the computational effort is reduced to one third.

(123) FIG. 7.4 shows a case of a block **18** to be predicted with dimensions $M \times N = 16 \times 16$ and having $Q = M \times N = 16 \times 16 = 256$ values to be predicted at the end, with $P = M + N = 16 + 16 = 32$ boundary samples. This would lead to a prediction matrix with dimensions $Q \times P = 256 \times 32$, which would imply $256 \times 32 = 8192$ multiplications!

(124) However, by applying the method **820**, it is possible, at step **811**, to reduce (e.g. by averaging or downsampling) the number of boundary samples, e.g., from 32 to 8: for example, for every group **120** of four consecutive samples of the row **17a**, one single sample (e.g., selected among the four samples, or the average of the samples) remains. Also for every group of four consecutive samples of the column **17c**, one single sample (e.g., selected among the four samples, or the average of the samples) remains.

(125) Here, the ALWIP matrix **17M** is a $Q_{sub.red} \times P_{sub.red} = 64 \times 8$ matrix: this comes from the fact that it has been chosen $P_{sub.red} = 8$ (by using 8 averaged or selected samples from the 32 ones of the boundary) and by the fact that the reduced block to be predicted at step **812** is an 8×8 block (in the scheme **109**, the grey squares are 64).

(126) Hence, once the 64 samples of the reduced 8×8 block are obtained at step **812**, it is possible to derive, at step **813**, the remaining $Q - Q_{sub.red} = 256 - 64 = 192$ values **104** of the block **18** to be predicted.

(127) In this case, in order to perform the interpolations, it has been chosen to use all the samples of the boundary column **17a** and only alternate samples in the boundary row **17c**. other choices may be made.

(128) While with the present method the ratio between the number of multiplications and the number of finally obtained values is $Q_{sub.red} \times P_{sub.red} / Q = 8 \times 64 / 256 = 2$, which is much less than the 32 multiplications for each value without the present technique!

(129) A comparison between using the present technique and non-using it is: Without the present

technique: Block **18** to be predicted, the block having dimensions $M=16$, $N=16$
 $Q=M*N=16*16=256$ values to be predicted; $P=M+N=16+16=32$ samples in the boundary; $P=32$
multiplications for each of the $Q=256$ values to be predicted, a total number of $P*Q=32*256=8192$
multiplications; the ratio between the number of multiplications and the number of final values to
be obtained is $P*Q/Q=32$ With the present technique: Block **18** to be predicted, the block having
dimensions $M=16$, $N=16$ $Q=M*N=16*16=256$ values to be predicted at the end; but a
 $Q_{\text{sub.red}} \times P_{\text{sub.red}} = 64 \times 8$ ALWIP matrix to be used, with $M_{\text{sub.red}}=4$, $N_{\text{sub.red}}=4$,
 $Q_{\text{sub.red}}=8*8=64$ samples to be predicted by ALWIP, $P_{\text{sub.red}}=M_{\text{sub.red}}+N_{\text{sub.red}}=4+4=8$
 $P_{\text{sub.red}}=M_{\text{sub.red}}+N_{\text{sub.red}}=4+4=8$ samples in the boundary, with $P_{\text{sub.red}} < P$ $P_{\text{sub.red}}=8$
multiplications for each of the $Q_{\text{sub.red}}=64$ values of the reduced block to be predicted, a total
number of $Q_{\text{sub.red}}*P_{\text{sub.red}}=64*8=512$ multiplications (less than 8192!) the ratio between the
number of multiplications and the number of final values to be obtained is
 $P_{\text{sub.red}}*Q_{\text{sub.red}}/Q=8*64/256=2$ (much less than the 32 obtained without the present
technique!).

(130) Accordingly, the computational power needed by the present technique is 16 times less than
the traditional technique!

(131) Therefore, it is possible to predict a predetermined block (**18**) of the picture using a plurality
of neighbouring samples (**17**) by reducing (**100, 813**) the plurality of neighbouring samples to
obtain a reduced set (**102**) of samples values lower, in number of samples, than compared to the
plurality of neighbouring samples (**17**), subjecting (**812**) the reduced set of sample values (**102**) to a
linear or affine linear transformation (**19, 17M**) to obtain predicted values for predetermined
samples (**104, 118', 118''**) of the predetermined block (**18**).

(132) In particular, it is possible to perform the reducing (**100, 813**) by downsampling the plurality
of neighbouring samples to obtain the reduced set (**102**) of samples values lower, in number of
samples, than compared to the plurality of neighbouring samples (**17**).

(133) Alternatively, it is possible to perform the reducing (**100, 813**) by averaging the plurality of
neighbouring samples to obtain the reduced set (**102**) of samples values lower, in number of
samples, than compared to the plurality of neighbouring samples (**17**).

(134) Further, it is possible to derive (**813**), by interpolation, prediction values for further samples
(**108, 108'**) of the predetermined block (**18**) on the basis of the predicted values for the
predetermined samples (**104, 118', 118''**) and the plurality of neighbouring samples (**17**).

(135) The plurality of neighbouring samples (**17a, 17c**) may extend one-dimensionally along two
sides (e.g. towards right and toward below in FIGS. 7.1-7.4) of the predetermined block (**18**). The
predetermined samples (e.g. those which are obtained by ALWIP in step **812**) may also be arranged
in rows and columns and, along at least one of the rows and columns, the predetermined samples
may be positioned at every n.sup.th position from a sample (**112**) of the predetermined sample **112**
adjoining the two sides of the predetermined block **18**.

(136) Based on the plurality of neighbouring samples (**17**), it is possible to determine for each of
the at least one of the rows and the columns, a support value (**118**) for one (**118**) of the plurality of
neighbouring positions, which is aligned to the respective one of the at least one of the rows and
the columns. It is also possible to derive, by interpolation, the prediction values **118** for the further
samples (**108, 108'**) of the predetermined block (**18**) on the basis of the predicted values for the
predetermined samples (**104, 118', 118''**) and the support values for the neighbouring samples (**118**)
aligned to the at least one of rows and columns.

(137) The predetermined samples (**104**) may be positioned at every n.sup.th position from the
sample (**112**) which adjoins the two sides of the predetermined block **18** along the rows and the
predetermined samples are positioned at every m.sup.th position from the sample (**112**) of the
predetermined sample which (**112**) adjoins the two sides of the predetermined block (**18**) along the
columns, wherein $n, m > 1$. In some cases, $n=m$ (e.g., in FIGS. 7.2 and 7.3, where the samples **104**,
118', 118'', directly obtained by ALWIP at **812** and indicated with grey squares, are alternated,

along rows and columns, to the samples **108**, **108'** subsequently obtained at step **813**).

(138) Along at least one of the rows (**17c**) and columns (**17a**), it may be possible to perform the determining the support values e.g. by downsampling or averaging (**122**), for each support value, a group (**120**) of neighbouring samples within the plurality of neighbouring samples which includes the neighbouring sample (**118**) for which the respective support value is determined. Hence, in FIG. **7.4**, at step **813** it is possible to obtain the value of sample **119** by using the values of the predetermined sample **118'''** (previously obtained at step **812**) and the neighbouring sample **118** as support values.

(139) The plurality of neighbouring samples may extend one-dimensionally along two sides of the predetermined block (**18**). It may be possible to perform the reduction (**811**) by grouping the plurality of neighbouring samples (**17**) into groups (**110**) of one or more consecutive neighbouring samples and performing a downsampling or an averaging on each of the group (**110**) of one or more neighbouring samples which has two or more than two neighbouring samples.

(140) In examples, the linear or affine linear transformation may comprise $P_{\text{sub.red}} \times Q_{\text{sub.red}}$ or $P_{\text{sub.red}} \times Q$ weighting factors with $P_{\text{sub.red}}$ being the number of sample values (**102**) within the reduced set of sample values and $Q_{\text{sub.red}}$ or Q is the number predetermined samples within the predetermined block (**18**). At least $\frac{1}{4} P_{\text{sub.red}} \times Q_{\text{sub.red}}$ or $\frac{1}{4} P_{\text{sub.red}} \times Q$ weighting factors are non-zero weighting values. The $P_{\text{sub.red}} \times Q_{\text{sub.red}}$ or $P_{\text{sub.red}} \times Q$ weighting factors may comprise, for each of the Q or $Q_{\text{sub.red}}$ predetermined samples, a series of $P_{\text{sub.red}}$ weighting factors relating to the respective predetermined sample, wherein the series, when being arranged one below the other according to a raster scan order among the predetermined samples of the predetermined block (**18**), form an envelope which is omnidirectionally non-linear. The $P_{\text{sub.red}} \times Q$ or $P_{\text{sub.red}} \times Q_{\text{sub.red}}$ weighting factors may be unrelated to each other via any regular mapping rule. A mean of maxima of cross correlations between a first series of weighting factors relating to the respective predetermined sample, and a second series of weighting factors relating to predetermined samples other than the respective predetermined sample, or a reversed version of the latter series, whatever leads to a higher maximum, is lower than a predetermined threshold. The predetermined threshold may 0.3 [or in some cases 0.2 or 0.1]. The $P_{\text{sub.red}}$ neighbouring samples (**17**) may be located along a one-dimensional path extending along two sides of the predetermined block (**18**) and, for each of the Q or $Q_{\text{sub.red}}$ predetermined samples, the series of $P_{\text{sub.red}}$ weighting factors relating to the respective predetermined sample are ordered in a manner traversing the one-dimensional path in a predetermined direction.

(141) 6.1 Description of a Method and Apparatus

(142) For predicting the samples of a rectangular block of width W (also indicated with N) and height H (also indicated with M), Affine-linear weighted intra prediction (ALWIP) may take one line of H reconstructed neighbouring boundary samples left of the block and one line of W reconstructed neighbouring boundary samples above the block as input. If the reconstructed samples are unavailable, they may be generated as it is done in the conventional intra prediction.

(143) A generation of the prediction signal (e.g., the values for the complete block **18**) may be based on at least some of the following three steps: 1. Out of the boundary samples **17**, samples **102** (e.g., four samples in the case of $W=H=4$ and/or eight samples in other case) may be extracted by averaging or downsampling (e.g., step **811**). 2. A matrix vector multiplication, followed by addition of an offset, may be carried out with the averaged samples (or the samples remaining from downsampling) as an input. The result may be a reduced prediction signal on a subsampled set of samples in the original block (e.g., step **812**). 3. The prediction signal at the remaining position may be generated, e.g. by upsampling, from the prediction signal on the subsampled set, e.g., by linear interpolation (e.g., step **813**).

(144) Thanks to steps 1. (**811**) and/or 3. (**813**), the total number of multiplications needed in the computation of the matrix-vector product may be such that it is smaller or equal than $4 \times W \times H$.

(145) Moreover, the averaging operations on the boundary and the linear interpolation of the

reduced prediction signal are carried out by solely using additions and bit-shifts. In other words, in examples at most four multiplications per sample are needed for the ALWIP modes.

(146) In some examples, the matrices (e.g., **17M**) and offset vectors (e.g., $b_{sub.k}$) needed to generate the prediction signal may be taken from sets (e.g., three sets), e.g., $S_{sub.0}$, $S_{sub.1}$, $S_{sub.2}$, of matrices which may be stored, for example, in storage unit(s) of the decoder and of the encoder.

(147) In some examples, the set $S_{sub.0}$ may comprise (e.g., consist of) $n_{sub.0}$ (e.g., $n_{sub.0}=16$ or $n_{sub.0}=18$ or another number) matrices $A_{sub.0.sup.i}$, $i \in \{0, \dots, n_{sub.0}-1\}$ each of which may have 16 rows and 4 columns and 18 offset vectors $b_{sub.0.sup.i}$, $i \in \{0, \dots, n_{sub.0}-1\}$ each of size 16 to perform the technique according to FIG. 7.1. Matrices and offset vectors of this set are used for blocks **18** of size 4×4 . Once the boundary vector has been reduced to a $P_{sub.red}=4$ vector (as for step **811** of FIG. 7.1), it is possible to map the $P_{sub.red}=4$ samples of the reduced set of samples **102** directly into the $Q=16$ samples of the 4×4 block **18** to be predicted.

(148) In some examples, the set $S_{sub.1}$ may comprise (e.g., consist of) $n_{sub.1}$ (e.g., $n_{sub.1}=8$ or $n_{sub.1}=18$ or another number) matrices $A_{sub.1.sup.i}$, $i \in \{0, \dots, n_{sub.1}-1\}$, each of which may have 16 rows and 8 columns and 18 offset vectors $b_{sub.1.sup.i}$, $i \in \{0, \dots, n_{sub.1}-1\}$ each of size 16 to perform the technique according to FIG. 7.2 or 7.3. Matrices and offset vectors of this set $S_{sub.1}$ may be used for blocks of sizes 4×8 , 4×16 , 4×32 , 4×64 , 16×4 , 32×4 , 64×4 , 8×4 and 8×8 . Additionally, it may also be used for blocks of size $W \times H$ with $\max(W, H) > 4$ and $\min(W, H) = 4$, i.e. for blocks of size 4×16 or 16×4 , 4×32 or 32×4 and 4×64 or 64×4 . The 16×8 matrix refers to the reduced version of the block **18**, which is a 4×4 block, as obtained in FIGS. 7.2 and 7.3.

(149) Additionally or alternatively, the set $S_{sub.2}$ may comprise (e.g., consists of) $n_{sub.2}$ (e.g., $n_{sub.2}=6$ or $n_{sub.2}=18$ or another number) matrices $A_{sub.2.sup.i}$, $i \in \{0, \dots, n_{sub.2}-1\}$, each of which may have 64 rows and 8 columns and of 18 offset vectors $b_{sub.2.sup.i}$, $i \in \{0, \dots, n_{sub.2}-1\}$ of size 64. The 64×8 matrix refers to the reduced version of the block **18**, which is an 8×8 block, e.g. as obtained in FIG. 7.4. Matrices and offset vectors of this set may be used for blocks of sizes 8×16 , 8×32 , 8×64 , 16×8 , 16×16 , 16×32 , 16×64 , 32×8 , 32×16 , 32×32 , 32×64 , 64×8 , 64×16 , 64×32 , 64×64 .

(150) Matrices and offset vectors of that set or parts of these matrices and offset vectors may be used for all other block-shapes.

(151) 6.2 Averaging or Downsampling of the Boundary

(152) Here, features are provided regarding step **811**.

(153) As explained above, the boundary samples (**17a**, **17c**) may be averaged and/or downsampled (e.g., from P samples to $P_{sub.red} < P$ samples).

(154) In a first step, the input boundaries $bdry_{sup.top}$ (e.g., **17c**) and $bdry_{sup.left}$ (e.g., **17a**) may be reduced to smaller boundaries $bdry_{sub.red.sup.top}$ and $bdry_{sub.red.sup.left}$ to arrive at the reduced set **102**. Here, $bdry_{sub.red.sup.top}$ and $bdry_{sub.red.sup.left}$ both consists of 2 samples in the case of a 4×4 -block and both consist of 4 samples in other cases.

(155) In the case of a 4×4 -block, it is possible to define

$$bdry_{sub.red.sup.top}[0] = (bdry_{sup.top}[0] + bdry_{sup.top}[1] + 1) \gg 1,$$

$$bdry_{sub.red.sup.top}[1] = (bdry_{sup.top}[2] + bdry_{sup.top}[3] + 1) \gg 1,$$

(156) and define $bdry_{sub.red.sup.left}$ analogously. Accordingly, $bdry_{sub.red.sup.top}[0]$, $bdry_{sub.red.sup.top}[1]$, $bdry_{sub.red.sup.left}[0]$ $bdry_{sub.red.sup.left}[1]$ are average values obtained e.g. using bit-shifting operations.

(157) In all other cases (e.g., for blocks of wither width or height different from 4), if the block-width W is given as $W = 4 * 2^{sup.k}$, for $0 \leq i < 4$ one defines

$$(158) \quad bdry_{red}^{top}[i] = ((\text{Math}.\overset{2^k-1}{j=0} bdry_{red}^{top}[i * 2^k + j]) + 1 \ll (k - 1)) \gg k.$$

(159) and defines $bdry_{sub.red.sup.left}$ analogously.

(160) In still other cases, it is possible to downsample the boundary (e.g., by selecting one

particular boundary sample from a group of boundary samples) to arrive at a reduce number of samples. For example, $\text{bdry.sub.red.sup.top}[0]$ may be chosen among $\text{bdry.sup.top}[0]$ and $\text{bdry.sup.top}[1]$, and $\text{bdry.sup.top}[1]$ may be chosen among $\text{bdry.sup.top}[2]$ and $\text{bdry.sup.top}[3]$. It is also possible to define $\text{bdry.sub.red.sup.left}$ analogously.

(161) The two reduced boundaries $\text{bdry.sub.red.sup.top}$ and $\text{bdry.sub.red.sup.left}$ may be concatenated to a reduced boundary vector bdry.sub.red (associated to the reduced set **102**), also indicated with **17P**. The reduced boundary vector bdry.sub.red may be thus of size four red ($P_{\text{sub.red}}=4$) for blocks of shape 4×4 (example of FIG. 7.1) and of size eight ($P_{\text{sub.red}}=8$) for blocks of all other shapes (examples of FIG. 7.2-7.4).

(162) Here, if $\text{mode} < 18$ (or the number of matrixes in the set of matrixes), it is possible to define $\text{bdry.sub.red} = [\text{bdry.sub.red.sup.top}, \text{bdry.sub.red.sup.left}]$.

(163) If $\text{mode} \geq 18$, which corresponds to the transposed mode of mode -17 , it is possible to define $\text{bdry.sub.red} = [\text{bdry.sub.left.sup.top}, \text{bdry.sub.red.sup.top}]$.

(164) Hence, according to a particular state (one state: $\text{mode} < 18$; one other state: $\text{mode} \geq 18$) it is possible to distribute the predicted values of the output vector along a different scan order (e.g., one scan order: $[\text{bdry.sub.red.sup.top}, \text{bdry.sub.red.sup.left}]$; one other scan order: $[\text{bdry.sub.red.sup.left}, \text{bdry.sub.red.sup.top}]$).

(165) Other strategies may be carried out. In other examples, the mode index 'mode' is not necessarily in the range 0 to 35 (other ranges may be defined). Further, it is not necessary that each of the three sets $S_{\text{sub.0}}$, $S_{\text{sub.1}}$, $S_{\text{sub.2}}$ has 18 matrixes (hence, instead of expressions like mode **18**, it is possible to $\text{mode} \geq n_{\text{sub.0}}$, $n_{\text{sub.1}}$, $n_{\text{sub.2}}$, which are the number of matrixes for each set of matrixes $S_{\text{sub.0}}$, $S_{\text{sub.1}}$, $S_{\text{sub.2}}$ respectively). Further, the sets may have different numbers of matrixes each (for example, it may be that $S_{\text{sub.0}}$ has 16 matrixes $S_{\text{sub.1}}$ has eight matrixes, and $S_{\text{sub.2}}$ has six matrixes).

(166) The mode and transposed information are not necessarily stored and/or transmitted as one combined mode index 'mode': in some examples there is the possibility of signalling explicitly as a transposed flag and the matrix index (0-15 for $S_{\text{sub.0}}$, 0-7 for $S_{\text{sub.1}}$ and 0-5 for $S_{\text{sub.2}}$).

(167) In some cases, the combination of the transposed flag and matrix index may be interpreted as a set index. For example, there may be one bit operating as transposed flag, and some bits indicating the matrix index, collectively indicated as "set index".

(168) 5.4 Generation of the Reduced Prediction Signal by Matrix Vector Multiplication

(169) Here, features are provided regarding step **812**.

(170) Out of the reduced input vector bdry.sub.red (boundary vector **17P**) one may generate a reduced prediction signal pred.sub.red . The latter signal may be a signal on the downsampled block of with $W_{\text{sub.red}}$ and height $H_{\text{sub.red}}$. Here, $W_{\text{sub.red}}$ and $H_{\text{sub.red}}$ may be defined as:

$W_{\text{sub.red}}=4, H_{\text{sub.red}}=4; \text{if } \max(W, H) \leq 8,$
 $W_{\text{sub.red}}=\min(W, 8), H_{\text{sub.red}}=\min(H, 8); \text{else.}$

(171) The reduced prediction signal pred.sub.red may be computed by calculating a matrix vector-product and adding an offset:

$\text{pred.sub.red} = A \cdot \text{bdry.sub.red} + b.$

(172) Here, A is a matrix (e.g., prediction matrix **17M**) that may have $W_{\text{sub.red}} \times H_{\text{sub.red}}$ rows and 4 columns if $W=H=4$ and 8 columns in all other cases and b is a vector that may be of size $W_{\text{sub.red}} \times H_{\text{sub.red}}$.

(173) If $W=H=4$, then A may have 4 columns and 16 rows and thus 4 multiplications per sample may be needed in that case to compute pred.sub.red . In all other cases, A may have 8 columns and one may verify that in these cases one has $8 \times W_{\text{sub.red}} \times H_{\text{sub.red}} \leq 4 \times W \times H$, i.e. also in these cases, at most 4 multiplications per sample are needed to compute pred.sub.red .

(174) The matrix A and the vector b may be taken from one of the sets $S_{\text{sub.0}}$, $S_{\text{sub.1}}$, $S_{\text{sub.2}}$ as follows. One defines an index $\text{idx} = \text{idx}(W, H)$ by setting $\text{idx}(W, H)=0$, if $W=H=4$, $\text{idx}(W, H)=1$, if $\max(W, H)=8$ and $\text{idx}(W, H)=2$ in all other cases. Moreover, one may put $m = \text{mode}$, if $\text{mode} < 18$

and $m = \text{mode} - 17$, else. Then, if $\text{idx} \leq 1$ or $\text{idx} = 2$ and $\min(W, H) > 4$, one may put $A = A.\text{sub}.\text{idx}.\text{sup}.\text{m}$ and $b = b.\text{sub}.\text{idx}.\text{sup}.\text{m}$. In the case that $\text{idx} = 2$ and $\min(W, H) = 4$, one lets A be the matrix that arises by leaving out every row of $A.\text{sub}.\text{idx}.\text{sup}.\text{m}$ that, in the case $W = 4$, corresponds to an odd x-coordinate in the downsampled block, or, in the case $H = 4$, corresponds to an odd y-coordinate in the downsampled block. If mode **18**, one replaces the reduced prediction signal by its transposed signal. In alternative examples, different strategies may be carried out. For example, instead of reducing the size of a larger matrix (“leave out”), a smaller matrix of $S.\text{sub}.\text{1}$ ($\text{idx} = 1$) with $W.\text{sub}.\text{red} = 4$ and $H.\text{sub}.\text{red} = 4$ is used. I.e., such blocks are now assigned to $S.\text{sub}.\text{1}$ instead of $S.\text{sub}.\text{2}$.

(175) Other strategies may be carried out. In other examples, the mode index ‘mode’ is not necessarily in the range 0 to 35 (other ranges may be defined). Further, it is not necessary that each of the three sets $S.\text{sub}.\text{0}$, $S.\text{sub}.\text{1}$, $S.\text{sub}.\text{2}$ has 18 matrices (hence, instead of expressions like $\text{mode} < 18$, it is possible to $\text{mode} < n.\text{sub}.\text{0}$, $n.\text{sub}.\text{1}$, $n.\text{sub}.\text{2}$, which are the number of matrixes for each set of matrixes $S.\text{sub}.\text{0}$, $S.\text{sub}.\text{1}$, $S.\text{sub}.\text{2}$, respectively). Further, the sets may have different numbers of matrixes each (for example, it may be that $S.\text{sub}.\text{0}$ has 16 matrixes $S.\text{sub}.\text{1}$ has eight matrixes, and $S.\text{sub}.\text{2}$ has six matrixes).

(176) 6.4 Linear Interpolation to Generate the Final Prediction Signal

(177) Here, features are provided regarding step **812**.

(178) Interpolation of the subsampled prediction signal, on large blocks a second version of the averaged boundary may be needed. Namely, if $\min(W, H) > 8$ and $W \geq H$, one writes $W = 8 * 2.\text{sup}.\text{l}$, and for $0 \leq i < 8$ defines

$$(179) \text{bdry}_{\text{redII}}^{\text{top}}[i] = ((\text{Math}.\text{pow}(2, 2.\text{sup}.\text{l} - 1) \text{bdry}^{\text{top}}[i * 2.\text{sup}.\text{l} + j]) + 1 \ll (l - 1)) \gg l.$$

(180) If $\min(W, H) > 8$ and $H > W$, one defines $\text{bdry}.\text{sub}.\text{redII}.\text{sup}.\text{left}$ analogously.

(181) In addition or alternative, it is possible to have a “hard downsampling”, in which the $\text{bdr}.\text{sub}.\text{redII}.\text{sup}.\text{top}[i]$ is equal to

$$\text{bdry}.\text{sub}.\text{redII}.\text{sup}.\text{top}[i] = \text{bdry}.\text{sup}.\text{top}[(i + 1) * 2.\text{sup}.\text{l} - 1].$$

(182) Also, $\text{bdry}.\text{sub}.\text{redII}.\text{sup}.\text{left}$ can be defined analogously.

(183) At the sample positions that were left out in the generation of $\text{pred}.\text{sub}.\text{red}$, the final prediction signal may arise by linear interpolation from $\text{pred}.\text{sub}.\text{red}$ (e.g., step **813** in examples of FIGS. 7.2-7.4). This linear interpolation may be unnecessary, in some examples, if $W = H = 4$ (e.g., example of FIG. 7.1).

(184) The linear interpolation may be given as follows (other examples are notwithstanding possible). It is assumed that $W \geq H$. Then, if $H > H.\text{sub}.\text{red}$, a vertical upsampling of $\text{pred}.\text{sub}.\text{red}$ may be performed.

(185) In that case, $\text{pred}.\text{sub}.\text{red}$ may be extended by one line to the top as follows. If $W = 8$, $\text{pred}.\text{sub}.\text{red}$ may have width $W.\text{sub}.\text{red} = 4$ and may be extended to the top by the averaged boundary signal $\text{bdry}.\text{sub}.\text{red}.\text{sup}.\text{top}$, e.g. as defined above. If $W > 8$, $\text{pred}.\text{sub}.\text{red}$ is of width $W.\text{sub}.\text{red} = 8$ and it is extended to the top by the averaged boundary signal $\text{bdry}.\text{sub}.\text{redII}.\text{sup}.\text{top}$, e.g. as defined above. One may write $\text{pred}.\text{sub}.\text{red}[x][-1]$ for the first line of $\text{pred}.\text{sub}.\text{red}$. Then the signal $\text{pred}.\text{sub}.\text{red}.\text{sup}.\text{ups},\text{ver}$ on a block of width $W.\text{sub}.\text{red}$ and height $2 * H.\text{sub}.\text{red}$ may be given as

$$\text{pred}.\text{sub}.\text{red}.\text{sup}.\text{ups},\text{ver}[x][2 * y + 1] = \text{pred}.\text{sub}.\text{red}[x][y],$$

$$\text{pred}.\text{sub}.\text{red}.\text{sup}.\text{ups},\text{ver}[x][2 * y] = (\text{pred}.\text{sub}.\text{red}[x][y - 1] + \text{pred}.\text{sub}.\text{red}[x][y] + 1) \gg 1,$$

(186) where $0 \leq x < W.\text{sub}.\text{red}$ and $0 \leq y < H.\text{sub}.\text{red}$. The latter process may be carried out k times until $2.\text{sup}.\text{k} * H.\text{sub}.\text{red} = H$. Thus, if $H = 8$ or $H = 16$, it may be carried out at most once. If $H = 32$, it may be carried out twice. If $H = 64$, it may be carried out three times. Next, a horizontal upsampling operation may be applied to the result of the vertical upsampling. The latter upsampling operation may use the full boundary left of the prediction signal. Finally, if $H > W$, one may proceed analogously by first upsampling in the horizontal direction (if needed) and then in the vertical

direction.

(187) This is an example of an interpolation using reduced boundary samples for the first interpolation (horizontally or vertically) and original boundary samples for the second interpolation (vertically or horizontally). Depending on the block size, only the second or no interpolation is needed. If both horizontal and vertical interpolation is needed, the order depends on the width and height of the block.

(188) However, different techniques may be implemented: for example, original boundary samples may be used for both the first and the second interpolation and the order may be fixed, e.g. first horizontal then vertical (in other cases, first vertical then horizontal).

(189) Hence, the interpolation order (horizontal/vertical) and the use of reduced/original boundary samples may be varied.

(190) 6.5 Illustration of an Example of the Entire ALWIP Process

(191) The entire process of averaging, matrix-vector-multiplication and linear interpolation is illustrated for different shapes in FIGS. 7.1-7.4. Note, that the remaining shapes are treated as in one of the depicted cases. 1. Given a 4×4 block, ALWIP may take two averages along each axis of the boundary by using the technique of FIG. 7.1. The resulting four input samples enter the matrix-vector-multiplication. The matrices are taken from the set S.sub.0. After adding an offset, this may yield the 16 final prediction samples. Linear interpolation is not necessary for generating the prediction signal. Thus, a total of $(4 \cdot 16)/(4 \cdot 4) = 4$ multiplications per sample are performed. See, for example, FIG. 7.1. 2. Given an 8×8 block, ALWIP may take four averages along each axis of the boundary. The resulting eight input samples enter the matrix-vector-multiplication, by using the technique of FIG. 7.2. The matrices are taken from the set S.sub.1. This yields 16 samples on the odd positions of the prediction block. Thus, a total of $(8 \cdot 16)/(8 \cdot 8) = 2$ multiplications per sample are performed. After adding an offset, these samples may be interpolated, e.g., vertically by using the top boundary and, e.g. horizontally by using the left boundary. See, for example, FIG. 7.2. 3. Given an 8×4 block, ALWIP may take four averages along the horizontal axis of the boundary and the four original boundary values on the left boundary by using the technique of FIG. 7.3. The resulting eight input samples enter the matrix-vector-multiplication. The matrices are taken from the set S.sub.1. This yields 16 samples on the odd horizontal and each vertical positions of the prediction block. Thus, a total of $(8 \cdot 16)/(8 \cdot 4) = 4$ multiplications per sample are performed. After adding an offset, these samples are interpolated horizontally by using the left boundary, for example. See, for example, FIG. 7.3. The transposed case is treated accordingly. 4. Given a 16×16 block, ALWIP may take four averages along each axis of the boundary. The resulting eight input samples enter the matrix-vector-multiplication by using the technique of FIG. 7.2. The matrices are taken from the set S.sub.2. This yields 64 samples on the odd positions of the prediction block. Thus, a total of $(8 \cdot 64)/(16 \cdot 16) = 2$ multiplications per sample are performed. After adding an offset, these samples are interpolated vertically by using the top boundary and horizontally by using the left boundary, for example. See, for example, FIG. 7.2. See, for example, FIG. 7.4. For larger shapes, the procedure may be essentially the same and it is easy to check that the number of multiplications per sample is less than two. For $W \times 8$ blocks, only horizontal interpolation is needed as the samples are given at the odd horizontal and each vertical positions. Thus, at most $(8 \cdot 64)/(16 \cdot 8) = 4$ multiplications per sample are performed in these cases. Finally for $W \times 4$ blocks with $W > 8$, let A.sub.k be the matrix that arises by leaving out every row that correspond to an odd entry along the horizontal axis of the downsampled block. Thus, the output size may be 32 and again, only horizontal interpolation remains to be performed. At most $(8 \cdot 32)/(16 \cdot 4) = 4$ multiplications per sample may be performed. The transposed cases may be treated accordingly.

6.6 Number of Parameters Needed and Complexity Assessment

(192) The parameters needed for all possible proposed intra prediction modes may be comprised by the matrices and offset vectors belonging to the sets S.sub.0, S.sub.1, S.sub.2. All matrix-coefficients and offset vectors may be stored as 10-bit values. Thus, according to the above

description, a total number of 14400 parameters, each in 10-bit precision, may be needed for the proposed method. This corresponds to 0,018 Megabyte of memory. It is pointed out that currently, a CTU of size 128×128 in the standard 4:2:0 chroma-subsampling consists of 24576 values, each in 10 bit. Thus, the memory requirement of the proposed intra-prediction tool does not exceed the memory requirement of the current picture referencing tool that was adopted at the last meeting. Also, it is pointed out that the conventional intra prediction modes need four multiplications per sample due to the PDPC tool or the 4-tap interpolation filters for the angular prediction modes with fractional angle positions. Thus, in terms of operational complexity the proposed method does not exceed the conventional intra prediction modes.

(193) 6.7 Signalization of the Proposed Intra Prediction Modes

(194) For luma blocks, 35 ALWIP modes are proposed, for example, (other numbers of modes may be used). For each Coding Unit (CU) in intra mode, a flag indicating if an ALWIP mode is to be applied on the corresponding Prediction Unit (PU) or not is sent in the bitstream. The signalization of the latter index may be harmonized with MRL in the same way as for the first CE test. If an ALWIP mode is to be applied, the index *predmode* of the ALWIP mode may be signaled using an MPM-list with 3 MPMS.

(195) Here, the derivation of the MPMs may be performed using the intra-modes of the above and the left PU as follows. There may be tables, e.g. three fixed tables *map_angular_to_alwip.sub.idx*, $\text{idx} \in \{0,1,2\}$ that may assign to each conventional intra prediction mode *predmode.sub.Angular* an ALWIP mode

predmode.sub.ALWIP = *map_angular_to_alwip.sub.idx*[*predmode.sub.Angular*].

(196) For each PU of width W and height H one defines an index

idx(PU) = *idx*(W,H) $\in \{0,1,2\}$

(197) that indicates from which of the three sets the ALWIP-parameters are to be taken as in section 4 above. If the above Prediction Unit PU.sub.above is available, belongs to the same CTU as the current PU and is in intra mode, if *idx*(PU) = *idx*(PU.sub.above) and if ALWIP is applied on PU.sub.above with ALWIP-mode *predmode.sub.ALWIP.sup.above*, one puts

mode.sub.ALWIP.sup.above = *predmode.sub.ALWIP.sup.above*.

(198) If the above PU is available, belongs to the same CTU as the current PU and is in intra mode and if a conventional intra prediction mode *predmode.sub.Angular.sup.above* is applied on the above PU, one puts

mode.sub.ALWIP.sup.above = *map_angular_to_alwip.sub.idx*(PU.sub.above)
[*predmode.sub.Angular.sup.above*]

(199) In all other cases, one puts

mode.sub.ALWIP.sup.above = -1

(200) which means that this mode is unavailable. In the same way but without the restriction that the left PU needs to belong to the same CTU as the current PU, one derives a mode *mode.sub.ALWIP.sup.left*.

(201) Finally, three fixed default lists *list.sub.idx*, $\text{idx} \in \{0,1,2\}$ are provided, each of which contains three distinct ALWIP modes. Out of the default list *list.sub.idx*(PU) and the modes *mode.sub.ALWIP.sup.above* and *mode.sub.ALWIP.sup.left*, one constructs three distinct MPMs by substituting -1 by default values as well as eliminating repetitions.

(202) The herein described embodiments are not limited by the above described Signalization of the proposed intra prediction modes. According to an alternative embodiment, no MPMs and/or mapping tables are used for MIP (ALWIP).

(203) 6.8 Adapted MPM-List Derivation for Conventional Luma and Chroma Intra-Prediction Modes

(204) The proposed ALWIP-modes may be harmonized with the MPM-based coding of the conventional intra-prediction modes as follows. The luma and chroma MPM-list derivation processes for the conventional intra-prediction modes may use fixed tables

map_alwip_to_angular.sub.idx, $\text{idx} \in \{0,1,2\}$, mapping an ALWIP-mode predmode.sub.ALWIP on a given PU to one of the conventional intra-prediction modes

$\text{predmode.sub.Angular} = \text{map_alwip_to_angular.sub.idx}(\text{PU})[\text{predmode.sub.ALWIP}]$.

(205) For the luma MPM-list derivation, whenever a neighboring luma block is encountered which uses an ALWIP-mode predmode.sub.ALWIP, this block may be treated as if it was using the conventional intra-prediction mode predmode.sub.Angular. For the chroma MPM-list derivation, whenever the current luma block uses an LWIP-mode, the same mapping may be used to translate the ALWIP-mode to a conventional intra prediction mode.

(206) It is clear, that the ALWIP-modes can be harmonized with the conventional intra-prediction modes also without the usage of MPMs and/or mapping tables. It is, for example, possible that for the chroma block, whenever the current luma block uses an ALWIP-mode, the ALWIP-mode is mapped to a planar-intra prediction mode.

7. IMPLEMENTATION EFFICIENT EMBODIMENTS

(207) Let's briefly summarize the above examples as they might form a basis for further extending the embodiments described herein below.

(208) For predicting a predetermined block **18** of the picture **10**, using a plurality of neighbouring samples **17a,c** is used.

(209) A reduction **100**, by averaging, of the plurality of neighbouring samples has been done to obtain a reduced set **102** of samples values lower, in number of samples, than compared to the plurality of neighbouring samples. This reduction is optional in the embodiments herein and yields the so called sample value vector mentioned in the following. The reduced set of sample values is the subject to a linear or affine linear transformation **19** to obtain predicted values for predetermined samples **104** of the predetermined block. It is this transformation, later on indicated using matrix A and offset vector b which has been obtained by machine learning (ML) and should be implementation efficiently preformed.

(210) 2By interpolation, prediction values for further samples **108** of the predetermined block are derived on the basis of the predicted values for the predetermined samples and the plurality of neighbouring samples. It should be said that, theoretically, the outcome of the affine/linear transformation could be associated with non-full-pel sample positions of block **18** so that all samples of block **18** might be obtained by interpolation in accordance with an alternative embodiment. No interpolation might be needed at all, too.

(211) The plurality of neighbouring samples might extend one-dimensionally along two sides of the predetermined block, the predetermined samples are arranged in rows and columns and, along at least one of the rows and columns, wherein the predetermined samples may be positioned at every n.sup.th position from a sample (**112**) of the predetermined sample adjoining the two sides of the predetermined block. Based on the plurality of neighbouring samples, for each of the at least one of the rows and the columns, a support value for one (**118**) of the plurality of neighbouring positions might be determined, which is aligned to the respective one of the at least one of the rows and the columns, and by interpolation, the prediction values for the further samples **108** of the predetermined block might be derived on the basis of the predicted values for the predetermined samples and the support values for the neighbouring samples aligned to the at least one of rows and columns. The predetermined samples may be positioned at every n.sup.th position from the sample **112** of the predetermined sample which adjoins the two sides of the predetermined block along the rows and the predetermined samples may be positioned at every m.sup.th position from the sample **112** of the predetermined sample which adjoins the two sides of the predetermined block along the columns, wherein $n, m > 1$. It might be that $n = m$. Along at least one of the rows and column, the determination of the support values may be done by averaging (**122**), for each support value, a group **120** of neighbouring samples within the plurality of neighbouring samples which includes the neighbouring sample **118** for which the respective support value is determined. The plurality of neighbouring samples may extend one-dimensionally along two sides of the predetermined block

and the reduction may be done by grouping the plurality of neighbouring samples into groups **110** of one or more consecutive neighbouring samples and performing an averaging on each of the group of one or more neighbouring samples which has more than two neighbouring samples. (212) For the predetermined block, a prediction residual might be transmitted in the data stream. It might be derived therefrom at the decoder and the predetermined block be reconstructed using the prediction residual and the predicted values for the predetermined samples. At the encoder, the prediction residual is encoded into the data stream at the encoder.

(213) The picture might be subdivided into a plurality of blocks of different block sizes, which plurality comprises the predetermined block. Then, it might be that the linear or affine linear transformation for block **18** is selected depending on a width W and height H of the predetermined block such that the linear or affine linear transformation selected for the predetermined block is selected out of a first set of linear or affine linear transformations as long as the width W and height H of the predetermined block are within a first set of width/height pairs and a second set of linear or affine linear transformations as long as the width W and height H of the predetermined block are within a second set of width/height pairs which is disjoint to the first set of width/height pairs. Again, later on it gets clear that the affine/linear transformations are represented by way of other parameters, namely weights of C and, optionally, offset and scale parameters.

(214) Decoder and encoder may be configured to subdivide the picture into a plurality of blocks of different block sizes, which comprises the predetermined block, and to select the linear or affine linear transformation depending on a width W and height H of the predetermined block such that the linear or affine linear transformation selected for the predetermined block is selected out of a first set of linear or affine linear transformations as long as the width W and height H of the predetermined block are within a first set of width/height pairs, a second set of linear or affine linear transformations as long as the width W and height H of the predetermined block are within a second set of width/height pairs which is disjoint to the first set of width/height pairs, and a third set of linear or affine linear transformations as long as the width W and height H of the predetermined block are within a third set of one or more width/height pairs, which is disjoint to the first and second sets of width/height pairs.

(215) The third set of one or more width/height pairs merely comprises one width/height pair, W' , H' , and each linear or affine linear transformation within first set of linear or affine linear transformations is for transforming N' sample values to $W' \times H'$ predicted values for an $W' \times H'$ array of sample positions.

(216) Each of the first and second sets of width/height pairs may comprise a first width/height pairs $W_{\text{sub.p}}, H_{\text{sub.p}}$ with $W_{\text{sub.p}}$ being unequal to $H_{\text{sub.p}}$ and a second width/height pair $W_{\text{sub.q}}, H_{\text{sub.q}}$ with $H_{\text{sub.q}} = W_{\text{sub.p}}$ and $W_{\text{sub.q}} = H_{\text{sub.p}}$.

(217) Each of the first and second sets of width/height pairs may additionally comprise a third width/height pairs $W_{\text{sub.p}}, H_{\text{sub.p}}$ with $W_{\text{sub.p}}$ being equal to $H_{\text{sub.p}}$ and $H_{\text{sub.p}} > H_{\text{sub.q}}$.

(218) For the predetermined block, a set index might be transmitted in the data stream, which indicates which linear or affine linear transformation to be selected for block **18** out of a predetermined set of linear or affine linear transformations.

(219) The plurality of neighbouring samples may extend one-dimensionally along two sides of the predetermined block and the reduction may be done by, for a first subset of the plurality of neighbouring samples, which adjoin a first side of the predetermined block, grouping the first subset into first groups **110** of one or more consecutive neighbouring samples and, for a second subset of the plurality of neighbouring samples, which adjoin a second side of the predetermined block, grouping the second subset into second groups **110** of one or more consecutive neighbouring samples and performing an averaging on each of the first and second groups of one or more neighbouring samples which has more than two neighbouring samples, so as to obtain first sample values from the first groups and second sample values for the second groups. Then, the linear or affine linear transformation may be selected depending on the set index out of a predetermined set

of linear or affine linear transformations such that two different states of the set index result into a selection of one of the linear or affine linear transformations of the predetermined set of linear or affine linear transformations, the reduced set of sample values may be subject to the predetermined linear or affine linear transformation in case of the set index assuming a first of the two different states in form of a first vector to yield an output vector of predicted values, and distribute the predicted values of the output vector along a first scan order onto the predetermined samples of the predetermined block and in case of the set index assuming a second of the two different states in form of a second vector, the first and second vectors differing so that components populated by one of the first sample values in the first vector are populated by one of the second sample values in the second vector, and components populated by one of the second sample values in the first vector are populated by one of the first sample values in the second vector, so as to yield an output vector of predicted values, and distribute the predicted values of the output vector along a second scan order onto the predetermined samples of the predetermined block which is transposed relative to the first scan order.

(220) Each linear or affine linear transformation within first set of linear or affine linear transformations may be for transforming $N_{\text{sub}.1}$ sample values to $w_{\text{sub}.1} \times h_{\text{sub}.1}$ predicted values for an $w_{\text{sub}.1} \times h_{\text{sub}.1}$ array of sample positions and each linear or affine linear transformation within second set of linear or affine linear transformations is for transforming $N_{\text{sub}.2}$ sample values to $w_{\text{sub}.2} \times h_{\text{sub}.2}$ predicted values for an $w_{\text{sub}.2} \times h_{\text{sub}.2}$ array of sample positions, wherein for a first predetermined one of the first set of width/height pairs, $w_{\text{sub}.1}$ may exceed the width of the first predetermined width/height pair or $h_{\text{sub}.1}$ may exceed the height of the first predetermined width/height pair, and for a second predetermined one of the first set of width/height pairs neither $w_{\text{sub}.1}$ may exceed the width of the second predetermined width/height pair nor $h_{\text{sub}.1}$ exceeds the height of the second predetermined width/height pair. The reducing (100), by averaging, the plurality of neighbouring samples to obtain the reduced set (102) of samples values might then be done so that the reduced set 102 of samples values has $N_{\text{sub}.1}$ sample values if the predetermined block is of the first predetermined width/height pair and if the predetermined block is of the second predetermined width/height pair, and the subjecting the reduced set of sample values to the selected linear or affine linear transformation might be performed by using only a first sub-portion of the selected linear or affine linear transformation which is related to a subsampling of the $w_{\text{sub}.1} \times h_{\text{sub}.1}$ array of sample positions along width dimension if $w_{\text{sub}.1}$ exceeds the width of the one width/height pair, or along height dimension if $h_{\text{sub}.1}$ exceeds the height of the one width/height pair if the predetermined block is of the first predetermined width/height pair, and the selected linear or affine linear transformation completely if the predetermined block is of the second predetermined width/height pair.

(221) Each linear or affine linear transformation within first set of linear or affine linear transformations may be for transforming $N_{\text{sub}.1}$ sample values to $w_{\text{sub}.1} \times h_{\text{sub}.1}$ predicted values for an $w_{\text{sub}.1} \times h_{\text{sub}.1}$ array of sample positions with $w_{\text{sub}.1} = h_{\text{sub}.1}$ and each linear or affine linear transformation within second set of linear or affine linear transformations is for transforming $N_{\text{sub}.2}$ sample values to $w_{\text{sub}.2} \times h_{\text{sub}.2}$ predicted values for an $w_{\text{sub}.2} \times h_{\text{sub}.2}$ array of sample positions with $w_{\text{sub}.2} = h_{\text{sub}.2}$.

(222) All of the above described embodiments are merely illustrative in that they may form the basis for the embodiment described herein below. That is, above concepts and details shall serve to understand the following embodiments and shall serve as a reservoir of possible extensions and amendments of the embodiments described herein below. In particular, many of the above described details are optional such as the averaging of neighboring samples, the fact the neighboring samples are used as reference samples and so forth.

(223) More generally, the embodiments described herein assume that a prediction signal on a rectangular block is generated out of already reconstructed samples such as an intra prediction signal on a rectangular block is generated out of neighboring, already reconstructed samples left

and above the block. The generation of the prediction signal is based on the following steps. 1. Out of the reference samples, called boundary sample now without, however, excluding the possibility of transferring the description to reference samples positioned elsewhere, samples may be extracted by averaging. Here, the averaging is carried out either for both the boundary samples left and above the block or only for the boundary samples on one of the two sides. If no averaging is carried out on a side, the samples on that side are kept unchanged. 2. A matrix vector multiplication, optionally followed by addition of an offset, is carried out where the input vector of the matrix vector multiplication is either the concatenation of the averaged boundary samples left of the block and the original boundary samples above the block if averaging was applied only on the left side, or the concatenation of the original boundary samples left of the block and the averaged boundary samples above the block if averaging was applied only on the above side or the concatenation of the averaged boundary samples left of the block and the averaged boundary samples above the block if averaging was applied on both sides of the block. Again, alternatives would exist, such as ones where averaging isn't used at all. 3. The result of the matrix vector multiplication and the optional offset addition may optionally be a reduced prediction signal on a subsampled set of samples in the original block. The prediction signal at the remaining positions may be generated from the prediction signal on the subsampled set by linear interpolation.

(224) The computation of the matrix vector product in Step 2 should be carried out in integer arithmetic. Thus, if $x=(x_{\text{sub.1}}, \dots, x_{\text{sub.n}})$ denotes the input for the matrix vector product, i.e. x denotes the concatenation of the (averaged) boundary samples left and above the block, then out of x , the (reduced) prediction signal computed in Step 2 has should be computed using only bit shifts, the addition of offset vectors, and multiplications with integers. Ideally, the prediction signal in Step 2 would be given as $Ax+b$ where b is an offset vector that might be zero and where A is derived by some machine-learning based training algorithm. However, such a training algorithm usually only results in a matrix $A=A_{\text{sub.float}}$ that is given in floating point precision. Thus, one is faced with the problem to specify integer operations in the aforementioned sense such that the expression $A_{\text{sub.float}}x$ is well approximated using these integer operations. Here, it is important to mention that these integer operations are not necessarily chosen such that they approximate the expression $A_{\text{sub.float}}x$ assuming a uniform distribution of the vector x but typically take into account that the input x vectors x for which the expression $A_{\text{sub.float}}x$ is to be approximated are (averaged) boundary samples from natural video signals where one can expect some correlations between the components $x_{\text{sub.i}}$ of x .

(225) FIG. 8 shows an improved ALWIP-prediction. Samples of a predetermined block can be predicted based on a first matrix-vector product between a matrix **A 1100** derived by some machine-learning based training algorithm and a sample value vector **x 400**. Optionally an offset **b 1110** can be added. To achieve an integer approximation or a fixed-point approximation of this first matrix-vector product, the sample value vector can undergo an invertible linear transformation **403** to determine a further vector **402**. A second matrix-vector product between a further matrix **B 1200** and the further vector **402** can equal the result of the first matrix-vector product.

(226) Because of the features of the further vector **402** the second matrix-vector product can be integer approximated by a matrix-vector product **404** between a predetermined prediction matrix **C 405** and the further vector **402** plus a further offset **408**. The further vector **402** and the further offset **408** can consist of integer or fixed-point values. All components of the further offset are, for example, the same. The predetermined prediction matrix **405** can be a quantized matrix or a matrix to be quantized. The result of the matrix-vector product **404** between the predetermined prediction matrix **405** and the further vector **402** can be understood as a prediction vector **406**.

(227) In the following more details regarding this integer approximation are provided.

(228) Possible Solution According to an Example I: Subtracting and Adding Mean Values

(229) One possible incorporation of an integer approximation of an expression $A_{\text{sub.float}}x$ useable in a scenario above, is to replace the $i_{\text{sub.0}}$ -th component $x_{\text{sub.i.sub.0}}$, i.e. a predetermined

component **1500**, of x , i.e. the sample value vector **400**, by the mean value $\text{mean}(x)$, i.e. a predetermined value **1400**, of the components of x and to subtract this mean value from all other components. In other words, the invertible linear transform **403**, as shown in FIG. **9a**, is defined such that a predetermined component **1500** of the further vector **402** becomes a, and each of other components of the further vector **402**, except the predetermined component **1500**, equal a corresponding component of the sample value vector **400** minus a, wherein a is a predetermined value **1400** which is, for example, an average, such as an arithmetic mean or weighted average, of components of the sample value vector **400**. This operation on the input is given by an invertible transform **T 403** that has an obvious integer implementation in particular if the dimension n of x is a power of two.

(230) Since $A.\text{sub.float} = (A.\text{sub.float}T.\text{sup.} - 1)T$, if one does such a transformation on the input x , one has to find an integral approximation of the matrix vector product By , where $B = (A.\text{sub.float}T.\text{sup.} - 1)$ and $y = Tx$. Since the matrix-vector product $A.\text{sub.float}x$ represents a prediction on a rectangular block, i.e. a predetermined block, and since x **400** is comprised by (e.g., averaged) boundary samples of that block, one should expect that in the case where all sample values of x are equal, i.e. where $x.\text{sub.}i = \text{mean}(x)$ for all i , each sample value in the prediction signal $A.\text{sub.float}x$ should be close to $\text{mean}(x)$ or be exactly equal to $\text{mean}(x)$. This means that one should expect that the $i.\text{sub.}0$ -th column, i.e. the column corresponding to the predetermined component, of B is very close or equal to a column that consist only of ones. Thus, if $M(i.\text{sub.}0)$, i.e. an integer matrix **1300**, is the matrix whose $i.\text{sub.}0$ th column consists of ones and all of whose other columns are zero, writing $By = Cy + M(i.\text{sub.}0)y$ with $C = B - M(i.\text{sub.}0)$, one should expect that the $i.\text{sub.}0$ -th column **412** of C , i.e. the predetermined prediction matrix **405**, has rather small entries or is zero, as shown in FIG. **9b**. Moreover, since the components of x are correlated, one can expect that for each $i \neq i.\text{sub.}0$, the i -th component $y.\text{sub.}i = x.\text{sub.}i - \text{mean}(x)$ of y often has a much smaller absolute value than the i -th component of x . Since the matrix $M(i.\text{sub.}0)$ **1300** is an integer matrix, an integer approximation of By is achieved if an integer approximation of Cy is given and, by the above arguments, one can expect that the quantization error that arises by quantizing each entry of C **405** in a suitable way should only marginally impact the error in the resulting quantization of By resp. of $A.\text{sub.float}x$.

(231) The predetermined value **1400** is not necessarily the mean value $\text{mean}(x)$. The herein described integer approximation of the expression $A.\text{sub.float}X$ can also be achieved with the following alternative definitions of the predetermined value **1400**:

(232) In another possible incorporation of an integer approximation of an expression $A.\text{sub.float}x$, the $i.\text{sub.}0$ -th component $x.\text{sub.}i.\text{sub.}0$ of x remains unaltered and the same value $x.\text{sub.}i.\text{sub.}0$ is subtracted from all other components. That is, $y.\text{sub.}i.\text{sub.}0 = x.\text{sub.}i.\text{sub.}0$ and $y.\text{sub.}i = x.\text{sub.}i - x.\text{sub.}i.\text{sub.}0$ for each $i \neq i.\text{sub.}0$. In other words, the predetermined value **1400** can be a component of the sample value vector **400** corresponding to the predetermined component **1500**.

(233) Alternatively, the predetermined value **1400** is a default value or a value signaled in a data stream into which a picture is coded.

(234) The predetermined value **1400** equals, for example, $2.\text{sup.bitdepth} - 1$. In this case, the further vector **402** can be defined by $y.\text{sub.}0 = 2.\text{sup.bitdepth} - 1$ and $y.\text{sub.}i = x.\text{sub.}i - x.\text{sub.}0$ for $i > 0$.

(235) Alternatively, the predetermined component **1500** becomes a constant minus the predetermined value **1400**. The constant equals, for example, $2.\text{sup.bitdepth} - 1$. According to an embodiment, the predetermined component $y.\text{sub.}i.\text{sub.}0$ **1500** of the further vector y **402** equals $2.\text{sup.bitdepth} - 1$ minus a component $x.\text{sub.}i.\text{sub.}0$ of the sample value vector **400** corresponding to the predetermined component **1500** and all other components of the further vector **402** equal the corresponding component of the sample value vector **400** minus the component of the sample value vector **400** corresponding to the predetermined component **1500**.

(236) It is, for example, advantageous if the predetermined value **1400** has a small deviation from

prediction values of samples of the predetermined block.

(237) According to an embodiment, the apparatus **1000** is configured to comprise a plurality of invertible linear transforms **403**, each of which is associated with one component of the further vector **402**. Furthermore, the apparatus is, for example, configured to select the predetermined component **1500** out of the components of the sample value vector **400** and use the invertible linear transform **403** out of the plurality of invertible linear transforms which is associated with the predetermined component **1500** as the predetermined invertible linear transform. This is, for example, due to different positions of the i .sub.0.sup.th row, i.e. a row of the invertible linear transform **403** corresponding to the predetermined component, dependent on a position of the predetermined component in the further vector. If, for example, the first component, i.e. y .sub.1, of the further vector **402** is the predetermined component, the i .sub.0.sup.th row would replace the first row of the invertible linear transform.

(238) As shown in FIG. **9b**, matrix components **414** of the predetermined prediction matrix **C 405** within a column **412**, i.e. an i .sub.0.sup.th column, of the predetermined prediction matrix **405** which corresponds to the predetermined component **1500** of the further vector **402** are, for example, all zero. In this case, the apparatus is, for example, configured to compute the matrix-vector product **404** by performing multiplications by computing a matrix vector product **407** between a reduced prediction matrix **C' 405** resulting from the predetermined prediction matrix **C 405** by leaving away the column **412** and an even further vector **410** resulting from the further vector **402** by leaving away the predetermined component **1500**, as shown in FIG. **9c**. Thus a prediction vector **406** can be calculated with less multiplications.

(239) As shown in FIGS. **8**, **9b** and **9c**, the apparatus **1000** can be configured to, in predicting the samples of the predetermined block on the basis of the prediction vector **406**, compute for each component of the prediction vector **406** a sum of the respective component and a , i.e. the predetermined value **1400**. This summation can be represented by a sum of the prediction vector **406** and a vector **409** with all components of the vector **409** being equal to the predetermined value **1400**, as shown in FIG. **8** and FIG. **9c**. Alternatively the summation can be represented by a sum of the prediction vector **406** and a matrix-vector product **1310** between an integer matrix **M 1300** and the further vector **402**, as shown in FIG. **9b**, wherein matrix components of the integer matrix **1300** are 1 within a column, i.e. an i .sub.0.sup.th column, of the integer matrix **1300** which corresponds to the predetermined component **1500** of the further vector **402**, and all other components are, for example, zero.

(240) A result of a summation of the predetermined prediction matrix **C 405** and the integer matrix **1300** equals or approximates, for example, the further matrix **B 1200**, shown in FIG. **8**.

(241) In other words, a matrix, i.e. the further matrix **B 1200**, which results from summing each matrix component of the predetermined prediction matrix **C 405** within a column **412**, i.e. the i .sub.0.sup.th column, of the predetermined prediction matrix **405**, which corresponds to the predetermined component **1500** of the further vector **402**, with one, (i.e. matrix **B**) times the invertible linear transform **403** corresponds, for example, to a quantized version of a machine learning prediction matrix **A 1100**, as shown in FIG. **8**, FIG. **9a** and FIG. **9b**. The summing of each matrix component of the predetermined prediction matrix **C 405** within the i .sub.0.sup.th column **412** with one can correspond to the summation of the predetermined prediction matrix **405** and the integer matrix **1300**, as shown in FIG. **9b**. As shown in FIG. **8** the machine learning prediction matrix **A 1100** can equal the result of the further matrix **1200** times the invertible linear transform **403**. This is due to $A \cdot \text{Math.x} = B \cdot \text{Math.yT} \cdot \text{sup.} - 1$. The predetermined prediction matrix **405** is, for example, a quantized matrix, an integer matrix and/or a fixed-point matrix, whereby the quantized version of the machine learning prediction matrix **A 1100** can be realized.

(242) Matrix Multiplication Using Integer Operations Only

(243) For a low complexity implementation (in terms of complexity of adding and multiplying scalar values, as well as in terms of storage needed for the entries of the partaking matrix), it is

desirable to perform the matrix multiplications **404** using integer arithmetic only. To calculate an approximation of $z=Cy$, i.e.

$$(244) z_i = \text{Math.} \sum_{j=0}^{n-1} C_{ij} * y_j,$$

(245) using operations on integers only, the real values $C_{\text{sub.i,j}}$ is to be mapped to integer values $\hat{C}_{\text{sub.i,j}}$, according to an embodiment. This can be done for example by uniform scalar quantization, or by taking into account specific correlations between values $y_{\text{sub.i}}$. The integer values represent, for example fixed-point numbers that can each be stored with a fixed number of bits n_{bits} , for example $n_{\text{bits}}=8$.

(246) The matrix vector product **404** with a matrix, i.e. the predetermined prediction matrix **405**, of size $m \times n$ can then be carried out like shown in this pseudo code, where $\ll$, $\gg$ are arithmetic binary left- and right-shift operations and $+$, $-$ and $*$ operate on integer values only.

(247) TABLE-US-00003 (1) final_offset = 1 $\ll$ (right_shift_result - 1); for i in 0.. $m-1$ { accumulator = 0 for j in 0.. $n-1$ { accumulator := accumulator + $y[j]*C[i,j]$ } $z[i] = (\text{accumulator} + \text{final_offset}) \gg \text{right_shift_result}$; }

(248) Here, the array C, i.e. the predetermined prediction matrix **405**, stores the fixed point numbers, for example, as integers. The final addition of final_offset and the right-shift operation with right_shift_result reduce precision by rounding to obtain a fixed point format needed at the output.

(249) To allow for an increased range of real values representable by the integers in C, two additional matrices offset.sub.i,j and scale.sub.i,j can be used, as shown in the embodiments of FIG. **10** and FIG. **11**, such that each coefficient $b_{\text{sub.i,j}}$ of $y_{\text{sub.j}}$ in the matrix-vector product

$$(250) z_i = \text{Math.} \sum_{j=0}^{n-1} b_{ij} * y_j$$

is given by

$$b_{\text{sub.i,j}} = (\hat{C}_{\text{sub.i,j}} - \text{offset}_{\text{sub.i,j}}) * \text{scale}_{\text{sub.i,j}}.$$

(251) The values offset.sub.i,j and scale.sub.i,j are themselves integer values. For example these integers can represent fixed-point numbers that can each be stored with a fixed number of bits, for example 8 bits, or for example the same number of bits n_{bits} that is used to store the values $\hat{C}_{\text{sub.i,j}}$.

(252) In other words, the apparatus **1000** is configured to represent the predetermined prediction matrix **405** using prediction parameters, e.g. integer values $\hat{C}_{\text{sub.i,j}}$ and the values offset.sub.i,j and scale.sub.i,j, and to compute the matrix-vector product **404** by performing multiplications and summations on the components of the further vector **402** and the prediction parameters and intermediate results resulting therefrom, wherein absolute values of the prediction parameters are representable by an n -bit fixed point number representation with n being equal to or lower than 14, or, alternatively, 10, or, alternatively, 8. For instance, the components of the further vector **402** are multiplied with the prediction parameters to yield products as intermediate results which, in turn, are subject to, or form addends of, a summation.

(253) According to an embodiment, the prediction parameters comprise weights each of which is associated with a corresponding matrix component of the prediction matrix. In other words, the predetermined prediction matrix is, for example, replaced or represented by the prediction parameters. The weights are, for example, integer and/or fixed point values.

(254) According to an embodiment, the prediction parameters further comprise one or more scaling factors, e.g. the values scale.sub.i,j, each of which is associated with one or more corresponding matrix components of the predetermined prediction matrix **405** for scaling the weight, e.g. an integer value $\hat{C}_{\text{sub.i,j}}$, associated with the one or more corresponding matrix component of the predetermined prediction matrix **405**. Additionally or Alternatively, the prediction parameters comprise one or more offsets, e.g. the values offset.sub.i,j, each of which is associated with one or more corresponding matrix components of the predetermined prediction matrix **405** for offsetting

the weight, e.g. an integer value $\hat{C}_{sub.i,j}$, associated with the one or more corresponding matrix component of the predetermined prediction matrix **405**.

(255) In order to reduce the amount of storage needed for $offset_{sub.i,j}$ and $scale_{sub.i,j}$, their values can be chosen to be constant for particular sets of indices i,j . For example, their entries can be constant for each column or they can be constant for each row, or they can be constant for all i,j , as shown in FIG. **10**.

(256) For example, in one embodiment, $offset_{sub.i,j}$ and $scale_{sub.i,j}$ are constant for all values of a matrix of one prediction mode, as shown in FIG. **11**. Thus, when there are K prediction modes with $k=0 \dots K-1$, only a single value $o_{sub.k}$ and a single value $s_{sub.k}$ is needed to calculate the prediction for mode k .

(257) According to an embodiment, $offset_{sub.i,j}$ and/or $scale_{sub.i,j}$ are constant, i.e. identical, for all matrix-based intra prediction modes. Additionally or Alternatively, it is possible, that $offset_{sub.i,j}$ and/or $scale_{sub.i,j}$ are constant, i.e. identical, for all block sizes.

(258) With offset representing $o_{sub.k}$ and scale representing $s_{sub.k}$, the calculation in (1) can be modified to be:

(259) TABLE-US-00004 (2) $final_offset = 0$; for i in $0..n-1$ { $final_offset := final_offset - y[i]$; } $final_offset *= final_offset * offset * scale$; $final_offset += 1 \ll (right_shift_result - 1)$; for i in $0..m-1$ { $accumulator = 0$ for j in $0..n-1$ { $accumulator := accumulator + y[j]*C[i,j]$ } $z[i] = (accumulator*scale + final_offset) >> right_shift_result$; }

(260) Broadened embodiments arising from that solution

(261) The above solution implies the following embodiments: 1. A prediction method as in Section I, where in Step 2 of Section I, the following is done for an integer approximation of the involved matrix vector product: Out of the (averaged) boundary samples $x=(x_{sub.1}, \dots, x_{sub.n})$, for a fixed $i_{sub.0}$ with $1 \leq i_{sub.0} \leq n$, the vector $y=(y_{sub.1}, \dots, y_{sub.n})$ is computed, where $y_{sub.i}=x_{sub.i}-mean(x)$ for $i \neq i_{sub.0}$ and where $y_{sub.i_{sub.0}}=mean(x)$ and where $mean(x)$ denotes the mean-value of x . The vector y then serves as an input for (an integer realization of) a matrix vector product Cy such that the (downsampled) prediction signal $pred$ from Step 2 of Section I is given as $pred=Cy+meanpred(x)$. In this equation, $meanpred(x)$ denotes the signal that is equal to $mean(x)$ for each sample position in the domain of the (downsampled) prediction signal. (see, e.g., FIG. **9b**) 2. A prediction method as in Section I, where in Step 2 of Section I, the following is done for an integer approximation of the involved matrix vector product: Out of the (averaged) boundary samples $x=(x_{sub.1}, \dots, x_{sub.n})$, for a fixed $i_{sub.0}$ with $1 \leq i_{sub.0} \leq n$, the vector $y=(y_{sub.i}, \dots, y_{sub.n-1})$ is computed, where $y_{sub.i}=x_{sub.i}-mean(x)$ for $i < i_{sub.0}$ and where $y_{sub.i}=x_{sub.i+1}-mean(x)$ for $i \geq i_{sub.0}$ and where $mean(x)$ denotes the mean-value of x . The vector y then serves as an input for (an integer realization of) a matrix vector product Cy such that the (downsampled) prediction signal $pred$ from Step 2 of Section I is given as $pred=Cy+meanpred(x)$. In this equation, $meanpred(x)$ denotes the signal that is equal to $mean(x)$ for each sample position in the domain of the (downsampled) prediction signal. (see, e.g., FIG. **9c**) 3. A prediction method as in Section I, where the integer realization of the matrix vector product Cy is given by using coefficients $b_{sub.i,j}=(\hat{C}_{sub.i,j}-offset_{sub.i,j})*scale_{sub.i,j}$ in the matrix-vector product $z_{sub.i}=\sum_{sub.j} b_{sub.i,j}*y_{sub.j}$. (see, e.g., FIG. **10**) 4. A prediction method as in Section I, where step 2 uses one of K matrices, such that multiple prediction modes can be calculated, each using a different matrix $\hat{C}_{sub.k}$ with $k=0 \dots K-1$, where the integer realization of the matrix vector product $C_{sub.k}y$ is given by using coefficients $b_{sub.i,j}=(\hat{C}_{sub.k,i,j}-offset_{sub.k})*scale_{sub.k}$ in the matrix-vector product $z_{sub.i}=\sum_{sub.j} b_{sub.i,j}*y_{sub.j}$. (see, e.g., FIG. **11**)

(262) That is, in accordance with embodiments of the present application, encoder and decoder act as follows in order to predict a predetermined block **18** of a picture **10**, see FIG. **8**. For predicting, a plurality of reference samples is used. As outlined above, embodiments of the present application would not be restricted to intra-coding and accordingly, reference samples would not be restricted

to be neighboring samples, i.e. samples of picture **10** neighboring block **18**. In particular, the reference samples would not be restricted to the ones arranged alongside an outer edge of block **18** such as samples abutting the block's outer edge. However, this circumstance is certainly one embodiment of the present application.

(263) In order to perform the prediction, a sample value vector **400** is formed out of the reference samples such as reference samples **17a** and **17c**. A possible formation has been described above. The formation may involve an averaging, thereby reducing the number of samples **102** or the number of components of vector **400** compared to the reference samples **17** contributing to the formation. The formation may also, as described above, somehow depend on the dimension or size of block **18** such as its width and height.

(264) It is this vector **400** which is ought to be subject to an affine or linear transform in order to obtain the prediction of block **18**. Different nomenclatures have been used above. Using the most recent one, it is the aim to perform the prediction by applying vector **400** to matrix A by way of a matrix vector product within performing a summation with an offset vector b. The offset vector b is optional. The affine or linear transformation determined by A or A and b, might be determined by encoder and decoder or, to be more precise, for sake of prediction on the basis of the size and dimension of block **18** as already described above.

(265) However, in order to achieve the above-outlined computational efficiency improvement or render the prediction more effective in terms of implementation, the affine or linear transform has been quantized, and encoder and decoder, or the predictor thereof, used the above-mentioned C and T in order to represent and perform the linear or affine transformation, with C and T, applied in the manner described above, representing a quantized version of the affine transformation. In particular, instead of applying vector **400** directly to a matrix A, the predictor in encoder and decoder, applies vector **402** resulting from the sample value vector **400** by way of subjecting same to a mapping via a predetermined invertible linear transform T. It might be that transform T as used here is the same as long as vector **400** has the same size, i.e. does not depend on the block's dimensions, i.e. width and height, or is at least the same for different affine/linear transformations. In the above, vector **402** has been denoted y. The exact matrix in order to perform the affine/linear transform as determined by machine learning would have been B. However, instead of exactly performing B, the prediction in encoder and decoder is done by way of an approximation or quantized version thereof. In particular, the representation is done via appropriately representing C in the manner outlined above with C+M representing the quantized version of B.

(266) Accordingly, the prediction in encoder and decoder is further prosecuted by computing the matrix-vector product **404** between vector **402** and the predetermined prediction matrix C appropriately represented and stored at encoder and decoder in the manner described above. The vector **406** which results from this matrix-vector product, is then used for predicting the samples **104** of block **18**. As described above, for sake of prediction, each component of vector **406** might be subject to a summation with parameter a as indicated at **408** in order to compensate for the corresponding definition of C. The optional summation of vector **406** with offset vector b may also be involved in the derivation of the prediction of block **18** on the basis of vector **406**. It might be that, as described above, each component of vector **406**, and accordingly, each component of the summation of vector **406**, the vector of all a's indicated at **408** and the optional vector b, might directly correspond to samples **104** of block **18** and, thus, indicate the predicted values of the samples. It may also be that only a sub-set of the block's samples **104** is predicted in that manner and that the remaining samples of block **18**, such as **108**, are derived by interpolation.

(267) As described above, there are different embodiments for setting a. For instance, it might be the arithmetic mean of the components of vector **400**. For that case, see FIG. **9a**. The invertible linear transform T **403** may be as indicated in the FIG. **9a**. i.sub.0 is the predetermined component of the sample value vector and vector **402**, respectively, which is replaced by a. However, as also indicated above, there are other possibilities. However, as far as the representation of C is

concerned, it has also been indicated above that same may be embodied differently. For instance, the matrix-vector product **404** may, in its actual computation, end up in the actual computation of a smaller matrix-vector product with lower dimensionality. In particular, as indicated above, it might be that owing to the definition of C, its whole i.sub.0.sup.th column **412** gets 0 so that the actual computation of product **404** may be done by a reduced version of vector **402** which results from vector **402** by the omission of component y.sub.i.sub.0, namely by multiplying this reduced vector **410** with the reduced matrix C' resulting from C by leaving out the i.sub.0.sup.th column **412**.

(268) The weights of C or the weights of C', i.e. the components of this matrix, may be represented and stored in fixed-point number representation. These weights **414** may, however, also, as described above, be stored in a manner related to different scales and/or offsets. Scale and offset might be defined for the whole matrix C, i.e. be equal for all weights **414** of matrix C or matrix C', or may be defined in a manner so as to be constant or equal for all weights **414** of the same row or all weights **414** of the same column of matrix C and matrix C', respectively. FIG. **10** illustrates, in this regard, that the computation of the matrix-vector product, i.e. the result of the product, may in fact be performed slightly different, namely for instance, by shifting the multiplication with the scale(s) towards the vector **402** or **410**, thereby reducing the number of multiplications having to be performed further. FIG. **11** illustrates the case of using one scale and one offset for all weights **414** of C or C' such as done in above calculation (2).

(269) According to an embodiment, the herein described apparatus for predicting a predetermined block of a picture can be configured to use a matrix-based intra sample prediction comprising the following features:

(270) The apparatus is configured to form a sample value vector pTemp[x] **400** out of the plurality of reference samples **17**. Assuming pTemp[x] to be 2*boundarySize, pTemp[x] might be populated by—e.g. by direct copying or by sub-sampling or pooling—the neighboring samples located at the top of the predetermined block, redT[x] with x=0 . . . boundarySize-1, followed by the neighboring samples located to the left of the predetermined block, redL[x] with x=0 . . . boundarySize-1, (e.g. in case of isTransposed=0) or vice versa in case of the transposed processing (e.g. in case of isTransposed=1).

(271) The input values p[x] with x=0 . . . inSize-1 are derived, i.e. the apparatus is configured to derive from the sample value vector pTemp[x] a further vector p[x] onto which the sample value vector pTemp[x] is mapped by a predetermined invertible linear transform, or to be more specific predetermined invertible affine linear transform, as follows: If mipSizeId is equal to 2, the following applies: p[x]=pTemp[x+1]-pTemp[0] Otherwise (mipSizeId is less than 2), the following applies: p[0]=(1<<(BitDepth-1))-pTemp[0] p[x]=pTemp[x]-pTemp[0] for x=1 . . . inSize-1

(272) Here, the variable mipSizeId is indicative of the size of predetermined block. That is, according to the present embodiment, the invertible transform using which the further vector is derived from the sample value vector, depends on the size of the predetermined block. The dependency might be given according to

(273) TABLE-US-00005 mipSizeId boundarySize predSize 0 2 4 1 4 4 2 4 8

(274) Where predSize is indicative of the number of predicted samples within the predetermined block, and 2*boundarySize is indicative of the size of the sample value vector and is related to inSize, i.e. the further vector's size, according to inSize=(2*boundarySize)-(mipSizeId==2)? 1:0. To be more precise, inSize indicates the number of those components of the further vector which actually participate in the computation. inSize is as large as the size of sample value vector for smaller block sizes, and one component smaller for larger block sizes. In the former case, one component may be disregarded, namely the one which would correspond to the predetermined component of the further vector, as in the matrix vector product to be computed later on, the contribution of the corresponding vector component would yield zero anyway and, thus, needs not to be actually computed. The dependency on the block size might be left off in case of alternative embodiments, where merely one of the two alternatives is used inevitably, i.e. irrespective of the

block size (the option corresponding to mipSizeId is less than 2, or the option corresponding to mipSizeId equal to 2).

(275) In other words, the predetermined invertible linear transform is, for example, defined such that a predetermined component of the further vector p becomes a, while all others correspond to a component of the sample value vector minus a, wherein e.g. $a=pTemp[0]$. In case of the first option corresponding to mipSizeId equal to 2, this is readily visible and only the differentially formed components of the further vector are further taken into account. That is, in the case of the first option, the further vector is actually $\{p[0 \dots inSize]; pTemp[0]\}$ wherein pTemp[0] is a and the actually computed part of the matrix vector multiplication to yield the matrix vector product, i.e. the result of the multiplication, is restricted to only inSize components of the further vector and the corresponding columns of the matrix, as the matrix has a zero column which needs no computation. In other case, corresponding to mipSizeId smaller than 2, $a=pTemp[0]$ is chosen, as all components of the further vector except p[0], i.e. each of other components p[x] (for $x=1 \dots inSize-1$) of the further vector p, except the predetermined component p[0], equal a corresponding component of the sample value vector pTemp[x] minus a, but p[0] is chosen to be a constant minus a. The matrix vector product is then computed. The constant is the mean of representable values, i.e. $2^{sup.x-1}$ (i.e. $1 < (BitDepth-1)$) with x denoting the bit depth of the computational representation used. It should be noted that, if p[0] was selected to be pTemp[0] instead, then the product computed would simply deviate from the one computed using p[0] as indicated above ($p[0]=(1 < (BitDepth-1)) - pTemp[0]$), by a constant vector which could be taken into account when predicting the block inner based on the product, i.e. the prediction vector. The value a is, thus, a predetermined value, e.g., pTemp[0]. The predetermined value pTemp[0] is in this case, for example, a component of the sample value vector pTemp corresponding to the predetermined component p[0]. It might be the neighboring sample to the top of the predetermined, or the left of the predetermined block, nearest to the upper left corner of the predetermined block.

(276) For the intra sample prediction process according to predModeIntra, e.g., specifying the intra prediction mode, the apparatus is, for example, configured to apply the following steps, e.g. perform at least the first step: 1. The matrix-based intra prediction samples predMip[x][y], with $x=0 \dots predSize-1$, $y=0 \dots predSize-1$ are derived as follows: The variable modeId is set equal to predModeIntra. The weight matrix mWeight[x][y] with $x=0 \dots inSize-1$, $y=0 \dots predSize*predSize-1$ is derived by invoking the MIP weight matrix derivation process with mipSizeId and modeId as inputs. The matrix-based intra prediction samples predMip[x][y], with $x=0 \dots predSize-1$, $y=0 \dots predSize-1$ are derived as follows:

$$(277) oW = 32 - 32 * (\text{Math}.\sum_{i=0}^{inSize-1} p[i])$$

$predMip[x][y] = (((\text{Math}.\sum_{i=0}^{inSize-1} mWeight[i][y*predSize+x]*p[i]) + oW) \gg 6) + pTemp[0]$ In other words, the apparatus is configured to compute a matrix-vector product between the further vector p[i] or, in case of mipSizeId equal to 2, $\{p[i]; pTemp[0]\}$ and a predetermined prediction matrix mWeight or, in case of mipSizeId smaller than 2, the prediction matrix mWeight having an additional zero weight line corresponding to the omitted component of p, so as to obtain a prediction vector, which, here, has already been assigned to an array of block positions {x,y} distributed in the inner of the predetermined block so as to result in the array predMip[x][y]. The prediction vector would correspond to a concatenation of the rows of predMip[x][y] or the columns of predMip[x][y], respectively. According to an embodiment, or according to a different interpretation, only the component $((\sum_{sub.i=0}^{sup.inSize-1} mWeight[i][y*predSize+x]*p[i]) + oW) \gg 6$ is understood as the prediction vector and the apparatus is configured to, in predicting the samples of the predetermined block on the basis of the prediction vector, compute for each component of the prediction vector a sum of the respective component and a, e.g. pTemp[0]. The apparatus can optionally be configured to perform additionally the following steps in predicting the samples of the predetermined block on the basis of the prediction vector, e.g. predMip or $((\sum_{sub.i=0}^{sup.inSize-1} mWeight[i][y*predSize+x]*p[i]) + oW) \gg 6$. 2. The

matrix-based intra prediction samples $\text{predMip}[x][y]$, with $x=0 \dots \text{predSize}-1$, $y=0 \dots \text{predSize}-1$ are, for example, clipped as follows:

$\text{predMip}[x][y] = \text{Clip1}(\text{predMip}[x][y])$ 3. When isTransposed is equal to TRUE, the $\text{predSize} \times \text{predSize}$ array $\text{predMip}[x][y]$ with $x=0 \dots \text{predSize}-1$, $y=0 \dots \text{predSize}-1$ is, for example, transposed as follows:

$\text{predTemp}[y][x] = \text{predMip}[x][y]$

$\text{predMip} = \text{predTemp}$ 4. The predicted samples $\text{predSamples}[x][y]$, with $x=0 \dots \text{nTbW}-1$, $y=0 \dots \text{nTbH}-1$ are, for example, derived as follows: If nTbW , specifying the transform block width, is greater than predSize or nTbH , specifying the transform block height, is greater than predSize , the MIP prediction upsampling process is invoked with the input block size predSize , matrix-based intra prediction samples $\text{predMip}[x][y]$ with $x=0 \dots \text{predSize}-1$, $y=0 \dots \text{predSize}-1$, the transform block width nTbW , the transform block height nTbH , the top reference samples $\text{refT}[x]$ with $x=0 \dots \text{nTbW}-1$, and the left reference samples $\text{refL}[y]$ with $y=0 \dots \text{nTbH}-1$ as inputs, and the output is the predicted sample array predSamples . Otherwise, $\text{predSamples}[x][y]$, with $x=0 \dots \text{nTbW}-1$, $y=0 \dots \text{nTbH}-1$ is set equal to $\text{predMip}[x][y]$.

(278) In other words, the apparatus is configured to predict samples predSamples of the predetermined block on the basis of the prediction vector predMip .

8. USING BLOCK/MATRIX-BASED INTRA PREDICTION MODES ALONG WITH OTHER INTRA-PREDICTION MODES

(279) The following description presents, again, possibilities for combining block/matrix based prediction with other intra-prediction modes. It represents a further presentation of possibilities based on which the embodiments described in the subsequent section may be embodied.

(280) Please note that in the following, the term block-based intra prediction is used to denote an intra-prediction mode which may be embodied or equal those indicated by ALWIP above.

(281) With this, the embodiments described in the following with respect to FIG. 12 relate to decoders and encoders supporting intra-prediction for decoding/encoding a predetermined block 18 wherein different intra-prediction modes are supported. There are angular intra-prediction modes 500 according to which reference samples 17 neighboring the predetermined block 18 are used in order to fill the predetermined block 18 so as to obtain an intra-prediction signal for the predetermined block 18. In particular, the reference samples 17 which are arranged alongside a boundary of the predetermined block 18 such as alongside the upper and left hand edge of the predetermined block 18, represent picture content which is extrapolated, or copied, along a predetermined direction 502 into the inner of the predetermined block 18. Before the extrapolation or copying, the picture content represented by the neighboring samples 17 might be subject to interpolation filtering or differently speaking may be derived from the neighboring samples 17 by way of interpolation filtering. The angular intra-prediction modes 500 mutually differ in the intra-prediction direction 502. Each angular intra-prediction mode 500 may have an index associated with, wherein the association of indexes to the angular intra-prediction modes 500 may be such that the directions 500, when ordering the angular intra-prediction mode 500 according to the associated mode indexes, monotonically rotate clockwise or anticlockwise.

(282) There may also be non-angular intra-prediction modes. 504, for instance, illustrates in FIG. 12 a planar intra-prediction mode as optionally contained in set 508, according to which a two-dimensional linear function defined by a horizontal slope, a vertical slope and an offset is derived based on neighboring samples 17, with this linear function defining predicted sample values of the predetermined block 18. Horizontal slope, vertical slope and offset are derived on the basis of the neighboring samples 17. According to an embodiment, the first set 508 of intra-prediction modes comprises the planar intra-prediction mode 504.

(283) A specific non-angular intra prediction mode, the DC mode, which is contained in set 508, is illustrated at 506. Here, one value, quasi a DC value, is derived on the basis of the neighboring sample 17 and this one DC value is attributed to all samples of the predetermined block 18 so as to

obtain the intra-prediction signal. Although two examples for a non-intra-prediction mode are shown, merely one or more than two may be present.

(284) The intra-prediction modes **500**, **504** and **506** form a set **508** of intra-prediction modes which are supported by encoder and decoder in which compete, in terms of rate/distortion optimization sense, with the block-based intra-prediction modes generally indicated using reference sign **510** for which examples where discussed above using the abbreviation ALWIP. As described above, according to these block-based intra-prediction modes **510**, a matrix-vector product **520** is performed between a vector **514** which is derived from the neighboring samples **17** on the one hand and a predetermined prediction matrix **516** on the other hand. The result of the multiplication **520** is a prediction vector **518** which is used to predict the samples of the predetermined block **18**. The block-based intra-prediction modes **510** mutually differ in the prediction matrix **516** associated with the respective mode.

(285) Thus, briefly summarizing, encoders and decoders according to embodiments described herein comprise a set **508** of intra-prediction modes, i.e. a first set of intra-prediction modes and a set **520** of block-based intra-prediction modes, i.e. a second set of matrix-based intra-prediction modes, and they compete with each other.

(286) In accordance with embodiments of the present application, the predetermined block **18** is coded/decoded using intra-prediction in the following manner. In particular, firstly a set-selecting syntax element **522** whether the predetermined block **18** is to be predicted using any of the set **508** of intra-prediction modes, or any of modes of set **520** of block-based intra-prediction modes. If the set-selected syntax element indicates that the predetermined block **18** is to be predicted using any mode of set **508**, i.e. of the first set of intra-prediction modes, a list **528** of most probable candidates out of set **508** is construed/formed at decoder and encoder on the basis of intra-prediction modes using which neighboring blocks, which neighbor block **18**, and which are exemplarily indicated at **524** and **526**, have been predicted. The neighboring blocks **524** and **526** may be determined relative to the position of predetermined block **18** in a predetermined manner such as by determining those neighboring blocks which overlay certain neighboring samples of block **18** such as the sample to the top of the upper left hand sample of block **18**, and the block **526** containing the sample to the left of the just-mentioned corner sample. Naturally, this is only an example. The same applies to the number of neighbouring blocks used for mode prediction which is not restricted to be two for all embodiments. More than two or just one may be used. If any of these blocks **524** and **526** is missing, a default intra-prediction mode may be used by default as a substitute for the intra-prediction mode of that missing neighbouring block. The same may apply if any of the blocks **524** and **526** has been coded/decoded using an inter-prediction mode such as by motion compensated prediction.

(287) The construction of the list of modes out of set **508**, i.e., list **528** of most probable intra-prediction modes is as follows. The list-length of list **528**, i.e., the number of most probable modes therein, may be fixed by default. The length may be four as illustrated in FIG. **12**, or may be different therefrom, such as being five or six. The latter case applies to the specific example described hereinbelow. An index in the data stream to be described later may indicate one mode out of list **528** to be used for predetermined block **18**. The indexing is performed along a list order or ranking **530** with a list index being, for instance, variable length coded so that the length of the index increases monotonically along order **530**. Accordingly, it is worthwhile to, firstly, populate list **528** with the most probable modes out of set **508** only, and to place, along order **530**, modes more probable upstream relative to modes having lower probability of being suitable for block **18**. The modes of list **528** are derived based on the modes used for blocks **524** and **526**, i.e. neighbouring blocks neighbouring the predetermined block **18**. If any of blocks **524** and **526** has been intra-predicted using a block-based mode **510** out of set **520**, the afore-described mapping from such

(288) “ALWIP” or block-based modes **510** onto the modes within set **508**, let's say non-ALWIP

modes, is used. The latter mapping may, for instance, map a majority (i.e. more than the half) of the block-based modes **510** onto the DC mode **506** (or any of the DC **506** or planar mode **504**).

(289) According to an embodiment, the list **528** of most probable intra-prediction modes is populated with the planar intra-prediction mode **504** in a manner independent from the intra-prediction modes using when the neighboring blocks are predicted. Thus, for example, only the DC intra-prediction mode **506** and the angular intra-prediction modes **500** are populated in the list **528** dependent on the intra-prediction modes used for a prediction of the neighboring blocks **524** and **526**. The planar intra-prediction mode **504** is, for example, positioned at a first position of the list **528** of most-probable intra-prediction modes independent from the intra-prediction modes using when the neighboring blocks **524** and **526** are predicted.

(290) In a manner exemplarily illustrated in more detail below, the list construction of list **528** of most probable intra-prediction modes is done in a manner so that the list **528** is free of the DC intra-prediction mode **506** if the neighboring blocks **524** and **526** have exclusively been predicted by any angular intra-prediction mode **500**. The DC intra prediction mode **506** is not in the list **528** of most probable intra-prediction modes if one neighboring blocks **524** or **526** is predicted by any angular intra-prediction mode **500** and/or if both neighboring blocks **524** and **526** are predicted by any angular intra-prediction mode **500**. In accordance with the embodiment set out herein below, for instance, list **528** is populated with the DC mode **506** only in case of the following circumstance being true for all neighboring blocks **524** and **526**: either same has been coded using any of the non-angular intra-prediction modes **504** and **506**, or same has been intra-predicted using any block-based intra-prediction mode **510** which, by way of the afore-mentioned mapping from block-based intra-prediction modes **510** onto the modes within set **508**, is mapped onto any of the non-angular intra-prediction modes **504** and **506**. Merely in the that case, the DC intra-prediction mode **506**, is positioned in list **528**. In that case, it might be positioned before any angular intra-prediction mode **500** in the order **530** as may be seen from the subsequent example.

(291) In other words, the list **528** of most probable intra-prediction modes is, for example, populated with the DC intra-prediction mode **506** only in case of, for each of the neighboring blocks **524** and **526**, the respective neighbouring block predicted using any of at least one non-angular intra-prediction modes **504** and **506** with the first set **508**, which comprise the DC intra-prediction mode **506**, or predicted using any of block-based intra-prediction modes **510** which, by way of a mapping from the second set **520** of block-based intra-prediction modes **510** onto the intra-prediction modes within the first set **508**, which is used for the formation of the list **528** of most probable intra-prediction modes, is mapped onto any of the at least one non-angular intra-prediction modes **500**. The DC intra-prediction mode **506**, for example, is positioned before any angular intra-prediction mode **500** in the list **528** of most probable intra-prediction modes.

(292) Thus, resuming the description as to how predetermined block **18** is coded into the data stream **12**, the data stream **12** contains, if the set-selective syntax element **522** indicates that the predetermined block **18** is to be coded by any mode out of the first set **508**, optionally an MPM syntax element **532** which indicates whether the intra-prediction mode to be used for predetermined block **18** is within list **528** and if yes, the data stream **12** comprises an MPM list index **534** pointing into list **528** indicating the mode, i.e. a predetermined intra-prediction mode, to be used for predetermined block **18** out of list **528** by indexing same along order **530**. If, however, the mode out of set **508** is not within list **528**, as indicated by the MPM syntax element **532**, then the data stream **12** comprises for block **18** a further syntax element **536** indicating which mode, i.e. a predetermined intra-prediction mode, is to be used for block **18** out of set **508**. The further syntax element **536** may indicate the mode in a manner by merely distinguishing between those modes out of set **508**, which are not contained in list **528**.

(293) In other words, an apparatus for decoding the predetermined block **18**, for example, is configured to derive the MPM syntax element **532** from the data stream which indicates whether the predetermined intra-prediction mode of the first set **508** of intra-prediction modes is within the

list **528** of most probable intra-prediction modes or not, if the set-selective syntax element **522** indicates that the predetermined block **18** is to be predicted using one of the first set **508** of intra-prediction modes. If the MPM syntax element **532** indicates that the predetermined intra-prediction mode of the first set **508** of intra-prediction modes is within the list **528** of most probable intra-prediction modes, the apparatus, for example, is configured to perform the formation of the list **528** of most probable intra-prediction modes on the basis of intra-prediction modes using when neighbouring blocks **524**, **526** neighbouring the predetermined block **100** are predicted and perform the derivation of the MPM list index **534** from the data stream **12** which points to a predetermined intra-prediction mode of the list **528** of most probable intra-prediction modes. If the MPM syntax element **532** from the data stream **12** indicates that the predetermined intra-prediction mode of the first set **508** of intra-prediction modes is not within the list **528** of most probable intra-prediction modes, the apparatus is configured to derive a further list index **536** from the data stream which indicates the predetermined intra-prediction mode out of the first set of intra-prediction modes. Thus based on the MPM syntax element **532** the data stream **12** comprises either the MPM list index **534** or the further list index **536** for the prediction of the predetermined block **18**.

(294) By removing the circumstances where list **528** comprises a DC intra-prediction mode **506**, the following advantage is achieved. In particular, the inventors of the present application found out that “consuming” valuable list positions of list **528** with the DC intra-prediction mode **506** out of set **508** for coding/decoding the predetermined block **18** which is ought to use any of the intra-prediction modes of set **508** as indicated by syntax element **522**, i.e. the set-selective syntax element, would negatively affect the coding efficiency as such DC intra-prediction mode **506** out of set **508** competes, anyway, with the block-based intra-prediction modes **510**. Accordingly, “consuming” the list positions of list **528** with such DC intra-prediction mode **506** out of set **508** would result into an increased likelihood for a situation where the intra-prediction mode, i.e. the predetermined intra-prediction mode, to be finally used for the predetermined block **18** is not within list **528** so that the syntax element **536**, i.e. the further list index, needs to be transmitted in data stream **12**.

(295) In particular, as the syntax element **522** already indicates for a block **18** whether the same should be predicted using any of the modes within set **508** or any of the block-based modes **510** of the set **520**, it seems as if, if the syntax element **522** indicates that the modes within set **508** are to be advantageous for block **18**, and that, accordingly, the block-based modes **510** are not to be used for block **18**, the likelihood that the DC prediction mode **506** out of set **508** could be suitable for block **18** is so low that the occurrence thereof in list **528** should be restricted to a very limited set of constellations of modes used for neighboring blocks **524** and **526**, namely the constellations set out above.

(296) In the other case, i.e., in the case where the set-selective syntax element **522** indicates that the pre-determined block **18** is to be predicted using any of the block-based intra-prediction modes **510**, the coding of block **18** into data stream **12** and this decoding there from may be done in the manner set out above. To this end, indexing may be used in order to index the selected one out of, or indicate as to which of, the block-based intra-prediction modes **510** out of set **520**, i.e. second set of block-based intra-prediction modes, is to be used. A further MPM syntax element **538** may indicate whether the indexing is done by an index **540**, i.e. by a further MPM list index, which indicates the block-based intra-prediction mode **510** to be used for block **18** out of a list **542** of most probable block-based intra-prediction modes **510**, namely by indexing along a list order **544**, or whether the block-based intra-prediction mode **510** to be used for block **18** is indicated by a further syntax element **546**, i.e. by an even further list index, which indicates the block-based intra-prediction modes **510** out of set **520**, wherein the latter syntax element **546** may, for instance, only distinguish between those modes **510** within set **520** not already contained within list **542**. The list construction of list **542** may be done based on the modes using which block **524** and **526** have been predicted. If any of the blocks **524** and **526** is not available since being outside the picture or since

being inter-predicted, a default intra-prediction mode such as one out of set **508** may be used instead. For each block **524** and **526**, having been intra-predicted using a mode out of set **508** rather than set **520**, the afore-described mapping from modes of set **508** onto modes out of set **520** is used to obtain an intra-prediction mode **510**, i.e. a predetermined block-based intra-prediction mode, for the respective block, i.e. the predetermined block **18**, and based on the resulting block-based intra-prediction modes for blocks **524** and **526**, the list **542** is construed.

(297) According to an embodiment, the apparatus for decoding the predetermined block **18** is configured to derive a further MPM syntax element **538** from the data stream **12** which indicates whether the predetermined block-based intra-prediction mode of the second set **520** of block-based intra-prediction modes **510** is within a list **542** of most probable block-based intra-prediction modes or not, if the set-selective syntax element **522** indicates that the predetermined block **18** is not to be predicted using one of the first set **508** of intra-prediction modes. If the further MPM syntax element **538** indicates that the predetermined block-based intra-prediction mode of the second set **520** of block-based intra-prediction modes **510** is within a list **542** of most probable block-based intra-prediction modes, the apparatus, for example, is configured to form the list **542** of most probable block-based intra-prediction modes on the basis of intra-prediction modes using when neighbouring blocks **524**, **526** neighbouring the predetermined block **18** are predicted and derive a further MPM list index **540** from the data stream **12** which points into the list **542** of most probable block-based intra-prediction modes onto the predetermined block-based intra-prediction mode. If the further MPM syntax element **538** indicates that the predetermined block-based intra-prediction mode of the second set **520** of block-based intra-prediction modes is not within a list **542** of most probable block-based intra-prediction modes, the apparatus is configured to derive an even further list index **546** from the data stream **12** which indicates the predetermined block-based intra-prediction mode out of the second set **520** of block-based intra-prediction modes. Thus based on the further MPM syntax element **538** the data stream **12** comprises either the further MPM list index **540** or the even further list index **546** for the prediction of the predetermined block **18**.

(298) Although the further MPM syntax element **538**, the further MPM list index **540** and the even further list index **546** are represented in the data stream **12** in FIG. **12** as being parallel to the MPM syntax element **532**, the MPM list index **534** and the further list index **536**, it is clear, that either the further MPM syntax element **538** and the index associated with the further MPM syntax element **538**, e.g. the further MPM list index **540** or the even further list index **546**, are comprised by the data stream **12** or the MPM syntax element **532** and the index associated with the MPM syntax element **532**, e.g. the MPM list index **534** or the further list index **536**. Which of this syntax elements and indices are comprised by the data stream **12**, depends, for example, on the set-selective syntax element **522**.

(299) An example for a syntax element portion of data stream **12** written as a pseudo code could look as shown in FIGS. **19a** to **19d**, wherein the reference signs indicate as to which syntax element correspond to the syntax elements discussed before.

(300) The list construction of list **528** may be defined as follows, wherein `candIntraPredModeA/B` indicating the intra-prediction mode using which any of blocks **524** and **526** has been predicted, such as A for block **524** and B for block **526**, or onto which mode the intra-prediction mode is mapped out of set **508**, in case of the corresponding block **524** or **526** have been intra-predicted using any of the block-based intra-prediction modes **510**. `INTRA_DC` is used to indicate mode **506**, and the angular modes **500** are indicated by `INTRA_ANGULAR#` with the numbering (#) ordering the angular modes as exemplarily indicated above, namely in a manner so that the angular direction **502** monotonically decreases or increases with increasing number. The ordering among the modes within set **508** may be as defined in the subsequent table where `INTRA_PLANAR` indicates mode **504**.

(301) Note that in the example above, the index **534** is, in fact, distributed onto the syntax elements **534'** and **534''**: The former **534'** is specific for the first, in order **530**, position of list **528** where,

according to this example, the INTRA_PLANAR mode **504** is inevitably positioned. The latter **534** points to any of the subsequent positions of list **528** where, as described, the DC mode **506** is only included in the described special circumstances.

(302) Further, in the example above, further syntax elements are included in the data stream in case of syntax element **522** indicating that any among the modes within set **508** are used, which further syntax elements somehow parametrize the intra-prediction modes within set **500**. For instance, a syntax element **600** parametrizes or varies a region where the reference samples **17** are positioned based on which the modes in set **508** intra-predict the inner of block **18**, such as in terms of distance towards block's **18** outer circumference. Additionally or alternatively, a syntax element **602** parametrizes or varies whether the reference samples **17** are used by the modes in set **508** to intra-predict the inner of block **18** globally or en block, or whether the intra-prediction is done in pieces or portions into which the block **18** is sub-divided, and which are intra-predicted sequentially so that the prediction residual coded into the data stream for one portion may serve for recruiting new reference samples for intra-predicting a following portion. The latter coding option controlled by syntax element may be available only (and the corresponding syntax element may be present in the data stream only) if the syntax element **600** has a predetermined state corresponding to, for instance, the region, where the reference samples **17** lie, abutting the block **18**. The portions may be defined by subdividing the block along a predetermined direction such as either horizontally, thereby leading to portions being as high as block **18**, or vertically, thereby leading to portions being as wide as block **18**. A syntax element **604** may be present in the data stream if the partitioning is signaled to be active, which controls as to which split direction is used. As can be seen, it might be that the position in list **528** which is reserved for the INTRA_PLANAR mode, is available only in case of a certain parametrizing of the modes by the just-mentioned parametrizing syntax elements such as only if the syntax element **600** has a predetermined state corresponding to, for instance, the region where the reference samples **17** lie, abutting the block **18** and/or if the portion wise intra-prediction mode is not active as signaled by syntax element **602**.

(303) All syntax element shown in the table and not specifically mentioned above are optional and are not further discussed herein. If $\text{candIntraPredModeB}$ is equal to $\text{candIntraPredModeA}$ and $\text{candIntraPredModeA}$ is greater than INTRA_DC, $\text{candModeList}[x]$ with $x=0 \dots 4$ is derived as follows: $\text{candModeList}[0]=\text{candIntraPredModeA}$ $\text{candModeList}[1]=2+((\text{candIntraPredModeA}+61) \% 64)$ $\text{candModeList}[2]=2+((\text{candIntraPredModeA}-1) \% 64)$ $\text{candModeList}[3]=2+((\text{candIntraPredModeA}+60) \% 64)$ $\text{candModeList}[4]=2+(\text{candIntraPredModeA} \% 64)$ Otherwise if $\text{candIntraPredModeB}$ is not equal to $\text{candIntraPredModeA}$ and $\text{candIntraPredModeA}$ or $\text{candIntraPredModeB}$ is greater than INTRA_DC, the following applies: The variables minAB and maxAB are derived as follows: $\text{minAB}=\text{Min}(\text{candIntraPredModeA}, \text{candIntraPredModeB})$ $\text{maxAB}=\text{Max}(\text{candIntraPredModeA}, \text{candIntraPredModeB})$ If $\text{candIntraPredModeA}$ and $\text{candIntraPredModeB}$ are both greater than INTRA_DC, $\text{candModeList}[x]$ with $x=0 \dots 4$ is derived as follows: $\text{candModeList}[0]=\text{candIntraPredModeA}$ $\text{candModeList}[1]=\text{candIntraPredModeB}$ If $\text{maxAB}-\text{minAB}$ is equal to 1, the following applies: $\text{candModeList}[2]=2+((\text{minAB}+61) \% 64)$ $\text{candModeList}[3]=2+((\text{maxAB}-1) \% 64)$ $\text{candModeList}[4]=2+((\text{minAB}+60) \% 64)$ Otherwise, if $\text{maxAB}-\text{minAB}$ is greater than or equal to 62, the following applies: $\text{candModeList}[2]=2+((\text{minAB}-1) \% 64)$ $\text{candModeList}[3]=2+((\text{maxAB}+61) \% 64)$ $\text{candModeList}[4]=2+(\text{minAB} \% 64)$ Otherwise, if $\text{maxAB}-\text{minAB}$ is equal to 2, the following applies: $\text{candModeList}[2]=2+((\text{minAB}-1) \% 64)$ $\text{candModeList}[3]=2+((\text{minAB}+61) \% 64)$ $\text{candModeList}[4]=2+((\text{maxAB}-1) \% 64)$ Otherwise, the following applies: $\text{candModeList}[2]=2+((\text{minAB}+61) \% 64)$ $\text{candModeList}[3]=2+((\text{minAB}-1) \% 64)$ (8-36) $\text{candModeList}[4]=2+(((\text{maxAB}+61)) \% 64)$ Otherwise ($\text{candIntraPredModeA}$ or $\text{candIntraPredModeB}$ is greater than INTRA DC), $\text{candModeList}[x]$ with $x=0 \dots 4$ is derived as follows: $\text{candModeList}[0]=\text{maxAB}$ $\text{candModeList}[1]=2+((\text{maxAB}+61) \% 64)$ $\text{candModeList}[2]=2+((\text{maxAB}-1) \% 64)$ (8-41) $\text{candModeList}[3]=2+((\text{maxAB}+60) \% 64)$

candModeList[4]=2+(maxAB % 64) Otherwise, the following applies:

(304) candModeList[0]=INTRA_DC

(305) candModeList[1]=INTRA_ANGULAR50 (

(306) candModeList[2]=INTRA_ANGULAR18

(307) candModeList[3]=INTRA_ANGULAR46

(308) candModeList[4]=INTRA_ANGULAR54

(309) TABLE-US-00006 Intra prediction mode Associated name 0 INTRA_PLANAR 1

INTRA_DC 2 . . . 66 INTRA_ANGULAR2 . . . INTRA_ANGULAR66

9. EMBODIMENTS MAKING USE OF BLOCK/MATRIX-BASED INTRA PREDICTION MODES ALONG WITH OTHER INTRA-PREDICTION MODES AND USE OF SECONDARY TRANSFORMS

(310) The following description presents embodiments for combining block/matrix-based prediction with other intra-prediction modes along with using secondary transforms for coding the prediction residual. Above presentation of possibilities for matrix-based intra prediction (ALWIP) and combination thereof with other intra prediction modes shall serve as examples to implement the embodiments described in hereinbelow. In FIG. 12, for instance, all details regarding the MPM list constructions with respect to the restricted inclusion of the DC mode therein are optional.

(311) As described above, matrix-based intra prediction (MIP), also denoted as block-based intra prediction and ALWIP herein, generates an intra-prediction signal on a rectangular block by performing a matrix-vector multiplication where the output of the matrix-vector multiplication may be regarded as being a prediction signal on a downsampled block and where the input of the matrix vector multiplication may be comprised by downsampled boundary samples. If the output is regarded as a prediction signal on a downsampled block, this prediction signal needs to undergo an upsampling (or linear interpolation) stage before the final prediction signal is obtained.

(312) On the other hand, for the conventional intra prediction modes like the Planar mode 504, the DC mode 506 and the angular modes 500, also denoted as modes of the set 508 in the above description, non-separable secondary transform (LFNST) is a tool used to transform the prediction residuals corresponding to these intra prediction modes. Here, a set S of transform sets is given such that each conventional intra prediction mode is associated with one of these transform sets. Then, at the decoder, it can be extracted from the bitstream whether on a given block LFNST is to be applied. If this is the case, one transform set out of the set S is given, depending on the intra prediction mode used on the current block, and, if this transform set consist of more than one transform, it can be extracted from the bitstream which transform T out of this set is to be used. Then, at the decoder, the transform T is applied as a secondary transform Ts, meaning that it is applied to a subset 622 of the residual transform coefficients 620 of a separable primary transform Tp as, for example, shown in FIG. 14.

(313) The problem is that the aforementioned secondary transforms Ts are a priori only defined for the conventional intra prediction modes. Providing specific secondary transforms Ts for each MIP mode 510 may be too costly in terms of the memory requirement to additionally store extra transforms.

(314) FIG. 13 illustrates a decoder solving this problem. The decoder decodes a predetermined block 18 of a picture using intra-prediction. An encoder, according to an embodiment, comprises parallel features and/or functionalities as the decoder.

(315) The decoder/encoder is configured to select 602 a predetermined intra prediction mode 604 out of a plurality 600 of intra-prediction modes which comprises a first set 508 of intra-prediction modes and a second set 520 of matrix-based intra-prediction modes 510. This intra-mode selection 602 is performed based on a data stream 12, by the decoder, wherein the encoder is configured to signal the predetermined intra prediction mode 604 in the data stream 12. The intra-mode selection 602 may be performed as described with regard to FIG. 12.

(316) The first set 508 of intra-prediction modes comprises a DC intra prediction mode 506 and

angular prediction modes **500** and optionally a planar intra prediction mode **504**. In case of the predetermined intra prediction mode **604** being a matrix-based intra-prediction mode **510** out of the second set **520**, the decoder/encoder is configured to use a matrix-vector product **512** between a vector **514** derived from reference samples **17** in a neighbourhood of the predetermined block **18** and a prediction matrix **516** associated with the respective matrix-based intra-prediction mode **510** is used to obtain a prediction vector **518**, on the basis of which samples of the predetermined block **18** are predicted. A prediction of the predetermined block **18** using a matrix-based intra-prediction mode **510** as the predetermined intra prediction mode **604** can be performed by the decoder/encoder according to embodiments of FIGS. **6** to **11**. The decoder/encoder is configured to derive a prediction signal **606** for the predetermined block **18** using the predetermined intra-prediction mode **604**.

(317) The decoder/encoder is configured to select **608** a subset **610** of one or more secondary transforms $T_{sub.s.sup.(i1)-T_{sub.s.sup.(in)}}$, with $i_{sub.1}$ being in a range of 1 to N and $i_{sub.n}$ being in a range of $i_{sub.1}$ to N , out of a set **612** of secondary transforms T_s , e.g. $T_{s.sup.(1)-T_{s.sup.(N)}}$, in a manner dependent on the predetermined intra prediction mode **604** so that the subset **610** is nonempty in case of the predetermined intra prediction mode **604** being contained in the first set **508** of intra-prediction modes and in case of the predetermined intra prediction mode **604** being contained in the second set **520** of matrix-based intra-prediction modes **510**.

(318) According to an embodiment, the decoder/encoder is configured to select **608** the subset **610** so that each secondary transform T_s of the set **612** of secondary transforms T_s is contained in the subset **610** of one or more secondary transforms T_s selected for at least one of the intra-prediction modes within the first **508** and second **520** sets. Thus the subset **610** may be equal to the set **612** of secondary transforms. Such a subset may be selected for one or more matrix-based intra-prediction modes **510**. For one or more matrix-based intra-prediction modes **510**, it might be possible to select all the secondary transforms T_s of the set **612** of secondary transforms, whereby the subset **610** for this one or more matrix-based intra-prediction modes **510** comprises secondary transform T_s selectable for intra-prediction modes within the first set **508** of intra-prediction modes. Thus, for at least one of the matrix-based intra-prediction modes **510** no specific additional secondary transforms are needed in the set **612** of secondary transforms.

(319) According to an embodiment, the decoder/encoder is configured to select **608** the subset **610** in a manner so that each secondary transform T_s of each subset $610_{sub.matrix}$ of secondary transforms T_s selected for any matrix-based intra-prediction mode **510** is contained by a subset, e.g. $610_{sub.DC}$ and/or $610_{sub.planar}$, of secondary transforms T_s selected for at least one intra-prediction mode within the first set **508** not belonging to the angular prediction modes **500**. FIG. **15** indicates different possible subsets of secondary transforms T_s selected for any matrix-based intra-prediction mode **510**. The decoder/encoder may be configured to select, for each matrix-based intra-prediction mode **510**, a subset **610** of a first union $611_{sub.matrix}$ of subsets **610** of secondary transforms for the matrix-based intra-prediction modes **510**.

(320) As shown in FIG. **15**, a subset **610** selectable for one or more matrix-based intra-prediction modes **510** can be equal to a subset, e.g. $610_{sub.DC1}$ or $610_{sub.DC2}$, selectable for DC intra-prediction modes **506** or can be equal to a subset, e.g. $610_{sub.planar1}$ or $610_{sub.planar2}$, selectable for planar intra-prediction modes **504**. It is possible, that a subset **610** selectable for one or more matrix-based intra-prediction modes **510** comprises only one or more secondary transforms, e.g. $T_{s.sup.(ax)}$ to $T_{s.sup.(ay)}$, of a subset, e.g. $610_{sub.DC}$, of secondary transforms T_s selected for one intra-prediction mode within the first set **508** not belonging to the angular prediction modes **500**, as indicated by the subset $610_{sub.matrix4}$.

(321) A subset **610** selectable for matrix-based intra-prediction modes **510** may contain one or more secondary transforms out of two or more subsets, e.g. $610_{sub.DC1}$ and $610_{sub.DC2}$, selectable for DC intra-prediction modes **506**, as indicated by the subset $610_{sub.matrix1}$, or may contain one or more secondary transforms out of two or more subsets, e.g. $610_{sub.planar1}$ and

610.sub.planar2, selectable for planar intra-prediction modes **504**, as indicated by the subset **610.sub.matrix3**.

(322) A further possible subset **610** selectable for matrix-based intra-prediction modes **510** may comprise one or more secondary transforms out of one or more subsets, e.g. **610.sub.DC2**, selectable for DC intra-prediction modes **506** and one or more secondary transforms out of one or more subsets, e.g. **610.sub.planar1**, selectable for planar intra-prediction modes **504**, as indicated by the subset **610.sub.matrix2**.

(323) According to an embodiment, the decoder/encoder is configured to select **608** the subset **610** in a manner so that an intersection between the first union **611** matrix of subsets **610** of secondary transforms selected for the matrix-based intra-prediction modes **510** and a second union **611.sub.angular** of subsets **610.sub.angular** of secondary transforms selected for all angular intra-prediction modes is empty. A third union **611.sub.DC** comprises all subsets **610.sub.DC** selected for the DC intra-prediction modes **506** and a fourth union **611.sub.planar** comprises all subsets **610.sub.planar** selected for the planar intra-prediction modes **504**. For example, due to a downsampling optionally applied to a reduced prediction signal **606**, the MIP modes **510** are, as the Planar-**504** and the DC-mode **506**, non-directional and thus their prediction residuals **618** have more statistical similarities with those of the DC-**506** and the Planar-modes **504** than with those of the angular modes **500**.

(324) Furthermore, as shown in FIG. **13**, the decoder is configured to derive **614**, from the data stream, encoded by the encoder into the data stream, a transformed version **616** of a prediction residual for the predetermined block **18**, which is related to a spatial domain version **618** of the prediction residual of the predetermined block **18** via a transform **T** defined by a concatenation of a primary transform **T_p** and a predetermined secondary transform **T_s** out of the subset **610** of secondary transforms. As shown in FIG. **14**, the encoder can be configured to apply the transform **T** onto a subset **622** of coefficients **620** of the primary transform **T_p**, in case of the predetermined intra prediction mode being contained in the first set **508** of intra-prediction modes and in case of the predetermined intra prediction mode being contained in the second set **520** of matrix-based intra-prediction modes **510**. The decoder can be configured to use an inverse **T_{sup.-1}** of the transform **T** to obtain the spatial domain version **618** of the prediction residual of the predetermined block **18**. The primary transform, for example, is a separable 2D transform and the secondary transform, for example, is a non-separable 2D transform.

(325) The decoder is configured to reconstruct **624** the predetermined block **18** using the prediction signal **606** and the prediction residual **618** for the predetermined block **18**.

(326) If the subset **610** of one or more secondary transforms **T_s** contains more than one secondary transform **T_s**, the decoder may be configured to select the predetermined secondary transform **T_s** out of the subset **610** of one or more secondary transforms depending on a secondary-transform-indicating syntax element transmitted in the data stream **12** for the predetermined block. The secondary-transform-indicating syntax element may be an index pointing into the selected subset **610** of one or more secondary transforms. The encoder may in this case be configured to transmit the secondary-transform-indicating syntax element in the data stream **12**.

(327) According to an embodiment, the decoder is configured to infer that the transform **T** via which the transformed version **616** of a prediction residual for the predetermined block **18** is related to the spatial domain version **618** of the prediction residual of the predetermined block **18** is the primary transform **T_p**, if dimensions of the predetermined block **18** meet a predetermined criterion. Otherwise the transform **T** may be the concatenation of a primary transform **T_p** and the predetermined secondary transform **T_s**. The decoder renders available the second set **520** of matrix-based intra-prediction modes **510** for the selection **602** of the predetermined intra prediction mode **604** irrespective of the dimensions of the predetermined block **18** meeting the predetermined criterion. The predetermined criterion for the dimensions of the predetermined block **18** may only be relevant for the subset selection **608** and not for the intra-mode selection **602**. There are, for

example, block dimensions for which MIP/ALWIP **510** is available although LFNST, i.e. the subset selection **608**, is not. For a block **18** of such dimensions, no secondary-transform-indicating syntax element needs to be transmitted in, and read from, the data stream. The predetermined criterion, for example, is met if the dimensions fall below a predetermined threshold. For small predetermined blocks **18**, it might not be beneficial, meaning that for the latter shapes, the additional signalization costs to signal whether LFNST is to be applied for a block in MIP mode or not is, on average, higher than the gain one obtains by allowing LFNST transforms for the MIP modes.

(328) According to an embodiment, the decoder is configured to read a non-zero zone indication transmitted in the data stream **12** for the respective predetermined block **18** which indicates a non-zero transform domain area **623** within the transformed version **616** of the prediction residual for the predetermined block **18**, as shown in FIG. **16**. All non-zero coefficients are located exclusively in the non-zero transform domain area **623**. The non-zero zone indication, for example, is transmitted in the data stream **12** by the encoder. The decoder/encoder is configured to decode/encode the coefficients within the non-zero transform domain area **623** from/into the data stream **12**. A LP syntax element may act as the non-zero zone indication. A last non-zero coefficient position along a scan path leading from a DC coefficient position to opposite, or highest frequency, coefficient position, is indicated by the LP syntax element herein. The LP syntax element may quasi serve as a measure for an expected count of non-zero coefficients within the non-zero transform domain area **623**.

(329) According to an embodiment, the decoder is configured to infer that the transform T via which the transformed version **616** of the prediction residual for the predetermined block **18** is related to the spatial domain version **618** of the prediction residual of the predetermined block **18** is the primary transform Tp depending on an extension and/or position of the non-zero transform domain area **623** meeting a first predetermined criterion and/or a number of non-zero coefficients within the non-zero transform domain area **623** meeting a second predetermined criterion.

(330) The first predetermined criterion, for example, is such that same is met if the non-zero transform domain area **623** does not exclusively cover the subset **622** of coefficients of the primary transform Tp onto which the secondary transform Tp is applied by the concatenation. This is based on the idea, that the secondary transform Ts should cover all non-zero coefficients of the transform coefficients of the primary transform Tp. In case of non-zero coefficients being outside of the subset **622** of coefficients of the primary transform Tp, it may not be advantageous to apply the predetermined secondary transform, for which reason the decoder infers that the transform T is the primary transform Tp. The decoder may perform the subset selection **608** and apply the transform T defined by the concatenation of a primary transform Tp and the predetermined secondary transform Ts out of the subset **610** of secondary transforms applied onto the subset **622** of coefficients of the primary transform Tp to obtain the spatial domain version **618** of the prediction residual of the predetermined block **18** if the non-zero transform domain area **623** is positioned completely inside the subset **622** of coefficients of the primary transform Tp onto which the secondary transform Tp is applied by the concatenation, see, e.g., FIG. **16**.

(331) The second predetermined criterion, for example, is such that same is met if the number of non-zero coefficients within the non-zero transform domain area **623** falls below a predetermined threshold. This is based on the idea, that the number of non-zero coefficients within the non-zero transform domain area **623** does not need to be further reduced by a secondary transform Ts, if the number falls below the predetermined threshold. In case of a small number of non-zero coefficients of the primary transform Tp, it may not be advantageous to apply additionally the predetermined secondary transform, for which reason the decoder infers that the transform T is the primary transform Tp. The additional signalling costs for the predetermined secondary transform would be higher than the achieved increased coding efficiency by the predetermined secondary transform in case of the number of non-zero coefficients falling below a predetermined threshold. The decoder may perform the subset selection **608** and apply the transform T defined by the concatenation of a

primary transform **1p** and the predetermined secondary transform **Ts** out of the subset **610** of secondary transforms applied onto the subset **622** of coefficients of the primary transform **1p** to obtain the spatial domain version **618** of the prediction residual of the predetermined block **18** if the number of non-zero coefficients within the non-zero transform domain area **623** equals or exceeds the predetermined threshold.

(332) According to an embodiment, the decoder/encoder is configured to derive/encode a set-selective syntax element **522** from/into the data stream **12** which indicates whether the predetermined block **18** is to be predicted using one of the first set **508** of intra-prediction modes, as, e.g., described with regard to FIG. **12**. If the set-selective syntax element **522** indicates that the predetermined block **18** is to be predicted using one of the first set **508** of intra-prediction modes, the decoder/encoder is configured to form a list **528** of most probable intra-prediction modes on the basis of intra-prediction modes using which neighbouring blocks **524** and **526** neighbouring the predetermined block **18** are predicted and derive/signal a MPM list index **534** from/into the data stream **12** which points into the list **528** of most probable intra-prediction modes onto the predetermined intra-prediction mode **604**. If the set-selective syntax element **522** indicates that the predetermined block **18** is not to be predicted using one of the first set **508** of intra-prediction modes, the decoder/encoder is configured to derive/encode a further index **540** and/or **546** from/into the data stream which indicates the predetermined intra-prediction mode **604** out of the second set **520** of matrix-based intra-prediction modes **510**.

(333) The decoder and the encoder, described with regard to FIG. **13**, may comprise further features and/or functionalities as described with regard to FIG. **12**.

(334) In case of the predetermined intra-prediction mode **604** for the predetermined block **18** being a matrix-based intra-prediction mode **510** out of the second set **520**, the apparatus, i.e. the decoder according to FIG. **13**, for decoding the predetermined block **18** and/or the apparatus, i.e. the encoder according to FIG. **13**, for encoding the predetermined block **18** can comprise one or more of the following features.

(335) According to an embodiment, the apparatus is configured to form a sample value vector, e.g. the sample value vector **400** as described with regard to one of the embodiments of FIGS. **6** to **9**, out of the plurality of reference samples **17** and derive from the sample value vector the vector **514** so that the sample value vector is mapped by a predetermined invertible linear transform onto the vector **514**. In this case, the vector **514** can be understood as a further vector. The vector **514** is, for example, determined and/or defined as described for the further vector **402** with regard to one of the embodiment of FIGS. **8** to **11**.

(336) According to an embodiment, the apparatus is configured to form the sample value vector out of the plurality of reference samples **17** by, for each component of the sample value vector, adopting one reference sample of the plurality of reference samples as the respective component of the sample value vector, and/or averaging two or more components of the sample value vector to obtain the respective component of the sample value vector.

(337) The plurality of reference samples **17** are, for example, arranged within the picture alongside an outer edge of the predetermined block **18**.

(338) The invertible linear transform is, for example, defined such that a predetermined component of the vector **514**, e.g. of the further vector, becomes a , and each of other components of the vector **514**, except the predetermined component, equal a corresponding component of the sample value vector minus a . The value a is, for example, a predetermined value **1400**.

(339) According to an embodiment, the predetermined value **1400** is one of an average, such as an arithmetic mean or weighted average, of components of the sample value vector, a default value, a value signalled in a data stream into which the picture is coded, and a component of the sample value vector corresponding to the predetermined component.

(340) The invertible linear transform is, for example, defined such that a predetermined component of the vector **514**, e.g. of the further vector, becomes a , and each of other components of the vector

514, except the predetermined component, equal a corresponding component of the sample value vector minus **a**, wherein **a** is an arithmetic mean of components of the sample value vector.

(341) The invertible linear transform is, for example, defined such that a predetermined component of the vector **514**, e.g. of the further vector, becomes **a**, and each of other components of the vector **514**, except the predetermined component, equal a corresponding component of the sample value vector minus **a**, wherein **a** is a component of the sample value vector corresponding to the predetermined component. The apparatus is, for example, configured to comprise a plurality of invertible linear transforms, each of which is associated with one component of the vector **514**, select the predetermined component out of the components of the sample value vector and use the invertible linear transform out of the plurality of invertible linear transforms which is associated with the predetermined component as the predetermined invertible linear transform.

(342) According to an embodiment, matrix components of the prediction matrix **516** within a column of the prediction matrix **516** which corresponds to the predetermined component of the vector **514**, e.g. of the further vector, are all zero. The apparatus is configured to compute the matrix-vector product **512** by performing multiplications by computing a matrix vector product **512** between a reduced prediction matrix resulting from the prediction matrix **516** by leaving away the column and a further vector **410** resulting from the vector **514** by leaving away the predetermined component, as shown in FIG. **9c**.

(343) According to an embodiment, the apparatus is configured to, in predicting the samples of the predetermined block **18** on the basis of the prediction vector **518**, compute for each component of the prediction vector **518** a sum of the respective component and **a**.

(344) A matrix, which results from summing each matrix component of the prediction matrix **516** within a column of the prediction matrix **516**, which corresponds to the predetermined component of the vector **514**, e.g. of the further vector, with one (i.e. a summation of the matrix **C 405** and the matrix **M 1300**, illustrated in FIG. **9a**, resulting in matrix **B** in FIG. **8**), times the invertible linear transform corresponds, for example, to a quantized version of a machine learning prediction matrix (i.e. the prediction matrix **A 1100** shown in FIG. **8**).

(345) According to an embodiment, the apparatus is configured to compute the matrix-vector product **512** using fixed point arithmetic operations.

(346) According to an embodiment, the apparatus is configured to compute the matrix-vector product **512** without floating point arithmetic operations.

(347) According to an embodiment, the apparatus is configured to store a fixed point number representation of the prediction matrix **516**.

(348) According to an embodiment, the apparatus is configured to represent the prediction matrix **516** using prediction parameters and to compute the matrix-vector product **512** by performing multiplications and summations on the components of the vector **514**, e.g. of the further vector, and the prediction parameters and intermediate results resulting therefrom, wherein absolute values of the prediction parameters are representable by an **n**-bit fixed point number representation with **n** being equal to or lower than 14, or, alternatively, 10, or, alternatively, 8. This can be performed similarly or as described in FIG. **10** or FIG. **11**.

(349) The prediction parameters comprise, for example, weights each of which is associated with a corresponding matrix component of the prediction matrix **516**.

(350) The prediction parameters further comprise, for example, one or more scaling factors each of which is associated with one or more corresponding matrix components of the prediction matrix **516** for scaling the weight associated with the one or more corresponding matrix component of the prediction matrix **516**, and/or one or more offsets each of which is associated with one or more corresponding matrix components of the prediction matrix **516** for offsetting the weight associated with the one or more corresponding matrix component of the prediction matrix **516**.

(351) According to an embodiment, the apparatus is configured to, in predicting the samples of the predetermined block **18** on the basis of the prediction vector **518**, use interpolation to compute at

least one sample position of the predetermined block **18** based on the prediction vector **518** each component of which is associated with a corresponding position within the predetermined block **18**.

(352) The decoder and the encoder, described with regard to FIG. **13**, may comprise further features and/or functionalities as described with regard to one or more embodiments of FIGS. **6-11**.

(353) Thus, a solution provided by the present invention is to associate to each MIP mode **510** one specific set **160** of transforms out of the given transforms set **S 612**, the latter being originally defined for the conventional intra prediction modes, i.e. the intra-prediction modes within the first set **508**. One specific way to do this would be that all MIP modes **510** use the LFNST transforms, i.e. the secondary transforms, that are initially designed for the Planar **504** and the DC mode **506**. For example, due to the downsampling optionally applied to the reduced prediction signal, the MIP modes **510** are, as the Planar-**504** and the DC-mode **506**, non-directional and thus their prediction residuals have more statistical similarities with those of the DC-**506** and the Planar-modes **504** than with those of the angular modes **500**.

(354) It may turn out that to allow LFNST, i.e. to allow the usage of a secondary transform, for MIP **510** in the aforementioned way might be beneficial in terms of coding efficiency for some block shapes and for other block shapes, it might not be beneficial, meaning that for the latter shapes, the additional signalization costs to signal whether LFNST is to be applied for a block **18** in MIP mode **510** or not is, on average, higher than the gain one obtains by allowing LFNST transforms for the MIP modes **510**. Thus, an embodiment of the present invention, the aforementioned combination of LFNST and MIP **510** is only allowed on a subset of all those block shapes for which such a combination would in principle be possible.

(355) FIG. **17** shows a method **6000** for decoding a predetermined block (**18**) of a picture using intra-prediction, comprising selecting (**602**), based on a data stream, a predetermined intra prediction mode (**604**) out of a plurality of intra-prediction modes which comprises a first set (**508**) of intra-prediction modes comprising a DC intra prediction mode (**506**) and angular prediction modes (**500**) and optionally a planar intra-prediction mode (**504**), and a second set (**520**) of matrix-based intra-prediction modes (**510**) according to each of which a matrix-vector product (**512**) between a vector (**514**) derived from reference samples (**17**) in a neighbourhood of the predetermined block and a prediction matrix (**516**) associated with the respective matrix-based intra-prediction mode is used to obtain a prediction vector (**518**), on the basis of which samples of the predetermined block are predicted. A prediction signal (**606**) for the predetermined block is derived **6100** using the predetermined intra-prediction mode and a subset (**610**) of one or more secondary transforms out of a set (**612**) of secondary transforms is selected in a manner dependent on the predetermined intra prediction mode so that the subset (**610**) is nonempty in case of the predetermined intra prediction mode being contained in the first set (**508**) of intra-prediction modes and the predetermined intra prediction mode being contained in the second set (**520**) of matrix-based intra-prediction modes (**510**). The method **6000** comprises deriving (**614**), from the data stream, a transformed version (**616**) of a prediction residual for the predetermined block (**18**), which is related to a spatial domain version (**618**) of the prediction residual of the predetermined block via a transform (**T**) defined by a concatenation of a primary transform (**Tp**) and a predetermined secondary transform (**Ts**) out of the subset (**610**) of secondary transforms applied onto a subset (**622**) of coefficients (**620**) of the primary transform, in case of the predetermined intra prediction mode being contained in the first set (**508**) of intra-prediction modes and in case of the predetermined intra prediction mode being contained in the second set (**520**) of matrix-based intra-prediction modes (**510**). Additionally, the method **6000** comprises reconstructing (**624**) the predetermined block using the prediction signal and the prediction residual for the predetermined block (**18**).

(356) FIG. **18** shows a method **7000** for encoding a predetermined block (**18**) of a picture using intra-prediction, comprising selecting (**602**) a predetermined intra prediction mode (**604**) out of a

plurality (600) of intra-prediction modes which comprises a first set (508) of intra-prediction modes comprising a DC intra prediction mode (506) and angular prediction modes (500), and a second set (520) of matrix-based intra-prediction modes (510) according to each of which a matrix-vector product (512) between a vector (514) derived from reference samples (17) in a neighbourhood of the predetermined block and a prediction matrix (516) associated with the respective matrix-based intra-prediction mode is used to obtain a prediction vector (518), on the basis of which samples of the predetermined block are predicted. Additionally, the method 7000 comprises signalling 7100 the predetermined intra prediction mode (604) in the data stream, deriving 7200 a prediction signal (606) for the predetermined block using the predetermined intra-prediction mode and selecting a subset (610) of one or more secondary transforms out of a set (612) of secondary transforms in a manner dependent on the predetermined intra prediction mode so that the subset (610) is nonempty in case of the predetermined intra prediction mode being contained in the first set (508) of intra-prediction modes and the predetermined intra prediction mode being contained in the second set (520) of matrix-based intra-prediction modes (510). The method comprises encoding (614), into the data stream, a transformed version (616) of a prediction residual for the predetermined block (18), which is related to a spatial domain version (618) of the prediction residual of the predetermined block via a transform (T) defined by a concatenation of a primary transform (Tp) and a predetermined secondary transform (Ts) out of the subset (610) of secondary transforms applied onto a subset (622) of coefficients (620) of the primary transform, in case of the predetermined intra prediction mode being contained in the first set (508) of intra-prediction modes and in case of the predetermined intra prediction mode being contained in the second set (520) of matrix-based intra-prediction modes (510), wherein the predetermined block is reconstructable (624) using the prediction signal and the prediction residual for the predetermined block (18).

REFERENCES

(357) [1] P. Helle et al., "Non-linear weighted intra prediction", JVET-L0199, Macao, China, October 2018. [2] F. Bossen, J. Boyce, K. Suehring, X. Li, V. Seregin, "JVET common test conditions and software reference configurations for SDR video", JVET-K1010, Ljubljana, SI, July 2018.

FURTHER EMBODIMENTS AND EXAMPLES

(358) Generally, examples may be implemented as a computer program product with program instructions, the program instructions being operative for performing one of the methods when the computer program product runs on a computer. The program instructions may for example be stored on a machine readable medium.

(359) Other examples comprise the computer program for performing one of the methods described herein, stored on a machine-readable carrier.

(360) In other words, an example of method is, therefore, a computer program having program instructions for performing one of the methods described herein, when the computer program runs on a computer.

(361) A further example of the methods is, therefore, a data carrier medium (or a digital storage medium, or a computer-readable medium) comprising, recorded thereon, the computer program for performing one of the methods described herein. The data carrier medium, the digital storage medium or the recorded medium are tangible and/or non-transitory, rather than signals which are intangible and transitory.

(362) A further example of the method is, therefore, a data stream or a sequence of signals representing the computer program for performing one of the methods described herein. The data stream or the sequence of signals may for example be transferred via a data communication connection, for example via the Internet.

(363) A further example comprises a processing means, for example a computer, or a programmable logic device performing one of the methods described herein.

(364) A further example comprises a computer having installed thereon the computer program for performing one of the methods described herein.

(365) A further example comprises an apparatus or a system transferring (for example, electronically or optically) a computer program for performing one of the methods described herein to a receiver.

(366) The receiver may, for example, be a computer, a mobile device, a memory device or the like. The apparatus or system may, for example, comprise a file server for transferring the computer program to the receiver.

(367) In some examples, a programmable logic device (for example, a field programmable gate array) may be used to perform some or all of the functionalities of the methods described herein. In some examples, a field programmable gate array may cooperate with a microprocessor in order to perform one of the methods described herein. Generally, the methods may be performed by any appropriate hardware apparatus.

(368) While this invention has been described in terms of several advantageous embodiments, there are alterations, permutations, and equivalents, which fall within the scope of this invention. It should also be noted that there are many alternative ways of implementing the methods and compositions of the present invention. It is therefore intended that the following appended claims be interpreted as including all such alterations, permutations, and equivalents as fall within the true spirit and scope of the present invention.

Claims

1. An apparatus for decoding a picture from a data stream, the apparatus comprising: a processor configured to: for a block of the picture, select, an intra prediction mode from a first set of intra-prediction modes or a second set of intra-prediction modes based on an indication included in the data stream, wherein the first set of intra-prediction modes comprises at least one angular prediction mode, a planar intra-prediction mode, and a DC intra-prediction mode, and wherein the second set of intra-prediction modes comprises at least one matrix based intra-prediction mode; derive a prediction signal for the block using the selected intra-prediction mode, select a subset of secondary transforms out of a set of secondary transforms including multiple low-frequency non-separable secondary transforms (LFNST) based on the selected intra-prediction mode, wherein the selected subset of secondary transforms includes at least one of the multiple LFNST; derive, from the data stream, a prediction residual for the block; transform the prediction residual using a LFNST from the selected subset; and reconstruct the block using the prediction signal and the transformed prediction residual for the block, wherein the same subset of secondary transforms is selected for the planar intra-prediction mode and each of the at least one matrix based intra-prediction mode.
2. A method for decoding a picture from a data stream, the method comprising: for a block of the picture, selecting, an intra prediction mode from a first set of intra-prediction modes or a second set of intra-prediction modes based on an indication included in the data stream, wherein the first set of intra-prediction modes comprises at least one angular prediction mode, a planar intra-prediction mode, and a DC intra-prediction mode, and wherein the second set of intra-prediction modes comprises at least one matrix based intra-prediction mode; deriving a prediction signal for the block using the selected intra-prediction mode, selecting a subset of secondary transforms out of a set of secondary transforms including multiple low-frequency non-separable secondary transforms (LFNST) based on the selected intra-prediction mode, wherein the selected subset of secondary transforms includes at least one of the multiple LFNST, deriving, from the data stream, a prediction residual for the block; transforming the prediction residual using a LFNST from the selected subset; and reconstructing the block using the prediction signal and the transformed prediction residual for the block, wherein the same subset of secondary transforms is selected for the planar

intra-prediction mode and each of the at least one matrix based intra-prediction mode.

3. A non-transitory, computer-readable medium storing instructions that, when executed by at least one processor of an electronic device, cause the at least one processor to: for a block of a picture, select, an intra-prediction mode from a first set of intra-prediction modes or a second set of intra-prediction modes based on an indication included in a data stream, wherein the first set of intra-prediction modes comprises at least one angular prediction mode, a planar intra-prediction mode, and a DC intra-prediction mode, and wherein the second set of intra-prediction modes comprises at least one matrix based intra-prediction mode; derive a prediction signal for the block using the selected intra-prediction mode, select a subset of secondary transforms out of a set of secondary transforms including multiple low-frequency non-separable secondary transforms (LFNST) based on the selected intra-prediction mode, wherein the selected subset of secondary transforms includes at least one of the multiple LFNST; derive, from the data stream, a prediction residual for the block; transform the prediction residual using a LFNST from the selected subset; and reconstruct the block using the prediction signal and the transformed prediction residual for the block, wherein the same subset of secondary transforms is selected for the planar intra-prediction mode and each of the at least one matrix based intra-prediction mode.

4. The apparatus of claim 1, wherein to derive the prediction signal when the intra-prediction mode is selected from the second set of intra-prediction modes, deriving the prediction signal, the processor is configured to: derive a prediction vector generated from a matrix-vector product between a vector derived from reference samples in a neighborhood of the block and a prediction matrix associated with the selected intra-prediction mode, and up sample the prediction vector to obtain the prediction signal of the block.

5. The apparatus of claim 1, wherein the processor is further configured to select the subset of secondary transforms based on: the selected intra-prediction mode, and a size of the block.

6. The apparatus of claim 1, wherein the processor is further configured to: decode an indication indicating the LFNST from the selected subset of secondary transforms; and select the LFNST, for transforming the prediction residual, from the subset based on the indication specifying one of two LFNST.

7. The apparatus of claim 1, wherein to transform the prediction residual, the processor is configured to: apply the LFNST (T.sub.s) onto a subset of coefficients of a primary transform (T.sub.p) to obtain a transform; and transform the prediction residual using the transform.

8. The apparatus of claim 7, wherein the primary transform (T.sub.p) is a separable 2D transform.

9. The apparatus of claim 1, wherein to transform the prediction residual, the processor is configured to: use a transform defined by a concatenation of a primary transfer (T.sub.p) and a secondary transform (T.sub.s) selected from the subset of secondary transforms, the secondary transform (T.sub.s) corresponds to the LFNST.

10. The apparatus of claim 1, wherein after selecting the intra-prediction mode from the second set of intra-prediction modes, the processor is configured to: select a matrix based intra-prediction mode from the at least one matrix based intra-prediction mode for deriving the prediction signal.

11. The apparatus of claim 10, wherein to derive the prediction signal using the matrix based intra-prediction mode the processor is configured to: generate a prediction vector from a matrix-vector product between a vector derived from reference samples in a neighborhood of the block and a prediction matrix associated with the selected matrix-based intra-prediction mode, according to which samples of the block are predicted.

12. The method of claim 2, wherein deriving the prediction signal when the intra-prediction mode is selected from the second set of intra-prediction modes, comprises: deriving a prediction vector generated from a matrix-vector product between a vector derived from reference samples in a neighborhood of the block and a prediction matrix associated with the selected intra-prediction mode, and upsampling the prediction vector to obtain the prediction signal of the block.

13. The method of claim 2, wherein selecting the subset of secondary transforms is based on: the

selected intra-prediction mode, and a size of the block.

14. The method of claim 2, further comprising: decoding an indication indicating the LFNST from the selected subset of secondary transforms; and selecting the LFNST, for transforming the prediction residual, from the subset based on the indication specifying one of two LFNST.

15. The method of claim 2, wherein transforming the prediction residual comprises: applying the LFNST (T.sub.s) onto a subset of coefficients of a primary transform (T.sub.p) to obtain a transform; and transforming the prediction residual using the transform.

16. The method of claim 15, wherein the primary transform (T.sub.p) is a separable 2D transform.

17. The method of claim 2, wherein transforming the prediction residual, comprises: using a transform defined by a concatenation of a primary transfer (Tp) and a secondary transform (Ts) selected from the subset of secondary transforms, the secondary transform (Ts) corresponds to the LFNST.

18. The method of claim 2, the method comprises: after selecting the intra-prediction mode from the second set of intra-prediction modes, selecting a matrix based intra-prediction mode from the at least one matrix based intra-prediction mode for deriving the prediction signal.

19. The method of claim 18, wherein deriving the prediction signal using the matrix based intra-prediction mode comprises: generating a prediction vector from a matrix-vector product between a vector derived from reference samples in a neighborhood of the block and a prediction matrix associated with the selected matrix-based intra-prediction mode, according to which samples of the block are predicted.

20. The non-transitory, computer-readable medium of claim 3, wherein the instructions that when executed cause the at least one processor to derive the prediction signal when the intra-prediction mode is selected from the second set of intra-prediction modes, comprise instructions that when executed cause the at least one processor to: derive a prediction vector generated from a matrix-vector product between a vector derived from reference samples in a neighborhood of the block and a prediction matrix associated with the selected intra-prediction mode, and up sample the prediction vector to obtain the prediction signal of the block.

21. The non-transitory, computer-readable medium of claim 3, further containing instructions that when executed cause the at least one processor to select the subset of secondary transforms is based on: the selected intra-prediction mode, and a size of the block.

22. The non-transitory, computer-readable medium of claim 3, further containing instructions that when executed cause the at least one processor to: decode an indication indicating the LFNST from the selected subset of secondary transforms; and select the LFNST, for transforming the prediction residual, from the subset based on the indication specifying one of two LFNST.

23. The non-transitory, computer-readable medium of claim 3, wherein the instructions that when executed cause the at least one processor to transform the prediction residual comprise instructions that when executed cause the at least one processor to: apply the LFNST (T.sub.s) onto a subset of coefficients of a primary transform (T.sub.p) to obtain a transform; and transform the prediction residual using the transform.

24. The non-transitory, computer-readable medium of claim 23, wherein the primary transform (T.sub.p) is a separable 2D transform.

25. The non-transitory, computer-readable medium of claim 3, wherein the instructions that when executed cause the at least one processor to transform the prediction residual, comprise instructions that when executed cause the at least one processor to: use a transform defined by a concatenation of a primary transfer (Tp) and a secondary transform (Ts) selected from the subset of secondary transforms, the secondary transform (Ts) corresponds to the LFNST.

26. The non-transitory, computer-readable medium of claim 3, further comprise instructions that when executed cause the at least one processor to: select a matrix based intra-prediction mode from the at least one matrix based intra-prediction mode for deriving the prediction signal, after the intra-prediction mode from the second set of intra-prediction modes is selected.

27. The non-transitory, computer-readable medium of claim 26, wherein the instructions that when executed cause the at least one processor to derive the prediction signal using the matrix based intra-prediction mode, comprise instructions that when executed cause the at least one processor to: generate a prediction vector from a matrix-vector product between a vector derived from reference samples in a neighborhood of the block and a prediction matrix associated with the selected matrix-based intra-prediction mode, according to which samples of the block are predicted.

28. A method for encoding a picture from a data stream, the method comprising: generating, for a block of the picture, an indication of an intra-prediction mode selected from a first set of intra-prediction modes or a second set of intra-prediction modes, wherein the first set of intra-prediction modes comprises at least one angular prediction mode, a planar intra-prediction mode, and a DC intra-prediction mode, and wherein the second set of intra-prediction modes comprises at least one matrix based intra-prediction mode; encoding a prediction signal for the block using the selected intra-prediction mode; selecting a subset of secondary transforms out of a set of secondary transforms including multiple low-frequency non-separable secondary transforms (LFNST) based on the selected intra-prediction mode, wherein the selected subset of secondary transforms includes at least one of the multiple LFNST; deriving a prediction residual for the block; transforming the prediction residual using a LFNST from the selected subset; and encoding into the data stream, the transformed prediction residual for the block, wherein the same subset of secondary transforms is selected for the planar intra-prediction mode and each of the at least one matrix based intra-prediction mode.

29. The method of claim 28, further comprising: in response to the intra-prediction mode being selected from the second set of intra-prediction modes, deriving a prediction vector generated from a matrix-vector product between a vector derived from reference samples in a neighborhood of the block and a prediction matrix associated with the selected intra-prediction mode; and generating the prediction signal based on the prediction vector.

30. The method of claim 28, further comprising: selecting the subset of secondary transforms is based on: the selected intra-prediction mode, and a size of the block.

31. An apparatus for encoding a picture from a data stream, the apparatus comprising: a processor configured to: generate, for a block of the picture, an indication of an intra-prediction mode selected from a first set of intra-prediction modes or a second set of intra-prediction modes, wherein the first set of intra-prediction modes comprises at least one angular prediction mode, a planar intra-prediction mode, and a DC intra-prediction mode, and wherein the second set of intra-prediction modes comprises at least one matrix based intra-prediction mode; encode a prediction signal for the block using the selected intra-prediction mode; select a subset of secondary transforms out of a set of secondary transforms including multiple low-frequency non-separable secondary transforms (LFNST) based on the selected intra-prediction mode, wherein the selected subset of secondary transforms includes at least one of the multiple LFNST; derive a prediction residual for the block; transform the prediction residual using a LFNST from the selected subset; and encode into the data stream, the transformed prediction residual for the block, wherein the same subset of secondary transforms is selected for the planar intra-prediction mode and each of the at least one matrix based intra-prediction mode.

32. The apparatus of claim 31, wherein in response to the intra-prediction mode being selected from the second set of intra-prediction modes, the processor is configured to: derive a prediction vector generated from a matrix-vector product between a vector derived from reference samples in a neighborhood of the block and a prediction matrix associated with the selected intra-prediction mode; and generate the prediction signal based on the prediction vector.

33. The apparatus of claim 31, wherein the processor is configured to select the subset of secondary transforms is based on: the selected intra-prediction mode, and a size of the block.

34. A non-transitory, computer-readable medium storing instructions that, when executed by at least one processor of an electronic device, cause the at least one processor to: generate, for a block of a

picture, an indication of an intra-prediction mode selected from a first set of intra-prediction modes or a second set of intra-prediction modes, wherein the first set of intra-prediction modes comprises at least one angular prediction mode, a planar intra-prediction mode, and a DC intra-prediction mode, and wherein the second set of intra-prediction modes comprises at least one matrix based intra-prediction mode; encode a prediction signal for the block using the selected intra-prediction mode; select a subset of secondary transforms out of a set of secondary transforms including multiple low-frequency non-separable secondary transforms (LFNST) based on the selected intra-prediction mode, wherein the selected subset of secondary transforms includes at least one of the multiple LFNST; derive a prediction residual for the block; transform the prediction residual using a LFNST from the selected subset; and encode into a data stream, the transformed prediction residual for the block, wherein the same subset of secondary transforms is selected for the planar intra-prediction mode and each of the at least one matrix based intra-prediction mode.

35. The non-transitory, computer-readable medium of claim 34, wherein in response to the intra-prediction mode being selected from the second set of intra-prediction modes, the instructions that when executed cause the at least one processor to: derive a prediction vector generated from a matrix-vector product between a vector derived from reference samples in a neighborhood of the block and a prediction matrix associated with the selected intra-prediction mode; and generate the prediction signal based on the prediction vector.
