

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250276131

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

Hee-Hanson; Alexander et al.

MEDICAMENT DELIVERY DEVICE

Abstract

A medicament delivery device includes a needle disposed at a distal end of the medicament delivery device, a body for a syringe, and a needle cover axially movable relative to the body between an extended position in which the needle cover covers the needle and a retracted position for dispensing medicament from the medicament delivery device. The needle protruding from the distal end of the needle cover when the needle cover is in the retracted position. The medicament delivery device includes an actuation member configured to be movable from an initial position to an engaged position such that when the actuation member is in its initial position, the needle cover can be axially moved between its retracted position and its extended position, and when the actuation member is in its engaged position, the actuation member engages with the needle cover to hold the needle cover in its retracted position.

Inventors: Hee-Hanson; Alexander (Melbourn, GB), Lever; Thomas (Melbourn, GB), Parrott; Michael (Melbourn, GB), Wilson; Robert (Melbourn, GB)

Applicant: Genzyme Corporation (Cambridge, MA)

Family ID: 96097227

Appl. No.: 18/594597

Filed: March 04, 2024

Publication Classification

Int. Cl.: A61M5/32 (20060101); A61M5/20 (20060101)

U.S. Cl.:

CPC A61M5/3245 (20130101); A61M5/2033 (20130101); A61M5/3257 (20130101); A61M2005/2013 (20130101); A61M2005/206 (20130101); A61M2005/208 (20130101)

Background/Summary

TECHNICAL FIELD

[0001] This application relates to a medicament delivery device for delivery of a medicament, for example an injector device such as an auto-injector device.

BACKGROUND

[0002] Injector devices are used to deliver a range of medicaments. In an auto-injector device, some or all of the actions required to use the injector device in administering medicament to a user are automated.

[0003] It is known to provide an auto-injector device having a needle cover which is axially movable to cover and uncover a needle, with the needle cover being biased by a spring to extend over the needle. Typically, the user presses the needle cover against an injection site, against the force of the spring, to push the needle cover into the housing and to uncover the needle which is pushed into the injection site. Medicament is automatically dispensed from the needle via an automated mechanism. A user typically holds the needle cover in a holding position for a predetermined period of time, to ensure that the correct dose of medicament is dispensed from the device, before removing the device from the injection site.

[0004] Some users find it difficult to fully depress the needle cover due to the force required or the change in force experienced during the activation movement. This may result in the needle not entering the user's skin to the correct depth, pain, discomfort, a wet injection site, early device removal and/or partial delivery of the medicament.

SUMMARY

[0005] A first aspect of this disclosure provides a medicament delivery device comprising: [0006] a needle for injecting medicament into a user, the needle disposed at a distal end of the medicament delivery device; [0007] a body for containing a pre-filled syringe; [0008] a needle cover axially movable relative to the body between an extended position, in which the needle cover covers the needle, and a retracted position for dispensing medicament from the medicament delivery device, wherein the needle protrudes from the distal end of the needle cover when the needle cover is in the retracted position; and [0009] an actuation member configured to be movable by the user from an initial position to an engaged position, [0010] wherein, when the actuation member is in its initial position, the needle cover can be axially moved between its retracted position and its extended position, and [0011] wherein, when the actuation member is in its engaged position, the actuation member engages with the needle cover to hold the needle cover in its retracted position.

[0012] The medicament delivery device may further comprise a biasing member configured to bias the actuation member from its engaged position to its initial position.

[0013] The actuation member may be configured to be moved from its initial position to its engaged position by the user applying an actuation force to an outer surface of the actuation member.

[0014] The actuation member may comprise a button arranged at an outer surface of the body.

[0015] The actuation member may comprise a protrusion; the needle cover may comprise a cooperating element; the protrusion may be engaged with the cooperating element when the actuation member is in its engaged position to hold the needle cover in its retracted position; and the protrusion may be disengaged from the cooperating element when the actuation member is in its initial position such that the needle cover can be axially moved between its retracted position and its extended position.

[0016] The protrusion may be configured to engage a distal-facing side of the cooperating element when the actuation member is in its engaged position to hold the needle cover in its retracted position.

[0017] The needle cover may comprise a resilient member for engaging with a cooperating element of the medicament delivery device, and the actuation member, when moved from its initial position to its engaged position, may be configured to cause the resilient member to be deflected such that the resilient member engages the cooperating element to hold the needle cover in its retracted position.

[0018] The resilient member may comprise a flexible arm and a protrusion disposed on a free end of the flexible arm; the actuation member may comprise an elongate arm; and the elongate arm may be configured to push the flexible arm when the actuation member is moved from its initial position to its engaged position, to cause the flexible arm to deflect such that the protrusion engages the cooperating element to hold the needle cover in its retracted position.

[0019] The resilient member may comprise a flexible arm and a protrusion disposed on a free end of the flexible arm; the actuation member may comprise an elongate arm; the body may comprise the cooperating element; the flexible arm may be movable between a first position, in which the protrusion engages the cooperating element to hold the needle cover in its retracted position, and a second position, in which the protrusion is disengaged from the cooperating element; the flexible arm may be biased to deflect from its second position to its first position; the elongate arm may be configured to hold the flexible arm in its second position when the actuation member is in its initial position; and the elongate arm may be configured to release the flexible arm to deflect to its first position when the actuation member is in its engaged position.

[0020] The actuation member comprises a slider, the slider comprising: a slider body arranged at an outer surface of the body; a resilient arm extending from the slider body through an aperture in the body; and a protrusion disposed at a free end of the resilient arm between an inner surface of the body and an outer surface of the needle cover, wherein the actuation member is configured to be moved from its initial position to its engaged position by a user sliding the slider body towards the aperture in the body such that the resilient arm is deflected by an edge of the aperture to cause the protrusion to engage a cooperating element disposed on the needle cover to hold the needle cover in its retracted position.

[0021] The actuation member may comprise a pivotable arm arranged to extend through an aperture in the body, the pivotable arm comprising: a first arm portion arranged outside the body; a second arm portion arranged inside the body and having a protrusion disposed at a free end of the second arm portion; and a pivot arranged between the first arm portion and the second arm portion, wherein the actuation member is configured to be moved from its initial position to its engaged position by a user applying an actuation force to the first arm portion to cause the first arm portion and the second arm portion to rotate about the pivot such that the protrusion disposed at the free end of the second arm portion is brought into engagement with a cooperating element disposed on the needle cover to hold the needle cover in its retracted position.

[0022] The actuation member may comprise a rotatable collar arranged to surround an outer surface of the body, the rotatable collar comprising a protrusion disposed on an inner surface of the rotatable collar, the protrusion extending through an aperture in the body, wherein the actuation member is configured to be moved from its initial position to its engaged position by a user rotating the rotatable collar about the body such that the protrusion is brought into engagement with a cooperating element disposed on the needle cover to hold the needle cover in its retracted position.

[0023] The actuation member may comprise a resilient portion of the body and a protrusion formed on an inner surface of the resilient portion of the body, wherein the actuation member is configured to be moved from its initial position to its engaged position by a user applying an actuation force to an outer surface of the resilient portion of the body such that the resilient portion of the body is deflected to cause the protrusion to engage a cooperating element disposed on the needle cover to hold the needle cover in its retracted position.

[0024] The medicament delivery device may further comprise a needle cover biasing member configured to exert a force which biases the needle cover axially, towards the distal end of the

medicament delivery device.

[0025] The medicament delivery device may further comprise the pre-filled syringe.

[0026] A second aspect of this disclosure provides a medicament delivery device comprising:

[0027] a body for containing a pre-filled syringe; [0028] a needle cover axially movable relative to the body between an extended position, in which the needle cover covers a needle coupled to the pre-filled syringe, and a retracted position, in which the needle protrudes from a distal end of the needle cover; and [0029] a button configured to be actuated by a user to hold the needle cover in its retracted position.

[0030] The button may be configured to be actuated such that it moves from an initial position, in which the needle cover can be axially moved between its retracted position and its extended position, to an engaged position, in which the button holds the needle cover in its retracted position.

[0031] The medicament delivery device may further comprise a biasing member configured to bias the button from its engaged position to its initial position.

[0032] The button may be configured to be actuated by the user applying an actuation force to an outer surface of the button.

[0033] The button may be arranged at an outer circumferential surface of the body and actuation of the button may cause the button to move radially into the body to hold the needle cover.

[0034] The button may be arranged to extend through an opening at a proximal end face of the body and actuation of the button may cause the button to move axially into the body to hold the needle cover.

[0035] The button may be integrally formed with the body.

[0036] The needle cover may be arranged to prevent the button from being actuated when the needle cover is in its extended position, and the needle cover may be arranged to allow the button to be actuated when the needle cover is in its extended position

[0037] The button may comprise a protrusion, the needle cover may comprise a cooperating element, and actuation of the button may cause the protrusion to engage the cooperating element to hold the needle cover in its retracted position.

[0038] The cooperating element may comprise an aperture, a recess, a ridge or a frictional surface.

[0039] The needle cover may comprise a resilient member for engaging with a cooperating element of the medicament delivery device, wherein actuation of the button causes the resilient member to be deflected such that the resilient member engages the cooperating element to hold the needle cover in its retracted position.

[0040] The resilient member may comprise a flexible arm and a protrusion disposed on a free end of the flexible arm, the button may comprise an elongate arm, and actuation of the button may cause the elongate arm to deflect the flexible arm such that the protrusion engages the cooperating element to hold the needle cover in its retracted position.

[0041] The resilient member may comprise a flexible arm and a protrusion disposed on a free end of the flexible arm; the button may comprise an elongate arm; the body may comprise the cooperating element; the flexible arm may be movable between a first position, in which the protrusion engages the cooperating element to hold the needle cover in its retracted position, and a second position, in which the protrusion is disengaged from the cooperating element; the flexible arm may be biased to deflect from its second position to its first position; the elongate arm may be configured to hold the flexible arm in its second position prior to actuation of the button; and actuation of the button may cause the elongate arm to release the flexible arm to deflect to its first position.

[0042] The medicament delivery device may further comprise a needle cover biasing member configured to exert a force to bias the needle cover from its retracted position to its extended position.

[0043] The medicament delivery device may further comprise the pre-filled syringe.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0044] Exemplary embodiments are described with reference to the accompanying drawings, in which:

[0045] FIG. 1A shows an injector device with a cap attached;

[0046] FIG. 1B shows the injector device of FIG. 1A with the cap removed;

[0047] FIG. 2A shows a simplified view of a injector device prior to use;

[0048] FIG. 2B shows a view of the device of FIG. 2A with injector device in the holding position;

[0049] FIG. 3A shows a medicament delivery device according to a first embodiment in an initial state;

[0050] FIG. 3B shows the medicament delivery device of FIG. 3A in an activated state;

[0051] FIG. 4A shows a medicament delivery device according to a second embodiment in an initial state;

[0052] FIG. 4B shows the medicament delivery device of FIG. 4A in an activated state, with the actuation member in an initial position;

[0053] FIG. 4C shows the medicament delivery device of FIG. 4B with the actuation member in an engaged position;

[0054] FIG. 4D shows the medicament delivery device of FIG. 4C with the actuation member having returned to the initial position;

[0055] FIG. 5 shows is a perspective view of a portion of the medicament delivery device of the second embodiment;

[0056] FIG. 6A shows a medicament delivery device according to a third embodiment in an initial state;

[0057] FIG. 6B shows the medicament delivery device of FIG. 6A in an activated state, with the actuation member in an initial position;

[0058] FIG. 6C shows the medicament delivery device of FIG. 6B with the actuation member in an engaged position;

[0059] FIG. 6D shows the medicament delivery device of FIG. 6C with the actuation member having returned to the initial position;

[0060] FIG. 7A shows a medicament delivery device according to a fourth embodiment in an initial state;

[0061] FIG. 7B shows the medicament delivery device of FIG. 7A in an activated state, with the actuation member in an initial position;

[0062] FIG. 7C shows the medicament delivery device of FIG. 7B with the actuation member in an engaged position;

[0063] FIG. 7D shows the medicament delivery device of FIG. 7C with the actuation member having returned to the initial position;

[0064] FIG. 8A shows a medicament delivery device according to a fifth embodiment in an initial state;

[0065] FIG. 8B shows the medicament delivery device of FIG. 8A in an activated state, with the actuation member in an initial position;

[0066] FIG. 8C shows the medicament delivery device of FIG. 8B with the actuation member in an engaged position;

[0067] FIG. 8D shows the medicament delivery device of FIG. 8C with the actuation member having returned to the initial position;

[0068] FIG. 9A shows a medicament delivery device according to a sixth embodiment in an initial state;

[0069] FIG. 9B shows the medicament delivery device of FIG. 9A in an activated state, with the

actuation member in an initial position;

[0070] FIG. 9C shows the medicament delivery device of FIG. 9B with the actuation member in an engaged position;

[0071] FIG. 9D shows the medicament delivery device of FIG. 9C with the actuation member having returned to the initial position;

[0072] FIG. 10A shows portions of a medicament delivery device according to a seventh embodiment with an actuation member in an initial position;

[0073] FIG. 10B shows portions of the medicament delivery device of FIG. 10A with the actuation member in an engaged position; and

[0074] FIG. 11A shows portions of a medicament delivery device according to an eighth embodiment with an actuation member in an initial position;

[0075] FIG. 11B shows portions of the medicament delivery device of FIG. 11A with the actuation member in an engaged position; and

[0076] FIG. 12A shows portions of a medicament delivery device according to a ninth embodiment with an actuation member in an initial position;

[0077] FIG. 12B shows portions of the medicament delivery device of FIG. 12A with the actuation member in an engaged position; and

[0078] FIG. 13A shows portions of a medicament delivery device according to a tenth embodiment with an actuation member in an initial position;

[0079] FIG. 13B shows portions of the medicament delivery device of FIG. 13A with the actuation member in an engaged position; and

[0080] FIG. 14 is a force profile graph illustrating the force profile of a first device and the medicament delivery devices according to the first to tenth embodiments.

DETAILED DESCRIPTION

[0081] A drug delivery device (also referred to as a medicament delivery device), as described herein, may be configured to inject a medicament into a patient. For example, delivery could be sub-cutaneous, intra-muscular, or intravenous. Such a device could be operated by a patient or caregiver, such as a nurse or physician, and can include various types of safety syringe, pen-injector, or auto-injector. The device can include a cartridge-based system that requires piercing a sealed ampule before use. Volumes of medicament delivered with these various devices can range from about 0.5 ml to about 2 ml. Yet another device can include a large volume device (“LVD”) or patch pump, configured to adhere to a patient's skin for a period of time (e.g., about 5, 15, 30, 60, or 120 minutes) to deliver a “large” volume of medicament (typically about 2 ml to about 10 ml).

[0082] In combination with a specific medicament, the presently described devices may also be customized in order to operate within required specifications. For example, the device may be customized to inject a medicament within a certain time period (e.g., about 3 to about 20 seconds for auto-injectors, and about 10 minutes to about 60 minutes for an LVD). Other specifications can include a low or minimal level of discomfort, or to certain conditions related to human factors, shelf-life, expiry, biocompatibility, environmental considerations, etc. Such variations can arise due to various factors, such as, for example, a drug ranging in viscosity from about 3 cP to about 50 cP. Consequently, a drug delivery device will often include a hollow needle ranging from about 25 to about 31 Gauge in size. Common sizes are 27 and 29 Gauge.

[0083] The delivery devices described herein can also include one or more automated functions. For example, one or more of needle insertion, medicament injection, and needle retraction can be automated. Energy for one or more automation steps can be provided by one or more energy sources. Energy sources can include, for example, mechanical, pneumatic, chemical, or electrical energy. For example, mechanical energy sources can include springs, levers, elastomers, or other mechanical mechanisms to store or release energy. One or more energy sources can be combined into a single device. Devices can further include gears, valves, or other mechanisms to convert energy into movement of one or more components of a device.

[0084] The one or more automated functions of an auto-injector may each be activated via an activation mechanism. Such an activation mechanism can include one or more of a button, a lever, a needle sleeve, or other activation component. Activation of an automated function may be a one-step or multi-step process. That is, a user may need to activate one or more activation components in order to cause the automated function. For example, in a one-step process, a user may depress a needle sleeve against their body in order to cause injection of a medicament. Other devices may require a multi-step activation of an automated function. For example, a user may be required to depress a button and retract a needle shield in order to cause injection.

[0085] In addition, activation of one automated function may activate one or more subsequent automated functions, thereby forming an activation sequence. For example, activation of a first automated function may activate at least two of needle insertion, medicament injection, and needle retraction. Some devices may also require a specific sequence of steps to cause the one or more automated functions to occur. Other devices may operate with a sequence of independent steps.

[0086] Some delivery devices can include one or more functions of a safety syringe, pen-injector, or auto-injector. For example, a delivery device could include a mechanical energy source configured to automatically inject a medicament (as typically found in an auto-injector) and a dose setting mechanism (as typically found in a pen-injector).

[0087] According to some embodiments of the present disclosure, an exemplary drug delivery device **10** is shown in FIGS. **1A** & **1B**. Device **10**, as described above, is configured to inject a medicament **15** into a patient's body. Device **10** includes a housing **11** which typically contains a reservoir **14** containing the medicament **15** to be injected (e.g., a syringe) and the components required to facilitate one or more steps of the delivery process. Device **10** can also include a cap assembly **12** that can be detachably mounted to the housing **11**. Typically, a user removes cap **12** from housing **11** before device **10** can be operated. Device **10** can include a window **11a** through which a user may view medicament **15** remaining in the reservoir **14**.

[0088] As shown, housing **11** is substantially cylindrical and has a substantially constant diameter along the longitudinal axis X of the device **10**. The housing **11** has a distal region **20** and a proximal region **21**. The term “distal” refers to a location that is relatively closer to a site of injection, and the term “proximal” refers to a location that is relatively further away from the injection site.

[0089] Device **10** can also include a needle sleeve **13** coupled to housing **11** to permit movement of sleeve **13** relative to housing **11**. For example, sleeve **13** can move in a longitudinal direction parallel to longitudinal axis X. Specifically, movement of sleeve **13** in a proximal direction can permit a needle **17** to extend from distal region **20** of housing **11**.

[0090] Insertion of needle **17** can occur via several mechanisms. For example, needle **17** may be fixedly located relative to housing **11** and initially be located within an extended needle sleeve **13**. Proximal movement of sleeve **13** by placing a distal end of sleeve **13** against an injection site such as a patient's body and moving housing **11** in a distal direction will uncover the distal end of needle **17**. Such relative movement allows the distal end of needle **17** to extend into the patient's body. Such insertion is termed “manual” insertion as needle **17** is manually inserted via the patient's manual movement of housing **11** relative to sleeve **13**.

[0091] Another form of insertion is “automated,” whereby needle **17** moves relative to housing **11**. Such insertion can be triggered by movement of sleeve **13** or by another form of activation, such as, for example, a button **22**. As shown in FIGS. **1A** & **1B**, button **22** is located at a proximal end **21** of housing **11**. However, in other embodiments, button **22** could be located on a side of housing **11**.

[0092] Other manual or automated features can include drug injection or needle retraction, or both. Injection is the process by which a bung or piston **23** is moved from a proximal location within a syringe to a more distal location within the syringe in order to force a medicament **15** from the syringe through needle **17**. In some embodiments, a drive spring is under compression before device **10** is activated. A proximal end of the drive spring can be fixed within proximal region **21** of

housing **11**, and a distal end of the drive spring can be configured to apply a compressive force to a proximal surface of piston **23**. Following activation, at least part of the energy stored in the drive spring can be applied to the proximal surface of piston **23**. This compressive force can act on piston **23** to move it in a distal direction. Such distal movement acts to compress the liquid medicament **15** within the syringe, forcing it out of needle **17**.

[0093] Following injection, needle **17** can be retracted within sleeve **13** or housing **11**. Retraction can occur when sleeve **13** moves distally as a user removes device **10** from a patient's body. This can occur as needle **17** remains fixedly located relative to housing **11**. Once a distal end of sleeve **13** has moved past a distal end of needle **17**, and needle **17** is covered, sleeve **13** can be locked. Such locking can include locking any proximal movement of sleeve **13** relative to housing **11**.

[0094] Another form of needle retraction can occur if needle **17** is moved relative to housing **11**. Such movement can occur if the syringe within housing **11** is moved in a proximal direction relative to housing **11**. This proximal movement can be achieved by using a retraction spring, located in distal region **20**. A compressed retraction spring, when activated, can supply sufficient force to the syringe to move it in a proximal direction. Following sufficient retraction, any relative movement between needle **17** and housing **11** can be locked with a locking mechanism. In addition, button **22** or other components of device **10** can be locked as required.

[0095] FIGS. 2A and 2B show a simplified view of a device **110** having a needle cover **113** which is axially movable to cover and uncover the needle **117**. The needle cover **113** is biased by a spring **104** to extend over the needle **117**.

[0096] FIG. 2A shows the device before use, in which the needle cover **113** is exposed out of the end of the device body **103** and covers the needle **117**. A force can be applied by a user against a spring force **125** to move the needle cover **113** from the position shown in FIG. 2A towards a holding position shown in FIG. 2B, and a holding force **120** can be applied to maintain the needle cover in the holding position.

[0097] Typically, the user presses the needle cover **113** against an injection site **115** to push the needle cover **113** at least partially into the device body **103**. The exposed needle **117** is pushed into the injection site **115**. In the holding position, medicament is automatically dispensed from the needle **117** via an automated mechanism. A user typically holds the needle cover **113** in the holding position for a predetermined period of time, to ensure that the correct dose of medicament is dispensed from the device **110**, before removing the device from the injection site **115**.

[0098] The spring force **125** against which the user applies a force to move the needle cover **113** is one component of the “activation force” of the device **110**. The activation force refers to the force or force profile that the user exerts on the device **110** to move the needle cover **113** from the position shown in FIG. 2A to the position shown in FIG. 2B. If this force or force profile is not well balanced, it can lead to difficulty in activating the device **100** for some users, or increase the pain or anxiety associated with using the device.

[0099] FIGS. 3A & 3B show features of a first embodiment of a medicament delivery device **300**, which is also referred to herein as an injector device. These Figures show a cross section of the device **300** before and after activation of the device **300**.

[0100] The device **300** has a distal end **302** and a proximal end **304** arranged along the longitudinal axis Y of the device **300**. The device **300** has a needle **306** for injecting medicament into a user at an injection site S (such as the user's skin), a needle cover **308** and a body **310** (also known as a housing). The body **310** may be substantially cylindrical and has a substantially constant diameter along the longitudinal axis Y. The body **310** forms part of the external surface of the device **300** and is configured to be gripped by a user, as indicated by the user's hand **350** in FIGS. 3A and 3B.

[0101] The device **300** houses a pre-filled syringe **312** containing a medicament and a carrier **322** which supports the pre-filled syringe **312** within the body **310**. The needle **306** is in fluid communication with the pre-filled syringe **312** and extends from the distal end of the pre-filled syringe **312**. The needle cover **308** is axially movable relative to the body **310** between an initial,

extended position, shown in FIG. 3A, in which the needle cover **308** covers (surrounds) the needle **306**, and a retracted position, shown in FIG. 3B, for dispensing medicament from the device **300**. In the retracted position, the needle **306** protrudes from the distal end of the needle cover **308**. [0102] A needle cover biasing member **314** such as a spring may be arranged in the body **310** to exert a biasing force against the needle cover **308** which biases the needle cover **308** axially, in the distal direction, from the retracted position towards the extended position. A force can be applied by the user against the biasing force of the needle cover biasing member **314** to move the needle cover **308** proximally from the extended position shown in FIG. 3A to the retracted position shown in FIG. 3B.

[0103] Medicament is dispensed from the medicament delivery device **300** via the needle **306** while the needle cover **308** is in the retracted position. An automated dispensing mechanism is triggered to start the dispensing of medicament when the needle cover **308** has moved proximally to reach a predetermined axial position within the body **310**. The predetermined position may be located just distally of the retracted position, but in other cases may be located just proximally of the retracted position or may be the same as the retracted position.

[0104] The automated dispensing mechanism may comprise a plunger **316** that is automatically released when the needle cover **308** reaches the predetermined axial position. Once the plunger **316** is released, it moves distally within the pre-filled syringe **312** to dispense medicament from the pre-filled syringe **312** through the needle **306**, in some embodiments by engaging a bung or piston **320** within the pre-filled syringe **312**. The plunger **316** may be moved by a driving force provided by a plunger driving mechanism such as a drive spring **318**, however other suitable forms of a plunger driving mechanism than a drive spring **318** may instead be used to move the plunger **316**, such as an electromechanical motor or a gas cartridge.

[0105] In preparation for using the device **300** to administer the medicament, the user may remove a cap from the distal end **302** of the medicament delivery device **300**. To initiate medicament delivery, the user presses the needle cover **308** against an injection site S such as the user's skin to move the needle cover **308** axially relative to the body **310** in a proximal direction and to uncover the needle **306**. The needle **306** is pushed into the injection site S. The automated dispensing mechanism is released, and medicament is automatically dispensed from the device **300** via the needle **306**. The user holds the needle cover **308** in the retracted position while the medicament is dispensed.

[0106] FIG. 3A shows the device **300** in a pre-use state, which may also be called an initial state or initial position. When the device **300** is in this state, the needle cover **308** is in an extended position with respect to the body **310** in which it covers the needle **306**.

[0107] The device **300** comprises an actuation member **324** for holding the needle cover **308** in its retracted position. In the first embodiment, the actuation member **324** takes the form of a button arranged at an outer surface of the body **310**. The actuation member **324** comprises an actuation element **326** arranged at an outer surface of the body **310** and having an actuation surface **327**. The actuation member **324** further comprises a protrusion **328** disposed at the actuation element **326** and extending through an aperture **330** in the body **310**. The actuation member **324** is movable with respect to the needle cover **308** between an initial position shown in FIG. 3A and an engaged position shown in FIG. 3B, as described below.

[0108] The needle cover **308** comprises a cooperating element **332**, which may take the form of an aperture, a recess, a ridge or a frictional surface. The cooperating element **332** is arranged to be engaged by the protrusion **328** of the actuation member **324** when the needle cover **308** is in its retracted position and the actuation member **324** is in its engaged position, to hold the needle cover **308** in its retracted position.

[0109] FIG. 3A shows the actuation member **324** in its initial position with respect to the needle cover **308**, in which the protrusion **328** is disengaged from the cooperating element **332**, thereby allowing the needle cover **308** to axially move back and forth between its retracted position and its

extended position. The device **300** may comprise a biasing member such as a spring that is configured to apply a biasing force to the actuation member **324** to bias the actuation member **324** into its initial position, from its engaged position.

[0110] As shown in FIG. **3A**, when the needle cover **308** is in its extended position with respect to the body **310**, the cooperating element **332** is not in alignment with the protrusion **328** of the actuation member **324**. Due to this misalignment, the protrusion **328** cannot engage the cooperating element **332** to hold the needle cover **308** relative to the body **310** while the needle cover **308** is in its extended position. As shown in FIG. **3A**, the actuation member **324** is prevented from being moved from its initial position to its engaged position to engage the cooperating element **332** due to an abutment between the protrusion **328** and an outer surface of the needle cover **308** while the needle cover **308** is in its extended position.

[0111] FIG. **3B** shows the device **300** in an activated state. To transition the device **300** from the initial state shown in FIG. **3A** to the activated state shown in FIG. **3B**, a distal force is applied via the body **310** while the needle cover **308** is placed against the injection site S, such as the user's skin, causing the needle cover **308** to move proximally into the device **300**.

[0112] When the device **300** is in the activated state as shown in FIG. **3B**, the needle cover **308** is fully displaced into the device **300** and is in its retracted position. The needle **306** protrudes from the end of the needle cover **308** to its maximum extent. The medicament dispensing mechanism of the device **300** is triggered. In this example, triggering of the dispensing mechanism comprises the drive spring **318** being released such that it expands from a compressed state to an extended state, applying a distal force to a plunger **316** of the pre-filled syringe **312**. The distal force causes the plunger **316** to move distally and in turn cause medicament to be expelled from the pre-filled syringe **312** via the needle **306**.

[0113] The user should hold the device **300** steady against the injection site S while the medicament is being dispensed. During medicament delivery, the needle cover biasing member **314** continues to exert a biasing force against the needle cover **308** to bias the needle cover **308** axially, in the distal direction. Some users such as those with dexterity impairments may encounter difficulty in overcoming the biasing force to maintain the needle cover **308** in its retracted position while the medicament is being dispensed. Such users may find it difficult to hold the device **300** steady against the injection site S due to the strength of biasing force, causing them to move the device **300** before medicament delivery is complete. This could result in underdosing of medicament, leakage of medicament, and/or pain or discomfort for the user. The actuation member **324** of the device **300** may be used to overcome such issues by preventing the biasing force of the needle cover biasing member **314** from being transferred to the user when the actuation member **324** is in its engaged position.

[0114] The actuation member **324** is movable by the user from the initial position shown in FIG. **3A** to an engaged position shown in FIG. **3B**. To overcome the biasing force of the needle cover biasing member **314**, the user can actuate the actuation member **324** while the needle cover **308** is in its retracted position such that the actuation member **324** moves from its initial position to its engaged position.

[0115] When the actuation member **324** is in its initial position, the protrusion **328** is disengaged from the cooperating element **332** and so the needle cover **308** can be axially moved between its retracted position and its extended position. However, when the actuation member **324** is in its engaged position (for example as shown in FIG. **3B**), the actuation member **324** engages with the needle cover **308** to hold the needle cover **308** in its retracted position. More specifically, when the actuation member **324** is in its engaged position, the protrusion **328** of the actuation member **324** engages with the cooperating element **332** of the needle cover **308** to hold the needle cover **308** in its retracted position.

[0116] During proximal translation of the needle sleeve **308** from its extended position to its retracted position, the cooperating element **332** of the needle sleeve **308** is brought into (axial and

radial) alignment with the protrusion **328** of the actuation member **324** such that, when the needle cover **308** is in its retracted position shown in FIG. 3B, the actuation member **324** is able to be moved from its initial position to its engaged position.

[0117] The actuation member **324** may be configured to be moved from its initial position to its engaged position by the user applying an actuation force to an outer surface of the actuation member **324**, such as the actuation surface **327**. As an example, the user may apply the actuation force by pushing the actuation surface **327** of the actuation member **324** with a finger **352** or thumb radially inwards, towards the needle cover **308**. The user may apply the actuation force by making direct contact between their finger **352** and the actuation surface **327**. The actuation force may be a separate force to any force provided by the user to retract the needle cover **308** and/or initiate medicament delivery. In other words, application of the actuation force may require a separate, distinct movement by the user to any movement used to retract the needle cover **308** and/or initiate medicament delivery.

[0118] Applying the actuation force to the actuation surface **327** causes the actuation element **326** and the protrusion **328** to move radially towards the needle cover **308**, with the protrusion **328** translating through the aperture **330** in the body **310** to engage the cooperating element **332**. Through the engagement between the protrusion **328** and the cooperating element **332**, the needle cover **308** is held in the retracted position by the actuation member **324**, as shown in FIG. 3B. More specifically, engagement between a distal-facing side of the cooperating element **332** and a proximal-facing side of the protrusion **328** (at the same time as engagement between a distal-facing side of the protrusion **328** and a proximal-facing side of the aperture **330**) prevents distal movement of the needle cover **308** relative to the body **310**. Proximal movement of the needle cover **308** relative to the body **310** may also be prevented by engagement between a proximal-facing side of the cooperating element **332** and a distal-facing side of the protrusion **328** (at the same time as engagement between a proximal-facing side of the protrusion **328** and a distal-facing side of the aperture **330**).

[0119] Where the cooperating element **332** comprises an aperture or recess formed in the needle cover **308**, the protrusion **328** may be dimensioned to have a slightly smaller cross-section than the aperture or recess. This is to allow for tolerance when inserting the protrusion **328** into the aperture or recess, but at the same time minimizing the amount of possible relative movement between the needle cover **308** and the body **310** while the actuation member **324** is in its engaged position that may occur if the cross-section of the aperture or recess is substantially greater than the cross-section of the protrusion **328**.

[0120] The needle cover **308** is prevented from moving distally with respect to the body **310** while the actuation member **324** is in its engaged position, regardless of the biasing force exerted on the needle cover **308** by the needle cover biasing member **314**. As a result, the biasing force exerted on the needle cover **308** is not transferred from the needle cover **308** to the injection site S. This means that the user is no longer required to overcome the biasing force of the needle cover biasing member **314** while the actuation member **324** is in its engaged position, making it easier for the user to hold the device **300** steady at the injection site S.

[0121] FIGS. 3A and 3B show the actuation member **324** located at the proximal end **304** of the device **300**. Such a position may make it easier for the user to push the actuation member **324** using their index finger or thumb while they grasp the body **310** of the device **300** during a medicament delivery. However, it should be understood that the actuation member **324** may instead be located at a different region of the device **300** that is not at the proximal end **304**.

[0122] After the medicament has been delivered, the user releases the actuation member **324** by removing their finger **352** from the actuation surface **327**, thereby removing the actuation force applied to the actuation member **324**. If the device **300** comprises a biasing member that is configured to bias the actuation member **324** from its engaged position to its initial position, the actuation member **324** may be caused to automatically return from its engaged position to its initial

position once the actuation force is removed. Alternatively, if no biasing member is present then the user may manually move the actuation member **324** from its engaged position to its initial position. [0123] In moving the actuation member **324** from its engaged position back to its initial position, the protrusion **328** moves radially away from the longitudinal axis Y of the device **300** and from the needle cover **308**, disengaging the cooperating element **332** of the needle cover **308**. As such, the needle cover **308** is no longer held in its retracted position by the actuation member **324** and is able to move distally with respect to the body **310**. The user may then remove the device **300** from the injection site S. Since the needle cover **308** is no longer being held by the actuation member **324**, the needle cover **308** moves distally from its retracted position to its initial position under the biasing force of the needle cover biasing member **314** once the body **310** and needle cover **308** are pulled away from the injection site S. The post-use state of the device **300** will appear similar to the pre-use state shown in FIG. 3A, where the needle cover **308** is in its initial position extending from the distal end **302** of the body **310** and covering the needle **306**, however the plunger **316**, drive spring **318** and piston **320** will each have moved distally.

[0124] The provision of a biasing member to bias the actuation member **324** towards its initial position can be beneficial in that it can ensure the actuation member **324** automatically returns to its initial position by default whenever it is not being actuated by a user, which in turn can ensure the needle cover **308** is automatically moved to its extended position to protect the user from the needle **306** by default. The presence of the biasing member may therefore improve the safety of the device **300** by reducing the likelihood of an accidental needle-stick event.

[0125] It has generally been described in relation to FIGS. 3A and 3B that, after the medicament has been delivered, the user releases the actuation member **324** before removing the device **300** from the injection site S. This order of steps can ensure that the needle cover **308** moves to cover the needle **306** as soon as the device **300** is removed from the injection site S, and therefore the needle **306** is not at any point exposed to the user (except when the distal end of the needle **306** is actually inserted into the user's skin during medicament delivery). However, it should be understood that in other instances the user may first remove the device **300** from the injection site **300** and subsequently release the actuation member **324**.

[0126] FIGS. 4A to 4D show features of a second embodiment of a medicament delivery device **400**, which is also referred to herein as an injector device. These Figures show a cross section of the device **400** before and after activation of the device **400**. Certain features of the device **400** may be omitted from FIGS. 4A to 4D for clarity.

[0127] The device **400** has a distal end **402** and a proximal end **404** arranged along a longitudinal axis of the device **400**. The device **400** has a needle **406** for injecting medicament into a user at an injection site (such as the user's skin), a needle cover **408** and a body **410** (also known as a housing). The body **410** may be substantially cylindrical and has a substantially constant diameter along the longitudinal axis. The body **410** forms part of the external surface of the device **400** and is configured to be gripped by a user during an injection process.

[0128] The device **400** houses a pre-filled syringe **412** containing a medicament and a carrier **422** which supports the pre-filled syringe **412** within the body **410**. The needle **406** is in fluid communication with the pre-filled syringe **412** and extends from the distal end of the pre-filled syringe **412**. The needle cover **408** is axially movable relative to the body **410** between an initial, extended position, shown in FIG. 4A, in which the needle cover **408** covers (surrounds) the needle **406**, and a retracted position, shown in FIG. 4B, for dispensing medicament from the device **400**. In the retracted position, the needle **406** protrudes from the distal end of the needle cover **408**.

[0129] A needle cover biasing member such as a spring may be arranged in the body **410** (e.g. at a proximal end of the body **410**) to exert a biasing force against the needle cover **408** which biases the needle cover **408** axially, in the distal direction. A force can be applied by the user against the biasing force of the needle cover biasing member to move the needle cover **408** proximally from the extended position shown in FIG. 4A to the retracted position shown in FIG. 4B.

[0130] Medicament is dispensed from the medicament delivery device **400** via the needle **406** while the needle cover **408** is in the retracted position. An automated dispensing mechanism is triggered to start the dispensing of medicament when the needle cover **408** has moved proximally to reach a predetermined axial position within the body **410**. The predetermined position may be located just distally of the retracted position, but in other cases may be located just proximally of the retracted position or may be the same as the retracted position.

[0131] The automated dispensing mechanism may comprise a plunger that is automatically released when the needle cover **408** reaches the predetermined axial position. Once the plunger is released, it moves distally within the pre-filled syringe **412** to dispense medicament from the pre-filled syringe **412** through the needle **406**. The plunger may be moved by a driving force provided by a plunger driving mechanism such as a drive spring, however other suitable forms of a plunger driving mechanism than a drive spring may instead be used to move the plunger, such as an electromechanical motor or a gas cartridge.

[0132] In preparation for using the device **400** to administer the medicament, the user may remove a cap from the distal end **402** of the medicament delivery device **400**. To initiate medicament delivery, the user presses the needle cover **408** against an injection site such as the user's skin to move the needle cover **408** axially relative to the body **410** in a proximal direction and to uncover the needle **406**. The needle **406** is pushed into the injection site. The automated dispensing mechanism is released, and medicament is automatically dispensed from the device **400** via the needle **406**. The user holds the needle cover **408** in the retracted position while the medicament is dispensed.

[0133] FIG. 4A shows the device **400** in a pre-use state, which may also be called an initial state or initial position. When the device **400** is in this state, the needle cover **408** is in an extended position with respect to the body **410** in which it covers the needle **406**.

[0134] The device **400** comprises an actuation member **424** for holding the needle cover **408** in its retracted position. In the second embodiment, the actuation member **424** takes the form of a resilient collar arranged circumferentially around an outer surface of the body **410**. The actuation member **424** comprises an actuation element **426** arranged at an outer surface of the body **410** and having an actuation surface **427**. The actuation member **424** further comprises a protrusion **428** disposed at the actuation element **426** and extending through an aperture **430** in the body **410**. The actuation member **424** is movable with respect to the needle cover **408** between an initial position shown in FIG. 4A and an engaged position shown in FIG. 4C, as described later.

[0135] Briefly turning to FIG. 5, an exploded perspective view of a portion of the device **400** of FIG. 4A is shown, showing the actuation member **424**. In FIG. 5, the actuation member **424** is shown radially separated from the body **410** of the device **400** for the sake of more clearly showing the features of the actuation member **424**. However, in actual use of the device **400**, the actuation member **424** will be arranged circumferentially around an outer surface of the body **410**. FIG. 5 shows the actuation element **426** of the actuation member **424** and the protrusion **428** extending away from the actuation element **426**, radially towards the body **410** and the inside of the device **400**. The protrusion **428** is aligned with the aperture **430** so that it may move through the aperture **430**. A flexible portion **504** of the actuation member **424** is configured to surround the outer surface of the body **410** when the actuation member **424** is mounted on the body **410**, to assist with holding the actuation member **424** in a fixed axial position along the body **410**. The flexible portion may be configured to be received within a circumferential recess **510** formed in the outer surface of the body **410**, to assist with holding the actuation member **424** in the fixed axial position along the body **410**. The resilient nature of the flexible portion **504** allows the actuation member **424**, and more particularly the flexible portion **504**, to be deformed upon application of a force F to the actuation element **426** to move the actuation member **424** from its initial position to its engaged position, as described later.

[0136] Returning to FIG. 4A, the needle cover **408** comprises a cooperating element **432**, which

may take the form of an aperture, a recess, a ridge or a frictional surface. The cooperating element **432** is arranged to be engaged by the protrusion **428** of the actuation member **424** when the needle cover **408** is in its retracted position and the actuation member **424** is in its engaged position. [0137] FIG. **4A** shows the actuation member **424** in its initial position with respect to the needle cover **408**, in which the protrusion **428** is disengaged from the cooperating element **432**, thereby allowing the needle cover **408** to axially move back and forth between its retracted position and its extended position. The flexible portion **504** of the actuation member **424** acts a biasing member that is configured to apply a biasing force to the actuation member **424** to bias it into its initial position, from its engaged position.

[0138] As shown in FIG. **4A**, when the needle cover **408** is in its extended position with respect to the body **410**, the cooperating element **432** is not in alignment with the protrusion **428** of the actuation member **424**. Due to this misalignment, the protrusion **428** cannot engage the cooperating element **432** to hold the needle cover **408** relative to the body **410** while the needle cover **408** is in its extended position. As shown in FIG. **4A**, the actuation member **424** may be prevented from being moved from its initial position to its engaged position to engage the cooperating element **432** due to an abutment between the protrusion **428** and an outer surface of the needle cover **408** while the needle cover **408** is in its extended position.

[0139] FIG. **4B** shows the device **400** in an activated state. To transition the device **400** from the initial state shown in FIG. **4A** to the activated state shown in FIG. **4B**, a distal force is applied via the body **410** while the needle cover **408** is placed against the injection site, such as the user's skin, causing the needle cover **408** to move proximally into the device **400**.

[0140] When the device **400** is in the activated state as shown in FIG. **4B**, the needle cover **408** is fully displaced into the device **400** and is in its retracted position. The needle **406** protrudes from the end of the needle cover **408** to its maximum extent. The medicament dispensing mechanism of the device **400** is triggered. In this example, triggering of the dispensing mechanism comprises the drive spring being released such that the drive spring expands from a compressed state to an extended state, applying a distal force to a plunger of the pre-filled syringe **412**. The distal force causes the plunger to move distally and in turn cause medicament to be expelled from the pre-filled syringe **412** via the needle **406**.

[0141] The user should hold the device **400** steady against the injection site while the medicament is being dispensed. During medicament delivery, the needle cover biasing member continues to exert a biasing force against the needle cover **408** to bias the needle cover **408** axially, in the distal direction. The actuation member **424** of the device **400** may be used to overcome this biasing force.

[0142] The actuation member **424** is movable by the user from the initial position shown in FIG. **4B** to an engaged position shown in FIG. **4C**. To overcome the biasing force of the needle cover biasing member, the user can actuate the actuation member **424** while the needle cover **408** is in its retracted position such that the actuation member **424** moves from its initial position shown in FIG. **4B** to its engaged position shown in FIG. **4C**.

[0143] When the actuation member **424** is in its initial position (for example as shown in FIG. **4B**), the protrusion **428** is disengaged from the cooperating element **432** and so the needle cover **408** can be axially moved between its retracted position and its extended position. However, when the actuation member **424** is in its engaged position (for example as shown in FIG. **4C**), the actuation member **424** engages with the needle cover **408** to hold the needle cover **408** in its retracted position. More specifically, when the actuation member **424** is in its engaged position, the protrusion **428** of the actuation member **424** engages with the cooperating element **432** of the needle cover **408** to hold the needle cover **408** in its retracted position.

[0144] During proximal translation of the needle sleeve **408** from its extended position shown in FIG. **4A** to its retracted position shown in FIG. **4B**, the cooperating element **432** of the needle sleeve **408** is brought into (axial and radial) alignment with the protrusion **428** of the actuation member **424** such that, when the needle cover **408** is in its retracted position shown in FIG. **4B**, the

actuation member **424** is able to be moved from its initial position to its engaged position.

[0145] The actuation member **424** may be configured to be moved from its initial position to its engaged position by the user applying an actuation force F to an outer surface of the actuation member **424**, such as the actuation surface **427**. As an example, the user may apply the actuation force F by pushing the actuation surface **427** of the actuation member **424** with a finger or thumb radially inwards, towards the needle cover **408**. The user may apply the actuation force F by making direct contact between their finger and the actuation surface **427**. The actuation force F may be a separate force to any force provided by the user to retract the needle cover **408** and/or initiate medicament delivery. In other words, application of the actuation force F may require a separate, distinct movement by the user to any movement used to retract the needle cover **408** and/or initiate medicament delivery.

[0146] Applying the actuation force F to the actuation surface **427** causes the actuation element **426** and the protrusion **428** to move radially towards the needle cover **408**, with the protrusion **428** translating through the aperture **430** in the body **410** to engage the cooperating element **432**. Through the engagement between the protrusion **428** and the cooperating element **432**, the needle cover **408** is held in the retracted position by the actuation member **424**, as shown in FIG. 4C. More specifically, engagement between a distal-facing side of the cooperating element **432** and a proximal-facing side of the protrusion **428** (at the same time as engagement between a distal-facing side of the protrusion **428** and a proximal-facing side of the aperture **430**) prevents distal movement of the needle cover **408** relative to the body **410**. Proximal movement of the needle cover **408** relative to the body **410** may also be prevented by engagement between a proximal-facing side of the cooperating element **432** and a distal-facing side of the protrusion **428** (at the same time as engagement between a proximal-facing side of the protrusion **428** and a distal-facing side of the aperture **430**).

[0147] Where the cooperating element **432** comprises an aperture or recess formed in the needle cover **408**, the protrusion **428** may be dimensioned to have a slightly smaller cross-section than the aperture or recess, for similar reasons as previously described in relation to cooperating element **332** and protrusion **328**.

[0148] The needle cover **408** is prevented from moving distally with respect to the body **410** while the actuation member **424** is in its engaged position, regardless of the biasing force exerted on the needle cover **408** by the needle cover biasing member. As a result, the biasing force exerted on the needle cover **408** by the needle cover biasing member is not transferred from the needle cover **408** to the injection site. This means that the user is no longer required to overcome the biasing force of the needle cover biasing member while the actuation member **424** is in its engaged position, making it easier for the user to hold the device **400** steady at the injection site.

[0149] After the medicament has been delivered, the user releases the actuation member **424** by removing their finger from the actuation surface **427** and thereby removing the actuation force F applied to the actuation member **424**. As shown in FIG. 4D, the actuation member **424** may be caused to automatically return from its engaged position to its initial position once the actuation force F is removed, due to the flexible portion **504** acting as biasing member exerting a biasing force K to bias the actuation member **424** towards its initial position.

[0150] In moving the actuation member **424** from its engaged position back to its initial position, the protrusion **428** moves radially away from the longitudinal axis of the device **400** and from the needle cover **408**, disengaging the cooperating element **432** of the needle cover **408**, as shown in FIG. 4D. As such, the needle cover **408** is no longer held in its retracted position by the actuation member **424** and is able to move distally with respect to the body **410**. The user may then remove the device **400** from the injection site. Since the needle cover **408** is no longer being held by the actuation member **424**, the needle cover **408** moves distally from its retracted position to its initial position under the biasing force of the needle cover biasing member once the body **410** and needle cover **408** are pulled away from the injection site. The post-use state of the device **400** may appear

similar to the pre-use state shown in FIG. 4A, where the needle cover **408** is in its initial position extending from the distal end **402** of the body **410** and covering the needle **406**, however the plunger, drive spring and piston will each have been moved distally due to medicament delivery. [0151] The provision of a biasing member to bias the actuation member **424** towards its initial position can be beneficial for similar reasons to those described in relation to FIGS. 3A & 3B and the biasing member used to bias the actuation member **324**.

[0152] It has generally been described in relation to FIGS. 4A to 4D that, after the medicament has been delivered, the user releases the actuation member **424** before removing the device **400** from the injection site **400**, however, it should be understood that in other instances the user may first remove the device **400** from the injection site and subsequently release the actuation member **424**.

[0153] FIGS. 4A to 4D show the actuation member **424** located at the proximal end **404** of the device **400**, however, it should be understood that the actuation member **424** may instead be located at a different region of the device **400** other than the proximal end **404**.

[0154] FIGS. 6A to 6D show features of a third embodiment of a medicament delivery device **600**, which is also referred to herein as an injector device. These Figures show a cross section of the device **600** before and after activation of the device **600**. Certain features of the device **600** may be omitted from FIGS. 6A to 6D for clarity.

[0155] The device **600** has a distal end **602** and a proximal end **604** arranged along a longitudinal axis of the device **600**. The device **600** has a needle **606** for injecting medicament into a user at an injection site (such as the user's skin), a needle cover **608** and a body **610** (also known as a housing). The body **610** may be substantially cylindrical and has a substantially constant diameter along the longitudinal axis. The body **610** forms part of the external surface of the device **600** and is configured to be gripped by a user during an injection process.

[0156] The device **600** houses a pre-filled syringe **612** containing a medicament and a carrier **622** which supports the pre-filled syringe **612** within the body **610**. The needle **606** is in fluid communication with the pre-filled syringe **612** and extends from the distal end of the pre-filled syringe **612**. The needle cover **608** is axially movable relative to the body **610** between an initial, extended position, shown in FIG. 6A, in which the needle cover **608** covers (surrounds) the needle **606**, and a retracted position, shown in FIG. 6B, for dispensing medicament from the device **600**. In the retracted position, the needle **606** protrudes from the distal end of the needle cover **608**.

[0157] A needle cover biasing member such as a spring may be arranged in the body **610** to exert a biasing force against the needle cover **608** which biases the needle cover **608** axially, in the distal direction. A force can be applied by the user against the biasing force of the needle cover biasing member to move the needle cover **608** proximally from the extended position shown in FIG. 6A to the retracted position shown in FIG. 6B.

[0158] Medicament is dispensed from the medicament delivery device **600** via the needle **606** while the needle cover **608** is in the retracted position. An automated dispensing mechanism is triggered to start the dispensing of medicament when the needle cover **608** has moved proximally to reach a predetermined axial position within the body **610**. The predetermined position may be located just distally of the retracted position, but in other cases may be located just proximally of the retracted position or may be the same as the retracted position.

[0159] The automated dispensing mechanism may comprise a plunger that is automatically released when the needle cover **608** reaches the predetermined axial position. Once the plunger is released, it moves distally within the pre-filled syringe **612** to dispense medicament from the pre-filled syringe **612** through the needle **606**. The plunger may be moved by a driving force provided by a plunger driving mechanism such as a drive spring, however other suitable forms of a plunger driving mechanism than a drive spring may instead be used to move the plunger, such as an electromechanical motor or a gas cartridge.

[0160] In preparation for using the device **600** to administer the medicament, the user may remove a cap from the distal end **602** of the medicament delivery device **600**. To initiate medicament

delivery, the user presses the needle cover **608** against an injection site such as the user's skin to move the needle cover **608** axially relative to the body **610** in a proximal direction and to uncover the needle **606**. The needle **606** is pushed into the injection site. The automated dispensing mechanism is released, and medicament is automatically dispensed from the device **600** via the needle **606**. The user holds the needle cover **608** in the retracted position while the medicament is dispensed.

[0161] FIG. **6A** shows the device **600** in a pre-use state, which may also be called an initial state or initial position. When the device **600** is in this state, the needle cover **608** is in an extended position with respect to the body **610** in which it covers the needle **606**.

[0162] The device **600** comprises an actuation member **624** for holding the needle cover **608** in its retracted position. In the third embodiment, the actuation member **424** takes the form of a button arranged at an outer surface of the body **610**. The actuation member **624** comprises an actuation element **626** arranged at an outer surface of the body **610** and having an actuation surface **627**. The actuation member **624** further comprises a protrusion **628** disposed at the actuation element **626** and extending through an aperture **630** in the body **610**. The actuation member **624** is movable with respect to the needle cover **608** between an initial position shown in FIG. **6A** and an engaged position shown in FIG. **6C**, as described later.

[0163] The needle cover **608** comprises a cooperating element **632**, which may take the form of an aperture, a recess, a ridge or a frictional surface. The cooperating element **632** is arranged to be engaged by the protrusion **628** of the actuation member **624** when the needle cover **608** is in its retracted position and the actuation member **624** is in its engaged position.

[0164] FIG. **6A** shows the actuation member **624** in an initial position with respect to the needle cover **608**, in which the protrusion **628** is disengaged from the cooperating element **632**, thereby allowing the needle cover **608** to axially move back and forth between its retracted position and its extended position. The device **600** comprises a biasing member **652** that is configured to bias the actuation member **624** into its initial position. As shown in FIG. **6A**, the biasing member **652** comprises a leaf spring extending from the actuation element **626** to contact the outer surface of the body **610**, however it should be understood that alternative forms of biasing member **652** may be used in different examples, for example a different type of spring, and/or that the biasing member **652** may be arranged in a different location. As shown in FIG. **6A**, the actuation member **624** also comprises a stopping protrusion **650** extending from the protrusion **628** to retain the actuation member **624** in the body **610**.

[0165] As shown in FIG. **6A**, when the needle cover **608** is in its extended position with respect to the body **610**, the cooperating element **632** is not in axial alignment with the protrusion **628**. Due to this misalignment, the protrusion **628** cannot engage the cooperating element **632** to hold the needle cover **608** relative to the body **610** while the needle cover **608** is in its extended position. As shown in FIG. **6A**, the actuation member **624** may be prevented from being moved from its initial position to its engaged position to engage the cooperating element **632** due to an abutment between the protrusion **628** and an outer surface of the needle cover **608** while the needle cover **608** is in its extended position.

[0166] FIG. **6B** shows the device **600** in an activated state. To transition the device **600** from the initial state shown in FIG. **6A** to the activated state shown in FIG. **6B**, a distal force is applied via the body **610** while the needle cover **608** is placed against the injection site, such as the user's skin, causing the needle cover **608** to move proximally into the device **600**.

[0167] When the device **600** is in the activated state as shown in FIG. **6B**, the needle cover **608** is fully displaced into the device **600** and is in its retracted position. The needle **606** protrudes from the end of the needle cover **608** to its maximum extent. The medicament dispensing mechanism of the device **600** is triggered. In this example, triggering of the dispensing mechanism comprises the drive spring being released such that the drive spring expands from a compressed state to an extended state, applying a distal force to a plunger of the pre-filled syringe **612**. The distal force

causes the plunger to move distally and in turn cause medicament to be expelled from the pre-filled syringe **612** via the needle **606**.

[0168] The actuation member **624** is movable by the user from the initial position shown in FIG. **6B** to an engaged position shown in FIG. **6C**. To overcome the biasing force of the needle cover biasing member, the user can actuate the actuation member **624** while the needle cover **608** is in its retracted position such that the actuation member **624** moves from its initial position shown in FIG. **6B** to its engaged position shown in FIG. **6C**.

[0169] When the actuation member **624** is in its initial position (for example as shown in FIG. **6B**), the protrusion **628** is disengaged from the cooperating element **632** and so the needle cover **608** can be axially moved between its retracted position and its extended position. However, when the actuation member **624** is in its engaged position (for example as shown in FIG. **6C**), the actuation member **624** engages with the needle cover **608** to hold the needle cover **608** in its retracted position. More specifically, when the actuation member **624** is in its engaged position, the protrusion **628** of the actuation member **624** engages with the cooperating element **632** of the needle cover **608** to hold the needle cover **608** in its retracted position.

[0170] During proximal translation of the needle sleeve **608** from its extended position shown in FIG. **6A** to its retracted position shown in FIG. **6B**, the cooperating element **632** of the needle sleeve **608** is brought into (axial and radial) alignment with the protrusion **628** of the actuation member **624** such that, when the needle cover **608** is in its retracted position shown in FIG. **6B**, the actuation member **624** is able to be moved from its initial position to its engaged position.

[0171] The actuation member **624** may be configured to be moved from its initial position to its engaged position by the user applying an actuation force F to an outer surface of the actuation member **624**, such as the actuation surface **627**. As an example, the user may apply the actuation force F by pushing the actuation surface **627** of the actuation member **624** with a finger or thumb inwards, towards the needle cover **608**. The user may apply the actuation force F by making direct contact between their finger and the actuation surface **627**. The actuation force F may be a separate force to any force provided by the user to retract the needle cover **608** and/or initiate medicament delivery. In other words, application of the actuation force F may require a separate, distinct movement by the user to any movement used to retract the needle cover **608** and/or initiate medicament delivery.

[0172] Applying the actuation force F to the actuation surface **627** causes the actuation element **626** and the protrusion **628** to move radially towards the needle cover **608** against the biasing force of the biasing member **652**, with the protrusion **628** translating through the aperture **630** in the body **610** to engage the cooperating element **632**. Through the engagement between the protrusion **628** and the cooperating element **632**, the needle cover **608** is held in the retracted position by the actuation member **624**, as shown in FIG. **6C**. More specifically, engagement between a distal-facing side of the cooperating element **632** and a proximal-facing side of the protrusion **628** (at the same time as engagement between a distal-facing side of the protrusion **628** and a proximal-facing side of the aperture **630**) prevents distal movement of the needle cover **608** relative to the body **610**. Proximal movement of the needle cover **608** relative to the body **610** may also be prevented by engagement between a proximal-facing side of the cooperating element **632** and a distal-facing side of the protrusion **628** (at the same time as engagement between a proximal-facing side of the protrusion **628** and a distal-facing side of the aperture **630**).

[0173] Where the cooperating element **632** comprises an aperture or recess formed in the needle cover **608**, the protrusion **628** may be dimensioned to have a slightly smaller cross-section than the aperture or recess, for similar reasons as previously described in relation to cooperating element **332** and protrusion **328**.

[0174] The needle cover **608** is prevented from moving distally with respect to the body **610** while the actuation member **624** is in its engaged position, regardless of the biasing force exerted on the needle cover **608** by the needle cover biasing member **614**. As a result, the biasing force exerted on

the needle cover **608** by the needle cover biasing member is not transferred from the needle cover **608** to the injection site. This means that the user is no longer required to overcome the biasing force of the needle cover biasing member while the actuation member **624** is in its engaged position, making it easier for the user to hold the device **600** steady at the injection site.

[0175] After the medicament has been delivered, the user releases the actuation member **624** by removing their finger from the actuation surface **627** and thereby removing the actuation force F applied to the actuation member **624**. As shown in FIG. **6D**, the actuation member **624** is caused to automatically return from its engaged position to its initial position once the actuation force F is removed, due to the biasing member **652** exerting a biasing force K to bias the actuation member **624** towards its initial position.

[0176] In moving the actuation member **624** from its engaged position back to its initial position, the protrusion **628** moves radially away from the longitudinal axis of the device **600** and from the needle cover **608**, disengaging the cooperating element **632** of the needle cover **608**, as shown in FIG. **6D**. As such, the needle cover **608** is no longer held in its retracted position by the actuation member **624** and is able to move distally with respect to the body **610**. The user may then remove the device **600** from the injection site. Since the needle cover **608** is no longer being held by the actuation member **624**, the needle cover **608** moves distally from its retracted position to its initial position under the biasing force of the needle cover biasing member once the body **610** and needle cover **608** are pulled away from the injection site. The post-use state of the device **600** may appear similar to the pre-use state shown in FIG. **6A**, where the needle cover **608** is in its initial position extending from the distal end **602** of the body **610** and covering the needle **606**, however the plunger, drive spring and piston will each have been moved distally due to medicament delivery.

[0177] The provision of a biasing member **652** to bias the actuation member **624** towards its initial position can be beneficial for similar reasons to those described in relation to FIGS. **3A** & **3B**.

[0178] It has generally been described in relation to FIGS. **6A** to **6D** that, after the medicament has been delivered, the user releases the actuation member **624** before removing the device **600** from the injection site **600**, however, it should be understood that in other instances the user may first remove the device **600** from the injection site and subsequently release the actuation member **624**.

[0179] FIGS. **6A** to **6D** show the actuation member **624** located at the proximal end **604** of the device **600**, however, it should be understood that the actuation member **624** may instead be located at a different region of the device **600** that is not at the proximal end **604**.

[0180] FIGS. **7A** to **7D** show features of a fourth embodiment of a medicament delivery device **700**, which is also referred to herein as an injector device. These Figures show a cross section of the device **700** before and after activation of the device **700**. Certain features of the device **700** may be omitted from FIGS. **7A** to **7D** for clarity.

[0181] The device **700** has a distal end **702** and a proximal end **704** arranged along a longitudinal axis of the device **700**. The furthest proximal end of the device **700** is omitted from FIGS. **7A** to **7D** for clarity. The device **700** has a needle **706** for injecting medicament into a user at an injection site (such as the user's skin), a needle cover **708** and a body **710** (also known as a housing). The body **710** may be substantially cylindrical and has a substantially constant diameter along the longitudinal axis. The body **710** forms part of the external surface of the device **700** and is configured to be gripped by a user during an injection process.

[0182] The device **700** houses a pre-filled syringe **712** containing a medicament and a carrier **722** which supports the pre-filled syringe **712** within the body **710**. The needle **706** is in fluid communication with the pre-filled syringe **712** and extends from the distal end of the pre-filled syringe **712**. The needle cover **708** is axially movable relative to the body **710** between an initial, extended position, shown in FIG. **7A**, in which the needle cover **708** covers (surrounds) the needle **706**, and a retracted position, shown in FIG. **7B**, for dispensing medicament from the device **700**. In the retracted position, the needle **706** protrudes from the distal end of the needle cover **708**.

[0183] A needle cover biasing member such as a spring may be arranged in the body **710** to exert a

biasing force against the needle cover **708** which biases the needle cover **708** axially, in the distal direction. A force can be applied by the user against the biasing force of the needle cover biasing member to move the needle cover **708** proximally from the extended position shown in FIG. 7A to the retracted position shown in FIG. 7B.

[0184] Medicament is dispensed from the medicament delivery device **700** via the needle **706** while the needle cover **708** is in the retracted position. An automated dispensing mechanism is triggered to start the dispensing of medicament when the needle cover **708** has moved proximally to reach a predetermined axial position within the body **710**. The predetermined position may be located just distally of the retracted position, but in other cases may be located just proximally of the retracted position or may be the same as the retracted position.

[0185] The automated dispensing mechanism may comprise a plunger that is automatically released when the needle cover **708** reaches the predetermined axial position. Once the plunger is released, it moves distally within the pre-filled syringe **712** to dispense medicament from the pre-filled syringe **712** through the needle **706**. The plunger may be moved by a driving force provided by a plunger driving mechanism such as a drive spring, however other suitable forms of a plunger driving mechanism than a drive spring may instead be used to move the plunger, such as an electromechanical motor or a gas cartridge.

[0186] In preparation for using the device **700** to administer the medicament, the user may remove a cap from the distal end **702** of the medicament delivery device **700**. To initiate medicament delivery, the user presses the needle cover **708** against an injection site such as the user's skin to move the needle cover **708** axially relative to the body **710** in a proximal direction and to uncover the needle **706**. The needle **706** is pushed into the injection site. The automated dispensing mechanism is released, and medicament is automatically dispensed from the device **700** via the needle **706**. The user holds the needle cover **708** in the retracted position while the medicament is dispensed.

[0187] FIG. 7A shows the device **700** in a pre-use state, which may also be called an initial state or initial position. When the device **700** is in this state, the needle cover **708** is in an extended position with respect to the body **710** in which it covers the needle **706**.

[0188] The device **700** comprises an actuation member **724** for holding the needle cover **708** in its retracted position. In the fourth embodiment, the actuation member **724** takes the form of a button integrally formed with the body **710**. The actuation member **724** comprises an actuation element **726** having an actuation surface **727**, and one or more flexible portions **750a**, **750b** resiliently coupling the actuation element **726** to the remainder of the body **710**. The actuation member **724** further comprises a protrusion **728** disposed at a rear surface of the actuation element **726** and extending radially towards the needle cover **708**. The actuation member **724** is movable with respect to the needle cover **708** between an initial position shown in FIG. 7A and an engaged position shown in FIG. 7C, as described later.

[0189] The needle cover **708** comprises a cooperating element **732**, which may take the form of an aperture, a recess, a ridge or a frictional surface. The cooperating element **732** is arranged to be engaged by the protrusion **728** of the actuation member **724** when the needle cover **708** is in its retracted position and the actuation member **724** is in its engaged position.

[0190] FIG. 7A shows the actuation member **724** in its initial position in which the protrusion **728** is disengaged from the cooperating element **732**, thereby allowing the needle cover **708** to axially move back and forth between its retracted position and its extended position. The one or more flexible portions **750a**, **750b** act as a biasing member to bias the actuation member **724** into its initial position, from its engaged position.

[0191] As shown in FIG. 7A, when the needle cover **708** is in its extended position with respect to the body **710**, the cooperating element **732** is not in alignment with the protrusion **728**. Due to this misalignment, the protrusion **728** cannot engage the cooperating element **732** to hold the needle cover **708** relative to the body **710** while the needle cover **708** is in its extended position. As shown

in FIG. 7A, the actuation member **724** may be prevented from being moved from its initial position to its engaged position to engage the cooperating element **732** due to an abutment between the protrusion **728** and an outer surface of the needle cover **708** while the needle cover **708** is in its extended position.

[0192] FIG. 7B shows the device **700** in an activated state. To transition the device **700** from the initial state shown in FIG. 7A to the activated state shown in FIG. 7B, a distal force is applied via the body **710** while the needle cover **708** is placed against the injection site, such as the user's skin, causing the needle cover **708** to move proximally into the device **700**.

[0193] When the device **700** is in the activated state as shown in FIG. 7B, the needle cover **708** is fully displaced into the device **700** and is in its retracted position. The needle **706** protrudes from the end of the needle cover **708** to its maximum extent. The medicament dispensing mechanism of the device **700** is triggered. In this example, triggering of the dispensing mechanism comprises the drive spring being released such that the drive spring expands from a compressed state to an extended state, applying a distal force to a plunger of the pre-filled syringe **712**. The distal force causes the plunger to move distally and in turn cause medicament to be expelled from the pre-filled syringe **712** via the needle **706**.

[0194] The actuation member **724** is movable by the user from the initial position shown in FIG. 7B to an engaged position shown in FIG. 7C. To overcome the biasing force of the needle cover biasing member, the user can actuate the actuation member **724** while the needle cover **708** is in its retracted position such that the actuation member **724** moves from its initial position shown in FIG. 7B to its engaged position shown in FIG. 7C.

[0195] When the actuation member **724** is in its initial position (for example as shown in FIG. 7B), the protrusion **728** is disengaged from the cooperating element **732** and so the needle cover **708** can be axially moved between its retracted position and its extended position. However, when the actuation member **724** is in its engaged position (for example as shown in FIG. 7C), the actuation member **724** engages with the needle cover **708** to hold the needle cover **708** in its retracted position. More specifically, when the actuation member **724** is in its engaged position, the protrusion **728** of the actuation member **724** engages with the cooperating element **732** of the needle cover **708** to hold the needle cover **708** in its retracted position.

[0196] During proximal translation of the needle sleeve **708** from its extended position shown in FIG. 7A to its retracted position shown in FIG. 7B, the cooperating element **732** of the needle sleeve **708** is brought into (axial and radial) alignment with the protrusion **728** of the actuation member **724** such that, when the needle cover **708** is in its retracted position shown in FIG. 7B, the actuation member **724** is able to be moved from its initial position to its engaged position.

[0197] The actuation member **724** may be configured to be moved from its initial position to its engaged position by the user applying an actuation force F to an outer surface of the actuation member **724**, such as the actuation surface **727**. As an example, the user may apply the actuation force F by pushing the actuation surface **727** of the actuation member **724** with a finger or thumb radially inwards, towards the needle cover **708**. The user may apply the actuation force F by making direct contact between their finger and the actuation surface **727**. The actuation force F may be a separate force to any force provided by the user to retract the needle cover **708** and/or initiate medicament delivery. In other words, application of the actuation force F may require a separate, distinct movement by the user to any movement used to retract the needle cover **708** and/or initiate medicament delivery.

[0198] Applying the actuation force F to the actuation surface **727** causes the actuation element **726** and the protrusion **728** to move radially towards the needle cover **408** against the biasing force of the one or more flexible portions **750a**, **750b** such that the protrusion **728** engages the cooperating element **732**. Through the engagement between the protrusion **728** and the cooperating element **732**, the needle cover **708** is held in the retracted position by the actuation member **724**, as shown in FIG. 7C. More specifically, engagement between a distal-facing side of the cooperating element

732 and a proximal-facing side of the protrusion **728** (with the protrusion **728** being axially fixed relative to the body **710** by the one or more flexible portions **750a**, **750b**) prevents distal movement of the needle cover **708** relative to the body **710**. Proximal movement of the needle cover **708** relative to the body **710** may also be prevented by engagement between a proximal-facing side of the cooperating element **732** and a distal-facing side of the protrusion **728**.

[0199] Where the cooperating element **732** comprises an aperture or recess formed in the needle cover **708**, the protrusion **728** may be dimensioned to have a slightly smaller cross-section than the aperture or recess, for similar reasons as previously described in relation to cooperating element **332** and protrusion **328**.

[0200] The needle cover **708** is prevented from moving distally with respect to the body **710** while the actuation member **724** is in its engaged position, regardless of the biasing force exerted on the needle cover **708** by the needle cover biasing member **714**. As a result, the biasing force exerted on the needle cover **708** by the needle cover biasing member is not transferred from the needle cover **708** to the injection site. This means that the user is no longer required to overcome the biasing force of the needle cover biasing member while the actuation member **724** is in its engaged position, making it easier for the user to hold the device **700** steady at the injection site.

[0201] After the medicament has been delivered, the user releases the actuation member **724** by removing their finger from the actuation surface **727** and thereby removing the actuation force **F** applied to the actuation member **724**. As shown in FIG. 7D, the actuation member **724** is caused to automatically return from its engaged position to its initial position once the actuation force **F** is removed, due to the one or more flexible portions **750a**, **750b** acting a biasing member and exerting a biasing force **K** to bias the actuation member **724** towards its initial position.

[0202] In moving the actuation member **724** from its engaged position back to its initial position, the protrusion **728** moves radially away from the longitudinal axis of the device **700** and from the needle cover **708**, disengaging the cooperating element **732** of the needle cover **708**, as shown in FIG. 7D. As such, the needle cover **708** is no longer held in its retracted position by the actuation member **724** and is able to move distally with respect to the body **710**. The user may then remove the device **700** from the injection site. Since the needle cover **708** is no longer being held by the actuation member **724**, the needle cover **708** moves distally from its retracted position to its initial position under the biasing force of the needle cover biasing member once the body **710** and needle cover **708** are pulled away from the injection site. The post-use state of the device **700** may appear similar to the pre-use state shown in FIG. 7A, where the needle cover **708** is in its initial position extending from the distal end **702** of the body **710** and covering the needle **706**, however the plunger, drive spring and piston will each have been moved distally due to medicament delivery.

[0203] The provision of one or more flexible portions **750a**, **750b** acting as a biasing member to bias the actuation member **724** towards its initial position can be beneficial for similar reasons to those described in relation to FIGS. 3A & 3B and the biasing member used to bias the actuation member **324**.

[0204] It has generally been described in relation to FIGS. 7A to 7D that, after the medicament has been delivered, the user releases the actuation member **724** before removing the device **700** from the injection site, however, it should be understood that in other instances the user may first remove the device **700** from the injection site and subsequently release the actuation member **724**.

[0205] FIGS. 7A to 7D show the actuation member **724** located at the proximal end **704** of the device **700**, however, it should be understood that the actuation member **724** may instead be located at a different region of the device **700** that is not at the proximal end **704**.

[0206] FIGS. 8A to 8D show features of a fifth embodiment of a medicament delivery device **800**, which is also referred to herein as an injector device. These Figures each show a cross section of the device **800** during various stages of activation of the device **800**. Certain features of the device **800** may have been omitted from FIGS. 8A to 8D for clarity.

[0207] The device **800** may have a similar form as a medicament delivery device described

previously, having a distal end **802** and a proximal end **804** arranged along a longitudinal axis of the device **800**. The device **800** has a needle for injecting medicament into a user at an injection site (such as the user's skin), a needle cover **808** and a body **810** (also known as a housing). The body **810** may be substantially cylindrical and has a substantially constant diameter along the longitudinal axis. The body **810** forms part of the external surface of the device **800** and is configured to be gripped by a user during an injection process.

[0208] The device **800** houses a pre-filled syringe **812** containing a medicament and a carrier **822** which supports the pre-filled syringe **812** within the body **810**. The needle is in fluid communication with the pre-filled syringe **812** and extends from the distal end of the pre-filled syringe **812**. The needle cover **808** is axially movable relative to the body **810** between an initial, extended position, shown in FIG. **8A**, in which the needle cover **808** covers (surrounds) the needle, and a retracted position, shown in FIG. **8B**, for dispensing medicament from the device **800**. In the retracted position, the needle protrudes from the distal end of the needle cover **808**.

[0209] A needle cover biasing member **896** such as a spring may be arranged in the body **810** (e.g. at a proximal end of the body **810**) to exert a biasing force against the needle cover **808** which biases the needle cover **808** axially, in the distal direction. The needle cover biasing member **896** may exert the biasing force against the needle cover **808** via a collar **870** arranged concentrically about the longitudinal axis of the device **800**, where the collar **870** is configured to move axially within the device **800** to transfer the biasing force from the needle cover biasing member **896** to the needle cover **808**. However, in other examples the collar **870** may not be present and the needle cover biasing member **896** may act directly on the needle cover **808**.

[0210] Medicament is dispensed from the medicament delivery device **800** via the needle while the needle cover **808** is in the retracted position. An automated dispensing mechanism is triggered to start the dispensing of medicament when the needle cover **808** has moved proximally to reach a predetermined axial position within the body **810**. The predetermined position may be located just distally of the retracted position, but in other cases may be located just proximally of the retracted position or may be the same as the retracted position.

[0211] The automated dispensing mechanism may comprise a plunger **894** that is automatically released when the needle cover **808** reaches the predetermined axial position. Once the plunger **816** is released, it moves distally within the pre-filled syringe **812** to dispense medicament from the pre-filled syringe **812** through the needle. The plunger **894** may be moved by a driving force provided by a plunger driving mechanism such as a drive spring **898**, however other suitable forms of a plunger driving mechanism than a drive spring **898** may instead be used to move the plunger **894**, such as an electromechanical motor or a gas cartridge.

[0212] In preparation for using the device **800** to administer the medicament, the user may remove a cap from the distal end **802** of the medicament delivery device **800**. To initiate medicament delivery, the user presses the needle cover **808** against an injection site such as the user's skin to move the needle cover **808** axially relative to the body **810** in a proximal direction and to uncover the needle. The needle is pushed into the injection site. The automated dispensing mechanism is released, and medicament is automatically dispensed from the device **800** via the needle. The user holds the needle cover **808** in the retracted position while the medicament is dispensed.

[0213] FIG. **8A** shows the device **800** in a pre-use state, which may also be called an initial state or initial position. When the device **800** is in this state, the needle cover **808** is in an extended position with respect to the body **810** in which it covers the needle.

[0214] The device **800** comprises an actuation member **824** for holding the needle cover **808** in its retracted position. In the fifth embodiment, the actuation member **824** takes the form of a button arranged to extend through an opening **830** at a proximal end face of the body **810**. The actuation member **824** comprises an actuation element **826** having a proximally-facing actuation surface **827**, and one or more elongate arms **856** extending distally from a distal-facing surface of the actuation element **826**. The one or more elongate arms **856** extend distally within the body **810**.

[0215] The needle cover **808** comprises a resilient member **809** at a proximal end thereof for engaging with a cooperating element **854** of the medicament delivery device **800**. The resilient member **809** may take the form of a flexible arm extending proximally and having a first protrusion **850** and a second protrusion **852** each disposed at a free end of the flexible arm, in opposite directions. The first protrusion **850** may extend from the flexible arm towards the carrier **822**, while the second protrusion **852** may extend away from the carrier **822** and toward the body **810**.

[0216] The actuation member **824**, when moved from an initial position to an engaged position, is configured to cause the resilient member **809** to be deflected (as indicated by pivot arrow **890a**) such that the resilient member **809** engages the cooperating element **854**, to hold the needle cover **808** in its retracted position. More particularly, the actuation member **824**, when moved from the initial position to the engaged position, is configured to cause flexible arm of the resilient member **809** to be deflected such that the first protrusion **850** engages the cooperating element **854**, to hold the needle cover **808** in its retracted position.

[0217] The cooperating element **854** may take the form of an aperture, a recess, a ridge, or a frictional surface. FIG. **8A** shows the cooperating element **854** formed at the carrier **822**, the cooperating element **854** comprising a proximal-facing edge of the carrier **822**.

[0218] FIG. **8A** shows the actuation member **824** in an initial position. The actuation member **824** may be biased into the initial position by a biasing member **816** such as a spring. While the actuation member **824** is in its initial position, the resilient member **809** is disengaged from the cooperating element **854**, thereby allowing the needle cover **808** to axially move back and forth between its retracted position and its extended position. More specifically, while the actuation member **824** is in its initial position, the first protrusion **850** of the flexible arm is disengaged from the cooperating element **854** formed at the carrier **822**, thereby allowing the needle cover **808** to axially move back and forth between its retracted position and its extended position.

[0219] As shown in FIG. **8A**, when the needle cover **808** is in its extended position with respect to the body **810**, the first protrusion **850** of the resilient member **809** is not in alignment with the cooperating element **854**. Due to this misalignment, the first protrusion **850** does not hold the needle cover **808** relative to the body **810** while the needle cover **808** is in its extended position. As shown in FIG. **8A**, the first protrusion **850** is located against an outer surface of the carrier **822** while the needle cover **808** is in its extended position.

[0220] FIG. **8B** shows the device **800** in an activated state. To transition the device **800** from the initial state shown in FIG. **8A** to the activated state shown in FIG. **8B**, a distal force is applied via the body **810** while the needle cover **808** is placed against the injection site, such as the user's skin, causing the needle cover **808** to move proximally into the device **800** against the biasing force of the needle cover biasing member **896**.

[0221] When the device **800** is in the activated state as shown in FIG. **8B**, the needle cover **808** is fully displaced into the device **800** and is in its retracted position. The needle protrudes from the end of the needle cover **808** to its maximum extent. The medicament dispensing mechanism of the device **800** is triggered. In this example, triggering of the dispensing mechanism comprises the drive spring **898** being released such that the drive spring **898** expands from a compressed state to an extended state, applying a distal force to a plunger **894** of the pre-filled syringe **812**. The distal force causes the plunger **894** to move distally and in turn cause medicament to be expelled from the pre-filled syringe **812** via the needle.

[0222] To overcome the biasing force of the needle cover biasing member **896**, the user can actuate the actuation member **824** while the needle cover **808** is in its retracted position such that the actuation member **824** moves distally from its initial position shown in FIG. **8B** to its engaged position shown in FIG. **8C**.

[0223] When the actuation member **824** is in its initial position (for example as shown in FIG. **8B**), the elongate arm **856** does not deflect the flexible arm. As such, the first protrusion **850** remains disengaged from the cooperating element **854** and so the needle cover **808** can be axially moved

between its retracted position and its extended position. However, when the actuation member **824** is moved from its initial position to its engaged position, the elongate arm **856** is configured to push the resilient member **809** to cause the flexible arm to deflect, such that the first protrusion **850** engages the cooperating element **854** to hold the needle cover **808** in its retracted position. More particularly, distal movement of the actuation member **824** from its initial position to its engaged position causes a distal end of the elongate arm **856** to engage with the second protrusion **852** of the flexible arm, which causes the flexible arm to be deflected such that the first protrusion **850** engages the cooperating element **854**, as shown in FIG. **8C**. A proximal-facing edge of the second protrusion **852** may be beveled, to allow the second protrusion **852** and therefore the flexible arm to be forced radially inwards to engage the cooperating element **854** when the proximal-facing edge of the second protrusion **852** is pushed distally by the elongate arm **856**.

[0224] During proximal translation of the needle sleeve **808** from its extended position shown in FIG. **8A** to its retracted position shown in FIG. **8B**, the first protrusion **850** is brought into (axial and radial) alignment with the cooperating element **854** of the carrier **822** such that, when the needle cover **808** is in its retracted position shown in FIG. **8C**, the flexible arm is able to be deflected by the actuation member **824** to engage the cooperating element **854**.

[0225] The actuation member **824** may be configured to be moved from its initial position to its engaged position by the user applying an actuation force F to an outer surface of the actuation member **824**, such as the actuation surface **827**, as shown in FIG. **8C**. As an example, the user may apply the actuation force F by pushing the actuation surface **827** of the actuation member **824** with a finger or thumb distally, towards the needle cover **808**. The user may apply the actuation force F by making direct contact between their finger **852** and the actuation surface **827**. The actuation force F may be a separate force to any force provided by the user to retract the needle cover **808** and/or initiate medicament delivery. In other words, application of the actuation force F may require a separate, distinct movement by the user to any movement used to retract the needle cover **808** and/or initiate medicament delivery.

[0226] Where the cooperating element **854** comprises an aperture or recess formed in the needle cover **808**, the first protrusion **850** may be dimensioned to have a slightly smaller cross-section than the aperture or recess, for similar reasons as previously described in relation to cooperating element **332** and protrusion **328**.

[0227] The needle cover **808** is unable to move distally with respect to the body **810** while the actuation member **824** is in its engaged position, regardless of the biasing force exerted on the needle cover **808** by the needle cover biasing member **896**. As a result, the biasing force exerted on the needle cover **808** by the needle cover biasing member **896** is not transferred from the needle cover **808** to the injection site. This means that the user is no longer required to overcome the biasing force of the needle cover biasing member **896** while the actuation member **824** is in its engaged position, making it easier for the user to hold the device **800** steady at the injection site.

[0228] After the medicament has been delivered, the user releases the actuation member **824** by removing their finger from the actuation surface **827** and thereby removing the actuation force F applied to the actuation member **824**. As shown in FIG. **8D**, the actuation member **824** is caused to automatically return from its engaged position to its initial position once the actuation force F is removed, due to the biasing member **816** exerting a biasing force K to bias the actuation member **824** towards its initial position.

[0229] In moving the actuation member **824** from its engaged position back to its initial position, deflection of the flexible arm by the elongate arm **856** is reversed (as indicated by pivot arrow **892a**) such that the first protrusion **850** becomes disengaged from the cooperating element **854**, as shown in FIG. **8D**. As such, the needle cover **808** is no longer held in its retracted position by the actuation member **824** and is able to move distally with respect to the body **810**. The user may then remove the device **800** from the injection site. Since the needle cover **808** is no longer being held by the actuation member **824**, the needle cover **808** moves distally from its retracted position to its

initial position under the biasing force of the needle cover biasing member, as the body **810** and needle cover **808** are pulled away from the injection site. The post-use state of the device **800** may appear similar to the pre-use state shown in FIG. **8A**, where the needle cover **808** is in its initial position extending from the distal end **802** of the body **810** and covering the needle **806**, however the plunger, drive spring and piston will each have been moved distally due to medicament delivery.

[0230] FIGS. **8A** to **8D** show the medicament delivery device **800** comprising a second resilient member arranged opposite the first resilient member **809**, about the longitudinal axis of the device **800**, and which comprises a first protrusion and a second protrusion similar to the first protrusion **850** and the second protrusion **852** of the first resilient member **809**. The second resilient member may be arranged to act in a similar manner to the first resilient member **809**, with deflection of the second resilient member by the actuation member **824** indicated by the pivot arrows **890b** and **892b** being similar to the deflection of the first resilient member **809** indicated by arrows **890a** and **892b**, but in an opposite direction. It should be understood that in various examples, the medicament delivery device **800** could comprise one resilient member **809**, two resilient members **809**, or greater than two resilient members **809**.

[0231] FIGS. **9A** to **9D** show features of a sixth embodiment of a medicament delivery device **900**, which is also referred to herein as an injector device. These Figures each show a cross section of the device **900** during various stages of activation of the device **900**. Certain features of the device **900** may have been omitted from FIGS. **9A** to **9D** for clarity.

[0232] The device **900** may have a similar form as a medicament delivery device described previously, having a distal end **902** and a proximal end **904** arranged along a longitudinal axis of the device **900**. The device **900** has a needle for injecting medicament into a user at an injection site (such as the user's skin), a needle cover **908** and a body **910** (also known as a housing). The body **910** may be substantially cylindrical and has a substantially constant diameter along the longitudinal axis. The body **910** forms part of the external surface of the device **900** and is configured to be gripped by a user during an injection process.

[0233] The device **900** houses a pre-filled syringe **912** containing a medicament and a carrier **922** which supports the pre-filled syringe **912** within the body **910**. The needle is in fluid communication with the pre-filled syringe **912** and extends from the distal end of the pre-filled syringe **912**. The needle cover **908** is axially movable relative to the body **910** between an initial, extended position, shown in FIG. **9A**, in which the needle cover **908** covers (surrounds) the needle, and a retracted position, shown in FIG. **9B**, for dispensing medicament from the device **900**. In the retracted position, the needle protrudes from the distal end of the needle cover **908**.

[0234] A needle cover biasing member **996** such as a spring may be arranged in the body **910** (e.g. at a proximal end of the body **910**) to exert a biasing force against the needle cover **908** which biases the needle cover **908** axially, in the distal direction. The needle cover biasing member **996** may exert the biasing force against the needle cover **908** via a collar **970** arranged concentrically about the longitudinal axis of the device **900**, where the collar **970** is configured to move axially within the device **900** to transfer the biasing force from the needle cover biasing member **996** to the needle cover **908**. However, in other examples the collar **970** may not be present and the needle cover biasing member **996** may act directly on the needle cover **908**.

[0235] Medicament is dispensed from the medicament delivery device **900** via the needle while the needle cover **908** is in the retracted position. An automated dispensing mechanism is triggered to start the dispensing of medicament when the needle cover **908** has moved proximally to reach a predetermined axial position within the body **910**. The predetermined position may be located just distally of the retracted position, but in other cases may be located just proximally of the retracted position or may be the same as the retracted position.

[0236] The automated dispensing mechanism may comprise a plunger **994** that is automatically released when the needle cover **908** reaches the predetermined axial position. Once the plunger **916**

is released, it moves distally within the pre-filled syringe **912** to dispense medicament from the pre-filled syringe **912** through the needle. The plunger **994** may be moved by a driving force provided by a plunger driving mechanism such as a drive spring **998**, however other suitable forms of a plunger driving mechanism than a drive spring **998** may instead be used to move the plunger **994**, such as an electromechanical motor or a gas cartridge.

[0237] In preparation for using the device **900** to administer the medicament, the user may remove a cap from the distal end **902** of the medicament delivery device **900**. To initiate medicament delivery, the user presses the needle cover **908** against an injection site such as the user's skin to move the needle cover **908** axially relative to the body **910** in a proximal direction and to uncover the needle. The needle is pushed into the injection site. The automated dispensing mechanism is released, and medicament is automatically dispensed from the device **900** via the needle. The user holds the needle cover **908** in the retracted position whilst the medicament is dispensed.

[0238] FIG. **9A** shows the device **900** in a pre-use state, which may also be called an initial state or initial position. When the device **900** is in this state, the needle cover **908** is in an extended position with respect to the body **910** in which it covers the needle.

[0239] The device **900** comprises an actuation member **924** for holding the needle cover **908** in its retracted position. In the sixth embodiment, the actuation member **924** takes the form of a button arranged to extend through an opening **930** at a proximal end face of the body **910**. The actuation member **924** comprises an actuation element **926** having a proximally-facing actuation surface **927**, and one or more elongate arms **956** extending distally from a distal-facing surface of the actuation element **926**. The one or more elongate arms **956** extend distally within the body **910**.

[0240] The needle cover **908** comprises a resilient member **909** at a proximal end thereof for engaging with a cooperating element **940** of the medicament delivery device **900**. The resilient member **909** may take the form of a flexible arm extending proximally and having a first protrusion **952** and a second protrusion **950** each disposed at a free end of the flexible arm. The first protrusion **952** and second protrusion **950** may each extend from the flexible arm radially outwards towards the body **910**.

[0241] The actuation member **924**, when moved from an initial position to an engaged position, is configured to cause the resilient member **909** to be deflected (as indicated by pivot arrow **992**) such that the resilient member **909** engages the cooperating element **940**, to hold the needle cover **908** in its retracted position. More particularly, the actuation member **924**, when moved from the initial position to the engaged position, is configured to cause flexible arm of the resilient member **909** to be deflected such that the first protrusion **952** engages the cooperating element **940**, to hold the needle cover **908** in its retracted position.

[0242] The flexible arm is movable between a first position (shown in FIG. **9C**), in which the first protrusion **952** engages the cooperating element **940** to hold the needle cover in its retracted position, and a second position (shown in FIG. **9B**), in which the protrusion is disengaged from the cooperating element **940**. The flexible arm is biased to deflect from its second position to its first position, due to the resilient nature of the flexible arm. The elongate arm **956** is configured to hold the flexible arm in its second position when the actuation member **924** is in its initial position (as shown in FIG. **9B**), and is configured to release the flexible arm to deflect to its first position when the actuation member **924** is in its engaged position (as shown in FIG. **9C**).

[0243] The cooperating element **940** may take the form of an aperture, a recess, a ridge, or a frictional surface. FIG. **9A** shows the cooperating element **940** formed at the body **910**, the cooperating element **940** comprising an aperture in the body **910**.

[0244] FIG. **9A** shows the actuation member **924** in its initial position. The actuation member **924** may be biased into the initial position by a biasing member **916** such as a spring. While the actuation member **924** is in its initial position, the resilient member **909** is disengaged from the cooperating element **940**, thereby allowing the needle cover **908** to axially move back and forth between its retracted position and its extended position. More specifically, while the actuation

member **924** is in its initial position, the first protrusion **952** of the flexible arm is disengaged from the cooperating element **940** formed at the body **910**, thereby allowing the needle cover **908** to axially move back and forth between its retracted position and its extended position.

[0245] As shown in FIG. **9A**, when the needle cover **908** is in its extended position with respect to the body **910**, the first protrusion **952** of the resilient member **909** is not in alignment with the cooperating element **940**. Due to this misalignment, the first protrusion **952** cannot engage the cooperating element **940** to hold the needle cover **908** relative to the body **910** while the needle cover **908** is in its extended position.

[0246] FIG. **9B** shows the device **900** in an activated state. To transition the device **900** from the initial state shown in FIG. **9A** to the activated state shown in FIG. **9B**, a distal force is applied via the body **910** while the needle cover **908** is placed against the injection site, such as the user's skin, causing the needle cover **908** to move proximally into the device **900** against the biasing force of the needle cover biasing member **996**.

[0247] When the device **900** is in the activated state as shown in FIG. **9B**, the needle cover **908** is fully displaced into the device **900** and is in its retracted position. The needle protrudes from the end of the needle cover **908** to its maximum extent. The medicament dispensing mechanism of the device **900** is triggered. In this example, triggering of the dispensing mechanism comprises the drive spring **998** being released such that the drive spring **998** expands from a compressed state to an extended state, applying a distal force to a plunger **994** of the pre-filled syringe **912**. The distal force causes the plunger **994** to move distally and in turn cause medicament to be expelled from the pre-filled syringe **912** via the needle.

[0248] To overcome the biasing force of the needle cover biasing member **996**, the user can actuate the actuation member **924** while the needle cover **908** is in its retracted position such that the actuation member **924** moves distally from its initial position shown in FIG. **9B** to its engaged position shown in FIG. **9C**.

[0249] During proximal translation of the needle sleeve **908** from its extended position shown in FIG. **9A** to its retracted position shown in FIG. **9B**, the first protrusion **952** is brought into (axial and radial) alignment with the cooperating element **940** such that, when the needle cover **908** is in its retracted position shown in FIG. **9C**, the flexible arm is able to be deflected by the actuation member **924** to engage the cooperating element **940**.

[0250] When the actuation member **924** is in its initial position (for example as shown in FIG. **9B**), the second protrusion **950** abuts an inner surface of the elongate arm **956**, preventing the flexible arm from deflecting radially outwards toward the body **910**. As such, the first protrusion **952** remains disengaged from the cooperating element **940** and so the needle cover **908** can be axially moved between its retracted position and its extended position. However, when the actuation member **924** is moved from its initial position to its engaged position, the elongate arm **956** is configured to move axially such that an aperture **942** in the elongate arm **956** is aligned with the second protrusion **950**. When the actuation member **924** is in its engaged position, the second protrusion **950** is configured to enter the aperture **942**, thereby allowing the flexible arm to deflect radially outwards and towards the body **910** due to the resilient nature of the flexible arm, bringing the first protrusion **952** into engagement with the cooperating element **940** to hold the needle cover **908** in its retracted position.

[0251] The actuation member **924** may be configured to be moved from its initial position to its engaged position by the user applying an actuation force **F** to an outer surface of the actuation member **924**, such as the actuation surface **927**, as shown in FIG. **9C**. As an example, the user may apply the actuation force **F** by pushing the actuation surface **927** of the actuation member **924** with a finger or thumb distally, towards the needle cover **908**. The user may apply the actuation force **F** by making direct contact between their finger **952** and the actuation surface **927**. The actuation force **F** may be a separate force to any force provided by the user to retract the needle cover **908** and/or initiate medicament delivery. In other words, application of the actuation force **F** may

require a separate, distinct movement by the user to any movement used to retract the needle cover **908** and/or initiate medicament delivery.

[0252] Where the cooperating element **940** comprises an aperture or recess, the first protrusion **952** may be dimensioned to have a slightly smaller cross-section than the aperture or recess, for similar reasons as previously described in relation to cooperating element **332** and protrusion **328**.

[0253] The needle cover **908** is unable to move distally with respect to the body **910** while the actuation member **924** is in its engaged position, regardless of the biasing force exerted on the needle cover **908** by the needle cover biasing member **996**. As a result, the biasing force exerted on the needle cover **908** by the needle cover biasing member **996** is not transferred from the needle cover **908** to the injection site. This means that the user is no longer required to overcome the biasing force of the needle cover biasing member **996** while the actuation member **924** is in its engaged position, making it easier for the user to hold the device **900** steady at the injection site.

[0254] After the medicament has been delivered, the user releases the actuation member **924** by removing their finger from the actuation surface **927** and thereby removing the actuation force **F** applied to the actuation member **924**. As shown in FIG. **9D**, the actuation member **924** is caused to automatically return from its engaged position to its initial position once the actuation force **F** is removed, due to the biasing member **916** exerting a biasing force **K** to bias the actuation member **924** towards its initial position.

[0255] In moving the actuation member **924** from its engaged position back to its initial position, deflection of the flexible arm is reversed (as indicated by pivot arrow **992a** in FIG. **9D**) such that the first protrusion **952** becomes disengaged from the cooperating element **940**. This may be achieved by a distal-facing edge of the second protrusion **950** being beveled, to allow the second protrusion **950** (and therefore the flexible arm) to be forced radially inwards by engagement of the distal-facing edge with a proximal-facing edge of the aperture **942** as the elongate arm **956** moves proximally. Once the actuation member **924** has returned to its initial position and the flexible arm has returned to its second position, the needle cover **908** is no longer held in its retracted position by the actuation member **924** and is able to move distally with respect to the body **910**.

[0256] The user may then remove the device **900** from the injection site. Since the needle cover **908** is no longer being held by the actuation member **924**, the needle cover **908** moves distally from its retracted position to its initial position under the biasing force of the needle cover biasing member, as the body **910** and needle cover **908** are pulled away from the injection site. The post-use state of the device **900** may appear similar to the pre-use state shown in FIG. **9A**, where the needle cover **908** is in its initial position extending from the distal end **902** of the body **910** and covering the needle **906**, however the plunger, drive spring and piston will each have been moved distally due to medicament delivery.

[0257] FIGS. **10A** and **10B** show features of a seventh embodiment of a medicament delivery device **1000**, which is also referred to herein as an injector device. These Figures each show a cross section of a portion of a needle cover **1008** and a body **1010** of the device **1000**.

[0258] FIG. **10A** shows a close up of an actuation member **1024** and the region of the needle cover **1008** with which it interacts. The other parts of the medicament delivery device **1000** may be the same as those shown and described in the preceding embodiments.

[0259] FIG. **10A** shows the device **1000** in an activated state in which the needle cover **1008** is in a retracted position within the body **1010** to expose the needle. The needle cover **1008** may have been moved from an extended position (in which it covers the needle) to its retracted position by any manner described herein. A needle cover biasing member may bias the needle cover **1008** from its retracted position to its extended position. The actuation member **1024** takes the form of a slider arranged at the body **1010**. The slider comprises a slider body **1050** arranged at an outer surface of the body **1010**, a resilient arm **1052** extending from the slider body **1050** through an aperture **1030** in the body **1010**, and a protrusion **1054** disposed at a free end of the resilient arm **1052** between an inner surface of the body **1010** and an outer surface of the needle cover **1008**.

[0260] FIG. **10A** shows the actuation member **1024** in an initial position in which the protrusion **1054** is disengaged from a cooperating element **1032** disposed on the needle cover **1008**. As such, the needle cover **1008** remains free to be axially moved between its retracted position and its extended position. The cooperating element **1032** may take the form of an aperture, a recess, a ridge or a frictional surface.

[0261] The slider body **1050** may be slidably coupled to the body **1010**. The actuation member **1024** is configured to be moved from its initial position to its engaged position by a user applying a sliding force **1056** to the slider body **1050** (e.g. to an actuation surface **1051** of the slider body **1050**) to slide the slider body **1050** towards the aperture **1030**. As the slider body **1050** is moved towards the aperture **1030**, the resilient arm **1052** is deflected by an edge **1058** of the aperture **1030**, causing the resilient arm **1052** to pivot towards the needle cover **1032** as indicated by the pivot arrow **1060**, and therefore causing the protrusion **1054** to engage the cooperating element **1032** disposed on the needle cover.

[0262] FIG. **10B** shows the actuation member **1024** in its engaged position, where the needle cover **1030** is held in its retracted position by the engagement between the protrusion **1054** and the cooperating element **1032**. The actuation member **1024** may be moved back to its initial position by moving the slider body **1050** in the opposite direction to previously, causing the protrusion **1054** to disengage from the cooperating element **1032** such that the needle cover **1008** is no longer held in its retracted position. In some examples, the resilient arm **1052** may act as a biasing member to bias the actuation member **1024** from its engaged position towards its initial position by applying a biasing force. In such examples, the user may move the actuation member **1024** from its engaged position to its initial position simply by releasing the slider body **1050** (i.e. the user no longer applying a sliding force to the slider body **1050**) to allow the actuation member **1024** to automatically move from its engaged position to its initial position due to the biasing force.

[0263] FIGS. **11A** and **11B** show features of a eighth embodiment of a medicament delivery device **1100**, which is also referred to herein as an injector device. These Figures each show a cross section of a portion of a needle cover **1108** and a body **1110** of the device **1100**.

[0264] FIG. **11A** shows a close up of an actuation member **1124** and the region of the needle cover **1108** with which it interacts. The other parts of the medicament delivery device **1100** may be the same as those shown and described in the preceding embodiments.

[0265] FIG. **11A** shows the device **1100** in an activated state in which the needle cover **1108** is in a retracted position within the body **1110** to expose the needle. The needle cover **1108** may have been moved from an extended position (in which it covers the needle) to its retracted position by any manner described herein. A needle cover biasing member may bias the needle cover **1108** from its retracted position to its extended position. The actuation member **1124** takes the form of a pivotable arm **1150** arranged at the body **1110**. The pivotable arm **1150** is arranged to extend through an aperture **1130** in the body **1110**. The pivotable arm **1150** comprising a first arm portion **1152** arranged outside the body **1110**, a second arm portion **1154** arranged inside the body **1110** and having a protrusion **1156** disposed at a free end of the second arm portion **1154**, and a pivot **1188** arranged between the first arm portion **1152** and the second arm portion **1154**.

[0266] FIG. **11A** shows the actuation member **1124** in an initial position in which the protrusion **1156** is disengaged from a cooperating element **1132** disposed on the needle cover **1108**. As such, the needle cover **1108** remains free to be axially moved between its retracted position and its extended position. The cooperating element **1132** may take the form of an aperture, a recess, a ridge or a frictional surface.

[0267] The actuation member **1124** is configured to be moved from its initial position shown in FIG. **11A** to an engaged position shown in FIG. **11B** by a user applying an actuation force **1160** to the first arm portion **1152** (e.g. to an actuation surface **1153** of the first arm portion **1152**) to cause the first arm portion **1152** and the second arm portion **1154** to rotate about the pivot **1188**, as indicated by pivot arrow **1162**. The first arm portion **1152** and the second arm portion **1154** are

caused to rotate such that the protrusion **1156** disposed at the free end of the second arm portion **1154** is brought into engagement with the cooperating element **1132** disposed on the needle cover **1108**, to hold the needle cover **1108** in its retracted position.

[0268] FIG. **11B** shows the actuation member **1124** in its engaged position, where the needle cover **1130** is held in its retracted position by the engagement between the protrusion **1156** and the cooperating element **1132**. The actuation member **1124** may be moved back to its initial position by a user moving first arm portion **1152** in the opposite direction to previously, causing the protrusion **1156** to disengage from the cooperating element **1132** such that the needle cover **1108** is no longer held in its retracted position. In some examples, a biasing member **1158** such as a leaf spring may be arranged to bias the actuation member **1124** from its engaged position towards its initial position by applying a biasing force. In such examples, the user may move the actuation member **1124** from its engaged position to its initial position simply by releasing the first arm portion **1152** (i.e. the user no longer applying an actuation force **1160** to the first arm portion **1152**) to allow the actuation member **1124** to automatically move from its engaged position to its initial position due to the biasing force.

[0269] FIGS. **12A** and **12B** show features of a ninth embodiment of a medicament delivery device **1200**, which is also referred to herein as an injector device. These Figures each show a cross section of a portion of a needle cover **1208** and a body **1210** of the device **1200**, as viewed along the longitudinal axis of the device **1200**.

[0270] FIG. **12A** shows a close up of an actuation member **1224** and the region of the needle cover **1208** with which it interacts. The other parts of the medicament delivery device **1200** may be the same as those shown and described in the preceding embodiments.

[0271] FIG. **12A** shows the device **1200** in an activated state in which the needle cover **1208** is in a retracted position within the body **1210** to expose the needle. The needle cover **1208** may have been moved from an extended position (in which it covers the needle) to its retracted position by any manner described herein. A needle cover biasing member may bias the needle cover **1208** from its retracted position to its extended position. The actuation member **1224** takes the form of a rotatable collar **1250** arranged at the body **1210**. The rotatable collar **1250** is arranged to surround an outer surface of the body **1210** such that the rotatable collar **1250** is concentric with the body **1210** about the longitudinal axis of the device **1200**. The rotatable collar **1250** comprises a protrusion **1252** disposed on an inner surface of the rotatable collar **1250**, the protrusion **1252** extending through an aperture in the body **1210**.

[0272] FIG. **12A** shows the actuation member **1224** in an initial position in which the protrusion **1252** is disengaged from a cooperating element disposed on the needle cover **1208**. As such, the needle cover **1208** remains free to be axially moved between its retracted position and its extended position. The cooperating element may take the form of an aperture, a recess, a ridge or a frictional surface.

[0273] The actuation member **1224** is configured to be moved from its initial position shown in FIG. **12A** to an engaged position shown in FIG. **12B** by a user rotating the rotatable collar **1250** about the body **1210** such that the protrusion **1252** is brought into engagement with the cooperating element disposed on the needle cover **1208**, to hold the needle cover **1208** in its retracted position. The user may rotate the rotatable collar **125** by applying a rotation force **1270** to the rotatable collar **1250** (e.g. to an actuation surface **1251** of the rotatable collar **1250**) to cause the rotatable collar **1250** to rotate about the longitudinal axis of the device **1200** relative to the body **1210** and needle cover **1208**.

[0274] FIG. **12B** shows the actuation member **1224** in its engaged position, where the needle cover **1230** is held in its retracted position by the engagement between the protrusion **1252** and the cooperating element. The actuation member **1224** may be moved back to its initial position by a user rotating the rotatable collar **1250** in the opposite direction to previously, causing the protrusion **1252** to disengage from the cooperating element such that the needle cover **1208** is no longer held

in its retracted position. In some examples, a biasing member such as a spring may be arranged to bias the actuation member **1124** from its engaged position towards its initial position by applying a biasing force. In such examples, the user may move the actuation member **1224** from its engaged position to its initial position simply by releasing the rotatable collar **1250** (i.e. the user no longer applying a rotation force **1270** to the rotatable collar **1250**) to allow the actuation member **1224** to automatically move from its engaged position to its initial position due to the biasing force.

[0275] FIGS. **13A** and **13B** show features of a tenth embodiment of a medicament delivery device **1300**, which is also referred to herein as an injector device. These Figures each show a cross section of a portion of a needle cover **1308** and a body **1310** of the device **1300**.

[0276] FIG. **13A** shows a close up of an actuation member **1324** and the region of the needle cover **1308** with which it interacts. The other parts of the medicament delivery device **1300** may be the same as those shown and described in the preceding embodiments.

[0277] FIG. **13A** shows the device **1300** in an activated state in which the needle cover **1308** is in a retracted position within the body **1310** to expose the needle. The needle cover **1308** may have been moved from an extended position (in which it covers the needle) to its retracted position by any manner described herein. A needle cover biasing member may bias the needle cover **1308** from its retracted position to its extended position. The actuation member **1324** takes the form of a resilient portion **1312** of the body **1310** and a protrusion **1314** formed on an inner surface of the resilient portion **1312** of the body **1310**, the protrusion **1314** extending into the device **1300**, towards the needle cover **1308**.

[0278] FIG. **13A** shows the actuation member **1324** in an initial position in which the protrusion **1314** is disengaged from a cooperating element **1332** disposed on the needle cover **1308**. As such, the needle cover **1308** remains free to be axially moved between its retracted position and its extended position. The cooperating element **1332** may take the form of an aperture, a recess, a ridge or a frictional surface.

[0279] The actuation member **1324** is configured to be moved from its initial position shown in FIG. **13A** to an engaged position shown in FIG. **13B** by a user applying an actuation force **1370** to an outer surface (e.g. actuation surface **1313**) of the resilient portion **1312** of the body **1310** such that the resilient portion **1312** of the body **1310** is deflected inwards, to cause the protrusion **1314** to engage the cooperating element **1332** disposed on the needle cover **1308** and therefore hold the needle cover **1308** in its retracted position.

[0280] Since the resilient portion **1312** of the body **1310** acts as biasing member to bias the actuation member **1324** from its engaged position towards its initial position by applying a biasing force, the user may move the actuation member **1324** from its engaged position to its initial position simply by releasing the resilient portion **1312** (i.e. the user no longer applying an actuating force to the resilient portion **1312**), to allow the actuation member **1324** to automatically move from its engaged position to its initial position due to the biasing force.

[0281] Referring to FIG. **14**, a force profile graph **1400** is shown illustrating the force profile of a medicament delivery device, such as any of the medicament delivery devices **300**, **400**, **600**, **700**, **800**, **900**, **1000**, **1100**, **1200** or **1300** described herein. The horizontal axis is the displacement of the needle cover of the device in millimeters (mm) and the vertical axis is the user applied force in Newtons (N).

[0282] The first trace **1402** shows the force profile of the activation force of a medicament delivery device, such as any of the medicament delivery devices **300**, **400**, **600**, **700**, **800**, **900**, **1000**, **1100**, **1200** or **1300**, when the user is pushing the device onto an injection site. The second trace **1406** shows the force profile of the medicament delivery device when the user is removing the medicament delivery device from the injection site after completion of medicament delivery, where the user has not utilized the actuation member of the medicament delivery device during medicament delivery. In other words, the user has not moved the actuation member of the medicament delivery device from its initial position to its engaged position at any point during the

injection procedure. As such, the needle cover biasing member continues to apply a non-zero biasing force to the needle while the needle cover is at its maximum displacement within the body, as indicated by the second trace **1406**. This biasing force is matched by a corresponding vertical user force if the user is to hold the medicament delivery device steady at an injection site.

[0283] In order to overcome the biasing force of the needle cover biasing member, the user may instead utilize the actuation member of the medicament delivery device during medicament delivery. In other words, the user may move the actuation member of the medicament delivery device from its initial position to its engaged position while the needle cover is at its maximum displacement, before moving the actuation member back to its initial position once medicament delivery is complete.

[0284] The third trace **1404** shows a modification to the force profile of the second trace **1406** which occurs when the user has instead utilized the actuation member during medicament delivery. The user has moved the actuation member of the medicament delivery device from its initial position to its engaged position while the needle cover is at its maximum displacement such that the needle cover biasing member no longer exerts a biasing force on the needle cover. This is shown in FIG. **14** by the third trace **1404** indicating a zero vertical user force near the maximum displacement of the needle cover. The user therefore is no longer required to provide a corresponding vertical user force to overcome a biasing force of the needle cover biasing member if the user is to hold the medicament delivery device steady at an injection site. Once medicament delivery is complete, the user moves the actuation member back to its initial position to release the needle cover, after which the force profile of the medicament delivery device will once again follow the second trace **1406** as the medicament delivery device is removed from the injection site.

[0285] While embodiments have been generally disclosed herein in which an actuation member engages with a needle cover to hold the needle cover in its retracted position, it should be noted that in other embodiments the actuation member may be arranged to engage with an intermediate member that is used to transfer the biasing force from the needle cover biasing means to the needle cover, to hold that intermediate member relative to the body of the medicament delivery device.

[0286] The intermediate member may comprise a collar, for example, such as the collar **870** or collar **970** previously described in relation to FIGS. **8A** to **8D** and FIGS. **9A** to **9D**. The needle cover biasing means may be arranged to provide the biasing force to the intermediate member, which in turn provides the biasing force to the needle cover. In such examples, the actuation member may be arranged to engage with the collar when in its engaged position to hold the collar and prevent the collar from moving distally. As such, the collar is unable to transfer the biasing force of the needle cover biasing means to the needle cover while the actuation member is in its engaged position.

[0287] The terms “drug” or “medicament” are used synonymously herein and describe a pharmaceutical formulation containing one or more active pharmaceutical ingredients or pharmaceutically acceptable salts or solvates thereof, and optionally a pharmaceutically acceptable carrier. An active pharmaceutical ingredient (“API”), in the broadest terms, is a chemical structure that has a biological effect on humans or animals. In pharmacology, a drug or medicament is used in the treatment, cure, prevention, or diagnosis of disease or used to otherwise enhance physical or mental well-being. A drug or medicament may be used for a limited duration, or on a regular basis for chronic disorders.

[0288] As described below, a drug or medicament can include at least one API, or combinations thereof, in various types of formulations, for the treatment of one or more diseases. Examples of API may include small molecules having a molecular weight of **500** Da or less; polypeptides, peptides and proteins (e.g., hormones, growth factors, antibodies, antibody fragments, and enzymes); carbohydrates and polysaccharides; and nucleic acids, double or single stranded DNA (including naked and cDNA), RNA, antisense nucleic acids such as antisense DNA and RNA, small interfering RNA (siRNA), ribozymes, genes, and oligonucleotides. Nucleic acids may be

incorporated into molecular delivery systems such as vectors, plasmids, or liposomes. Mixtures of one or more drugs are also contemplated.

[0289] The drug or medicament may be contained in a primary package or “drug container” adapted for use with a drug delivery device. The drug container may be, e.g., a cartridge, syringe, reservoir, or other solid or flexible vessel configured to provide a suitable chamber for storage (e.g., short-or long-term storage) of one or more drugs. For example, in some instances, the chamber may be designed to store a drug for at least one day (e.g., 1 to at least 30 days). In some instances, the chamber may be designed to store a drug for about 1 month to about 2 years. Storage may occur at room temperature (e.g., about 20° C.), or refrigerated temperatures (e.g., from about -4° C. to about 4° C.). In some instances, the drug container may be or may include a dual-chamber cartridge configured to store two or more components of the pharmaceutical formulation to-be-administered (e.g., an API and a diluent, or two different drugs) separately, one in each chamber. In such instances, the two chambers of the dual-chamber cartridge may be configured to allow mixing between the two or more components prior to and/or during dispensing into the human or animal body. For example, the two chambers may be configured such that they are in fluid communication with each other (e.g., by way of a conduit between the two chambers) and allow mixing of the two components when desired by a user prior to dispensing. Alternatively or in addition, the two chambers may be configured to allow mixing as the components are being dispensed into the human or animal body.

[0290] The drugs or medicaments contained in the drug delivery devices as described herein can be used for the treatment and/or prophylaxis of many different types of medical disorders. Examples of disorders include, e.g., diabetes mellitus or complications associated with diabetes mellitus such as diabetic retinopathy, thromboembolism disorders such as deep vein or pulmonary thromboembolism. Further examples of disorders are acute coronary syndrome (ACS), angina, myocardial infarction, cancer, macular degeneration, inflammation, hay fever, atherosclerosis and/or rheumatoid arthritis. Examples of APIs and drugs are those as described in handbooks such as Rote Liste 2014, for example, without limitation, main groups 12 (anti-diabetic drugs) or 86 (oncology drugs), and Merck Index, 15th edition.

[0291] Examples of APIs for the treatment and/or prophylaxis of type 1 or type 2 diabetes mellitus or complications associated with type 1 or type 2 diabetes mellitus include an insulin, e.g., human insulin, or a human insulin analogue or derivative, a glucagon-like peptide (GLP-1), GLP-1 analogues or GLP-1 receptor agonists, or an analogue or derivative thereof, a dipeptidyl peptidase-4 (DPP4) inhibitor, or a pharmaceutically acceptable salt or solvate thereof, or any mixture thereof. As used herein, the terms “analogue” and “derivative” refers to a polypeptide which has a molecular structure which formally can be derived from the structure of a naturally occurring peptide, for example that of human insulin, by deleting and/or exchanging at least one amino acid residue occurring in the naturally occurring peptide and/or by adding at least one amino acid residue. The added and/or exchanged amino acid residue can either be codable amino acid residues or other naturally occurring residues or purely synthetic amino acid residues. Insulin analogues are also referred to as “insulin receptor ligands”. In particular, the term “derivative” refers to a polypeptide which has a molecular structure which formally can be derived from the structure of a naturally occurring peptide, for example that of human insulin, in which one or more organic substituent (e.g., a fatty acid) is bound to one or more of the amino acids. Optionally, one or more amino acids occurring in the naturally occurring peptide may have been deleted and/or replaced by other amino acids, including non-codeable amino acids, or amino acids, including non-codeable, have been added to the naturally occurring peptide.

[0292] Examples of insulin analogues are Gly(A21), Arg(B31), Arg(B32) human insulin (insulin glargine); Lys(B3), Glu(B29) human insulin (insulin glulisine); Lys(B28), Pro(B29) human insulin (insulin lispro); Asp(B28) human insulin (insulin aspart); human insulin, wherein proline in position B28 is replaced by Asp, Lys, Leu, Val or Ala and wherein in position B29 Lys may be

replaced by Pro; Ala(B26) human insulin; Des(B28-B30) human insulin; Des(B27) human insulin and Des(B30) human insulin.

[0293] Examples of insulin derivatives are, for example, B29-N-myristoyl-des(B30) human insulin, Lys(B29) (N-tetradecanoyl)-des(B30) human insulin (insulin detemir, Levemir®); B29-N-palmitoyl-des(B30) human insulin; B29-N-myristoyl human insulin; B29-N-palmitoyl human insulin; B28-N-myristoyl LysB28ProB29 human insulin; B28-N-palmitoyl-LysB28ProB29 human insulin; B30-N-myristoyl-ThrB29LysB30 human insulin; B30-N-palmitoyl-ThrB29LysB30 human insulin; B29-N-(N-palmitoyl-gamma-glutamyl)-des(B30) human insulin, B29-N-omega-carboxypentadecanoyl-gamma-L-glutamyl-des(B30) human insulin (insulin degludec, Tresiba®); B29-N-(N-lithocholyl-gamma-glutamyl)-des(B30) human insulin; B29-N-(ω-carboxyheptadecanoyl)-des(B30) human insulin and B29-N-(ω-carboxyheptadecanoyl) human insulin.

[0294] Examples of GLP-1, GLP-1 analogues and GLP-1 receptor agonists are, for example, Lixisenatide (Lyxumia®), Exenatide (Exendin-4, Byetta®, Bydureon®, a 39 amino acid peptide which is produced by the salivary glands of the Gila monster), Liraglutide (Victoza®), Semaglutide, Taspoglutide, Albiglutide (Syncria®), Dulaglutide (Trulicity®), rExendin-4, CJC-1134-PC, PB-1023, TTP-054, Langlenatide/HM-11260C (Efpeglenatide), HM-15211, CM-3, GLP-1 Eligen, ORMD-0901, NN-9423, NN-9709, NN-9924, NN-9926, NN-9927, Nodexen, Viador-GLP-1, CVX-096, ZYOG-1, ZYD-1, GSK-2374697, DA-3091 March-701, MAR709, ZP-2929, ZP-3022, ZP-DI-70, TT-401 (Pegapamodtide), BHM-034, MOD-6030, CAM-2036, DA-15864, ARI-2651, ARI-2255, Tirzepatide (LY3298176), Bamadutide (SAR425899), Exenatide-XTEN and Glucagon-Xten.

[0295] An example of an oligonucleotide is, for example: mipomersen sodium (Kynamro®), a cholesterol-reducing antisense therapeutic for the treatment of familial hypercholesterolemia or RG012 for the treatment of Alport syndrom.

[0296] Examples of DPP4 inhibitors are Linagliptin, Vildagliptin, Sitagliptin, Denagliptin, Saxagliptin, Berberine.

[0297] Examples of hormones include hypophysis hormones or hypothalamus hormones or regulatory active peptides and their antagonists, such as Gonadotropine (Follitropin, Lutropin, Choriogonadotropin, Menotropin), Somatropine (Somatropin), Desmopressin, Terlipressin, Gonadorelin, Triptorelin, Leuprorelin, Buserelin, Nafarelin, and Goserelin.

[0298] Examples of polysaccharides include a glucosaminoglycane, a hyaluronic acid, a heparin, a low molecular weight heparin or an ultra-low molecular weight heparin or a derivative thereof, or a sulphated polysaccharide, e.g. a poly-sulphated form of the above-mentioned polysaccharides, and/or a pharmaceutically acceptable salt thereof. An example of a pharmaceutically acceptable salt of a poly-sulphated low molecular weight heparin is enoxaparin sodium. An example of a hyaluronic acid derivative is Hylan G-F 20 (Synvisc®), a sodium hyaluronate.

[0299] The term “antibody”, as used herein, refers to an immunoglobulin molecule or an antigen-binding portion thereof. Examples of antigen-binding portions of immunoglobulin molecules include F(ab) and F(ab')₂ fragments, which retain the ability to bind antigen. The antibody can be polyclonal, monoclonal, recombinant, chimeric, de-immunized or humanized, fully human, non-human, (e.g., murine), or single chain antibody. In some embodiments, the antibody has effector function and can fix complement. In some embodiments, the antibody has reduced or no ability to bind an Fc receptor. For example, the antibody can be an isotype or subtype, an antibody fragment or mutant, which does not support binding to an Fc receptor, e.g., it has a mutagenized or deleted Fc receptor binding region. The term antibody also includes an antigen-binding molecule based on tetravalent bispecific tandem immunoglobulins (TBTI) and/or a dual variable region antibody-like binding protein having cross-over binding region orientation (CODV).

[0300] The terms “fragment” or “antibody fragment” refer to a polypeptide derived from an antibody polypeptide molecule (e.g., an antibody heavy and/or light chain polypeptide) that does

not comprise a full-length antibody polypeptide, but that still comprises at least a portion of a full-length antibody polypeptide that is capable of binding to an antigen. Antibody fragments can comprise a cleaved portion of a full length antibody polypeptide, although the term is not limited to such cleaved fragments. Antibody fragments that are useful in the present invention include, for example, Fab fragments, F(ab')₂ fragments, scFv (single-chain Fv) fragments, linear antibodies, monospecific or multispecific antibody fragments such as bispecific, trispecific, tetraspecific and multispecific antibodies (e.g., diabodies, triabodies, tetrabodies), monovalent or multivalent antibody fragments such as bivalent, trivalent, tetravalent and multivalent antibodies, minibodies, chelating recombinant antibodies, tribodies or bibodies, intrabodies, nanobodies, small modular immunopharmaceuticals (SMIP), binding-domain immunoglobulin fusion proteins, camelized antibodies, and VHH containing antibodies. Additional examples of antigen-binding antibody fragments are known in the art.

[0301] The terms “Complementarity-determining region” or “CDR” refer to short polypeptide sequences within the variable region of both heavy and light chain polypeptides that are primarily responsible for mediating specific antigen recognition. The term “framework region” refers to amino acid sequences within the variable region of both heavy and light chain polypeptides that are not CDR sequences, and are primarily responsible for maintaining correct positioning of the CDR sequences to permit antigen binding. Although the framework regions themselves typically do not directly participate in antigen binding, as is known in the art, certain residues within the framework regions of certain antibodies can directly participate in antigen binding or can affect the ability of one or more amino acids in CDRs to interact with antigen.

[0302] Examples of antibodies are anti PCSK-9 mAb (e.g., Alirocumab), anti IL-6 mAb (e.g., Sarilumab), and anti IL-4 mAb (e.g., Dupilumab).

[0303] Pharmaceutically acceptable salts of any API described herein are also contemplated for use in a drug or medicament in a drug delivery device. Pharmaceutically acceptable salts are for example acid addition salts and basic salts.

[0304] Those of skill in the art will understand that modifications (additions and/or removals) of various components of the APIs, formulations, apparatuses, methods, systems and embodiments described herein may be made without departing from the full scope and spirit of the present invention, which encompass such modifications and any and all equivalents thereof.

[0305] An example drug delivery device may involve a needle-based injection system as described in Table 1 of section 5.2 of ISO 11608-1:2014(E). As described in ISO 11608-1:2014(E), needle-based injection systems may be broadly distinguished into multi-dose container systems and single-dose (with partial or full evacuation) container systems. The container may be a replaceable container or an integrated non-replaceable container.

[0306] As further described in ISO 11608-1:2014(E), a multi-dose container system may involve a needle-based injection device with a replaceable container. In such a system, each container holds multiple doses, the size of which may be fixed or variable (pre-set by the user). Another multi-dose container system may involve a needle-based injection device with an integrated non-replaceable container. In such a system, each container holds multiple doses, the size of which may be fixed or variable (pre-set by the user).

[0307] As further described in ISO 11608-1:2014(E), a single-dose container system may involve a needle-based injection device with a replaceable container. In one example for such a system, each container holds a single dose, whereby the entire deliverable volume is expelled (full evacuation). In a further example, each container holds a single dose, whereby a portion of the deliverable volume is expelled (partial evacuation). As also described in ISO 11608-1:2014(E), a single-dose container system may involve a needle-based injection device with an integrated non-replaceable container. In one example for such a system, each container holds a single dose, whereby the entire deliverable volume is expelled (full evacuation). In a further example, each container holds a single dose, whereby a portion of the deliverable volume is expelled (partial evacuation).

[0308] Those of skill in the art will understand that modifications (additions and/or removals) of various components of the embodiments described herein may be made without departing from the full scope and spirit of the present invention, which encompass such modifications and any and all equivalents thereof.

LIST OF REFERENCE NUMBERS

[0309] **10**—drug delivery device [0310] **11**—housing [0311] **11a**—window [0312] **12**—cap [0313] **13**—needle sleeve [0314] **14**—reservoir [0315] **15**—medicament [0316] **17**—needle [0317] **20**—distal region [0318] **21**—proximal region [0319] **22**—button [0320] **23**—bung or piston [0321] **103**—device body [0322] **104**—spring [0323] **110**—device [0324] **113**—needle cover [0325] **115**—injection site [0326] **117**—needle [0327] **120**—holding force [0328] **125**—spring force [0329] **300**—medicament delivery device [0330] **302**—distal end [0331] **304**—proximal end [0332] **306**—needle [0333] **308**—needle cover [0334] **310**—body [0335] **312**—pre-filled syringe [0336] **314**—needle cover biasing member [0337] **316**—plunger [0338] **318**—drive spring [0339] **320**—bung or piston [0340] **322**—carrier [0341] **324**—actuation member [0342] **326**—actuation element [0343] **327**—actuation surface [0344] **328**—protrusion [0345] **330**—aperture [0346] **332**—cooperating element [0347] **350**—hand [0348] **352**—finger [0349] **400**—medicament delivery device [0350] **402**—distal end [0351] **404**—proximal end [0352] **406**—needle [0353] **408**—needle cover [0354] **410**—body [0355] **412**—pre-filled syringe [0356] **422**—carrier [0357] **424**—actuation member [0358] **426**—actuation element [0359] **427**—actuation surface [0360] **428**—protrusion [0361] **430**—aperture [0362] **432**—cooperating element [0363] **504**—flexible portion [0364] **510**—recess [0365] **600**—medicament delivery device [0366] **602**—distal end [0367] **604**—proximal end [0368] **606**—needle [0369] **608**—needle cover [0370] **610**—body [0371] **612**—pre-filled syringe [0372] **622**—carrier [0373] **624**—actuation member [0374] **626**—actuation element [0375] **627**—actuation surface [0376] **628**—protrusion [0377] **630**—aperture [0378] **632**—cooperating element [0379] **650**—stopping protrusion [0380] **652**—biasing member [0381] **700**—medicament delivery device [0382] **702**—distal end [0383] **704**—proximal end [0384] **706**—needle [0385] **708**—needle cover [0386] **710**—body [0387] **712**—pre-filled syringe [0388] **722**—carrier [0389] **724**—actuation member [0390] **726**—actuation element [0391] **727**—actuation surface [0392] **728**—protrusion [0393] **730**—aperture [0394] **732**—cooperating element [0395] **750a**, **750b**—flexible portions [0396] **800**—medicament delivery device [0397] **802**—distal end [0398] **804**—proximal end [0399] **808**—needle cover [0400] **809**—resilient member [0401] **810**—body [0402] **812**—pre-filled syringe [0403] **816**—biasing member [0404] **822**—carrier [0405] **824**—actuation member [0406] **826**—actuation element [0407] **827**—actuation surface [0408] **830**—opening [0409] **850**—first protrusion [0410] **852**—second protrusion [0411] **854**—cooperating element [0412] **856**—elongate arm [0413] **870**—collar [0414] **890a**—pivot arrow [0415] **890b**—pivot arrow [0416] **892a**—pivot arrow [0417] **892b**—pivot arrow [0418] **894**—plunger [0419] **896**—needle cover biasing member [0420] **898**—drive spring [0421] **900**—medicament delivery device [0422] **902**—distal end [0423] **904**—proximal end [0424] **908**—needle cover [0425] **909**—resilient member [0426] **910**—body [0427] **912**—pre-filled syringe [0428] **922**—carrier [0429] **924**—actuation member [0430] **926**—actuation element [0431] **927**—actuation surface [0432] **930**—opening [0433] **940**—cooperating element [0434] **942**—aperture [0435] **950**—second protrusion [0436] **952**—first protrusion [0437] **956**—elongate arm [0438] **970**—collar [0439] **992**—pivot arrow [0440] **994**—plunger [0441] **996**—needle cover biasing member [0442] **997**—pivot arrow [0443] **998**—drive spring [0444] **1000**—medicament delivery device [0445] **1008**—needle cover [0446] **1010**—body [0447] **1024**—actuation member [0448] **1030**—aperture [0449] **1032**—cooperating element [0450] **1050**—slider body [0451] **1051**—actuation surface [0452] **1052**—resilient arm [0453] **1054**—protrusion [0454] **1056**—sliding force [0455] **1058**—edge [0456] **1060**—pivot arrow [0457] **1100**—medicament delivery device [0458] **1108**—needle cover [0459] **1110**—body [0460] **1124**—actuation member [0461] **1130**—aperture [0462] **1132**—cooperating element [0463] **1150**—pivotable arm [0464] **1152**—first arm portion [0465] **1153**—actuation surface [0466] **1154**—

second arm portion [0467] **1156**—protrusion [0468] **1158**—biasing member [0469] **1160**—actuation force [0470] **1162**—pivot arrow [0471] **1188**—pivot [0472] **1200**—medicament delivery device [0473] **1208**—needle cover [0474] **1210**—body [0475] **1224**—actuation member [0476] **1250**—rotatable collar [0477] **1251**—actuation surface [0478] **1252**—protrusion [0479] **1270**—rotation force [0480] **1300**—medicament delivery device [0481] **1308**—needle cover [0482] **1310**—body [0483] **1312**—resilient portion [0484] **1313**—actuation surface [0485] **1314**—protrusion [0486] **1324**—actuation member [0487] **1332**—cooperating element [0488] **1370**—actuating force [0489] **1400**—force profile graph [0490] **1402**—first trace [0491] **1404**—third trace [0492] **1406**—second trace

Claims

1.-30. (canceled)

31. A medicament delivery device comprising: a needle for injecting medicament, the needle disposed at a distal end of the medicament delivery device; a body for containing a syringe; a needle cover axially movable relative to the body between an extended position, in which a distal end of the needle cover is distal to a distal end of the needle, and a retracted position for dispensing a medicament from the medicament delivery device, wherein the distal end of the needle is distal to the distal end of the needle cover when the needle cover is in the retracted position; and an actuation member configured to be movable by a user from an initial position to an engaged position, wherein, when the actuation member is in the initial position, the needle cover is axially movable between the retracted position and the extended position, and when the actuation member is in the engaged position, the actuation member engages with the needle cover to hold the needle cover in the retracted position.

32. The medicament delivery device of claim 31, further comprising a biasing member configured to bias the actuation member from the engaged position to the initial position.

33. The medicament delivery device of claim 31, wherein the actuation member is configured to be moved from the initial position to the engaged position by the user applying a force to an outer surface of the actuation member.

34. The medicament delivery device of claim 31, wherein the actuation member comprises a button arranged at an outer surface of the body.

35. The medicament delivery device of claim 31, wherein: the actuation member comprises a protrusion; the needle cover comprises a cooperating element; the protrusion is engaged with the cooperating element when the actuation member is in the engaged position to hold the needle cover in the retracted position; and the protrusion is disengaged from the cooperating element when the actuation member is in the initial position such that the needle cover is axially movable between the retracted position and the extended position.

36. The medicament delivery device of claim 35, wherein the protrusion is configured to engage a distal-facing side of the cooperating element when the actuation member is in the engaged position to hold the needle cover in the retracted position.

37. The medicament delivery device of claim 31, wherein the needle cover comprises a resilient member for engaging with a cooperating element of the medicament delivery device, wherein when the actuation member is moved from the initial position to the engaged position, the actuation member is configured to cause the resilient member to be deflected such that the resilient member engages the cooperating element to hold the needle cover in the retracted position.

38. The medicament delivery device of claim 37, wherein: the resilient member comprises a flexible arm and a protrusion disposed on a free end of the flexible arm; and the actuation member comprises an elongate arm configured to push the flexible arm when the actuation member is moved from the initial position to the engaged position to cause the flexible arm to deflect such that the protrusion engages the cooperating element to hold the needle cover in the retracted position.

39. The medicament delivery device of claim 37, wherein: the resilient member comprises a flexible arm and a protrusion disposed on a free end of the flexible arm; the actuation member comprises an elongate arm; the body comprises the cooperating element; the flexible arm is movable between a first position, in which the protrusion engages the cooperating element to hold the needle cover in the retracted position, and a second position, in which the protrusion is disengaged from the cooperating element; the flexible arm is biased to deflect from the second position to the first position; the elongate arm is configured to hold the flexible arm in the second position when the actuation member is in the initial position; and the elongate arm is configured to release the flexible arm to deflect to the first position when the actuation member is in the engaged position.

40. The medicament delivery device of claim 31, wherein the actuation member comprises a slider comprising: a slider body arranged at an outer surface of the body; a resilient arm extending from the slider body through an aperture in the body; and a protrusion disposed at a free end of the resilient arm between an inner surface of the body and an outer surface of the needle cover, wherein the actuation member is configured to be moved from the initial position to the engaged position by the user sliding the slider body towards the aperture in the body such that the resilient arm is deflected by an edge of the aperture to cause the protrusion to engage a cooperating element disposed on the needle cover to hold the needle cover in its retracted position.

41. The medicament delivery device of claim 31, wherein the actuation member comprises a pivotable arm arranged to extend through an aperture in the body, the pivotable arm comprising: a first arm portion arranged external to the body; a second arm portion arranged inside the body and having a protrusion disposed at a free end of the second arm portion; and a pivot arranged between the first arm portion and the second arm portion, wherein the actuation member is configured to be moved from the initial position to the engaged position by the user applying a force to the first arm portion to cause the first arm portion and the second arm portion to rotate about the pivot such that the protrusion disposed at the free end of the second arm portion is brought into engagement with a cooperating element disposed on the needle cover to hold the needle cover in the retracted position.

42. The medicament delivery device of claim 31, wherein the actuation member comprises a rotatable collar arranged to surround an outer surface of the body, the rotatable collar comprising a protrusion disposed on an inner surface of the rotatable collar, the protrusion extending through an aperture in the body, wherein the actuation member is configured to be moved from the initial position to the engaged position by the user rotating the rotatable collar about the body such that the protrusion is brought into engagement with a cooperating element disposed on the needle cover to hold the needle cover in the retracted position.

43. The medicament delivery device of claim 31, wherein the actuation member comprises a resilient portion of the body and a protrusion formed on an inner surface of the resilient portion of the body, wherein the actuation member is configured to be moved from the initial position to the engaged position by the user applying a force to an outer surface of the resilient portion of the body such that the resilient portion of the body is deflected to cause the protrusion to engage a cooperating element disposed on the needle cover to hold the needle cover in the retracted position.

44. The medicament delivery device of claim 31, further comprising a needle cover biasing member configured to exert a force which biases the needle cover axially towards the distal end of the medicament delivery device.

45. The medicament delivery device of claim 31, further comprising the syringe containing the medicament.

46. A medicament delivery device comprising: a body for containing a syringe; a needle cover axially movable relative to the body between an extended position, in which a distal end of the needle cover is distal to a distal end of a needle coupled to the syringe, and a retracted position, in which the distal end of the needle is distal to the distal end of the needle cover; and a button configured to be actuated by a user to hold the needle cover in the retracted position.

47. The medicament delivery device of claim 46, wherein the button is configured to be actuated such that the button moves from (i) an initial position, in which the needle cover is axially movable between the retracted position and the extended position, to (ii) an engaged position, in which the button holds the needle cover in the retracted position.
48. The medicament delivery device of claim 47, further comprising a biasing member configured to bias the button from the engaged position to the initial position.
49. The medicament delivery device of claim 46, wherein the button is configured to be actuated by the user applying a force to an outer surface of the button.
50. The medicament delivery device of claim 46, wherein the button is arranged at an outer circumferential surface of the body, and the medicament delivery device is configured such that actuation of the button causes the button to move radially into the body to hold the needle cover.
51. The medicament delivery device of claim 46, wherein the button is arranged to extend through an opening at a proximal end face of the body, and the medicament delivery device is configured such that actuation of the button causes the button to move axially into the body to hold the needle cover.
52. The medicament delivery device of claim 46, wherein the button is integrally formed with the body.
53. The medicament delivery device of claim 46, wherein the needle cover is arranged to (i) prevent the button from being actuated when the needle cover is in the extended position, and (ii) allow the button to be actuated when the needle cover is in the extended position
54. The medicament delivery device of claim 46, wherein: the button comprises a protrusion; and the needle cover comprises a cooperating element, and wherein the medicament delivery device is configured such that actuation of the button causes the protrusion to engage the cooperating element to hold the needle cover in the retracted position.
55. The medicament delivery device of claim 54, wherein the cooperating element comprises an aperture, a recess, a ridge, or a frictional surface.
56. The medicament delivery device of claim 46, wherein the needle cover comprises a resilient member for engaging with a cooperating element of the medicament delivery device, and the medicament delivery device is configured such that actuation of the button causes the resilient member to be deflected such that the resilient member engages the cooperating element to hold the needle cover in the retracted position.
57. The medicament delivery device of claim 56, wherein: the resilient member comprises a flexible arm and a protrusion disposed on a free end of the flexible arm; the button comprises an elongate arm; and the medicament delivery device is configured such that actuation of the button causes the elongate arm to deflect the flexible arm such that the protrusion engages the cooperating element to hold the needle cover in the retracted position.
58. The medicament delivery device of claim 56, wherein: the resilient member comprises a flexible arm and a protrusion disposed on a free end of the flexible arm; the button comprises an elongate arm; the body comprises the cooperating element; the flexible arm is movable between a first position, in which the protrusion engages the cooperating element to hold the needle cover in the retracted position, and a second position, in which the protrusion is disengaged from the cooperating element; the flexible arm is biased to deflect from the second position to the first position; the elongate arm is configured to hold the flexible arm in the second position prior to actuation of the button; and the medicament delivery device is configured such that actuation of the button causes the elongate arm to release the flexible arm to deflect to the first position.
59. The medicament delivery device of claim 46, further comprising the syringe containing a medicament.
60. A medicament delivery device comprising: a body configured to hold a syringe having a needle and containing a medicament; a needle cover axially movable relative to the body between an extended position in which a distal end of the needle cover is distal to a distal end of the needle,

and a retracted position in which the distal end of the needle is distal to the distal end of the needle cover, and a member configured to releasably hold the needle cover in the retracted position against a force biasing the needle cover in the extended position.
