

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250276567

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

Wang; Lizhao et al.

HARD FOLDING CAR COVER

Abstract

The disclosure provides a hard folding car cover including a fixed cover plate and a reversible cover plate, wherein the fixed cover plate is provided with one and the reversible cover plate is provided with at least one, the reversible cover plate is connected to another reversible cover plate by a first rotational shaft system, the first rotational shaft system includes a first intermediate bar, the fixed cover plate is connected to the reversible cover plate by a second rotational shaft system, the second rotational shaft system includes a second intermediate bar wherein the second intermediate bar is of the same width as the first intermediate bar. The present disclosure sets the first intermediate bar and the second intermediate bar to equal width, making the first intermediate bar and the second intermediate bar require only one set of mold for processing, saving production costs and improving production and installation productivity.

Inventors: Wang; Lizhao (Katy, TX), Lin; Yi (Katy, TX), Lin; Lei (Katy, TX)

Applicant: CHIU; TONY WAYGONG (Katy, TX)

Family ID: 92461928

Appl. No.: 19/211333

Filed: May 19, 2025

Related U.S. Application Data

parent US continuation 18173240 20230223 PENDING child US 19211333

Publication Classification

Int. Cl.: B60J7/14 (20060101); B60J7/19 (20060101)

U.S. Cl.:

Background/Summary

CROSS REFERENCES TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 18/173,240, filed Feb. 23, 2023, entitled “HARD FOLDING CAR COVER”, the entirety of which is incorporated herein by reference for all purposes.

TECHNICAL FIELD

[0002] This invention is relevant to automobile accessories, especially a hard folding car cover.

BACKGROUND OF THE INVENTION

[0003] The cargo hopper of a pickup truck (also known as a sedan truck) is used to carry goods. Since the cargo hopper of the pickup truck is open, in order to avoid the rain from wetting the goods inside the cargo hopper in rainy and snowy weather, a rear car cover is invented and installed on the cargo hopper of the pickup truck to cover the goods inside to prevent the goods in the cargo hopper from being wet by rain.

[0004] The existing car cover has different sizes of rotating shaft system between each cover plate, which is not only time consuming to manufacture, but also troublesome to install; secondly, the locking parts of the existing car cover are mostly a whole through groove, which needs to be disassembled as a whole during maintenance, which is also troublesome.

BRIEF SUMMARY OF THE INVENTION

[0005] The purpose of the present invention is to make the rotating shaft system more convenient in both production and installation by changing the original rotating shaft structure.

[0006] In order to solve the above-mentioned problems, the technical solution adopted in the present invention is as follows:

[0007] A hard folding car cover, including a fixed cover plate and a reversible cover plate, the fixed cover plate is provided with one and the reversible cover plate is provided with at least one.

[0008] The reversible cover plate is connected to another reversible cover plate by a first rotational shaft system, the first rotational shaft system includes a first intermediate bar.

[0009] The fixed cover plate is connected to the reversible cover plate by a second rotating shaft system, the second rotating shaft system includes a second intermediate bar, the second intermediate bar is of the same width as the first intermediate bar.

[0010] When there is only one reversing cover plate, there is only a second rotating shaft system and no first rotating shaft system, which is also included here in the case of only one rotating shaft system.

[0011] When there is more than one reversing cover plate, there is both a first and a second rotating shaft system, both with the same width intermediate bar.

[0012] The reversible cover plate is connected with a limiting system, the limiting system includes a limiting component and a guide groove, the guide groove is connected to the reversible cover plate, the guide groove is set in correspondence with the limiting component, the fixed cover plate is connected with a fixing buckle groove system.

[0013] Further, the fixed cover plate is the third cover plate, the reversing cover plate includes a first cover plate and a second cover plate.

[0014] The first cover plate is connected to the second cover plate by a first rotating shaft system, the first rotating shaft system includes a first intermediate bar, the second cover plate is connected to the third cover plate by a second rotational shaft system, the second rotating shaft system includes a second intermediate bar, the second intermediate bar is of the same width as the first intermediate bar. By setting the first intermediate bar and the second intermediate bar to equal width, the first intermediate bar and the second intermediate bar require only one set of mould for

processing, saving production costs and improving production and installation efficiency. At the same time, by setting the two intermediate bars to equal width, the middle part of the car cover can hold spare parts after folding, making the overall size of the car cover smaller after packing, which not only facilitates the delivery of the car cover but also reduces transportation costs.

[0015] Further, the first rotating shaft system includes a first frame and a second frame, the first frame and the second frame are rotatably connected to both sides of the first intermediate bar, both the first frame and the second frame are used for connecting the cover plate, specifically, the first frame is connected to the first cover plate, the second frame is connected to the second cover plate; the second rotating shaft system further includes a third frame and a forth frame, the third frame and forth frame are rotatably connected to both sides of the second intermediate bar, both the third frame and the forth frame are used for connecting the cover plate, specifically, the third frame is connected to the second cover plate, the forth frame is connected to the third cover plate.

[0016] Further, the first cover plate and second cover plate are respectively connected to a limiting system, the limiting system includes a limiting component and a guide groove, the guide groove is set in correspondence with the limiting component, the third cover plate is connected to a fixing buckle groove system. By setting the limiting system, the car cover can be locked with the cargo hopper, the car cover not only refer to the cover plate, both sides of the cover plate need to be connected with the cargo hopper so as to ensure that the car cover has good stability when the vehicle is running. By connecting the guide rail assembly on both sides of the cargo hopper, then locking the two ends of the cover plate with the guide rail to achieve the locking of the car cover, the limiting system is used to lock the car cover with the guide rail.

[0017] Further, the limiting system is a spanner groove system, the spanner groove system includes a spanner, a short spanner groove, a spanner fixing block, a spanner slider and a first T-rod, the short spanner groove is attached to the cover plate, the spanner fixing block is fixedly connected in the short spanner groove, the spanner slider is slidingly set in the short spanner groove, one end of the spanner is rotatably connected to the spanner slider by the first T-rod, the limiting component is a spanner, the guide groove is a short spanner groove. By setting the spanner groove system, the cover can be locked and opened by simply pulling the spanner, setting the short spanner groove on the cover plate greatly reduces the processing cost compared to the traditional through groove, moreover, each spanner corresponds to a short spanner groove, which is relatively independent and easy to replace.

[0018] Further, the limiting system is a lock bolt system, the lock bolt system includes a lock bolt, a handle, a first lock bolt groove, a second lock bolt groove and a wire support block, the first lock bolt groove and the second lock bolt groove are connected by a wire support block, the first lock bolt groove is slidingly connected with a lock bolt, the second lock bolt groove is slidingly connected with a lock bolt, the two lock bolts are connected to each other by a wire, the wire passes through the wire support block, the steel wire is threaded with a handle, the first lock bolt groove and the second lock bolt groove are both guide grooves, the lock bolt is a limiting component. By setting the lock bolt system, the car cover can be opened by simply pulling the handle, which drives the lock bolt contracted by the wire, by setting the first lock bolt groove and the second lock bolt groove on the cover plate, the two lock bolts are produced and installed independently of each other and are only connected by the wire support block.

[0019] Further, it includes a guide rail system, the guide rail system is connected to the cargo hopper by means of a clamp system, the guide rail system including two guide rails, the guide rail is provided with a guide rail notch, the guide rail notch is connected with a lock bolt positioning system, the lock bolt positioning system includes a lock bolt positioning system connected to the guide rail notch, the lock bolt positioning block is used for seating the lock bolt; the lock bolt positioning block is provided with a beveled contact surface, an insert section, a fixing hole and lateral sides, the insert section is inserted into guide rail, the screw passes through the fixing hole to connected lock bolt positioning block with the guide rail, the beveled contact surface is angled

downwards, the two lateral sides are used to limit the lock bolt.

[0020] Further, the clamp system includes a left clamp, a right clamp, a fixing block, a screw and a second T-rod, the left clamp and right clamp are connected by a screw, the fixing block is connected to the left clamp, the fixing block is threaded to the screw, the left clamp includes a left clamp lug groove and a left clamp surface, the left clamp lug groove is used to attach the fixing block, the left clamp surface is used to clamp the guide rail, the fixing block includes a clamping section, the clamping section is seated with the left clamping lug groove, the right clamp includes a right clamping surface, the right clamping surface cooperates with the left clamping surface to clamp the cargo hopper to the guide rail, the bottom of the left clamp is connected to the bottom of the right clamp by a second T-rod, the bottom of the second T-rod is connected with a nut, the upper part of the second T-rod is a transverse section.

[0021] Further, the third cover plate is connected to the guide rails by a front bar fixing system, the front bar fixing system includes a stumbling positioning block, a stumbling fixing block, a screw positioning block and a plum screw; the stumbling positioning block and screw positioning block are attached to the third cover plate, the stumbling positioning block is provided with a positioning threaded hole, the screw positioning block is provided with an insertion block and a fixing hole, the screw connects the screw positioning block to the third cover plate through the fixing hole, the insertion block is set between the stumbling positioning block and the stumbling fixing block, the stumbling fixing block is connected to the guide rail, the stumbling fixing block is provided with a positioning recess and a connection hole, the connection hole is provided in correspondence with the positioning threaded hole, the plum screw includes a snap-in section and a threaded head, the plum screw passes through the connection hole and the positioning threaded hole, the threaded head is threaded into the positioning threaded hole, the insertion block is seated with the snap-in section. A stumbling fixing block and a stumbling positioning block are set to connect the third cover plate and the guide rail respectively, the stumbling fixing block and the stumbling positioning block are connected by a plum screw to achieve the connection between the third cover plate and the guide rail, and finally the plum screw is clamped in place by a screw positioning block to prevent the plum screw from loosening.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0022] FIG. 1 is the structure schematic diagram 1 of new car cover of the present invention.

[0023] FIG. 2 is the structure schematic diagram 2 of new car cover of the present invention.

[0024] FIG. 3 is the partial enlarged view of part A in FIG. 2.

[0025] FIG. 4 is the structure schematic diagram of the Embodiment 6.

[0026] FIG. 5 is the partial enlarged view of part B in FIG. 4

[0027] FIG. 6 is the installation schematic diagram 1 of the lock bolt positioning system.

[0028] FIG. 7 is the installation schematic diagram 2 of the lock bolt positioning system.

[0029] FIG. 8 is the installation schematic diagram 3 of the lock bolt positioning system.

[0030] FIG. 9 is the connection schematic diagram of the clamp system.

[0031] FIG. 10 is the connection schematic diagram 1 of the clamp system.

[0032] FIG. 11 is the connection schematic diagram 2 of the clamp system.

[0033] FIG. 12 is the connection schematic diagram 1 of the front bar fixing system.

[0034] FIG. 13 is the connection schematic diagram 2 of the front bar fixing system.

[0035] In the picture: 11—Front bar fixing system; 111—stumbling positioning block; 1112—Positioning recess, 112—stumbling fixing block, 113—Screw positioning block, 1131—Insertion block, 1132—Fixing hole, 114—Plum screw, 1141—Snap-in section, 1142—Threaded head, 12—Lock bolt system, 1201—Wire support block, 1202—First lock bolt groove, 1203—Second lock

bolt groove, **13**—Lock bolt positioning system, **131**—Guide rail notch, **132**—Lock bolt, **133**—Lock bolt positioning block, **1331**—Beveled contact surface, **1332**—Lateral side, **1333**—Insert section, **1334**—Fixing hole, **14**—Clamp system, **141**—Left clamp, **1411**—Left clamping lug groove, **1412**—Left clamping surface, **142**—Fixing block, **1422**—Clamping section, **143**—Right clamp, **1431**—Right clamping surface, **144**—Screw, **145**—Second T-rod, **1451**—Transverse section, **146**—Nut, **16**—Guide rail system, **161**—Guide rail, **21**—First rotating shaft system, **211**—First frame, **212**—First intermediate bar, **213**—Second frame, **22**—Spanner groove system, **222**—Spanner, **223**—Short spanner groove, **224**—Spanner fixing block, **225**—Spanner slider, **226**—First T-rod, **23**—Second rotating shaft system, **231**—Third frame, **232**—Second intermediate bar, **233**—Forth frame, **24**—Fixing buckle groove system, **31**—First cover plate, **32**—Second cover plate, **33**—Third cover plate.

DETAILED DESCRIPTION OF THE INVENTION

[0036] The following instruction further explains the invention's concrete implementation method.

[0037] In order to enable a clearer understanding of the objects mentioned above, features and advantages of the present invention, the invention is described in detail below in connection with the accompanying stumblings and specific embodiments. It should be noted that the embodiments of the present application and the features in the embodiments can be combined without conflict.

[0038] The terms “first”, “second”, “third”, etc. are only used to differentiate the description and should not be construed as indicating or implying relative importance.

[0039] In the description of the invention, it should also be noted that, unless otherwise expressly specified and limited, the terms “arranged,” “installed,” “connected,” and “combined” should be understood in a broad sense. for example, it may be a fixing connection, it can also be a detachable connection or an integral connection. it can be a mechanical connection or an electrical connection. it can be a direct connection or an indirect connection through an intermediate media, and it can be internal connection within two assemblies. For those of ordinary skill in this field, specific meanings of the above terms in the present invention can be understood in specific situations.

[0040] The specific embodiments of the present invention will be described in detail below in connection with the accompanying stumblings. It should be understood that the specific embodiments described herein are intended only to illustrate and explain the present invention and not to limit it.

Embodiment 1

[0041] As shown in FIGS. **1**, a hard folding car cover, including a plurality of cover plates, two adjacent plates are connected to each other by a rotational shaft system, the rotational shaft system is provided with at least one.

[0042] The cover plates body includes one fixed cover plate and at least one reversible cover plate, the rotational shaft system includes a first rotating shaft system **21** and a second rotating shaft system **23**.

[0043] The reversible cover plate is connected to another reversible cover plate by a first rotating shaft system **21**, the first rotating shaft system **21** includes a first intermediate bar **212**.

[0044] The fixed cover plate is connected to the reversible cover plate by a second rotating shaft system **23**, the second rotating shaft system **23** includes a second intermediate bar **232**, the second intermediate bar **232** is of the same width as the first intermediate bar **212**.

[0045] When there is only one reversing cover plate, there is only a second rotating shaft system **23** and no first rotating shaft system **21**, which is also included here in the case of only one rotating shaft system.

[0046] When there is more than one reversing cover plate, there is both a first rotating shaft system **21** and a second rotating shaft system **23**, both with the same width intermediate bar.

[0047] The reversible cover plate is connected with a limiting system, the limiting system includes a limiting component and a guide groove, the guide groove is connected to the reversible cover

plate (here the connection can be fixed or removable), the guide groove is set in correspondence with the limiting component, the fixed cover plate is connected with a fixing buckle groove system.

Embodiment 2

[0048] On the basis of Embodiment 1, as shown in FIGS. 2, the fixed cover plate is the third cover plate **33**, the reversing cover plate includes a first cover plate **31** and a second cover plate **32**.

[0049] The first cover plate **31** is connected to the second cover plate **32** by a first rotating shaft system **21**, the first rotating shaft system includes a first intermediate bar **212**.

[0050] The second cover plate **32** is connected to the third cover plate **33** by a second rotational shaft system **23**, the second rotating shaft system **23** includes a second intermediate bar **232**, the second intermediate bar **232** is of the same width as the first intermediate bar **212**.

[0051] By setting the first intermediate bar **212** and the second intermediate bar **232** to equal width, the first intermediate bar **212** and the second intermediate bar **232** require only one set of mould for processing, saving production costs and improving production and installation efficiency. At the same time, by setting the two intermediate bars to equal width, the middle part of the car cover can hold spare parts after folding, making the overall size of the car cover smaller after packing, which not only facilitates the delivery of the car cover but also reduces transportation costs.

Embodiment 3

[0052] On the basis of Embodiment 1 or 2, the first rotating shaft system **21** further includes a first frame **211** and a second frame **213**, the first frame **211** and the second frame **213** are rotatably connected to both sides of the first intermediate bar **212**, both the first frame **211** and the second frame **213** are used for connecting the cover plate, specifically, the first frame **211** is connected to the first cover plate **31**, the second frame **213** is connected to the second cover plate **32**.

[0053] The second rotating shaft system **23** further includes a third frame **231** and a forth frame **233**, the third frame **231** and forth frame **233** are rotatably connected to both sides of the second intermediate bar **232**, both the third frame **231** and the forth frame **233** are used for connecting the cover plate, specifically, the third frame **231** is connected to the second cover plate **32**, the forth frame **233** is connected to the third cover plate **33**.

[0054] The relative rotation of the frames and intermediate bars enables the opening and closing of the cover plate.

Embodiment 4

[0055] On the basis of Embodiment 3, as shown in FIGS. 10, the first cover plate **31** and second cover plate **32** are respectively connected to a limiting system, the limiting system includes a limiting component and a guide groove, the guide groove is set in correspondence with the limiting component, the third cover plate **33** is connected to a fixing buckle groove system.

[0056] By setting the limiting system, the car cover can be locked with the cargo hopper, the car cover not only refer to the cover plate, both sides of the cover plate need to be connected with the cargo hopper so as to ensure that the car cover has good stability when the vehicle is running. By connecting the guide rail **161** assembly on both sides of the cargo hopper, then locking the two ends of the cover plate with the guide rail **161** to achieve the locking of the car cover, the limiting system is used to lock the car cover with the guide rail **161**.

Embodiment 5

[0057] On the basis of Embodiment 4, as shown in FIGS. 3, the limiting system is a spanner groove system **22**, the spanner groove system **22** includes a spanner **222**, a short spanner groove **223**, a spanner fixing block **224**, a spanner slider **225** and a first T-rod **226**, the short spanner groove **223** is attached to the cover plate, the spanner fixing block **224** is fixedly connected in the short spanner groove **223**, the spanner slider **225** is slidingly set in the short spanner groove **223**, one end of the spanner **222** is rotatably connected to the spanner slider **225** by the first T-rod **226**.

[0058] The limiting component is a spanner **222**, the guide groove is a short spanner groove **223**.

[0059] By setting the spanner groove system **22**, the cover can be locked and opened by simply pulling the spanner **222**, and setting the short spanner groove **223** on the cover plate greatly reduces

the processing cost compared to the traditional through groove, moreover, each spanner **222** corresponds to a short spanner groove **233**, which is relatively independent and easy to replace.

Embodiment 6

[0060] On the basis of Embodiment 4, as shown in FIGS. **4** and **5**, the limiting system is a lock bolt system **12**, the lock bolt system **12** includes a lock bolt **132**, a handle, a first lock bolt groove **1202**, a second lock bolt groove **1203** and a wire support block **1201**.

[0061] The first lock bolt groove **1202** and the second lock bolt groove **1203** are connected by a wire support block **1201**, the first lock bolt groove **1202** is slidingly connected with a lock bolt **132**, the second lock bolt groove **1203** is slidingly connected with a lock bolt **132**, the two lock bolts **132** are connected to each other by a wire, the wire passes through the wire support block **1201**, the steel wire is threaded with a handle.

[0062] The first lock bolt groove **1202** and the second lock bolt groove **1203** are both guide grooves, the lock bolt **132** is a limiting component.

[0063] By setting the lock bolt system **12**, the car cover can be opened by simply pulling the handle, which drives the lock bolt **132** contracted by the wire, by setting the first lock bolt groove **1202** and the second lock bolt groove **1203** on the cover plate, the two lock bolt grooves **132** are produced and installed independently of each other and are only connected by the wire support block **1201**.

Embodiment 7

[0064] On the basis of Embodiment 5 or 6, as shown in FIGS. **6** to **8**, it includes a guide rail system **16**, the guide rail system **16** is connected to the cargo hopper by means of a clamp system **14**, the guide rail system **16** including two guide rails **161**.

[0065] The guide rail **161** is provided with a guide rail notch **131**, the guide rail notch **131** is connected with a lock bolt positioning system **13**, the lock bolt positioning system **13** includes a lock bolt positioning system **133** connected to the guide rail notch **131**, the lock bolt positioning block **133** is used for seating the lock bolt **132**.

[0066] The lock bolt positioning block **133** is provided with a beveled contact surface **1331**, an insert section **1333**, a fixing hole **1334** and lateral sides **1332**, the insert section **1333** is inserted into guide rail **161**, the screw passes through the fixing hole **1334** to connected lock bolt positioning block **133** with the guide rail **161**, the beveled contact surface **1331** is angled downwards, the lateral sides **1332** are used to limit the lock bolt.

[0067] In order to make the car cover with good strength, the guide rail **161** is generally made of metal, so that it has good force strength, but the metal guide rail **161** makes the lock bolt **132** more laborious to lock, the locking of the lock bolt **132** is achieved by pressing the cover plate, as the contacting surface of the lock bolt **132** and the guide rail **161** is beveled, after the contact between the lock bolt **132** and the guide rail **161**, the lock bolt **132** is first contracted by the pressure, then passing through the guide **161**, and finally extended under the action of the spring to complete the locking. Since the guide rail **161** is made of metal, the metal material is not prone to deformation in the process of mutual extrusion with the lock bolt **132**, which makes it difficult to lock the lock bolt **132**. Therefore, remove one piece from the guide rail **161** and install a plastic lock bolt positioning block **133** instead, not only can the lateral sides **1332** of the lock bolt positioning block **133** be used to limit the lock bolt **132**, but also the plastic parts are easier to produce deformation, making it easier to lock.

Embodiment 8

[0068] On the basis of Embodiment 7, as shown in FIGS. **9** and **11**, the clamp system **14** includes a left clamp **141**, a right clamp **142**, a fixing block **142**, a screw **144** and a second T-rod **145**, the left clamp **141** and right clamp **143** are connected by a screw **144**, the fixing block **142** is connected to the left clamp **141**, the fixing block **142** is threaded to the screw **144**.

[0069] The left clamp **141** includes a left clamp lug groove **1411** and a left clamp surface **1412**, the left clamp lug groove **1411** is used to attach the fixing block **142**, the left clamp surface **1412** is

used to clamp the guide rail **161**.

[0070] The fixing block **142** includes a clamping section **1422**, the clamping section **1422** is seated with the left clamping lug groove **1411**.

[0071] The right clamp **143** includes a right clamping surface **1431**, the right clamping surface **1431** cooperates with the left clamping surface **1412** to clamp the cargo hopper to the guide rail **161**.

[0072] The bottom of the left clamp **143** is connected to the bottom of the right clamp **141** by a second T-rod **145**, the bottom of the second T-rod **145** is connected with a nut **146**, the upper part of the second T-rod **145** is a transverse section **1451**.

[0073] A clamp system **14** is used to connect the guide rails **161** to the cargo hopper, thus enabling the car cover to be connected to the cargo hopper. In order to improve the stability of the connection between the guide rail **161** and the cargo hopper, a fixing block **142** is added to the left clamp **141**. As the fixing block **142** both snaps into the left clamp **141** and threads into the screw **144**, it can effectively prevent the screw **144** from loosening and improve the stability of the connection between the guide rail **161** and the cargo hopper.

Embodiment 9

[0074] On the basis of Embodiment 8, as shown in FIGS. **12** and **13**, the third cover plate **33** is connected to the guide rails **161** by a front bar fixing system **11**, the front bar fixing system **11** includes a stumbling positioning block **111**, a stumbling fixing block **112**, a screw positioning block **113** and a plum screw **114**.

[0075] The stumbling positioning block **111** and screw positioning block **113** are attached to the third cover plate **33**, the stumbling positioning block **111** is provided with a positioning threaded hole **1111**, the screw positioning block **113** is provided with an insertion block **1131** and a fixing hole **1334**, the screw **144** connects the screw positioning block **113** to the third cover plate **33** through the fixing hole **1334**, the insertion block **1131** is set between the stumbling positioning block **111** and the stumbling fixing block **112**.

[0076] The stumbling fixing block **112** is connected to the guide rail **161**, the stumbling fixing block **112** is provided with a positioning recess **1112** and a connection hole, the connection hole is provided in correspondence with the positioning threaded hole **1111**.

[0077] The plum screw **114** includes a snap-in section **1141** and a threaded head **1142**, the plum screw **114** passes through the connection hole and the positioning threaded hole **1111**, the threaded head **1142** is threaded into the positioning threaded hole **1111**, the insertion block **1131** is seated with the snap-in section **1141**.

[0078] A stumbling fixing block **112** and a stumbling positioning block **111** are set to connected the third cover plate **33** and the guide rail **161** respectively, the stumbling fixing block **112** and the stumbling positioning block **111** are connected by a plum screw **114** to achieve the connection between the third cover plate **33** and the guide rail **161**, and finally the plum screw **114** is clamped in place by a screw positioning block **113** to prevent the plum screw **114** from loosening.

[0079] The invention is not limited to the above-mentioned optional embodiments, anyone can come up with various other forms of products under the inspiration of the invention, however, regardless of any changes in its shape or structure, all technical solutions that fall within the scope defined by the claims of the present invention shall fall within the scope of protection of the invention.

Claims

1. A hard folding car cover, wherein, including two cover plates and one shaft system, the two cover plates are connected by the shaft system.
2. A hard folding car cover including a plurality of cover plates, two adjacent plates are connected to each other by a rotational shaft system, wherein the rotational shaft system is provided with at

least two; wherein the cover plates body includes one fixed cover plate and at least one reversible cover plate, the rotational shaft system includes a first rotating shaft system (21) and a second rotating shaft system (23), the reversible cover plate is connected to another reversible cover plate by a first rotating shaft system (21), the first rotating shaft system (21) includes a first intermediate bar (212), the fixed cover plate is connected to the reversible cover plate by a second rotating shaft system (23), the second rotating shaft system (23) includes a second intermediate bar (232), the second intermediate bar (232) is of the same width as the first intermediate bar (212).

3. The hard folding car cover according to claim 2, wherein the reversible cover plate is connected with a limiting system, the limiting system includes a limiting component and a guide groove, the guide groove is connected to the reversible cover plate, the guide groove is set in correspondence with the limiting component, the fixed cover plate is connected with a fixing buckle groove system (24).

4. The hard folding car cover according to claim 2, wherein the fixed cover plate is the third cover plate (33), the reversing cover plate includes a first cover plate (31) and a second cover plate (32); the first cover plate (31) is connected to the second cover plate (32) by a first rotating shaft system (21); the second cover plate (32) is connected to the third cover plate (33) by a second rotational shaft system (23).

5. The hard folding car cover according to claim 4, wherein the first cover plate (31) and second cover plate (32) are respectively connected to a limiting system, the limiting system includes a limiting component and a guide groove, the guide groove is connected to the reversible cover plate, the guide groove is set in correspondence with the limiting component, the third cover plate (33) is connected to a fixing buckle groove system (24).

6. The hard folding car cover according to claim 4, wherein it includes a guide rail system (16), the guide rail system (16) is connected to the cargo hopper by means of a clamp system (14), the guide rail system (16) including two guide rails (161); the guide rail (161) is provided with a guide rail notch (131), the guide rail notch (131) is connected with a lock bolt positioning system (13), the lock bolt positioning system (13) includes a lock bolt positioning system (13) connected to the guide rail notch (131), the lock bolt positioning block (133) is used for seating the lock bolt (132); the lock bolt positioning block (133) is provided with a beveled contact surface (1331), an insert section (1333), a fixing hole (1334) and lateral sides (1332), the insert section (1333) is inserted into the guide rail (161), the screw passes through the fixing hole to connected the lock bolt positioning block (133) with the guide rail (161), the beveled contact surface (1331) is angled downwards, the lateral sides (1332) are used to limit the lock bolt.

7. The hard folding car cover according to claim 6, wherein the third cover plate (33) is connected to the guide rails (161) by a front bar fixing system (11), the front bar fixing system (11) includes a stumbling positioning block (111), a stumbling fixing block (112), a screw positioning block (113) and a plum screw (114); the stumbling positioning block (111) and screw positioning block (113) are attached to the third cover plate (33), the stumbling positioning block (111) is provided with a positioning threaded hole (1111), the screw positioning block (113) is provided with an insertion block (1131) and a fixing hole (1334), the screw (144) connects the screw positioning block (113) to the third cover plate (33) through the fixing hole (1334), the insertion block (1131) is set between the stumbling positioning block (111) and the stumbling fixing block (112); the stumbling fixing block (112) is connected to the guide rail (161), the stumbling fixing block (112) is provided with a positioning recess (1112) and a connection hole, the connection hole is provided in correspondence with the positioning threaded hole (1111); the plum screw (114) includes a snap-in section (1141) and a threaded head (1142), the plum screw (114) passes through the connection hole and the positioning threaded hole (1111), the threaded head (1142) is threaded into the positioning threaded hole (1111), the insertion block (1131) is seated with the snap-in section (1141).

8. The hard folding car cover according to claim 2, wherein the first rotating shaft system (21)

further includes a first frame (211) and a second frame (213), the first frame (211) and the second frame (213) are rotatably connected to both sides of the first intermediate bar (212), both the first frame (211) and the second frame (213) are used for connecting the cover plate; the second rotating shaft system (23) further includes a third frame (231) and a forth frame (233), the third frame (231) and forth frame (233) are rotatably connected to both sides of the second intermediate bar (232), both the third frame (231) and the forth frame (233) are used for connecting the cover plate.

9. The hard folding car cover according to claim 5, wherein the limiting system is a spanner groove system (22), the spanner groove system (22) includes a spanner (222), a short spanner groove (223), a spanner fixing block (224), a spanner slider (225) and a first T-rod (226), the short spanner groove (223) is attached to the cover plate, the spanner fixing block (224) is fixedly connected in the short spanner groove (223), the spanner slider (225) is slidingly set in the short spanner groove (223), one end of the spanner (222) is rotatably connected to the spanner slider (225) by the first T-rod (226).

10. The hard folding car cover according to claim 5, wherein the limiting system is a lock bolt system (12), the lock bolt system (12) includes a lock bolt (132), a handle, a first lock bolt groove (1202), a second lock bolt groove (1203) and a wire support block (1201); the first lock bolt groove (1202) and the second lock bolt groove (1203) are connected by a wire support block (1201), the first lock bolt groove (1202) is slidingly connected with a lock bolt (132), the second lock bolt groove (1203) is slidingly connected with a lock bolt (132), the two lock bolt (132) are connected to each other by a wire, the wire passes through the wire support block (1201), the steel wire is threaded with a handle.

11. The hard folding car cover according to claim 6, wherein the clamp system (14) includes a left clamp (141), a right clamp (143), a fixing block (142), a screw (144) and a second T-rod (145), the left clamp (141) and right clamp (143) are connected by a screw (144), the fixing block (142) is connected to the left clamp (141), the fixing block (142) is threaded to the screw (144); the left clamp (141) includes a left clamp lug groove (1411) and a left clamp surface (1412), the left clamp lug groove (1411) is used to attach the fixing block (142), the left clamp surface (1412) is used to clamp the guide rail (161); the fixing block (142) includes a clamping section (1422), the clamping section (1422) seating with the left clamping lug groove (1411), the right clamp (143) includes a right clamping surface (1431), the right clamping surface (1431) cooperates with the left clamping surface (1412) to clamp the cargo hopper to the guide rail (161), the bottom of the right clamp (143) is connected to the bottom of the left clamp (141) by a second T-rod (145), the bottom of the second T-rod (145) is connected with a nut (146), the upper part of the second T-rod (145) is a transverse section (1451).
