

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250277923

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

CHANG; Pei-Chi et al.

---

### **MOLDED PRISM, CAMERA MODULE AND ELECTRONIC DEVICE**

---

#### **Abstract**

A molded prism includes an optical body and a sheet shading element. The optical body has a light path passing through the optical body, and includes a reflecting surface and a gate trace. The sheet shading element is covered via the optical body, and the sheet shading element includes a first surface, a second surface and a first light blocking structure. The second surface is relative to the first surface, and the first light blocking structure includes a first periphery that is connected to the first surface and the second surface. The first periphery includes a plurality of light blocking petals, and the light blocking petals are adjacent arranged. Each of the light blocking petals of the first periphery includes a tapered portion tapering towards a direction close to the light path, and the light blocking petals are covered inside the optical body.

---

**Inventors:** CHANG; Pei-Chi (Taichung City, TW), LAI; Yu-Chen (Taichung City, TW)

**Applicant:** LARGAN PRECISION CO., LTD. (Taichung City, TW)

**Family ID:** 95563275

**Appl. No.:** 19/021514

**Filed:** January 15, 2025

#### **Foreign Application Priority Data**

TW

113107328

Feb. 29, 2024

---

#### **Publication Classification**

**Int. Cl.:** G02B5/04 (20060101)

**U.S. Cl.:**

**CPC** G02B5/04 (20130101);

---

## **Background/Summary**

### **RELATED APPLICATIONS**

[0001] This application claims priority to Taiwan Application Serial Number 113107328, filed Feb. 29, 2024, which is herein incorporated by reference.

### **BACKGROUND**

#### **Technical Field**

[0002] The present disclosure relates to a molded prism and a camera module. More particularly, the present disclosure relates to a molded prism and a camera module applicable to portable electronic devices.

#### **Description of Related Art**

[0003] In recent years, portable electronic devices have developed rapidly. For example, intelligent electronic devices and tablets have been filled in the lives of modern people, and camera modules and molded prisms thereof mounted on portable electronic devices have also prospered.

[0004] However, as technology advances, the quality requirements of the molded prism are becoming higher and higher. In particular, the unpredicted reflection is easily occurred inside of the molded prism owing to the light folding in the molded prism, so that the flare is caused. Therefore, a molded prism, which can solve the light blocking problem, needs to be developed.

### **SUMMARY**

[0005] According to one aspect of the present disclosure, a molded prism includes an optical body and a sheet shading element. The optical body has a light path passing through the optical body, and includes a reflecting surface and a gate trace. The light path is folded on the reflecting surface, and the light path does not pass through the gate trace. The sheet shading element is covered via the optical body, the sheet shading element is closer to the light path than the gate trace to the light path, and the sheet shading element includes a first surface, a second surface and a first light blocking structure. The second surface is relative to the first surface, and the second surface is farther away from the reflecting surface than the first surface from the reflecting surface. The first light blocking structure includes a first periphery that is connected to the first surface and the second surface, the first periphery faces towards the light path, the first periphery surrounds the light path, and the optical body is physically contacted with the first periphery, the first surface and the second surface. The first periphery includes a plurality of light blocking petals, a number of the light blocking petals of the first periphery is between 14 and 250, and the light blocking petals are adjacent arranged. Each of the light blocking petals of the first periphery includes a tapered portion tapering towards a direction close to the light path, and the light blocking petals are covered inside the optical body.

[0006] According to one aspect of the present disclosure, a camera module includes the molded prism of the aforementioned aspect.

[0007] According to one aspect of the present disclosure, an electronic device includes the camera module of the aforementioned aspect.

[0008] According to one aspect of the present disclosure, a molded prism includes an optical body and a sheet shading element. The optical body has a light path passing through the optical body, and includes a reflecting surface and a gate trace. The light path is folded on the reflecting surface,

and the light path does not pass through the gate trace. The sheet shading element is covered via the optical body, the sheet shading element is closer to the light path than the gate trace to the light path, and the sheet shading element includes a first surface, a second surface and a first light blocking structure. The second surface is relative to the first surface, and the second surface is farther away from the reflecting surface than the first surface from the reflecting surface. The first light blocking structure includes a first periphery that is connected to the first surface and the second surface, the first periphery faces towards the light path, the first periphery surrounds the light path, and the optical body is physically contacted with the first periphery, the first surface and the second surface. The optical body further includes a release structure disposed on a side of the sheet shading element away from the first periphery, and the release structure is tapered along an extending direction of the sheet shading element. At least one portion of the sheet shading element is disposed on the release structure.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0009] FIG. 1A is a three-dimensional view of a molded prism according to the 1st example of the present disclosure.

[0010] FIG. 1B is a partial enlarged view of the molded prism according to the 1st example in FIG. 1A.

[0011] FIG. 1C is a top view of the molded prism according to the 1st example in FIG. 1A.

[0012] FIG. 1D is a partial enlarged view of the molded prism according to the 1st example in FIG. 1C.

[0013] FIG. 1E is a side view of the molded prism according to the 1st example in FIG. 1A.

[0014] FIG. 1F is a cross-sectional view of the molded prism according to the 1st example in FIG. 1E.

[0015] FIG. 1G is a partial enlarged view of the molded prism according to the 1st example in FIG. 1F.

[0016] FIG. 1H is another partial enlarged view of the molded prism according to the 1st example in FIG. 1F.

[0017] FIG. 1I is a reflectance diagram of an anti-reflecting surface according to the 1st example in FIG. 1A.

[0018] FIG. 1J is a transmittance diagram of the molded prism according to the 1st example in FIG. 1A.

[0019] FIG. 1K is another transmittance diagram of the molded prism according to the 1st example in FIG. 1A.

[0020] FIG. 2A is a three-dimensional view of a molded prism according to the 2nd example of the present disclosure.

[0021] FIG. 2B is a schematic view of the molded prism according to the 2nd example in FIG. 2A.

[0022] FIG. 2C is a top view of the molded prism according to the 2nd example in FIG. 2A.

[0023] FIG. 2D is a partial enlarged view of the molded prism according to the 2nd example in FIG. 2C.

[0024] FIG. 2E is a cross-sectional view of the molded prism according to the 2nd example in FIG. 2A.

[0025] FIG. 2F is a partial enlarged view of the molded prism according to the 2nd example in FIG. 2E.

[0026] FIG. 3A is a three-dimensional view of a molded prism according to the 3rd example of the present disclosure.

[0027] FIG. 3B is a partial enlarged view of the molded prism according to the 3rd example in FIG.

3A.

[0028] FIG. 3C is a side view of the molded prism according to the 3rd example in FIG. 3A.

[0029] FIG. 3D is a top view of the molded prism according to the 3rd example in FIG. 3A.

[0030] FIG. 3E is a partial enlarged view of the molded prism according to the 3rd example in FIG. 3D.

[0031] FIG. 3F is a cross-sectional view of the molded prism according to the 3rd example in FIG. 3A.

[0032] FIG. 3G is a partial enlarged view of the molded prism according to the 3rd example in FIG. 3F.

[0033] FIG. 4A is a three-dimensional view of a molded prism according to the 4th example of the present disclosure.

[0034] FIG. 4B is a partial enlarged view of the molded prism according to the 4th example in FIG. 4A.

[0035] FIG. 4C is a top view of the molded prism according to the 4th example in FIG. 4A.

[0036] FIG. 4D is a cross-sectional view of the molded prism according to the 4th example in FIG. 4A.

[0037] FIG. 4E is a partial enlarged view of the molded prism according to the 4th example in FIG. 4D.

[0038] FIG. 4F is a cross-sectional schematic view of the molded prism along line 4F-4F in FIG. 4D.

[0039] FIG. 4G is a partial enlarged view of the molded prism according to the 4th example in FIG. 4F.

[0040] FIG. 5A is a three-dimensional view of a molded prism according to the 5th example of the present disclosure.

[0041] FIG. 5B is a top view of the molded prism according to the 5th example in FIG. 5A.

[0042] FIG. 5C is a partial enlarged view of the molded prism according to the 5th example in FIG. 5B.

[0043] FIG. 5D is a cross-sectional view of the molded prism according to the 5th example in FIG. 5A.

[0044] FIG. 5E is another cross-sectional view of the molded prism according to the 5th example in FIG. 5A.

[0045] FIG. 5F is a partial enlarged view of the molded prism according to the 5th example in FIG. 5E.

[0046] FIG. 6A is a three-dimensional view of a molded prism according to the 6th example of the present disclosure.

[0047] FIG. 6B is a side view of the molded prism according to the 6th example in FIG. 6A.

[0048] FIG. 6C is a partial enlarged view of the molded prism according to the 6th example in FIG. 6B.

[0049] FIG. 6D is another side view of the molded prism according to the 6th example in FIG. 6A.

[0050] FIG. 6E is a partial enlarged view of the molded prism according to the 6th example in FIG. 6D.

[0051] FIG. 6F is a cross-sectional view of the molded prism according to the 6th example in FIG. 6A.

[0052] FIG. 6G is a partial enlarged view of the molded prism according to the 6th example in FIG. 6F.

[0053] FIG. 7A is a three-dimensional view of a molded prism according to the 7th example of the present disclosure.

[0054] FIG. 7B is a partial enlarged view of the molded prism according to the 7th example in FIG. 7A.

[0055] FIG. 7C is a top view of the molded prism according to the 7th example in FIG. 7A.

[0056] FIG. 7D is a partial enlarged view of the molded prism according to the 7th example in FIG. 7C.

[0057] FIG. 7E is a side view of the molded prism according to the 7th example in FIG. 7A.

[0058] FIG. 7F is a cross-sectional view of the molded prism according to the 7th example in FIG. 7E.

[0059] FIG. 7G is a partial enlarged view of the molded prism according to the 7th example in FIG. 7F.

[0060] FIG. 8 is a schematic view of a camera module according to the 8th example of the present disclosure.

[0061] FIG. 9 is a schematic view of a camera module according to the 9th example of the present disclosure.

[0062] FIG. 10 is a schematic view of a camera module according to the 10th example of the present disclosure.

[0063] FIG. 11 is a schematic view of a camera module according to the 11th example of the present disclosure.

[0064] FIG. 12A is a schematic view of an electronic device according to the 12th example of the present disclosure.

[0065] FIG. 12B is another schematic view of the electronic device according to the 12th example in FIG. 12A.

[0066] FIG. 13 is a schematic view of an electronic device applied to a computer according to the 13th example of the present disclosure.

[0067] FIG. 14 is a schematic view of an electronic device applied to a wearable device according to the 14th example of the present disclosure.

#### DETAILED DESCRIPTION

[0068] The present disclosure provides a molded prism, which includes an optical body and a sheet shading element, wherein the optical body has a light path passing through the optical body, and the sheet shading element is covered via the optical body. The optical body includes a reflecting surface and a gate trace, wherein the light path is folded on the reflecting surface, the light path does not pass through the gate trace, and a number of the reflecting surface can be plurality. The sheet shading element is closer to the light path than the gate trace to the light path, and the sheet shading element includes a first surface, a second surface and a first light blocking structure, wherein the second surface is relative to the first surface, and the second surface is farther away from the reflecting surfaces than the first surface from the reflecting surfaces. The first light blocking structure includes a first periphery, wherein the first periphery is connected to the first surface and the second surface, the first periphery faces towards the light path, the first periphery surrounds the light path, and the optical body is physically contacted with the first periphery, the first surface and the second surface.

[0069] By the sheet shading element being closer to the light path than the gate trace to the light path, the flare, which is formed owing to the light via the plastic gate trace, can be avoided, so that the optical quality can be ensured, wherein the aforementioned structure of the sheet shading element can be further formed by the manufacturing process, such as the sheet metal process, the stamping process, the laser process and the etching process, but the present disclosure is not limited thereto. Further, the internal light blocking structure is formed by the optical body being physically contacted with the first periphery, and the internal light blocking structure is simultaneously and physically contacted with the first surface and the second surface, so that the combination of the sheet shading element and the optical body can be ensured.

[0070] In detail, the optical body can be made of transparent material, such as plastic material and glass material, so that the optical body can further obtain the function of absorbing and filtering the light with the specific wavelength. The gate trace is the trace of the optical body flowing during the manufacturing process, the specific spatial geometric features of the gate trace are formed by the

mold and the post-processing, and the gate trace can also be a flow mark, a sink mark and a void, but the idiomatic expression is not limited thereto, wherein the aforementioned spatial geometric features can be the shape of the injection channel, the shape of the shearing, the shape of the flash, but the present disclosure is not limited thereto. The first periphery of the first light blocking structure can be closed and surround the light path or be opened and surround the light path. [0071] The first periphery can include a plurality of light blocking petals, wherein a number of the light blocking petals of the first periphery can be between 14 and 250, and the light blocking petals are adjacent arranged, so that the effectiveness of the sheet shading element can be ensured. Moreover, each of the light blocking petals of the first periphery can include a tapered portion tapering towards a direction close to the light path, and the light blocking petals are covered inside the optical body, so that the vignetting of the periphery can be smoothly transited for enhancing the imaging quality.

[0072] The optical body can further include a release structure disposed on a side of the sheet shading element away from the first periphery, the release structure is tapered along an extending direction of the sheet shading element, and at least one portion of the sheet shading element is disposed on the release structure. By the design of disposing the sheet shading element on the release structure, the manufacturing stability can be enhanced, and the shifting of the sheet shading element can be reduced, so that the yield rate can be enhanced. Furthermore, the metal light blocking sheet can be fixed in the specific position during the embedded injection process by the release structure, so that the shifting of the light blocking sheet can be reduced to further ensure the optical quality.

[0073] The sheet shading element can further include a cutting mark farther away from the light path than the first periphery from the light path, and the cutting mark exposes on the optical body. Therefore, the stability of the sheet shading element during the manufacturing process can be enhanced. Further, the cutting mark can be further and physically contacted with the gate trace, and the sheet shading element and the optical body can be finished cutting once so as to enhance the manufacturing efficiency.

[0074] The optical body can further include an incident surface and an exit surface, wherein the light path passes through the incident surface, the reflecting surface and the exit surface in sequence, and the sheet shading element extends along a direction away from one of the incident surface, the reflecting surface and the exit surface. Therefore, the forming quality of the optical surface and the shifting amount of the light blocking structure can be simultaneously considered by cooperating the extending direction of the sheet shading element with the optical surface, so that the optical quality can be enhanced and ensured. Further, the optical quality can be improved by cooperating the release direction with optical surface. Moreover, the aforementioned direction can be perpendicular to one of the incident surface, the reflecting surface and the exit surface so as to simplify the design and improve the efficiency of the quality control, and the release structure is tapered on the aforementioned direction to further cooperate the release direction with the optical surface, so that the optical quality can be enhanced.

[0075] The optical body can further include a ridge structure, wherein the ridge structure can include a plurality of recesses arranged along a direction surrounding the light path, each of the recesses can include a recess end, the recess end is corresponding to the first periphery of the first light blocking structure, and each of the recesses is gradually widened from the recess end towards a direction away from the light path. Therefore, the better optical quality can be achieved by cooperating the first periphery with the multiple times of the light blocking. Furthermore, the release structure can include the ridge structure.

[0076] The molded prism can further include an opaque layer disposed on the ridge structure. Therefore, the function of blocking the light of the ridge structure can be further enhanced so as to improve the light blocking quality.

[0077] The ridge structure can further include a plurality of ribs, wherein the ribs extend from the

recesses towards a direction away from the light path. Therefore, the anti-reflecting ability of the optical body can be further enhanced.

[0078] The sheet shading element can further include at least one bending portion, wherein at least one portion of the first periphery is disposed on the bending portion. Therefore, the light from the different directions can be blocked, and the mechanical property of the sheet shading element can be enhanced via the bending portion so as to improve the manufacturing process.

[0079] The sheet shading element can further include a second light blocking structure, and the second light blocking structure can include a second periphery, wherein the second periphery is connected to the first surface and the second surface, the second periphery faces towards the light path, the second periphery surrounds the light path, and the second periphery and the optical body are physically contacted. The second periphery can include a plurality of light blocking petals, wherein a number of the light blocking petals of the second periphery is between 14 and 250, and the light blocking petals are adjacently arranged. Each of the light blocking petals of the second periphery can include a tapered portion tapering towards a direction close to the light path, and the light blocking petals are covered inside of the optical body. By simultaneously providing multiple of the light blocking structures via the sheet shading element, the elements can be reduced so as to lower the assembling cost.

[0080] A number of the sheet shading element can be plurality. Therefore, the degree of freedom of the light blocking type of the molded prism can be enhanced, so that the optical requirements can be satisfied.

[0081] A thickness of each of the light blocking petals can gradually increase towards a direction away from the light path. Therefore, the moldability can be ensured.

[0082] The light path can be folded at least twice occurring in the optical body. Therefore, the spatial utilization of an electronic device used a camera module with the prism can be enhanced.

[0083] The molded prism can further include an exposed structure, wherein the sheet shading element is exposed on the exposed structure to the optical body, and the release structure is tapered on a direction away from the exposed structure. Therefore, the demolding process can be stable so as to avoid the molding defects.

[0084] The tapered portion of each of the light blocking petals is tapered towards the direction close to the light path to form a rear portion. When a distance between adjacent two of the rear portions is  $D1$ , the following condition can be satisfied:  $0.018\text{ mm} \leq D1 \leq 0.8\text{ mm}$ . Therefore, the peripheral quality can be further enhanced. Moreover, the rear portion can be a tip, an arc or a plane, but the present disclosure is not limited thereto. Further, the following condition can be satisfied:  $0.02\text{ mm} \leq D1 \leq 0.6\text{ mm}$ .

[0085] When a thickness of the sheet shading element is defined via a distance between the first surface and the second surface, and the thickness of the sheet shading element is  $T$ , the following condition can be satisfied:  $0.03\text{ mm} \leq T \leq 0.5\text{ mm}$ . Therefore, the balance between the manufacturing process and the optical quality can be obtained so as to ensure the manufacturing feasibility.

[0086] The release structure can include a first release surface, wherein the first release surface is gradually close to the sheet shading element along the extending direction of the sheet shading element. When a minimum distance between the first release surface and the sheet shading element is  $G1$ , the following condition can be satisfied:  $0.02\text{ mm} \leq G1 \leq 0.32\text{ mm}$ . Further, the following condition can be satisfied:  $0.03\text{ mm} \leq G1 \leq 0.24\text{ mm}$ . Moreover, the release surface can be a plane, an arc surface or a curved surface, but the present disclosure is not limited thereto.

[0087] The release structure can further include a second release surface, wherein the second release surface is relative to the first release surface, and the sheet shading element is disposed between the first release surface and the second release surface. When a minimum distance between the first release surface and the second release surface is  $G12$ ; a thickness of the sheet shading element is defined via a distance between the first surface and the second surface, and the thickness of the sheet shading element is  $T$ , the following condition can be satisfied:

$0.12 \leq T/G12 \leq 0.91$ . Therefore, the effect of the release structure can be further enhanced. Further, the following condition can be satisfied:  $0.15 \leq T/G12 \leq 0.68$ .

[0088] When a distance between adjacent two of the recess ends is D2, the following condition can be satisfied:  $0.028 \text{ mm} \leq D2 \leq 0.6 \text{ mm}$ . Further, the following condition can be satisfied:  $0.038 \text{ mm} \leq D2 \leq 0.45 \text{ mm}$ .

[0089] The optical body can further include an anti-reflecting surface, wherein the light path passes through the anti-reflecting surface, and a maximum reflectivity of the anti-reflecting surface in a wavelength range of 450 nm to 750 nm is less than or equal to 0.49%. Therefore, the transmittance can be enhanced so as to improve the optical quality. Furthermore, the surface reflectivity of the anti-reflecting surface can be reduced by disposing an anti-reflecting layer and a microstructure layer, but the present disclosure is not limited thereto.

[0090] An infrared light is partially filtered via the molded prism, and a wavelength providing a transmittance of the molded prism being 50% can be between 600 nm and 700 nm. Therefore, the optical quality can be enhanced by filtering the light with the specific range of the wavelength. Further, the aforementioned purpose of the molded prism can be achieved by disposing the coating layer, disposing the optical body with the absorbing property of the infrared light or simultaneously multiple filtering methods.

[0091] Each of the aforementioned features of the molded prism can be utilized in various combinations for achieving the corresponding effects.

[0092] The present disclosure provides a camera module, which includes the aforementioned molded prism.

[0093] The camera module can further include a carrier, wherein at least one portion of the carrier is disposed on the exposed structure. Therefore, the combination between the carrier and the molded prism can be enhanced so as to reduce the defective rate.

[0094] Each of the aforementioned features of the camera module can be utilized in various combinations for achieving the corresponding effects.

[0095] The present disclosure provides an electronic device, which includes the aforementioned camera module. Furthermore, the electronic device can further include an image sensor module and a flash module, but the present disclosure is not limited thereto.

[0096] According to the aforementioned embodiment, specific examples are provided, and illustrated via figures.

#### 1st Example

[0097] FIG. 1A is a three-dimensional view of a molded prism **100** according to the 1st example of the present disclosure. FIG. 1B is a partial enlarged view of the molded prism **100** according to the 1st example in FIG. 1A. FIG. 1C is a top view of the molded prism **100** according to the 1st example in FIG. 1A. FIG. 1D is a partial enlarged view of the molded prism **100** according to the 1st example in FIG. 1C. In FIGS. 1A to 1D, the molded prism **100** includes an optical body **110** and a sheet shading element **120**, wherein the optical body **110** has a light path L passing through the optical body **110**, and the sheet shading element **120** is covered via the optical body **110**. In detail, the optical body **110** is made of plastic material, so that the optical body **110** can further obtain the function of absorbing and filtering the light with the specific wavelength, and the sheet shading element **120** can be made of metal material.

[0098] FIG. 1E is a side view of the molded prism **100** according to the 1st example in FIG. 1A. FIG. 1F is a cross-sectional view of the molded prism **100** according to the 1st example in FIG. 1E. In FIGS. 1A, 1C, 1E and 1F, the optical body **110** includes a gate trace **111** and reflecting surfaces **112**, wherein the light path L is folded on the reflecting surfaces **112**, and the light path L does not pass through the gate trace **111**. In particular, the gate trace **111** is the trace of the injection channel of the optical body **110**.

[0099] FIG. 1G is a partial enlarged view of the molded prism **100** according to the 1st example in FIG. 1F. In FIGS. 1B to 1D and 1G, the sheet shading element **120** is closer to the light path L than



the gate trace **111** to the light path L, and the sheet shading element **120** includes a first surface **121**, a second surface **122** and a first light blocking structure **123**, wherein the second surface **122** is relative to the first surface **121**, and the second surface **122** is farther away from the reflecting surfaces **112** than the first surface **121** from the reflecting surfaces **112**. The first light blocking structure **123** includes a first periphery **141**, wherein the first periphery **141** is connected to the first surface **121** and the second surface **122**, the first periphery **141** faces towards the light path L, the first periphery **141** surrounds the light path L, and the optical body **110** is physically contacted with the first periphery **141**, the first surface **121** and the second surface **122**. By the sheet shading element **120** being closer to the light path L than the gate trace **111** to the light path L, the flare, which is formed owing to the light via the gate trace **111**, can be avoided, so that the optical quality can be ensured. Further, the internal light blocking structure is formed by the optical body **110** being physically contacted with the first periphery **141**, and the internal light blocking structure is simultaneously and physically contacted with the first surface **121** and the second surface **122**, so that the combination of the sheet shading element **120** and the optical body **110** can be ensured.

[0100] Moreover, the first periphery **141** of the first light blocking structure **123** is closed and surrounds the light path L, and the aforementioned structure of the sheet shading element **120** can be further formed by the manufacturing process, such as the sheet metal process, the stamping process, the laser process and the etching process, but the present disclosure is not limited thereto.

[0101] In FIGS. **1A**, **1B** and **1G**, the first periphery **141** includes a plurality of light blocking petals **142**, and the light blocking petals **142** are adjacent arranged, wherein each of the light blocking petals **142** of the first periphery **141** includes a tapered portion **143** tapering towards a direction close to the light path L, and the light blocking petals **142** are covered inside the optical body **110**. Therefore, the vignetting of the first periphery **141** can be smooth transited via the tapered portion **143** so as to enhance the imaging quality. According to the 1st example, a number of the light blocking petals **142** is 194. Via the light blocking petals **142**, the effectiveness of the first light blocking structure **123** can be ensured. Furthermore, a thickness of each of the light blocking petals **142** gradually increases towards a direction away from the light path L. Therefore, the moldability can be ensured.

[0102] In FIGS. **1B** and **1D**, the tapered portion **143** of each of the light blocking petals **142** is tapered towards the direction close to the light path L to form a rear portion **144**. Therefore, the peripheral quality can be further enhanced. Moreover, the rear portion **144** can be a tip, an arc or a plane, but the present disclosure is not limited thereto.

[0103] In FIGS. **1A** and **1C**, the sheet shading element **120** can further include a cutting mark **124** farther away from the light path L than the first periphery **141** from the light path L, and the cutting mark **124** exposes on the optical body **110**.

[0104] Therefore, the stability of the sheet shading element **120** during the manufacturing process can be enhanced.

[0105] In FIG. **1F**, the optical body **110** can further include an incident surface (its reference numeral is omitted) and an exit surface (its reference numeral is omitted), wherein the light path L passes through the incident surface, the reflecting surfaces **112** and the exit surface in sequence, and the sheet shading element **120** extends along directions away from the incident surface and the exit surface. Therefore, the forming quality of the optical surface and the shifting amount of the first light blocking structure **123** can be simultaneously considered by cooperating the extending direction of the sheet shading element **120** with the optical surface, so that the optical quality can be enhanced and ensured. Further, the optical quality can be improved by cooperating the release direction with optical surface. According to the 1st example, the incident surface and the exit surface are coplanar, and the incident surface and the exit surface can further obtain the reflecting function by the optical design of the total-reflection.

[0106] Moreover, the aforementioned direction is perpendicular to the incident surface and the exit surface so as to simplify the design and improve the efficiency of the quality control. Further, the

light path L is folded at least twice occurring in the optical body **110**. Therefore, the spatial utilization of an electronic device used a camera module with the molded prism **100** can be enhanced.

[0107] In FIGS. **1E** and **1G**, the optical body **110** can further include a release structure **115** disposed on a side of the sheet shading element **120** away from the first periphery **141**, the release structure **115** is tapered along an extending direction of the sheet shading element **120**, and at least one portion of the sheet shading element **120** is disposed on the release structure **115**. By the design of disposing the sheet shading element **120** on the release structure **115**, the manufacturing stability can be enhanced, and the shifting of the sheet shading element **120** can be reduced, so that the yield rate can be enhanced.

[0108] Furthermore, the sheet shading element **120** can be fixed in the specific position during the embedded injection process by the release structure **115**, so that the shifting of the sheet shading element **120** can be reduced to further ensure the optical quality. In detail, the release structure **115** is tapered along the directions perpendicular to the incident surface and the exit surface to further cooperate the release direction with the optical surface, so that the optical quality can be enhanced.

[0109] In FIGS. **1A**, **1B**, **1C**, **1E** and **1G**, the optical body **110** can further include a ridge structure **116**, wherein the ridge structure **116** can include a plurality of recesses **161** arranged along a direction surrounding the light path L, each of the recesses **161** includes a recess end **162**, the recess end **162** is corresponding to the first periphery **141** of the first light blocking structure **123**, and each of the recesses **161** is gradually widened from the recess end **162** towards a direction away from the light path L. Therefore, the better optical quality can be achieved by cooperating the first periphery **141** with the multiple times of the light blocking.

[0110] In FIG. **1G**, the optical body **110** can further include an anti-reflecting surface **117**, wherein the light path L passes through the anti-reflecting surface **117**. Therefore, the transmittance can be enhanced via the anti-reflecting surface **117** so as to improve the optical quality. Furthermore, the surface reflectivity of the anti-reflecting surface **117** can be reduced by disposing an anti-reflecting layer and a microstructure layer, but the present disclosure is not limited thereto.

[0111] FIG. **1H** is another partial enlarged view of the molded prism **100** according to the 1st example in FIG. **1F**. In FIGS. **1G** and **1H**, the release structure **115** can include a first release surface **151**, a second release surface **152**, a third release surface **153** and a fourth release surface **154**, wherein the first release surface **151** is gradually close to the sheet shading element **120** along the extending direction of the sheet shading element **120**, the second release surface **152** is relative to the first release surface **151**, the third release surface **153** is relative to the fourth release surface **154**, and the sheet shading element **120** is partially disposed between the first release surface **151** and the second release surface **152** and partially disposed between the third release surface **153** and the fourth release surface **154**. Therefore, the effect of the release structure **115** can be further enhanced. Further, each of the release surfaces (that is, the first release surface **151**, the second release surface **152**, the third release surface **153** and the fourth release surface **154**) can be a plane, an arc surface or a curved surface, but the present disclosure is not limited thereto.

[0112] In FIGS. **1B**, **1C**, **1E** and **1G**, the molded prism **100** can further include an opaque layer **170** and an exposed structure **180**, wherein the opaque layer **170** is disposed on the ridge structure **116**, the sheet shading element **120** is exposed on the exposed structure **180** to the optical body **110**, and the release structure **115** is tapered on a direction away from the exposed structure **180**. Therefore, the function of blocking the light of the ridge structure **116** can be further enhanced via the opaque layer **170** so as to improve the light blocking quality. Furthermore, the demolding process can be stable via the exposed structure **180** so as to avoid the molding defects. It should be mentioned that the cross pattern in FIGS. **1B**, **1C** and **1G** is configured to indicate the range of the opaque layer **170**.

[0113] Moreover, the sheet shading element **120** is exposed on the surface of the molded prism **100** at the exposed structure **180**, so that the sheet shading element **120** can cooperate with the mold

during forming. Therefore, the sheet shading element **120** can be fixed, and the sheet shading element **120** can be cooperated with another elements during disposing the molded prism **100** so as to enhance the light blocking quality. Simultaneously, the exposed structure **180** and the release structure **115** are disposed on relative sides, respectively, and the release structure **115** is tapered towards a direction away from the exposed structure **180**. Therefore, the demolding process can be stable so as to avoid the forming defects.

[0114] In FIGS. **1A**, **1C** and **1E**, the sheet shading element **120** can further include at least one bending portion **125** and a second light blocking structure **126**, wherein at least one portion of the first periphery **141** is disposed on the bending portion **125**, the second light blocking structure **126** includes a second periphery (its reference numeral is omitted), the second periphery faces towards the light path **L**, the second periphery surrounds the light path **L**, and the second periphery and the optical body **110** are physically contacted. The second periphery includes a plurality of light blocking petals **146**, and the light blocking petals **146** are adjacently arranged, wherein each of the light blocking petals **146** of the second periphery includes a tapered portion **147** tapering towards a direction close to the light path **L**, and the light blocking petals **146** are covered inside of the optical body **110**. According to the 1st example, a number of the light blocking petals **146** is 179. Via the bending portion **125**, the mechanical property of the sheet shading element **120** can be enhanced so as to improve the manufacturing process, and the light from the different directions can be blocked. Further, by simultaneously providing multiple of the light blocking structures (that is, the first light blocking structure **123** and the second light blocking structure **126**) via the sheet shading element **120**, the elements can be reduced so as to lower the assembling cost.

[0115] An infrared light can be partially filtered via the molded prism **100**. Therefore, the optical quality can be enhanced by filtering the light with the specific range of the wavelength. In detail, the aforementioned purpose of the molded prism **100** can be achieved by disposing the coating layer, disposing the optical body with the absorbing property of the infrared light or simultaneously multiple filtering methods.

[0116] FIG. **1I** is a reflectance diagram of an anti-reflecting surface **117** according to the 1st example in FIG. **1A**. FIG. **1J** is a transmittance diagram of the molded prism **100** according to the 1st example in FIG. **1A**. FIG. **1K** is another transmittance diagram of the molded prism **100** according to the 1st example in FIG. **1A**. In FIGS. **1D** and **1G** to **1K**, when a distance between adjacent two of the rear portions **144** is **D1**; a distance between adjacent two of the recess ends **162** is **D2**; a thickness of the sheet shading element **120** is defined via a distance between the first surface **121** and the second surface **122**, and the thickness of the sheet shading element **120** is **T**; a minimum distance between the first release surface **151** and the sheet shading element **120** is **G1**; a minimum distance between the first release surface **151** and the second release surface **152** is **G12**; a minimum distance between the third release surface **153** and the sheet shading element **120** is **G3**; a minimum distance between the third release surface **153** and the fourth release surface **154** is **G34**; a wavelength providing a transmittance of the molded prism **100** being 50% is **T50**, the following conditions of Table 1 are satisfied. It should be mentioned that all of the anti-reflecting surfaces **117** of the samples 1 to 9 in FIG. **1I** can be applied to the 1st example.

TABLE-US-00001 TABLE 1 1st example **D1** (mm) 0.096 **G3** (mm) 0.1 **D2** (mm) 0.2 **G34** (mm) 0.4 **T** (mm) 0.1 **T/G34** 0.25 **G1** (mm) 0.1 **T50** (nm) 680 (FIG. **1J**) **G12** (mm) 0.3 **T50** (nm) 610 (FIG. **1K**) **T/G12** 0.33

[0117] It should be mentioned that the partial structures and elements are omitted in the partial drawings for clearly indicating the relationship between the optical body **110** and the sheet shading element **120**.

## 2nd Example

[0118] FIG. **2A** is a three-dimensional view of a molded prism **200** according to the 2nd example of the present disclosure. FIG. **2B** is a schematic view of the molded prism **200** according to the 2nd example in FIG. **2A**. FIG. **2C** is a top view of the molded prism **200** according to the 2nd example

in FIG. 2A. FIG. 2D is a partial enlarged view of the molded prism **200** according to the 2nd example in FIG. 2C. In FIGS. 2A to 2D, the molded prism **200** includes an optical body **210** and a sheet shading element **220**, wherein the optical body **210** has a light path L passing through the optical body **210**, and the sheet shading element **220** is covered via the optical body **210**.

[0119] FIG. 2E is a cross-sectional view of the molded prism **200** according to the 2nd example in FIG. 2A. In FIGS. 2A to 2C and 2E, the optical body **210** includes a gate trace **211** and a reflecting surface **212**, wherein the light path L is folded on the reflecting surface **212**, and the light path L does not pass through the gate trace **211**.

[0120] In FIGS. 2B to 2E, the sheet shading element **220** is closer to the light path L than the gate trace **211** to the light path L, and the sheet shading element **220** includes a first surface **221**, a second surface **222** and a first light blocking structure **223**, wherein the second surface **222** is relative to the first surface **221**, and the second surface **222** is farther away from the reflecting surface **212** than the first surface **221** from the reflecting surface **212**. The first light blocking structure **223** includes a first periphery **241**, wherein the first periphery **241** is connected to the first surface **221** and the second surface **222**, the first periphery **241** faces towards the light path L, the first periphery **241** surrounds the light path L, and the optical body **210** is physically contacted with the first periphery **241**, the first surface **221** and the second surface **222**.

[0121] In FIGS. 2B and 2D, the first periphery **241** includes a plurality of light blocking petals **242**, and the light blocking petals **242** are adjacent arranged, wherein each of the light blocking petals **242** of the first periphery **241** includes a tapered portion **243** tapering towards a direction close to the light path L, the light blocking petals **242** are covered inside the optical body **210**, and the tapered portion **243** of each of the light blocking petals **242** is tapered towards the direction close to the light path L to form a rear portion **244**. According to the 2nd example, a number of the light blocking petals **242** is 28. Moreover, the first periphery **241** is embedded in the optical body **210**, and the portion of the second surface **222** close to the first periphery **241** is exposed on the surface of the optical body **210**.

[0122] FIG. 2F is a partial enlarged view of the molded prism **200** according to the 2nd example in FIG. 2E. In FIGS. 2A, 2B, **20**, 2E and 2F, the sheet shading element **220** can further include a cutting mark **224** farther away from the light path L than the first periphery **241** from the light path L, and the cutting mark **224** exposes on the optical body **210**.

[0123] In FIG. 2E, the optical body **210** can further include an incident surface **213** and an exit surface **214**, wherein the light path L passes through the incident surface **213**, the reflecting surface **212** and the exit surface **214** in sequence, and two ends of the sheet shading element **220** extend along directions away from the incident surface **213** and away from the exit surface **214**, respectively. Furthermore, the aforementioned directions are perpendicular to the reflecting surface **212**.

[0124] In FIGS. 2E and 2F, the optical body **210** can further include a release structure **215** disposed on a side of the sheet shading element **220** away from the first periphery **241**, the release structure **215** is tapered along an extending direction of the sheet shading element **220**, and at least one portion of the sheet shading element **220** is disposed on the release structure **215**. In FIG. 2E, the release structure **215** at the upper left position is tapered along the direction perpendicular to the exit surface **214**, and the release structure **215** at the lower right position is tapered along the direction perpendicular to the incident surface **213**. Further, the cutting mark **224** can be further disposed on the release structure **215**, so that the shifting of the sheet shading element **220** during the forming process can be reduced, but the present disclosure is not limited thereto.

[0125] In FIG. 2F, the release structure **215** can include a first release surface **251** and a second release surface **252**, wherein the first release surface **251** is gradually close to the sheet shading element **220** along the extending direction of the sheet shading element **220**, the second release surface **252** is relative to the first release surface **251**, and the sheet shading element **220** is disposed between the first release surface **251** and the second release surface **252**.

[0126] In FIGS. 2A to 2C, the molded prism **200** can further include an exposed structure **280**, wherein the sheet shading element **220** is exposed on the exposed structure **280** to the optical body **210**, and the release structure **215** is tapered on a direction away from the exposed structure **280**.

[0127] In FIGS. 2B and 2E, the sheet shading element **220** can further include a second light blocking structure **226**, wherein the second light blocking structure **226** includes a second periphery **245**, the second periphery **245** is connected to the first surface **221** and the second surface **222**, the second periphery **245** faces towards the light path L, the second periphery **245** surrounds the light path L, and the second periphery **245** is physically contacted with the optical body **210**. The second periphery **245** includes a plurality of light blocking petals **246**, and the light blocking petals **246** are adjacently arranged, wherein each of the light blocking petals **246** of the second periphery **245** includes a tapered portion **247** tapering towards a direction close to the light path L, and the light blocking petals **246** are covered inside of the optical body **210**. According to the 2nd example, a number of the light blocking petals **246** is 28.

[0128] In FIGS. 2D and 2F, when a distance between adjacent two of the rear portions **244** is D1; a thickness of the sheet shading element **220** is defined via a distance between the first surface **221** and the second surface **222**, and the thickness of the sheet shading element **220** is T; a minimum distance between the first release surface **251** and the sheet shading element **220** is G1; a minimum distance between the first release surface **251** and the second release surface **252** is G12, the following conditions of Table 2 are satisfied.

TABLE-US-00002 TABLE 2 2nd example D1 (mm) 0.4 T (mm) 0.1 G1 (mm) 0.06 T/G12 0.454 G12 (mm) 0.22

[0129] It should be mentioned that the partial structures and elements are omitted in the partial drawings for clearly indicating the relationship between the optical body **210** and the sheet shading element **220**.

### 3rd Example

[0130] FIG. 3A is a three-dimensional view of a molded prism **300** according to the 3rd example of the present disclosure. FIG. 3B is a partial enlarged view of the molded prism **300** according to the 3rd example in FIG. 3A. FIG. 3C is a side view of the molded prism **300** according to the 3rd example in FIG. 3A. FIG. 3D is a top view of the molded prism **300** according to the 3rd example in FIG. 3A. FIG. 3E is a partial enlarged view of the molded prism **300** according to the 3rd example in FIG. 3D. In FIGS. 3A to 3E, the molded prism **300** includes an optical body **310** and a sheet shading element **320**, wherein the optical body **310** has a light path L passing through the optical body **310**, and the sheet shading element **320** is covered via the optical body **310**. According to the 3rd example, a number of the sheet shading element **320** is two. Therefore, the degree of freedom of the light blocking type of the prism can be enhanced so as to satisfy the optical requirements.

[0131] FIG. 3F is a cross-sectional view of the molded prism **300** according to the 3rd example in FIG. 3A. In FIGS. 3A, 3C and 3F, the optical body **310** includes a gate trace **311** and a reflecting surface **312**, wherein the light path L is folded on the reflecting surface **312**, and the light path L does not pass through the gate trace **311**.

[0132] FIG. 3G is a partial enlarged view of the molded prism **300** according to the 3rd example in FIG. 3F. In FIGS. 3A, 3B and 3E to 3G, the sheet shading element **320** is closer to the light path L than the gate trace **311** to the light path L, and the sheet shading element **320** includes a first surface **321**, a second surface **322** and a first light blocking structure **323**, wherein the second surface **322** is relative to the first surface **321**, and the second surface **322** is farther away from the reflecting surface **312** than the first surface **321** from the reflecting surface **312**. The first light blocking structure **323** includes a first periphery **341**, wherein the first periphery **341** is connected to the first surface **321** and the second surface **322**, the first periphery **341** faces towards the light path L, the first periphery **341** surrounds the light path L, and the optical body **310** is physically contacted with the first periphery **341**, the first surface **321** and the second surface **322**.

[0133] In FIGS. 3B and 3E, the first periphery **341** includes a plurality of light blocking petals **342**, and the light blocking petals **342** are adjacent arranged, wherein each of the light blocking petals **342** of the first periphery **341** includes a tapered portion **343** tapering towards a direction close to the light path L, the light blocking petals **342** are covered inside the optical body **310**, and the tapered portion **343** of each of the light blocking petals **342** is tapered towards the direction close to the light path L to form a rear portion **344**. According to the 3rd example, a number of the light blocking petals **342** is 72.

[0134] In FIGS. 3A and 3D, the sheet shading element **320** can further include a cutting mark **324** farther away from the light path L than the first periphery **341** from the light path L, and the cutting mark **324** exposes on the optical body **310**.

[0135] In FIG. 3F, the optical body **310** can further include an incident surface **313** and an exit surface **314**, wherein the light path L passes through the incident surface **313**, the reflecting surface **312** and the exit surface **314** in sequence, and the two sheet shading elements **320** extend along directions away from the incident surface **313** and from the exit surface **314**, respectively.

Furthermore, the aforementioned directions are perpendicular to the incident surface **313** and the exit surface **314**.

[0136] In FIGS. 3A to 3G, the optical body **310** can further include a release structure **315**, a ridge structure **316** and an anti-reflecting surface **317**, wherein the light path L passes through the anti-reflecting surface **317**. The release structure **315** is disposed on a side of the sheet shading element **320** away from the first periphery **341**, the release structure **315** is tapered along an extending direction of the sheet shading element **320**, and at least one portion of the sheet shading element **320** is disposed on the release structure **315**, wherein the release structure **315** is tapered along a direction perpendicular to the reflecting surface **312**. The ridge structure **316** includes a plurality of recesses **361** arranged along a direction surrounding the light path L, each of the recesses **361** includes a recess end **362**, the recess end **362** is corresponding to the first periphery **341** of the first light blocking structure **323**, and each of the recesses **361** is gradually widened from the recess end **362** towards a direction away from the light path L.

[0137] In FIG. 3G, the release structure **315** can include a first release surface **351** and a second release surface **352**, wherein the first release surface **351** is gradually close to the sheet shading element **320** along the extending direction of the sheet shading element **320**, the second release surface **352** is relative to the first release surface **351**, and the sheet shading element **320** is disposed between the first release surface **351** and the second release surface **352**.

[0138] In FIGS. 3C and 3G, the molded prism **300** can further include an opaque layer **370**, wherein the opaque layer **370** is disposed on the ridge structure **316**. It should be mentioned that the cross pattern in FIGS. 3C to 3E and 3G is configured to indicate the range of the opaque layer **370**.

[0139] In FIGS. 3E and 3G, when a distance between adjacent two of the rear portions **344** is D1; a distance between adjacent two of the recess ends **362** is D2; a thickness of the sheet shading element **320** is defined via a distance between the first surface **321** and the second surface **322**, and the thickness of the sheet shading element **320** is T; a minimum distance between the first release surface **351** and the sheet shading element **320** is G1; a minimum distance between the first release surface **351** and the second release surface **352** is G12, the following conditions of Table 3 are satisfied.

TABLE-US-00003 TABLE 3 3rd example D1 (mm) 0.287 G1 (mm) 0.05 D2 (mm) 0.3 G12 (mm) 0.4 T (mm) 0.15 T/G12 0.375

[0140] It should be mentioned that the partial structures and elements are omitted in the partial drawings for clearly indicating the relationship between the optical body **310** and the sheet shading element **320**.

#### 4th Example

[0141] FIG. 4A is a three-dimensional view of a molded prism **400** according to the 4th example of

the present disclosure. FIG. 4B is a partial enlarged view of the molded prism **400** according to the 4th example in FIG. 4A. FIG. 4C is a top view of the molded prism **400** according to the 4th example in FIG. 4A. In FIGS. 4A to 4C, the molded prism **400** includes an optical body **410** and a sheet shading element **420**, wherein the optical body **410** has a light path L passing through the optical body **410**, and the sheet shading element **420** is covered via the optical body **410**.

[0142] FIG. 4D is a cross-sectional view of the molded prism **400** according to the 4th example in FIG. 4A. FIG. 4E is a partial enlarged view of the molded prism **400** according to the 4th example in FIG. 4D. In FIGS. 4A, 4D and 4E, the optical body **410** includes a gate trace **411** and a reflecting surface **412**, wherein the light path L is folded on the reflecting surface **412**, and the light path L does not pass through the gate trace **411**.

[0143] FIG. 4F is a cross-sectional schematic view of the molded prism **400** along line 4F-4F in FIG. 4D. FIG. 4G is a partial enlarged view of the molded prism **400** according to the 4th example in FIG. 4F. In FIGS. 4A and 4C to 4G, the sheet shading element **420** is closer to the light path L than the gate trace **411** to the light path L, and the sheet shading element **420** includes a first surface **421**, a second surface **422** and a first light blocking structure **423**, wherein the second surface **422** is relative to the first surface **421**, and the second surface **422** is farther away from the reflecting surface **412** than the first surface **421** from the reflecting surface **412**. The first light blocking structure **423** includes a first periphery **441**, wherein the first periphery **441** is connected to the first surface **421** and the second surface **422**, the first periphery **441** faces towards the light path L, the first periphery **441** surrounds the light path L, and the optical body **410** is physically contacted with the first periphery **441**, the first surface **421** and the second surface **422**.

[0144] In FIG. 4G, the first periphery **441** includes a plurality of light blocking petals **442**, and the light blocking petals **442** are adjacent arranged, wherein each of the light blocking petals **442** of the first periphery **441** includes a tapered portion **443** tapering towards a direction close to the light path L, the light blocking petals **442** are covered inside the optical body **410**, and the tapered portion **443** of each of the light blocking petals **442** is tapered towards the direction close to the light path L to form a rear portion **444**. According to the 4th example, a number of the light blocking petals **442** is 128.

[0145] In FIGS. 4A and 4C, the sheet shading element **420** can further include a cutting mark **424** farther away from the light path L than the first periphery **441** from the light path L, and the cutting mark **424** exposes on the optical body **410**.

[0146] In FIG. 4D, the optical body **410** can further include an incident surface **413** and an exit surface **414**, wherein the light path L passes through the incident surface **413**, the reflecting surface **412** and the exit surface **414** in sequence, the sheet shading element **420** extends along directions away from the incident surface **413** and from the exit surface **414**, and the light path L is folded at least twice occurring in the optical body **410**. Furthermore, the aforementioned direction is perpendicular to the incident surface **413** and the exit surface **414**.

[0147] In FIGS. 4A to 4G, the optical body **410** can further include a release structure **415**, wherein the release structure **415** is disposed on a side of the sheet shading element **420** away from the first periphery **441**, the release structure **415** is tapered along an extending direction of the sheet shading element **420**, at least one portion of the sheet shading element **420** is disposed on the release structure **415**, and the release structure **415** includes a ridge structure **416**. The ridge structure **416** includes a plurality of recesses **461** arranged along a direction surrounding the light path L, each of the recesses **461** includes a recess end **462**, the recess end **462** is corresponding to the first periphery **441** of the first light blocking structure **423**, and each of the recesses **461** is gradually widened from the recess end **462** towards a direction away from the light path L.

[0148] In FIG. 4B, the ridge structure **416** can further include a plurality of ribs **463** extending from the recesses **461** towards a direction away from the light path L. Therefore, the anti-reflecting ability of the optical body **410** can be further enhanced.

[0149] In FIG. 4E, the release structure **415** can further include a first release surface **451**, wherein

the first release surface **451** is gradually close to the sheet shading element **420** along the extending direction of the sheet shading element **420**.

[0150] In FIGS. **4B** and **4D**, the molded prism **400** can further include an opaque layer **470** and an exposed structure **480**, wherein the opaque layer **470** is disposed on the ridge structure **416**, the sheet shading element **420** is exposed on the exposed structure **480** to the optical body **410**, and the release structure **415** is tapered on a direction away from the exposed structure **480**. It should be mentioned that the cross pattern in FIG. **4B** is configured to indicate the range of the opaque layer **470**.

[0151] In FIGS. **4A**, **4C** and **4D**, the sheet shading element **420** can further include a second light blocking structure **426**, wherein the second light blocking structure **426** includes a second periphery (its reference numeral is omitted), the second periphery is connected to the first surface **421** and the second surface **422**, the second periphery faces towards the light path L, the second periphery surrounds the light path L, the second periphery is physically contacted with the optical body **410**, and the first light blocking structure **423** and the second light blocking structure **426** surround the light path L, respectively. The second periphery includes a plurality of light blocking petals (its reference numeral is omitted), and the light blocking petals are adjacently arranged, wherein each of the light blocking petals of the second periphery includes a tapered portion (its reference numeral is omitted) tapering towards a direction close to the light path L, and the light blocking petals are covered inside of the optical body **410**. According to the 4th example, the disposition of the first light blocking structure **423** and the disposition of the second light blocking structure **426** are the same, and will not be described again herein.

[0152] In FIGS. **4E** and **4G**, when a distance between adjacent two of the rear portions **444** is D1; a distance between adjacent two of the recess ends **462** is D2; a thickness of the sheet shading element **420** is defined via a distance between the first surface **421** and the second surface **422**, and the thickness of the sheet shading element **420** is T; a minimum distance between the first release surface **451** and the sheet shading element **420** is G1, the following conditions of Table 4 are satisfied.

TABLE-US-00004 TABLE 4 4th example D1 (mm) 0.1 G1 (mm) 0.0866 D2 (mm) 0.1 T (mm) 0.05

[0153] It should be mentioned that the partial structures and elements are omitted in the partial drawings for clearly indicating the relationship between the optical body **410** and the sheet shading element **420**.

#### 5th Example

[0154] FIG. **5A** is a three-dimensional view of a molded prism **500** according to the 5th example of the present disclosure. FIG. **5B** is a top view of the molded prism **500** according to the 5th example in FIG. **5A**. FIG. **5C** is a partial enlarged view of the molded prism **500** according to the 5th example in FIG. **5B**. In FIGS. **5A** to **5C**, the molded prism **500** includes an optical body **510** and a sheet shading element **520**, wherein the optical body **510** has a light path L passing through the optical body **510**, and the sheet shading element **520** is covered via the optical body **510**.

[0155] FIG. **5D** is a cross-sectional view of the molded prism **500** according to the 5th example in FIG. **5A**. In FIGS. **5A**, **5B** and **5D**, the optical body **510** includes a gate trace **511** and a reflecting surface **512**, wherein the light path L is folded on the reflecting surface **512**, and the light path L does not pass through the gate trace **511**.

[0156] FIG. **5E** is another cross-sectional view of the molded prism **500** according to the 5th example in FIG. **5A**. FIG. **5F** is a partial enlarged view of the molded prism **500** according to the 5th example in FIG. **5E**. In FIGS. **5A**, **5B** and **5D** to **5F**, the sheet shading element **520** is closer to the light path L than the gate trace **511** to the light path L, and the sheet shading element **520** includes a first surface **521**, a second surface **522** and a first light blocking structure **523**, wherein the second surface **522** is relative to the first surface **521**, and the second surface **522** is farther away from the reflecting surface **512** than the first surface **521** from the reflecting surface **512**. The



first light blocking structure 523 includes a first periphery 541, wherein the first periphery 541 is connected to the first surface 521 and the second surface 522, the first periphery 541 faces towards the light path L, the first periphery 541 surrounds the light path L, and the optical body 510 is physically contacted with the first periphery 541, the first surface 521 and the second surface 522. [0157] In FIG. 5C, the first periphery 541 includes a plurality of light blocking petals 542, and the light blocking petals 542 are adjacently arranged, wherein each of the light blocking petals 542 of the first periphery 541 includes a tapered portion 543 tapering towards a direction close to the light path L, the light blocking petals 542 are covered inside the optical body 510, and the tapered portion 543 of each of the light blocking petals 542 is tapered towards the direction close to the light path L to form a rear portion 544. According to the 5th example, a number of the light blocking petals 542 is 110.

[0158] In FIGS. 5A, 5B and 5D, the sheet shading element 520 can further include a cutting mark 524 farther away from the light path L than the first periphery 541 from the light path L, and the cutting mark 524 exposes on the optical body 510. Furthermore, the cutting mark 524 can further be physically contacted with the gate trace 511, and the sheet shading element 520 and the optical body 510 can be finished cutting once so as to enhance the manufacturing efficiency.

[0159] In FIG. 5D, the optical body 510 can further include an incident surface 513 and an exit surface 514, wherein the light path L passes through the incident surface 513, the reflecting surface 512 and the exit surface 514 in sequence, the sheet shading element 520 extends along a direction away from the exit surface 514, and the light path L is folded at least twice occurring in the optical body 510. Furthermore, the aforementioned direction is perpendicular to the reflecting surface 512.

[0160] In FIGS. 5E and 5F, the optical body 510 can further include a release structure 515, wherein the release structure 515 is disposed on a side of the sheet shading element 520 away from the first periphery 541, the release structure 515 is tapered along an extending direction of the sheet shading element 520, and at least one portion of the sheet shading element 520 is disposed on the release structure 515.

[0161] In FIG. 5F, the release structure 515 can include a first release surface 551 and a second release surface 552, wherein the first release surface 551 is gradually close to the sheet shading element 520 along the extending direction of the sheet shading element 520, the second release surface 552 is relative to the first release surface 551, and the sheet shading element 520 is disposed between the first release surface 551 and the second release surface 552.

[0162] In FIG. 5E, the molded prism 500 can further include an exposed structure 580, wherein the sheet shading element 520 is exposed on the exposed structure 580 to the optical body 510, and the release structure 515 is tapered on a direction away from the exposed structure 580.

[0163] In FIGS. 5A, 5B and 5D, the first periphery 541 of the first light blocking structure 523 is closed and surrounds the light path L.

[0164] In FIGS. 5C and 5F, when a distance between adjacent two of the rear portions 544 is D1; a thickness of the sheet shading element 520 is defined via a distance between the first surface 521 and the second surface 522, and the thickness of the sheet shading element 520 is T; a minimum distance between the first release surface 551 and the sheet shading element 520 is G1; a minimum distance between the first release surface 551 and the second release surface 552 is G12, the following conditions of Table 5 are satisfied.

TABLE-US-00005 TABLE 5 5th example D1 (mm) 0.175 T (mm) 0.2 G1 (mm) 0.1 T/G12 0.4 G12 (mm) 0.5

[0165] It should be mentioned that the partial structures and elements are omitted in the partial drawings for clearly indicating the relationship between the optical body 510 and the sheet shading element 520.

#### 6th Example

[0166] FIG. 6A is a three-dimensional view of a molded prism 600 according to the 6th example of the present disclosure, FIG. 6B is a side view of the molded prism 600 according to the 6th

example in FIG. 6A, FIG. 6C is a partial enlarged view of the molded prism **600** according to the 6th example in FIG. 6B, FIG. 6D is another side view of the molded prism **600** according to the 6th example in FIG. 6A, and FIG. 6E is a partial enlarged view of the molded prism **600** according to the 6th example in FIG. 6D. In FIGS. 6A to 6E, the molded prism **600** includes an optical body **610** and a sheet shading element **620**, wherein the optical body **610** has a light path L passing through the optical body **610**, and the sheet shading element **620** is covered via the optical body **610**.

[0167] FIG. 6F is a cross-sectional view of the molded prism **600** according to the 6th example in FIG. 6A. In FIGS. 6A, 6B, 6D and 6F, the optical body **610** includes a gate trace **611** and a reflecting surface **612**, wherein the light path L is folded on the reflecting surface **612**, and the light path L does not pass through the gate trace **611**.

[0168] FIG. 6G is a partial enlarged view of the molded prism **600** according to the 6th example in FIG. 6F. In FIGS. 6B, 6F and 6G, the sheet shading element **620** is closer to the light path L than the gate trace **611** to the light path L, and the sheet shading element **620** includes a first surface **621**, a second surface **622** and a first light blocking structure **623**, wherein the second surface **622** is relative to the first surface **621**, and the second surface **622** is farther away from the reflecting surface **612** than the first surface **621** from the reflecting surface **612**. The first light blocking structure **623** includes a first periphery **641**, wherein the first periphery **641** is connected to the first surface **621** and the second surface **622**, the first periphery **641** faces towards the light path L, the first periphery **641** surrounds the light path L, and the optical body **610** is physically contacted with the first periphery **641**, the first surface **621** and the second surface **622**.

[0169] In FIG. 6C, the first periphery **641** includes a plurality of light blocking petals **642**, and the light blocking petals **642** are adjacently arranged, wherein each of the light blocking petals **642** of the first periphery **641** includes a tapered portion **643** tapering towards a direction close to the light path L, the light blocking petals **642** are covered inside the optical body **610**, and the tapered portion **643** of each of the light blocking petals **642** is tapered towards the direction close to the light path L to form a rear portion **644**. According to the 6th example, a number of the light blocking petals **642** is 176.

[0170] In FIGS. 6B and 6F, the sheet shading element **620** can further include a cutting mark **624** farther away from the light path L than the first periphery **641** from the light path L, and the cutting mark **624** exposes on the optical body **610**.

[0171] In FIG. 6F, the optical body **610** can further include an incident surface **613** and an exit surface **614**, wherein the light path L passes through the incident surface **613**, the reflecting surface **612** and the exit surface **614** in sequence, and the light path L is folded at least twice occurring in the optical body **610**.

[0172] In FIGS. 6A, 6D, 6E and 6F, the optical body **610** can further include a release structure **615** and a ridge structure **616**, wherein the release structure **615** is disposed on a side of the sheet shading element **620** away from the first periphery **641**, the release structure **615** is tapered along an extending direction of the sheet shading element **620**, and at least one portion of the sheet shading element **620** is disposed on the release structure **615**. Furthermore, the release structure **615** is tapered along the directions perpendicular to the exit surface **614**. The ridge structure **616** can include a plurality of recesses **661** arranged along a direction surrounding the light path L, each of the recesses **661** includes a recess end **662**, the recess end **662** is corresponding to the first periphery **641** of the first light blocking structure **623**, and each of the recesses **661** is gradually widened from the recess end **662** towards a direction away from the light path L.

[0173] In FIG. 6E, the ridge structure **616** can further include a plurality of ribs **663** extending from the recesses **661** towards a direction away from the light path L.

[0174] In FIG. 6G, the release structure **615** can include a first release surface **651** and a second release surface **652**, wherein the first release surface **651** is gradually close to the sheet shading element **620** along the extending direction of the sheet shading element **620**, the second release surface **652** is relative to the first release surface **651**, and the sheet shading element **620** is

disposed between the first release surface **651** and the second release surface **652**.

[0175] In FIGS. **6D** and **6E**, the molded prism **600** can further include an opaque layer **670**, wherein the opaque layer **670** is disposed on the ridge structure **616**. It should be mentioned that the cross pattern in FIGS. **6D** and **6E** are configured to indicate the range of the opaque layer **670**. [0176] In FIGS. **6B** and **6F**, the first periphery **641** of the first light blocking structure **623** is closed and surrounds the light path L.

[0177] In FIGS. **60**, **6E** and **6G**, when a distance between adjacent two of the rear portions **644** is D1; a distance between adjacent two of the recess ends **662** is D2; a thickness of the sheet shading element **620** is defined via a distance between the first surface **621** and the second surface **622**, and the thickness of the sheet shading element **620** is T; a minimum distance between the first release surface **651** and the sheet shading element **620** is G1; a minimum distance between the first release surface **651** and the second release surface **652** is G12, the following conditions of Table 6 are satisfied.

TABLE-US-00006 TABLE 6 6th example D1 (mm) 0.036 G12 (mm) 0.335 D2 (mm) 0.057 T (mm) 0.15 G1 (mm) 0.158 T/G12 0.448

[0178] It should be mentioned that the partial structures and elements are omitted in the partial drawings for clearly indicating the relationship between the optical body **610** and the sheet shading element **620**.

#### 7th Example

[0179] FIG. **7A** is a three-dimensional view of a molded prism **700** according to the 7th example of the present disclosure, FIG. **7B** is a partial enlarged view of the molded prism **700** according to the 7th example in FIG. **7A**, FIG. **7C** is a top view of the molded prism **700** according to the 7th example in FIG. **7A**, FIG. **7D** is a partial enlarged view of the molded prism **700** according to the 7th example in FIG. **7C**, and FIG. **7E** is a side view of the molded prism **700** according to the 7th example in FIG. **7A**. In FIGS. **7A** to **7E**, the molded prism **700** includes an optical body **710** and a sheet shading element **720**, wherein the optical body **710** has a light path L passing through the optical body **710**, and the sheet shading element **720** is covered via the optical body **710**.

[0180] FIG. **7F** is a cross-sectional view of the molded prism **700** according to the 7th example in FIG. **7E**. In FIGS. **7C** and **7F**, the optical body **710** includes a gate trace **711** and a reflecting surface **712**, wherein the light path L is folded on the reflecting surface **712**, and the light path L does not pass through the gate trace **711**.

[0181] FIG. **7G** is a partial enlarged view of the molded prism **700** according to the 7th example in FIG. **7F**. In FIGS. **7A** to **7C**, **7F** and **7G**, the sheet shading element **720** is closer to the light path L than the gate trace **711** to the light path L, and the sheet shading element **720** includes a first surface **721**, a second surface **722** and a first light blocking structure **723**, wherein the second surface **722** is relative to the first surface **721**, and the second surface **722** is farther away from the reflecting surface **712** than the first surface **721** from the reflecting surface **712**. The first light blocking structure **723** includes a first periphery **741**, wherein the first periphery **741** is connected to the first surface **721** and the second surface **722**, the first periphery **741** faces towards the light path L, the first periphery **741** is closed and surrounds the light path L, and the optical body **710** is physically contacted with the first periphery **741**, the first surface **721** and the second surface **722**.

[0182] In FIGS. **7B** and **7D**, the first periphery **741** includes a plurality of light blocking petals **742**, and the light blocking petals **742** are adjacently arranged, wherein each of the light blocking petals **742** of the first periphery **741** includes a tapered portion **743** tapering towards a direction close to the light path L, the light blocking petals **742** are covered inside the optical body **710**, and the tapered portion **743** of each of the light blocking petals **742** is tapered towards the direction close to the light path L to form a rear portion **744**. According to the 7th example, a number of the light blocking petals **742** is 72. Furthermore, a thickness of each of the light blocking petals **742** gradually increases towards a direction away from the light path L.

[0183] In FIGS. **7A** and **7C**, the sheet shading element **720** can further include a cutting mark **724**

farther away from the light path L than the first periphery **741** from the light path L, and the cutting mark **724** exposes on the optical body **710**.

[0184] In FIG. 7F, the optical body **710** can further include an incident surface **713** and an exit surface **714**, wherein the light path L passes through the incident surface **713**, the reflecting surface **712** and the exit surface **714** in sequence, the sheet shading element **720** extends along a direction away from the exit surface **714**, and the light path L is folded at least twice occurring in the optical body **710**. Furthermore, the aforementioned direction is perpendicular to the exit surface **714**.

[0185] The optical body **710** can further include a release structure **715** disposed on a side of the sheet shading element **720** away from the first periphery **741**, the release structure **715** is tapered along an extending direction of the sheet shading element **720**, and at least one portion of the sheet shading element **720** is disposed on the release structure **715**.

[0186] In FIG. 7G, the release structure **715** can include a first release surface **751**, wherein the first release surface **751** is gradually close to the sheet shading element **720** along the extending direction of the sheet shading element **720**.

[0187] In FIGS. 7A, 7C, 7E and 7F, the sheet shading element **720** can further include at least one bending portion **725** and a second light blocking structure **726**, wherein at least one portion of the first periphery **741** is disposed on the bending portion **725**, the second light blocking structure **726** includes a second periphery (its reference numeral is omitted), the second periphery is connected to the first surface **721** and the second surface **722**, the second periphery faces towards the light path L, the second periphery is opened and surrounds the light path L, and the second periphery and the optical body **710** are physically contacted. The second periphery includes a plurality of light blocking petals **746**, and the light blocking petals **746** are adjacently arranged, wherein each of the light blocking petals **746** of the second periphery includes a tapered portion **747** tapering towards a direction close to the light path L, and the light blocking petals **746** are covered inside of the optical body **710**. According to the 7th example, a number of the light blocking petals **746** is 42.

[0188] In FIGS. 7D and 7G, when a distance between adjacent two of the rear portions **744** is D1; a thickness of the sheet shading element **720** is defined via a distance between the first surface **721** and the second surface **722**, and the thickness of the sheet shading element **720** is T; a minimum distance between the first release surface **751** and the sheet shading element **720** is G1, the following conditions of Table 7 are satisfied.

TABLE-US-00007 TABLE 7 7th example D1 (mm) 0.32 T (mm) 0.15 G1 (mm) 0.06

[0189] It should be mentioned that the partial structures and elements are omitted in the partial drawings for clearly indicating the relationship between the optical body **710** and the sheet shading element **720**.

#### 8th Example

[0190] FIG. 8 is a schematic view of a camera module **80** according to the 8th example of the present disclosure. In FIG. 8, the camera module **80** includes a molded prism **81**, a first carrier **82**, a second carrier **83**, an image sensor module **84** and a camera **85**, wherein the molded prism **81** is disposed in the first carrier **82**, the camera **85** is disposed in the second carrier **83**, the image sensor module **84** is disposed relative to the camera **85**, and an optical body (its reference numeral is omitted) of the molded prism **81** has a light path L. It should be mentioned that a number of lens element, a position, and a shape of the camera **85** are only for example, and the present disclosure is not limited thereto.

[0191] The molded prism **81** can include an exposed structure **880**, wherein at least one portion of the first carrier **82** is disposed on the exposed structure **880** so as to improve the combination of the first carrier **82** and the molded prism **81**, and the assembling defection can be reduced. Specifically, a connecting element **821** of the first carrier **82** is disposed on the exposed structure **880** of the molded prism **81**. The aforementioned arrangement can be achieved through electric riveting, gluing, ultrasonic bonding and so on, but the present disclosure is not limited thereto. The configuration of additional carriers can be reduced through a directly connection between the

exposed structure **880** and the connecting element **821**.

[0192] Further, the exposed structure **280** of the molded prism **200** of the 2nd example can be relative to the exposed structure **880** of the camera module **80** of the 8th example, and the molded prism **200** of the 2nd example can be applied to the camera module **80** of the 8th example, that is the structural detail of the molded prism **200** of the 2nd example and the structural detail of the molded prism **81** of the 8th example are the same.

#### 9th Example

[0193] FIG. **9** is a schematic view of a camera module **90** according to the 9th example of the present disclosure. In FIG. **9**, the camera module **90** includes a molded prism **91**, a carrier **92**, a camera driver **93**, an image sensor driver **941**, an image sensor **942**, an image signal processor (ISP) **943**, a filter element **944** and a camera **95**, wherein the carrier **92** carries both of the molded prism **91** and the camera **95**. The camera driver **93** is configured for the zooming function, the image sensor driver **941** is configured for providing the image stabilizing function, the image sensor driver **941** is connected to the image sensor **942** and the image signal processor **943**, the filter element **944** is disposed between the camera **95** and the molded prism **91**, and an optical body (its reference numeral is omitted) of the molded prism **91** has a light path L. It should be mentioned that a number of lens element, a position, and a shape of the camera **95** are only for example, and the present disclosure is not limited thereto. Further, the image sensor driver **941** can simultaneously include functions of image computing, driver collaborative computing, and heat dissipating, but the present disclosure is not limited thereto.

[0194] The molded prism **91** can include an exposed structure **980**, wherein at least one portion of the carrier **92** is disposed on the exposed structure **980**. In detail, the molded prism **91** is disposed on a rack **921** of the carrier **92** via the exposed structure **980**. The aforementioned arrangement can be achieved through electric riveting, gluing, ultrasonic bonding and so on, but the present disclosure is not limited thereto.

[0195] Further, the molded prism **400** of the 4th example can be applied to the camera module **90** of the 9th example, that is, the structural detail of the molded prism **400** of the 4th example and the structural detail of the molded prism **91** of the 9th example are the same.

#### 10th Example

[0196] FIG. **10** is a schematic view of a camera module **1000** according to the 10th example of the present disclosure. In FIG. **10**, the camera module **1000** includes a molded prism **1010**, a carrier **1020**, an image sensor module **1030**, a retainer **1040** and a camera **1050**, wherein the carrier **1020** carries all of the molded prism **1010**, the image sensor module **1030** and the camera **1050** so as to reduce the geometric tolerance superposition during assembly, and an optical body (its reference numeral is omitted) of the molded prism **1010** has a light path L. It should be mentioned that a number of lens element, a position, and a shape of the camera **1050** are only for example, and the present disclosure is not limited thereto.

[0197] The molded prism **1010** can include two exposed structures **1081**, **1082**, wherein at least one portion of the carrier **1020** is disposed on the exposed structures **1081**, **1082**. In detail, the retainer **1040** is simultaneously and physically contacted with the molded prism **1010** and the exposed structures **1081**, **1082**, and the retainer **1040** is fixed in the carrier **1020** with an adhesive G so as to fix the molded prism **1010** in the carrier **1020**.

[0198] Further, the molded prism **700** of the 7th example can be applied to the camera module **1000** of the 10th example, that is the structural detail of the molded prism **700** of the 7th example and the structural detail of the molded prism **1010** of the 10th example are the same.

#### 11th Example

[0199] FIG. **11** is a schematic view of a camera module **1100** according to the 11th example of the present disclosure. In FIG. **11**, the camera module **1100** includes a molded prism **1110**, a carrier **1120** and an electric element **1130**, wherein the carrier **1120** carries the molded prism **1110** and the electric element **1130**, and an optical body (its reference numeral is omitted) of the molded prism

**1110** has a light path **L**.

[0200] In detail, the sheet shading element (its reference numeral is omitted) of the molded prism **1110** can be disposed on the carrier **1120** so as to have the light blocking function. Moreover, the carrier **1120** can further provide the functions of supporting and shielding, and the carrier **1120** can further carry the electric element **1130**, wherein the electric element **1130** can be an image sensor, computing element and passive element, but the present disclosure is not limited thereto.

[0201] The molded prism **1110** can include an exposed structure **1180**, wherein at least one portion of the carrier **1120** is disposed on the exposed structure **1180**.

[0202] Further, the molded prism **600** of the 6th example can be applied to the camera module **1100** of the 11th example, that is the structural detail of the molded prism **600** of the 6th example and the structural detail of the molded prism **1110** of the 11th example are the same.

#### 12th Example

[0203] FIG. **12A** is a schematic view of an electronic device **1200** according to the 12th example of the present disclosure, and FIG. **12B** is another schematic view of the electronic device **1200** according to the 12th example in FIG. **12A**. In FIGS. **12A** and **12B**, the electronic device **1200** is a smartphone, and the electronic device **1200** includes a camera module and an image-capturing control interface **1210**, wherein the camera module includes a molded prism. Moreover, each of the molded prism can be the molded prisms according to the aforementioned 1st example to the 11th example, but the present disclosure is not limited thereto.

[0204] According to the 12th example, the camera modules are a front camera module **1221**, a wide angle camera module **1222**, a ultra-wide angle camera module **1223**, a micro camera module **1224**, a telephoto camera module **1225** and a Time-Of-Flight (TOF) module **1226**, wherein the TOF module **1226** can be another camera modules with other functions, but the disposition is not limited thereto.

[0205] In detail, according to the 12th example, the front camera module **1221** and the TOF module **1226** are disposed on a front of the electronic device **1200**, and the wide angle camera module **1222**, the ultra-wide angle camera module **1223**, the micro camera module **1224** and the telephoto camera module **1225** are disposed on a back of the electronic device **1200**.

[0206] The image-capturing control interface **1210** can be a touch screen for displaying the scene and having the touch function, and the shooting angle can be manually adjusted. In detail, the image-capturing control interface **1210** includes an image replay button **1211**, a camera module switching button **1212**, a focus capturing button **1213**, an integrated menu button **1214** and a zoom control button **1215**. Furthermore, users enter a shooting mode via the image-capturing control interface **1210** of the electronic device **1200**, the camera module switching button **1212** can be flexibly configured to switch one of the front camera module **1221**, the wide angle camera module **1222**, the ultra-wide angle camera module **1223**, the micro camera module **1224** and the telephoto camera module **1225** to capture the image, the zoom control button **1215** is configured to adjust the zoom, the focus capturing button **1213** is configured to be undergo image capturing after capturing the images and confirming one of the front camera module **1221**, the wide angle camera module **1222**, the ultra-wide angle camera module **1223**, the micro camera module **1224** and the telephoto camera module **1225** to capture the image, the users can view the images by the image replay button **1211** after undergoing image capturing, and the integrated menu button **1214** is configured to adjust the details of the image capturing (such as timed photo, photo ratio, and etc.).

[0207] The electronic device **1200** can further include a reminding light **1230**, the reminding light **1230** is disposed on the front of the electronic device **1200**, and the reminding light **1230** can be configured to remind the users of unread messages, missed calls and the condition of the phone.

[0208] Moreover, after entering the shooting mode via the image-capturing control interface **1210** of the electronic device **1200**, the imaging light is gathered on the image sensor via the camera module, and an electronic signal about an image is output to an image signal processor (its reference numeral is omitted) of a single chip system **1250**. The single chip system **1250** can

further include a random access memory (RAM) (its reference numeral is omitted), a central processing unit (its reference numeral is omitted) and a storage unit (its reference numeral is omitted). Also, the single chip system **1250** can further include, but not be limited to, a display, a control unit, a read-only memory (ROM), or the combination thereof.

[0209] Further, the electronic device **1200** can further include an image software processor and an image signal processor, and further integrates the image software processor, the image signal processor, a position locator, a transmit signal processor, a gyroscope, a storage unit and a random access memory in the single chip system **1250**.

[0210] To meet a specification of the electronic device **1200**, the electronic device **1200** can further include an optical anti-shake mechanism (not shown). Furthermore, the electronic device **1200** can further include at least one focusing assisting module **1260** and at least one sensing element (not shown). The focusing assisting module **1260** can include a flash element **1261** for compensating a color temperature, an infrared distance measurement component (not shown), a laser focus module (not shown), etc. The sensing element can have functions for sensing physical momentum and kinetic energy, such as an accelerator, a gyroscope, a Hall Effect Element, a position locator, a signal transmitter module, to sense shaking or jitters applied by hands of the user or external environments. Accordingly, the electronic device **1200** equipped with an auto-focusing mechanism and the optical anti-shake mechanism can be enhanced to achieve the superior image quality. Furthermore, the electronic device **1200** according to the present disclosure can have a capturing function with multiple modes, such as taking optimized selfies, high dynamic range (HDR) under a low light condition, 4K resolution recording, etc. Furthermore, the users can visually see a captured image of the camera through the image-capturing control interface **1210** and manually operate the view finding range on the image-capturing control interface **1210** to achieve the autofocus function of what you see is what you get.

[0211] Moreover, the camera module, the optical anti-shake mechanism, the sensing element, the focusing assisting module **1260** and an electronic element **1242** can be disposed on a circuit board **1240** and electrically connected to the associated components via a connector **1241** to perform a capturing process, wherein the circuit board **1240** can be a flexible printed circuit board (FPC). Since the current electronic devices, such as smart phones, have a tendency of being compact, the way of firstly disposing the camera module and related components on the flexible printed circuit board and secondly integrating the circuit thereof into the main board of the electronic device via the connector can satisfy the requirements of the mechanical design and the circuit layout of the limited space inside the electronic device, and obtain more margins. The autofocus function of the image capturing apparatus can also be controlled more flexibly via the touch screen of the electronic device. According to the 12th example, the sensing element and the focusing assisting module **1260** are disposed on the circuit board **1240** and at least one other flexible printed circuit board (not shown) and electrically connected to the associated components, such as the image signal processor, via corresponding connectors to perform the capturing process. In other examples (not shown), the sensing elements and the focusing assisting modules can also be disposed on the main board of the electronic device or carrier boards of other types according to requirements of the mechanical design and the circuit layout.

[0212] Moreover, the image of the certain range with the high resolution can be captured via the wide angle camera module **1222**, and the wide angle camera module **1222** has the function of the high resolution and the low deformation. Comparing with the image captured via the wide angle camera module **1222**, the image captured via the telephoto camera module **1225** has narrower visual angle and narrower depth of field. Hence, the telephoto camera module **1225** can be configured to capture the moving targets, that is, the telephoto camera module **1225** can be driven via an actuator (not shown) of the electronic device **1200** to quick and continuous auto focus the moving targets so as to make the image of the moving targets is not fuzzy owing to defocus. Comparing with the image captured via the wide angle camera module **1222**, the image captured

via the ultra-wide angle camera module **1223** has wider visual angle and wider depth of field, but the image captured via the ultra-wide angle camera module **1223** also has greater distortion. [0213] In particular, the zooming function can be obtained via the electronic device **1200**, when the scene is captured via the camera module with different focal lengths cooperated with the function of image processing.

#### 13th Example

[0214] FIG. **13** is a schematic view of an electronic device applied to a computer **1300** according to the 13th example of the present disclosure. In FIG. **13**, the electronic device (its reference numeral is omitted) includes a camera module and an infrared transmitter module **1330**, wherein the camera module includes a molded prism. Moreover, each of the molded prism can be the molded prisms according to the aforementioned 1st example to the 11th example, but the present disclosure is not limited thereto.

[0215] According to the 13th example, the camera modules are a webcam camera module **1310** and an infrared camera module **1320**, and the infrared camera module **1320** is configured to the space recognition, the distance measurement and so on.

#### 14th Example

[0216] FIG. **14** is a schematic view of an electronic device applied to a wearable device **1400** according to the 14th example of the present disclosure. In FIG. **14**, the electronic device (its reference numeral is omitted) includes a camera module, wherein the camera module includes a molded prism. Moreover, the molded prism can be the molded prisms according to the aforementioned 1st example to the 11th example, but the present disclosure is not limited thereto.

[0217] According to the 14th example, the camera module is a webcam camera module **1410**.

[0218] The foregoing description, for purpose of explanation, has been described with reference to specific embodiments. It is to be noted that Tables show different data of the different embodiments; however, the data of the different embodiments are obtained from experiments. The embodiments were chosen and described in order to best explain the principles of the disclosure and its practical applications, to thereby enable others skilled in the art to best utilize the disclosure and various embodiments with various modifications as are suited to the particular use contemplated. The embodiments depicted above and the appended drawings are exemplary and are not intended to be exhaustive or to limit the scope of the present disclosure to the precise forms disclosed. Many modifications and variations are possible in view of the above teachings.

## Claims

1. A molded prism, comprising: an optical body, having a light path passing through the optical body, and comprising: a reflecting surface, the light path folded on the reflecting surface; and a gate trace, the light path not passing through the gate trace; and a sheet shading element covered via the optical body, wherein the sheet shading element is closer to the light path than the gate trace to the light path, and the sheet shading element comprises: a first surface; a second surface relative to the first surface, and the second surface farther away from the reflecting surface than the first surface from the reflecting surface; and a first light blocking structure, comprising: a first periphery connected to the first surface and the second surface, the first periphery facing towards the light path, the first periphery surrounding the light path, and the optical body physically contacted with the first periphery, the first surface and the second surface; wherein the first periphery comprises a plurality of light blocking petals, a number of the light blocking petals of the first periphery is between 14 and 250, and the light blocking petals are adjacent arranged; wherein each of the light blocking petals of the first periphery comprises a tapered portion tapering towards a direction close to the light path, and the light blocking petals are covered inside the optical body.

2. The molded prism of claim 1, wherein the tapered portion of each of the light blocking petals is tapered towards the direction close to the light path to form a rear portion; wherein a distance



between adjacent two of the rear portions is  $D1$ , and the following condition is satisfied:  
 $0.018\text{mm} \leq D1 \leq 0.8\text{mm}$ .

3. The molded prism of claim 2, wherein the distance between the adjacent two of the rear portions is  $D1$ , and the following condition is satisfied:  $0.02\text{ mm} \leq D1 \leq 0.6\text{ mm}$ .

4. The molded prism of claim 1, wherein a thickness of the sheet shading element is defined via a distance between the first surface and the second surface, the thickness of the sheet shading element is  $T$ , and the following condition is satisfied:  $0.03\text{mm} \leq T \leq 0.5\text{mm}$ .

5. The molded prism of claim 1, wherein the sheet shading element further comprises: a cutting mark farther away from the light path than the first periphery from the light path, and the cutting mark exposing on the optical body.

6. The molded prism of claim 1, wherein the optical body further comprises: a release structure disposed on a side of the sheet shading element away from the first periphery, wherein the release structure is tapered along an extending direction of the sheet shading element, and at least one portion of the sheet shading element is disposed on the release structure; wherein the release structure comprises a first release surface gradually close to the sheet shading element along the extending direction of the sheet shading element, a minimum distance between the first release surface and the sheet shading element is  $G1$ , and the following condition is satisfied:  
 $0.03\text{mm} \leq G1 \leq 0.24\text{mm}$ .

7. The molded prism of claim 6, wherein the release structure further comprises: a second release surface relative to the first release surface, and the sheet shading element disposed between the first release surface and the second release surface; wherein a minimum distance between the first release surface and the second release surface is  $G12$ ; a thickness of the sheet shading element is defined via a distance between the first surface and the second surface, the thickness of the sheet shading element is  $T$ , and the following condition is satisfied:  $0.15 \leq T / G12 \leq 0.68$ .

8. The molded prism of claim 1, wherein the optical body further comprises an incident surface and an exit surface, and the light path passes through the incident surface, the reflecting surface and the exit surface in sequence; wherein the sheet shading element extends along a direction away from one of the incident surface, the reflecting surface and the exit surface.

9. The molded prism of claim 8, wherein the direction is perpendicular to the one of the incident surface, the reflecting surface and the exit surface.

10. The molded prism of claim 1, wherein the optical body further comprises: a ridge structure comprising a plurality of recesses arranged along a direction surrounding the light path, wherein each of the recesses comprises a recess end, the recess end is corresponding to the first periphery of the first light blocking structure, and each of the recesses is gradually widened from the recess end towards a direction away from the light path; wherein a distance between adjacent two of the recess ends is  $D2$ , and the following condition is satisfied:  $0.028\text{mm} \leq D2 \leq 0.6\text{mm}$ .

11. The molded prism of claim 10, wherein the distance between the adjacent two of the recess ends is  $D2$ , and the following condition is satisfied:  $0.038\text{mm} \leq D2 \leq 0.45\text{mm}$ .

12. The molded prism of claim 10, further comprising: an opaque layer disposed on the ridge structure.

13. The molded prism of claim 10, wherein the ridge structure further comprises: a plurality of ribs extending from the recesses towards a direction away from the light path.

14. The molded prism of claim 1, wherein the sheet shading element further comprises: at least one bending portion, at least one portion of the first periphery disposed on the at least one bending portion.

15. The molded prism of claim 1, wherein the sheet shading element further comprises: a second light blocking structure comprising a second periphery, wherein the second periphery is connected to the first surface and the second surface, the second periphery faces towards the light path, the second periphery surrounds the light path, and the second periphery and the optical body are physically contacted; wherein the second periphery comprises a plurality of light blocking petals, a

number of the light blocking petals of the second periphery is between 14 and 250, and the light blocking petals are adjacently arranged; wherein each of the light blocking petals of the second periphery comprises a tapered portion tapering towards a direction close to the light path, and the light blocking petals are covered inside of the optical body.

**16.** The molded prism of claim 1, wherein a number of the sheet shading element is plurality.

**17.** The molded prism of claim 1, wherein a thickness of each of the light blocking petals gradually increases towards a direction away from the light path.

**18.** The molded prism of claim 1, wherein the light path is folded at least twice occurring in the optical body.

**19.** The molded prism of claim 1, wherein the optical body further comprises: an anti-reflecting surface, the light path passing through the anti-reflecting surface; wherein a maximum reflectivity of the anti-reflecting surface in a wavelength range of 450 nm to 750 nm is less than or equal to 0.49%.

**20.** The molded prism of claim 1, wherein an infrared light is partially filtered via the molded prism, and a wavelength providing a transmittance of the molded prism being 50% is between 600 nm and 700 nm.

**21.** A camera module, comprising: the molded prism of claim 1.

**22.** The camera module of claim 21, further comprising: a carrier; wherein the molded prism further comprises an exposed structure, the sheet shading element is exposed on the exposed structure to the optical body, and at least one portion of the carrier is disposed on the exposed structure.

**23.** An electronic device, comprising: the camera module of claim 21.

**24.** A molded prism, comprising: an optical body, having a light path passing through the optical body, and comprising: a reflecting surface, the light path folded on the reflecting surface; and a gate trace, the light path not passing through the gate trace; and a sheet shading element covered via the optical body, wherein the sheet shading element is closer to the light path than the gate trace to the light path, and the sheet shading element comprises: a first surface; a second surface relative to the first surface, and the second surface farther away from the reflecting surface than the first surface from the reflecting surface; and a first light blocking structure, comprising: a first periphery connected to the first surface and the second surface, the first periphery facing towards the light path, the first periphery surrounding the light path, and the optical body physically contacted with the first periphery, the first surface and the second surface; wherein the optical body further comprises a release structure disposed on a side of the sheet shading element away from the first periphery, and the release structure is tapered along an extending direction of the sheet shading element; wherein at least one portion of the sheet shading element is disposed on the release structure.

**25.** The molded prism of claim 24, wherein the release structure comprises a first release surface gradually close to the sheet shading element along an extending direction of the sheet shading element, a minimum distance between the first release surface and the sheet shading element is  $G1$ , and the following condition is satisfied:  $0.02\text{mm} \leq G1 \leq 0.32\text{mm}$ .

**26.** The molded prism of claim 24, wherein the release structure comprises: a first release surface; and a second release surface relatively disposed to the first release surface, and the sheet shading element disposed between the first release surface and the second release surface; wherein a minimum distance between the first release surface and the second release surface is  $G12$ ; a thickness of the sheet shading element is defined by a distance between the first surface and the second surface, the thickness of the sheet shading element is  $T$ , and the following condition is satisfied:  $0.12 \leq T / G12 \leq 0.91$ .

**27.** The molded prism of claim 24, wherein the optical body further comprises an incident surface and an exit surface, and the light path passes through the incident surface, the reflecting surface and the exit surface in sequence; wherein the sheet shading element extends along a direction away

from one of the incident surface, the reflecting surface and the exit surface, and the release structure is tapered on the direction.

**28.** The molded prism of claim 24, wherein the release structure comprises: a ridge structure comprising a plurality of recesses arranged along a direction surrounding the light path, wherein each of the recesses comprises a recess end, the recess end is corresponding to the first periphery of the first light blocking structure, and each of the recesses is gradually widened from the recess end towards a direction away from the light path; wherein a distance between adjacent two of the recess ends is  $D2$ , and the following condition is satisfied:  $0.028\text{mm} \leq D2 \leq 0.6\text{mm}$ .

**29.** The molded prism of claim 28, wherein the ridge structure further comprises: a plurality of ribs extending from the recesses towards a direction away from the light path.

**30.** The molded prism of claim 24, wherein the sheet shading element further comprises: a cutting mark farther away from the light path than the first periphery from the light path, and the cutting mark exposing on the optical body.

**31.** The molded prism of claim 24, wherein the sheet shading element further comprises: at least one bending portion, at least one portion of the first periphery disposed on the at least one bending portion.

**32.** The molded prism of claim 24, wherein the sheet shading element further comprises: a second light blocking structure comprising a second periphery, wherein the second periphery is connected to the first surface and the second surface, the second periphery faces towards the light path, the second periphery surrounds the light path, and the second periphery and the optical body are physically contacted.

**33.** The molded prism of claim 24, wherein the optical body further comprises: at least one anti-reflecting surface, wherein a maximum reflectivity of the at least one anti-reflecting surface in a wavelength range of 450 nm to 750 nm is less than or equal to 0.49%.

**34.** The molded prism of claim 24, wherein an infrared light is partially filtered via the molded prism, and a wavelength providing a transmittance of the molded prism being 50% is between 600 nm and 700 nm.

**35.** The molded prism of claim 24, further comprising: an exposed structure, wherein the sheet shading element is exposed on the exposed structure to the optical body, and the exposed structure is tapered in a direction away from the exposed structure.

---