

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250278561

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

KATO; Takumi

DEFECT KNOWLEDGE CIRCULATION SYSTEM

Abstract

A method for performing defect summarization, the method comprising: receiving, by a processor, defect records associated with an operation; receiving, by the processor, work information associated with the operation linking, by the processor, the defect records and the work information using a first Artificial Intelligence (AI) model to generate linked information; and performing, by the processor, summary generation using a second AI model to generate work summary using summarization keywords, the defect records, and the work information, as input to the second AI model.

Inventors: KATO; Takumi (Santa Clara, CA)

Applicant: HITACHI, Ltd. (Tokyo, JP)

Family ID: 93704530

Appl. No.: 18/593718

Filed: March 01, 2024

Publication Classification

Int. Cl.: G06F40/20 (20200101); G06F16/34 (20250101)

U.S. Cl.:

CPC G06F40/20 (20200101); G06F16/345 (20190101);

Background/Summary

BACKGROUND

Field

[0001] The present disclosure is generally directed to a method and a system for performing defect summarization.

Related Art

[0002] Factory workers regularly perform inspections during the manufacturing processes, including the assembly and the final inspection before shipping. During the inspections, they often discover defects that need to be fixed. It is important to find the defects at each manufacturing phase prior to shipping. It is also essential to avoid the same defects in future manufacturing processes.

[0003] It is essential to reflect the inspection results on future work instructions for manufacturing and inspection tasks. The inspection results usually include some notes describing the defects found. Although it is an essential source of knowledge to improve the processes to avoid future defects, the notes can be easily wasted since organizing notes and inspecting the results is a great burden on the workers. Existing systems, like MES (Manufacturing Execution System), can help workers automate and record the inspection results. However, they need more technologies to organize the notes and the knowledge that can be extracted from them.

[0004] In the related art, a method for performing defect detection through images is disclosed. Polygons are applied over the images for defect-pattern detection and collection. While defect detections help workers fix the defects, it does not help the workers understand which processes may have caused the defect.

[0005] There exists a need for a method and a system that is capable of intelligently circulating defect knowledge and performing defect summarization based on the circulated defect knowledge.

SUMMARY

[0006] Aspects of the present disclosure involve an innovative method for performing defect summarization. The method may include receiving, by a processor, defect records associated with an operation; receiving, by the processor, work information associated with the operation; linking, by the processor, the defect records and the work information using a first Artificial Intelligence (AI) model to generate linked information; and performing, by the processor, summary generation using a second AI model to generate work summary using summarization keywords, the defect records, and the work information, as input to the second AI model.

[0007] Aspects of the present disclosure involve an innovative non-transitory computer readable medium, storing instructions for performing defect summarization. The instructions may include receiving defect records associated with an operation; receiving work information associated with the operation; linking the defect records and the work information using a first AI model to generate linked information; and performing summary generation using a second AI model to generate work summary using summarization keywords, the defect records, and the work information, as input to the second AI model.

[0008] Aspects of the present disclosure involve an innovative server system for performing defect summarization. The system may include receiving, by a processor, defect records associated with an operation; receiving, by the processor, work information associated with the operation; linking, by the processor, the defect records and the work information using a first AI model to generate linked information; and performing, by the processor, summary generation using a second AI model to generate work summary using summarization keywords, the defect records, and the work information, as input to the second AI model.

[0009] Aspects of the present disclosure involve an innovative system for performing defect summarization. The system may include means for receiving defect records associated with an operation; means for receiving work information associated with the operation; means for linking the defect records and the work information using a first AI model to generate linked information; and means for performing summary generation using a second AI model to generate work summary using summarization keywords, the defect records, and the work information, as input to the second AI model.

Description

BRIEF DESCRIPTION OF DRAWINGS

[0010] A general architecture that implements the various features of the disclosure will now be described with reference to the drawings. The drawings and the associated descriptions are provided to illustrate example implementations of the disclosure and not to limit the scope of the disclosure. Throughout the drawings, reference numbers are reused to indicate correspondence between referenced elements.

[0011] FIG. **1** illustrates an example defect knowledge circulation system **100**, in accordance with an example implementation.

[0012] FIG. **2** illustrates an example process flow **200** for performing the data acquisition steps, in accordance with an example implementation.

[0013] FIG. **3** illustrates an example process flow **300** for performing the linking function processing steps, in accordance with an example implementation.

[0014] FIG. **4** illustrates an example process flow **400** for performing the summarization function processing steps, in accordance with an example implementation

[0015] FIG. **5** illustrates an example process flow **500** for performing the knowledge provision function processing steps, in accordance with an example implementation.

[0016] FIG. **6** illustrates an example architecture of the linking function **140a**, in accordance with an example implementation.

[0017] FIG. **7** illustrates an example architecture of the summarization function **140b**, in accordance with an example implementation.

[0018] FIG. **8** illustrates example work instructions **800**, in accordance with an example implementation.

[0019] FIG. **9** illustrates an example defect record **900**, in accordance with an example implementation.

[0020] FIG. **10** illustrates an example text file **1000** aggregated by the data aggregator **140a-1**, in accordance with an example implementation.

[0021] FIG. **11** illustrates an example output **1100** of the linking function **140a**, in accordance with an example implementation.

[0022] FIG. **12** illustrates an example output **1200** of the summarization function **140b** using “customer” as summary keyword, in accordance with an example implementation.

[0023] FIG. **13** illustrates an example computing environment with an example computer device suitable for use in some example implementations.

DETAILED DESCRIPTION

[0024] The following detailed description provides details of the figures and example implementations of the present application. Reference numerals and descriptions of redundant elements between figures are omitted for clarity. Terms used throughout the description are provided as examples and are not intended to be limiting. For example, the use of the term “automatic” may involve fully automatic or semi-automatic implementations involving user or administrator control over certain aspects of the implementation, depending on the desired implementation of one of the ordinary skills in the art practicing implementations of the present application. Selection can be conducted by a user through a user interface or other input means, or can be implemented through a desired algorithm. Example implementations as described herein can be utilized either singularly or in combination and the functionality of the example implementations can be implemented through any means according to the desired implementations.

[0025] Present example implementations relate to methods and systems for effectively associating/linking inspection results, especially the defect records, with work instructions and other work-related information. Example implementations summarize the defect records for ease of

review, and provide associated information and summarized defect records for work information requested by a user. In some example implementations, work information is information related to industrial systems and associated operations. The information format includes, but not limited to, document files, images, videos, Hypertext Markup Language (HTML) files, Uniform Resource Locators (URLs) indicating the location of the data, etc. Target users are the workers in industrial facilities/systems, such as factories, distribution centers, etc. The workers may include, but not limited to, shop floor operators/workers, operation managers, etc.

[0026] FIG. 1 illustrates an example defect knowledge circulation system **100**, in accordance with an example implementation. The defect knowledge circulation system **100** may include components such as, but not limited to, a data acquisition function **110**, a knowledge provision function **120**, a data store **130**, an inference function **140**, etc.

[0027] Two types of users exist for the defect knowledge circulation system **100**: a data acquisition function user **150** and a knowledge provision function user **160**. The data acquisition function user **150** and the knowledge provision function user **160** can be the same person/worker, as the titles represent roles only. The data acquisition function user **150** operates from a computing device **170**, and the knowledge provision function user **160** operates from a computing device **180**. The computing device **170** has a result recording function **172** for recording and transmitting defect-related record data to the defect knowledge circulation system **100**. The computing device **170** can be any computing device such as, but not limited to a mobile phone, a smart device, a tablet computer, a desktop computer, a laptop computer, a virtual/augmented reality device, internet of things (IoT) device, etc.

[0028] The computing device **180** has a request acquisition and display function **182** for receiving work information retrieval request from the knowledge provision function user **160**. In response to receiving the work information retrieval request, the request acquisition and display function **182** retrieves the defect-related data for the knowledge provision function user **160** to review. The computing device **180** can be any computing device such as, but not limited to a mobile phone, a smart device, a tablet computer, a desktop computer, a laptop computer, a virtual/augmented reality device, internet of things (IoT) device, etc.

[0029] The data store **130** may include components such as, but not limited to, a summarization keyword data store **130a**, a defect-related record data store **130b**, a work information data store **130c**, and a summary and link data store **130d**. The data store **130** may be one or more storage media such as, but not limited to, a non-volatile memory device, volatile memory device, removable disk, hard disk drive, optical disk, etc. In some example implementations, the data store **130** is external to the defect knowledge circulation system **100**.

[0030] The inference function **140** may include components such as, but not limited to, a linking function **140a**, a summarization function **140b**, and a trigger function **140c**. The inference function **140** associates the reported defect-related records and the work information (e.g., work instructions, etc.), to help users/workers discover the potential cause of the defects. The linking function **140a** imports data from the data store **130** to infer linkage between the data in the defect-related record data store **130b** and the work information data store **130c**, and stores the inference results in the summary and link data store **130d**. The inference function **140** also has a summarization function **140b** that summarizes the defect-related records according to the inferred links between the defect-related record data store **130b** and the work information data store **130c**, and stores the summarization result in the summary and link data store **130d**. The summarization keyword data store **130a** stores summarization key words that are used by the summarization function **140b** in generating summaries, which will be described in more detail below.

[0031] The data acquisition function **110** receives defect-related records from the computing device **170** and stores the data in the defect-related record data store **130b**. The knowledge provision function **120** retrieves work information based on a work information request input by the knowledge provision function user **160**. The knowledge provision function **120** then retrieves the

associated defect-related records and summary, and provides/transmits them to the computing device **180** for the knowledge provision function user **160** to review.

[0032] FIG. **2** illustrates an example process flow **200** for performing the data acquisition steps, in accordance with an example implementation. The process flow **200** begins at step **S202** where a defect record is provided/entered by a data acquisition function user **150**. The defect record is provided as an inspection result using the result recording function **172** of the computing device **170**. Defect records may include text notes for the defect, photos/videos, metadata such as the reporter, reporting time, and process ID of the inspection tasks, etc. The data acquisition function user **150** may be a worker on a shop floor where inspection was performed. Defect record input may occur in every inspection task throughout the various processes in the factory.

[0033] At step **S204**, the defect record from is sent to the defect knowledge circulation system **100**. The defect record is sent/transmitted by the computing device **170** to the data acquisition function **110** of the defect knowledge circulation system **100**. At step **S206**, the data acquisition function **110** stores the defect record in the defect-related record data store **130b** in the data store **130**.

[0034] FIG. **3** illustrates an example process flow **300** for performing the linking function processing steps, in accordance with an example implementation. At step **S302**, the trigger function **140c** detects a triggering event (e.g., the addition of defect record in the defect-related record data store **130b**, etc.) to initiate the linking function **140a**. A triggering event may include, but not limited to, the addition of defect record in the defect-related record data store **130b**, a user request for initiating the linking function **140a**, the number of last added defect records since last execution of the linking function **140a**, a time threshold since last execution of the linking function **140a**, etc.

[0035] The process then continues to step **S304** where the linking function **140a** imports defect records from the defect-related record data store **130b** and work information, such as work instructions, from the work information data store **130c**. At step **S306**, the linking function **140a** infers and generates a relationship between the defect records and the work information, and stores the inference results in the summary and link data store **130d**. The linking function **140a** is described in more detail below.

[0036] FIG. **4** illustrates an example process flow **400** for performing the summarization function processing steps, in accordance with an example implementation. The process flow **400** begins at step **S402** where the trigger function **140c** detects a triggering event to initiate the summarization function **140b**. A triggering event may include, but not limited to, the addition of defect record in the defect-related record data store **130b**, a user request for initiating the summarization function **140b**, the number of last added defect records since last execution of the summarization function **140b**, a time threshold since last execution of the summarization function **140b**, etc.

[0037] The process then continues to step **S404** where the summarization function **140b** imports keywords for summarization from the summarization keyword data store **130a**, defect records from the defect-related record data store **130b**, work information such as work instructions and customer information from work information data store **130c**, and current link data and summary records from the summary and link data store **130d**. At step **S406**, the summarization function **140b** generates a summary of the links between the retrieved defect records and the work information using the imported keywords, and stores the inference results in the summary and link data store **130d**. The summarization function **140b** is described in more detail below. The output of the summarization function **140b** may be based on one or more imported keywords/categories. For example, if the keyword is: [0038] “Process”: a summary of the defects is generated for each process. [0039] “Role of workers”: a summary of the defects is generated for each role of the workers. [0040] “Machine”: a summary of the defects is generated for each machine in the factory. [0041] “Customer”: a summary of the defects is generated for each customer of the factory. [0042] “Product”: a summary of the defects is generated for each type of the product.

[0043] FIG. **5** illustrates an example process flow **500** for performing the knowledge provision function processing steps, in accordance with an example implementation. At step **S502**, the

knowledge provision function user **160** inputs work information request through the request acquisition and display function **182** of the computing device **180**. In some example implementations, the work information request may be, but not limited to, an identification number/identifier associated with the work information.

[0044] At step **S504**, the request acquisition and display function **182** of the computing device **180** transmits/sends the work information request to the knowledge provision function **120** of the defect knowledge circulation system **100**. At step **S506**, the knowledge provision function **120** retrieves the work information using the work information request.

[0045] The process then proceeds to step **S508** where the knowledge provision function **120** retrieves the link data and the summary records associated with the work information request. At step **S510**, the knowledge provision function **120** retrieves the defect records from the defect-related record data store **130b** according to the retrieved link data.

[0046] At step **S512**, the knowledge provision function **120** sends the retrieved work information, the retrieved link data, the retrieved summary records, and the retrieved defect records to the request acquisition and display function **182**. The request acquisition and display function **182** then displays the received data at step **S514**.

[0047] FIG. **6** illustrates an example architecture of the linking function **140a**, in accordance with an example implementation. As illustrated in FIG. **6**, the linking function **140a** may include components such as, but not limited to, a data aggregator **140a-1**, a data converter **140a-2**, a prompt generator **140a-3**, prompt snippets **140a-4**, a RAG (Retrieval Augmented Generation) function **140a-5**, a parser **140a-6**, etc.

[0048] The data aggregator **140a-1** aggregates the imported information into a single text file, which is then converted into chunks for embedding by the data converter **140a-2** when the file size exceeds a predetermined size (e.g., the file size exceeds the context window size of the RAG function **140a-5**). The prompt snippets **104a-4** are defined text blocks or codes that may be utilized by the prompt generator **140a-3** in prompt generation.

[0049] The RAG function **140a-5** generates a response using the prompt derived from the prompt generator **140a-3** and the converted chunks derived from the data converter **140a-2**. The RAG function **140a-5** may utilize a Machine Learning (ML)/Artificial Intelligence (AI) model, an ontology-based reasoning function, or any other formal reasoning techniques. The Machine Learning (ML)/Artificial Intelligence (AI) model may be a deep learning model such as a Large Language Model (LLM). The response generated by the RAG function **140a-5** is then parsed and stored by the parser **140a-6**.

[0050] FIG. **7** illustrates an example architecture of the summarization function **140b**, in accordance with an example implementation. As illustrated in FIG. **7**, the summarization function **140b** may include components similar to those of FIG. **6**, such as, but not limited to, a data aggregator **140b-1**, a data converter **140b-2**, a prompt generator **140b-3**, prompt snippets **140b-4**, a RAG (Retrieval Augmented Generation) function **140b-5**, a parser **140b-6**, etc.

[0051] The data aggregator **140b-1** aggregates the imported information into a single text file, which is then converted into chunks for embedding by the data converter **140b-2** when the file size exceeds a predetermined size (e.g., the file size exceeds the context window size of the RAG function **140b-5**). The prompt snippets **104b-4** are defined text blocks or codes that may be utilized by the prompt generator **140b-3** in prompt generation.

[0052] The RAG function **140b-5** generates a response using the prompt derived from the prompt generator **140b-3** and the converted chunks derived from the data converter **140b-2**. The RAG function **140b-5** may utilize a Machine Learning (ML)/Artificial Intelligence (AI) model, an ontology-based reasoning function, or any other formal reasoning techniques. The Machine Learning (ML)/Artificial Intelligence (AI) model may be a deep learning model such as a Large Language Model (LLM). In some example implementations, the input and output of the LLM may comprise a sequence of words (e.g., using the prompt provided as input, etc.). The LLM may

include a module that takes the prompt as an input, generates a single token (e.g., a word, space, etc.) as a part of the output, and repeats the token generation process until the end of the sequence is reached. The LLM may be trained using different types of data dependent on the model architecture (e.g., a large training set of text data, etc.). The set of text data may be tokenized to train the LLM to predict the next word in a sequence of text with any of unsupervised, semi-supervised, supervised, or reinforcement learning method. The response generated by the RAG function **140b-5** is then parsed and stored by the parser **140b-6**.

[0053] FIG. **8** illustrates example work instructions **800**, in accordance with an example implementation. As illustrated in FIG. **8**, work instructions **800** may include a first work instruction **802** for TrainA and TrainB, and a second work instruction **804** for TrainA. The first work instruction is associated with the customer CompanyA, whereas the second work instruction is associated with the customer CompanyB. For ease of parsing, each instruction has beginning and ending tags like “INSTRUCTION BEGIN” and “INSTRUCTION END.”

[0054] FIG. **9** illustrates an example defect record **900**, in accordance with an example implementation. Defect record **900** is the defect record of TrainA associated with CompanyA. As shown in FIG. **9**, the defect record **900** provides information on noted defect and metadata associated with the defect (e.g., reporting date, location of occurrence, product ID, reporting worker, product description, etc.). For ease of parsing, each defect record has beginning and ending tags like “DEFECT NOTE BEGIN” and “DEFECT NOTE END.”

[0055] FIG. **10** illustrates an example text file **1000** aggregated by the data aggregator **140a-1**, in accordance with an example implementation. The work instructions **800** and the defect record **900** are aggregated to form a single text file for chunking by the data converter **140a-2** and subsequently for processing by the RAG function **140a-5**.

[0056] FIG. **11** illustrates an example output **1100** of the linking function **140a**, in accordance with an example implementation. The linking function **140a** infers the links between the work information and defect records, and groups the inferred links by the summary keywords (e.g., “Train” and “Customer”). In some example implementations, additional defect records may be derived using components such as RAG functions **140a-5** and **140b-5** and used for further processing. FIG. **12** illustrates an example output **1200** of the summarization function **140b** using “customer” as summary keyword, in accordance with an example implementation.

[0057] The foregoing example implementation may have various benefits and advantages, such as reducing the burden of organizing defect knowledge and improving the quality and efficiency of factory operations. By intelligently linking the defect records and work instructions, the system provides users with unique operational insights that can be used in performing production or system optimizations.

[0058] FIG. **13** illustrates an example computing environment with an example computer device suitable for use in some example implementations. Computer device **1305** in computing environment **1300** can include one or more processing units, cores, or processors **1310**, memory **1315** (e.g., RAM, ROM, and/or the like), internal storage **1320** (e.g., magnetic, optical, solid-state storage, and/or organic), and/or IO interface **1325**, any of which can be coupled on a communication mechanism or bus **1330** for communicating information or embedded in the computer device **1305**. IO interface **1325** is also configured to receive images from cameras or provide images to projectors or displays, depending on the desired implementation.

[0059] Computer device **1305** can be communicatively coupled to input/user interface **1335** and output device/interface **1340**. Either one or both of the input/user interface **1335** and output device/interface **1340** can be a wired or wireless interface and can be detachable. Input/user interface **1335** may include any device, component, sensor, or interface, physical or virtual, that can be used to provide input (e.g., buttons, touch-screen interface, keyboard, a pointing/cursor control, microphone, camera, braille, motion sensor, accelerometer, optical reader, and/or the like). Output device/interface **1340** may include a display, television, monitor, printer, speaker, braille, or the

like. In some example implementations, input/user interface **1335** and output device/interface **1340** can be embedded with or physically coupled to the computer device **1305**. In other example implementations, other computer devices may function as or provide the functions of input/user interface **1335** and output device/interface **1340** for a computer device **1305**.

[0060] Examples of computer device **1305** may include, but are not limited to, highly mobile devices (e.g., smartphones, devices in vehicles and other machines, devices carried by humans and animals, and the like), mobile devices (e.g., tablets, notebooks, laptops, personal computers, portable televisions, radios, and the like), and devices not designed for mobility (e.g., desktop computers, other computers, information kiosks, televisions with one or more processors embedded therein and/or coupled thereto, radios, and the like).

[0061] Computer device **1305** can be communicatively coupled (e.g., via IO interface **1325**) to external storage **1345** and network **1350** for communicating with any number of networked components, devices, and systems, including one or more computer devices of the same or different configuration. Computer device **1305** or any connected computer device can be functioning as, providing services of, or referred to as a server, client, thin server, general machine, special-purpose machine, or another label.

[0062] IO interface **1325** can include but is not limited to, wired and/or wireless interfaces using any communication or IO protocols or standards (e.g., Ethernet, 802.11x, Universal System Bus, WiMax, modem, a cellular network protocol, and the like) for communicating information to and/or from at least all the connected components, devices, and network in computing environment **1300**. Network **1350** can be any network or combination of networks (e.g., the Internet, local area network, wide area network, a telephonic network, a cellular network, satellite network, and the like).

[0063] Computer device **1305** can use and/or communicate using computer-usable or computer readable media, including transitory media and non-transitory media. Transitory media include transmission media (e.g., metal cables, fiber optics), signals, carrier waves, and the like. Non-transitory media include magnetic media (e.g., disks and tapes), optical media (e.g., CD ROM, digital video disks, Blu-ray disks), solid-state media (e.g., RAM, ROM, flash memory, solid-state storage), and other non-volatile storage or memory.

[0064] Computer device **1305** can be used to implement techniques, methods, applications, processes, or computer-executable instructions in some example computing environments. Computer-executable instructions can be retrieved from transitory media, and stored on and retrieved from non-transitory media. The executable instructions can originate from one or more of any programming, scripting, and machine languages (e.g., C, C++, C #, Java, Visual Basic, Python, Perl, JavaScript, and others).

[0065] Processor(s) **1310** can execute under any operating system (OS) (not shown), in a native or virtual environment. One or more applications can be deployed that include logic unit **1360**, application programming interface (API) unit **1365**, input unit **1370**, output unit **1375**, and inter-unit communication mechanism **1395** for the different units to communicate with each other, with the OS, and with other applications (not shown). The described units and elements can be varied in design, function, configuration, or implementation and are not limited to the descriptions provided. Processor(s) **1310** can be in the form of hardware processors such as central processing units (CPUs) or in a combination of hardware and software units.

[0066] In some example implementations, when information or an execution instruction is received by API unit **1365**, it may be communicated to one or more other units (e.g., logic unit **1360**, input unit **1370**, output unit **1375**). In some instances, logic unit **1360** may be configured to control the information flow among the units and direct the services provided by API unit **1365**, the input unit **1370**, the output unit **1375**, in some example implementations described above. For example, the flow of one or more processes or implementations may be controlled by logic unit **1360** alone or in conjunction with API unit **1365**. The input unit **1370** may be configured to obtain input for the

calculations described in the example implementations, and the output unit **1375** may be configured to provide an output based on the calculations described in example implementations.

[0067] Processor(s) **1310** can be configured to receive defect records associated with an operation; receive work information associated with the operation; link the defect records and the work information using a first Artificial Intelligence (AI) model to generate linked information; and perform summary generation using a second AI model to generate work summary using summarization keywords, the defect records, and the work information, as input to the second AI model as shown in FIGS. **1-5**. The processor(s) **1310** may also be configured to receive a work information retrieval request from a user for retrieving the work information from a database; and retrieve and display using the linked information to retrieve the defect records, the work information, and the work summary to the user as shown in FIGS. **1** and **5**.

[0068] Some portions of the detailed description are presented in terms of algorithms and symbolic representations of operations within a computer. These algorithmic descriptions and symbolic representations are the means used by those skilled in the data processing arts to convey the essence of their innovations to others skilled in the art. An algorithm is a series of defined steps leading to a desired end state or result. In example implementations, the steps carried out require physical manipulations of tangible quantities for achieving a tangible result.

[0069] Unless specifically stated otherwise, as apparent from the discussion, it is appreciated that throughout the description, discussions utilizing terms such as “processing,” “computing,” “calculating,” “determining,” “displaying,” or the like, can include the actions and processes of a computer system or other information processing device that manipulates and transforms data represented as physical (electronic) quantities within the computer system's registers and memories into other data similarly represented as physical quantities within the computer system's memories or registers or other information storage, transmission or display devices.

[0070] Example implementations may also relate to an apparatus for performing the operations herein. This apparatus may be specially constructed for the required purposes, or it may include one or more general-purpose computers selectively activated or reconfigured by one or more computer programs. Such computer programs may be stored in a computer readable medium, such as a computer readable storage medium or a computer readable signal medium. A computer readable storage medium may involve tangible mediums such as, but not limited to optical disks, magnetic disks, read-only memories, random access memories, solid-state devices, and drives, or any other types of tangible or non-transitory media suitable for storing electronic information. A computer readable signal medium may include mediums such as carrier waves. The algorithms and displays presented herein are not inherently related to any particular computer or other apparatus. Computer programs can involve pure software implementations that involve instructions that perform the operations of the desired implementation.

[0071] Various general-purpose systems may be used with programs and modules in accordance with the examples herein, or it may prove convenient to construct a more specialized apparatus to perform desired method steps. In addition, the example implementations are not described with reference to any particular programming language. It will be appreciated that a variety of programming languages may be used to implement the teachings of the example implementations as described herein. The instructions of the programming language(s) may be executed by one or more processing devices, e.g., central processing units (CPUs), processors, or controllers.

[0072] As is known in the art, the operations described above can be performed by hardware, software, or some combination of software and hardware. Various aspects of the example implementations may be implemented using circuits and logic devices (hardware), while other aspects may be implemented using instructions stored on a machine-readable medium (software), which if executed by a processor, would cause the processor to perform a method to carry out implementations of the present application. Further, some example implementations of the present application may be performed solely in hardware, whereas other example implementations may be

performed solely in software. Moreover, the various functions described can be performed in a single unit, or can be spread across a number of components in any number of ways. When performed by software, the methods may be executed by a processor, such as a general-purpose computer, based on instructions stored on a computer readable medium. If desired, the instructions can be stored on the medium in a compressed and/or encrypted format.

[0073] Moreover, other implementations of the present application will be apparent to those skilled in the art from consideration of the specification and practice of the teachings of the present application. Various aspects and/or components of the described example implementations may be used singly or in any combination. It is intended that the specification and example implementations be considered as examples only, with the true scope and spirit of the present application being indicated by the following claims.

Claims

1. A method for performing defect summarization, the method comprising: receiving, by a processor, defect records associated with an operation; receiving, by the processor, work information associated with the operation; linking, by the processor, the defect records and the work information using a first Artificial Intelligence (AI) model to generate linked information; and performing, by the processor, summary generation using a second AI model to generate work summary using summarization keywords, the defect records, and the work information, as input to the second AI model.
2. The method of claim 1, wherein the first AI model and the second AI model are large language models (LLM).
3. The method of claim 1, further comprising: receiving, by the processor, a work information retrieval request from a user for retrieving the work information from a database; and retrieving and displaying, by the processor, using the linked information to retrieve the defect records, the work information, and the work summary to the user.
4. The method of claim 1, wherein linking the defect records and the work information using the first AI model is triggered by receipt of the defect records.
5. The method of claim 1, wherein the processor is configured to link the defect records and the work information using the first AI model to generate the linked information by: inferring and generating a relationship between the defect records and the work information using the first AI model, wherein the relationship is the linked information.
6. The method of claim 5, wherein the work summary comprises a summary of the relationship between the defect records and the work information grouped by the summarization keywords.
7. The method of claim 6, wherein the summary of the relationship comprises one or more of a process defect summary, a role defect summary, a machine defect summary, a customer defect summary, or a product defect summary.
8. The method of claim 1, wherein the work information comprises work instructions and process information associated with the operation.
9. A system for performing defect summarization, the system comprising: a data storage; and a processor in communication with the data storage, wherein the processor is configured to: receive defect records associated with an operation and store the defect records in the data storage; receive work information associated with the operation and store the work information in the data storage; link the defect records and the work information using a first Artificial Intelligence (AI) model to generate linked information and store the linked information in the data storage; and perform summary generation using a second AI model, wherein the second AI model generates work summary using summarization keywords, the defect records, and the work information, as input to the second AI model, and store the work summary in the data storage.
10. The system of claim 9, wherein the first AI model and the second AI model are large language

models (LLM).

- 11.** The system of claim 9, wherein the processor is further configured to: receive a work information retrieval request from a user for retrieving the work information from a database; and retrieve and display, using the linked information to retrieve the defect records, the work information, and the work summary to the user.
 - 12.** The system of claim 9, wherein linking the defect records and the work information using the first AI model is triggered by receipt of the defect records.
 - 13.** The system of claim 9, wherein the processor is configured to link the defect records and the work information using the first AI model to generate the linked information by: inferring and generating a relationship between the defect records and the work information using the first AI model, wherein the relationship is the linked information.
 - 14.** The system of claim 13, wherein the work summary comprises a summary of the relationship between the defect records and the work information grouped by the summarization keywords.
 - 15.** The system of claim 14, wherein the summary of the relationship comprises one or more of a process defect summary, a role defect summary, a machine defect summary, a customer defect summary, or a product defect summary.
 - 16.** The system of claim 9, wherein the work information comprises work instructions and process information associated with the operation.
-