

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409524
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Kato; Heizaburo

Barrel cam device

Abstract

A barrel cam device includes a barrel cam, an output table that includes a plurality of cam followers that engage with the barrel cam, and that rotates by rotation of the barrel cam, and a clamp device that clamps the output table when the output table is stopping.

Inventors:	Kato; Heizaburo (Shizuoka, JP)
Applicant:	TECHNO DYNAMICS, INC. (Shizuoka, JP)
Family ID:	84979862
Assignee:	TECHNO DYNAMICS, INC. (Shizouka, JP)
Appl. No.:	18/577100
Filed (or PCT Filed):	March 29, 2022
PCT No.:	PCT/JP2022/015427
PCT Pub. No.:	WO2023/002717
PCT Pub. Date:	January 26, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240316715 A1	Sep. 26, 2024

Foreign Application Priority Data

JP	2021-118967	Jul. 19, 2021
----	-------------	---------------

Publication Classification

Int. Cl.: B23Q16/00 (20060101); B23Q1/26 (20060101); B23Q16/10 (20060101)

U.S. Cl.:

CPC B23Q16/001 (20130101); B23Q1/26 (20130101); B23Q16/10 (20130101);

Field of Classification Search

CPC: B23Q (16/001); B23Q (1/26); B23Q (16/10); B23Q (16/105)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4512214	12/1984	Surman	N/A	N/A
5481944	12/1995	Oketani et al.	N/A	N/A
6279219	12/2000	Ohsawa	29/434	B23Q 7/02
6948402	12/2004	Amendolea	N/A	N/A
8544363	12/2012	Tatsuda	74/813L	B23Q 16/105
9166457	12/2014	Yamagishi	N/A	H02K 11/225
2012/0180584	12/2011	Weiss	74/25	B23Q 16/025
2017/0326702	12/2016	Osaki	N/A	B23Q 16/105

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
29812055	12/1998	DE	B23Q 16/02
U1981089407	12/1980	JP	N/A
U1991126545	12/1991	JP	N/A
2001-277074	12/2000	JP	N/A
2001-287138	12/2000	JP	N/A
2004-74328	12/2003	JP	N/A
2005-138216	12/2004	JP	N/A
2009-90422	12/2008	JP	N/A
2010-25245	12/2009	JP	N/A
2010131740	12/2009	JP	N/A
2018155276	12/2017	JP	N/A
2019147212	12/2018	JP	N/A

OTHER PUBLICATIONS

Japanese Office Action for JP2021-118967 dated Oct. 31, 2024. cited by applicant
Japanese International Search Report dated May 19, 2022. cited by applicant
Japanese International Search Report dated Jun. 7, 2022. cited by applicant

Primary Examiner: Diaz; Thomas C

Attorney, Agent or Firm: Dickinson Wright PLLC

Background/Summary

RELATED APPLICATIONS

(1) The present disclosure is a national phase application of PCT Application PCT/JP2022/015427, filed Mar. 29, 2022, which claims priority to Japanese Patent Application No. 2021-118967, filed Jul. 19, 2021, the entire contents both of which is incorporated herein by reference.

FIELD

(2) The present disclosure relates to a barrel cam device.

BACKGROUND

(3) The indexing device which uses a cam mechanism is known as an indexing device for workpieces processed by machine tools, etc. (One example of such an indexing device is shown in Japanese Patent Application Publication No. 2001-287138.

(4) In the case of providing at a low cost a clamp device which clamp an output table to an indexing device, we have found there has been a problem that the indexing device have to be made large so that the clamp device can fit in. Alternatively, in the case of configuring the clamp device with small parts so that the clamp device can fit in, there has been a problem of increasing cost.

SUMMARY

(5) The present disclosure was achieved in light of the above-described problem, an aspect of the present disclosure is to realize an indexing device including a clamp device which is compact and inexpensive.

(6) A main aspect of the present disclosure of achieving the above-described aspect is a barrel cam device including: a barrel cam; an output table that includes a plurality of cam followers that engage with the barrel cam, and that rotates by rotation of the barrel cam; and a clamp device that clamps the output table when the output table is stopping.

(7) Features of the present disclosure other than the above will become clear by reading the description of the present specification with reference to the accompanying drawings.

(8) According to the present disclosure, it is possible to realize an indexing device including a clamp device which is compact and inexpensive.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a schematic plan view and a schematic side view of an indexing device 1.

(2) FIG. 2 is a diagram illustrating a clamp device.

(3) FIG. 3 is a schematic plan view of a pressing member 32.

DESCRIPTION

(4) At least the following matters will be clear with the description of this specification and the attached drawings.

(5) A barrel cam device including: a barrel cam; an output table that includes a plurality of cam followers that engage with the barrel cam, and that rotates by rotation of the barrel cam; and a clamp device that clamps the output table when the output table is stopping.

(6) According to such a barrel cam device, it is possible to realize the indexing device that includes a compact and inexpensive clamp device.

(7) In such a barrel cam device, it is desirable that the barrel cam device further comprises a supporting portion that rotatably supports the output table, and that the clamp device includes: a plate member that includes a fixed portion that is fixed to the output table, and a opposing portion that faces the supporting portion with being in a non-contact state, when the output table is rotating; and a pressing member that presses the plate member against the supporting portion when the output table is stopping.

(8) According to such a barrel cam device, the clamp device has a simple structure consisting of the plate member and the pressing member, making it possible to realize an inexpensive clamp device.

- (9) In such a barrel cam device, it is desirable that the barrel cam device further comprises a housing that accommodates the output table, and that the plate member and the pressing member are provided within the housing.
- (10) According to such a barrel cam device, it is possible to effectively utilize a relatively large space in the housing the barrel cam device.
- (11) In such a barrel cam device, it is desirable that the fixed portion is fixed to a table lower surface of the output table, that, when the output table is rotating, the opposing portion faces a supporting-portion lower surface of the supporting portion with being in the non-contact state, and that the pressing member presses the opposing portion against the supporting-portion lower surface when the output table is stopping.
- (12) According to the barrel cam device, it becomes possible to easily realize to clamp the output table.
- (13) In such a barrel cam device, it is desirable that the fixed portion has a through hole, and that the fixed portion and the cam follower are fixed to the table lower surface by a common bolt in a state where the cam follower passes through the through hole.
- (14) According to the barrel cam device, by fixing the plate member and the cam follower using a common bolt, it makes bolts for fixing the plate member unnecessary. This makes is possible to reduce costs by reducing the number of parts.
- (15) In such a barrel cam device, it is desirable that the pressing member is a piston member that deforms the opposing portion and presses the opposing portion against the supporting portion by moving and being in contact with the opposing portion when the output table is stopping.
- (16) According to the barrel cam device, the output table is clamped not only by the frictional force that occurs between the plate member and the supporting portion, but also by the frictional force that occurs between the plate member and the piston member, and this increases the clamping force.
- (17) In such a barrel cam device, it is desirable that the barrel cam device further comprises a rotating shaft body that is mounted to a central portion of the output table and that rotates integrally with the output table, and that the piston member is provided throughout from a side where the barrel cam is located when viewed from the rotating shaft body to a side where the barrel cam is not located when viewed from the rotating shaft body.
- (18) According to the barrel cam device, the area of the piston member can be increased compared to the case where the piston member is not provided throughout from the side where the barrel cam is located to the side where the barrel cam is not located. Accordingly, the pressure of the compressed gas, etc. becomes greater and presses the plate member, making it possible to clamp the output table with a greater force.
- (19) In such a barrel cam device, it is desirable that the piston member has a groove that accommodates the cam follower with being in the non-contact state.
- (20) According to the barrel cam device, while increasing the rigidity of the piston member, it possible to prevent the piston member from interfering with the rotation of the output table.
- (21) In such a barrel cam device, it is desirable that the barrel cam device further comprises a housing that accommodates the output table, that a part of the housing serves as a cylinder member that accommodates the piston member, that the housing is provided with a compressed-air introducing hole that introduces a compressed air into the cylinder member, and that an area of a pressed surface of the piston member that is pressed by the compressed air is more than half of an area of a table surface of the output table.
- (22) According to the barrel cam device, by increasing the area of the piston member to more than half of the area of the output table, compared to the case where the area of the piston member is less than half of the area of the output table, the pressure of compressed gas, etc. become greater and presses the plate member. This makes it possible to clamp the output table with a great force.
- (23) Indexing Device 1

(24) The following describes an indexing device **1** (corresponding to the barrel cam device) according to the present embodiment with reference to the drawings. Note that the indexing device **1** can be used for, for example, NC tables for machine tools, positioners for robots, pivots of robots, and the like.

(25) FIG. **1** is a schematic plan view and a schematic side view of the indexing device **1**; the upper diagram is the schematic plan view and the bottom diagram is the schematic side view. Note that, in the drawings according to the present embodiment, members may be omitted as appropriate in order to explain the present disclosure in an easy-to-understand manner.

(26) Further, the indexing device **1** according to the present embodiment has the X direction, the Y direction, and the Z direction. The X direction and the Y direction intersect with each other, and the X direction and the Y direction both intersect with the Z direction. In the upper diagram of FIG. **1**, the transverse direction of the page is called the X direction, and the left side (right side) of the page is called the left (right). The longitudinal direction of the page is called the Y direction, and the upper side (lower side) of the page is called the far side (near side). In addition, in the lower diagram of FIG. **1**, the longitudinal direction on the page is called the Z direction (vertical direction), and the upper side (lower side) of the page is called up (down).

(27) The indexing device **1** has a housing **3**, and the housing **3** accommodates an input shaft **12**, a barrel cam **14**, an output table **20**, a rotating shaft body **22**, a plate member **30**, and a pressing member **32**. Further, a motor **10** is mounted to the housing **3** as a drive unit.

(28) The motor **10** is provided so that its rotation shaft is aligned with the Y direction, and is connected to the input shaft **12** by a coupling **16**.

(29) The input shaft **12** is provided extending along the Y direction and is rotatably supported by an input bearing **18**. A portion of the input shaft **12** on the near side extends further on the near side beyond the input bearing **18**, and this extending portion is connected to the rotation shaft of the motor **10** by the coupling **16**.

(30) Further, the input shaft **12** is provided in both ends of the barrel cam **14** in the Y direction, and the barrel cam **14** and the input shaft **12** rotate integrally.

(31) Further, the barrel cam **14** has a barrel cam groove **14a**, and the spiral-shaped barrel cam groove **14a** is provided along the direction of the input shaft **12**. Then, by engaging a later-described cam followers **20a** of the output table **20** with the barrel cam groove **14a**, the rotation of the barrel cam **14** is transmitted to the output table **20**. Note that the input shaft **12** and the barrel cam **14** may be integrated by joining together separately processed components, or may be manufactured by forming a cam groove in an integrally-manufactured shaft-shaped component.

(32) The output table **20** has a circular shape and is rotatably supported by a supporting portion **24**. In addition, the supporting portion **24** in the present embodiment is a large-diameter four-point contact ball bearing. The output table **20** includes a plurality of cam followers **20a** that engage with the barrel cam **14** (the barrel cam groove **14a**), and rotates around the rotation shaft extending along the Z direction due to rotation of the barrel cam **14** around the input shaft **12** extending along the Y direction.

(33) The cam followers **20a** are portions that engage with the barrel cam groove **14a**, and are cylindrical rotating bodies that can rotate. The cam followers **20a** are arranged such that the rotation axis direction conforms to the Z direction. A plurality of the cam followers **20a** are provided at equal intervals along a circle centered on the rotation center of the output table **20**. In the present embodiment, 16 cam followers **20a** are provided at equal intervals (every 22.5 degrees).

(34) Further, the cam followers **20a** engage with the barrel cam groove **14a** of the barrel cam **14** below the output table **20**, and the engaged cam followers **20a** are guided by the barrel cam groove **14a** and move.

(35) Specifically, when the barrel cam **14** rotates counterclockwise in a view from the near side, the engaged cam followers **20a** are guided by the spiral barrel cam groove **14a** to move from the near side to the far side along the circumferential direction of the output table **20**. That is, the output

table **20** rotates clockwise in a view from above.

(36) In order to make the rotation of the output table **20** highly accurate, that is to say, in order to realize highly-accurate output, the cam followers **20a** and the barrel cam groove **14a** are engaged with high accuracy such that backlash, displacement, rattling, and the like do not occur (an engagement method for realizing highly-accurate output of cam mechanism is a well-known technique, so a description thereof will be omitted here).

(37) The rotating shaft body **22** extends along the Z direction and is mounted to the central portion (the hollow portion) of the output table **20**. The rotating shaft body **22** rotates integrally with the output table **20**.

(38) Further, the rotating shaft body **22** may be one without a hollow portion in the center (solid shaft), but the rotating shaft body **22** according to the present embodiment is a so-called hollow shaft with the hollow portion in it. That is, at the center of the rotating shaft body **22**, a circular space is provided that passes through the rotating shaft body **22** in the vertical direction.

(39) Clamp Device

(40) The indexing device **1** according to the present embodiment has a clamp device which clamps the output table **20** when the output table **20** is stopping. The clamp device is, for example, a device that fixes an NC table (output table **20**) for machine tools so that the NC table does not move during processing after indexing. The clamp device is provided for the purpose of improving the machining accuracy, for example.

(41) In other words, the indexing device **1** includes: the barrel cam **14**; the output table **20** that includes a plurality of the cam followers **20a** that engage with the barrel cam **14**, and that rotates by rotation of the barrel cam **14**; and the clamp device that clamps the output table **20** when the output table **20** is stopping.

(42) The following describes the clamp device in detail with reference to diagrams. FIG. **2** is a diagram illustrating the clamp device. FIG. **2a** is a diagram when the output table **20** is rotating and the output table **20** is not clamped, and FIG. **2b** is a diagram when the output table **20** is stopped and the output table **20** is clamped.

(43) As shown in FIGS. **1** and **2**, the clamp device includes: the plate member **30**; the pressing member **32**; and a piston back member **34**. The plate member **30** and the pressing member **32** are provided within the housing **3**. Then, as shown in FIG. **2B**, when the output table **20** is stopping, the pressing member **32** presses the plate member **30** onto the supporting portion **24**, thereby clamping the output table **20**.

(44) The plate member **30** is a disc-shaped metal plate made of stainless steel, phosphor bronze, etc., and has high rigidity in the circumferential direction, but has low rigidity in the thickness direction. In other words, if the plate member **30** is subject to a force applied in the circumferential direction, it is less likely to deform, but if the plate member **30** is subject to a force in the thickness direction (force to deform in the thickness direction), it deforms easily. Further, since the plate member **30** is fixed to the output table **20**, it rotates as the output table **20** rotates.

(45) The plate member **30** includes: a fixed portion **30b** that is fixed to the output table **20**; and an opposing portion **30c** that faces the supporting portion **24** with being in the non-contact state, when the output table **20** is rotating. As shown in FIG. **2A**, when the output table **20** is rotating, the opposing portion **30c** is held so as not to come into contact with any of the pressing member **32**, the housing **3**, and the supporting portion **24** (in other words, it does not interfere with the rotation of the output table **20**).

(46) Further, the fixed portion **30b** is fixed to the table lower surface **20d** of the output table **20**. The opposing portion **30c** faces the supporting-portion lower surface **24a** of the supporting portion **24** with being in the non-contact state, when the output table **20** is rotating. The pressing member presses the opposing portion **30c** against the supporting-portion lower surface **24a** when the output table **20** is stopping.

(47) Further, the fixed portion **30b** of the plate member **30** has through holes **30a**, through which

the cam followers **20a** pass. The plate member **30** and each of the cam followers **20a** are fixed to the table lower surface **20d** of the output table **20** by one bolt **20b**. That is, the fixed portion **30b** has the through holes **30a**, and the fixed portion **30b** and each of the cam followers **20a** are fixed to the table lower surface **20d** by the common bolt **20b** in a state where the cam followers **20a** pass through the through holes **30a**.

(48) FIG. 3 is a schematic plan view of the pressing member **32**. The pressing member **32** is substantially D-shaped in plan view (when viewed from above in the Z direction), and has a projection **32a** (a portion hatched obliquely upward to the right in FIG. 3) and the groove **32b** (a portion hatched obliquely downward to the right in FIG. 3) on the surface.

(49) The projection **32a** is provided, as shown in FIG. 2, outside the outer circumferential edge of the output table **20** when being installed, and extends, as shown in FIG. 3, along the outer periphery of the pressing member **32**. The projection **32a** is provided so that the contact area is as small as possible in order to increase the contact surface pressure with the plate member **30**. Further, the groove **32b** is provided, as shown in FIGS. 1 and 3, extending along the arrangement of the cam follower **20a**.

(50) In addition, the pressing member **32** is moved upward (to the plate member **30** side) by the compressed air introduced from the compressed-air introducing hole **36** (see FIG. 1), which is provided in the housing **3** and below the pressing member **32**, and this makes the projection **32a** come into contact with and be pressed against the plate member **30**. As a result, as shown in FIG. 2B, the projection **32a** of the pressing member **32** deforms the plate member **30**, and presses against the supporting portion **24** a portion of the plate member **30** that is located on the side opposite to the side where the projection **32a** is in contact, making the output table **20** be clamped. Further, as will be described in detail later, when the introduced compressed air is removed, the pressing member **32** is moved downward by the piston back member **34**, and becomes the unclamped state from the clamped state as shown in FIG. 2A. In other words, the pressing member **32** makes a piston movement up and down within the housing **3**.

(51) In other words, the pressing member **32** (the projection **32a**) is a piston member that deforms the opposing portion **30c** and presses it against the supporting portion **24** by moving and being in contact with the opposing portion **30c** when the output table **20** is stopping.

(52) Further, as shown in FIG. 1, the piston member (pressing member **32**) is provided throughout the rotating shaft body **22** from the left side to the right side in the X direction. In other words, the piston member (pressing member **32**) is provided throughout from the side where the barrel cam **14** is located when viewed from the rotating shaft body **22** to the side where the barrel cam **14** is not located when viewed from the rotating shaft body **22**.

(53) In addition, as shown in FIGS. 1 to 3, the piston member (pressing member **32**) has the groove **32b** that is for accommodating the cam followers **20a** that are fixed to the output table **20**, with being in the non-contact state, so as not to interfere with the rotation of the output table **20**.

(54) Also, as mentioned above, the piston member is moved upward by the compressed air introduced from the compressed-air introducing hole **36**, but this is achieved by making a part of the housing **3** serve as a cylinder member through which the piston member moves. The introduced the compressed air is received by the entire surface of the piston member (the entirety of an approximately D-shaped surface shown in FIG. 3), and therefore this area is more than half of the area **20c** of the table surface of the output table **20** (the hatched portion in FIG. 1).

(55) In other words, a part of the housing **3** serves as the cylinder member for accommodating the piston member (pressing member **32**), and the housing **3** is provided with the compressed-air introducing hole **36** that introduces the compressed air into the cylinder member, and the area of the pressed surface of the piston member (pressing member **32**) that is pressed by the compressed air is more than half of the area **20c** of the table surface of the output table **20**.

(56) The piston back member **34** is a member that releases the contact between the opposing portion **30c** and the supporting portion **24** and the projection **32a** (create a gap) by moving the

piston member (pressing member **32**) downward. In the piston back member **34**, its upper end portion is fixed to the piston member (pressing member **32**) within the housing **3**, and its lower end portion receives a force from above to below by a spring **34a**, outside the housing **3**.
(57) In other words, when the pressure of the compressed air that has been introduced at the time of clamping decreases (when the compressed air is excluded from the cylinder member), it decreases the force of the compressed air that pushes the piston member (pressing member **32**) upward. As a result, the spring force of the spring **34a** causes the piston member (pressing member **32**) to move downward, making the output table **20** be in the unclamped state from the clamped state.

(58) Effectiveness of the Indexing Device

(59) As mentioned above, the indexing device **1** according to the present embodiment includes: the barrel cam **14**; and the output table **20** which includes the plurality of cam followers **20a** that engage with the barrel cam **14**, and which rotates by rotation of the barrel cam **14**; and the clamp device which clamps the output table **20** when the output table **20** is stopping. This makes it possible to realize the indexing device **1** that includes a compact and inexpensive clamp device.

(60) In the case of providing at a low cost a clamp device which clamp an output table to an indexing device, there has been a problem that the indexing device have to be made large so that the clamp device can fit in. Alternatively, in the case of configuring the clamp device with small parts so that the clamp device can fit in, there has been a problem of increasing cost.

(61) In contrast, in the case where the barrel cam device is employed as the indexing device **1**, it increases locations where the clamp device can be installed compared to, for example, the case where a roller gear cam is used. In other words, by employing the barrel cam device as the indexing device **1**, it increases the number of locations where the clamp device can be installed, making it possible to realize the indexing device **1** with a compact and inexpensive clamp device.

(62) By providing the clamp device with the indexing device **1**, it increases the rigidity of the output table **20** in the direction of rotation, for example. This makes it possible to improve the machining accuracy of workpieces. Further, for example, when an overload occurs on the output table **20**, the clamp device can ensure safety. Also, for example, if the clamp device is provided, workers can work with peace of mind.

(63) In the above embodiment, the indexing device **1** further includes the supporting portion **24** which rotatably supports the output table **20**, and the clamp device includes: the plate member **30** which includes the fixed portion **30b** fixed to the output table **20**, and the opposing portion **30c** facing the supporting portion **24** with being in the non-contact state when the output table **20** is rotating; and the pressing member **32** which presses the plate member **30** against the supporting portion **24** when the output table **20** is stopping. As a result, the clamp device has a simple structure consisting of the plate member **30** and the pressing member **32**, making it possible to realize an inexpensive clamp device.

(64) Further, in the above embodiment, the indexing device **1** further includes the housing **3** which accommodates the output table **20**, and the plate member **30** and the pressing member **32** are provided within the housing **3**. This makes it possible to effectively utilize a relatively large space in the housing **3** of the indexing device **1** (barrel cam device).

(65) In the above embodiment, the fixed portion **30b** is fixed to the table lower surface **20d** of the output table **20**, and when the output table **20** is rotating, the opposing portion **30c** faces the supporting-portion lower surface **24a** of the supporting portion **24** with being in the non-contact state, and the pressing member **32** presses the opposing portion **30c** against the supporting-portion lower surface **24a** when the output table **20** is stopping.

(66) The supporting-portion lower surface **24a** and the table lower surface **20d** are both structurally arranged on substantially the same plane. Therefore, if the design is such that there is a slight difference between both surfaces instead of making both surfaces completely on the same plane, the following state can easily create by using that difference: in no-clamping state, the fixed portion **30b** of the plate member **30** is fixed to the table lower surface **20d** and the opposing portion **30c** of

the plate member **30** faces the supporting-portion lower surface **24a** with a slight gap. In other words, by using the supporting-portion lower surface **24a** and the table lower surface **20d**, it is possible to easily realize to clamp the output table **20**.

(67) Further, in the above embodiment, the fixed portion **30b** has the through holes **30a**, and the fixed portion **30b** and each of the cam followers **20a** are fixed to the table lower surface **20d** by the common bolt **20b** in the state where the cam followers **20a** pass through the through holes **30a**.

(68) By fixing the plate member **30** and each of the cam followers **20a** by the common bolt **20b**, it makes bolts for fixing the plate member **30** unnecessary. This makes it possible to reduce costs by reducing the number of parts.

(69) Further, in the above embodiment, the pressing member **32** is the piston member that deforms the opposing portion **30c** and presses it against the supporting portion **24** by moving and being in contact with the opposing portion **30c** when the output table **20** is stopping.

(70) As a result, the output table **20** is clamped not only by the frictional force that occurs between the plate member **30** and the supporting portion **24**, but also by the frictional force that occurs between the plate member **30** and the piston member (pressing member **32**), and this increases the clamping force.

(71) Further, in the above embodiment, the indexing device **1** further includes the rotating shaft body **22** which is mounted to the central portion of the output table **20** and which rotates integrally with the output table **20**, and the piston member (pressing member **32**) is provided throughout from the side where the barrel cam **14** is located when viewed from the rotating shaft body **22** to the side where the barrel cam **14** is not located when viewed from the rotating shaft body **22**.

(72) As a result, the area of the piston member (pressing member **32**) can be increased compared to the case where the piston member (pressing member **32**) is not provided throughout from the side where the barrel cam **14** is located to the side where the barrel cam **14** is not located. Accordingly, the pressure of the compressed gas, etc. becomes greater and presses the plate member **30**, making it possible to clamp the output table **20** with a greater force.

(73) Furthermore, in the above embodiment, the piston member (pressing member **32**) has the groove **32b** that accommodates the cam followers **20a** with being in the non-contact state. This makes it possible to prevent the piston member (pressing member **32**) from interfering with the rotation of the output table **20**.

(74) Further, in the above embodiment, the indexing device **1** further includes the housing **3** which accommodates the output table **20**, and a part of the housing **3** serves as the cylinder member that accommodates the piston member (pressing member **32**), and the housing **3** is provided with the compressed-air introducing hole **36** which introduces the compressed air into the cylinder member, and the area of the pressed surface of the piston member (pressing member **32**), which is pressed by the compressed air, is more than half the area of the table surface of the output table **20**.

(75) By increasing the area of the piston member (pressing member **32**) to more than half of the area of the output table **20**, compared to the case where the area of the piston member is less than half of the area of the output table **20**, the pressure of the compressed air becomes greater and presses the plate member. This makes it possible to clamp the output table with a great force.

Other Embodiments

(76) The above embodiment is simply to facilitate understanding of the present disclosure and is not in any way to be construed as limiting the present disclosure. The present disclosure may variously be changed or altered without departing from its gist and encompass equivalents thereof.

(77) Further, in the above embodiment, a four-point contact ball bearing is used for the supporting portion **24**, but the present disclosure is not limited to this. For example, a cross roller bearing may be used.

(78) Further, in the above embodiment, the pressing member **32** is moved upward by the compressed air, but the present disclosure is not limited to this. For example, the pressing member **32** may be moved upward using hydraulic pressure.

REFERENCE SIGNS LIST

(79) **1.** indexing device (barrel cam device), **3** housing, **10** motor, **12** input shaft, **14** barrel cam, **14a** barrel cam groove, **16** coupling, **18** input bearing, **20** output table, **20a** cam follower, **20b** bolt, **22** rotating shaft body, **24**, supporting portion, **30** plate member, **30a** through hole, **30b** fixed portion, **30c** opposing portion, **32** pressing member (piston member), **32a** projection, **32b** groove, **34** piston back member, **34a** spring, **36** compressed-air introducing hole

Claims

1. A barrel cam device comprising: a barrel cam; an output table that includes a plurality of cam followers that engage with the barrel cam, and that rotates by rotation of the barrel cam; and a clamp device that clamps the output table when the output table is stopping; wherein the barrel cam device further comprises a supporting portion that rotatably supports the output table; wherein the clamp device includes, a plate member that includes a fixed portion that is fixed to the output table, and an opposing portion that faces the supporting portion with being in a non-contact state, when the output table is rotating, and a pressing member that presses the plate member against the supporting portion when the output table is stopping, the pressing member being a piston member that deforms the opposing portion and presses the opposing portion against the supporting portion by moving and being in contact with the opposing portion when the output table is stopping; wherein the barrel cam device further comprises a rotating shaft body, that is mounted to a central portion of the output table and that rotates integrally with the output table; and wherein the piston member is provided throughout from a side where the barrel cam is located when viewed from the rotating shaft body to a side where the barrel cam is not located when viewed from the rotating shaft body.
2. The barrel cam device according to claim 1, wherein the barrel cam device further comprises a housing that accommodates the output table, and the plate member and the pressing member are provided within the housing.
3. The barrel cam device according to claim 1, wherein the fixed portion is fixed to a table lower surface of the output table, when the output table is rotating, the opposing portion faces a supporting-portion lower surface of the supporting portion while being in the non-contact state, and the pressing member presses the opposing portion against the supporting-portion lower surface when the output table is stopping.
4. The barrel cam device according to claim 3, wherein the fixed portion has a through hole, and the fixed portion and the cam follower are fixed to the table lower surface by a common bolt in a state where the cam follower passes through the through hole.
5. A barrel cam device comprising: a barrel cam; an output table that includes a plurality of cam followers that engage with the barrel cam, and that rotates by rotation of the barrel cam; and a clamp device that clamps the output table when the output table is stopping; wherein the barrel cam device further comprises a supporting portion that rotatably supports the output table; wherein the clamp device includes, a plate member that includes a fixed portion that is fixed to the output table, and an opposing portion that faces the supporting portion with being in a non-contact state, when the output table is rotating, and a pressing member that presses the plate member against the supporting portion when the output table is stopping, the pressing member being a piston member that deforms the opposing portion and presses the opposing portion against the supporting portion by moving and being in contact with the opposing portion when the output table is stopping; and wherein the piston member has a groove that accommodates the cam follower with being in the non-contact state.
6. The barrel cam device according to claim 5, wherein the barrel cam device further comprises a rotating shaft body that is mounted to a central portion of the output table and that rotates integrally with the output table, and the piston member is provided throughout from a side where the barrel

cam is located when viewed from the rotating shaft body to a side where the barrel cam is not located when viewed from the rotating shaft body.

7. A barrel cam device comprising: a barrel cam; an output table that includes a plurality of cam followers that engage with the barrel cam, and that rotates by rotation of the barrel cam; and a clamp device that clamps the output table when the output table is stopping; wherein the barrel cam device further comprises a supporting portion that rotatably supports the output table; wherein the clamp device includes, a plate member that includes a fixed portion that is fixed to the output table, and an opposing portion that faces the supporting portion with being in a non-contact state, when the output table is rotating, and a pressing member that presses the plate member against the supporting portion when the output table is stopping, the pressing member being a piston member that deforms the opposing portion and presses the opposing portion against the supporting portion by moving and being in contact with the opposing portion when the output table is stopping; and wherein the barrel cam device further comprises, a housing that accommodates the output table, a part of the housing serves as a cylinder member that accommodates the piston member, the housing is provided with a compressed-air introducing hole that introduces a compressed air into the cylinder member, and an area of a pressed surface of the piston member that is pressed by the compressed air is more than half of an area of a table surface of the output table.
