

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409970
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Learn; Angela E.

Container with integral condiment pocket

Abstract

Unitary blank for forming a container includes a base panel, a back body panel, a front body panel, a first side panel, a second side panel, and a pocket portion. The pocket portion includes a support panel, a pocket flap, a first side tab, and a second side tab. The first and second side panels are configured to be joined to the back body panel such that the front and back body panels and the first and second side panels define a container. A support panel of the pocket portion is configured to be separated from the front body panel along a front upper edge and joined to the back body panel such that the pocket portion and the back body panel define a pocket therebetween. A container and a method for forming a container from a unitary blank are also provided.

Inventors:	Learn; Angela E. (Gilbertsville, PA)
Applicant:	PACTIV LLC (Lake Forest, IL)
Family ID:	84798496
Assignee:	PACTIV LLC (Lake Forest, IL)
Appl. No.:	18/648878
Filed:	April 29, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240359860 A1	Oct. 31, 2024

Related U.S. Application Data

continuation parent-doc US 17860245 20220708 US 11999538 child-doc US 18648878
us-provisional-application US 63219634 20210708

Publication Classification

Int. Cl.: **B65D5/44** (20060101); **B65D5/02** (20060101); **B65D5/18** (20060101); **B65D5/42** (20060101)

U.S. Cl.:

CPC **B65D5/44** (20130101); **B65D5/0209** (20130101); **B65D5/18** (20130101); **B65D5/4279** (20130101);

Field of Classification Search

CPC: B65D (5/44); B65D (5/0209); B65D (5/18); B65D (5/4279); B65D (5/48002); B65D (81/3205); B65D (5/6685); B65D (31/12); B65D (5/443); A47G (21/001); A45F (2003/205)

USPC: 229/400; 229/904; 229/906; 229/120.18; 229/120.13; 229/120.22; 229/72; 229/120.08; 229/120.02; 229/902; 229/106; 206/541; 206/561; 220/23.8; 220/23.86; 220/505; 220/62; 383/38; 426/120

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4126261	12/1977	Cook	N/A	N/A
4955528	12/1989	Schluckebier	N/A	N/A
5540333	12/1995	Gonzalez et al.	N/A	N/A
5626283	12/1996	Mellon	N/A	N/A
5720429	12/1997	Cordle	N/A	N/A
5875957	12/1998	Yocum	N/A	N/A
6050482	12/1999	Cai	N/A	N/A
6053403	12/1999	Cai	N/A	N/A
6102208	12/1999	Huang	206/541	B65D 81/3205
6119930	12/1999	Lunstra	229/116	B65D 5/48002
6182890	12/2000	Sattler	229/104	B65D 5/3685
6216946	12/2000	Cai	N/A	N/A
6349874	12/2001	Hill	229/405	B65D 5/48002
6471119	12/2001	Cai	N/A	N/A
6561414	12/2002	Cai	N/A	N/A
7140532	12/2005	Holt	229/405	B65D 81/3205
8584884	12/2012	Learn et al.	N/A	N/A
8955738	12/2014	Cai	229/404	B65D 5/18
9499296	12/2015	Mills et al.	N/A	N/A
9809373	12/2016	Gallimore	N/A	N/A
9957080	12/2017	Kastanek	N/A	N/A
10329049	12/2018	Learn et al.	N/A	N/A
10661940	12/2019	Hajek	N/A	N/A
11059621	12/2020	Nowak et al.	N/A	N/A
11198536	12/2020	Lombard et al.	N/A	N/A

11440697	12/2021	Holley, Jr.	N/A	N/A
2006/0016863	12/2005	Holt et al.	N/A	N/A
2012/0292382	12/2011	Cai et al.	N/A	N/A
2013/0075392	12/2012	Learn et al.	N/A	N/A
2017/0057689	12/2016	Learn et al.	N/A	N/A
2022/0185539	12/2021	Barlow	N/A	B65D 5/48

OTHER PUBLICATIONS

U.S. Appl. No. 17/860,245 (U.S. Pat. No. 11,999,538), filed Jul. 8, 2022 (Jun. 4, 2024). cited by applicant

U.S. Appl. No. 17/860,245, filed Apr. 29, 2024 Issue Fee Payment. cited by applicant

U.S. Appl. No. 17/860,245, filed Jan. 31, 2024 Notice of Allowance and Fees Due. cited by applicant

U.S. Appl. No. 17/860,245, filed Dec. 28, 2023 Amendment After Non-Final Action. cited by applicant

U.S. Appl. No. 17/860,245, filed Aug. 29, 2023 Non-Final Rejection. cited by applicant

U.S. Appl. No. 17/860,245, filed Aug. 22, 2023 Response to Restriction Requirement Filed. cited by applicant

U.S. Appl. No. 17/860,245, filed Jul. 5, 2023 Requirement for Restriction/Election. cited by applicant

International Search Report and Written Opinion mailed Dec. 28, 2022 in International Application No. PCT/US22/36443. cited by applicant

Primary Examiner: Demeree; Christopher R

Attorney, Agent or Firm: Baker Botts L.L.P.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application claims priority to U.S. Provisional Application Ser. No. 63/219,634 filed Jul. 8, 2021, and U.S. application Ser. No. 17/860,245 filed Jul. 8, 2022, the entire contents of which are hereby incorporated by reference in their entirety.

BACKGROUND

Field of the Disclosed Subject Matter

(1) The present disclosed subject matter relates to a container for packaging and serving of food items, such as chicken nuggets, french fries, and other bite-size foods. Particularly, the present disclosed subject matter is directed to a container for holding food items, wherein the container has an integral pocket for holding items, such as condiments.

DESCRIPTION OF RELATED ART

(2) A variety of food items, such as french fries, onion rings, chicken nuggets, popcorn shrimp, and other bite-size foods, are often served from small paperboard containers. These containers can be pouch-shaped, such as commonly used for french fries, or can be box-shaped and have a lid to contain the food item, such as deli items or the like. Exemplary containers for packaging and serving a variety of food items are provided in U.S. Pat. Nos. 10,329,049; 6,050,482; 6,053,403; 6,216,946; 6,561,414; and 8,584,884, each of which is incorporated by reference herein in its entirety.

(3) Containers of this type can be formed of foldable paperboard, and can be a single-use product

used in large quantities. As such, it can be desirable to reduce or minimize the costs associated with materials, manufacturing, storage, shipping, manner of use, and the like, of such containers.

(4) It can also be desirable to provide a container with an integral pocket therein to hold items such as condiments. In this manner, each portion or compartment can contain a serving of a different product, with the different products separated by the divider.

SUMMARY

(5) The purpose and advantages of the disclosed subject matter will be set forth in and apparent from the description that follows, as well as will be learned by practice of the disclosed subject matter. Additional advantages of the disclosed subject matter will be realized and attained by the methods and systems particularly pointed out in the written description and claims hereof, as well as from the appended drawings.

(6) To achieve these and other advantages and in accordance with the purpose of the disclosed subject matter, as embodied and broadly described, the disclosed subject matter includes a unitary blank for forming a container. The blank includes a base panel, a back body panel, a front body panel, a first side panel, a second side panel, and a pocket portion. The base panel has a base front edge and a base back edge. The back body panel extends from the base back edge to define a back base fold line therebetween. The back body panel has a back upper edge. The front body panel extending from the base front edge to define a front base fold line therebetween. The front body panel has a first front side edge, a second front side edge, and a front upper edge. The first side panel extends from the first front side edge to define a first front side fold line therebetween. The second side panel extends from the second front side edge to define a second front side fold line therebetween. The pocket portion extends from the front upper edge. The pocket portion includes a support panel, a pocket flap, a first side tab, and a second side tab. The support panel has a support top edge, a first support side edge, and a second side support edge. The pocket flap extends from the support top edge to define a pocket portion fold line therebetween. The first side tab extends from the first support side edge, and the first side tab is coupled to the first side panel. The second side tab extends from the second support side edge, and the second side tab is coupled to the second side panel. The first and second side panels are configured to be joined to the back body panel such that the front body panel, back body panel, first side panel, and second side panel define a container. The support panel of the pocket portion is configured to be separated from the front body panel along the front upper edge and joined to the back body panel such that the pocket portion and back body panel define a pocket therebetween.

(7) As embodied herein, the first side panel can include a first side first portion, a first side second portion, and a first side third portion. The first side first portion can extend from the first front side fold line to a first side second portion fold line. The first side second portion can extend from the first side second portion fold line to a first side third portion fold line. The first side third portion can extend from the first side third portion fold line. The second side panel can include a second side first portion, a second side second portion, and second side third portion. The second side first portion can extend from the second front side fold line to a second side second portion fold line. The second side second portion can extend from the second side second portion fold line to a second side third portion fold line. The second side third portion can extend from the second side third portion fold line. The first side tab of the pocket portion can be joined to the first side second portion of the first side panel along the first side second portion fold line. The second side tab of the pocket portion can be joined to the second side second portion of the second side panel along the second side second portion fold line.

(8) As embodied herein, the front upper edge can be cut along at least a length thereof. The front upper edge can be substantially arcuate in shape. The back upper edge can be substantially arcuate in shape and can have a concave notch defined therein. The pocket portion can have a pocket upper edge substantially arcuate in shape and can have a convex projection extending therefrom. The base panel can have a base fold line defined therein spaced from the base front edge and base back

edge.

(9) The disclosed subject matter also includes a container having a base panel, a back body panel, a front body panel, a first side panel, a second side panel, and a pocket portion. The base panel has a base front edge and a base back edge. The back body panel extends from the base back edge to define a back base fold line therebetween. The back body panel has a back upper edge. The front body panel extends from the base front edge to define a front base fold line therebetween. The front body panel has a first front side edge, a second front side edge, and a front upper edge. The first side panel is joined to the back body panel, and the first side panel extending from the first front side edge to define a first front side fold line therebetween. The second side panel is joined to the back body panel, and the second side panel extending from the second front side edge to define a second front side fold line therebetween. The pocket portion is joined to the back body panel. The pocket portion includes a support panel, a pocket flap, a first side tab, and a second side tab. The support panel has a support top edge, a first support side edge, and a second side support edge. The pocket flap extends from the support top edge to define a pocket portion fold line therebetween. The first side tab extends from the first support side edge, and the first side tab is coupled to the first side panel. The second side tab extends from the second support side edge, and the second side tab is coupled to the second side panel. The pocket portion and back body panel define a pocket therebetween. The pocket is moveable between a closed configuration and an open configuration by pivoting the pocket flap about the pocket portion fold line.

(10) As embodied herein, the first side panel can include a first side first portion, a first side second portion, and a first side third portion. The first side first portion can extend from the first front side fold line to a first side second portion fold line. The first side second portion can extend from the first side second portion fold line to a first side third portion fold line. The first side third portion can extend from the first side third portion fold line. The second side panel can include a second side first portion, a second side second portion, and second side third portion. The second side first portion can extend from the second front side fold line to a second side second portion fold line. The second side second portion can extend from the second side second portion fold line to a second side third portion fold line. The second side third portion can extend from the second side third portion fold line. The first side tab of the pocket portion can be joined to the first side second portion of the first side panel. The second side tab of the pocket portion can be joined to the second side second portion of the second side panel.

(11) The disclosed subject matter also includes a method of forming a container including providing a blank. The blank includes a base panel, a back body panel, a front body panel, a first side panel, a second side panel, and a pocket portion. The base panel has a base front edge and a base back edge. The back body panel extends from the base back edge to define a back base fold line therebetween. The back body panel has a back upper edge. The front body panel extending from the base front edge to define a front base fold line therebetween. The front body panel has a first front side edge, a second front side edge, and a front upper edge. The first side panel extends from the first front side edge to define a first front side fold line therebetween. The second side panel extends from the second front side edge to define a second front side fold line therebetween. The pocket portion extends from the front upper edge. The pocket portion includes a support panel, a pocket flap, a first side tab, and a second side tab. The support panel has a support top edge, a first support side edge, and a second side support edge. The pocket flap extends from the support top edge to define a pocket portion fold line therebetween. The first side tab extends from the first support side edge, and the first side tab is coupled to the first side panel. The second side tab extends from the second support side edge, and the second side tab is coupled to the second side panel. The method further includes joining the first and second side panels to the back body panel such that the front body panel, back body panel, first side panel, and second side panel define a container. The method further includes separating the support panel of the pocket portion from the front body panel and joining the support panel to the back body panel such that the pocket portion

and back body panel define a pocket therebetween.

(12) As embodied herein, the first side panel can include a first side first portion, a first side second portion, and a first side third portion. The first side first portion can extend from the first front side fold line to a first side second portion fold line. The first side second portion can extend from the first side second portion fold line to a first side third portion fold line. The first side third portion can extend from the first side third portion fold line. The second side panel can include a second side first portion, a second side second portion, and second side third portion. The second side first portion can extend from the second front side fold line to a second side second portion fold line. The second side second portion can extend from the second side second portion fold line to a second side third portion fold line. The second side third portion can extend from the second side third portion fold line. The method can further include joining the first side tab of the pocket portion to the first side second portion of the first side panel. The method can further include joining the second side tab of the pocket portion to the second side second portion of the second side panel.

(13) It is to be understood that both the foregoing general description and the following detailed description are exemplary and are intended to provide further explanation of the disclosed subject matter claimed.

(14) The accompanying drawings, which are incorporated in and constitute part of this specification, are included to illustrate and provide a further understanding of the method and system of the disclosed subject matter. Together with the description, the drawings serve to explain the principles of the disclosed subject matter.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1a is a plan view of a unitary blank for a container according to an aspect of the disclosed subject matter.

(2) FIG. 1b is another plan view of the unitary blank for a container of FIG. 1a.

(3) FIG. 2a is a right perspective view of a container formed from the unitary blank of FIG. 1a.

(4) FIG. 2b is a left perspective view of the container formed from the unitary blank of FIG. 1a.

DESCRIPTION OF THE DISCLOSED SUBJECT MATTER

(5) Reference will now be made in detail to the disclosed subject matter, examples of which are illustrated in the accompanying drawings. The structure and corresponding method of operation of the disclosed subject matter will be described in conjunction with the detailed description of the system.

(6) The apparatus and methods presented herein may be used for transport of food items and other perishable and nonperishable products. The disclosed subject matter is particularly suited for packaging, serving, and storing of food items.

(7) In accordance with the disclosed subject matter herein, the unitary blank for forming a container generally includes a base panel, a back body panel, a front body panel, a first side panel, a second side panel, and a pocket portion. The base panel has a base front edge and a base back edge. The back body panel extends from the base back edge to define a back base fold line therebetween. The back body panel has a back upper edge. The front body panel extends from the base front edge to define a front base fold line therebetween. The front body panel has a first front side edge, a second front side edge, and a front upper edge. The first side panel extends from the first front side edge to define a first front side fold line therebetween. The second side panel extends from the second front side edge to define a second front side fold line therebetween. The pocket portion extends from the front upper edge. The pocket portion includes a support panel, a pocket flap, a first side tab, and a second side tab. The support panel has a support top edge, a first support side edge, and a second

side support edge. The pocket flap extends from the support top edge to define a pocket portion fold line therebetween. The first side tab extends from the first support side edge, and the first side tab is coupled to the first side panel. The second side tab extends from the second support side edge, and the second side tab is coupled to the second side panel. The first and second side panels are configured to be joined to the back body panel such that the front body panel, back body panel, first side panel, and second side panel define a container. The support panel of the pocket portion is configured to be separated from the front body panel along the front upper edge and joined to the back body panel such that the pocket portion and back body panel define a pocket therebetween. A container having a base panel, front and back body panels, first and second side panels, and a pocket portion is also provided. A method for forming a container is also provided.

(8) The accompanying figures, where like reference numerals refer to identical or functionally similar elements throughout the separate views, serve to further illustrate the disclosed subject matter and to explain various principles and advantages all in accordance with the disclosed subject matter. For purpose of explanation and illustration, and not limitation, the disclosed subject matter is shown in FIGS. **1a-2b**. The container is suitable for use with a wide variety of hot and cold food items, such as fruit slices, chips, bread sticks, candies, and other suitable bite-size food items, particularly if typically consumed with a dipping sauce or the like. The container disclosed herein is particularly suitable and beneficial for use with hot, prepared food items, such as chicken nuggets, french fries, onion rings, and popcorn shrimp, wherein the container can be used for transporting such food items as well as serving of different type of products (e.g., french fries with condiments) each in separate portions or compartments in the container.

(9) For purpose of illustration, and not limitation, reference will made herein to a container intended to contain food items. Additionally, as used herein, the terms “front,” “back,” “side,” “upper,” “top,” and “base” are used for the purpose of illustration only, and not limitation. That is, it is recognized that the terms “front,” “back,” “side,” “upper,” “top,” and “base” are merely used herein as a point of reference.

(10) For purpose of illustration and not limitation, reference is made to a unitary blank **100** for a container shown in FIGS. **1a** and **1b**. Additionally, for purpose of understanding, reference is made in conjunction to the container **200** of FIGS. **2a** and **2b** formed by the blank **100** of FIGS. **1a** and **1b**.

(11) As shown in FIG. **1a**, the blank **100** generally includes a base panel **104**, a front body panel **102**, a back body panel **106**, a first side panel **110a**, a second side panel **110b**, and a pocket portion **112**. The base panel **104** has a base front edge **107a** and a base back edge **107b**. The back body panel **106** extends from the base back edge **107b** to define a back base fold line **109b** therebetween and along the base back edge **107b**. The back body panel **106** has a back upper edge **140**. The front body panel **102** extends from the base front edge **107a** to define a front base fold line **109a** therebetween and along the base front edge **107a**. The front body panel **102** has a first front side edge **108a**, a second front side edge **108b**, and a front upper edge **114**. The first side panel **110a** extends from the first front side edge **108a** to define a first front side fold line **124a** therebetween. The second side panel **110b** extends from the second front side edge **108b** to define a second front side fold line **124b** therebetween. The pocket portion **112** extends from the front upper edge **114**. The pocket portion **112** includes a support panel **116**, a pocket flap **118**, a first side tab **122a**, and a second side tab **122b**. The support panel **116** has a support top edge **117**, a first support side edge **119a**, and a second side support edge **119b**. The pocket flap **118** extends from the support top edge **117** to define a pocket portion fold line **120** therebetween. The first side tab **122a** extends from the first support side edge **119a**. The first side tab **122a** is coupled to the first side panel **110a**. The second side tab **122b** extends from the second support side edge **119b**. The second side tab **122b** is coupled to the second side panel **110b**. The first and second side panels **110a**, **110b** are configured to be joined to the back body panel **106** such that the front body panel **102**, back body panel **106**, first side panel **110a**, and second side panel **110b** define a container **200**, as shown in FIGS. **2a** and

2b. The support panel **116** of the pocket portion **112** is configured to be separated from the front body panel **102** along the front upper edge **114** and joined to the back body panel **106** such that the pocket portion **112** and back body panel **106** define a pocket **211** therebetween, as shown in FIGS. **2a** and **2b**. Although front and back body panels **102**, **106** are illustrated, any suitable number of body portions can be used.

(12) With reference to the blank **100** of FIG. **1a**, the first side panel **110a** can include a first side first portion **126a**, a first side second portion **128a**, and a first side third portion **130a**. The first side first portion **126a** can extend from the first front side fold line **124a** to a first side second portion fold line **132a**. The first side second portion **128a** can extend from the first side second portion fold line **132a** to a first side third portion fold line **134a**. The first side third portion **130a** can extend from the first side third portion fold line **134a**. The second side panel **110b** can include a second side first portion **126b**, a second side second portion **128b**, and second side third portion **130b**. The second side first portion **126b** can extend from the second front side fold line **124b** to a second side second portion fold line **132b**. The second side second portion **128b** can extend from the second side second portion fold line **132b** to a second side third portion fold line **134b**. The second side third portion **130b** can extend from the second side third portion fold line **134b**. The first side tab **122a** of the pocket portion **112** can be joined to the first side second portion **128a** of the first side panel **110a** along the first side second portion fold line **132a**. The second side tab **122b** of the pocket portion **112** can be joined to the second side second portion **128b** of the second side panel **110b** along the second side second portion fold line **132b**. Side panels **110a**, **110b** and portions **126a**, **126b**, **128a**, **128b**, **130a**, **130b** can be of any suitable shape and dimension. Although side panels **110a**, **110b** and portions **126a**, **126b**, **128a**, **128b**, **130a**, **130b** are illustrated, any suitable number of side panels and portions can be used.

(13) For purpose of illustration and not limitation, and as embodied herein, the front upper edge **114** of front body panel **102** can have any suitable shape and dimension, including but not limited to substantially arcuate in shape. The upper edge **114** can be die-cut during manufacture along at least a length thereof. The back upper edge **140** of back body panel **106** can have any suitable shape and dimension, including but not limited to substantially arcuate in shape. The back upper edge **140** can have a concave notch **142** defined therein. The notch **142** can have any suitable shape and dimension, including but not limited to “c”-shaped or arcuate, radius corners, or angled straight edges. The pocket portion **112** can have a pocket upper edge **136**, and the pocket upper edge **136** can have any suitable shape and dimension, including but not limited to substantially arcuate in shape. The pocket upper edge **136** can have a convex projection **138** extending therefrom. The projection **138** can be of any suitable shape and dimension, including but not limited to “c”-shaped or arcuate, radius corners, or angled straight edges. Additionally or alternatively, the convex projection **138** can be the convex mirror image of the concave notch **142**. The support top edge **117** and pocket portion fold line **120** of support panel **116** can have any suitable shape and dimension, including but not limited to substantially arcuate in shape.

(14) For purpose of illustration and not limitation, and as embodied herein, the base panel **104** of blank **100** can have a base fold line **105** defined therein spaced from the base front edge **107a** and the base back edge **107b**. The base front edge **107a** and the base back edge **107b** can have any suitable shape and dimension, including but not limited to curved, straight, or substantially arcuate in shape.

(15) It is to be recognized that the dimensions and relative proportions of the front body panels **102**, **202**, back body panels **106**, **206**, etc., of the blank **100** or container **200** will vary according to the exact size and intended use of the blank **100** or container **200**. For purpose of illustration and not limitation, with reference to the blank **100** of FIG. **1b**, the blank can have a length **L1** of about 10.0 to 14.0 inches, a length **L2** of about 1.5 to 3.0 inches, a length **L3** of about 5.0 to 6.5 inches, a length **L4** of about 1.0 to 2.5 inches. The blank can have a width **H1** of about 8.0 to 9.5 inches, a width **H2** of about 3.5 to 5.0 inches, a width **H3** of about 3.0 to 4.0 inches. The blank can have

radius R of about 2.0 to 3.0 degrees. Although particular dimensions are described, any suitable dimensions can be used. It will be apparent to those skilled in the art that various modifications and variations to the exemplary dimensions and angles can be made without departing from the spirit or scope of the disclosed subject matter. One of ordinary skill will recognize that any suitable shape and depth of the container and corresponding blank can be employed, and the disclosed subject matter is not limited to the sizes and shapes illustrated in FIGS. **1a-2b**. Other suitable shapes include rectangles, triangles, cylinders, ovals, various polygons, etc., having any suitable dimensions.

(16) With reference to the blank **100** of FIG. **1a**, as embodied herein, container **200** can be formed from blank **100** by folding the back body panel **106** along the base fold line **105** to extend parallel to the front body panel **102**, and folding the first and second side panels **110a**, **110b** away from the front body panel **102** to join to the back body panel **106**. For purpose of illustration and not limitation, the first side third portion **130a** of the first side panel **110a** can be joined to the back body panel **106**, and the second side third portion **130b** of the second side panels **110b** can be joined to the back body panel **106**. The front body panel **102**, back body panel **106**, first side panel **110a**, and second side panel **110b** can define container **200**. The container **200** can have an interior **201**, front and back body panels **202**, **206**, first and second side panels **210a**, **210b**, and base **204**, as shown in FIGS. **2a** and **2b**. The first and second side panels **110a**, **110b** can be joined to the back body panel **106** using conventional techniques, such as by glue or thermal adhesive or the like. The first and second side third portions **130a**, **130b** can be joined to the back body panel **106** using conventional techniques, such as by glue or thermal adhesive or the like. Although particular features are described, the container **200** can have one or more of the features as included in blank **100**.

(17) Additionally, and with reference to FIG. **1a**, the support panel **116** of the pocket portion **112** can be separated from the front body panel **102** and joined to the back body panel **106** to define pocket **211** of container **200** therebetween having a pocket flap **218**, as shown in FIGS. **2a** and **2b**. The support panel **116** can be joined to the back body panel **106** using conventional techniques, such as by glue or thermal adhesive or the like. The pocket **211** can have a pocket flap **218**. When support panel **116** is joined to the back body panel **106**, the first side tab **122a** can be joined to the first side second portion **128a** of the first side panel **110a** to form first side tab **222a** of container **200**, and the second side tab **122b** can be joined to the second side second portion **128b** of the second side panel **110b** to form second side tab **222b** of container **200**. The first and second side tabs **122a**, **122b** can be joined to the first and second side second portions **128a**, **128b** free of adhesive, or using conventional techniques, such as by glue or thermal adhesive or the like.

(18) For purpose of illustration and not limitation, and as embodied herein, the pocket **211** of container **200** can be moveable between an open position and a closed position by pivoting the pocket flap **218** about a pocket portion fold line **220**. The pocket **211** can have a closed configuration (as shown, for example, in FIG. **2b**) when the pocket flap **218** is parallel to the back body panel **206**. The pocket **211** can have an open configuration (as shown, for example, in FIG. **2a**) when the pocket flap **218** extends towards the interior **201** of the container **200**. For example, for purpose of illustration and not limitation, the pocket flap **218** can be folded about pocket portion fold line **220**, or the pocket flap **218** can fold about pocket portion fold line **220** when an exterior pressure is applied to the tabs **222a**, **222b** or side panels **210a**, **210b**.

(19) The container **200** can have one or more of the features as included in blank **100**. For example, the container **200** can include upper edges **214**, **236**, **240**. The upper edges **214**, **236**, **240** can be of any suitable shape and dimension, including the shapes and dimensions of upper edges **114**, **136**, **140** of blank **100**.

(20) The containers disclosed herein are preferably disposable, but it is contemplated that they may be reused at a future time. Also, the containers can be constructed from materials suitable to be placed in a heating apparatus, such as a microwave, to heat the food and/or used for storage in the

refrigerator or freezer. Additionally, the materials from which the containers are made need not be the same throughout. The containers and blanks described herein can be manufactured from any suitable material, including but not limited to paperboard.

(21) In addition to the disclosed subject matter claimed below, the disclosed subject matter is also directed to other aspects of the disclosed subject matter having any other possible combination of the dependent features claimed below and those disclosed above. As such, the particular features presented in the dependent claims and disclosed above can be combined with each other in other manners within the scope of the disclosed subject matter such that the disclosed subject matter should be recognized as also specifically directed to other aspects of the disclosed subject matter having any other possible combinations. Thus, the foregoing description of the disclosed subject matter has been presented for purposes of illustration and description. It is not intended to be exhaustive or to limit the disclosed subject matter to the aspects of the disclosed subject matter disclosed.

(22) It will be apparent to those skilled in the art that various modifications and variations can be made in the method and system of the disclosed subject matter without departing from the spirit or scope of the disclosed subject matter. Thus, it is intended that the disclosed subject matter include modifications and variations that are within the scope of the appended claims and their equivalents.

Claims

1. A unitary blank for forming a container comprising: a base panel having a base front edge and a base back edge; a back body panel extending from the base back edge to define a back base fold line therebetween, the back body panel having a back upper edge, the back upper edge having a concave notch defined therein; a front body panel extending from the base front edge to define a front base fold line therebetween, the front body panel having a first front side edge, a second front side edge, and a front upper edge; a first side panel extending from the first front side edge to define a first front side fold line therebetween; a second side panel extending from the second front side edge to define a second front side fold line therebetween; and a pocket portion extending from the front upper edge, the pocket portion comprising: a support panel having a support top edge, a first support side edge coupled to the first side panel, and a second side support edge coupled to the second side panel; and a pocket flap extending from the support top edge to define a pocket portion fold line therebetween, the pocket flap having a pocket upper edge with a convex projection extending therefrom, the convex projection having a shape being a mirror image of the concave notch; wherein the first and second side panels are configured to be joined to the back body panel such that the front body panel, back body panel, first side panel, and second side panel define a container, and further wherein the support panel of the pocket portion is configured to be separated from the front body panel along the front upper edge and joined to the back body panel such that the pocket portion and back body panel define a pocket therebetween.

2. The blank of claim 1, wherein the first side panel comprises a first side first portion, a first side second portion, and a first side third portion, the first side first portion extending from the first front side fold line to a first side second portion fold line, the first side second portion extending from the first side second portion fold line to a first side third portion fold line, the first side third portion extending from the first side third portion fold line; and wherein the second side panel comprises a second side first portion, a second side second portion, and second side third portion, the second side first portion extending from the second front side fold line to a second side second portion fold line, the second side second portion extending from the second side second portion fold line to a second side third portion fold line, the second side third portion extending from the second side third portion fold line.

3. The blank of claim 1, wherein the front upper edge is substantially arcuate in shape.

4. The blank of claim 1, wherein the back upper edge is substantially arcuate in shape.

5. The blank of claim 1, wherein the pocket upper edge is substantially arcuate in shape.
6. The blank of claim 1, wherein the base panel has a base fold line defined therein spaced from the base front edge and base back edge.
7. The blank of claim 1, wherein the pocket portion fold line is arcuate.
8. The blank of claim 1, further comprising a first side tab extending from the first support side edge to couple the first support side edge to the first side panel, and a second side tab extending from the second support side edge to couple the second support side edge to the second side panel.
9. The blank of claim 8, wherein the first side tab of the pocket portion is coupled to the first side second portion of the first side panel along the first side second portion fold line, and the second side tab of the pocket portion is coupled to the second side second portion of the second side panel along the second side second portion fold line.
10. A container comprising: a base panel having a base front edge and a base back edge; a back body panel extending from the base back edge to define a back base fold line therebetween, the back body panel having a back upper edge, the back upper edge having a concave notch defined therein; a front body panel extending from the base front edge to define a front base fold line therebetween, the front body panel having a first front side edge, a second front side edge, and a front upper edge; a first side panel joined to the back body panel, the first side panel extending from the first front side edge to define a first front side fold line therebetween; a second side panel joined to the back body panel, the second side panel extending from the second front side edge to define a second front side fold line therebetween; and a pocket portion joined to the back body panel, the pocket portion comprising: a support panel having a support top edge, a first support side edge coupled to the first side panel, and a second side support edge coupled to the second side panel; and a pocket flap extending from the support top edge to define a pocket portion fold line therebetween, the pocket flap having a pocket upper edge with a convex projection extending therefrom, the convex projection having a shape being a mirror image of the concave notch; wherein the pocket portion and back body panel define a pocket therebetween; wherein the pocket is moveable between a closed configuration and an open configuration by pivoting the pocket flap about the pocket portion fold line.
11. The container of claim 10, wherein the first side panel comprises a first side first portion, a first side second portion, and a first side third portion, the first side first portion extending from the first front side fold line to a first side second portion fold line, the first side second portion extending from the first side second portion fold line to a first side third portion fold line, the first side third portion extending from the first side third portion fold line; and wherein the second side panel comprises a second side first portion, a second side second portion, and second side third portion, the second side first portion extending from the second front side fold line to a second side second portion fold line, the second side second portion extending from the second side second portion fold line to a second side third portion fold line, the second side third portion extending from the second side third portion fold line.
12. The container of claim 10, wherein the pocket portion fold line is arcuate.
13. The container of claim 10, further comprising a first side tab extending from the first support side edge to couple the first support side edge to the first side panel, and a second side tab extending from the second support side edge to couple the second support side edge to the second side panel.
14. The container of claim 13, wherein the first side tab of the pocket portion is coupled to the first side second portion of the first side panel, and the second side tab of the pocket portion is coupled to the second side second portion of the second side panel.
15. A method of forming a container comprising: providing a blank comprising: a base panel having a base front edge and a base back edge; a back body panel extending from the base back edge to define a back base fold line therebetween, the back body panel having a back upper edge, the back upper edge having a concave notch defined therein; a front body panel extending from the

base front edge to define a front base fold line therebetween, the front body panel having a first front side edge, a second front side edge, and a front upper edge; a first side panel extending from the first front side edge to define a first front side fold line therebetween; a second side panel extending from the second front side edge to define a second front side fold line therebetween; and a pocket portion extending from the front upper edge, the pocket portion comprising: a support panel having a support top edge, a first support side edge coupled to the first side panel, and a second side support edge coupled to the second side panel; and a pocket flap extending from the support top edge to define a pocket portion fold line therebetween, the pocket flap having a pocket upper edge with a convex projection extending therefrom, the convex projection having a shape being a mirror image of the concave notch; joining the first and second side panels to the back body panel such that the front body panel, back body panel, first side panel, and second side panel define a container; and separating the support panel of the pocket portion from the front body panel and joining the support panel to the back body panel such that the pocket portion and back body panel define a pocket therebetween.

16. The method of claim 15, wherein the first side panel comprises a first side first portion, a first side second portion, and a first side third portion, the first side first portion extending from the first front side fold line to a first side second portion fold line, the first side second portion extending from the first side second portion fold line to a first side third portion fold line, the first side third portion extending from the first side third portion fold line; and wherein the second side panel comprises a second side first portion, a second side second portion, and second side third portion, the second side first portion extending from the second front side fold line to a second side second portion fold line, the second side second portion extending from the second side second portion fold line to a second side third portion fold line, the second side third portion extending from the second side third portion fold line.

17. The method of claim 15, wherein the pocket portion fold line is arcuate.

18. The method of claim 15, wherein the blank further comprises a first side tab extending from the first support side edge to couple the first support side edge to the first side panel, and a second side tab extending from the second support side edge to couple the second support side edge to the second side panel.
