

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12411459
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Anderson; Molly J. et al.

Electronic device

Abstract

An electronic device includes a housing sidewall defining an opening and a display component, such as a display cover, disposed in the opening to form a gap between the housing sidewall and the display component. In at least one example, the cavity is defined by the sidewall and the display cover with the cavity in fluid communication with an external environment through the gap. In at least one example, an epoxy component at least partially defines the cavity and can be in direct contact with the housing sidewall.

Inventors: Anderson; Molly J. (San Francisco, CA), Tissandier; Clement C. (San Francisco, CA), Atura Bushnell; Tyler S. (San Francisco, CA), Werner; Christopher M. (San Jose, CA), Boozer; Brad G. (Campbell, CA), Deschamps; Daniela M. (Palo Alto, CA), Robison; David W. (San Jose, CA), Parker; Michael R. (Loomis, CA)

Applicant: Apple Inc. (Cupertino, CA)

Family ID: 84887279

Assignee: APPLE INC. (Cupertino, CA)

Appl. No.: 18/151177

Filed: January 06, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230229117 A1	Jul. 20, 2023

Related U.S. Application Data

us-provisional-application US 63374738 20220906
us-provisional-application US 63364012 20220502
us-provisional-application US 63266829 20220114

Publication Classification

Int. Cl.: G04G17/04 (20060101); G04G17/08 (20060101); G04G21/08 (20100101)

U.S. Cl.:

CPC G04G17/045 (20130101); G04G17/08 (20130101); G04G21/08 (20130101);

Field of Classification Search

CPC: G04G (17/045); G04G (21/08); G04G (17/02); G04G (17/04); G04G (21/00); G04B (3/048); G06F (1/1637); G06F (1/1656); G06F (1/1671); G06F (1/1688); G06F (1/163); G06F (1/1692); H04R (1/403)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7804453	12/2009	Chiang et al.	N/A	N/A
8630441	12/2013	Shi et al.	N/A	N/A
8818006	12/2013	Yamauchi et al.	N/A	N/A
10484958	12/2018	Sayem et al.	N/A	N/A
10599101	12/2019	Rothkopf et al.	N/A	N/A
10782742	12/2019	Spencer et al.	N/A	N/A
11188151	12/2020	Bushnell	N/A	H10N 30/206
11553608	12/2022	Ko	N/A	N/A
2006/0146650	12/2005	Dinger	N/A	N/A
2009/0120715	12/2008	Saiki	N/A	N/A
2012/0045081	12/2011	Mittleman et al.	N/A	N/A
2013/0129135	12/2012	Gregg et al.	N/A	N/A
2015/0110335	12/2014	Telemaque et al.	N/A	N/A
2016/0058375	12/2015	Rothkopf	N/A	N/A
2017/0135239	12/2016	Hyun et al.	N/A	N/A
2017/0245032	12/2016	Yoon et al.	N/A	N/A
2017/0311812	12/2016	Husheer	N/A	N/A
2018/0020283	12/2017	Zhang et al.	N/A	N/A
2018/0077813	12/2017	Lancaster-Larocque et al.	N/A	N/A
2018/0173166	12/2017	Kayano	N/A	N/A
2018/0241115	12/2017	Cho et al.	N/A	N/A
2019/0045642	12/2018	Prest et al.	N/A	N/A
2019/0082547	12/2018	Werner	N/A	H05K 5/0213
2019/0373360	12/2018	Yu et al.	N/A	N/A
2020/0037460	12/2019	Jeong et al.	N/A	N/A
2020/0203802	12/2019	Jeon et al.	N/A	N/A
2020/0265212	12/2019	Jung et al.	N/A	N/A
2020/0365972	12/2019	Jeon et al.	N/A	N/A
2021/0006876	12/2020	Moon et al.	N/A	N/A
2021/0167487	12/2020	Varma et al.	N/A	N/A

2021/0168230	12/2020	Baker et al.	N/A	N/A
2021/0195772	12/2020	Ko	N/A	N/A
2021/0275030	12/2020	Ghoreyshi	N/A	N/A
2021/0303028	12/2020	Cho et al.	N/A	N/A
2021/0312153	12/2020	Su et al.	N/A	N/A
2023/0225619	12/2022	Tang et al.	N/A	N/A
2023/0229197	12/2022	Deschamps et al.	N/A	N/A
2023/0229205	12/2022	Deschamps et al.	N/A	N/A
2023/0232151	12/2022	Chiang et al.	N/A	N/A
2023/0232547	12/2022	Canales et al.	N/A	N/A
2023/0232560	12/2022	Parker et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
105659626	12/2015	CN	N/A
108227459	12/2017	CN	N/A
111542787	12/2019	CN	N/A
111855020	12/2019	CN	N/A
112788480	12/2020	CN	N/A
112911048	12/2020	CN	N/A
113093511	12/2020	CN	N/A
115552339	12/2021	CN	N/A
3617814	12/2019	EP	N/A
3883266	12/2020	EP	N/A
3929668	12/2020	EP	N/A
4027124	12/2021	EP	N/A
20170001187	12/2016	KR	N/A
2012127812	12/2011	WO	N/A
2015054226	12/2014	WO	N/A
2018016906	12/2017	WO	N/A
2019135856	12/2018	WO	N/A
2020198088	12/2019	WO	N/A
2021057873	12/2020	WO	N/A
2021125815	12/2020	WO	N/A
2021231221	12/2020	WO	N/A

OTHER PUBLICATIONS

Extended European Search Report for EP Application No. 23151557.8, mailed Oct. 11, 2023 (15 pp.). cited by applicant

European Search Report for EP Application No. 23150549.6, mailed Jun. 9, 2023 (9 pp.). cited by applicant

European Search Report for EP Application No. 23150553.8, filed Jun. 15, 2023 (11 pp.). cited by applicant

European Search Report for EP Application No. 23150554.6, mailed Jun. 16, 2023 (11 pp.). cited by applicant

Primary Examiner: Leon; Edwin A.

Attorney, Agent or Firm: Dorsey & Whitney LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S) (1) This claims priority to U.S. Provisional Patent Application No. 63/374,738, filed 6 Sep. 2022, and entitled “ELECTRONIC DEVICE,” to U.S. Provisional Patent Application No. 63/364,012, filed 2 May 2022, and entitled “ELECTRONIC DEVICE,” and to U.S. Provisional Patent Application No. 63/266,829, filed 14 Jan. 2022, and entitled “ELECTRONIC DEVICE,” the disclosures of which are hereby incorporated by reference in their entireties.

FIELD

(1) The present disclosure relates generally to electronic devices. More particularly, the present disclosure relates to wearable electronic devices.

BACKGROUND

(2) Electronic devices are increasingly being designed with device portability in mind, for example, to allow users to use these devices in a wide variety of situations and environments. In the context of wearable devices, these devices can be designed to include many different functionalities and to be operated in many different locations and environments. The components of an electronic device, for example, the processors, memory, antennas, display, and other components can partially determine a level of performance of the electronic device. Further, the arrangement of these components with respect to one another in the device can also determine the level of overall performance of the electronic device.

(3) Continued advances in electronic devices and their components have enabled considerable increases in performance. Existing components and structures for electronic devices can, however, limit the levels of performance of such devices. For example, while some components can achieve high levels of performance in some situations, the inclusion of multiple components in devices sized to enhance portability can limit the performance of the components, and thus, the performance of the device. Consequently, further tailoring and arrangement of components for electronic devices to provide additional or enhanced functionality, without introducing or increasing undesirable device properties, can be desirable.

SUMMARY

(4) In at least one example of the present disclosure, an electronic device can include a housing including a sidewall defining an upper peripheral edge surrounding an opening and a transparent display cover disposed in the opening, the transparent display cover including an outward facing surface. In such an example, the transparent display cover is positioned such that the upper peripheral edge is level with the outward facing surface.

(5) In one example, the electronic device includes a display assembly including the transparent display cover. In one example, the outward facing surface is planar. In one example, the display assembly further includes a touch interface. In one example, the electronic device further includes a protrusion extending from the sidewall, the protrusion defining a recess. In one example, the electronic device further includes a crown disposed in the recess. In one example, the protrusion surrounds a portion of the crown. In one example, the recess includes a first recess, the protrusion further defines a second recess, and the electronic device further includes a button disposed in the second recess.

(6) In at least one example of the present disclosure, an electronic device includes a housing sidewall defining a first speaker vent, a second speaker vent, and an aperture between the first speaker vent and the second speaker vent, and a button disposed in the aperture.

(7) In one example, the housing sidewall defines an internal volume, the electronic device further includes a first speaker disposed within the internal volume, the first speaker positioned to direct sound through the first speaker vent, and the electronic device further includes a second speaker

disposed within the internal volume, the second speaker positioned to direct sound through the second speaker vent. In one example, the housing sidewall further defines a front speaker volume disposed between the housing sidewall and the first and second speakers. In one example, the first speaker vent includes at least two openings defined by the housing sidewall and the second speaker vent consists of a single opening defined by the housing sidewall. In one example, the housing sidewall defines a first side of the electronic device and a second side of the electronic device opposite the first side. In such an example, the first side defines the first and second speaker vents and the aperture. In one example, the second side defines a protrusion defining a recessed feature. In one example, the electronic device further includes a crown disposed in the recessed feature.

(8) In at least one example of the present disclosure, an electronic device includes a housing defining an internal volume and an upper peripheral edge, the housing including a first sidewall defining a first speaker vent and a second speaker vent and a second sidewall opposite the first sidewall, the second sidewall including a protrusion defining a recessed feature, a transparent display cover flush with the upper peripheral edge, a button disposed between the first speaker vent and the second speaker vent, and a dial disposed in the recessed feature. In one example, the upper peripheral edge of the housing is configured to protect the transparent display cover from inadvertent contact during use. In one example, the protrusion is configured to protect the dial from inadvertent contact during use. In one example, the first sidewall defines an aperture between the first speaker vent and the second speaker vent and the button is disposed in the aperture. In one example, the protrusion is a first protrusion, the housing includes a second protrusion extending upward toward the upper peripheral edge, the second protrusion including an upper portion separated from a lower portion by a non-metallic material portion, the upper portion defining the upper peripheral edge, and the upper peripheral edge surrounds the display cover.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The disclosure will be readily understood by the following detailed description in conjunction with the accompanying drawings, wherein like reference numerals designate like structural elements, and in which:

- (2) FIG. 1A shows an example of a wearable electronic device;
- (3) FIG. 1B shows a top view of a portion of the wearable electronic device;
- (4) FIG. 1C shows a bottom view of a portion of the wearable electronic device;
- (5) FIG. 2A shows a perspective view of an example of a wearable electronic device;
- (6) FIG. 2B shows a perspective view of an example of a wearable electronic device;
- (7) FIG. 2C shows an exploded view of an example of a wearable electronic device;
- (8) FIG. 3 shows an exploded view of an example of a wearable electronic device;
- (9) FIG. 4 shows a portion of a sidewall of an example of a wearable electronic device;
- (10) FIG. 5A shows a cross-sectional view of a sidewall of an example of a wearable electronic device;
- (11) FIG. 5B shows another cross-sectional view of a sidewall of an example of a wearable electronic device;
- (12) FIG. 5C shows another cross-sectional view of a sidewall of an example of a wearable electronic device;
- (13) FIG. 6 shows a cross sectional view of an interface between a plastic and metal portion of a sidewall of an example of an electronic device;
- (14) FIG. 7A shows another view of the interface of FIG. 6;
- (15) FIG. 7B shows another view of the interface of FIG. 6;
- (16) FIG. 7C shows another view of the interface of FIG. 6;

(17) FIG. 8 shows a method of bonding a metal substrate to a non-metal substrate;

(18) FIG. 9A shows a cross-sectional view of a sidewall and internal components of an example of a wearable electronic device;

(19) FIG. 9B shows another cross-sectional view of a sidewall and internal components of an example of a wearable electronic device;

(20) FIG. 9C shows another cross-sectional view of a sidewall and internal components of an example of a wearable electronic device;

(21) FIG. 10A shows a top perspective view of a housing sidewall of an example of an electronic device;

(22) FIG. 10B shows a top view of the housing sidewall of FIG. 10A;

(23) FIG. 10C shows a close up top view of a portion of the housing sidewall of FIG. 10A;

(24) FIG. 11 shows a cross-sectional view of a sidewall and internal components of an example of a wearable electronic device;

(25) FIG. 12 shows a top view of a portion of an example of an electronic device including a printed circuit board (PCB) and surrounding electrical contacts;

(26) FIG. 13 shows a top view of a portion of an example of an electronic device including a printed circuit board (PCB) and surrounding electrical contacts;

(27) FIG. 14A shows a cross-sectional view of a sidewall and internal components of an example of a wearable electronic device;

(28) FIG. 14B shows a cross-sectional view of a sidewall and internal components of an example of a wearable electronic device;

(29) FIG. 15A shows a side view of an example of a wearable electronic device;

(30) FIG. 15B shows a cross sectional view thereof;

(31) FIG. 15C shows a circuit diagram equivalent of the device shown in FIGS. 15A and 15B worn by a user;

(32) FIG. 16 shows a PCB of an example of an electronic device;

(33) FIG. 17 shows a portion of a PCB of an example of an electronic device;

(34) FIG. 18 shows a portion of a PCB of an example of an electronic device;

(35) FIG. 19 shows a temperature sensor disposed on an ALS module of an example of an electronic device;

(36) FIG. 20A shows a cross sectional view of a portion of an example of an electronic device;

(37) FIG. 20B shows a close up view of the portion of FIG. 20A;

(38) FIG. 20C shows an example of a speaker frame;

(39) FIG. 20D shows an example of a speaker assembly of an electronic device;

(40) FIG. 20E shows the speaker assembly of FIG. 20D with an example of a button;

(41) FIG. 20F shows another cross sectional view of the speaker assembly of FIG. 20E;

(42) FIG. 20G shows another cross sectional view of the speaker and button assembly of FIG. 20E;

(43) FIG. 20H shows another cross sectional view of the speaker and button assembly of FIG. 20E;

(44) FIG. 20I shows another cross sectional view of the speaker and button assembly of FIG. 20F;

(45) FIG. 20J shows another cross sectional view of the speaker and button assembly of FIG. 20F;

(46) FIG. 20K shows another cross sectional view of the speaker and button assembly of FIG. 20F;

(47) FIG. 21 shows another cross sectional view of the speaker assembly of FIG. 20E;

(48) FIG. 22 shows a user riding a bike while wearing an example of a wearable electronic device;

(49) FIG. 23 shows an example of an electronic device subjected to wind;

(50) FIG. 24 shows an example of an electronic device subjected to wind from various directions;

(51) FIG. 25 shows a top view of an example of an electronic device;

(52) FIG. 26 shows a top view of an example of an electronic device;

(53) FIG. 27 shows a top view of an example of an electronic device; and

(54) FIG. 28 shows a top view of an example of an electronic device.

(55) FIG. 29A shows a bottom view of an example of an electronic device;

- (56) FIG. **29B** shows a cross sectional view of a rear cover of an example of an electronic device;
- (57) FIG. **30** shows a partial cross-sectional view of a rear cover and a fastener of an example of an electronic device;
- (58) FIG. **31** shows a partial cross-sectional view of a rear cover and a fastener of an example of an electronic device;
- (59) FIG. **32** shows an example of a rear cover fastener;
- (60) FIG. **33A** shows another example of a rear cover fastener;
- (61) FIG. **33B** shows another example of a rear cover fastener;
- (62) FIG. **34** shows a top view of another example of a fastener;
- (63) FIG. **35** shows a top view of another example of a fastener;
- (64) FIG. **36A** shows a top view of another example of a fastener;
- (65) FIG. **36B** shows a side view thereof;
- (66) FIG. **37** shows a method of forming the fastener shown in FIG. **36A** and FIG. **36B**;

DETAILED DESCRIPTION

(67) Reference will now be made in detail to representative examples illustrated in the accompanying drawings. It should be understood that the following descriptions are not intended to limit the embodiments to one preferred example or embodiment. To the contrary, it is intended to cover alternatives, modifications, and equivalents as can be included within the spirit and scope of the described embodiments as defined by the appended claims.

(68) The following disclosure generally relates to electronic devices. More particularly, the present disclosure relates to wearable electronic devices. The wearable electronic devices of the present disclosure include tailored arrangements of components to provide additional or enhanced functionality, without introducing or increasing undesirable device properties or performance. In this way, more functionality and componentry can be included in wearable devices for user's to wear and operate in any condition or activity without limiting the functionality and durability of the devices.

(69) Specific examples and embodiments of electronic devices, including wearable electronic devices, are discussed below with reference to FIGS. **1-28**. However, those skilled in the art will readily appreciate that the detailed description given herein with respect to these Figures is for explanatory purposes only and should not be construed as limiting. Furthermore, as used herein, a system, a method, an article, a component, a feature, or a sub-feature comprising at least one of a first option, a second option, or a third option should be understood as referring to a system, a method, an article, a component, a feature, or a sub-feature that can include one of each listed option (e.g., only one of the first option, only one of the second option, or only one of the third option), multiple of a single listed option (e.g., two or more of the first option), two options simultaneously (e.g., one of the first option and one of the second option), or combination thereof (e.g., two of the first option and one of the second option).

(70) FIG. **1A** shows an example of an electronic device **100**. The electronic device shown in FIG. **1A** is a watch, such as a smartwatch. The smartwatch of FIG. **1A** is merely one representative example of a device that can be used in conjunction with the systems and methods disclosed herein. Electronic device **100** can correspond to any form of wearable electronic device, a portable media player, a media storage device, a portable digital assistant ("PDA"), a tablet computer, a computer, a mobile communication device, a GPS unit, a remote control device, or other electronic device. The electronic device **100** can be referred to as an electronic device, or a consumer device. In some examples, the electronic device **100** can include a housing **102** that can carry operational components, for example, in an internal volume at least partially defined by the housing. The electronic device **100** can also include a strap **104**, or other retaining component that can secured the device **100** to a body of a user as desired. Further details of the electronic device are provided below with reference to FIG. **1B**.

(71) FIG. **1B** illustrates the electronic device **100**, for example a smartwatch, that can be

substantially similar to and can include some or all of the features of the devices described herein, including the electronic device **100** shown in FIG. **1A** but without the strap **104**. The device **100** can include a housing **102**, and a display assembly **106** attached to the housing **102**. The housing **102** can substantially define at least a portion of an exterior surface of the device **100**.

(72) The display assembly **106** can include a glass, a plastic, or any other substantially transparent exterior layer, material, component, or assembly. The display assembly **106** can include multiple layers, with each layer providing a unique function, as described herein. Accordingly, the display assembly **106** can be, or can be a part of, an interface component. The display assembly **106** can define a front exterior surface of the device **100** and, as described herein, this exterior surface can be considered an interface surface. In some examples, the interface surface defined by display assembly **106** can receive inputs, such as touch inputs, from a user. In other words, the display assembly **106** can include a touch sensitive layer, or form a touch interface, configured to receive touch inputs from a user.

(73) In some examples, the housing **102** can be a substantially continuous or unitary component and can define one or more openings to receive components of the electronic device **100**. In some examples, the device **100** can include input components such as one or more buttons **108** and/or a crown **110** that can be disposed in the openings. In some examples, a material can be disposed between the buttons **108** and/or crown **110** and the housing **102** to provide an airtight and/or watertight seal at the locations of the openings. The housing **102** can also define one or more openings or apertures, such as aperture **112** that can allow for sound to pass into or out of the internal volume defined by the housing **102**. For example, the aperture **112** can be in communication with a microphone component disposed in the internal volume. In some examples, the housing **102** can define or include a feature, such as an indentation to removably couple the housing **102** and a strap or retaining component.

(74) FIG. **1C** shows a bottom perspective view of the electronic device **100**. The device **100** can include a back cover **114** that can be attached to the housing **102**, for example, opposite the display assembly **106**. The back cover **114** can include ceramic, plastic, metal, or combinations thereof. In some examples, the back cover **114** can include an at least partially electromagnetically transparent component **116**. The electromagnetically transparent component **116** can be transparent to any desired wavelengths of electromagnetic radiation, such as visible light, infrared light, radio waves, or combinations thereof. In some examples, the electromagnetically transparent component **116** can allow sensors and/or emitters disposed in the housing **102** to communicate with the external environment. Together, the housing **102**, display assembly **106** and back cover **114** can substantially define an internal volume and an external surface of the device **100**.

(75) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIGS. **1A-1C** can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts shown in the other figures. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown in the other figures can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIGS. **1A-1C**.

(76) As noted above, portable and wearable electronic devices can be designed to be used in many different environments and during any kind of activity throughout a user's day. For example, wearable electronic watches, headphones, and phones can be carried by a user during exercise, sleep, driving, biking, hiking, swimming, diving, outside in the rain, outside in the sun, and so forth. Wearable electronic devices described herein are configured to withstand the varied and often harsh conditions of various environments, including changing environments and wet environments. Wet environments can include wearing devices in the rain or when submerged during bathing or swimming, for example.

(77) Examples of electronic devices disclosed herein include components, features, arrangements, and configurations that resists damage and corrosion due to exposure to moisture. Some aspects of

devices described herein can include gaps between components through which moisture, water, or other fluids could enter. The gaps may be present for aesthetic purposes or for functional purposes. However, one or more components, including epoxy seals, insulating materials and frames, and other components of devices described herein can be configured to prevent such moisture from entering into the internal volume of the device where sensitive electronic component could be damaged thereby.

(78) Along these lines, FIGS. 2A and 2B show right and left perspective views, respectively, of an example of a wearable electronic device **200** including a housing **202** including sidewalls **228** defining an opening in which the display cover **222** is disposed. The sidewalls can include an upper portion **232** defining an upper peripheral edge surrounding the display cover **222**, a lower portion **234**, and a middle portion **236** disposed between the upper portion **232** and the lower portion **234**. The wearable electronic device **200** can also include a securement strap **203** configured to secure the wearable electronic device **200** to an appendage of the user. In at least one example, the sidewalls **228** of the housing **202** can define an upper peripheral edge of the device **200** surrounding the display cover **222**.

(79) In at least one example, the display cover **222** defines a top surface disposed in a plane. The top surface can include an outward facing surface of the display cover **222**. In at least one example, the display cover **222** can be a transparent display cover disposed above or over other display layers. In at least one example, the outward facing surface of the display cover **222** can be planar. The plane can be level/flush with or set below and recessed relative to the upper peripheral edge of the sidewalls **228**. In this way, when the wearable electronic device **200** comes into contact with a surface or object at or near the upper surface of the display cover **222** and/or the upper peripheral edge of the sidewalls **228**, contact and potential damage to the display cover **222** can be reduced. In one example, the display cover **222** is set flush with or below the upper peripheral edges of the sidewalls **228** to protect the display cover **222** from damage.

(80) In at least one example, as shown in FIG. 2A, the sidewalls **228** can define a first side of the wearable electronic device **200** having a turret or protrusion defining a recessed feature in which a crown **210** is positioned. The turret can include a protrusion extending from a surrounding surface of the sidewall **228**. The crown **210** can be a part of a turn dial button or other functional knob configured to be manipulated by the user. The crown **210** can be disposed in the recessed portion, as noted above, such that the first side of the sidewalls **228** extend outward in a turret configuration and at least partially around the crown **210**. In this way, contacts and bumps against of other objects against the first side of the sidewall **228** during use can contact the sidewall **228** without pressing or turning the crown **210**. In this way, the protrusion and the recessed portion of the first side of the sidewalls **228** prevents inadvertent manipulation of the crown **210**. In at least one example, the protrusion can include a window exposing a circumferential side surface of the crown **210** where a user can manually manipulate the crown **210** within the recess of the turret protrusion. The button **209** shown in FIG. 2A can also be at least partially surrounded by an outwardly extending portion of the sidewall **228**, such that the button **209** is disposed within another recess thereof, to protect the button **209** from inadvertent contacts.

(81) In at least one example, as shown in FIG. 2B, the sidewalls **228** can define a second side opposite the first side shown in FIG. 2A. In such an example, the wearable electronic device **200** can include a first speaker vent **249**, a second speaker vent **247**, and a button **208** disposed within an aperture defined by the sidewalls **228** between the first speaker vent **249** and the second speaker vent **247**. The first and second speaker vents **249**, **247** can provide fluid communication from a common speaker volume behind the sidewall **228** (e.g., within an internal volume defined by the sidewalls **228**) and the external environment. The button **208** can be disposed between the first and second speaker vents **249**, **247** to save space and provide a compact design without interrupting the functionality of the one or more speakers communicating with the external environment through the first and second speaker vents **247**, **249**.

(82) FIG. 2C illustrates an exploded view of another example of an electronic device **200**, which can also be a portion of a wearable electronic watch or other wearable electronic device. Device **200** includes a display assembly **206**, housing **202**, back cover **214**, and electromagnetically transparent component **216**. In addition, the exploded view of FIG. 2A illustrates various internal components that may be disposed within an internal volume defined by the housing **202**, back cover **214**, electromagnetically transparent component **216**, and display assembly **206**. For example, the device **200** can include one or more printed circuit boards (PCBs) **218** and one or more antenna components **220**, electrical connectors and flexes, buttons, seals, gaskets, memory components, processors, sensors, dials, batteries, and so forth.

(83) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIGS. 2A-2C can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts shown in the other figures. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown in the other figures can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIGS. 2A-2C.

(84) FIG. 3 illustrates a close-up view of a portion of the exploded view of the device **200** shown in FIG. 2, including the housing **202** and the display assembly **206**, with the display assembly further exploded to illustrate the display cover **222** and display layers **224**. In addition, the exploded view of FIG. 3 shows a wave ring **226** (also referred to herein as an “elongate conductive member”), which will be described and discussed in more detail hereafter with reference to other figures. In at least one example, the housing **202** includes sidewall or sidewalls **228** that define an internal volume and an opening **230**. When assembled, the display assembly **206** or one or more components of the display assembly **206** can be disposed in the opening to form an outer surface of the device **200** and define the internal volume.

(85) In at least one example, the sidewall **228** can include an upper portion **232** and a lower portion **234**. The upper portion **232** and the lower portion **234** can be separated by a middle portion **236** disposed between the upper portion **232** and the lower portion **234**. In at least one example, the upper portion **232** and the lower portion **234** of the sidewall **228** can include one or more electrically conductive materials and the middle portion **236** can include one or more electrically non-conductive materials and/or an insulating material. The middle portion **236** can be molded to or otherwise adhered to the upper portion **232** and/or the lower portion **234** such that the upper portion **232**, the lower portion **234**, and the middle portion **236** form a single, unitary sidewall **228** of the housing **202**, as shown.

(86) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIG. 3 can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts shown in the other figures. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown in the other figures can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIG. 3.

(87) FIG. 4 illustrates an example of a middle portion **336** separated from the rest of a sidewall of a housing, similar to the middle portion **236** shown as part of the sidewall **228** of FIG. 3. In the example shown in FIG. 4, a non-conductive material component or ring **338** is bonded to the middle portion **336**. In at least one example, the non-conductive material ring **338** can include an epoxy component **338**. The term “epoxy,” as used herein, can include non-conductive adhesives as generally used and understood in the art, including hot-melt adhesives. The middle portion **336** can also include a ridge feature **340** extending at least partially around an internal surface of the middle portion **336**. The ridge feature **340** can form a lower surface of the middle portion **336**. In addition, at least one example, the middle portion **336** can include one or more upper protrusions **342** spaced about and extending inward relative to an external surface of the sidewall **328**. In addition, at least one example of the middle portion **336** can include one or more lower protrusions **344** spaced

about and extending from the middle portion **336**, as shown in FIG. **4**. FIGS. **5A**, **5B**, and **5C** illustrate partial cross-sectional views, as indicated in FIG. **3**, but around various points along the sidewall **228** in order to illustrate the positions and configurations of the middle portion **336**, epoxy component **338**, upper portion **332**, and lower portion **334**.

(88) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIG. **4** can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts shown in the other figures. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown in the other figures can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIG. **4**.

(89) In the first cross-sectional view of FIG. **5A**, the ridge feature **340** and lower protrusion **344** of the middle portion **336** can be seen. In at least one example, the epoxy component **338** is bonded to an upper surface **348** defined by the lower portion **334** of the sidewall **328**. The epoxy component **338** can also be bonded directly to the middle portion **336**, for example including the lower protrusion **344** and a lower surface **346** of the middle portion **336** defined by the ridge feature **340**. FIG. **5B** illustrates another cross-sectional view at a point along the sidewall **328** where an upper protrusion **342** and a lower protrusion **344** of the middle portion **336** can be seen and FIG. **5C** illustrates another cross-sectional view at a point along the sidewall **328** where an upper protrusion **342** of the middle portion **336** can be seen.

(90) As shown in FIGS. **5A**, **5B**, and **5C**, any possible path for moisture to travel from an external environment **350** to the internal volume **352** through the sidewall **328** of the device is blocked by the epoxy component **338** bonded directly to either the lower portion **334** of the sidewall **328** or the middle portion **336**. Thus, the tight bond of the epoxy component **338** against one or more portions **334**, **336** prevents water and moisture from entering into the internal volume **352** from the external environment **350** through the sidewall **328**. In addition to the moisture-tight bond between the epoxy component **338** and the sidewall **328**, in at least one example, the middle portion **336** of the sidewall **328** can be bonded to the upper and lower portions **332**, **334**, respectively, such that the bond therebetween substantially or completely prevents moisture from passing through or into the sidewall **328** at the interface between the middle portion **336** and the upper and lower portions **332**, **334**, respectively. FIGS. **6-8** illustrate the interface and methods of bonding the middle portion **336** to the lower portion **334** and/or the upper portion **332** of the sidewall **328**.

(91) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIGS. **5A-5C** can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts shown in the other figures. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown in the other figures can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIGS. **5A-5C**.

(92) On example of a plastic-metal interface, such as an interface between a conductive bottom portion **434** and a non-conductive middle portion **436**, is shown in FIG. **6**. In at least one example, the bottom portion **434** can include titanium and the middle portion **436** can include a polymer material. In one example, polymer material can include polybutylene terephthalate (PBT) including glass filled PBT. As shown, the titanium material of bottom portion **434** can be treated to form enhanced polymer-Ti bonding at the interface.

(93) In at least one example, surface features including nano-pores and protrusions **454** can be present and the polymer can flow into and around the pores and protrusions during formation to increase the bonding therebetween. In at least one example, an etching treatment can be carried out to form the features **454** shown in FIG. **6**. In at least one example, the etching treatment can include etching with sulfuric acid to form roughened macro-pockets or features in the titanium substrate of the bottom portion **434**. Also, an oxide layer can be formed using a sodium hydroxide oxidation step resulting in the nano-pores and protrusions **454** shown in FIG. **6**.

(94) Along these lines, FIGS. 7A-7C show images of the bottom portion **434** at various stages of the process described above, including a 1,000×SEM image of an acid etched surface in FIG. 7A. FIG. 7B shows a 50,000×SEM image of an oxide surface with uniform oxide formation exhibiting plate-like morphology. FIG. 7C shows a layered double hydroxide interface including protrusions **454**, similar to those illustrated in FIG. 6, into and around which the plastic polymer material of the middle portion **436** can flow and interlock with the metal material of the bottom portion **434** for enhanced bonding, as described above.

(95) FIG. 8 shows a flowchart of an example of a method **460** of forming the interface shown in FIGS. 6-7C. In at least one example, a step **456** includes the sulfuric acid etching step noted above and another step **458** includes the sodium hydroxide oxidation step noted above. In at least one example of the method **460**, between steps **456** and **458**, a de-smutting method **462** can be carried out to de-smut the surface. In at least one example of the de-smutting method **462** shown in FIG. 8, a step **464** can include an alkaline de-smut, for example using sodium hydroxide (NaOH) and another step **466** can include an acid de-smutting step, for example using nitric acid (HNO₃).

(96) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIGS. 6-8 can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts shown in the other figures. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown in the other figures can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIGS. 6-8.

(97) FIGS. 9A-9C illustrate a cross-sectional view of a device **500** similar to FIGS. 5A-5C but with a display assembly **506** disposed in the opening **530** formed by the sidewall **528**. In at least one example, the display assembly **506**, which includes the display cover **522** and one or more other display layers **524** disposed below the display cover **522**, can be disposed in the opening **530** such that a gap **568** is formed between the display assembly **506** and the sidewall **528**. The gap **568** can be understood as a space between the display assembly **506**, or the display cover **522** thereof, and the sidewall **528**, or upper portion **532** thereof, wherein the display cover **522** does not contact the sidewall **528**. In at least one example, an upper surface of the display cover **522** can be flush with, or disposed lower than, an upper surface of the upper portion **532**.

(98) In at least one example, a cavity **570** is formed in which the wave ring **526** is disposed. The cavity can be defined by the sidewall **528**, including the upper portion **532** and the middle portion **536**, the epoxy component **538**, and the display assembly **506** or at least the display cover **522** thereof. In at least one example, the cavity can also be defined by an insulating material **576** disposed between the display assembly **506** and/or display cover **522** thereof and the epoxy component **538**. One or more other components, including an lth (or last) antenna layer **578** or other layers. As noted above, the epoxy component **538** can bond to other layers and components, including the lth antenna layer **578**, middle portion **536**, lower portion **534**, and/or the insulating material **576** to prevent moisture from entering the internal volume **552** from an external environment **550** of the device **500**, such that any moisture or fluids entering the cavity **570** through the gap **568** do not continue on into the internal volume **552**. In this way, the cavity can be fluid-tight.

(99) FIGS. 9A, 9B, and 9C show cross-sectional views at various locations around the sidewall **528** to illustrate how the wave ring **526** disposed in the cavity **570** can contact the upper portion **532** of the sidewall **528** at one or more locations along a length of the wave ring **526**, as shown in FIG. 9B, and contact an electrical contact **572** on the other side of the cavity **570** at one or more other locations along the length of the wave ring **526**, as shown in FIG. 9C.

(100) Accordingly, in at least one example of the present disclosure, the housing sidewall **528** can define an opening **532** and a display component, such as the display cover **522**, can be disposed in the opening **532** to form the gap **568** between the housing sidewall **528** and the display component. In at least one example, the cavity **570** is defined by the sidewall **528** and the display cover **522**

with the cavity **570** in fluid communication with the external environment **550** through the gap **568**. In at least one example, the epoxy component **538** at least partially defines the cavity **570** and can be in direct contact with the housing sidewall **528**.

(101) In at least one example of the electronic device **500**, the housing sidewall **528** has an upper sidewall portion **532** and a lower sidewall portion **534** bonded to a middle sidewall portion **536** disposed between the upper and lower sidewall portions **532**, **534**, respectively. The housing can define the opening **532** and the display assembly **506** can be disposed in the opening **532** to form the gap **568** between the housing and the display assembly **506**. Also, in at least one example, the epoxy component **538** can serve as a seal disposed underneath the display assembly **506** and extend laterally across the gap **568** with the epoxy component seal **538** bonded directly to the middle portion **536** of the sidewall **528**.

(102) In at least one example of the present disclosure, the electronic device **500** can include the sidewall **528** defining the internal volume **552** and the opening **532**. In at least one example, the sidewall **528** can include an upper portion **532**, a lower portion **534**, and a middle portion **536** disposed between and bonded to the upper portion **532** and the lower portion **534**. The device **500** can also include the display cover **522** disposed in the opening **532** and defining the internal volume **552**, the side cavity **570** defined by the display assembly **506** and the sidewall **528**, with the cavity **570** in fluid communication with an external environment **550** through the gap **568** formed between the display assembly **506** and the sidewall **528**, and an epoxy layer **538** contacting the lower portion **534** and the middle portion **536**, and at least partially defining the cavity **570**.

(103) As noted above and as shown in FIGS. **9A-9C**, the device **500** can include the epoxy component **538** at least partially disposed between the display cover **522** of the display assembly **506** and the lower portion **534**, or between one or more other components of the display assembly **506**, including the display layers **524**, and the lower portion **534**. One or more other components can also be disposed or stacked between the epoxy component **538** and the display assembly **506** or cover **522**, for example the *l*th antenna layer **578**. In addition, as shown in FIG. **9C**, one or more examples of the device **500** can include an insulating material **576**. The insulating polymer **576** can include and support a printed circuit board (PCB) **574** disposed in the internal volume **552**.

(104) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIGS. **9A-9C** can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts shown in the other figures. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown in the other figures can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIGS. **9A-9C**.

(105) As noted above, FIGS. **9A**, **9B**, and **9C** show cross-sectional views at various locations around the sidewall **528** to illustrate how the wave ring **526** disposed in the cavity **570** can contact the upper portion **532** of the sidewall **528** at one or more locations along a length of the wave ring **526**, as shown in FIG. **9B**. Accordingly, in at least one example, the middle portion **536** can include gaps or windows through which columns or other portions of the upper portion **532** of the sidewall **528** are exposed through the middle portion **536** such that the wave ring **526** can contact the upper portion **532** directly, as shown in FIG. **9B**. Also, the wave ring **526** can contact an electrical contact **572** on the other side of the cavity **570** at one or more other locations along the length of the wave ring **526**, as shown in FIG. **9C**. The electrical contact **572** can extend through the insulating material **576** and electrically connect to the PCB **574**. In this way, the upper portion **532** of the sidewall **528** can be electrically connected to the PCB **574** through the wave ring **526**. While the contact between the wave ring **526** and the electrical contact **572** is shown in FIGS. **9A-9C** (as well as in FIGS. **12** and **13** below) as resulting from an undulation or circumferential variation (or wave) in the wave ring **526**, the electrical contacts can be made by any number of discrete or continuous geometries such as indents or protrusions on the wave ring **526**, or by discrete or continuous protrusions on the housing. According to this example, any number of mating geometries can be

used between the wave ring **526** and the housing.

(106) In at least one example, the upper portion **532** of the sidewall **528** can be electrically isolated from the lower portion **534** via the intermediary and non-conductive middle portion **536**. In this way, the upper portion **532** can be a resonating element of an antenna of the device **500** with the lower portion **534** of the sidewall **528** acting as an electrical grounding plane relative to the resonating plane of the upper portion **532**. As noted above, the upper portion **532** can be electrically connected to the PCB **574** of the device **500** such that signals received and sent by the resonating upper portion **532** can be directed to the PCB **574** and can be processed with one or more processors or other electronic components of the device **500**, including any processors or other electronic components mounted on the PCB.

(107) The wearable electronic devices described herein can include antennas configured to send and receive electromagnetic signals during use. Incorporating effective antennas into small, compact devices such as wearable electronic watches can be challenging because the greater the distance between a resonating plane and a grounding plane of an antenna, among other factors, the better the performance of the antenna will be. However, space is often limited to create the required Z-distances necessary in compact wearable electronic devices. In devices described herein, the housing and sidewalls of the device can be electrically separated into multiple portions to create resonating elements and grounding elements of an antenna with sufficient separation (Z-distance) therebetween for the housing itself to act as an antenna. However, this design has its own challenges, including electrically connecting the resonating element to a PCB, processor, or other electronic device without reducing the Z-distance of the antenna. Wearable electronic devices described herein are configured to overcome these challenges.

(108) Along these lines, FIGS. **10A** and **10B** show a top perspective view and a top view, respectively, of a subassembly of a device **600**, according to the present disclosure. The subassembly includes housing sidewall **628** that includes the upper portion **632**, lower portion **634**, and middle portion **636** separating the upper portion **632** from the lower portion **634**. As noted above, the upper portion **632** and the lower portion **632** can include electrically conductive material and the middle portion **636** can include electrically insulating or non-conductive material such that the upper portion **632** of the sidewall **628** forms a resonating element of an antenna separated by a distance in the vertical or “Z” direction (or a “Z-distance”) relative to the electrical grounding plane of the lower portion **634**.

(109) The epoxy component **638** can also be bonded to an inside of the sidewall **628** and to the middle portion **636** and the lower portion **634**. In addition, the wave ring **626** is also shown in FIG. **10A**. A close-up view of the subassembly from a top view is shown in FIG. **10C**, with the close-up region indicated in FIG. **10B**, to illustrate a portion of the wave ring **626** extending away from the sidewall **628** to make contact with an electrical contact in the internal volume of the device. As shown in FIG. **10B**, the interior portion of the wave ring **626** includes a number of dimples or protrusions **640** configured to engage electrical contacts **572** that can extend through the insulating material **576** and electrically connect to the PCB **574** (as shown in FIG. **9C**). As noted above, in addition or alternative to the protrusions **640** on the wave ring **626**, protrusions can be formed on the housing to facilitate or ensure a secure connection between the wave ring **626** and the electrical contacts **572**.

(110) FIG. **10A** also illustrates a cutout **650** formed in the inner surface of the housing sidewall **628**. As shown, the cutout **650** extends into the housing sidewall **628** below the middle portion **636** and the epoxy portion **638**. According to one example, the cutout **650** is formed by machining or otherwise removing a slot of the housing sidewall **628** to create a cavity on the upper portion of the interior volume, prior to assembly of the device **600**. As shown, the cutout **650** provides for additional volume within the housing sidewall **628** that can be used for connections or other housings. According to one example, the cutout provides an isolated volume where component connections can be made, such as for microphones or pressure sensors that are typically located

near the exterior of the device **600**, without consuming valuable interior volume. In one example, board to board connections, such as hot-bar soldering, can be performed on the main PCB within the main cavity, and a flexible cable can then extend from the main PCT to the cutout **650** formed in the inner surface of the housing sidewall **628**. Within the cutout **650**, according to one example, a tray **652** that can be fastened to the housing can include a circuit board **654** with any number of components **656**, such as connectors, components, gyroscopes, accelerometers, etc. that can then be connected to the PCB via the flexible cable. According to this example, the transition of a number of connections to previously unused portions of the housing sidewall **628** allows for added room within the housing for additional battery volume or the inclusion of additional connectors or features on the main PCB.

(111) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIGS. **10A-10C** can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts shown in the other figures. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown in the other figures can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIGS. **10A-10C**.

(112) FIG. **11** shows another cross-sectional view similar to the cross-sectional views shown in FIGS. **9A-9C**, where a sidewall **728** includes an upper portion **732**, a middle portion **736**, and a lower portion **734**. The sidewall **728** defines an opening **732** in which a display assembly **706** is disposed, the display assembly **706** including a display cover **722** and one or more other display layers or components **724**. An epoxy component **738** can contact the lower portion **734** and the middle portion **736** as shown and one or more other layers or components can be stacked or disposed between the display cover **722** and the epoxy component **738**, for example the lth antenna layer **772** and the insulating material **776**. In at least one example, the insulating material **776**, which can also be referred to herein as a mounting component **776**, can structurally support one or more other components, including the electrical contact **772** extending there through and/or the display cover **722** or other components **724** of the display assembly **706**.

(113) In at least one example, the display mounting component **776** may be formed from a molded material, such as a molded insulating material, including a polymer (e.g., a low-injection-pressure-overmolded polymer). The material that forms component **776** may be epoxy, polyurethane, and/or other polymer materials. Thermoplastic and/or thermoset polymer may be used in forming component **776**. Heat and/or light (e.g., ultraviolet light) may be used in curing the polymer forming component **776**. As one illustrative example, component **776** may be formed from a thermoset structural adhesive such as a one-part heat-cured epoxy. Other polymer(s) may be used, if desired. Vacuum may be applied to the interior of a mold to help draw liquid polymer into a desired shape within a mold during formation of component **776**.

(114) One or more surfaces of component **776** can serve as a reference surface (datum) that helps establish a desired physical relationship between component **776** and other portions of a device including the display assembly **706**. As an example, component **776** can be attached to an opposing surface of a housing using a layer of adhesive. The shape and location of component **776** relative to display cover layer **722**, display layers **724**, and other structures in display **706** can help establish a desired position for display **706** relative to a device housing. The upper surface of component **776** can be molded directly to the underside of display cover **722** to help form an environmental seal. In some examples, however, the display assembly **706** can include a separate seal that can aid in forming an environmental seal between the display assembly **706** and a housing.

(115) The location of the display mounting component is indicated in FIGS. **11** and **12**. As can be seen, the display mounting component **776** extends around a periphery of the PCB **774**. As the PCB **774** is smaller than the display cover **722**, the molded insulating material of the display mounting component **776** may be adjacent to an edge of the PCB **774**.

(116) In some examples, however, a display assembly **706** for an electronic device can include a

PCB 774 that has one or more major dimensions, such as a width and/or height, which are substantially similar to the corresponding major dimension of the display cover 722 or other components 724 of the display assembly 706. By using a PCB 774 with these dimensional relationships, a tail of the display layer 724 can be made flush with a major surface of the PCB 774 so that only a single shut-off is needed during the molding operation which can be used to form the display mounting component. Accordingly, the molded insulating material of the display mounting component 776 can be disposed on a major surface of the PCB 774 and adjacent to a periphery thereon while also at least partially surrounding the flexible tail of an associated display layers 724. (117) In the present example, the molded material of the display mounting component 776 can also serve to affix the display assembly 706 to the device housing sidewall 728, or at least to a component of the sidewall 728 such as the lower portion 734, and/or to provide an environmental seal between the display cover 722 and the device housing sidewall 728. In some examples, the display mounting component 776 can at least partially define an exterior surface of the device, such as at an upper surface of the upper portion 732. Thus, in some examples, a portion of the insulating molded material of the display mounting component 776 that defines the exterior surface of the device can be positioned between the display cover 722 and a sidewall 728 of the housing. Further, in some examples, the portion of the exterior surface defined by the display mounting component 776 can be substantially level, in line with, and/or flush with portion of the exterior surface defined by the housing sidewall 728 and/or display cover 722.

(118) As noted above, in order to electrically connect the upper portion 732 of the sidewall 728, as a resonating element of an antenna, the electrical connector 772 can extend through the insulating material 776 from the wave ring 726 to the PCB 774 and the wave ring 726 can contact the upper portion 732 of the sidewall 728 at another point or location along the length of the wave ring 726, similar to that shown in FIG. 9B and described above. In this way, while the PCB 774 is disposed lower than the upper portion 732 of the sidewall 728, the upper portion 732 of the sidewall 728 can predominantly define an upper resonating plane separated from the grounding plane defined by the lower portion 734 of the sidewall 728. This increased Z-distance between the upper and lower portions 732, 734 of the sidewall 728 correspondingly increases the performance of the antenna of which the upper portion 732 forms a part, or at least forms a part of a resonating element thereof.

(119) As illustrated in FIG. 11, the wavering 726 can vary in profile. According to one example, the wavering 726 is asymmetric in shape, placing the protrusion or dimple lower on the body so that it provides a better contact with the extension feature 784 of the electrical connector 772. In other words, due to the asymmetric profile of the wave ring 726, the dimple or protrusion sits lower in the channel formed by the sidewall 728, and can make a more secure connection to an extension feature 784 having a lower profile. Additionally, as shown in FIG. 11, the wave ring 726 can include any number of optional back dimples 727 to extend toward the wave ring 726 and towards the extension feature 784, ensuring a consistent contact therewith, as well as promoting contact with the housing. Alternatively, or additionally, the sidewall 728 can have selective protrusions or bump-outs 729 that reduce the distance between the wave ring 726 and the extension feature 784, ensuring a secure contact. Such added connection securement features can be especially beneficial in corners of the sidewall 728 where antenna feeds can be located.

(120) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIG. 11 can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts shown in the other figures. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown in the other figures can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIG. 11.

(121) FIG. 12 shows a top view of a subassembly of a device according to the present disclosure, including a wave ring 826, insulating material 876, electrical contact 872, and PCB 874, which can be similar or part of any of the devices, systems, or subassemblies described herein with reference

to other figures. As shown in FIG. 12, portions of the wave ring **826** can be selectively overmolded **827** or otherwise insulated in areas where metal on metal contact with the housing is not desired, such as where plastic to metal housing interlocks may occur. In the illustrated example of FIG. 12, the electrical contact **872** forms a singular unitary piece extending around the PCB **874** with discrete connection points **882** extending onto and contacting the PCB **882** or electrical circuits/pathways or other components of or on the PCB **882**.

(122) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIG. 12 can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts shown in the other figures. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown in the other figures can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIG. 12.

(123) FIG. 13 shows another example of top view of a subassembly similar to that shown in FIG. 12 but with multiple discrete and separate electrical connectors **972a**, **972b**, and **972c** making contact with the PCB **974**. Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIG. 13 can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts shown in the other figures. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown in the other figures can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIG. 13.

(124) In at least one example, an electronic device can include a sidewall **728** including an antenna, the sidewall defining an internal volume. The device can also include a PCB **774** disposed in the internal volume, an insulating material **776** disposed in the internal volume, and an electrical connector **772** contacting the PCB **774**, the electrical connector **772** extending through the insulating material **776** and forming an electrical contact between the antenna and the PCB **774**.

(125) In one example, the device can include a conductive housing sidewall **728** defining an internal volume, a PCB **774** disposed in the internal volume, an electrical connector **772** contacting the PCB **774** and extending through the insulating material **776**, and an elongate conductive member **726** (also referred to herein as the wave ring **726**) disposed between the housing sidewall **728** and the electrical connector **772**, the elongate conductive member **726** contacting the electrical connector **772** and the housing sidewall **728**.

(126) In one example, an electronic device can include a housing sidewall **728** including a lower portion **734** and an electrically conductive upper portion **732** separated from the lower portion **734** by a non-conductive material **736**, the housing sidewall **728** defining an internal volume and an opening **732**, a display component **722** disposed in the opening **732**, a PCB **774** disposed in internal volume below the display component **722**, an insulating material **776** disposed in the internal volume between the housing sidewall **728** and the PCB **774**, and a connector **772** forming an electrical pathway between the upper conductive portion **732** of the sidewall **728** and the PCB **774**. In such an example, the upper portion **732** can form a ring surrounding a periphery of the display component **722**.

(127) In at least one example, the insulating material **776** is molded to the electrical connector **772**. In one example, as shown in FIG. 12, the insulating material **776** can include a continuous member extending around a periphery of the PCB **774**. Similarly, in at least one example, the insulating material **776** can form or include a closed ring disposed between the PCB **774** and the antenna **732** formed by the upper portion **732** of the sidewall **728**. In one example, the elongate conductive member **726** contacts the electrical connector **772** at a first location along a length of the elongate conductive member **726** and contacts the housing sidewall **728** at a second location along the length of the elongate conductive member **726**. In at least one example, the elongate conductive member **726** contacts the electrical connector **772** at a third location along the length of the elongate conductive member **726** and contacts the housing sidewall **728** at a fourth location along

the length of the elongate conductive member **772**.

(128) In at least one example, the electrical connector **772** includes a continuous member **886**, shown in FIG. **12**, that has one or more discrete extensions features **784**, as shown in FIG. **11**, extending from the continuous member **886** and through the insulating material **776**. The extension features **784** extend through the insulating material **776** to contact the wave ring **726** (or “elongate conductive member”), as shown in FIG. **11**.

(129) As noted above, and with reference now to FIG. **14A**, an increased Z-distance between the upper portion **1032** as a resonating element of an antenna relative to the electrical ground plane of the lower portion **1034** of the sidewall **1028** can increase the performance of the antenna. In order to increase the Z-distance, the display cover **1022** of the device can include a lower beveled surface to make room for the electrical connector **1072** to extend further upward when making contact with the wave ring **1026**, thus increasing the overall plane of the resonating element of the antenna above the grounding plane of the lower portion **1034** of the housing.

(130) For example, as shown in FIG. **14A**, the display cover **1022** includes a lower beveled surface **1084**, which provides a space for the electrical connector **1072** to make an electrical connection with the wave ring **1026**, and thus the upper portion **1032** of the sidewall **1028** that contacts the wave ring **1026**, further upward to increase the Z-distance. The Z-distance between the resonating plane **1088** and the grounding plane **1090** is illustrated in FIG. **14B**. As shown in FIG. **14A**, the electrical connector **1072** extends upward toward the display cover **1022** and into the space that would otherwise be occupied by the display cover **1022** if not for the beveled surface **1084**.

(131) The wave ring **1026** can likewise be raised to the level of contact with the electrical connector **1072** shown in FIG. **14A** to raise the average height/level of the resonating plane relative to the grounding plane formed at least in part by the lower portion **1034** of the sidewall **1028**. In this way, the Z-distance shown in FIG. **14B** can be maximized to increase the average height/level of the resonating plane relative to the grounding plane for improved antenna performance.

(132) In at least one example, the insulating material **1076**, elsewhere referred to herein as the display mounting component, can extend into the spaced adjacent to the beveled surface of the display cover **1022** to support the display cover and other components of the display assembly **1006**, including the various display layers **1024** shown. In addition, in at least one example, a mask layer that can include a PVD layer, ink layer, or other masking layer can be disposed on a lower flat surface **1086** of the display cover **1022** adjacent the beveled surface **1085**. The mask can provide an aesthetic feature that reduces unwanted light scattering and reflections at the transition between the lower surface of the display cover **1022** and the beveled surface **1084**. In at least one example, the mask can be between about 50 microns and 150 microns thick, for example about 100 microns thick.

(133) Thus, in at least one example, an electronic device described herein can include a sidewall **1028** defining an opening, a display component such as the display cover **1022** disposed in the opening. The display cover **1022** can include a lower beveled edge forming a beveled surface facing the internal volume of the device. In such an example, the insulating material **1076** can contact the beveled surface of the display cover **1022** forming a beveled boundary **1078** as shown in FIG. **14A**.

(134) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIGS. **14A** and **14B** can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts shown in the other figures.

Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown in the other figures can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIGS. **14A** and **14B**.

(135) Referring briefly back to the exploded view of a device shown in FIG. **2**, at least one example of the device **200** can include a back cover **214** and an electromagnetically transparent component

216.

(136) Because wearable electronic devices are in contact with the user's body during use, it can be advantageous to use the device for detecting a user's body temperature, including surface and core temperature. However, the temperature of the device and the environment in which it is used can change from moment to moment during use such that detecting the user's core temperature with a wearable device can be challenging. However, devices described herein can overcome this challenge by incorporating more than one temperature sensor in the device at different locations and applying one or more algorithms that include the temperature sensed by each sensor as an input to determine a core temperature of the user.

(137) FIG. 15A illustrates an example of a device, for example a wearable electronic watch device **1700**. In at least one example, the electronic device **1700** can include a housing **1702** defining front and rear openings, with a display component **1706** disposed at the front opening and a rear cover **1714** disposed at the rear opening. The device **1700** of FIG. 15A can also include strap retention features **1779** defined by the housing **1702** for securing a strap to the device **1700**. When a strap is connected to the device **1700** via the strap retention features **1779**, the device **1700** can be configured to be worn by a user, for example on the wrist of a user, with the strap securing the rear cover **1714** against the skin of the user.

(138) In such an example, the device **1700** can be configured to detect a wrist or skin temperature of the user and extrapolate or detect/measure the user's core temperature. In order to do this, in at least one example, the device **1700** can include two or more temperature sensors on or within the device **1700**. For example, a first temperature sensor **1777** can be located at, near, or adjacent the rear cover **1714**, as indicated by the lower dot shown in FIG. 15A, also referred to as the bottom or lower side of the device **1700**. The dot is not a representation of a sensor itself but indicates an approximate location of the first temperature sensor **1777**. In addition, the device **1700** can include a second temperature sensor **1775** located at, near, or adjacent the display component **1706** on an opposite side from the first temperature sensor, also referred to as a top side of the device **1700**.

(139) In at least one example, a processor (not shown in FIG. 15A but disposed inside the device **1700**) can be electrically connected to the first temperature sensor **1777** and the second temperature sensor **1775** and configured to determine a core temperature of a user based on a first temperature detected by the first temperature sensor **1777** and a second temperature detected by the second temperature sensor **1775**.

(140) FIG. 15A shows a partial cross-sectional view of the device **1700** shown in FIG. 15A to illustrate various internal components thereof. As shown, the device **1700** can include a housing **1702** defining front and rear openings and an internal volume, with a display component **1706** disposed at the front opening and a rear cover **1714** disposed at the rear opening. The internal components can include various processors, batteries, microphones, speakers, wires and electrical flexes, antennas, display components, and so forth. In addition, the internal components of the device **1700** can include a first PCB **1773** disposed near, adjacent, and above the rear cover **1714**. In at least one example, the first PCB **1773** can be adhered to the rear cover **1714**. The device **1700** can also include a second PCB **1774** disposed near, adjacent, and beneath the display component **1706**.

(141) As shown in the cross-sectional view of FIG. 15B, the first temperature sensor **1777** can be disposed on the first PCB **1773** and the second temperature sensor **1775** can be disposed on the second PCB **1774**. In at least one example, one or more other electronic components, including heat generating electronic components can be disposed between the first temperature sensor **1777** and the second temperature sensor **1775** or, if not between the temperature sensors, **1777**, **1775**, a part of a thermal path defined from one temperature sensor to the other through one or more internal component of the device **1700**. For example, a battery **1767** can be disposed within the internal volume of the device **1700** at least partially between the first temperature sensor **1777** and the second temperature sensor **1775**.

(142) While the first temperature sensor **1777** can be near the user's wrist to determine the temperature at or near the user's wrist, the device **1700** can include other internal components that may generate or absorb heat such that the system temperature of the device **1700** can affect the accuracy of the measurement of the user's wrist with the first temperature sensor **1777**. Accordingly, in at least some examples, the device **1700** can include the second temperature sensor **1775** that takes into account the system temperature of the device **1700** and one or more algorithms can be used to determine the user's core temperature using measurement taken from both the first temperature sensor **1777** and the second temperature sensor **1775**. In at least one example, the first temperature sensor **1777** and the second temperature sensor can be in electrical communication with one another.

(143) In at least one example, the device **1700** can include one or more processors in electrical communication with the first temperature sensor **1777** and the second temperature sensor **1775**. The one or more processors can determine the user's core temperature from measurement taken by both the first and second temperature sensors **1777**, **1775** with one or more algorithms applied to the measurement to take into account the system temperature and any thermal path existing through the device **1700** and its internal components disposed therein, some of which may be disposed between the first and second temperature sensors **1777**, **1775** or, if not between the temperature sensors, **1777**, **1775**, a part of a thermal path defined from one temperature sensor to the other through one or more internal component of the device **1700**. In this way, determining the user's core temperature can be based, at least in part, on the heat generated by the heat generating components or heat absorbing component or any other components disposed in the internal volume of the device **1700**.

(144) Along these lines, FIG. **15C** illustrates a circuit diagram equivalent to the device **1700** contacting a user **1771** with a contact interface shown at **1769**. The illustrated diagram identifies temperature sensors T.sub.1 and T.sub.2, which can equate to the first and second temperature sensors **1777**, **1775** shown in FIG. **15B**, respectively. The heat transfer path from the user **1771**, through the device **1700**, and out to an external environment can be modeled as a series of resistances illustrated by resistors R.sub.phys, R.sub.contact, R.sub.BC, R.sub.1-2, and R.sub.FC, as shown in FIG. **15C** with R.sub.phys equating to the resistance of the user, R.sub.contact equating to the resistance at the contact interface, R.sub.BC equating to the resistance of the back cover or any other components of the device **1700** between the first temperature sensor T.sub.1 (**1777** in FIG. **15B**) measuring temperature T.sub.1 and the contact interface **1769**, R.sub.1-2 equating to any resistance in the system of the device **1700** including the thermal path between the first temperature sensor **1777** and the second temperature sensor **1775**, and R.sub.FC equating to the resistance of the display component **1706** or any other components of the device **1700** between the second temperature sensor (**1775** in FIG. **15B**) measuring temperature T.sub.2 and the external surface or external environment of the device **1700**.

(145) Using the modeled circuit diagram of heat flow from the wrist through the device **1700** as shown in FIG. **15C**, one or more algorithms can be used to determine the core temperature of the user. For example, a first algorithm modeling the temperature T.sub.BC at the rear cover **1714** of the device **1700** can include:

$$T_{\text{sub.BC}} = T_{\text{sub.1}} + a_{\text{sub.o}}(T_{\text{sub.1}} - T_{\text{sub.2}})$$

where:

$$a_{\text{sub.o}} = R_{\text{sub.BC}} / R_{\text{sub.1-2}}$$

An algorithm modeling a corrected temperature can include:

$$T_{\text{sub.c}} = T_{\text{sub.1}} + c_{\text{sub.o}}(T_{\text{sub.1}} - T_{\text{sub.2}})$$

where:

$$c_{\text{sub.o}} = a_{\text{sub.o}} + h_{\text{sub.o}}$$

and where:

$$h_{\text{sub.o}} = R_{\text{sub.o}} / R_{\text{sub.1-2}}$$

Furthermore, the model can also include self-heating constants (i.e., c.sub.1, a.sub.1, h.sub.1).

(146) In at least one example, more than two temperature sensors can be disposed in the device **1700** with measurement taken and input into one or more algorithms to determine the core temperature of the user when the device **1700** contacts the user. As noted above, in at least one example, one or more electrical and/or heat generating components can be disposed in internal volume of the device **1700** and at least partially between the various sensors or at least as part of a thermal path between the various sensors.

(147) In at least one example, the first temperature sensor **1777** can be disposed directly against or adhered directly to the rear cover **1714** or another portion of the housing **1702** near or adjacent or in contact with the user during use. Similarly, in at least one example, the second temperature sensor **1775** can be disposed directly against, or adhered directly to, the display component **1706** or other portion of the housing **1702**. In at least one example, regardless of where each temperature sensor **1777**, **1775** is disposed, a thermally conductive adhesive, such as a thermally conductive pressure-sensitive adhesive, can be used to secure the temperature sensors **1777**, **1775** to another component within the internal volume of the device **1700**.

(148) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIGS. **15A-15C** can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts shown in the other figures. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown in the other figures can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIGS. **15A-15C**.

(149) FIG. **16** illustrates a PCB **1773** with an example of a location of a temperature sensor **1777**. The PCB **1773** can be disposed near the rear cover **1714** similar to the first PCB **1773** shown in FIG. **15B**. FIG. **26** illustrates a PCB **1774** similar to the second PCB shown in FIG. **15B** that can be disposed in the internal volume of the device **1700** near the display component **1706**. In the illustrated example of FIG. **17**, two locations of a temperature sensor **1775** are shown where the temperature sensor **1775** can be disposed on the PCB **1774** to be at or near the display component **1706** of the device **1700**. In one example shown, the temperature sensor **1775** can be disposed on the ALS module **1765**. FIG. **18** shows another example of locations of the temperature sensor **1775** on an example of a PCB **1774** with one example location of the temperature sensor **1775** being on an ALS module **1765** of the PCB **1774**.

(150) In at least one example, the temperature sensors **1777**, **1775** described herein can be adhered or otherwise secured to a PCB or other component, including the housing **1702** of the device **1700** without any under-fill material between the temperature sensor **1777**, **1775** and the housing **1702** or PCB **1774**. In at least one example, the temperature sensors **1777**, **1775** can be mounted to a PCB **1774**, housing **1702**, or other portion of the device **1700** without any encapsulation over the temperature sensor **1777**, **1775**. The absence of under-fill material and/or encapsulation over the temperature sensor **1777**, **1775** reduces the complexity and uncertainty of the thermal path between the sensors **1777**, **1775** and/or between the sensors **1777**, **1775** and the user's body or the external environment, thus simplifying the modeling and processing of the user's core temperature.

(151) In at least one example, as shown in FIG. **19**, a temperature sensor **1777** is disposed on the ALS module **1765**. In at least one example, as noted above, the temperature sensor **1777** can be adhered to the ALS module **1765** using an SMT/solder or other adhesive or bonding medium without any encapsulation material disposed over and/or encapsulating the temperature sensor **1777**. In such an example, in order to protect the temperature sensor **1777** from physical damage, one or more shields **1767a**, **1767b**, **1767c**, and **1767d** can be disposed around the temperature sensor **1777** such that other components are likely to come into contact with the shields **1767a-d** before coming into contact with the temperature sensor **1777** during assembly or use. The shields **1767a-d** can vary in number, size, position, and configuration but generally are taller than the temperature sensor **1777** such that the shields **1767a-d** physically protect the temperature sensor

1777. In at least one example, the shields **1767a-d** include inexpensive, non-electrically functioning or connected components. In this way, the shields **1767a-d** can absorb contact, be dented, chipped, or otherwise physically damaged during assembly or use of the device **1700** without negatively affecting the functionality of the device **1700** and the temperature sensor **1777**.

(152) In many scenarios or environments where a user may want to wear the devices disclosed herein, it may be advantageous to output high-frequency, high decibel sounds to alert others of an emergency situation such as a fall or injury to the user. These sounds or alerts can be referred to herein as siren alerts and/or sounds. In order to produce high-frequency siren sounds alongside typical lower frequency outputs for normal use, including music, voice outputs, and so forth, at least one example of a device can include a dual speaker system as shown in FIGS. **20A-21**. The speaker assemblies shown herein generally include two speakers sharing a front volume but having separate back volumes associated with each speaker. Separate vents to the external environment, in addition to the separate back volumes, can enable tuning of the speaker assembly to produce clear frequencies in various high and low ranges from the various speakers in the device **1800** shown.

(153) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIGS. **16-19** can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts shown in the other figures. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown in the other figures can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIGS. **16-19**.

(154) FIG. **20A** shows an example of an electronic device **1800** that includes an outer housing **1802** defining an internal volume **1852**, a first speaker **1863** and a second speaker **1861** disposed in the internal volume **1852**, the first speaker **1863** including a frame **1859** disposed around a periphery of a diaphragm **1857** of the first speaker **1863**, a front volume **1855** defined by the outer housing, the first speaker **1863**, and the second speaker **1861**, a first back volume **1853** defined by the first speaker **1863** and the frame **1859**, and a second back volume **1845** defined by the second speaker **1861** and the frame **1859**.

(155) In at least one example, the electronic device **1800** can include an outer housing **1802**, an inner housing **1851** spaced apart from the outer housing **1802**, a speaker assembly disposed between the inner and outer housings **1802**, **1851**. The speaker assembly can include the first speaker **1863**, the second speaker **1861**, and the speaker frame **1859** supporting the first speaker **1863**. The device can further include the first back volume **1853** defined by the inner housing **1851** and the first speaker **1863** and the second back volume **1845** defined by the inner housing **1851** and the second speaker **1861**, with the second back volume **1845** separated from the first back volume **1853** by the speaker frame **1859**.

(156) Another example of the electronic device **1800** can include the outer housing **1802**, the inner housing **1851**, the speaker assembly disposed between the inner and outer housings **1851**, **1802** including the first speaker **1863** and the second speaker **1861**. The device **1800** can also include a front volume **1855** defined by the outer housing **1802** and the speaker assembly, the back volume defined by the inner housing and the speaker assembly and separated into first and second isolated portions **1853** and **1845**, respectively. In at least one example, the device **1800** can also include first vent **1849** defined by the housing **1802** through which a first end of the front volume **1855** is in fluid communication with an external environment and a second vent **1847** defined by the housing **1802** through which a second end of the front volume **1855** is in fluid communication with the external environment.

(157) In at least one example, the front volume **1855** can be isolated from the first and second back volumes **1853** and **1845**, respectively. The speakers **1863**, **1861** can be disposed between the front volume **1855** and the first and second back volumes **1853**, **1845** and the frame **1859** can structurally support the first speaker **1863**. In at least one example, the frame **1859** forms an air-tight seal between the first back volume **1853** and the second back volume **1845**. In addition, as

noted above, the inner housing **1851** can at least partially define the first back volume **1853**. For example, the frame **1859** can include a collar **1843** and a molded seal **1841** extending from the collar **1843** toward the internal volume **1852** and contacting the inner housing **1851** to seal the first back volume **1853** as shown behind/below the first speaker **1863**. The collar **1843** can include a metal ring disposed around the speaker **1863** and configured to redirect magnetic flux around the speaker **1863**. In at least one example, the speaker frame **1859** structurally supports the second speaker **1861**.

(158) In one example, the first speaker **1863** is smaller than the second speaker **1861**. The first speaker **1863** can be referred to as a tweeter and be configured to output higher frequency sound waves than the larger second speaker **1861**. Accordingly, to accommodate the smaller volumetric air displacement caused by the first speaker **1863**, in at least one example, the first back volume **1853** can be smaller than the second back volume **1845**.

(159) In at least one example, as shown in FIGS. **20A** and **20B**, the electronic device **1800** can also include a valve **1839** disposed in an aperture defined by the inner housing **1851** to vent air from the first isolated portion **1853** of the back volume to the internal volume **1852**. In at least one example, the pressure valve **1839** can be configured to equalize pressure between the internal volume **1852** and the back volume **1853**. In at least one example, the valve **1839** can include a mesh and a channel passing through and defined by the inner housing **1851**.

(160) The shared front volume **1855** can be in fluid communication with an external environment through various vents passing through the outer housing **1802**. The location and configuration of each vent can be designed to accommodate high siren-type frequencies output by the smaller tweeter speaker (first speaker **1863**) and lower frequencies output by the second speaker **1861**. In this way, a broader range of frequencies can be output by the speaker assembly clearly and effectively.

(161) In at least one example, the first vent **1849** is formed of a single aperture defined by the outer housing **1802**. The second vent **1847** can include two or more apertures defined by the outer housing **1802**. In at least one example, a distance between any two adjacent apertures of the second vent **1847** can be less than a distance between any aperture of the second vent **1847** and the single aperture of the first vent **1849**.

(162) As noted above, the arrangement and configuration of the speaker assembly of the electronic device **1800** shown in FIGS. **20A** and **20B** enables the speaker assembly to output frequencies in the normal range of daily use, including music, voice, and other typical audio outputs, as well as loud, high frequencies in the range of above 3 kHz, 3.5 kHz, or even above 4.5 kHz from the first smaller speaker **1863** to be used as a siren. The siren can be used in conjunction with a fall-detection system of the device **1800** to alert others if the user has fallen or been injured. During other activities, for example during mountain biking, the siren can output warning signals when coming around a blind corner on a trail or the like. A guardian mode of the device **1800** could activate the siren as an assault whistle or a mugging deterrent.

(163) In order to fit the dual speaker assembly within a tight space between the inner housing **1851** and the outer housing **1802** of the device **1800**, some of the components discussed above and shown in FIGS. **20A-20B** are configured to interface with and be disposed with other component of the device **1800** to form a tight, compact, space-saving device **1800**. For example, the speaker assembly shown in FIGS. **20A** and **20B** can be disposed within the device **1800** in generally the same location as a button of the device, such that the button and the speaker assembly share the same location or portion of the internal volume of the device **1800**. In such an example, the button may include one or more components disposed between through, or with one or more components of the speaker assembly.

(164) In order to accommodate the speaker assembly and the button together in the same area, the speaker frame **1859**, as shown in FIG. **20C**, can include an opening **1835** defined by the frame **1859**. The opening can be positioned to receive one or more components of a button that pass

through the frame **1859**. FIG. 20D illustrates the frame **1859** supporting the first speaker **1863** and the second speaker **1861** and defining the opening **1835**. The opening **1835** can be defined/disposed between the first speaker **1863** and the second speaker **1861**. As shown in FIG. 20E, a button **1808** can include a plunger **1837** that is aligned with and/or extends through the opening **1835** between the first speaker **1863** and the second speaker **1861**.

(165) In at least one example of the electronic device **1800**, the external housing **1802** can define an internal volume **1852** and an aperture **1833**, as labeled in FIG. 20B. The button **1808** can be disposed in the aperture **1833**. The button **1808** can include the plunger **1837** extending into or toward the internal volume **1852** and the speaker frame **1859** can be disposed in the internal volume **1852** and define the opening **1835**. In such an example, the plunger can extend through the opening.

(166) In one example, the frame **1859** can structurally support the first speaker **1863** and the second speaker **1861**. The frame **1859** can be disposed in the internal volume **1852** with the frame **1859** defining the opening **1835** (otherwise referred to herein as a “hole”) between the first and second speakers **1863**, **1861**, respectively. In at least one example, the plunger **1837** can be aligned with the hole/opening **1835**. A portion of the internal volume **1852** between the inner housing **1851** spaced part from the outer housing **1802** can define a speaker volume including the front volume **1855** and the first and second back volumes **1853**, **1845**, respectively. The plunger **1837** can be aligned with the hole **1835** and extend into the speaker volume toward the inner housing **1851**.

(167) In at least one example, the speaker frame **1859** supports the first speaker **1863** and the second speaker **1861** and the opening **1835** is defined between the first speaker **1863** and the second speaker **1861**. Accordingly, in at least one example, the plunger **1837** extends between the first speaker **1863** and the second speaker **1861**. In at least one example, the plunger **1837** can extend through the front volume **1855** and into the back volume **1845**.

(168) In order to seal off the front volume **1855** from the second back volume **1845**, the device **1800** can include a gasket **1825** surrounding the plunger **1837** and forming a fluid-tight seal between the frame **1859** and the plunger **1837**. Thus a fluid-tight seal is formed by the gasket **1825** between the front volume **1855** and the second back volume **1845**. In at least one example, the gasket can include an O-ring disposed around the plunger **1837**. The plunger **1837** can define a recess in which the O-ring can be disposed and positioned between the plunger **1837** and the speaker frame **1859**. The materials, size, and shape of the O-ring **1825** can be selected to keep fluid out of the volumes surrounding the speakers **1863**, **1861** and to tune the tactile sensation experienced by the user when depressing the button **1808**.

(169) In addition, as the button is pressed downward, the plunger can make contact with an electrical contact **1823** disposed on the inner housing, as shown in at least FIG. 20F. The plunger is aligned with the electrical contact **1823** so that an electrical pathway or circuit can be completed between the plunger **1837** and the electrical contact **1823** when the button **1808** is pressed down during operation. Accordingly, the plunger can include or be formed from electrically conductive material.

(170) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIGS. 20A-20F can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts shown in the other figures. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown in the other figures can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIGS. 20A-20F.

(171) FIG. 20G illustrates a side, cross-sectional view of a portion of the device **1800** showing a viewing plane orthogonal to the cross-sectional viewing plane of FIG. 20F and extending through the plunger **1837**. FIG. 20G shows the button **1808** and the plunger **1837** extending through the hole **1835** defined by the speaker frame **1859** and the electrical contact **1823** against which a lower surface of the plunger **1837** presses or contacts when the button **1808** is depressed, as shown, to

complete an electrical circuit between the plunger **1837** and the electrical contact **1823**. When the button **1808** is not depressed, the plunger **1837** and the electrical contact **1823** are separated so that no electrical connection is made therebetween. The electrical contact **1823** can also be referred to herein as a “tactile switch” or a “tac switch.”

(172) The tac switch **1823** can electrically couple and/or physically contact an electrical flex **1804** partially disposed on a top surface of the inner housing **1851** and at least partially extending under the tac switch **1823** between the tac switch **1823** and the inner housing **1851**. The flex **1804** can extend around an edge of the inner housing **1851** and continue underneath or on a lower surface, opposite the top surface of the inner housing **1851**, as shown. In one example, the bend formed in the flex **1804** as the flex rounds the edge of the inner housing **1851** from one surface to the other can, on its own, bias the portion of the flex **1804** disposed between the tac switch **1823** and the inner housing **1851** away from the inner housing **1851**.

(173) In order to counteract this biasing force away from the inner housing **1851**, the device **1800** can include a foot **1806** pressing downward onto the flex **1804** to keep the flex **1804** in position between the tac switch **1823** and the inner housing **1851**, as shown in FIG. 20G. The foot **1806** can be a molded plastic piece or other non-conductive material anchored to the speaker frame **1859**, the inner housing **1851**, or other component to produce the force of the foot **1806** pressing the flex **1804** against the inner housing as shown. In at least one example, the foot **1806** can also engage the tac switch **1823** such that the foot **1806** presses the tac switch against or toward the flex **1804** and/or the inner housing **1851**. Additionally, or alternatively, one or more adhesives or adhesive layers can be disposed between the flex **1804** and the inner housing **1851**, between the tac switch **1823** and the flex **1804**, and/or between the tac switch **1823** and the inner housing **1851**, to maintain the flex **1804** and tac switch **1823** in position as shown in FIG. 20G.

(174) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIG. 20G can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts shown in the other figures. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown in the other figures can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIG. 20G.

(175) FIG. 20H shows another example of a portion of a device **1800**, including a button **1808** and a button spring **1810**. In at least one example, the button spring **1810** can include upwardly extending spring arms **1812** fixed to the button **1808**. The button spring **1810**, and specifically the spring arms **1812**, can be formed of conductive material, including metal, and shaped so as to provide an upward biasing force against the button **1808**. The button spring **1810** can include a lower portion **1814** anchored to the speaker housing **1859** or other component of the device **1800** relative to which the button **1808** travels when depressed. In at least one example, the button spring **1810** provides a constant force to maintain an upper/outer surface of the button **1808** flush with an outer surface of the housing **1802** of the device **1800** (not shown in FIG. 20H but shown in at least FIGS. 20A and 20B). The materials, shapes, lengths of the spring arms **1814**, and other factors of the button spring **1810** can be tuned to alter the tactile response of the button **1808** when depressed by the user.

(176) Referring briefly to FIG. 20A, when the button **1808** is not depressed, an electrical grounding path can be formed through one or more screws **1816** contacting a portion of the housing **1802**. Accordingly, the screws **1816** and the housing **1802** can be formed of electrically conductive materials. The screws **1816** can act as a stop feature or datum contacting an inner surface of the housing **1802** to prevent the button **1808** from extending beyond the housing **1802** and maintaining a flush external surface with the housing **1802**. Referring again to FIG. 20H, when the button **1808** is partially depressed, the screws **1816** separate from the housing **1802** but the plunger **1837**, which is also in electrical communication with the button **1808**, is not yet in electrical contact with the tac switch **1823**.

(177) As shown in FIG. 20I, in this partially depressed position of the button **1808**, the button spring **1810** can form an electrical grounding pathway between a grounding component or plane of the device **1800** and the button. The button spring **1810** can form such a grounding pathway with the button **1808** whether the button **1808** is fully depressed to contact the plunger against the tac switch **1823**, partially depressed as discussed above, or when not depressed. The lower portion **1814** of the button spring **1810** can electrically contact or couple to a collar **1818**, which can be coupled to ground, or one or more other components forming the grounding pathway. The spring arms **1812** can contact the button **1808** as shown in FIG. 20H to complete the pathway to the button **1808**.

(178) In at least one example, the lower portion **1814** of the button spring **1810** defines an aperture **1820** through which the plunger **1837** extends. In at least one example, the lower portion **1814** of the button spring **1810** forms a bend **1822** that biases portions of the button spring **1810** on either side of the bend **1822** away from each other, contributing to the upward force from the button spring **1810**. For example, the bend **1822** can bias a first portion **1824** on one side of the bend **1822** away from a second portion **1826** on the other side of the bend **1822**.

(179) In at least one example, the first portion **1824** contacts or extends into the housing **1802** at **1828** to complete an electrical pathway from the button **1808**, through the button spring **1810**, to the housing **1802**. In addition, in at least one example, a collar **1818** defines an aperture **1830** and an anti-rotation feature or extension **1832** of the second portion **1826** can extend through the aperture **1830** or at least partially into the aperture **1830** to prevent the button spring **1810** from rotating out of position as the button **1808** is depressed and travels up and down during use. In at least one example, the anti-rotation feature **1832** engages the collar **1818** without adhesives. In general, the button spring can be disposed and fixed in position as shown without adhesives. The area or volume in which the button spring **1810** is disposed can include an area between the inner housing **1851** and the outer housing **1802** such that any adhesives present could be exposed to chemical aggressors from the external environment, for example through the various vents defined by the housing, including first and second vents **1849** and **1847**, respectively. Thus, the button spring **1810** can be fixed in position via the anti-rotation feature **1832**, an interface with the housing **1802** at **1828**, and/or with the button **1808**.

(180) In at least one example, the device **1800** can include a shim **1834** disposed between the button **1808** or the button cap and the plunger **1837**. In at least one example, the shim **1834** can include a material more elastic or compressible than the button **1808** and/or the plunger **1837**. In one example, the button **1808** and the plunger **1837** include conductive metals and the shim **1834** includes a plastic or rubber material. The shim **1834** can be disposed between and in contact with the button **1808** and the plunger **1837** as shown such that the shim **1834** absorbs forces and movements from the plunger **1837** and the button **1808** as the components of the speakers **1863**, **1861** vibrate and pressure sound waves impinge on the plunger **1837** and button **1808**, the shim **1834** reduces chattering or buzzing caused by the plunger **1837** and button **1808** vibrating against one another. In at least one example, the shim **1834** can include an elastic material. In at least one example, the shim **1834** can include a compressible material. In at least one example, the compressible material can include foam.

(181) Referring back to FIG. 20H, the device **1800** can include speaker meshes **1836a**, **1836b** disposed over speakers **1863**, **1861**, respectively. Each screw **1816** of the button **1808** can include a lower surface **1838** of the screw head facing the mesh **1836a-b**. The lower surface **1838** can be chamfered. The meshes **1836a-b** can be recessed to match or accommodate the curvature of the lower surfaces **1838** of the screws **1816**. The recessed geometry of the meshes **1836a-b** can provide extra space or volume into which the screws **1816** can extend toward the meshes **1836** without the screws **1816** and meshes **1836a-b** contacting or colliding when the button **1808** is depressed. Additionally, the speaker meshes **1836a**, **1836b** can include any number of stacked meshes of varying pore size and material. Pore size can be identified and selected to balance the resistance to

ingress of foreign materials, cosmetic benefits, water ejection, and acoustic performance. In some examples, the speaker meshes can both be metal and be welded to the device **1800**. In other examples, the meshes can be metal, fabric, polymer, or a combination thereof, and can be attached to the device **1800** by adhesives, fasteners, welding or other joining methods, and the like.

(182) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIGS. **20H-20I** can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts shown in the other figures. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown in the other figures can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIGS. **20H-20I**.

(183) FIG. **20J** shows a cross-sectional view of a portion of a device **1800**, including a button **1808** disposed in an aperture **1833** defined by a housing **1802** and a speaker diaphragm **1836** disposed in an internal volume of the device **1800**. The speaker diaphragm **1836**, the button **1808**, and the housing **1802** can define the front volume **1855**, which is also shown and labeled in FIG. **20A**. In at least one example, the device **1800** can include an acoustic gasket **1840** extending between the button **1808** and the housing **1802**. In at least one example, the gasket **1840** is greater than or equal to about 100 microns thick where the gasket **1840** contacts the housing **1802**. In at least one example, an upper surface of the gasket **1840** interfaces at an angle with the vertical surface of the housing **1802** defining the aperture **1833** at greater than 0-degrees, for example at least about 20-degrees or more relative to the horizontal plane orthogonal to the surface of the housing **1802** defining the aperture **1833**. In at least one example, the gasket includes an elastic material. In at least one example, the gasket **1840** includes a material with a Shore-A hardness of between about 30 A and 90 A, or between about 40 A and 80 A, or between about 50 A and 70 A, for example about 60 A.

(184) Accordingly, with a gasket **1840** having the above-noted dimensions and material properties, the gasket **1840** can maintain and rebound to its resting shape after the button **1808** is depressed by the user. In addition, according to the above-noted dimensions and material properties, the gasket **1840** can seal the front volume **1855** such that pressure can build up greater than an atmospheric pressure external to the device **1800**. In this way, the volume of the first speaker **1863** can be increased. In at least one example, the material properties, shape, and dimensions of the gasket **1840** can be tuned to maximize at least one of the resonant frequencies of the first speaker **1863**. In at least one example, the gasket **1840** can be permeable to water but impermeable to dust and debris from the external environment.

(185) The first speaker **1863** can include two peak resonance frequencies, a mechanical resonant frequency generated by shape of the first speaker **1863** itself operating in open air and front port resonance leveraging the length of the first vent **1849** as a tube that creates a higher pitch frequency and lets sound out from the first speaker **1863** through the housing **1802**. The pressure built up in the front volume **1855**, in part due to the seal formed by the gasket **1840**, affects the pressure waves of sound from the first speaker **1863** exiting the first vent **1849**. In this way, the gasket **1840** can tune the sound from the first speaker **1863** and increase the resonant tube frequency. In this way, multiple resonant frequencies (mechanical and tube) can be utilized and a broader range of sound frequencies can be increased.

(186) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIG. **20J** can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts shown in the other figures. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown in the other figures can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIG. **20J**.

(187) FIG. **20K** illustrates a cross-sectional view of a portion of a device **1800** including a button **1808**, a housing **1802**, and a gasket **1840** extending between the housing **1802** and the button **1808**.

The button **1808** can include an exterior color layer **1842** that can be formed by physical vapor deposition. The color layer **1842** can also be referred to as a PVD layer **1842**. The PVD layer can extend over a first surface **1844** angled or curved at a first angle or curvature and a second surface **1848** angled at a second angle different than the angle of the first surface **1844**. During the PVD process of forming the PVD layer **1842**, the PVD layer **1842** can be deposited onto the button **1808** in a constant direction regardless of the curvature, angles, or portion of the surface being deposited, in order to simplify the PVD process. In one example, the direction of deposition is indicated by the deposition direction **1850**.

(188) Because the first angle of the first surface **1844** is different than the second angle of the second surface **1848**, relative to the deposition direction **1850**, the PVD layer **1842** deposited on the first surface **1844** is formed thicker than the PVD layer **1842** of the second surface **1848**. This can be due to the steeper angle of the second surface **1848** relative to the horizontal plane of FIG. 20K orthogonal to the deposition direction **1850**. As shown, the PVD layer **1842** of the second surface **1848** is thinner than the PVD layer **1842** of the first surface **1844** due to this difference in angle relative to the deposition direction **1850**. The thickness of the PVD layer **1842** affects the color of the PVD layer **1842**. In one example, the thicker PVD layer **1842** at the first surface **1844** can appear red while the color of the PVD layer **1842** at a transition or corner surface **1846** between the first and second surfaces **1844**, **1848** can appear blue and the color of the thinner PVD layer **1842** of the second surface **1848** can shift back toward red, for example appearing orange or red-orange. The thickness of the PVD layer **1842** at the corner **1846** can be thicker than the PVD layer **1842** at the second surface **1848** but thinner than the PVD layer **1842** at the first surface **1844**.

(189) In the example noted above, the blue color of the PVD layer **1842** at the corner **1846** stands out more visually compared to the red color of the PVD layer **1842** at the first surface **1844** than the orange color of the PVD layer **1842** at the second surface **1848**. In order to minimize the contrast of the blue and red between the corner **1846** and the first surface **1844**, the corner **1846** can include a small radius of curvature to minimize the area of the surface of the button **1808** defined by the corner **1846**. While the PVD layer **1842** at the second surface **1848** is thinner than the PVD layer **1842** at the corner **1846**, the orange color of the PVD layer **1842** at the second surface **1848** is closer to red and visually less contrasting or noticeable. Thus, the angle of the second surface **1848** can be chosen to tune the thickness of the PVD layer **1842** on the second surface **1848** relative to the thickness of the PVD layer **1842** of the first surface **1844** in order to minimize the color difference.

(190) In at least one example, the second surface **1848** is angled between about 1-degree and 10-degrees relative to the deposition direction **1850**, or between about 3-degrees and about 7-degrees relative to the deposition direction **1850**, for example at about 5-degrees relative to the deposition angle **1850**. In this way, the thickness of the PVD layer **1842** at the second surface **1848** can be less than about 50% of the thickness or less than the thickness of the PVD layer **1842** of the first surface **1844**. In examples where the PVD layer **1842** at the second surface **1848** is less than about 50% of the thickness of the PVD layer **1842** at the first surface, the color difference between the PVD layer **1842** of the first and second surfaces **1844**, **1848** can be visually minimized.

(191) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIG. 20K can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts shown in the other figures. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown in the other figures can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIG. 20K.

(192) FIG. 21 illustrates a cross-sectional view of the assembly shown in FIGS. 20A-20F, with **1852** showing an internal volume of the device and **1802** being the outer housing. During manufacturing, in order to simplify machining of the housing **1802**, an angled receiving cavity for the speaker assembly can be machined into an inner surface of the housing **1802** so that machining

tools can reach needed points in the housing to machine the cavity. Thus, in at least one example, the speaker assembly, including the speaker **1863** shown in FIG. **21**, can be disposed at an angle relative to the horizontal plane **1831** of the device **1800**. In one example, the speaker angle θ can be between about 5-degrees and 10-degrees from the horizontal plane **1831** of the device **1800**, for example about 7.5-degrees, and the cavity angle β can be between about 7-degrees and 13-degrees beyond the speaker angle θ , for example about 10-degrees.

(193) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIG. **21** can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts shown in the other figures. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown in the other figures can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIG. **21**.

(194) As noted above, the wearable electronic devices described herein can be configured to be used during any daily activity of the user. Often, the wearable device will rub against other objects, including clothing, or be subjected to wind if outside during use. Typically, these types of interactions, including rubbing, scratching, and wind blowing can cause negatively affect the performance of one or more microphones of the device. For example, some wearable devices can include a microphone to receive the user's voice during a cellular call using the device. However, often when speaking in an outside environment where wind is present, the wind can cause unwanted noise as it passed over the device and specifically as it passed over one or more microphone apertures in the housing of the device, which can create unwanted background noise and unclear voice transmission from the device.

(195) For example, as shown in FIG. **22**, a user is wearing a wearable electronic watch **1900** on his/her wrist while riding a bicycle. Such an activity causes wind to pass over and contact the device **1900**. The same may be true while walking, jogging, hiking, or any other active and/or outdoor activity. FIG. **23** shows the device **1900** subject to wind flowing toward and around the device **1900**. Flow lines **1919** illustrate one possible flow path of wind crossing over the device **1900**. In some examples, turbulent currents **1921** can be created at one or more sides of the device **1900**. Such wind and turbulent flow can travel over certain components or opening to microphones and speakers of the device **1900** and cause unwanted noise when transmitting the user's voice during a cellular call or while recording his or her voice with the device **1900**.

(196) The extent of such noise interference from wind can vary depending on the location of the microphone and the direction of the wind. As noted above, the principles discussed with respect to wind interference can also be true for other types of interference such as water and moisture interference and rubbing or scratching the device **1900** against other objects such as clothes. FIG. **24** shows wind **1919** coming from various different directions all around the device **1900**. The locations **1917a**, **1917b**, **1917c**, and **1917d** on the device **1900** illustrate potential locations of a microphone of the device **1900**. Again, the extent of noise interference from wind can vary depending on the location of the microphone and the direction of the wind and those directions and locations can vary from one moment to another during use.

(197) In order to reduce the interference from wind and other objects, wearable electronic devices of the present systems and methods can include three microphones disposed in the internal volume of the device and configured to receive sound through three respective apertures. The location and orientation of the apertures and microphones can be such that while one or two of the microphones may pick up wind interference during use, at least one of the microphones and apertures will be positioned and oriented to pick up less interference noise. In such a configuration, the device can be configured to process the combined noise detected by all three microphones to reduce the noise. In one example, the device can be configured to rely more heavily on microphones picking up less interference noise such that the detected noise is clear and un-affected by the interference noise caused by the wind.

(198) In at least one example, as shown in FIG. 25, a wearable electronic watch **2000** can include a housing sidewall **2028** defining an internal volume **2052** with the sidewall **2028** extending 360-degrees circumferentially around the internal volume **2052**. The sidewall **2028** can also define a first aperture **2015**, a second aperture **2013** between about 155-degrees and 205-degrees relative to the first aperture **2015**, and a third aperture **2011** closer to the second aperture **2013** than the first aperture **2015**.

(199) In addition, the device **2000** can include a first microphone **2009** disposed in the internal volume **2052** and configured to receive sound through the first aperture **2015**, a second microphone **2007** disposed in the internal volume **2052** and configured to receive sound through the second aperture **2013**, and a third microphone **2005** disposed in the internal volume **2052** and configured to receive sound through the third aperture **2011**.

(200) In one example, the device **2000** can include a first strap receiving feature **2001** and a second strap receiving feature **2003** opposite the first strap receiving feature **2001**. A first sidewall portion **2004** can extend between the first strap receiving feature **2001** and the second strap receiving feature **2003** with the first sidewall portion **2004** defining the first aperture **2015** closer to the first strap receiving feature **2001** than the second strap receiving feature **2003**. Further, one example can include a second sidewall portion **2006** disposed opposite the first sidewall portion **2004** and extending between the first strap receiving feature **2001** and the second strap receiving feature **2003**, the second sidewall portion **2006** defining a second aperture **2013** and a third aperture **2011**, the second aperture **2013** defined closer to the second strap receiving feature **2003** than the first strap receiving feature **2001**. In such an example, as shown in FIG. 25, the device **2000** can include a first microphone **2009** disposed in the internal volume **2052** adjacent the first aperture **2015**, a second microphone **2007** disposed in the internal volume **2052** adjacent the second aperture **2013**, and a third microphone **2005** disposed in the internal volume **2052** adjacent the third aperture **2011**. While the present system is described as detecting noises and wind from various side directions, the present system can also include microphones oriented to detect sounds and wind from various orientations including into and out of the page illustrated in FIG. 24.

(201) In one example, as shown in FIG. 25, the electronic device **2000** can include a fourth aperture **2008**. The first microphone **2009** can be disposed in the internal volume **2052** adjacent the first aperture **2015**, the second microphone **2007** can be disposed in the internal volume **2052** adjacent the second aperture **2013**, and the third microphone **2005** can be disposed in the internal volume **2052** adjacent the third aperture **2011**. In addition, a speaker **2010** can be disposed in the internal volume **2052** adjacent the fourth aperture **2008** such that a distance along the sidewall **2028** between the first and second apertures **2015**, **2013** is larger than a distance along the sidewall **2028** between the second and third apertures **2013**, **2011** and the fourth aperture **2008** is adjacent the first aperture **2015**.

(202) In at least one example, the second aperture **2013** and the third aperture **2011** can be defined on a distal side of the wearable electronic watch. The distal side of the wearable electronic watch **2000** can include or be defined by the second sidewall portion **2006** where the term “distal” refers to anatomically distal when worn on the wrist of the user. In other words, the distal side of the wearable electronic watch **2000** includes the side facing the hand of the user when worn.

Conversely, the proximal side of the wearable electronic watch **2000** can include or be defined by the first sidewall portion **2004** where the term “proximal” refers to anatomically proximal when worn on the wrist of the user. In other words, the proximal side of the wearable electronic watch **200** includes the side facing the forearm of the user when worn. In at least one example, the first aperture **2015** can be defined on the proximal side of the wearable electronic watch **2000**.

(203) In at least one example, the second aperture **2013** can be defined between about 170 and 190 degrees relative to the first aperture **2015**. In such an example, the third aperture **2011** can be defined between about 30 and 60 degrees counterclockwise along the sidewall **2028** relative to the second aperture **2013**. In one example, the third aperture **2011** can be defined between about 40 and

50 degrees counterclockwise along the sidewall **2028** relative to the second aperture **2013**.

(204) In at least one example of the wearable electronic watch **2000**, the sidewall **2028** defines the strap receiving feature **2001** between the first aperture **2015** and the second aperture **2013**. The sidewall **2028** can further define the second strap receiving feature **2003** opposite the first strap receiving feature **2001** and between the third aperture **2011** and the first aperture **2015**. In at least one example, the first aperture **2015** can be defined closer to the first strap receiving feature **2001** than the second strap receiving feature **2003** and the second aperture **2013** can be defined closer to the second strap receiving feature **2003** than the first strap receiving feature **2001**. In one example, the third aperture **2011** can be defined between the second aperture **2013** and the first strap receiving feature **2001**.

(205) In at least one example, the third aperture **2011** is defined between about 30 and 60 degrees counterclockwise from the second aperture **2013** along the housing sidewall **2028**. The first aperture **2015** can be defined between about 170 and 190 degrees from the second aperture **2013** along the housing sidewall **2028**. In at least one example, the first aperture **2015** can be defined proximally relative to the first strap receiving feature **2001** and the second strap receiving feature **2003** and the second aperture **2013** and the third aperture **2011** can be defined distally relative to the first strap receiving feature **2001** and the second strap receiving feature **2003**.

(206) In at least one example, the first microphone **2009** can be oriented to receive sound from a first direction and the second microphone **2007** can be oriented to receive sound from a second direction different than the first direction. In one example, the second direction is opposite the first direction. In such an example, the first aperture **2015** and the fourth aperture **2008** can be defined on a proximal side of the electronic device **2000**. In such an example, the second and third apertures **2013**, **2011** can be defined on a distal side of the electronic device **2000**.

(207) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIGS. **22-25** can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts shown in the other figures. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown in the other figures can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIGS. **22-25**.

(208) FIG. **26** illustrates another example of a wearable electronic device **2100** including a sidewall **2128** defining an internal volume **2152** and first, second, and third apertures **2115**, **2113**, and **2111**, respectively. A first microphone **2109** is disposed in the internal volume **2152** adjacent the first aperture **2115** and configured to receive sound through the first aperture **2115**. A second microphone **2107** is disposed in the internal volume **2152** adjacent the second aperture **2113** and configured to receive sound through the second aperture **2113**. A third microphone **2105** is disposed in the internal volume **2152** adjacent the third aperture **2111** and configured to receive sound through the third aperture **2111**. In the illustrated example of FIG. **26**, the apertures **2115**, **2113**, and **2111** are defined by a distal sidewall portion **2106** between the first and second strap receiving features **2101** and **2103**, respectively.

(209) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIG. **26** can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts shown in the other figures. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown in the other figures can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIG. **26**.

(210) FIG. **27** shows another example of a wearable electronic device **2200** including a sidewall **2228** defining an internal volume **2252** and first and second apertures **2215** and **2213**, respectively. A first microphone **2209** is disposed in the internal volume **2252** adjacent the first aperture **2215** and configured to receive sound through the first aperture **2215**. A second microphone **2207** is disposed in the internal volume **2252** adjacent the second aperture **2213** and configured to receive

sound through the second aperture **2213**. In the illustrated example of FIG. **27**, the aperture **2215** is defined by a proximal sidewall portion **2204** between the first and second strap receiving features **2201** and **2203**, respectively. The second aperture **2213** is defined by a distal sidewall portion **2206** between the first and second strap receiving features **2201** and **2203**, respectively.

(211) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIG. **27** can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts shown in the other figures. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown in the other figures can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIG. **27**.

(212) FIG. **28** illustrates another example of a wearable electronic device **2300** including a sidewall **2328** defining an internal volume **2352** and first and second apertures **2313** and **2311**, respectively. A first microphone **2307** is disposed in the internal volume **2352** adjacent the first aperture **2313** and configured to receive sound through the first aperture **2313**. A second microphone **2305** is disposed in the internal volume **2352** adjacent the second aperture **2311** and configured to receive sound through the second aperture **2311**. In the illustrated example of FIG. **28**, the apertures **2312** and **2111** are defined by a distal sidewall portion **2306** between the first and second strap receiving features **2301** and **2303**, respectively.

(213) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIG. **28** can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts shown in the other figures. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown in the other figures can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIG. **28**.

(214) In each example shown in FIGS. **25-28**, the device can be configured to receive and process multiple audio signals from the multiple microphones through the multiple apertures and identify the microphone with the lowest perceived wind noise. This microphone can be used as the baseline and data can be extracted from the other locations to process a clear audio signal. This can improve audio transmission and detection performance in windy conditions, when the device is rubbed against another object, or when one or more microphone apertures gets clogged with debris and/or liquid.

(215) FIG. **29A** shows a bottom elevation view of an example of a back cover **1114** and an electromagnetically transparent component **1116** assembled together to form the back side or back surface of a device **1100**. In at least one example, the back cover **1114** can be secured to the sidewalls **1128** of the device **1100**.

(216) In at least one example, the back cover **1114** can be secured to the sidewalls **1128** using one or more fasteners **1192**. In the illustrated example of FIG. **29A**, four fasteners **1192** are used to secure the back cover **1114** to the sidewalls **1128**, with one fastener **1192** disposed at each corner of the device **1100**. Using the fasteners shown, the back cover **1114**, which in some examples can be made of ceramic, glass, or other brittle material, the back cover **1114** can be secured to the sidewalls **1128** without cracking, separating from the sidewalls **1128**, or otherwise being damaged during assembly.

(217) In at least one example, the back cover **1114** can include zirconia, or other brittle material, which is hard to CNC and machine to form intricate connection features. Using the fasteners shown in the figures to secure the back cover **1114** to the sidewalls **1128** of the device **1100** can simplify the geometry of the back cover **1114** in order to simplify the manufacturing process thereof. For example, as shown in the cross-sectional view of FIG. **15B**, the back cover **1114** can be formed of a simple geometry extending around the electromagnetically transparent component **1116** and defining a through hole **1194** for each fastener **1192** to pass through.

(218) In at least one example, each fastener **1192** can be disposed through the back cover **1114** a

certain distance away from an outer peripheral edge of the back cover **1114** such that enough material is present between the fastener **1192** and the outer peripheral edge of the back cover **1114** to prevent cracking of the back cover between the fastener and the outer edge. This distance is also designed to reduce any stress concentrations in the back cover **1114** during and after assembly as the fastener **1192** presses the material of the back cover **1114** against the sidewalls **1128**.

(219) As shown in FIGS. **30** and **31**, in at least one example, the through hole **1194** defined by the back cover **1114** can include a counter bore in which the head **1196** of the fastener **1192** is disposed when assembled. In addition, in at least one example, the head **1196** of the fastener **1192** can include an outwardly extend flange **1198** with a gasket **1199** pressed between the flange **1198** and the back cover **1114**. In one example, the fastener **1192** can include a threaded screw. When assembled, the threaded screw can be threaded into a threaded receiving hole defined by the sidewalls **1128** such that the head **1196** of the fastener **1192** presses the back cover **1114** against the sidewalls **1128**.

(220) The flange **1198** thus presses against the gasket **1199** forming an environmental seal against external moisture and other debris from entering the through hole **1194**. This environmental seal can also reduce corrosion of the fastener itself as it prevent water or other moisture/fluid from entering the through hole **1194** and coming into contact with the fastener **1192** disposed inside the through hole **1194**. FIG. **31** shows an O-ring seal **1197** instead of the gasket shown in the example of FIG. **30**, and FIG. **32** shows a side view of the fastener **1192** with the gasket **1199** disposed underneath the flange **1198**.

(221) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIGS. **29A-32** can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts shown in the other figures. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown in the other figures can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIGS. **29A-32**.

(222) In at least one example, as shown in FIG. **33A**, the fastener **1292** can include an eave feature **1295** defined by the flange **1298** on a lower side of the head **1296** configured to constrain an O-ring or gasket laterally as the fastener **1292** pressed downward on the O-ring or gasket. FIG. **33B** shows an example of an O-ring **1297** disposed in the eave feature **1295**. Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIGS. **33A** and **33B** can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts shown in the other figures. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown in the other figures can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIGS. **33A** and **33B**.

(223) FIG. **34** illustrates a five-pointed punch **1393** indented into a top surface of the head **1396** of a fastener **1392** with convex transition edges between each of the five points of the punch shape. FIG. **35** illustrates a five-pointed punch **1493** indented into a top surface of the head **1496** of a fastener **1492** with five concave points to form a five-leaf clover shape of the punch **1493**. These punches **1393**, **1493** can provide aesthetically pleasing punch designs and tool-specific mating features for assembly and disassembly that increase surface area and engagement for secure fastening and removal thereof.

(224) Further, as shown in the top and side views of FIGS. **36A** and **36B**, respectively, the top surface of a fastener head **1596** can include patterns and lines **1591** to further improve the aesthetic appeal, while improving surface engagement and secure removal, of the fastener **1592** and other fasteners described herein and shown in other figures. In at least one example, the lines **1591** can be scored, machines, etches, or otherwise physically formed into the surface of the head **1596**. As shown from the side view of FIG. **36B**, the lines or scoring features **1591** can be formed to a certain depth into the head **1596** of the fastener **1592**.

(225) FIG. 37 illustrates a flow chart of a method **1600** of forming the score lines and/or machined features **1591** shown in FIGS. 36A and 36B. In a first step of the method **1600**, a 50-degree feature is machined or otherwise formed into the surface at a depth of approximately 0.01 mm. Next, in step **1687** of the method **1600**, the feature can be widened to approximately 130-degrees at the same depth. Next, at step **1685**, the feature can be increased to a depth of approximately 0.05 mm to form an approximately 45-degree feature. Then, at step **1683**, the feature can be widened to approximately 60-degrees at the same depth of approximately 0.05 mm. Next, the depth of the feature can be increased to approximately 0.10 mm to form an approximately 45-degree feature. The angles and depth dimensions shown in FIG. 37 and described herein are exemplary only and can vary to form features of different sizes, shapes, number, and depth. In general, the depth and angle of the features can be iteratively widened and deepened as described until the desired depth and angle of each feature is accomplished.

(226) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIGS. 33A-37 can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts shown in the other figures. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown in the other figures can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIGS. 33A-37.

(227) Wearable electronic devices currently on the market, including current wearable electronic watches, cannot accurately detect environmental pressures in both submerged environments and above water. Usually, this is because the scale of pressures is so different between air pressure above water and fluid pressure below water. It can be especially difficult to configure a single pressure sensor into such a device that is sensitive enough to detect changes in air pressure above water but robust enough to detect pressure changes under water, for example up to 10-bar under water.

(228) However, devices of the present disclosure, including the wearable electronic devices and watches described herein, can include a single pressure sensor to detect pressure above water and below water up to 10-bar. In at least one example, the pressure sensor can be electrically connected to an ASIC switch and associated circuitry and processors to switch pressure scales when high pressures are detected when the device is submerged under water.

(229) For example, such an ASIC circuitry connected to the sensor can include a low gain mode that measures depth and a high gain mode that measures depth and elevation. This change in gain can be switched with the ASIC to tune the sensor between water and air sensitivities. The processor of the device can also receive temperature measurement from a temperature sensor of the device to take into account the temperature of the external environment, which can affect the pressure sensor reading and sensitivity. Along these lines, at least one example of such a device can also include a heater to apply heat to the pressure sensor in order to perform a health check on the sensor to calibrate the sensor to its original calibration that was performed or set at the same temperature to which it is heated by the heater.

(230) To the extent applicable to the present technology, gathering and use of data available from various sources can be used to improve the delivery to users of invitational content or any other content that may be of interest to them. The present disclosure contemplates that in some instances, this gathered data may include personal information data that uniquely identifies or can be used to contact or locate a specific person. Such personal information data can include demographic data, location-based data, telephone numbers, email addresses, TWITTER® ID's, home addresses, data or records relating to a user's health or level of fitness (e.g., vital signs measurements, medication information, exercise information), date of birth, or any other identifying or personal information.

(231) The present disclosure recognizes that the use of such personal information data, in the present technology, can be used to the benefit of users. For example, the personal information data can be used to deliver targeted content that is of greater interest to the user. Accordingly, use of

such personal information data enables users to calculated control of the delivered content. Further, other uses for personal information data that benefit the user are also contemplated by the present disclosure. For instance, health and fitness data may be used to provide insights into a user's general wellness, or may be used as positive feedback to individuals using technology to pursue wellness goals.

(232) The present disclosure contemplates that the entities responsible for the collection, analysis, disclosure, transfer, storage, or other use of such personal information data will comply with well-established privacy policies and/or privacy practices. In particular, such entities should implement and consistently use privacy policies and practices that are generally recognized as meeting or exceeding industry or governmental requirements for maintaining personal information data private and secure. Such policies should be easily accessible by users, and should be updated as the collection and/or use of data changes. Personal information from users should be collected for legitimate and reasonable uses of the entity and not shared or sold outside of those legitimate uses. Further, such collection/sharing should occur after receiving the informed consent of the users. Additionally, such entities should consider taking any needed steps for safeguarding and securing access to such personal information data and ensuring that others with access to the personal information data adhere to their privacy policies and procedures. Further, such entities can subject themselves to evaluation by third parties to certify their adherence to widely accepted privacy policies and practices. In addition, policies and practices should be adapted for the particular types of personal information data being collected and/or accessed and adapted to applicable laws and standards, including jurisdiction-specific considerations. For instance, in the US, collection of or access to certain health data may be governed by federal and/or state laws, such as the Health Insurance Portability and Accountability Act (HIPAA); whereas health data in other countries may be subject to other regulations and policies and should be handled accordingly. Hence different privacy practices should be maintained for different personal data types in each country.

(233) Despite the foregoing, the present disclosure also contemplates embodiments in which users selectively block the use of, or access to, personal information data. That is, the present disclosure contemplates that hardware and/or software elements can be provided to prevent or block access to such personal information data. For example, in the case of advertisement delivery services, the present technology can be configured to allow users to select to “opt in” or “opt out” of participation in the collection of personal information data during registration for services or anytime thereafter. In another example, users can select not to provide mood-associated data for targeted content delivery services. In yet another example, users can select to limit the length of time mood-associated data is maintained or entirely prohibit the development of a baseline mood profile. In addition to providing “opt in” and “opt out” options, the present disclosure contemplates providing notifications relating to the access or use of personal information. For instance, a user may be notified upon downloading an app that their personal information data will be accessed and then reminded again just before personal information data is accessed by the app.

(234) Moreover, it is the intent of the present disclosure that personal information data should be managed and handled in a way to minimize risks of unintentional or unauthorized access or use. Risk can be minimized by limiting the collection of data and deleting data once it is no longer needed. In addition, and when applicable, including in certain health related applications, data de-identification can be used to protect a user's privacy. De-identification may be facilitated, when appropriate, by removing specific identifiers (e.g., date of birth, etc.), controlling the amount or specificity of data stored (e.g., collecting location data a city level rather than at an address level), controlling how data is stored (e.g., aggregating data across users), and/or other methods.

(235) Therefore, although the present disclosure broadly covers use of personal information data to implement one or more various disclosed embodiments, the present disclosure also contemplates that the various embodiments can also be implemented without the need for accessing such personal information data. That is, the various embodiments of the present technology are not

rendered inoperable due to the lack of all or a portion of such personal information data. For example, content can be selected and delivered to users by inferring preferences based on non-personal information data or a bare minimum amount of personal information, such as the content being requested by the device associated with a user, other non-personal information available to the content delivery services, or publicly available information.

(236) The foregoing description, for purposes of explanation, used specific nomenclature to provide a thorough understanding of the described embodiments. However, it will be apparent to one skilled in the art that the specific details are not required in order to practice the described embodiments. Thus, the foregoing descriptions of the specific embodiments described herein are presented for purposes of illustration and description. They are not intended to be exhaustive or to limit the embodiments to the precise forms disclosed. It will be apparent to one of ordinary skill in the art that many modifications and variations are possible in view of the above teachings.

Claims

1. An electronic device, comprising: a housing including a sidewall defining an upper peripheral edge surrounding an opening; and a transparent display cover disposed in the opening, the transparent display cover including an outward facing surface; wherein; the transparent display cover is positioned such that the upper peripheral edge is level with the outward facing surface; and the transparent display cover is spaced apart from the sidewall to define a gap forming a cavity extending below the transparent display cover.
2. The electronic device of claim 1, wherein the electronic device includes a display assembly comprising the transparent display cover.
3. The electronic device of claim 2, wherein the outward facing surface is planar.
4. The electronic device of claim 1, wherein the display assembly further comprises a touch interface.
5. The electronic device of claim 1, further comprising a protrusion extending from the sidewall, the protrusion defining a recess.
6. The electronic device of claim 5, further comprising a crown disposed in the recess.
7. The electronic device of claim 6, wherein the protrusion surrounds a portion of the crown.
8. The electronic device of claim 5, wherein: the recess is a first recess; the protrusion further defines a second recess; and the electronic device further comprises a button disposed in the second recess.
9. An electronic device, comprising: a housing sidewall defining: a first speaker vent; a second speaker vent; and an aperture between the first speaker vent and the second speaker vent; and a button disposed between the first speaker vent and the second speaker vent in the aperture.
10. The electronic device of claim 9, wherein: the housing sidewall defines an internal volume; the electronic device further comprises a first speaker disposed within the internal volume, the first speaker positioned to direct sound through the first speaker vent; and the electronic device further comprises a second speaker disposed within the internal volume, the second speaker positioned to direct sound through the second speaker vent.
11. The electronic device of claim 10, wherein the housing sidewall further defines a front speaker volume disposed between the housing sidewall and the first and second speakers.
12. The electronic device of claim 9, wherein: the first speaker vent comprises at least two openings defined by the housing sidewall; and the second speaker vent consists of a single opening defined by the housing sidewall.
13. The electronic device of claim 9, wherein the housing sidewall defines: a first side of the electronic device; and a second side of the electronic device opposite the first side; wherein the first side defines the first and second speaker vents and the aperture.
14. The electronic device of claim 13, wherein the second side defines a protrusion defining a

recessed feature.

15. The electronic device of claim 14, further comprising a crown disposed in the recessed feature.
 16. An electronic device, comprising: a housing defining an internal volume and an upper peripheral edge, the housing including: a first sidewall defining a first speaker vent and a second speaker vent; and a second sidewall opposite the first sidewall, the second sidewall including a protrusion defining a recessed feature; a transparent display cover flush with the upper peripheral edge; a button disposed between the first speaker vent and the second speaker vent; and a dial disposed in the recessed feature.
 17. The electronic device of claim 16, wherein the upper peripheral edge of the housing is configured to protect the transparent display cover from inadvertent contact during use.
 18. The electronic device of claim 16, wherein the protrusion is configured to protect the dial from inadvertent contact during use.
 19. The electronic device of claim 16, wherein: the first sidewall defines an aperture between the first speaker vent and the second speaker vent; and the button is disposed in the aperture.
 20. The electronic device of claim 16, wherein: the protrusion is a first protrusion; the housing includes a second protrusion extending upward toward the upper peripheral edge, the second protrusion including an upper portion separated from a lower portion by a non-metallic material portion, the upper portion defining the upper peripheral edge; and the upper peripheral edge surrounds the display cover.
-