

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12413506
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Wouhaybi; Rita et al.

Systems, apparatus, articles of manufacture, and methods for proactive data routing

Abstract

Methods, apparatus, systems, and articles of manufacture are disclosed for proactive data routing. An example apparatus includes at least one memory, machine-readable instructions, and processor circuitry to execute the machine-readable instructions to at least execute a machine-learning model to output a first data routing path in a network environment based on metadata associated with an event in the network environment. The processor circuitry is further to, after a detection of a change of the first data routing path to a second data routing path, retrain the machine-learning model to output a third data routing path based on the second data routing path. The processor circuitry is additionally to cause transmission of a second message to a first node based on the third data routing path after an identification of the event.

Inventors: Wouhaybi; Rita (Portland, OR), Mo; Stanley (Portland, OR), Moustafa; Hassnaa (San Jose, CA), Pisharody; Greeshma (Portland, OR)

Applicant: Intel Corporation (Santa Clara, CA)

Family ID: 84891277

Assignee: Intel Corporation (Santa Clara, CA)

Appl. No.: 17/947009

Filed: September 16, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230016946 A1	Jan. 19, 2023

Related U.S. Application Data

Publication Classification

Int. Cl.: H04L45/00 (20220101); G06F16/901 (20190101); G06F16/908 (20190101); G06F21/62 (20130101); H04L45/16 (20220101)

U.S. Cl.:

CPC H04L45/22 (20130101); G06F16/9024 (20190101); G06F16/908 (20190101); G06F21/6209 (20130101); H04L45/16 (20130101);

Field of Classification Search

CPC: H04L (45/22); H04L (45/16); G06F (16/9024); G06F (16/908); G06F (21/6209); G06F (16/901); G06F (16/907)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2008/0226046	12/2007	Shaffer et al.	N/A	N/A
2015/0186635	12/2014	Nakhjiri et al.	N/A	N/A
2018/0300124	12/2017	Malladi et al.	N/A	N/A
2019/0364130	12/2018	Rogynskyy	N/A	N/A
2019/0370089	12/2018	Patton	N/A	G06F 9/542
2020/0134423	12/2019	Shinde et al.	N/A	N/A
2020/0167205	12/2019	Guim Bernat et al.	N/A	N/A
2020/0267110	12/2019	Nolan et al.	N/A	N/A
2020/0372016	12/2019	Rogynskyy	N/A	H04L 67/1095
2021/0004265	12/2020	Guim Bernat et al.	N/A	N/A
2021/0011765	12/2020	Doshi et al.	N/A	N/A
2021/0014113	12/2020	Guim Bernat et al.	N/A	N/A
2021/0125083	12/2020	Ogawa et al.	N/A	N/A
2021/0203739	12/2020	Calegari et al.	N/A	N/A
2022/0198562	12/2021	Cella	N/A	G06Q 40/04
2022/0303828	12/2021	Gamage et al.	N/A	N/A
2022/0335340	12/2021	Moustafa et al.	N/A	N/A
2024/0386054	12/2023	Wouhaybi et al.	N/A	N/A
2024/0386442	12/2023	Mo et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2017035536	12/2016	WO	N/A
2023048770	12/2022	WO	N/A

OTHER PUBLICATIONS

International Searching Authority, “International Search Report and Written Opinion,” issued in connection with International Application No. PCT/US2021/065156, Jul. 1, 2022, 16 pages. cited by applicant

Song et al., “Practical Techniques for Searches on Encrypted Data,” In the Proceedings of the IEEE Symposium on Security and Privacy, May 14-17, 2000, 12 pages. cited by applicant

Gentry, “Fully Homomorphic Encryption Using Ideal Lattices,” In Proceedings of the Annual ACM Symposium on Theory of Computing, May 31 through Jun. 2, 2009, 10 pages. cited by applicant

Kamara et al., “Dynamic Searchable Symmetric Encryption,” Proceedings of the 2012 ACM Conference on Computer and Communications Security, Oct. 2012, 24 pages. cited by applicant

Garg et al., “Candidate Indistinguishability Obfuscation and Functional Encryption for all circuits,” In the Proceedings of the IEEE Symposium on Theory of Computing Science, Oct. 2013, 46 pages. cited by applicant

International Searching Authority, “Written Opinion,” issued in connection with International Application No. PCT/US2022/023107, Jul. 1, 2022, 7 pages. cited by applicant

International Searching Authority, “International Search Report,” issued in connection with International Application No. PCT/US2022/023107, Jul. 1, 2022, 3 pages. cited by applicant

Netherlands Patent Office, “Search Report,” issued in connection with Netherlands Application No. NL2032844, Jun. 5, 2023, 28 pages, with machine English translation. cited by applicant

Netherlands Patent Office, “Notice of Grant,” issued in connection with Netherlands Application No. NL2032844, Aug. 11, 2023, 4 pages, with machine English translation. cited by applicant

International Searching Authority, “International Preliminary Report on Patentability,” issued in connection with International Application No. PCT/US2021/065156, Mar. 26, 2024, 11 pages. cited by applicant

International Searching Authority, “International Preliminary Report on Patentability,” issued in connection with International Application No. PCT/US2022/023107, Mar. 26, 2024, 8 pages. cited by applicant

United States Patent and Trademark Office, “Requirement for Restriction/Election,” issued in connection with U.S. Appl. No. 18/571,142, dated Sep. 29, 2024, 10 pages. cited by applicant

United States Patent and Trademark Office, “Non-Final Office Action,” issued in connection with U.S. Appl. No. 18/571,142, dated Mar. 21, 2025, 33 pages. cited by applicant

Ismail, “A Machine Learning Approach for Energy-Efficient IoT Systems,” Journal of Intelligent Systems and Internet of Things (JISIoT), vol. 01, No. 02, 2020, 10 pages. cited by applicant

United States Patent and Trademark Office, “Non-Final Office Action,” issued in connection with U.S. Appl. No. 18/571,149, dated Jun. 5, 2025, 18 pages. cited by applicant

Primary Examiner: Butt; Walli Z

Attorney, Agent or Firm: Hanley, Flight & Zimmerman, LLC

Background/Summary

RELATED APPLICATIONS (1) This patent arises from a continuation-in part of International Patent Application PCT/US21/65156, which was filed on Dec. 23, 2021, which claims the benefit of U.S. Provisional Patent Application No. 63/248,312, which was filed on Sep. 24, 2021. International Patent Application PCT/US21/65156 and U.S. Provisional Patent Application No. 63/248,312 are hereby incorporated herein by reference in their entireties. Priority to International Patent Application PCT/US21/65156 and U.S. Provisional Patent Application No. 63/248,312 is hereby claimed.

FIELD OF THE DISCLOSURE

(1) This disclosure relates generally to data management and, more particularly, to systems, apparatus, articles of manufacture, and methods for proactive data routing.

BACKGROUND

(2) Data management systems gather data and/or otherwise monitor many different complex activities and processes. The gathering of sufficient and relevant data to verify that a specific activity, tool, or task is performing as expected (or identifying a problem with the activity, tool, or task) can be intensive. As analytics efforts within data management systems increase, the need to quickly verify the state and/or sequence of complex actions or processes will increase as well.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a block diagram of an example adaptive data management (ADM) system to implement adaptive data management in a network environment.
- (2) FIG. 2 is an illustration of an example edge network environment including an example edge gateway and an example edge switch that may implement the example ADM system of FIG. 1.
- (3) FIG. 3 is a block diagram of an example data routing management system including an example data routing manager to implement proactive data routing in a network environment.
- (4) FIG. 4 is a block diagram of an example implementation of the data routing manager of FIG. 3.
- (5) FIG. 5 is an illustration of example data graph models to facilitate proactive data routing in a network environment.
- (6) FIG. 6 is an illustration of an example event chain.
- (7) FIG. 7 is an illustration of example implementations of the event chain of FIG. 6.
- (8) FIG. 8 is an illustration of example data graph models to facilitate proactive data routing in a network environment.
- (9) FIGS. 9A-9C are illustrations of example environments to implement examples disclosed herein.
- (10) FIG. 10 depicts an example dataset including example metadata for proactive data routing in a network environment.
- (11) FIG. 11 depicts an example workflow to identify and/or output example data routing paths in a network environment.
- (12) FIG. 12 illustrates an overview of an Edge cloud configuration for Edge computing.
- (13) FIG. 13 illustrates operational layers among endpoints, an Edge cloud, and cloud computing environments.
- (14) FIG. 14 illustrates an example approach for networking and services in an Edge computing system.
- (15) FIG. 15 illustrates deployment of a virtual Edge configuration in an Edge computing system operated among multiple Edge nodes and multiple tenants.
- (16) FIG. 16 is a schematic diagram of an example infrastructure processing unit (IPU).
- (17) FIG. 17 is a flowchart representative of example machine-readable instructions and/or example operations that may be executed and/or instantiated by processor circuitry to implement the example ADM system of FIG. 1, the example data routing manager of FIG. 3, and/or the example data routing management circuitry of FIG. 4 to generate an example recommendation to integrate a hardware, software, and/or firmware feature in a semiconductor-based device (e.g., a silicon-based device).
- (18) FIG. 18 is a flowchart representative of example machine-readable instructions and/or example operations that may be executed and/or instantiated by processor circuitry to implement the example ADM system of FIG. 1, the example data routing manager of FIG. 3, and/or the

example data routing management circuitry of FIG. 4 to analyze ingested data in a network.

(19) FIG. 19 is another flowchart representative of example machine-readable instructions and/or example operations that may be executed and/or instantiated by processor circuitry to implement the example ADM system of FIG. 1, the example data routing manager of FIG. 3, and/or the example data routing management circuitry of FIG. 4 to analyze ingested data in a network.

(20) FIG. 20 is a flowchart representative of example machine-readable instructions and/or example operations that may be executed and/or instantiated by processor circuitry to implement the example ADM system of FIG. 1, the example data routing manager of FIG. 3, and/or the example data routing management circuitry of FIG. 4 to route a message to user(s).

(21) FIG. 21 is another flowchart representative of example machine-readable instructions and/or example operations that may be executed and/or instantiated by processor circuitry to implement the example ADM system of FIG. 1, the example data routing manager of FIG. 3, and/or the example data routing management circuitry of FIG. 4 to route a message to user(s).

(22) FIG. 22 is a flowchart representative of example machine-readable instructions and/or example operations that may be executed and/or instantiated by processor circuitry to implement the example ADM system of FIG. 1, the example data routing manager of FIG. 3, and/or the example data routing management circuitry of FIG. 4 to present a message to user(s).

(23) FIG. 23 is a flowchart representative of example machine-readable instructions and/or example operations that may be executed and/or instantiated by processor circuitry to implement the example ADM system of FIG. 1, the example data routing manager of FIG. 3, and/or the example data routing management circuitry of FIG. 4 to present a message to user(s) based on activity information associated with the user(s).

(24) FIG. 24 is a flowchart representative of example machine-readable instructions and/or example operations that may be executed and/or instantiated by processor circuitry to implement the example ADM system of FIG. 1, the example data routing manager of FIG. 3, and/or the example data routing management circuitry of FIG. 4 to escalate presentation of a message to user(s).

(25) FIG. 25 is a flowchart representative of example machine-readable instructions and/or example operations that may be executed and/or instantiated by processor circuitry to implement the example ADM system of FIG. 1, the example data routing manager of FIG. 3, and/or the example data routing management circuitry of FIG. 4 to augment a data object to present to a user based on metadata associated with the user.

(26) FIG. 26 is a flowchart representative of example machine-readable instructions and/or example operations that may be executed and/or instantiated by processor circuitry to implement the example ADM system of FIG. 1, the example data routing manager of FIG. 3, and/or the example data routing management circuitry of FIG. 4 to adjust metadata associated with a user.

(27) FIG. 27 is a flowchart representative of example machine-readable instructions and/or example operations that may be executed and/or instantiated by processor circuitry to implement the example ADM system of FIG. 1, the example data routing manager of FIG. 3, and/or the example data routing management circuitry of FIG. 4 to train and/or retrain a machine-learning model.

(28) FIG. 28 is a flowchart representative of example machine-readable instructions and/or example operations that may be executed and/or instantiated by processor circuitry to implement the example ADM system of FIG. 1, the example data routing manager of FIG. 3, and/or the example data routing management circuitry of FIG. 4 to persist a contextual data graph model in a shared datastore to be accessible by a node.

(29) FIG. 29 is a flowchart representative of example machine-readable instructions and/or example operations that may be executed and/or instantiated by processor circuitry to implement the example ADM system of FIG. 1, the example data routing manager of FIG. 3, and/or the example data routing management circuitry of FIG. 4 to determine a strength of association

between a first data object and a second data object of a contextual data graph model.

(30) FIG. **30** is a flowchart representative of example machine-readable instructions and/or example operations that may be executed and/or instantiated by processor circuitry to implement the example ADM system of FIG. **1**, the example data routing manager of FIG. **3**, and/or the example data routing management circuitry of FIG. **4** to update one(s) of contextual data graph models based on correlation(s).

(31) FIG. **31** is a flowchart representative of example machine-readable instructions and/or example operations that may be executed and/or instantiated by processor circuitry to implement the example ADM system of FIG. **1**, the example data routing manager of FIG. **3**, and/or the example data routing management circuitry of FIG. **4** to provide updated contextual data graph models to at least one of node(s) or a shared datastore.

(32) FIG. **32** is a flowchart representative of example machine-readable instructions and/or example operations that may be executed and/or instantiated by processor circuitry to implement the example ADM system of FIG. **1**, the example data routing manager of FIG. **3**, and/or the example data routing management circuitry of FIG. **4** to update a contextual data graph model based on a machine-learning output.

(33) FIG. **33** is a flowchart representative of example machine-readable instructions and/or example operations that may be executed and/or instantiated by processor circuitry to implement the example ADM system of FIG. **1**, the example data routing manager of FIG. **3**, and/or the example data routing management circuitry of FIG. **4** to cause transmission of a message to a node based on a data routing path.

(34) FIG. **34** is a flowchart representative of example machine-readable instructions and/or example operations that may be executed and/or instantiated by processor circuitry to implement the example ADM system of FIG. **1**, the example data routing manager of FIG. **3**, and/or the example data routing management circuitry of FIG. **4** to cause an action to occur in an environment based on a message.

(35) FIG. **35** is a flowchart representative of example machine-readable instructions and/or example operations that may be executed and/or instantiated by processor circuitry to implement the example ADM system of FIG. **1**, the example data routing manager of FIG. **3**, and/or the example data routing management circuitry of FIG. **4** to present a message to a user.

(36) FIG. **36** is a flowchart representative of example machine-readable instructions and/or example operations that may be executed and/or instantiated by processor circuitry to implement the example ADM system of FIG. **1**, the example data routing manager of FIG. **3**, and/or the example data routing management circuitry of FIG. **4** to present data to a user based on one or more communication mediums.

(37) FIG. **37** is a flowchart representative of example machine-readable instructions and/or example operations that may be executed and/or instantiated by processor circuitry to implement the example ADM system of FIG. **1**, the example data routing manager of FIG. **3**, and/or the example data routing management circuitry of FIG. **4** to output a message to a user based on bandwidth associated with the user.

(38) FIG. **38** is a flowchart representative of example machine-readable instructions and/or example operations that may be executed and/or instantiated by processor circuitry to implement the example ADM system of FIG. **1**, the example data routing manager of FIG. **3**, and/or the example data routing management circuitry of FIG. **4** to cause an action to occur in an environment based on a digital twin associated with the environment.

(39) FIG. **39** is a flowchart representative of example machine-readable instructions and/or example operations that may be executed and/or instantiated by processor circuitry to implement the example ADM system of FIG. **1**, the example data routing manager of FIG. **3**, and/or the example data routing management circuitry of FIG. **4** to train and/or retrain a machine-learning model associated with a digital twin.

(40) FIG. 40 is a flowchart representative of example machine-readable instructions and/or example operations that may be executed and/or instantiated by processor circuitry to implement the example ADM system of FIG. 1, the example data routing manager of FIG. 3, and/or the example data routing management circuitry of FIG. 4 to cause device(s) to select one(s) of the device(s) to execute task(s).

(41) FIG. 41 is a block diagram of an example processing platform including processor circuitry structured to execute the example machine-readable instructions and/or the example operations of one(s) of FIGS. 17-40 to implement the ADM system of FIG. 1.

(42) FIG. 42 is a block diagram of an example processing platform including processor circuitry structured to execute the example machine-readable instructions and/or the example operations of one(s) of FIGS. 17-40 to implement the example data routing manager of FIG. 3 and/or the example data routing management circuitry system of FIG. 4.

(43) FIG. 43 is a block diagram of an example implementation of the processor circuitry of FIGS. 41 and/or 42.

(44) FIG. 44 is a block diagram of another example implementation of the processor circuitry of FIG. 4.

(45) FIG. 45 is a block diagram of an example software distribution platform (e.g., one or more servers) to distribute software (e.g., software corresponding to the example machine-readable instructions of FIGS. 17-40) to client devices associated with end users and/or consumers (e.g., for license, sale, and/or use), retailers (e.g., for sale, re-sale, license, and/or sub-license), and/or original equipment manufacturers (OEMs) (e.g., for inclusion in products to be distributed to, for example, retailers and/or to other end users such as direct buy customers).

DETAILED DESCRIPTION

(46) The figures are not to scale. In general, the same reference numbers will be used throughout the drawing(s) and accompanying written description to refer to the same or like parts. As used herein, connection references (e.g., attached, coupled, connected, and joined) may include intermediate members between the elements referenced by the connection reference and/or relative movement between those elements unless otherwise indicated. As such, connection references do not necessarily infer that two elements are directly connected and/or in fixed relation to each other.

(47) Unless specifically stated otherwise, descriptors such as “first,” “second,” “third,” etc., are used herein without imputing or otherwise indicating any meaning of priority, physical order, arrangement in a list, and/or ordering in any way, but are merely used as labels and/or arbitrary names to distinguish elements for ease of understanding the disclosed examples. In some examples, the descriptor “first” may be used to refer to an element in the detailed description, while the same element may be referred to in a claim with a different descriptor such as “second” or “third.” In such instances, it should be understood that such descriptors are used merely for identifying those elements distinctly that might, for example, otherwise share a same name.

(48) As used herein “substantially real time” and “substantially-real time” refer to occurrence in a near instantaneous manner recognizing there may be real-world delays for computing time, transmission, etc. Thus, unless otherwise specified, “substantially real time” and “substantially-real time” refer to being within a 1-second time frame of real time. As used herein, the phrase “in communication,” including variations thereof, encompasses direct communication and/or indirect communication through one or more intermediary components, and does not require direct physical (e.g., wired) communication and/or constant communication, but rather additionally includes selective communication at periodic intervals, scheduled intervals, aperiodic intervals, and/or one-time events.

(49) As used herein, “processor circuitry” is defined to include (i) one or more special purpose electrical circuits structured to perform specific operation(s) and including one or more semiconductor-based logic devices (e.g., electrical hardware implemented by one or more transistors), and/or (ii) one or more general purpose semiconductor-based electrical circuits

programmed with instructions to perform specific operations and including one or more semiconductor-based logic devices (e.g., electrical hardware implemented by one or more transistors). Examples of processor circuitry include programmed microprocessors, Field Programmable Gate Arrays (FPGAs) that may instantiate instructions, Central Processor Units (CPUs), Graphics Processor Units (GPUs), Digital Signal Processors (DSPs), XPU, or microcontrollers and integrated circuits such as Application Specific Integrated Circuits (ASICs). For example, an XPU may be implemented by a heterogeneous computing system including multiple types of processor circuitry (e.g., one or more FPGAs, one or more CPUs, one or more GPUs, one or more DSPs, etc., and/or a combination thereof) and application programming interface(s) (API(s)) that may assign computing task(s) to whichever one(s) of the multiple types of the processing circuitry is/are best suited to execute the computing task(s).

(50) Network environments today have many different complex activities and processes, and the gathering of sufficient and relevant data to verify that a specific activity, tool, or task is performing as expected (or identifying a problem with the activity, tool, or task) can be intensive. As Edge analytics efforts increase, the need to quickly verify the state and/or sequence of complex actions or processes will increase as well. This will enable faster and more effective decisions and actions an organization can make in their complex environments.

(51) Examples disclosed herein include systems, apparatus, articles of manufacture, and methods for proactive and/or adaptive data management and analytics. In some disclosed examples, proactive and/or otherwise adaptive data management is implemented by an example proactive and/or otherwise adaptive data management system. Advantageously, an example proactive and/or otherwise adaptive data management and analytics system as disclosed herein is an improvement over conventional, static data management systems that may require constant adjustments and modifications to satisfy complex and diverse network workloads.

(52) Examples disclosed herein include proactive and/or adaptive data retention in an automated and contextual manner as a part of proactive and/or otherwise adaptive data management for a network environment. Examples disclosed herein retain, analyze, and/or store ingested data. Once data is retained, analyzed, and/or stored, examples disclosed herein include presenting relevant information to a user, which can be a human or device. In some disclosed examples, presenting the relevant information to a user can be implemented by determining an optimum representation of data for the user through customization and creation of a network of subject matter experts and stakeholders. In some disclosed examples, the network of the subject matter experts and/or the stakeholders can be implemented by users whom the data could be sent for supervisory inputs, timeliness, addition of relevant information, and the like. In some disclosed examples, the data itself and/or associated metadata can provide guidance to whom or what (e.g., an application or service) the data should be provided based on the context and urgency of the data.

(53) FIG. 1 is a block diagram of an example adaptive data management (ADM) system **100** to implement adaptive data management in a network environment. In some examples, the ADM system **100** can effectuate and/or otherwise implement proactive data management in the network environment. The ADM system **100** of FIG. 1 may be instantiated (e.g., creating an instance of, bring into being for any length of time, materialize, implement, etc.) by processor circuitry such as a central processing unit (CPU) executing instructions. Additionally or alternatively, the ADM system **100** of FIG. 1 may be instantiated by an ASIC or an FPGA structured to perform operations corresponding to the instructions. It should be understood that some or all of the ADM system **100** of FIG. 1 may, thus, be instantiated at the same or different times. Some or all of the ADM system **100** of FIG. 1 may be instantiated, for example, in one or more threads executing concurrently on hardware and/or in series on hardware. Moreover, in some examples, some or all of the ADM system **100** of FIG. 1 may be implemented by microprocessor circuitry executing instructions to implement one or more virtual machines and/or containers.

(54) In some examples, the ADM system **100** is implemented using an example logical entity **101**.

For example, the logical entity **101** can be implemented using a client compute node, such as any type of endpoint component, device, appliance, or other tangible element capable of communicating as a producer or consumer of data. In some examples, the logical entity **101** can be implemented by, for example, a server, a personal computer, a workstation, a self-learning machine (e.g., a neural network), a mobile device (e.g., a cell phone, a smart phone, a tablet such as an iPad™), a personal digital assistant (PDA), an Internet appliance, a sensor, a personal video recorder, a headset (e.g., an augmented reality (AR) headset, a virtual reality (VR) headset, etc.) or other wearable device, or any other type of computing and/or electronic device. In some examples, the logical entity **101** can be implemented using one or more compute nodes (e.g., client compute nodes), one or more servers, one or more personal computers, etc., and/or any combination(s) thereof. For example, a first portion of the logical entity **101** can be implemented using a first client compute node and a second portion of the logical entity **101** can be implemented using a second client compute node. Any other combinations are contemplated.

(55) In the illustrated example of FIG. **1**, the ADM system **100** includes an example ADM console **102**, example data sources **104**, and an example data ingestion manager **106**, which includes an example pre-processing manager **108**. The ADM system **100** includes an example data query manager **110**, which includes an example data query handler **112**, an example query cache cluster manager **114**, and an example metadata cluster manager **116**. The ADM system **100** includes an example data publishing manager **118**, which includes an example scheduler **120**. The ADM system **100** includes an example node manager **122**, which includes an example preferred nodes table **124**. The ADM system **100** includes an example network plane **126**, which includes an example data plane **128** and an example control plane **130**. The ADM system **100** includes an example data security manager **132**, an example algorithm manager and/or recommender (AMR) **134**, and an example analytics manager **136**, which includes example algorithms **138** (identified by ALGO1, ALGO2, ALGO3), and an example metadata and/or data enrichment manager **140**. The ADM system **100** includes an example resource manager and/or orchestration agent **142**. The ADM system **100** includes an example distributed datastore **144**, which includes an example metadata datastore **146** and an example raw datastore **148**.

(56) In the illustrated example, the ADM system **100** includes the ADM console **102** to instantiate, setup, and/or configure portion(s) of the ADM system **100** (e.g., the data ingestion manager **106**, the node manager **122**, etc.). For example, the ADM console **102** can configure the metadata/data enrichment manager **140**. In some examples, the ADM console **102** can effectuate and/or otherwise execute metadata tagging by adding, removing, and/or modifying metadata. In some examples, the ADM console **102** can enforce and/or otherwise implement security policies. For example, the ADM console **102** can add, remove, and/or modify access policies generated, managed, and/or otherwise handled by the data security manager **132**. In some examples, the ADM console **102** can configure data management settings (e.g., locality, expiration date, etc., of data) associated with data that is generated, accessed, and/or stored by the ADM system **100**. In some examples, the ADM console **102** can be implemented using one or more user experience (UX) and/or user interface (UI) (e.g., graphical user interface (GUI)) consoles, displays, interfaces, etc.

(57) In the illustrated example, the ADM system **100** includes the data ingestion manager **106** to ingest, receive, and/or otherwise obtain data from one(s) of the data sources **104**. For example, the data sources **104** can be implemented using hardware alone, and/or any combination of hardware, software, and/or firmware as disclosed herein (e.g., hardware, software, and/or firmware of an autonomous guided vehicle (AGV), a server, an IoT device, an Edge appliance, a robot, etc.). In some examples, the data ingestion manager **106** includes the pre-processing manager **108** to pre-process data obtained from the data sources **104**. For example, the data ingestion manager **106** can extract portion(s) of the data, convert portion(s) of the data from a first data format to a second data format, compress or decompress the data, decrypt or encrypt the data, etc., and/or any combination(s) thereof.

(58) In the illustrated example, the ADM system **100** includes the data query manager **110** to queue and/or otherwise process data search requests from users and/or applications. For example, the data query handler **112** can queue and/or otherwise process the data search requests. In some examples, the data query handler **112** can generate and/or return results associated with the data search results to the requester (e.g., the requesting user, the requesting device, the requesting application/service, etc.). In some examples, the data query manager **110** can utilize the existence of metadata tables extracted from data files (e.g., media (e.g., multimedia, audio, video, text, image, etc.), alphanumeric, spatial, etc., data files) that have been pre-generated by the metadata/data enrichment manager **140**. In some examples, the data query manager **110** can be implemented using a search and match of topical terms to metadata tags. In some examples, the data query manager **110** can be implemented using a search and match of weighted topics and phrases with Boolean operations to perform complex contextual matches, prioritizations, and sequences of topics mapping.

(59) In some examples, the data query manager **110** manages multiple metadata context, which can result from metadata generating engines, sub-metadata tables specific to user/applications with unique context, permissions, etc., etc. In some examples, the data query manager **110** can inspect and/or scan a metadata file (e.g., a metadata array, data structure, data graph or data graph model, table, etc.), for primary search and recommendation of most appropriate data file links associated with portion(s) of the metadata file. For example, the data query manager **110** can include the metadata cluster manager **116** to scan the metadata file and/or return a number of excerpts (e.g., a user selectable number of excerpts, portions, etc.) for final selection and output. In some examples, the data query manager **110** can check selections for permission level appropriateness. For example, different departments, regions, sections, sectors, zones, etc., of an environment can have security and access control. In some examples, the data query manager **110** can cross-reference the selections with the security and access control to determine whether a requester has access to the selections. In some examples, the data query manager **110** can link a user/application to a returned and/or otherwise identified data source file. In some examples, the data query manager **110** and a metadata database (e.g., the metadata datastore **146**) need not be co-resident.

(60) In some examples, the data query manager **110** can include the query cache cluster manager **114** to effectuate and/or otherwise execute selective caching. For example, the query cache cluster manager **114** can activate and/or otherwise enable caching for frequently requested and/or accessed topics, most recently used search terms with user selected and preferred data source file links, data source file linkages that have a high correlation to one another (e.g., occurs frequently), etc., and/or any combination(s) thereof.

(61) In some examples, the data query manager **110** facilitates capacity scaling for data and/or resource demand volume and for serving local organizations, personnel, teams, etc. For example, the data query manager **110** can instantiate and/or otherwise launch additional instances of the data query manager **110** proximate and/or otherwise near to demand sources (e.g., a department server, an individual personal computer, etc.) that may be associated with the data sources **104**.

(62) Advantageously, in some examples, a locality of the metadata datastore **146** to the data query manager **110** can reduce network traffic and latency to ensure that even if a file (e.g., a data file) is unavailable, the existence of the file can be confirmed. In some examples, the data query manager **110** can effectuate and/or otherwise enable synchronization with other components of the ADM system **100** more frequently for metadata (e.g., metadata files, tables, etc.) of the metadata datastore **146** that is/are accessed most frequently or undergo significant changes (e.g., usually another feature of frequent use or recent capture). In some examples, the data query manager **110** can achieve interactive and/or programmatic access to portion(s) of the ADM system **100**.

(63) In the illustrated example, the ADM system **100** includes the data publishing manager **118** to implement publish-subscribe messaging. For example, a subscriber (e.g., a data subscriber, a device or user subscriber, etc.) can coordinate with the scheduler **120** to subscribe to alerts, changes,

updates, etc., of data of the metadata datastore **146**, the raw datastore **148**, and/or data generated by one(s) of the data sources **104**. In some examples, the data publishing manager **118** can publish data of interest to the appropriate subscribers.

(64) In the illustrated example, the ADM system **100** includes the node manager **122** to enable nodes (e.g., edge nodes) to maintain lists (e.g., a friends list, a neighboring nodes list, a trusted or verified node list, etc.) on the network. In some examples, the list(s) can include(s) the preferred nodes table **124**. For example, the preferred nodes table **124** can be implemented using a routing table in networking examples. In some examples, the node manager **122** can maintain the table/list/index as a dynamic and/or evolving table/list/index by considering previous interactions and/or transactions between neighboring nodes. For example, the node manager **122** can control the table/list/index to rate neighboring nodes based on the context of data requested, the frequency of data requested, the Quality-of-Service (QoS) of past interactions, etc., and/or any combination(s) thereof. In some examples, the table/list/index can exist in the distributed datastore **144**, which can be quickly accessible upon a request from the data query manager **110**.

(65) In the illustrated example, the ADM system **100** includes the network plane **126** to facilitate the transmission, distribution, and/or propagation of data within a network environment. In some examples, the network plane **126** can be implemented by one or more networks. For example, the network plane **126** can be implemented by the Internet. However, the network plane **126** can be implemented using any suitable wired and/or wireless network(s) including, for example, one or more data buses, one or more Local Area Networks (LANs), one or more wireless Local Area Networks (WLANs), one or more cellular networks (e.g., fifth generation cellular (5G), sixth generation cellular (6G), etc., networks), one or more private networks, one or more public networks, one or more fiber networks, one or more satellite networks, one or more terrestrial networks, one or more non-terrestrial networks, etc., and/or any combination(s) thereof. In the illustrated example, component(s) of the ADM system **100** can provide, deliver, propagate, etc., data in the ADM system **100** by way of the data plane **128**. In the illustrated example, component(s) of the ADM system **100** can provide, deliver, propagate, etc., controls, commands, directions, instructions, etc., in the ADM system **100** via the control plane **130**.

(66) In the illustrated example, the ADM system **100** includes the data security manager **132** to control (e.g., add, create, change, delete, remove, modify, etc.) one(s) of the access policies. For example, the data security manager **132** can control the access policies rather than the node/platform level security components and/or a user who may be authenticated to access the network. In some examples, the data security manager **132** can be accessed through the ADM console **102**.

(67) In some examples, the data security manager **132** assigns initial security/access levels to data files, data streams, etc., based on user provided policy or explicit settings. In some examples, the data security manager **132** can facilitate autonomous control of access policies. For example, an access policy can define and/or stipulate that content can inherit security levels from other similar data files based on metadata, data topics, etc. In some examples, the data security manager **132** can ensure compatible security level data match for the user/application/service level security with appropriate data levels. In some examples, the data security manager **132** can define the scope of data availability (e.g., geographic, topical, personnel, security level, etc.). In some examples, the data security manager **132** can log audits for a query log (e.g., requests, copies, moves, successes/fails, reasons for the requests, successes, fails, etc., etc.) maintained by the data query manager **110**. In some examples, the data security manager **132** can ensure data/metadata from high security areas are not copied/moved to lower-level security environments. In some examples, the data security manager **132** can enforce top secret level access to confidential areas or non-top secret level access to unsecured servers. In some examples, the data security manager **132** can monitor with the data query manager **110** the data request traffic for potential irregularities. In some examples, the data security manager **132** can provide and/or implement encryption services, keys-

as-a service (KaaS), etc., and/or any combination(s) thereof for improved security of the ADM system **100**.

(68) In the illustrated example, the ADM system **100** includes the AMR **134** to monitor the data on the data plane **128** and/or in the distributed datastore **144** (e.g., when invoked or triggered to run analytics) and/or after a detection of a gap in the existing algorithms **138** of the analytics manager **136**. In some examples, the AMR **134** can interface with the resource manager **142** by using an example interface **150**. For example, the resource manager **142** can include and/or implement an orchestration agent that receives a request for new one(s) of the algorithms **138** to act on of data of interest. For example, if a node that was previously monitoring a video stream and now has some additional time series data, the AMR **134** can request the resource manager/orchestrator agent **142** for a new one of the algorithms **138** to update the analytics manager **136** to run insights on both modalities.

(69) In some examples, the analytics manager **136** includes a metadata and/or data agent (e.g., a metadata and/or data agent that can be implemented by the metadata/data enrichment manager **140**) that can request analytics to be executed by the AMR **134** for generating metadata from source streams/files. In some examples, the AMR **134** can instantiate one(s) of the algorithms **138** to generate the analytics. For example, one or more of the algorithms **138** can be implemented as microservice(s). For example, ALGO1 can be compiled, executed, run, and/or implemented as a microservice. In some examples, the microservice, when accessed and/or instantiated, can execute an application, a container, a service, a virtual machine, etc., to implement ALGO1. In some examples, a combination of the algorithms **138** can be implemented as microservice(s). For example, ALGO1 and ALGO2 can be compiled, executed, run, and/or implemented as a single microservice or multiple microservices. In some examples, the microservice(s), when accessed and/or instantiated, can execute an application, a container, a service, a virtual machine, etc., to implement ALGO1 and ALGO2. In some examples, the analytics can be generated by an Artificial Intelligence/Machine Learning (AI/ML) model (e.g., a neural network (NN)) for classification, a neural natural language processing (NNLP) network or model to parse documentation, etc., and/or any combination(s) thereof.

(70) In some examples, in the data or user domain, an application or a direct user request can request an analytics container (e.g., an analytics container, microservice, etc., that can be instantiated and/or implemented by the analytics manager **136**) with appropriate configuration(s) and optimization(s) for the requested task. In some examples, certain one(s) of the algorithms **138** or AI/ML models may be preferred over time as a function of accuracy and performance and priorities may be assigned to the one(s) of the algorithms **138** for utilization in the ADM system **100**.

(71) In some examples, the resource manager/orchestration agent **142** can orchestrate new one(s) of the algorithms **138** either from a centralized algorithm library based on example algorithm ratings, scores, etc., if available, or through a pointer or other reference to a local datastore (e.g., if available in a library) of the analytics manager **136** for faster access or the distributed datastore **144**.

(72) Artificial intelligence (AI), including machine-learning (ML), deep learning (DL), and/or other artificial machine-driven logic, enables machines (e.g., computers, logic circuits, etc.) to use a model to process input data to generate an output based on patterns and/or associations previously learned by the model via a training process. For instance, one(s) of the algorithms **138** may be trained with data to recognize patterns and/or associations and follow such patterns and/or associations when processing input data such that other input(s) result in output(s) consistent with the recognized patterns and/or associations. In some examples, an association can be implemented using a data association. For example, the association may itself be data. For example, the association can be implemented using an address (e.g., a storage or memory address), a pointer, a reference, etc., or any other data connection or linkage that may be stored in a mass storage device,

memory, etc.

(73) Many different types of machine-learning models and/or machine-learning architectures exist. In some examples, the analytics manager **136** may generate one(s) of the algorithms **138** as neural network model(s). In some examples, the resource manager/orchestration agent **142** may obtain and/or generate one(s) of the algorithms **138**. Using a neural network model enables the analytics manager **136** to execute AI/ML workload(s). In general, machine-learning models/architectures that are suitable to use in the example approaches disclosed herein include recurrent neural networks. However, other types of machine-learning models could additionally or alternatively be used such as supervised learning ANN models, clustering models, classification models, etc., and/or a combination thereof. Example supervised learning ANN models may include two-layer (2-layer) radial basis neural networks (RBN), learning vector quantization (LVQ) classification neural networks, etc. Example clustering models may include k-means clustering, hierarchical clustering, mean shift clustering, density-based clustering, etc. Example classification models may include logistic regression, support-vector machine or network, Naive Bayes, etc. In some examples, the analytics manager **136** may compile and/or otherwise generate one(s) of the algorithm(s) **138** as lightweight machine-learning models.

(74) In general, implementing an ML/AI system involves two phases, a learning/training phase and an inference phase. In the learning/training phase, a training algorithm is used to train the one(s) of the algorithms **138** to operate in accordance with patterns and/or associations based on, for example, training data. In general, the one(s) of the algorithms **138** include(s) internal parameters (e.g., indices, raw data, metadata, insights, models, weights, etc.) that guide how input data is transformed into output data, such as through a series of nodes and connections within the one(s) of the algorithms **138** to transform input data into output data. Additionally, hyperparameters are used as part of the training process to control how the learning is performed (e.g., a learning rate, a number of layers to be used in the machine-learning model, etc.). Hyperparameters are defined to be training parameters that are determined prior to initiating the training process.

(75) Different types of training may be performed based on the type of ML/AI model and/or the expected output. For example, the analytics manager **136** may invoke supervised training to use inputs and corresponding expected (e.g., labeled) outputs to select parameters (e.g., by iterating over combinations of select parameters) for the one(s) of the algorithms **138** that reduce model error. As used herein, “labeling” refers to an expected output of the machine-learning model (e.g., a classification, an expected output value, etc.). Alternatively, the analytics manager **136** may invoke unsupervised training (e.g., used in deep learning, a subset of machine-learning, etc.) that involves inferring patterns from inputs to select parameters for the one(s) of the algorithms **138** (e.g., without the benefit of expected (e.g., labeled) outputs).

(76) In some examples, the analytics manager **136** trains the one(s) of the algorithms **138** using unsupervised clustering of operating observables. For example, the operating observables may include data from the data sources **104**, metadata in the metadata datastore **146**, data in the raw datastore **148**, etc., and/or combination(s) thereof. However, the analytics manager **136** may additionally or alternatively use any other training algorithm such as stochastic gradient descent, Simulated Annealing, Particle Swarm Optimization, Evolution Algorithms, Genetic Algorithms, Nonlinear Conjugate Gradient, etc.

(77) In some examples, the analytics manager **136** may train the one(s) of the algorithms **138** until the level of error is no longer reducing. In some examples, the analytics manager **136** may train the one(s) of the algorithms **138** locally on the analytics manager **136** and/or remotely at an external computing system (e.g., on external computing device(s) in communication with the resource manager/orchestration agent **142**) communicatively coupled to the analytics manager **136**. In some examples, the analytics manager **136** trains the one(s) of the algorithms **138** using hyperparameters that control how the learning is performed (e.g., a learning rate, a number of layers to be used in the machine-learning model, etc.). In some examples, the analytics manager **136** may use

hyperparameters that control model performance and training speed such as the learning rate and regularization parameter(s). The analytics manager **136** may select such hyperparameters by, for example, trial and error to reach an optimal model performance. In some examples, the analytics manager **136** Bayesian hyperparameter optimization to determine an optimal and/or otherwise improved or more efficient network architecture to avoid model overfitting and improve the overall applicability of the one(s) of the algorithms **138**. Alternatively, the analytics manager **136** may use any other type of optimization. In some examples, the analytics manager **136** may perform re-training. The analytics manager **136** may execute such re-training in response to override(s) by a user of the ADM system **100**, a receipt of new training data, change(s) to node(s), change(s) observed and/or otherwise identified by node(s), etc.

(78) In some examples, the analytics manager **136** facilitates the training of the one(s) of the algorithms **138** using training data. In some examples, the analytics manager **136** utilizes training data that originates from locally generated data, such as one(s) of the data from the data sources **104**, metadata in the metadata datastore **146**, data in the raw datastore **148**, etc., and/or combination(s) thereof. In some examples, the analytics manager **136** utilizes training data that originates from externally generated data, such as data from the data sources **104**, data from the resource manager/orchestration agent **142**, etc., and/or combination(s) thereof. In some examples where supervised training is used, the analytics manager **136** may label the training data (e.g., label training data or portion(s) thereof with appropriate metadata). Labeling is applied to the training data by a user manually or by an automated data pre-processing system. In some examples, the analytics manager **136** may pre-process the training data. In some examples, the analytics manager **136** sub-divides the training data into a first portion of data for training the one(s) of the algorithms **138**, and a second portion of data for validating the one(s) of the algorithms **138**.

(79) Once training is complete, the analytics manager **136** may deploy the one(s) of the algorithms **138** for use as an executable construct that processes an input and provides an output based on the network of nodes and connections defined in the one(s) of the algorithms **138**. The analytics manager **136** may store the one(s) of the algorithms **138** in the analytics manager **136**. In some examples, the analytics manager **136** may invoke the interface **150** to transmit the one(s) of the algorithms **138** to one(s) of the external computing systems in communication with the resource manager/orchestration agent **142**. In some examples, in response to transmitting the one(s) of the algorithms **138** to the one(s) of the external computing systems, the one(s) of the external computing systems may execute the one(s) of the algorithms **138** to execute AI/ML workloads with at least one of improved efficiency or performance.

(80) Once trained, the deployed one(s) of the algorithms **138** may be operated in an inference phase to process data. In the inference phase, data to be analyzed (e.g., live data) is input to the one(s) of the algorithms **138**, and the one(s) of the algorithms **138** execute(s) to create an output. This inference phase can be thought of as the AI “thinking” to generate the output based on what it learned from the training (e.g., by executing the one(s) of the algorithms **138** to apply the learned patterns and/or associations to the live data). In some examples, input data undergoes pre-processing before being used as an input to the one(s) of the algorithms **138**. Moreover, in some examples, the output data may undergo post-processing after it is generated by the one(s) of the algorithms **138** to transform the output into a useful result (e.g., a display of data, a detection and/or identification of an object, an instruction to be executed by a machine, etc.).

(81) In some examples, output of the deployed one(s) of the algorithms **138** may be captured and provided as feedback. By analyzing the feedback, an accuracy of the deployed one(s) of the algorithm(s) **138** can be determined. If the feedback indicates that the accuracy of the deployed model is less than a threshold or other criterion, training of an updated model can be triggered using the feedback and an updated training data set, hyperparameters, etc., to generate an updated, deployed model.

(82) In the illustrated example, the ADM system **100** includes the metadata/data enrichment

manager **140** to schedule and/or execute metadata creation and/or post-processing routines intended to extract context and meaning from the source data stream/data files to enhance source data files to decrease noise and/or clarify/focus subjects or topics of interest. In some examples, the metadata/data enrichment manager **140** includes a metadata and/or enhancement request routine, an online metadata agent, and/or an offline metadata agent. In some examples, the metadata/enhancement request routine can be configured and/or otherwise instantiated to take inputs from a user or process/application to articulate the types of metadata/enhancement and determine what operations can be done in real time and what can be done offline based on a complexity of the request, type of data, available processing resources, priority/urgency of the operation, and the like. In some examples, the metadata/data enrichment manager **140** can augment, enhance, and/or otherwise enrich metadata by adding and/or otherwise including new metadata after ingesting data from an environment. In some examples, the metadata/data enrichment manager **140** can enrich metadata by deleting and/or otherwise removing portion(s) of the metadata that is/are determined to be irrelevant (or not as relevant as once determined) or not useful for determining output(s) with a high likelihood of accuracy, relevancy, etc., and/or any combination(s) thereof.

(83) In some examples, the online metadata agent can access existing metadata or enhancement functionality within a node or launch a selected algorithm package to perform real time metadata/enhancement actions on the data stream and create a source-file linked metadata record that may be passed to the data query manager **110** for incorporation and synchronization with other authorized and/or relevant instances of the data query manager **110**. In the example of source file enhancement, the original file may be archived and linked with appropriate metadata record while the modified file is returned to the requestor.

(84) In some examples, the offline metadata agent can be implemented as the real time agent instantiated on the server/file storage that runs metadata/enhancement routines offline due to resource availability, complexity of operations, and/or lower priority setting. Subsequent behavior may be similar to the online metadata once post-processing has been completed.

(85) In some examples, the metadata/data enrichment manager **140** evaluates metadata/enhancement requests and priority. In some examples, the metadata/data enrichment manager **140** can select appropriate operations for base metadata and enhancement operations. In some examples, the metadata/data enrichment manager **140** can invoke and/or otherwise provoke the AMR **134** to heuristically suggest proper algorithm(s) for advanced data operations and/or recommend algorithm combinations (e.g., algorithm recipes) from prior operations that may be preferred by different customers or observed to operate best on certain hardware.

(86) In some examples, the metadata/data enrichment manager **140** can identify real-time operations from post-processed operations and confirm with the user allowing the user to modify. In some examples, the metadata/data enrichment manager **140** can launch modules (e.g., AI, NLP, analytics, statistics, etc.) to generate metadata (e.g., generate association(s) of data portion(s) and metadata) and/or enhance existing data (e.g., hyper-resolution or false image enhancements) on local node or supporting compute platform(s). In some examples, the metadata/data enrichment manager **140** can manage archiving of sources, appending metadata records requested or provided by the data query manager **110** (with source links), etc. In some examples, a single instance of the metadata/data enrichment manager **140** can manage multiple metadata/enhancement operations.

(87) In the illustrated example, the ADM system **100** includes the distributed datastore **144** to record data. For example, the distributed datastore **144** can include the metadata datastore **146** to record and/or otherwise store metadata. In some examples, the distributed datastore **144** can include the raw datastore **148** to record raw and/or otherwise unprocessed data. The distributed datastore **144** can be implemented by one or more volatile memories (e.g., a Synchronous Dynamic Random Access Memory (SDRAM), Dynamic Random Access Memory (DRAM), RAMBUS Dynamic Random Access Memory (RDRAM), etc.), one or more non-volatile memories (e.g., flash

memory), and/or combination(s) thereof. The distributed datastore **144** may additionally or alternatively be implemented by one or more double data rate (DDR) memories, such as DDR, DDR2, DDR3, DDR4, DDR5, mobile DDR (mDDR), etc. The distributed datastore **144** may additionally or alternatively be implemented by one or more mass storage devices such as hard disk drive(s) (HDD(s)), compact disk (CD) drive(s), digital versatile disk (DVD) drive(s), solid-state disk (SSD) drive(s), etc. While in the illustrated example the distributed datastore **144** is illustrated as a single datastore, the distributed datastore **144** may be implemented by any number and/or type(s) of datastores. For example, the distributed datastore **144** can be implemented by a plurality of one or more types of mass storage devices. In some examples, the one or more types of mass storage devices can be spread or distributed across one or more devices, logical entities, etc. In some examples, the one or more devices, logical entities, etc., need not be co-resident, located in the same geographical location (e.g., same mailing address, city, state, country, continent, etc.). Furthermore, the data stored in the distributed datastore **144** may be in any data format such as, for example, binary data, comma delimited data, tab delimited data, structured query language (SQL) structures, etc.

(88) In some examples, the metadata datastore **146**, the raw datastore **148**, and/or, more generally, the distributed datastore **144**, can implement and/or include one or more databases. The term “database” as used herein means an organized body of related data, regardless of the manner in which the data or the organized body thereof is represented.

(89) For example, the organized body of related data may be in the form of one or more of a table, a map, a grid, a packet, a datagram, a frame, a model (e.g., an AI/ML model, a data graph model, etc.), a file, an e-mail, a message, a document, a report, a spreadsheet, a business-related document (e.g., an invoice, a shipping manifest, etc.), a user manual or guide, a maintenance manual or guide, an installation manual or guide, a workflow manual or guide, a media file, an audio file, an image file, a video file, a list, or in any other form.

(90) As used herein, “data” is information in any form that may be ingested, processed, interpreted and/or otherwise manipulated by processor circuitry to produce a result. The produced result may itself be data.

(91) As used herein, “metadata” is information in any form that may be ingested, processed, interpreted and/or otherwise manipulated by processor circuitry to produce a result. The produced result may itself be data.

(92) As used herein, a “threshold” is expressed as data such as a numerical value represented in any form, that may be used by processor circuitry as a reference for a comparison operation.

(93) As used herein, a “model” is a set of instructions and/or data that may be ingested, processed, interpreted and/or otherwise manipulated by processor circuitry to produce a result. Often, a model is operated using input data to produce output data in accordance with one or more relationships reflected in the model. The model may be based on training data.

(94) The terms “media data” and “media” as used herein refer to data that is accessible, whether over-the-air, or via cable, satellite, network, internetwork (including the Internet), print, displayed, distributed on storage media, or by any other technique that is humanly perceptible, without regard to the form or content of such data, and include but are not limited to audio, video, audio/video, text, images, advertisements, animations, databases, broadcasts, content, displays (including but not limited to video displays, posters and billboards), signs, signals, web pages, print media, streaming media data, etc. For example, “media data” and “media” can be information in any form (e.g., alphanumeric characters, bits, bytes, etc.) that can be ingested, processed, interpreted and/or otherwise manipulated by processor circuitry to produce a result. The produced result may itself be data. In some examples, the result can be the presentation of audio, image, text, and/or video data on one or more display devices or playback devices (e.g., a monitor, a display panel, a television, a display wall, a touchscreen, a wearable device, a printer, a plotter, a speaker, a projector, headphones (e.g., wireless or wired headphones), an audio amplifier, a stereo, etc.).

(95) As used herein, “multimedia” refers to two or more types of media combined in order to convey information. For example, a video can be multimedia by including audio, text, and/or video data in the video. In some examples, a request for media can be a request for multimedia. For example, a request for a web site can be a multimedia request, which can include requesting a video and/or an accompanying video advertisement, each of which can include more than one type of media such as audio, text, and/or video. For example, “multimedia” can be information in any form (e.g., alphanumeric characters, bits, bytes, etc.) that can be ingested, processed, interpreted and/or otherwise manipulated by processor circuitry to produce a result. The produced result may itself be data. In some examples, the result can be the presentation of audio, image, text, and/or video data on one or more display devices or playback devices (e.g., a monitor, a display panel, a television, a display wall, a touchscreen, a wearable device, a printer, a plotter, a speaker, a projector, headphones (e.g., wireless or wired headphones), an audio amplifier, a stereo, etc.).

(96) In some examples, data from the data sources **104** and/or data output from the ADM system **100** can be data in and/or based on any type of data representation. For example, the data can have and/or include a data type, an object type, a data object type, a sub-object type, a data sub-object type, etc. In some examples, data ingested from the data sources **104** and/or data output from the ADM system **100** can include one or more different types of data objects, such as an audio object, an image object, a text object, or a video object, and/or, more generally, a media object or a multimedia object. An object (e.g., a data object, an image object, a media object, a text object, a video object, etc.), such as an audio object, an image object, a text object, a video object, etc., can be information in any form (e.g., alphanumeric characters, bits, bytes, etc.) that can be ingested, processed, interpreted and/or otherwise manipulated by processor circuitry to produce a result. The produced result may itself be data. In some examples, the result can be the presentation of audio, image, text, and/or video data on one or more display devices of an electronic and/or computing system.

(97) In some examples, video objects can include different types of video data. For example, a video object (e.g., a video data object) can be an MP4 video object (e.g., video data in an MP4 or MPEG-4 Part 14 video format), a MOV video object (e.g., video data in a MOV video format), a WMV video object (e.g., video data in a WMV video format), an AVI video object (e.g., video data in an AVI video format), etc. In some examples, the video object can be video data in any other video format such as AVCHD, FLV, F4V, SWF, etc.

(98) In some examples, audio objects can include different types of audio data. For example, an audio object (e.g., an audio data object) can be an MP3 audio object (e.g., audio data in an MP3 or MPEG-1 Audio Layer 3 audio format), an AAC audio object (e.g., audio data in an AAC audio format), a FLAC audio object (e.g., audio data in a FLAC audio format), an ALAC audio object (e.g., audio data in an ALAC audio format), etc. In some examples, the audio object can be audio data in any other audio format such as Ogg Vorbis, WAV, AIFF, DSD, etc.

(99) In some examples, image objects can include different types of image data. For example, an image object (e.g., an image data object) can be a Bitmap (BMP) object or file, a Graphics Interchange Format (GIF) object or file, a Joint Photographic Experts Group (JPEG) object or file, a Portable Document Format (PDF) object or file, a Portable Network Graphic (PNG) object or file, etc. In some examples, the image object can be image data in any other image format such as a RAW object or file, a Tag Image File Format (TIFF) object or file, etc.

(100) In some examples, text objects can include different types of text data. For example, a text object (e.g., a text data object) can be a character or CHAR text object (e.g., text data in character text format), a string or STR text object (e.g., text data in string text format), an ASCII text object (e.g., text data in ASCII text format), etc. In some examples, the text object can be text data in any other text format such as DAT, TXT, CSV, etc.

(101) While an example manner of implementing the ADM system **100** is illustrated in FIG. **1**, one or more of the elements, processes, and/or devices illustrated in FIG. **1** may be combined, divided,

re-arranged, omitted, eliminated, and/or implemented in any other way. Further, the logical entity **101**, the ADM console **102**, the data sources **104**, the data ingestion manager **106**, the pre-processing manager **108**, the data query manager **110**, the data query handler **112**, the query cache cluster manager **114**, the metadata cluster manager **116**, the data publishing manager **118**, the scheduler **120**, the node manager **122**, the preferred nodes table **124**, the network plane **126**, the data plane **128**, the control plane **130**, the data security manager **132**, the AMR **134**, the analytics manager **136**, the algorithms **138**, the metadata/data enrichment manager **140**, the resource manager **142**, the distributed datastore **144**, the metadata datastore **146**, the raw datastore **148**, the interface **150**, and/or, more generally, the ADM system **100** of FIG. **1**, may be implemented by hardware alone or by hardware in combination with software and/or firmware. Thus, for example, any of the logical entity **101**, the ADM console **102**, the data sources **104**, the data ingestion manager **106**, the pre-processing manager **108**, the data query manager **110**, the data query handler **112**, the query cache cluster manager **114**, the metadata cluster manager **116**, the data publishing manager **118**, the scheduler **120**, the node manager **122**, the preferred nodes table **124**, the network plane **126**, the data plane **128**, the control plane **130**, the data security manager **132**, the AMR **134**, the analytics manager **136**, the algorithms **138**, the metadata/data enrichment manager **140**, the resource manager **142**, the distributed datastore **144**, the metadata datastore **146**, the raw datastore **148**, the interface **150**, and/or, more generally, the ADM system **100**, could be implemented by processor circuitry, analog circuit(s), digital circuit(s), logic circuit(s), programmable processor(s), programmable microcontroller(s), GPU(s), DSP(s), ASIC(s), programmable logic device(s) (PLD(s)), and/or field programmable logic device(s) (FPLD(s)) such as Field Programmable Gate Arrays (FPGAs). Further still, the ADM system **100** of FIG. **1** may include one or more elements, processes, and/or devices in addition to, or instead of, those illustrated in FIG. **1**, and/or may include more than one of any or all of the illustrated elements, processes and devices.

(102) FIG. **2** is an illustration of an example environment **200** including an example gateway **202** and an example switch **204** that may implement the ADM system **100** of FIG. **1** and/or otherwise as disclosed herein. In some examples, the environment **200** is a network environment, an edge network environment, etc. In some examples, the gateway **202** is an edge gateway. In some examples, the switch **204** is an edge switch. In some examples, the gateway **202** and/or the switch **204** may implement resources of the edge devices layer **1310** of FIG. **13** as disclosed below. In some examples the gateway **202** and/or the switch **204** may implement the access point or base station **1240** of FIG. **12**, the local processing hub **1250** of FIG. **12**, and/or the nodes **1315** of FIG. **13** as disclosed below. For example, the gateway **202** and/or the switch **204** may implement the edge devices layer **1310** of FIG. **13** as disclosed below.

(103) The environment **200** of the illustrated example includes an example public network **206**, an example private network **208**, and an example edge cloud **210**. In this example, the public network **206** can implement and/or include a telephone service provider (TSP) network (e.g., a Long-Term Evolution (LTE) network, a 5G network, a 6G network, a telecommunications (telco) network, etc.). For example, the public network **206** can implement and/or include the network access layer **1320** of FIG. **13**, the core network **1330** of FIG. **13**, and/or the cloud data center layer **1340** of FIG. **13** as disclosed below. In this example, the private network **208** can implement and/or include an enterprise network (e.g., a close campus network, a closed network, a private LTE network, a private 5G network, a private 6G network, etc.). For example, the private network **208** can implement and/or include the endpoint layer **1300** of FIG. **13** and/or the edge devices layer **1310** of FIG. **13**. In some examples, the edge cloud **210** can be implemented by hardware alone, or by any of combination of hardware, software, and/or firmware resources. For example, the edge cloud **210** can be implemented by one or more servers (e.g., computer and/or electronic servers, rack-mounted servers, blade servers, etc.). In this example, the edge cloud **210** can implement and/or include an enterprise edge cloud. For example, the edge cloud **210** can implement and/or include the edge cloud **1210** of FIGS. **12**, **13**, and/or **14**.

(104) In the illustrated example of FIG. 2, the environment **200** can be and/or implement a smart factory (e.g., a smart industrial factory), a process control environment, a smart warehouse, etc. For example, the environment **200** can implement one(s) of the computational use cases **1305** of FIG. **13**, such as a manufacturing, smart building, logistics, vehicle, and/or video computational use cases. Additionally or alternatively, the environment **200** may be an office building, a commercial building, a hospital or other medical facility, a research facility, a school or other education facility, an airport, a rail or railway station, a bus depot or station, a government services building or campus, etc., and/or any combination(s) thereof.

(105) The environment **200** of the illustrated example includes an example process control system **212**, example robots (e.g., collaborative robots, robot arms, etc.) **214**, a first example industrial machine (e.g., an autonomous industrial machine) **216**, a second example industrial machine **218**, a third example industrial machine **220**, a fourth example industrial machine **222**, an example predictive maintenance system **224**, an example vehicle (e.g., a truck, an autonomous truck, an autonomous vehicle, etc.) **226**, a first example monitoring sensor **228**, a second example monitoring sensor **230**, and example endpoint devices **232**, **234**, **236**. In some examples, the process control system **212** can include one or more industrial machines such as a silo, a smokestack, a conveyor belt, a mixer, a pump, etc., and/or any combination(s) thereof. For example, the process control system **212** can implement and/or include the business and industrial equipment **1263** of FIG. **12**, the smart cities and building devices **1266** of FIG. **12**, etc., as disclosed below.

(106) In some examples, the robots **214** can be hydraulic and/or electromechanical robots, which can be configured to execute and/or otherwise carry out or perform manufacturing tasks (e.g., lifting equipment or components, assembling components, disassembling components, etc.), industrial tasks, etc. For example, the robots **214** can implement and/or include the business and industrial equipment **1263** of FIG. **12**, the smart cities and building devices **1266** of FIG. **12**, etc., as disclosed below. In some examples, the industrial machines **216**, **218**, **220**, **222** are autonomous machines, such as AGVs, autonomous forklifts, scissor lifts, etc. For example, the industrial machines **216**, **218**, **220** can implement and/or include the business and industrial equipment **1263** of FIG. **12**, the drones **1265** of FIG. **12**, the smart cities and building devices **1266** of FIG. **12**, etc., as disclosed below. In some examples, the predictive maintenance system **224** can implement and/or include one or more computing devices, servers, etc., that identify maintenance alerts, fault predictions, etc., associated with equipment of the environment **200** based on sensor data (e.g., prognostic health data, sensor measurements, raw and/or processed sensor data or measurements, etc.). For example, the predictive maintenance system **224** can implement and/or include the business and industrial equipment **1263** of FIG. **12**, the smart cities and building devices **1266** of FIG. **12**, the sensors and IoT devices **1267** of FIG. **12**, etc., as disclosed below.

(107) In some examples, the vehicle **226** can be one of the autonomous vehicles **1261** of FIG. **12** as disclosed below. In some examples, the first monitoring sensor **228** and/or the second monitoring sensor **230** is/are video cameras, video sensors, etc. For example, the first monitoring sensor **228** and/or the second monitoring sensor **230** can implement and/or include the business and industrial equipment **1263** of FIG. **12**, the video capture devices **1264** of FIG. **12**, the smart cities and building devices **1266** of FIG. **12**, the sensors and IoT devices **1267** of FIG. **12**, etc., as disclosed below. Alternatively, the first monitoring sensor **228** and/or the second monitoring sensor **230** may be an environmental sensor, such as an air pollution sensor, an air pressure sensor, a carbon dioxide sensor, a carbon monoxide sensor, a humidity sensor, a light sensor, a temperature sensor, a water sensor, a wind speed sensor, etc., or any other type of sensor. Any other type and/or quantity of sensors are contemplated. For example, accelerometers, audio sensors, biometric sensors (e.g., facial recognition detectors, fingerprint sensors, heartbeat sensors, iris recognition sensors, speech recognition sensors, etc.), capacitive sensors (e.g., fingerprint sensors, floor-based sensors to detect when a device and/or an object is on a portion of a floor, etc.), chemical and/or gas sensors,

direction sensors (e.g., radio direction finders), electro-optical sensors, encoders (e.g., rotary encoders), geophones, gyroscopes, harmonic sensors, hydrophones, infrared sensors (e.g., infrared position sensors, infrared temperature sensors, etc.), laser rangefinders, laser surface velocimeters, map sensors, microphones, millimeter wave scanners, nanosensors, optical position sensors, photodetectors, pickup sensors, pressure sensors (e.g., floor-based and/or wall-based pressure sensors to detect when a device and/or an object is on a portion of a floor or in contact with a portion of a wall), position sensors, proximity sensors, radar systems (e.g., doppler, ground speed radar ultra-wideband radar), seismometers, shock detectors, sound locators, strain gauges (e.g., floor-based and/or wall-based strain gauges to detect when a device and/or an object is on a portion of a floor or in contact with a portion of a wall), time-of-flight sensors (e.g., time-of-flight cameras), triangulation and LIDAR Automated Rendezvous and Docking (TriDAR), tilt sensors, vibration sensors, etc., and/or any combination(s) thereof, can be included in the ADM system **100** of FIG. **1** (e.g., can be one(s) of the data sources **104** of FIG. **1**), and/or the environment **200** of FIG. **2**, generate and/or output data to be ingested by the data ingestion manager **106** of FIG. **1**, etc., (e.g., utilized as input(s) to an AI/ML model, microservice, algorithm, etc., as disclosed herein).

(108) Examples disclosed herein can utilize any type of wireless communication, technology, technique, or schema. For example, data routing determination techniques as disclosed herein can utilize and/or be based on ANT®, ANT+®, Dash 7, DigiMesh, EnOcean®, Global System for Mobile Communication (GSM), third generation cellular (i.e., 3G), Long-Term Evolution (e.g., LTE Category or Cat 0, LTE Cat 1, LTE Cat 3, LTE-M1, 4G LTE, etc.), 5G, 6G, Bluetooth®, Bluetooth Low-Energy (LE) (or also referred to as BLE), code division multiple access (CDMA), IPv6 over Low-Power Wireless Personal Area Networks (6LoWPAN), LoRaWAN™ (Long Range Wide Area Network), infrared, Narrowband IoT (NB-IoT®), near field communication (NFC®), radiofrequency identification (RFID), random phase multiple access (RPMA), satellite communication (e.g., GPS, a satellite communication protocol based on L-Band, S-Band, C-Band, Ka-Band, Ku-Band, Very High Frequency (VHF), Ultra High Frequency (UHF), etc.) SigFox®, Thread®, Weightless-N, Weightless-P, Weightless-W, Wi-Fi®, Wi-Fi® Direct, WiFi-ah (HaLow), WirelessHART, Zigbee®, Z-Wave®, etc. For example, the terms “wireless,” “wireless connection,” “wireless communication,” “wireless data,” and/or the like as used herein can refer to one(s) of the above list. For example, “wireless communication” as used herein can be Wi-Fi® communication, Zigbee® communication, etc. The aforementioned list is not exhaustive but provided as an illustrative range of wireless technologies, techniques, or schemas that are contemplated to effectuate example data routing determination techniques as disclosed herein. Furthermore, the aforementioned list may be used to implement unicast and/or multicast data routing to cause the routing of data between nodes in an adaptive and/or proactive manner.

(109) Turning back to the illustrated example of FIG. **2**, the endpoint devices **232**, **234**, **236** include a first example endpoint device **232**, a second example endpoint device **234**, and a third example endpoint device **236**. In some examples, one(s) of the endpoint devices **232**, **234**, **236** can be and/or implement consumer computing and/or electronic devices, user equipment, etc. For example, one or more of the endpoint devices **232**, **234**, **236** can implement and/or include the user equipment **1262** of FIG. **12** as disclosed below. In some examples, one or more of the endpoint devices **232**, **234**, **236** can be and/or be implemented by a smartphone, a tablet computer, a desktop computer, a laptop computer, a wearable device (e.g., a biometric device or sensor, a headset or headset display, an AR headset, a VR headset, a smartwatch, smart glasses, etc.), etc.

(110) In the illustrated example of FIG. **2**, the gateway **202** can facilitate communication, data transfers, data routing, etc., between different networks, such as communication from a source service, a source appliance, etc., of the public network **206** to a target service, a target appliance, etc., of the private network **208**. For example, the gateway **202** can receive a data stream including one or more data packets (or messages) from a source (e.g., a data source), a producer (e.g., a data

producer), etc. In some examples, the gateway **202** can receive the data stream from the vehicle **226**, the second endpoint device **234**, the third endpoint device **236**, etc., to be transmitted to a target service, a target appliance, etc., which can be implemented by the cloud data center **1230** of FIG. **12**, the cloud data center **1345** of FIG. **13**, the cloud or data center **1460** of FIG. **14**, etc., as disclosed below. In some examples, the gateway **202** can effectuate unicast and/or multicast data routing. By way of example, a message that is applicable and/or relevant to multiple electronic devices can be multicast to the multiple electronic devices. For example, a message indicative of a finished end product assembled by one of the robots **214** can be multicast to multiples ones of the industrial machines **216, 218, 220, 222** to cause one(s) of the industrial machines **216, 218, 220, 222** to transport and/or move the finished end product from the one of the robots **214** to elsewhere (e.g., one of the shelves, onto the vehicle **226**, etc.).

(111) In some examples, the gateway **202** can facilitate communication, data transfers, data routing, etc., between a source service, a source appliance, etc., of the private network **208** to a target service, a target appliance, etc., of the public network **206**. For example, the gateway **202** can receive a data stream, a packet stream, a data packet stream, a message stream, a data message stream, etc., including one or more data packets (or messages) from a source (e.g., a data source), a producer (e.g., a data producer), etc., which can be implemented by the cloud data center **1230** of FIG. **12**, the cloud data center **1345** of FIG. **13**, the cloud or data center **1460** of FIG. **14**, etc., as disclosed below. In some examples, the gateway **202** can receive the data stream from the cloud data center **1230** of FIG. **12**, the cloud data center **1345** of FIG. **13**, the cloud or data center **1460** of FIG. **14**, etc., to be transmitted to the vehicle **226**, the second endpoint device **234**, the third endpoint device **236**, etc.

(112) In the illustrated example of FIG. **2**, the switch **204** can facilitate communication, data transfers, data routing, etc., between different sources and targets within a network, such as communication from a source service, a source appliance, etc., of the private network **208** to a target service, a target appliance, etc., of the private network **208**. For example, the switch **204** can receive a data stream from the gateway **202**, the edge cloud **210**, the process control system **212**, one(s) of the robots **214**, one(s) of the industrial machines **216, 218, 220, 222**, the predictive maintenance system **224** (or sensor(s) thereof), the first monitoring sensor **228**, the second monitoring sensor **230**, the first endpoint device **232**, the second endpoint device **234**, the third endpoint device **236**, etc. In some examples, the switch **204** can transmit or cause transmission of the data stream to a destination within the private network **208**. For example, the switch **204** can transmit or cause transmission of the data stream to at least one of the gateway **202**, the edge cloud **210**, the process control system **212**, one(s) of the robots **214**, one(s) of the industrial machines **216, 218, 220, 222**, the predictive maintenance system **224** (or sensor(s) thereof), the vehicle **226**, the first monitoring sensor **228**, the second monitoring sensor **230**, the first endpoint device **232**, the second endpoint device **234**, or the third endpoint device **236**.

(113) In some examples, the gateway **202** and/or the switch **204** can implement and/or effectuate adaptive data management based on global observability at the edge, which can be implemented by the environment **200** or portion(s) thereof. In some examples, the environment **200** can implement a large number and/or different types of applications, such as machine vision applications implemented by the robots **214**, autonomous driving applications implemented by the vehicle **226**, etc. In some examples, the data generated by the private network **208** is relatively diverse because of the vast range of data sources, such as sensors, controllers, services (e.g., applications, microservices, virtual machines, containers, etc.), and/or user input (e.g., input from a human user or a device user, such as a robot) that can be processed and analyzed to identify anomalies and trends in the data. For example, the gateway **202** and/or the switch **204** can facilitate the transmission and/or routing of data, which can include sensor data or measurements, alerts, steps or operations of a workflow (e.g., a maintenance workflow to repair the robots **214**, an installation workflow to install the robots **214**, etc.), video feeds, still images, predictive maintenance alerts or

control commands, robotic control commands, etc., and/or any combination(s) thereof.

(114) In some examples, the gateway **202** and/or the switch **204** can transfer and/or route data to components of the ADM system **100** of FIG. **1** to execute one(s) of the algorithms **138** to implement adaptive and/or proactive data routing and/or, more generally, ADM as disclosed herein. In some examples, the gateway **202** and/or the switch **204** can execute and/or instantiate the one(s) of the algorithms **138** to implement adaptive and/or proactive data routing, and/or, more generally, ADM as disclosed herein. In some examples, there are a plurality of the gateways **202** and/or a plurality of the switches **204** in the environment **200**. The algorithms **138** of FIG. **1** can be executed and/or instantiated in multiple places of the environment **200** (e.g., by ones of the gateways **202**, the switches **204**, etc., or by any other device(s)). In some examples, the different ones of the edge gateways **202**, the edge switches **204**, etc., may have more or less observability based on the data that they process, ingest, and/or otherwise encounter. Accordingly, two different ones of the devices of FIG. **2** can develop, train (or retrain), and/or generate different one(s) of the algorithms **138** based on the data (and/or metadata) processed by each of the different ones of the devices. For example, a first one of the switches **204** may observe 10% of the environment **200** and a second one of the switches **204** may observe 90% of the environment **200**, which may become the basis for the differences in data outputs generated by the algorithms **138** executed and/or instantiated by the first and second one of the devices. In some examples, the first one of the devices may transmit and/or cause routing of model outputs (e.g., data outputs, AI/ML model outputs, etc.) from its execution and/or instantiation of the algorithms **138** to the second one of the devices. In some examples, the second one of the devices may transmit and/or cause routing of model outputs (e.g., data outputs, AI/ML model outputs, etc.) from its execution and/or instantiation of the algorithms **138** to the first one of the devices for cross-training and/or cross-correlation of the algorithms **138**.

(115) In some examples, data (and/or metadata) generated by the private network **208** may be immense. In some examples, a data source, such as the process control system **212**, one(s) of the robots **214**, one(s) of the industrial machines **216**, **218**, **220**, **222**, the predictive maintenance system **224** (or sensor(s) thereof), the vehicle **226**, the first monitoring sensor **228**, the second monitoring sensor **230**, the first endpoint device **232**, the second endpoint device **234**, and/or the third endpoint device **236**, may have insufficient computing resources (e.g., one or more processors, one or more accelerators, one or more memories, one or more mass storage discs, etc.) to analyze the data (and/or metadata) generated by the data source. In some examples, the data source may be unable to identify redundant data, less important or less significant data, etc., due to insufficient computing resources and therefore may flood the private network **208** with a significant quantity of data at relatively short intervals. Advantageously, the gateway **202**, the switch **204**, and/or, more generally, the ADM system **100** of FIG. **1**, may implement ADM as disclosed herein to process data based on at least one of a content and/or a context of the data to effectuate adaptive and/or proactive data routing to appropriate and/or optimal end users.

(116) FIG. **3** is a block diagram of an example data routing management system **300** including an example data routing manager **302A-I** to implement proactive data routing in a network environment, which can be implemented by an example network environment **304**. In some examples, the network environment **304** can be implemented by one of the computational use cases **1305** of FIG. **13**. For example, the network environment **304** can be implemented by a manufacturing plant, a healthcare facility (e.g., a hospital), a smart building, a smart city, a transportation logistics system, a retail store, etc. The network environment **304** of the illustrated example includes example data producers **306** and example data consumers **308**. In some examples, the data producers **306** can be implemented using one(s) of the data sources **104** of FIG. **1**, one(s) of the data sources **1260** of FIG. **12**, etc. For example, the data producers **306** can be implemented using a sensor, a vehicle, a mobile or handheld electronic device (e.g., a smartphone, a tablet computer, etc.), an IoT device, etc. In some examples, the data consumers **308** can be implemented using one(s) of the central office **1220**, the cloud data center **1230**, the access point or

base station **1240**, the local processing hub **1250**, etc., of FIG. **12**, the nodes **1315**, the local network equipment **1325**, the core network data center **1335**, the cloud data center **1345**, etc., or any other type of electronic device such as a server, an infrastructure processing unit (IPU), etc. (117) The data producers **306** include a first example data routing manager **302A** and the data consumers **308** include a second example data routing manager **302B**. A third example data routing manager **302C**, a fourth example data routing manager **302D**, a fifth example data routing manager **302E**, a sixth example data routing manager **302F**, a seventh example data routing manager **302G**, an eighth example data routing manager **302H**, and a ninth example data routing manager **302I** are also depicted in the illustrated example. The first through ninth data routing managers **302A-I** are collectively referred to as the data routing manager **302A-I**. For example, each of the data routing managers **302A-I** can have the same functionality. In some examples, one(s) of the data routing managers **302A-I** can have first functionality that is the same across the data routing managers **302A-I** and second functionality that is different from other one(s) of the data routing managers **302A-I**.

(118) In example operation, the data producers **306** can generate and/or otherwise produce data for consumption by the data consumers **308**. For example, the data producers **306** can generate data, which can include one or more data objects and/or associated metadata. In some examples, the data producers **306** can generate data (and/or metadata) formatted as an Internet message (e.g., a Hypertext Transfer Protocol (HTTP) message). However, the data producers **306** can generate data based on any other message format and/or protocol such as, for example, file transfer protocol (FTP), simple message transfer protocol (SMTP), HTTP secure (HTTPS), JavaScript Object Notation (JSON), Abstract Syntax Notation One (ASN.1), eXtensible Markup Language (XML), etc., and/or any Information-centric networking protocol/format/scheme, etc.

(119) In example operation, the data routing manager **302A-I** can cause propagation of and/or route data generated by the data producers **306** to example users **310, 312, 314, 316, 318, 320** by way of an example network **322**. In some examples, the data can be unicast to one of the users **310, 312, 314, 316, 318, 320**. In some examples, the data can be multicast to one(s) of the users **310, 312, 314, 316, 318, 320**. For example, if a message is relevant and/or associated with more than one of the users **310, 312, 314, 316, 318, 320**, then the message can be multicast to the multiple users **310, 312, 314, 316, 318, 320**. The network **322** of the illustrated example is the Internet. However, the network **322** may be implemented using any suitable wired and/or wireless network(s) including, for example, one or more data buses, one or more LANs, one or more WLANs, one or more cellular networks, one or more satellite networks, one or more private networks, one or more public networks, one or more terrestrial networks, one or more non-terrestrial networks, one or more beyond-line-of-site (BLOS) networks, one or more line-of-site (LOS) networks, etc. In some examples, one(s) of the users **310, 312, 314, 316, 318, 320** can be associated with a node (e.g., a logical node or entity) of the data routing management system **300**.

(120) The network **322** enables the data routing manager **302A-I** to be in communication with one(s) of the users **310, 312, 314, 316, 318, 320** by way of a respective example electronic device **324, 326, 328, 330, 332, 334**. The users **310, 312, 314, 316, 318, 320** are associated with the network environment **304**. For example, the users **310, 312, 314, 316, 318, 320** can be supervisors and/or technicians in a manufacturing plant or factory, medical personnel (e.g., a doctor, nurse, orderly, administrator, maintenance personnel, etc.) in a healthcare facility, office workers (e.g., engineers and/or project managers in a technology company, accountants and/or lawyers in an accounting or consulting firm, etc.) in an office or commercial building, etc. The users **310, 312, 314, 316, 318, 320** include a first example user **310**, a second example user **312**, a third example user **314**, a fourth example user **316**, a fifth example user **318**, and a sixth example user **320**.

(121) In some examples, one(s) of the users **310, 312, 314, 316, 318, 320** can be human users, such as a human user associated with a computing and/or electronic device. For example, the first user **310** can be a maintenance technician associated with one of the robots **214**. In some examples, the

fourth user **316** can be a magnetic resonance imaging (MRI) technician associated with an Mill machine. In some examples, one(s) of the users **310**, **312**, **314**, **316**, **318**, **320** can be non-human users, such as the robots **214**, the first industrial machine **216**, the second industrial machine **218**, the third industrial machine **220**, the fourth industrial machine **222**, the predictive maintenance system **224**, the vehicle **226**, the first monitoring sensor **228**, the second monitoring sensor **230**, and/or one(s) of the endpoint devices **232**, **234**, **236** of FIG. 2. In some examples, the users can be a combination of a human user and a computing/electronic device. For example, the first user **310** can be the vehicle **226**, which can provide automated or autonomous outputs to control the vehicle **226**, and an associated driver, which can provide manual and/or override outputs to control the vehicle **226**.

(122) The electronic devices **324**, **326**, **328**, **330**, **332**, **334** of the illustrated example of FIG. 3 include a first example electronic device **324**, a second example electronic device **326**, a third example electronic device **328**, a fourth example electronic device **330**, a fifth example electronic device **332**, and a sixth example electronic device **334**. In this example, the first electronic device **324** is a headset electronic device associated with the first user **310**. The second electronic device **326** is a pair of smart glasses (or a headset or headset display, an AR headset, a VR headset, etc.) associated with the second user **312**. The third electronic device **328** is a smartwatch (or other type of wearable device such as a smart band or smart wristband, a fitness tracker, a biometric sensor/tracker/device, etc.) associated with the third user **314**. The fourth electronic device **330** is a tablet computer associated with the fourth user **316**. The fifth electronic device **332** is a handheld mobile device (e.g., a smartphone, a personal digital assistant (PDA), etc.) associated with the fifth user **318**. The sixth electronic device **334** is a laptop computer (or a desktop computer, workstation, computing terminal, etc.) associated with the sixth user **320**. A different quantity and/or different type(s) of electronic device(s) may additionally and/or alternatively be included in the data routing management system **300**.

(123) In the illustrated example, the data routing manager **302A-I** can be executed and/or instantiated by respective ones of the data producers **306**, the data consumers **308**, and the electronic devices **324**, **326**, **328**, **330**, **332**, **334**. For example, the fourth electronic device **330** can execute and/or instantiate the seventh data routing manager **302G** on the fourth electronic device **330**. In some examples, one(s) of the electronic devices **324**, **326**, **328**, **330**, **332**, **334** can execute and/or instantiate portion(s) of the data routing manager **302A-I**. In some examples, the data routing manager **302A-I** can be implemented by hardware alone, and/or by using any combination of hardware, software (e.g., one or more software applications, one or more services, one or more microservices, etc.), and/or firmware. The third data routing manager **302C** can be executed and/or instantiated by a central or centralized node. For example, the third data routing manager **302C** can be executed and/or instantiated by processor circuitry separate from the data producers **306**, the data consumers **308**, and the electronic devices **324**, **326**, **328**, **330**, **332**, **334**.

(124) In example operation, the data producers **306** and/or one(s) of the electronic devices **324**, **326**, **328**, **330**, **332**, **334** can generate data (and/or metadata) associated with the network environment **304**. For example, one(s) of the data producers **306** can generate data (and/or metadata) associated with a completion and/or operation of a vehicle manufacturing stage (e.g., assembling a vehicle door, painting a vehicle body, etc.). In some examples, the one(s) of the data producers **306** can transmit the data to one(s) of the electronic devices **324**, **326**, **328**, **330**, **332**, **334**. For example, the first data routing manager **302A** can transmit and/or route the data to the second electronic device **326** via the network **322** and/or one or more intervening device(s) (e.g., a gateway, a switch, a router, one(s) of the electronic devices **324**, **326**, **328**, **330**, **332**, **334**, etc.). The following description is in connection with the first data routing manager **302A** of the data producers **306** (e.g., one or more of the data producers **306**), but is applicable to any other one(s) of the data routing manager **302A-I**.

(125) In example operation, the first data routing manager **302A** can determine that the data (and/or

metadata) is to be published, routed, and/or propagated to other one(s) of the users **310, 312, 314, 316, 318, 320**. In some examples, the first data routing manager **302A** can generate a list of the users **310, 312, 314, 316, 318, 320** associated with a first node of the data routing management system **300**. In some examples, the first data routing manager **302A** can query one or more second nodes (e.g., neighboring nodes, trusted or authorized nodes, relevant nodes, etc.) for their respective lists of users. In some examples, the first data routing manager **302A** can generate a list (e.g., a primary list) of first user(s) (e.g., one(s) of the users **310, 312, 314, 316, 318, 320** associated with the first node) and/or second user(s) (e.g., users associated with the one or more neighboring nodes).

(126) In example operation, the first data routing manager **302A** can execute and/or instantiate an AI/ML model (e.g., a classification model, a neural network model, etc.) with the data (and/or metadata) as model input(s) to generate model output(s), which can include a relevancy score for respective one(s) of the first user(s) and/or the second user(s). For example, the relevancy score can refer to a representation of a relevancy or strength of association of data, or portion(s) thereof, with a user and/or metadata associated with the user. In some examples, the first data routing manager **302A** can identify one(s) of the first user(s) and/or the second user(s) whose relevancy score satisfies a threshold (e.g., a relevancy score threshold). In some examples, the first data routing manager **302A** can deliver, provide, and/or otherwise cause transmission of a data message including the data (or portion(s) thereof) and/or associated metadata to the one(s) of the first user(s) and/or the second user(s) whose relevancy score satisfies the threshold.

(127) Advantageously, the first data routing manager **302A** can surface the data message, which can implement an alert or urgent notification, to appropriate one(s) of the users **310, 312, 314, 316, 318, 320** to ensure an appropriate action, operation, task, etc., is executed to address and/or mitigate the alert or the urgent notification. Advantageously, the first data routing manager **302A** can continuously learn (e.g., by training/retraining the AI/ML model) which one(s) of the users **310, 312, 314, 316, 318, 320** is/are associated with different types of data (and/or metadata). For example, the first data routing manager **302A** can update (e.g., add, change, remove, modify, etc.) metadata associated with user(s) who respond and/or user(s) who do not respond to the data message to improve future routing of data (and/or metadata) to the appropriate and/or necessary user. In some examples, the first data routing manager **302A** can propagate the metadata to one(s) of the data consumers **308**, one(s) of the electronic devices **324, 326, 328, 330, 332, 334**, etc., and/or any combination(s) thereof, to improve their respective learning associated with future routing of data in the data routing management system **300**. Advantageously, by improving their respective learning associated with future routing of data, reduced latency can be achieved in the data routing management system **300** by routing data to appropriate one(s) of the users **310, 312, 314, 316, 318, 320**, one(s) of the electronic devices **324, 326, 328, 330, 332, 334**, etc., with reduced time compared to previous iterations, instantiations, etc., of the data routing management system **300**.

(128) FIG. 4 is a block diagram of example data routing management circuitry **400**. In some examples, the data routing management circuitry **400** can implement the data routing manager **302A-I** of FIG. 3. In some examples, the data routing management circuitry **400** can implement portion(s) of the ADM system **100** of FIG. 1, such as the data ingestion manager **106**, the data query manager **110**, the data publishing manager **118**, the node manager **122**, the data security manager **132**, the AMR **134**, the analytics manager **136**, the distributed datastore **144**, etc. The data routing management circuitry **400** of FIG. 4 may be instantiated (e.g., creating an instance of, bring into being for any length of time, materialize, implement, etc.) by processor circuitry such as a central processing unit executing instructions. Additionally or alternatively, the data routing management circuitry **400** of FIG. 4 may be instantiated (e.g., creating an instance of, bring into being for any length of time, materialize, implement, etc.) by an ASIC or an FPGA structured to perform operations corresponding to the instructions. It should be understood that some or all of

the data routing management circuitry **400** of FIG. **4** may, thus, be instantiated at the same or different times. Some or all of the data routing management circuitry **400** may be instantiated, for example, in one or more threads executing concurrently on hardware and/or in series on hardware. Moreover, in some examples, some or all of the data routing management circuitry **400** of FIG. **4** may be implemented by microprocessor circuitry executing instructions to implement one or more virtual machines and/or containers.

(129) The data routing management circuitry **400** of the illustrated example includes example data ingestion circuitry **410**, example machine-learning circuitry **420**, example data query management circuitry **430**, example node management circuitry **440**, example data publishing circuitry **450**, an example datastore **460**, and an example bus **480**. The datastore **460** of the illustrated example includes example raw data **462**, example metadata **464**, example users **466**, example nodes **468**, example machine-learning models **470**, an example environment topology **472**, example contextual data graph models **474**, and example digital twins **476**.

(130) In the illustrated example, the data ingestion circuitry **410**, the machine-learning circuitry **420**, the data query management circuitry **430**, the node management circuitry **440**, the data publishing circuitry **450**, and the example datastore **460** are in communication with one(s) of each other by way of the bus **480**. For example, the bus **480** can be implemented using at least one of an I2C bus, a SPI bus, a PCI bus, or a PCIe or PCIE bus. Additionally or alternatively, the bus **480** can be implemented by any other type of computing or electrical bus. In some examples, the bus **480** can implement the data plane **128**, the control plane **130**, and/or, more generally, the network plane **126** of FIG. **1**, or portion(s) thereof.

(131) The data routing management circuitry **400** of the illustrated example includes the data ingestion circuitry **410** to receive data (e.g., one or more messages), determine whether new data is received and/or otherwise ready to be ingested, etc. In some examples, the data ingestion circuitry **410** can implement the data ingestion manager **106** of FIG. **1**, or portion(s) thereof. In some examples, the data ingestion circuitry **410** is instantiated by processor circuitry executing data ingestion instructions and/or configured to perform operations such as those represented by one(s) of the flowcharts of FIGS. **17-40**.

(132) In some examples, the data ingestion circuitry **410** extracts data object(s) from data, message(s), etc., and/or pre-processes the data object(s). In some examples, the data ingestion circuitry **410** obtains metadata associated with an environment, such as the environment **200** of FIG. **2**. For example, the data ingestion circuitry **410** can obtain the metadata **464** from the datastore **460**, or metadata from one or more nodes of the environment **200**.

(133) In some examples, the data ingestion circuitry **410** tracks and/or identifies a routing of data, metadata, etc., in an environment, such as the environment **200**. For example, the data ingestion circuitry **410** can obtain telemetry data associated with data as the data is transmitted from node-to-node in the environment **200**. In some examples, node(s) of the environment **200** can execute a telemetry microservice to transmit telemetry data associated with data the node(s) receive to other node(s) (e.g., neighboring nodes, a central or centralized node, an orchestrator, etc.). For example, at each hop (e.g., node hop) in the routing of data from a first node to a second node via one or more third nodes, the data ingestion circuitry **410** can determine which of the one or more third nodes the data is routed through and/or a timestamp at which the one or more third nodes received the data. In some examples, the data routing is based on the environment topology **472**.

Advantageously, the data ingestion circuitry **410** can determine an actual data routing path of data, a message, etc., in an environment, such as the environment **200**.

(134) In some examples, the data ingestion circuitry **410** can determine whether a message is associated with a user. In some examples, the data ingestion circuitry **410** can determine whether the message indicates that the user initiated an action in response to receiving a different message. In some examples, the data ingestion circuitry **410** can determine whether a user acknowledged that a portion of a data object (e.g., an augmented data object) is relevant to a user. For example, the

second user **312** can receive a message, which includes an augmented and/or otherwise modified data object. In some examples, the second user **312** can generate a message (e.g., by using the second electronic device **326**) that indicates that one or more portions of the augmented data object is relevant to the user **312** and/or one or more portions of the augmented data object are not relevant to the user **312**. In some examples, the data ingestion circuitry **410** can determine whether a received message is indicative of a user affirming a relevancy, an association, etc., of a message that was presented to the user.

(135) In some examples, the data ingestion circuitry **410** can receive and/or otherwise ingest sensor and/or location data. For example, the data ingestion circuitry **410** can receive video data from a video camera, a beacon signal from a radio frequency identification device (RFID) terminal, a use of login credentials (e.g., a username or user identifier, a password, biometric data such as an eye scan or fingerprint, etc.) at an electronic terminal (e.g., a laptop computer, a desktop computer, a control station, etc.), etc. In some examples, the data ingestion circuitry **410** can determine whether a location of a user changed based on the ingested sensor and/or location data. For example, the data ingestion circuitry **410** can receive first sensor data that locates and/or places the first user **310** in a first location at a first time and receive second sensor data that locates the first user **310** in a second location at a second time after the first time.

(136) In some examples, the data ingestion circuitry **410** determines whether an event associated with an environment has occurred. For example, the data ingestion circuitry **410** can obtain and/or ingest data that has been transmitted and/or routed over one or more nodes of one or more networks. In some examples, the data includes metadata. In some examples, the data ingestion circuitry **410** can determine that the metadata includes a first tag associated with one of the robots **214** and a second tag associated with an alert, error code, and/or fault code associated with the one of the robots **214**. For example, the data ingestion circuitry **410** can detect an event, which can be an error, fault, and/or maintenance condition, associated with the one of the robots **214** based on the ingested data. In some examples, the data ingestion circuitry **410** determines whether to continue monitoring an environment, such as the environment **200** of FIG. 2, for events or event generation. In some examples, the data ingestion circuitry **410** determines whether to continue monitoring an environment, such as the environment **200** of FIG. 2, for received data, metadata, messages, etc.

(137) The data routing management circuitry **400** of the illustrated example includes the machine-learning circuitry **420** to execute a machine-learning model (e.g., the machine-learning model **470**) to generate output(s) (e.g., model output(s)), which can include an authorization score, a confidence score, and/or a relevancy score associated with a user. In some examples, the output(s) can include the users **466**, the nodes **468**, etc. In some examples, the output(s) can include a data routing path associated with the environment topology **472**. For example, the output(s) can include a data routing path representative of transmission of data from a first node to a second node either directly (e.g., without intervening node(s)) or indirectly (e.g., via one or more third nodes).

(138) As used herein, the terms “data routing path,” “message routing path,” “metadata routing path,” “message data routing path,” and “network routing path” are used interchangeably and refer to the delivery, transmission, provisioning, and/or propagation of data, messages, metadata, etc., and/or any combination(s) thereof from a source (e.g., a source node, a source computing and/or electronic device, etc.) to a destination (e.g., a destination node, a destination computing and/or electronic device, etc.) either directly (e.g., via direct and/or point-to-point transmission, via zero intervening nodes, via zero intervening computing/electronic devices, etc.) or indirectly (e.g., via a network, via one or more intervening nodes, via one or more intervening computing/electronic devices, etc.). For example, a data routing path from a first node to a second node can be implemented by transmission of data from the first node to one or more third nodes and finally to the second node. In some examples, a data routing path from a first node to a second node can be implemented by transmission of data from the first node to the second node via a direct wired or wireless connection.

(139) In some examples, the machine-learning circuitry **420** can implement the algorithms **138**, and/or, more generally, the analytics manager **136** of FIG. **1**, or portion(s) thereof. In some examples, the machine-learning circuitry **420** executes and/or instantiates a machine-learning microservice to generate machine-learning output(s) based on machine-learning input(s). In some examples, the machine-learning circuitry **420** determines whether a machine-learning microservice is deployed. For example, the machine-learning circuitry **420** can determine that a trained one of the machine-learning models **470** is deployed for use as a microservice. In some examples, the determination can be based on whether the microservice is accessible for use by a node, such as by being stored as one of the algorithms **138** of FIG. **1**. In some examples, the machine-learning circuitry **420** is instantiated by processor circuitry executing machine-learning instructions and/or configured to perform operations such as those represented by one(s) of the flowcharts of FIGS. **17-40**.

(140) In some examples, the machine-learning circuitry **420** executes and/or instantiates a machine-learning microservice to generate the machine-learning model **470** based on data associated with an environment, such as the network environment **304**. In some examples, the machine-learning circuitry **420** executes and/or instantiates a machine-learning microservice to analyze received data, such as data ingested by the data ingestion circuitry **410**. In some examples, the machine-learning circuitry **420** executes and/or instantiates the machine-learning model **470** to generate data graphs (or data graph models) corresponding to respective portions of the environment. In some examples, the machine-learning circuitry **420** executes and/or instantiates the machine-learning model **470** to identify hotspots of at least one of expert nodes or stakeholder nodes.

(141) In some examples, the machine-learning model **470** updates metadata associated with response(s) and/or non-response(s) by user(s) to data traffic (e.g., one or more messages). In some examples, the machine-learning model **470** updates metadata associated with cause(s) of action(s) and effect(s) of the action(s) based on the data traffic. In some examples, the machine-learning model **470** updates at least one of the data graphs (or data graph models) or the hotspots based on a routing of the data traffic. In some examples, the machine-learning model **470** identifies a stratification of nodes and super nodes based on the routing of the data traffic. In some examples, the machine-learning model **470** retrains the machine-learning model **470** based on at least one of the update(s) or other data, which can include activity information, sensor data, etc.

(142) As used herein, the term “authorization score” refers to a value (e.g., a data value) that represents a likelihood or probability that a user has access (e.g., is authorized to access) to specific data. For example, an authorization score for a user can be based on an organization structure to which the user belongs. In some examples, the authorization score can be based on organizational data associated with the user, which can include a name, a job description or role, technical expertise or knowledge, a level of organizational seniority, a level of an organization hierarchy to which the user belongs (e.g., a manager that the user reports to, direct report(s) of the user or those that report to the user, etc.), security credentials, and the like.

(143) As used herein, the term “confidence score” refers to a likelihood or probability that an output from the machine-learning model **470** is accurate, appropriate, and/or otherwise useful. In some examples, the confidence score can refer to a representation of accuracy or a level of error of the machine-learning model **470**. For example, the machine-learning model **470** can generate an output, which can be an identification of the first user **310** as being associated with data, and a corresponding confidence score. In some examples, the machine-learning model **470** can generate a confidence score of 0.8, which can be representative of an 80% likelihood that the data is relevant to the first user **310**.

(144) As used herein, the term “relevancy score” refers to a value that represents a likelihood or probability that data, or portion(s) thereof, is relevant to a user. In some examples, the relevancy score can refer to a representation of a relevancy or strength of association of data, or portion(s) thereof, with a user and/or metadata associated with the user. In some examples, metadata can have

a direct association, such as by being directly associated with a user, a node, a device, an event (e.g., a physical or actual event in a physical or actual environment, a virtual or simulated event in a virtual or simulated environment, event data, etc.), etc., and/or any combination(s) thereof. For example, metadata can have a first-order or primary-order relationship with a user, a node, a device, an event, etc., in which the metadata corresponds to the user, the node, the device, the event, etc. By way of example, metadata can include a first serial number of a first one of the robots **214**. In this example, the metadata can be directly associated with the first one of the robots **214** based on a determination that the first one of the robots **214** has the first serial number.

(145) In some examples, metadata can have an indirect association, such as by being indirectly associated with a user, a node, a device, an event (e.g., a physical or actual event in a physical or actual environment, a virtual or simulated event in a virtual or simulated environment, event data, etc.), etc., and/or any combination(s) thereof. For example, metadata can have a second-order, third-order, etc., or secondary-order relationship with a user, a node, a device, an event, etc., in which the metadata indirectly corresponds to the user, the node, the device, the event, etc. By way of example, metadata can include a first serial number of a first one of the robots **214** and a manufacturer identifier that identifies a manufacturer of the first one of the robots **214**. In this example, the metadata can be indirectly associated with a second one of the robots **214** based on a determination that the first and second one of the robots **214** have different serial numbers and the same manufacturer identifier (e.g., they have the same manufacturer).

(146) In some examples, the machine-learning circuitry **420** can determine whether the authorizations score, the confidence score, and/or the relevancy score satisfies a respective one of a first threshold (e.g., an authorization score threshold), a second threshold (e.g., a confidence score threshold), or a third threshold (e.g., a relevancy score threshold). In some examples, the machine-learning circuitry **420** can update metadata associated with a user, such as the first user **310**, in response to a determination whether the user responded to a message or did not respond to the message. For example, the machine-learning circuitry **420** can determine that the first user **310** may find a message relevant because first metadata associated with the first user **310** can be associated with second metadata associated with the message. In some examples, in response to the first user **310** ignoring and/or otherwise not responding to the message, the machine-learning circuitry **420** can penalize the first metadata by reducing a relevancy score corresponding to the first metadata, removing portion(s) of the first metadata that matched and/or otherwise corresponded to the second metadata, and/or any combination(s) thereof. In some examples, the machine-learning circuitry **420** can penalize the first metadata in response to the first user **310** responding to the message by acknowledging that one or more portions of the message are not relevant to the first user **310**. In some examples, in response to the first user **310** responding to the message by performing an action in connection with the message, acknowledging that the message is relevant to the first user **310**, etc., the machine-learning circuitry **420** can reward the first metadata. For example, the machine-learning circuitry **420** can reward the first metadata by increasing a relevancy score corresponding to the first metadata. In some examples, by increasing the relevancy score of the first metadata, future or subsequent messages that have metadata corresponding to the first metadata may be prioritized to be routed to the first user **310**.

(147) In some examples, the machine-learning circuitry **420** penalizes metadata associated with a non-responsive user based on a level of busyness or lack of availability of the non-responsive user based on activity information (e.g., electronic activity information), sensor data, etc. For example, the fourth user **316** can receive a message associated with an event (e.g., a manufacturing operation has been completed, halted due to a failure or fault, etc.) in the network environment **304** and the fourth user **316** may ignore the message. In some examples, the machine-learning circuitry **420** can analyze sensor data associated with the first user **310**. For example, the machine-learning circuitry **420** can determine, based on video data that includes the fourth user **316**, that the fourth user **316** picked up the fourth electronic device **330** at approximately the time the message is transmitted to

the fourth electronic device **330**, but the fourth user **316** did not acknowledge the message or respond to the message. In some examples, the machine-learning circuitry **420** can penalize the metadata associated with the fourth user **316** because the fourth user **316** appeared to not find the message relevant. By way of another example, the machine-learning circuitry **420** can determine, based on utilization data of the fourth electronic device **330**, that the fourth user **316** ignored the message because the fourth user **316** is executing a time-sensitive task (e.g., a time-sensitive task indicated by increased levels of applications or services in operation, increased levels of computational, storage, or memory resources indicative of heavy utilization, etc.). In some examples, the machine-learning circuitry **420** may not penalize the metadata associated with the fourth user **316** because the fourth user **316** is identified as busy or not available to respond to the message. In some examples, the machine-learning circuitry **420** can determine that the message is to be presented to the fourth user **316** again in response to determining that the fourth user **316** completed the time-sensitive task.

(148) By way of example, if a user dismisses a message, then the machine-learning circuitry **420** can generate an updated relevancy score that penalizes the metadata that matched this user to the message. The machine-learning circuitry **420** can determine how much to penalize by attempting to quantify how busy is this user at that point in time. The machine-learning circuitry **420** can determine a level of busyness using sensors (e.g., a video camera) in the network environment **304**, behavior on all electronic devices that the user can engage with, and, if approved, biometric sensors that are embedded in wearable devices that the user can engage with such as smartwatches, smart glasses, etc. Examples of collected data can include gaze (e.g., using a laptop camera), heart rate from a smartwatch, and emotional status from a video camera in the network environment **304**. In some examples, the machine-learning circuitry **420** can generate and maintain a baseline for each user to determine a deviation from the baseline. For example, the deviation can be interpreted as an increase in busyness of the user, a distraction level of the user, a level of engagement of the user with an electronic device or other type of machinery or equipment in the network environment **304**, etc.

(149) In some examples, the machine-learning circuitry **420** determines to update a relevancy score of a location associated with a user based on sensor data. For example, the machine-learning circuitry **420** can increase a relevancy score of a location for a user in response to determining that the user is at the location. In some examples, the machine-learning circuitry **420** can decrease a relevancy score of a location for a user in response to determining that the user is not at the location or has not been at the location longer than a specified time duration.

(150) In some examples, the machine-learning circuitry **420** determines that data received at a node indicates that an action is required by a user. For example, the machine-learning circuitry **420** can determine that data indicates a message is to be provided to a user based on the context and/or content of the data. In some examples, the machine-learning circuitry **420** can determine that the message is to be an alert that requires immediate attention (e.g., to avert, avoid, and/or mitigate a potential or predicted failure).

(151) In some examples, the machine-learning circuitry **420** determines that data received at a node indicates that feedback is requested from one or more users (e.g., technical or subject matter experts, management personnel, technicians, financial or other administrative personnel, etc.). In some examples, the machine-learning circuitry **420** can update metadata associated with the one or more users based on received feedback.

(152) In some examples, the machine-learning circuitry **420** can determine that a user acknowledged that a first portion of a data object (e.g., an augmented data object) is relevant to a user and a second portion of the data object is not relevant to the user. In some examples, the machine-learning circuitry **420** can modify metadata associated with the user to associate the first portion with the user and disassociate the second portion from the user.

(153) In some examples, the machine-learning circuitry **420** can determine to increase a relevancy

score of a topic associated with a user in response to the user responding to a message having the topic. In some examples, the machine-learning circuitry **420** can determine to decrease a relevancy score of a topic associated with a user in response to the user ignoring a message having the topic. In some examples, the machine-learning circuitry **420** can determine whether a relevancy score of a topic associated with a user satisfies a threshold. For example, in response to determining that the topic relevancy score is greater than the threshold, the user may be identified as an expert, a stakeholder, etc., in connection with the topic.

(154) In some examples, the machine-learning circuitry **420** can execute the machine-learning models **470** to output a first data routing path in an environment, such as the environment **200** and/or the network environment **304**, based on first metadata associated with an event in the environment. For example, the machine-learning circuitry **420** can execute and/or instantiate the machine-learning models **470** as microservice(s) to generate output(s), which can be representative of, indicative of, and/or correspond to a data routing path of a data message from the first data routing manager **302A** to the fifth data routing manager **302E** via one or more nodes, such as gateways, switches, other data routing managers, etc., and/or any combination(s) thereof. In some examples, the machine-learning circuitry **420** can execute and/or instantiate the machine-learning models **470** to detect a pattern of data routing paths associated with event(s) and/or associated metadata. For example, output(s) from the machine-learning models **470** can be representative of a detection of a pattern of a recurring or similarly recurring data routing path in response to an event associated with particular metadata. In some examples, the machine-learning circuitry **420** can train (or retrain) the machine-learning models **470** based on the detection of the pattern to strengthen, reinforce, and/or emphasize the generation of the data routing path in response to an event associated with the particular metadata (or partial metadata). In some examples, the machine-learning circuitry **420** can deploy the trained (or retrained) machine-learning models **470** as microservices to be executed and/or instantiated by node(s) in an environment.

(155) In some examples, the machine-learning models **470** can output a data routing path as a predicted data routing path. For example, one(s) of the machine-learning models **470** can be digital twin(s) of an environment including the users **466**, the nodes **468**, etc. Digital twin is an emerging technology and is a key enabler for a range of advanced applications. Examples disclosed herein utilize digital twin to enable a range of data routing efficiency related applications. As such, digital twin technology can be deployed in Multi-access Edge Computing (MEC) systems alongside the next generation wireless networks to effectuate adaptive and/or proactive data routing.

(156) In some examples, the machine-learning models **470** can be executed and/or instantiated to create a digital twin of an environment. The digital twin of an environment can be a virtual environment of a physical scenario in which the physical entities in the real scenario (e.g., vehicles, pedestrians, buildings, road infrastructure, etc.) are represented as digital actors (e.g., models) in the virtual environment. The machine-learning circuitry **420** can obtain actual and/or live information of the semantic and kinematic parameters of the physical entities in the environment. The semantic parameters provide information about the type of an entity such as person, car, bicyclist, building, road, AGV, industrial machine, etc., while the kinematic parameters provide information about the mobility of an entity that include position, velocity, heading direction, etc. The machine-learning circuitry **420** can obtain data and/or metadata that propagate through a network to obtain information about connected devices, users, etc.

(157) The machine-learning circuitry **420** can synchronize (e.g., continuously synchronize) the digital models (actors) in a virtual environment with their respective physical entities through the live information obtained from data sources. Then, the machine-learning circuitry **420** can perform analytics and simulations (and/or emulations) using the digital models to generate future predictions (e.g., in real-time) of the parameters of interest such as future positions of actors, optimal and/or improved data routing, predicted user responses or feedback to messages, etc. For example, the machine-learning circuitry **420** can execute and/or instantiate one(s) of the machine-

learning models **470** to effectuate simulation(s) and/or emulation(s) of how data may be routed in a network environment in response to action(s), feedback, etc., from user(s), node(s), etc., as the user(s), the node(s), etc., interact and/or is/are presented with the data. The scope of the simulations, the emulations, etc., covers the parameters of interest like locations and velocities of users, predicted user activity, etc. The simulations, the emulations, etc., in the machine-learning circuitry **420** can be based on deterministic and/or AI based algorithms to generate the future predictions, such as by execution and/or instantiation of the machine-learning models **470**. The live measured parameters, such as user or device locations, actual data routing paths, user provided feedback to messages, etc., received by the machine-learning circuitry **420** can be used as ground truth data to continuously train (or retrain) the machine-learning models **470** and improve the prediction accuracies.

(158) Based on the insights obtained from future predictions, the machine-learning circuitry **420** can implement a digital twin (e.g., by executing and/or instantiating the machine-learning models **470**) to generate and/or output recommendation data routing paths that can be used to improve and/or optimize the routing of data in an environment. The recommended data routing paths generated by the machine-learning circuitry **420** can include identifications of network hops, relevant nodes to which data is to be routed, communications and compute resource allocations of nodes, etc. The machine-learning circuitry **420** can send and/or output the recommended data routing paths to the data publishing circuitry **450** to cause transmission of data from a first node to a second node.

(159) In some examples, the machine-learning circuitry **420** retrains the machine-learning models **470** to output a third data routing path based on the second data routing path. For example, after a detection of a change of a first data routing path (e.g., a predicted data routing path output from the machine-learning models **470**) to a second data routing path (e.g., an actual data routing path taken by a message from a first node to a second node), the machine-learning circuitry **420** can provide the second data routing path (and/or associated metadata) to the machine-learning models **470** as feedback to improve future predictions of data routing paths by the machine-learning models **470**.

(160) In some examples, the machine-learning circuitry **420** can generate digital twin representations of nodes in an environment. For example, the machine-learning circuitry **420** can generate a digital twin representation (e.g., a model) for respective ones of the process control system **212**, the robots **214**, the first industrial machine **216**, the second industrial machine **218**, the third industrial machine **220**, the fourth industrial machine **222**, the predictive maintenance system **224**, the vehicle **226**, the first monitoring sensor **228**, the second monitoring sensor **230**, the endpoint devices **232**, **234**, **236**, etc., and/or any combination(s) thereof, of FIG. 2. In some examples, the machine-learning circuitry **420** can generate a digital twin representation (e.g., a model) for respective ones of the users **310**, **312**, **314**, **316**, **318**, **320** of FIG. 3. In some examples, the machine-learning circuitry **420** can generate a digital twin representation (e.g., a model) for respective ones of the data routing managers **302A-I** of FIG. 3. In some examples, the machine-learning circuitry **420** can generate a digital twin representation (e.g., a model) for respective ones of the devices **324**, **326**, **328**, **330**, **332**, **334** of FIG. 3.

(161) In some examples, the machine-learning circuitry **420** generates a machine-learning model, such as one(s) of the machine-learning models **470**, to utilize digital twin representations of node(s) in an environment as machine-learning input(s). For example, after a determination that an event associated with an environment has occurred, the machine-learning circuitry **420** can execute and/or instantiate the one(s) of the machine-learning models **470** to utilize digital twin representations of node(s) in the environment. For example, the event can have associated metadata, and the machine-learning circuitry **420** can provide the metadata to the one(s) of the machine-learning models **470** as machine-learning input(s) to generate machine-learning output(s), which can be representative of data routing path(s) for message(s) associated with the event. In some examples, the data routing path(s) can be predicted or estimated data routing path(s) that the

message(s) should take, but may be changed in transit due to user feedback or action.

(162) The data routing management circuitry **400** of the illustrated example includes the data query management circuitry **430** to generate a message with metadata based on data received at a first node. For example, in response to an ingestion of data, the data query management circuitry **430** can determine to generate a message based on the data. In some examples, the data query management circuitry **430** can generate the message by embedding and/or otherwise including the metadata **464** in the message. In some examples, the data query management circuitry **430** can implement the data query handler **112**, the data cache cluster manager **114**, the metadata cluster manager **116**, and/or, more generally, the data query manager **110** of FIG. 1, or portion(s) thereof. In some examples, the data query management circuitry **430** is instantiated by processor circuitry executing data query management instructions and/or configured to perform operations such as those represented by one(s) of the flowcharts of FIGS. 17-40.

(163) In some examples, the data query management circuitry **430** generates the message to solicit feedback from a user. In some examples, the data query management circuitry **430** generates the message to solicit an action from a user. In some examples, the data query management circuitry **430** determines whether another message is to be generated.

(164) In some examples, the data query management circuitry **430** requests data to process, such as sensor data from a data producer, activity information associated with one(s) of the electronic devices **324**, **326**, **328**, **330**, **332**, **334**, etc. For example, the data query management circuitry **430** can request and/or otherwise retrieve the raw data **462**, or portion(s) thereof, to process.

(165) In some examples, the data query management circuitry **430** applies local node customization data to a data object to generate an augmented data object. For example, the local node customization data can be based on the metadata **464** associated with a user. In some examples, the local node customization data can include a technique of data presentation (e.g., a text-based message, a graphic based message, an auditory or verbal message via a speaker, etc.), an amount of data to convey (e.g., present a portion of data rather than an entirety of the data), a time at which to present data to a user and/or interrupt the user, etc., and/or any combination(s) thereof.

(166) In some examples, the data query management circuitry **430** determines whether to age ingested data. For example, the data query management circuitry **430** can determine whether there is a difference between first data to be included in a message and second data stored in the raw data **462**. In some examples, the data query management circuitry **430** can determine to age the second data in response to determining that the difference does not satisfy a threshold because the first data and the second data are the same or substantially similar. For example, the data query management circuitry **430** can age the second data by deleting or removing the second data from the raw data **462**, moving the second data to a lower level of storage (e.g., from cache storage to mass storage), reducing a level of redundancy of the second data (e.g., remove the second data from one or more storage discs or devices), etc., and/or any combination(s) thereof.

(167) In some examples, the data query management circuitry **430** obtains metadata associated with a data routing path taken or used by a message associated with an event. For example, the data query management circuitry **430** can obtain telemetry data, which can include metadata, associated with transmission of a message from node-to-node, network hop-to-network hop, etc., from a node, a network hop, etc., that received the message. In some examples, the data query management circuitry **430** can provide the telemetry data and/or the metadata to a machine-learning microservice as input(s) to generate output(s), which can include a classification of the data routing path taken by the message, a pattern detection associated with the data routing path, etc.

(168) In some examples, the data query management circuitry **430** determines that a first device is to execute a task with second device(s) based on received and/or ingested data. For example, the data query management circuitry **430** can determine that ingested data has associated metadata (e.g., a robot identifier, a manufacturer identifier of a manufacturer that manufactures robots, an identifier of a step of a workflow, etc.) that identifies an operation, a task, etc., to be completed by

one or more robots, such as the robots **214** of FIG. 2. In some examples, the data query management circuitry **430** can cause propagation of and/or cause transmission of the ingested data and/or the associated metadata to a first one of the robots **214**.

(169) In some examples, the data query management circuitry **430** can identify the first one of the robots **214** based on the contextual data graph models **474** to which the ingested data and/or associated metadata is to be routed. In some examples, the node management circuitry **440** can select one(s) of the robots **214**, such as the first one of the robots **214**, to execute the operation, the task, etc. For example, after receiving the ingested data and/or associated metadata, the node management circuitry **440** can determine whether the first one of the robots **214**, or a neighboring or proximate robot to the first one of the robots **214**, is the appropriate selection to carry out the operation, the task, etc. In some examples, the node management circuitry **440** can make the determination based on which one(s) of the robots **214** are in an environment based on the environment topology **472** and/or which one(s) of the robots **214** is/are relevant to the operation, the task, etc., based on the contextual data graph models **474**. In some examples, the node management circuitry **440** can make the determination based on whether one(s) of the robots **214** have historical metadata associated with the operation, the task, etc. For example, the node management circuitry **440** can determine that the first one of the robots **214** has a history or previous experience of completing operation(s)/task(s) that is/are either the same or substantially similar to the instant operation/task. In some examples, the node management circuitry **440** can determine that the first one of the robots **214** has the requisite history based on the metadata **464** associated with the first one of the robots **214**. For example, the metadata **464** can include tags, data entries, etc., which can be indicative of identifiers corresponding to the operation(s)/task(s), timestamps at which the operation(s)/task(s) was/were completed, etc.

(170) In some examples, the data query management circuitry **430** can receive a request from the first one of the robots **214** for metadata associated with the operation, the task, etc., from a machine-learning microservice to improve execution of the operation, the task, etc. For example, the machine-learning circuitry **420** can execute and/or instantiate the contextual data graph models **474** to generate output(s), which can include identification(s) of relevant data, metadata, etc., associated with the operation, the task, etc. For example, the relevant data, metadata, etc., can include a step-by-step or process-by-process workflow to complete the operation, the task, etc. In some examples, the step-by-step workflow can be implemented by machine-readable instructions (e.g., software and/or firmware, an application, a service, a microservice, a robot configuration, etc.), a maintenance manual, a user guide, or other technical documentation on how to complete the operation, the task, etc. In some examples, the step-by-step workflow can be representative of data that can be ingested by the requesting one of the robots **214** to complete the operation, the task, etc. In some examples, after the identification(s), the data query management circuitry **430** can return the identified relevant data, metadata, etc., to the requesting one of the robots **214**. Advantageously, the requesting one of the robots **214** can execute the operation, the task, etc., with improved efficiency and/or accuracy by utilizing the relevant data, metadata, etc. Advantageously, the data query management circuitry **430** can provide feedback to the machine-learning microservice to improve selection of device(s) in connection with completing subsequent operation(s), task(s), etc. For example, the feedback can include a determination of whether the operation, the task, etc., is completed, an accuracy of the operation/task output, a time-to-completion of the operation/task, an identification of one(s) of the robots **214** that completed the operation/task, etc., and/or any combination(s) thereof.

(171) The data routing management circuitry **400** of the illustrated example includes the node management circuitry **440** to generate a list of users of which to provide a message based on relevancy of the data to one(s) of the list. In some examples, the node management circuitry **440** can implement the node manager **122** of FIG. 1, or portion(s) thereof. In some examples, the node management circuitry **440** is instantiated by processor circuitry executing node management

instructions and/or configured to perform operations such as those represented by one(s) of the flowcharts of FIGS. 17-40.

(172) In some examples, the node management circuitry **440** can generate the list of users based on user(s) associated with a first node or one or more second nodes. For example, the node management circuitry **440** can compile a list of users based on first user(s) associated with a first one of the data producers **306** (and/or a first one of the data consumers **308**) and second user(s) associated with a second one of the data producers **306** (and/or a second one of the data consumers **308**). In some examples, the node management circuitry **440** ranks the list based on a relevancy score of respective ones of the list. In some examples, the node management circuitry **440** identifies a set of users of the list as having a relevancy score that satisfies a threshold. For example, the node management circuitry **440** can select a user in the list to process. The node management circuitry **440** can determine whether a relevancy score associated with the user for a particular data item is greater than a threshold. In response to determining that the relevancy score is greater than the threshold (and thereby satisfies the threshold in this example), the node management circuitry **440** can identify the user as likely finding the specific data item relevant to the user. In some examples, the node management circuitry **440** identifies a user as an expert associated with a topic in response to determining that a relevancy score for the user in connection with the topic satisfies a threshold (e.g., a relevancy score threshold, a topic relevancy score threshold, etc.).

(173) In some examples, the node management circuitry **440** identifies a node at which to route a message associated with received and/or ingested data. For example, the node management circuitry **440** can identify the fourth data routing manager **302D**, and/or, more generally, the first electronic device **324**, and/or, more generally, the first user **310** of FIG. 3, as a node at which to route a data message from one of the data producers **306**.

(174) In some examples, the node management circuitry **440** can determine whether a user associated with a node is able to hear audio and view video (and/or image(s)) and text. For example, the node management circuitry **440** can obtain utilization data associated with the first electronic device **324** and determine, based the utilization data, that the first user **310** is wearing a headset audio device and is unable to view a video and/or text-based message (e.g., unable to view video data, unable to view text data, etc.). In some examples, the node management circuitry **440** can determine to generate an audio message and cause presentation of the audio message to the first user **310** via a speaker of the first electronic device **324**.

(175) In some examples, the node management circuitry **440** can determine whether a user associated with a node is able to hear audio and view video (and/or image(s)) and text. For example, the node management circuitry **440** can obtain utilization data associated with the second device **326** and determine, based on the utilization data, that the second user **312** is wearing a pair of smart glasses and is able to view a video, audio, and/or text-based message. In some examples, the node management circuitry **440** can determine to generate data message(s) including video, audio, and/or text data (or data objects) and cause presentation of the video, audio, and/or text data to the second user **312** via at least one of a display device or a speaker of the second device **326**.

(176) In some example, the node management circuitry **440** can obtain utilization data associated with the first electronic device **324** and determine, based the utilization data, that the first user **310** is wearing a headset audio device and is unable to view a video and/or text-based message. In some examples, the node management circuitry **440** can determine to generate an audio message and cause presentation of the audio message to the first user **310** via a speaker of the first electronic device **324**.

(177) In some example, the node management circuitry **440** can obtain utilization data associated with the fourth device **330** and determine, based the utilization data, that the fourth user **316** is unable to hear audio via a speaker (e.g., the fourth user **316** has accessibility settings enabled on the fourth device **330** indicating that the fourth user **316** is hearing impaired, the fourth user **316** is

located in an area with high-decibel sound (e.g., a manufacturing plant, an airport, an electricity plant, etc.). In some examples, the node management circuitry **440** can cause the data publishing circuitry **450** to generate a video and/or text-based message and cause presentation of the video and/or text-based message to the fourth user **316** via a display device of the fourth device **330**. In some examples, the node management circuitry **440** can cause the data publishing circuitry **450** to include metadata in the video and/or text-based message that, when read or evaluated by the fourth device **330**, can cause the fourth device **330** to vibrate and/or otherwise physically alert the fourth user **316** regarding the video and/or text-based message.

(178) In some example, the node management circuitry **440** can obtain utilization data associated with the fourth device **330** and determine, based the utilization data, that the fourth user **316** is not attentive to the fourth device **330**. For example, the utilization data can include and/or be associated with biometric data generated from an eye-tracking sensor of the fourth device **330**. In some examples, the biometric data can be representative of the fourth user **316** not looking at a display of the fourth device **330**. In some examples, the node management circuitry **440** can cause the data publishing circuitry **450** to generate an audio message and cause presentation of the audio message to the fourth user **316** via a speaker device of the fourth device **330**, which can audibly alert the fourth user **316** that an event requires attention from the fourth user **316**.

(179) In some examples, the node management circuitry **440** can determine a bandwidth associated with a device based on utilization data associated with the device. In some examples, the node management circuitry **440** can cause the data publishing circuitry **450** to change a format, delivery, and/or presentation of a message to a user based on the bandwidth. For example, after a determination that the fourth device **330** has relatively low bandwidth (e.g., the fourth device **330** has a poor or reduced speed network connection, the fourth device **330** is utilizing a substantial portion of its network interface resources, etc.), the node management circuitry **440** can cause the data publishing circuitry **450** to output a message, or portion(s) thereof, in reduced data formats, such as audio data, image data, and/or text data. In some examples, after a determination that the fourth device **330** has relatively high bandwidth (e.g., the fourth device **330** has a strong or high speed network connection, the fourth device **330** is utilizing a relatively low portion of its network interface resources, etc.), the node management circuitry **440** can cause the data publishing circuitry **450** to output a message, or portion(s) thereof, in data formats that have higher data usage requirements, such as video data or high-quality audio data.

(180) In some examples, the node management circuitry **440** can determine whether a user associated with a node is ready and/or available to access a message, or portion(s) thereof. For example, the node management circuitry **440** can determine that the fourth user **316** is attentive to the fourth device **330** based on biometric data generated by the fourth device **330**. In some examples, the node management circuitry **440** can determine that the fourth user **316** is ready to consume and/or be presented with a second portion of a message after consuming and/or being presented with a first portion of the message. For example, the message can include three audible operations of a maintenance workflow to repair and/or perform maintenance on a first one of the robots **214**. In some examples, each of the audible operations can be associated with metadata that is representative of expected time durations for the respective audible operations to be completed. In some examples, the fourth device **330** can audibly present the first audible operation via a speaker of the fourth device **330**. In some examples, after a first time duration (as indicated by metadata associated with the first audible operation) has elapsed, the node management circuitry **440** can determine that the fourth user **316** is ready to be presented with the second audible operation via the speaker. In some examples, the node management circuitry **440** can determine that the fourth user **316** is ready to be presented with the second audible operation in response to an audible command or instruction from the fourth user **316**. For example, the audible command/instruction can be the fourth user **316** speaking “first operation complete,” “start second operation,” “present next operation,” etc. In some examples, the fourth device **330** can execute a

natural language processing (NLP) model, such as one of the machine-learning models **470**, to translate the audible command/instruction into a machine-executable operation, such as to present the second audible operation to the fourth user **316** via the speaker of the fourth device **330**.

(181) In some examples, the node management circuitry **440** can determine whether a node is equipped with different network interfaces (e.g., a Bluetooth interface, a Wi-Fi interface, a cellular network interface, etc.). For example, the node management circuitry **440** can obtain configuration data associated with a device, and determine, based on the configuration data, that the device includes one or more types of network interfaces, network interface circuitry, etc. For example, the configuration data can include an inventory or listing of hardware (e.g., a Wi-Fi network interface card, a Bluetooth network interface card, a cellular radio unit, etc.), software (e.g., software drivers), and/or firmware (e.g., Basic Input/Output System (BIOS), Wi-Fi network interface firmware, Bluetooth firmware, cellular network firmware, etc.) of a device.

(182) The data routing management circuitry **400** of the illustrated example includes the data publishing circuitry **450** to publish a message for presentation to a user. In some examples, the data publishing circuitry **450** can publish the message to one or more data subscribers, consumers, etc. In some examples, the data publishing circuitry **450** can implement the scheduler **120**, and/or, more generally, the data publishing manager **118** of FIG. 1, or portion(s) thereof. In some examples, the data publishing circuitry **450** is instantiated by processor circuitry executing data publishing instructions and/or configured to perform operations such as those represented by one(s) of the flowcharts of FIGS. 17-40.

(183) In some examples, the data publishing circuitry **450** queries neighboring nodes to a local node for user(s) associated with metadata. For example, a neighboring node can inform the data ingestion circuitry **410** that the first user **310** is associated with the metadata. In some examples, the data publishing circuitry **450** can deliver the message to the first user **310** via the network **322**. In some examples, the data publishing circuitry **450** can publish a message that references or points to portion(s) of the raw data **462** to the network **322**. In some examples, the message, when received by the fourth data routing manager **302D**, can cause the fourth data routing manager **302D** to determine that the raw data **462** is relevant to the first user **310**. In response to the determination, the fourth data routing manager **302D** can retrieve (or request to retrieve) the referenced portion(s) of the raw data **462** for presentation to the first user **310**.

(184) In some examples, the data publishing circuitry **450** delivers a message, which includes portion(s) of the metadata **464**, to a set of users. In some examples, the data publishing circuitry **450** delivers the message, which can include an augmented data object, to a user to cause a presentation of the augmented data object to the user. In some examples, the data publishing circuitry **450** provides updated portion(s) of the metadata **464** to one or more neighboring or associated nodes.

(185) In some examples, the data publishing circuitry **450** causes transmission of message(s) to node(s) based on a data routing path. For example, the data publishing circuitry **450** can transmit a message from a first node, such as the predictive maintenance system **224** of FIG. 2, to a second node, such as one of the endpoint devices **232**, **234**, **236** of FIG. 2, based on a data routing path, which can include one or more nodes of the environment **200** of FIG. 2. For example, the one or more nodes can include one(s) of the endpoint devices **232**, **234**, **236** to implement peer-to-peer transmission of the message. In some examples, the one or more nodes can include the gateway **202**, the switch **204**, the edge cloud **210**, etc., and/or any combination(s) thereof.

(186) In some examples, the data publishing circuitry **450** generates a message based on at least one of audio, image, text, or video data. For example, the data publishing circuitry **450** can generate a video-based message (e.g., a video file, streaming video data, an HTTP message including a hyperlink to access a video file, etc.) and cause presentation of the video-based message to one(s) of the users **310**, **312**, **314**, **316**, **318**, **320** via display device(s) of corresponding devices. In some examples, the data publishing circuitry **450** can cause presentation of the video-

based message by transmitting the video-based message to one(s) of the corresponding devices associated with the users **310, 312, 314, 316, 318, 320**. In some examples, the data publishing circuitry **450** can cause presentation of the video-based message by accessing the video-based message. For example, the data publishing circuitry **450** can be executed and/or instantiated by the second device **326** to access the video-based message and display the video-based message on one or both display lenses of the second device **326**.

(187) In some examples, the data publishing circuitry **450** can generate an image and/or text-based message and cause presentation of the image and/or text-based message to one(s) of the users **310, 312, 314, 316, 318, 320** via display device(s) of corresponding devices. In some examples, the data publishing circuitry **450** can generate an audio-based message and cause presentation of the audio-based message to one(s) of the users **310, 312, 314, 316, 318, 320** via speaker(s) of corresponding devices. In some examples, the data publishing circuitry **450** generates an alert in response to a determination that a user is unable to be presented with a message.

(188) In some examples, the data publishing circuitry **450** can transmit a message over one or more network interfaces. For example, the data publishing circuitry **450** can cleave, divide, split, and/or otherwise separate a message into multiple message portions, slices, segments, etc. In some examples, the data publishing circuitry **450** can transmit one or more message portions via a first network interface, such as Bluetooth, one or more message portions via a second network interface, such as Wi-Fi, one or more message portions via a third network interface, such as a cellular radio, and so forth.

(189) In some examples, the data publishing circuitry **450** can unicast message portions to a node via one or more network interfaces. For example, the data publishing circuitry **450** can unicast a first message portion of a message to the second electronic device **326** via a first network interface and a second message portion of the message to the second electronic device via a second network interface.

(190) In some examples, the data publishing circuitry **450** can multicast messages to multiple nodes via one or more network interfaces. For example, the data publishing circuitry **450** can multicast a first message to multiple ones of the electronic devices **324, 326, 328, 330, 332, 334** of FIG. 3. In some examples, the data publishing circuitry **450** can multicast the first message via the same network interface. For example, the data publishing circuitry **450** can multicast the first message to ones of the electronic devices **324, 326, 328, 330, 332, 334** of FIG. 3 via Wi-Fi, or a different network interface, communication medium, connection technology, etc. In some examples, the data publishing circuitry **450** can multicast the first message via different network interfaces. For example, the data publishing circuitry **450** can multicast the first message to first ones of the electronic devices **324, 326, 328, 330, 332, 334** of FIG. 3 via Wi-Fi and second ones of the electronic devices **324, 326, 328, 330, 332, 334** of FIG. 3 via 5G cellular, or a different network interface, communication medium, connection technology, etc. Advantageously, the data publishing circuitry **450** can multicast messages to ones of the electronic devices **324, 326, 328, 330, 332, 334** based on what type(s) of network interface(s), communication medium(s), connection technologies, etc., that the ones of the electronic devices **324, 326, 328, 330, 332, 334** are adapted to, configured to, and/or otherwise capable of using to receive and/or transmit data.

(191) In some examples, the data publishing circuitry **450** can multicast data portions, message portions, etc., to multiple nodes via one or more network interfaces. For example, the data publishing circuitry **450** can multicast a first message portion (e.g., video data) of a first message to multiple ones of the electronic devices **324, 326, 328, 330, 332, 334** of FIG. 3. In some examples, the data publishing circuitry **450** can multicast the first message portion via the same network interface. For example, the data publishing circuitry **450** can multicast the first message portion to ones of the electronic devices **324, 326, 328, 330, 332, 334** of FIG. 3 via Wi-Fi, or a different network interface, communication medium, connection technology, etc. In some examples, the data publishing circuitry **450** can multicast a second message portion (e.g., audio data, image data, text

data, etc.) of the message via the same network interface (e.g., Wi-Fi) or a different network interface, communication medium, connection technology, etc.

(192) In some examples, the data publishing circuitry **450** can multicast data portions, message portions, etc., via different network interfaces. For example, the data publishing circuitry **450** can multicast a first message portion of a first message to first ones of the electronic devices **324, 326, 328, 330, 332, 334** of FIG. 3 via Wi-Fi and second ones of the electronic devices **324, 326, 328, 330, 332, 334** of FIG. 3 via 5G cellular, or a different network interface, communication medium, connection technology, etc. Advantageously, the data publishing circuitry **450** can multicast message portion(s) to ones of the electronic devices **324, 326, 328, 330, 332, 334** based on what type(s) of network interface(s), communication medium(s), connection technologies, etc., that the ones of the electronic devices **324, 326, 328, 330, 332, 334** are adapted to, configured to, and/or otherwise capable of using to receive and/or transmit data.

(193) In some examples, the data publishing circuitry **450** can multicast data portions, message portions, etc., via different network interfaces during the same communication session. For example, the data publishing circuitry **450** can multicast a first message portion of a first message to first ones of the electronic devices **324, 326, 328, 330, 332, 334** of FIG. 3 via Wi-Fi and second ones of the electronic devices **324, 326, 328, 330, 332, 334** of FIG. 3 via 5G cellular, or a different network interface, communication medium, connection technology, etc. In some examples, the data publishing circuitry **450** can multicast a second message portion of the first message to the first ones of the electronic devices **324, 326, 328, 330, 332, 334** of FIG. 3 via Bluetooth and second ones of the electronic devices **324, 326, 328, 330, 332, 334** of FIG. 3 via Wi-Fi, or a different network interface, communication medium, connection technology, etc. Advantageously, the data publishing circuitry **450** can multicast and/or otherwise cause transmission of data to node(s) based on a bandwidth associated with the node(s), identification(s) of what network interface(s)/communication medium(s)/connection technologies/etc., the node(s) is/are equipped with, utilization data associated with the network interface(s)/communication medium(s)/connection technologies/etc., etc., and/or any combination(s) thereof.

(194) In some examples, the data publishing circuitry **450** can output the message portions, and/or, more generally, the message, to a user based on a bandwidth of a device associated with the user. For example, the data publishing circuitry **450** can transmit data to the first electronic device **324** via Wi-Fi after a determination that the first electronic device **324** has available Wi-Fi bandwidth. In some examples, the data publishing circuitry **450** can transmit data to the first electronic device **324** via a cellular connection after a determination that the first electronic device **324** has relatively low or no available Wi-Fi bandwidth. In some examples, the data ingestion circuitry **410** can reassemble and/or recompile the message portions at a receiving node. In some examples, the data publishing circuitry **450** can cause an action to occur and/or otherwise be carried out based on the reassembled message. For example, the data publishing circuitry **450** can cause the first user **310** to execute a maintenance operation associated with a first one of the robots **214** in response to receiving a message indicative of a maintenance alert in connection with the first one of the robots **214**.

(195) In some examples, the data publishing circuitry **450** propagates ingested and/or received data to a first node, a first device, etc. In some examples, the data publishing circuitry **450** can determine that the first node is associated with a second node based on one of the contextual data graph models **474**. In some examples, the data publishing circuitry **450** can determine to route the ingested and/or received data from the first node to the second node, which can cause the second node to execute an operation, a task, etc., associated with metadata of the ingested and/or received data.

(196) The data routing management circuitry **400** of the illustrated example includes the datastore **460** to record data, such as the raw data **462**, the metadata **464**, the users **466**, the nodes **468**, the machine-learning models **470**, the environment topology **472**, the contextual data graph models

474, and the digital twins **476**. In some examples, the datastore **460** can implement the metadata datastore **146**, the raw datastore **148**, and/or, more generally, the distributed datastore **144** of FIG. **1**, or portion(s) thereof.

(197) In some examples, the raw data **462** is raw and/or otherwise unprocessed data. In some examples, the raw data **462** can be sensor data, location data, activity information, electronic device utilization data, etc.

(198) In some examples, the metadata **464** is data that provides information about one or more aspects of other data. For example, the metadata **464** can include descriptive information associated with the raw data **462**, the users **466**, the nodes **468**, etc., and/or any combination(s) thereof.

(199) In some examples, the users **466** are implemented using data that describes, represents, and/or otherwise corresponds to the users **310**, **312**, **314**, **316**, **318**, **320** of FIG. **3**. For example, the users **466** can be implemented with user data, such as user data corresponding to the first user **310**, which can include a name, a job description or role, technical expertise or knowledge, a level of organizational seniority, a level of an organization hierarchy to which the user belongs (e.g., a manager that the user reports to, direct report(s) of the user or those that report to the user, etc.), security credentials, and the like. In some examples, the users **466** are human users, such as one(s) of the users **310**, **312**, **314**, **316**, **318**, **320**. In some examples, the users **466** are not human or biological. For example, the users **466** can be electronic and/or computing devices, such as one(s) of the industrial machines **218**, **220**, **222**, the predictive maintenance system **224**, the vehicle **226**, etc., of FIG. **2**. In some examples, the users **466** can be electronic and/or computing devices, such as one(s) of the devices **324**, **326**, **328**, **330**, **332**, **334** of FIG. **3**.

(200) In some examples, the nodes **468** are implemented using data that describes, represents, and/or otherwise corresponds to nodes of the network environment **304**. For example, the nodes **468** can be implemented using node data, which can include identification(s) of user(s) of the node, identification(s) of electronic device(s) of the node, electronic device information (e.g., an Internet Protocol (IP) address, a Media Access Control (MAC) number, quantity and/or type of hardware resource of the electronic device, a version of firmware and/or software of the electronic device, etc.), etc., and/or any combination(s) thereof.

(201) In some examples, the machine-learning models **470** are and/or include neural network(s). In some examples, the machine-learning models **470** are and/or include NLP model(s). Additionally and/or alternatively, the machine-learning models **470** may be implemented using any other type of AWL model described herein. In some examples, the machine-learning models **470** can be implemented using more than one type and/or quantity of AI/ML models. For example, the machine-learning models **470** can include a neural network (or portion(s), layer(s), or slice(s) thereof) and a reinforcement learning network (or portion(s), layer(s), or slice(s) thereof). In some examples, output(s) of the neural network can be coupled and/or otherwise provided to input(s) of the reinforcement learning network.

(202) In some examples, the environment topology **472** is implemented using data that describes, represents, and/or otherwise corresponds to environment **200** of FIG. **2**, the data routing management system **300** of FIG. **3**, the network environment **304** of FIG. **3**, etc. For example, the environment topology **472** can be implemented with data that describes an architecture, an order, an organization of levels or tiers, etc., of the environment **200**. In some examples, the environment topology **472** can be implemented with data that describes that first component(s), equipment, device(s), user(s), etc., is/are topologically coupled to second component(s), equipment, device(s), user(s), etc. In some examples, the environment topology **472** can be implemented with data that describes that the environment **200** is topologically coupled to another environment. In some examples, the environment topology **472** can be implemented using data that describes, represents, and/or otherwise corresponds to the environment **200** of FIG. **2**, the data routing management system **300** of FIG. **3**, and/or the network environment **304** of FIG. **3**. For example, the environment topology **472** can be implemented using node data, which can include identification(s)

of user(s) of the node, identification(s) of electronic device(s) of the node, electronic device information (e.g., an Internet Protocol (IP) address, a Media Access Control (MAC) number, quantity and/or type of hardware resource of an electronic device such as the first soldering station, a version of firmware and/or software of the electronic device, etc.), etc., and/or any combination(s) thereof. In some examples, the environment topology **472** is implemented using data in any data format such as, for example, binary data, comma delimited data, tab delimited data, SQL structures, a table, a map, a graph (e.g., a data graph, a data graph structure, a contextual data graph model, etc.), a grid, a packet, a datagram, a frame, a file, an e-mail, a message, a document, a report, a list, etc.

(203) In some examples, the contextual data graph models **474** are models that represent relationships of data with respect to other related data. For example, the contextual data graph models **474** can include a model with a plurality of nodes that are connected to one(s) of each other based on their affiliation, relatedness, and/or similarity with respect to each other. In some examples, a first node may be connected to a second node with a vector having an angle with respect to a reference axis and a length. The angle may be representative of a likelihood that the first node may cause an event that affects the second node. The length may be representative of a similarity of the first node and the second node. For example, if the first node is a first lexical term and the second node is a second lexical term, the length of a vector that connects the first node and the second node may be based on a cosine similarity (or any other NLP or text similarity measure or metric) between the first and second lexical terms.

(204) The datastore **460** of the illustrated example can be implemented by one or more volatile memories (e.g., an SDRAM), DRAM, RDRAM, etc.), one or more non-volatile memories (e.g., flash memory), and/or any combination(s) thereof. In some examples, the datastore **460** is instantiated by processor circuitry executing datastore instructions and/or configured to perform operations such as those represented by one(s) of the flowcharts of FIGS. **17-40**. The datastore **460** may additionally or alternatively be implemented by one or more DDR memories, such as DDR, DDR2, DDR3, DDR4, DDR5, mDDR, etc. The datastore **460** may additionally or alternatively be implemented by one or more mass storage devices such as HDD(s), CD drive(s), DVD drive(s), SSD drive(s), etc. While in the illustrated example the datastore **460** is illustrated as a single datastore, the datastore **460** may be implemented by any number and/or type(s) of datastores. Furthermore, the data stored in the datastore **460** may be in any data format such as, for example, binary data, comma delimited data, tab delimited data, SQL structures, a table, a map, a graph (e.g., a data graph, a graph data structure, etc.), a grid, a packet, a datagram, a frame, a file, an e-mail, a message, a document, a report, a list, etc. In some examples, the datastore **460** can implement one or more databases.

(205) In some examples, the data routing management circuitry **400** includes means for ingesting data and/or metadata. For example, the means for ingesting may be implemented by data ingestion circuitry **410**. In some examples, means for detecting a change of a data routing path may be implemented by the data ingestion circuitry **410**. In some examples, the data ingestion circuitry **410** may be instantiated by processor circuitry such as the example processor circuitry **4112** of FIG. **41** and/or the example processor circuitry **4212** of FIG. **42**. For instance, the data ingestion circuitry **410** may be instantiated by the example microprocessor **4300** of FIG. **43** executing machine executable instructions such as those implemented by block(s) of one(s) of FIGS. **17-40**. In some examples, the data ingestion circuitry **410** may be instantiated by hardware logic circuitry, which may be implemented by an ASIC, XPU, or the FPGA circuitry **4400** of FIG. **44** structured to perform operations corresponding to the machine-readable instructions. Additionally or alternatively, the data ingestion circuitry **410** may be instantiated by any other combination of hardware, software, and/or firmware. For example, the data ingestion circuitry **410** may be implemented by at least one or more hardware circuits (e.g., processor circuitry, discrete and/or integrated analog and/or digital circuitry, an FPGA, an ASIC, an XPU, a comparator, an

operational-amplifier (op-amp), a logic circuit, etc.) structured to execute some or all of the machine-readable instructions and/or to perform some or all of the operations corresponding to the machine-readable instructions without executing software or firmware, but other structures are likewise appropriate.

(206) In some examples, the data routing management circuitry **400** includes means for executing and/or instantiating a machine-learning model. For example, the means for executing and/or instantiating may be implemented by the machine-learning circuitry **420**. In some examples, means for determining and/or generating a data routing path may be implemented by the machine-learning circuitry **420**. In some examples, means for detecting a change of a data routing path may be implemented by the machine-learning circuitry **420**. In some examples, the machine-learning circuitry **420** may be instantiated by processor circuitry such as the example processor circuitry **4112** of FIG. **41** and/or the example processor circuitry **4212** of FIG. **42**. For instance, the machine-learning circuitry **420** may be instantiated by the example microprocessor **4300** of FIG. **43** executing machine executable instructions such as those implemented by block(s) of one(s) of FIGS. **17-40**. In some examples, the machine-learning circuitry **420** may be instantiated by hardware logic circuitry, which may be implemented by an ASIC, XPU, or the FPGA circuitry **4400** of FIG. **44** structured to perform operations corresponding to the machine-readable instructions. Additionally or alternatively, the machine-learning circuitry **420** may be instantiated by any other combination of hardware, software, and/or firmware. For example, the machine-learning circuitry **420** may be implemented by at least one or more hardware circuits (e.g., processor circuitry, discrete and/or integrated analog and/or digital circuitry, an FPGA, an ASIC, an XPU, a comparator, an operational-amplifier (op-amp), a logic circuit, etc.) structured to execute some or all of the machine-readable instructions and/or to perform some or all of the operations corresponding to the machine-readable instructions without executing software or firmware, but other structures are likewise appropriate.

(207) In some examples, the data routing management circuitry **400** includes means for obtaining metadata. For example, the means for obtaining metadata may be implemented by the data query management circuitry **430**. In some examples, means for retrieving metadata may be implemented by the data query management circuitry **430**. In some examples, means for providing metadata may be implemented by the data query management circuitry **430**. In some examples, the data query management circuitry **430** may be instantiated by processor circuitry such as the example processor circuitry **4112** of FIG. **41** and/or the example processor circuitry **4212** of FIG. **42**. For instance, the data query management circuitry **430** may be instantiated by the example microprocessor **4300** of FIG. **43** executing machine executable instructions such as those implemented by block(s) of one(s) of FIGS. **17-40**. In some examples, the data query management circuitry **430** may be instantiated by hardware logic circuitry, which may be implemented by an ASIC, XPU, or the FPGA circuitry **4400** of FIG. **44** structured to perform operations corresponding to the machine-readable instructions. Additionally or alternatively, the data query management circuitry **430** may be instantiated by any other combination of hardware, software, and/or firmware. For example, the data query management circuitry **430** may be implemented by at least one or more hardware circuits (e.g., processor circuitry, discrete and/or integrated analog and/or digital circuitry, an FPGA, an ASIC, an XPU, a comparator, an operational-amplifier (op-amp), a logic circuit, etc.) structured to execute some or all of the machine-readable instructions and/or to perform some or all of the operations corresponding to the machine-readable instructions without executing software or firmware, but other structures are likewise appropriate.

(208) In some examples, the data routing management circuitry **400** includes means for managing a node. For example, the means for managing a node may be implemented by the node management circuitry **440**. In some examples, means for determining a configuration of a node may be implemented by the node management circuitry **440**. In some examples, the node management circuitry **440** may be instantiated by processor circuitry such as the example processor circuitry

4112 of FIG. **41** and/or the example processor circuitry **4212** of FIG. **42**. For instance, the node management circuitry **440** may be instantiated by the example microprocessor **4300** of FIG. **43** executing machine executable instructions such as those implemented by block(s) of one(s) of FIGS. **17-40**. In some examples, the node management circuitry **440** may be instantiated by hardware logic circuitry, which may be implemented by an ASIC, XPU, or the FPGA circuitry **4400** of FIG. **44** structured to perform operations corresponding to the machine-readable instructions. Additionally or alternatively, the node management circuitry **440** may be instantiated by any other combination of hardware, software, and/or firmware. For example, the node management circuitry **440** may be implemented by at least one or more hardware circuits (e.g., processor circuitry, discrete and/or integrated analog and/or digital circuitry, an FPGA, an ASIC, an XPU, a comparator, an operational-amplifier (op-amp), a logic circuit, etc.) structured to execute some or all of the machine-readable instructions and/or to perform some or all of the operations corresponding to the machine-readable instructions without executing software or firmware, but other structures are likewise appropriate.

(209) In some examples, the data routing management circuitry **400** includes means for transmitting data. For example, the means for transmitting data may be implemented by the data publishing circuitry **450**. In some examples, means for causing transmission of data may be implemented by the data publishing circuitry **450**. In some examples, means for publishing data may be implemented by the data publishing circuitry **450**. In some examples, the data publishing circuitry **450** may be instantiated by processor circuitry such as the example processor circuitry **4112** of FIG. **41** and/or the example processor circuitry **4212** of FIG. **42**. For instance, the data publishing circuitry **450** may be instantiated by the example microprocessor **4300** of FIG. **43** executing machine executable instructions such as those implemented by block(s) of one(s) of FIGS. **17-40**. In some examples, the data publishing circuitry **450** may be instantiated by hardware logic circuitry, which may be implemented by an ASIC, XPU, or the FPGA circuitry **4400** of FIG. **44** structured to perform operations corresponding to the machine-readable instructions. Additionally or alternatively, the data publishing circuitry **450** may be instantiated by any other combination of hardware, software, and/or firmware. For example, the data publishing circuitry **450** may be implemented by at least one or more hardware circuits (e.g., processor circuitry, discrete and/or integrated analog and/or digital circuitry, an FPGA, an ASIC, an XPU, a comparator, an operational-amplifier (op-amp), a logic circuit, etc.) structured to execute some or all of the machine-readable instructions and/or to perform some or all of the operations corresponding to the machine-readable instructions without executing software or firmware, but other structures are likewise appropriate.

(210) In some examples, the data routing management circuitry **400** includes means for storing data and/or metadata. For example, the means for storing may be implemented by the datastore **460**. In some examples, the datastore **460** may be instantiated by processor circuitry such as the example processor circuitry **4112** of FIG. **41** and/or the example processor circuitry **4212** of FIG. **42**. For instance, the datastore **460** may be instantiated by the example microprocessor **4300** of FIG. **43** executing machine executable instructions such as those implemented by block(s) of one(s) of FIGS. **17-40**. In some examples, the datastore **460** may be instantiated by hardware logic circuitry, which may be implemented by an ASIC, XPU, or the FPGA circuitry **4400** of FIG. **44** structured to perform operations corresponding to the machine-readable instructions. Additionally or alternatively, the datastore **460** may be instantiated by any other combination of hardware, software, and/or firmware. For example, the datastore **460** may be implemented by at least one or more hardware circuits (e.g., processor circuitry, discrete and/or integrated analog and/or digital circuitry, an FPGA, an ASIC, an XPU, a comparator, an operational-amplifier (op-amp), a logic circuit, mass storage, memory, etc.) structured to execute some or all of the machine-readable instructions and/or to perform some or all of the operations corresponding to the machine-readable instructions without executing software or firmware, but other structures are likewise appropriate.

(211) While an example manner of implementing the data routing manager **302A-I** of FIG. 3 is illustrated in FIG. 4, one or more of the elements, processes, and/or devices illustrated in FIG. 4 may be combined, divided, re-arranged, omitted, eliminated, and/or implemented in any other way. Further, the example data ingestion circuitry **410**, the example machine-learning circuitry **420**, the example data query management circuitry **430**, the example node management circuitry **440**, the example data publishing circuitry **450**, the example datastore **460**, the example raw data **462**, the example metadata **464**, the example users **466**, the example nodes **468**, the example machine-learning models **470**, the example environment topology **472**, the example contextual data graph models **474**, the example digital twins **476**, the example bus **480**, and/or, more generally, the example data routing manager **302A-I** of FIG. 3, may be implemented by hardware alone or by hardware in combination with software and/or firmware. Thus, for example, any of the example data ingestion circuitry **410**, the example machine-learning circuitry **420**, the example data query management circuitry **430**, the example node management circuitry **440**, the example data publishing circuitry **450**, the example datastore **460**, the example raw data **462**, the example metadata **464**, the example users **466**, the example nodes **468**, the example machine-learning models **470**, the example environment topology **472**, the example contextual data graph models **474**, the example digital twins **476**, the example bus **480**, and/or, more generally, the example data routing manager **302A-I**, could be implemented by processor circuitry, analog circuit(s), digital circuit(s), logic circuit(s), programmable processor(s), programmable microcontroller(s), GPU(s), DSP(s), ASIC(s), PLD(s), and/or FPLD(s) such as FPGAs. Further still, the example data routing manager **302A-I** of FIG. 3 may include one or more elements, processes, and/or devices in addition to, or instead of, those illustrated in FIG. 4, and/or may include more than one of any or all of the illustrated elements, processes and devices.

(212) FIG. 5 is an illustration of example contextual data graph models **502**, **504**, which include a first example contextual data graph model **502** and a second example contextual data graph model **504**, to achieve adaptive and/or proactive data routing in network environment. In some examples, the first contextual data graph model **502** and/or the second contextual data graph model **504** can implement the contextual data graph models **474** of FIG. 4. The first contextual data graph model **502** has a first example primary or major node **506** and the second contextual data graph model **504** has a second example primary or major node **508**. The first contextual data graph model **502** has a plurality of example adjacent nodes including a first example adjacent node **510**. For example, the first adjacent node **510** is connected to the first primary node **506** by a vector having an angle (relative to a reference axis), a length, an orientation, and a position with respect to the first primary node **506**. The second contextual data graph model **504** has a plurality of example adjacent nodes including a second example adjacent node **512**. For example, the second adjacent node **512** is connected to the second primary node **508** by a vector having an angle (relative to a reference axis), a length, an orientation, and a position with respect to the second primary node **508**.

(213) In some examples, if the primary nodes **506**, **508** are the same, then the weighting of adjacent nodes **510**, **512** may provide context and associated terms that may be customized and/or otherwise coopted for a particular department or discipline of an environment (e.g., an industrial, commercial, or office environment, etc.), such as the environment **200** of FIG. 2. In some examples, if the primary nodes **506**, **508** are different, but are connected to similar adjacent nodes **510**, **512**, then it would imply the primary nodes **506**, **508** have the same contextual definition. In some examples, establishing the initial definitions (e.g., vector lengths, angles, orientations, spacings, etc.) may be done prescriptively by a person or inductively if it was an event, task, or object in common between the contextual data graph models **502**, **504**. In some examples, the machine-learning circuitry **420** of FIG. 4 can execute, instantiate, and/or otherwise cause the machine-learning models **470** of FIG. 4 to establish the initial definitions by analyzing, inspecting, and/or otherwise evaluating data passing through a network in an environment to identify causes/events, correlations, patterns, etc., observed in the data with respect to previously observed data.

(214) In some examples, correlation of the primary nodes **506**, **508** to one another may be calculated based on similarity in the depicted nodes (common adjacent terms) and strength of connection, which may be implemented by a vector length. In this example, cross hatched nodes and dotted nodes of the contextual data graphs models **502**, **504** may constitute differentials that highlight differences between use/definition of same terms (e.g., lexical terms, data terms, etc.) in different disciplines, processes, departments, environments, etc.

(215) FIG. **6** is an illustration of an example event chain **600**. For example, the data routing manager **302A-I** can intervene in and/or monitor and/or control the event chain **600**. The event chain **600** includes a first example process **602** (identified by PROCESS **1**), a second example process **604** (identified by PROCESS **2**), a third example process **606** (identified by PROCESS **3**), and an example adjacent process **608** (identified by ADJACENT PROCESS **A**). In some examples, the event chain **600** can be implemented by a workflow including one or more activities, operations, tasks, etc., associated with an environment. For example the event chain **600** can be implemented by warehouse operations of the environment **200** of FIG. **2**. Alternatively, the event chain **600** may be any other process, such as operations associated with manufacturing a product (e.g., a vehicle assembly line, a semiconductor manufacturing workflow, an autonomous vehicle infrastructure (e.g., coordinating autonomous vehicles on a roadway), etc.). For example, the first process **602** can be carried out and/or otherwise implemented by the robots **214** completing actions, operations, procedures, workflows, etc. In some examples, the first process **602** can be carried out and/or otherwise implemented by one(s) of the robots **214** performing one or more assembly and/or manufacturing actions, operations, procedures, workflows, etc., followed by (e.g., followed by in sequence) the second process **604**, which can be one(s) of the industrial machines **216**, **218**, **220**, **222** moving assembled and/or manufactured products from the robots **214** to a storage area (e.g., shelves). In some examples, the second process **604** can be carried out and/or otherwise implemented by the industrial machines **216**, **218**, **220**, **222** performing one or more actions, operations, procedures, workflows, etc., followed by (e.g., followed by in sequence) the third process **606**, which can be the fourth industrial machine **222** loading the assembled and/or manufactured products from storage to the vehicle **226**.

(216) In some examples, the event chain **600** implements a model (e.g., a contextual model) that is representative of an event-sequence dataset. Each of the processes **602**, **604**, **606**, **608** can have a data model (e.g., a contextual data graph model) generated continuously from control and/or sensor data inputs which, ordinarily, show little change under nominal conditions. In some examples, a significant change from the normal model (e.g., detection of a deviation from a baseline or nominal condition or value(s)) may result in a response/adjustment in the subsequent process to address the change identified in the prior process. For example, recent correlated raw control and/or sensor data can provide indicators to which of the identified events has a high likelihood of occurrence based on which specific elements of the data have changed significantly. In some examples, the detection of the deviation can trigger a proposed adjustment and forwarding of supporting cross-data to increase confidence (or not) to assist autonomous and/or human supervised decision-making.

(217) In example operation, the first process **602** can execute a first operation and generate sensor data associated with the first operation. For example, the first process **602** can include a first one of the robots **214** executing and/or performing a first assembly action (e.g., coupling a first component to a second component). In some examples, the data can show a repeated or cyclical impact on the second process **604** when the first process **602** satisfies a threshold (e.g., sensor data values of sensors monitoring the first one of the robots **214** have stabilized within a tolerance range (e.g., a torque associated with the coupling has reached a threshold) or indicated that the coupling is complete). For example, the second process **604** can include the first industrial machine **216** executing and/or performing a transportation action (e.g., moving the newly coupled first and second components to one of the shelves). In some examples, the data from the first process **602** can have a cyclical impact on the second process **604** because the second process **604** can be

initiated in response to a completion of the first process **602**.

(218) Advantageously, the data routing manager **302A-I** can monitor event sequencing of the event chain **600** to identify insight and/or pattern(s) allowing connected one(s) of the processes **602**, **604**, **606**, **608** to make early adjustments based on data variation. For example, in response to detecting that an electrical power source powering the first one of the robots **214** has overheated and been turned off (e.g., turned off in response to a temperature sensor measurement exceeding a temperature threshold), the data routing manager **302A-I** can generate an alert and transmit the alert to the second process **604** to indicate the failure (or halting of the first process **602**) due to the detection of the failure of the electrical power source. In some examples, the data routing manager **302A-I** can cause the second process **604** (e.g., the first industrial machine **216**) to take mitigation measures (e.g., disable power to the first industrial machine **216** to conserve power or other resources, divert the first industrial machine **216** to a different one of the robots **214**, etc.) and/or alert a subsequent process (e.g., the third process **606**) of the alert.

(219) In some examples, the data routing manager **302A-I** can also identify non-in process activities, such as the adjacent process **608**, that may be impacted of a data event (e.g., the disabling of the electrical power source of the first one of the robots **214**). In some examples, the adjacent process **608** can be implemented using a marketing process, an inventory process, a warehouse process, a transportation process, or the like. For example, the data routing manager **302A-I** can provide the alert to the adjacent process **608** to adjust as needed, such as changes in materials (e.g., material ordering, procurement, storing, etc.), changes in availability of a product, etc., and/or any combination(s) thereof.

(220) In the illustrated example, the data routing manager **302A-I** can generate example contextual data graph models **610**, **612**, **614** based on the event chain **600**. In some examples, the contextual data graph models **610**, **612**, **614** can implement the contextual data graph models **474** of FIG. 4. The contextual data graph models **610**, **612**, **614** include a first example contextual data graph model **610**, a second example contextual data graph model **612**, and a third example contextual data graph model **614**. In some examples, the first contextual data graph model **610** can be based on raw data correlations. For example, the first contextual data graph model **610** can be generated, curated, etc., based on standalone data analysis of sensor input related directly to a corresponding inline process. For example, the first process **602** can have a corresponding one of the first contextual data graph model **610**, which can be generated based on control and/or sensor data generated by the first process **602**. In some examples, the first contextual data graph model **610** may not have correlation to other data sets, events, or processes.

(221) In some examples, the second contextual data graph model **612** can be based on event data correlations. For example, the second contextual data graph model **612** can be generated, adapted, constructed, etc., based on captures of event sequences surrounding processes that the second contextual data graph model **612** is associated with. For example, the second contextual data graph model **612** can include data based on the second process **604** and associated processes (e.g., the first process **602**, the third process **606**, the adjacent process **608**, etc.). In some examples, the second contextual data graph model **612** can represent impact(s) of subsequent inline processes (e.g., an impact of an output of the second process **604** to an input of the third process **606**). In some examples, a length of a vector connecting two nodes in the second contextual data graph model **612** can define and/or otherwise be representative of a likelihood of event sequence (e.g., how probable, often, likely, etc., does the third process **606** follows the second process **604**). In some examples, angles of deviation (e.g., an angle of a connecting vector with respect to a reference axis) can define and/or otherwise be representative of a degree of similarity of adjacent events that appear to be impacted (e.g., if not in a direct line of process events). For example, the third process **606** is a direct inline process with respect to the second process **604** while the adjacent process **608** is an indirect or adjacent process with respect to the second process **604**.

(222) In some examples, the third contextual data graph model **614** can be based on cross data

correlations. For example, the third contextual data graph model **614** can be created, generated, modified, etc., based on a first data object. In some examples, the third contextual data graph model **614** can be created, generated, modified, etc., based on captures or ingestions of other second data objects (e.g., documents, data files, etc.) that are frequently associated with or used in conjunction with the first data object. In some examples, a length of a vector of connecting nodes can define and/or otherwise be representative of a strength of association of the connected nodes. For example, the strength of association can be quantified based on a strength or high likelihood of connection and/or co-utilization (e.g., a frequency or likelihood that two data objects are used in tandem, combination, or sequence) of the first data object and one of the second data objects.

(223) In some examples, the first contextual data graph model **610** can be based on raw data correlations. For example, the first contextual data graph model **610** can be generated, curated, etc., based on standalone data analysis of sensor input related directly to a corresponding inline process. For example, the first process **602** can have a corresponding one of the first contextual data graph model **610**, which can be generated based on control and/or sensor data generated by the first process **602**. In some examples, the first contextual data graph model **610** may not have correlation to other data sets, events, or processes.

(224) In some examples, local contextual data graph models and associated data can be cached together, where analytics (e.g., execution of analytics by executing and/or instantiating the machine-learning models **470** of FIG. 4) is performed to weigh the strength of various graph node combinations between datasets being correlated and over extended periods of time gaining additional insights based on event chaining from one dataset which influences/impacts another. In some examples, each of the contextual data graph models **610**, **612**, **614** can be tagged with metadata such as system vendor, sensor type, unit, resolution, location zones (e.g., a zone or segment of the environment **200** of FIG. 2), alerts, past alerts, provenance, relevance to a fault, user access etc.

(225) In some examples, the contextual data graph models **610**, **612**, **614** and/or the event chain **600** can be persisted to the data routing manager **302A-I** of FIG. 3, which can enable shared access to the contextually correlated datasets. Advantageously, the data routing manager **302A-I** can send the contextual data graph models **610**, **612**, **614**, the event chain **600**, and/or associated data to other parts of the environment **200** (e.g., sent from the first industrial machine **216** to the predictive maintenance system **224**) to provide improved insights and correlation of cross-operations data and a means to quickly bootstrap information and data services operations. In some examples, security of data stored by the data routing manager **302A-I** can be ensured with access rights. In some examples, raw data can be hidden, while just surfacing the translated alert or context of the alert, which can then be used in a different zone on the floor of the environment **200** of FIG. 2.

(226) Advantageously, the deployment of the contextual data graph models **610**, **612**, **614** and/or the event chain **600** between different data managers of the environment **200** can enable each data routing manager **302A-I** to learn, understand, and potentially align the vocabulary of other teams that may be requesting data (e.g., requesting an access of data, requesting a search for the data, etc.), the relationship between different data/information sources, and the importance of data and adjacent datasets when viewed from an end-to-end process standpoint, which is depicted by the event chain **600**.

(227) FIG. 7 is an illustration of a first example contextual data graph model **702** and a second example contextual data graph model **704**. In some examples, the contextual data graph models **702**, **704** can implement the contextual data graph models **474** of FIG. 4 and/or the second contextual data graph model **612** of FIG. 6. In some examples, the contextual data graph models **702**, **704** can be implemented using data that defines, represents, and/or otherwise implements the event chain **600** of FIG. 6. In some examples, the data routing manager **302A-I** can generate the first contextual data graph model **702** and/or the second contextual data graph model **704**.

(228) In the illustrated example, the first contextual data graph model **702** is an event sequence

graph. Inline direct events of the first contextual data graph model **702** are identified as nodes 1, 2, and 3. Such inline direct events represent events that are expected to be or have been observed in sequence, frequently. Example inline direct vectors **706**, **708** have lengths (e.g., a length of the vector connecting node 1 and node 2, node 2 and node 3, etc.) that are relatively short, which can represent the events to be, apparently, closely coupled and/or otherwise tightly correlated. Example adjacent vectors **710**, **712** are representative of connected events that have been observed to occur with lower frequency (as illustrated with longer vectors than the inline direct vectors **706**, **708**) with respect to the inline direct events. Although the adjacent vectors **710**, **712** are representative of lower frequency events, the adjacent vectors **710**, **712** may still represent connected events that are related in a statistically significant manner. Advantageously, the data routing manager **302A-I** can dynamically generate, modify (e.g., add or remove a node, lengthen or shorten a vector, increase or decrease an angle of a vector, a change in location or connection of a vector, etc.), etc., the first contextual data graph model **702** and/or the second contextual data graph model **704** over time as events and associated data are recorded and observed.

(229) In the illustrated example, the second contextual data graph model **704** is another event sequence graph. In some examples, an event sequence can represent multiple coincidental events (e.g., events that may have an equal or substantially equal likelihood of occurrence) as depicted by two instances of node 3. For example, depending upon the adjacency of the outcomes of the two instances of node 3, these two instances can be two different events that can occur at the same time on two different process lines (e.g., two different manufacturing lines) or two equally or substantially equal possible events on a single process line.

(230) FIG. **8** is an illustration of an example user graph **800**, which includes example data graphs **802**, **804**, **806**, **808** associated with an example user **810** (identified by USER A) to facilitate proactive data routing in an example network environment (e.g., the environment **200** of FIG. **2**, the network environment **304** of FIG. **3**, etc.). In some examples, the machine-learning circuitry **420** can execute the machine-learning models **470** to generate one(s) of the data graphs **802**, **804**, **806**, **808**, and/or, more generally, the user graph **800**. In some examples, the user **810** can be one of the users **310**, **312**, **314**, **316**, **318**, **320** of FIG. **3**, the users **466** of FIG. **4**, etc. For example, the user **810** can be a physical person, such as one of the users **310**, **312**, **314**, **316**, **318**, **320**. In some examples, the user **810** can be user data, such as user data stored in the users **466** of the datastore **460**. In some examples, the user **810** can be an electronic and/or computing device.

(231) The data graphs **802**, **804**, **806**, **808** include a first example data graph **802** (identified by ZONE 1, FLOOR 1), a second example data graph **804** (identified by WELDING), a third example data graph **806** (identified by RIVETING), and a fourth example data graph **808** (identified by ROBOTICS). The illustrated example depicts the user graph **800** and how the user graph **800** is connected to multiple metadata (and communities). For example, the first data graph **802** includes a plurality of example nodes (e.g., data graph nodes) **812**. Each of the plurality of the nodes **812** represent and/or otherwise correspond to a user (e.g., one of the users **466** of FIG. **4**). For example, each of the plurality of the nodes **812** can be implemented using metadata corresponding to a respective user. For example, the first data graph **802** is depicted as having 5 data graph nodes, or 5 sets of metadata corresponding to a respective one of 5 users (e.g., USER B, USER C, USER D, USER E, USER F). In this example, the user **810** is connected by way of metadata to USER B and USER D. For example, a first portion of first metadata associated with the user **810** can match, point to, reference, etc., a second portion of second metadata associated with USER B, a third portion of third metadata associated with USER D, etc. By way of another example, USER B is connected by way of metadata to USER E and USER F.

(232) In the illustrated example, the first data graph **802** is representative of users in Zone 1, Location 1 of an environment (e.g., a factory, a warehouse, an office building, etc.). For example, the plurality of the data graph nodes **812** is coupled to one(s) of each other based on matching (or substantially matching) portion(s) of metadata (e.g., first metadata of a first user matching second

metadata of a second user). In some examples, the data graph nodes **812** are included in the first data graph **802** because they share the same location. The data graph nodes **812** can be connected to one(s) of each other based on metadata relationships. For example, USER B may be a manager that supervises USER E and USER F.

(233) In the illustrated example, the second data graph **804** is representative of users that are associated with a topic of welding. For example, data graph nodes of the second data graph **804** are likely to find data associated with welding relevant. In the illustrated example, the third data graph **806** is representative of users that are associated with a topic of riveting. For example, data graph nodes of the third data graph **806** are likely to find data associated with riveting relevant. In the illustrated example, the fourth data graph **808** is representative of users that are associated with a topic of robotics. For example, data graph nodes of the fourth data graph **808** are likely to find data associated with riveting relevant.

(234) In the illustrated example, the user **810** represents a person and the metadata associated with the person (e.g., portion(s) of the metadata **464** corresponding to the user **810**) based on the communities the person belongs to. In some examples, these communities could be based on expertise/knowledge/tasks (e.g., welding, riveting, robotics, etc.) or context (e.g., a location of Zone 1, Floor 1). In some examples in which a group of users in the same area (e.g., a location of Zone 1, Floor 1) are expected to receive the same data at the substantially same time, then multicast routing can be applied to one(s) of the users in the same area. In some examples, this metadata is collected based on activity of users as reported by sensors in the network environment (e.g., reported by video cameras on a factory floor). Additionally and/or alternatively, this metadata can be collected using passive sensing such as a wireless access point receiving a login in a particular location, a user scanning security credentials by way of RFID at a terminal, etc. In some examples, a context of a user can be collected using which applications the user uses, a role of the user in their organization, access rights of the user as determined by Information Technology (IT) personnel, internal groups (e.g., knowledge boards, message groups, special interest groups, etc.) the user is signed up to, etc. In some examples, the data routing manager **302A-I** can execute NLP techniques to group words into context in the form of metadata.

(235) FIGS. **9A-9C** are illustrations of an example environment **902** to implement examples disclosed herein. The environment **902** of the illustrated example is a physical environment, such as the environment **200** of FIG. **2**. In some examples, the environment **902** is a virtual environments, such as a digital and/or virtual representation of a physical environment. For example, the environment **902** can be a digital twin of the environment **200**. In some examples, the environment **902** is a network environment, such as the network environment **304** of FIG. **3**. For example, the environment **902** can be representative of a network topology and interconnected nodes.

(236) The environment **902** includes a first example zone **904** (identified by ZONE 1) and a second example zone **906** (identified by ZONE 2). The zones **904**, **906** are respective portions of the environment **902**. For example, the first zone **904** can be a first area that includes the robots **214** of FIG. **2** and the second zone **906** can be a second area that includes the industrial machines **216**, **218**, **220**, **222** of FIG. **2**.

(237) The first zone **904** includes example nodes **908**, **910**, **912**, **914** including a first example node **908** (identified by A), a second example node **910** (identified by B), a third example node **912** (identified by C), and a fourth example node **914** (identified by D). For example, the first node **908**, the second node **910**, the third node **912**, and/or the fourth node **914** can be respective ones of the robots **214** of FIG. **2** (e.g., the first node **908** can be a first one of the robots **214**, etc.).

(238) The second zone **906** includes example nodes **916**, **918**, **920**, **922** including a fifth example node **916** (identified by E), a sixth example node **918** (identified by F), a seventh example node **920** (identified by G), and an eighth example node **922** (identified by H). For example, the fifth node **916**, the sixth node **918**, the seventh node **920**, and/or the eighth node **922** can be respective ones of the industrial machines **216**, **218**, **220**, **222** of FIG. **2** (e.g., the fifth node **916** can be the first

industrial machine **216**, etc.).

(239) In the illustrated example of FIG. **9B**, two example events **924**, **926** are generated, present, and/or otherwise have occurred. The events **924**, **926** include a first example event **924** in the first zone **904** and a second example event **926** in the second zone **906**. For example, the first event **924** can be the first node **908** becoming inoperable, non-responsive, etc., due to a fault and/or maintenance condition. In some examples, the first event **924** can be the first one of the robots **214** transitioning from an online state to an offline state due to a fault, an error, a mechanical and/or electrical failure, etc., and/or any combination(s) thereof. For example, the first node **908** can be offline while the second through fourth nodes **910**, **912**, **914** are online and/or otherwise not experiencing a fault and/or maintenance condition.

(240) In some examples, the second event **926** can be the eighth node **922** becoming inoperable, non-responsive, etc., due to a fault and/or maintenance condition. In some examples, the second event **926** can correspond to the fourth industrial machine **222** transitioning from an online state to an offline state due to a fault, an error, a mechanical and/or electrical failure, etc., and/or any combination(s) thereof. For example, the eighth node **922** can be offline while the fifth through seventh nodes **916**, **918**, **920** are online and/or otherwise not experiencing a fault and/or maintenance condition.

(241) In some examples, the events **924**, **926** are generated by a node experiencing and/or associated with the events **924**, **926**. For example, the first event **924** can be generated by the first node **908** in response to a determination by the first node **908** that it is undergoing and/or experiencing a fault and/or maintenance condition or state. In some examples, the first event **924** can be generated by one(s) of the second through fourth nodes **910**, **912**, **914** after a determination by the one(s) of the second through fourth nodes **910**, **912**, **914** that there is an issue (e.g., a fault and/or unplanned maintenance condition) with the first node **908**. In some examples, the determination can be based on sensor measurements of the second through fourth nodes **910**, **912**, **914** that detect the first node **908** is not moving, operating, etc. In some examples, the determination can be based on network telemetry data associated with the first node **908**, such as ping requests going unanswered and/or not having associated replies, a lack of detection of a heartbeat signal, a watchdog timer not being updated, etc., is indicative of the eighth node **922** being offline.

(242) In some examples, the second event **926** can be generated by the eighth node **922** in response to a determination by the eighth node **922** that it is undergoing and/or experiencing a fault and/or maintenance condition or state. In some examples, the second event **926** can be generated by one(s) of the fifth through seventh nodes **916**, **918**, **920** after a determination by the one(s) of the fifth through seventh nodes **916**, **918**, **920** that there is an issue (e.g., a fault and/or unplanned maintenance condition) with the eighth node **922**. In some examples, the determination can be based on sensor measurements of the fifth through seventh nodes **916**, **918**, **920** that detect the eighth node **922** is not moving, operating, etc. In some examples, the determination can be based on network telemetry data associated with the eighth node **922**, such as ping requests going unanswered and/or not having associated replies, a lack of detection of a heartbeat signal, a watchdog timer not being updated, etc., is indicative of the eighth node **922** being offline.

(243) In some examples, the events **924**, **926** can have associated metadata, such as the metadata **464** of FIG. **4**. For example, the first event **924** can have metadata including and/or associated with an identifier of the first node **908**, sensor data/measurements associated with the first node **908**, an alarm/fault/maintenance condition identifier associated with the first node **908**, a location of the first node **908** (e.g., an identifier or location of the first zone **904**), characteristics associated with the first node **908** to assist in user relevancy determinations, etc., and/or any combination(s) thereof.

(244) In the illustrated example of FIG. **9C**, a ninth example node **928** (identified by J) moved (or has been moved) to the first zone **904**. In some examples, the ninth node **928** can be another one of

the robots **214**. For example, in response to the first event **924**, another one of the robots **214** can be moved to the first zone **904** to take over workloads from the first node **908**. In some examples, the ninth node **928** can be a user, such as a human user (e.g., a maintenance technician, an engineer, repair personnel, etc.) and/or a non-human user (e.g., a robot technician, a repair robot, a device, etc.), that moved to the first zone **904** to address the first event **924**. For example, in response to the first event **924**, a human user can enter the first zone **904** to diagnose, repair, and/or replace the first node **908**. In some examples, in response to the first event **924**, a robot can enter the first zone **904** to diagnose, repair, and/or replace the first node **908** without human intervention (or collaboratively with human intervention, such as working with a human user).

(245) In the illustrated example of FIG. 9C, a tenth example node **930** (identified by K) moved (or has been moved) to the second zone **906**. In some examples, the tenth node **928 930** can be another one of the industrial machines **216, 218, 220, 222**. For example, in response to the second event **926**, another one of the industrial machines **216, 218, 220, 222** can be moved to the second zone **906** to pick up workloads in place of the eighth node **922**. In some examples, the tenth node **930** can be a user, such as a human user (e.g., a maintenance technician, an engineer, repair personnel, a human forklift operator, etc.) and/or a non-human user (e.g., a robot technician, a repair robot, a device, an autonomous forklift, etc.), that moved to the second zone **906** to attend to the second event **926**. For example, in response to the second event **926**, a human user can enter the second zone **906** to diagnose, repair, and/or replace the eighth node **922**. In some examples, in response to the second event **926**, an autonomous forklift can enter the second zone **906** to diagnose, repair, take away, and/or replace the eighth node **922** without human intervention (or collaboratively with human intervention, such as working with a human user).

(246) In some examples, metadata associated with the events **924, 926** can be augmented, changed, and/or modified in response to the addition of the ninth node **928** and/or the tenth node **930** to the zones **904, 906**. For example, after the ninth node **928** is dispatched to the first zone **904**, the ninth node **928** can generate metadata such as an identifier of the ninth node **928**, action(s)/operation(s) carried out by the ninth node **928** after generation of the first event **924**, etc., and/or any combination(s) thereof. In some examples, the metadata generated by the ninth node **928** (or different node(s) of the first zone **904**) can be associated with the first event **924**, one(s) of the first through fourth nodes **908, 910, 912, 914**, the first zone **904**, and/or, more generally, the environment **902**. For example, the metadata can be stored in the metadata datastore **146** of FIG. 1, the datastore **460** as the metadata **464**, etc. In some examples, the machine-learning circuitry **420** can retrain the machine-learning models **470** based on the metadata. In some examples, the machine-learning circuitry **420** can change and/or update the environment topology **472** based on the ninth node **928** entering the first zone **904**. In some examples, the machine-learning circuitry **420** can change and/or update one(s) of the contextual data graph models **474** based on the metadata, such as strengthening an association between the first event **924** and the ninth node **928** (e.g., the metadata is routed to the ninth node **928** and the ninth node **928** confirmed or affirmed that the metadata is relevant to the ninth node **928**). In some examples, the machine-learning circuitry **420** can change and/or update one of the digital twins **476** corresponding to the first zone **904**, and/or, more generally, the environment **902**, based on the ninth node **928** transitioning to the first zone **904**, the first node **908** going offline, etc.

(247) In some examples, after the tenth node **930** is dispatched to the second zone **906**, the tenth node **930** can generate metadata such as an identifier of the tenth node **930**, action(s)/operation(s) carried out by the tenth node **930** after generation of the second event **926**, etc., and/or any combination(s) thereof. In some examples, the metadata generated by the tenth node **930** (or different node(s) of the second zone **906**) can be associated with the second event **926**, one(s) of the fifth through eighth nodes **916, 918, 920, 922**, the second zone **906**, and/or, more generally, the environment **902**. For example, the metadata can be stored in the metadata datastore **146** of FIG. 1, the datastore **460** as the metadata **464**, etc. In some examples, the machine-learning circuitry **420**

can retrain the machine-learning models **470** based on the metadata. In some examples, the machine-learning circuitry **420** can change and/or update the environment topology **472** based on the tenth node **930** entering the second zone **906**. In some examples, the machine-learning circuitry **420** can change and/or update one(s) of the contextual data graph models **474** based on the metadata, such as strengthening an association between the second event **926** and the tenth node **930** (e.g., the metadata is routed to the tenth node **930** and the tenth node **930** acknowledged that the metadata is relevant to the tenth node **930**). In some examples, the machine-learning circuitry **420** can change and/or update one of the digital twins **476** corresponding to the second zone **906**, and/or, more generally, the environment **902**, based on the tenth node **930** moving to the second zone **906**, the eighth node **922** going offline, etc.

(248) FIG. **10** depicts an example dataset **1000**, which includes example metadata **1002**. In some examples, the metadata **1002**, and/or, more generally, the dataset **1000**, can implement the metadata **464** of FIG. **4**, or portion(s) thereof, metadata stored in the metadata datastore **146** of FIG. **1**, or portion(s) thereof, etc. In some examples, the data routing manager **302A-I** can effectuate adaptive and/or proactive data routing in the network environment **304** of FIG. **3** based on the metadata **1002**. For example, the machine-learning circuitry **420** can execute and/or instantiate one(s) of the machine-learning models **470** to carry out time based and/or content type analysis of the metadata **1002**. For example, the one(s) of the machine-learning models **470** can generate model output(s), which can include individual user data traffic and content selection/preference. In some examples, the one(s) of the machine-learning models **470** can identify preference(s) for each user in private node dataset to be stored in the datastore **460**.

(249) In the illustrated example, the dataset **1000** includes data associated with a network environment, such as a user organization, user discipline(s), discipline categories, comparable disciplines, user organization level of responsibility and/or ranking, and the like. For example, the data included in the dataset **1000** can be associated with and/or otherwise correspond to a user, such as one of the users **466**. In the illustrated example, the dataset **1000** can include user event cycles, which can be used to identify user(s) of interest to whom to deliver alerts. In the illustrated example, the dataset **1000** can include user topics of interest, user secondary topics, user common format preference(s), etc., from which alert(s) may be generated and/or a routing of which may be determined.

(250) FIG. **11** depicts an example workflow **1100** to identify and/or output example data routing paths in an example network environment **1102**. The network environment **1102** includes a plurality of example nodes **1104** (identified by 1, 2, 3, 4, etc., and referred to herein as Node 1, Node 2, Node 3, Node 4, etc.). The workflow **1100** begins at first example operation(s) **1106** when a machine-learning model, such as one of the machine-learning models **470** of FIG. **4**, is executed and/or instantiated to observe data flowing through the network environment **1102** along data routing paths (e.g., a data routing path from Node 1 to Node 2, etc.). For example, the data ingestion circuitry **410** can ingest event data associated with the network environment **1102**, such as identifications of data and/or metadata transmitted and/or received at the nodes **1104**; the data ingestion circuitry **410** can output the ingested event data to the machine-learning circuitry **420**; and the machine-learning circuitry **420** can execute and/or instantiate the machine-learning model to build and/or output patterns (e.g., data patterns, data routing patterns, etc.) in the network environment **1102**. In the illustrated example, data is routed from Node 1 to Nodes 3 and 4 via Node 2 (and intervening nodes) along a first example data routing path **1108**. For example, Node 1 transmits data to Node 2, which processes the data and forwards the processed data to Nodes 3 and 4 to cause Nodes 3 and 4 to act in connection with the processed data.

(251) During second example operation(s) **1110** of the workflow **1100**, the machine-learning circuitry **420** executes and/or instantiates (e.g., repeatedly, iteratively, etc., executes and/or instantiates) the machine-learning model with observed repeated similar and/or same event data associated with the network environment **1102**. For example, the machine-learning model can be

trained (or retrained) to strengthen data routing paths between Nodes 1 and 2 based on historical data, such as previously ingested and/or observed routing of data with similar or the same metadata from Node 1 to Node 2.

(252) During third example operation(s) **1112** of the workflow **1100**, the machine-learning circuitry **420** executes and/or instantiates the machine-learning model to embed neural response pattern(s) or reflex(es) into the network structure of the machine-learning model (e.g., if the machine-learning model is a neural network or other type of AI/ML network-based model). For example, the recognized event data of the first data routing path **1108** can strengthen other data routing paths **1114** that may be used in connection with subsequent events having the previously ingested/observed event data.

(253) During fourth example operation(s) **1116** of the workflow **1100**, the machine-learning circuitry **420**, over time, executes and/or instantiates the machine-learning model to generate outputs representative of, indicative of, and/or otherwise correspond to particular event and response pattern associations (e.g., a particular event is generated and a corresponding response pattern is detected and/or effectuated, such as a data routing path taken by data/metadata in the network environment **1102**). For example, the machine-learning model can generate outputs representative of response pattern identifications, reinforcements, and strengthening of optimized data routing paths in connection with generated events. In some examples, the machine-learning model can prune and/or remove excess nodes and segments (e.g., a segment in a data routing path directly between nodes without an intervening node) from data routing paths to optimize and/or otherwise improve the responsiveness becoming reflexive in nature. In some examples, during the fourth operation(s) **1116**, the machine-learning model outputs other example reflex paths **1117** (e.g., data routing paths, reflex data routing paths, etc.) for other identified repetitive events and issues. In some examples, the machine-learning model identifies unsuccessful data routing paths and cause them not to be repeated by removing them from the network structure of the machine-learning model and, thus, advantageously, leaving only successful responses, such as one(s) of the other reflex paths **1117**. For example, the machine-learning model can remove the segment between Node 3 and Node 7 during the fourth operation(s) **1116** after a determination that the segment is an unsuccessful segment.

(254) During fifth example operation(s) **1118**, the machine-learning circuitry **420** can identify, based on outputs from the machine-learning model, multiple successful data routing paths (e.g., data pathways, data routing pathways, or simply pathways) through the same nodes. Advantageously, the multiple successful data routing paths can cause the creation of centers of example expertise nodes **1120** in specific types of information, technology, or issues (e.g., events). Advantageously, the data routing manager **302A-I**, the data routing management circuitry **400**, and/or, more generally, the ADM system **100** of FIG. 1, can use the multiple successful data routing paths to construct and test new data routing paths for issues or data input not previously encountered and learn affinities between those nodes and types of issues or problems. Such construction and testing of new data routing paths advantageously achieves a faster, proactive cycle of sense or analyze, make sense or rationalize, select an action, and perform the action, in response to a detection and/or ingesting of data/metadata associated with an event in an environment. Advantageously, the data routing manager **302A-I**, the data routing management circuitry **400**, and/or, more generally, the ADM system **100** of FIG. 1, can utilize the centers of expertise nodes to guide human decision-making on how to handle new events and thereby shorten the cycle for getting event data to the right person, system, device, etc., for dispositioning. After the fifth operation(s) **1118**, the workflow can be repeated by returning to the first operation(s) **1106** to generate data routing paths for data/metadata after event generation.

(255) FIG. 12 is a block diagram **1200** showing an overview of a configuration for Edge computing, which includes a layer of processing referred to in many of the following examples as an “Edge cloud”. For example, the block diagram **1200** may implement an example adaptive data

management system (also referred to herein as a smart data management system) as disclosed herein. As shown, the Edge cloud **1210** is co-located at an Edge location, such as an access point or base station **1240**, a local processing hub **1250**, or a central office **1220**, and thus may include multiple entities, devices, and equipment instances. The Edge cloud **1210** is located much closer to the endpoint (consumer and producer) data sources **1260** (e.g., autonomous vehicles **1261**, user equipment **1262**, business and industrial equipment **1263**, video capture devices **1264**, drones **1265**, smart cities and building devices **1266**, sensors and IoT devices **1267**, etc.) than the cloud data center **1230**. Compute, memory, and storage resources which are offered at the edges in the Edge cloud **1210** are critical to providing ultra-low latency response times for services and functions used by the endpoint data sources **1260** as well as reduce network backhaul traffic from the Edge cloud **1210** toward cloud data center **1230** thus improving energy consumption and overall network usages among other benefits.

(256) Compute, memory, and storage are scarce resources, and generally decrease depending on the Edge location (e.g., fewer processing resources being available at consumer endpoint devices, than at a base station, than at a central office). However, the closer that the Edge location is to the endpoint (e.g., user equipment (UE)), the more that space and power is often constrained. Thus, Edge computing attempts to reduce the amount of resources needed for network services, through the distribution of more resources which are located closer both geographically and in network access time. In this manner, Edge computing attempts to bring the compute resources to the workload data where appropriate, or, bring the workload data to the compute resources.

(257) The following describes aspects of an Edge cloud architecture that covers multiple potential deployments and addresses restrictions that some network operators or service providers may have in their own infrastructures. These include, variation of configurations based on the Edge location (because edges at a base station level, for instance, may have more constrained performance and capabilities in a multi-tenant scenario); configurations based on the type of compute, memory, storage, fabric, acceleration, or like resources available to Edge locations, tiers of locations, or groups of locations; the service, security, and management and orchestration capabilities; and related objectives to achieve usability and performance of end services. These deployments may accomplish processing in network layers that may be considered as “near Edge”, “close Edge”, “local Edge”, “middle Edge”, or “far Edge” layers, depending on latency, distance, and timing characteristics.

(258) Edge computing is a developing paradigm where computing is performed at or closer to the “Edge” of a network, typically through the use of a compute platform (e.g., x86 or ARM compute hardware architecture) implemented at base stations, gateways, network routers, or other devices which are much closer to endpoint devices producing and consuming the data. For example, Edge gateway servers may be equipped with pools of memory and storage resources to perform computation in real-time for low latency use-cases (e.g., autonomous driving or video surveillance) for connected client devices. Or as an example, base stations may be augmented with compute and acceleration resources to directly process service workloads for connected user equipment, without further communicating data via backhaul networks. Or as another example, central office network management hardware may be replaced with standardized compute hardware that performs virtualized network functions and offers compute resources for the execution of services and consumer functions for connected devices. Within Edge computing networks, there may be scenarios in services which the compute resource will be “moved” to the data, as well as scenarios in which the data will be “moved” to the compute resource. Or as an example, base station compute, acceleration and network resources can provide services in order to scale to workload demands on an as needed basis by activating dormant capacity (subscription, capacity on demand) in order to manage corner cases, emergencies or to provide longevity for deployed resources over a significantly longer implemented lifecycle.

(259) FIG. **13** illustrates operational layers among endpoints, an Edge cloud, and cloud computing

environments. For example, FIG. 13 may implement an example adaptive data management system as disclosed herein. Specifically, FIG. 13 depicts examples of computational use cases **1305**, utilizing the Edge cloud **1210** among multiple illustrative layers of network computing. The layers begin at an endpoint (devices and things) layer **1300**, which accesses the Edge cloud **1210** to conduct data creation, analysis, and data consumption activities. The Edge cloud **1210** may span multiple network layers, such as an Edge devices layer **1310** having gateways, on-premise servers, or network equipment (nodes **1315**) located in physically proximate Edge systems; a network access layer **1320**, encompassing base stations, radio processing units, network hubs, regional data centers (DC), or local network equipment (equipment **1325**); and any equipment, devices, or nodes located therebetween (in layer **1312**, not illustrated in detail). The network communications within the Edge cloud **1210** and among the various layers may occur via any number of wired or wireless mediums, including via connectivity architectures and technologies not depicted.

(260) Examples of latency, resulting from network communication distance (e.g., distance between I/O interfaces such as PCIe or NICs) and processing time constraints, may range from less than a millisecond (ms) when among the endpoint layer **1300**, under 5 ms at the Edge devices layer **1310**, to even between 10 to 40 ms when communicating with nodes at the network access layer **1320**. Beyond the Edge cloud **1210** are core network **1330** and cloud data center **1340** layers, each with increasing latency (e.g., between 50-60 ms at the core network layer **1330**, to 100 or more ms at the cloud data center layer). As a result, operations at a core network data center **1335** or a cloud data center **1345**, with latencies of at least 50 to 100 ms or more, will not be able to accomplish many time-critical functions of the use cases **1305**. Each of these latency values are provided for purposes of illustration and contrast; it will be understood that the use of other access network mediums and technologies may further reduce the latencies. In some examples, respective portions of the network may be categorized as “close Edge”, “local Edge”, “near Edge”, “middle Edge”, or “far Edge” layers, relative to a network source and destination. For instance, from the perspective of the core network data center **1335** or a cloud data center **1345**, a central office or content data network may be considered as being located within a “near Edge” layer (“near” to the cloud, having high latency values when communicating with the devices and endpoints of the use cases **1305**), whereas an access point, base station, on-premise server, or network gateway may be considered as located within a “far Edge” layer (“far” from the cloud, having low latency values when communicating with the devices and endpoints of the use cases **1305**). It will be understood that other categorizations of a particular network layer as constituting a “close”, “local”, “near”, “middle”, or “far” Edge may be based on latency, distance, number of network hops, or other measurable characteristics, as measured from a source in any of the network layers **1300-1340**.

(261) The various use cases **1305** may access resources under usage pressure from incoming streams, due to multiple services utilizing the Edge cloud. To achieve results with low latency, the services executed within the Edge cloud **1210** balance varying requirements in terms of: (a) Priority (throughput or latency) and Quality of Service (QoS) (e.g., traffic for an autonomous car may have higher priority than a temperature sensor in terms of response time requirement; or, a performance sensitivity/bottleneck may exist at a compute/accelerator, memory, storage, or network resource, depending on the application); (b) Reliability and Resiliency (e.g., some input streams need to be acted upon and the traffic routed with mission-critical reliability, where as some other input streams may be tolerate an occasional failure, depending on the application); and (c) Physical constraints (e.g., power, cooling and form-factor, etc.).

(262) The end-to-end service view for these use cases involves the concept of a service-flow and is associated with a transaction. The transaction details the overall service requirement for the entity consuming the service, as well as the associated services for the resources, workloads, workflows, and business functional and business level requirements. The services executed with the “terms” described may be managed at each layer in a way to assure real time, and runtime contractual compliance for the transaction during the lifecycle of the service. When a component in the

transaction is missing its agreed to Service Level Agreement (SLA), the system as a whole (components in the transaction) may provide the ability to (1) understand the impact of the SLA violation, and (2) augment other components in the system to resume overall transaction SLA, and (3) implement steps to remediate.

(263) Thus, with these variations and service features in mind, Edge computing within the Edge cloud **1210** may provide the ability to serve and respond to multiple applications of the use cases **1305** (e.g., object tracking, video surveillance, connected cars, etc.) in real-time or near real-time, and meet ultra-low latency requirements for these multiple applications. These advantages enable a whole new class of applications (e.g., Virtual Network Functions (VNFs), Function as a Service (FaaS), Edge as a Service (EaaS), standard processes, etc.), which cannot leverage conventional cloud computing due to latency or other limitations.

(264) However, with the advantages of Edge computing comes the following caveats. The devices located at the Edge are often resource constrained and therefore there is pressure on usage of Edge resources. Typically, this is addressed through the pooling of memory and storage resources for use by multiple users (tenants) and devices. The Edge may be power and cooling constrained and therefore the power usage needs to be accounted for by the applications that are consuming the most power. There may be inherent power-performance tradeoffs in these pooled memory resources, as many of them are likely to use emerging memory technologies, where more power requires greater memory bandwidth. Likewise, improved security of hardware and root of trust trusted functions are also required, because Edge locations may be unmanned and may even need permissioned access (e.g., when housed in a third-party location). Such issues are magnified in the Edge cloud **1210** in a multi-tenant, multi-owner, or multi-access setting, where services and applications are requested by many users, especially as network usage dynamically fluctuates and the composition of the multiple stakeholders, use cases, and services changes.

(265) At a more generic level, an Edge computing system may be described to encompass any number of deployments at the previously discussed layers operating in the Edge cloud **1210** (network layers **1300-1340**), which provide coordination from client and distributed computing devices. One or more Edge gateway nodes, one or more Edge aggregation nodes, and one or more core data centers may be distributed across layers of the network to provide an implementation of the Edge computing system by or on behalf of a telecommunication service provider (“telco”, or “TSP”), internet-of-things service provider, cloud service provider (CSP), enterprise entity, or any other number of entities. Various implementations and configurations of the Edge computing system may be provided dynamically, such as when orchestrated to meet service objectives.

(266) Consistent with the examples provided herein, a client compute node may be embodied as any type of endpoint component, device, appliance, or other thing capable of communicating as a producer or consumer of data. Further, the label “node” or “device” as used in the Edge computing system does not necessarily mean that such node or device operates in a client or agent/minion/follower role; rather, any of the nodes or devices in the Edge computing system refer to individual entities, nodes, or subsystems which include discrete or connected hardware or software configurations to facilitate or use the Edge cloud **1210**.

(267) As such, the Edge cloud **1210** is formed from network components and functional features operated by and within Edge gateway nodes, Edge aggregation nodes, or other Edge compute nodes among network layers **1310-1330**. The Edge cloud **1210** thus may be embodied as any type of network that provides Edge computing and/or storage resources which are proximately located to radio access network (RAN) capable endpoint devices (e.g., mobile computing devices, IoT devices, smart devices, etc.), which are discussed herein. In other words, the Edge cloud **1210** may be envisioned as an “Edge” which connects the endpoint devices and traditional network access points that serve as an ingress point into service provider core networks, including mobile carrier networks (e.g., Global System for Mobile Communications (GSM) networks, Long-Term Evolution (LTE) networks, 5G/6G networks, etc.), while also providing storage and/or compute

capabilities. Other types and forms of network access (e.g., Wi-Fi, long-range wireless, wired networks including optical networks, etc.) may also be utilized in place of or in combination with such 3GPP carrier networks.

(268) The network components of the Edge cloud **1210** may be servers, multi-tenant servers, appliance computing devices, and/or any other type of computing devices. For example, the Edge cloud **1210** may include an appliance computing device that is a self-contained electronic device including a housing, a chassis, a case, or a shell. In some circumstances, the housing may be dimensioned for portability such that it can be carried by a human and/or shipped. Example housings may include materials that form one or more exterior surfaces that partially or fully protect contents of the appliance, in which protection may include weather protection, hazardous environment protection (e.g., electromagnetic interference (EMI), vibration, extreme temperatures, etc.), and/or enable submergibility. Example housings may include power circuitry to provide power for stationary and/or portable implementations, such as alternating current (AC) power inputs, direct current (DC) power inputs, AC/DC converter(s), DC/AC converter(s), DC/DC converter(s), power regulators, transformers, charging circuitry, batteries, wired inputs, and/or wireless power inputs. Example housings and/or surfaces thereof may include or connect to mounting hardware to enable attachment to structures such as buildings, telecommunication structures (e.g., poles, antenna structures, etc.), and/or racks (e.g., server racks, blade mounts, etc.). Example housings and/or surfaces thereof may support one or more sensors (e.g., temperature sensors, vibration sensors, light sensors, acoustic sensors, capacitive sensors, proximity sensors, infrared or other visual thermal sensors, etc.). One or more such sensors may be contained in, carried by, or otherwise embedded in the surface and/or mounted to the surface of the appliance. Example housings and/or surfaces thereof may support mechanical connectivity, such as propulsion hardware (e.g., wheels, rotors such as propellers, etc.) and/or articulating hardware (e.g., robot arms, pivotable appendages, etc.). In some circumstances, the sensors may include any type of input devices such as user interface hardware (e.g., buttons, switches, dials, sliders, microphones, etc.). In some circumstances, example housings include output devices contained in, carried by, embedded therein and/or attached thereto. Output devices may include displays, touchscreens, lights, light-emitting diodes (LEDs), speakers, input/output (I/O) ports (e.g., universal serial bus (USB)), etc. In some circumstances, Edge devices are devices presented in the network for a specific purpose (e.g., a traffic light), but may have processing and/or other capacities that may be utilized for other purposes. Such Edge devices may be independent from other networked devices and may be provided with a housing having a form factor suitable for its primary purpose; yet be available for other compute tasks that do not interfere with its primary task. Edge devices include Internet of Things devices. The appliance computing device may include hardware and software components to manage local issues such as device temperature, vibration, resource utilization, updates, power issues, physical and network security, etc. Example hardware for implementing an appliance computing or electronic device is described in conjunction with FIGS. **41**, **42**, **43**, and/or **44**. The Edge cloud **1210** may also include one or more servers and/or one or more multi-tenant servers. Such a server may include an operating system and implement a virtual computing environment. A virtual computing environment may include a hypervisor managing (e.g., spawning, deploying, commissioning, destroying, decommissioning, etc.) one or more virtual machines (VMs), one or more containers, etc. Such virtual computing environments provide an execution environment in which one or more applications and/or other software, code, or scripts may execute while being isolated from one or more other applications, software, code, or scripts.

(269) In FIG. **14**, various client endpoints **1410** (in the form of mobile devices, computers, autonomous vehicles, business computing equipment, industrial processing equipment) exchange requests and responses that are specific to the type of endpoint network aggregation. For example, FIG. **14** may implement an example adaptive data management system as disclosed herein. For instance, client endpoints **1410** may obtain network access via a wired broadband network, by

exchanging requests and responses **1422** through an on-premise network system **1432**. Some client endpoints **1410**, such as mobile computing devices, may obtain network access via a wireless broadband network, by exchanging requests and responses **1424** through an access point (e.g., a cellular network tower) **1434**. Some client endpoints **1410**, such as autonomous vehicles may obtain network access for requests and responses **1426** via a wireless vehicular network through a street-located network system **1436**. However, regardless of the type of network access, the TSP may deploy aggregation points **1442**, **1444** within the Edge cloud **1210** to aggregate traffic and requests. Thus, within the Edge cloud **1210**, the TSP may deploy various compute and storage resources, such as at Edge aggregation nodes **1440**, to provide requested content. The Edge aggregation nodes **1440** and other systems of the Edge cloud **1210** are connected to a cloud or data center **1460**, which uses a backhaul network **1450** to fulfill higher-latency requests from a cloud/data center for websites, applications, database servers, etc. Additional or consolidated instances of the Edge aggregation nodes **1440** and the aggregation points **1442**, **1444**, including those deployed on a single server framework, may also be present within the Edge cloud **1210** or other areas of the TSP infrastructure.

(270) FIG. **15** illustrates deployment and orchestration for virtualized and container-based Edge configurations across an Edge computing system operated among multiple Edge nodes and multiple tenants (e.g., users, providers) which use such Edge nodes. For example, FIG. **15** may implement an example adaptive data management system as disclosed herein. Specifically, FIG. **15** depicts coordination of a first Edge node **1522** and a second Edge node **1524** in an Edge computing system **1500**, to fulfill requests and responses for various client endpoints **1510** (e.g., smart cities/building systems, mobile devices, computing devices, business/logistics systems, industrial systems, etc.), which access various virtual Edge instances. Here, the virtual Edge instances **1532**, **1534** provide Edge compute capabilities and processing in an Edge cloud, with access to a cloud/data center **1540** for higher-latency requests for websites, applications, database servers, etc. However, the Edge cloud enables coordination of processing among multiple Edge nodes for multiple tenants or entities.

(271) In the example of FIG. **15**, these virtual Edge instances include: a first virtual Edge **1532**, offered to a first tenant (Tenant 1), which offers a first combination of Edge storage, computing, and services; and a second virtual Edge **1534**, offered to a second tenant (Tenant 2), which offers a second combination of Edge storage, computing, and services. The virtual Edge instances **1532**, **1534** are distributed among the Edge nodes **1522**, **1524**, and may include scenarios in which a request and response are fulfilled from the same or different Edge nodes. The configuration of the Edge nodes **1522**, **1524** to operate in a distributed yet coordinated fashion occurs based on Edge provisioning functions **1550**. The functionality of the Edge nodes **1522**, **1524** to provide coordinated operation for applications and services, among multiple tenants, occurs based on orchestration functions **1560**.

(272) It should be understood that some of the devices in **1510** are multi-tenant devices where Tenant 1 may function within a tenant1 'slice' while a Tenant 2 may function within a tenant2 slice (and, in further examples, additional or sub-tenants may exist; and each tenant may even be specifically entitled and transactionally tied to a specific set of features all the way day to specific hardware features). A trusted multi-tenant device may further contain a tenant specific cryptographic key such that the combination of key and slice may be considered a "root of trust" (RoT) or tenant specific RoT. A RoT may further be computed dynamically composed using a DICE (Device Identity Composition Engine) architecture such that a single DICE hardware building block may be used to construct layered trusted computing base contexts for layering of device capabilities (such as a Field Programmable Gate Array (FPGA)). The RoT may further be used for a trusted computing context to enable a "fan-out" that is useful for supporting multi-tenancy. Within a multi-tenant environment, the respective Edge nodes **1522**, **1524** may operate as security feature enforcement points for local resources allocated to multiple tenants per node.

Additionally, tenant runtime and application execution (e.g., in instances **1532**, **1534**) may serve as an enforcement point for a security feature that creates a virtual Edge abstraction of resources spanning potentially multiple physical hosting platforms. Finally, the orchestration functions **1560** at an orchestration entity may operate as a security feature enforcement point for marshalling resources along tenant boundaries.

(273) Edge computing nodes may partition resources (memory, central processing unit (CPU), GPU, interrupt controller, input/output (I/O) controller, memory controller, bus controller, etc.) where respective partitionings may contain a RoT capability and where fan-out and layering according to a DICE model may further be applied to Edge Nodes. Cloud computing nodes often use containers, FaaS engines, servlets, servers, or other computation abstraction that may be partitioned according to a DICE layering and fan-out structure to support a RoT context for each. Accordingly, the respective RoTs spanning devices **1510**, **1522**, and **1540** may coordinate the establishment of a distributed trusted computing base (DTCB) such that a tenant-specific virtual trusted secure channel linking all elements end to end can be established.

(274) Further, it will be understood that a container may have data or workload specific keys protecting its content from a previous Edge node. As part of migration of a container, a pod controller at a source Edge node may obtain a migration key from a target Edge node pod controller where the migration key is used to wrap the container-specific keys. When the container/pod is migrated to the target Edge node, the unwrapping key is exposed to the pod controller that then decrypts the wrapped keys. The keys may now be used to perform operations on container specific data. The migration functions may be gated by properly attested Edge nodes and pod managers (as described above).

(275) In further examples, an Edge computing system is extended to provide for orchestration of multiple applications through the use of containers (a contained, deployable unit of software that provides code and needed dependencies) in a multi-owner, multi-tenant environment. A multi-tenant orchestrator may be used to perform key management, trust anchor management, and other security functions related to the provisioning and lifecycle of the trusted ‘slice’ concept in FIG. **15**. For instance, an Edge computing system may be configured to fulfill requests and responses for various client endpoints from multiple virtual Edge instances (and, from a cloud or remote data center). The use of these virtual Edge instances may support multiple tenants and multiple applications (e.g., augmented reality (AR)/virtual reality (VR), enterprise applications, content delivery, gaming, compute offload, etc.) simultaneously. Further, there may be multiple types of applications within the virtual Edge instances (e.g., normal applications; latency sensitive applications; latency-critical applications; user plane applications; networking applications; etc.). The virtual Edge instances may also be spanned across systems of multiple owners at different geographic locations (or, respective computing systems and resources which are co-owned or co-managed by multiple owners).

(276) For instance, each Edge node **1522**, **1524** may implement the use of containers, such as with the use of a container “pod” **1526**, **1528** providing a group of one or more containers. In a setting that uses one or more container pods, a pod controller or orchestrator is responsible for local control and orchestration of the containers in the pod. Various Edge node resources (e.g., storage, compute, services, depicted with hexagons) provided for the respective Edge slices **1532**, **1534** are partitioned according to the needs of each container.

(277) With the use of container pods, a pod controller oversees the partitioning and allocation of containers and resources. The pod controller receives instructions from an orchestrator (e.g., orchestrator **1560**) that instructs the controller on how best to partition physical resources and for what duration, such as by receiving key performance indicator (KPI) targets based on SLA contracts. The pod controller determines which container requires which resources and for how long in order to complete the workload and satisfy the SLA. The pod controller also manages container lifecycle operations such as: creating the container, provisioning it with resources and

applications, coordinating intermediate results between multiple containers working on a distributed application together, dismantling containers when workload completes, and the like. Additionally, the pod controller may serve a security role that prevents assignment of resources until the right tenant authenticates or prevents provisioning of data or a workload to a container until an attestation result is satisfied.

(278) Also, with the use of container pods, tenant boundaries can still exist but in the context of each pod of containers. If each tenant specific pod has a tenant specific pod controller, there will be a shared pod controller that consolidates resource allocation requests to avoid typical resource starvation situations. Further controls may be provided to ensure attestation and trustworthiness of the pod and pod controller. For instance, the orchestrator **1560** may provision an attestation verification policy to local pod controllers that perform attestation verification. If an attestation satisfies a policy for a first tenant pod controller but not a second tenant pod controller, then the second pod could be migrated to a different Edge node that does satisfy it. Alternatively, the first pod may be allowed to execute and a different shared pod controller is installed and invoked prior to the second pod executing.

(279) FIG. **16** depicts an example of an infrastructure processing unit (IPU) **1600**. In some examples, the IPU **1600** can effectuate and/or otherwise facilitate proactive and/or adaptive data management and analytics as described herein. Different examples of IPU's disclosed herein enable improved performance, management, security and coordination functions between entities (e.g., cloud service providers), and enable infrastructure offload and/or communications coordination functions. As disclosed in further detail below, IPU's may be integrated with smart NICs and storage or memory (e.g., on a same die, system on chip (SoC), or connected dies) that are located at on-premises systems, base stations, gateways, neighborhood central offices, and so forth. Different examples of one or more IPU's disclosed herein can perform an application including any number of microservices, where each microservice runs in its own process and communicates using protocols (e.g., an HTTP resource API, message service or gRPC). Microservices can be independently deployed using centralized management of these services. A management system may be written in different programming languages and use different data storage technologies.

(280) Furthermore, one or more IPU's can execute platform management, networking stack processing operations, security (crypto) operations, storage software, identity and key management, telemetry, logging, monitoring and service mesh (e.g., control how different microservices communicate with one another). The IPU can access an xPU to offload performance of various tasks. For instance, an IPU exposes xPU, storage, memory, and CPU resources and capabilities as a service that can be accessed by other microservices for function composition. This can improve performance and reduce data movement and latency. An IPU can perform capabilities such as those of a router, load balancer, firewall, TCP/reliable transport, a service mesh (e.g., proxy or API gateway), security, data-transformation, authentication, quality of service (QoS), security, telemetry measurement, event logging, initiating and managing data flows, data placement, or job scheduling of resources on an xPU, storage, memory, or CPU.

(281) In the illustrated example of FIG. **16**, the IPU **1600** includes or otherwise accesses secure resource managing circuitry **1602**, network interface controller (NIC) circuitry **1604**, security and root of trust circuitry **1606**, resource composition circuitry **1608**, time stamp managing circuitry **1610**, memory and storage **1612**, processing circuitry **1614**, accelerator circuitry **1616**, and/or translator circuitry **1618**. Any number and/or combination of other structure(s) can be used such as but not limited to compression and encryption circuitry **1620**, memory management and translation unit circuitry **1622**, compute fabric data switching circuitry **1624**, security policy enforcing circuitry **1626**, device virtualizing circuitry **1628**, telemetry, tracing, logging and monitoring circuitry **1630**, quality of service circuitry **1632**, searching circuitry **1634**, network functioning circuitry (e.g., routing, firewall, load balancing, network address translating (NAT), etc.) **1636**, reliable transporting, ordering, retransmission, congestion controlling circuitry **1638**, and high

availability, fault handling and migration circuitry **1640** shown in FIG. **16**. Different examples can use one or more structures (components) of the example IPU **1600** together or separately. For example, compression and encryption circuitry **1620** can be used as a separate service or chained as part of a data flow with vSwitch and packet encryption.

(282) In some examples, the IPU **1600** includes a field programmable gate array (FPGA) **1670** structured to receive commands from an CPU, XPU, or application via an API and perform commands/tasks on behalf of the CPU, including workload management and offload or accelerator operations. The illustrated example of FIG. **16** may include any number of FPGAs configured and/or otherwise structured to perform any operations of any IPU described herein.

(283) Example compute fabric circuitry **1650** provides connectivity to a local host or device (e.g., server or device (e.g., xPU, memory, or storage device)). Connectivity with a local host or device or smartNIC or another IPU is, in some examples, provided using one or more of peripheral component interconnect express (PCIe), ARM AXI, Intel® QuickPath Interconnect (QPI), Intel® Ultra Path Interconnect (UPI), Intel® On-Chip System Fabric (IOSF), Omnipath, Ethernet, Compute Express Link (CXL), HyperTransport, NVLink, Advanced Microcontroller Bus Architecture (AMBA) interconnect, OpenCAPI, Gen-Z, CCIX, Infinity Fabric (IF), and so forth. Different examples of the host connectivity provide symmetric memory and caching to enable equal peering between CPU, XPU, and IPU (e.g., via CXL.cache and CXL.mem).

(284) Example media interfacing circuitry **1660** provides connectivity to a remote smartNIC or another IPU or service via a network medium or fabric. This can be provided over any type of network media (e.g., wired or wireless) and using any protocol (e.g., Ethernet, InfiniBand, Fiber channel, ATM, to name a few).

(285) In some examples, instead of the server/CPU being the primary component managing IPU **1600**, IPU **1600** is a root of a system (e.g., rack of servers or data center) and manages compute resources (e.g., CPU, xPU, storage, memory, other IPUs, and so forth) in the IPU **1600** and outside of the IPU **1600**. Different operations of an IPU are described below.

(286) In some examples, the IPU **1600** performs orchestration to decide which hardware or software is to execute a workload based on available resources (e.g., services and devices) and considers service level agreements and latencies, to determine whether resources (e.g., CPU, xPU, storage, memory, etc.) are to be allocated from the local host or from a remote host or pooled resource. In examples when the IPU **1600** is selected to perform a workload, secure resource managing circuitry **1602** offloads work to a CPU, xPU, or other device and the IPU **1600** accelerates connectivity of distributed runtimes, reduce latency, CPU and increases reliability.

(287) In some examples, secure resource managing circuitry **1602** runs a service mesh to decide what resource is to execute workload, and provide for L7 (application layer) and remote procedure call (RPC) traffic to bypass kernel altogether so that a user space application can communicate directly with the example IPU **1600** (e.g., the IPU **1600** and application can share a memory space). In some examples, a service mesh is a configurable, low-latency infrastructure layer designed to handle communication among application microservices using application programming interfaces (APIs) (e.g., over remote procedure calls (RPCs)). The example service mesh provides fast, reliable, and secure communication among containerized or virtualized application infrastructure services. The service mesh can provide critical capabilities including, but not limited to service discovery, load balancing, encryption, observability, traceability, authentication and authorization, and support for the circuit breaker pattern.

(288) In some examples, infrastructure services include a composite node created by an IPU at or after a workload from an application is received. In some cases, the composite node includes access to hardware devices, software using APIs, RPCs, gRPCs, or communications protocols with instructions such as, but not limited, to iSCSI, NVMe-oF, or CXL.

(289) In some cases, the example IPU **1600** dynamically selects itself to run a given workload (e.g., microservice) within a composable infrastructure including an IPU, xPU, CPU, storage, memory,

and other devices in a node.

(290) In some examples, communications transit through media interfacing circuitry **1660** of the example IPU **1600** through a NIC/smartNIC (for cross node communications) or loopback back to a local service on the same host. Communications through the example media interfacing circuitry **1660** of the example IPU **1600** to another IPU can then use shared memory support transport between xPUs switched through the local IPU. Use of IPU-to-IPU communication can reduce latency and jitter through ingress scheduling of messages and work processing based on service level objective (SLO).

(291) For example, for a request to a database application that requires a response, the example IPU **1600** prioritizes its processing to minimize the stalling of the requesting application. In some examples, the IPU **1600** schedules the prioritized message request issuing the event to execute a SQL query database and the example IPU constructs microservices that issue SQL queries and the queries are sent to the appropriate devices or services.

(292) Flowcharts representative of example hardware logic circuitry, machine-readable instructions, hardware implemented state machines, and/or any combination thereof for implementing the example ADM system **100** of FIG. **1**, the example data routing manager **302A-I** of FIG. **3**, and/or the example data routing management circuitry **400** of FIG. **4** are shown in FIGS. **17-40**. The machine-readable instructions may be one or more executable programs or portion(s) of an executable program for execution by processor circuitry, such as the processor circuitry **4112** shown in the example processor platform **4100** discussed below in connection with FIG. **41**, the processor circuitry **4212** shown in the example processor platform **4200** discussed below in connection with FIG. **42**, and/or the processor circuitry of FIGS. **43** and/or **44**. The program may be embodied in software stored on one or more non-transitory computer readable storage media such as a CD, a floppy disk, a hard disk drive (HDD), a solid-state drive (SSD), a DVD, a Blu-ray disk, a volatile memory (e.g., Random Access Memory (RAM) of any type, etc.), or a non-volatile memory (e.g., electrically erasable programmable read-only memory (EEPROM), FLASH memory, an HDD, an SSD, etc.) associated with processor circuitry located in one or more hardware devices, but the entire program and/or parts thereof could alternatively be executed by one or more hardware devices other than the processor circuitry and/or embodied in firmware or dedicated hardware. The machine-readable instructions may be distributed across multiple hardware devices and/or executed by two or more hardware devices (e.g., a server and a client hardware device). For example, the client hardware device may be implemented by an endpoint client hardware device (e.g., a hardware device associated with a user) or an intermediate client hardware device (e.g., a radio access network (RAN)) gateway that may facilitate communication between a server and an endpoint client hardware device). Similarly, the non-transitory computer readable storage media may include one or more mediums located in one or more hardware devices. Further, although the example program is described with reference to the flowcharts illustrated in FIGS. **17-40**, many other methods of implementing the example ADM system **100** of FIG. **1**, the example data routing manager **302A-I** of FIG. **3**, and/or the example data routing management circuitry **400** of FIG. **4** may alternatively be used. For example, the order of execution of the blocks may be changed, and/or some of the blocks described may be changed, eliminated, or combined. Additionally or alternatively, any or all of the blocks may be implemented by one or more hardware circuits (e.g., processor circuitry, discrete and/or integrated analog and/or digital circuitry, an FPGA, an ASIC, a comparator, an operational-amplifier (op-amp), a logic circuit, etc.) structured to perform the corresponding operation without executing software or firmware. The processor circuitry may be distributed in different network locations and/or local to one or more hardware devices (e.g., a single-core processor (e.g., a single core central processor unit (CPU)), a multi-core processor (e.g., a multi-core CPU), etc.) in a single machine, multiple processors distributed across multiple servers of a server rack, multiple processors distributed across one or more server racks, a CPU and/or a FPGA located in the same package (e.g., the same integrated

circuit (IC) package or in two or more separate housings, etc.).

(293) The machine-readable instructions described herein may be stored in one or more of a compressed format, an encrypted format, a fragmented format, a compiled format, an executable format, a packaged format, etc. machine-readable instructions as described herein may be stored as data or a data structure (e.g., as portions of instructions, code, representations of code, etc.) that may be utilized to create, manufacture, and/or produce machine executable instructions. For example, the machine-readable instructions may be fragmented and stored on one or more storage devices and/or computing devices (e.g., servers) located at the same or different locations of a network or collection of networks (e.g., in the cloud, in edge devices, etc.). The machine-readable instructions may require one or more of installation, modification, adaptation, updating, combining, supplementing, configuring, decryption, decompression, unpacking, distribution, reassignment, compilation, etc., in order to make them directly readable, interpretable, and/or executable by a computing device and/or other machine. For example, the machine-readable instructions may be stored in multiple parts, which are individually compressed, encrypted, and/or stored on separate computing devices, wherein the parts when decrypted, decompressed, and/or combined form a set of machine executable instructions that implement one or more operations that may together form a program such as that described herein.

(294) In another example, the machine-readable instructions may be stored in a state in which they may be read by processor circuitry, but require addition of a library (e.g., a dynamic link library (DLL)), a software development kit (SDK), an application programming interface (API), etc., in order to execute the machine-readable instructions on a particular computing device or other device. In another example, the machine-readable instructions may need to be configured (e.g., settings stored, data input, network addresses recorded, etc.) before the machine-readable instructions and/or the corresponding program(s) can be executed in whole or in part. Thus, machine-readable media, as used herein, may include machine-readable instructions and/or program(s) regardless of the particular format or state of the machine-readable instructions and/or program(s) when stored or otherwise at rest or in transit.

(295) The machine-readable instructions described herein can be represented by any past, present, or future instruction language, scripting language, programming language, etc. For example, the machine-readable instructions may be represented using any of the following languages: C, C++, Java, C#, Perl, Python, JavaScript, HyperText Markup Language (HTML), Structured Query Language (SQL), Swift, etc.

(296) As mentioned above, the example operations of FIGS. **17-40** may be implemented using executable instructions (e.g., computer and/or machine-readable instructions) stored on one or more non-transitory computer and/or machine-readable media such as optical storage devices, magnetic storage devices, an HDD, a flash memory, a read-only memory (ROM), a CD, a DVD, a cache, a RAM of any type, a register, and/or any other storage device or storage disk in which information is stored for any duration (e.g., for extended time periods, permanently, for brief instances, for temporarily buffering, and/or for caching of the information). As used herein, the terms non-transitory computer readable medium, non-transitory computer readable storage medium, non-transitory machine-readable medium, and non-transitory machine-readable storage medium are expressly defined to include any type of computer readable storage device and/or storage disk and to exclude propagating signals and to exclude transmission media. As used herein, the terms “computer readable storage device” and “machine readable storage device” are defined to include any physical (mechanical and/or electrical) structure to store information, but to exclude propagating signals and to exclude transmission media. Examples of computer readable storage devices and machine-readable storage devices include random access memory of any type, read only memory of any type, solid state memory, flash memory, optical discs, magnetic disks, disk drives, and/or redundant array of independent disks (RAID) systems. As used herein, the term “device” refers to physical structure such as mechanical and/or electrical equipment, hardware,

and/or circuitry that may or may not be configured by computer readable instructions, machine-readable instructions, etc., and/or manufactured to execute computer readable instructions, machine-readable instructions, etc.

(297) “Including” and “comprising” (and all forms and tenses thereof) are used herein to be open ended terms. Thus, whenever a claim employs any form of “include” or “comprise” (e.g., comprises, includes, comprising, including, having, etc.) as a preamble or within a claim recitation of any kind, it is to be understood that additional elements, terms, etc., may be present without falling outside the scope of the corresponding claim or recitation. As used herein, when the phrase “at least” is used as the transition term in, for example, a preamble of a claim, it is open-ended in the same manner as the term “comprising” and “including” are open ended. The term “and/or” when used, for example, in a form such as A, B, and/or C refers to any combination or subset of A, B, C such as (1) A alone, (2) B alone, (3) C alone, (4) A with B, (5) A with C, (6) B with C, or (7) A with B and with C. As used herein in the context of describing structures, components, items, objects and/or things, the phrase “at least one of A and B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, or (3) at least one A and at least one B. Similarly, as used herein in the context of describing structures, components, items, objects and/or things, the phrase “at least one of A or B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, or (3) at least one A and at least one B. As used herein in the context of describing the performance or execution of processes, instructions, actions, activities and/or steps, the phrase “at least one of A and B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, or (3) at least one A and at least one B. Similarly, as used herein in the context of describing the performance or execution of processes, instructions, actions, activities and/or steps, the phrase “at least one of A or B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, or (3) at least one A and at least one B.

(298) As used herein, singular references (e.g., “a”, “an”, “first”, “second”, etc.) do not exclude a plurality. The term “a” or “an” object, as used herein, refers to one or more of that object. The terms “a” (or “an”), “one or more”, and “at least one” are used interchangeably herein.

Furthermore, although individually listed, a plurality of means, elements or method actions may be implemented by, e.g., the same entity or object. Additionally, although individual features may be included in different examples or claims, these may possibly be combined, and the inclusion in different examples or claims does not imply that a combination of features is not feasible and/or advantageous.

(299) FIG. 17 is a flowchart representative of example machine-readable instructions and/or example operations 1700 that may be executed and/or instantiated by processor circuitry to implement the ADM system 100 of FIG. 1, the data routing manager 302A-I of FIG. 3, and/or the data routing management circuitry 400 of FIG. 4 to generate an example recommendation to integrate a hardware, software, and/or firmware feature in a semiconductor-based device (e.g., a silicon-based device). For example, the machine-readable instructions and/or the operations 1700 of FIG. 17 can be executed by the ADM system 100 of FIG. 1, or portion(s) thereof, the data routing manager 302A-I of FIG. 3, the example data routing management circuitry 400 of FIG. 4, and/or any other hardware, software, and/or firmware disclosed herein.

(300) The example machine-readable instructions and/or the example operations 1700 of FIG. 17 begin at block 1702, at which a candidate algorithm (e.g., an AI/ML algorithm) is identified. At block 1704, a business impact of the candidate algorithm may be quantified. At block 1706, end-to-end use case(s) that may utilize the candidate algorithm are defined. At block 1708, current and future candidate platforms that may be utilized for the end-to-end use case(s) may be identified. At block 1710, target key performance indicators (KPIs) may be defined and technical benchmarking may be implemented at block 1712. At block 1714, potential changes to a semiconductor-based device may be identified and computer-aided design (e.g., CAD, UCAD, etc.) experiments may be

conducted at block **1716**. At block **1718**, an impact of different hypotheses are quantified, which may result in generating a semiconductor-device based recommendation at block **1720**. For example, a recommendation to change (e.g., add, remove, and/or modify) hardware, software, and/or firmware associated with a semiconductor-based device may be generated at block **1720**. In some examples, the semiconductor-based device may be manufactured based on the recommendation. In some examples, the manufactured semiconductor-based device may execute and/or otherwise implement the candidate algorithm identified at block **1702** using hardware, software, and/or firmware of the manufactured semiconductor-based device.

(301) FIG. **18** is a flowchart representative of example machine-readable instructions and/or example operations **1800** that may be executed and/or instantiated by processor circuitry to implement the ADM system **100** of FIG. **1**, the data routing manager **302A-I** of FIG. **3**, and/or the data routing management circuitry **400** of FIG. **4** to analyze ingested data in a network. The example machine-readable instructions and/or the example operations **1800** of FIG. **18** begin at block **1802**, at which the ADM system **100** of FIG. **1** identifies node(s) in a network environment.

(302) At block **1804**, the ADM system **100** identifies one(s) of the node(s) as data subscribers. For example, the node manager **122** can identify one or more nodes based on the preferred nodes table **124**. In some examples, the data publishing manager **118** can identify one(s) of the one or more nodes as subscribing for data updates, alerts, indications, etc. In some examples, the data publishing manager **118** can consult the scheduler **120** to determine which one(s) of the one or more nodes are data subscribers.

(303) At block **1806**, the ADM system **100** ingests data from data source(s). For example, the data ingestion manager **106** can obtain data from the data sources **104**. In some examples, the pre-processing manager **108** can pre-process the ingested data.

(304) At block **1808**, the ADM system **100** enforces data access policies based on the data. For example, the data security manager **132** can enforce the access policies. In some examples, the data security manager **132** can implement one or more security operations in connection with a data requester, data that is being requested, access to components of the ADM system **100**, etc., and/or combination(s) thereof based on the access policies.

(305) At block **1810**, the ADM system **100** assigns metadata to portion(s) of the data. For example, the metadata/data enrichment manager **140** can add, remove, and/or modify metadata associated with portion(s) of the data. In some examples, the metadata/data enrichment manager **140** can store the metadata in the metadata datastore **146**.

(306) At block **1812**, the ADM system **100** executes Artificial Intelligence/Machine-Learning algorithm(s) on the data. For example, the AMR **134** can identify one(s) of the algorithms **138** to apply to the data. In some examples, the analytics manager **136** can execute the identified one(s) of the algorithms **138** on the data, or portion(s) thereof, to implement data classification, clustering, etc., operation(s) to generate recommendations, identify action(s) to carry out, generate alert(s), etc., and/or any combination(s) thereof.

(307) At block **1814**, the ADM system **100** identifies portion(s) of the data to store in a distributed datastore. For example, the data ingestion manager **106** can identify portion(s) of the ingested data to be stored in the raw datastore **148** (e.g., record in cold storage, hot storage, etc.). In some examples, the data ingestion manager **106** can consult the data query manager **110** and/or the analytics manager **136** to determine whether portion(s) of the data is/are to be stored in the distributed datastore **144**.

(308) At block **1816**, the ADM system **100** determines whether to generate alert(s). For example, the AMR **134** can invoke the analytics manager **136** to execute one(s) of the algorithms **138** to determine whether an alert is to be generated. In some examples, the alert can be a predictive alert associated with an event yet to occur, an immediate alert associated with an imminent or ongoing event, etc., and/or combination(s) thereof.

(309) If, at block **1816**, the ADM system **100** determines not to generate an alert, control proceeds

to block **1820** to determine whether to continue monitoring for new data to ingest. Otherwise, control proceeds to block **1818**. At block **1808**, the ADM system **100** propagates alert(s) to appropriate user(s) based on the portion(s) of the data. For example, the data publishing manager **118** can identify one or more users, one or more devices associated with the one or more users, etc., to which alert(s) is/are to be propagated, distributed, and/or otherwise provided to.

(310) At block **1820**, the ADM system **100** determines whether to continue monitoring for new data to ingest. If, at block **1820**, the ADM system **100** determines to continue monitoring for new data to ingest, control returns to block **1802**. Otherwise, the example machine-readable instructions and/or the example operations **1800** of FIG. **18** conclude.

(311) FIG. **19** is a flowchart representative of example machine-readable instructions and/or example operations **1900** that may be executed and/or instantiated by processor circuitry to implement the ADM system **100** of FIG. **1**, the data routing manager **302A-I** of FIG. **3**, and/or the data routing management circuitry **400** of FIG. **4** to analyze ingested data in a network. The example machine-readable instructions and/or the example operations **1900** of FIG. **19** begin at block **1902**, at which the ADM system **100** of FIG. **1** generates data graph(s) associated with data from disparate data sources in an environment. For example, the analytics manager **136** can instantiate, invoke, etc., the one(s) of the algorithms **138** to generate a new data graph (e.g., a data graph model, a contextual data graph model, etc.) based on data (e.g., control data, sensor data, corporate and/or organizational data, etc., from one(s) of the data sources **104** of FIG. **1** that may be of different types) in an environment (e.g., the environment **200** of FIG. **2**) and/or identify an existing data graph based on the data as described herein. In some examples, the analytics manager **136** can instantiate, invoke, etc., one(s) of the algorithms **138** to identify one or more portions of the data to be stored in a datastore, such as the distributed datastore **144**, as described herein. For example, the analytics manager **136** can determine to store the one or more portions of the data in hot storage, warm storage, or cold storage based on a data retention policy, which may be implemented using output(s) from the one(s) of the algorithms **138**, as described herein. For example, the analytics manager **136** can use the one(s) of the algorithms **138** to predict at least one of an access frequency or a use frequency of the first data object by user(s) of the environment based on a data retention policy. In some examples, the analytics manager **136** can cause storage of the first data object in hot storage, warm storage, or cold storage based on the data retention policy.

(312) In some examples, the analytics manager **136** obtains metadata from the metadata datastore **146** using the data plane **128** to be utilized in a generation of a data graph. The metadata can include one or more second portions of second metadata associated with a second data object and one or more third portions of third metadata associated with a third data object. In some examples, the third metadata includes one or more of the portion(s) of the second metadata. In some examples, the second metadata and the third metadata are associated with each other based on the portion(s) of the second metadata that are included in the second metadata and the third metadata. In some examples, the analytics manager **136** obtains the second data object from the raw datastore **148** using the data plane **128**. In some examples, the analytics manager **136** generates a primary data graph node based on the second data object. For example, the second data object, or an identifier or reference to the second data object, can be the primary data graph node. In some examples, the analytics manager **136** generates a first strength vector to connect the primary data graph node to portion(s) of the second metadata. In some examples, the analytics manager **136** generates a second strength vector to connect the primary data graph node to portion(s) of the third metadata. In some examples, the analytics manager **136** generates the data graph based on at least one of the primary data graph node, the first strength vector, and the second strength vector. In some examples, the analytics manager **136** stores the data graph in the distributed datastore **144**.

(313) In some examples, the first data object includes a first lexical term and the second data object includes a second lexical term. In some examples, the analytics manager **136** is to, in response to a determination that a strength of a vector (e.g., the first strength vector, the second strength vector,

etc.) in the data graph to connect a first portion of the first metadata to a second portion of the second metadata satisfies a threshold, generate an association of the first lexical term and the second lexical term. In some examples, the analytics manager **136** can cause storage of the association in the distributed datastore **144**. For example, the association can be accessed by electronic devices in the environment or a different environment.

(314) At block **1904**, the ADM system **100** extracts a first data object from ingested data. For example, the data ingestion manager **106** can ingest data, which can include one or more data objects, from one(s) of the data sources **104** as described herein. In some examples, the data object can be a data file (e.g., a manufacturing report associated with a completion of an assembly, a supply chain purchase order, a spreadsheet, etc.), a sensor data object (e.g., data describing a controller that generated data, data representative of a sensor and a sensor measurement sensed by the sensor, etc.), audio data, text data, image data, video data, etc., and/or any combination(s) thereof as described herein.

(315) In some examples, the first data object is a first instance of the data object. In some examples, the data ingestion manager **106** and/or the data query manager **110** locate a second instance of the first data object in the raw datastore **148** of the distributed datastore **144**. In some examples, the first instance has one or more first values and the second instance to have one or more second values. In some examples, the analytics manager **136** can determine whether a correlation error based on a comparison of the one or more first values and the one or more second values satisfies a threshold. In some examples, the analytics manager **136**, in response to a determination that the correlation error satisfies the threshold, can apply an error correction value to the first instance to reduce the correlation error, and expire the second instance. For example, the raw datastore **148** can age, expire, and/or otherwise cause the second instance to be removed from the environment immediately or over a period of time.

(316) At block **1906**, the ADM system **100** tags a first portion of the first data object with first metadata. For example, the data ingestion manager **106** and/or the data query manager **110** can tag a portion of the first data object with first metadata based on an environment of the one(s) of the data sources **104** and/or a type of one(s) of the data sources **104** that generated the first data object as described herein.

(317) At block **1908**, the ADM system **100** identifies a second data object and second metadata in a distributed datastore based on at least a partial match of the first metadata and the second metadata. For example, the data query manager **110** and/or the analytics manager **136** can identify a match (e.g., a partial match, a complete match, a substantial match, etc.) of first portion(s) of the first metadata to second portion(s) of second metadata. In some examples, the metadata datastore **146** can store the second metadata and association(s) of the second metadata with a second data object. In some examples, the raw datastore **148** can store the second data object. In some examples, the first portion and the second portion may be coupled and/or otherwise graphically connected or linked in a data graph as described herein.

(318) In some examples, the first strength vector has a vector length and an angle with respect to a reference axis. For example, the vector length can be representative of a strength of association between the one of the one or more second portions of the second metadata and the second data object. In some examples, the first angle can be representative of a first probability that a first event associated with the one of the one or more second portions of the second metadata is to precede or follow a second event associated with the second data object.

(319) At block **1910**, the ADM system **100** augments portion(s) of the second metadata based on portion(s) of the first metadata to output enriched second metadata in a data graph. For example, the analytics manager **136** can direct, instruct, and/or otherwise cause the metadata/data enrichment manager **140** to augment the second metadata by adding and/or otherwise connecting one(s) of the first portion(s) of the first metadata to one(s) of the second portion(s) of the second metadata in a data graph (e.g., a data graph including connection(s) to link the first metadata and the second

metadata). In some examples, the metadata/data enrichment manager **140** can augment the second metadata by writing and/or otherwise including the one(s) of the first portion(s) of the first metadata into one or more data entries of the second metadata. In some examples, the metadata/data enrichment manager **140** can enrich the second metadata in response to execution of one or more machine-learning models with the first data object, the second data object, the first metadata, and/or the second metadata as data input(s) to the one or more machine-learning models. In some examples, the metadata/data enrichment manager **140** can enrich the second metadata by removing and/or otherwise deleting portion(s) of the first metadata from the second metadata. In some examples, the metadata/data enrichment manager **140** can enrich the second metadata by removing and/or otherwise deleting portion(s) of the second metadata that is/are determined to not be as relevant as once determined and/or observed, not useful for determining decisions, outputs, etc., and/or any combination(s) thereof. Advantageously, the metadata/data enrichment manager **140** can make subsequent queries for the first data object, the second data object, etc., more enriching and/or otherwise more relevant or useful to a data requester by identifying other data object(s) that have strong or substantially relevant association(s) to the first data object, the second data object, etc., by linking the one(s) of the first portion(s) of the first metadata to one(s) of the second portion(s) of the second metadata.

(320) At block **1912**, the ADM system **100** identifies a partial match of the first metadata to the second metadata associated with a node in a preferred nodes table. For example, the analytics manager **136** can identify a match, such as a partial match, of the first metadata to second metadata associated with a node, such as the first endpoint device **832**, or a user associated thereof. In some examples, the analytics manager **136** can provide the identification of the node to the node manager **122**. In some examples, the node manager **122** can search and/or query the preferred nodes table **124** to determine whether the node is included in the preferred nodes table **124**.

(321) At block **1914**, the ADM system **100** enforces a data access policy in connection with the first data object. For example, the data security manager **132** can determine that the second metadata includes a description of, a pointer to, a reference to, etc., a data access policy as described herein. In some examples, the data security manager **132** can determine whether the node identified by the second metadata is allowed access to the first data object (and/or similar or other relevant data to the first data object) based on the data access policy as described herein. In response to a determination by the data security manager **132** that the node does not have access to the first data object based on the data access policy, the data security manager **132** can enforce the data access policy by denying the node access to the first data object. For example, the data security manager **132** can instruct the data query manager **110** to deny the node access to the first data object as described herein. In some examples, the data security manager **132** can direct the data publishing manager **118** to not publish the first data object for access by the node. In some examples, in response to a determination that the node has access to the first data object based on the data access policy, the data security manager **132** can enforce the data access policy causing the first data object to be published for access by the node. For example, the data security manager **132** can instruct the data query manager **110** to grant the node access to the first data object as described herein. In some examples, the data publishing manager **118** can publish the first data object for access by the node as described herein. For example, the data publishing manager **118** can encrypt the first data object using an encryption key that the node possesses as described herein.

(322) At block **1916**, the ADM system **100** identifies an electronic device in the environment to access one(s) of the first or second data objects. For example, the node manager **122** can search the metadata datastore **146** using the second metadata as search input(s) to identify one or more electronic devices as search output(s) or result(s). In some examples, the node manager **122** can search the preferred nodes table **124** using the second metadata as search input(s) to identify one or more electronic devices as search output(s) or result(s). For example, the node manager **122** can identify an electronic device, such as the first endpoint device **832**, referenced by the second

metadata.

(323) At block **1918**, the ADM system **100** publishes at least one of the first data object or a second data object for access by the electronic device. For example, the data publishing manager **118** can publish at least one of the first data object or the second data object for access by the first endpoint device **832**.

(324) In some examples, the analytics manager **136** can identify one or more nodes representative of logical entities in the environment based on the data graph. For example, the analytics manager **136** can identify the one or more nodes based on a relevancy score associated with the one or more nodes and the first data object. In some examples, the node manager **122** can determine whether the one or more nodes are included in the preferred nodes table **124**. In some examples, the data publishing manager **118** can publish the first data object for access by the one or more nodes in response to a determination that the one or more nodes are included in the preferred nodes table **124**. In some examples, a score can be implemented using data. For example, the score may itself be data. For example, the score can be implemented using a value (e.g., a binary value, an alphanumeric value, etc.) that may be stored in a mass storage device, memory, etc. In some examples, a score can be implemented using any type of mathematical representation. For example, a score can be a probability or likelihood having a value in a particular range, such as from **0** to **1** (or any other range of values). In some examples, a score can be a value from a distribution, such as a probability distribution, a normal distribution, a logarithmic distribution, etc., or any other type of distribution. In some examples, a score can be a mathematical representation such as a ratio, a proportion, a percentage, a fraction, etc., or any other type of mathematical representation to describe a relationship between two components, elements, etc.

(325) At block **1920**, the ADM system **100** determines whether to generate and/or update a data graph and/or continue monitoring for new data to ingest. For example, the data ingestion manager **106** can determine whether to continue monitoring for data (e.g., new data including one or more data objects) that is created, generated, and/or otherwise made available by the one(s) of the data sources **104** as described herein. In some examples, the analytics manager **136** can determine whether to generate a new data graph and/or update an existing data graph based on feedback data (e.g., a user acknowledging a relevancy of the first and/or second data object presented to the user, an event that occurred after a publishing of the first and/or second data object, etc., and/or any combination(s) thereof. If, at block **1920**, the ADM system **100** determines to generate and/or update a data graph and/or continue monitoring for new data to ingest at block **1920**, control returns to block **1902**. Otherwise, the example machine-readable instructions and/or the example operations **1900** of FIG. **19** conclude.

(326) FIG. **20** is a flowchart representative of example machine-readable instructions and/or example operations **2000** that may be executed and/or instantiated by processor circuitry to implement the ADM system **100** of FIG. **1**, the data routing manager **302A-I** of FIG. **3**, and/or the data routing management circuitry **400** of FIG. **4** to route a message to user(s). The example machine-readable instructions and/or the example operations **2000** of FIG. **20** begin at block **2002**, at which the data routing management circuitry **400** generates a message with metadata based on data received at a first node. For example, the data query management circuitry **430** can generate a message including the metadata **464** that describes data received (or generated) at a first node, such as the first data routing manager **302A**. In some examples, the data can be patient data (e.g., in a medical facility) such as a medical test result (e.g., an X-ray scan, a blood test, etc.), vehicle data (e.g., in an automotive manufacturing factory) such as a completion of a vehicle part, etc. In some examples, the metadata **464** can be a patient name, a doctor, a wing of a hospital in which the patient is being treated, etc. In some examples, the metadata **464** can be a serial number of a vehicle being manufactured, a location of the vehicle, etc.

(327) At block **2004**, the data routing management circuitry **400** queries second node(s) for first user(s) associated with the metadata. For example, the data publishing circuitry **450** can query

one(s) of the data routing managers **302A-I** for one(s) of the users **310, 312, 314, 316, 318, 320** associated with the metadata.

(328) At block **2006**, the data routing management circuitry **400** generates a list based on the first user(s), the list including a second user. For example, the node management circuitry **440** can generate a list of users including the first user **310** and the second user **312** that are associated with the metadata. For example, the first user **310** can be the nurse, doctor, surgeon, etc., treating the patient. In some examples, the second user **312** can be an oncologist, an X-ray technician, etc., treating the patient. In some examples, the first user **310** can be a supervisor on a factory floor, a technician on the factory floor, etc. In some examples, the second user **312** can be a supply chain engineer, a sales representative, etc., associated with the vehicle.

(329) At block **2008**, the data routing management circuitry **400** generates with a machine-learning model a relevancy score for the second user based on an association of the second user and the metadata. For example, the machine-learning circuitry **420** can execute and/or instantiate the machine-learning models **470** using the list of the users as model inputs to generate model outputs. In some examples, the model outputs can include a relevancy score for a respective one of the first user **310** and the second user **312**. For example, the relevancy score for the first user **310** and the second user **312** can be correlated to a strength of association of the metadata with respective metadata of the first user **310** and the second user **312**.

(330) At block **2010**, the data routing management circuitry **400** determines whether the relevancy score satisfies a threshold. For example, the machine-learning circuitry **420** can determine that a first relevancy score of 0.9 (e.g., a probability of 0.9, a 90% likelihood, etc.) for the first user **310** satisfies a relevancy score threshold of 0.8 because the first relevancy score of 0.9 is greater than or equal to 0.8. In some examples, the machine-learning circuitry **420** can determine that a second relevancy score of 0.4 (e.g., a probability of 0.4, a 40% likelihood, etc.) for the second user **312** does not satisfy the relevancy score threshold of 0.8 because the second relevancy score of 0.4 is less than 0.8.

(331) If, at block **2010**, the data routing management circuitry **400** determines that the relevancy score does not satisfy the threshold, the example machine-readable instructions and/or the example operations **2000** of FIG. **20** conclude. If, at block **2010**, the data routing management circuitry **400** determines that the relevancy score satisfies the threshold, then, at block **2012**, the data routing management circuitry **400** delivers the message to the second user. For example, the data publishing circuitry **450** can transmit the message to the first user **310** by way of the network **322**. In some examples, the first electronic device **324** can present the message to the first user **310** by speaking the message through a speaker of the first electronic device **324**. In some examples, the data routing management circuitry **400** can publish the message to a server from which data subscribers, such as the fourth data routing manager **302D**, can identify the message as being addressed to the first user **310** and thereby retrieving the message for presenting to the first user **310** by way of the first electronic device **324**. In response to delivering the message to the second user at block **2012**, the example machine-readable instructions and/or the example operations **2000** of FIG. **20** conclude.

(332) FIG. **21** is another flowchart representative of example machine-readable instructions and/or example operations **2100** that may be executed and/or instantiated by processor circuitry to implement the ADM system **100** of FIG. **1**, the data routing manager **302A-I** of FIG. **3**, and/or the data routing management circuitry **400** of FIG. **4** to route a message to user(s). The example machine-readable instructions and/or the example operations **2100** of FIG. **21** begin at block **2102**, at which the data routing management circuitry **400** generates a message with metadata based on data received at a first node. For example, the data query management circuitry **430** can generate a message including the metadata **464** that describes data received (or generated) at a first node, such as the ninth data routing manager **302I**. In some examples, the metadata included in or with the message can be first metadata. In some examples, the data can be financial data (e.g., the network

environment **304** is a corporate or commercial office) such as invoices (e.g., sale invoices, service invoices, expense receipts, etc.), inventory data (e.g., the network environment **304** is a warehouse) such as shipping manifests, bills of lading, etc. In some examples, the metadata **464** can describe and/or include an identifier of a corporate officer, an accountant, a floor of an office building in which the financial data is generated, etc. In some examples, the metadata **464** can reference and/or include a license plate of a truck to transport a pallet of goods, a location of the pallet of goods, a truck driver associated with the license plate or the truck, etc.

(333) At block **2104**, the data routing management circuitry **400** generates a list of users associated with the first node or second node(s). For example, the node management circuitry **440** can generate a list of users including the third user **314**, the fourth user **316**, and the fifth user **318** that are associated with the metadata. For example, the third user **314** can be the corporate officer associated with the financial data, the fourth user **316** can be an accountant associated with the financial data, and the fifth user **318** can be an IT professional on the floor of the corporate office on which the financial data is generated. In some examples, the corporate officer can be associated with second metadata, the accountant can be associated with third metadata, and/or the IT professional can be associated with fourth metadata. In some examples, the third user **314** can be a warehouse supervisor, the fourth user **316** can be a forklift operator, and the fifth user **318** can be a truck driver associated with the warehouse. For example, the warehouse supervisor can be associated with fifth metadata, the forklift operator can be associated with sixth metadata, and/or the truck driver can be associated with seventh metadata. In some examples, one(s) of the second through seventh metadata can be implemented using the metadata **1002**.

(334) At block **2106**, the data routing management circuitry **400** ranks the list based on a relevancy score for a respective one of the users. For the node management circuitry **440** can rank the third user **314**, the fourth user **316**, and the fifth user **318** based on their respective relevancy score for the metadata. In some examples, a first relevancy score of the third user **314** can be based on matching portion(s) of the first metadata and the second metadata (or the fifth metadata). In some examples, a second relevancy score of the fourth user **316** can be based on matching portion(s) of the first metadata and the third metadata (or the sixth metadata). In some examples, a third relevancy score of the fifth user **318** can be based on matching portion(s) of the first metadata and the fourth metadata (or the seventh metadata).

(335) At block **2108**, the data routing management circuitry **400** identifies a set of the users of the list as having a relevancy score that satisfies a threshold. For example, the node management circuitry **440** can determine that the third user **314** has a relevancy score of 0.85, the fourth user **316** has a relevancy score of 0.92, and the fifth user **318** has a relevancy score of 0.18. In some examples, the node management circuitry **440** can identify the third user **314** and the fourth user **316** as having a relevancy score that satisfies a threshold of 0.75 because 0.85 and 0.92 are greater than or equal to the threshold.

(336) At block **2110**, the data routing management circuitry **400** delivers the message to the set of the users. For example, the data publishing circuitry **450** can deliver, transmit, and/or otherwise provide the message to the third user **314** and the fourth user **316** by way of the network **322**. In some examples, the sixth data routing manager **302F** and the seventh data routing manager **302G** can apply local node customization data to the message to improve and/or otherwise optimize the presentation of the message. For example, the sixth data routing manager **302F** can apply local node customization data by removing graphics from the message to emphasize text-based data on the third electronic device **328**. In some examples, the seventh data routing manager **302G** can resize and/or reorient graphics of the message to surround a current application window that the fourth user **316** is using on the fourth electronic device **330**. In some examples, the local node customization data can be implemented using portion(s) of one(s) of the second through seventh metadata.

(337) At block **2112**, the data routing management circuitry **400** updates relevancy score(s) for

responsive user(s) and/or non-responsive user(s). For example, the third user **314** may ignore the message while the fourth user **316** responds to the message (e.g., the fourth user **316** taps the message on the fourth electronic device **330** to increase the size of the message, electronically engaging with the message by editing the message, copying the message, saving the message, responding with a reply message, etc.). In some examples, the machine-learning circuitry **420** can decrease the relevancy score of the third user **314**. For example, the machine-learning circuitry **420** can decrease the relevancy score associated with portion(s) of the second metadata (or the fifth metadata) that matched portion(s) of the first metadata because the third user **314** ignored the message. In some examples, the machine-learning circuitry **420** can increase or maintain the relevancy score of the fourth user **316** because the fourth user **316** engaged with and/or responded to the message. For example, the machine-learning circuitry **420** can increase the relevancy score associated with portion(s) of the third metadata (or the sixth metadata) that matched portion(s) of the first metadata because the fourth user **316** acknowledged in some manner that the message is relevant to the fourth user **316** (e.g., relevant to interest(s) of the fourth user **316**).

(338) At block **2114**, the data routing management circuitry **400** penalizes metadata that identified non-responsive user(s) based on a level of busyness determined by sensor data. For example, the machine-learning circuitry **420** can analyze sensor data (e.g., video data from a video camera that has the third user **314** in a field of view of the video camera), activity information (e.g., hardware, software, and/or firmware utilization of the third electronic device **328**), etc., and/or any combination(s) thereof. In some examples, in response to determining that the third user **314** is not busy based on the sensor data and/or the activity information, the machine-learning circuitry **420** can penalize (e.g., remove, modify, alter, change, etc.) the second metadata (or the fifth metadata) associated with the third user **314** that matched a portion of the first metadata of the message. In some examples, in response to determining that the third user **314** is busy based on the sensor data and/or the activity information, the machine-learning circuitry **420** may not penalize the second metadata (or the fifth metadata) associated with the third user **314** that matched a portion of the first metadata of the message.

(339) At block **2116**, the data routing management circuitry **400** provides updated metadata to the second node(s). For example, the data publishing circuitry **450** can provide updated metadata (e.g., updated version(s) of the second (or fifth) metadata that has been penalized) associated with the third user **314** to neighboring nodes of the ninth data routing manager **302I**, such as one(s) of the other data routing managers **302A-I**. In some examples, the data publishing circuitry **450** provides the updated metadata to the neighboring nodes to synchronize the updated metadata with metadata associated with the third user **314** that is stored at the neighboring nodes (e.g., to improve AI/ML learning capabilities at the neighboring nodes by using updated metadata).

(340) At block **2118**, the data routing management circuitry **400** determines whether there is another message to be generated. If, at block **2118**, the data routing management circuitry **400** determines that another message is to be generated, control returns to block **2102**. Otherwise, the example machine-readable instructions and/or the example operations **2100** of FIG. **21** conclude.

(341) FIG. **22** is a flowchart representative of example machine-readable instructions and/or example operations **2200** that may be executed and/or instantiated by processor circuitry to implement the ADM system **100** of FIG. **1**, the data routing manager **302A-I** of FIG. **3**, and/or the data routing management circuitry **400** of FIG. **4** to present a message to user(s). The example machine-readable instructions and/or the example operations **2200** of FIG. **22** begin at block **2202**, at which the data routing management circuitry **400** instantiates a machine-learning microservice to analyze received data. For example, the machine-learning circuitry **420** can execute and/or instantiate a machine-learning microservice based on one(s) of the machine-learning models **470**. In some examples, the machine-learning circuitry **420** can provide ingested data at a node as input(s) to the machine-learning microservice.

(342) At block **2204**, the data routing management circuitry **400** determines whether the data

indicates action is required. For example, the machine-learning circuitry **420** can determine, based on output(s) from the machine-learning microservice, that the received data is associated with an event, such as the first event **924** of FIGS. **9B-9C**.

(343) If, at block **2204**, the data routing management circuitry **400** determines that the data does not indicate action is required, control proceeds to block **2206**. At block **2206**, the data routing management circuitry **400** publishes the data to data subscriber(s). For example, the data publishing circuitry **450** can publish the ingested data to one or more nodes associated with metadata of the ingested data. After publishing the data to data subscriber(s) at block **2206**, control proceeds to block **2218**.

(344) If, at block **2204**, the data routing management circuitry **400** determines that the data indicates action is required, control proceeds to block **2208**. At block **2208**, the data routing management circuitry **400** determines whether the data indicates feedback is requested from user(s). For example, the machine-learning circuitry **420** can determine, based on the outputs from the machine-learning microservice, that the ingested data requires feedback from one or more nodes, users, devices, etc.

(345) If, at block **2208**, the data routing management circuitry **400** determines that the data indicates feedback is requested from user(s), control proceeds to block **2210**. At block **2210**, the data routing management circuitry **400** generates a message including metadata to the user(s) to solicit the feedback. For example, the data query management circuitry **430** can generate a message, which can include the metadata **464**. In some examples, the data query management circuitry **430** can generate the message to be routed to one or more users, nodes, etc.

(346) After generating the message at block **2210**, control proceeds to block **2212**. At block **2212**, the data routing management circuitry **400** updates the metadata based on the feedback to update user score(s). For example, the machine-learning circuitry **420** can update the metadata **464** based on the feedback (e.g., indications of whether the message is relevant) from the one or more users, nodes, etc. After updating the metadata at block **2212**, control proceeds to block **2218**.

(347) If, at block **2208**, the data routing management circuitry **400** determines that the data indicates feedback is not requested from user(s), control proceeds to block **2214**. At block **2214**, the data routing management circuitry **400** generates a message including metadata to user(s) to solicit action. For example, the data query management circuitry **430** can generate a message, which can include the metadata **464**. In some examples, the data query management circuitry **430** can generate the message to be routed to one or more users, nodes, etc., to cause the one or more users, nodes, etc., to perform an activity, action, operation, task, etc., associated with the received data.

(348) After generating the message at block **2214**, control proceeds to block **2216**. At block **2216**, the data routing management circuitry **400** modifies the metadata based on response(s) and/or non-response(s) to update user score(s). For example, the machine-learning circuitry **420** can increase a user score associated with a user, node, etc., based on a determination that the feedback from the user, node, etc., indicates that the message is relevant to the user, node, etc.

(349) At block **2218**, the data routing management circuitry **400** determines whether additional data is received. For example, the data ingestion circuitry **410** can determine whether to continue monitoring a network environment for data to ingest, analyze, etc.

(350) If, at block **2218**, the data routing management circuitry **400** determines that additional data is received, control returns to block **2202**. Otherwise, the example machine-readable instructions and/or the example operations **2200** of FIG. **22** conclude.

(351) FIG. **23** is a flowchart representative of example machine-readable instructions and/or example operations **2300** that may be executed and/or instantiated by processor circuitry to implement the ADM system **100** of FIG. **1**, the data routing manager **302A-I** of FIG. **3**, and/or the data routing management circuitry **400** of FIG. **4** to present a message to user(s) based on activity information associated with the user(s). The example machine-readable instructions and/or the example operations **2300** of FIG. **23** begin at block **2302**, at which the data routing management

circuitry **400** ingests data at a node. For example, the data ingestion circuitry **410** can ingest data generated by one(s) of the data producers **306**.

(352) At block **2304**, the data routing management circuitry **400** determines whether the data indicates a message is to be provided to a user. For example, the machine-learning circuitry **420** can determine, based on one or more data objects, portions, etc., included in the message, that the one or more data objects, portions, etc., is/are to be presented and/or otherwise provided to a user, such as the second user **312**. In some examples, the machine-learning circuitry **420** can determine to present the one or more data objects, portions, etc., to the second user **312** based on first metadata associated with the one or more data objects, portions, etc., that correlate with second metadata associated with the second user **312**.

(353) If, at block **2304**, the data routing management circuitry **400** determines that the data does not indicate that a message is to be provided to a user, control proceeds to block **2320**. Otherwise, control proceeds to block **2306**. At block **2306**, the data routing management circuitry **400** determines whether the message is an alert requiring immediate attention. For example, the machine-learning circuitry **420** can determine that the message is an alert generated by a programmable logic controller (PLC) controlling and/or otherwise monitoring heavy machinery (e.g., a robotic arm, a crane, an electric motor drive, etc.) in the network environment **304**. In some examples, the heavy machinery can be associated with the second user **314** (e.g., the second user **314** is a technician whose job function is to maintain the heavy machinery that caused the alarm).

(354) If, at block **2306**, data routing management circuitry **400** determines that the message is an alert requiring immediate attention control proceeds to block **2312**. Otherwise, control proceeds to block **2308**. At block **2308**, the data routing management circuitry **400** requests activity information of an electronic device associated with the user. For example, the data query management circuitry **430** can ping the fifth data routing manager **302E** for activity information of the second electronic device **326**, which can include resource utilization data, an identification of application(s) and/or service(s) in operation on the second electronic device **326**, etc.

(355) At block **2310**, the data routing management circuitry **400** determines whether the activity information indicates that the user is executing a time-sensitive task. For example, the machine-learning circuitry **420** can provide the activity information to the machine-learning model **470** to generate model output(s), which can include a determination of whether the second user **312** is busy executing a time-sensitive task (e.g., mitigating an alarm from different heavy machinery).

(356) If, at block **2310**, the data routing management circuitry **400** determines that the activity information indicates that the user is executing a time-sensitive task, control returns to block **2308** to request (e.g., periodically or iteratively request) activity information of the electronic device associated with the user in an effort to determine when the second user **312** is no longer busy and/or otherwise available to be presented with the message.

(357) If, at block **2310**, the data routing management circuitry **400** determines that the activity information indicates that the user is not executing a time-sensitive task, control proceeds to block **2312**. At block **2312**, the data routing management circuitry **400** transmits the message including metadata to user(s). For example, the data publishing circuitry **450** can deliver, via the network **322**, the message including metadata associated with the message.

(358) At block **2314**, the data routing management circuitry **400** determines whether the user(s) initiated an action in response to the message. For example, the data ingestion circuitry **410** can receive an acknowledgement that the message is relevant to the second user **312**, a response message indicating that an action is being carried out (or has been carried out) by the second user **312**. In some examples, the response message can be generated by the PLC indicating that a fault of the heavy machinery that caused the alarm has been resolved, mitigated, fixed, etc.

(359) If, at block **2314**, the data routing management circuitry **400** determines that the user(s) initiated an action in response to the message, control proceeds to block **2316**. At block **2316**, the data routing management circuitry **400** updates metadata associated with the user(s) to increase

user relevancy score(s). For example, the machine-learning circuitry **420** can provide the acknowledgment, the response message, etc., to the machine-learning models **470** to generate model output(s), which can include an increase in a relevancy score representative of the relevancy of the metadata of the message with metadata associated with the second user **312**. In response to updating the metadata associated with the user(s) to increase user relevancy score(s) at block **2316**, control proceeds to block **2320**.

(360) If, at block **2314**, the data routing management circuitry **400** determines that the user(s) did not initiate an action in response to the message, control proceeds to block **2318**. At block **2318**, the data routing management circuitry **400** updates metadata associated with the user(s) to decrease user relevancy score(s). For example, the machine-learning circuitry **420** can provide data to the machine-learning model **470** indicative of the second user **312** ignoring the message, acknowledging that the message is not relevant to the second user **312** (e.g., the heavy machinery is in a different department than the department the second user **312** belongs to, etc.) to generate model output(s), which can include a decrease in a relevancy score representative of the relevancy of the metadata of the message with metadata associated with the second user **312**. In response to updating the metadata associated with the user(s) to decrease user relevancy score(s) at block **2318**, control proceeds to block **2320**.

(361) At block **2320**, the data routing management circuitry **400** determines whether additional data is received. For example, the data ingestion circuitry **410** can determine that there is additional data to ingest from one(s) of the data producers **306**. If, at block **2320**, the data routing management circuitry **400** determines that additional data is received, control returns to block **2302**. Otherwise, the example machine-readable instructions and/or the example operations **2300** of FIG. **23** conclude.

(362) FIG. **24** is a flowchart representative of example machine-readable instructions and/or example operations **2400** that may be executed and/or instantiated by processor circuitry to implement the ADM system **100** of FIG. **1**, the data routing manager **302A-I** of FIG. **3**, and/or the data routing management circuitry **400** of FIG. **4** to escalate presentation of a message to user(s). The example machine-readable instructions and/or the example operations **2400** begin at block **2402**, at which the data routing management circuitry **400** generates a message including metadata to be delivered to users. For example, the data query management circuitry **430** can generate a message (e.g., one or more data packets) associated with a medical patient in a medical facility (e.g., a hospital). In some examples, the message includes and/or otherwise is representative of medical test results (e.g., a magnetic resonance imaging (MRI) scan, a blood test result, etc.) associated with the medical patient. In some examples, the message is intended to be delivered to a medical doctor treating the medical patient.

(363) At block **2404**, the data routing management circuitry **400** selects a user to process. For example, the node management circuitry **440** can select the first user **310** to process. In some examples, the first user **310** is a medical doctor treating the medical patient.

(364) At block **2406**, the data routing management circuitry **400** executes a machine-learning model to determine an authorization score for the user. For example, the machine-learning circuitry **420** can execute and/or instantiate the machine-learning models **470** to determine an authorization score for the first user **310**. In some examples, the machine-learning circuitry **420** can provide portion(s) of the message to the machine-learning models **470** as model input(s) to generate model output(s), which can include an authorization score of 0.9 for the first user **310**. For example, the first user **310** can have an authorization score of 0.9 because the message is highly likely (e.g., a 90% likelihood) to be relevant to the medical doctor treating the medical patient.

(365) At block **2408**, the data routing management circuitry **400** determines whether the authorization score satisfies a threshold. For example, the machine-learning circuitry **420** can determine that the authorization score of 0.9 for the first user **310** satisfies an authorization score threshold of 0.85 because the authorization score of 0.9 is greater than or equal to the authorization

score threshold of 0.85

(366) If, at block **2408**, the data routing management circuitry **400** determines that the authorization score does not satisfy a threshold, control proceeds to block **2420**. For example, the first user **310** may not be authorized based on the authorization score of the first user **310** to access the message (e.g., the medical patient is not being treated by the first user **310**).

(367) If, at block **2408**, the data routing management circuitry **400** determines that the authorization score satisfies a threshold, control proceeds to block **2410**. At block **2410**, the data routing management circuitry **400** executes the machine-learning model to determine a relevancy score for the user. For example, the machine-learning circuitry **420** can execute and/or instantiate the machine-learning models **470** to determine a relevancy score associated with the first user **310** for the message. In some examples, the machine-learning model **470** can output a relevancy score of 0.95 associated with the first user **310** for the message because the first user **310** is substantially likely to find the medical test result for the medical patient being treated by the first user **310** as substantially or materially relevant.

(368) At block **2412**, the data routing management circuitry **400** determines whether the relevancy score satisfies a threshold. For example, the machine-learning circuitry **420** can determine that the relevancy score of 0.95 for the first user **310** for the message satisfies a relevancy score threshold of 0.80 because the relevancy score of 0.95 is greater than or equal to the relevancy score threshold of 0.80.

(369) If, at block **2412**, the data routing management circuitry **400** determines that the relevancy score does not satisfy a threshold, control proceeds to block **2420**. For example, the machine-learning circuitry **420** can determine that the first user **310** may not find the medical test result relevant (e.g., the medical patient is not being treated by the first user **310**).

(370) If, at block **2412**, the data routing management circuitry **400** determines that the relevancy score satisfies a threshold, control proceeds to block **2414**. At block **2414**, the data routing management circuitry **400** executes the machine-learning model to determine a confidence score. For example, the machine-learning circuitry **420** can invoke the machine-learning models **470** to generate model output(s) based on at least one of the authorization score or the relevancy score as model input(s). In some examples, the model output(s) can include a confidence score representative of a likelihood, probability, etc., that at least one of the authorization score or the relevancy score are accurate or are likely to cause a satisfactory result.

(371) At block **2416**, the data routing management circuitry **400** delivers the message to the user. For example, the data publishing circuitry **450** can provide, deliver, and/or otherwise cause transmission of the message to the first user **310** by way of the network **322**.

(372) At block **2418**, the data routing management circuitry **400** updates at least one of the relevancy score or the confidence score based on message user interaction. For example, in response to the first user **310** engaging with the message (e.g., by reviewing the medical test result, executing an action such as scheduling another medical test or discharging the patient in response to the message, etc.), the machine-learning circuitry **420** can provide feedback to the machine-learning models **470** to affirm the confidence score (or increase the confidence score). In some examples, in response to the first user **310** engaging with the message, the machine-learning circuitry **420** can provide feedback from the first user **310** to the machine-learning models **470** to increase (or maintain) the relevancy score associated with the first user **310** for the message (or portion(s) thereof). In some examples, in response to the first user **310** ignoring the message, the machine-learning circuitry **420** can provide feedback (e.g., the ignoring of the message) to the machine-learning models **470** to decrease at least one of the authorization score or the relevancy score because the first user **310** ignored the message.

(373) At block **2420**, the data routing management circuitry **400** determines whether to select another user to process. For example, the node management circuitry **440** can determine to select the second user **312** (or a different user) to process. If, at block **2420**, the data routing management

circuitry **400** determines to select another user to process, control returns to block **2404**. Otherwise, the example machine-readable instructions and/or the example operations **2400** of FIG. **24** conclude.

(374) FIG. **25** is a flowchart representative of example machine-readable instructions and/or example operations **2500** that may be executed and/or instantiated by processor circuitry to implement the ADM system **100** of FIG. **1**, the data routing manager **302A-I** of FIG. **3**, and/or the data routing management circuitry **400** of FIG. **4** to augment a data object to present to a user based on metadata associated with the user. The example machine-readable instructions and/or example operations **2500** of FIG. **25** begin at block **2502**, at which the data routing management circuitry **400** obtains data at a node. For example, the data ingestion circuitry **410** can obtain a data packet, a message (e.g., a data message), or any other implementation of data generation from one(s) of the data producers **306**. In some examples, the data ingestion circuitry **410** can be part of the fifth data routing manager **302E**.

(375) At block **2504**, the data routing management circuitry **400** extracts a data object from the data. For example, the data ingestion circuitry **410** can determine that an obtained data packet includes a header (e.g., a data header, a packet header, a data packet header, etc.) and a payload (e.g., a data payload, a packet payload, a data packet payload, etc.), which can include one or more portions of data, such as audio, image, text, and/or video data. In some examples, the data ingestion circuitry **410** can extract a portion of data from the payload as a data object.

(376) At block **2506**, the data routing management circuitry **400** applies local node customization data to the data object to generate an augmented data object, and the local node customization data based on metadata associated with a user. For example, the data query management circuitry **430** can identify the data object as data to be used to render and/or otherwise generate a graphic (e.g., a graph, a plot, an image, etc.). In some examples, the data query management circuitry **430** can be part of the fifth data routing manager **302E**. For example, the data query management circuitry **430** can optimize display of the graphic on the second electronic device **326** based on metadata associated with the second user **312**. In some examples, the metadata associated with the second user **312** can indicate that the second user **312** prefers to view bar graphs rather than scatter plots. For example, the data query management circuitry **430** can instantiate the graphic as a bar graph to increase a likelihood that the second user **312** will engage with the graphic and/or otherwise find the graphic relevant.

(377) At block **2508**, the data routing management circuitry **400** presents the augmented data object to the user. For example, the data publishing circuitry **450** can present the data object as a bar graph to the second user **312** on the second electronic device **326**.

(378) At block **2510**, the data routing management circuitry **400** determines whether the user acknowledged that a portion of the augmented data object is relevant to the user. For example, the data ingestion circuitry **410** can determine whether the second user **312** identified one or more portions of the data object as relevant. In some examples, the data ingestion circuitry **410** can receive data indicative that the second user **312** identified a first portion of the data object as relevant, a second portion of the data object as not relevant, etc., and/or any combination(s) thereof.

(379) If, at block **2510**, the data routing management circuitry **400** determines that the user did acknowledge that a portion of the augmented data object is relevant to the user, control proceeds to block **2512**. At block **2512**, the data routing management circuitry **400** modifies the metadata to associate relevant portion(s) of the data object with the user. For example, the machine-learning circuitry **420** can provide an acknowledgement from the second user **312** that the first portion of the data object is relevant to the machine-learning models **470** as model input(s) to generate model output(s). In some examples, the model output(s) can include an increased relevancy score associated with the second user **312** for the first portion of the data object.

(380) At block **2514**, the data routing management circuitry **400** modifies the metadata to disassociate non-relevant portion(s) of the data object with the user. For example, the machine-

learning circuitry **420** can provide an acknowledgement from the second user **312** that the second portion of the data object is not relevant to the machine-learning model **470** as model input(s) to generate model output(s). In some examples, the model output(s) can include a decreased relevancy score associated with the second user **312** for the second portion of the data object. For example, the machine-learning models **470** can output modified metadata for the second user **312** that removes a portion of the metadata that correlated with the second portion of the data object. In response to modifying the metadata to disassociate non-relevant portion(s) of the data object from the user at block **2514**, control proceeds to block **2518**.

(381) If, at block **2510**, the data routing management circuitry **400** determines that the user did not acknowledge that a portion of the augmented data object is relevant to the user, control proceeds to block **2516**. At block **2516**, the data routing management circuitry **400** penalizes the metadata associated with the user. For example, the machine-learning circuitry **420** can obtain an acknowledgement from the second user **312** that portion(s) of the data object is/are not relevant. In some examples, the machine-learning circuitry **420** can provide the acknowledgment (or an indicia of a lack of acknowledgment because the second user **312** may have ignored the data object) to the machine-learning models **470** as model input(s) to generate model output(s). In some examples, the model output(s) can include revised or updated metadata for the second user **312** that removes a portion of the metadata that correlated with the portion(s) of the data object. In response to penalizing the metadata associated with the user at block **2516**, control proceeds to block **2518**.

(382) At block **2518**, the data routing management circuitry **400** determines whether another message is obtained at the node. For example, the data ingestion circuitry **410** can determine whether another data packet, message, or any other implementation of data generation is obtained from one(s) of the data producers **306**. If, at block **2518**, the data routing management circuitry **400** determines that another message is obtained at the node, control returns to block **2502**. Otherwise, the example machine-readable instructions and/or the example operations **2500** of FIG. **25** conclude.

(383) FIG. **26** is a flowchart representative of example machine-readable instructions and/or example operations **2600** that may be executed and/or instantiated by processor circuitry to implement the ADM system **100** of FIG. **1**, the data routing manager **302A-I** of FIG. **3**, and/or the data routing management circuitry **400** of FIG. **4** to adjust metadata associated with a user. The example machine-readable instructions and/or example operations **2600** begin at block **2602**, at which the data routing management circuitry **400** presents a message to a user having a relevancy score associated with a topic. For example, the data publishing circuitry **450** can present a message, which can include audio, visual (e.g., image and/or video data), and/or text data, to the fourth user **316** using the fourth electronic device **330**. In some examples, the fourth user **316** is a supervisor for an automobile manufacturing assembly line and, more specifically, an engine assembly line. For example, the message can be associated with a topic of engine assembly.

(384) At block **2604**, the data routing management circuitry **400** determines whether the user affirmed a relevancy of the message to the user. For example, the fourth user **316** can acknowledge receipt of the message and/or acknowledge that the message includes data that the fourth user **316** finds relevant. In some examples, the data ingestion circuitry **410** can receive the acknowledgment(s) and provide the acknowledgment(s) (and/or associated data) to the machine-learning circuitry **420**.

(385) If, at block **2604**, the data routing management circuitry **400** determines that the user did not affirm a relevancy of the message to the user, control proceeds to block **2608**. At block **2608**, the data routing management circuitry **400** decreases a relevancy score of the topic associated with the user. For example, if the message has a topic of automobile infotainment system and the fourth user **316** ignored the message, then the machine-learning circuitry **420** can determine that the relevancy score for the message having the topic of automobile infotainment system is to be reduced and/or otherwise decreased. Advantageously, by reducing the relevancy score for the message having the

topic of automobile infotainment system, the fourth user **316** can receive subsequent messages that are more relevant to the fourth user **316**, such as messages having the topic of engine assembly. In response to decreasing the relevancy score of the topic associated with the user at block **2608**, control proceeds to block **2610**.

(386) If, at block **2604**, the data routing management circuitry **400** determines that the user did affirm a relevancy of the message to the user, control proceeds to block **2606**. At block **2606**, the data routing management circuitry **400** increases a relevancy score of the topic associated with the user. For example, if the message has a topic of engine assembly and the fourth user **316** engaged with and/or otherwise acknowledged a relevancy of the message, then the machine-learning circuitry **420** can determine that the relevancy score for the message having the topic of engine assembly is to be increased (or maintained). Advantageously, by increasing the relevancy score for the message having the topic of engine assembly, the fourth user **316** can receive subsequent messages that are more relevant to the fourth user **316**, such as messages having the topic of engine assembly, or related topics such as transmission assembly, radiator assembly, etc. In response to increasing the relevancy score of the topic associated with the user at block **2606**, control proceeds to block **2610**.

(387) At block **2610**, the data routing management circuitry **400** determines whether the relevancy score of the topic satisfies a threshold. For example, the machine-learning circuitry **420** can determine whether the fourth user **316** is an expert, such as a stakeholder, a technical lead or expert, a subject matter expert, etc., based on a relevancy score of the topic for the fourth user **316**. In some examples, the machine-learning circuitry **420** can determine that a relevancy score of 0.92 of the topic of engine assembly for the fourth user **316** is greater than a threshold (e.g., a relevancy score threshold) of 0.8, which can be indicative of the fourth user **316** being an expert on the topic of engine assembly.

(388) If, at block **2610**, the data routing management circuitry **400** determines that the relevancy score of the topic does not satisfy a threshold, control proceeds to block **2614**. If, at block **2610**, the data routing management circuitry **400** determines that the relevancy score of the topic satisfies a threshold, control proceeds to block **2612**. At block **2612**, the data routing management circuitry **400** identifies the user as an expert. For example, the node management circuitry **440** can identify the fourth user **316** as an expert on the topic of engine assembly based on the relevancy score of 0.92 satisfying the threshold of 0.8. Advantageously, the node management circuitry **440** can identify the fourth user **316** to be part of a list of users whom messages having the topic of engine assembly are to be routed for presentation. Advantageously, the node management circuitry **440** can identify the fourth user **316** to be part of the list of users in response to a determination the fourth user **316** is an expert in connection with the topic of engine assembly.

(389) At block **2614**, the data routing management circuitry **400** determines whether a location of the user changed. For example, the data ingestion circuitry **410** can ingest video data from a video camera. In some examples, the data ingestion circuitry **410** can invoke the machine-learning circuitry **420** to execute the machine-learning models **470** to identify users in a location (e.g., Zone 1, Floor 1 of a factory). For example, the data ingestion circuitry **410** can determine whether the fourth user **316** is in the location, has left the location, or has not been in the location longer than a specified time duration (e.g., a day, a week, a month, etc.) based on output(s) from the machine-learning model **470**.

(390) If, at block **2614**, the data routing management circuitry **400** determines that the location of the user did not change, control proceeds to block **2618**. If, at block **2614**, the data routing management circuitry **400** determines that the location of the user did change, control proceeds to block **2616**. At block **2616**, the data routing management circuitry **400** updates the relevancy score based on the location of the user using sensor data. For example, the machine-learning circuitry **420** can determine that the location of Zone 1, Floor 1 of the factory is for engine assembly. In some examples, the machine-learning circuitry **420** can increase a relevancy score of the topic of

engine assembly for the fourth user **316** in response to determining that the fourth user **316** is identified (e.g., based on sensor data such as video data from a video camera) as being in the location proximate the engine assembly area. In response to updating the relevancy score based on the location of the user using sensor data at block **2616**, control proceeds to block **2618**.

(391) At block **2618**, the data routing management circuitry **400** determines whether a difference between first data of the message and second data satisfies a threshold. For example, the data query management circuitry **430** can determine whether first data of the message is different from second data, which may be stored on the fourth electronic device **330** or elsewhere (e.g., different one(s) of the electronic devices **324**, **326**, **328**, **330**, **332**, **334**, one(s) of the data producers **306**, one(s) of the data consumers **308**, a datastore associated with the network environment **304**, etc., and/or any combination(s) thereof). In some examples, the data query management circuitry **430** can proceed with the determination in an effort to determine whether the first data of the message is cumulative, repetitive, redundant, etc., with respect to the second data.

(392) If, at block **2618**, the data routing management circuitry **400** determines that a difference between first data of the message and second data does not satisfy a threshold, control proceeds to block **2622**. If, at block **2618**, the data routing management circuitry **400** determines that a difference between first data of the message and second data satisfies a threshold, control proceeds to block **2620**. At block **2620**, the data routing management circuitry **400** ages non-updated data by at least one of expiring the non-updated data or remove portion of metadata. For example, the data query management circuitry **430** can age the second data by expiring the second data (e.g., delete the second data from one or more datastores, reduce an availability or storage redundancy of the second data, etc.). In some examples, the data query management circuitry **430** can age the second data by removing portion(s) of metadata of the second data that correlate to, correspond to, match etc., portion(s) of metadata associated with the fourth user **316**.

(393) At block **2622**, the data routing management circuitry **400** determines whether another message is to be presented to the user. For example, the data publishing circuitry **450** can determine that another message is to be presented to the fourth user **316**. If, at block **2622**, the data routing management circuitry **400** determines that another message is to be presented to the user, control returns to block **2602**. Otherwise, the example machine-readable instructions and/or the example operations **2600** of FIG. **26** conclude.

(394) FIG. **27** is a flowchart representative of example machine-readable instructions and/or example operations **2700** that may be executed and/or instantiated by processor circuitry to implement the ADM system **100** of FIG. **1**, the data routing manager **302A-I** of FIG. **3**, and/or the data routing management circuitry **400** of FIG. **4** to train and/or retrain a machine-learning model. The example machine-readable instructions and/or example operations **2700** begin at block **2702**, at which the data routing management circuitry **400** instantiates a machine-learning microservice to generate a machine-learning model based on data associated with an environment. For example, the machine-learning circuitry **420** can instantiate a microservice to generate one of the machine-learning models **470**, which can be a neural network or any other type of AI/ML model, based on data associated with the network environment **304**.

(395) At block **2704**, the data routing management circuitry **400** executes the machine-learning model to generate data graphs corresponding to respective portions of the environment. For example, the machine-learning circuitry **420** can cause the machine-learning model **470** to generate one(s) of the data graphs **802**, **804**, **806**, **808**, which can correspond to portions of the network environment **304**.

(396) At block **2706**, the data routing management circuitry **400** executes the machine-learning model to identify hotspots of at least one of expert nodes or stakeholder nodes. For example, the machine-learning circuitry **420** can cause the machine-learning model **470** to identify hotspot(s) of at least one of expert nodes (e.g., expert data graph nodes) or stakeholder nodes (e.g., stakeholder data graph nodes) of the data graphs **802**, **804**, **806**, **808**.

(397) At block **2708**, the data routing management circuitry **400** determines whether data traffic is received. For example, the data ingestion circuitry **410** can determine whether one or more messages is received at a node, which may be implemented using the first data routing manager **302A**, and/or, more generally, one(s) of the data producers **306**. If, at block **2708**, the data routing management circuitry **400** determines that data traffic is not received, control waits at block **2708** to make another determination whether data traffic is received.

(398) If, at block **2708**, the data routing management circuitry **400** determines that data traffic is received, control proceeds to block **2710**. At block **2710**, the data routing management circuitry **400** updates metadata associated with response(s) and non-response(s) to the data traffic. For example, the machine-learning circuitry **420** can update (e.g., add, delete, modify, etc.) metadata associated with the first user **310** in response to whether the first user **310** responded, ignored, and/or acknowledged the data traffic.

(399) At block **2712**, the data routing management circuitry **400** updates metadata associated with cause(s) of action(s) and effect(s) of the action(s) based on the data traffic. For example, the data ingestion circuitry **410** can receive data representative of one or more actions carried out by the first user **310** after the first user **310** received the data traffic. In some examples, the machine-learning circuitry **420** can provide the data representative of the one or more actions to the machine-learning model **470** as model input(s) to determine model output(s). For example, the model output(s) can include update(s) (e.g., addition(s), deletion(s), modification(s), etc.) to metadata associated with the first user **310** in response to whether the first user **310** performed one or more actions in response to being presented with the data traffic.

(400) At block **2714**, the data routing management circuitry **400** updates at least one of the data graphs or the hotspots based on the data traffic routing. For example, the machine-learning circuitry **420** can update one(s) of the data graphs **802**, **804**, **806**, **808**, hotspot(s) associated thereof, etc., and/or any combination(s) thereof, based on a routing of the data traffic. In some examples in which the user **810** of FIG. **8** is presented with data, the routing of the data traffic can include the user **810** forwarding and/or otherwise providing the data to USER B, who then may forward the data to USER E. In some examples, the machine-learning circuitry **420** can receive indications of the data forwarding and correspondingly update metadata associated with USER B and USER E to increase an association and/or relevancy of the data with USER B and USER E. Advantageously, in response to new data being generated that is related to the previous data, the machine-learning circuitry **420** can cause the new data to be delivered to USER B and/or USER E in addition to and/or alternatively to the user **810**.

(401) At block **2716**, the data routing management circuitry **400** identifies a stratification of nodes and super nodes based on the data traffic routing. For example, the machine-learning circuitry **420** can identify USER B as a node and USER F as a super node because USER F receives an increasing number of data forwards with respect to USER B and/or other one(s) of the users of FIG. **8**. Advantageously, in some examples, the node management circuitry **440** can identify super node(s), such as USER F, to receive a higher priority when determining who to present data to with respect to non-super nodes.

(402) At block **2718**, the data routing management circuitry **400** retrains the machine-learning model based on at least one of the update(s) or sensor data. For example, the machine-learning circuitry **420** can retrain and/or otherwise cause a retraining of the machine-learning model **470** based on the update(s) in connection with at least one of block **2710**, **2712**, **2714**, **2716**. In some examples, the machine-learning circuitry **420** can retrain and/or otherwise cause a retraining of the machine-learning model **470** based on sensor data associated with the first user **310**, such as video camera data, RFID pings, electronic terminal logins, etc., and/or any combination(s) thereof.

(403) At block **2720**, the data routing management circuitry **400** determines whether additional data traffic is received. For example, the data ingestion circuitry **410** can determine whether additional data traffic is received. If, at block **2720**, the data routing management circuitry **400** determines that

additional data traffic is received, control returns to block **2708**. Otherwise, the example machine-readable instructions and/or the example operations **2700** of FIG. **27** conclude.

(404) FIG. **28** is a flowchart representative of example machine-readable instructions and/or example operations **2800** that may be executed and/or instantiated by processor circuitry to implement the ADM system **100** of FIG. **1**, the data routing manager **302A-I** of FIG. **3**, and/or the data routing management circuitry **400** of FIG. **4** to persist a contextual data graph model in a shared datastore to be accessible by a node. The example machine-readable instructions and/or the example operations **2800** of FIG. **28** begin at block **2802**, at which the data routing management circuitry **400** tags a first data object generated at a first node with metadata based on an environment of the first node. For example, the data query management circuitry **430** can tag a first data object, which can be sensor data, generated by a first one of the robots **214**. In some examples, the data query management circuitry **430** can tag the first data object with the metadata **464** (e.g., generate an association of the first data object with the metadata **464**), which can include a make, model, vendor, manufacturer, serial number, etc., of the first one of the robots **214**.

(405) At block **2804**, the data routing management circuitry **400** identifies a contextual data graph model associated with the metadata. For example, the machine-learning circuitry **420** can identify (e.g., by executing one(s) of the machine-learning models **470**) a first one of the contextual data graph models **474** that corresponds to the first one of the robots **214**. In some examples, the machine-learning circuitry **420** can identify at least one of the first contextual data graph model **502** or the second contextual data graph model **504** that corresponds to the first one of the robots **214**.

(406) At block **2806**, the data routing management circuitry **400** determines a strength of association between the first data object and a second data object of the contextual data graph model. For example, the machine-learning circuitry **420** can determine (e.g., by executing the machine-learning model **470**) a strength of association of the primary node **506** of the first contextual data graph model **502** and a first node connected to the primary node **506** of the first contextual data graph model **502**. In some examples, the first node can be implemented with and/or otherwise representative of the first data object (and/or associated metadata) and the primary node **506** can be implemented with and/or otherwise representative of a second data object, such as sensor data generated by a second one of the robots **214** that may be co-located (and/or communicatively coupled) with the first one of the robots **214**. Example machine-readable instructions and/or the example operations that may be executed and/or instantiated by processor circuitry to implement block **2806** is described below in connection with FIG. **29**.

(407) At block **2808**, the data routing management circuitry **400** determines whether the strength of the association satisfies a threshold. For example, the machine-learning circuitry **420** can determine (e.g., by executing the one(s) of the machine-learning models **470**) whether a vector angle, length, placement, location, etc., satisfies a threshold (e.g., a similarity threshold, a strength or strength of association threshold, etc.). If, at block **2808**, the data routing management circuitry **400** determines that the strength of the association does not satisfy a threshold, the example machine-readable instructions and/or the example operations **2800** of FIG. **28** conclude. Otherwise, control proceeds to block **2810**.

(408) At block **2810**, the data routing management circuitry **400** updates the contextual data graph model based on the strength of the association. For example, the machine-learning circuitry **420** can modify or update (e.g., by executing the one(s) of the machine-learning models **470**) an angle, a length, a placement, a location, etc., of a vector connecting the first data object and the second data object or a different vector connecting the first data object to the first contextual data graph model **502** based on the strength of the association.

(409) At block **2812**, the data routing management circuitry **400** stores the contextual data graph model in a shared datastore to be accessible by a second node. For example, the data publishing circuitry **450** can push and/or otherwise publish update(s) to the first contextual data graph model **502** to be stored in a shared datastore, such as the distributed datastore **144** of FIG. **1**, to be

accessible by another node of the environment **200** of FIG. **2**, such as one of the industrial machines **216**, **218**, **220**, **222**. In response to persisting the contextual data graph model in a shared datastore to be accessible by a second node at block **2812**, the example machine-readable instructions and/or example operations **2800** of FIG. **28** conclude.

(410) FIG. **29** is a flowchart representative of example machine-readable instructions and/or example operations **2900** that may be executed and/or instantiated by processor circuitry to implement the ADM system **100** of FIG. **1**, the data routing manager **302A-I** of FIG. **3**, and/or the data routing management circuitry **400** of FIG. **4** to determine a strength of association between a first data object and a second data object of a contextual data graph model. In some examples, the machine-readable instructions and/or the operations **2900** of FIG. **29** can be executed and/or instantiated by processor circuitry to implement block **2806** of the machine-readable instructions and/or the operations **2800** of FIG. **28**.

(411) The example machine-readable instructions and/or the example operations **2900** of FIG. **29** begin at block **2902**, at which the data routing management circuitry **400** connects the first data object to the second data object using a vector in the contextual data graph model. For example, the machine-learning circuitry **420** can connect and/or otherwise identify a placement and/or orientation of a vector to be connected from a first data object to a second data object in the first contextual data graph model **502**. In some examples, the second data object can be implemented by the primary node **506** and the first data object can be implemented by the first adjacent node **510**.

(412) At block **2904**, the data routing management circuitry **400** determines an angle of the vector with respect to a reference axis. For example, the first contextual data graph model **502** can have one or more axes, such as an x-axis, a y-axis, a z-axis (in the case of a three-dimensional implementation), etc. In some examples, the machine-learning circuitry **420** can determine an angle of the vector connecting the primary node **506** and the first adjacent node **510**.

(413) At block **2906**, the data routing management circuitry **400** determines a length of the vector. For example, the machine-learning circuitry **420** can determine a length of the vector connecting the primary node **506** and the first adjacent node **510**.

(414) At block **2908**, the data routing management circuitry **400** determines the strength of the association based on at least one of the angle or the length of the vector. For example, the machine-learning circuitry **420** can determine the strength of the association between the first and second data objects based on quantifications of their relationship to each other in the first contextual data graph model **502**, which can include at least one of the angle or the length of the vector connecting the primary node **506** and the first adjacent node **510**. In response to determining the strength of the association based on at least one of the angle or the length of the vector at block **2908**, the example machine-readable instructions and/or the example operations **2900** of FIG. **29** conclude. For example, the machine-readable instructions and/or the example operations **2900** of FIG. **29** can return to block **2808** of the machine-readable instructions and/or the example operations **2800** of FIG. **28** to determine whether the strength of the association satisfies a threshold.

(415) FIG. **30** is a flowchart representative of example machine-readable instructions and/or example operations **3000** that may be executed and/or instantiated by processor circuitry to implement the ADM system **100** of FIG. **1**, the data routing manager **302A-I** of FIG. **3**, and/or the data routing management circuitry **400** of FIG. **4** to update one(s) of contextual data graph models based on correlation(s). The example machine-readable instructions and/or the example operations **3000** of FIG. **30** begin at block **3002**, at which the data routing management circuitry **400** selects a process in an environment. For example, the node management circuitry **440** can select the first process **602** in an environment, such as the environment **200** of FIG. **2**.

(416) At block **3004**, the data routing management circuitry **400** selects a node associated with the process. For example, the node management circuitry **440** can select a node, such as the first industrial machine **216** that is associated with the first process **602**.

(417) At block **3006**, the data routing management circuitry **400** generates a first contextual data

graph model based on first data associated with the node. For example, the machine-learning circuitry **420** can generate (e.g., by executing one(s) of the machine-learning models **470**) the first contextual data graph model **610** based on first data generated, ingested, and/or published by the first industrial machine **216** (e.g., a controller and/or sensor associated with the first industrial machine **216**).

(418) At block **3008**, the data routing management circuitry **400** generates a second contextual data graph model based on a sequence of events observed in the process. For example, the machine-learning circuitry **420** can generate (e.g., by executing the one(s) of the machine-learning models **470**) the second contextual data graph model **612** based on a sequence of events observed in the first process **602**, the second process **604**, etc., and/or, more generally, the event chain **600**.

(419) At block **3010**, the data routing management circuitry **400** generates a third contextual data graph model based on second data associated with the first data. For example, the machine-learning circuitry **420** can generate (e.g., by executing and/or instantiating the one(s) of the machine-learning models **470**) the third contextual data graph model **614** based on associated data objects (e.g., ancillary, auxiliary, etc., types of data objects) that can be frequently associated with or used in conjunction with the first data associated with the first industrial machine **216**.

(420) At block **3012**, the data routing management circuitry **400** stores the contextual data graph models at the node. For example, the data query management circuitry **430** can store at least one of the first contextual data graph model **610**, the second contextual data graph model **612**, or the third contextual data graph model **614** as one(s) of the contextual data graph models **474** of the datastore **460**. In some examples, the datastore **460** can be implemented using memory, one or more mass storage devices, etc., of the first industrial machine **216** (e.g., a controller and/or sensor associated with the first industrial machine **216**).

(421) At block **3014**, the data routing management circuitry **400** determines whether to select another node in the process. For example, the node management circuitry **440** can select the second industrial machine **218** to process. If, at block **3014**, the data routing management circuitry **400** determines to select another node in the process, control returns to block **3004**. Otherwise, control proceeds to block **3016**.

(422) At block **3016**, the data routing management circuitry **400** provides the contextual data graph models to a shared datastore. For example, the data publishing circuitry **450** can push and/or otherwise provide the at least one of the first contextual data graph model **610**, the second contextual data graph model **612**, or the third contextual data graph model **614** to memory, one or more mass storage devices, etc., of the edge cloud **210**, which can be accessed by different nodes of the environment **200**.

(423) At block **3018**, the data routing management circuitry **400** determines whether to select another process in the environment. For example, the node management circuitry **440** can select the second process **604** to analyze and/or otherwise process for generation of one(s) of the contextual data graph models **474**. If, at block **3018**, the data routing management circuitry **400** determines to select another process in the environment, control returns to block **3002**. Otherwise, control proceeds to block **3020**.

(424) At block **3020**, the data routing management circuitry **400** identifies correlation(s) amongst the contextual data graph models in the shared datastore. For example, the machine-learning circuitry **420** can identify correlation(s), association(s), relationship(s), etc., amongst at least one of the first contextual data graph model **610**, the second contextual data graph model **612**, or the third contextual data graph model **614**, and/or, more generally, the contextual data graph models **474**, based on placements, locations, positions, angles, lengths, etc., of node connecting vectors. In some examples, the machine-learning circuitry **420** can couple the first contextual data graph model **610** to the second contextual data graph model **612** to identify whether first node(s) of the first contextual data graph model **610** can be coupled to second node(s) of the second contextual data graph model **612** based on relatedness between the first node(s) and the second node(s). In some

examples, the machine-learning circuitry **420** can identify correlation(s) between the first contextual data graph model **610** and the second contextual data graph model **612** based on the coupling(s) of the first node(s) and the second node(s).

(425) At block **3022**, the data routing management circuitry **400** updates one(s) of the contextual data graph models based on the correlation(s). For example, the machine-learning circuitry **420** can update at least one of the one of the first contextual data graph model **610**, the second contextual data graph model **612**, or the third contextual data graph model **614**, and/or, more generally, the contextual data graph models **474**, based on placements, locations, positions, angles, lengths, etc., of node connecting vectors indicative of correlation(s) amongst them. In response to updating one(s) of the contextual data graph models based on the correlation(s) at block **3022**, the example machine-readable instructions and/or example operations **3000** of FIG. **30** conclude.

(426) FIG. **31** is a flowchart representative of example machine-readable instructions and/or example operations **3100** that may be executed and/or instantiated by processor circuitry to implement the ADM system **100** of FIG. **1**, the data routing manager **302A-I** of FIG. **3**, and/or the data routing management circuitry **400** of FIG. **4** to provide updated contextual data graph models to at least one of node(s) or a shared datastore. The example machine-readable instructions and/or the example operations **3100** of FIG. **31** begin at block **3102**, at which the data routing management circuitry **400** ingests first data at a first node. For example, the data ingestion circuitry **410** can receive and/or otherwise ingest first data generated by a node, such as a first one of the robots **214**.

(427) At block **3104**, the data routing management circuitry **400** translates the first data. For example, the data ingestion circuitry **410** can convert, reformat, decrypt/encrypt, etc., the first data from a first data format to a second data format.

(428) At block **3106**, the data routing management circuitry **400** tags the first data with first metadata. For example, the first data can be an operating amperage measurement of the first one of the robots **214**, and the data query management circuitry **430** can tag the amperage measurement with first metadata, such as a user, make, model, vendor, manufacturer, serial number, etc., of the first one of the robots **214**.

(429) At block **3108**, the data routing management circuitry **400** identifies match(es) of the first metadata with second metadata associated with second data. For example, the machine-learning circuitry **420** can determine whether a first portion of the first metadata matches a second portion of second metadata associated with second data, such as an operating amperage measurement of a second one of the robots **214**.

(430) At block **3110**, the data routing management circuitry **400** identifies contextual data graph models associated with the second metadata. For example, the machine-learning circuitry **420** can identify one(s) of the contextual data graph models **474** that includes the second metadata.

(431) At block **3112**, the data routing management circuitry **400** updates the contextual data graph models based on the first data. For example, the machine-learning circuitry **420** can update the one(s) of the contextual data graph models **474** by adding and/or removing the first portion of the first metadata to node(s) of the one(s) of the contextual data graph models **474**.

(432) At block **3114**, the data routing management circuitry **400** provides the updated contextual data graph models to at least one of second node(s) or a shared datastore. For example, the data publishing circuitry **450** can push and/or otherwise provide the one(s) of the contextual data graph models **474** to memory, one or more mass storage devices, etc., of the edge cloud **210**, which can be accessed by different nodes of the environment **200**. In some examples, the data publishing circuitry **450** can provide the one(s) of the contextual data graph models **474** to the different nodes of the environment **200**, such as the second one of the robots **214**, the predictive maintenance system **224**, etc.

(433) At block **3116**, the data routing management circuitry **400** determines whether additional data is to be ingested. For example, the data ingestion circuitry **410** can determine whether another

measurement is available from the first one of the robots **214** to be ingested for updating the contextual data graph models **474**. If, at block **3116**, the data routing management circuitry **400** determines that additional data is to be ingested, control returns to block **3102**. Otherwise, the example machine-readable instructions and/or the example operations **3100** of FIG. **31** conclude.

(434) FIG. **32** is a flowchart representative of example machine-readable instructions and/or example operations **3200** that may be executed and/or instantiated by processor circuitry to implement the ADM system **100** of FIG. **1**, the data routing manager **302A-I** of FIG. **3**, and/or the data routing management circuitry **400** of FIG. **4** to update a contextual data graph model based on a machine-learning output. The example machine-readable instructions and/or the example operations **3200** of FIG. **32** begin at block **3202**, at which the data routing management circuitry **400** tags data ingested at a first node associated with a first process in an environment with first metadata. For example, the data query management circuitry **430** can tag first data, which can be sensor data, generated by the first industrial machine **216**. In some examples, the data query management circuitry **430** can tag the first data with the metadata **464** (e.g., generate an association of the first data with the metadata **464**), which can include a make, model, vendor, manufacturer, serial number, etc., of the first industrial machine **216**. In some examples, the first industrial machine **216** can be included in and/or otherwise part of the first process **602** of FIG. **6**.

(435) At block **3204**, the data routing management circuitry **400** determines whether portion(s) of the data deviate from a baseline by a threshold. For example, the machine-learning circuitry **420** can determine whether a value of the sensor data is different from an average value of the sensor data by more than a threshold value, which can be indicative of an abnormal, anomalous, or irregular event in connection with the first industrial machine **216**.

(436) If, at block **3204**, the data routing management circuitry **400** determines that portion(s) of the data do not deviate from a baseline by a threshold, control proceeds to block **3220**. Otherwise, control proceeds to block **3206**. At block **3206**, the data routing management circuitry **400** identifies a contextual data graph model based on the first metadata. For example, the machine-learning circuitry **420** can search the contextual data graph models **474** for one(s) that include portion(s) of the first metadata, and/or, more generally, the first metadata. In some examples, the search can result in the second contextual data graph model **612** of FIG. **6**.

(437) At block **3208**, the data routing management circuitry **400** identifies a second process in sequence with the first process based on the contextual data graph model. For example, the machine-learning circuitry **420** can identify that the second process **604** is in sequence with the first process **602** based on connections of the second contextual data graph model **612**.

(438) At block **3210**, the data routing management circuitry **400** identifies a second node associated with the second process based on the contextual data graph model. For example, the node management circuitry **440** can identify the vehicle **226** as a part of the second process **604**. In some examples, the identification of the vehicle **226** is based on connections of the second contextual data graph model **612**.

(439) At block **3212**, the data routing management circuitry **400** transmits an alert based on the data to the second node. For example, the data publishing circuitry **450** can transmit an alert, based on the sensor data, from the first industrial machine **216** to the vehicle **226** in response to a determination that output(s) from the first industrial machine **216** can affect input(s) of the vehicle **226**.

(440) At block **3214**, the data routing management circuitry **400** receives an indication of an execution of a response or an adjustment in the second process in response to the alert. For example, the vehicle **226** can be halted and/or otherwise cease operation in response to the alert (e.g., loading of the vehicle **226** can be paused). In some examples, a user may carry out an activity in connection with the vehicle **226** in response to the alert. In some examples, the data ingestion circuitry **410** can receive data indicative of the halting/ceasing operation of the vehicle **226**, the carrying out of the activity, etc., and/or any combination(s) thereof.

(441) At block **3216**, the data routing management circuitry **400** provides the indication to a machine-learning model to generate a machine-learning output. For example, the data ingestion circuitry **410** can provide the data to the machine-learning model **470** as model input(s) to generate model output(s). In some examples, the model output(s) can include change(s) to one(s) of the contextual data graph models **474**, such as one of the contextual data graph models **474** that is associated with the vehicle **226** and/or another one of the contextual data graph models **474** that is associated with the first industrial machine **216**.

(442) At block **3218**, the data routing management circuitry **400** updates the contextual data graph model based on the machine-learning output. For example, the machine-learning circuitry **420** can update the one of the contextual data graph models **474** that is associated with the vehicle **226** and/or the one of the contextual data graph models **474** that is associated with the first industrial machine **216** based on the model output(s) from the machine-learning model **470**.

(443) At block **3220**, the data routing management circuitry **400** determines whether additional data is received. For example, the data ingestion circuitry **410** can determine whether additional data is received from the first industrial machine **216** (and/or the vehicle **226**). If, at block **3220**, the data routing management circuitry **400** determines that additional data is received, control returns to block **3202**. Otherwise, the example machine-readable instructions and/or the example operations **3200** of FIG. **32** conclude.

(444) FIG. **33** is a flowchart representative of example machine-readable instructions and/or example operations **3300** that may be executed and/or instantiated by processor circuitry to implement the ADM system **100** of FIG. **1**, the data routing manager **302A-I** of FIG. **3**, and/or the data routing management circuitry **400** of FIG. **4** to cause transmission of a message to a node based on a data routing path. The example machine-readable instructions and/or the example operations **3300** of FIG. **33** begin at block **3302**, at which the data routing management circuitry **400** executes a machine-learning (ML) model to output a first data routing path in an environment based on first metadata associated with an event in the environment. For example, the machine-learning circuitry **420** can execute and/or instantiate one(s) of the machine-learning models **470** to output the first data routing path **1108**. In some examples, the first data routing path **1108** can correspond to a data routing path from a first node, such as a first one of the robots **214**, to a second node, such as the first endpoint device **232**. For example, the machine-learning circuitry **420** can execute and/or instantiate one(s) of the machine-learning models **470** with the metadata **464** associated with an event generated by and/or associated with the first one of the robots **214** as input(s) to generate output(s), which can include the first data routing path **1108**.

(445) At block **3304**, the data routing management circuitry **400** detects whether there is a change of the first data routing path to a second data routing path. For example, the machine-learning circuitry **420** can determine that the first data routing path **1108** included one or more first intervening nodes, such as the switch **204**. In some examples, the machine-learning circuitry **420** can determine that the actual data routing path taken by a message associated with the event included one or more second intervening nodes, such as the second endpoint device **234**. In some examples, the machine-learning circuitry **420** can detect the deviation and/or difference between the first data routing path and the second data routing path based on telemetry data associated with the one or more second intervening nodes, such as an identification of the second endpoint device **234**.

(446) If, at block **3304**, the data routing management circuitry **400** does not detect a change of the first data routing path to a second data routing path, the example machine-readable instructions and/or the example operations **3300** of FIG. **33** conclude. Otherwise, control proceeds to block **3306**.

(447) At block **3306**, the data routing management circuitry **400** retrains the ML model to output a third data routing path based on the second data routing path. For example, the machine-learning circuitry **420** can retrain the one(s) of the machine-learning models **470** using the second data

routing path, the one or more second intervening nodes, the telemetry data, etc., as training data (or retraining data). In some examples, based on the retraining, the machine-learning circuitry **420** can execute and/or instantiate the machine-learning models **470** to output one(s) of the other data routing paths **1114** of FIG. **11**.

(448) At block **3308**, the data routing management circuitry **400** causes transmission of a message to a node based on a third data routing path. For example, the data publishing circuitry **450** can cause transmission from the first one of the robots **214** to the first endpoint device **232** based on the one(s) of the other data routing paths **1114** of FIG. **11**, such as the data routing path from Node 1 (e.g., the first one of the robots **214**) to Node 4 (e.g., the first endpoint device **232**). After causing transmission of a message to a node based on a third data routing path at block **3308**, the example machine-readable instructions and/or the example operations **3300** of FIG. **33** conclude.

(449) FIG. **34** is a flowchart representative of example machine-readable instructions and/or example operations **3400** that may be executed and/or instantiated by processor circuitry to implement the ADM system **100** of FIG. **1**, the data routing manager **302A-I** of FIG. **3**, and/or the data routing management circuitry **400** of FIG. **4** to cause an action to occur in an environment based on a message.

(450) At block **3402**, the data routing management circuitry **400** determines whether an event associated with an environment occurred. For example, the data ingestion circuitry **410** can detect that the first event **924** is generated in the first zone **904** of the environment **900** of FIGS. **9A-9C**.

(451) If, at block **3402**, the data routing management circuitry **400** did not determine that an event associated with an environment occurred, control waits at block **3402**, such as waiting for new data to be ingested, analyzed, etc. If, at block **3402**, the data routing management circuitry **400** did not determine that an event associated with an environment occurred, control proceeds to block **3404**.

(452) At block **3404**, the data routing management circuitry **400** determines whether a machine-learning (ML) microservice is deployed. For example, the machine-learning circuitry **420** can determine whether one(s) of the machine-learning models **470** is/are deployed for use in connection with the first zone **904**, and/or, more generally, the environment **902**.

(453) If, at block **3404**, the data routing management circuitry **400** determines that a machine-learning (ML) microservice is not deployed, control proceeds to block **3420**. Otherwise, control proceeds to block **3406**.

(454) At block **3406**, the data routing management circuitry **400** obtains metadata associated with a data routing path taken by message associated with the event. For example, the data query management circuitry **430** can obtain the metadata **464** associated with a first message transmitted from the first node **908** to the ninth node **928**. In some examples, the metadata **464** can be based on feedback from the ninth node **928**, telemetry data associated with the ninth node **928**, etc.

(455) At block **3408**, the data routing management circuitry **400** provides the metadata to the ML microservice to generate a ML output. For example, the data query management circuitry **430** can provide the metadata to the machine-learning microservice as model input(s) to generate model output(s).

(456) At block **3410**, the data routing management circuitry **400** determines whether a pattern is detected based on the ML output. For example, the machine-learning circuitry **420** can detect a pattern utilizing the workflow **1100** of FIG. **11**.

(457) If, at block **3410**, the data routing management circuitry **400** determines that a pattern is not detected based on the ML output, control proceeds to block **3416**. Otherwise, control proceeds to block **3412**.

(458) At block **3412**, the data routing management circuitry **400** retrains the ML microservice based on the detected pattern. For example, the machine-learning circuitry **420** can retrain the machine-learning microservice based on the detected pattern to strengthen and/or reinforce associations of previously identified data routing paths and the first event **924**.

(459) At block **3414**, the data routing management circuitry **400** deploys the ML microservice. For

example, the machine-learning circuitry **420** can deploy the retrained machine-learning microservice for use in connection with the first zone **904**, and/or, more generally, the environment **902**.

(460) At block **3416**, the data routing management circuitry **400** generates a data routing path for a message associated with the event using the ML microservice. For example, the machine-learning circuitry **420** can generate and/or output a data routing path for a second message associated with the first event **924**, or another instance of the first event **924**, using the retrained machine-learning services.

(461) At block **3418**, the data routing management circuitry **400** causes an action to occur in the environment based on the message. For example, the data publishing circuitry **450** can cause transmission of the second message from the first node **908** to the ninth node **928** based on the data routing path output from the retrained machine-learning microservice. In some examples, the data publishing circuitry **450** can cause an action, such as a repair and/or maintenance action on the first node **908**, by causing transmission of the second message to a relevant node, such as the ninth node **928**.

(462) At block **3402**, the data routing management circuitry **400** determines whether to continue monitoring the environment for events. For example, the data ingestion circuitry **410** can determine whether to continue monitoring the first zone **904**, and/or, more generally, the environment **902**, for generation of events. If, at block **3402**, the data routing management circuitry **400** determines to continue monitoring the environment for events, control returns to block **3402**. Otherwise, the example machine-readable instructions and/or example operations **3400** of FIG. **34** conclude.

(463) FIG. **35** is a flowchart representative of example machine-readable instructions and/or example operations **3500** that may be executed and/or instantiated by processor circuitry to implement the ADM system **100** of FIG. **1**, the data routing manager **302A-I** of FIG. **3**, and/or the data routing management circuitry **400** of FIG. **4** to present a message to a user.

(464) At block **3502**, the data routing management circuitry **400** instantiates a machine-learning microservice to analyze received data. For example, the machine-learning circuitry **420** can compile, generate, and/or output a machine-learning microservice based on execution and/or instantiation of one(s) of the machine-learning models **470**. For example, one of the data routing managers **302A-I** can execute and/or instantiate the machine-learning service locally on respective one of the devices **324**, **326**, **328**, **330**, **332**, **334**, remotely by accessing a cloud-hosted application, etc., and/or any combination(s) thereof.

(465) At block **3504**, the data routing management circuitry **400** identifies a node at which to route a message associated with the received data. For example, the node management circuitry **440** can identify a first node implemented by the fourth device **330** and/or the fourth user **316** at which to route a message associated with received and/or ingested data (e.g., an alarm or alert condition from a first one of the robots **214**, the first event **924**, etc.).

(466) At block **3506**, the data routing management circuitry **400** determines whether a user associated with the node is able to hear audio and view video and text. For example, the node management circuitry **440** can obtain utilization data from the fourth device **330**, which can include biometric data associated with the fourth user **316**, configuration data and/or settings of the fourth device **330**, etc. In some examples, the node management circuitry **440** can determine that the user is unable to hear audio because the fourth user **316** muted and/or disabled audio of the fourth device **330**. In some examples, the node management circuitry **440** can determine that the user is able to view text and/or video because eye-tracking data from an eye-tracking sensor indicates that the fourth user **316** is looking at a display of the fourth device **330**.

(467) If, at block **3506**, the data routing management circuitry **400** determines that a user associated with the node is able to hear audio and view video and text, control proceeds to block **3508**. For example, after a determination that the fourth user **316** can hear audio as well as view text and/or video(s), control proceeds to block **3508**.

(468) At block **3508**, the data routing management circuitry **400** presents the message to the user as audio, video, and/or text. For example, the data publishing circuitry **450** can generate the message to include audio, video, and/or text data. In some examples, the data publishing circuitry **450** can cause transmission of the message to the fourth device **330** via the network **322**. Upon receipt of the message by the fourth device **330**, the fourth device **330** can present audio data via a speaker of the fourth device **330** and/or text and/or video data via a display of the fourth device **330**. After presenting the message at block **3508**, control proceeds to block **3520**.

(469) If, at block **3506**, the data routing management circuitry **400** determines that a user associated with the node is not able to hear audio and view video and text, control proceeds to block **3510**.

(470) At block **3510**, the data routing management circuitry **400** determines whether a user associated with the node is able to hear audio. For example, the node management circuitry **440** can determine that the fourth user **316** is holding the fourth device **330** based on accelerometer data from an accelerometer of the fourth device **330**, but the fourth user **416** is not looking at the fourth device **330** based on eye-tracking data from an eye-tracking sensor of the fourth device **330**, a human-presence sensor of the fourth device **330**, etc. In some examples, the node management circuitry **440** can determine that the fourth user **316** can hear audio but may not be able to view video and/or text. In some examples, the node management circuitry **440** can determine that the fourth user **316** is unable to hear audio because a speaker of the fourth device **330** is broken, muted, and/or disabled. In some examples, the node management circuitry **440** can determine that the fourth user **316** is unable to hear audio because the fourth device **330** does not have audio output (e.g., does not have a speaker or other transducer).

(471) If, at block **3510**, the data routing management circuitry **400** determines that a user associated with the node is able to hear audio, control proceeds to block **3512**. At block **3512**, the data routing management circuitry **400** presents the message to the user as audio. For example, the data publishing circuitry **450** can generate the message to include audio data. In some examples, the data publishing circuitry **450** can cause transmission of the message to the fourth device **330** via the network **322**. In response to receiving the message at the fourth device **330**, the fourth device **330** can present audio data via a speaker of the fourth device **330**. After presenting the message at block **3512**, control proceeds to block **3520**.

(472) If, at block **3510**, the data routing management circuitry **400** determines that a user associated with the node is unable to hear audio, control proceeds to block **3514**. At block **3514**, the data routing management circuitry **400** determines whether a user associated with the node is able to view video and/or read text. For example, the node management circuitry **440** can determine that the fourth user **316** is unable to view text and/or video because the fourth user **316** is not holding the fourth device **330** and/or otherwise near or proximate the fourth device **330** based on accelerometer data from an accelerometer of the fourth device **330**, eye-tracking data from an eye-tracking sensor of the fourth device **330**, a human-presence sensor of the fourth device **330**, etc. In some examples, the node management circuitry **440** can determine that the fourth user **316** can view text and/or video because the fourth device **330** is powered on and/or the fourth device **330** includes a display to present a text and/or video-based message.

(473) If, at block **3514**, the data routing management circuitry **400** determines that a user associated with the node is able to view video and/or read text, control proceeds to block **3516**. For example, the data publishing circuitry **450** can generate the message to include text and/or video data. In some examples, the data publishing circuitry **450** can cause transmission of the message to the fourth device **330** via the network **322**. After receiving the message at the fourth device **330**, the fourth device **330** can present text and/or video data via a display of the fourth device **330**. After presenting the message at block **3516**, control proceeds to block **3520**.

(474) If, at block **3514**, the data routing management circuitry **400** determines that a user associated with the node is not able to view video and/or read text, control proceeds to block **3518**. At block **3518**, the data routing management circuitry **400** generates an alert. For example, the data

publishing circuitry **450** can generate an alert that the fourth user **316** is unable to be presented with an audio, text, and/or video-based message. In some examples, the alert can be surfaced to and/or routed to a supervisor of the fourth user **316**, another one of the users **310**, **312**, **314**, **316**, **318**, **320** that may be related to the received and/or ingested data, etc. After generating the alert at block **3518**, control proceeds to block **3520**.

(475) At block **3520**, the data routing management circuitry **400** determines whether to continue monitoring the environment for received data. For example, the data ingestion circuitry **410** can determine whether another event is generated, additional data is received, etc. If, at block **3520**, the data routing management circuitry **400** determines to continue monitoring the environment for received data, control returns to block **3502**. Otherwise, the example machine-readable instructions and/or the example operations **3500** of FIG. **35** conclude.

(476) FIG. **36** is a flowchart representative of example machine-readable instructions and/or example operations **3600** that may be executed and/or instantiated by processor circuitry to implement the ADM system **100** of FIG. **1**, the data routing manager **302A-I** of FIG. **3**, and/or the data routing management circuitry **400** of FIG. **4** to present data to a user based on one or more communication mediums. The example machine-readable instructions and/or the example operations **3600** of FIG. **36** begin at block **3602**, at which the data routing management circuitry **400** instantiates a machine-learning microservice to analyze received data. For example, the machine-learning circuitry **420** can assemble, compile, generate, and/or output a machine-learning microservice based on execution and/or instantiation of one(s) of the machine-learning models **470**. For example, one of the data routing managers **302A-I** can execute and/or instantiate the machine-learning service locally on respective one of the devices **324**, **326**, **328**, **330**, **332**, **334**, remotely by accessing a cloud-hosted application, etc., and/or any combination(s) thereof.

(477) At block **3604**, the data routing management circuitry **400** identifies a node at which to route a message associated with the received data. For example, the node management circuitry **440** can identify a first node implemented by the second device **326** and/or the second user **312** at which to route a message associated with received and/or ingested data (e.g., an alarm or alert condition from the first industrial machine **216**, the first event **924**, etc.).

(478) At block **3606**, the data routing management circuitry **400** determines whether the node is equipped with different network interfaces. For example, the node management circuitry **440** can determine based on utilization data of the second device **326**, such as a listing of hardware, software, and/or firmware associated with the second device **326**, that the second device **326** includes at least a first network interface and a second network interface. In some examples, the first network interface can be based on a first type of communication medium, such as Wi-Fi. In some examples, the second network interface can be based on a second type of communication medium, such as Bluetooth or 5G cellular. Alternatively, the node management circuitry **440** can determine that the second device **326** only has a single type of network interface, such as Wi-Fi.

(479) If, at block **3606**, the data routing management circuitry **400** determines that the node is not equipped with different network interfaces, control proceeds to block **3608**. At block **3608**, the data routing management circuitry **400** transmits the message to the node over a network interface. For example, the data publishing circuitry **450** can transmit a message to the second device **326** via Wi-Fi. After transmitting the message at block **3608**, control proceeds to block **3620**.

(480) If, at block **3606**, the data routing management circuitry **400** determines that the node is equipped with different network interfaces, control proceeds to block **3610**. At block **3610**, the data routing management circuitry **400** splits the message into a first message portion and a second message portion. For example, the data publishing circuitry **450** can divide, segment, split, etc., the message into one or more first data objects and one or more second data objects. In some examples, the one or more first data objects are the same type (e.g., audio data objects) as the one or more second data objects. In some examples, the one or more first data objects have a first type (e.g., audio) and the one or more second data objects have a second type (e.g., text, video, etc.) different

from the first type.

(481) At block **3612**, the data routing management circuitry **400** transmits the first message portion to the node over a first network interface. For example, the data publishing circuitry **450** can cause transmission of the one or more first data objects to the second device **326** via the network **322** using Wi-Fi.

(482) At block **3614**, the data routing management circuitry **400** transmits the second message portion to the node over a second network interface. For example, the data publishing circuitry **450** can cause transmission of the one or more second data objects to the second device **326** via the network **322** using 5G cellular.

(483) At block **3616**, the data routing management circuitry **400** causes reassembly of the message based on the first message portion and the second message portion. For example, the one or more first data objects and/or the one or more second data objects can be transmitted with metadata, such as respective sequence numbers or identifiers, that can instruct the second device **326** on how to reassemble the message (e.g., by arranging the data objects based on their associated sequence numbers/identifiers).

(484) At block **3618**, the data routing management circuitry **400** causes an action to occur based on the reassembled message. For example, the second device **326** can present the reassembled message to the second user **312**. In some examples, the reassembled message can be an alert indicating that a first one of the robots **214** generated an error code and shut down (e.g., ceased operation, became inoperable, etc.). In some examples, the second user **312** can carry out an action, such as fixing the first one of the robots **214** and/or clearing the error code to resume operation of the first one of the robots **214**, based on the presented message.

(485) At block **3620**, the data routing management circuitry **400** determines whether to continue monitoring for received data. For example, the data ingestion circuitry **410** can determine whether another event is generated, additional data is received, etc. If, at block **3620**, the data routing management circuitry **400** determines to continue monitoring the environment for received data, control returns to block **3602**. Otherwise, the example machine-readable instructions and/or the example operations **3600** of FIG. **36** conclude.

(486) FIG. **37** is a flowchart representative of example machine-readable instructions and/or example operations **3700** that may be executed and/or instantiated by processor circuitry to implement the ADM system **100** of FIG. **1**, the data routing manager **302A-I** of FIG. **3**, and/or the data routing management circuitry **400** of FIG. **4** to output a message to a user based on bandwidth associated with the user. The example machine-readable instructions and/or example operations **3700** begin at block **3702**, at which the data routing management circuitry **400** instantiates a machine-learning microservice to analyze received data. For example, the machine-learning circuitry **420** can assemble, compile, generate, output, and/or deploy a machine-learning microservice based on execution and/or instantiation of one(s) of the machine-learning models **470**. For example, one of the data routing managers **302A-I** can execute and/or instantiate the machine-learning service locally on respective one of the devices **324**, **326**, **328**, **330**, **332**, **334**, remotely by accessing a cloud-hosted application, etc., and/or any combination(s) thereof.

(487) At block **3704**, the data routing management circuitry **400** identifies a node at which to route a message associated with the received data. For example, the node management circuitry **440** can identify a node implemented by the fifth user **318** and/or the fifth device **332** at which to route a message associated with received and/or ingested data (e.g., an alarm or alert condition from the first industrial machine **216**, the first event **924**, etc.).

(488) At block **3706**, the data routing management circuitry **400** generates the message to include message portions. For example, the data publishing circuitry **450** can divide, segment, split, etc., the message into one or more first data objects and one or more second data objects. In some examples, the one or more first data objects are the same type (e.g., audio data objects) as the one or more second data objects. In some examples, the one or more first data objects have a first type

(e.g., audio) and the one or more second data objects have a second type (e.g., text, video, etc.) different from the first type.

(489) At block **3708**, the data routing management circuitry **400** determines whether a user associated with the node is ready to access a portion of the message. For example, the node management circuitry **440** can obtain an acknowledgement from the fifth user **318**, such as an audible command or instruction, a hand gesture interpreted by the fifth device **332**, an input received by a touchscreen display of the fifth device **332**, etc.

(490) If, at block **3708**, the data routing management circuitry **400** determines that a user associated with the node is not ready to access a portion of the message, control waits at block **3708** until the user is ready and/or an acknowledgement is received indicating that the user is ready.

(491) If, at block **3708**, the data routing management circuitry **400** determines that a user associated with the node is ready to access a portion of the message, control proceeds to block **3710**. At block **3710**, the data routing management circuitry **400** determines a bandwidth associated with the node. For example, the node management circuitry **440** can determine that the second device **326** has relatively low network bandwidth (e.g., weak Wi-Fi signal, low 5G cellular connection, etc.) based on utilization data associated with the second device **326**.

(492) At block **3712**, the data routing management circuitry **400** outputs the portion of the message to a user based on the bandwidth. For example, the data publishing circuitry **450** can output the one or more first data objects to the second device **326** via Wi-Fi based on a determination that the Wi-Fi bandwidth associated with the second device **326** is greater than a 5G cellular bandwidth.

(493) At block **3714**, the data routing management circuitry **400** determines whether there is another portion of the message to process. For example, the data publishing circuitry **450** can determine that the one or more second data objects are to be output and/or transmitted to the second device **326**.

(494) If, at block **3714**, the data routing management circuitry **400** determines that there is another portion of the message to process, control returns to block **3708**. Otherwise, control proceeds to block **3716**. At block **3716**, the data routing management circuitry **400** determines whether to continue monitoring the environment for received data. For example, the data ingestion circuitry **410** can determine whether another event is generated, additional data is received, etc. If, at block **3716**, the data routing management circuitry **400** determines to continue monitoring the environment for received data, control returns to block **3702**. Otherwise, the example machine-readable instructions and/or the example operations **3700** of FIG. **37** conclude.

(495) FIG. **38** is a flowchart representative of example machine-readable instructions and/or example operations **3800** that may be executed and/or instantiated by processor circuitry to implement the ADM system **100** of FIG. **1**, the data routing manager **302A-I** of FIG. **3**, and/or the data routing management circuitry **400** of FIG. **4** to cause an action to occur in an environment based on a digital twin associated with the environment.

(496) At block **3802**, the data routing management circuitry **400** obtains first metadata associated with an environment. For example, the data ingestion circuitry **410** can obtain first metadata, such as portion(s) of the metadata **464**, associated with the first zone **904**, and/or, more generally, the environment **902**, of FIGS. **9A-9C**.

(497) At block **3804**, the data routing management circuitry **400** generates digital twin data representations of node(s) in the environment. For example, the machine-learning circuitry **420** can generate a first one of the digital twins **476** based on a digital and/or virtual representation of a first one of the robots **214** of FIG. **2**. In some examples, the first one of the digital twins **476** can be implemented by the first node **908** of FIGS. **9A-9C**.

(498) At block **3806**, the data routing management circuitry **400** generates a machine-learning (ML) model to utilize the digital twin data representations of the node(s) as ML input(s). For example, the machine-learning circuitry **420** can generate and/or output a first one of the machine-learning models **470** to utilize the first one of the digital twins **476** as machine-learning input(s).

(499) At block **3808**, the data routing management circuitry **400** determines whether an event associated with the environment occurred. For example, the data ingestion circuitry **410** can determine that the first event **924** is generated and/or otherwise present. If, at block **3808**, the data routing management circuitry **400** determines that an event associated with the environment did not occur, control proceeds to block **3818**. Otherwise control proceeds to block **3810**.

(500) At block **3810**, the data routing management circuitry **400** executes the ML model with second metadata associated with the event as ML input(s) to generate ML output(s). For example, the machine-learning circuitry **420** can execute and/or instantiate the first one of the machine-learning models **470** using second metadata, such as portion(s) of the metadata **464**, associated with the first event **924** as machine-learning input(s) to the first one of the machine-learning models **470**.

(501) At block **3812**, the data routing management circuitry **400** identifies data routing path(s) based on the ML output(s). For example, the machine-learning circuitry **420** can execute the first one of the machine-learning models **470** to generate machine-learning output(s), which can include a data routing path for a message based on the first event **924** to be transmitted from the first node **908** to different node(s) of the environment **902**, such as the ninth node **928** of FIG. **9C**.

(502) At block **3814**, the data routing management circuitry **400** transmits message(s) to one(s) of the node(s) based on the data routing path(s). For example, the data publishing circuitry **450** can cause transmission of the message from the first node to the different node(s) based on the data routing path indicated by the machine-learning output(s).

(503) At block **3816**, the data routing management circuitry **400** causes action(s) to occur based on the message(s). For example, after transmission of the message, the ninth node **928** can be invoked to act in connection with the first node **908**, which can include a repair and/or maintenance action on the physical counterpart to the first node **908**, which can be the first one of the robots **214**.

(504) At block **3818**, the data routing management circuitry **400** determines whether to continue monitoring the environment for events. For example, the data ingestion circuitry **410** can determine whether another event is generated, additional data is received, etc. If, at block **3818**, the data routing management circuitry **400** determines to continue monitoring the environment for events, control returns to block **3802**. Otherwise, the example machine-readable instructions and/or the example operations **3800** of FIG. **38** conclude.

(505) FIG. **39** is a flowchart representative of example machine-readable instructions and/or example operations **3900** that may be executed and/or instantiated by processor circuitry to implement the ADM system **100** of FIG. **1**, the data routing manager **302A-I** of FIG. **3**, and/or the data routing management circuitry **400** of FIG. **4** to train and/or retrain a machine-learning model associated with a digital twin. The example machine-readable instructions and/or the example operations **3900** of FIG. **39** begin at block **3902**, at which the data routing management circuitry **400** determines whether an event associated with an environment occurred. For example, the data ingestion circuitry **410** can determine that the first event **924** is generated and/or otherwise present. If, at block **3902**, the data routing management circuitry **400** determines that an event associated with the environment did not occur, control waits at block **3902** (e.g., waits for an event to occur and/or be generated). Otherwise control proceeds to block **3904**.

(506) At block **3904**, the data routing management circuitry **400** executes a machine-learning (ML) model with first metadata associated with the event as ML input(s) to generate ML output(s). For example, during the first operation(s) **1106** of FIG. **11**, the machine-learning circuitry **420** can execute and/or instantiate one(s) of the machine-learning models **470** with first metadata associated with the first event **924** as machine-learning input(s) to the one(s) of the machine-learning models **470** to generate machine-learning output(s).

(507) At block **3906**, the data routing management circuitry **400** identifies a predicted data routing path for message to be routed based on the ML output(s). For example, the machine-learning circuitry **420** can identify a first data routing path from Node 1 to Node 4 via Nodes 7, 3, 5, and 4

of FIG. 11.

(508) At block **3908**, the data routing management circuitry **400** obtains second metadata associated with an actual data routing path of the message. For example, during the first operation(s) **1106** of FIG. 11, the machine-learning circuitry **420** can obtain second metadata associated with the actual data routing path of the message, which can be the first data routing path **1108** of FIG. 11. In some examples, the second metadata corresponds to and/or is representative of an actual data routing path of a message from Node 1 to Node 4 via Nodes 6, 5, 2, and 4 of FIG. 11, which can be the first data routing path **1108** of FIG. 11.

(509) At block **3910**, the data routing management circuitry **400** determines whether there is a difference between the predicted and actual data routing path. For example, the machine-learning circuitry **420** can determine that the actual data routing path used Nodes 7, 3, and 5 instead of Nodes 6, 5, and 2 based on the second metadata and/or comparison(s) of the first metadata to the second metadata, comparison(s) of the predicted data routing path (e.g., Node 1-Node 7-Node 3-Node 5-Node 4) to the actual data routing path (e.g., Node 1-Node 6-Node 5-Node 2-Node 4), etc., and/or any combination(s) thereof.

(510) If, at block **3910**, the data routing management circuitry **400** determines that there is not a difference between the predicted and actual data routing path, control proceeds to block **3918**. Otherwise, control proceeds to block **3912**. At block **3912**, the data routing management circuitry **400** retrains the ML model based on the difference. For example, during the second operation(s) **1110**, the machine-learning circuitry **420** can retrain the one(s) of the machine-learning models **470** using the difference(s) as training data (or retraining data).

(511) At block **3914**, the data routing management circuitry **400** determines whether to deploy the ML model to generate the actual data routing path. For example, the machine-learning circuitry **420** can determine that an accuracy of the output(s) of the one(s) of the machine-learning models **470** does not satisfy an accuracy threshold, and therefore needs further training before deployment. In some examples, the machine-learning circuitry **420** can determine that an accuracy of the output(s) of the one(s) of the machine-learning models **470** is greater than an accuracy threshold and thereby can satisfy an accuracy threshold, and therefore can be deployed to generate actual data routing paths.

(512) If, at block **3914**, the data routing management circuitry **400** determines not to deploy the ML model to generate the actual data routing path, control proceeds to block **3918**. Otherwise control proceeds to block **3916**.

(513) At block **3916**, the data routing management circuitry **400** deploys the ML model to generate the actual data routing path. For example, in response to detection of another event that has metadata associated with the first event **924**, the machine-learning circuitry **420** can execute and/or instantiate the one(s) of the machine-learning models **470** to generate and/or output actual data routing paths of message(s) based on the detected event.

(514) At block **3918**, the data routing management circuitry **400** causes an action to occur associated with the actual data routing path. For example, user(s) associated with Nodes 2, 3, and/or 4 can be presented with a message based on the detected event. In some examples, the user(s) can carry out actions, activities, operations, tasks, etc., based on the message. In some examples, the message presented to the user(s) are routed from an origin node to Nodes 2, 3, and/or 4 based on an actual data routing path output from the one(s) of the machine-learning models **470**.

(515) At block **3920**, the data routing management circuitry **400** continue monitoring the environment for events. For example, the data ingestion circuitry **410** can determine whether another event is generated, additional data is received, etc. If, at block **3920**, the data routing management circuitry **400** determines to continue monitoring the environment for events, control returns to block **3902**. Otherwise, the example machine-readable instructions and/or the example operations **3900** of FIG. 39 conclude.

(516) FIG. 40 is a flowchart representative of example machine-readable instructions and/or

example operations **4000** that may be executed and/or instantiated by processor circuitry to implement the ADM system **100** of FIG. **1**, the data routing manager **302A-I** of FIG. **3**, and/or the data routing management circuitry **400** of FIG. **4** to cause device(s) to select one(s) of the device(s) to execute task(s). The example machine-readable instructions and/or example operations **4000** of FIG. **40** begin at block **4002**, at which the data routing management circuitry **400** propagates ingested data to a first device. For example, the data publishing circuitry **450** can cause transmission of a first message with first metadata to a first one of the robots **214**. In some examples, the first message can be representative of an event generated by the third endpoint device **236**. For example, the event can be generated by a human user associated with the third endpoint device **236**. In some examples, the event can be representative of a failed inspection of an assembly manufactured by the first one of the robots **214**. For example, the first message can include instructions to the first one of the robots **214** to disassemble the assembly and to re-assemble the assembly. In some examples, the first message can be routed to the first industrial machine **216** to move the identified assembly for reassembly from one of the shelves to the first one of the robots **214**.

(517) At block **4004**, the data routing management circuitry **400** determines that the first device is to execute a task with second device(s) based on the received data. For example, the data query management circuitry **430** can determine, based on the first metadata, that a second one of the robots **214** partially assembled the assembly. In some examples, the data query management circuitry **430** can identify the first one of the robots **214** and/or the second one of the robots **214** to carry out a reassembly operation based on the first metadata.

(518) At block **4006**, the data routing management circuitry **400** propagates the received data from the first device to the second device(s) based on a contextual data graph model. For example, the data publishing circuitry **450** can cause transmission of the message to the first one and the second one of the robots **214**.

(519) At block **4008**, the data routing management circuitry **400** determines whether one(s) of the second device(s) have historical metadata associated with the task. For example, the data publishing circuitry **450** can determine that the first metadata is partially included and/or entirely included in second metadata associated with the first one and the second one of the robots **214**.

(520) If, at block **4008**, the data routing management circuitry **400** determines that one(s) of the second device(s) have historical metadata associated with the task, control proceeds to block **4010**. At block **4010**, the data routing management circuitry **400** causes the one(s) of the second device(s) to execute the task with the first device. For example, the data publishing circuitry **450** can cause, based on the transmission of the message, the first and second ones of the robots **214** to disassemble the assembly and put it back together in the correct manner (e.g., so not to fail another inspection) based on technical specifications, an autonomous workflow, etc., associated with the assembly. After causing the one(s) of the second device(s) to execute the task with the first device, control proceeds to block **4016**.

(521) If, at block **4008**, the data routing management circuitry **400** determines that one(s) of the second device(s) do not have historical metadata associated with the task, control proceeds to block **4012**. For example, the node management circuitry **440** can determine that the first and second ones of the robots **214** did not produce the assembly based on the first metadata not being associated with portion(s) of the second metadata of the first and second ones of the robots **214**.

(522) At block **4012**, the data routing management circuitry **400** selects one(s) of the second device(s) to execute the task. For example, the node management circuitry **440** can invoke the first and second ones of the robots **214** to choose amongst each other who is to fix the assembly. In some examples, the node management circuitry **440** can select one of the first and second ones of the robots **214** to redo the assembly.

(523) At block **4014**, the data routing management circuitry **400** requests metadata associated with the task from machine-learning microservice to improve execution of the task. For example, in

response to the first one of the robots **214** being selected (either from the robots themselves and/or from the node management circuitry **440**), the first one of the robots **214** can request the metadata **464**, one(s) of the machine-learning models **470**, and/or one(s) of the digital twins **476** in connection with the assembly. For example, the data query management circuitry **430** can obtain a request from the first one of the robots **214** for more information that the first one of the robots **214** can utilize to carry out the task. In some examples, the data query management circuitry **430** can map metadata associated with the request to one(s) of the contextual data graph models **474**. For example, based on the mapping, the data query management circuitry **430** can identify the one(s) of the machine-learning models **470**, and/or the one(s) of the digital twins **476** in connection with the assembly. In some examples, the data publishing circuitry **450** can output and/or cause transmission of the one(s) of the machine-learning models **470** and/or one(s) of the digital twins **476** in connection with the assembly to the first one of the robots **214** for consumption.

(524) At block **4016**, the data routing management circuitry **400** provides feedback to the machine-learning microservice to improve selection of device(s). For example, the data query management circuitry **430** can obtain feedback from the first one of the robots that one of the provided machine-learning models was not relevant to the assembly. In some examples, the data query management circuitry **430** can obtain feedback in the form of an acknowledgment of successful completion of the task and thereby determine that the provided one(s) of the machine-learning models **470** and/or one(s) of the digital twins **476** is/are relevant to the assembly.

(525) At block **4018**, the data routing management circuitry **400** instantiates the machine-learning microservice. For example, the machine-learning circuitry **420** can retrain the one(s) of the machine-learning models **470** based on the feedback and instantiate (or reinstantiate) the one(s) of the machine-learning models **470** for deployment to process AI/ML workloads. After instantiating the machine-learning microservice at block **4018**, the example machine-readable instructions and/or the example operations **4000** of FIG. **40** conclude.

(526) FIG. **41** is a block diagram of an example processor platform **4100** structured to execute and/or instantiate the example machine readable instructions and/or the example operations of one(s) of FIGS. **17-40** to implement the ADM system **100** of FIG. **1**. The processor platform **4100** can be, for example, a server, a personal computer, a workstation, a self-learning machine (e.g., a neural network), a mobile device (e.g., a cell phone, a smart phone, a tablet such as an iPad™), a personal digital assistant (PDA), an Internet appliance, a DVD player, a CD player, a digital video recorder, a Blu-ray player, a gaming console, a personal video recorder, a set top box, a headset (e.g., an augmented reality (AR) headset, a virtual reality (VR) headset, etc.) or other wearable device, an IoT device, an IPU, or any other type of computing and/or electronic device.

(527) The processor platform **4100** of the illustrated example includes processor circuitry **4112**. The processor circuitry **4112** of the illustrated example is hardware. For example, the processor circuitry **4112** can be implemented by one or more integrated circuits, logic circuits, FPGAs microprocessors, CPUs, GPUs, DSPs, and/or microcontrollers from any desired family or manufacturer. The processor circuitry **4112** may be implemented by one or more semiconductor based (e.g., silicon based) devices. In this example, the processor circuitry **4112** implements the example data ingestion manager **106**, the example data query manager **110**, the example data publishing manager **118**, the example node manager **122**, the example data security manager **132**, the example algorithm manager **134**, and the example analytics manager **136**.

(528) The processor circuitry **4112** of the illustrated example includes a local memory **4113** (e.g., a cache, registers, etc.). The processor circuitry **4112** of the illustrated example is in communication with a main memory including a volatile memory **4114** and a non-volatile memory **4116** by a bus **4118**. In some examples, the bus **4118** can implement the data plane **128**, the control plane **130**, and/or, more generally, the network plane **126**, of FIG. **1**. The volatile memory **4114** may be implemented by SDRAM, DRAM, RDRAM®, and/or any other type of RAM device. The non-volatile memory **4116** may be implemented by flash memory and/or any other desired type of

memory device. Access to the main memory **4114**, **4116** of the illustrated example is controlled by a memory controller **4117**.

(529) The processor platform **4100** of the illustrated example also includes interface circuitry **4120**. The interface circuitry **4120** may be implemented by hardware in accordance with any type of interface standard, such as an Ethernet interface, a USB interface, a Bluetooth® interface, an NFC interface, a PCI interface, and/or a PCIe interface.

(530) In the illustrated example, one or more input devices **4122** are connected to the interface circuitry **4120**. The input device(s) **4122** permit(s) a user to enter data and/or commands into the processor circuitry **4112**. The input device(s) **4122** can be implemented by, for example, an audio sensor, a microphone, a camera (still or video), a keyboard, a button, a mouse, a touchscreen, a track-pad, a trackball, an isopoint device, and/or a voice recognition system.

(531) One or more output devices **4124** are also connected to the interface circuitry **4120** of the illustrated example. The output device(s) **4124** can be implemented, for example, by display devices (e.g., a light emitting diode (LED), an organic light emitting diode (OLED), a liquid crystal display (LCD), a cathode ray tube (CRT) display, an in-place switching (IPS) display, a touchscreen, etc.), a tactile output device, a printer, and/or speaker. The interface circuitry **4120** of the illustrated example, thus, typically includes a graphics driver card, a graphics driver chip, and/or graphics processor circuitry such as a GPU.

(532) The interface circuitry **4120** of the illustrated example also includes a communication device such as a transmitter, a receiver, a transceiver, a modem, a residential gateway, a wireless access point, and/or a network interface to facilitate exchange of data with external machines (e.g., computing devices of any kind) by a network **4126**. The communication can be by, for example, an Ethernet connection, a digital subscriber line (DSL) connection, a telephone line connection, a coaxial cable system, a satellite system, a line-of-site wireless system, a cellular telephone system, an optical connection, etc.

(533) The processor platform **4100** of the illustrated example also includes one or more mass storage devices **4128** to store software and/or data. Examples of such mass storage devices **4128** include magnetic storage devices, optical storage devices, floppy disk drives, HDDs, CDs, Blu-ray disk drives, redundant array of independent disks (RAID) systems, solid state storage devices such as flash memory devices and/or SSDs, and DVD drives. In this example, the one or more mass storage devices **4128** implement the distributed datastore **144**, which includes the example metadata datastore **146** and the example raw datastore **148** of FIG. 1.

(534) The machine executable instructions **4132**, which may be implemented by the machine-readable instructions of one(s) of FIGS. 17-40, may be stored in the mass storage device **4128**, in the volatile memory **4114**, in the non-volatile memory **4116**, and/or on a removable non-transitory computer readable storage medium such as a CD or DVD.

(535) The processor platform **4100** of the illustrated example of FIG. 41 includes example acceleration circuitry **4140**, which includes an example GPU **4142**, an example vision processor unit (VPU) **4144**, and an example neural network processor **4146**. In this example, the GPU **4142**, the VPU **4144**, the neural network processor **4146**, and/or, more generally, the acceleration circuitry **4140**, are in communication with different hardware of the processor platform **4100**, such as the volatile memory **4114**, the non-volatile memory **4116**, etc., via the bus **4118**. In this example, the neural network processor **4146** may be implemented by one or more integrated circuits, logic circuits, microprocessors, GPUs, DSPs, or controllers from any desired family or manufacturer that can be used to execute an AI/ML model, such as a neural network. In some examples, one or more of the example data ingestion manager **106**, the example data query manager **110**, the example data publishing manager **118**, the example node manager **122**, the example data security manager **132**, the example algorithm manager **134**, and/or the example analytics manager **136** can be implemented in or with at least one of the GPU **4142**, the VPU **4144**, the neural network processor **4146**, and/or, more generally, the acceleration circuitry **4140**, instead of or in addition to the

processor circuitry **4112**.

(536) FIG. **42** is a block diagram of an example processor platform **4200** structured to execute and/or instantiate the example machine readable instructions and/or the example operations of one(s) of FIGS. **17-40** to implement the data routing management circuitry **400** of FIG. **4**. The processor platform **4200** can be, for example, a server, a personal computer, a workstation, a self-learning machine (e.g., a neural network), a mobile device (e.g., a cell phone, a smart phone, a tablet such as an iPad™), a PDA, an Internet appliance, a DVD player, a CD player, a digital video recorder, a Blu-ray player, a gaming console, a personal video recorder, a set top box, a headset (e.g., an AR headset, a VR headset, etc.) or other wearable device, or any other type of computing device.

(537) The processor platform **4200** of the illustrated example includes processor circuitry **4212**. The processor circuitry **4212** of the illustrated example is hardware. For example, the processor circuitry **4212** can be implemented by one or more integrated circuits, logic circuits, FPGAs, microprocessors, CPUs, GPUs, DSPs, and/or microcontrollers from any desired family or manufacturer. The processor circuitry **4212** may be implemented by one or more semiconductor based (e.g., silicon based) devices. In this example, the processor circuitry **4212** implements the example machine-learning circuitry **420** (identified by ML CIRCUITRY), the example data query management circuitry **430** (identified by DATA QUERY MGMT CIRCUITRY), the example node management circuitry **440** (identified by NODE MGMT CIRCUITRY), and the example data publishing circuitry **450** (identified by DATA PUBLISH CIRCUITRY) of FIG. **4**.

(538) The processor circuitry **4212** of the illustrated example includes a local memory **4213** (e.g., a cache, registers, etc.). The processor circuitry **4212** of the illustrated example is in communication with a main memory including a volatile memory **4214** and a non-volatile memory **4216** by a bus **4218**. In some examples, the bus **4218** can implement the bus **480** of FIG. **4**. The volatile memory **4214** may be implemented by SDRAM, DRAM, RDRAM®, and/or any other type of RAM device. The non-volatile memory **4216** may be implemented by flash memory and/or any other desired type of memory device. Access to the main memory **4214**, **4216** of the illustrated example is controlled by a memory controller **4217**.

(539) The processor platform **4200** of the illustrated example also includes interface circuitry **4220**. The interface circuitry **4220** may be implemented by hardware in accordance with any type of interface standard, such as an Ethernet interface, a USB interface, a Bluetooth® interface, an NFC interface, a PCI interface, and/or a PCIe interface. In this example, the interface circuitry **4220** implements the example data ingestion circuitry **410** of FIG. **4**.

(540) In the illustrated example, one or more input devices **4222** are connected to the interface circuitry **4220**. The input device(s) **4222** permit(s) a user to enter data and/or commands into the processor circuitry **4212**. The input device(s) **4222** can be implemented by, for example, an audio sensor, a microphone, a camera (still or video), a keyboard, a button, a mouse, a touchscreen, a track-pad, a trackball, an isopoint device, and/or a voice recognition system.

(541) One or more output devices **4224** are also connected to the interface circuitry **4220** of the illustrated example. The output device(s) **4224** can be implemented, for example, by display devices (e.g., an LED, an OLED, an LCD, a CRT display, an IPS display, a touchscreen, etc.), a tactile output device, a printer, and/or speaker. The interface circuitry **4220** of the illustrated example, thus, typically includes a graphics driver card, a graphics driver chip, and/or graphics processor circuitry such as a GPU.

(542) The interface circuitry **4220** of the illustrated example also includes a communication device such as a transmitter, a receiver, a transceiver, a modem, a residential gateway, a wireless access point, and/or a network interface to facilitate exchange of data with external machines (e.g., computing devices of any kind) by a network **4226**. The communication can be by, for example, an Ethernet connection, a DSL connection, a telephone line connection, a coaxial cable system, a satellite system, a line-of-site wireless system, a cellular telephone system, an optical connection,

etc.

(543) The processor platform **4200** of the illustrated example also includes one or more mass storage devices **4228** to store software and/or data. Examples of such mass storage devices **4228** include magnetic storage devices, optical storage devices, floppy disk drives, HDDs, CDs, Blu-ray disk drives, RAID systems, solid state storage devices such as flash memory devices and/or SSDs, and DVD drives. In this example, the one or more mass storage devices **4228** implement the example datastore **460**, the example raw data **462** (identified by reference numeral **462**), the example metadata **464** (identified by reference numeral **464**), the example users **466** (identified by reference numeral **466**), the example nodes **468** (identified by reference numeral **468**), the example machine-learning models **470** (identified by reference numeral **470**), the example environment topology **472** (identified by reference numeral **472**), the example contextual data graph models **474** (identified by reference numeral **474**), and the example digital twins **476** (identified by reference numeral **476**) of FIG. 4.

(544) The machine executable instructions **4232**, which can be implemented by the example machine readable instructions of one(s) of FIGS. 17-40, may be stored in the mass storage device **4228**, in the volatile memory **4214**, in the non-volatile memory **4216**, and/or on a removable non-transitory computer readable storage medium such as a CD or DVD.

(545) The processor platform **4200** of the illustrated example of FIG. 42 includes example acceleration circuitry **4240**, which includes an example GPU **4242**, an example VPU **4244**, and an example neural network processor **4246**. In this example, the GPU **4242**, the VPU **4244**, the neural network processor **4246**, and/or, more generally, the acceleration circuitry **4240**, are in communication with different hardware of the processor platform **4200**, such as the volatile memory **4214**, the non-volatile memory **4216**, etc., via the bus **4218**. In this example, the neural network processor **4246** may be implemented by one or more integrated circuits, logic circuits, microprocessors, GPUs, DSPs, or controllers from any desired family or manufacturer that can be used to execute an AI/ML model, such as a neural network, which may be implemented by the machine-learning model **470**. In some examples, one or more of the example data ingestion circuitry **410**, the example machine-learning circuitry **420**, the example data query management circuitry **430**, the example node management circuitry **440**, and/or the example data publishing circuitry **450** can be implemented in or with at least one of the GPU **4242**, the VPU **4244**, the neural network processor **4246**, and/or, more generally, the acceleration circuitry **4240**, instead of or in addition to the processor circuitry **4212** and/or the interface circuitry **4220**.

(546) FIG. 43 is a block diagram of an example implementation of the processor circuitry **4112** of FIG. 41 and/or the processor circuitry **4212** of FIG. 42. In this example, the processor circuitry **4112** of FIG. 41 and/or the processor circuitry **4212** of FIG. 42 is implemented by a microprocessor **4300**. For example, the microprocessor **4300** may be a general purpose microprocessor (e.g., general purpose microprocessor circuitry). The microprocessor **4300** executes some or all of the machine-readable instructions of the flowcharts of FIGS. 17-40 to effectively instantiate the example data routing management circuitry **400** of FIG. 4 as logic circuits to perform the operations corresponding to those machine-readable instructions. In some such examples, the example data routing management circuitry **400** of FIG. 4 is instantiated by the hardware circuits of the microprocessor **4300** in combination with the instructions. For example, the microprocessor **4300** may be implemented by multi-core hardware circuitry such as a CPU, a DSP, a GPU, an XPU, etc. Although it may include any number of example cores **4302** (e.g., 1 core), the microprocessor **4300** of this example is a multi-core semiconductor device including N cores. The cores **4302** of the microprocessor **4300** may operate independently or may cooperate to execute machine-readable instructions. For example, machine code corresponding to a firmware program, an embedded software program, or a software program may be executed by one of the cores **4302** or may be executed by multiple ones of the cores **4302** at the same or different times. In some examples, the machine code corresponding to the firmware program, the embedded software

program, or the software program is split into threads and executed in parallel by two or more of the cores **4302**. The software program may correspond to a portion or all of the machine-readable instructions and/or operations represented by the flowcharts of FIGS. **17-40**.

(547) The cores **4302** may communicate by a first example bus **4304**. In some examples, the first bus **4304** may be implemented by a communication bus to effectuate communication associated with one(s) of the cores **4302**. For example, the first bus **4304** may be implemented by at least one of an Inter-Integrated Circuit (I2C) bus, a Serial Peripheral Interface (SPI) bus, a PCI bus, or a PCIe bus. Additionally or alternatively, the first bus **4304** may be implemented by any other type of computing or electrical bus. The cores **4302** may obtain data, instructions, and/or signals from one or more external devices by example interface circuitry **4306**. The cores **4302** may output data, instructions, and/or signals to the one or more external devices by the interface circuitry **4306**. Although the cores **4302** of this example include example local memory **4320** (e.g., Level 1 (L1) cache that may be split into an L1 data cache and an L1 instruction cache), the microprocessor **4300** also includes example shared memory **4310** that may be shared by the cores (e.g., Level 2 (L2 cache)) for high-speed access to data and/or instructions. Data and/or instructions may be transferred (e.g., shared) by writing to and/or reading from the shared memory **4310**. The local memory **4320** of each of the cores **4302** and the shared memory **4310** may be part of a hierarchy of storage devices including multiple levels of cache memory and the main memory (e.g., the main memory **4114**, **4116** of FIG. **41**, the main memory **4214**, **4216** of FIG. **42**, etc.). Typically, higher levels of memory in the hierarchy exhibit lower access time and have smaller storage capacity than lower levels of memory. Changes in the various levels of the cache hierarchy are managed (e.g., coordinated) by a cache coherency policy.

(548) Each core **4302** may be referred to as a CPU, DSP, GPU, etc., or any other type of hardware circuitry. Each core **4302** includes control unit circuitry **4314**, arithmetic and logic (AL) circuitry (sometimes referred to as an ALU) **4316**, a plurality of registers **4318**, the local memory **4320**, and a second example bus **4322**. Other structures may be present. For example, each core **4302** may include vector unit circuitry, single instruction multiple data (SIMD) unit circuitry, load/store unit (LSU) circuitry, branch/jump unit circuitry, floating-point unit (FPU) circuitry, etc. The control unit circuitry **4314** includes semiconductor-based circuits structured to control (e.g., coordinate) data movement within the corresponding core **4302**. The AL circuitry **4316** includes semiconductor-based circuits structured to perform one or more mathematic and/or logic operations on the data within the corresponding core **4302**. The AL circuitry **4316** of some examples performs integer based operations. In other examples, the AL circuitry **4316** also performs floating point operations. In yet other examples, the AL circuitry **4316** may include first AL circuitry that performs integer based operations and second AL circuitry that performs floating point operations. In some examples, the AL circuitry **4316** may be referred to as an Arithmetic Logic Unit (ALU). The registers **4318** are semiconductor-based structures to store data and/or instructions such as results of one or more of the operations performed by the AL circuitry **4316** of the corresponding core **4302**. For example, the registers **4318** may include vector register(s), SIMD register(s), general purpose register(s), flag register(s), segment register(s), machine specific register(s), instruction pointer register(s), control register(s), debug register(s), memory management register(s), machine check register(s), etc. The registers **4318** may be arranged in a bank as shown in FIG. **43**.

Alternatively, the registers **4318** may be organized in any other arrangement, format, or structure including distributed throughout the core **4302** to shorten access time. The second bus **4322** may be implemented by at least one of an I2C bus, a SPI bus, a PCI bus, or a PCIe bus

(549) Each core **4302** and/or, more generally, the microprocessor **4300** may include additional and/or alternate structures to those shown and described above. For example, one or more clock circuits, one or more power supplies, one or more power gates, one or more cache home agents (CHAs), one or more converged/common mesh stops (CMSs), one or more shifters (e.g., barrel shifter(s)) and/or other circuitry may be present. The microprocessor **4300** is a semiconductor

device fabricated to include many transistors interconnected to implement the structures described above in one or more integrated circuits (ICs) contained in one or more packages. The processor circuitry may include and/or cooperate with one or more accelerators. In some examples, accelerators are implemented by logic circuitry to perform certain tasks more quickly and/or efficiently than can be done by a general purpose processor. Examples of accelerators include ASICs and FPGAs such as those discussed herein. A GPU or other programmable device can also be an accelerator. Accelerators may be on-board the processor circuitry, in the same chip package as the processor circuitry and/or in one or more separate packages from the processor circuitry. (550) FIG. 44 is a block diagram of another example implementation of the processor circuitry 4112 of FIG. 41 and/or the processor circuitry 4212 of FIG. 42. In this example, the processor circuitry 4112 of FIG. 41 and/or the processor circuitry 4212 of FIG. 42 is implemented by FPGA circuitry 4400. For example, the FPGA circuitry 4400 may be implemented by an FPGA. The FPGA circuitry 4400 can be used, for example, to perform operations that could otherwise be performed by the example microprocessor 4300 of FIG. 43 executing corresponding machine-readable instructions. However, once configured, the FPGA circuitry 4400 instantiates the machine-readable instructions in hardware and, thus, can often execute the operations faster than they could be performed by a general purpose microprocessor executing the corresponding software.

(551) More specifically, in contrast to the microprocessor 4300 of FIG. 43 described above (which is a general purpose device that may be programmed to execute some or all of the machine-readable instructions represented by the flowcharts of FIGS. 17-40 but whose interconnections and logic circuitry are fixed once fabricated), the FPGA circuitry 4400 of the example of FIG. 44 includes interconnections and logic circuitry that may be configured and/or interconnected in different ways after fabrication to instantiate, for example, some or all of the machine-readable instructions represented by the flowcharts of FIGS. 17-40. In particular, the FPGA circuitry 4400 may be thought of as an array of logic gates, interconnections, and switches. The switches can be programmed to change how the logic gates are interconnected by the interconnections, effectively forming one or more dedicated logic circuits (unless and until the FPGA circuitry 4400 is reprogrammed). The configured logic circuits enable the logic gates to cooperate in different ways to perform different operations on data received by input circuitry. Those operations may correspond to some or all of the software represented by the flowcharts of FIGS. 17-40. As such, the FPGA circuitry 4400 may be structured to effectively instantiate some or all of the machine-readable instructions of the flowcharts of FIGS. 17-40 as dedicated logic circuits to perform the operations corresponding to those software instructions in a dedicated manner analogous to an ASIC. Therefore, the FPGA circuitry 4400 may perform the operations corresponding to the some or all of the machine-readable instructions of FIGS. 17-40 faster than the general purpose microprocessor can execute the same.

(552) In the example of FIG. 44, the FPGA circuitry 4400 is structured to be programmed (and/or reprogrammed one or more times) by an end user by a hardware description language (HDL) such as Verilog. The FPGA circuitry 4400 of FIG. 44, includes example input/output (I/O) circuitry 4402 to obtain and/or output data to/from example configuration circuitry 4404 and/or external hardware 4406. For example, the configuration circuitry 4404 may be implemented by interface circuitry that may obtain machine-readable instructions to configure the FPGA circuitry 4400, or portion(s) thereof. In some such examples, the configuration circuitry 4404 may obtain the machine-readable instructions from a user, a machine (e.g., hardware circuitry (e.g., programmed or dedicated circuitry) that may implement an Artificial Intelligence/Machine Learning (AI/ML) model to generate the instructions), etc. In some examples, the external hardware 4406 may be implemented by external hardware circuitry. For example, the external hardware 4406 may be implemented by the microprocessor 4300 of FIG. 43. The FPGA circuitry 4400 also includes an array of example logic gate circuitry 4408, a plurality of example configurable interconnections 4410, and example

storage circuitry **4412**. The logic gate circuitry **4408** and the configurable interconnections **4410** are configurable to instantiate one or more operations that may correspond to at least some of the machine-readable instructions of FIGS. **17-40** and/or other desired operations. The logic gate circuitry **4408** shown in FIG. **44** is fabricated in groups or blocks. Each block includes semiconductor-based electrical structures that may be configured into logic circuits. In some examples, the electrical structures include logic gates (e.g., And gates, Or gates, Nor gates, etc.) that provide basic building blocks for logic circuits. Electrically controllable switches (e.g., transistors) are present within each of the logic gate circuitry **4408** to enable configuration of the electrical structures and/or the logic gates to form circuits to perform desired operations. The logic gate circuitry **4408** may include other electrical structures such as look-up tables (LUTs), registers (e.g., flip-flops or latches), multiplexers, etc.

(553) The configurable interconnections **4410** of the illustrated example are conductive pathways, traces, vias, or the like that may include electrically controllable switches (e.g., transistors) whose state can be changed by programming (e.g., using an HDL instruction language) to activate or deactivate one or more connections between one or more of the logic gate circuitry **4408** to program desired logic circuits.

(554) The storage circuitry **4412** of the illustrated example is structured to store result(s) of the one or more of the operations performed by corresponding logic gates. The storage circuitry **4412** may be implemented by registers or the like. In the illustrated example, the storage circuitry **4412** is distributed amongst the logic gate circuitry **4408** to facilitate access and increase execution speed.

(555) The example FPGA circuitry **4400** of FIG. **44** also includes example Dedicated Operations Circuitry **4414**. In this example, the Dedicated Operations Circuitry **4414** includes special purpose circuitry **4416** that may be invoked to implement commonly used functions to avoid the need to program those functions in the field. Examples of such special purpose circuitry **4416** include memory (e.g., DRAM) controller circuitry, PCIe controller circuitry, clock circuitry, transceiver circuitry, memory, and multiplier-accumulator circuitry. Other types of special purpose circuitry may be present. In some examples, the FPGA circuitry **4400** may also include example general purpose programmable circuitry **4418** such as an example CPU **4420** and/or an example DSP **4422**. Other general purpose programmable circuitry **4418** may additionally or alternatively be present such as a GPU, an XPU, etc., that can be programmed to perform other operations.

(556) Although FIGS. **43** and **44** illustrate two example implementations of the processor circuitry **4112** of FIG. **41** and/or the processor circuitry **4212** of FIG. **42**, many other approaches are contemplated. For example, as mentioned above, modern FPGA circuitry may include an on-board CPU, such as one or more of the example CPU **4420** of FIG. **44**. Therefore, the processor circuitry **4112** of FIG. **41** and/or the processor circuitry **4212** of FIG. **42** may additionally be implemented by combining the example microprocessor **4300** of FIG. **43** and the example FPGA circuitry **4400** of FIG. **44**. In some such hybrid examples, a first portion of the machine-readable instructions represented by the flowcharts of FIGS. **17-40** may be executed by one or more of the cores **4302** of FIG. **43**, a second portion of the machine-readable instructions represented by the flowcharts of FIGS. **17-40** may be executed by the FPGA circuitry **4400** of FIG. **44**, and/or a third portion of the machine-readable instructions represented by the flowcharts of FIGS. **17-40** may be executed by an ASIC. It should be understood that some or all of the example data routing management circuitry **400** of FIG. **4** may, thus, be instantiated at the same or different times. Some or all of the circuitry may be instantiated, for example, in one or more threads executing concurrently and/or in series. Moreover, in some examples, some or all of the example data routing management circuitry **400** of FIG. **4** may be implemented within one or more virtual machines and/or containers executing on the microprocessor.

(557) In some examples, the processor circuitry **4112** of FIG. **41** and/or the processor circuitry **4212** of FIG. **42** may be in one or more packages. For example, the microprocessor **4300** of FIG. **43** and/or the FPGA circuitry **4400** of FIG. **44** may be in one or more packages. In some examples,

an XPU may be implemented by the processor circuitry **4112** of FIG. **41** and/or the processor circuitry **4212** of FIG. **42**, which may be in one or more packages. For example, the XPU may include a CPU in one package, a DSP in another package, a GPU in yet another package, and an FPGA in still yet another package.

(558) A block diagram illustrating an example software distribution platform **4505** to distribute software such as the example machine-readable instructions **4132** of FIG. **41** and/or the example machine-readable instructions **4232** of FIG. **42** to hardware devices owned and/or operated by third parties is illustrated in FIG. **45**. The example software distribution platform **4505** may be implemented by any computer server, data facility, cloud service, etc., capable of storing and transmitting software to other computing devices. The third parties may be customers of the entity owning and/or operating the software distribution platform **4505**. For example, the entity that owns and/or operates the software distribution platform **4505** may be a developer, a seller, and/or a licensor of software such as the example machine-readable instructions **4132** of FIG. **41** and/or the example machine-readable instructions **4232** of FIG. **42**. The third parties may be consumers, users, retailers, OEMs, etc., who purchase and/or license the software for use and/or re-sale and/or sub-licensing. In the illustrated example, the software distribution platform **4505** includes one or more servers and one or more storage devices. The storage devices store the example machine-readable instructions **4132** of FIG. **41** and/or the example machine-readable instructions **4232** of FIG. **42**, which may correspond to the example machine-readable instructions **1700, 1800, 1900, 2000, 2100, 2200, 2300, 2400, 2500, 2600, 2700, 2800, 2900, 3000, 3100, 3200, 3300, 3400, 3500, 3600, 3700, 3800, 3900, 4000** of FIGS. **17-40**, as described above. The one or more servers of the example software distribution platform **4505** are in communication with an example network **4510**, which may correspond to any one or more of the Internet and/or any of the example networks **126, 128, 130, 206, 208, 210, 322, 1210, 4126, 4226** described above. In some examples, the one or more servers are responsive to requests to transmit the software to a requesting party as part of a commercial transaction. Payment for the delivery, sale, and/or license of the software may be handled by the one or more servers of the software distribution platform and/or by a third party payment entity. The servers enable purchasers and/or licensors to download the example machine-readable instructions **4132** of FIG. **41** and/or the example machine-readable instructions **4232** of FIG. **42** from the software distribution platform **4505**. For example, the software, which may correspond to the example machine-readable instructions **4132** of FIG. **41**, may be downloaded to the example processor platform **4100**, which is to execute the example machine-readable instructions **4132** to implement the example ADM system **100** of FIG. **1**. In some examples, the software, which may correspond to the example machine-readable instructions **4232** of FIG. **42**, may be downloaded to the example processor platform **4200**, which is to execute the example machine-readable instructions **4232** to implement the example data routing management circuitry **400** of FIG. **4**. In some examples, one or more servers of the software distribution platform **4505** periodically offer, transmit, and/or force updates to the software (e.g., the example machine-readable instructions **4132** of FIG. **41** and/or the example machine-readable instructions **4232** of FIG. **42**) to ensure improvements, patches, updates, etc., are distributed and applied to the software at the end user devices.

(559) From the foregoing, it will be appreciated that example systems, methods, apparatus, and articles of manufacture have been disclosed for proactive data routing. Disclosed systems, methods, apparatus, and articles of manufacture improve the efficiency of using a computing device by routing data, messages, alerts, and the like to pertinent users rather than broadcasting to an entire network, which can reduce the computational, memory, and network resources needed to convey data to the pertinent users. Disclosed systems, methods, apparatus, and articles of manufacture are accordingly directed to one or more improvement(s) in the operation of a machine such as a computer or other electronic and/or mechanical device.

(560) Example methods, apparatus, systems, and articles of manufacture for proactive data routing

are disclosed herein. Further examples and combinations thereof include the following:

(561) Example 1 includes an apparatus for data routing, the apparatus comprising at least one memory, machine-readable instructions, and processor circuitry to execute the machine-readable instructions to at least execute a machine-learning model to output a first data routing path in a network environment based on metadata associated with an event in the network environment, a first message based on the event to be transmitted to a first node based on the first data routing path, the first data routing path to have a first strength of association with at least one of the metadata or the event, after a detection of a change of the first data routing path to a second data routing path, retrain the machine-learning model to output a third data routing path based on the second data routing path, the third data routing path to have a second strength of association with the at least one of the metadata or the event, the second strength of association to be greater than the first strength of association, and cause transmission of a second message to the first node based on the third data routing path after an identification of the event.

(562) Example 2 includes the apparatus of example 1, wherein the processor circuitry is to be instantiated after receiving the machine-readable instructions.

(563) Example 3 includes the apparatus of example 1, wherein the metadata is first metadata, the identification is a first identification, and the processor circuitry is to cause transmission of a third message after a second identification of a second event, the second event associated with second metadata, the second metadata to include a portion of the first metadata.

(564) Example 4 includes the apparatus of example 1, wherein the processor circuitry is to generate the third data routing path to be representative of the transmission of the second message to the first node via one or more second nodes.

(565) Example 5 includes the apparatus of example 1, wherein the first data routing path is representative of transmission of the first message to the first node via one or more second nodes, and the processor circuitry is to detect the change to be representative of the transmission of the first message to the first node via one or more third nodes.

(566) Example 6 includes the apparatus of example 1, wherein the processor circuitry is to, after a determination that a user associated with the first node is unable to view video data, generate the second message to include audio data to be output to the user.

(567) Example 7 includes the apparatus of example 1, wherein the processor circuitry is to, after a determination that the first node has a bandwidth less than a threshold, generate the second message to include at least one of audio data or text data.

(568) Example 8 includes the apparatus of example 7, wherein the processor circuitry is to cause transmission of the at least one of audio data or text data via a first network interface, and cause transmission of video data via a second network interface, the second network interface different from the first network interface.

(569) Example 9 includes the apparatus of example 1, wherein the processor circuitry is to, after a determination that the first node has a bandwidth that satisfies a threshold, generate the second message to include at least one of audio data, text data, or video data.

(570) Example 10 includes the apparatus of example 1, wherein the processor circuitry is to multicast the second message to the first node and one or more second nodes, the one or more second nodes associated with the metadata.

(571) Example 11 includes the apparatus of example 1, wherein the metadata is first metadata, the processor circuitry is to generate the second message to include first data, second data, and second metadata, the first data associated with a time duration, and the second metadata to cause the first node to access the second data after the time duration has elapsed.

(572) Example 12 includes the apparatus of example 1, wherein the processor circuitry is to generate the second message to include first data and second data, the first data associated with a time duration, and after transmission of the first data to the first node, cause the transmission of the second data to the first node after the time duration has elapsed.

(573) Example 13 includes the apparatus of example 1, wherein the processor circuitry is to, after a determination that the first node is associated with a first network interface and a second network interface, cause transmission of a first portion of the second message to the first network interface and a second portion of the second message to the second network interface.

(574) Example 14 includes the apparatus of example 13, wherein the first network interface is a Wi-Fi network interface and the second network interface is a cellular network interface.

(575) Example 15 includes the apparatus of example 1, wherein the processor circuitry is to execute a machine-learning microservice to cause execution of the machine-learning model.

(576) Example 16 includes the apparatus of example 1, wherein the machine-learning model is a digital twin associated with the network environment.

(577) Example 17 includes the apparatus of example 16, wherein the processor circuitry is to predict the first data routing path based on simulation of the transmission of the first message in the network environment, the simulation based on the digital twin.

(578) Example 18 includes the apparatus of example 1, wherein the metadata is first metadata, the first node is a first device, the network environment includes a second device and a third device, the processor circuitry is to generate the second message to include second metadata, the first device is not associated with an operation indicated by the second metadata, and the first device to cause at least one of the second device or the third device to perform the operation based on the second metadata.

(579) Example 19 includes the apparatus of example 18, wherein the processor circuitry is to cause transmission of data associated with the operation to the at least one of the second device or the third device to effectuate performance of the operation by the at least one of the second device or the third device.

(580) Example 20 includes an apparatus for data routing, the apparatus comprising means for executing a machine-learning model, the means for executing to output a first data routing path in a network environment based on metadata associated with an event in the network environment, a first message based on the event to be transmitted to a first node based on the first data routing path, the first data routing path to have a first strength of association with at least one of the metadata or the event, and after a detection of a change of the first data routing path to a second data routing path, retrain the machine-learning model to output a third data routing path based on the second data routing path, the third data routing path to have a second strength of association with the at least one of the metadata or the event, the second strength of association to be greater than the first strength of association, and means for causing transmission of a second message to the first node based on the third data routing path after an identification of the event.

(581) Example 21 includes the apparatus of example 20, wherein the metadata is first metadata, the identification is a first identification, and the means for causing is to cause transmission of a third message after a second identification of a second event, the second event associated with second metadata, the second metadata to include a portion of the first metadata.

(582) Example 22 includes the apparatus of example 20, wherein the means for executing is to generate the third data routing path to be representative of the transmission of the second message to the first node via one or more second nodes.

(583) Example 23 includes the apparatus of example 20, wherein the first data routing path is representative of transmission of the first message to the first node via one or more second nodes, and further including means for detecting the change to be representative of the transmission of the first message to the first node via one or more third nodes.

(584) Example 24 includes the apparatus of example 20, wherein the means for causing is to, after a determination that a user associated with the first node is unable to view video data, generate the second message to include audio data to be output to the user.

(585) Example 25 includes the apparatus of example 20, wherein the means for causing is to, after a determination that the first node has a bandwidth less than a threshold, generate the second

message to include at least one of audio data or text data.

(586) Example 26 includes the apparatus of example 25, wherein the means for causing is to cause transmission of the at least one of audio data or text data via a first network interface, and cause transmission of video data via a second network interface, the second network interface different from the first network interface.

(587) Example 27 includes the apparatus of example 20, wherein the means for causing is to, after a determination that the first node has a bandwidth that satisfies a threshold, generate the second message to include at least one of audio data, text data, or video data.

(588) Example 28 includes the apparatus of example 20, wherein the means for causing is to multicast the second message to the first node and one or more second nodes, the one or more second nodes associated with the metadata.

(589) Example 29 includes the apparatus of example 20, wherein the metadata is first metadata, the means for causing is to generate the second message to include first data, second data, and second metadata, the first data associated with a time duration, and the second metadata to cause the first node to access the second data after the time duration has elapsed.

(590) Example 30 includes the apparatus of example 20, wherein the means for causing is to generate the second message to include first data and second data, the first data associated with a time duration, and after transmission of the first data to the first node, cause the transmission of the second data to the first node after the time duration has elapsed.

(591) Example 31 includes the apparatus of example 20, wherein the means for causing is to, after a determination that the first node is associated with a first network interface and a second network interface, cause transmission of a first portion of the second message to the first network interface and a second portion of the second message to the second network interface.

(592) Example 32 includes the apparatus of example 31, wherein the first network interface is a Wi-Fi network interface and the second network interface is a cellular network interface.

(593) Example 33 includes the apparatus of example 20, wherein the means for executing is to execute a machine-learning microservice to cause execution of the machine-learning model.

(594) Example 34 includes the apparatus of example 20, wherein the machine-learning model is a digital twin associated with the network environment.

(595) Example 35 includes the apparatus of example 34, wherein the means for executing is to predict the first data routing path based on simulation of the transmission of the first message in the network environment, the simulation based on the digital twin.

(596) Example 36 includes the apparatus of example 19, wherein the metadata is first metadata, the first node is a first device, the network environment includes a second device and a third device, the means for causing is to generate the second message to include second metadata, the first device is not associated with an operation indicated by the second metadata, and the first device to cause at least one of the second device or the third device to perform the operation based on the second metadata.

(597) Example 37 includes the apparatus of example 36, wherein the means for causing is to cause transmission of data associated with the operation to the at least one of the second device or the third device to effectuate performance of the operation by the at least one of the second device or the third device.

(598) Example 38 includes at least one non-transitory computer readable storage medium comprising instructions that, when executed, cause programmable circuitry to at least execute a machine-learning model to output a first data routing path in a network environment based on metadata associated with an event in the network environment, a first message based on the event to be transmitted to a first node based on the first data routing path, the first data routing path to have a first strength of association with at least one of the metadata or the event, after a detection of a change of the first data routing path to a second data routing path, retrain the machine-learning model to output a third data routing path based on the second data routing path, the third data

routing path to have a second strength of association with the at least one of the metadata or the event, the second strength of association to be greater than the first strength of association, and cause transmission of a second message to the first node based on the third data routing path after an identification of the event.

(599) Example 39 includes the at least one non-transitory computer readable storage medium of example 38, wherein the metadata is first metadata, the identification is a first identification, and the instructions are to cause the programmable circuitry to cause transmission of a third message after a second identification of a second event, the second event associated with second metadata, the second metadata to include a portion of the first metadata.

(600) Example 40 includes the at least one non-transitory computer readable storage medium of example 38, wherein the instructions are to cause the programmable circuitry to generate the third data routing path to be representative of the transmission of the second message to the first node via one or more second nodes.

(601) Example 41 includes the at least one non-transitory computer readable storage medium of example 38, wherein the first data routing path is representative of transmission of the first message to the first node via one or more second nodes, and the instructions are to cause the programmable circuitry to detect the change to be representative of the transmission of the first message to the first node via one or more third nodes.

(602) Example 42 includes the at least one non-transitory computer readable storage medium of example 38, wherein the instructions are to cause the programmable circuitry to, after a determination that a user associated with the first node is unable to view video data, generate the second message to include audio data to be output to the user.

(603) Example 43 includes the at least one non-transitory computer readable storage medium of example 38, wherein the instructions are to cause the programmable circuitry to, after a determination that the first node has a bandwidth less than a threshold, generate the second message to include at least one of audio data or text data.

(604) Example 44 includes the at least one non-transitory computer readable storage medium of example 43, wherein the instructions are to cause the programmable circuitry to cause transmission of the at least one of audio data or text data via a first network interface, and cause transmission of video data via a second network interface, the second network interface different from the first network interface.

(605) Example 45 includes the at least one non-transitory computer readable storage medium of example 38, wherein the instructions are to cause the programmable circuitry to, after a determination that the first node has a bandwidth that satisfies a threshold, generate the second message to include at least one of audio data, text data, or video data.

(606) Example 46 includes the at least one non-transitory computer readable storage medium of example 38, wherein the instructions are to cause the programmable circuitry to multicast the second message to the first node and one or more second nodes, the one or more second nodes associated with the metadata.

(607) Example 47 includes the at least one non-transitory computer readable storage medium of example 38, wherein the metadata is first metadata, the instructions are to cause the programmable circuitry to generate the second message to include first data, second data, and second metadata, the first data associated with a time duration, and the second metadata to cause the first node to access the second data after the time duration has elapsed.

(608) Example 48 includes the at least one non-transitory computer readable storage medium of example 38, wherein the instructions are to cause the programmable circuitry to generate the second message to include first data and second data, the first data associated with a time duration, and after transmission of the first data to the first node, cause the transmission of the second data to the first node after the time duration has elapsed.

(609) Example 49 includes the at least one non-transitory computer readable storage medium of

example 38, wherein the instructions are to cause the programmable circuitry to, after a determination that the first node is associated with a first network interface and a second network interface, cause transmission of a first portion of the second message to the first network interface and a second portion of the second message to the second network interface.

(610) Example 50 includes the at least one non-transitory computer readable storage medium of example 49, wherein the first network interface is a Wi-Fi network interface and the second network interface is a cellular network interface.

(611) Example 51 includes the at least one non-transitory computer readable storage medium of example 38, wherein the instructions are to cause the programmable circuitry to execute a machine-learning microservice to cause execution of the machine-learning model.

(612) Example 52 includes the at least one non-transitory computer readable storage medium of example 38, wherein the machine-learning model is a digital twin associated with the network environment.

(613) Example 53 includes the at least one non-transitory computer readable storage medium of example 52, wherein the instructions are to cause the programmable circuitry to predict the first data routing path based on emulation of the transmission of the first message in the network environment, the emulation based on the digital twin.

(614) Example 54 includes the at least one non-transitory computer readable storage medium of example 38, wherein the metadata is first metadata, the first node is a first device, the network environment includes a second device and a third device, the instructions are to cause the programmable circuitry to generate the second message to include second metadata, the first device is not associated with an operation indicated by the second metadata, and the first device to cause at least one of the second device or the third device to perform the operation based on the second metadata.

(615) Example 55 includes the at least one non-transitory computer readable storage medium of example 54, wherein the instructions are to cause the programmable circuitry to cause transmission of data associated with the operation to the at least one of the second device or the third device to effectuate performance of the operation by the at least one of the second device or the third device.

(616) Example 56 includes a method for data routing, the method comprising executing a machine-learning model to output a first data routing path in a network environment based on metadata associated with event data in the network environment, a first message based on the event data to be transmitted to a first node based on the first data routing path, the first data routing path to have a first strength of association with at least one of the metadata or the event data, after detecting a change of the first data routing path to a second data routing path, retraining the machine-learning model to output a third data routing path based on the second data routing path, the third data routing path to have a second strength of association with the at least one of the metadata or the event data, the second strength of association to be greater than the first strength of association, and transmitting a second message to the first node based on the third data routing path after an identification of the event data.

(617) Example 57 includes the method of example 56, wherein the metadata is first metadata, the identification is a first identification, and further including transmitting a third message after a second identification of second event data, the second event data associated with second metadata, the second metadata to include a portion of the first metadata.

(618) Example 58 includes method of example 57, wherein the third message includes at least one of data or the second metadata directly associated with the data.

(619) Example 59 includes the method of example 56, further including generating the third data routing path to be representative of the transmitting of the second message to the first node via one or more second nodes.

(620) Example 60 includes the method of example 56, wherein the first data routing path is representative of transmission of the first message to the first node via one or more second nodes,

and further including detecting the change to be representative of the transmission of the first message to the first node via one or more third nodes.

(621) Example 61 includes the method of example 56, further including, after a determination that a user associated with the first node is unable to view video data, generating the second message to include audio data to be output to the user.

(622) Example 62 includes the method of example 56, further including, after a determination that the first node has a bandwidth less than a threshold, generating the second message to include at least one of audio data or text data.

(623) Example 63 includes the method of example 62, further including transmitting the at least one of audio data or text data via a first network interface, and transmitting video data via a second network interface, the second network interface different from the first network interface.

(624) Example 64 includes the method of example 56, further including, after a determination that the first node has a bandwidth that satisfies a threshold, generating the second message to include at least one of audio data, text data, or video data.

(625) Example 65 includes the method of example 56, further including multicasting the second message to the first node and one or more second nodes, the one or more second nodes associated with the metadata.

(626) Example 66 includes the method of example 56, wherein the metadata is first metadata, and further including generating the second message to include first data, second data, and second metadata, the first data associated with a time duration, and the second metadata to cause the first node to access the second data after the time duration has elapsed.

(627) Example 67 includes the method of example 56, further including generating the second message to include first data and second data, the first data associated with a time duration, and after transmitting the first data to the first node, transmitting the second data to the first node after the time duration has elapsed.

(628) Example 68 includes the method of example 56, further including, after a determination that the first node is associated with a first network interface and a second network interface, transmitting a first portion of the second message to the first network interface and a second portion of the second message to the second network interface.

(629) Example 69 includes the method of example 68, wherein the first network interface is a Wi-Fi network interface and the second network interface is a cellular network interface.

(630) Example 70 includes the method of example 56, further including executing a machine-learning microservice to cause execution of the machine-learning model.

(631) Example 71 includes the method of example 56, wherein the machine-learning model is a digital twin associated with the network environment.

(632) Example 72 includes the method of example 71, further including predicting the first data routing path based on simulating the transmitting of the first message in the network environment, the simulating based on the digital twin.

(633) Example 73 includes the method of example 56, wherein the metadata is first metadata, the first node is a first device, the network environment includes a second device and a third device, and further including generating the second message to include second metadata, the first device is not associated with an operation indicated by the second metadata, and the first device to cause at least one of the second device or the third device to perform the operation based on the second metadata.

(634) Example 74 includes the method of example 73, further including transmitting data associated with the operation to the at least one of the second device or the third device to effectuate performance of the operation by the at least one of the second device or the third device.

(635) The following claims are hereby incorporated into this Detailed Description by this reference. Although certain example systems, methods, apparatus, and articles of manufacture have been disclosed herein, the scope of coverage of this patent is not limited thereto. On the contrary, this

patent covers all systems, methods, apparatus, and articles of manufacture fairly falling within the scope of the claims of this patent.

Claims

1. An apparatus comprising: at least one memory; machine-readable instructions; and at least one processor circuit to utilize the machine-readable instructions to at least: execute a machine-learning model to output a first data routing path in a network environment based on metadata associated with an event in the network environment, a first message based on the event to be transmitted to a first node based on the first data routing path, the first data routing path representative of transmission of the first message to the first node via one or more second nodes, the first data routing path to have a first strength of association with at least one of the metadata or the event; detect a change of the first data routing path to a second data routing path, the second data routing path representative of transmission of the first message to the first node via one or more third nodes; after detection of the change, retrain the machine-learning model to output a third data routing path based on the second data routing path, the third data routing path to have a second strength of association with the at least one of the metadata or the event, the second strength of association to be greater than the first strength of association; and cause transmission of a second message to the first node based on the third data routing path after an identification of the event.
2. The apparatus of claim 1, wherein one or more of the at least one processor circuit is to be instantiated after receiving the machine-readable instructions.
3. The apparatus of claim 1, wherein the event is a first event, the metadata is first metadata, the identification is a first identification, and one or more of the at least one processor circuit is to cause transmission of a third message after a second identification of a second event, the second event associated with second metadata, the second metadata to include a portion of the first metadata.
4. The apparatus of claim 1, wherein the first data routing path is representative of predicted transmission of the first message to the first node via the one or more second nodes, and the second data routing path is representative of actual transmission of the first message to the first node via the one or more third nodes.
5. The apparatus of claim 1, wherein one or more of the at least one processor circuit is to multicast the second message to the first node and one or more fourth nodes, the one or more fourth nodes associated with the metadata.
6. An apparatus comprising: at least one memory; machine-readable instructions; and at least one processor circuit to utilize the machine-readable instruction to at least: execute a machine-learning model to output a first data routing path in a network environment based on metadata associated with an event in the network environment, a first message based on the event to be transmitted to a first node based on the first data routing path, the first data routing path to have a first strength of association with at least one of the metadata or the event; after a detection of a change of the first data routing path to a second data routing path, retrain the machine-learning model to output a third data routing path based on the second data routing path, the third data routing path to have a second strength of association with the at least one of the metadata or the event, the second strength of association to be greater than the first strength of association; cause transmission of a second message to the first node based on the third data routing path after an identification of the event; and after a determination that the first node is associated with a first network interface and a second network interface, cause transmission of a first portion of the second message to the first network interface and a second portion of the second message to the second network interface.
7. The apparatus of claim 6, wherein the first network interface is a Wi-Fi network interface and the second network interface is a cellular network interface.
8. At least one non-transitory computer readable storage medium comprising instructions to cause

at least one processor circuit to at least: execute a machine-learning model to output a first data routing path in a network environment based on metadata associated with an event in the network environment, a first message based on the event to be transmitted to a first node based on the first data routing path, the first data routing path to have a first strength of association with at least one of the metadata or the event; after a detection of a change of the first data routing path to a second data routing path, retrain the machine-learning model to output a third data routing path based on the second data routing path, the third data routing path to have a second strength of association with the at least one of the metadata or the event, the second strength of association to be greater than the first strength of association; and cause transmission of a second message to the first node based on the third data routing path after an identification of the event, the third data routing path representative of transmission of the second message to the first node via one or more second nodes.

9. The at least one non-transitory computer readable storage medium of claim 8, wherein the first data routing path is representative of transmission of the first message to the first node via one or more third nodes, and the instructions cause one or more of the at least one processor circuit to detect the change to be representative of transmission of the first message to the first node via one or more fourth nodes.

10. The at least one non-transitory computer readable storage medium of claim 8, wherein the instructions cause one or more of the at least one processor circuit to, after a determination that a user associated with the first node is unable to view video data, generate the second message to include audio data to be output to the user.

11. The at least one non-transitory computer readable storage medium of claim 8, wherein the instructions cause one or more of the at least one processor circuit to, after a determination that the first node has a bandwidth less than a threshold, generate the second message to include at least one of audio data or text data.

12. At least one non-transitory computer readable storage medium comprising instructions to cause at least one processor circuit to at least: execute a machine-learning model to output a first data routing path in a network environment based on metadata associated with an event in the network environment, a first message based on the event to be transmitted to a first node based on the first data routing path, the first data routing path to have a first strength of association with at least one of the metadata or the event; after a detection of a change of the first data routing path to a second data routing path, retrain the machine-learning model to output a third data routing path based on the second data routing path, the third data routing path to have a second strength of association with the at least one of the metadata or the event, the second strength of association to be greater than the first strength of association; after a determination that the first node has a bandwidth that satisfies a threshold, generate a second message to include at least one of audio data, text data, or video data; and cause transmission of the second message to the first node based on the third data routing path after an identification of the event.

13. The at least one non-transitory computer readable storage medium of claim 8, wherein the metadata is first metadata, the instructions cause one or more of the at least one processor circuit to generate the second message to include first data, second data, and second metadata, the first data associated with a time duration, and the second metadata to cause the first node to access the second data after the time duration has elapsed.

14. The at least one non-transitory computer readable storage medium of claim 8, wherein the instructions cause one or more of the at least one processor circuit to: generate the second message to include first data and second data, the first data associated with a time duration; and after transmission of the first data to the first node, cause the transmission of the second data to the first node after the time duration has elapsed.

15. A method comprising: executing a machine-learning model to output a first data routing path in a network environment based on first metadata associated with event data in the network

environment, a first message based on the event data to be transmitted to a first node based on the first data routing path, the first data routing path to have a first strength of association with at least one of the first metadata or the event data; after detecting a change of the first data routing path to a second data routing path, retraining the machine-learning model to output a third data routing path based on the second data routing path, the third data routing path to have a second strength of association with the at least one of the first metadata or the event data, the second strength of association to be greater than the first strength of association; generating a second message to include first data, second data, and second metadata, the first data associated with a time duration; and transmitting the second message to the first node based on the third data routing path after an identification of the event data, the second metadata to cause the first node to access the second data after the time duration has elapsed.

16. The method of claim 15, wherein the event data is first event data, the identification is a first identification, and the method includes transmitting a third message after a second identification of second event data, the second event data associated with third metadata, the third metadata to include a portion of the first metadata.

17. The method of claim 16, wherein the third message includes at least one of data or the third metadata directly associated with the data.

18. The method of claim 15, including, after a determination that the first node is associated with a first network interface and a second network interface, transmitting a first portion of the second message to the first network interface and a second portion of the second message to the second network interface.

19. The method of claim 15, including executing a machine-learning microservice to cause execution of the machine-learning model.

20. The method of claim 15, wherein the machine-learning model is a digital twin associated with the network environment.

21. A method comprising: executing a machine-learning model to predict a first data routing path in a network environment based on metadata associated with event data in the network environment, the machine-learning model being a digital twin associated with the network environment, a first message based on the event data to be transmitted to a first node based on the first data routing path, prediction of the first data routing path based on simulating transmission of the first message in the network environment, the simulating based on the digital twin, the first data routing path to have a first strength of association with at least one of the metadata or the event data; after detecting a change of the first data routing path to a second data routing path, retraining the machine-learning model to output a third data routing path based on the second data routing path, the third data routing path to have a second strength of association with the at least one of the metadata or the event data, the second strength of association to be greater than the first strength of association; and transmitting a second message to the first node based on the third data routing path after an identification of the event data.

22. The method of claim 21, wherein the metadata is first metadata, the first node is a first device, the network environment includes a second device and a third device, and including generating the second message to include second metadata, the first device is not associated with an operation indicated by the second metadata, and the first device is to cause at least one of the second device or the third device to perform the operation based on the second metadata.

23. The apparatus of claim 6, wherein the determination is a first determination, and one or more of the at least one processor circuit is to, after a second determination that the first node has a bandwidth that satisfies a threshold, generate the second message to include at least one of audio data, text data, or video data.

24. The at least one non-transitory computer readable storage medium of claim 12, wherein the instructions cause one or more of the at least one processor circuit to multicast the second message to the first node and one or more second nodes associated with the metadata.

