

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12413629
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Robinson; James S. et al.

Artificial intelligence (AI) devices control based on policies

Abstract

A policy-controlled access security system for managing access security to electronic agents in cloud based multi-tenant systems includes a client device, a mid-link server, and a web server. A local application running on the client device requests access to an electronic agent of a remote application of the web server. Policies are determined for controlled access to the electronic agent. A token for the electronic agent is correlated with a plurality of tokens for identifying a user application associated with the token. The remote application is compared with the user application. A non-compliance of the set of policies is identified by determining enabling of one or more AI devices by the plurality of end users. The set of policies are modified based on the non-compliance and the functionality associated with the electronic agent and the plurality of privileges are updated for the end user based on the modified policies.

Inventors: Robinson; James S. (Indianapolis, IN), Chung; Damian C. (Gilbert, AZ), Orange; Lamont (Florissant, MO)

Applicant: Netskope, Inc. (Santa Clara, CA)

Family ID: 84810635

Assignee: Netskope, Inc. (N/A, N/A)

Appl. No.: 18/152088

Filed: January 09, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230216892 A1	Jul. 06, 2023

Related U.S. Application Data

continuation parent-doc US 17566125 20211230 US 11553008 child-doc US 18152088

Publication Classification

Int. Cl.: H04L9/40 (20220101)

U.S. Cl.:

CPC H04L63/205 (20130101); H04L63/0807 (20130101); H04L63/10 (20130101);
H04L63/105 (20130101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5440723	12/1994	Arnold et al.	N/A	N/A
6513122	12/2002	Magdych et al.	N/A	N/A
6622248	12/2002	Hirai	N/A	N/A
6853988	12/2004	Dickinson	705/75	H04L 63/20
7080408	12/2005	Pak et al.	N/A	N/A
7298864	12/2006	Jones	N/A	N/A
7376719	12/2007	Shafer et al.	N/A	N/A
7735116	12/2009	Gauvin	N/A	N/A
7966654	12/2010	Crawford	N/A	N/A
8000329	12/2010	Fendick et al.	N/A	N/A
8051491	12/2010	Cavage	726/16	H04L 63/0227
8296178	12/2011	Hudis et al.	N/A	N/A
8332464	12/2011	Dispensa	709/229	H04L 63/0272
8464335	12/2012	Sinha	713/153	G06F 21/51
8468582	12/2012	Kuang	713/186	G06F 21/577
8572689	12/2012	Radhakrishnan	N/A	N/A
8595810	12/2012	Ben Ayed	713/168	H04L 63/0815
8646060	12/2013	Ben Ayed	726/9	H04W 4/20
8793151	12/2013	DelZoppo et al.	N/A	N/A
8839417	12/2013	Jordan	N/A	N/A
9043480	12/2014	Barton	709/229	H04W 12/06
9083750	12/2014	Gomez et al.	N/A	N/A
9185095	12/2014	Moritz	N/A	H04L 63/0861
9197601	12/2014	Pasdar	N/A	N/A
9225734	12/2014	Hastings	N/A	N/A
9231968	12/2015	Fang et al.	N/A	N/A

9280678	12/2015	Redberg	N/A	N/A
9306954	12/2015	Movassaghi	N/A	G06F 21/32
9369493	12/2015	Sweet	N/A	G06F 21/56
9374379	12/2015	Hew	N/A	H04L 63/108
9432381	12/2015	Dyor	N/A	H04W 48/04
9571285	12/2016	Kassaei et al.	N/A	N/A
9652911	12/2016	Fedronic	N/A	G07C 9/27
9722991	12/2016	Canning et al.	N/A	N/A
9811662	12/2016	Sharpe et al.	N/A	N/A
9853993	12/2016	Zhou	N/A	G06Q 20/3224
9860223	12/2017	Anderson	N/A	G06F 16/183
10049514	12/2017	Outwater	N/A	H04L 63/102
10084825	12/2017	Xu	N/A	N/A
10237282	12/2018	Nelson et al.	N/A	N/A
10334442	12/2018	Vaughn et al.	N/A	N/A
10382468	12/2018	Dods	N/A	N/A
10397186	12/2018	Clark	N/A	H04L 63/0272
10454940	12/2018	Ander et al.	N/A	N/A
10462135	12/2018	Varadarajan	N/A	H04L 63/0428
10462188	12/2018	Terrill	N/A	H04L 63/1441
10484334	12/2018	Lee et al.	N/A	N/A
10530759	12/2019	Alison	N/A	H04L 63/0281
10601831	12/2019	Ezell	N/A	H04L 67/02
10609087	12/2019	Zhou	N/A	H04L 63/10
10623410	12/2019	Leibmann	N/A	H04L 67/10
10673861	12/2019	Karunakaran et al.	N/A	N/A
10727973	12/2019	Kumar	N/A	H04L 45/70
10749677	12/2019	Agrawal	N/A	H04W 4/70
10771407	12/2019	Youssefi	N/A	H04L 51/02
10771458	12/2019	Xia	N/A	H04W 12/64
10826941	12/2019	Jain et al.	N/A	N/A
10846390	12/2019	Subramanian et al.	N/A	N/A
10929352	12/2020	Nation	N/A	H04L 9/3247
10938567	12/2020	Martino	N/A	G06Q 20/065
10956377	12/2020	Todd	N/A	G06F 16/29
10965673	12/2020	Smith	N/A	H04L 63/0823
11032301	12/2020	Mandrychenko et al.	N/A	N/A

11036856	12/2020	Graun et al.	N/A	N/A
11140061	12/2020	Sanders	N/A	G06F 8/75
11165783	12/2020	Eiers	N/A	H04L 41/0893
11184766	12/2020	Lord	N/A	G06V 10/75
11233776	12/2021	Muddapappu	N/A	H04L 63/102
11245640	12/2021	Maurya	N/A	G06F 18/217
11250125	12/2021	Bhamidipati	N/A	G06Q 20/405
11263315	12/2021	Bhamidipati	N/A	G06F 21/64
11281775	12/2021	Burdett et al.	N/A	N/A
11283884	12/2021	Mercadie	N/A	H04L 63/10
11322050	12/2021	Arbajian	N/A	G09C 1/00
11386405	12/2021	Pandit	N/A	G06Q 20/065
11405182	12/2021	Bhamidipati	N/A	H04L 9/0637
11449799	12/2021	Arbajian	N/A	H04L 9/3013
11500929	12/2021	Choudhury	N/A	G06F 16/909
11501202	12/2021	Stefani	N/A	G06F 16/9038
11531776	12/2021	Buckley	N/A	H04L 63/102
11533175	12/2021	Rao	N/A	G06N 20/00
11546358	12/2022	Robinson	N/A	H04L 63/205
11563542	12/2022	Yoo	N/A	H04L 27/2646
11676135	12/2022	Bhamidipati	705/64	G06Q 20/02
11689521	12/2022	Fletcher	726/8	H04L 63/102
11768699	12/2022	Esibov	718/104	G06F 21/564
11785050	12/2022	Roh	N/A	H04L 63/1425
11902280	12/2023	Cheng	N/A	H04L 63/101
11928426	12/2023	Gutzeit	N/A	G06F 16/35
11930048	12/2023	Dadon	N/A	H04L 63/1425
12019653	12/2023	Habiba	N/A	G06F 21/64
12068848	12/2023	Goldhamer	N/A	H04L 1/0063
12081550	12/2023	Zhang	N/A	H04L 41/16
12153705	12/2023	Marino	N/A	G06F 21/6245

2002/0099666	12/2001	Dryer et al.	N/A	N/A
2003/0055994	12/2002	Herrmann et al.	N/A	N/A
2003/0063321	12/2002	Inoue et al.	N/A	N/A
2003/0172292	12/2002	Judge	N/A	N/A
2003/0191964	12/2002	Satyavolu	726/5	H04L 63/108
2003/0204632	12/2002	Willebeek-LeMair et al.	N/A	N/A
2004/0015719	12/2003	Lee et al.	N/A	N/A
2005/0010593	12/2004	Fellenstein et al.	N/A	N/A
2005/0022012	12/2004	Bluestone	726/4	H04L 12/2876
2005/0120214	12/2004	Yeates	713/171	H04L 63/08
2005/0271246	12/2004	Sharma et al.	N/A	N/A
2006/0112188	12/2005	Albanese	709/238	H04L 63/08
2006/0156401	12/2005	Newstadt et al.	N/A	N/A
2007/0083655	12/2006	Pedersen	709/226	H04L 63/102
2007/0107061	12/2006	Engle	726/1	H04L 63/0272
2007/0185815	12/2006	Boccon-Gibod	705/51	H04L 63/08
2007/0192329	12/2006	Croft	N/A	G06F 3/1415
2007/0204018	12/2006	Chandra et al.	N/A	N/A
2007/0237147	12/2006	Quinn et al.	N/A	N/A
2007/0244987	12/2006	Pedersen	709/217	H04L 67/568
2008/0069480	12/2007	Aarabi et al.	N/A	N/A
2008/0101598	12/2007	Dillaway	380/44	H04L 63/20
2008/0134332	12/2007	Keohane et al.	N/A	N/A
2008/0222696	12/2007	Nicodemus	726/1	H04L 63/102
2008/0235782	12/2007	Johnson	726/12	H04L 63/10
2009/0144818	12/2008	Kumar et al.	N/A	N/A
2009/0183225	12/2008	Malakapalli et al.	N/A	N/A
2009/0249470	12/2008	Litvin et al.	N/A	N/A
2009/0300351	12/2008	Lei et al.	N/A	N/A
2010/0017436	12/2009	Wolge	N/A	N/A
2010/0325419	12/2009	Kanekar	713/151	H04L 67/1001
2011/0119481	12/2010	Auradkar et al.	N/A	N/A
2011/0145594	12/2010	Jho et al.	N/A	N/A
2012/0054625	12/2011	Pugh	715/736	G06F 21/105
2012/0246098	12/2011	Chari	706/12	G06N 20/00
2012/0278896	12/2011	Fang et al.	N/A	N/A
2012/0295587	12/2011	Paya	455/411	H04L 63/0492
2012/0317624	12/2011	Llorente et al.	N/A	N/A
2013/0014206	12/2012	Rao	713/153	H04L 45/72

2013/0080785	12/2012	Ruhlen	713/176	H04L 67/51
2013/0159694	12/2012	Chiueh et al.	N/A	N/A
2013/0254335	12/2012	Inoue	709/217	H04L 67/51
2013/0263212	12/2012	Faltyn	726/1	H04W 12/37
2013/0276082	12/2012	Kuang	726/7	H04L 63/0869
2013/0290434	12/2012	Bank	709/204	H04L 12/1822
2013/0298190	12/2012	Sikka et al.	N/A	N/A
2013/0347085	12/2012	Hawthorn et al.	N/A	N/A
2014/0013112	12/2013	Cidon et al.	N/A	N/A
2014/0020070	12/2013	Angal	726/5	H04L 63/10
2014/0068030	12/2013	Chambers et al.	N/A	N/A
2014/0068705	12/2013	Chambers et al.	N/A	N/A
2014/0108558	12/2013	Borzycki	709/205	H04L 63/10
2014/0123237	12/2013	Gaudet	726/4	G06F 21/60
2014/0196104	12/2013	Chari	726/1	H04L 63/102
2014/0259093	12/2013	Narayanaswamy et al.	N/A	N/A
2014/0282843	12/2013	Buruganahalli et al.	N/A	N/A
2014/0282919	12/2013	Mason	N/A	N/A
2014/0331273	12/2013	Koneru	726/8	H04L 63/0815
2014/0337528	12/2013	Barton	709/225	G06F 21/54
2014/0359282	12/2013	Shikfa et al.	N/A	N/A
2014/0359696	12/2013	Mallia	N/A	N/A
2014/0366079	12/2013	Pasdar	N/A	N/A
2014/0373126	12/2013	Hussain	726/9	H04L 63/0807
2015/0089569	12/2014	Sondhi et al.	N/A	N/A
2015/0089586	12/2014	Ballesteros	726/3	G06F 21/44
2015/0100357	12/2014	Seese et al.	N/A	N/A
2015/0113608	12/2014	Chermside	726/4	H04L 63/061
2015/0222637	12/2014	Hung	726/1	G06F 9/54
2015/0326559	12/2014	Kuang	726/5	G06F 21/34
2015/0326565	12/2014	Kuang	726/4	H04L 63/0869
2015/0381580	12/2014	Graham, III	713/168	H04L 63/20
2016/0088021	12/2015	Jayanti Venkata	726/1	H04L 63/104
2016/0323318	12/2015	Terrill et al.	N/A	N/A
2016/0350145	12/2015	Botzer et al.	N/A	N/A
2016/0381021	12/2015	Moore et al.	N/A	N/A
2017/0019396	12/2016	Bettenburg	N/A	G06F 21/34
2017/0024130	12/2016	Beale	N/A	G06F 3/062
2017/0064005	12/2016	Lee	N/A	N/A
2017/0078154	12/2016	Ansari	N/A	H04L 12/2803

2017/0093917	12/2016	Chandra et al.	N/A	N/A
2017/0180993	12/2016	Kelly	N/A	H04W 12/086
2017/0201588	12/2016	Schmidt	N/A	H04L 63/105
2017/0250951	12/2016	Wang et al.	N/A	N/A
2017/0295181	12/2016	Parimi	N/A	H04L 63/1433
2017/0302644	12/2016	Goodwin	N/A	N/A
2018/0041491	12/2017	Gupta	N/A	G06F 9/547
2018/0063152	12/2017	Erich	N/A	H04L 63/0861
2018/0075250	12/2017	Chasman	N/A	G06F 21/6227
2018/0103028	12/2017	Stuntebeck	N/A	H04L 67/303
2018/0212973	12/2017	Ganapathy	N/A	H04L 67/10
2018/0332042	12/2017	Yu	N/A	H04L 51/02
2018/0359259	12/2017	Leon	N/A	G06F 9/445
2018/0359639	12/2017	Trama	N/A	H04W 48/04
2018/0365440	12/2017	Horowitz	N/A	G06F 16/2452
2019/0018719	12/2018	Brin	N/A	G06F 9/547
2019/0028474	12/2018	Chen	N/A	H04L 63/0884
2019/0050476	12/2018	Florentino	N/A	G06F 16/34
2019/0057204	12/2018	Marcovecchio	N/A	H04L 67/146
2019/0109713	12/2018	Clark	N/A	G06F 16/182
2019/0132321	12/2018	Pitchaimani	N/A	H04L 63/102
2019/0140849	12/2018	Kravitz	N/A	H04L 9/3236
2019/0149531	12/2018	Kakumani	726/1	H04L 63/08
2019/0149579	12/2018	Kakumani	726/1	H04L 63/0876
2019/0238619	12/2018	Mantrana-Exposito	N/A	H04L 63/104
2019/0258953	12/2018	Lang	N/A	G06N 3/08
2019/0289017	12/2018	Agarwal	N/A	H04L 9/0643
2019/0305955	12/2018	Verma	N/A	H04L 9/3247
2019/0306169	12/2018	Statia	N/A	H04L 63/0853
2019/0319843	12/2018	Telfer	N/A	H04L 41/0893
2019/0327271	12/2018	Saxena	N/A	G06F 8/38

2019/0347384	12/2018	Smith	N/A	H04L 63/1491
2019/0364020	12/2018	Wardell	N/A	H04W 12/062
2019/0370468	12/2018	Soby	N/A	G06F 21/57
2019/0373000	12/2018	Garnett	N/A	H04L 63/1416
2020/0050686	12/2019	Kamalapuram et al.	N/A	N/A
2020/0053090	12/2019	Kliger	N/A	H04L 63/107
2020/0084295	12/2019	Hayward	N/A	H04L 51/063
2020/0117817	12/2019	Chen	N/A	H04L 63/20
2020/0136825	12/2019	Gupta	N/A	G06F 9/445
2020/0145217	12/2019	Clark	N/A	H04L 63/06
2020/0162447	12/2019	Fletcher	N/A	H04L 63/107
2020/0186520	12/2019	Oberheide	N/A	G06Q 20/356
2020/0213251	12/2019	Shah	N/A	G06N 20/00
2020/0220875	12/2019	Harguindeguy	N/A	H04L 63/101
2020/0242536	12/2019	Schwantes	N/A	G06F 17/16
2020/0255301	12/2019	Budampati	N/A	C02F 1/42
2020/0257774	12/2019	Mintz	N/A	H04L 9/0637
2020/0274898	12/2019	Xie	N/A	H04L 63/1458
2020/0322151	12/2019	Latimer	N/A	H04L 63/10
2020/0336310	12/2019	Jain	N/A	H04L 63/105
2020/0336466	12/2019	Goldschlag et al.	N/A	N/A
2020/0348662	12/2019	Cella	N/A	G05B 19/41865
2020/0372382	12/2019	Trim	N/A	G06N 5/043
2020/0394709	12/2019	Cella	N/A	G06Q 20/405
2020/0403994	12/2019	Bitterfeld	N/A	H04L 63/0884
2021/0014256	12/2020	Malhotra	N/A	H04L 63/1433
2021/0051180	12/2020	Barnett	N/A	H04L 69/16
2021/0075794	12/2020	Gazit	N/A	H04L 63/1408
2021/0152542	12/2020	Palop et al.	N/A	N/A
2021/0157312	12/2020	Cella	N/A	G01M 13/045
2021/0157945	12/2020	Cobb	N/A	G06F 21/32
2021/0200864	12/2020	Rudnik	N/A	G06F 21/567

2021/0208173	12/2020	Lighton	N/A	G01N 35/00623
2021/0234903	12/2020	Chauhan	N/A	H04L 63/083
2021/0266329	12/2020	Fuhry	N/A	G06F 21/604
2021/0298557	12/2020	Budampati	N/A	G01M 3/26
2021/0300804	12/2020	Broga	N/A	D06F 39/088
2021/0301985	12/2020	Brown	N/A	G05B 23/0221
2021/0309539	12/2020	Budampati	N/A	H04L 67/30
2021/0342836	12/2020	Cella	N/A	H04L 9/3239
2021/0352064	12/2020	Tsarfati	N/A	H04L 63/1416
2021/0367977	12/2020	Beckman	N/A	H04L 63/20
2021/0388627	12/2020	Brown	N/A	E04H 4/1281
2022/0038453	12/2021	Chauhan	N/A	H04L 63/0853
2022/0046063	12/2021	Peterson	N/A	H04L 63/102
2022/0083810	12/2021	Khanna	N/A	G06F 18/2411
2022/0083815	12/2021	Khanna	N/A	G06F 18/10
2022/0083900	12/2021	Khanna	N/A	G06F 17/18
2022/0083901	12/2021	Khanna	N/A	G06N 20/10
2022/0108262	12/2021	Cella	N/A	G05B 19/41885
2022/0116345	12/2021	Xu	N/A	H04L 67/141
2022/0198562	12/2021	Cella	N/A	G06Q 40/04
2022/0212952	12/2021	Veloo	N/A	G06Q 50/06
2022/0239655	12/2021	Viswanathan	N/A	H04L 63/105
2022/0294686	12/2021	Triplet	N/A	H04W 12/06
2022/0311656	12/2021	Vaishnavi	N/A	H04L 41/0813
2022/0318420	12/2021	Marino	N/A	G06F 21/6245
2022/0366494	12/2021	Cella	N/A	H04L 9/50
2022/0402485	12/2021	Kobilarov	N/A	B60W 30/0956
2023/0014970	12/2022	Gujarathi	N/A	H04L 63/10
2023/0048174	12/2022	Priisalu	N/A	H04L 67/1034
2023/0129276	12/2022	Satake	726/26	G06F 21/604

2023/0169522	12/2022	Narayanan	705/7.29	H04L 63/101
2023/0173395	12/2022	Cella	463/25	G06Q 30/06
2023/0176557	12/2022	Cella	700/117	G05B 23/024
2023/0177169	12/2022	Bulut	726/1	H04L 63/1433
2023/0186201	12/2022	Cella	705/7.17	G05B 19/41885
2023/0196230	12/2022	Cella	705/7.17	G06V 10/82
2023/0206329	12/2022	Cella	N/A	H04L 43/0852
2023/0209370	12/2022	Pateromichelakis	370/328	G06N 20/00
2023/0214925	12/2022	Cella	705/37	G06Q 30/06
2023/0246724	12/2022	Pateromichelakis	370/329	H04W 72/0453
2023/0254132	12/2022	Ramanathan	380/28	H04L 9/0869
2023/0254288	12/2022	Nair	726/6	H04L 63/0281
2023/0254302	12/2022	Ramezanpour	713/156	G06F 21/44
2023/0281527	12/2022	Cella	705/7.17	G06V 20/17
2023/0337043	12/2022	Pateromichelakis	N/A	H04W 28/0263
2023/0345297	12/2022	Karampatsis	N/A	H04L 41/342
2023/0351206	12/2022	Butt	N/A	G06N 20/00
2023/0376859	12/2022	Miller	N/A	H04L 63/101
2023/0394129	12/2022	Boyapalle	N/A	H04L 9/3247
2023/0401332	12/2022	Vahidnia	N/A	G06F 21/31
2023/0403543	12/2022	Pateromichelakis	N/A	H04L 41/0686
2023/0412608	12/2022	Vaishnavi	N/A	H04L 63/102
2023/0418958	12/2022	Kanderall	N/A	G06Q 10/0635
2024/0007884	12/2023	Kovács	N/A	G06N 3/006
2024/0031146	12/2023	Marosi-Bauer	N/A	H04L 9/50
2024/0039799	12/2023	Parichehrehteroujeni	N/A	H04W 74/0833
2024/0064142	12/2023	Pandit	N/A	H04L 63/0884
2024/0073109	12/2023	Vaishnavi	N/A	H04L 41/5058
2024/0073709	12/2023	Karampatsis	N/A	H04W 24/02
2024/0095100	12/2023	Pateromichelakis	N/A	G06F 9/541
2024/0119127	12/2023	Li	N/A	G06F 21/53

2024/0220831	12/2023	Wyman	N/A	G06N 20/00
2024/0230839	12/2023	Yajnanarayana	N/A	G01S 7/006
2024/0236766	12/2023	Shete	N/A	H04W 24/02
2024/0249008	12/2023	Inokuchi	N/A	G06F 21/62
2024/0283792	12/2023	Mitani	N/A	G06F 21/62
2024/0291679	12/2023	Marosi-Bauer	N/A	H04L 9/3297
2024/0298194	12/2023	Mueck	N/A	G06N 20/00
2024/0345551	12/2023	Ramanasankaran	N/A	G05B 13/027

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
3093444	12/2020	CA	N/A
103460215	12/2012	CN	N/A
1063833	12/1999	EP	N/A
1643340	12/2005	EP	G06F 21/00
2019153330	12/2018	JP	N/A
2020502616	12/2019	JP	N/A

OTHER PUBLICATIONS

Zhao et al “A Review of Computer Vision Methods in Computer Security,” IEEE Communications Surveys & Tutorials, vol. 23, No. 3 , Third Quarter, pp. 1838-1878 (Year: 2021). cited by examiner

IEESoro et al “Prolonging the Lifetime of Wireless Sensor Networks Via Unequal Clustering,” IEEE Computer Society, pp. 1-8 (Year: 2005). cited by examiner

Cheng et al “Wireless Intelligent ATM Network and Protocol Design for Future Personal Communications Systems,” IEEE Journal on Selected Areas in Communications, pp. 1289-1307, (Year: 1997). cited by examiner

Sackmann et al “A Classification Model for Automating Compliance,” IEEE Computer Society, pp. 79-86 (Year: 2008). cited by examiner

Alkhresheh et al “DACIoT: Dynamic Access Control Framework for IoT Deployments,” IEEE, pp. 11401-11419 (Year: 2020). cited by examiner

Martin, Victoria “Cooperative Security Fabric,” The Fortinet Cookbook, Jun. 8, 2016, 6 pgs., archived Jul. 28, 2016 at <https://web.archive.org/web/20160728170025/http://cookbook.fortinet.com/cooperative-security-fabric-54>. cited by applicant

Huckaby, Jeff Ending Clear Text Protocols, Rackaid.com, Dec. 9, 2008, 3 pgs. cited by applicant

Nevvton, Harry “fabric,” Newton's Telecom Dictionary, 30th Updated, Expanded, Anniversary Edition, 2016, 3 pgs. cited by applicant

Fortinet, “Fortinet Security Fabric Earns 100% Detection Scores Across Several Attack Vectors in NSS Labs' Latest Breach Detection Group Test [press release]”, Aug. 2, 2016, 4 pgs, available at <https://www.fortinet.com/de/corporate/about-us/newsroom/press-releases/2016/security-fabric-earns-100-percent-breach-detection-scores-nss-labs>. cited by applicant

Fortinet, “Fortinet Security Fabric Named 2016 CRN Network Security Product of the Year [press release]”, Dec. 5, 2016, 4 pgs, available at <https://www.fortinet.com/corporate/about-us/newsroom/press-releases/2016/fortinet-security-fabric-named-2016-crn-network-security-product>. cited by applicant

McCullagh, Declan, "How safe is instant messaging? A security and privacy survey," CNET, Jun. 9, 2008, 14 pgs. cited by applicant

Beck et al. "IBM and Cisco: Together for a World Class Data Center," IBM Redbooks, Jul. 2013, 654 pgs. cited by applicant

Martin, Victoria "Installing internal FortiGates and enabling a security fabric," The Fortinet Cookbook, Jun. 8, 2016, 11 pgs, archived Aug. 28, 2016 at <https://web.archive.org/web/20160828235831/http://cookbook.fortinet.com/installing-isfw-fortigate-enabling-csf-54>. cited by applicant

Zetter, Kim, "Revealed: The Internet's Biggest Security Hole," Wired, Aug. 26, 2008, 13 pgs. cited by applicant

Adya et al., Farsite: Federated, available, and reliable storage for an incompletely trusted environment, SIGOPS Oper. Syst. Rev. 36, SI, Dec. 2002, pp. 1-14. cited by applicant

Agrawal et al., "Order preserving encryption for numeric data," In Proceedings of the 2004 ACM SIGMOD international conference on Management of data, Jun. 2004, pp. 563-574. cited by applicant

Balakrishnan et al., "A layered naming architecture for the Internet," ACM SIGCOMM Computer Communication Review, 34(4), 2004, pp. 343-352. cited by applicant

Downing et al. , Naming Dictionary of Computer and Internet Terms, (11th Ed.) Barron's, 2013, 6 pgs. cited by applicant

Downing et al., Dictionary of Computer and Internet Terms, (10th Ed.) Barron's, 2009, 4 pgs. cited by applicant

Zoho Mail, "Email Protocols: What they are & their different types," 2006, 7 pgs. available at <https://www.zoho.com/mail/glossary/email-protocols.html#:~:text=mode of communication.-,What are the different email protocols%3F, and also has defined functions.> cited by applicant

NIIT, Special Edition Using Storage Area Networks, Que, 2002, 6 pgs. cited by applicant

Chapple, Mike, "Firewall redundancy: Deployment scenarios and benefits," Tech Target, 2005, 5 pgs. available at https://www.techtarget.com/searchsecurity/tip/Firewall-redundancy-Deployment-scenarios-and-benefits?%20Offer=abt_pubpro_AI-Insider. cited by applicant

Fortinet, FortiGate—3600 User Manual (vol. 1 , Version 2.50 MR2) Sep. 5, 2003, 329 pgs. cited by applicant

Fortinet, FortiGate SOHO and SMB Configuration Example, (Version 3.0 MR5), Aug. 24, 2007, 54 pgs. cited by applicant

Fortinet, FortiSandbox—Administration Guide, (Version 2.3.2), Nov. 9, 2016, 191 pgs. cited by applicant

Fortinet, FortiSandbox Administration Guide, (Version 4.2.4) Jun. 12, 2023, 245 pgs. available at https://fortinetweb.s3.amazonaws.com/docs.fortinet.com/v2/attachments/fba32b46-b7c0-11ed-8e6d-fa163e15d75b/FortiSandbox-4.2.4-Administration_Guide.pdf. cited by applicant

Fortinet, FortiOS—Administration Guide, (Versions 6.4.0), Jun. 3, 2021, 1638 pgs. cited by applicant

Heady et al., "The Architecture of a Network Level Intrusion Detection System," University of New Mexico, Aug. 15, 1990, 21 pgs. cited by applicant

Kephart et al., "Fighting Computer Viruses," Scientific American (vol. 277, No. 5) Nov. 1997, pp. 88-93. cited by applicant

Wang, L., Chapter 5: Cooperative Security in D2D Communications, "Physical Layer Security in Wireless Cooperative Networks," 41 pgs. first online on Sep. 1, 2017 at https://link.springer.com/chapter/%2010.1007/978-3-319-61863-0_5. cited by applicant

Lee et al., "A Data Mining Framework for Building Intrusion Detection Models," Columbia University, n.d. 13 pgs. cited by applicant

Merriam-Webster Dictionary, 2004, 5 pgs. cited by applicant

Microsoft Computer Dictionary, (5th Ed.), Microsoft Press, 2002, 8 pgs. cited by applicant

Microsoft Computer Dictionary, (4th Ed.), Microsoft Press, 1999, 5 pgs. cited by applicant
Mika et al. "Metadata Statistics for a Large Web Corpus," LDOW2012, Apr. 16, 2012, 6 pgs. cited by applicant
Oxford Dictionary of Computing (6th Ed.), 2008, 5 pgs. cited by applicant
Paxson, Vern, "Bro: a System for Detecting Network Intruders in Real-Time," Proceedings of the 7th USENIX Security Symposium, Jan. 1998, 22 pgs. cited by applicant
Fortinet Inc., U.S. Appl. No. 62/503,252, "Building a Cooperative Security Fabric of Hierarchically Interconnected Network Security Devices." n.d., 87 pgs. cited by applicant
Song et al., "Practical techniques for searches on encrypted data," In Proceeding 2000 IEEE symposium on security and privacy. S&P 2000, May 2000, pp. 44-55. cited by applicant
Dean, Tamara, Guide to Telecommunications Technology, Course Technology, 2003, 5 pgs. cited by applicant
U.S. Appl. No. 60/520,577, "Device, System, and Method for Defending a Computer Network," Nov. 17, 2003, 21 pgs. cited by applicant
U.S. Appl. No. 60/552,457, "Fortinet Security Update Technology," Mar. 2004, 6 pgs. cited by applicant
Tittel, Ed, Unified Threat Management For Dummies, John Wiley & Sons, Inc., 2012, 76 pgs. cited by applicant
Fortinet, FortiOS Handbook: UTM Guide (Version 2), Oct. 15, 2010, 188 pgs. cited by applicant
Full Definition of Security, Wayback Machine Archive of Merriam-Webster on Nov. 17, 2016, 1 pg. cited by applicant
Definition of Cooperative, Wayback Machine Archive of Merriam-Webster on Nov. 26, 2016, 1 pg. cited by applicant
Pfaffenberger, Bryan, Webster's New World Computer Dictionary, (10th Ed.), 2003, 5 pgs. cited by applicant

Primary Examiner: Pham; Luu T

Assistant Examiner: Wilcox; James J

Attorney, Agent or Firm: MUGHAL GAUDRY & FRANKLIN PC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. application Ser. No. 17/566,125, filed Dec. 30, 2021, and entitled "ELECTRONIC AGENT SCRIBE AND COMMUNICATION PROTECTIONS," the contents of which is incorporated by reference in its entirety for all purposes.

BACKGROUND

(1) This disclosure relates in general to electronic agent security systems and, but not by way of limitation, to policy-controlled access security and token management for electronic agents among other things.

(2) Popular electronic agents used by organizations boost innovation, improve communication, and develop efficient processes for businesses. Various software tools and mobile applications of the electronic agents are available nowadays that provide enhanced functionalities crucial for communication use of the organizations. However, the electronic agents accompany privacy issues, abuse of recording, sharing and access rights, and involvement of unauthorized third parties that might raise security concerns for the organizations. The misuse of transcript function, unwarranted

communication, and access to extremely confidential and sensitive information are some of the major problems faced by the organizations while using the electronic agents.

(3) Unrestricted use of the electronic agents by employees may pose threat to the security and integrity of the organizations. The ill-use of the electronic agents may result in legal matters, disputes, and assault leading to ransom or public acknowledgement. This may in turn cause financial loss and reputational damage to the organizations.

SUMMARY

(4) In one embodiment, the present disclosure provides a policy-controlled access security system for managing access security to electronic agents in cloud based multi-tenant systems includes a client device, a mid-link server, and a web server. A local application running on the client device requests access to an electronic agent of a remote application of the web server. Policies are determined for controlled access to the electronic agent. A token for the electronic agent is correlated with a plurality of tokens for identifying a user application associated with the token. The remote application is compared with the user application. A non-compliance of the set of policies is identified by determining enabling of one or more AI devices by the plurality of end users. The set of policies are modified based on the non-compliance and the functionality associated with the electronic agent and the plurality of privileges are updated for the end user based on the modified policies.

(5) In an embodiment, a policy-controlled access security system for managing access security to electronic agents in a cloud based multi-tenant system. The policy-controlled access security system includes a client device, a mid-link server, and a web server. The client device includes a local application. The local application is configured to execute on the client device and is further configured to provide a request for access to an electronic agent of a remote application run on a remote instance of a web server. A token is required by the electronic agent. A policy component includes a plurality of policies. The plurality of policies specifies controlled access to a plurality of electronic agents of a plurality of remote applications. The controlled access includes restrictive use of a functionality associated with the electronic agent, access to shared content, and/or access to the electronic agent by a plurality of end users. The mid-link server coupled to the client device includes a confidentiality enterprise agent configured to determine a set of policies from the plurality of policies corresponding to the electronic agent. A plurality of privileges are assigned to the client device for access to the electronic agent based on the set of policies. The set of policies specifies the plurality of privileges associated with the controlled access to the electronic agent. Artificial intelligence (AI) devices of the plurality of end users are identified within a threshold distance from the plurality of end users. A non-compliance of the set of policies is identified by determining enabling of one or more AI devices by the plurality of end users. The set of policies are modified based on the non-compliance. The functionality associated with the electronic agent and the plurality of privileges are updated for the end user based on the modified set of policies.

(6) In another embodiment, a method for policy-controlled access security to electronic agents in cloud-based multi-tenant systems. In one step, a local application running on a client device requests access to an electronic agent of a remote application run on a remote instance of an agent server. A token is required by the electronic agent. A set of policies from a plurality of policies corresponding to the electronic agent is determined. The plurality of policies specifies controlled access to a plurality of electronic agents of a plurality of remote applications. The controlled access includes restrictive use of a functionality associated with the electronic agents, access to shared content, and/or access to the electronic agent by a plurality of end users. The token is correlated with a plurality of tokens in a token repository for identifying a user application associated with the token. The remote application corresponding to the token from the request is compared with the identified user application. An authorization by a mid-link server corresponding to the token for accessing the electronic agent is determined based on the comparison. The set of policies is enforced on the client device. A non-compliance with the set of policies during the access of the

electronic agents, the non-compliance of the set of policies is identified by determining enabling of one or more AI devices by the plurality of end users. An alert is generated for one or more of the plurality of end users based on the non-compliance. The access to the electronic agent is provided based on the set of policies via the agent server. The set of policies are modified based on the non-compliance, and the functionality associated with the electronic agent is updated based on the modified set of policies.

(7) In yet another embodiment, a policy-based access system for managing secure access to electronic agents in cloud-based multi-tenant systems, the policy-based access system comprising a plurality of servers, collectively having code for: requesting by a local application running on a client device access to an electronic agent of a remote application run on a remote instance of an agent server, wherein a token is required by the electronic agent; determining a set of policies from a plurality of policies corresponding to the electronic agent, wherein: the plurality of policies specifies controlled access to a plurality of electronic agents of a plurality of remote applications, and the controlled access includes restrictive use of a functionality associated with the electronic agents, access to shared content, and/or access to the electronic agent by a plurality of end users; correlating the token with a plurality of tokens in a token repository for identifying a user application associated with the token; comparing the remote application corresponding to the token from the request with the identified user application; determining an authorization by a mid-link server corresponding to the token for accessing the electronic agent based on the comparison; assigning a plurality of privileges to the client device for accessing the electronic agent based on the set of policies, wherein the set of policies specifies the plurality of privileges associated with the controlled access to the electronic agent; enforcing the set of policies on the client device; providing the access to the electronic agent based on the set of policies via the agent server; identifying artificial intelligence (AI) devices within a threshold distance from an end user of the plurality of end users accessing the electronic agent; identifying a non-compliance with the set of policies during the access of the electronic agents, wherein the non-compliance of the set of policies is identified by determining enabling of one or more AI devices by the plurality of end users, and an alert is generated for one or more of the plurality of end users based on the non-compliance; modifying the set of policies based on the non-compliance; and updating the functionality associated with the electronic agent based on the modified set of policies.

(8) Further areas of applicability of the present disclosure will become apparent from the detailed description provided hereinafter. It should be understood that the detailed description and specific examples, while indicating various embodiments, are intended for purposes of illustration only and are not intended to necessarily limit the scope of the disclosure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The present disclosure is described in conjunction with the appended figures:
- (2) FIG. 1 illustrates a block diagram of a policy-controlled security system;
- (3) FIG. 2 illustrates a block diagram of a client device;
- (4) FIG. 3 illustrates a block diagram of a mid-link server is shown that hosts software environments that the client device(s) remote into;
- (5) FIG. 4 illustrates a block diagram of a token inspector configured to categorize, correlate, and authorize the tokens;
- (6) FIG. 5 illustrates a block diagram of a confidentiality enterprise agent configured to determine policies for electronic agents;
- (7) FIG. 6A illustrates a flow diagram of communication between an end user at a client device, and remote instances at a web server for electronic agents;

- (8) FIG. 6B illustrates a flow diagram of communication between end users attending a meeting from their respective client devices and an agent service;
- (9) FIG. 6C illustrates a flow diagram of detection of unauthorized electronic agents/scribe services;
- (10) FIG. 7A illustrates a Graphical User Interface (GUI) associated with a policy-controlled security system for accessing an electronic agent;
- (11) FIG. 7B illustrates a Graphical User Interface (GUI) associated with a policy-controlled security system for scheduling a meeting using an electronic agent;
- (12) FIG. 8 illustrates a flowchart of a method of a policy-controlled security system for a client device;
- (13) FIG. 9 illustrates a flowchart of a method of a policy-controlled security system for performing an audit while accessing an electronic agent; and
- (14) FIG. 10 illustrates a flowchart of a method of a policy-controlled security system for managing policies associated with an electronic agent.
- (15) In the appended figures, similar components and/or features may have the same reference label. Further, various components of the same type may be distinguished by following the reference label by a dash and a second label that distinguishes among the similar components. If only the first reference label is used in the specification, the description is applicable to any one of the similar components having the same first reference label irrespective of the second reference label.

DETAILED DESCRIPTION

(16) The ensuing description provides preferred exemplary embodiment(s) only, and is not intended to limit the scope, applicability or configuration of the disclosure. Rather, the ensuing description of the preferred exemplary embodiment(s) will provide those skilled in the art with an enabling description for implementing a preferred exemplary embodiment. It is understood that various changes may be made in the function and arrangement of elements without departing from the spirit and scope as set forth in the appended claims.

(17) Referring first to FIG. 1, a block diagram of a policy-controlled security system **100** is shown. The policy-controlled security system **100** is a policy-controlled access security system for electronic agents. The policy-controlled security system **100** includes client device(s) **102**, a web server **104**, end user(s) **106**, a mid-link server **108**, a policy store **110**, and services **112**. The client device(s) **102** such as smartphones, tablets, PCs, and any other computing devices communicate with the web server **104** over encryption links using the internet. The client device(s) **102** may be secured by using the mid-link server **108** that remotely hosts a secured software environment. The client device(s) **102** run any popular operating system (OS) such as Windows™, iOS™, Android™, Linux, set top box OSes such as Real-Time Operating System (RTOS), Unix OS, Linux-Kernel, and Linux OS in the Internet of Things (IoT)/Industrial control systems (ICS)/Distributed Control Systems (DCS)/Operational Technology (OT), and Chromebook™. The operating system of the client device(s) **102** runs third party apps. The policy store **110** holds policies for each client device **102** and the mid-link server **108**.

(18) The client device(s) **102** use content and processing from the web server **104** (or an agent server) including content sites for example, web sites, streaming content, etc. and the services **112** for example, SaaS tools, databases, cloud service providers, etc. Under policy control, the client device **102** routes some interaction to the mid-link server **108** that hosts a controlled software environment for each end user **106** to securely interact with the web server **104** and the services **112** or enterprise tools in a way limited by specified policies. For example, policies may specify configuration settings of the electronic agents that are used on the client device **102** while using the controlled software environment by remote access. The electronic agents are part of the services **112** for example, collaboration services such as online meeting, chatbots, web conferences, webinars, chatting platforms, calling, chatting, and/or messaging applications. The policies for

electronic agents specify a manner in which the electronic agents are to be used at the client device(s) **102**.

(19) The policies control the manner in which the electronic agents are accessed at the client device **102**. Other policies may enable certain software applications or interaction on the client device **102** while physically on premise and allowing different software applications or interaction while working in the field or at home away from the enterprise premises. In one example, a policy on the client device **102** for accessing a meeting application using a token on a remote software environment may be disabled for some or all applications when accessed from a mobile of the end user **106** during offline hours. In some cases, enforcement of the policy depends on whether the client device **102** is within the enterprise or away from the office. Tokens are required by the electronic agents to provide access to the end user **106** using various token protocols. The token protocols for example may be but not limited to, Open Authorization (OAuth), Federated Identity Management (FIM), OpenID Connect (OIDC), Security Access Markup Language (SAML), Web Services Federation (WS-Fed), and Single Sign On (SSO) provide communication along a network in an encrypted manner. These token protocols are used for establishing secure links between the local applications on the client device(s) **102** and electronic agent sites on the web server **104**. An example of the policies is illustrated in Table 1 discussed below.

(20) Table 1 below illustrates a list of policies for the electronic agents, functionalities of the electronic agents, a list of remote applications of the electronic agents and the corresponding tokens. The table is stored in the policy store **110**.

(21) TABLE-US-00001

TABLE 1	Electronic Remote Policies	Agent	Functionality	Application	Token	Policy
1	Meeting	Recording, sharing,	Application	Tokens	invite	allowed
A, B, C	allowed					
2	Chatbot	Sharing	allowed,	Application	OAuth	access to A tokens
calendar	blocked	allowed				
3	Calendar	Access to calendar	Application	SAML,	allowed	B SSO, and Open ID tokens
allowed						
4	Webinar	Official invitees,	Application	Tokens	allowed,	sharing and D, E, F
allowed						
5	Online	Sharing	allowed,	Application	Tokens	Conference
recording	blocked	X	allowed			
6	Call	Only official invitees	Application	Tokens	allowed	B
allowed						
7	Chat	Only within team	Application	OAuth	members	B tokens only
allowed,						
sharing of official files	allowed					
8	Messaging	Only within team	Application	Tokens	members,	sharing
A	allowed					

(22) As illustrated in Table 1, the policies are specified with respective electronic agents, tokens, remote applications, and functionalities. Each policy specifies restrictive use of the functionalities associated with the electronic agents and authorization of the tokens corresponding to the remote applications. For example, policy **1** allows recording, sharing, and sending invites using one of the applications A, B, or C for organizing a meeting. Tokens from the applications A, B, and C are authorized for accessing the electronic agents. Similarly, policy **2** allows sharing content while using chatbots through OAuth tokens.

(23) However, access to calendar by the chatbots is blocked under the policy **2**. Application A is allowed to be used for chatbots and the tokens from the application A are authorized for accessing the electronic agents. Another example, setting up calendars using application B and the corresponding tokens allows access to personal calendars under policy **3**. SAML, SSO, and Open ID tokens are allowed. Webinars may be set up using one of the applications D, E, or F and their corresponding tokens. Official invitees are allowed in the webinar. Sharing and recording of content is blocked as per policy **4**. Policy **5** allows setting online conferences using application X, sharing content is allowed, recording during the online conference is blocked. Tokens corresponding to the application X are allowed. Policy **6** enables setting up calls with official invitees using application B and corresponding tokens. Policy **7** allows chat sessions using application B with team members only. Tokens other than OAuth tokens are not authorized. The sharing of official files is allowed. Policy **8** allows messaging using application A with only team members. The sharing of content is allowed. Tokens corresponding to the application A are

allowed.

(24) These policies are set based on a number of factors. The factors include a tenant/enterprise of the client device **102**, a type of network connection of the client device **102**, confidentiality associated with the functionality like sharing, recording and inviting, the remote applications for the electronic agents, user logs, types of the client device(s) **102** such as phone, laptop, mobile, and/or designation of the end user(s) **106** such as President, Manager, Analyst etc. The policies are set by an administrator of the organization of the end user **106** based on the factors. In another embodiment, the policies may be set by the end user **106** of the client device **102**. The remote applications that have been allowed access using the tokens are authorized for use by the end user **106**.

(25) By way of an example, a president may have access to sharing and recording the content during a meeting with employees via a remote application. By way of another example, a manager organizing a webinar may be assigned sharing rights based on a policy. Sharing content using personal mobile phones of employees may not be allowed during messaging sessions based on the policy. Based on a confidentiality of the file, sharing of the file may not be allowed based on the policy. User browsing activities from user logs and a type of personal Virtual Private Network (VPN) connection used at the client device **102** influences the policies of the electronic agents. Enterprises may also set up restrictions on use of specific remote applications based on organization policy. For example, an application A may be allowed but another application B might not be allowed as per the organization policy.

(26) The web server **104** includes the electronic agent sites such as meeting application web sites, conferencing web sites, content sites such as web sites, streaming content, or application web sites etc. in order to provide services of the electronic agents, and/or provide content to the client device(s) **102**. The web server **104** also allows the end user(s) **106** of the client device(s) **102** to upload and download content from the content sites. The web server **104** also allows the end user(s) **106** of the client device(s) **102** to download the remote application of the electronic agent. The web server **104** is in communication with the client device(s) **102** via the mid-link server **108** over the internet. In another embodiment, the policy-controlled security system **100** includes one or more application servers (not shown) for providing dynamic content to the client device(s) **102**.

(27) The mid-link server **108** for the work systems resides as a “man-in-the-middle” intentionally take over some or all: processing, application execution and/or content sites at the web server **104** and the services **112** interaction. The remote software environment is hosted by the mid-link server **108** for a policy-controlled experience using the policy store **110** for authorization and control. For example, the electronic agent sites at the web server **104** may have certain functionalities like recording, or sharing content disabled, filtered or modified by the mid-link server **108** so that the client device(s) **102** behaves differently than if it were to directly connect to the content sites of the web server **104**. For example, a policy may specify connection using a token via the web server **104** for a meeting application allowed by the policy.

(28) Some embodiments have the policies that selectively direct tokens to the mid-link server **108** based on a label or tag of the content to be discussed during a session initiated using the electronic agents. A classifier may identify the label or the tag of the content. For example, the content may be classified as restricted, critical, secret, or public based on a type of the content. For example, a meeting application using files from a zipped folder may be confidential and restricted. By way of another example, the content sharing may be allowed for the webinar application during office hours or at an official PC but may be restricted on the mobile or at a remote location from the office. Similarly, the functionality of sharing content may be restricted for the meeting application based on the policies. The tokens may not be allowed for accessing a confidential document using an unauthorized remote application.

(29) The policy store **110** is a database that includes predefined policies for authorizing the tokens to access the electronic agents. The policy store **110** also includes the remote applications and the

local applications associated with the policies. The remote applications include electronic agent applications such as meeting applications, webinar application, web conference applications, chatbots apps and third party applications such as social media, emails, calendar, chats or streaming applications. The local applications are used to access the remote applications using the tokens. For example, a policy associated with a calendar application specifies use of authorized access tokens. The policies may be predefined by the enterprise or the client device **102**. The policies may be modified based on user requirements. Modified policies are also stored in the policy store **110** by the administrator or the enterprise.

(30) In an embodiment, the policy-controlled security system **100** allows multiple-tenants in different domains to communicate with the web server **104** over the internet. The policy-controlled security system **100** allows multiple tenants or enterprises (not shown) to all use the same network separated by domain or some other logical separation. The policy-controlled security system **100** manages tokens and policies used to access electronic agents in cloud-based multi-tenant system(s) (not shown). Encryption, leased/encrypted tunnels, firewalls, and/or gateways can be used to keep the data from one enterprise separate from other enterprises. Each client device **102** can communicate with the web server **104** for the services **112** and storage using the internet. The mid-link server **108** provides multi-tenancy control, policies and routing for each domain.

(31) Referring specifically to FIG. 2, a block diagram of the client device **102** is shown. This embodiment of the client device **102** uses a client **210** to establish connections with the mid-link server **108**. A user app **206** exclusively uses the client **210** to communicate with the mid-link server **108** to maintain security for operation of the user app **206**.

(32) Display of the remote software environment is performed by the user app **206**. In an embodiment, the user app **206** includes a local application. The entire interface of the remote software environment could be displayed, or the interface of a single user app could be displayed. Several instances of the user app **206** could display several user app interfaces respectively. Multiple instances of the user app **206** could have several remote software environments respectively running. For example, a user of Chromebook™ may have one user app **206** running iOS™ and another user app **206** running Linux™ with the ability to switch back-and-forth in full-screen or windowed mode. The user app **206** is a web browser or a video player in some embodiments merely displaying a stream of video.

(33) The client **210** may apply policies that are stored locally in a policy cache **208** to the client device **102**. The policy cache **208** is populated with the policies from the policy store **110** that are relevant for the respective client device **102**. As conditions change, the policies that are in effect could also change. For example, use of tokens associated with the camera/video sensors based applications for recording meetings on the client device **102** could be disabled inside the office or factory, but re-enabled outside of a geofenced area. By way of an example, artificial intelligence (AI) devices may be required to be disabled inside the geofenced area based on the policies. The AI devices include AI speakers, AI entry access, or IoT devices. Non-compliance with recording or sharing content during a meeting as per the policies is identified which enables alerts to be generated and flagged to the end user **106** and/or other participants/users of the meeting. Certain features, functions or applications might be disabled by a specific policy for the tokens until certain conditions exist. For example, there may be a policy that restricts tokens for accessing meeting apps on the mobile of the end user **106** during offline hours or when using unrecognized Virtual Private Network (VPN). Further, another policy allows use of the tokens for accessing calendar applications from the client device **102**. The client **210** supports the user app **206**, apps **212** running on the client device **102** or a browser **202** in communication with the mid-link server **108** via a Local Area Network (LAN) **204**.

(34) A privilege cache **216** stores privileges associated with the policies. These privileges allow the end user **106** to assign access rights to other participants of the electronic agents based on the policies. The access rights to various functionalities of the electronic agents include recording,

sharing content, inviting participants, and/or use of AI devices in a vicinity of the participants. The privilege cache **216** includes a mapping of policies, functionalities of the electronic agents and the corresponding privileges.

(35) The user app **206** is used as an interface for analyzing the alerts, providing feedback and assigning the privileges to the participants accessing the electronic agents. The user app **206** may be used to assign privileges to functionalities like sharing, recording, sending invites to participants based on the policy associated with the remote application of the electronic agent. The interface may be a graphical user interface (GUI) for presenting the electronic agents to the end user **106** of the client device **102**.

(36) An Information Technology (IT) module **214** provides an interface for an administrator or IT staff of an organization of the end user **106** for analyzing log reports, status of the tokens and assigning policies to the client device(s) **102**. The administrator of the enterprise reviews the policies, the tokens, established connections, and/or local applications and the remote applications. The administrator may also modify the policies by updating and/or upgrading the policies using the IT module **214**.

(37) Referring next to FIG. 3, a block diagram of the mid-link server **108** is shown that hosts software environments that the client device(s) **102** remote into. Traffic is passed with the Internet **310** accessed through a router **302** to enable the various depicted components of the mid-link server **108** to communicate with each other, specifically, the client **210**, a policy database **304**, remote devices **306**, remote instances **308**, a token repository **312**, a token inspector **314**, a confidentiality enterprise agent **316**, and an authorizer **318**. Dashed line used in the figure for representing the client **210** indicate that the client **210** is not a part of the mid-link server **108** and is used in the figure for illustrating inputs/outputs from the client **210**. Similar representations used in other block diagrams signify the same illustration.

(38) The mid-link server **108** hosts many different enterprises and domains keeping usage from their different client device(s) **102** separated. In other cases, the mid-link server **108** could be dedicated to a particular enterprise and hosted inside their network or the LAN **204** or with a third party hosting service. In any event, each remote instance **308** is dedicated to a client device **102** for use, although an Information Technology (IT) staff have access to update software, apply policies, make configuration changes, modify admin settings and rights, etc. to maintain the remote instance **308**. The client **210** connects with the client device(s) **102** over the Internet **310** in digitally segregated connections.

(39) In an embodiment, the remote devices **306** may be physical remote devices **306** and the remote instances **308** may be virtual-machine remote instances **308**. Both the physical remote devices **306** and the virtual-machine remote instances **308** are supported to run software environments. For example, the physical remote devices **306** may be tablets, smartphones, personal computers (Mac or PC), Chromebooks™, Linux™ servers, kiosks, or any personal computing device that employees might use. Any operating system running in a virtual machine on a physical device is supported to enable any enterprise to have their software environments running in a secure, controlled and potentially high performance instantiations. The remote instances **308** host content sites, websites or streaming content for the client device(s) **102**. The router **302** provides communication between the client **210** and the remote instances **308**. The router **302** allows the access or denial of the tokens based on the communication from the token inspector **314** before the token is used at the remote instances **308**.

(40) The remote devices **306** are physical hardware that hosts the remote instance **308** and is dedicated to the client device **102** currently connected to the mid-link server **108**. Not all operating systems enable running in a development mode or as a virtual machine to support all the functionality of the remote instance **308**. For those situations, the operating system is running on a physical device temporarily dedicated to the client device **102** with software to enable the end user **106** to control the remote instance **308**.

(41) The policy database **304** includes a list of policies for setting up an access security link for the electronic agents between the client device **102** and the remote instances **308** using authorized tokens. The policy database **304** also includes a list of authorized applications based on which the connection with the remote instances **308** is established. The policy database **304** includes the policies from the policy store **110**. The token and the application to be used are matched within the list of policies and their corresponding electronic agents and remote applications for establishing the connection. The policies are set by the administrator of the enterprise. By way of an example, the tokens of the calendar application may be allowed, and the tokens of social media applications may not be allowed based on the policies set by the enterprise. In other embodiments, these policies are further modified based on the new policies or requirements of the enterprise. For example, one of a social media application might be allowed based on the modified policy. Usage history of the functionalities of the electronic agents further influence the modification of the policies associated with the tokens. For example, based on a misuse of the functionality of sharing content in the meeting, the policy may be modified to raise alert and/or prevent such users from the meeting. By way of another example, the applications may be re-authorized by the administrator based on receiving a re-authorization request from the end user **106** regarding a denial of the token for an application or a functionality being disabled according to the policy.

(42) The token repository **312** includes a database of the tokens either authorized or restricted by the administrator or the enterprise/tenants of the end user **106** of the client device **102** for accessing the electronic agents. The token repository **312** includes a list of the tokens from the policy database **304** which is categorized by the token inspector **314** based on their respective policies.

(43) The token inspector **314** retrieves the policies corresponding to the tokens and the remote applications from the policy database **304** to monitor the tokens. The token inspector **314** categorizes the tokens in the token repository **312** based on the policies set by the administrator or the enterprise. The token inspector **314** monitors each token, matches the token with the list of tokens in the token repository **312**, correlates the token with the list of the tokens in the policy database **304**, and identifies the corresponding applications, electronic agents, functionalities, and policies associated with the token. The token inspector **314** further determines whether the token is authorized to be used according to the policy. The authorization on the token is provided to the authorizer **318** for further analysis.

(44) The token inspector **314** further keeps a log of tokens each time the tokens are used for the electronic agents. A compliance with the respective policies is checked in order to track any compromise or misconduct in complying the policy. For example, there may be malicious or unidentifiable tokens for the electronic agents that creates the non-compliance. Unidentified, unauthorized or malicious tokens are flagged to the IT module **214** for re-authorization. For example, the token inspector **314** determines a threat associated with the token, categorizes the token as malicious for the client device **102**, and flags the client device **102** and/or the IT module **214** for inspection and re-authorization.

(45) The token inspector **314** identifies and tracks the tokens by inline (i.e. by watching and inspecting traffic), via management connection monitoring (i.e. watching what administrators do), by Application Programming Interface (API) application monitoring (i.e. looking specifically for authorizations) and by performing behavioral analysis to identify new connection.

(46) The confidentiality enterprise agent **316** determines the policies for the electronic agents based on the confidentiality of, enterprise content, user logs, user designation, and network connections used. The electronic agents are requested by the end user **106** of the client device **102**. The confidentiality enterprise agent **316** retrieves the policies from the policy database **304** and provides the policies based on the electronic agents to the authorizer **318**. The confidentiality enterprise agent **316** determines the policies using the list of policies from the policy database **304**. The confidentiality enterprise agent **316** further assigns privileges to the client device **102** based on the policies. Audit of the AI devices within a threshold distance from the users of the electronic

agents is performed to identify any non-compliance with the policies. The AI devices may be disabled based on the policies. Modification of the policies is performed by the administrator from the IT module **214** and applied using the confidentiality enterprise agent **316**.

(47) The authorizer **318** receives the token authorization from the token inspector **314** and the policies determined by the confidentiality enterprise agent **316** to correlate the policies and the token to authorize the use of the tokens and the remote application on the client device **102** based on the policy. Based on the authorization, the authorizer **318** allows the token to be used by the user app **206** at the router **302** for accessing the electronic agents from the remote instances **308**.

(48) Referring next to FIG. 4, a block diagram of the token inspector **314** configured to categorize, correlate, and authorize the tokens is shown. The token inspector **314** includes a categorizer **402**, a correlator **404**, a correlation repository **406**, and a token history database **408**.

(49) The categorizer **402** receives the list of policies for the tokens as set by the administrator or the enterprise/tenants from the policy database **304**. The categorizer **402** uses the list of policies to categorize each of the tokens in the token repository **312**. The tokens are categorized into multiple categories based on their respective policies.

(50) The tokens that are new and do not have a past usage history are categorized as new. New policies may be set for the new tokens. The categorizer **402** flags an alert via the router **302** to the IT module **214** or to the end user **106** of the client device **102** for authorization of the new tokens. The categorization is performed using machine learning algorithms or fuzzy logic. The categorizer **402** continuously monitors and updates the categories of the tokens based on a usage of the tokens acquired from the user logs within the token history database **408**.

(51) The correlator **404** uses the list of categorized tokens in the token repository **312** to match a token received from a request of the client device **102** with the categorized tokens in the list. If the token is found matching within the list of categorized tokens, the policy associated with the matched token, the corresponding electronic agent and the application for which it is used are identified. The application of the token from the request is compared with the application of the matched token in the list. If the application is matched in the list, then the authorization of the token is determined. If the token is determined as authorized as per the policy of the token, the token is allowed to be used. If the token is determined as unauthorized, the token is reported for re-authorization to the IT module **214** and prevented access to the electronic agent. Authorization information of the tokens is stored in the correlation repository **406** for further analysis.

(52) The correlation repository **406** is a database for the correlated tokens. After being matched with the list of categorized tokens in the correlator **404**, the authorization information of the tokens is stored in the correlation repository **406**. The authorizer **318** retrieves the authorization information of the tokens from the correlation repository **406** for authorizing the use of the tokens for the electronic agents.

(53) The token history database **408** stores the usage history of the tokens acquired from logs of the client device(s) **102**. The usage history also includes administrator reports and user reports. The administrator reports include information on blocked tokens, re-authorized tokens or unidentified tokens obtained from the administrator. Also, information on the tokens from the client device **102** and other data sources such as blogs, websites and social media are incorporated in the user reports. The usage history is useful in categorizing and identifying the tokens. The usage history is shared with the IT module **214** via the router **302** for further analysis.

(54) Referring next to FIG. 5, a block diagram of the confidentiality enterprise agent **316** configured to determine the policies for the electronic agents is shown. The confidentiality enterprise agent **316** includes a policy comparator **502**, a logger **504**, a privilege store **506**, a policy enforcer **508**, a modifier **510**, a confidentiality store **512**, and an auditor **514**.

(55) The policy comparator **502** receives the policies for the electronic agents from the policy store **110** and confidentiality information from the confidentiality store **512**. The confidential information includes confidentiality of content to be shared while accessing the electronic agents, user

designation, enterprise policies, and/or network connections to be used. The confidentiality information is correlated with the set of restrictions in the functionalities set by the policies. Based on the correlation, policies are identified corresponding to the electronic agent requested by the client device **102**. For example, based on the enterprise policy of restricting use of recording functionality by participants or restrictive use of an unauthorized VPN connection by the participants, the policies are identified. Log reports of past usage of the electronic agents from the logger **504** further influence the selection of the policies. The determined policies are provided to the policy enforcer **508** for implementing the policies at the client device **102**.

(56) The policy comparator **502** further identifies privileges associated with the determined policies from the privilege store **506**. The privilege store **506** includes a mapping of the policies and their respective privileges. The privileges are pre-defined by the administrator of the enterprise based on the enterprise policies. For example, the privileges may be assigned to the end user **106** of the client device **102** to provide access rights for sharing the content to the other participants while using the electronic agent. Another example, where the policy may specify privileges to all the participants to access the content while using the electronic agent. The policy comparator **502** further matches each of the tokens used by the application of the electronic agent at the client device **102** within a token mapping list stored in the policy store **110**. After matching the tokens, their respective policies or the modified policies are identified from the token mapping list. A comparison output is generated based on the comparison of each token with the respective policy and the associated privileges are provided to the policy enforcer **508**.

(57) The policy enforcer **508** identifies any compliance related issues with the past and current tokens based on the comparison output and enforces the policies to the client device **102**. The policy enforcer **508** further assigns the privileges associated with the policies to the end user **106** of the client device **102**.

(58) The logger **504** is a repository of the log reports of the tokens and functionalities used at the client device(s) **102**. The logger **504** also stores past log reports of policies implemented on the client device(s) **102**. The logger **504** stores events such as sharing, recording, inviting, or applying privileges while accessing the electronic agents. For example, the log reports include sharing of content by participants, unauthorized participant barging into a session of the electronic agent or unauthorized or authorized recording by the participants. The logger **504** continuously monitors the tokens used by the applications of the electronic agents at the client device(s) **102** and gathers log data from the client device(s) **102**. The log reports are provided to the IT module **214** for further analysis. The log reports are provided to the policy comparator **502** for selecting appropriate policies based on the log data.

(59) The auditor **514** identifies any non-compliance with the functionalities associated with the electronic agents. The auditor **514** performs an inspection regarding the usage of the functionalities while the electronic agent is being accessed. Any non-compliance with the functionalities is against the policies of the electronic agent. The AI devices are identified within a threshold distance from the participants accessing the electronic agent. For example, enabling the AI devices within the threshold distance from the participants may also indicate a non-compliance of the policies. Such incidents of non-compliances are reported in the form of audit reports and provided to the modifier **510**. The AI devices may be disabled based on the policies. The modifier **510** changes the policies or flags the incidents to the administrator/IT module **214** for further action.

(60) The modifier **510** processes the log reports from the logger **504** and the audit reports from the auditor **514** to modify the policies if required. For example, the client device **102** may be enforced with updated policies and the corresponding functionalities and the privileges may be updated accordingly. Threat levels associated with the tokens are updated from time to time which require the policies to be updated in the policy store **110**. Newly identified or unidentifiable tokens further require re-authorization from the administrator. Use of functionalities like sharing or recording may be subjected to abuse by the participants. The audit reports indicate the abuse of the functionalities

or the non-compliance with the policies. The policies then require to be updated after re-authorization. Based on a history of the usage of the functionalities associated with the electronic agents and the remote applications, the policies may be modified and implemented. The modified policies are provided for storage to the policy store **110**.

(61) Referring next to FIG. **6A**, a flow diagram **600** of communication between the end user **106** at the client device **102**, and the remote instances **308** at the web server **104** for accessing the electronic agents is shown.

(62) At step **1**, the end user **106** of the client device **102** requests a remote instance **308** for accessing an electronic agent by signing or visiting an electronic agent website **608** or a software application of the electronic agent. The end user **106** of the client device **102** may use a local application to perform the request by transmitting a token for accessing the electronic agent. A security administrator applies policies to the local application of the end user **106** corresponding to access to the electronic agent. When the end user **106** requests the access to the electronic agent, an audit is performed based on the policy. At step **2**, after receiving the request for access to the electronic agent, the electronic agent website **608** sends an authorization request to a mail application site **604**. The mail application site may be an email website associated with the end user **106**.

(63) At step **3**, the end user **106** logs into the email by providing user credentials and performs authorization. The end user **106** is authorized based on the user credentials. At step **4**, the end user **106** may read schedules for example, meetings for connecting to the electronic agent associated with the meeting application. The end user **106** is provided access to read the schedules based on a policy associated with the electronic agent. At step **5**, the end user **106** connects to a remote application site of the electronic agent to access the electronic agent based on the policy associated with the electronic agent. For example, the end user **106** may join the meeting via a meeting application site based on the policy. The end user **106** accesses the electronic agent via the remote application. Based on the policy associated with the electronic agent, the end user **106** is provided with a recording of the meeting at step **6** from the electronic agent website **608**.

(64) Referring next to FIG. **6B**, a flow diagram **610** of communication between the end users **106** attending a meeting from their respective client devices **102**, and an agent service **612** is shown.

(65) While accessing the electronic agent or scribe service, the user will request from one web server **104**, the connection and use another service (server to server) where the mid-link server **108** can analyze the interaction with the electronic agent/scribe service. The API service of the policy-controlled security system **100** analyzes administrative traces and connections to applications like calendaring, cloud storage, and email. Therefore, cloud service to cloud service interactions are also tracked and analyzed by the mid-link server **108**.

(66) At step **1**, the end user **106** of the client device **102** requests the agent service **612** for accessing an electronic agent for a virtual meeting application **616**. The end user **106** of the client device **102** may use a local application to perform the request by transmitting a token for accessing the virtual meeting application. At step **2**, an authentication of the request of the end user **106** is sent to a calendar application **614**. The calendar application **614** provides the slot for the virtual meeting by authenticating the request. At step **3**, the end user **106** approves the slot provided by the calendar application **614** based on an availability of the end user **106**.

(67) At step **4**, the end user **106** joins the virtual meeting **616** using the client device **102**. The agent service **612** connects the end user **106** to the virtual meeting **616** by reading the calendar from the calendar application **614**. Recording may also be allowed by reading the calendar. At step **5**, the agent service **612** may allow storage of the interactions and recordings which is optional. Other members **106** also connect to the virtual meeting **616** similarly from their respective client devices **102**.

(68) Referring next to FIG. **6C**, a flow diagram **618** of detection of unauthorized electronic agents/scribe services is shown.

(69) At step 1, an administrator **620** of an enterprise sends a request for authorization of the electronic agent/scribe service to the mid-link server **108**. The electronic agent/scribe service is the virtual meeting application **616**. The virtual meeting application **616** is linked with a calendar application **614** to identify slots in the calendar of the end users **106**. At step 2, the mid-link server **108** and the administrator authorizes the calendar from the calendar application **614**.

(70) At step 3, the mid-link server **108** connects to the virtual meeting application **616** based on the authorization at step 2. The electronic agent/scribe service **622** initiates the connection to the virtual meeting application **616**. The mid-link server **108** allows the end user **106** to join the virtual meeting application **616**. The mid-link server **108** analyzes the interactions during the meeting among the members (end users **106**). Based on the analysis and behavior of the end users **106** during the meeting, the mid-link server **108** can block any of the members (end users **106**). At step 4, the mid-link server **108** may initiate kick or do not record trigger for the members of the meeting based on a suspicious activity of the end user(s) **106** or the authorization associated the virtual meeting application **616**.

(71) At step 5, an alert is triggered to the administrator **620** for action from the mid-link server **108**. At step 6, the log of all meeting attendees (end users **106**) is collected, and historical and behavioral analysis is performed by the mid-link server **108** to determine unauthorized electronic agents/scribe services.

(72) Referring next to FIG. 7A, a Graphical User Interface (GUI) **700** associated with the policy-controlled security system **100** for accessing an electronic agent is shown. In present embodiment, the electronic agent is an online conference call application. However, in other embodiments, the electronic agent may be for example, a meeting application, a chatbot, a messaging application or a webinar tool. The GUI **700** is displayed to the end user(s) **106** on the client device(s) **102** for setting up conference calls by accessing the electronic agent via a remote application at the web server **104**. The remote application is the online conference call application.

(73) The GUI **700** includes a section **702** with various fields of a conference call system. A conference call client field **708** includes options field **710** for setting up a conference call such as sending invites to participants in the conference call. An organizer such as the end user **106** may use the options field **710** to set up the conference call. The conference call client field **708** is customized based on policies set by an administrator of an enterprise. The organizer and/or the participants are members of the enterprise. A status field **704** indicates a status of the conference call like scheduled, plan, or completed. The status field **704** is set by the organizer.

(74) A transcript button **712** allows the organizer to enable transcript rights for the call using a select button **706**. For example, selecting the transcript button **712** may enable sharing transcript of the call to the participants of the call after the call is over. A participant status field **714** enables the organizer to view responses from the participants on the call invite sent using the options filed **710**. The status of the conference call from the participants may be displayed as accepted, declined or tentative. The participants may request the organizer for access to the recording of the call. The requests for recording the call from the participants is also displayed along with the responses.

(75) An access designation field **716** has options for setting up calendar access and disabling AI devices around. Using the access designation field **716** enables the organizer to set up calendar access rights for the participants. Accessing calendars while setting up calls or chats may pose privacy concerns for the participants. AI devices within a certain area of the participants for example, within 20-30 meters from the participants may be disabled or powered off for the security and privacy of the conference call according to an enterprise policy.

(76) Referring next to FIG. 7B, a Graphical User Interface (GUI) **720** associated with the policy-controlled security system **100** for scheduling a meeting using an electronic agent is shown. The GUI **720** is presented to the end user(s) **106** on the client device(s) **102** for scheduling meetings by accessing the electronic agent via a remote application at the web server **104**. The remote application being a meeting application in this example. A meeting setup field **718** of the meeting

application is used to set up the meeting by the end user **106**. A schedule meeting tab **722** populates various options for the end user **106** to set up the meeting.

(77) A title of the meeting may be setup using the title field **724**. For example, 'walkthrough' may be the title for the meeting. The start and end time indicating day, date and time is set using time selection fields **726** and **728**, respectively. A time zone for the meeting may be setup using a time zone selection field **730**. Meeting ID and password are generated using selection fields **732** and **734**, respectively. Videos may be set for the host that is the end user **106** and the participants using a video setup field **736**. An audio setup **738** may be used for setting up an audio for the host. Calendar applications to be used for the meetings may be set using a calendar setup field **740**. Transcript of the meeting conversation may be set for the host and the other participants using a transcript setup field **742**. Finally, after setting up all the fields of the meeting application, the meeting is scheduled by pressing a schedule button **744**. A meeting notification is sent to all the participants as the meeting schedule is set by the end user **106**.

(78) Referring next to FIG. **8**, a flowchart of a method **800** of a policy-controlled security system **100** for a client device **102** is shown. The depicted portion of the process begins at block **802** where an end user **106** of the client device **102** loads a browser or a local application at the client device **102** to request access to an electronic agent. A token is required for accessing the electronic agent. The end user **106** desires to access the service at a first mile that is the client device **102** by sending the request using the token to a remote application at the web server **104**. The mid-link server **108** acts as an intermediate server controlling the token at a middle mile based on a set of policies. The web server **104** provides the end user **106** access to the electronic agent at a last mile.

(79) At block **804**, a set of policies corresponding to the electronic agent is determined from the policy database **304**. A number of policies are set by an administrator of an enterprise of the end user **106** based on an enterprise policy, a confidentiality associated with a functionality of the electronic agent, the remote application of the electronic agent, user logs, and/or a role of the end user **106**. The number of policies specifies controlled access to electronic agents. The controlled access includes restrictive use of a functionality of the electronic agents, authorized access to shared content, and/or access to the electronic agent by only authorized participants.

(80) At block **806**, privileges associated with the policies are assigned from the privilege store **506**. The privileges allow the end user **106** to assign access rights to other participants of the electronic agents based on the policies. The access rights are related to accessing of various functionalities of the electronic agents like recording, sharing content, inviting members, and/or use of AI devices in a vicinity of the members.

(81) At block **808**, the token is correlated with a list of tokens in the token repository **312** to identify a user application associated with the token. The list of tokens also includes an authorization information associated with the token. If the token has a match within the list of tokens, then the control moves to block **810**, else if there is no match found within the list of tokens, then the access is denied at block **812**. The end user **106** may request for re-authorization to the administrator when the token is denied. Based on an analysis performed by the administrator either the token is granted access or is blocked.

(82) At block **810**, after the user application of the token is identified, it is compared with the remote application in the request. If the user application is the remote application, then the remote application and the corresponding token is authorized at block **814** else the access using the token is denied at block **818**.

(83) At block **814**, the token is authorized for use based on the match of the user application with the remote application. A list of the remote applications and their corresponding tokens are authorized for accessing the electronic agent. The authorized remote application and the token enables access to the electronic agent.

(84) At block **820**, based on the authorization, the access is granted to the token. The end user **106** is provided access to the electronic agent using the token. The end user **106** is provided controlled

access to the electronic agent based on the set of policies.

(85) Referring next to FIG. 9, a flowchart of a method **900** of a policy-controlled security system **100** for performing an audit while accessing the electronic agent is shown. The depicted portion of the process begins at block **902** where the end user **106** of the client device **102** is provided access to the electronic agent based on a set of policies. The end user **106** who is a host initiates a session of the electronic agent. The end user **106** invites other participants to the session. The end user **106** assigns the privileges to the participants based on the set of policies. The privileges are associated with usage of different functionalities of the electronic agent during the session such as recording, sharing, enabling/disabling AI devices, or inviting other participants. The functionalities are based on the set of policies.

(86) At block **904**, access to a functionality may be disabled based on the set of policies. For example, recording during the session may be disabled based on the set of policies. However, the end user **106** may require access to the recording. The end user **106** may send a request for re-authorization to an administrator of an enterprise at block **906**.

(87) At block **908**, the administrator analyses the request and based on the analysis, performs re-authorization. The request may be granted access at block **912** or denied access at block **910** based on the re-authorization.

(88) At block **912**, the access to the functionality is granted access based on the re-authorization. The end user **106** has access enabled for the functionality that was initially disabled based on the set of policies. The policies associated with the functionality are modified based on the re-authorization. The modified policies are updated in the policy store **110**. The session is initiated by the end user **106** and the other participants.

(89) At block **914**, during the session, an audit is performed to identify whether AI devices around the end user **106** and the other participants are working based on the set of policies. The identification is performed using the remote application of the electronic agent. For example, the policies may require the AI devices around the end user **106** and the other participants within a distance of 50 meters to be disabled or only AI devices near the host may be enabled. Compliance with the policies is checked corresponding to AI devices.

(90) At block **916**, based on the audit, the AI devices around the end user **106** and the other participants that does not comply with the requirements of the policies are requested to be disabled or powered off. The non-complying participant or the host is provided with a notification to disable the AI devices as enabling them is against the policies. In cases of further non-compliance, the session may be revoked for the non-complying participant by the administrator or the end user **106**.

(91) At block **918**, non-compliance to any of the policies during the session is monitored. For example, if recording functionality is not allowed, however a participant starts recording the session, an alert notification is immediately flashed to the participant and/or all other participants including the host regarding the non-compliance at block **920**. In further cases of non-compliance by same participant, the access to the session may be blocked for the participant. The non-compliance of the policies and requests for re-authorization is continuously monitored until the session is complete. The control moves at block **904** for monitoring the requests.

(92) Referring next to FIG. 10, a flowchart of a method **1000** of a policy-controlled security system **100** for managing the policies associated with the electronic agent is shown. The depicted portion of the process begins in block **1002** where a token mapping is generated by the administrator and/or the enterprise at the IT module **214**. The token mapping includes a list of tokens mapped with their corresponding remote applications, and the electronic agents. The token mapping is stored in the token repository **312** of the mid-link server **108** by the IT module **214**.

(93) At block **1004**, a policy mapping including a list of policies of the electronic agents mapped with their corresponding tokens, functionalities, and the remote applications is generated. The policies are preset by the administrator based on user logs, tenants of the client device(s) **102**, confidentiality associated with the electronic agents or the remote applications of the electronic

agents, and/or designations of the end user(s) **106** such as manager, trainee, or employee. The functionalities associated with the electronic agents include recording, sharing, inviting, or accessing calendars. The tokens of specific remote applications to be used for accessing the electronic agents are allowed by the policies. The policies also specify controlled access to the functionalities of the electronic agents.

(94) At block **1006**, a request for access to an electronic agent is received from the end user **106** of the client device **102**. The end user **106** uses a local application running on the client device **102** to transmit the request to a remote application of the electronic agent which is running on a remote instance of the web server **104**. A token is required by the electronic agent for the access.

(95) At block **1008**, the token associated with the request is authorized. A policy associated with the electronic agent is identified from the policy mapping. The corresponding token and the remote application of the request is identified from the token mapping and correlated within the list of tokens and the remote applications. Based on the correlation, the token is authorized.

(96) At block **1010**, after authorization, the policies are enforced on the client device **102**. The access to the electronic agent based on the policy is provided to the end user **106** on the client device **102** from the remote instance. The access to the functionalities is provided based on the policies to the end user **106**. The end user **106** may be assigned privileges for providing the controlled access to the functionalities of the electronic agent. For example, the end user **106** may assign recording rights to one or more other users while using the electronic agent.

(97) At block **1012**, a re-request is received from the client device **102** regarding access to a disabled functionality. The functionality like sharing content might be disabled based on the policy associated with the electronic agent. However, the end user **106** may re-request for consideration on the disabled functionality according to user requirement. The re-request is provided to the IT module **214** for analysis.

(98) At block **1014**, an authorization of the re-request is determined by the administrator from the IT module **214**. Based on analyzing the policy and the user requirement, the administrator may either grant access to the functionality or keep the access to the functionality denied at block **1016**.

(99) At block **1018**, the access to the functionality is granted and the policy corresponding to the electronic agent is modified. For example, the access to the functionality of sharing content may be enabled by the administrator and the corresponding policy is updated. The modified policy is updated in the policy mapping at block **1004**.

(100) At block **1020**, another token corresponding to a new request for access to the electronic agent may be received. The token is compared with tokens in the list of tokens stored in the token mapping at block **1002**. In case the token is new which is not found in the list of tokens. The token is verified by the administrator and then added to the list of tokens in the token mapping.

(101) Specific details are given in the above description to provide a thorough understanding of the embodiments. However, it is understood that the embodiments may be practiced without these specific details. For example, circuits may be shown in block diagrams in order not to obscure the embodiments in unnecessary detail. In other instances, well-known circuits, processes, algorithms, structures, and techniques may be shown without unnecessary detail in order to avoid obscuring the embodiments.

(102) Implementation of the techniques, blocks, steps and means described above may be done in various ways. For example, these techniques, blocks, steps and means may be implemented in hardware, software, or a combination thereof. For a hardware implementation, the processing units may be implemented within one or more application specific integrated circuits (ASICs), digital signal processors (DSPs), digital signal processing devices (DSPDs), programmable logic devices (PLDs), field programmable gate arrays (FPGAs), processors, controllers, micro-controllers, microprocessors, other electronic units designed to perform the functions described above, and/or a combination thereof.

(103) Also, it is noted that the embodiments may be described as a process which is depicted as a

flowchart, a flow diagram, a swim diagram, a data flow diagram, a structure diagram, or a block diagram. Although a depiction may describe the operations as a sequential process, many of the operations can be performed in parallel or concurrently. In addition, the order of the operations may be re-arranged. A process is terminated when its operations are completed, but could have additional steps not included in the figure. A process may correspond to a method, a function, a procedure, a subroutine, a subprogram, etc. When a process corresponds to a function, its termination corresponds to a return of the function to the calling function or the main function.

(104) Furthermore, embodiments may be implemented by hardware, software, scripting languages, firmware, middleware, microcode, hardware description languages, and/or any combination thereof. When implemented in software, firmware, middleware, scripting language, and/or microcode, the program code or code segments to perform the necessary tasks may be stored in a machine readable medium such as a storage medium. A code segment or machine-executable instruction may represent a procedure, a function, a subprogram, a program, a routine, a subroutine, a module, a software package, a script, a class, or any combination of instructions, data structures, and/or program statements. A code segment may be coupled to another code segment or a hardware circuit by passing and/or receiving information, data, arguments, parameters, and/or memory contents. Information, arguments, parameters, data, etc. may be passed, forwarded, or transmitted via any suitable means including memory sharing, message passing, token passing, network transmission, etc.

(105) For a firmware and/or software implementation, the methodologies may be implemented with modules (e.g., procedures, functions, and so on) that perform the functions described herein. Any machine-readable medium tangibly embodying instructions may be used in implementing the methodologies described herein. For example, software codes may be stored in a memory. Memory may be implemented within the processor or external to the processor. As used herein the term “memory” refers to any type of long term, short term, volatile, nonvolatile, or other storage medium and is not to be limited to any particular type of memory or number of memories, or type of media upon which memory is stored.

(106) Moreover, as disclosed herein, the term “storage medium” may represent one or more memories for storing data, including read only memory (ROM), random access memory (RAM), magnetic RAM, core memory, magnetic disk storage mediums, optical storage mediums, flash memory devices and/or other machine readable mediums for storing information. The term “machine-readable medium” includes, but is not limited to portable or fixed storage devices, optical storage devices, and/or various other storage mediums capable of storing that contain or carry instruction(s) and/or data.

(107) While the principles of the disclosure have been described above in connection with specific apparatuses and methods, it is to be clearly understood that this description is made only by way of example and not as limitation on the scope of the disclosure.

Claims

1. A method for policy-controlled access security to electronic agents in cloud-based multi-tenant systems comprising a plurality of memories, the method comprising: requesting by a local application running on a client device access to an electronic agent of a remote application run on a remote instance of an agent server, wherein a token is required by the electronic agent; determining a set of policies from a plurality of policies corresponding to the electronic agent, wherein: the plurality of policies specifies controlled access to a plurality of electronic agents of a plurality of remote applications, the controlled access includes restrictive use of a functionality associated with the electronic agents, access to shared content, and/or access to the electronic agent by a plurality of end users, and the plurality of electronic agents includes online meeting, chatbots, web conferences, webinars, chatting platforms, and/or messaging applications; correlating the token

with a plurality of tokens in a token repository for identifying a user application associated with the token; comparing the remote application corresponding to the token from the request with the identified user application; determining an authorization by a mid-link server corresponding to the token for accessing the electronic agent based on the comparing, wherein the determining the authorization comprising either: authorizing the token for accessing the electronic agent via the remote application, or blocking the token when unauthorized to prevent access to the electronic agent, wherein machine learning algorithms are used to categorize the token based on token usage, and the token is subcategorized as blocked in case the token was blocked in past; enforcing the set of policies on the client device; identifying a non-compliance with the set of policies during the access of the electronic agents, wherein the non-compliance of the set of policies is identified by determining enabling of one or more Artificial Intelligence (AI) devices within a threshold distance from an end user of the client device, and an alert is generated for one or more of the plurality of end users based on the non-compliance; providing the access to the electronic agent based on the set of policies via the agent server; modifying the set of policies based on the non-compliance; and updating the functionality associated with the electronic agent based on the modified set of policies, wherein access rights to the functionality of the plurality of electronic agents comprise one or more of: recording, sharing content, inviting participants, and use of the one or more AI devices in a vicinity of the participants.

2. The method for policy-controlled access security to electronic agents in cloud-based multi-tenant systems as recited in claim 1, wherein the plurality of policies corresponding to the functionality are modified based on a new request from the client device.

3. The method for policy-controlled access security to electronic agents in cloud-based multi-tenant systems as recited in claim 1, wherein the plurality of policies is based on a tenant of the client device, a type of network connection, confidentiality associated with the functionality and the plurality of remote applications, user logs, and/or a user designation associated with the client device.

4. The method for policy-controlled access security to electronic agents in cloud-based multi-tenant systems as recited in claim 1, further comprising assigning a plurality of privileges to the client device for accessing the electronic agent based on the set of policies, wherein the set of policies specifies the plurality of privileges associated with the controlled access to the electronic agent.

5. The method for policy-controlled access security to electronic agents in cloud-based multi-tenant systems as recited in claim 1, wherein a plurality of privileges allows the end user of the plurality of end users to assign access rights to other participants of the electronic agents based on the set of policies.

6. The method for policy-controlled access security to electronic agents in cloud-based multi-tenant systems as recited in claim 1, wherein the modifying of the set of policies associated with the token is based on usage history of the functionality of the electronic agent.

7. A policy-based access system for managing secure access to electronic agents in cloud-based multi-tenant systems, the policy-based access system comprising one or more servers including one or more memories, collectively having code for: requesting by a local application running on a client device access to an electronic agent of a remote application run on a remote instance of an agent server, wherein a token is required by the electronic agent; determining a set of policies from a plurality of policies corresponding to the electronic agent, wherein: the plurality of policies specifies controlled access to a plurality of electronic agents of a plurality of remote applications, the controlled access comprises one or more of restrictive use of a functionality associated with the electronic agents, access to shared content, and access to the electronic agent by a plurality of end users, and the plurality of electronic agents comprises one or more of: online meetings, chatbots, web conferences, webinars, chatting platforms, and messaging applications; correlating the token with a plurality of tokens in a token repository for identifying a user application associated with the token; comparing the remote application corresponding to the token from the request with the

identified user application; determining an authorization by a mid-link server corresponding to the token for accessing the electronic agent based on the comparing, wherein the determining the authorization comprising either: authorizing the token for accessing the electronic agent via the remote application, or blocking the token when unauthorized to prevent access to the electronic agent, wherein machine learning algorithms are used to categorize the token based on token usage, and the token is subcategorized as blocked in case the token was blocked in past; enforcing the set of policies on the client device; identifying a non-compliance with the set of policies during access of the electronic agents, wherein the non-compliance of the set of policies is identified by determining enabling of one or more Artificial Intelligence (AI) devices within a threshold distance from an end user of the client device, and an alert is generated for one or more of the plurality of end users based on the non-compliance; providing access to the electronic agent based on the set of policies via the agent server; modifying the set of policies based on the non-compliance; and updating the functionality associated with the electronic agent based on the modified set of policies, wherein access rights to the functionality of the plurality of electronic agents comprise one or more of: recording, sharing content, inviting participants, and use of the one or more AI devices in a vicinity of the participants.

8. The policy-based access system for managing secure access to electronic agents in cloud-based multi-tenant systems as recited in claim 7, wherein the plurality of policies corresponding to the functionality are modified based on a new request from the client device.

9. The policy-based access system for managing secure access to electronic agents in cloud-based multi-tenant systems as recited in claim 7, wherein the plurality of policies is based on a tenant of the client device, a type of network connection, confidentiality associated with the functionality and the plurality of remote applications, user logs, and/or a user designation associated with the client device.

10. The policy-based access system for managing secure access to electronic agents in cloud-based multi-tenant systems as recited in claim 7, further comprising code for assigning a plurality of privileges to the client device for accessing the electronic agent based on the set of policies, wherein the set of policies specifies the plurality of privileges associated with the controlled access to the electronic agent.

11. The policy-based access system for managing secure access to electronic agents in cloud-based multi-tenant systems as recited in claim 7, wherein a plurality of privileges allows the end user of the plurality of end users to assign access rights to other participants of the electronic agents based on the set of policies.

12. The policy-based access system for managing secure access to electronic agents in cloud-based multi-tenant systems as recited in claim 7, wherein the modifying of the set of policies associated with the token is based on usage history of the functionality of the electronic agent.

13. A policy-controlled access security system for managing access security to electronic agents in a cloud based multi-tenant system, the policy-controlled access security system comprising: a client device having a local application, the local application executes on the client device to request by a local application running on a client device access to an electronic agent of a remote application run on a remote instance of an agent server, wherein a token is required by the electronic agent; and a mid-link server for: determine a set of policies from a plurality of policies corresponding to the electronic agent, wherein: the plurality of policies specifies controlled access to a plurality of electronic agents of a plurality of remote applications, the controlled access comprises one or more of: restrictive use of a functionality associated with the electronic agents, access to shared content, and access to the electronic agent by a plurality of end users, and the plurality of electronic agents comprises one or more of: online meetings, chatbots, web conferences, webinars, chatting platforms, and messaging applications; correlate the token with a plurality of tokens in a token repository for identifying a user application associated with the token; compare the remote application corresponding to the token from the request with the identified user application;

determine an authorization by a mid-link server corresponding to the token for accessing the electronic agent based on the comparing, wherein the determining the authorization comprises either: authorizing the token for accessing the electronic agent via the remote application, or blocking the token when unauthorized to prevent access to the electronic agent, wherein machine learning algorithms are used to categorize the token based on token usage, and the token is subcategorized as blocked in case the token was blocked in past; enforce the set of policies on the client device; identify a non-compliance with the set of policies during access of the electronic agents, wherein the non-compliance of the set of policies is identified by determining enabling of one or more Artificial Intelligence (AI) devices within a threshold distance from an end user of the client device, and an alert is generated for one or more of the plurality of end users based on the non-compliance; provide access to the electronic agent based on the set of policies via the agent server; modify the set of policies based on the non-compliance; and updating the functionality associated with the electronic agent based on the modified set of policies, wherein access rights to the functionality of the plurality of electronic agents comprises one or more of: recording, sharing content, inviting participants, and use of the one or more AI devices in a vicinity of the participants.

14. The policy-controlled access security system for managing access security to electronic agents in the cloud based multi-tenant system recited in claim 13, wherein the plurality of policies corresponding to the functionality are modified based on a new request from the client device.

15. The policy-controlled access security system for managing access security to electronic agents in the cloud based multi-tenant system recited in claim 13, wherein the plurality of policies is based on a tenant of the client device, a type of network connection, confidentiality associated with the functionality and the plurality of remote applications, user logs, and/or a user designation associated with the client device.

16. The policy-controlled access security system for managing access security to electronic agents in the cloud based multi-tenant system recited in claim 13, wherein the policy-controlled access security system assigns a plurality of privileges to the client device for accessing the electronic agent based on the set of policies, wherein the set of policies specifies the plurality of privileges associated with the controlled access to the electronic agent.

17. The policy-controlled access security system for managing access security to electronic agents in the cloud based multi-tenant system recited in claim 13, wherein a plurality of privileges allows the end user of the plurality of end users to assign access rights to other participants of the electronic agents based on the set of policies.

18. The policy-controlled access security system for managing access security to electronic agents in the cloud based multi-tenant system recited in claim 13, wherein the modifying of the set of policies associated with the token is based on usage history of the functionality of the electronic agent.
