

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12414150
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Lee; Soonho et al.

Electronic device and method for scheduling of data link

Abstract

An electronic device according to various example embodiments includes: at least one wireless communication module comprising wireless communication circuitry configured to support a first communication protocol and a second communication protocol, at least one processor operatively connected to the wireless communication module, and a memory electrically connected to the processor and configured to store instructions executable by the processor. When the instructions are executed by the processor, the processor may, using the wireless communication module, set a schedule for a first data link that uses a first frequency band as the second communication protocol with a first external electronic device, set a schedule for a second data link that uses a second frequency band as the second communication protocol with a second external electronic device, and change the second data link to a third data link that uses a third frequency band and perform communication with the second external electronic device, based on the third frequency band being available due to a termination of the first data link.

Inventors: Lee; Soonho (Suwon-si, KR), Jung; Buseop (Suwon-si, KR), Kim; Beomjip (Suwon-si, KR), Bang; Hyejung (Suwon-si, KR), Lee; Dooho (Suwon-si, KR), Lee; Sunkee (Suwon-si, KR), Jang; Wonjun (Suwon-si, KR)

Applicant: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Family ID: 85200270

Assignee: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Appl. No.: 17/967849

Filed: October 17, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230063981 A1	Mar. 02, 2023

Foreign Application Priority Data

Related U.S. Application Data

continuation parent-doc WO PCT/KR2022/010449 20220723 PENDING child-doc US 17967849

Publication Classification

Int. Cl.: H04W72/12 (20230101); H04L69/18 (20220101); H04W72/566 (20230101);
H04W80/00 (20090101)

U.S. Cl.:

CPC H04W72/569 (20230101); H04L69/18 (20130101); H04W80/00 (20130101)

Field of Classification Search

CPC: H04W (72/569); H04W (80/00); H04W (72/21); H04W (84/12); H04W (72/563); H04W (72/51); H04W (76/20); H04W (84/18); H04W (88/06); H04L (69/18); Y02D (30/70)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9516540	12/2015	Emmanuel et al.	N/A	N/A
10004095	12/2017	Jung	N/A	N/A
2015/0103740	12/2014	Emmanuel et al.	N/A	N/A
2016/0286574	12/2015	Abraham et al.	N/A	N/A
2016/0350973	12/2015	Shapira	N/A	G06F 3/011
2017/0311341	12/2016	Patil et al.	N/A	N/A
2017/0325230	12/2016	Abraham et al.	N/A	N/A
2018/0014341	12/2017	Jung	N/A	N/A
2019/0124660	12/2018	Huang	N/A	H04W 76/14
2020/0008095	12/2019	Patil	N/A	H04W 12/03
2021/0185746	12/2020	Mullati et al.	N/A	N/A
2024/0057062	12/2023	Homchaudhuri	N/A	H04W 72/52

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
10-2018-0005471	12/2017	KR	N/A
10-2018-0054694	12/2017	KR	N/A
10-1983362	12/2018	KR	N/A
10-2019-0124534	12/2018	KR	N/A
10-2021-0051274	12/2020	KR	N/A

OTHER PUBLICATIONS

Neighbor Awareness Networking Specification Addendum version 3.0.3, 2019, pp. 1-50. cited by applicant

Neighbor Awareness Networking Technical Specification Version 2.0 r6, 2017, pp. 1-220. cited by

applicant

Search Report dated Oct. 19, 2022 issued in International Patent Application No.

PCT/KR2022/010449. cited by applicant

Extended European Search Report dated Sep. 4, 2024 issued in European Patent Application No.

22856042.1. cited by applicant

Primary Examiner: Truong; Lan-Huong

Attorney, Agent or Firm: Nixon & Vanderhye P.C.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of International Application No. PCT/KR2022/010449 designating the United States, filed on Jul. 23, 2022, in the Korean Intellectual Property Receiving Office and claiming priority to Korean Patent Application No. 10-2021-0105114, filed on Aug. 10, 2021, in the Korean Intellectual Property Office, the disclosures of which are incorporated by reference herein in their entireties.

BACKGROUND

1. Field

(1) The disclosure relates to an electronic device and a method of scheduling a data link.

2. Description of Related Art

(2) Recently, various proximity services using low-power discovery technology employing short-range communication technology are being actively developed. For example, a proximity communication service that enables neighboring electronic devices to quickly exchange data through a proximity network is being developed.

(3) Recently, in the wireless fidelity (Wi-Fi) standard, low-power discovery technology called neighbor awareness networking (NAN) is being developed, and a short-range proximity service based on NAN is being actively developed.

(4) An electronic device may form a data link with each of external electronic devices (e.g., a neighbor awareness networking (NAN) supporting device, and an access point (AP)). A data link may be set between an electronic device and external electronic devices according to device performance (e.g., support for various frequency bands, and support for real simultaneous dual band (RSDB)). If a data link between the electronic device and an arbitrary external electronic device is terminated, a data link formed between the electronic device and each of external electronic devices other than the arbitrary external electronic device may be maintained without a change. If an available frequency band is present due to a termination of the data link, it may be advantageous in terms of performance to perform communication using a data link that uses the available frequency band. Accordingly, the electronic device may need to schedule a data link by efficiently using multiple frequency bands according to circumstances.

SUMMARY

(5) Embodiments of the disclosure may provide a technology of scheduling a data link using multiple frequency bands in response to a change in an available frequency band.

(6) An electronic device according to various example embodiments includes: at least one wireless communication module including wireless communication circuitry configured to support a first communication protocol and a second communication protocol, at least one processor operatively connected to the wireless communication module, and a memory electrically connected to the processor and configured to store instructions executable by the processor. When the instructions are executed by the processor, the processor may be configured to: using the wireless

communication module, set a schedule for a first data link that uses a first frequency band as the second communication protocol with a first external electronic device, set a schedule for a second data link that uses a second frequency band as the second communication protocol with a second external electronic device, change the second data link to a third data link that uses a third frequency band and perform communication with the second external electronic device based on the third frequency band being available due to a termination of the first data link.

(7) An electronic device according to various example embodiments includes: at least one wireless communication module comprising wireless communication circuitry configured to support a first communication protocol and a second communication protocol, at least one processor operatively connected to the wireless communication module, and a memory electrically connected to the processor and configured to store instructions executable by the processor. When the instructions are executed by the processor, the processor may be configured to: using the wireless communication module, set a schedule for a first data link that uses a first frequency band as the first communication protocol with a first external electronic device, set a schedule for a second data link that uses both the first frequency band and a second frequency band as the second communication protocol with a second external electronic device, and change the second data link to a third data link that uses an interval of a frequency band having a lower priority between the first frequency band and the second frequency band as an interval of a third frequency band and perform communication with the second external electronic device based on an interval of a frequency band used in the second data link being changeable due to a termination of the first data link.

(8) A method of operating an electronic device according to various example embodiments includes: setting a schedule for a first data link that uses a first frequency band as a second communication protocol with a first external electronic device, setting a schedule for a second data link that uses a second frequency band as the second communication protocol with a second external electronic device, and changing the second data link to a third data link that uses a third frequency band and performing communication with the second external electronic device based on the third frequency band being available due to a termination of the first data link.

(9) An electronic device according to various example embodiments includes: at least one wireless communication module comprising wireless communication circuitry configured to support a first communication protocol and a second communication protocol, at least one processor operatively connected to the wireless communication module, and a memory electrically connected to the processor and configured to store instructions executable by the processor. When the instructions are executed by the processor, the processor may be configured to: using the wireless communication module, set a schedule for a first data link that uses a first frequency band as the first communication protocol with a first external electronic device, set a schedule for a second data link that uses a second frequency band as the second communication protocol with a second external electronic device, and change the second data link to a third data link that uses a third frequency band and perform communication with the second external electronic device based on the third frequency band being available due to a termination of the first data link.

(10) According to various example embodiments, an existing data link may be changed to a new data link through scheduling of a data link using multiple frequency bands according to a situation in which an available frequency band is changed, and communication may be performed, and thus it is possible to enhance communication performance by efficiently using the multiple frequency bands.

(11) In addition, various effects directly or indirectly ascertained through the present disclosure may be provided.

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The above and other aspects, features, and advantages of certain embodiments of the present disclosure will be more apparent from the following detailed description, taken in conjunction with the accompanying drawings, in which:
- (2) FIG. 1 is a diagram illustrating an example neighbor awareness networking (NAN) cluster according to various embodiments;
- (3) FIG. 2 is a diagram illustrating an example of communication based on a NAN protocol according to various embodiments;
- (4) FIG. 3 is a diagram illustrating communication between electronic devices in a NAN cluster according to various embodiments;
- (5) FIG. 4 is a diagram illustrating an example of communication based on a NAN protocol according to various embodiments;
- (6) FIG. 5 is a signal flow diagram illustrating a NAN data link (NDL) scheduling operation according to various embodiments;
- (7) FIG. 6 is a diagram illustrating an example of an NDL scheduling method by a change in a frequency band according to various embodiments;
- (8) FIG. 7 is a flowchart illustrating an example operation of an electronic device to perform NDL scheduling by a change in a frequency band according to various embodiments;
- (9) FIG. 8 is a diagram illustrating an example of an NDL scheduling operation performed based on the NDL scheduling method of FIG. 6 according to various embodiments;
- (10) FIG. 9 is a diagram illustrating an example of an NDL scheduling operation performed based on the NDL scheduling method of FIG. 6 according to various embodiments;
- (11) FIG. 10 is a diagram illustrating an example of an NDL scheduling operation performed based on the NDL scheduling method of FIG. 6 according to various embodiments;
- (12) FIG. 11A is a diagram illustrating an example in which a scheduling operation of FIG. 8 is performed according to various embodiments;
- (13) FIG. 11B is a diagram illustrating an example in which a scheduling operation of FIG. 9 is performed according to various embodiments;
- (14) FIG. 11C is a diagram illustrating an example in which a scheduling operation of FIG. 10 is performed according to various embodiments;
- (15) FIG. 11D is a diagram illustrating slots of newly set data links of FIGS. 11A, 11B and 11C according to various embodiments;
- (16) FIG. 12A is a diagram illustrating an example in which the scheduling operation of FIG. 8 is performed according to various embodiments;
- (17) FIG. 12B is a diagram illustrating an example in which the scheduling operation of FIG. 9 is performed according to various embodiments;
- (18) FIG. 12C is a diagram illustrating an example in which the scheduling operation of FIG. 10 is performed according to various embodiments;
- (19) FIG. 12D is a diagram illustrating slots of newly set data links of FIGS. 12A, 12B and 12C according to various embodiments;
- (20) FIG. 13A is a diagram illustrating an example in which the scheduling operation of FIG. 8 is performed according to various embodiments;
- (21) FIG. 13B is a diagram illustrating an example in which the scheduling operation of FIG. 9 is performed according to various embodiments;
- (22) FIG. 13C is a diagram illustrating an example in which the scheduling operation of FIG. 10 is performed according to various embodiments;
- (23) FIG. 13D is a diagram illustrating slots of newly set data links of FIGS. 13A, 13B and 13C according to various embodiments;
- (24) FIG. 14A is a diagram illustrating an example in which the scheduling operation of FIG. 8 is

performed according to various embodiments;

(25) FIG. 14B is a diagram illustrating an example in which the scheduling operation of FIG. 9 is performed according to various embodiments;

(26) FIG. 14C is a diagram illustrating an example in which the scheduling operation of FIG. 10 is performed according to various embodiments;

(27) FIG. 14D is a diagram illustrating slots of newly set data links of FIGS. 14A, 14B and 14C according to various embodiments;

(28) FIG. 15 is a diagram illustrating an example of an NDL scheduling method by a change in a frequency band according to various embodiments;

(29) FIG. 16 is a flowchart illustrating an example operation of an electronic device to perform NDL scheduling by a change in a frequency band according to various embodiments;

(30) FIG. 17 is a diagram illustrating an example of an NDL scheduling operation performed based on the NDL scheduling method of FIG. 15 according to various embodiments;

(31) FIG. 18 is a diagram illustrating an example of an NDL scheduling operation performed based on the NDL scheduling method of FIG. 15 according to various embodiments;

(32) FIG. 19 is a diagram illustrating an example of an NDL scheduling operation performed based on the NDL scheduling method of FIG. 15 according to various embodiments;

(33) FIG. 20A is a diagram illustrating an example in which a scheduling operation of FIG. 17 is performed according to various embodiments;

(34) FIG. 20B is a diagram illustrating an example in which a scheduling operation of FIG. 18 is performed according to various embodiments;

(35) FIG. 20C is a diagram illustrating an example in which a scheduling operation of FIG. 19 is performed according to various embodiments;

(36) FIG. 20D is a diagram illustrating slot configurations of data links of FIGS. 20A, 20B and 20C according to various embodiments;

(37) FIG. 21A is a diagram illustrating an example in which the scheduling operation of FIG. 18 is performed;

(38) FIG. 21B is a diagram illustrating an example in which the scheduling operation of FIG. 18 is performed according to various embodiments;

(39) FIG. 21C is a diagram illustrating an example in which the scheduling operation of FIG. 19 is performed according to various embodiments;

(40) FIG. 21D is a diagram illustrating slot configurations of data links of FIGS. 21A, 21B and 21C according to various embodiments;

(41) FIG. 22A is a diagram illustrating an example in which the scheduling operation of FIG. 18 is performed according to various embodiments;

(42) FIG. 22B is a diagram illustrating an example in which the scheduling operation of FIG. 18 is performed according to various embodiments;

(43) FIG. 22C is a diagram illustrating an example in which the scheduling operation of FIG. 19 is performed according to various embodiments;

(44) FIG. 22D is a diagram illustrating slot configurations of data links of FIGS. 22A, 22B and 22C according to various embodiments; and

(45) FIG. 23 is a block diagram illustrating an example electronic device in a network environment according to various embodiments.

DETAILED DESCRIPTION

(46) Hereinafter, various example embodiments will be described in greater detail with reference to the accompanying drawings. When describing the example embodiments with reference to the accompanying drawings, like reference numerals refer to like elements and a repeated description related thereto may not be provided.

(47) FIG. 1 is a diagram illustrating an example neighbor awareness networking (NAN) cluster according to various embodiments.

(48) Referring to FIG. 1, according to various example embodiments, a NAN cluster **100** may include at least one device (e.g., an electronic device **101**, an electronic device **102**, an electronic device **103** and/or an electronic device **104** of FIG. 1). Within the NAN cluster **100**, the electronic devices **101**, **102**, **103**, and/or **104** may communicate with each other through a NAN. The NAN cluster **100** may refer to a set of the electronic devices **101**, **102**, **103**, and/or **104** that configure a proximity network to transmit and receive data between the electronic devices **101**, **102**, **103**, and/or **104**.

(49) According to various example embodiments, the electronic device **101**, **102**, **103**, or **104** may refer to a device that supports NAN, which is a low-power discovery technology, and may also be referred to as a “NAN device (or a NAN terminal)”. In addition, the electronic device **101**, **102**, **103**, or **104** may operate in a frequency band of 2.4 GHz, 5 GHz, and/or 6 GHz, and may exchange signals based on the institute of electrical and electronic engineers (IEEE) 802.11 protocol (e.g., 802.11 a/b/g/n/ac/ax/be). The electronic devices **101**, **102**, **103**, and/or **104** may exchange signals in a unicast, broadcast, and/or multicast manner.

(50) According to various example embodiments, the electronic devices **101**, **102**, **103**, and/or **104** may configure one NAN cluster **100** by transmitting and receiving beacons (e.g., discovery beacons). The electronic device **101**, **102**, **103**, or **104** in the NAN cluster **100** may perform time and channel synchronization.

(51) According to various example embodiments, the discovery beacon may refer to a beacon signal for discovering an electronic device for forming a cluster in order to form a cluster (e.g., the NAN cluster **100**) for a proximity network. The discovery beacon may be a signal transmitted to allow another electronic device that failed to join the NAN cluster **100** to discover the NAN cluster **100**. For example, the discovery beacon may be a signal to inform of the existence of the NAN cluster **100**, and an electronic device that does not join the NAN cluster **100** may perform a passive scan to receive the discovery beacon, thereby discovering and joining the NAN cluster **100**.

(52) According to various example embodiments, the discovery beacon may include information necessary for synchronization with the NAN cluster **100**. For example, the discovery beacon may include at least one of a frame control (FC) field indicating a function of a signal (e.g., a beacon), a broadcast address, a media access control (MAC) address of a transmission electronic device, a cluster identifier (ID), a sequence control field, a time stamp for a beacon frame, a beacon interval indicating a transmission interval of the discovery beacon, or capability information on a transmission electronic device. In addition, the discovery beacon may further include an information element related to at least one proximity network (or cluster) (e.g., the NAN cluster **100**). Proximity network-related information may be referred to as “attribute information”.

(53) According to various example embodiments, the electronic devices **101**, **102**, **103**, and/or **104** may transmit and receive signals (e.g., synchronization beacons, service discovery frames (SDFs) or NAN action frames (NAFs)) within a synchronized time duration (e.g., a discovery window (DW)). For example, the electronic devices **101**, **102**, **103**, and/or **104** may have time clocks synchronized with each other, and transmit and receive beacons and SDFs to and from each other in DWs synchronized in the same time.

(54) According to various example embodiments, the synchronization beacon may indicate a signal for maintaining synchronization between the synchronized electronic devices **101**, **102**, **103**, and/or **104** in the NAN cluster **100**. The synchronization beacon may be periodically transmitted and received in each DW in order to continuously maintain the time and channel synchronization of the electronic devices **101**, **102**, **103**, and/or **104** in the NAN cluster **100**. The synchronization beacon may be transmitted by any electronic device among the electronic devices **101**, **102**, **103**, and **104** in the cluster **100**. An electronic device that transmits a synchronization beacon may include or may be referred to as an anchor master device defined in the NAN standard, a master device, or a non-master sync device.

(55) According to various example embodiments, the synchronization beacon may include

information necessary for synchronization of the electronic devices **101**, **102**, **103**, and **104** in the NAN cluster **100**. For example, the synchronization beacon may include at least one of an FC field indicating a function of a signal (e.g., a beacon), a broadcast address, a MAC address of a transmission electronic device, a cluster ID, a sequence control field, a time stamp for a beacon frame, a beacon interval indicating an interval between start points of a DW, and capability information on the transmission electronic device. The synchronization beacon may further include an information element related to at least one proximity network (or cluster) (e.g., the NAN cluster **100**). Proximity network-related information may include content for a service provided through the proximity network.

(56) According to various example embodiments, the SDF may be a signal to exchange data through a proximity network (or cluster) (e.g., the NAN cluster **100**). The SDF may indicate a vendor-specific public action frame and may include various fields. For example, the SDF may include a category or an action field, and may further include at least one piece of proximity network (e.g., the NAN cluster **100**)-related information

(57) According to various example embodiments, the electronic device **101**, **102**, **103**, or **104** included in the NAN cluster **100** may transmit and receive a NAF within the DW. For example, the NAF may include at least one of information for setup of a NAN data path (NDP), information for schedule update, and information to perform NAN ranging (e.g., NAN ranging in a fine timing measurement (FTM) period), to perform data communication in an interval between DWs. The NAF may be used to control a schedule of radio resources for coexistence of a NAN operation and a non-NAN operation (e.g., wireless fidelity (Wi-Fi) direct, mesh, independent basic service set (IBSS), wireless local area network (WLAN), Bluetooth™, or near-field communication (NFC)). The NAF may include time and channel information available for NAN communication.

(58) FIG. 2 is a diagram illustrating an example of communication based on a NAN protocol according to various embodiments.

(59) FIG. 2 illustrates an example of a DW, and an electronic device (e.g., the electronic device **101**, **102**, **103**, or **104** of FIG. 1) included in one cluster (e.g., the NAN cluster **100** of FIG. 1) may perform discovery, synchronization, and data exchange operations according to the NAN protocol. In FIG. 2, it may be assumed that communication is performed through a specific channel (e.g., channel 6 (CH6)) based on the NAN standard.

(60) According to various example embodiments, the electronic device **101**, **102**, **103**, or **104** may broadcast a discovery beacon **230** for discovering another electronic device **101**, **102**, **103**, or **104** in a predetermined first period (e.g., about 100 milliseconds (msec)), and may perform scanning in a predetermined second cycle (e.g., about 10 msec), to receive a discovery beacon **230** broadcast from the other electronic device **101**, **102**, **103**, or **104**. One electronic device among the electronic devices **101**, **102**, **103**, and **104** may recognize at least one of the other electronic devices located near the one electronic device, based on the discovery beacon **230** received through scanning, and may perform time and channel synchronization with the at least one recognized electronic device. Accordingly, one NAN cluster **100** may be configured.

(61) According to various example embodiments, the time and channel synchronization may be performed based on a time and channel of an electronic device having the highest master preference in the NAN cluster **100**. For example, the electronic device **101**, **102**, **103**, or **104** in the NAN cluster **100** configured through discovery may exchange signals regarding master preference information indicating a preference for operating as an anchor master, and an electronic device having the highest master preference may be determined to be an anchor master (or a master electronic device) through the exchanged signals. The anchor master may refer to a reference electronic device for time and channel synchronization of the electronic device **101**, **102**, **103**, or **104** in the NAN cluster **100**. The anchor master may vary depending on the master preference of the electronic device.

(62) According to various example embodiments, the anchor master may transmit the discovery

beacon **230** including information such as a cluster ID (e.g., an ID of the NAN cluster **100**) in an interval **240** (e.g., an interval between DWs **225**) other than the DW **225**. Here, the discovery beacon **230** may be used to inform of the existence of the NAN cluster **100**, and the anchor master may transmit the discovery beacon **230** to allow another electronic device that failed to join the NAN cluster **100** to discover the NAN cluster **100**.

(63) According to various example embodiments, the DW **225** may be an interval in which a corresponding electronic device is activated by switching from a sleep state, which corresponds to a power saving mode, to a wake-up state in order for the electronic devices **101**, **102**, **103**, and/or **104** to exchange data with each other. For example, the DW **225** may be divided into time units (TUs) in milliseconds. The DW **225** for transmitting and receiving a synchronization beacon **210** and an SDF **220** may occupy “16” TUs, and may have a cycle (or period) that is repeated every “512” TUs.

(64) According to various example embodiments, the electronic device **101**, **102**, **103**, or **104** may operate in an active state during the DW **225**, and may operate in a low-power state (e.g., a sleep state) during intervals other than the DW **225**, thereby reducing power consumption. For example, the DW **225** may be a period of time (e.g., milliseconds) during which the electronic device **101**, **102**, **103**, or **104** is in an active state (or a wake-up state) in which a large amount of power is consumed, and the electronic device **101**, **102**, **103**, or **104** may remain in a sleep state in intervals other than the DW **225**, so that low-power discovery may be possible. Accordingly, the electronic devices **101**, **102**, **103**, and/or **104** may be simultaneously activated at the start time (e.g., a DW start) of the DW **225**, which is time-synchronized, and may simultaneously switch to the sleep state at the end time (e.g., a DW end) of the DW **225**.

(65) According to various example embodiments, the electronic device **101**, **102**, **103**, or **104** included in the NAN cluster **100** may transmit the synchronization beacon **210** within the DW **225** (e.g., a synchronized DW). In addition, the electronic device **101**, **102**, **103**, or **104** may transmit the SDF **220** within the DW **225**. The electronic device **101**, **102**, **103**, or **104** may transmit the synchronization beacon **210** and the SDF **220** on a contention basis. For example, a transmission priority of the synchronization beacon **210** may be higher than that of the SDF **220**.

(66) FIG. 3 is a diagram illustrating example communication between electronic devices in a NAN cluster according to various embodiments.

(67) FIG. 3 illustrates an operation in which the electronic devices **101**, **102** and **103** (which may be referred to as devices **101** to **103**) form one cluster (e.g., the NAN cluster **100** of FIG. 2) through a wireless short-range communication technology and communicate with each other. For convenience of description, it may be assumed that the electronic device **101** is a master electronic device in FIG. 3.

(68) Referring to FIG. 3, according to various example embodiments, the electronic device **101** may transmit a beacon (e.g., a synchronization beacon), an SDF, or a NAF within a DW **350**. For example, the electronic device **101** may broadcast a beacon, SDF, or NAF within the DW **350** that is repeated every predetermined interval (or period) (e.g., an interval **360**).

(69) According to various example embodiments, the electronic devices **102** and **103** may receive beacons, SDFs, or NAFs transmitted by the electronic device **101**. For example, each of the electronic devices **102** and **103** may receive a beacon, SDF, or NAF broadcast from the electronic device **101** every DW **350**.

(70) According to various example embodiments, the beacon transmitted in the DW **350** may indicate a synchronization beacon and may include information for maintaining synchronization between the electronic devices **101** to **103**. For example, when the electronic devices **101** to **103** are included in a cluster, a time clock may be synchronized with a master electronic device (e.g., the electronic device **101**), so that the DW **350** may be simultaneously activated.

(71) According to various example embodiments, the electronic devices **101** to **103** may remain in a sleep state in intervals (e.g., the interval **360**) other than the DW **350**, to reduce current

consumption. For example, the electronic devices **101** to **103** may operate in a wake-up state only in the DW **350**, based on the synchronized time clock, thereby reducing power consumption.

(72) FIG. **4** is a diagram illustrating an example of communication based on a NAN protocol according to various embodiments.

(73) According to various example embodiments, a NAN data link (NDL) (or NDP) may be set up between the electronic devices **101**, **102**, **103**, and/or **104**. Unlike other communication schemes, the NDL may enable data communication with a fast setup time by operating on a connectionless basis. Through the NDL, flexible data communication with a plurality of electronic devices **101**, **102**, **103**, and **104** may be possible. The electronic device **101**, **102**, **103**, or **104** may define (e.g., set) a time slot (e.g., an active time slot) for data transmission using an interval between DWs without a separate connection between devices, and may perform additional communication (e.g., NAN communication and/or non-NAN communication) using the time slot. Here, data transmitted through a corresponding NDL may be encrypted with security.

(74) According to various example embodiments, the electronic device **101**, **102**, **103**, or **104** may perform an operation of controlling a schedule of resources (e.g., radio resources) for concurrence of a NAN operation (e.g., a NAN communication operation) and a non-NAN operation (e.g., a non-NAN communication operation). Each electronic device **101**, **102**, **103**, or **104** may transfer schedule information including an available time and channel for a NAN function and a concurrent operation to neighboring devices.

(75) According to various example embodiments, the electronic device **101**, **102**, **103**, or **104** may set a schedule of a further available window (FAW) and an unaligned window (ULW) for a NAN operation and/or a non-NAN operation (e.g., WLAN, Wi-Fi direct, IBSS, mobile hotspot, and/or mesh) in an interval between DWs. The FAW may have radio resources allocated for a NAN operation and/or a non-NAN operation, and may be divided into TUs in milliseconds. The ULW may have radio resources allocated for a non-NAN operation, and may be divided in units of microseconds.

(76) According to various example embodiments, the FAW may be set based on a NAN availability attribute (or NAN availability information), and the ULW may be set based on an unaligned schedule attribute (or unaligned schedule information). The NAN availability attribute and/or the unaligned schedule attribute may be included in at least one of management frames such as beacons (e.g., synchronization beacons), SDFs, and NAFs transmitted within a DW, and may be transmitted.

(77) According to various example embodiments, a plurality of NAN availability attributes and/or unaligned schedule attributes may be included in the management frame. Various FAWs may be configured based on a combination of the plurality of NAN availability attributes, and various ULWs may be configured based on a combination of the plurality of unaligned schedule attributes.

(78) According to various example embodiments, the FAW and the ULW may overlap each other. If the FAW and the ULW overlap each other, the ULW may have priority over the FAW.

(79) According to various example embodiments, the NAN availability attribute may be an attribute (or information) for setting an FAW to allocate and use radio resources for a NAN operation and/or a non-NAN operation. The NAN availability attribute may include a plurality of fields (e.g., Attribute ID, Length, Sequence ID, Attribute Control, and Availability Entry List). Table 1 shows a format of the NAN availability attribute.

(80) TABLE-US-00001

TABLE 1	Size	Field (octets)	Value	Description
Attribute ID	1	0x12		

Identifies the type of a NAN attribute.	Length	2	Variable	The length in octets of the fields following the length field in the attribute.
Sequence ID	1	Variable		An integer value that identifies the sequence of the advertised availability schedule. It is incremented by one when any schedule change flag in the Attribute Control field is set to 1; otherwise, it remains unchanged.
Attribute Control	2	Variable	Refer to Table 2.	Availability
Availability	Variable	Variable	Including one or more	Availability Entries. The format Entry List of an Availability Entry List is defined in Table 3.

(81) Table 2 shows a format of an Attribute Control field included in the NAN availability attribute. The Attribute Control field may include a plurality of fields (e.g., Map ID, Committed Changed, Potential Changed, Public Availability Attribute Changed, NDC Attribute Changed, Reserved (Multicast Schedule Attribute Changed), Reserved (Multicast Schedule Change Attribute Changed), and Reserved).

(82) TABLE-US-00002

TABLE 2	Size	Field (bits)	Value	Description
Map ID	4	Variable	Identify the associated NAN Availability attribute	
Committed Changed	1	0 or 1	Set to 1 if Committed Availability changed, compared with last schedule advertisement; or any Conditional Availability is included. Set to 0, otherwise. This setting shall be the same for all the maps in a frame	
Potential Changed	1	0 or 1	Set to 1 if Potential Availability changed, compared with last schedule advertisement. Set to 0, otherwise. This setting shall be the same for all the maps in a frame	
Public Availability	1	0 or 1	Set to 1 if Public Availability attribute changed, Attribute Changed compared with last schedule advertisement. Set to 0, otherwise.	
NDC	1	0 or 1	Set to 1 if NDC attribute changed, compared with last Attribute Changed schedule advertisement. Set to 0, otherwise.	
Reserved	1	0 or 1	Set to 1 if Multicast Schedule attribute changed, (Multicast Schedule compared with last schedule advertisement. Attribute Changed) Set to 0, otherwise.	
Reserved	1	0 or 1	Set to 1 if Multicast Schedule Change attribute (Multicast Schedule changed, compared with last schedule advertisement. Change Attribute Changed) Set to 0, otherwise.	
Reserved	6	Variable	Reserved	

(83) Table 3 shows a format of the Availability Entry List field included in the NAN availability attribute. The Availability Entry List field may include a plurality of fields (e.g., Length, Entry Control, Time Bitmap Control, Time Bitmap Length, Time Bitmap, and Band/Channel Entry List).

(84) TABLE-US-00003

TABLE 3	Size	Field (octets)	Value	Description
Length	2	Variable	The length of the fields following the Length field in the attribute, in the number of octets.	
Entry Control	2	Variable	See Table 4 for details.	
Time Bitmap	2	Variable	Indicates the parameters associated with the Control subsequent Time Bitmap field. See Table 5 for details.	
Time Bitmap Length	1	Variable	Indicate the length of the following Time Bitmap Length field, in the number of octets.	
Time Bitmap	Variable	Variable	Each bit in the Time Bitmap corresponds to a time duration indicated by the value of Bit Duration subfield in the Time Bitmap Control field. When the bit is set to 1, the NAN Device indicates its availability for any NAN operations for the whole time duration associated with the bit. When the bit is set to 0, the NAN Device indicates unavailable for any NAN related operations for the time duration associated with the bit.	
Band/Channel	Variable	Variable	The list of one or more Band or Channel Entries corresponding Entry List to this Availability Entry. See Table 6 for details.	

(85) Table 4 shows a format of the Entry Control field included in the Availability Entry List field.

(86) TABLE-US-00004

TABLE 4	Number of Bit(s)	Information	Notes
Availability	b0: 1,	Committed; 0, otherwise;	
Type	b1: 1,	Potential; 0, otherwise.	
	b2: 1,	Conditional; 0, otherwise.	
000, 101, and 111			are reserved. Note - At least one of the three bits is set to 1 to be meaningful.
3-4			Usage An integer ranging from 0 to 3, which represents the Preference preference of being available in the associated FAWs. The preference is higher when the value is set larger. Note: It does not apply to Committed or Conditional FAWs.
5-7			Utilization Values 0-5 indicating proportion within the associated FAWs that are already utilized for other purposes quantized to 20%. Value 6 is reserved. Value 7 indicates unknown utilization.
8-11			Rx Nss Indicate the max number of spatial streams the NAN Device can receive during the associated FAWs.
12	Time 1:	Time Bitmap Control, Time Bitmap Length, and Time Bitmap	Bitmap fields are present
Present 0:		Time Bitmap Control, Time Bitmap Length, and Time Bitmap	are NOT present, and all NAN Slots are available
13-15			Reserved

(87) Table 5 shows a format of the Time Bitmap Control field included in the Availability Entry List field. The Time Bitmap Control field may include a plurality of fields (e.g., Bit Duration, Period, Start Offset, and Reserved). The Bit Duration field may indicate how long a corresponding FAW lasts, and the Period field may indicate a length of a period in which the same FAW starts.

The Start Offset field may indicate an amount of time from DW0 to a start of a corresponding FAW, and may determine a start time of an FAW.

(88) TABLE-US-00005 TABLE 5 Bit(s) Field Notes 0-2 Bit 0: 16 TU Duration 1: 32 TU 2: 64 TU 3: 128 TU 4-7 reserved 3-5 Period Indicate the repeat interval of the following bitmap. When set to 0, the indicated bitmap is not repeated. When set to non-zero, the repeat interval is: 1: 128 TU 2: 256 TU 3: 512 TU 4: 1024 TU 5: 1048 TU 6: 4096 TU 7: 8192 TU 6-14 Start Start Offset is an integer. The time period specified by the Offset Time Bitmap field starts at the 16 * Start Offset TUs after DW0. Note that the NAN Slots not covered by any Time Bitmap are assumed to be NOT available. 15 Reserved Reserved

(89) Table 6 shows a Band/Channel Entries List field included in the Availability Entry List field. The Band/Channel Entries List field may include a plurality of fields (e.g., Type, Non-contiguous Bandwidth, Reserved, Number of Band or Channel Entries, and Band or Channel Entries). The Band or Channel Entries field may include one or more Band Entries and/or one or more Channel Entries.

(90) TABLE-US-00006 TABLE 6 Bit(s) Field Description 0 Type Specifies whether the list refers to a set of indicated bands or a set of operating classes and channel entries. 0: The list is a set of indicated bands. 1: the list is a set of Operating Classes and channel entries 1 Non-contiguous 0: Contiguous bandwidth Bandwidth 1: Non-contiguous bandwidth This field is set to 1 if there is at least one Channel Entry indicates non-contiguous bandwidth. 2-3 Reserved Reserved 4-7 Number of Band The number of band entries or channel entries in the list. or Channel Entries Value 0 is reserved. Variable Band or If the Type value is 0, including one or more Band Entries, as Channel Entries shown FIG. 55 in Neighbor Awareness Networking Technical Specification. The value of each Band Entry is specified by the Table 9-63 Band ID field in IEEE Std. 802.11, which is also quoted in Table 7. If the Type value is 1, including one or more Channel Entries as defined in Table 8.

(91) Table 7 shows a list of Band Entries. The list of Band Entries may be used to determine a frequency band (e.g., 2.4 GHz, 5 GHz, or 6 GHz) to be used in an FAW. For example, when Band IDs are 6 to 255 in the list of Band Entries, an FAW may use a frequency band of 6 GHz.

(92) TABLE-US-00007 TABLE 7 Band ID Meaning 0 Reserved (for TV white spaces) 1 Sub-1 GHz (excluding TV white spaces) 2 2.4 GHz 3 Reserved (for 3.6 GHz) 4 4.9 and 5 GHz 5 Reserved (for 60 GHz) 6-255 Reserved

(93) Table 8 shows a format of a Channel Entry field included in the Band/Channel Entries List field. The Channel Entry field may include a plurality of fields (e.g., Operating Class, Channel Bitmap, Primary Channel Bitmap, and Auxiliary Channel Bitmap). The Channel Entry field may include channel information to be used for an FAW. The Channel Bitmap field may be used to designate a channel corresponding to a specific Operating Class, and the Primary Channel Bitmap field may be used to designate a specific channel.

(94) TABLE-US-00008 TABLE 8 Size Field (octets) Value Description Operating Class 1 Variable Global Operating Class as defined in Table E-4 in Annex E of IEEE Std. 802.11. Channel Bitmap 2 Variable Channels are as defined in Annex E of IEEE Std. 802.11 for the given Operating Class. One or more channels are defined per Operating Class. Bit i of the Channel Bitmap is set to one when the ith Channel, in increasing numerical order, of the possible channels within the Operating Class is selected, and set to zero otherwise. Primary 1 Variable If exactly one bit is set in the Channel Bitmap subfield, Channel Bitmap then this field indicates the set of selected preferred primary channels. It is reserved otherwise. The detailed setting of Primary Channel Bitmap is shown in Table 93 in Neighbor Awareness Networking Technical Specification. For 11ah, this field is a Channel Bitmap extension if the channel bandwidth is 1 MHz. Note: The field is reserved when the Operating Class field indicates a 20 MHz or 40 MHz bandwidth Auxiliary 2 Variable Present only if the Non-contiguous Bandwidth field is Channel Bitmap set to one For an 80 + 80 MHz operating channel width, indicates the channel center frequency index of the 80 MHz channel of

frequency segment 1 on which the device operates. Bit i of the Auxiliary Channel Bitmap is set to one when the ith Channel, in increasing numerical order, of the possible channels within the Operating Class is selected, and set to zero otherwise. When the whole field is set to zero, the field is ignored.

(95) According to various example embodiments, the unaligned schedule attribute may be an attribute (or information) for setting a ULW to allocate and use radio resources for a non-NAN operation. The unaligned schedule attribute may include a plurality of fields (e.g., Attribute ID, Length, Attribute Control, Starting Time, Duration, Period, Count Down, ULW Overwrite, ULW Control, and Band ID or Channel Entry).

(96) Table 9 shows a format of the unaligned schedule attribute, Table 10 shows a format of the Attribute Control field included in the unaligned schedule attribute, and Table 11 shows a format of the ULW Overwrite field included in the unaligned schedule attribute. The Starting Time field may include a point in time at which a ULW starts (e.g., based on 1 TU in the NAN standard). The Duration field may include a time (e.g., in microseconds) for maintaining a ULW. The Period field may include time information regarding a length of a period in which a ULW starts. The Band ID or Channel Entry field may include information (e.g., frequency band information, Operating Class setting, and Primary Channel setting information) described in Tables 7 and 8.

(97) TABLE-US-00009

TABLE 9	Size Field (octets)	Value	Description
Attribute ID	1	0x17	Identifies the type of NAN attribute.
Length	2	Variable	Length of the following fields in the attribute.
Attribute Control	2	Variable	Refer to Table 10.
Starting Time	4	Variable	The starting time of the first indicated ULW expressed in terms of the lower 4 bytes of the NAN TSF
Duration	4	Variable	The duration for each ULW in units of microseconds
Period	4	Variable	The time between consecutive ULWs in units of microseconds
Count Down	1	Variable	Number of indicated ULWs. The value of 255 indicates the ULWs does not end until next schedule update. The value of 0 indicates that the remaining ULWs are cancelled.
ULW Overwrite	1	Variable	See Table 11.
ULW Control	0 or 1	Variable	Optional field, when NOT present, indicating the NAN Device is NOT available on any channel during all ULWs, and all the following fields are not present; when present, see Table 12.
Band ID or Channel Entry	Variable	Variable	If present and the Type value is 00, a Band ID as Channel Entry specified by the Table 9-63 Band ID field in IEEE Std. 802.11, which is also quoted in Table 7. If present, and the Type value is 01 or 10, a Channel Entry as defined in Table 8.

(98) TABLE-US-00010

TABLE 10	Size Field (bits)	Value	Description
Schedule ID	4	Variable	Identify the associated Unaligned Schedule
Reserved	4	Variable	Reserved
Sequence ID	8	Variable	An integer value that identifies the sequence of the Unaligned Schedule. It is incremented by one when the schedule changes to indicate the freshness of the information contained in the corresponding attribute

(99) TABLE-US-00011

TABLE 11	Size Field (bits)	Value	Description
Overwrite	1	Variable	Set to 1 when the unaligned All schedule takes precedence over all NAN Availability attributes; set to 0, otherwise.
Map ID	4	Variable	When Overwrite All flag set to 0, identify the NAN Availability attribute, which the unaligned schedule takes precedence over; reserved otherwise.
Reserved	3	Variable	Reserved

(100) Table 12 shows a format of the ULW Control field included in the unaligned schedule attribute. The ULW Control field may include information on whether a ULW uses a channel or a frequency band. The ULW Control field may include a plurality of fields (e.g., Type, Channel Availability, Rx Nss, and Reserved).

(101) TABLE-US-00012

TABLE 12	Size Field (bits)	Value	Description
Type	2	Variable	00: Followed by a Band ID field 01: Followed by Channel Entry field without Auxiliary Channel 10: Followed by a Channel Entry field with Auxiliary Channel 11: Reserved
Channel	1	Variable	1: Indicate the NAN Device is available during the Availability ULWs on the channel specified in the followed Channel Entry field; and the Channel Entry field only specifies one channel 0: Indicate the NAN Device cannot be available on the band or channels specified in the followed Band ID

field or Channel Entry field Rx Nss 4 Variable Indicate the max number of spatial streams the NAN Device can receive during ULWs, if the Channel Availability subfield is set to 1; otherwise, reserved Reserved 1 Variable Reserved

(102) According to various example embodiments, the NAN availability attribute and the unaligned schedule attribute may configure a schedule for using a NAN operation and a non-NAN operation. The unaligned schedule attribute may be used to configure a schedule for use of a non-NAN operation. If the Channel Availability field included in the ULW Control field of the unaligned schedule attribute is set to “1”, a NAN operation may be performed even within a schedule configured with the unaligned schedule attribute. For example, If NDL schedules (e.g., including an NDP schedule) are generated for each frequency band information, the electronic device **101**, **102**, **103**, or **104** may generate an NDL schedule with only the NAN availability attribute, or an NDL schedule with the NAN availability attribute and the unaligned schedule attribute.

(103) FIG. 5 is a signal flow diagram illustrating an example NDL scheduling operation according to various embodiments.

(104) In FIG. 5, the NDL scheduling operation may include an operation of setting up a data link (e.g., an NDL) for a NAN operation between the electronic device **101** and the external electronic device **102**, and an operation of updating the data link. In FIG. 5, it may be assumed that an electronic device **101** is an NDL schedule initiator and that an external electronic device **102** is an NDL schedule responder.

(105) In operation **510**, the electronic device **101** may transmit a schedule request to the external electronic device **102**. In the schedule request, an NDL Attribute Type (e.g., an NDL Attribute Type subfield) may be set to “(Schedule) Request”. The schedule request may include a schedule proposal (e.g., an NDL Schedule Initial Proposal). The schedule proposal may include one or more availability attributes and/or unaligned schedule attributes.

(106) In operation **520**, the external electronic device **102** may transmit a schedule response to the electronic device **101** in response to the schedule request. In the schedule response, an NDL Attribute Type (e.g., an NDL Attribute Type subfield) may be set to “(Schedule) Response”. The schedule response may include one of “acceptance” (e.g., Accepted), “counter proposal” (or modification proposal) (e.g., Counter), or “rejection” (e.g., Rejected). The “acceptance” may indicate a case in which a schedule proposal is suitable for constructing an NDL schedule. The “rejection” may indicate a case in which the schedule proposal is invalid or in which it is impossible to use the schedule proposal due to a conflict with an NDP schedule proposed by the electronic device **102**. The “counter proposal” may indicate a case of reconstituting the NDP schedule so as to be changed according to the standard through the schedule proposal. In the “counter proposal”, the external electronic device **102** may analyze a schedule intended by the electronic device **101**, modify the schedule according to the intention of the electronic device **101**, and transmit a modification schedule proposal (e.g., an NDL Schedule Counter Proposal) to the electronic device **101** through the schedule response. The modification schedule proposal may include one or more availability attributes and/or unaligned schedule attributes.

(107) In operation **530**, the electronic device **101** may optionally transmit a schedule confirmation (e.g., schedule confirm) based on the schedule response. If the schedule response includes “acceptance” or “rejection”, the electronic device **101** may not transmit the schedule confirmation to the external electronic device **102**. If the schedule response includes “counter proposal” (e.g., if the schedule response includes a modified schedule proposal), the electronic device **101** may transmit the schedule confirmation to the external electronic device **102**. The schedule confirmation may indicate acceptance. In the schedule confirmation, an NDL Attribute Type (e.g., an NDL Attribute Type subfield) may be set to “(Schedule) Confirm”. The schedule confirmation may include an availability attribute included in the modification schedule proposal, an availability attribute identical to an unaligned schedule attribute, and/or an unaligned schedule attribute.

(108) In operation **530**, the electronic devices **101** and **102** may set an NDL according to an NDL

schedule (e.g., a negotiated NDL schedule) and may communicate with each other.

(109) According to various example embodiments, one of management frames such as beacons (e.g., synchronization beacons), SDFs, and NAFs may be used for the schedule request, the schedule response, and the schedule confirmation. An NDL Attribute Type (e.g., an NDL Attribute Type subfield) of a management frame may be set to “(Schedule) Request”, “(Schedule) Response”, or “(Schedule) Confirm” to be used for NDL scheduling.

(110) FIG. 6 is a diagram illustrating an example of an NDL scheduling method by a change in a frequency band according to various embodiments.

(111) Referring to FIG. 6, according to various example embodiments, an electronic device **101** may perform NDL scheduling (e.g., updating, or rescheduling) based on a change in a frequency band due to a termination (e.g., a connection termination) of at least one data link formed in the electronic device **101**. For example, the electronic device **101** may schedule a data link of an external electronic device **102** or **103** that maintains a connection to the electronic device **101**, in response to a change in a frequency band due to a termination of at least one data link among a plurality of data links formed between the electronic device **101** and the external electronic device **102**, **103**. For convenience of description, an operation of the NDL scheduling method based on the change in the frequency band is described based on the electronic device **101**. However, an operation of the electronic device **101** may be substantially identically applied to the external electronic devices **102** and **103**, and operations of the external electronic devices **102** and **103** may be substantially identically applied to the electronic device **101**. Although only two external electronic devices are illustrated in FIG. 6 for convenience of description, various example embodiments are not limited thereto, and substantially the same operations as those described above may be performed even though three or more external electronic devices are connected to the electronic device **101**.

(112) According to various example embodiments, the electronic devices **101** to **103** may be divided into three types (e.g., a first type, a second type, and a third type) according to frequency bands that may be supported (or used) and whether to support a real simultaneous dual band (RSDB). A device of the first type may support frequency bands of 2.4 GHz, 5 GHz, and 6 GHz, and the RSDB. The device of the first type may simultaneously use 2.4 GHz and 5 GHz and simultaneously use 2.4 GHz and 6 GHz, however, it may be difficult to simultaneously use 5 GHz and 6 GHz. A device of the second type may support frequency bands of 2.4 GHz and 5 GHz, and the RSDB. The device of the second type may simultaneously use 2.4 GHz and 5 GHz. A device of the third type may support frequency bands of 2.4 GHz and 5 GHz, and may not support the RSDB. Here, it may be difficult for the device of the third type to simultaneously use 2.4 GHz and 5 GHz, however, the device of the third type may alternately use 2.4 GHz and 5 GHz through time division.

(113) According to various example embodiments, a data link using a frequency band (e.g., 2.4 GHz, 5 GHz, or 6 GHz) may be formed between the electronic devices **101** to **103**. If NAN communication is performed, the electronic devices **101** to **103** may be excellent in performance for scheduling (e.g., forming) of a data link in a priority order of 6 GHz>5 GHz>2.4 GHz based on at least one of performance (e.g., NAN throughput in a NAN terminal) and congestion (e.g., real environment congestion) according to a frequency band.

(114) According to various example embodiments, the electronic device **101** may set a schedule for a first data link **610** that uses a first frequency band (e.g., 2.4 GHz, 5 GHz, or 6 GHz) as a communication protocol (e.g., NAN) with the first external electronic device **102**, and may set a schedule for a second data link **620** that uses a second frequency band (e.g., 2.4 GHz, 5 GHz, or 6 GHz) as a communication protocol (e.g., NAN) with the second external electronic device **103**. A communication protocol may be a communication protocol that supports a NAN communication operation. The first frequency band and the second frequency band may be the same or different.

(115) According to various example embodiments, the electronic device **101** may perform

scheduling to change the second data link **620** to a third data link **630** that uses a third frequency band (e.g., 2.4 GHz, 5 GHz, or 6 GHz) if the third frequency band is available, in response to a termination of the first data link **610** (e.g., a termination of connection to the first external electronic device **102**). The third data link **630** using the third frequency band may be substantially the same as the second data link **620** using the third frequency band. For example, the third data link **630** may be obtained by changing at least one of a channel (or channel information) and bandwidth information other than a frequency band (e.g., the third frequency band) in the second data link **620**. The third frequency band may be different from the second frequency band, and may have a higher priority than that of the second frequency band based on the performance according to the frequency band. The third frequency band may also be the same as the first frequency band. (116) According to various example embodiments, the NDL scheduling according to the termination of the first data link **610** may be performed through exchanging of a schedule request, a schedule response, and/or a schedule confirmation between the electronic device **101** and the second external electronic device **103**. In order to set a schedule for the third data link **630** that is a new data link, the schedule request and the schedule response may include a NAN availability attribute and/or unaligned schedule attribute based on information on an available frequency band (e.g., available frequency band information, and channel information and/or bandwidth information of the available frequency band). If the available frequency band is changed due to the termination of the first data link **610**, the information on the available frequency band (e.g., available frequency band information, and channel information and/or bandwidth information of the available frequency band) may be added to the NAN availability attribute and/or the unaligned schedule attribute. The available frequency band information may be included in the List of Band Entries of the NAN availability attribute and/or unaligned schedule attribute, and the channel information and/or bandwidth information of the available frequency band may be included in a Channel Entry field of the NAN availability attribute and/or the unaligned schedule attribute.

(117) According to various example embodiments, to use an available frequency band as the third frequency band used in the new third data link **630**, available frequency bands may be selected in a priority order of 6 GHz>5 GHz>2.4 GHz from the NAN availability attribute and/or the unaligned schedule attribute included in the schedule request and schedule response. Accordingly, the electronic device **101** may efficiently configure multiple frequency bands by detecting a change in a data link with a neighboring device, and may efficiently use the multiple frequency bands.

(118) FIG. 7 is a flowchart illustrating an example operation of an electronic device to perform NDL scheduling by a change in a frequency band according to various embodiments.

(119) Referring to FIG. 7, according to various example embodiments, the electronic device **101** may support a first communication protocol and a second communication protocol. For example, the first communication protocol may support a communication operation (e.g., Wi-Fi) other than a NAN communication operation, and the second communication protocol may support the NAN communication operation. Operations **710** through **730** may be performed sequentially, but not be necessarily performed sequentially. For example, the order of operations **710** through **730** may be changed, and at least two of operations **710** through **730** may be performed in parallel.

(120) In operation **710**, the electronic device **101** may set a schedule for the first data link **610** that uses the first frequency band as the second communication protocol with the first external electronic device **102**.

(121) In operation **720**, the electronic device **101** may set a schedule for the second data link **620** that uses the second frequency band as the second communication protocol with the second external electronic device **103**.

(122) In operation **730**, the electronic device **101** may change the second data link **620** to the third data link **630** that uses the third frequency band and may perform communication with the second external electronic device **103**, when the third frequency band is available due to the termination of the first data link **610**. The third frequency band may be an available frequency band that has a

higher priority than that of the second frequency band used in the second data link **620** among one or more available frequency bands that may be used by both the electronic device **101** and the second external electronic device **103**.

(123) FIG. **8** is a diagram illustrating an example of an NDL scheduling operation performed based on the NDL scheduling method of FIG. **6** according to various embodiments.

(124) Referring to FIG. **8**, operations **810** through **890** may be performed sequentially, but not be necessarily performed sequentially. For example, the order of operations **810** through **890** may be changed, and at least two of operations **810** through **890** may be performed in parallel.

(125) In operation **810**, the electronic device **101** may set a schedule for the first data link **610** that uses the first frequency band as a communication protocol (e.g., NAN) with the first external electronic device **102**. The first data link **610** may be set between the electronic device **101** and the first external electronic device **102**.

(126) In operation **820**, the electronic device **101** may set a schedule for the second data link **620** that uses the second frequency band as a communication protocol (e.g., NAN) with the second external electronic device **103**. The second data link **620** may be set between the electronic device **101** and the second external electronic device **103**.

(127) In operation **825**, the first data link **610** formed between the electronic device **101** and the first external electronic device **102** may be terminated.

(128) In operation **830**, the electronic device **101** may identify a change in an available frequency band of the electronic device **101**, in response to the termination of the first data link **610** (e.g., a termination of connection to the first external electronic device **102**).

(129) In operation **835**, when the available frequency band is not changed, the second data link **620** set between the electronic device **101** and the second external electronic device **103** may be maintained.

(130) In operation **840**, when the available frequency band is changed, the electronic device **101** may transmit a schedule request (e.g., SCHEDULE REQUEST) including information on an available frequency band (e.g., frequency bands that may be used by the electronic device **101** due to the termination of the first data link **610**) of the electronic device **101** to the second external electronic device **103**, to effectively set (or reset) a data link between the electronic device **101** and the second external electronic device **103**.

(131) In operation **850**, the second external electronic device **103** may receive the schedule request, and may select at least one available frequency band that may be concurrently used by both the second external electronic device **103** and the electronic device **101**, based on the information on the available frequency band of the electronic device **101** included in the schedule request.

(132) In operation **860**, the second external electronic device **103** may compare a priority of at least one available frequency band to a priority of the second frequency band of the second data link **620** and may determine whether a frequency band having a higher priority than that of the second frequency band is present.

(133) In operation **870**, when the available frequency band having the higher priority than that of the second frequency band is absent, the second data link **620** set between the electronic device **101** and the second external electronic device **103** may be maintained. Here, the second external electronic device **103** may or may not transmit a schedule response (e.g., SCHEDULE RESPONSE) including “rejection” (e.g., Rejected) to the electronic device **101**.

(134) In operation **880**, when the available frequency band having the higher priority than that of the second frequency band is present, the second external electronic device **103** may transmit a schedule response (e.g., SCHEDULE RESPONSE) including information on the available frequency band (e.g., available frequency band information, and channel information and/or bandwidth information of the available frequency band) to the electronic device **101**.

(135) In operation **890**, the electronic device **101** and the second external electronic device **103** may change the second data link **620** to the third data link **630** that uses an available frequency

band (e.g., a third frequency band) and may perform communication (e.g., NAN communication).

(136) FIG. 9 is a diagram illustrating an example of an NDL scheduling operation performed based on the NDL scheduling method of FIG. 6 according to various embodiments.

(137) Referring to FIG. 9, operations 910 through 975 may be performed sequentially, but not be necessarily performed sequentially. For example, the order of operations 910 through 975 may be changed, and at least two of operations 910 through 975 may be performed in parallel.

(138) In operation 910, the electronic device 101 may set a schedule for the first data link 610 that uses the first frequency band as a communication protocol (e.g., NAN) with the first external electronic device 102. The first data link 610 may be set between the electronic device 101 and the first external electronic device 102.

(139) In operation 913, the electronic device 101 may set a schedule for the second data link 620 that uses the second frequency band as a communication protocol (e.g., NAN) with the second external electronic device 103. The second data link 620 may be set between the electronic device 101 and the second external electronic device 103.

(140) In operation 915, the first data link 610 formed between the electronic device 101 and the first external electronic device 102 may be terminated.

(141) In operation 920, the electronic device 101 may obtain information on an available frequency band (e.g., frequency bands that may be used by the second external electronic device 103 due to the termination of the first data link 610) of the second external electronic device 103 from the second external electronic device 103. The second external electronic device 103 may broadcast at least one of a beacon and a NAF to a neighboring device in real time. For example, the second external electronic device 103 may include information on an available frequency band in at least one of the beacon and the NAF and may transmit at least one of the beacon and the NAF including the information to the electronic device 101. The second external electronic device 103 may broadcast at least one of the beacon and the NAF in real time regardless of the termination of the first data link 610. The electronic device 101 may receive the beacon and/or NAF from the second external electronic device 103 at a point in time at which the first data link 610 is terminated.

(142) In operation 923, the electronic device 101 may compare a frequency band (e.g., frequency bands that may be used by the electronic device 101 due to the termination of the first data link 610) that may be used by the electronic device 101 and a frequency band that may be used by the second external electronic device 103, based on the information on the available frequency band of the second external electronic device 103. The electronic device 101 may select at least one available frequency band that may be concurrently used by both the electronic device 101 and the second external electronic device 103.

(143) In operation 925, the electronic device 101 may compare a priority of at least one available frequency band and a priority of the second frequency band of the second data link 620 and may determine whether a frequency band having a higher priority than that of the second frequency band is present.

(144) In operation 930, when the available frequency band having the higher priority than that of the second frequency band is absent, the second data link 620 set between the electronic device 101 and the second external electronic device 103 may be maintained.

(145) In operation 935, when an available frequency band (e.g., a first available frequency band) having a higher priority than that of the second frequency band is present, the electronic device 101 may transmit a schedule request (e.g., SCHEDULE REQUEST) including information on a first available frequency band (e.g., first available frequency band information, and channel information and/or bandwidth information of the first available frequency band) to the second external electronic device 103.

(146) In operation 940, the second external electronic device 103 may receive the schedule request from the electronic device 101, and may determine whether setting of a new data link using the first available frequency band received from the electronic device 101 is most appropriate.

(147) In operation **945**, when the setting of the new data link using the first available frequency band received from the electronic device **101** is most appropriate, the second external electronic device **103** may transmit a schedule response (e.g., SCHEDULE RESPONSE) including the information on the first available frequency band (e.g., first available frequency band information, and channel information and/or bandwidth information of the first available frequency band) to the electronic device **101**.

(148) In operation **950**, the electronic device **101** and the second external electronic device **103** may change the second data link **620** to the third data link **630** that uses the first available frequency band (e.g., a third frequency band) and may perform communication (e.g., NAN communication).

(149) In operation **955**, when the setting of the new data link using the first available frequency band received from the electronic device **101** is not most appropriate, the second external electronic device **103** may determine whether a second available frequency band having a higher priority (or a highest priority) than that of the second frequency band of the second data link **620** is present.

(150) In operation **960**, when the second available frequency band having the higher priority than that of the second frequency band of the second data link **620** is absent, the second data link **620** set between the electronic device **101** and the second external electronic device **103** may be maintained. Here, the second external electronic device **103** may or may not transmit a schedule response (e.g., SCHEDULE RESPONSE) including “rejection” (e.g., Rejected) to the electronic device **101**.

(151) In operation **965**, when the second available frequency band having the higher priority than that of the second frequency band of the second data link **620** is present, the second external electronic device **103** may transmit a schedule response including a modification schedule proposal to set the third data link **630** using the second available frequency band to the electronic device **101**.

(152) In operation **970**, the electronic device **101** may transmit a schedule confirmation (e.g., SCHEDULE CONFIRM) to the second external electronic device **103**, in response to the schedule response. The schedule confirmation may include information on the second available frequency band (e.g., second available frequency band information, and channel information and/or bandwidth information of the second available frequency band), or “rejection” (e.g., Rejected).

(153) In operation **975**, when the schedule confirmation includes the information on the second available frequency band (e.g., second available frequency band information, and channel information and/or bandwidth information of the second available frequency band), the electronic device **101** and the second external electronic device **103** may change the second data link **620** to the third data link **630** that uses the second available frequency band (e.g., a third frequency band) and may perform communication (e.g., NAN communication). When the schedule confirmation includes “rejection” (e.g., Rejected), the second data link **620** set between the electronic device **101** and the second external electronic device **103** may be maintained.

(154) FIG. **10** is a diagram illustrating an example of an NDL scheduling operation performed based on the NDL scheduling method of FIG. **6** according to various embodiments.

(155) Referring to FIG. **10**, operations **1010** through **1075** may be performed sequentially, but not be necessarily performed sequentially. For example, the order of operations **1010** through **1075** may be changed, and at least two of operations **1010** through **1075** may be performed in parallel.

(156) In operation **1010**, the electronic device **101** may set a schedule for the first data link **610** that uses the first frequency band as a communication protocol (e.g., NAN) with the first external electronic device **102**. The first data link **610** may be set between the electronic device **101** and the first external electronic device **102**.

(157) In operation **1013**, the electronic device **101** may set a schedule for the second data link **620** that uses the second frequency band as a communication protocol (e.g., NAN) with the second external electronic device **103**. The second data link **620** may be set between the electronic device

101 and the second external electronic device **103**.

(158) In operation **1015**, the first data link **610** formed between the electronic device **101** and the first external electronic device **102** may be terminated.

(159) In operation **1020**, the electronic device **101** may transmit information on an available frequency band (e.g., frequency bands that may be used by the electronic device **101** due to the termination of the first data link **610**) of the electronic device **101** to the second external electronic device **103**, in response to the termination of the first data link **610**. The electronic device **101** may include the information on the available frequency band in at least one of a beacon and a NAF and may transmit at least one of the beacon and the NAF including the information to the second external electronic device **103**.

(160) In operation **1023**, the second external electronic device **103** may compare a frequency band (e.g., frequency bands that may be used by the second external electronic device **103** due to the termination of the first data link **610**) that may be used by the second external electronic device **103** and a frequency band that may be used by the electronic device **101**, based on the information on the available frequency band of the electronic device **101**. The second external electronic device **103** may select at least one available frequency band that may be concurrently used by both the second external electronic device **103** and the electronic device **101**.

(161) In operation **1025**, the second external electronic device **103** may compare a priority of at least one available frequency band to a priority of the second frequency band of the second data link **620** and may determine whether an available frequency band having a higher priority than that of the second frequency band is present.

(162) In operation **1030**, when the available frequency band having the higher priority than that of the second frequency band is absent, the second data link **620** set between the electronic device **101** and the second external electronic device **103** may be maintained.

(163) In operation **1035**, when an available frequency band (e.g., a first available frequency band) having a higher priority than that of the second frequency band is present, the second external electronic device **103** may transmit a schedule request (e.g., SCHEDULE REQUEST) including information on a first available frequency band (e.g., first available frequency band information, and channel information and/or bandwidth information of the first available frequency band) to the electronic device **101**.

(164) In operation **1040**, the electronic device **101** may receive the schedule request from the second external electronic device **103**, and may determine whether setting of a new data link using the first available frequency band received from the second external electronic device **103** is most appropriate.

(165) In operation **1045**, when the setting of the new data link using the first available frequency band received from the second external electronic device **103** is most appropriate, the electronic device **101** may transmit a schedule response (e.g., SCHEDULE RESPONSE) including the information on the first available frequency band (e.g., first available frequency band information, and channel information and/or bandwidth information of the first available frequency band) to the second external electronic device **103**.

(166) In operation **1050**, the electronic device **101** and the second external electronic device **103** may change the second data link **620** to the third data link **630** that uses the first available frequency band (e.g., a third frequency band) and may perform communication (e.g., NAN communication).

(167) In operation **1055**, when the setting of the new data link using the first available frequency band received from the second external electronic device **103** is not most appropriate, the electronic device **101** may determine whether a second available frequency band having a higher priority (or highest priority) than that of the second frequency band of the second data link **620** is present.

(168) In operation **1060**, when the second available frequency band having the higher priority than that of the second frequency band of the second data link **620** is absent, the second data link **620** set

between the electronic device **101** and the second external electronic device **103** may be maintained. Here, the electronic device **101** may or may not transmit a schedule response (e.g., SCHEDULE RESPONSE) including “rejection” (e.g., Rejected) to the second external electronic device **103**.

(169) In operation **1065**, when the second available frequency band having the higher priority than that of the second frequency band of the second data link **620** is present, the electronic device **101** may transmit a schedule response including a modification schedule proposal to set the third data link **630** using the second available frequency band to the second external electronic device **103**.

(170) In operation **1070**, the second external electronic device **103** may transmit a schedule confirmation (e.g., SCHEDULE CONFIRM) to the electronic device **101**, in response to the schedule response. The schedule confirmation may include information on the second available frequency band (e.g., second available frequency band information, and channel information and/or bandwidth information of the second available frequency band), or “rejection” (e.g., Rejected).

(171) In operation **1075**, when the schedule confirmation includes the information on the second available frequency band (e.g., second available frequency band information, and channel information and/or bandwidth information of the second available frequency band), the electronic device **101** and the second external electronic device **103** may change the second data link **620** to the third data link **630** that uses the second available frequency band (e.g., a third frequency band) and may perform communication (e.g., NAN communication). When the schedule confirmation includes “rejection” (e.g., Rejected), the second data link **620** set between the electronic device **101** and the second external electronic device **103** may be maintained.

(172) Hereinafter, examples of scheduling operations of FIGS. **8**, **9** and **10** will be described with reference to FIGS. **11A**, **11B**, **11C**, **11D**, **12A**, **12B**, **12C**, **12D**, **13A**, **13B**, **13C**, **13D**, **14A**, **14B**, **14C** and **14D** (which may be referred to as FIGS. **11A** to **14D**). Referring to FIGS. **11A** to **14D**, for convenience of description, priority levels based on performance (e.g., NAN throughput in a NAN terminal) according to frequency bands may be assumed to be in the order of 6 GHz (e.g., 1600 Mbps)>5 GHz (e.g., 900 Mbps)>2.4 GHz (e.g., 150 Mbps).

(173) FIG. **11A** is a diagram illustrating an example in which a scheduling operation of FIG. **8** is performed according to various embodiments.

(174) In FIG. **11A**, it may be assumed that the electronic device **101** and the first external electronic device **102** are devices of the first type (e.g., devices for supporting frequency bands of 2.4 GHz, 5 GHz, and 6 GHz, and supporting an RSDB) and that the second external electronic device **103** is a device of the second type (e.g., a device for supporting frequency bands of 2.4 GHz and 5 GHz, and supporting an RSDB).

(175) In operation **1101**, a first data link (e.g., NDL 6 GHz CH 101) using a frequency band (e.g., 6 GHz) as a communication protocol (e.g., NAN) may be set between the electronic device **101** and the first external electronic device **102**, and a second data link (e.g., NDL 2.4 GHz CH 6) using a frequency band (e.g., 2.4 GHz) as a communication protocol (e.g., NAN) may be set between the electronic device **101** and the second external electronic device **103**.

(176) When the first data link (e.g., NDL 6 GHz CH 101) between the electronic device **101** and the first external electronic device **102** is terminated, the electronic device **101** may determine that an available frequency band of the electronic device **101** is changed from 6 GHz+2.4 GHz to 6 GHz+5 GHz+2.4 GHz in operation **1102**.

(177) In operation **1103**, the electronic device **101** may transmit a schedule request (e.g., SCHEDULE REQUEST) including available frequency band information (e.g., 6 GHz, 5 GHz, and 2.4 GHz) to the second external electronic device **103**. A frequency band of the second data link (e.g., NDL 2.4 GHz CH 6) of the second external electronic device **103** may be 2.4 GHz, and the second external electronic device **103**, which is the device of the second type, may use frequency bands of 5 GHz and 2.4 GHz. The second external electronic device **103** may select at least one available frequency band (e.g., 5 GHz, and 2.4 GHz) that may be used by both the electronic device

101 and the second external electronic device **103**, based on the available frequency band information (e.g., 6 GHz, 5 GHz, and 2.4 GHz) included in the schedule request received from the electronic device **101**. An available frequency band (e.g., 5 GHz) having a higher priority than 2.4 GHz that is the frequency band of the second data link (e.g., NDL 2.4 GHz CH 6) of the second external electronic device **103** may be used, and accordingly the second external electronic device **103** may select a channel (e.g., CH 149) that may be used by both the electronic device **101** and the second external electronic device **103** in the available frequency band (e.g., 5 GHz) and may transmit a schedule response (e.g., SCHEDULE RESPONSE) including the available frequency band (e.g., 5 GHz) and the channel (e.g., CH 149) (e.g., channel information and/or bandwidth information) of the available frequency band (e.g., 5 GHz) to the electronic device **101**.

(178) In operation **1104**, the electronic device **101** and the second external electronic device **103** may change the second data link (e.g., NDL 2.4 GHz CH 6) to a third data link (e.g., NDL 5 GHz CH 149) that uses the channel (e.g., CH 149) of the available frequency band (e.g., 5 GHz), and may perform communication.

(179) FIG. **11B** is a diagram illustrating an example in which a scheduling operation of FIG. **9** is performed according to various embodiments.

(180) In FIG. **11B**, it may be assumed that the electronic device **101** and the first external electronic device **102** are devices of the first type (e.g., devices for supporting frequency bands of 2.4 GHz, 5 GHz, and 6 GHz, and supporting an RSDB) and that the second external electronic device **103** is a device of the second type (e.g., a device for supporting frequency bands of 2.4 GHz and 5 GHz, and supporting an RSDB).

(181) In operation **1111**, a first data link (e.g., NDL 6 GHz CH 101) using a frequency band (e.g., 6 GHz) as a communication protocol (e.g., NAN) may be set between the electronic device **101** and the first external electronic device **102**, and a second data link (e.g., NDL 2.4 GHz CH 6) using a frequency band (e.g., 2.4 GHz) as a communication protocol (e.g., NAN) may be set between the electronic device **101** and the second external electronic device **103**.

(182) In operation **1112**, the first data link (e.g., NDL 6 GHz CH 101) between the electronic device **101** and the first external electronic device **102** may be terminated.

(183) In operation **1113**, the electronic device **101** may receive a beacon (e.g., a synchronization beacon) or NAF including available frequency band information (e.g., 5 GHz, and 2.4 GHz) of the second external electronic device **103** from the second external electronic device **103**.

(184) In operation **1114**, the electronic device **101** may identify at least one available frequency band (e.g., 5 GHz, and 2.4 GHz) that may be used by both the electronic device **101** and the second external electronic device **103** among available frequency bands (e.g., 5 GHz, and 2.4 GHz) of the second external electronic device **103** and available frequency bands (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the electronic device **101**. The electronic device **101** may compare the frequency band (e.g., 2.4 GHz) of the second data link (e.g., NDL 2.4 GHz CH 6) to an available frequency band (e.g., 5 GHz, and 2.4 GHz) that may be newly used between the electronic device **101** and the second external electronic device **103** according to priorities. An available frequency band (e.g., 5 GHz) having a higher priority than that of 2.4 GHz that is the frequency band of the second data link (e.g., NDL 2.4 GHz CH 6) may be used, and accordingly the electronic device **101** may transmit a schedule request (e.g., SCHEDULE REQUEST) including a new available frequency band (e.g., 5 GHz) and/or a channel (e.g., CH 149) (e.g., channel information and/or bandwidth information) of the available frequency band (e.g., 5 GHz) to the second external electronic device **103** in order to use the new available frequency band (e.g., 5 GHz). The second external electronic device **103** may identify the new available frequency band (e.g., 5 GHz) and the channel (e.g., CH 149) of the available frequency band (e.g., 5 GHz) included in the schedule request received from the electronic device **101**, and may transmit a schedule response (e.g., SCHEDULE RESPONSE), which includes set information on the available frequency band (e.g., 5 GHz) and/or the channel (e.g., CH 149) (e.g., channel information and/or bandwidth information) to set a frequency band of

a new data link, to the electronic device **101**.

(185) In operation **1115**, the electronic device **101** and the second external electronic device **103** may change the second data link (e.g., NDL 2.4 GHz CH 6) to a third data link (e.g., NDL 5 GHz CH 149) that uses the channel (e.g., CH 149) of the available frequency band (e.g., 5 GHz), and may perform communication.

(186) FIG. **11C** is a diagram illustrating an example in which a scheduling operation of FIG. **10** is performed according to various embodiments.

(187) In FIG. **11C**, it may be assumed that the electronic device **101** and the first external electronic device **102** are devices of the first type (e.g., devices for supporting frequency bands of 2.4 GHz, 5 GHz, and 6 GHz, and supporting an RSDB) and that the second external electronic device **103** is a device of the second type (e.g., a device for supporting frequency bands of 2.4 GHz and 5 GHz, and supporting an RSDB).

(188) In operation **1121**, a first data link (e.g., NDL 6 GHz CH 101) using a frequency band (e.g., 6 GHz) as a communication protocol (e.g., NAN) may be set between the electronic device **101** and the first external electronic device **102**, and a second data link (e.g., NDL 2.4 GHz CH 6) using a frequency band (e.g., 2.4 GHz) as a communication protocol (e.g., NAN) may be set between the electronic device **101** and the second external electronic device **103**.

(189) In operation **1122**, the first data link (e.g., NDL 6 GHz CH 101) between the electronic device **101** and the first external electronic device **102** may be terminated.

(190) In operation **1123**, the electronic device **101** may transmit a beacon (e.g., a synchronization beacon) or NAF including available frequency band information (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the electronic device **101** to the second external electronic device **103**.

(191) In operation **1124**, the second external electronic device **103** may identify at least one available frequency band (e.g., 5 GHz, and 2.4 GHz) that may be used by both the electronic device **101** and the second external electronic device **103** among available frequency bands (e.g., 5 GHz, and 2.4 GHz) of the second external electronic device **103** and available frequency bands (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the electronic device **101**. The second external electronic device **103** may compare the frequency band (e.g., 2.4 GHz) of the second data link (e.g., NDL 2.4 GHz CH 6) to an available frequency band (e.g., 5 GHz, and 2.4 GHz) that may be newly used between the electronic device **101** and the second external electronic device **103** according to priorities. An available frequency band (e.g., 5 GHz) having a higher priority than that of 2.4 GHz that is the frequency band of the second data link (e.g., NDL 2.4 GHz CH 6) may be used, and accordingly the second external electronic device **103** may transmit a schedule request (e.g., SCHEDULE REQUEST) including a new available frequency band (e.g., 5 GHz) and/or a channel (e.g., CH 149) (e.g., channel information and/or bandwidth information) of the available frequency band (e.g., 5 GHz) to the electronic device **101** in order to use the new available frequency band (e.g., 5 GHz). The electronic device **101** may identify the new available frequency band (e.g., 5 GHz) and/or the channel (e.g., CH 149) of the available frequency band (e.g., 5 GHz) included in the schedule request received from the second external electronic device **103**, and may transmit a schedule response (e.g., SCHEDULE RESPONSE), which includes set information on the available frequency band (e.g., 5 GHz) and/or the channel (e.g., CH 149) (e.g., channel information and/or bandwidth information) to set a frequency band of a new data link, to the second external electronic device **103**.

(192) In operation **1125**, the electronic device **101** and the second external electronic device **103** may change the second data link (e.g., NDL 2.4 GHz CH 6) to a third data link (e.g., NDL 5 GHz CH 149) that uses the channel (e.g., CH 149) of the available frequency band (e.g., 5 GHz), and may perform communication.

(193) FIG. **11D** is a diagram illustrating slots of newly set data links of FIGS. **11A**, **11B** and **11C** according to various embodiments.

(194) FIG. **11D** illustrates a slot of a data link finally formed between the electronic device **101** and

the second external electronic device **103** in FIGS. **11A** to **11C**.

(195) Referring to FIG. **11D**, the electronic device **101**, which is a device of the first type, may support all of NAN 6 GHz, NAN 5 GHz, and NAN 2.4 GHz, and the second external electronic device **103**, which is a device of the second type, may support NAN 5 GHz and NAN 2.4 GHz. Both the electronic device **101** and the second external electronic device **103** may support NAN 5 GHz and NAN 2.4 GHz. NAN 5 GHz may be superior in performance to NAN 2.4 GHz among frequency bands that may be supported by both the electronic device **101** and the second external electronic device **103**, and accordingly NAN 5 GHz may have a higher priority than that of NAN 2.4 GHz. Thus, a new scheduling operation may be performed between the electronic device **101** and the second external electronic device **103** so that a data link may be formed between the electronic device **101** and the second external electronic device **103** using a NAN 5 GHz frequency band and may be used. As shown in FIG. **11D**, the data link between the electronic device **101** and the second external electronic device **103** may be formed as NAN 5 GHz Band CH 149, and actually measured performance of NAN 5 GHz Band CH 149 may be about 900 Mbps.

(196) FIG. **12A** is a diagram illustrating an example in which the scheduling operation of FIG. **8** is performed according to various embodiments.

(197) In FIG. **12A**, it may be assumed that the electronic device **101** and the second external electronic device **103** are devices of the first type (e.g., devices for supporting frequency bands of 2.4 GHz, 5 GHz, and 6 GHz, and supporting an RSDB) and that the first external electronic device **102** is a device of the second type (e.g., a device for supporting frequency bands of 2.4 GHz and 5 GHz, and supporting an RSDB).

(198) In operation **1201**, a first data link (e.g., NDL 5 GHz CH 149) using a frequency band (e.g., 5 GHz) as a communication protocol (e.g., NAN) may be set between the electronic device **101** and the first external electronic device **102**, and a second data link (e.g., NDL 5 GHz CH 149) using a frequency band (e.g., 5 GHz) as a communication protocol (e.g., NAN) may be set between the electronic device **101** and the second external electronic device **103**.

(199) When the first data link (e.g., NDL 5 GHz CH 149) between the electronic device **101** and the first external electronic device **102** is terminated, the electronic device **101** may determine that an available frequency band of the electronic device **101** is changed from 5 GHz+2.4 GHz to 6 GHz+5 GHz+2.4 GHz in operation **1202**.

(200) In operation **1203**, the electronic device **101** may transmit a schedule request (e.g., SCHEDULE REQUEST) including available frequency band information (e.g., 6 GHz, 5 GHz, and 2.4 GHz) to the second external electronic device **103**. A frequency band of the second data link (e.g., NDL 5 GHz CH 149) of the second external electronic device **103** may be 5 GHz, and the second external electronic device **103**, which is the device of the first type, may use frequency bands of 6 GHz, 5 GHz, and 2.4 GHz. The second external electronic device **103** may select at least one available frequency band (e.g., 6 GHz, 5 GHz, and 2.4 GHz) that may be used by both the electronic device **101** and the second external electronic device **103**, based on the available frequency band information (e.g., 6 GHz, 5 GHz, and 2.4 GHz) included in the schedule request received from the electronic device **101**. An available frequency band (e.g., 6 GHz) having a higher priority than that of 5 GHz that is the frequency band of the second data link (e.g., NDL 5 GHz CH 149) of the second external electronic device **103** may be used, and accordingly the second external electronic device **103** may select a channel (e.g., CH 101) that may be used by both the electronic device **101** and the second external electronic device **103** in the available frequency band (e.g., 6 GHz) and may transmit a schedule response (e.g., SCHEDULE RESPONSE) including information on the available frequency band (e.g., 6 GHz) and the channel (e.g., CH 101) (e.g., channel information and/or bandwidth information) of the available frequency band (e.g., 6 GHz) to the electronic device **101**.

(201) In operation **1204**, the electronic device **101** and the second external electronic device **103** may change the second data link (e.g., NDL 5 GHz CH 149) to a third data link (e.g., NDL 6 GHz

CH 101) that uses the channel (e.g., CH 101) of the available frequency band (e.g., 6 GHz), and may perform communication.

(202) FIG. 12B is a diagram illustrating an example in which the scheduling operation of FIG. 9 is performed according to various embodiments.

(203) In FIG. 12B, it may be assumed that the electronic device 101 and the second external electronic device 103 are devices of the first type (e.g., devices for supporting frequency bands of 2.4 GHz, 5 GHz, and 6 GHz, and supporting an RSDB) and that the first external electronic device 102 is a device of the second type (e.g., a device for supporting frequency bands of 2.4 GHz and 5 GHz, and supporting an RSDB).

(204) In operation 1211, a first data link (e.g., NDL 5 GHz CH 149) using a frequency band (e.g., 5 GHz) as a communication protocol (e.g., NAN) may be set between the electronic device 101 and the first external electronic device 102, and a second data link (e.g., NDL 5 GHz CH 149) using a frequency band (e.g., 5 GHz) as a communication protocol (e.g., NAN) may be set between the electronic device 101 and the second external electronic device 103.

(205) In operation 1212, the first data link (e.g., NDL 5 GHz CH 149) between the electronic device 101 and the first external electronic device 102 may be terminated.

(206) In operation 1213, the electronic device 101 may receive a beacon (e.g., a synchronization beacon) or NAF including available frequency band information (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the second external electronic device 103 from the second external electronic device 103.

(207) In operation 1214, the electronic device 101 may identify at least one available frequency band (e.g., 6 GHz, 5 GHz, and 2.4 GHz) that may be used by both the electronic device 101 and the second external electronic device 103 among available frequency bands (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the second external electronic device 103 and available frequency bands (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the electronic device 101. The electronic device 101 may compare the frequency band (e.g., 5 GHz) of the second data link (e.g., NDL 5 GHz CH 149) to an available frequency band (e.g., 6 GHz, 5 GHz, and 2.4 GHz) that may be newly used between the electronic device 101 and the second external electronic device 103 according to priorities. An available frequency band (e.g., 6 GHz) having a higher priority than that of 5 GHz that is the frequency band of the second data link (e.g., NDL 5 GHz CH 149) may be used, and accordingly the electronic device 101 may transmit a schedule request (e.g., SCHEDULE REQUEST) including a new available frequency band (e.g., 6 GHz) and/or a channel (e.g., CH 101) (e.g., channel information and/or bandwidth information) of the available frequency band (e.g., 6 GHz) to the second external electronic device 103 in order to use the new available frequency band (e.g., 6 GHz). The second external electronic device 103 may identify the new available frequency band (e.g., 6 GHz) and/or the channel (e.g., CH 101) of the available frequency band (e.g., 6 GHz) included in the schedule request received from the electronic device 101, and may transmit a schedule response (e.g., SCHEDULE RESPONSE), which includes set information on the available frequency band (e.g., 6 GHz) and/or the channel (e.g., CH 101) (e.g., channel information and/or bandwidth information) to set a frequency band of a new data link, to the electronic device 101.

(208) In operation 1215, the electronic device 101 and the second external electronic device 103 may change the second data link (e.g., NDL 5 GHz CH 149) to a third data link (e.g., NDL 6 GHz CH 101) that uses the channel (e.g., CH 101) of the available frequency band (e.g., 6 GHz), and may perform communication.

(209) FIG. 12C is a diagram illustrating an example in which the scheduling operation of FIG. 10 is performed according to various embodiments.

(210) In FIG. 12C, it may be assumed that the electronic device 101 and the second external electronic device 103 are devices of the first type (e.g., devices for supporting frequency bands of 2.4 GHz, 5 GHz, and 6 GHz, and supporting an RSDB) and that the first external electronic device 102 is a device of the second type (e.g., a device for supporting frequency bands of 2.4 GHz and 5 GHz, and supporting an RSDB).

(211) In operation **1221**, a first data link (e.g., NDL 5 GHz CH 149) using a frequency band (e.g., 5 GHz) as a communication protocol (e.g., NAN) may be set between the electronic device **101** and the first external electronic device **102**, and a second data link (e.g., NDL 5 GHz CH 149) using a frequency band (e.g., 5 GHz) as a communication protocol (e.g., NAN) may be set between the electronic device **101** and the second external electronic device **103**.

(212) In operation **1222**, the first data link (e.g., NDL 5 GHz CH 149) between the electronic device **101** and the first external electronic device **102** may be terminated.

(213) In operation **1223**, the electronic device **101** may transmit a beacon (e.g., a synchronization beacon) or NAF including available frequency band information (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the electronic device **101** to the second external electronic device **103**.

(214) In operation **1224**, the second external electronic device **103** may identify at least one available frequency band (e.g., 6 GHz, 5 GHz, and 2.4 GHz) that may be used by both the electronic device **101** and the second external electronic device **103** among available frequency bands (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the second external electronic device **103** and available frequency bands (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the electronic device **101**. The second external electronic device **103** may compare the frequency band (e.g., 5 GHz) of the second data link (e.g., NDL 5 GHz CH 149) to an available frequency band (e.g., 6 GHz, 5 GHz, and 2.4 GHz) that may be newly used between the electronic device **101** and the second external electronic device **103** according to priorities. An available frequency band (e.g., 6 GHz) having a higher priority than that of 5 GHz that is the frequency band of the second data link (e.g., NDL 5 GHz CH 149) may be used, and accordingly the second external electronic device **103** may transmit a schedule request (e.g., SCHEDULE REQUEST) including a new available frequency band (e.g., 6 GHz) and/or a channel (e.g., CH 101) (e.g., channel information and/or bandwidth information) of the available frequency band (e.g., 6 GHz) to the electronic device **101** in order to use the new available frequency band (e.g., 6 GHz). The electronic device **101** may identify the new available frequency band (e.g., 6 GHz) and/or the channel (e.g., CH 101) of the available frequency band (e.g., 6 GHz) included in the schedule request received from the second external electronic device **103**, and may transmit a schedule response (e.g., SCHEDULE RESPONSE), which includes set information on the available frequency band (e.g., 6 GHz) and/or the channel (e.g., CH 101) (e.g., channel information and/or bandwidth information) to set a frequency band of a new data link, to the second external electronic device **103**.

(215) In operation **1225**, the electronic device **101** and the second external electronic device **103** may change the second data link (e.g., NDL 5 GHz CH 149) to a third data link (e.g., NDL 6 GHz CH 101) that uses the channel (e.g., CH 101) of the available frequency band (e.g., 6 GHz), and may perform communication.

(216) FIG. **12D** is a diagram illustrating slots of newly set data links of FIGS. **12A**, **12B** and **12C** according to various embodiments.

(217) FIG. **12D** illustrates a slot of a data link finally formed between the electronic device **101** and the second external electronic device **103** in FIGS. **12A** to **12C**.

(218) Referring to FIG. **12D**, the electronic device **101** and the second external electronic device **103**, which are devices of the first type, may support all of NAN 6 GHz, NAN 5 GHz, and NAN 2.4 GHz. In other words, both the electronic device **101** and the second external electronic device **103** may support NAN 6 GHz, NAN 5 GHz, and NAN 2.4 GHz. Among frequency bands that may be supported by both the electronic device **101** and the second external electronic device **103**, NAN 6 GHz may be superior in performance to NAN 5 GHz, and NAN 5 GHz may be superior in performance to NAN 2.4 GHz. Accordingly, NAN 6 GHz may have a highest priority. Thus, a new scheduling operation may be performed between the electronic device **101** and the second external electronic device **103** so that a data link may be formed between the electronic device **101** and the second external electronic device **103** using a NAN 6 GHz frequency band and may be used. As shown in FIG. **12D**, the data link between the electronic device **101** and the second external

electronic device **103** may be formed as the NAN 6 GHz Band CH 101, and actually measured performance of the NAN 6 GHz Band CH 101 may be about 1600 Mbps.

(219) FIG. **13A** is a diagram illustrating an example in which the scheduling operation of FIG. **8** is performed according to various embodiments.

(220) In FIG. **13A**, it may be assumed that the electronic device **101** and the first external electronic device **102** are devices of the first type (e.g., devices for supporting frequency bands of 2.4 GHz, 5 GHz, and 6 GHz, and supporting an RSDB) and that the second external electronic device **103** and the third external electronic device **104** are devices of the second type (e.g., a device for supporting frequency bands of 2.4 GHz and 5 GHz, and supporting an RSDB).

(221) In operation **1301**, a first data link (e.g., NDL 6 GHz CH 101) using a frequency band (e.g., 6 GHz) as a communication protocol (e.g., NAN) may be set between the electronic device **101** and the first external electronic device **102**, and a second data link (e.g., NDL 2.4 GHz CH 6) using a frequency band (e.g., 2.4 GHz) as a communication protocol (e.g., NAN) may be set between the electronic device **101** and the second external electronic device **103**. A third data link (e.g., NDL 2.4 GHz CH 6) using a frequency band (e.g., 2.4 GHz) as a communication protocol (e.g., NAN) may be set between the electronic device **101** and the third external electronic device **104**.

(222) When the first data link (e.g., NDL 6 GHz CH 101) between the electronic device **101** and the first external electronic device **102** is terminated, the electronic device **101** may determine that an available frequency band of the electronic device **101** is changed from 6 GHz+2.4 GHz to 6 GHz+5 GHz+2.4 GHz in operation **1302**.

(223) In operation **1303**, the electronic device **101** may transmit a schedule request (e.g., SCHEDULE REQUEST) including available frequency band information (e.g., 6 GHz, 5 GHz, and 2.4 GHz) to the second external electronic device **103**. A frequency band of the second data link (e.g., NDL 2.4 GHz CH 6) of the second external electronic device **103** may be 2.4 GHz, and the second external electronic device **103**, which is the device of the second type, may use frequency bands of 5 GHz and 2.4 GHz. The second external electronic device **103** may select at least one available frequency band (e.g., 5 GHz, and 2.4 GHz) that may be used by both the electronic device **101** and the second external electronic device **103**, based on the available frequency band information (e.g., 6 GHz, 5 GHz, and 2.4 GHz) included in the schedule request received from the electronic device **101**. An available frequency band (e.g., 5 GHz) having a higher priority than 2.4 GHz that is the frequency band of the second data link (e.g., NDL 2.4 GHz CH 6) of the second external electronic device **103** may be used, and accordingly the second external electronic device **103** may select a channel (e.g., CH 149) that may be used by both the electronic device **101** and the second external electronic device **103** in the available frequency band (e.g., 5 GHz) and may transmit a schedule response (e.g., SCHEDULE RESPONSE) including information on the available frequency band (e.g., 5 GHz) and the channel (e.g., CH 149) (e.g., channel information and/or bandwidth information) of the available frequency band (e.g., 5 GHz) to the electronic device **101**.

(224) In operation **1304**, the electronic device **101** and the second external electronic device **103** may change the second data link (e.g., NDL 2.4 GHz CH 6) to a fourth data link (e.g., NDL 5 GHz CH 149) that uses the channel (e.g., CH 149) of the available frequency band (e.g., 5 GHz), and may perform communication.

(225) In addition, a scheduling operation for changing a data link between the electronic device **101** and the third external electronic device **104** may be performed. A scheduling operation described with reference to operation **1303** may be substantially identically applied to a change of a data link between the electronic device **101** and the third external electronic device **104**.

(226) In operation **1304**, the electronic device **101** may transmit a schedule request (e.g., SCHEDULE REQUEST) including available frequency band information (e.g., 6 GHz, 5 GHz, and 2.4 GHz) to the third external electronic device **104**. The electronic device **101** may also transmit available frequency band information (e.g., 5 GHz, and 2.4 GHz) to the third external electronic

device **104** based on the second external electronic device **103** and the fourth data link (e.g., NDL 5 GHz CH 149) that is newly set. A frequency band of the third data link (e.g., NDL 2.4 GHz CH 6) of the third external electronic device **104** may be 2.4 GHz, and the third external electronic device **104**, which is the device of the second type, may use frequency bands of 5 GHz and 2.4 GHz. The third external electronic device **104** may select at least one available frequency band (e.g., 5 GHz, and 2.4 GHz) that may be used by both the electronic device **101** and the third external electronic device **104**, based on the available frequency band information (e.g., 6 GHz, 5 GHz, and 2.4 GHz) included in the schedule request received from the electronic device **101**. An available frequency band (e.g., 5 GHz) having a higher priority than 2.4 GHz that is the frequency band of the third data link (e.g., NDL 2.4 GHz CH 6) of the third external electronic device **104** may be used, and accordingly the third external electronic device **104** may select a channel (e.g., CH 149) that may be used by both the electronic device **101** and the third external electronic device **104** in the available frequency band (e.g., 5 GHz) and may transmit a schedule response (e.g., SCHEDULE RESPONSE) including information on the available frequency band (e.g., 5 GHz) and the channel (e.g., CH 149) (e.g., channel information and/or bandwidth information) of the available frequency band (e.g., 5 GHz) to the electronic device **101**.

(227) In operation **1305**, the electronic device **101** and the third external electronic device **104** may change the third data link (e.g., NDL 2.4 GHz CH 6) to a fifth data link (e.g., NDL 5 GHz CH 149) that uses the channel (e.g., CH 149) of the available frequency band (e.g., 5 GHz), and may perform communication.

(228) FIG. **13B** is a diagram illustrating an example in which the scheduling operation of FIG. **9** is performed according to various embodiments.

(229) In FIG. **13B**, it may be assumed that the electronic device **101** and the first external electronic device **102** are devices of the first type (e.g., devices for supporting frequency bands of 2.4 GHz, 5 GHz, and 6 GHz, and supporting an RSDB) and that the second external electronic device **103** and the third external electronic device **104** are devices of the second type (e.g., a device for supporting frequency bands of 2.4 GHz and 5 GHz, and supporting an RSDB).

(230) In operation **1311**, a first data link (e.g., NDL 6 GHz CH 101) using a frequency band (e.g., 6 GHz) as a communication protocol (e.g., NAN) may be set between the electronic device **101** and the first external electronic device **102**, and a second data link (e.g., NDL 2.4 GHz CH 6) using a frequency band (e.g., 2.4 GHz) as a communication protocol (e.g., NAN) may be set between the electronic device **101** and the second external electronic device **103**. A third data link (e.g., NDL 2.4 GHz CH 6) using a frequency band (e.g., 2.4 GHz) as a communication protocol (e.g., NAN) may be set between the electronic device **101** and the third external electronic device **104**.

(231) In operation **1312**, the first data link (e.g., NDL 6 GHz CH 101) between the electronic device **101** and the first external electronic device **102** may be terminated.

(232) In operation **1313**, the electronic device **101** may receive a beacon (e.g., a synchronization beacon) or NAF including available frequency band information (e.g., 5 GHz, and 2.4 GHz) of the second external electronic device **103** from the second external electronic device **103**.

(233) In operation **1314**, the electronic device **101** may identify at least one available frequency band (e.g., 5 GHz, and 2.4 GHz) that may be used by both the electronic device **101** and the second external electronic device **103** among available frequency bands (e.g., 5 GHz, and 2.4 GHz) of the second external electronic device **103** and available frequency bands (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the electronic device **101**. The electronic device **101** may compare the frequency band (e.g., 2.4 GHz) of the second data link (e.g., NDL 2.4 GHz CH 6) to an available frequency band (e.g., 5 GHz, and 2.4 GHz) that may be newly used between the electronic device **101** and the second external electronic device **103** according to priorities. An available frequency band (e.g., 5 GHz) having a higher priority than that of 2.4 GHz that is the frequency band of the second data link (e.g., NDL 2.4 GHz CH 6) may be used, and accordingly the electronic device **101** may transmit a schedule request (e.g., SCHEDULE REQUEST) including a new available frequency

band (e.g., 5 GHz) and/or a channel (e.g., CH 149) of the available frequency band (e.g., 5 GHz) to the second external electronic device **103** in order to use the new available frequency band (e.g., 5 GHz). The second external electronic device **103** may identify the new available frequency band (e.g., 5 GHz) and the channel (e.g., CH 149) of the available frequency band (e.g., 5 GHz) included in the schedule request received from the electronic device **101**, and may transmit a schedule response (e.g., SCHEDULE RESPONSE), which includes set information on the available frequency band (e.g., 5 GHz) and/or the channel (e.g., CH 149) (e.g., channel information and/or bandwidth information) to set a frequency band of a new data link, to the electronic device **101**.

(234) In operation **1315**, the electronic device **101** and the second external electronic device **103** may change the second data link (e.g., NDL 2.4 GHz CH 6) to a fourth data link (e.g., NDL 5 GHz CH 149) that uses the channel (e.g., CH 149) of the available frequency band (e.g., 5 GHz), and may perform communication.

(235) In addition, a scheduling operation for changing a data link between the electronic device **101** and the third external electronic device **104** may be performed. A scheduling operation described with reference to operations **1313** and **1314** may be substantially identically applied to a change of a data link between the electronic device **101** and the third external electronic device **104**.

(236) In operation **1315**, the electronic device **101** may receive a beacon (e.g., a synchronization beacon) or NAF including available frequency band information (e.g., 5 GHz, and 2.4 GHz) of the third external electronic device **104** from the third external electronic device **104**.

(237) In operation **1316**, the electronic device **101** may identify at least one available frequency band (e.g., 5 GHz, and 2.4 GHz) that may be used by both the electronic device **101** and the third external electronic device **104** among available frequency bands (e.g., 5 GHz, and 2.4 GHz) of the third external electronic device **104** and available frequency bands (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the electronic device **101**. The electronic device **101** may compare the frequency band (e.g., 2.4 GHz) of the third data link (e.g., NDL 2.4 GHz CH 6) to an available frequency band (e.g., 5 GHz, and 2.4 GHz) that may be newly used between the electronic device **101** and the third external electronic device **104** according to priorities. An available frequency band (e.g., 5 GHz) having a higher priority than that of 2.4 GHz that is the frequency band of the third data link (e.g., NDL 2.4 GHz CH 6) may be used, and accordingly the electronic device **101** may transmit a schedule request (e.g., SCHEDULE REQUEST) including a new available frequency band (e.g., 5 GHz) and/or a channel (e.g., CH 149) (e.g., channel information and/or bandwidth information) of the available frequency band (e.g., 5 GHz) to the third external electronic device **104** in order to use the new available frequency band (e.g., 5 GHz). The third external electronic device **104** may identify the new available frequency band (e.g., 5 GHz) and/or the channel (e.g., CH 149) of the available frequency band (e.g., 5 GHz) included in the schedule request received from the electronic device **101**, and may transmit a schedule response (e.g., SCHEDULE RESPONSE), which includes set information on the available frequency band (e.g., 5 GHz) and/or the channel (e.g., CH 149) (e.g., channel information and/or bandwidth information) to set a frequency band of a new data link, to the electronic device **101**.

(238) In operation **1317**, the electronic device **101** and the third external electronic device **104** may change the third data link (e.g., NDL 2.4 GHz CH 6) to a fifth data link (e.g., NDL 5 GHz CH 149) that uses the channel (e.g., CH 149) of the available frequency band (e.g., 5 GHz), and may perform communication.

(239) FIG. **13C** is a diagram illustrating an example in which the scheduling operation of FIG. **10** is performed according to various embodiments.

(240) In FIG. **13C**, it may be assumed that the electronic device **101** and the first external electronic device **102** are devices of the first type (e.g., devices for supporting frequency bands of 2.4 GHz, 5 GHz, and 6 GHz, and supporting an RSDB) and that the second external electronic device **103** and the third external electronic device **104** are devices of the second type (e.g., a device for supporting frequency bands of 2.4 GHz and 5 GHz, and supporting an RSDB).

(241) In operation **1321**, a first data link (e.g., NDL 6 GHz CH 101) using a frequency band (e.g., 6 GHz) as a communication protocol (e.g., NAN) may be set between the electronic device **101** and the first external electronic device **102**, and a second data link (e.g., NDL 2.4 GHz CH 6) using a frequency band (e.g., 2.4 GHz) as a communication protocol (e.g., NAN) may be set between the electronic device **101** and the second external electronic device **103**. A third data link (e.g., NDL 2.4 GHz CH 6) using a frequency band (e.g., 2.4 GHz) as a communication protocol (e.g., NAN) may be set between the electronic device **101** and the third external electronic device **104**.

(242) In operation **1322**, the first data link (e.g., NDL 6 GHz CH 101) between the electronic device **101** and the first external electronic device **102** may be terminated.

(243) In operation **1323**, the electronic device **101** may transmit a beacon (e.g., a synchronization beacon) or NAF including available frequency band information (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the electronic device **101** to the second external electronic device **103**.

(244) In operation **1324**, the second external electronic device **103** may identify at least one available frequency band (e.g., 5 GHz, and 2.4 GHz) that may be used by both the electronic device **101** and the second external electronic device **103** among available frequency bands (e.g., 5 GHz, and 2.4 GHz) of the second external electronic device **103** and available frequency bands (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the electronic device **101**. The second external electronic device **103** may compare the frequency band (e.g., 2.4 GHz) of the second data link (e.g., NDL 2.4 GHz CH 6) to an available frequency band (e.g., 5 GHz, and 2.4 GHz) that may be newly used between the electronic device **101** and the second external electronic device **103** according to priorities. An available frequency band (e.g., 5 GHz) having a higher priority than that of 2.4 GHz that is the frequency band of the second data link (e.g., NDL 2.4 GHz CH 6) may be used, and accordingly the second external electronic device **103** may transmit a schedule request (e.g., SCHEDULE REQUEST) including a new available frequency band (e.g., 5 GHz) and/or a channel (e.g., CH 149) (e.g., channel information and/or bandwidth information) of the available frequency band (e.g., 5 GHz) to the electronic device **101** in order to use the new available frequency band (e.g., 5 GHz). The electronic device **101** may identify the new available frequency band (e.g., 5 GHz) and/or the channel (e.g., CH 149) of the available frequency band (e.g., 5 GHz) included in the schedule request received from the second external electronic device **103**, and may transmit a schedule response (e.g., SCHEDULE RESPONSE), which includes set information on the available frequency band (e.g., 5 GHz) and/or the channel (e.g., CH 149) (e.g., channel information and/or bandwidth information) to set a frequency band of a new data link, to the second external electronic device **103**.

(245) In operation **1325**, the electronic device **101** and the second external electronic device **103** may change the second data link (e.g., NDL 2.4 GHz CH 6) to a fourth data link (e.g., NDL 5 GHz CH 149) that uses the channel (e.g., CH 149) of the available frequency band (e.g., 5 GHz), and may perform communication.

(246) In addition, a scheduling operation for changing a data link between the electronic device **101** and the third external electronic device **104** may be performed. A scheduling operation described with reference to operations **1323** and **1324** may be substantially identically applied to a change of a data link between the electronic device **101** and the third external electronic device **104**.

(247) In operation **1325**, the electronic device **101** may transmit a beacon (e.g., a synchronization beacon) or NAF including available frequency band information (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the electronic device **101** to the third external electronic device **104**. The electronic device **101** may also transmit available frequency band information (e.g., 5 GHz, and 2.4 GHz) to the third external electronic device **104** based on the second external electronic device **103** and the fourth data link (e.g., NDL 5 GHz CH 149) that is newly set.

(248) In operation **1326**, the third external electronic device **104** may identify at least one available frequency band (e.g., 5 GHz, and 2.4 GHz) that may be used by both the electronic device **101** and the third external electronic device **104** among available frequency bands (e.g., 5 GHz, and 2.4

GHz) of the third external electronic device **104** and available frequency bands (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the electronic device **101**. The third external electronic device **104** may compare the frequency band (e.g., 2.4 GHz) of the third data link (e.g., NDL 2.4 GHz CH 6) to an available frequency band (e.g., 5 GHz, and 2.4 GHz) that may be newly used between the electronic device **101** and the third external electronic device **104** according to priorities. An available frequency band (e.g., 5 GHz) having a higher priority than that of 2.4 GHz that is the frequency band of the third data link (e.g., NDL 2.4 GHz CH 6) may be used, and accordingly the third external electronic device **104** may transmit a schedule request (e.g., SCHEDULE REQUEST) including a new available frequency band (e.g., 5 GHz) and/or a channel (e.g., CH 149) (e.g., channel information and/or bandwidth information) of the available frequency band (e.g., 5 GHz) to the electronic device **101** in order to use the new available frequency band (e.g., 5 GHz). The electronic device **101** may identify the new available frequency band (e.g., 5 GHz) and/or the channel (e.g., CH 149) of the available frequency band (e.g., 5 GHz) included in the schedule request received from the third external electronic device **104**, and may transmit a schedule response (e.g., SCHEDULE RESPONSE), which includes set information on the available frequency band (e.g., 5 GHz) and/or the channel (e.g., CH 149) (e.g., channel information and/or bandwidth information) to set a frequency band of a new data link, to the third external electronic device **104**.

(249) In operation **1327**, the electronic device **101** and the third external electronic device **104** may change the third data link (e.g., NDL 2.4 GHz CH 6) to a fifth data link (e.g., NDL 5 GHz CH 149) that uses the channel (e.g., CH 149) of the available frequency band (e.g., 5 GHz), and may perform communication.

(250) FIG. **13D** is a diagram illustrating slots of newly set data links of FIGS. **13A**, **13B** and **13C** according to various embodiments.

(251) FIG. **13D** illustrates slots of data links finally formed between the electronic device **101** and the second external electronic device **103** and between the electronic device **101** and the third external electronic device **104** in FIGS. **13A** to **13C**.

(252) Referring to FIG. **13D**, the electronic device **101**, which is a device of the first type, may support all of NAN 6 GHz, NAN 5 GHz, and NAN 2.4 GHz, and the second external electronic device **103** and the third external electronic device **104**, which are devices of the second type, may support NAN 5 GHz and NAN 2.4 GHz. The electronic device **101** and the second external electronic device **103** may support NAN 5 GHz and NAN 2.4 GHz, and the electronic device **101** and the third external electronic device **104** may support NAN 5 GHz and NAN 2.4 GHz. NAN 5 GHz may be superior in performance to NAN 2.4 GHz among frequency bands that may be supported by all (or both) of the electronic device **101**, the second external electronic device **103**, and the third external electronic device **104**, and accordingly NAN 5 GHz may have a higher priority than that of NAN 2.4 GHz. Thus, a new scheduling operation may be performed between the electronic device **101** and the second external electronic device **103** so that a data link may be formed between the electronic device **101** and the second external electronic device **103** using a NAN 5 GHz frequency band and may be used. In addition, a new scheduling operation may be performed between the electronic device **101** and the third external electronic device **104** so that a data link may be formed between the electronic device **101** and the third external electronic device **104** using the NAN 5 GHz frequency band and may be used. As illustrated in FIG. **13D**, the data link between the electronic device **101** and the second external electronic device **103** and the data link between the electronic device **101** and the third external electronic device **104** may be formed as NAN 5 GHz Band CH 149, and actually measured performance of the NAN 5 GHz Band CH 149 may be about 900 Mbps.

(253) FIG. **14A** is a diagram illustrating an example in which the scheduling operation of FIG. **8** is performed according to various embodiments.

(254) In FIG. **14A**, it may be assumed that the electronic device **101**, the second external electronic

device **103**, and the third external electronic device **104** are devices of the first type (e.g., devices for supporting frequency bands of 2.4 GHz, 5 GHz, and 6 GHz, and supporting an RSDB) and that the first external electronic device **102** is a device of the second type (e.g., a device for supporting frequency bands of 2.4 GHz and 5 GHz, and supporting an RSDB).

(255) In operation **1401**, a first data link (e.g., NDL 5 GHz CH 149) using a frequency band (e.g., 5 GHz) as a communication protocol (e.g., NAN) may be set between the electronic device **101** and the first external electronic device **102**, and a second data link (e.g., NDL 5 GHz CH 149) using a frequency band (e.g., 5 GHz) as a communication protocol (e.g., NAN) may be set between the electronic device **101** and the second external electronic device **103**. A third data link (e.g., NDL 5 GHz CH 149) using a frequency band (e.g., 5 GHz) as a communication protocol (e.g., NAN) may be set between the electronic device **101** and the second external electronic device **103**.

(256) When the first data link (e.g., NDL 5 GHz CH 149) between the electronic device **101** and the first external electronic device **102** is terminated, the electronic device **101** may determine that an available frequency band of the electronic device **101** is changed from 5 GHz+2.4 GHz to 6 GHz+5 GHz+2.4 GHz in operation **1402**.

(257) In operation **1403**, the electronic device **101** may transmit a schedule request (e.g., SCHEDULE REQUEST) including available frequency band information (e.g., 6 GHz, 5 GHz, and 2.4 GHz) to the second external electronic device **103**. A frequency band of the second data link (e.g., NDL 5 GHz CH 149) of the second external electronic device **103** may be 5 GHz, and the second external electronic device **103**, which is the device of the first type, may use frequency bands of 6 GHz, 5 GHz, and 2.4 GHz. The second external electronic device **103** may select at least one available frequency band (e.g., 6 GHz, 5 GHz, and 2.4 GHz) that may be used by both the electronic device **101** and the second external electronic device **103**, based on the available frequency band information (e.g., 6 GHz, 5 GHz, and 2.4 GHz) included in the schedule request received from the electronic device **101**. An available frequency band (e.g., 6 GHz) having a higher priority than that of 5 GHz that is the frequency band of the second data link (e.g., NDL 5 GHz CH 149) of the second external electronic device **103** may be used, and accordingly the second external electronic device **103** may select a channel (e.g., CH 101) that may be used by both the electronic device **101** and the second external electronic device **103** in the available frequency band (e.g., 6 GHz) and may transmit a schedule response (e.g., SCHEDULE RESPONSE) including information on the available frequency band (e.g., 6 GHz) and the channel (e.g., CH 101) (e.g., channel information and/or bandwidth information) of the available frequency band (e.g., 6 GHz) to the electronic device **101**.

(258) In operation **1404**, the electronic device **101** and the second external electronic device **103** may change the second data link (e.g., NDL 5 GHz CH 149) to a fourth data link (e.g., NDL 6 GHz CH 101) that uses the channel (e.g., CH 101) of the available frequency band (e.g., 6 GHz), and may perform communication.

(259) In addition, a scheduling operation for changing a data link between the electronic device **101** and the third external electronic device **104** may be performed. A scheduling operation described with reference to operation **1403** may be substantially identically applied to a change of a data link between the electronic device **101** and the third external electronic device **104**.

(260) In operation **1404**, the electronic device **101** may transmit a schedule request (e.g., SCHEDULE REQUEST) including available frequency band information (e.g., 6 GHz, 5 GHz, and 2.4 GHz) to the third external electronic device **104**. A frequency band of the third data link (e.g., NDL 5 GHz CH 149) of the third external electronic device **104** may be 5 GHz, and the third external electronic device **104**, which is the device of the first type, may use frequency bands of 6 GHz, 5 GHz, and 2.4 GHz. The third external electronic device **104** may select at least one available frequency band (e.g., 6 GHz, 5 GHz, and 2.4 GHz) that may be used by both the electronic device **101** and the third external electronic device **104**, based on the available frequency band information (e.g., 6 GHz, 5 GHz, and 2.4 GHz) included in the schedule request received

from the electronic device **101**. An available frequency band (e.g., 6 GHz) having a higher priority than that of 5 GHz that is the frequency band of the third data link (e.g., NDL 5 GHz CH 149) of the third external electronic device **104** may be used, and accordingly the third external electronic device **104** may select a channel (e.g., CH 101) that may be used by both the electronic device **101** and the third external electronic device **104** in the available frequency band (e.g., 6 GHz) and may transmit a schedule response (e.g., SCHEDULE RESPONSE) including information on the available frequency band (e.g., 6 GHz) and the channel (e.g., CH 101) (e.g., channel information and/or bandwidth information) of the available frequency band (e.g., 6 GHz) to the electronic device **101**.

(261) In operation **1405**, the electronic device **101** and the third external electronic device **104** may change the third data link (e.g., NDL 5 GHz CH 149) to a fifth data link (e.g., NDL 6 GHz CH 101) that uses the channel (e.g., CH 101) of the available frequency band (e.g., 6 GHz), and may perform communication.

(262) FIG. **14B** is a diagram illustrating an example in which the scheduling operation of FIG. **9** is performed according to various embodiments.

(263) In FIG. **14B**, it may be assumed that the electronic device **101**, the second external electronic device **103**, and the third external electronic device **104** are devices of the first type (e.g., devices for supporting frequency bands of 2.4 GHz, 5 GHz, and 6 GHz, and supporting an RSDB) and that the first external electronic device **102** is a device of the second type (e.g., a device for supporting frequency bands of 2.4 GHz and 5 GHz, and supporting an RSDB).

(264) In operation **1411**, a first data link (e.g., NDL 5 GHz CH 149) using a frequency band (e.g., 5 GHz) as a communication protocol (e.g., NAN) may be set between the electronic device **101** and the first external electronic device **102**, and a second data link (e.g., NDL 5 GHz CH 149) using a frequency band (e.g., 5 GHz) as a communication protocol (e.g., NAN) may be set between the electronic device **101** and the second external electronic device **103**. A third data link (e.g., NDL 5 GHz CH 149) using a frequency band (e.g., 5 GHz) as a communication protocol (e.g., NAN) may be set between the electronic device **101** and the second external electronic device **103**.

(265) In operation **1412**, the first data link (e.g., NDL 5 GHz CH 149) between the electronic device **101** and the first external electronic device **102** may be terminated.

(266) In operation **1413**, the electronic device **101** may receive a beacon (e.g., a synchronization beacon) or NAF including available frequency band information (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the second external electronic device **103** from the second external electronic device **103**.

(267) In operation **1414**, the electronic device **101** may identify at least one available frequency band (e.g., 6 GHz, 5 GHz, and 2.4 GHz) that may be used by both the electronic device **101** and the second external electronic device **103** among available frequency bands (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the second external electronic device **103** and available frequency bands (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the electronic device **101**. The electronic device **101** may compare the frequency band (e.g., 5 GHz) of the second data link (e.g., NDL 5 GHz CH 149) to an available frequency band (e.g., 6 GHz, 5 GHz, and 2.4 GHz) that may be newly used between the electronic device **101** and the second external electronic device **103** according to priorities. An available frequency band (e.g., 6 GHz) having a higher priority than that of 5 GHz that is the frequency band of the second data link (e.g., NDL 5 GHz CH 149) may be used, and accordingly the electronic device **101** may transmit a schedule request (e.g., SCHEDULE REQUEST) including a new available frequency band (e.g., 6 GHz) and/or a channel (e.g., CH 101) (e.g., channel information and/or bandwidth information) of the available frequency band (e.g., 6 GHz) to the second external electronic device **103** in order to use the new available frequency band (e.g., 6 GHz). The second external electronic device **103** may identify the new available frequency band (e.g., 6 GHz) and/or the channel (e.g., CH 101) of the available frequency band (e.g., 6 GHz) included in the schedule request received from the electronic device **101**, and may transmit a schedule response (e.g., SCHEDULE RESPONSE), which includes set information on the available frequency band (e.g., 6

GHz) and/or the channel (e.g., CH 101) (e.g., channel information and/or bandwidth information) to set a frequency band of a new data link, to the electronic device **101**.

(268) In operation **1415**, the electronic device **101** and the second external electronic device **103** may change the second data link (e.g., NDL 5 GHz CH 149) to a fourth data link (e.g., NDL 6 GHz CH 101) that uses the channel (e.g., CH 101) of the available frequency band (e.g., 6 GHz), and may perform communication.

(269) In addition, a scheduling operation for changing a data link between the electronic device **101** and the third external electronic device **104** may be performed. A scheduling operation described with reference to operations **1413** and **1414** may be substantially identically applied to a change of a data link between the electronic device **101** and the third external electronic device **104**.

(270) In operation **1415**, the electronic device **101** may receive a beacon (e.g., a synchronization beacon) or NAF including available frequency band information (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the third external electronic device **104** from the third external electronic device **104**.

(271) In operation **1416**, the electronic device **101** may identify at least one available frequency band (e.g., 6 GHz, 5 GHz, and 2.4 GHz) that may be used by both the electronic device **101** and the third external electronic device **104** among available frequency bands (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the third external electronic device **104** and available frequency bands (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the electronic device **101**. The electronic device **101** may compare the frequency band (e.g., 5 GHz) of the third data link (e.g., NDL 5 GHz CH 149) to an available frequency band (e.g., 6 GHz, 5 GHz, and 2.4 GHz) that may be newly used between the electronic device **101** and the third external electronic device **104** according to priorities. An available frequency band (e.g., 6 GHz) having a higher priority than that of 5 GHz that is the frequency band of the third data link (e.g., NDL 5 GHz CH 149) may be used, and accordingly the electronic device **101** may transmit a schedule request (e.g., SCHEDULE REQUEST) including a new available frequency band (e.g., 6 GHz) and/or a channel (e.g., CH 101) (e.g., channel information and/or bandwidth information) of the available frequency band (e.g., 6 GHz) to the third external electronic device **104** in order to use the new available frequency band (e.g., 6 GHz). The third external electronic device **104** may identify the new available frequency band (e.g., 6 GHz) and/or the channel (e.g., CH 101) of the available frequency band (e.g., 6 GHz) included in the schedule request received from the electronic device **101**, and may transmit a schedule response (e.g., SCHEDULE RESPONSE), which includes set information on the available frequency band (e.g., 6 GHz) and/or the channel (e.g., CH 101) (e.g., channel information and/or bandwidth information) to set a frequency band of a new data link, to the electronic device **101**.

(272) In operation **1417**, the electronic device **101** and the third external electronic device **104** may change the third data link (e.g., NDL 5 GHz CH 149) to a fifth data link (e.g., NDL 6 GHz CH 101) that uses the channel (e.g., CH 101) of the available frequency band (e.g., 6 GHz), and may perform communication.

(273) FIG. **14C** is a diagram illustrating an example in which the scheduling operation of FIG. **10** is performed according to various embodiments.

(274) In FIG. **14C**, it may be assumed that the electronic device **101**, the second external electronic device **103**, and the third external electronic device **104** are devices of the first type (e.g., devices for supporting frequency bands of 2.4 GHz, 5 GHz, and 6 GHz, and supporting an RSDB) and that the first external electronic device **102** is a device of the second type (e.g., a device for supporting frequency bands of 2.4 GHz and 5 GHz, and supporting an RSDB).

(275) In operation **1421**, a first data link (e.g., NDL 5 GHz CH 149) using a frequency band (e.g., 5 GHz) as a communication protocol (e.g., NAN) may be set between the electronic device **101** and the first external electronic device **102**, and a second data link (e.g., NDL 5 GHz CH 149) using a frequency band (e.g., 5 GHz) as a communication protocol (e.g., NAN) may be set between the electronic device **101** and the second external electronic device **103**. A third data link (e.g., NDL 5 GHz CH 149) using a frequency band (e.g., 5 GHz) as a communication protocol (e.g., NAN) may

be set between the electronic device **101** and the second external electronic device **103**.

(276) In operation **1422**, the first data link (e.g., NDL 5 GHz CH 149) between the electronic device **101** and the first external electronic device **102** may be terminated.

(277) In operation **1423**, the electronic device **101** may transmit a beacon (e.g., a synchronization beacon) or NAF including available frequency band information (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the electronic device **101** to the second external electronic device **103**.

(278) In operation **1424**, the second external electronic device **103** may identify at least one available frequency band (e.g., 6 GHz, 5 GHz, and 2.4 GHz) that may be used by both the electronic device **101** and the second external electronic device **103** among available frequency bands (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the second external electronic device **103** and available frequency bands (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the electronic device **101**. The second external electronic device **103** may compare the frequency band (e.g., 5 GHz) of the second data link (e.g., NDL 5 GHz CH 149) to an available frequency band (e.g., 6 GHz, 5 GHz, and 2.4 GHz) that may be newly used between the electronic device **101** and the second external electronic device **103** according to priorities. An available frequency band (e.g., 6 GHz) having a higher priority than that of 5 GHz that is the frequency band of the second data link (e.g., NDL 5 GHz CH 149) may be used, and accordingly the second external electronic device **103** may transmit a schedule request (e.g., SCHEDULE REQUEST) including a new available frequency band (e.g., 6 GHz) and/or a channel (e.g., CH 101) (e.g., channel information and/or bandwidth information) of the available frequency band (e.g., 6 GHz) to the electronic device **101** in order to use the new available frequency band (e.g., 6 GHz). The electronic device **101** may identify the new available frequency band (e.g., 6 GHz) and/or the channel (e.g., CH 101) of the available frequency band (e.g., 6 GHz) included in the schedule request received from the second external electronic device **103**, and may transmit a schedule response (e.g., SCHEDULE RESPONSE), which includes set information on the available frequency band (e.g., 6 GHz) and/or the channel (e.g., CH 101) (e.g., channel information and/or bandwidth information) to set a frequency band of a new data link, to the second external electronic device **103**.

(279) In operation **1425**, the electronic device **101** and the second external electronic device **103** may change the second data link (e.g., NDL 5 GHz CH 149) to a fourth data link (e.g., NDL 6 GHz CH 101) that uses the channel (e.g., CH 101) of the available frequency band (e.g., 6 GHz), and may perform communication.

(280) In addition, a scheduling operation for changing a data link between the electronic device **101** and the third external electronic device **104** may be performed. A scheduling operation described with reference to operations **1423** and **1424** may be substantially identically applied to a change of a data link between the electronic device **101** and the third external electronic device **104**.

(281) In operation **1425**, the electronic device **101** may transmit a beacon (e.g., a synchronization beacon) or NAF including available frequency band information (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the electronic device **101** to the third external electronic device **104**.

(282) In operation **1426**, the third external electronic device **104** may identify at least one available frequency band (e.g., 6 GHz, 5 GHz, and 2.4 GHz) that may be used by both the electronic device **101** and the third external electronic device **104** among available frequency bands (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the third external electronic device **104** and available frequency bands (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the electronic device **101**. The third external electronic device **104** may compare the frequency band (e.g., 5 GHz) of the second data link (e.g., NDL 5 GHz CH 149) to an available frequency band (e.g., 6 GHz, 5 GHz, and 2.4 GHz) that may be newly used between the electronic device **101** and the third external electronic device **104** according to priorities. An available frequency band (e.g., 6 GHz) having a higher priority than that of 5 GHz that is the frequency band of the third data link (e.g., NDL 5 GHz CH 149) may be used, and accordingly the third external electronic device **104** may transmit a schedule request (e.g., SCHEDULE REQUEST) including a new available frequency band (e.g., 6 GHz) and/or a channel (e.g., CH

101) (e.g., channel information and/or bandwidth information) of the available frequency band (e.g., 6 GHz) to the electronic device **101** in order to use the new available frequency band (e.g., 6 GHz). The electronic device **101** may identify the new available frequency band (e.g., 6 GHz) and/or the channel (e.g., CH 101) of the available frequency band (e.g., 6 GHz) included in the schedule request received from the third external electronic device **104**, and may transmit a schedule response (e.g., SCHEDULE RESPONSE), which includes set information on the available frequency band (e.g., 6 GHz) and/or the channel (e.g., CH 101) (e.g., channel information and/or bandwidth information) to set a frequency band of a new data link, to the third external electronic device **104**.

(283) In operation **1427**, the electronic device **101** and the third external electronic device **104** may change the third data link (e.g., NDL 5 GHz CH 149) to a fifth data link (e.g., NDL 6 GHz CH 101) that uses the channel (e.g., CH 101) of the available frequency band (e.g., 6 GHz), and may perform communication.

(284) FIG. **14D** is a diagram illustrating slots of newly set data links of FIGS. **14A**, **14B** and **14C** according to various embodiments.

(285) FIG. **14D** illustrates slots of data links finally formed between the electronic device **101** and the second external electronic device **103** and between the electronic device **101** and the third external electronic device **104** in FIGS. **14A** to **14C**.

(286) Referring to FIG. **14D**, the electronic device **101**, the second external electronic device **103**, and the third external electronic device **104**, which are devices of the first type, may support all of NAN 6 GHz, NAN 5 GHz, and NAN 2.4 GHz. In other words, the electronic device **101**, the second external electronic device **103**, and the third external electronic device **104** may support all (or both) of NAN 6 GHz, NAN 5 GHz, and NAN 2.4 GHz. Among frequency bands that may be supported by all (or both) of the electronic device **101**, the second external electronic device **103**, and the third external electronic device **104**, NAN 6 GHz may be superior in performance to NAN 5 GHz, and NAN 5 GHz may be superior in performance to NAN 2.4 GHz. Accordingly, NAN 6 GHz may have a highest priority. Thus, a new scheduling operation may be performed between the electronic device **101** and the second external electronic device **103** so that a data link may be formed between the electronic device **101** and the second external electronic device **103** using a NAN 6 GHz frequency band and may be used. In addition, a new scheduling operation may be performed between the electronic device **101** and the third external electronic device **104** so that a data link may be formed between the electronic device **101** and the third external electronic device **104** using the NAN 6 GHz frequency band and may be used. As illustrated in FIG. **14D**, the data link between the electronic device **101** and the second external electronic device **103** and the data link between the electronic device **101** and the third external electronic device **104** may be formed as NAN 6 GHz Band CH 101, and actually measured performance of the NAN 6 GHz Band CH 101 may be about 1600 Mbps.

(287) FIG. **15** is a diagram illustrating an example of an NDL scheduling method by a change in a frequency band according to various embodiments.

(288) Referring to FIG. **15**, according to various example embodiments, an electronic device **101** may perform NDL scheduling (e.g., updating, or rescheduling) based on a change in a frequency band due to a termination (e.g., a connection termination) of at least one data link formed in the electronic device **101**. For example, the electronic device **101** may schedule a data link of a first external electronic device **102** that maintains a connection to the electronic device **101** in response to a change in a frequency band due to a termination of a data link of a fourth external electronic device **1501** (e.g., an access point (AP)). For convenience of description, an operation of the NDL scheduling method based on the change in the frequency band is described based on the electronic device **101**. However, an operation of the electronic device **101** may be substantially identically applied to the external electronic device **102**, and an operation of the external electronic device **102** may be substantially identically applied to the electronic device **101**. Although only two external

electronic devices (e.g., the fourth external electronic device **1501** and the first external electronic device **102**) are illustrated in FIG. **15** for convenience of description, various example embodiments are not limited thereto, and substantially the same operations as those described above may be performed even though three or more external electronic devices are connected to the electronic device **101**.

(289) According to various example embodiments, the electronic device **101** and the fourth external electronic device **1501** may set a schedule for a first data link **1510** that uses a first frequency band (e.g., 2.4 GHz, 5 GHz, or 6 GHz) as a first communication protocol (e.g., Wi-Fi). The first communication protocol may be a protocol for supporting a non-NAN communication operation.

(290) According to various example embodiments, the electronic device **101** connected to the fourth external electronic device **1501** may schedule a second data link **1520** with the first external electronic device **102** by combining one or more frequency bands. For example, the electronic device **101** may schedule the second data link **1520** with the first external electronic device **102** by combining two different frequency bands, and may communicate with the first external electronic device **102** by switching the two frequency bands through time division (e.g., 50%). In this example, the electronic device **101** and the first external electronic device **102** may perform data communication with an efficiency of up to about 50%. If the electronic device **101** connected to the fourth external electronic device **1501** that supports a frequency band (e.g., 5 GHz) is a device of the first type (e.g., a device for supporting frequency bands 2.4 GHz, 5 GHz, and 6 GHz, and supporting an RSDB), it may be difficult for the electronic device **101** to use 5 GHz and 6 GHz bands at the same time. However, through the time division, the electronic device **101** may use the 5 GHz band for non-NAN communication (e.g., Wi-Fi) with the fourth external electronic device **1501** for 50%, and may use the 6 GHz band for NAN communication with the first external electronic device **102** for 50%. This is because using of the frequency band of 6 GHz to perform NAN communication is superior in performance to using a frequency band of 5 GHz.

(291) According to various example embodiments, the electronic device **101** and the first external electronic device **102** may set a schedule for a second data link **1520** that uses a second frequency band (e.g., 2.4 GHz, 5 GHz, or 6 GHz) as a second communication protocol (e.g., NAN). The second communication protocol may be a communication protocol for supporting a NAN communication operation. The first frequency band and the second frequency band may be different. According to various example embodiments, the electronic device **101** may perform scheduling to change the second data link **1520** to a third data link **1530** that uses a third frequency band (e.g., 2.4 GHz, 5 GHz, or 6 GHz) if the third frequency band is available, in response to a termination of the first data link **1510** (e.g., a termination of connection to the fourth external electronic device **1501**). The third data link **1530** using the third frequency band may be substantially the same as the second data link **1520** using the third frequency band. For example, the third data link **1530** may be obtained by changing at least one of a channel (or channel information) and bandwidth information other than a frequency band (e.g., a third frequency band) in the second data link **1520**. The third frequency band may be different from the second frequency band, and may have a higher priority than that the second frequency band based on at least one of performance and congestion according to the frequency band. The third frequency band may also be the same as the first frequency band. If the second data link **1520** using the second frequency band is formed between the electronic device **101** and the first external electronic device **102**, an operation of performing NDL scheduling by a change in a frequency band may be substantially the same as the NDL scheduling operation described above with reference to FIGS. **7**, **8** and **9**.

(292) According to various example embodiments, the electronic device **101** and the first external electronic device **102** may set a schedule for the second data link **1520** that uses both the first frequency band (e.g., 2.4 GHz, 5 GHz, or 6 GHz) and the second frequency band (e.g., 2.4 GHz, 5 GHz, or 6 GHz) as a second communication protocol (e.g., NAN). The second communication protocol may be a communication protocol for supporting a NAN communication operation. The

first frequency band and the second frequency band may be different. The second data link **1520** may be configured with the first frequency band and the second frequency band. The electronic device **101** may communicate with the first external electronic device **102** using a channel of the first frequency band in a first interval, and may communicate with the first external electronic device **102** using a channel of the second frequency band in a second interval. For example, the first interval and the second interval may be different.

(293) According to various example embodiments, if it is possible to change an interval (e.g., a used interval) of a frequency band (e.g., the first frequency band, and the second frequency band) used in the second data link **1520** in response to the termination of the first data link **1510** (e.g., a termination of connection to the fourth external electronic device **1501**), the electronic device **101** may perform scheduling to change the second data link **1520** to the third data link **1530** that uses an interval of a frequency band having a lower priority between the first frequency band and the second frequency band as an interval of the third frequency band. The third frequency band may be the same as the first frequency band or the second frequency band. If the second data link **1520** using the first frequency band and the second frequency band is formed between the electronic device **101** and the first external electronic device **102**, an operation of performing NDL scheduling by a change in a frequency band will be described in detail with reference to FIGS. **16** to **18**.

According to various example embodiments, NDL scheduling according to the termination of the first data link **1510** may be performed by exchanging a schedule request, a schedule response, and/or a schedule confirmation between the electronic device **101** and the first external electronic device **102**. In order to set a schedule for the third data link **1530** that is a new data link, the schedule request and the schedule response may include a NAN availability attribute and/or unaligned schedule attribute based on information on an available frequency band (e.g., available frequency band information, information on an interval of an available frequency band, and channel information and/or bandwidth information of the available frequency band). If an interval of the available frequency band is changed due to the termination of the first data link **1510**, the information on the available frequency band (e.g., available frequency band information, information on an interval of an available frequency band, and channel information and/or bandwidth information of the available frequency band) may be added to the NAN availability attribute and/or the unaligned schedule attribute. The available frequency band information may be included in the List of Band Entries of the NAN availability attribute and/or unaligned schedule attribute, and the channel information and/or bandwidth information of the available frequency band may be included in a Channel Entry field of the NAN availability attribute and/or the unaligned schedule attribute.

(294) According to various example embodiments, an available frequency band to be used for the new third data link **1530** may be selected in a priority order of 6 GHz>5 GHz>2.4 GHz from the NAN availability attribute and/or the unaligned schedule attribute included in the schedule request and schedule response. Accordingly, the electronic device **101** may efficiently configure multiple frequency bands by detecting a change in a data link with a neighboring device, and may efficiently use the multiple frequency bands.

(295) FIG. **16** is a flowchart illustrating an example operation of an electronic device to perform NDL scheduling by a change in a frequency band according to various embodiments.

(296) Referring to FIG. **16**, according to various example embodiments, the electronic device **101** may support a first communication protocol (e.g., Wi-Fi) and a second communication protocol (e.g., NAN). For example, the first communication protocol may support a communication operation other than a NAN communication operation, and the second communication protocol may support the NAN communication operation. Operations **1610** through **1630** may be performed sequentially, but not be necessarily performed sequentially. For example, the order of operations **1610** through **1630** may be changed, and at least two of operations **1610** through **1630** may be performed in parallel.

(297) In operation **1610**, the electronic device **101** may set a schedule for the first data link **1510** that uses the first frequency band as the first communication protocol with the fourth external electronic device **1501**.

(298) In operation **1620**, the electronic device **101** may set a schedule for the second data link **1520** that uses the first frequency band and the second frequency band as the second communication protocol with the first external electronic device **102**.

(299) If it is possible to change an interval of a frequency band (e.g., the first frequency band, and the second frequency band) used in the second data link **1520** in response to the termination of the first data link **1510**, the electronic device **101** may change the second data link **1520** to the third data link **1530** that uses an interval of a frequency band having a lower priority between the first frequency band and the second frequency band as an interval of the third frequency band and may communicate with the first external electronic device **102** in operation **1630**. The third frequency band may be an available frequency band having a higher priority than that of a frequency band (e.g., the first frequency band, and the second frequency band) used in the second data link **1520** among one or more available frequency bands that may be used by both the electronic device **101** and the first external electronic device **102**.

(300) FIG. **17** is a diagram illustrating an example of an NDL scheduling operation performed based on the NDL scheduling method of FIG. **15** according to various embodiments.

(301) Referring to FIG. **17**, operations **1710** through **1790** may be performed sequentially, but not be necessarily performed sequentially. For example, the order of operations **1710** through **1790** may be changed, and at least two of operations **1710** through **1790** may be performed in parallel.

(302) In operation **1710**, the electronic device **101** may set a schedule for the first data link **1510** that uses the first frequency band as the first communication protocol (e.g., Wi-Fi) with the fourth external electronic device **1501**. The first data link **1510** may be set between the electronic device **101** and the fourth external electronic device **1501**.

(303) In operation **1720**, the electronic device **101** may set a schedule for the second data link **1520** that uses both the first frequency band and the second frequency band as a communication protocol (e.g., NAN) with the first external electronic device **102**. The second data link **1520** may be set between the electronic device **101** and the first external electronic device **102**.

(304) In operation **1725**, the first data link **610** formed between the electronic device **101** and the first external electronic device **102** may be terminated.

(305) In operation **1730**, the electronic device **101** may identify a change in an interval of an available frequency band of the electronic device **101**, in response to the termination of the first data link **1510** (e.g., a termination of connection to the fourth external electronic device **1501**).

(306) In operation **1735**, when the interval of the available frequency band is not changed, the second data link **1520** set between the electronic device **101** and the first external electronic device **102** may be maintained.

(307) In operation **1740**, when the interval of the available frequency band is changed, the electronic device **101** may transmit a schedule request (e.g., SCHEDULE REQUEST) including information on an available frequency band (e.g., information on frequency bands that may be used by the electronic device **101** due to the termination of the first data link **1510** and information on intervals) of the electronic device **101** to the first external electronic device **102**, to effectively set (or reset) a data link between the electronic device **101** and the first external electronic device **102**.

(308) In operation **1750**, the first external electronic device **102** may receive the schedule request, and may select at least one available frequency band that may be concurrently used by both the electronic device **101** and the first external electronic device **102**, based on the information on the available frequency band of the electronic device **101** included in the schedule request.

(309) In operation **1760**, the first external electronic device **102** may compare a priority of at least one available frequency band to a priority of a frequency band (e.g., the first frequency band and the second frequency band) used in the second data link **1520**, and may determine whether a

frequency band having a higher priority than that of the frequency band used in the second data link **1520** is present.

(310) In operation **1770**, when an available frequency band having a higher priority than that of the frequency band used in the second data link **1520** is absent, the second data link **1520** set between the electronic device **101** and the first external electronic device **102** may be maintained. Here, the first external electronic device **102** may or may not transmit a schedule response (e.g., SCHEDULE RESPONSE) including “rejection” (e.g., Rejected) to the electronic device **101**.

(311) In operation **1780**, when the available frequency band having the higher priority than that of the frequency band used in the second data link **1520** is present, the first external electronic device **102** may transmit a schedule response including information on the available frequency band (e.g., available frequency band information, and channel information and/or bandwidth information of the available frequency band) to the electronic device **101**. The schedule response may also include information on an interval in which the available frequency band is used.

(312) In operation **1790**, the electronic device **101** and the first external electronic device **102** may change the second data link **1520** to the third data link **1530** that uses an interval of an available frequency band and may perform communication (e.g., NAN communication).

(313) FIG. **18** is a diagram illustrating an example of an NDL scheduling operation performed based on the NDL scheduling method of FIG. **15** according to various embodiments.

(314) Referring to FIG. **18**, in operation **1810**, the electronic device **101** may set a schedule for the first data link **1510** that uses the first frequency band as the first communication protocol (e.g., Wi-Fi) with the fourth external electronic device **1501**. The first data link **1510** may be set between the electronic device **101** and the fourth external electronic device **1501**.

(315) In operation **1813**, the electronic device **101** may set a schedule for the second data link **1520** that uses both the first frequency band and the second frequency band as a communication protocol (e.g., NAN) with the first external electronic device **102**. The second data link **1520** may be set between the electronic device **101** and the first external electronic device **102**.

(316) In operation **1815**, the first data link **1510** formed between the electronic device **101** and the fourth external electronic device **1501** may be terminated.

(317) In operation **1820**, the electronic device **101** may obtain information on an available frequency band (e.g., information on frequency bands that may be used by the first external electronic device **102** due to the termination of the first data link **1510**, and/or information on intervals) of the first external electronic device **102** from the first external electronic device **102**. The first external electronic device **102** may broadcast at least one of a beacon and a NAF to a neighboring device in real time. For example, the first external electronic device **102** may include information on an available frequency band in at least one of the beacon and the NAF and may transmit at least one of the beacon and the NAF including the information to the electronic device **101**. The first external electronic device **102** may broadcast at least one of the beacon and the NAF in real time regardless of the termination of the first data link **1510**. The electronic device **101** may receive the beacon and/or NAF from the first external electronic device **102** at a point in time at which the first data link **1510** is terminated.

(318) In operation **1823**, the electronic device **101** may compare a frequency band (e.g., frequency bands that may be used by the electronic device **101** due to the termination of the first data link **1510**) that may be used by the electronic device **101** and a frequency band that may be used by the first external electronic device **102**, based on the information on the available frequency band of the first external electronic device **102**. The electronic device **101** may select at least one available frequency band that may be concurrently used by both the electronic device **101** and the first external electronic device **102**.

(319) In operation **1825**, the electronic device **101** may compare a priority of at least one available frequency band to a priority of a frequency band (e.g., the first frequency band and the second frequency band) used in the second data link **1520**, and may determine whether an available

frequency band having a higher priority than that of the frequency band used in the second data link **1520** is present.

(320) In operation **1830**, when the available frequency band having the higher priority than that of the frequency band used in the second data link **1520** is absent, the second data link **1520** set between the electronic device **101** and the first external electronic device **102** may be maintained.

(321) In operation **1835**, when the available frequency band (e.g., a first available frequency band) having the higher priority than that of the frequency band used in the second data link **1520** is present, the electronic device **101** may transmit a schedule request (e.g., SCHEDULE REQUEST) including information on a first available frequency band (e.g., first available frequency band information, and channel information and/or bandwidth information of the first available frequency band) to the first external electronic device **102**.

(322) In operation **1840**, the first external electronic device **102** may receive the schedule request from the electronic device **101**, and may determine whether setting of a new data link using the first available frequency band received from the electronic device **101** is most appropriate.

(323) In operation **1845**, when the setting of the new data link using the first available frequency band received from the electronic device **101** is most appropriate, the first external electronic device **102** may transmit a schedule response (e.g., SCHEDULE RESPONSE) including the information on the first available frequency band (e.g., first available frequency band information, and channel information and/or bandwidth information of the first available frequency band) to the electronic device **101**. The schedule response may also include information on an interval in which the first available frequency band is used.

(324) In operation **1850**, the electronic device **101** and the first external electronic device **102** may change the second data link **1520** to the third data link **1530** that includes an interval in which the first available frequency band is used, and may perform communication (e.g., NAN communication).

(325) In operation **1855**, when the setting of the new data link using the first available frequency band received from the electronic device **101** is not most appropriate, the first external electronic device **102** may determine whether a second available frequency band having a higher priority (or highest priority) than that of the frequency band used in the second data link **1520** is present.

(326) In operation **1860**, when the second available frequency band having the higher priority than that of the frequency band used in the second data link **1520** is absent, the second data link **1520** set between the electronic device **101** and the first external electronic device **102** may be maintained. Here, the first external electronic device **102** may or may not transmit a schedule response (e.g., SCHEDULE RESPONSE) including “rejection” (e.g., Rejected) to the electronic device **101**.

(327) In operation **1865**, when the second available frequency band having the higher priority than that of the frequency band used in the second data link **1520** is present, the first external electronic device **102** may transmit a schedule response including a modification schedule proposal to set the third data link **1530** using an interval of the second available frequency band to the electronic device **101**. The schedule response may include information on the second available frequency band (e.g., second available frequency band information, and channel information and/or bandwidth information of the second available frequency band). The schedule response may also include information on an interval in which the second available frequency band is used.

(328) In operation **1870**, the electronic device **101** may transmit a schedule confirmation (e.g., SCHEDULE CONFIRM) to the first external electronic device **102**, in response to the schedule response. The schedule confirmation may include information on the second available frequency band (e.g., second available frequency band information, and channel information and/or bandwidth information of the second available frequency band), or “rejection” (e.g., Rejected).

(329) In operation **1875**, when the schedule confirmation includes the information on the second available frequency band (e.g., second available frequency band information, and channel information and/or bandwidth information of the second available frequency band), the electronic

device **101** and the first external electronic device **102** may change the second data link **1520** to the third data link **1530** that uses the interval of the second available frequency band and may perform communication (e.g., NAN communication). When the schedule confirmation includes “rejection” (e.g., Rejected), the second data link **1520** set between the electronic device **101** and the first external electronic device **102** may be maintained.

(330) FIG. **19** is a diagram illustrating an example of an NDL scheduling operation performed based on the NDL scheduling method of FIG. **15** according to various embodiments.

(331) Referring to FIG. **19**, operations **1910** through **1975** may be performed sequentially, but not be necessarily performed sequentially. For example, the order of operations **1910** through **1975** may be changed, and at least two of operations **1910** through **1975** may be performed in parallel.

(332) In operation **1910**, the electronic device **101** may set a schedule for the first data link **1510** that uses the first frequency band as the first communication protocol (e.g., Wi-Fi) with the fourth external electronic device **1501**. The first data link **1510** may be set between the electronic device **101** and the fourth external electronic device **1501**.

(333) In operation **1913**, the electronic device **101** may set a schedule for the second data link **1520** that uses both the first frequency band and the second frequency band as the second communication protocol (e.g., NAN) with the first external electronic device **102**. The second data link **1520** may be set between the electronic device **101** and the first external electronic device **102**.

(334) In operation **1915**, the first data link **1510** formed between the electronic device **101** and the fourth external electronic device **1501** may be terminated.

(335) In operation **1920**, the electronic device **101** may transmit information on an available frequency band (e.g., information on frequency bands that may be used by the electronic device **101** due to the termination of the first data link **1510**, and/or information on intervals) of the electronic device **101** to the first external electronic device **102**, in response to the termination of the first data link **1510**. The electronic device **101** may include the information on the available frequency band in at least one of a beacon and a NAF and may transmit at least one of the beacon and the NAF including the information to the first external electronic device **102**.

(336) In operation **1923**, the first external electronic device **102** may compare a frequency band (e.g., frequency bands that may be used by the first external electronic device **102** due to the termination of the first data link **1510**) that may be used by the first external electronic device **102** and a frequency band that may be used by the electronic device **101**, based on the information on the available frequency band of the electronic device **101**. The first external electronic device **102** may select at least one available frequency band that may be concurrently used by both the electronic device **101** and the first external electronic device **102**.

(337) In operation **1925**, the first external electronic device **102** may compare a priority of at least one available frequency band to a priority of a frequency band (e.g., the first frequency band, and the second frequency band) used in the second data link **1520**, and may determine whether an available frequency band having a higher priority than that of the frequency band used in the second data link **1520** is present.

(338) In operation **1930**, when the available frequency band having the higher priority than that of the frequency band used in the second data link **1520** is absent, the second data link **1520** set between the electronic device **101** and the first external electronic device **102** may be maintained.

(339) In operation **1935**, when the available frequency band (e.g., a first available frequency band) having the higher priority than that of the frequency band used in the second data link **1520** is present, the first external electronic device **102** may transmit a schedule request (e.g., SCHEDULE REQUEST) including information on a first available frequency band (e.g., first available frequency band information, and channel information and/or bandwidth information of the first available frequency band) to the electronic device **101**. The schedule request may also include information on an interval in which the first available frequency band is used.

(340) In operation **1940**, the electronic device **101** may receive the schedule request from the first

external electronic device **102**, and may determine whether setting of a new data link using the first available frequency band received from the first external electronic device **102** is most appropriate. (341) In operation **1945**, when the setting of the new data link using the first available frequency band received from the first external electronic device **102** is most appropriate, the electronic device **101** may transmit a schedule response (e.g., SCHEDULE RESPONSE) including the information on the first available frequency band (e.g., first available frequency band information, and channel information and/or bandwidth information of the first available frequency band) to the first external electronic device **102**.

(342) In operation **1950**, the electronic device **101** and the first external electronic device **102** may change the second data link **1520** to the third data link **1530** that uses an interval of the first available frequency band and may perform communication (e.g., NAN communication).

(343) In operation **1955**, when the setting of the new data link using the first available frequency band received from the first external electronic device **102** is not most appropriate, the electronic device **101** may determine whether a second available frequency band having a higher priority than that of the frequency band used in the second data link **1520** is present.

(344) In operation **1960**, when the second available frequency band having the higher priority than that of the frequency band used in the second data link **1520** is absent, the second data link **1520** set between the electronic device **101** and the first external electronic device **102** may be maintained. Here, the electronic device **101** may or may not transmit a schedule response (e.g., SCHEDULE RESPONSE) including “rejection” (e.g., Rejected) to the first external electronic device **102**.

(345) In operation **1965**, when the second available frequency band having the higher priority than that of the frequency band used in the second data link **1520** is present, the electronic device **101** may transmit a schedule response including a modification schedule proposal to set the third data link **1530** using an interval of the second available frequency band to the first external electronic device **102**. The schedule response may include information on the second available frequency band (e.g., second available frequency band information, and channel information and/or bandwidth information of the second available frequency band). The schedule response may also include information on an interval in which the second available frequency band is used.

(346) In operation **1970**, the first external electronic device **102** may transmit a schedule confirmation (e.g., SCHEDULE CONFIRM) to the electronic device **101**, in response to the schedule response. The schedule confirmation may include information on the second available frequency band (e.g., second available frequency band information, and channel information and/or bandwidth information of the second available frequency band), or “rejection” (e.g., Rejected).

(347) In operation **1975**, when the schedule confirmation includes the information on the second available frequency band (e.g., second available frequency band information, and channel information and/or bandwidth information of the second available frequency band), the electronic device **101** and the first external electronic device **102** may change the second data link **1520** to the third data link **1530** that uses the interval of the second available frequency band and may perform communication (e.g., NAN communication). When the schedule confirmation includes “rejection” (e.g., Rejected), the second data link **1520** set between the electronic device **101** and the first external electronic device **102** may be maintained.

(348) Hereinafter, examples of the scheduling operations of FIGS. **17**, **18** and **19** will be described with reference to FIGS. **20A**, **20B**, **20C**, **20D**, **21A**, **21B**, **21C**, **21D**, **22A**, **22B**, **22C** and **22D** (which may be referred to as FIGS. **20A** to **22D**). Referring to FIGS. **20A** to **22D**, for convenience of description, priority levels based on performance (e.g., NAN throughput in a NAN terminal) according to frequency bands may be assumed to be in the order of 6 GHz (e.g., 1600 Mbps)>5 GHz (e.g., 900 Mbps)>2.4 GHz (e.g., 150 Mbps).

(349) FIG. **20A** is a diagram illustrating an example in which a scheduling operation of FIG. **17** is performed according to various embodiments.

(350) In FIG. **20A**, it may be assumed that the electronic device **101** and the first external

electronic device **102** are devices of the first type (e.g., devices for supporting frequency bands of 2.4 GHz, 5 GHz, and 6 GHz, and supporting an RSDB).

(351) In operation **2001**, a first data link (e.g., AP1 5 GHz CH 36) using a frequency band (e.g., 5 GHz) as a first communication protocol (e.g., Wi-Fi) may be set between the electronic device **101** and the fourth external electronic device **1501**, and a second data link (e.g., NDL 6 GHz CH 101+5 GHz CH 36) using both frequency bands of 6 GHz and 5 GHz as a second communication protocol (e.g., NAN) may be set between the electronic device **101** and the first external electronic device **102**. For example, the second data link may be set to 50% use of 6 GHz CH 101+50% use of 5 GHz CH 36.

(352) When the first data link (e.g., AP1 5 GHz CH 36) between the electronic device **101** and the fourth external electronic device **1501** is terminated, the electronic device **101** may determine that an available frequency band of the electronic device **101** is changed from 6 GHz 50%+5 GHz 50%+2.4 GHz 100% to 6 GHz 100%+5 GHz 100%+2.4 GHz 100% in operation **2002**. An interval of the available frequency band of the electronic device **101** may be changed from 50% use of 6 GHz CH 101+50% use of 5 GHz CH 36 to 100% use of 6 GHz, 100% use of 5 GHz, or 100% use of 2.4 GHz.

(353) In operation **2003**, the electronic device **101** may transmit a schedule request (e.g., SCHEDULE REQUEST) including available frequency band information (e.g., 6 GHz, 5 GHz, and 2.4 GHz) to the first external electronic device **102**. The first external electronic device **102** may use 6 GHz CH 101 for 50% and 5 GHz CH 36 for 50% in the second data link (e.g., NDL 6 GHz CH 101+5 GHz CH 36). The first external electronic device **102**, which is the device of the first type, may use frequency bands of 6 GHz, 5 GHz, and 2.4 GHz. The first external electronic device **102** may select at least one available frequency band (e.g., 6 GHz, 5 GHz, and 2.4 GHz) that may be used by both the electronic device **101** and the first external electronic device **102**, based on the available frequency band information (e.g., 6 GHz, 5 GHz, and 2.4 GHz) included in the schedule request received from the electronic device **101**. An available frequency band (e.g., 6 GHz) having a relatively high priority may be used in an interval of a frequency band (e.g., 5 GHz) of the second data link (e.g., NDL 6 GHz CH 101+5 GHz CH 36), and accordingly the first external electronic device **102** may select a channel (e.g., CH 101) that may be used by both the electronic device **101** and the first external electronic device **102** in the available frequency band (e.g., 6 GHz), and may transmit a schedule response (e.g., SCHEDULE RESPONSE) including information on the available frequency band (e.g., 6 GHz) and the channel (e.g., CH 101) (e.g., channel information and/or bandwidth information) of the available frequency band (e.g., 6 GHz) to the electronic device **101**. The schedule response may include information on an interval in which the available frequency band (e.g., 6 GHz) is used.

(354) In operation **2004**, the electronic device **101** and the first external electronic device **102** may change an existing interval corresponding to 5 GHz CH 36 in the second data link (e.g., NDL 6 GHz CH 101+5 GHz CH 36) to an interval corresponding to the available frequency band (e.g., 6 GHz) and the channel (e.g., CH 101) of the available frequency band (e.g., 6 GHz), and may perform communication via a new third data link (e.g., NDL 6 GHz CH 101).

(355) FIG. **20B** is a diagram illustrating an example in which a scheduling operation of FIG. **18** is performed according to various embodiments.

(356) In FIG. **20B**, it may be assumed that the electronic device **101** and the first external electronic device **102** are devices of the first type (e.g., devices for supporting frequency bands of 2.4 GHz, 5 GHz, and 6 GHz, and supporting an RSDB).

(357) In operation **2011**, a first data link (e.g., AP1 5 GHz CH 36) using a frequency band (e.g., 5 GHz) as a first communication protocol (e.g., Wi-Fi) may be set between the electronic device **101** and the fourth external electronic device **1501**, and a second data link (e.g., NDL 6 GHz CH 101+5 GHz CH 36) using both frequency bands of 6 GHz and 5 GHz as a second communication protocol (e.g., NAN) may be set between the electronic device **101** and the first external electronic device

102. For example, the second data link may be set to 50% use of 6 GHz CH 101+50% use of 5 GHz CH 36.

(358) In operation **2012**, the first data link (e.g., AP1 5 GHz CH 36) between the electronic device **101** and the fourth external electronic device **1501** may be terminated.

(359) In operation **2013**, the electronic device **101** may receive a beacon (e.g., a synchronization beacon) or NAF including available frequency band information (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the first external electronic device **102** from the first external electronic device **102**.

(360) In operation **2014**, due to a termination of the first data link (e.g., AP1 5 GHz CH 36), an interval of an available frequency band of the electronic device **101** may be changed from 50% use of 6 GHz CH 101+50% use of 5 GHz CH 36 to 100% use of 6 GHz, 100% use of 5 GHz, or 100% use of 2.4 GHz. The electronic device **101** may identify at least one available frequency band (e.g., 6 GHz, 5 GHz, and 2.4 GHz) that may be used by both the electronic device **101** and the first external electronic device **102** among available frequency bands (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the first external electronic device **102** and available frequency bands (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the electronic device **101**. The electronic device **101** may compare a frequency band (e.g., 6 GHz, and 5 GHz) used in the second data link (e.g., NDL 6 GHz CH 101+5 GHz CH 36) to an available frequency band (e.g., 6 GHz, 5 GHz, and 2.4 GHz) that may be newly used between the electronic device **101** and the first external electronic device **102** according to priorities. An available frequency band (e.g., 6 GHz) having a relatively high priority may be used in an interval of a frequency band (e.g., 5 GHz) of the second data link (e.g., NDL 6 GHz CH 101+5 GHz CH 36), and accordingly the electronic device **101** may transmit a schedule request (e.g., SCHEDULE REQUEST), which includes a new available frequency band (e.g., 6 GHz), a channel (e.g., CH 101) (e.g., channel information and/or bandwidth information) of the available frequency band (e.g., 6 GHz), and/or information (e.g., available interval information) on an interval of the available frequency band (e.g., 6 GHz), to the first external electronic device **102** in order to use the new available frequency band (e.g., 6 GHz) in a corresponding interval. The first external electronic device **102** may identify the new available frequency band (e.g., 6 GHz) and/or the channel (e.g., CH 101) of the available frequency band (e.g., 6 GHz) included in the schedule request received from the electronic device **101**, and may transmit a schedule response (e.g., SCHEDULE RESPONSE), which includes set information on the available frequency band (e.g., 6 GHz) and/or the channel (e.g., CH 101) (e.g., channel information and/or bandwidth information) to set a frequency band of a new data link, to the electronic device **101**. The schedule response may include information on an interval in which an available frequency band (e.g., 6 GHz) is used.

(361) In operation **2015**, the electronic device **101** and the first external electronic device **102** may change an existing interval corresponding to 5 GHz CH 36 in the second data link (e.g., NDL 6 GHz CH 101+5 GHz CH 36) to an interval corresponding to the available frequency band (e.g., 6 GHz) and the channel (e.g., CH 101) of the available frequency band (e.g., 6 GHz), and may perform communication via a new third data link (e.g., NDL 6 GHz CH 101).

(362) FIG. **20C** is a diagram illustrating an example in which a scheduling operation of FIG. **19** is performed according to various embodiments.

(363) In FIG. **20C**, it may be assumed that the electronic device **101** and the first external electronic device **102** are devices of the first type (e.g., devices for supporting frequency bands of 2.4 GHz, 5 GHz, and 6 GHz, and supporting an RSDB).

(364) In operation **2021**, a first data link (e.g., AP1 5 GHz CH 36) using a frequency band (e.g., 5 GHz) as a first communication protocol (e.g., Wi-Fi) may be set between the electronic device **101** and the fourth external electronic device **1501**, and a second data link (e.g., NDL 6 GHz CH 101+5 GHz CH 36) using both frequency bands of 6 GHz and 5 GHz as a second communication protocol (e.g., NAN) may be set between the electronic device **101** and the first external electronic device **102**.

(365) In operation **2022**, the first data link (e.g., AP1 5 GHz CH 36) between the electronic device

101 and the fourth external electronic device **1501** may be terminated.

(366) In operation **2023**, due to a termination of the first data link (e.g., AP1 5 GHz CH 36), an interval of an available frequency band of the electronic device **101** may be changed from 50% use of 6 GHz CH 101+50% use of 5 GHz CH 36 to 100% use of 6 GHz, 100% use of 5 GHz, or 100% use of 2.4 GHz. The electronic device **101** may transmit a beacon (e.g., a synchronization beacon) or NAF including available frequency band information (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the electronic device **101** to the first external electronic device **102**.

(367) In operation **2024**, the first external electronic device **102** may identify at least one available frequency band (e.g., 6 GHz, 5 GHz, and 2.4 GHz) that may be used by both the electronic device **101** and the first external electronic device **102** among available frequency bands (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the first external electronic device **102** and available frequency bands (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the electronic device **101**. The first external electronic device **102** renews the frequency band (6 GHz, 5 GHz) used in the second data link (e.g., NDL 6 GHz CH 101+5 GHz CH 36) between the electronic device **101** and the first external electronic device **102**. Available frequency bands (6 GHz, 5 GHz, 2.4 GHz) and priority can be compared. An available frequency band (e.g., 6 GHz) having a relatively high priority may be used in an interval of a frequency band (e.g., 5 GHz) of the second data link (e.g., NDL 6 GHz CH 101+5 GHz CH 36), and accordingly the first external electronic device **102** may transmit a schedule request (e.g., SCHEDULE REQUEST), which includes a new available frequency band (e.g., 6 GHz), a channel (e.g., CH 101) (e.g., channel information and/or bandwidth information) of the available frequency band (e.g., 6 GHz), and/or information (e.g., available interval information) on an interval of the available frequency band (e.g., 6 GHz), to the electronic device **101** in order to use the new available frequency band (e.g., 6 GHz) in a corresponding interval. The electronic device **101** may identify the new available frequency band (e.g., 6 GHz) and/or the channel (e.g., CH 101) of the available frequency band (e.g., 6 GHz) included in the schedule request received from the first external electronic device **102**, and may transmit a schedule response (e.g., SCHEDULE RESPONSE), which includes set information on the available frequency band (e.g., 6 GHz) and/or the channel (e.g., CH 101) (e.g., channel information and/or bandwidth information) to set a frequency band of a new data link, to the first external electronic device **102**. The schedule response may include information on an interval in which an available frequency band (e.g., 6 GHz) is used.

(368) In operation **2025**, the electronic device **101** and the first external electronic device **102** may change an existing interval corresponding to 5 GHz CH 36 in the second data link (e.g., NDL 6 GHz CH 101+5 GHz CH 36) to an interval corresponding to the available frequency band (e.g., 6 GHz) and the channel (e.g., CH 101) of the available frequency band (e.g., 6 GHz), and may perform communication via a new third data link (e.g., NDL 6 GHz CH 101).

(369) FIG. **20D** is a diagram illustrating slot configurations of data links of FIGS. **20A**, **20B** and **20C** according to various embodiments.

(370) FIG. **20D** illustrates a slot configuration of a data link through an NDL scheduling operation. A first slot configuration **2031** may be a slot configuration of a data link formed when the electronic device **101** and the fourth external electronic device **1501** are connected and when the electronic device **101** and the first external electronic device **102** are connected. A second slot configuration **2033** may be a slot configuration of a data link formed when a schedule for a new data link is set between the electronic device **101** and the first external electronic device **102** due to a termination of the connection to the fourth external electronic device **1501**.

(371) Referring to the first slot configuration **2031** of FIG. **20D**, when the electronic device **101** is connected to the fourth external electronic device **1501**, the electronic device **101** may perform communication (e.g., NAN communication) based on 5 GHz CH 36 using a second communication protocol concurrently in a slot (or interval) in which communication (e.g., Wi-Fi communication) is performed based on 5 GHz CH 36 using a first communication protocol, and may perform

communication (e.g., NAN communication) based on 6 GHz CH 101 using the second communication protocol in a slot (or interval) in which the first communication protocol is not used. The second data link (e.g., NDL 6 GHz CH 101+5 GHz CH 36) may include 6 GHz CH 101 for 50% and 5 GHz CH 36 for 50%. The maximum performance of the second data link (e.g., NDL 6 GHz CH 101+5 GHz CH 36) may be a sum (e.g., 1250 Mbps) of performance (e.g., 800 Mbps) of NDL 6 GHz CH 101 and performance (e.g., 450 Mbps) of 5 GHz CH 36.

(372) Referring to the second slot configuration **2033** of FIG. **20D**, due to the termination of the first data link (e.g., AP1 5 GHz CH 36), an interval of an available frequency band of the electronic device **101** may be changed from 50% use of 6 GHz CH 101+50% use of 5 GHz CH 36 to 100% use of 6 GHz, 100% use of 5 GHz, or 100% use of 2.4 GHz. The electronic device **101** and the first external electronic device **102** may support all (or both) of NAN 6 GHz, NAN 5 GHz, and NAN 2.4 GHz. NAN 6 GHz may be superior in performance to NAN 5 GHz and NAN 2.4 GHz among frequency bands that may be supported by both the electronic device **101** and the first external electronic device **102**, and accordingly NAN 5 GHz may have a higher priority than that of NAN 6 GHz. A new scheduling operation may be performed between the electronic device **101** and the first external electronic device **102** so that the existing interval corresponding to 5 GHz CH 36 in the second data link (e.g., NDL 6 GHz CH 101+5 GHz CH 36) between the electronic device **101** and the first external electronic device **102** may be changed to a NAN 6 GHz frequency band and that the NAN 6 GHz frequency band may be used. The data link between the electronic device **101** and the first external electronic device **102** may be changed to 100% use of 6 GHz CH 101, and actually measured performance of the changed data link may be about 1600 Mbps.

(373) FIG. **21A** is a diagram illustrating an example in which the scheduling operation of FIG. **18** is performed according to various embodiments.

(374) In FIG. **21A**, it may be assumed that the electronic device **101** is a device of the first type (e.g., a device for supporting frequency bands of 2.4 GHz, 5 GHz, and 6 GHz, and supporting an RSDB) and that the first external electronic device **102** is a device of the second type (e.g., a device for supporting frequency bands of 2.4 GHz and 5 GHz, and supporting an RSDB).

(375) In operation **2101**, a first data link (e.g., AP1 6 GHz CH 101) using a frequency band (e.g., 6 GHz) as a first communication protocol (e.g., Wi-Fi) may be set between the electronic device **101** and the fourth external electronic device **1501**, and a second data link (e.g., NDL 5 GHz CH 149+2.4 GHz CH 6) using both frequency bands of 5 GHz and 2.4 GHz as a second communication protocol (e.g., NAN) may be set between the electronic device **101** and the first external electronic device **102**.

(376) When the first data link (e.g., AP1 6 GHz CH 101) between the electronic device **101** and the fourth external electronic device **1501** is terminated, the electronic device **101** may determine that an available frequency band of the electronic device **101** is changed from 6 GHz 50%+5 GHz 50%+2.4 GHz 50% to 6 GHz 100%+5 GHz 100%+2.4 GHz 100% in operation **2102**. An interval of the available frequency band of the electronic device **101** may be changed from 50% use of 5 GHz CH 149+50% use of 2.4 GHz CH 6 to 100% use of 6 GHz, 100% use of 5 GHz, or 100% use of 2.4 GHz.

(377) In operation **2103**, the electronic device **101** may transmit a schedule request (e.g., SCHEDULE REQUEST) including available frequency band information (e.g., 6 GHz, 5 GHz, and 2.4 GHz) to the first external electronic device **102**. The first external electronic device **102** may use 5 GHz CH 149 for 50% and 2.4 GHz CH 6 for 50% in the second data link (e.g., NDL 5 GHz CH 149+2.4 GHz CH 6). The first external electronic device **102**, which is the device of the second type, may use frequency bands of 5 GHz, and 2.4 GHz. The first external electronic device **102** may select at least one available frequency band (e.g., 5 GHz, and 2.4 GHz) that may be used by both the electronic device **101** and the first external electronic device **102**, based on the available frequency band information (e.g., 6 GHz, 5 GHz, and 2.4 GHz) included in the schedule request received from the electronic device **101**. An available frequency band (e.g., 5 GHz) having a

relatively high priority may be used in an interval of a frequency band (e.g., 2.4 GHz) of the second data link (e.g., NDL 5 GHz CH 149+2.4 GHz CH 6), and accordingly the first external electronic device **102** may select a channel (e.g., CH 149) that may be used by both the electronic device **101** and the first external electronic device **102** in the available frequency band (e.g., 5 GHz), and may transmit a schedule response (e.g., SCHEDULE RESPONSE) including information on the available frequency band (e.g., 5 GHz) and the channel (e.g., CH 149) (e.g., channel information and/or bandwidth information) of the available frequency band (e.g., 5 GHz) to the electronic device **101**. The schedule response may include information on an interval in which the available frequency band (e.g., 5 GHz) is used.

(378) In operation **2104**, the electronic device **101** and the first external electronic device **102** may change an existing interval corresponding to 2.4 GHz CH 6 in the second data link (e.g., NDL 5 GHz CH 149+2.4 GHz CH 6) to an interval corresponding to the available frequency band (e.g., 5 GHz) and the channel (e.g., CH 149) of the available frequency band (e.g., 5 GHz), and may perform communication via a new third data link (e.g., NDL 5 GHz CH **149**).

(379) FIG. **21B** is a diagram illustrating an example in which the scheduling operation of FIG. **18** is performed according to various embodiments.

(380) In FIG. **21B**, it may be assumed that the electronic device **101** is a device of the first type (e.g., a device for supporting frequency bands of 2.4 GHz, 5 GHz, and 6 GHz, and supporting an RSDB) and that the first external electronic device **102** is a device of the second type (e.g., a device for supporting frequency bands of 2.4 GHz and 5 GHz, and supporting an RSDB).

(381) In operation **2111**, a first data link (e.g., AP1 6 GHz CH 101) using a frequency band (e.g., 6 GHz) as a first communication protocol (e.g., Wi-Fi) may be set between the electronic device **101** and the fourth external electronic device **1501**, and a second data link (e.g., NDL 5 GHz CH 149+2.4 GHz CH 6) using both frequency bands of 5 GHz and 2.4 GHz as a second communication protocol (e.g., NAN) may be set between the electronic device **101** and the first external electronic device **102**.

(382) In operation **2112**, the first data link (e.g., AP1 6 GHz CH 101) between the electronic device **101** and the fourth external electronic device **1501** may be terminated.

(383) In operation **2113**, the electronic device **101** may receive a beacon (e.g., a synchronization beacon) or NAF including available frequency band information (e.g., 5 GHz, and 2.4 GHz) of the first external electronic device **102** from the first external electronic device **102**.

(384) In operation **2114**, due to the termination of the first data link (e.g., AP1 6 GHz CH 101), the interval of the available frequency band of the electronic device **101** may be changed from 50% use of 5 GHz CH 149+50% use of 2.4 GHz CH 6 to 100% use of 6 GHz, 100% use of 5 GHz, or 100% use of 2.4 GHz. The electronic device **101** may identify at least one available frequency band (e.g., 5 GHz, and 2.4 GHz) that may be used by both the electronic device **101** and the first external electronic device **102** among available frequency bands (e.g., 5 GHz, and 2.4 GHz) of the first external electronic device **102** and available frequency bands (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the electronic device **101**. The electronic device **101** may compare a frequency band (e.g., 5 GHz, and 2.4 GHz) used in the second data link (e.g., NDL 5 GHz CH 149+2.4 GHz CH 6) to an available frequency band (e.g., 5 GHz, and 2.4 GHz) that may be newly used between the electronic device **101** and the first external electronic device **102** according to priorities. An available frequency band (e.g., 5 GHz) having a relatively high priority may be used in an interval of a frequency band (e.g., 2.4 GHz) of the second data link (e.g., NDL 5 GHz CH 149+2.4 GHz CH 6), and accordingly the electronic device **101** may transmit a schedule request (e.g., SCHEDULE REQUEST) including a new available frequency band (e.g., 5 GHz) and/or a channel (e.g., CH 149) (e.g., channel information and/or bandwidth information) of the available frequency band (e.g., 5 GHz) to the first external electronic device **102** in order to use the new available frequency band (e.g., 5 GHz) in a corresponding interval. The first external electronic device **102** may identify the new available frequency band (e.g., 5 GHz) and/or the channel (e.g., CH 149) of the

available frequency band (e.g., 5 GHz) included in the schedule request received from the electronic device **101**, and may transmit a schedule response (e.g., SCHEDULE RESPONSE), which includes set information on the available frequency band (e.g., 5 GHz) and/or the channel (e.g., CH 149) (e.g., channel information and/or bandwidth information) to set a frequency band of a new data link, to the electronic device **101**. The schedule response may include information on an interval in which the available frequency band (e.g., 5 GHz) is used.

(385) In operation **2115**, the electronic device **101** and the first external electronic device **102** may change an existing interval corresponding to 2.4 GHz CH 6 in the second data link (e.g., NDL 5 GHz CH 149+2.4 GHz CH 6) to an interval corresponding to the available frequency band (e.g., 5 GHz) and the channel (e.g., CH 149) of the available frequency band (e.g., 5 GHz), and may perform communication via a new third data link (e.g., NDL 5 GHz CH 149).

(386) FIG. **21C** is a diagram illustrating an example in which the scheduling operation of FIG. **19** is performed according to various embodiments.

(387) In FIG. **21C**, it may be assumed that the electronic device **101** is a device of the first type (e.g., a device for supporting frequency bands of 2.4 GHz, 5 GHz, and 6 GHz, and supporting an RSDB) and that the first external electronic device **102** is a device of the second type (e.g., a device for supporting frequency bands of 2.4 GHz and 5 GHz, and supporting an RSDB).

(388) In operation **2121**, a first data link (e.g., AP1 6 GHz CH 101) using a frequency band (e.g., 6 GHz) as a first communication protocol (e.g., Wi-Fi) may be set between the electronic device **101** and the fourth external electronic device **1501**, and a second data link (e.g., NDL 5 GHz CH 149+2.4 GHz CH 6) using both frequency bands of 5 GHz and 2.4 GHz as a second communication protocol (e.g., NAN) may be set between the electronic device **101** and the first external electronic device **102**.

(389) In operation **2122**, the first data link (e.g., AP1 6 GHz CH 101) between the electronic device **101** and the fourth external electronic device **1501** may be terminated.

(390) In operation **2123**, due to the termination of the first data link (e.g., AP1 6 GHz CH 101), the interval of the available frequency band of the electronic device **101** may be changed from 50% use of 5 GHz CH 149+50% use of 2.4 GHz CH 6 to 100% use of 6 GHz, 100% use of 5 GHz, or 100% use of 2.4 GHz. The electronic device **101** may transmit a beacon (e.g., a synchronization beacon) or NAF including available frequency band information (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the electronic device **101** to the first external electronic device **102**.

(391) In operation **2124**, the first external electronic device **102** may identify at least one available frequency band (e.g., 5 GHz, and 2.4 GHz) that may be used by both the electronic device **101** and the first external electronic device **102** among available frequency bands (e.g., 5 GHz, and 2.4 GHz) of the first external electronic device **102** and available frequency bands (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the electronic device **101**. The first external electronic device **102** may compare a frequency band (e.g., 5 GHz, and 2.4 GHz) used in the second data link (e.g., NDL 5 GHz CH 149+2.4 GHz CH 6) to an available frequency band (e.g., 5 GHz, and 2.4 GHz) that may be newly used between the electronic device **101** and the first external electronic device **102** according to priorities. An available frequency band (e.g., 5 GHz) having a relatively high priority may be used in an interval of a frequency band (e.g., 2.4 GHz) of the second data link (e.g., NDL 5 GHz CH 149+2.4 GHz CH 6), and accordingly the first external electronic device **102** may transmit a schedule request (e.g., SCHEDULE REQUEST) including a new available frequency band (e.g., 5 GHz) and/or a channel (e.g., CH 149) (e.g., channel information and/or bandwidth information) of the available frequency band (e.g., 5 GHz) to the electronic device **101** in order to use the new available frequency band (e.g., 5 GHz) in a corresponding interval. The electronic device **101** may identify the new available frequency band (e.g., 5 GHz) and/or the channel (e.g., CH 149) of the available frequency band (e.g., 5 GHz) included in the schedule request received from the first external electronic device **102**, and may transmit a schedule response (e.g., SCHEDULE RESPONSE), which includes set information on the available frequency band (e.g., 5 GHz) and/or

the channel (e.g., CH 149) (e.g., channel information and/or bandwidth information) to set a frequency band of a new data link, to the first external electronic device **102**. The schedule response may include information on an interval in which the available frequency band (e.g., 5 GHz) is used.

(392) In operation **2125**, the electronic device **101** and the first external electronic device **102** may change an existing interval corresponding to 2.4 GHz CH 6 in the second data link (e.g., NDL 5 GHz CH 149+2.4 GHz CH 6) to an interval corresponding to the available frequency band (e.g., 5 GHz) and the channel (e.g., CH 149) of the available frequency band (e.g., 5 GHz), and may perform communication via a new third data link (e.g., NDL 5 GHz CH 149).

(393) FIG. **21D** is a diagram illustrating slot configurations of data links of FIGS. **21A**, **21B** and **21C** according to various embodiments.

(394) FIG. **21D** illustrates a slot configuration of a data link through an NDL scheduling operation. A first slot configuration **2131** may be a slot configuration of a data link formed when the electronic device **101** and the fourth external electronic device **1501** are connected and when the electronic device **101** and the first external electronic device **102** are connected. A second slot configuration **2133** may be a slot configuration of a data link formed when a schedule for a new data link is set between the electronic device **101** and the first external electronic device **102** due to a termination of the connection to the fourth external electronic device **1501**.

(395) Referring to the first slot configuration **2131** of FIG. **21D**, when the electronic device **101** is connected to the fourth external electronic device **1501**, the electronic device **101** may perform communication (e.g., NAN communication) based on 2.4 GHz CH 6 using a second communication protocol concurrently in a slot (or interval) in which communication (e.g., Wi-Fi communication) is performed based on 6 GHz CH 101 using a first communication protocol, and may perform communication (e.g., NAN communication) based on 5 GHz CH 149 using the second communication protocol in a slot (or interval) in which the first communication protocol is not used. The second data link (e.g., NDL 5 GHz CH 149+2.4 GHz CH 6) may use 5 GHz CH 149 for 50% and 2.4 GHz CH 6 for 50%. The maximum performance of the second data link (e.g., NDL 5 GHz CH 149+2.4 GHz CH 6) may be a sum (e.g., about 525 Mbps) performance (e.g., about 450 Mbps) of 5 GHz CH 149 and performance (e.g., about 75 Mbps) of 2.4 GHz CH 6.

(396) Referring to the second slot configuration **2133** of FIG. **21D**, due to the termination of the first data link (e.g., AP1 6 GHz CH 101), the interval of the available frequency band of the electronic device **101** may be changed from 50% use of 5 GHz CH 149+50% use of 2.4 GHz CH 6 to 100% use of 6 GHz, 100% use of 5 GHz, or 100% use of 2.4 GHz. The electronic device **101** and the first external electronic device **102** may support both NAN 5 GHz and NAN 2.4 GHz. NAN 5 GHz may be superior in performance to NAN 2.4 GHz among frequency bands that may be supported by both the electronic device **101** and the first external electronic device **102**, and accordingly NAN 5 GHz may have a higher priority than that of NAN 2.4 GHz. A new scheduling operation may be performed between the electronic device **101** and the first external electronic device **102** so that the existing interval corresponding to 2.4 GHz CH 6 in the second data link (e.g., NDL 5 GHz CH 149+2.4 GHz CH 6) between the electronic device **101** and the first external electronic device **102** may be changed to a NAN 5 GHz frequency band and that the NAN 5 GHz frequency band may be used. The data link between the electronic device **101** and the first external electronic device **102** may be changed to 100% use of 5 GHz CH 149, and actually measured performance of the changed data link may be about 900 Mbps.

(397) FIG. **22A** is a diagram illustrating an example in which the scheduling operation of FIG. **18** is performed according to various embodiments.

(398) In FIG. **22A**, it may be assumed that the electronic device **101** is a device of the third type (e.g., a device that supports frequency bands of 2.4 GHz and 5 GHz, and does not support an RSDB) and that the first external electronic device **102** is a device of the first type (e.g., a device for supporting frequency bands of 2.4 GHz, 5 GHz, and 6 GHz, and supporting an RSDB).

(399) In operation **2201**, a first data link (e.g., AP1 2.4 GHz CH 6) using a frequency band (e.g., 2.4 GHz) as a first communication protocol (e.g., Wi-Fi) may be set between the electronic device **101** and the fourth external electronic device **1501**, and a second data link (e.g., NDL 5 GHz CH 149+2.4 GHz CH 6) using both frequency bands of 5 GHz and 2.4 GHz as a second communication protocol (e.g., NAN) may be set between the electronic device **101** and the first external electronic device **102**. It may be difficult for the electronic device **101** in which the first data link (e.g., AP1 2.4 GHz CH 6) with the fourth external electronic device **1501** is formed to fully use a frequency band (e.g., 5 GHz) during setting a data link with the first external electronic device **102**, and the electronic device **101** may form a data link by time division of 5 GHz CH 149 50%+2.4 GHz CH 6 50%.

(400) When the first data link (e.g., AP1 2.4 GHz CH 6) between the electronic device **101** and the fourth external electronic device **1501** is terminated, the electronic device **101** may determine that an available frequency band of the electronic device **101** is changed to 5 GHz+2.4 GHz in operation **2202**. An interval of the available frequency band of the electronic device **101** may be changed from 50% use of 5 GHz CH 149+50% use of 2.4 GHz CH 6 to 100% use of 5 GHz, or 100% use of 2.4 GHz.

(401) In operation **2203**, the electronic device **101** may transmit a schedule request (e.g., SCHEDULE REQUEST) including available frequency band information (e.g., 5 GHz, and 2.4 GHz) to the first external electronic device **102**. The first external electronic device **102** may use 5 GHz CH 149 for 50% and 2.4 GHz CH 6 for 50% in the second data link (e.g., NDL 5 GHz CH 149+2.4 GHz CH 6). The first external electronic device **102**, which is the device of the first type, may use frequency bands of 6 GHz, 5 GHz, and 2.4 GHz. The first external electronic device **102** may select at least one available frequency band (e.g., 5 GHz, and 2.4 GHz) that may be used by both the electronic device **101** and the first external electronic device **102**, based on the available frequency band information (e.g., 5 GHz, and 2.4 GHz) included in the schedule request received from the electronic device **101**. An available frequency band (e.g., 5 GHz) having a relatively high priority may be used in an interval of a frequency band (e.g., 2.4 GHz) of the second data link (e.g., NDL 5 GHz CH 149+2.4 GHz CH 6), and accordingly the first external electronic device **102** may select a channel (e.g., CH 149) that may be used by both the electronic device **101** and the first external electronic device **102** in the available frequency band (e.g., 5 GHz), and may transmit a schedule response (e.g., SCHEDULE RESPONSE) including information on the available frequency band (e.g., 5 GHz) and the channel (e.g., CH 149) (e.g., channel information and/or bandwidth information) of the available frequency band (e.g., 5 GHz) to the electronic device **101**. The schedule response may include information on an interval in which the available frequency band (e.g., 5 GHz) is used.

(402) In operation **2204**, the electronic device **101** and the first external electronic device **102** may change an existing interval corresponding to 2.4 GHz CH 6 in the second data link (e.g., NDL 5 GHz CH 149+2.4 GHz CH 6) to an interval corresponding to the available frequency band (e.g., 5 GHz) and the channel (e.g., CH 149) of the available frequency band (e.g., 5 GHz), and may perform communication via a new third data link (e.g., NDL 5 GHz CH 149).

(403) FIG. **22B** is a diagram illustrating an example in which the scheduling operation of FIG. **18** is performed.

(404) In FIG. **22B**, it may be assumed that the electronic device **101** is a device of the third type (e.g., a device that supports frequency bands of 2.4 GHz and 5 GHz, and does not support an RSDB) and that the first external electronic device **102** is a device of the first type (e.g., a device for supporting frequency bands of 2.4 GHz, 5 GHz, and 6 GHz, and supporting an RSDB).

(405) In operation **2211**, a first data link (e.g., AP1 2.4 GHz CH 6) using a frequency band (e.g., 2.4 GHz) as a first communication protocol (e.g., Wi-Fi) may be set between the electronic device **101** and the fourth external electronic device **1501**, and a second data link (e.g., NDL 5 GHz CH 149+2.4 GHz CH 6) using both frequency bands of 5 GHz and 2.4 GHz as a second

communication protocol (e.g., NAN) may be set between the electronic device **101** and the first external electronic device **102**.

(406) In operation **2212**, the first data link (e.g., AP1 2.4 GHz CH 6) between the electronic device **101** and the fourth external electronic device **1501** may be terminated.

(407) In operation **2213**, the electronic device **101** may receive a beacon (e.g., a synchronization beacon) or NAF including available frequency band information (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the first external electronic device **102** from the first external electronic device **102**.

(408) In operation **2214**, due to the termination of the first data link (e.g., AP1 2.4 GHz CH 6), the interval of the available frequency band of the electronic device **101** may be changed from 50% use of 5 GHz CH 149+50% use of 2.4 GHz CH 6 to 100% use of 5 GHz, or 100% use of 2.4 GHz. The electronic device **101** may identify at least one available frequency band (e.g., 5 GHz, and 2.4 GHz) that may be used by both the electronic device **101** and the first external electronic device **102** among available frequency bands (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the first external electronic device **102** and available frequency bands (e.g., 5 GHz, and 2.4 GHz) of the electronic device **101**. The electronic device **101** may compare a frequency band (e.g., 5 GHz, and 2.4 GHz) used in the second data link (e.g., NDL 5 GHz CH 149+2.4 GHz CH 6) to an available frequency band (e.g., 5 GHz, and 2.4 GHz) that may be newly used between the electronic device **101** and the first external electronic device **102** according to priorities. An available frequency band (e.g., 5 GHz) having a relatively high priority may be used in an interval of a frequency band (e.g., 2.4 GHz) of the second data link (e.g., NDL 5 GHz CH 149+2.4 GHz CH 6), and accordingly the electronic device **101** may transmit a schedule request (e.g., SCHEDULE REQUEST) including a new available frequency band (e.g., 5 GHz) and/or a channel (e.g., CH 149) (e.g., channel information and/or bandwidth information) of the available frequency band (e.g., 5 GHz) to the first external electronic device **102** in order to use the new available frequency band (e.g., 5 GHz) in a corresponding interval. The first external electronic device **102** may identify the new available frequency band (e.g., 5 GHz) and/or the channel (e.g., CH 149) of the available frequency band (e.g., 5 GHz) included in the schedule request received from the electronic device **101**, and may transmit a schedule response (e.g., SCHEDULE RESPONSE), which includes set information on the available frequency band (e.g., 5 GHz) and/or the channel (e.g., CH 149) (e.g., channel information and/or bandwidth information) to set a frequency band of a new data link, to the electronic device **101**. The schedule response may include information on an interval in which the available frequency band (e.g., 5 GHz) is used.

(409) In operation **2215**, the electronic device **101** and the first external electronic device **102** may change an existing interval corresponding to 2.4 GHz CH 6 in the second data link (e.g., NDL 5 GHz CH 149+2.4 GHz CH 6) to an interval corresponding to the available frequency band (e.g., 5 GHz) and the channel (e.g., CH 149) of the available frequency band (e.g., 5 GHz), and may perform communication via a new third data link (e.g., NDL 5 GHz CH 149).

(410) FIG. **22C** is a diagram illustrating an example in which the scheduling operation of FIG. **19** is performed according to various embodiments.

(411) In FIG. **22C**, it may be assumed that the electronic device **101** is a device of the third type (e.g., a device that supports frequency bands of 2.4 GHz and 5 GHz, and does not support an RSDB) and that the first external electronic device **102** is a device of the first type (e.g., a device for supporting frequency bands of 2.4 GHz, 5 GHz, and 6 GHz, and supporting an RSDB).

(412) In operation **2221**, a first data link (e.g., AP1 2.4 GHz CH 6) using a frequency band (e.g., 2.4 GHz) as a first communication protocol (e.g., Wi-Fi) may be set between the electronic device **101** and the fourth external electronic device **1501**, and a second data link (e.g., NDL 5 GHz CH 149+2.4 GHz CH 6) using both frequency bands of 5 GHz and 2.4 GHz as a second communication protocol (e.g., NAN) may be set between the electronic device **101** and the first external electronic device **102**.

(413) In operation **2222**, the first data link (e.g., AP1 2.4 GHz CH 6) between the electronic device

101 and the fourth external electronic device **1501** may be terminated.

(414) In operation **2223**, due to the termination of the first data link (e.g., AP1 2.4 GHz CH 6), the interval of the available frequency band of the electronic device **101** may be changed from 50% use of 5 GHz CH 149+50% use of 2.4 GHz CH 6 to 100% use of 5 GHz, or 100% use of 2.4 GHz. The electronic device **101** may transmit a beacon (e.g., a synchronization beacon) or NAF including available frequency band information (e.g., 5 GHz, and 2.4 GHz) of the electronic device **101** to the first external electronic device **102**.

(415) In operation **2224**, the first external electronic device **102** may identify at least one available frequency band (e.g., 5 GHz, and 2.4 GHz) that may be used by both the electronic device **101** and the first external electronic device **102** among available frequency bands (e.g., 6 GHz, 5 GHz, and 2.4 GHz) of the first external electronic device **102** and available frequency bands (e.g., 5 GHz, and 2.4 GHz) of the electronic device **101**. The first external electronic device **102** may compare a frequency band (e.g., 5 GHz, and 2.4 GHz) used in the second data link (e.g., NDL 5 GHz CH 149+2.4 GHz CH 6) to an available frequency band (e.g., 5 GHz, and 2.4 GHz) that may be newly used between the electronic device **101** and the first external electronic device **102** according to priorities. An available frequency band (e.g., 5 GHz) having a relatively high priority may be used in an interval of a frequency band (e.g., 2.4 GHz) of the second data link (e.g., NDL 5 GHz CH 149+2.4 GHz CH 6), and accordingly the first external electronic device **102** may transmit a schedule request (e.g., SCHEDULE REQUEST) including a new available frequency band (e.g., 5 GHz) and/or a channel (e.g., CH 149) (e.g., channel information and/or bandwidth information) of the available frequency band (e.g., 5 GHz) to the electronic device **101** in order to use the new available frequency band (e.g., 5 GHz) in a corresponding interval. The electronic device **101** may identify the new available frequency band (e.g., 5 GHz) and/or the channel (e.g., CH 149) of the available frequency band (e.g., 5 GHz) included in the schedule request received from the first external electronic device **102**, and may transmit a schedule response (e.g., SCHEDULE RESPONSE), which includes set information on the available frequency band (e.g., 5 GHz) and/or the channel (e.g., CH 149) (e.g., channel information and/or bandwidth information) to set a frequency band of a new data link, to the first external electronic device **102**. The schedule response may include information on an interval in which the available frequency band (e.g., 5 GHz) is used.

(416) In operation **2225**, the electronic device **101** and the first external electronic device **102** may change an existing interval corresponding to 2.4 GHz CH 6 in the second data link (e.g., NDL 5 GHz CH 149+2.4 GHz CH 6) to an interval corresponding to the available frequency band (e.g., 5 GHz) and the channel (e.g., CH 149) of the available frequency band (e.g., 5 GHz), and may perform communication via a new third data link (e.g., NDL 5 GHz CH 149).

(417) FIG. **22D** is a diagram illustrating slot configurations of data links of FIGS. **22A**, **22B** and **22C** according to various embodiments.

(418) FIG. **22D** illustrates a slot configuration of a data link through an NDL scheduling operation. A first slot configuration **2231** may be a slot configuration of a data link formed when the electronic device **101** and the fourth external electronic device **1501** are connected and when the electronic device **101** and the first external electronic device **102** are connected. A second slot configuration **2233** may be a slot configuration of a data link formed when a schedule for a new data link is set between the electronic device **101** and the first external electronic device **102** due to a termination of the connection of the electronic device **101** and the fourth external electronic device **1501**.

(419) Referring to the first slot configuration **2231** of FIG. **22D**, when the electronic device **101** is connected to the fourth external electronic device **1501**, the electronic device **101** may perform communication (e.g., NAN communication) based on 2.4 GHz CH 6 using a second communication protocol concurrently in a slot (or interval) in which communication (e.g., Wi-Fi communication) is performed based on 2.4 GHz CH 6 using a first communication protocol, and

may perform communication (e.g., NAN communication) based on 5 GHz CH 149 using the second communication protocol in a slot (or interval) in which the first communication protocol is not used. The second data link (e.g., NDL 5 GHz CH 149+2.4 GHz CH 6) may use 5 GHz CH 149 for 50% and 2.4 GHz CH 6 for 50%. The maximum performance of the second data link (e.g., NDL 5 GHz CH 149+2.4 GHz CH 6) may be a sum (e.g., about 525 Mbps) performance (e.g., about 450 Mbps) of 5 GHz CH 149 and performance (e.g., about 75 Mbps) of 2.4 GHz CH 6.

(420) Referring to the second slot configuration **2233** of FIG. **22D**, due to the termination of the first data link (e.g., AP1 2.4 GHz CH 6), the electronic device **101** may change the interval of the available frequency band of the electronic device **101** from 50% use of 5 GHz CH 149+50% use of 2.4 GHz CH 6 to 100% use of 5 GHz, or 100% use of 2.4 GHz. The electronic device **101** and the first external electronic device **102** may support both NAN 5 GHz and NAN 2.4 GHz. NAN 5 GHz may be superior in performance to NAN 2.4 GHz among frequency bands that may be supported by both the electronic device **101** and the first external electronic device **102**, and accordingly NAN 5 GHz may have a higher priority than that of NAN 2.4 GHz. A new scheduling operation may be performed between the electronic device **101** and the first external electronic device **102** so that the existing interval corresponding to 2.4 GHz CH 6 in the second data link (e.g., NDL 5 GHz CH 149+2.4 GHz CH 6) between the electronic device **101** and the first external electronic device **102** may be changed to a NAN 5 GHz frequency band and that the NAN 5 GHz frequency band may be used. The data link between the electronic device **101** and the first external electronic device **102** may be changed to 100% use of 5 GHz CH 149, and actually measured performance of the changed data link may be about 900 Mbps.

(421) FIG. **23** is a block diagram illustrating an example electronic device **2301** in a network environment **2300** according to various example embodiments. Referring to FIG. **23**, the electronic device **2301** (e.g., the electronic devices **101**, **102**, **103**, or **104** of FIGS. **1** to **22D**) in the network environment **2300** may communicate with an electronic device **2302** via a first network **2398** (e.g., a short-range wireless communication network), or communicate with at least one of an electronic device **2304** or a server **2308** via a second network **2399** (e.g., a long-range wireless communication network). According to an example embodiment, the electronic device **2301** may communicate with the electronic device **2304** via the server **2308**. According to an example embodiment, the electronic device **2301** may include a processor **2320**, a memory **2330**, an input module **2350**, a sound output module **2355**, a display module **2360**, an audio module **2370**, and a sensor module **2376**, an interface **2377**, a connecting terminal **2378**, a haptic module **2379**, a camera module **2380**, a power management module **2388**, a battery **2389**, a communication module **2390**, a subscriber identification module (SIM) **2396**, or an antenna module **2397**. In various example embodiments, at least one of the components (e.g., the connecting terminal **2378**) may be omitted from the electronic device **2301**, or one or more other components may be added in the electronic device **101**. In various example embodiments, some of the components (e.g., the sensor module **2376**, the camera module **2380**, or the antenna module **2397**) may be integrated as a single component (e.g., the display module **2360**).

(422) The processor **2320** may execute, for example, software (e.g., a program **2340**) to control at least one other component (e.g., a hardware or software component) of the electronic device **2301** connected to the processor **2320**, and may perform various data processing or computation. According to an example embodiment, as at least a part of data processing or computation, the processor **2320** may store a command or data received from another component (e.g., the sensor module **2376** or the communication module **2390**) in a volatile memory **2332**, process the command or the data stored in the volatile memory **2332**, and store resulting data in a non-volatile memory **2334**. According to an example embodiment, the processor **2320** may include a main processor **2321** (e.g., a central processing unit (CPU) or an application processor (AP)), or an auxiliary processor **2323** (e.g., a graphics processing unit (GPU), a neural processing unit (NPU), an image signal processor (ISP), a sensor hub processor, or a communication processor (CP)) that

is operable independently from, or in conjunction with the main processor **2321**. For example, when the electronic device **2301** includes the main processor **2321** and the auxiliary processor **2323**, the auxiliary processor **2323** may be adapted to consume less power than the main processor **2321** or to be specific to a specified function. The auxiliary processor **2323** may be implemented separately from the main processor **2321** or as a part of the main processor **2321**.

(423) The auxiliary processor **2323** may control at least some of functions or states related to at least one (e.g., the display module **2360**, the sensor module **2376**, or the communication module **2390**) of the components of the electronic device **2301**, instead of the main processor **2321** while the main processor **2321** is in an inactive (e.g., sleep) state or along with the main processor **2321** while the main processor **2321** is in an active state (e.g., executing an application). According to an example embodiment, the auxiliary processor **2323** (e.g., an ISP or a CP) may be implemented as a portion of another component (e.g., the camera module **2380** or the communication module **2390**) that is functionally related to the auxiliary processor **2323**. According to an example embodiment, the auxiliary processor **2323** (e.g., an NPU) may include a hardware structure specified for artificial intelligence model processing. An artificial intelligence model may be generated by machine learning. Such learning may be performed by, for example, the electronic device **2301** in which artificial intelligence is performed, or performed via a separate server (e.g., the server **2308**). Learning algorithms may include, but are not limited to, for example, supervised learning, unsupervised learning, semi-supervised learning, or reinforcement learning. The AI model may include a plurality of artificial neural network layers. An artificial neural network may include, for example, a deep neural network (DNN), a convolutional neural network (CNN), a recurrent neural network (RNN), a restricted Boltzmann machine (RBM), a deep belief network (DBN), and a bidirectional recurrent deep neural network (BRDNN), a deep Q-network, or a combination of two or more thereof, but is not limited thereto. The AI model may additionally or alternatively include a software structure other than the hardware structure.

(424) The memory **2330** may store various data used by at least one component (e.g., the processor **2320** or the sensor module **2376**) of the electronic device **2301**. The various data may include, for example, software (e.g., the program **2340**) and input data or output data for a command related thereto. The memory **2330** may include the volatile memory **2332** or the non-volatile memory **2334**.

(425) The program **2340** may be stored as software in the memory **2330**, and may include, for example, an operating system (OS) **2342**, middleware **2344**, or an application **2346**.

(426) The input module **2350** may receive a command or data to be used by another component (e.g., the processor **2320**) of the electronic device **2301**, from the outside (e.g., a user) of the electronic device **2301**. The input module **2350** may include, for example, a microphone, a mouse, a keyboard, a key (e.g., a button), or a digital pen (e.g., a stylus pen).

(427) The sound output module **2355** may output a sound signal to the outside of the electronic device **2301**. The sound output module **2355** may include, for example, a speaker or a receiver. The speaker may be used for general purposes, such as playing multimedia or playing record. The receiver may be used to receive an incoming call. According to an example embodiment, the receiver may be implemented separately from the speaker or as a part of the speaker.

(428) The display module **2360** may visually provide information to the outside (e.g., a user) of the electronic device **2301**. The display module **2360** may include, for example, a control circuit for controlling a display, a hologram device, or a projector and control circuitry to control a corresponding one of the display, the hologram device, and the projector. According to an example embodiment, the display module **2360** may include a touch sensor adapted to detect a touch, or a pressure sensor adapted to measure the intensity of force incurred by the touch.

(429) The audio module **2370** may convert a sound into an electric signal or vice versa. According to an example embodiment, the audio module **2370** may obtain the sound via the input module **2350** or output the sound via the sound output module **2355** or an external electronic device (e.g.,

the electronic device **2302** such as a speaker or a headphone) directly or wirelessly connected to the electronic device **2301**.

(430) The sensor module **2376** may detect an operational state (e.g., power or temperature) of the electronic device **2301** or an environmental state (e.g., a state of a user) external to the electronic device **2301**, and generate an electrical signal or data value corresponding to the detected state. According to an example embodiment, the sensor module **2376** may include, for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a proximity sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor.

(431) The interface **2377** may support one or more specified protocols to be used for the electronic device **2301** to be coupled with the external electronic device (e.g., the electronic device **2302**) directly (e.g., wiredly) or wirelessly. According to an example embodiment, the interface **2377** may include, for example, a high-definition multimedia interface (HDMI), a universal serial bus (USB) interface, a secure digital (SD) card interface, or an audio interface.

(432) The connecting terminal **2378** may include a connector via which the electronic device **2301** may be physically connected to an external electronic device (e.g., the electronic device **2302**). According to an example embodiment, the connecting terminal **2378** may include, for example, an HDMI connector, a USB connector, an SD card connector, or an audio connector (e.g., a headphone connector).

(433) The haptic module **2379** may convert an electric signal into a mechanical stimulus (e.g., a vibration or a movement) or an electrical stimulus which may be recognized by a user via his or her tactile sensation or kinesthetic sensation. According to an example embodiment, the haptic module **2379** may include, for example, a motor, a piezoelectric element, or an electric stimulator.

(434) The camera module **2380** may capture a still image and moving images. According to an example embodiment, the camera module **2380** may include one or more lenses, image sensors, image signal processors, or flashes.

(435) The power management module **2388** may manage power supplied to the electronic device **2301**. According to an example embodiment, the power management module **2388** may be implemented as, for example, at least a part of a power management integrated circuit (PMIC).

(436) The battery **2389** may supply power to at least one component of the electronic device **2301**. According to an example embodiment, the battery **2389** may include, for example, a primary cell which is not rechargeable, a secondary cell which is rechargeable, or a fuel cell.

(437) The communication module **2390** may support establishing a direct (e.g., wired) communication channel or a wireless communication channel between the electronic device **2301** and the external electronic device (e.g., the electronic device **2302**, the electronic device **2304**, or the server **2308**) and performing communication via the established communication channel. The communication module **2390** may include one or more communication processors that are operable independently of the processor **2320** (e.g., an AP) and that support a direct (e.g., wired) communication or a wireless communication. According to an example embodiment, the communication module **2390** may include a wireless communication module **2392** (e.g., a cellular communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS) communication module) or a wired communication module **2394** (e.g., a local area network (LAN) communication module, or a power line communication (PLC) module). A corresponding one of these communication modules may communicate with the external electronic device **2304** via the first network **2398** (e.g., a short-range communication network, such as Bluetooth™, wireless-fidelity (Wi-Fi) direct, or infrared data association (IrDA)) or the second network **2399** (e.g., a long-range communication network, such as a legacy cellular network, a 5G network, a next-generation communication network, the Internet, or a computer network (e.g., a LAN or a wide region network (WAN))). These various types of communication modules may be implemented as a single component (e.g., a single chip), or may be implemented as multi

components (e.g., multi chips) separate from each other. The wireless communication module **2392** may identify and authenticate the electronic device **2301** in a communication network, such as the first network **2398** or the second network **2399**, using subscriber information (e.g., international mobile subscriber identity (IMSI)) stored in the SIM **2396**. The wireless communication module **2392** may support a first communication protocol (e.g., Wi-Fi) and a second communication protocol (e.g., NAN). The first communication protocol may support a communication operation other than the NAN communication operation, and the second communication protocol may support the NAN communication operation.

(438) The wireless communication module **2392** may support a 5G network after a 4G network, and next-generation communication technology, e.g., new radio (NR) access technology. The NR access technology may support enhanced mobile broadband (eMBB), massive machine type communications (mMTC), or ultra-reliable and low-latency communications (URLLC). The wireless communication module **2392** may support a high-frequency band (e.g., a mmWave band) to achieve, e.g., a high data transmission rate. The wireless communication module **2392** may support various technologies for securing performance on a high-frequency band, such as, e.g., beamforming, massive multiple-input and multiple-output (MIMO), full dimensional MIMO (FD-MIMO), an array antenna, analog beam-forming, or a large scale antenna. The wireless communication module **2392** may support various requirements specified in the electronic device **2301**, an external electronic device (e.g., the electronic device **2304**), or a network system (e.g., the second network **2399**). According to an example embodiment, the wireless communication module **2392** may support a peak data rate (e.g., 20 Gbps or more) for implementing eMBB, loss coverage (e.g., 164 dB or less) for implementing mMTC, or U-plane latency (e.g., 0.5 ms or less for each of downlink (DL) and uplink (UL), or a round trip of 1 ms or less) for implementing URLLC.

(439) The antenna module **2397** may transmit or receive a signal or power to or from the outside (e.g., the external electronic device) of the electronic device **101**. According to an example embodiment, the antenna module **2397** may include an antenna including a radiating element including a conductive material or a conductive pattern formed in or on a substrate (e.g., a printed circuit board (PCB)). According to an example embodiment, the antenna module **2397** may include a plurality of antennas (e.g., array antennas). In such a case, at least one antenna appropriate for a communication scheme used in a communication network, such as the first network **2398** or the second network **2399**, may be selected by, for example, the communication module **2390** from the plurality of antennas. The signal or the power may be transmitted or received between the communication module **2390** and the external electronic device via the at least one selected antenna. According to an example embodiment, another component (e.g., a radio frequency integrated circuit (RFIC)) other than the radiating element may be additionally formed as a part of the antenna module **2397**.

(440) According to various example embodiments, the antenna module **2397** may form a mmWave antenna module. According to an example embodiment, the mmWave antenna module may include a printed circuit board, an RFIC disposed on a first surface (e.g., the bottom surface) of the printed circuit board, or adjacent to the first surface and capable of supporting a designated high-frequency band (e.g., the mmWave band), and a plurality of antennas (e.g., array antennas) disposed on a second surface (e.g., the top or a side surface) of the printed circuit board, or adjacent to the second surface and capable of transmitting or receiving signals of the designated high-frequency band.

(441) At least some of the above-described components may be coupled mutually and communicate signals (e.g., commands or data) therebetween via an inter-peripheral communication scheme (e.g., a bus, general purpose input and output (GPIO), serial peripheral interface (SPI), or mobile industry processor interface (MIPI)).

(442) According to an example embodiment, commands or data may be transmitted or received between the electronic device **2301** and the external electronic device **2304** via the server **2308** coupled with the second network **2399**. Each of the external electronic devices **2302** or **2304** may

be a device of the same type as or a different type from the electronic device **2301**. According to an example embodiment, all or some of operations to be executed by the electronic device **2301** may be executed at one or more external electronic devices (e.g., the external devices **2302** and **2304**, and the server **2308**). For example, if the electronic device **2301** needs to perform a function or a service automatically, or in response to a request from a user or another device, the electronic device **2301**, instead of, or in addition to, executing the function or the service, may request the one or more external electronic devices to perform at least part of the function or the service. The one or more external electronic devices receiving the request may perform the at least part of the function or the service requested, or an additional function or an additional service related to the request, and may transfer an outcome of the performing to the electronic device **2301**. The electronic device **2301** may provide the outcome, with or without further processing of the outcome, as at least part of a reply to the request. To that end, a cloud computing, distributed computing, mobile edge computing (MEC), or client-server computing technology may be used, for example. The electronic device **2301** may provide ultra low-latency services using, e.g., distributed computing or mobile edge computing. In an example embodiment, the external electronic device **2304** may include an Internet-of-things (IoT) device. The server **2308** may be an intelligent server using machine learning and/or a neural network. According to an example embodiment, the external electronic device **2304** or the server **2308** may be included in the second network **2399**. The electronic device **2301** may be applied to intelligent services (e.g., smart home, smart city, smart car, or healthcare) based on 5G communication technology or IoT-related technology.

(443) The electronic devices according to various example embodiments may be various types of electronic devices. The electronic device may include, for example, a portable communication device (e.g., a smartphone), a computer device, a portable multimedia device, a portable medical device, a camera, a wearable device, a home appliance device, or the like. According to an example embodiment of the disclosure, the electronic device is not limited to those described above.

(444) It should be appreciated that various example embodiments of the present disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular example embodiments and include various changes, equivalents, or replacements for a corresponding example embodiment. In connection with the description of the drawings, like reference numerals may be used for similar or related components. It is to be understood that a singular form of a noun corresponding to an item may include one or more of the things, unless the relevant context clearly indicates otherwise. As used herein, “A or B”, “at least one of A and B”, “at least one of A or B”, “A, B or C”, “at least one of A, B and C”, and “A, B, or C,” each of which may include any one of the items listed together in the corresponding one of the phrases, or all possible combinations thereof. Terms such as “first”, “second”, or “first” or “second” may simply be used to distinguish the component from other components in question, and do not limit the components in other aspects (e.g., importance or order). It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively”, as “coupled with,” “coupled to,” “connected with,” or “connected to” another element (e.g., a second element), the element may be coupled with the other element directly (e.g., wiredly), wirelessly, or via a third element.

(445) As used in connection with various example embodiments of the disclosure, the term “module” may include a unit implemented in hardware, software, or firmware, or any combination thereof, and may interchangeably be used with other terms, for example, “logic,” “logic block,” “part,” or “circuitry”. A module may be a single integral component, or a minimum unit or part thereof, adapted to perform one or more functions. For example, according to an example embodiment, the module may be implemented in a form of an application-specific integrated circuit (ASIC).

(446) Various example embodiments as set forth herein may be implemented as software (e.g., the

program **2340**) including one or more instructions that are stored in a storage medium (e.g., the internal memory **2336** or the external memory **2338**) that is readable by a machine (e.g., the electronic device **2301**) For example, a processor (e.g., the processor **2320**) of the machine (e.g., the electronic device **2301**) may invoke at least one of the one or more instructions stored in the storage medium, and execute it. This allows the machine to be operated to perform at least one function according to the at least one instruction invoked. The one or more instructions may include a code generated by a compiler or a code executable by an interpreter. The machine-readable storage medium may be provided in the form of a non-transitory storage medium. Here, the “non-transitory” storage medium is a tangible device, and may not include a signal (e.g., an electromagnetic wave), but this term does not differentiate between where data is semi-permanently stored in the storage medium and where the data is temporarily stored in the storage medium.

(447) According to an example embodiment, a method according to various example embodiments of the disclosure may be included and provided in a computer program product. The computer program product may be traded as a product between a seller and a buyer. The computer program product may be distributed in the form of a machine-readable storage medium (e.g., compact disc read-only memory (CD-ROM)), or be distributed (e.g., downloaded or uploaded) online via an application store (e.g., PlayStore™), or between two user devices (e.g., smartphones) directly. If distributed online, at least part of the computer program product may be temporarily generated or at least temporarily stored in the machine-readable storage medium, such as memory of the manufacturer's server, a server of the application store, or a relay server.

(448) According to various example embodiments, each component (e.g., a module or a program) of the above-described components may include a single entity or multiple entities, and some of the multiple entities may be separately disposed in different components. According to various example embodiments, one or more of the above-described components may be omitted, or one or more other components may be added. Alternatively or additionally, a plurality of components (e.g., modules or programs) may be integrated into a single component. In such a case, according to various example embodiments, the integrated component may still perform one or more functions of each of the plurality of components in the same or similar manner as they are performed by a corresponding one of the plurality of components before the integration. According to various example embodiments, operations performed by the module, the program, or another component may be carried out sequentially, in parallel, repeatedly, or heuristically, or one or more of the operations may be executed in a different order or omitted, or one or more other operations may be added.

(449) An electronic device (e.g., the electronic device **2301** of FIG. **23**) according to various example embodiments may include: at least one wireless communication module (e.g., the wireless communication module **2392** of FIG. **23**) comprising wireless communication circuitry configured to support a first communication protocol and a second communication protocol, at least one processor (e.g., the processor **2320** of FIG. **23**) operatively connected to the wireless communication module, and a memory (e.g., the memory **2330** of FIG. **23**) electrically connected to the processor and configured to store instructions executable by the processor. When the instructions are executed by the processor, the processor may be configured to: using the wireless communication module, set a schedule for a first data link that uses a first frequency band as the second communication protocol with a first external electronic device (e.g., operation **710** of FIG. **7**), set a schedule for a second data link that uses a second frequency band as the second communication protocol with a second external electronic device (e.g., operation **720** of FIG. **7**), and change the second data link to a third data link that uses a third frequency band and perform communication with the second external electronic device based on the third frequency band being available due to a termination of the first data link (e.g., operation **730** of FIG. **7**).

(450) According to various example embodiments, the first communication protocol may support a

communication operation other than a neighbor awareness networking (NAN) communication operation, and the second communication protocol may support a NAN communication operation. (451) According to various example embodiments, the third frequency band may include an available frequency band having a higher priority than that of the second frequency band among one or more available frequency bands available by both the electronic device and the second external electronic device.

(452) According to various example embodiments, at least one of information on the third frequency band and an available frequency band available by the electronic device may be included in at least one of a NAN availability attribute and an unaligned schedule attribute.

(453) According to various example embodiments, the processor may be configured to control the electronic device to transmit, to the second external electronic device, a schedule request including information on an available frequency band available by the electronic device for setting a schedule for the third data link in response to the termination of the first data link.

(454) According to various example embodiments, the processor may be configured to: obtain information on an available frequency band available by the second external electronic device from the second external electronic device, select an available frequency band having a higher priority than a priority of the second frequency band from among one or more available frequency bands available by both the electronic device and the second external electronic device, based on the information on the available frequency band, and control the electronic device to transmit a schedule request including information on the available frequency band having the higher priority than the priority of the second frequency band to the second external electronic device.

(455) According to various example embodiments, the processor may be configured to control the electronic device to: transmit information on an available frequency band available by the electronic device to the second external electronic device, in response to the termination of the first data link, and receive a schedule request including information on an available frequency band having a higher priority than the priority of the second frequency band among one or more available frequency bands available by both the electronic device and the second external electronic device from the second external electronic device.

(456) According to various example embodiments, the processor may be configured to control the electronic device to receive at least one of a beacon and a NAN action frame (NAF) including information on the available frequency band available by the second external electronic device from the second external electronic device.

(457) According to various example embodiments, the processor may be configured to: include the information on the available frequency band available by the electronic device in at least one of a beacon and a NAF and transmit at least one of the beacon and the NAF including the information on the available frequency band available by the electronic device to the second external electronic device.

(458) An electronic device (e.g., the electronic device **2301** of FIG. **23**) according to various example embodiments may include at least one wireless communication module (e.g., the wireless communication module **2392** of FIG. **23**) comprising wireless communication circuitry configured to support a first communication protocol and a second communication protocol, at least one processor (e.g., the processor **2320** of FIG. **23**) operatively connected to the wireless communication module, and a memory (e.g., the memory **2330** of FIG. **23**) electrically connected to the processor and configured to store instructions executable by the processor. When the instructions are executed by the processor, the processor may be configured to: using the wireless communication module, set a schedule for a first data link that uses a first frequency band as the first communication protocol with a first external electronic device (e.g., operation **1610** of FIG. **16**), set a schedule for a second data link that uses both the first frequency band and a second frequency band as the second communication protocol with a second external electronic device (e.g., operation **1620** of FIG. **16**), and change the second data link to a third data link that uses an

interval of a frequency band having a lower priority between the first frequency band and the second frequency band as an interval of a third frequency band and perform communication with the second external electronic device, based on an interval of a frequency band used in the second data link being changeable due to a termination of the first data link (e.g., operation **1630** of FIG. **16**).

(459) According to various example embodiments, the first communication protocol may support a communication operation other than a neighbor aware networking (NAN) communication operation, and the second communication protocol may support a NAN communication operation.

(460) According to various example embodiments, the third frequency band may be an available frequency band having a higher priority than a priority of a frequency band used in the second data link among one or more available frequency bands available by both the electronic device and the second external electronic device.

(461) According to various example embodiments, at least one of information on the third frequency band and an available frequency band available by the electronic device may be included in at least one of a NAN availability attribute and an unaligned schedule attribute.

(462) According to various example embodiments, the processor may be configured to control the electronic device to transmit, to the second external electronic device, a schedule request including information on an available frequency band available by the electronic device for setting a schedule for the third data link in response to the termination of the first data link.

(463) According to various example embodiments, the processor may be configured to: obtain information on an available frequency band available by the second external electronic device from the second external electronic device, select an available frequency band having a higher priority than a priority of a frequency band used in the second data link from among one or more available frequency bands available by both the electronic device and the second external electronic device, based on the information on the available frequency band, and control the electronic device to transmit a schedule request including information on the available frequency band having the higher priority than that of the frequency band used in the second data link to the second external electronic device.

(464) According to various example embodiments, the processor may be configured to control the electronic device to: transmit information on an available frequency band available by the electronic device to the second external electronic device, in response to the termination of the first data link, and receive a schedule request including information on an available frequency band having a higher priority than a priority of a frequency band used in the second data link among one or more available frequency bands available by both the electronic device and the second external electronic device from the second external electronic device.

(465) According to various example embodiments, the processor may be configured to receive at least one of a beacon and a NAF including information on the available frequency band available by the second external electronic device from the second external electronic device.

(466) According to various example embodiments, the processor may be configured to include the information on the available frequency band available by the electronic device in at least one of a beacon and a NAN action frame (NAF) and transmit at least one of the beacon and the NAF including the information on the available frequency band available by the electronic device to the second external electronic device.

(467) A method of operating an electronic device (e.g., the electronic device **2301** of FIG. **23**) according to various example embodiments may include: (e.g., operation **710** of FIG. **7**) setting a schedule for a first data link that uses a first frequency band as a second communication protocol with a first external electronic device, (e.g., operation **720** of FIG. **7**) setting a schedule for a second data link that uses a second frequency band as the second communication protocol with a second external electronic device, and (e.g., operation **730** of FIG. **7**) changing the second data link to a third data link that uses a third frequency band and performing communication with the second

external electronic device based on the third frequency band being available due to a termination of the first data link.

(468) An electronic device (e.g., the electronic device **2301** of FIG. **23**) according to various example embodiments may include at least one wireless communication module (e.g., the wireless communication module **2392** of FIG. **23**) comprising wireless communication circuitry configured to support a first communication protocol and a second communication protocol, at least one processor (e.g., the processor **2320** of FIG. **23**) operatively connected to the wireless communication module, and a memory (e.g., the memory **2330** of FIG. **23**) electrically connected to the processor and configured to store instructions executable by the processor. When the instructions are executed by the processor, the processor may be configured to: using the wireless communication module, set a schedule for a first data link that uses a first frequency band as the first communication protocol with a first external electronic device (e.g., operation **710** of FIG. **7**), set a schedule for a second data link that uses a second frequency band as the second communication protocol with a second external electronic device (e.g., operation **720** of FIG. **7**), and change the second data link to a third data link that uses a third frequency band and perform communication with the second external electronic device based on the third frequency band being available due to a termination of the first data link (e.g., operation **730** of FIG. **7**).

(469) While the disclosure has been illustrated and described with reference to various example embodiments, it will be understood that the various example embodiments are intended to be illustrative, not limiting. It will be further understood by those skilled in the art that various changes in form and detail may be made without departing from the true spirit and full scope of the disclosure, including the appended claims and their equivalents. It will also be understood that any of the embodiment(s) described herein may be used in conjunction with any other embodiment(s) described herein.

Claims

1. An electronic device, comprising: at least one wireless communication module comprising wireless communication circuitry; at least one processor, comprising processor circuitry, operatively connected to the wireless communication module; and a memory electrically connected to the at least one processor and configured to store instructions executable by the processor, wherein when the instructions are executed by the at least one processor, the at least one processor is configured, using the wireless communication module, to: set a schedule for a first data link that uses a first frequency band with a first external electronic device; set a schedule for a second data link that uses a second frequency band with a second external electronic device; and change the second data link to a third data link that uses a third frequency band and perform communication with the second external electronic device, based on the third frequency band being available due to a termination of a connection on the first data link.
2. The electronic device of claim 1, wherein one of the first data link and the second data link uses a first communication protocol and the other of the first data link and the second data link uses a second communication protocol; the first communication protocol supports a communication operation other than a neighbor awareness networking (NAN) communication operation, and the second communication protocol supports the NAN communication operation.
3. The electronic device of claim 1, wherein the third frequency band is an available frequency band having a higher priority than a priority of the second frequency band among one or more available frequency bands available by both the electronic device and the second external electronic device.
4. The electronic device of claim 3, wherein at least one of information on the third frequency band and an available frequency band available by the electronic device is included in at least one of a neighbor awareness networking (NAN) availability attribute and an unaligned schedule

attribute.

5. The electronic device of claim 1, wherein the at least one processor is configured to control the electronic device to transmit, to the second external electronic device, a schedule request including information on an available frequency band available by the electronic device for setting a schedule for the third data link in response to the termination of the connection on the first data link.
6. The electronic device of claim 1, wherein the at least one processor is configured to: obtain information on an available frequency band available by the second external electronic device from the second external electronic device; select an available frequency band having a higher priority than a priority of the second frequency band from among one or more available frequency bands available by both the electronic device and the second external electronic device, based on the information on the available frequency band; and control the electronic device to transmit a schedule request including information on the available frequency band having the higher priority than that of the second frequency band to the second external electronic device.
7. The electronic device of claim 6, wherein the at least one processor is configured to receive at least one of a beacon and a neighbor awareness networking (NAN) action frame (NAF) including information on the available frequency band available by the second external electronic device from the second external electronic device.
8. The electronic device of claim 1, wherein the at least one processor is configured to: control the electronic device to transmit information on an available frequency band available by the electronic device to the second external electronic device, in response to the termination of the connection on the first data link; and control the electronic device to receive a schedule request including information on an available frequency band having a higher priority than a priority of the second frequency band among one or more available frequency bands available by both the electronic device and the second external electronic device from the second external electronic device.
9. The electronic device of claim 8, wherein the at least one processor is configured to: include the information on the available frequency band available by the electronic device in at least one of a beacon and a NAF and control the electronic device to transmit at least one of the beacon and the NAF including the information on the available frequency band available by the electronic device to the second external electronic device.
10. An electronic device, comprising: at least one wireless communication module comprising wireless communication circuitry; at least one processor comprising processor circuitry operatively connected to the wireless communication module; and a memory electrically connected to the at least one processor and configured to store instructions executable by the processor, wherein when the instructions are executed by the at least one processor, the at least one processor is configured, using the wireless communication module, to: set a schedule for a first data link that uses a first frequency band with a first external electronic device; set a schedule for a second data link that uses both the first frequency band and a second frequency band with a second external electronic device; and change the second data link to a third data link that uses an interval of a frequency band having a lower priority between the first frequency band and the second frequency band as an interval of a third frequency band, and perform communication with the second external electronic device, based on an interval of a frequency band used in the second data link being changeable due to a termination of a connection on the first data link.
11. The electronic device of claim 10, wherein one of the first data link and the second data link uses a first communication protocol and the other of the first data link and the second data link uses a second communication protocol; the first communication protocol supports a communication operation other than a neighbor awareness networking (NAN) communication operation, and the second communication protocol supports the NAN communication operation.
12. The electronic device of claim 10, wherein the third frequency band is an available frequency band having a higher priority than a priority of a frequency band used in the second data link among one or more available frequency bands available by both the electronic device and the

second external electronic device.

13. The electronic device of claim 12, wherein at least one of information on the third frequency band and an available frequency band available by the electronic device is included in at least one of a neighbor awareness networking (NAN) availability attribute and an unaligned schedule attribute.

14. The electronic device of claim 10, wherein the at least one processor is configured to control the electronic device to transmit a schedule request including information on an available frequency band available by the electronic device for setting a schedule of the third data link to the second external electronic device, in response to the termination of the connection on the first data link.

15. The electronic device of claim 10, wherein the at least one processor is configured to: obtain information on an available frequency band available by the second external electronic device from the second external electronic device; select an available frequency band having a higher priority than a priority of a frequency band used in the second data link from among one or more available frequency bands available by both the electronic device and the second external electronic device, based on the information on the available frequency band; and control the electronic device to transmit a schedule request including information on the available frequency band having the higher priority than the priority of the frequency band used in the second data link to the second external electronic device.

16. The electronic device of claim 15, wherein the at least one processor is configured to control the electronic device to receive at least one of a beacon and a neighbor awareness networking (NAN) action frame (NAF) including information on the available frequency band available by the second external electronic device from the second external electronic device.

17. The electronic device of claim 10, wherein the at least one processor is configured to: control the electronic device to transmit information on an available frequency band available by the electronic device to the second external electronic device, in response to the termination of the connection on the first data link; and control the electronic device to receive a schedule request including information on an available frequency band having a higher priority than a priority of a frequency band used in the second data link among one or more available frequency bands available by both the electronic device and the second external electronic device from the second external electronic device.

18. The electronic device of claim 17, wherein the at least one processor is configured to: include the information on the available frequency band available by the electronic device in at least one of a beacon and a neighbor awareness networking (NAF) and control the electronic device to transmit at least one of the beacon and the NAF including the information on the available frequency band available by the electronic device to the second external electronic device.

19. A method of operating an electronic device, the method comprising: setting a schedule for a first data link that uses a first frequency band with a first external electronic device; setting a schedule for a second data link that uses a second frequency band with a second external electronic device; and changing the second data link to a third data link that uses a third frequency band and performing communication with the second external electronic device, based on the third frequency band being available due to a termination of a connection on the first data link.
