

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402905
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Levy; Elad et al.

Serrated ultrasonic cutting blade with varied tooth pitch

Abstract

An ultrasonic blade is provided along a convexly arcuate distal edge and at least one longitudinal edge with a continuous array of teeth including a first subset of teeth along the convexly arcuate distal edge and a second subset of teeth along the at least one straight longitudinal edge. The teeth along the convexly arcuate distal edge differ in tooth length and optionally in inter-tooth separation or pitch from the teeth along one or both of the longitudinal edges.

Inventors: Levy; Elad (Amherst, NY), O'Connor; Timothy (Boca Raton, FL), Voic; Dan (Cedar Grove, NJ)

Applicant: Misonix, LLC (Farmingdale, NY)

Family ID: 85176257

Assignee: Misonix, LLC (Farmingdale, NY)

Appl. No.: 17/402295

Filed: August 13, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20230048993 A1	Feb. 16, 2023

Publication Classification

Int. Cl.: A61B17/32 (20060101)

U.S. Cl.:

CPC A61B17/320068 (20130101); A61B2017/320077 (20170801)

Field of Classification Search

CPC: A61B (2017/32006); A61B (17/14); A61B (17/142); A61B (17/144); A61B (17/149); A61B (17/01); B27B (19/008); B27B (19/006)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2349959	12/1943	Edward	N/A	N/A
2753666	12/1955	Sasse	N/A	N/A
3368280	12/1967	Friedman et al.	N/A	N/A
3680610	12/1971	Lindgren	30/502	B23D 1/126
3805787	12/1973	Banko	N/A	N/A
4188952	12/1979	Loschilov et al.	N/A	N/A
4425115	12/1983	Wuchinich	N/A	N/A
4804364	12/1988	Dieras et al.	N/A	N/A
4988334	12/1990	Hornlein et al.	N/A	N/A
5163433	12/1991	Kagawa et al.	N/A	N/A
5176677	12/1992	Wuchinich	N/A	N/A
5180363	12/1992	Idemoto et al.	N/A	N/A
5222937	12/1992	Kagawa	N/A	N/A
5261922	12/1992	Hood	N/A	N/A
5312329	12/1993	Beaty et al.	N/A	N/A
5342380	12/1993	Hood	N/A	N/A
5465468	12/1994	Manna	N/A	N/A
5484398	12/1995	Stoddard	N/A	N/A
5517889	12/1995	Logan	N/A	N/A
5527273	12/1995	Manna et al.	N/A	N/A
5531597	12/1995	Foulkes et al.	N/A	N/A
5769211	12/1997	Manna et al.	N/A	N/A
5906595	12/1998	Powell et al.	N/A	N/A
5935142	12/1998	Hood	N/A	N/A
5935143	12/1998	Hood	N/A	N/A
5976105	12/1998	Marcove et al.	N/A	N/A
6036667	12/1999	Manna et al.	N/A	N/A
6256859	12/2000	Stoddard et al.	N/A	N/A
6270471	12/2000	Hechel et al.	N/A	N/A
6352532	12/2001	Kramer et al.	N/A	N/A
6375648	12/2001	Edelman et al.	N/A	N/A
6379371	12/2001	Novak et al.	N/A	N/A
6436114	12/2001	Novak et al.	N/A	N/A
6454730	12/2001	Hechel et al.	N/A	N/A
6461314	12/2001	Pant et al.	N/A	N/A
6492762	12/2001	Pant et al.	N/A	N/A
6494714	12/2001	Copeland	N/A	N/A
6582440	12/2002	Brumbach	N/A	N/A

6602248	12/2002	Sharps et al.	N/A	N/A
6613056	12/2002	Brumbach et al.	N/A	N/A
6736814	12/2003	Manna et al.	N/A	N/A
6799729	12/2003	Voic	N/A	N/A
6869439	12/2004	White et al.	N/A	N/A
7025735	12/2005	Soring et al.	N/A	N/A
7223267	12/2006	Isola et al.	N/A	N/A
7431704	12/2007	Babaev	N/A	N/A
7442168	12/2007	Novak et al.	N/A	N/A
7494488	12/2008	Weber	N/A	N/A
7522955	12/2008	Rontal	N/A	N/A
7608054	12/2008	Söring et al.	N/A	N/A
7717913	12/2009	Novak et al.	N/A	N/A
7776027	12/2009	Manna et al.	N/A	N/A
7785278	12/2009	Babaev	N/A	N/A
D627463	12/2009	Voic et al.	N/A	N/A
7905854	12/2010	Hazut et al.	N/A	N/A
7931611	12/2010	Novak et al.	N/A	N/A
D644326	12/2010	Voic et al.	N/A	N/A
8025672	12/2010	Novak et al.	N/A	N/A
8109925	12/2011	Voic et al.	N/A	N/A
8221424	12/2011	Cha	N/A	N/A
D667117	12/2011	Darian et al.	N/A	N/A
8343178	12/2012	Novak et al.	N/A	N/A
8348880	12/2012	Messerly et al.	N/A	N/A
8353912	12/2012	Darian et al.	N/A	N/A
8430897	12/2012	Novak et al.	N/A	N/A
8562547	12/2012	Babaev	N/A	N/A
8659208	12/2013	Rose et al.	N/A	N/A
8690783	12/2013	Sinelnikov	N/A	N/A
8698377	12/2013	Sinelnikov	N/A	N/A
8814870	12/2013	Paraschiv et al.	N/A	N/A
8888783	12/2013	Young	N/A	N/A
8894673	12/2013	Darian	N/A	N/A
8961547	12/2014	Dietz et al.	N/A	N/A
9211137	12/2014	Voic	N/A	N/A
9226767	12/2015	Stulen et al.	N/A	N/A
9320528	12/2015	Voic et al.	N/A	N/A
9387005	12/2015	Voic	N/A	N/A
9603656	12/2016	Germain et al.	N/A	N/A
9622766	12/2016	Voic	N/A	N/A
9636187	12/2016	Voic	N/A	N/A
9693792	12/2016	Novak et al.	N/A	N/A
9763673	12/2016	Young	N/A	N/A
9861446	12/2017	Lang	N/A	N/A
9872697	12/2017	Voic	N/A	N/A
9949751	12/2017	Voic	N/A	N/A
9962182	12/2017	Dietz et al.	N/A	N/A
10016208	12/2017	Gouery et al.	N/A	N/A
10076349	12/2017	Voic	N/A	N/A

10092741	12/2017	Darian	N/A	N/A
10117666	12/2017	Voic	N/A	N/A
10182837	12/2018	Isola et al.	N/A	N/A
10206704	12/2018	Voic et al.	N/A	N/A
10299809	12/2018	Mikus et al.	N/A	N/A
10398463	12/2018	Darian et al.	N/A	N/A
10398465	12/2018	Darian	N/A	N/A
10405875	12/2018	Voic et al.	N/A	N/A
10463381	12/2018	Voic et al.	N/A	N/A
10470788	12/2018	Sinelnikov	N/A	N/A
10470789	12/2018	Mikus et al.	N/A	N/A
10471281	12/2018	Mikus	N/A	N/A
10543012	12/2019	Pantano	N/A	N/A
10588691	12/2019	Pellegrino et al.	N/A	N/A
10639733	12/2019	Campbell	N/A	B23D 61/126
10687824	12/2019	Shiels et al.	N/A	N/A
10835276	12/2019	Voic et al.	N/A	N/A
10842587	12/2019	Mikus et al.	N/A	N/A
11007308	12/2020	Payne et al.	N/A	N/A
11298434	12/2021	Isola et al.	N/A	N/A
11324531	12/2021	Voic et al.	N/A	N/A
11672558	12/2022	Voic	N/A	N/A
11950790	12/2023	Voic	N/A	N/A
12011190	12/2023	Theodore et al.	N/A	N/A
2001/0029370	12/2000	Hodva et al.	N/A	N/A
2003/0212395	12/2002	Woloszko et al.	N/A	N/A
2004/0265776	12/2003	Tipton et al.	N/A	N/A
2005/0033292	12/2004	Teitelbaum et al.	N/A	N/A
2006/0030797	12/2005	Zhou et al.	N/A	N/A
2006/0235305	12/2005	Cotter et al.	N/A	N/A
2006/0241533	12/2005	Geller	N/A	N/A
2007/0060926	12/2006	Escaf	N/A	N/A
2007/0213734	12/2006	Bleich et al.	N/A	N/A
2008/0015551	12/2007	Feine	N/A	N/A
2008/0057470	12/2007	Levy et al.	N/A	N/A
2008/0058775	12/2007	Darian et al.	N/A	N/A
2008/0108985	12/2007	Konesky	N/A	N/A
2008/0183173	12/2007	Jozat	N/A	N/A
2008/0234709	12/2007	Houser	N/A	N/A
2008/0234710	12/2007	Neurohr et al.	N/A	N/A
2009/0143678	12/2008	Keast et al.	N/A	N/A
2010/0022944	12/2009	Wilcox	N/A	N/A
2010/0049188	12/2009	Nelson et al.	N/A	N/A
2010/0076349	12/2009	Babaev	N/A	N/A
2011/0092880	12/2010	Gertner	N/A	N/A
2011/0105958	12/2010	Babaev	N/A	N/A
2011/0160624	12/2010	Babaev	N/A	N/A
2011/0264090	12/2010	Shadduck et al.	N/A	N/A

2012/0014868	12/2011	Roy	N/A	N/A
2012/0053492	12/2011	Chang et al.	N/A	N/A
2013/0103021	12/2012	Germain et al.	N/A	N/A
2013/0123774	12/2012	Zadeh	N/A	N/A
2013/0231528	12/2012	Voic	N/A	N/A
2013/0245638	12/2012	Horton et al.	N/A	N/A
2014/0107537	12/2013	Beaupre	N/A	N/A
2014/0277030	12/2013	Lauchner	N/A	N/A
2014/0277034	12/2013	Darian	N/A	N/A
2014/0350567	12/2013	Schmitz et al.	N/A	N/A
2014/0358043	12/2013	Akagane	N/A	N/A
2015/0066032	12/2014	Young	N/A	N/A
2015/0088137	12/2014	Manna	N/A	N/A
2015/0094723	12/2014	Darian	N/A	N/A
2015/0157387	12/2014	OuYang et al.	N/A	N/A
2015/0164534	12/2014	Felder et al.	N/A	N/A
2015/0297246	12/2014	Patel et al.	N/A	N/A
2016/0022283	12/2015	Wallace et al.	N/A	N/A
2016/0135835	12/2015	Onuma	N/A	N/A
2016/0166276	12/2015	Huang et al.	N/A	N/A
2016/0175150	12/2015	Banko	N/A	N/A
2016/0206302	12/2015	Eckermann	N/A	N/A
2016/0222526	12/2015	Rubinsky et al.	N/A	N/A
2016/0331439	12/2015	Winkelman et al.	N/A	N/A
2016/0354559	12/2015	Gavini et al.	N/A	N/A
2017/0340339	12/2016	Madan et al.	N/A	N/A
2018/0008138	12/2017	Thommen et al.	N/A	N/A
2019/0000553	12/2018	Lightcap et al.	N/A	N/A
2019/0307529	12/2018	Jacoby	N/A	N/A
2020/0121374	12/2019	McGahan et al.	N/A	N/A
2020/0178999	12/2019	Stabilini et al.	N/A	N/A
2020/0205850	12/2019	Cao et al.	N/A	N/A
2020/0246056	12/2019	Bonn	N/A	N/A
2020/0405501	12/2019	Orozco Castillo	N/A	N/A
2021/0145531	12/2020	Gee et al.	N/A	N/A
2021/0267622	12/2020	Ellegala	N/A	N/A
2023/0210549	12/2022	Voic et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
210249992	12/2019	CN	N/A
109152577	12/2021	CN	A61B 17/1644
2745797	12/2013	EP	N/A
2635192	12/2018	EP	N/A
H0614934	12/1993	JP	N/A
H10127682	12/1997	JP	N/A
20120093654	12/2011	KR	N/A

WO-2004060141	12/2003	WO	N/A
WO-2007049718	12/2006	WO	N/A
WO-2008014258	12/2007	WO	A61B 17/144
WO-2008017909	12/2007	WO	N/A
WO-2008118708	12/2007	WO	N/A
WO-2008118709	12/2007	WO	N/A
WO-2009035508	12/2008	WO	N/A
WO-2009098664	12/2008	WO	N/A
WO-2009105628	12/2008	WO	N/A
WO-2010109447	12/2009	WO	N/A
WO-2013062118	12/2012	WO	N/A
WO-2014024550	12/2013	WO	N/A
WO-2015045198	12/2014	WO	N/A
WO-2015046349	12/2014	WO	N/A
WO-2015145444	12/2014	WO	N/A
WO-2015188735	12/2014	WO	N/A
WO-2017180493	12/2016	WO	N/A
WO-2019095831	12/2018	WO	N/A
WO-2023018863	12/2022	WO	N/A

OTHER PUBLICATIONS

Extended European Search Report for EP Application No. 22856601.4, dated Apr. 16, 2025, 5 pages. cited by applicant

International Preliminary Report on Patentability for Application No. PCT/US2022/040047, dated Feb. 22, 2024, 6 pages. cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2022/040047, dated Nov. 30, 2022, 7 pages. cited by applicant

SonicOne O.R., Ultrasonic Surgical Debridement. Brochure [online]. Misonix Ultrasonic Surgical Devices, 2012. Retrieved from the Internet: <URL:

https://web.archive.org/web/20150218182717/http://www.misonix.com:80/wp-content/uploads/2013/11/SO-OR_2003-12_REV_A_SonicOne_OR_Brochure.pdf>, 6 Pages. cited by applicant

SonicOne Plus, Ultrasonic Debridement System. Brochure [online]. Misonix Ultrasonic Surgical Devices, 2013. Retrieved from the Internet: <URL:

<https://pdf.medicaexpo.com/pdf/misonix/sonicone-plus/79244-106567.html>>, 4 pages. cited by applicant

Primary Examiner: Fishback; Ashley L

Attorney, Agent or Firm: COOLEY LLP

Background/Summary

FIELD OF THE INVENTION

(1) This invention relates to an ultrasonic tool. More particularly, this invention relates to an ultrasonic cutting blade. The blade is particularly useful in a surgical application to cut tissue such as cartilage and bone.

BACKGROUND OF THE INVENTION

(2) In the field of orthopedics, the cutting of living bone is a prerequisite for many procedures. Such procedures include the reconstruction of damaged tissue structures due to accidents, the grafting of healthy bone into areas damaged by disease, or the correction of congenital facial abnormalities like a receding chin line. Over several centuries, these tasks were performed through the utilization of devices called bone saws.

(3) Traditional bone saws are categorized into several basic categories. Hand powered saws or drills are just that, hand held devices which require the operator to move the device in a fashion similar to that used for carpentry tools. Powered devices, whether electric or pneumatic, are of either the reciprocating or rotary type. The reciprocating devices use a flat, sword like blade where the back and forth motion is provided by a motor instead of the hand. The rotary devices use a rotating motor to spin a drill bit or a blade that has teeth arranged around its circumference similar to a table saw blade. All of these traditional bone saws are used today in medical procedures around the world.

(4) While traditional saws are functional, they have many disadvantages. With either the band or reciprocating saws, for instance, it is not easy to initiate and direct a cut. A cut must start from an edge or, alternatively, a starting hole must be used. To create a starting hole, a drill or similar instrument is operated to bore into the bone. Subsequently, a cutting blade is inserted into the bored hole. The user can then proceed to cut. Alternatively, a rotary type blade may be used. However, when a rotary blade is used, the cut must follow a relatively straight path to prevent the blade from binding in the cut. With all blades the ability to create a curved or compound angle cut is extremely limited by the blade chosen. The relatively thick blades have a wide kerf, so that a significant thickness of the viable bone is lost in the cutting procedure. Physicians would like this width to be as thin as possible in most procedures where reconstruction is necessary.

(5) Ultrasonic bone cutting blades as disclosed, for example, in U.S. Pat. Nos. 5,261,922; 6,379,371; 6,443,969; 6,763,673; 8,888,783; 9,387,005; 9,320,528; D680,218; and D667,117 overcome many of the disadvantages and problems discussed above. However room for improvement remains. One problem is that surgeons sometimes have difficulty in penetrating into particularly large and strong bone structures, including spinal vertebrae and spinal lamina and processes.

OBJECTS OF THE INVENTION

(6) It is an object of the present invention to provide an improved ultrasonic surgical tool or probe for ablating or dissecting osseous tissue and cartilage.

(7) Another object of the present invention is to provide such an ultrasonic surgical tool or probe that more readily facilitates bone cutting procedures, particularly, but not exclusively, spinal bone cutting procedures.

(8) Yet another object of the present invention is to provide such an ultrasonic surgical tool or probe that is less likely to cut non-osseous tissue than bone.

(9) Yet another object of the present invention is to provide a surgical disc space preparation procedure that may be used to access spinal discs in surgical procedures.

(10) These and other objects of the invention will be apparent from the drawings and descriptions herein. Although every object of the invention is attained in at least one embodiment of the invention, there is not necessarily any embodiment which attains all of the objects of the invention.

SUMMARY OF THE INVENTION

(11) An ultrasonic surgical tool in accordance with the present invention comprises a substantially planar blade body having a pair of opposed lateral surfaces, a pair of straight longitudinal edges, and a convexly arcuate distal edge contiguous with the straight longitudinal edges. A shank is integral on a distal side with the blade body and provided at a proximal side with a connector for operatively linking the blade to a source of ultrasonic mechanical vibrations. The blade body is provided along the convexly arcuate distal edge and at least one of the straight longitudinal edges

with a continuous array of teeth including a first subset of teeth along the convexly arcuate distal edge and a second subset of teeth along the at least one straight longitudinal edge. The first subset of teeth exhibits a first tooth length and a first inter-tooth gap depth, while the second subset of teeth has a second tooth length and a second inter-tooth gap depth. The first tooth length differs from the second tooth length, and the first inter-tooth gap depth differs from the second inter-tooth gap depth.

(12) Another feature of an ultrasonic surgical tool in accordance with the present invention is that the first tooth length and the first inter-tooth gap depth are each uniform among the first subset of teeth, while the second tooth length and the second inter-tooth gap depth are each uniform among the second subset of teeth.

(13) Pursuant to another feature of the present invention, the first tooth length and the first inter-tooth gap depth are smaller than the second tooth length and the second inter-tooth gap depth, respectively. Specifically, the first tooth length is between about 0.60 and about 0.85 times the second tooth length, and the first inter-tooth gap depth is between about 0.60 and about 0.85 times the second inter-tooth gap depth. Preferably, the first tooth length is about 0.80 times the second tooth length, and the first inter-tooth gap depth is about 0.80 times the second inter-tooth gap depth.

(14) As indicated above, the first tooth length and the first inter-tooth gap depth may be uniform among the first subset of teeth, while the second tooth length and the second inter-tooth gap depth are uniform among the second subset of teeth. However, this is not invariably the case. For instance, the first tooth length and the first inter-tooth gap depth may vary from a minimum at an extreme distal tip of the arcuate distal edge and increase gradually on each side towards the respective longitudinal edge of the blade.

(15) In a preferred embodiment of the invention, the teeth of the continuous array of teeth are all isometrically triangular and bear a common angle between opposing edges. In that event, where the characteristic tooth length of the first subset of teeth is smaller than the characteristic tooth length of the second subset of teeth, the pitch of the teeth of the first subset, along the distal edge of the blade, is necessarily smaller than the pitch of the teeth of the second subset, along one or two longitudinal edges of the blade.

(16) Pursuant to this preferred embodiment, an ultrasonic surgical tool in accordance with the present invention comprises a substantially planar blade body having a pair of opposed lateral surfaces, a pair of straight longitudinal edges and a convexly arcuate distal edge contiguous with the straight longitudinal edges, with a shank integral on a distal side with the blade body being provided at a proximal side with a connector for operatively linking the blade to a source of ultrasonic mechanical vibrations. The blade body is provided along the convexly arcuate distal edge and at least one of the straight longitudinal edges with a continuous array of teeth including a first subset of teeth along the convexly arcuate distal edge and a second subset of teeth along the at least one of the straight longitudinal edges. The first subset of teeth exhibit a first inter-tooth separation or pitch and the second subset of teeth has a second inter-tooth separation, wherein the first inter-tooth separation or pitch differs from the second inter-tooth separation or pitch.

(17) In accordance with a further feature of the present invention, the first inter-tooth separation or pitch is uniform among the first subset of teeth, and the second inter-tooth separation or pitch is uniform among the second subset of teeth.

(18) Pursuant to a more specific feature of the present invention, the first inter-tooth separation or pitch is smaller than the second inter-tooth separation or pitch. The teeth of the continuous array of teeth are preferably all isometrically triangular and may bear a common angle between opposing edges.

(19) Preferably, the first inter-tooth separation or pitch is between about 0.60 and about 0.85 times the second inter-tooth separation or pitch.

(20) An ultrasonic tool in accordance with the present invention facilitates the performance of spinal surgeries, particularly by reducing the likelihood of damage to non-target soft tissue. It is

believed that the smaller tooth length along the distal tip of the blade is less aggressive than longer tooth lengths against tissue not intended for removal, such as soft tissue of the spine.

(21) While a uniform tooth sharpness (per the angle between relatively inclined tooth edges) is preferred, largely for manufacturing reasons, it is contemplated that the tooth angle may be reduced along the longitudinal edges to reduce the pitch and thereby increase the fineness of cutting and produce a smoother kerf.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a top plan view of an ultrasonic surgical tool or probe, particularly an ultrasonic surgical blade, in accordance with the present invention, a bottom plan view being identical to the top plan view.
- (2) FIG. 2 is a rear, left side and top perspective view of the ultrasonic surgical tool or probe of FIG. 1.
- (3) FIG. 3 is a front elevational view of the ultrasonic surgical tool or probe of FIGS. 1 and 2.
- (4) FIG. 4 is a rear elevational view of the ultrasonic surgical tool or probe of FIGS. 1-3.
- (5) FIG. 5 is a right side elevational view of the ultrasonic surgical tool or probe of FIGS. 1-4, a left side elevation view being identical thereto.
- (6) FIG. 6 is longitudinal axial cross-sectional view of the ultrasonic surgical tool or probe of FIGS. 1-5.
- (7) FIG. 7 is partial top or bottom plan view thereof, on an enlarged scale, showing detail VI in FIG. 1.

DETAILED DESCRIPTION

- (8) As depicted in the drawings, an ultrasonic surgical tool or probe **10** includes a substantially planar blade body **12** having a pair of parallel opposed lateral surfaces or major faces **14** and **16**, a pair of straight substantially longitudinal edges **18** and **20**, and a convexly arcuate distal edge **22** contiguous and continuous with the straight longitudinal edges. Longitudinal edges **18** and **20** converge slightly towards one another at the distal end of blade body **12**; longitudinal edges **18** and **20** are oriented at an angle of several degrees of arc relative to one another.
- (9) A transversely enlarged proximal portion or shank **24** is integral on a distal side with blade body **12** and provided on a proximal side with an externally threaded connector **26** for operatively coupling the blade body ("blade") **12** to a source **27** of ultrasonic mechanical vibratory energy, particularly to a stack of piezoelectric crystal elements (not shown) and a waveform generator (not shown) that applies an ultrasonic-frequency voltage across the piezo-stack. Shank **24** is formed with a pair of opposed flats **40**, **42** engageable by a wrench (not illustrated) for screwing the tool or probe **10** to an ultrasonic handpiece and particularly the piezoelectric crystal stack therein.
- (10) Shank **24** and blade body **12** are formed with co-linear channels, bores or lumens **44** and **46** of different diameters that communicate with one another and at a distal end with a through slot **48** extending longitudinally and axially along a portion of blade body **12**. Liquid coolant, typically aqueous, is conveyed through channels **44** and **46** to slot **48** for maintaining the temperature of blade **12** and or adjacent biological tissue within a biologically safe range.
- (11) Blade body **12** is provided along convexly arcuate distal edge **22** and at least one but preferably both longitudinal edges **18** and **20** with a continuous array of teeth including a first subset of teeth **28** along convexly arcuate distal edge **22** and a second subset of teeth **30**, **32** along longitudinal edges **18** and **20**. Teeth **28** exhibit a first tooth length TL1 and an associated first inter-tooth gap depth (not designated) typically equal to one another, while teeth **30** and **32** have a second tooth length TL2 and a second inter-tooth gap depth (not designated) generally equal thereto. Tooth length TL1 differs from the tooth length TL2, and concomitantly the first inter-tooth

gap depth differs from the second inter-tooth gap depth. A conically tapered surface **50** at a distal end of through slot **48** serves to distribute coolant to arcuate edge **22** along the length thereof.

(12) Preferably, but not necessarily, tooth length TL1 and the associated inter-tooth gap depth are each uniform among teeth **28**, while tooth length TL2 and the associated inter-tooth gap depth are each uniform among at least teeth **30** or **32**. However, the lengths of teeth **28** and the associated first inter-tooth gap depth may vary from a minimum at an extreme distal tip of arcuate distal edge **22** and increase gradually on each side towards the respective longitudinal edge **30**, **32** of blade body **12**. Or one might provide teeth **30** and teeth **32** with different common tooth lengths TL2 and inter-tooth gap depths, where an application targets a region of different bone structures or densities.

(13) Preferably, tooth length TL1 and the inter-tooth gap depth of teeth **28** are respectively smaller than tooth length TL2 and the inter-tooth gap depth of teeth **30**, **32**. Specifically, tooth length TL1 lies between approximately 0.60 and approximately 0.85 times tooth length TL2, the associated inter-tooth gap depths exhibiting the same proportionality. Preferably, tooth length TL1 is about 0.80 times tooth length TL2, for instance, where tooth length TL1 is 0.0016 inch while tooth length TL2 is 0.0020 inch. Concomitantly, the inter-tooth gap depth of teeth **28** is 0.80 times the second inter-tooth gap depth of teeth **30** and/or **32**.

(14) Teeth **28**, **30**, **32** are preferably all isometrically triangular and bear a common angle a1, a2 between opposing edges. This geometric congruence simplifies manufacture. However, angles a1 and a2 may differ from one another. For instance, angle a1 may be larger than angle a2. Where the tooth length TL2 is unchanged, the reduction in the angle a2 and the consequent increase in sharpness of teeth **30**, **32** correlates to a reduction in a pitch TP2 thereof. Such a reduction in pitch may be implemented to increase the fineness of cutting action of edges **30**, **32**.

(15) Thus, an ultrasonic surgical tool in accordance with the present invention comprises planar blade body **12** with opposed lateral surfaces **14** and **16**, straight longitudinal edges **18** and **20** and convexly arcuate distal edge **22** contiguous with edges **18** and **20**, with shank **24** integral on a distal side with blade body **12** and provided with connector **26** for operatively linking blade **12** to vibration source **27**. As described above, blade body **12** is provided along convexly arcuate distal edge **22** and at least one of longitudinal edges **18**, **20** with a continuous array of teeth including teeth **28** along distal edge **22** and teeth **30**, **32** along longitudinal edges **30**, **32**. Teeth **28** exhibit a first inter-tooth separation or pitch TP1 and teeth **30** and/or **32** has a second inter-tooth separation or pitch TP2 which may be different from inter-tooth separation or pitch TP1.

(16) In a preferred embodiment, inter-tooth separation or pitch TP1 is uniform among teeth **28**, while inter-tooth separation or pitch TP2 is uniform among teeth **30** and/or **32**. Inter-tooth separation or pitch TP1 is smaller than inter-tooth separation or pitch TP2, where the teeth of the continuous array of teeth are all isometrically triangular and bear a common angle between opposing edges (a1=a2, exemplarily 60°). Alternatively, one might vary the manufacture, particularly the size of angles a1 and a2, so that pitches TP1 and TP2 are the same.

(17) Ultrasonic tool or probe **10** enables a finer control of ablation in spinal surgery by reducing the action of the probe on tissues distal of blade body **12**. The shorter tooth length TL1 renders arcuate edge **22** less aggressive, reducing the distal cutting action in relative to the rapidity of ultrasonic cutting along longitudinal edges **18** and **20**.

(18) Although the invention has been described in terms of particular embodiments and applications, one of ordinary skill in the art, in light of this teaching, can generate additional embodiments and modifications without departing from the spirit of or exceeding the scope of the claimed invention. For instance, the pitch and the tooth length (or depth or height) may gradually vary from characteristic values along edges **30** and **32** to different characteristic values along leading or distal edge **22**. Alternatively, as indicated schematically in FIG. 7, the change may occur in a single step at a first given point between edges **18** and **22** and at another demarcated point between edges **20** and **22**. Accordingly, it is to be understood that the drawings and descriptions

herein are proffered by way of example to facilitate comprehension of the invention and should not be construed to limit the scope thereof.

Claims

1. An ultrasonic surgical tool, comprising: a substantially planar blade body having a pair of opposed lateral surfaces, a pair of straight longitudinal edges and a convexly arcuate distal edge contiguous with said straight longitudinal edges; and a shank integral on a distal side with said blade body and provided at a proximal side with a connector for operatively linking the blade to a source of ultrasonic mechanical vibrations, said substantially planar blade body defining a through slot that extends longitudinally and axially along a portion of the substantially planar blade body, the through slot being configured to deliver a fluid to an area adjacent to the substantially planar blade body, said substantially planar blade body including an array of teeth disposed along said convexly arcuate distal edge and at least one straight longitudinal edge of said pair of straight longitudinal edges, the array of teeth including a first subset of teeth disposed along said convexly arcuate distal edge and a second subset of teeth disposed along said at least one straight longitudinal edge of said pair of straight longitudinal edges.
2. The ultrasonic surgical tool defined in claim 1, wherein said first tooth length and said first inter-tooth gap depth are each uniform among said first subset of teeth, and said second tooth length and said second inter-tooth gap depth being each uniform among said second subset of teeth.
3. The ultrasonic surgical tool defined in claim 2, wherein said first tooth length and said first inter-tooth gap depth are smaller than said second tooth length and said second inter-tooth gap depth, respectively.
4. The ultrasonic surgical tool defined in claim 3, wherein said first tooth length is between about 0.60 and about 0.85 times said second tooth length, said first inter-tooth gap depth being between about 0.60 and about 0.85 times said second inter-tooth gap depth.
5. The ultrasonic surgical tool defined in claim 4, wherein said first tooth length is about 0.80 times said second tooth length, said first inter-tooth gap depth being about 0.80 times said second inter-tooth gap depth.
6. The ultrasonic surgical tool defined in claim 3, wherein each tooth of said array of teeth includes isometric opposing edges that form a common angle therebetween, each tooth of said first subset of teeth having a first pitch and each tooth of said second subset of teeth having a second pitch, said first pitch being smaller than said second pitch.
7. The ultrasonic surgical tool defined in claim 1, wherein said first tooth length and said first inter-tooth gap depth are smaller than said second tooth length and said second inter-tooth gap depth, respectively.
8. The ultrasonic surgical tool defined in claim 7, wherein said first tooth length is between about 0.60 and about 0.85 times said second tooth length, said first inter-tooth gap depth being between about 0.60 and about 0.85 times said second inter-tooth gap depth.
9. The ultrasonic surgical tool defined in claim 8, wherein said first tooth length is about 0.80 times said second tooth length, said first inter-tooth gap depth being about 0.80 times said second inter-tooth gap depth.
10. The ultrasonic surgical tool defined in claim 7, wherein each tooth of said array of teeth includes isometric opposing edges that form a common angle therebetween, each tooth of said first subset of teeth having a first pitch and each tooth of said second subset of teeth having a second pitch, said first pitch being smaller than said second pitch.
11. The ultrasonic surgical tool defined in claim 1, wherein each tooth of said array of teeth includes isometric opposing edges that form a common angle therebetween, each tooth of said first subset of teeth having a first pitch and each tooth of said second subset of teeth having a second pitch different from said first pitch.

12. The ultrasonic surgical tool defined in claim 1, wherein said first subset of teeth having a first tooth length and a first inter-tooth gap depth, said second subset of teeth having a second tooth length and a second inter-tooth gap depth, said first tooth length being different from said second tooth length, said first inter-tooth gap depth being different from said second inter-tooth gap depth.
13. An ultrasonic surgical tool, comprising: a substantially planar blade body having a pair of opposed lateral surfaces, a pair of straight longitudinal edges and a convexly arcuate distal edge contiguous with said straight longitudinal edges; and a shank integral on a distal side with said blade body and provided at a proximal side with a connector for operatively linking the blade to a source of ultrasonic mechanical vibrations, said substantially planar blade body defining a through slot that extends longitudinally and axially along a portion of the substantially planar blade body, the through slot being configured to deliver a fluid to an area adjacent to the substantially planar blade body, said substantially planar blade body including an array of teeth disposed along said convexly arcuate distal edge and at least one straight longitudinal edge of said pair of straight longitudinal edges, the array of teeth including a first subset of teeth disposed along said convexly arcuate distal edge and a second subset of teeth disposed along at least one straight longitudinal edge of said pair of straight longitudinal edges, said first subset of teeth exhibiting a first inter-tooth separation or pitch and said second subset of teeth having a second inter-tooth separation, said first inter-tooth separation or pitch being different from said second inter-tooth separation or pitch.
14. The ultrasonic surgical tool defined in claim 13, wherein said first inter-tooth separation or pitch is uniform among said first subset of teeth, and said second inter-tooth separation or pitch is uniform among said second subset of teeth.
15. The ultrasonic surgical tool defined in claim 14, wherein said first inter-tooth separation or pitch is smaller than said second inter-tooth separation or pitch.
16. The ultrasonic surgical tool defined in claim 15, wherein each tooth of said array of teeth includes isometric opposing edges that form a common angle therebetween.
17. The ultrasonic surgical tool defined in claim 14, wherein said first inter-tooth separation or pitch is between 0.60 and 0.85 times said second inter-tooth separation or pitch.
18. The ultrasonic surgical tool defined in claim 13, wherein said first inter-tooth separation or pitch is smaller than said second inter-tooth separation or pitch.
19. The ultrasonic surgical tool defined in claim 18, wherein said first inter-tooth separation or pitch is between 0.60 and 0.85 times said second inter-tooth separation or pitch.
20. The ultrasonic surgical tool defined in claim 13, wherein each tooth of said array of teeth includes isometric opposing edges that form a common angle therebetween.
-