

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12403435
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	McConnell; Jessica R. et al.

Storage dust cover for a stand mixer bowl

Abstract

A dust cover for a stand mixer bowl includes a disc-shaped body defining a central aperture therethrough and extending from the central aperture to an outer extent and a rim extending from the outer extent of the disc-shaped body to define an interior portion of the dust cover with the disc-shaped body. The interior portion of the dust cover is configured to removably receive an upper portion of a mixing bowl with the disc-shaped body extending inwardly from a lip of the mixing bowl positioned adjacent the outer extent of the disc-shaped body over at least a portion of an interior of the mixing bowl. The central aperture is configured for a portion of a planetary hub of a stand mixer to extend therethrough with an outer surface of the portion of the planetary hub adjacent an inner edge of the central aperture.

Inventors: McConnell; Jessica R. (St. Joseph, MI), McConnell; John W. (St. Joseph, MI), Myers; John Jay (Saugatuck, MI)

Applicant: WHIRLPOOL CORPORATION (Benton Harbor, MI)

Family ID: 85076494

Assignee: WHIRLPOOL CORPORATION (Benton Harbor, MI)

Appl. No.: 17/585851

Filed: January 27, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230264157 A1	Aug. 24, 2023

Publication Classification

Int. Cl.: B01F35/00 (20220101); A47J43/07 (20060101); B01F35/45 (20220101); B01F101/06 (20220101)

U.S. Cl.:

CPC **B01F35/45** (20220101); **A47J43/0727** (20130101); B01F2101/06 (20220101)

Field of Classification Search

CPC: B01F (35/45); B01F (2101/06); A47J (43/0727)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2504727	12/1949	Post	N/A	N/A
2802499	12/1956	Tupper	D7/391	A47J 43/0727
2858118	12/1957	Perkins	N/A	N/A
3913896	12/1974	Hawke	N/A	N/A
5660469	12/1996	Seguin	N/A	N/A
6435708	12/2001	Huang	N/A	N/A
8985839	12/2014	Seidler et al.	N/A	N/A
2012/0170404	12/2011	Drees	366/204	B01F 27/96

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1006382	12/2008	GB	N/A
2015059455	12/2014	WO	N/A

Primary Examiner: Bhatia; Anshu

Attorney, Agent or Firm: Price Heneveld LLP

Background/Summary

BACKGROUND OF THE DISCLOSURE

(1) The present disclosure generally relates to a dust cover for a stand mixer bowl, and more specifically, to a dust cover adapted to be used with the mixing bowl when mounted on the associated stand mixer.

(2) Stand mixers are generally configured to be interoperable with a number of interchangeable mixing bowls. These mixing bowls are coupled with the stand mixer in a variety of ways to be removable from the stand mixer, either to add ingredients or remove mixed food products or to interchange with different mixing bowls. Users typically store one or more mixing bowls in place on the mixer, typically for space-saving purposes, and may additionally store smaller bowls and/or mixing accessories within a larger mixing bowl. In this type of arrangement, the interior of the bowl or bowls and/or the accessories may be susceptible to gathering dust. Particularly, when the bowls and/or accessories are stored with the outermost bowl coupled with the stand mixer, a typical closed dust cover may not be compatible with certain features of the stand mixer, including an implement attachment output and/or the related planetary hub that drives movement of the output, which may interfere with the central portion of the dust cover that is disposed therebetween. Some stand mixers and/or associated mixing bowls may include so-called “splash guards” in the form of

annular devices configured to rest over the outer edge of a mixing bowl and are open toward the center thereof to allow operation of the stand mixer and the introduction of ingredients. Such devices, however, may not be suitable for use as a dust cover because they do not fit closely enough to the stand mixer to prevent the entry of dust or other items when the stand mixer and bowl(s) are being stored.

SUMMARY OF THE DISCLOSURE

(3) According to one aspect of the present disclosure, a dust cover for a stand mixer bowl includes a disc-shaped body defining a central aperture therethrough and extending from the central aperture to an outer extent and a rim extending from the outer extent of the disc-shaped body to define an interior portion of the dust cover with the disc-shaped body. The interior portion of the dust cover is configured to removably receive an upper portion of a mixing bowl with the disc-shaped body extending inwardly from a lip of the mixing bowl positioned adjacent the outer extent of the disc-shaped body over at least a portion of an interior of the mixing bowl. The central aperture is configured for a portion of a planetary hub of a stand mixer to extend therethrough with an outer surface of the portion of the planetary hub adjacent an inner edge of the central aperture when the dust cover receives the upper portion of the mixing bowl when the mixing bowl is coupled to the stand mixer in a storage position thereof.

(4) According to another aspect of the present disclosure, a mixing bowl assembly for use with a stand mixer includes a mixing bowl having a body extending to a lip and defining an interior cavity and a dust cover having a disc-shaped body defining a central aperture therethrough and extending from the central aperture to an outer extent and a rim extending from the outer extent of the disc-shaped body to define an interior portion of the dust cover with the disc-shaped body. An upper portion of the mixing bowl is received within the interior portion of the dust cover, with the disc-shaped body extending inwardly from the lip of the mixing bowl positioned adjacent the outer extent of the disc-shaped body, over at least a portion of an interior of the mixing bowl. The central aperture is configured for a portion of a planetary hub of a stand mixer to extend therethrough into the interior cavity of the mixing bowl with an outer surface of the portion of the planetary hub adjacent an inner edge of the central aperture when the dust cover receives the upper portion of the mixing bowl and the mixing bowl is coupled to the stand mixer in a storage position thereof.

(5) According to yet another aspect of the present disclosure, a stand mixer includes a base having a bowl coupler, a mixing head coupled with the base and having an output hub extending therefrom, a mixing bowl having a base removably coupled with the bowl coupler and a body extending from the base to a lip and defining an interior cavity, and a dust cover. The dust cover has a disc-shaped body defining a central aperture therethrough and extending from the central aperture to an outer extent and a rim extending from the outer extent of the disc-shaped body to define an interior portion of the dust cover with the disc-shaped body. An upper portion of the mixing bowl is received within the interior portion of the dust cover, with the disc-shaped body extending inwardly from the lip of the mixing bowl positioned adjacent the outer extent of the disc-shaped body, over at least a portion of an interior of the mixing bowl. The central aperture is configured for a portion of a planetary hub to extend therethrough into the interior cavity of the mixing bowl with an outer surface of the portion of the planetary hub adjacent an inner edge of the central aperture.

(6) These and other features, advantages, and objects of the present disclosure will be further understood and appreciated by those skilled in the art by reference to the following specification, claims, and appended drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) In the drawings:

- (2) FIG. 1 is a perspective view of a dust cover for a stand mixer bowl according to an aspect of the disclosure;
- (3) FIG. 2 is a perspective view of the dust cover of FIG. 1 in place on a mixing bowl coupled with a stand mixer in a storage condition of the mixing bowl;
- (4) FIG. 3 is a detail view of an interface between the mixing bowl and a portion of the stand mixer in the storage condition of FIG. 2;
- (5) FIG. 4 is a bottom perspective assembly view of the dust cover and the mixing bowl; and
- (6) FIG. 5 is a cross-section view of the dust cover in a further use condition in connection with an assembly of nested mixing bowls.
- (7) The components in the figures are not necessarily to scale, emphasis instead being placed upon illustrating the principles described herein.

DETAILED DESCRIPTION

- (8) The present illustrated embodiments reside primarily in combinations of apparatus components related to a stand mixer appliance. Accordingly, the apparatus components have been represented, where appropriate, by conventional symbols in the drawings, showing only those specific details that are pertinent to understanding the embodiments of the present disclosure so as not to obscure the disclosure with details that will be readily apparent to those of ordinary skill in the art having the benefit of the description herein. Further, like numerals in the description and drawings represent like elements.
- (9) For purposes of description herein, the terms “upper,” “lower,” “right,” “left,” “rear,” “front,” “vertical,” “horizontal,” and derivatives thereof shall relate to the disclosure as oriented in FIG. 1. Unless stated otherwise, the term “front” shall refer to the surface of the element closer to an intended viewer, and the term “rear” shall refer to the surface of the element further from the intended viewer. However, it is to be understood that the disclosure may assume various alternative orientations, except where expressly specified to the contrary. It is also to be understood that the specific devices and processes illustrated in the attached drawings, and described in the following specification are simply exemplary embodiments of the inventive concepts defined in the appended claims. Hence, specific dimensions and other physical characteristics relating to the embodiments disclosed herein are not to be considered as limiting, unless the claims expressly state otherwise.
- (10) The terms “including,” “comprises,” “comprising,” or any other variation thereof, are intended to cover a non-exclusive inclusion, such that an article or apparatus that comprises a list of elements does not include only those elements but may include other elements not expressly listed or inherent to such process, method, article, or apparatus. An element preceded by “comprises a . . .” does not, without more constraints, preclude the existence of additional identical elements in the process, method, article, or apparatus that comprises the element.
- (11) Referring to FIGS. 1-5, reference numeral **10** generally designates a dust cover for a stand mixer bowl **12**. The dust cover **10** includes a disc-shaped body **14** defining a central aperture **16** therethrough and extending from the central aperture **16** to an outer extent **18** and a rim **20** extending from the outer extent **18** of the disc-shaped body **14** to define an interior portion **22** of the dust cover **10** with the disc-shaped body **14**. The interior portion **22** of the dust cover **10** is configured to removably receive an upper portion **24** of the mixing bowl **12** with the disc-shaped body **14** extending inwardly from a lip **26** of the mixing bowl **12** positioned adjacent the outer extent **18** of the disc-shaped body **14** over at least a portion of an interior **28** of the mixing bowl **12**. The central aperture **16** is configured for a portion of a planetary hub **30** of a stand mixer **32** to extend therethrough with an outer surface **34** of the portion of the planetary hub **30** adjacent an inner edge **36** of the central aperture **16** when the dust cover **10** receives the upper portion **24** of the mixing bowl **12** when the mixing bowl **12** is coupled to the stand mixer **32** in a storage position thereof.
- (12) As particularly shown in FIGS. 2 and 3, the central aperture **16** of the dust cover **10** is present and configured to allow the dust cover **10** to be used in connection with the mixing bowl **12** when

in place on the stand mixer **32**. In the illustrated example, the mixing bowl **12** is configured such that the lip **26** thereof is positioned in horizontal alignment with a portion of the planetary hub **30** of the stand mixer **32**. As can be appreciated, the planetary hub **30** includes a hub body **38** and an output shaft **40** and is configured such that the hub body **38** rotates along an orbital path that generally corresponds with the shape of the hub body **38**. The output shaft **40** moves along the orbital path of the hub body **38** while itself rotating (including, in one implementation, in an opposite direction) in a planetary motion due to its offset position within the hub body **38**. In this manner, depending on the height of the mixing bowl **12** and the particular configuration of the body **14** of the dust cover **10**, the planetary hub **30** can be received through the aperture **16**, to varying degrees, to allow the stand mixer **32** to be stored, for example, with a mixing head **42** of the stand mixer **32** in the lowered position (to further save space, as the stand mixer **32** is generally more compact with the mixing head **42** lowered, as opposed to raised). In this manner, the inner edge **36** of the aperture **16** may horizontally align, in particular, with the output shaft **40** or the hub body **38**. In either configuration, the aperture **16** is sized to allow the output shaft **40** to wholly or partially extend therethrough and into the interior **28** of the mixing bowl **12**.

(13) Because the position of the output shaft **40** moves with the orbital rotation of the hub body **38**, the aperture **16** can be sized to allow the output shaft **40** to pass therethrough throughout the range of motion thereof with additional clearance to allow for tolerance stack-up and ease of operation. In one respect, the clearance provided (i.e., the distance between the inner edge **36** of the aperture **16** and the adjacent outermost portion **34** of the planetary hub **30**, which may be defined on the output shaft **40**, as shown, or on the hub body **38**) can allow for location and or movement of any attachment structure **44** positioned on the output shaft **40**. In a further aspect, the aperture **16** can be sized to accommodate the hub body **38** therein, which may have a widest point along a collar **46** from which the output shaft **40** extends. Again, as the position of the collar **46** may vary when the stand mixer **32** is powered off for storage, the aperture **16** can be sized to allow clearance for the collar **46**. In one implementation, the aperture **16** can have a radius that is at least 3 mm greater than the distance from the outermost position along the collar **46** to a rotational center of the planetary hub **30**. As shown, the body **14** of the dust cover **10** can be somewhat concave such that there is vertical clearance between the mixing head **42** and the dust cover **10**, particularly when used with taller implementations of the mixing bowl **12**, as shown in FIGS. 1-3.

(14) As discussed, the central aperture **16** can be sized to correspond with an outer path of the outermost adjacent surface portion **34** of the planetary output hub **30** through an operational range of motion thereof. In this respect, the relevant portion **34** of the planetary hub **30** can vary between the hub body **38** and the output shaft **40** and may, further vary in the case of the output hub **30** as the output hub **30** rotates about its axis, as such portion **34** is, in at least one aspect, determined by its closest proximity to the inner edge **36** of the central aperture **16**. In one aspect, the fit between the planetary hub **30** and the aperture **16**, while being configured for reliable and convenient for use during storage of the mixing bowl **12** on the stand mixer **32**, can be unsuited for use as a “splash guard” during use of the mixing bowl **12** with the stand mixer **32**. In this respect, the fit between the central aperture **16** and the relevant portion **34** of the planetary hub **30** can be close enough that the central aperture **16** is within an operational tolerance of the outer path of the surface **34** of the planetary hub **30** within at least a portion of the operational range of motion thereof. In this respect, the rotation of the hub body **38** and the output shaft **40** under load, while mixing ingredients and/or food product(s) may cause the position of the surface **34** to vary by more than the operational path alone. This additional variance can be anticipated with respect to ordinary operation of the stand mixer **32**, including with a designated splash guard, but the distance between the surface portion **34** of the planetary hub **30** and the inner edge **36** of the central aperture **16** may be within such anticipated variation, such that interference may result if the dust cover **10** is left in place on the mixing bowl **12** during use of the same with the stand mixer **32**. In another aspect, the central aperture **16** may be positioned beneath the mixing head **42**, such that the introduction of ingredients

through the central aperture **16** is impeded. In one implementation, the outer surface **34** of the planetary output hub **30** can be within about 3 mm of the inner edge **36** of the central aperture **16** when the dust cover **10** is in place on the mixing bowl **12** and the mixing bowl **12** is mounted with the stand mixer **32**. In a further aspect, The central aperture **16** can have a radius of 40 mm or about 40 mm (e.g., $\pm 5\%$).

(15) As further shown in FIG. 2, the mixing bowl **12** includes a base **48** configured for mounting with a bowl coupling **50** of the stand mixer **32**. In one implementation, the bowl coupling **50** can be a twist-fit (also referred to as a bayonet-style) fitting, where the base **48** is positioned within the bowl coupling **50** and turned (e.g. one-quarter turn clockwise or anti-clockwise) to secure the mixing bowl **12** in place. In other implementations, the present dust cover **10** can be interchangeably used with a bowl-lift type mixer and the related compatible mixing bowl. As shown, the body **14** of the mixing bowl **12** extends upward from the base **48** to the upper portion **24** thereof, where the lip **26** is located. In this manner, the dust cover **10** can be useable in an assembly with the depicted mixing bowl **12** and in a further assembly with the mixing bowl **12** and the stand mixer **32** in a storage position of the assembled mixing bowl **12** and stand mixer **32**. The dust cover **10** is, accordingly, removable from the mixing bowl **12** for use of the stand mixer **32** in connection with the mixing bowl **12**. In one example, this can be accomplished without removing the mixing bowl **12** from the stand mixer **32** by tilting the mixing head **42** upward such that the planetary hub **30** is removed from the central aperture **16**, at which point the dust cover **10** can be lifted off of the upper portion **24** of the mixing bowl **12** and stored on its own or in connection with any other mixing bowls or items stored within the utilized mixing bowl **12**. Other use cases may be realized by the utilization of different mixing bowls and different storage combinations thereof.

(16) As particularly shown in FIG. 4, the rim **20** can extend away from the body **14** of the dust cover **10** by a distance greater than the height of the lip **26** of a compatible mixing bowl **12**. In one aspect, this can generally facilitate resting of the dust cover **10** on the mixing bowl **12** with reliable enough positioning to allow movement of the assembled dust cover **10**, mixing bowl **12** and stand mixer **32**, while allowing the dust cover **10** to be useable with mixing bowls **12** with varying lip **26** height or other configurations. In a particular aspect, shown in FIG. 5, the previously-described mixing bowl **12** can be a first mixing bowl **12a** and the lip **26** and interior cavity **28** can be, respectively, a first lip **26a** and a first interior cavity **28a** of the first mixing bowl **12a**. In this respect, an implementation of the above-described assemblies can further include a second mixing bowl **12b** having a second body **14b** extending to a second lip **26b** to define a second interior cavity **28b** with the second body **14b** of the second mixing bowl **12b** being received within the first mixing bowl **12a** with the second rim **20b** in supporting contact with the first rim **20a** of the first mixing bowl **12a**. In this arrangement, respective upper portions **24a** and **24b** of both the first and second mixing bowls **12a** and **12b** can be received within the interior portion **22** of the dust cover **10**. The rim **20** of the dust cover **10** can extend away from the body **14** to a first distance D that is greater than a height of the upper lip **26a** of the mixing bowl **12b** such that a portion of the rim **20** can engage with the first lip **26a** of the first mixing bowl **12a** over the second lip **26b** of the second mixing bowl **12b**.

(17) As further shown the rim **20** can further accommodate a third mixing bowl **12c** similarly positioned within the interior **28b** of the second mixing bowl **12b** with the lip **26c** of the third mixing bowl **12c** resting on the lip **26b** of the second mixing bowl **12b**. For compatibility with this arrangement of mixing bowls **12a**, **12b**, and **12c**, for example, the rim **20** can extend away from the body **14** of the dust cover **10** such that the first distance H is at least three times greater than a height of an upper lip **26a** of the mixing bowl **12a** such that a portion of the rim **20**, including a detent feature **52** thereof, can engage with the lip **26a** of the lowermost mixing bowl **12a** when the two additional mixing bowls **12b** and **12c** are nested within the outermost mixing bowl **12a** with the respective lips **26b** and **26c** thereof in a stacked arrangement with the lip **26a** of the mixing bowl **12a**. In one aspect, the inner surface **54** of the rim **20** can have a radius R that provides a

loose, sliding fit with the mixing bowl **12a**. In other aspects, the detent feature **52** can extend around all or a portion of the inner surface **54** of the rim **20** to facilitate a snap-fit engagement with the mixing bowl **12a**, which may help to retain the assembly of the mixing bowl **12a** and the depicted additional mixing bowls **12b** and **12c** together during storage and/or movement of the assembly. In a particular implementation, the radius R can be about of 115 mm (+/-5%) to fit on a similarly-sized mixing bowl **12a** (e.g., having a radius of between about 113 mm and 114.5 mm).

(18) The invention disclosed herein is further summarized in the following paragraphs and is further characterized by combinations of any and all of the various aspects described therein.

(19) According to another aspect of the present disclosure, a dust cover for a stand mixer bowl includes a disc-shaped body defining a central aperture therethrough and extending from the central aperture to an outer extent and a rim extending from the outer extent of the disc-shaped body to define an interior portion of the dust cover with the disc-shaped body. The interior portion of the dust cover is configured to removably receive an upper portion of a mixing bowl with the disc-shaped body extending inwardly from a lip of the mixing bowl positioned adjacent the outer extent of the disc-shaped body over at least a portion of an interior of the mixing bowl. The central aperture is configured for a portion of a planetary hub of a stand mixer to extend therethrough with an outer surface of the portion of the planetary hub adjacent an inner edge of the central aperture when the dust cover receives the upper portion of the mixing bowl when the mixing bowl is coupled to the stand mixer in a storage position thereof. The central aperture can be sized to correspond with an outer path of the surface of the planetary output hub through an operational range of motion thereof.

(20) The central aperture can be sized to be within an operational tolerance of the outer path of the surface of the planetary output hub within at least a portion of the operational range of motion thereof.

(21) The outer surface of the planetary output shaft can be within about 3 mm of an inner edge of the central aperture when the dust cover receives the upper portion of the mixing bowl.

(22) The central aperture can have a radius of 40 mm.

(23) An inner surface of the rim can have a radius of 115 mm.

(24) The rim can extend away from the disc-shaped body to a first distance that is at least three times greater than a height of an upper lip of the mixing bowl such that a portion of the rim can engage with the lip of the mixing bowl when a first and a second additional mixing bowl are nested within the mixing bowl with respective lips thereof in a stacked arrangement with the lip of the mixing bowl.

(25) According to yet another aspect, a mixing bowl assembly for use with a stand mixer includes a mixing bowl having a body extending to a lip and defining an interior cavity and a dust cover having a disc-shaped body defining a central aperture therethrough and extending from the central aperture to an outer extent and a rim extending from the outer extent of the disc-shaped body to define an interior portion of the dust cover with the disc-shaped body. An upper portion of the mixing bowl is received within the interior portion of the dust cover, with the disc-shaped body extending inwardly from the lip of the mixing bowl positioned adjacent the outer extent of the disc-shaped body, over at least a portion of an interior of the mixing bowl. The central aperture is configured for a portion of a planetary hub of a stand mixer to extend therethrough into the interior cavity of the mixing bowl with an outer surface of the portion of the planetary hub adjacent an inner edge of the central aperture when the dust cover receives the upper portion of the mixing bowl and the mixing bowl is coupled to the stand mixer in a storage position thereof.

(26) The mixing bowl can include a base configured for mounting with a bowl coupling of the stand mixer, the body of the mixing bowl extending from the base.

(27) The dust cover can be removable from the mixing bowl for use of the stand mixer in connection with the mixing bowl.

(28) The mixing bowl can be a first mixing bowl and the lip and interior cavity can be, respectively,

first and second interior cavities of the first mixing bowl, and the assembly can further include a second mixing bowl having a second body extending to a second lip to define a second interior cavity, the second body of the second mixing bowl being received within the first mixing bowl with the second rim in supporting contact with the first rim of the first mixing bowl.

(29) Upper portions of both the first and second mixing bowls can be received within the interior portion of the dust cover.

(30) The rim of the dust cover can extend away from the disc-shaped body to a first distance that is greater than a height of an upper lip of the mixing bowl such that a portion of the rim can engage with the first lip of the first mixing bowl over the second lip of the second mixing bowl.

(31) The central aperture of the dust cover can be sized to correspond with an outer path of the surface of the planetary output hub through an operational range of motion thereof.

(32) The central aperture can be sized to be within an operational tolerance of the outer path of the surface of the planetary output hub within at least a portion of the operational range of motion thereof.

(33) The outer surface of the planetary output shaft can be within about 3 mm of an inner edge of the central aperture when the mixing bowl is coupled with the base of the stand mixer.

(34) The central aperture can have a radius of 40 mm.

(35) An inner surface of the rim can have a radius of 115 mm.

(36) According to yet another aspect, a stand mixer includes a base having a bowl coupler, a mixing head coupled with the base and having an output hub extending therefrom, a mixing bowl having a base removably coupled with the bowl coupler and a body extending from the base to a lip and defining an interior cavity, and a dust cover. The dust cover has a disc-shaped body defining a central aperture therethrough and extending from the central aperture to an outer extent and a rim extending from the outer extent of the disc-shaped body to define an interior portion of the dust cover with the disc-shaped body. An upper portion of the mixing bowl is received within the interior portion of the dust cover, with the disc-shaped body extending inwardly from the lip of the mixing bowl positioned adjacent the outer extent of the disc-shaped body, over at least a portion of an interior of the mixing bowl. The central aperture is configured for a portion of the planetary hub to extend therethrough into the interior cavity of the mixing bowl with an outer surface of the portion of the planetary hub adjacent an inner edge of the central aperture.

(37) The mixing bowl can be a first mixing bowl and the lip and interior cavity can be, respectively, first and second interior cavities of the first mixing bowl, and the stand mixer can further include a second mixing bowl having a second body extending to a second lip to define a second interior cavity, the second body of the second mixing bowl being received within the first mixing bowl with the second rim in supporting contact with the first rim of the first mixing bowl.

(38) It will be understood by one having ordinary skill in the art that construction of the described disclosure and other components is not limited to any specific material. Other exemplary embodiments of the disclosure disclosed herein may be formed from a wide variety of materials, unless described otherwise herein.

(39) For purposes of this disclosure, the term “coupled” (in all of its forms, couple, coupling, coupled, etc.) generally means the joining of two components (electrical or mechanical) directly or indirectly to one another. Such joining may be stationary in nature or movable in nature. Such joining may be achieved with the two components (electrical or mechanical) and any additional intermediate members being integrally formed as a single unitary body with one another or with the two components. Such joining may be permanent in nature or may be removable or releasable in nature unless otherwise stated.

(40) It is also important to note that the construction and arrangement of the elements of the disclosure as shown in the exemplary embodiments is illustrative only. Although only a few embodiments of the present innovations have been described in detail in this disclosure, those skilled in the art who review this disclosure will readily appreciate that many modifications are

possible (e.g., variations in sizes, dimensions, structures, shapes and proportions of the various elements, values of parameters, mounting arrangements, use of materials, colors, orientations, etc.) without materially departing from the novel teachings and advantages of the subject matter recited. For example, elements shown as integrally formed may be constructed of multiple parts or elements shown as multiple parts may be integrally formed, the operation of the interfaces may be reversed or otherwise varied, the length or width of the structures and/or members or connector or other elements of the system may be varied, the nature or number of adjustment positions provided between the elements may be varied. It should be noted that the elements and/or assemblies of the system may be constructed from any of a wide variety of materials that provide sufficient strength or durability, in any of a wide variety of colors, textures, and combinations. Accordingly, all such modifications are intended to be included within the scope of the present innovations. Other substitutions, modifications, changes, and omissions may be made in the design, operating conditions, and arrangement of the desired and other exemplary embodiments without departing from the spirit of the present innovations.

(41) It will be understood that any described processes or steps within described processes may be combined with other disclosed processes or steps to form structures within the scope of the present disclosure. The exemplary structures and processes disclosed herein are for illustrative purposes and are not to be construed as limiting.

Claims

1. A mixing bowl assembly for use with a stand mixer, comprising: a first mixing bowl including a body extending to a first lip and defining a first interior cavity; a second mixing bowl including a second body extending to a second lip to define a second interior cavity, the second body of the second mixing bowl being received within the first mixing bowl with a second rim in supporting contact with the first lip of the first mixing bowl; and a dust cover, including: a disc-shaped body defining a central aperture therethrough and extending from the central aperture to an outer extent; and a rim extending from the outer extent of the disc-shaped body to define an interior portion of the dust cover with the disc-shaped body; wherein: an upper portion of the first mixing bowl and an upper portion of the second mixing bowl are received within the interior portion of the dust cover, with the disc-shaped body extending inwardly from the second lip of the second mixing bowl positioned adjacent the outer extent of the disc-shaped body over at least a portion of an interior of the mixing bowl; the rim of the dust cover extends away from the disc-shaped body to a first distance that is greater than a height of an upper lip of the mixing bowl such that a portion of the rim can engage with the first lip of the first mixing bowl over the second lip of the second mixing bowl; and the central aperture is configured for a portion of a planetary hub of the stand mixer to extend therethrough into the interior cavity of the mixing bowl with an outer surface of the portion of the planetary hub adjacent an inner edge of the central aperture when the dust cover receives the upper portion of the mixing bowl and the mixing bowl is coupled to the stand mixer in a storage position thereof.
2. The mixing bowl assembly of claim 1, wherein the mixing bowl includes a base configured for mounting with a bowl coupling of the stand mixer, the body of the mixing bowl extending from the base.
3. The mixing bowl assembly of claim 1, wherein the dust cover is removable from the mixing bowl for use of the stand mixer in connection with the mixing bowl.
4. The mixing bowl assembly of claim 1, wherein the central aperture of the dust cover is sized to correspond with an outer path of the surface of the planetary output hub through an operational range of motion thereof.
5. The mixing bowl assembly of claim 4, wherein the central aperture is sized to be within an operational tolerance of the outer path of the surface of the planetary output hub within at least a

portion of the operational range of motion thereof.

6. The mixing bowl assembly of claim 1, wherein the outer surface of the hub is within about 3 mm of the inner edge of the central aperture when the mixing bowl is coupled with the stand mixer.

7. The mixing bowl assembly of claim 1, wherein the central aperture has a radius of 40 mm.

8. The mixing bowl assembly of claim 1, wherein an inner surface of the rim has a radius of 115 mm.

9. The mixing bowl assembly for use with a stand mixer of claim 1, wherein: a portion of the disc-shaped body rests on the second lip of the second mixing bowl with the rim extending downwardly past the second lip to engage with the first lip of the first mixing bowl; and the rim of the dust cover defines a detent feature that is configured for a snap fit engagement over the first lip with the second lip captured between the first lip and a portion of the disc-shaped body adjacent the rim to retain the first and second mixing bowls in an assembly with the dust cover.

10. The mixing bowl assembly for use with a stand mixer of claim 1, further including a third mixing bowl having a third body extending to a third lip to define a third interior cavity, the third body of the third mixing bowl being received within the second mixing bowl with a third rim in supporting contact with the first lip of the first mixing bowl; wherein: an upper portion of the third mixing bowl is further received within the interior portion of the dust cover with the respective upper portions of the first and second mixing bowls; and the first distance is further such that the portion of the rim can engage with the first lip of the first mixing bowl over the second lip of the second mixing bowl and the third lip of the third mixing bowl with the third lip in contact with a portion of the disc-shaped body.

11. A stand mixer, comprising: a base including a bowl coupler; a mixing head coupled with the base and including an output hub extending therefrom; a first mixing bowl including a base removably coupled with the bowl coupler and a first body extending from the base to a first lip and defining a first interior cavity; a second mixing bowl including a second body extending to a second lip to define a second interior cavity, the second body of the second mixing bowl being received within the first mixing bowl with the second rim in supporting contact with the first rim of the first mixing bowl; and a dust cover, including: a disc-shaped body defining a central aperture therethrough and extending from the central aperture to an outer extent; and a rim extending from the outer extent of the disc-shaped body to define an interior portion of the dust cover with the disc-shaped body; wherein: respective upper portions of the first mixing bowl and second mixing bowl are received within the interior portion of the dust cover, with the disc-shaped body extending inwardly from the first lip of the first mixing bowl positioned adjacent the outer extent of the disc-shaped body over at least a portion of the first interior cavity of the first mixing bowl; and the central aperture is configured for a portion of the planetary hub to extend therethrough into the interior cavity of the mixing bowl with an outer surface of the portion of the planetary hub adjacent an inner edge of the central aperture.

12. The stand mixer of claim 11, further including a third mixing bowl having a third body extending to a third lip to define a third interior cavity, the third body of the third mixing bowl being received within the second mixing bowl with a third rim in supporting contact with the first lip of the first mixing bowl; wherein: an upper portion of the third mixing bowl is further received within the interior portion of the dust cover with the respective upper portions of the first and second mixing bowls; and the first distance is further such that the portion of the rim can engage with the first lip of the first mixing bowl over the second lip of the second mixing bowl and the third lip of the third mixing bowl with the third lip in contact with a portion of the disc-shaped body.
